

An Improvement over the GVW Algorithm for Inhomogeneous Polynomial Systems[☆]

Yao Sun^a, Dongdai Lin^a, Dinggang Wang^b

^a*SKLOIS, Institute of Information Engineering, CAS, Beijing 100093, China*

^b*KLMM, Academy of Mathematics and Systems Science, CAS, Beijing 100190, China*

Abstract

The GVW algorithm is a signature-based algorithm for computing Gröbner bases. If the input system is not homogeneous, some J-pairs with higher signatures but lower degrees are rejected by GVW's Syzygy Criterion, instead, GVW have to compute some J-pairs with lower signatures but higher degrees. Consequently, degrees of polynomials appearing during the computations may unnecessarily grow up higher and the computation become more expensive. In this paper, a variant of the GVW algorithm, called M-GVW, is proposed and mutant pairs are introduced to overcome inconveniences brought by inhomogeneous input polynomials. Some techniques from linear algebra are used to improve the efficiency. Both GVW and M-GVW have been implemented in C++ and tested by many examples from boolean polynomial rings. The timings show M-GVW usually performs much better than the original GVW algorithm when mutant pairs are found. Besides, M-GVW is also compared with intrinsic Gröbner bases functions on Maple, Singular and Magma. Due to the efficient routines from the M4RI library, the experimental results show that M-GVW is very efficient.

Keywords: Gröbner basis, the GVW algorithm, signature-based algorithm, linear algebra, boolean polynomial ring.

1. Introduction

Gröbner bases, proposed by Buchberger in 1965 ([Buchberger, 1965](#)), have been proven to be very useful in many aspects of algebra. In the past forty years, many efficient algorithms have been proposed to compute Gröbner bases. One important improvement is that Lazard pointed out the strong relation between Gröbner bases and linear algebra ([Lazard, 1983](#)).

[☆]The authors are supported by National Key Basic Research Program of China (No. 2013CB834203), National Natrue Science Foundation of China (No. 11301523), the Strategic Priority Research Program of the Chinese Academy of Sciences (No. XDA06010701), and IEE's Research Project on Cryptography (No. Y3Z0013102).

Email addresses: sunyao@iie.ac.cn (Yao Sun), ddlin@iie.ac.cn (Dongdai Lin), dwang@mmrc.iss.ac.cn (Dinggang Wang)

This idea has been implemented in F4 by Faugère (Faugère, 1999), and also as XL type algorithms by Courtois et al. (Courtois, 2000) and Ding et al. (Ding et al., 2008).

Faugère introduced the concept of signatures for polynomials and presented the famous F5 algorithm (Faugère, 2002). Since then, signature-based algorithms have been widely investigated, and several variants of F5 have been presented, including F5C (Eder and Perry, 2010), extended F5 (Hashemi and Ars, 2010), F5 with revised criterion (the AP algorithm) (Arri and Perry, 2011), and RB (Eder and Roune, 2013). Gao et al. proposed another signature based algorithm G2V (Gao et al., 2010) in a different way from F5, and GVW (Gao et al., 2010) (which is unpublished) is an extended version of G2V. The authors also studied generalized criteria and signature-based algorithms in solvable polynomial algebra in (Sun and Wang, 2011; Sun et al., 2012).

In GVW, criteria reject J-pairs with higher signatures, and process J-pairs with lower signatures instead. However, when input systems are inhomogeneous, J-pairs with higher signatures do not always have higher degrees, where by saying degrees of polynomials, we mean the total degrees of polynomials. This is not good for Gröbner basis computations, and particularly not good for an implementation of GVW using linear algebra, because as suggested by Faugère in (Faugère, 1999, 2002), a good strategy of dealing with critical pairs (equivalent to J-pairs in GVW) in a batch is to select all critical pairs with the minimal degree. The reason is that critical pairs with higher degrees usually lead to larger matrices, which will cost much more time for eliminations. Some influences of inhomogeneous input systems were also discussed by Eder (Eder, 2013).

We find that with GVW's Syzygy Criterion is possible to reject J-pairs with higher signatures but lower degrees such that GVW has to compute J-pairs with lower signatures but higher degrees. After analysis, we find that such phenomenons are caused by some mutant pairs, which will be defined in Section 2, and then we propose a variant of the GVW algorithm (called M-GVW). In M-GVW, when mutant pairs are found during the computations, we will append them to the initial input system and assign new signatures to such mutant pairs. In this way, J-pairs generated by mutant pairs will not be all rejected by GVW's Syzygy Criterion, and hence, the maximal degree of polynomials appearing in the computations will not become too high. Particularly, for homogeneous polynomial systems, no mutant pairs will be generated and M-GVW is exactly the GVW algorithm.

For implementations of signature-based algorithms, Roune and Stillman efficiently implemented GVW and AP without using linear algebra (Roune and Stillman, 2012). Faugère mentioned a matrix F5 in (Faugère and Rahmany, 2009). A matrix F5 was described in more detail in an unpublished paper by Albrecht and Perry (Albrecht and Perry, 2010). We have implemented both the original GVW and M-GVW with linear algebra over boolean polynomial rings. For eliminations of matrices, we hope to take the advantage of fast arithmetics of dense matrices over GF(2) provided by the library M4RI (Albrecht and Bard, 2013). However, reductions in signature-based algorithms must be done in one direction, i.e. rows with higher signatures can only be eliminated by rows with lower signatures. So functions from M4RI cannot be used directly. We propose a method to do such one-direction eliminations for dense matrices by modifying functions from M4RI in our implementations.

The timings show M-GVW usually performs much better than the original GVW al-

gorithm when mutant pairs are found. Besides, M-GVW is also compared with intrinsic Gröbner bases functions on Maple, Singular and Magma. The experimental results show that M-GVW is very efficient.

This paper is organized as follows. In Section 2, we revisit the GVW algorithm and present M-GVW on a theoretical level. In Section 3, we discuss details on implementing M-GVW over boolean polynomial rings. Some experimental results are shown in Section 4. Conclusion remarks follow in Section 5.

2. A variant of the GVW algorithm

In this section, we present a variant of GVW (M-GVW) in theoretical level. We give this new algorithm over general polynomial rings, i.e. with no special assumptions on ground fields and monomial orderings.

2.1. The GVW algorithm revisited

Most of notations and definitions are inherited from Gao et al.'s original paper. For more details, please see (Gao et al., 2010).

Let $R = K[x_1, \dots, x_n]$ be a polynomial ring over a field K with n variables, and $\{f_1, \dots, f_m\}$ is a finite subset of R . We want to compute a Gröbner basis for the ideal

$$I = \langle f_1, \dots, f_m \rangle = \{p_1 f_1 + \dots + p_m f_m \mid p_1, \dots, p_m \in R\}$$

with respect to some monomial ordering on R .

Let $\mathbf{F} = (f_1, \dots, f_m) \in R^m$, and consider the following R -module of $R^m \times R$:

$$\mathbf{M} = \{(\mathbf{u}, f) \in R^m \times R \mid \mathbf{u} \cdot \mathbf{F} = f\}.$$

Let \mathbf{e}_i be the i -th unit vector of R^m , i.e. $(\mathbf{e}_i)_j = \delta_{ij}$ where δ_{ij} is the Kronecker delta. Then the R -module \mathbf{M} is generated by $\{(\mathbf{e}_1, f_1), \dots, (\mathbf{e}_m, f_m)\}$.

A monomial in R has the form $x^\alpha = \prod_{i=1}^n x_i^{\alpha_i}$, where $\alpha = (\alpha_1, \dots, \alpha_n) \in \mathbb{N}^n$ and \mathbb{N} is the set of all non-negative integers. A monomial in R^m is of the form $x^\alpha \mathbf{e}_i$, where $1 \leq i \leq m$ and $\alpha \in \mathbb{N}^n$. For monomials in R^n , we say $x^\alpha \mathbf{e}_i$ divides $x^\beta \mathbf{e}_j$ (or $x^\alpha \mathbf{e}_i \mid x^\beta \mathbf{e}_j$ for short), if $i = j$ and x^α divides x^β , and the quotient is defined as $(x^\beta \mathbf{e}_i)/(x^\alpha \mathbf{e}_i) = x^{\beta-\alpha} \in R$.

Fix any monomial ordering \prec_p on R and any monomial ordering \prec_s on R^m (subscripts p and s stand for *polynomial* and *signature* respectively). Please note that \prec_s may or may not be related to \prec_p in theory, although we always assume \prec_s is **compatible** with \prec_p practically, i.e. $x^\alpha \prec_p x^\beta$ if and only if $x^\alpha \mathbf{e}_i \prec_s x^\beta \mathbf{e}_i$ for $1 \leq i \leq m$. To make descriptions simpler, we use the following notations for leading monomials:

$$\text{lm}(f) = \text{lm}_{\prec_p}(f) \text{ and } \text{lm}(\mathbf{u}) = \text{lm}_{\prec_s}(\mathbf{u}),$$

for any $f \in R$ and any $\mathbf{u} \in R^m$. Leading monomials of $f \in R$ and $\mathbf{u} \in R^m$ are monomials without coefficients in R and R^m respectively. We define $\text{lm}(f) = 0$ if $f = 0$, and $0 \prec_p x^\alpha$ for any non-zero monomial x^α in R ; similarly for monomials in R^m . In the rest of this paper, we use \prec to represent \prec_p and \prec_s for short, if no confusion occurs.

For a pair $(\mathbf{u}, f) \in \mathbf{M}$, $\text{lm}(\mathbf{u})$ is called the **signature** of (\mathbf{u}, f) . This definition is the same as that used in GVW, but different from those used in (Faugère, 2002; Arri and Perry, 2011). The difference is discussed in (Gao et al., 2010).

Let $(\mathbf{u}, f) \in \mathbf{M}$ and $B \subset \mathbf{M}$, we say (\mathbf{u}, f) is **top-reducible** by B , if there exists $(\mathbf{v}, g) \in B$ with $g \neq 0$, such that $\text{lm}(g)$ divides $\text{lm}(f)$ and $\text{lm}(\mathbf{u}) \succeq \text{lm}(t\mathbf{v})$ where $t = \text{lm}(f)/\text{lm}(g)$. The corresponding **top-reduction** is then

$$(\mathbf{u}, f) - ct(\mathbf{v}, g) = (\mathbf{u} - ct\mathbf{v}, f - ctg),$$

where $c = \text{lc}(f)/\text{lc}(g)$. Particularly, this top-reduction is called **regular**, if $\text{lm}(\mathbf{u}) \succ \text{lm}(t\mathbf{v})$; and **super** if $\text{lm}(\mathbf{u}) = \text{lm}(t\mathbf{v})$.¹ Clearly, $(\mathbf{u} - ct\mathbf{v}, f - ctg)$ is also an element in \mathbf{M} .

A subset G of \mathbf{M} is called a **strong Gröbner basis** for \mathbf{M} if every nonzero pair (pairs $\neq (\mathbf{0}, 0)$) in \mathbf{M} is top-reducible by G . By Proposition 2.2 of (Gao et al., 2010), let $G = \{(\mathbf{v}_i, g_i) \mid 1 \leq i \leq s\}$ be a strong Gröbner basis for \mathbf{M} . Then $\{g_i : 1 \leq i \leq s\}$ is a Gröbner basis for $I = \langle f_1, \dots, f_m \rangle$.

Next, we define *joint pairs/J-pairs*. Suppose $(\mathbf{u}, f), (\mathbf{v}, g) \in \mathbf{M}$ are two pairs with f and g both nonzero. Let $t = \text{lcm}(\text{lm}(f), \text{lm}(g))$, $t_f = t/\text{lm}(f)$ and $t_g = t/\text{lm}(g)$. Then the **J-pair** of (\mathbf{u}, f) and (\mathbf{v}, g) is defined as: $t_f(\mathbf{u}, f)$ (or $t_g(\mathbf{v}, g)$), if $\text{lm}(t_f\mathbf{u}) \succ \text{lm}(t_g\mathbf{v})$ (or $\text{lm}(t_f\mathbf{u}) \prec \text{lm}(t_g\mathbf{v})$). For the case $\text{lm}(t_f\mathbf{u}) = \text{lm}(t_g\mathbf{v})$, the J-pair is not defined. Note that the J-pair of $(\mathbf{u}, f), (\mathbf{v}, g) \in \mathbf{M}$ is also a pair in \mathbf{M} . Assume $t_f(\mathbf{u}, f)$ is the J-pair of (\mathbf{u}, f) and (\mathbf{v}, g) , the **degree** of $t_f(\mathbf{u}, f)$ is defined as $\deg(t_ff)$, i.e. the degree of the polynomial part. For convenience, we call a J-pair is of $G \subset \mathbf{M}$, if this J-pair is the J-pair of two pairs in G .

For a pair $(\mathbf{u}, f) \in \mathbf{M}$ and a set $G \subset \mathbf{M}$, we say (\mathbf{u}, f) is **covered** by G , if there is a pair $(\mathbf{v}, g) \in G$, such that $\text{lm}(\mathbf{v})$ divides $\text{lm}(\mathbf{u})$ and $t\text{lm}(g) \prec \text{lm}(f)$ (strictly smaller) where $t = \text{lm}(\mathbf{u})/\text{lm}(\mathbf{v})$.

Two criteria are used in the GVW algorithm.

[Syzygy Criterion] For a J-pair $t_f(\mathbf{u}, f)$ of a set $G \in \mathbf{M}$, if there exist $(\mathbf{v}, 0) \in G$ such that $\text{lm}(\mathbf{v})$ divides $t_f\text{lm}(\mathbf{u})$, then this J-pair can be discarded.

[Second Criterion] For a J-pair of a set $G \in \mathbf{M}$, if this J-pair is covered by G , then this J-pair can be discarded.

In this paper, we call the second criterion **Rewriting Criterion**. Arri and Perry proposed a quite similar criterion to Rewriting Criterion in (Arri and Perry, 2011). Comments on Arri-Perry's criterion and Rewriting Criterion can be found in (Gao et al., 2010; Roune and Stillman, 2012).

The following GVW algorithm is slightly modified from its original version. We delete the output of a Gröbner basis for the syzygy module of input polynomials, because we only care about the Gröbner basis of input polynomials in current paper. We emphasize that for a pair $(\mathbf{u}, f) \in \mathbf{M}$, only $(\text{lm}(\mathbf{u}), f)$ is stored in the latest version of the GVW algorithm. Related conceptions, such as *top-reduction*, *J-pairs* and *cover*, are defined similarly. Please see (Gao et al., 2010) for more details.

¹Regular top-reduction defined here is slightly different from its original version in (Gao et al., 2010), but this will not affect proofs of related propositions and theorems.

Algorithm 1: The GVW algorithm

Input : $f_1, \dots, f_m \in R = K[x_1, \dots, x_n]$, monomial orderings for R and R^m .

Output: A Gröbner basis of $I = \langle f_1, \dots, f_m \rangle$.

```
1 begin
2    $H \leftarrow \{\text{lm}(f_j \mathbf{e}_i - f_i \mathbf{e}_j) \mid 1 \leq i, j \leq m\}$ 
3    $G \leftarrow \{(\text{lm}(\mathbf{e}_i), f_i) \mid 1 \leq i \leq m\}$ 
4    $\text{JP} \leftarrow \{\text{all J-pairs of } G\}$ 
5   while  $\text{JP} \neq \emptyset$  do
6     Let  $t(x^\alpha \mathbf{e}_i, f) \in \text{JP}$  (★)
7      $\text{JP} \leftarrow \text{JP} \setminus \{t(x^\alpha \mathbf{e}_i, f)\}$ 
8     if  $tx^\alpha \mathbf{e}_i$  is divisible by monomials in  $H$  then
9       GotoStep5 (Syzygy Criterion)
10    if  $t(x^\alpha \mathbf{e}_i, f)$  is covered by  $G$  then
11      GotoStep5 (Rewriting Criterion)
12     $(x^\gamma \mathbf{e}_i, h) \leftarrow \text{Regular top-reduce } (tx^\alpha \mathbf{e}_i, tf) \text{ by } G.$ 
13    if  $h = 0$  then
14       $H \leftarrow H \cup \{x^\gamma \mathbf{e}_i\}$ 
15      GotoStep5
16    for  $(x^\beta \mathbf{e}_j, g) \in G$  s.t.  $\text{lm}(g)x^\gamma \mathbf{e}_i \neq \text{lm}(h)x^\beta \mathbf{e}_j$  do
17       $H \leftarrow H \cup \{\max(\text{lm}(g)x^\gamma \mathbf{e}_i, \text{lm}(h)x^\beta \mathbf{e}_j)\}$ 
18       $\text{JP} \leftarrow \text{JP} \cup \{\text{J-pair of } (x^\gamma \mathbf{e}_i, h) \text{ and } (x^\beta \mathbf{e}_j, g)\}$ 
19     $G \leftarrow G \cup \{(x^\gamma \mathbf{e}_i, h)\}$ 
20  return  $\{g \mid (x^\beta \mathbf{e}_j, g) \in G\}$ 
```

There are some remarks on the GVW algorithm.

1. At Step 6 (marked with black star), a J-pair can be selected from JP in **any** order. In Section 3, we prefer to choosing J-pairs with minimal degrees first.
2. Proposition 2.2 in (Gao et al., 2010) ensures correctness of GVW when J-pairs are computed in **any** order.
3. The finite termination of GVW is proved by Theorem 3.1 in (Gao et al., 2010) when monomial orderings of R and R^m are compatible. Particularly, GVW also terminates in finite steps when J-pairs are computed in **any** order. This proof is first given by Theorem 3.5 in (Sun et al., 2012).
4. The GVW algorithm in (Gao et al., 2010) retains only one J-pair (the one with the minimal polynomial part) when there are several J-pairs having the same signature. This process can be implied by the “cover check” at step 10.

2.2. Motivation and main ideas

The motivation of varying GVW arises when we are implementing GVW with linear algebra in boolean polynomial rings. To control the size of appearing matrices as small as possible, we deal with J-pairs with the *minimal degree* first. That is, at Step 6 of GVW, we find the minimal degree of all J-pairs in JP first, and then choose the J-pair with the smallest signature among J-pairs with the minimal degree.

However, we are quite surprised to find that when computing a Gröbner basis for HFE_25.96 from (Steel, 2004), degrees of matrices always grow up to 5, this makes our implementation much less efficient, because the sizes of matrices with degree 5 are much larger than those with degree 4, and moreover, it has been shown in (Faugère and Joux, 2003) that Gröbner basis of this example can definitely be obtained with degrees of matrices smaller than 5. Here the degree of a matrix is the maximal degree of the polynomials to construct this matrix.

We find the above phenomenon does not depend on the computing orders of J-pairs. In order to illustrate this phenomenon clearly, we finally get the following example after testing many examples.

Example 2.1. Let $\{f_1, f_2, \dots, f_{11}\} \subset R = \mathbb{F}_2[x_1, x_2, \dots, x_9]$, where \mathbb{F}_2 is the Galois Field $GF(2)$, and

$$f_1 = x_1x_2x_5x_6 + x_2x_3x_7x_9 + x_7, f_2 = x_1x_2x_6x_8 + x_3x_4x_7,$$

$$f_{i+2} = x_i^2 + x_i, \text{ for } 1 \leq i \leq 9.$$

Monomial ordering \prec_p in R is the Graded Reverse Lexicographic ordering, and \prec_s in R^{11} is a position over term extension of \prec_p :

$$x^\alpha \mathbf{e}_i \prec_s x^\beta \mathbf{e}_j \text{ iff } i > j, \text{ or } i = j \text{ and } x^\alpha \prec_p x^\beta.$$

Thus, $\mathbf{e}_1 \succ \mathbf{e}_2 \succ \dots \succ \mathbf{e}_{11}$.

For this example, GVW needs to deal with J-pairs having degree bigger than 5, while the maximal degree of matrices in the F4 algorithm with criteria from (Buchberger, 1979) is only 5. This implies some “useful” J-pairs with degrees not bigger than 5 have been rejected by GVW’s criteria.

Now, we will discuss this example in details. We compute a Gröbner basis for $\langle f_1, \dots, f_{11} \rangle$ by GVW with the following strategy for selecting J-pairs at Step 6:

1. $\text{deg} \leftarrow$ the minimal degree of J-pairs in JP.
2. $(x^\alpha \mathbf{e}_i, f) \leftarrow$ J-pair with the smallest signature in the set $\{(x^\beta \mathbf{e}_j, g) \in \text{JP} \mid \text{deg}(g) = \text{deg}\}$.

Since the f_i ’s are all inhomogeneous, the above strategy leads to that J-pairs are not handled in an increasing order on signatures².

²Even dealing with J-pairs in an increasing order on signatures, GVW still has to reduce J-pairs with degrees bigger than 5 before a strong Gröbner basis is obtained.

Due to page limitation, we only present some results here. Initially, we have $G = \{(\mathbf{e}_1, f_1), (\mathbf{e}_2, f_2), \dots, (\mathbf{e}_{11}, f_{11})\}$. Before dealing with J-pairs with degree 6, the following polynomials are generated one by one:

$$\begin{aligned}
(x_8 \mathbf{e}_2, f_{12} &= x_3 x_4 x_7 x_8 + x_3 x_4 x_7), \\
(x_6 \mathbf{e}_2, f_{13} &= x_3 x_4 x_6 x_7 + x_1 x_2 x_6 x_8), \\
(x_2 \mathbf{e}_2, f_{14} &= x_2 x_3 x_4 x_7 + x_1 x_2 x_6 x_8), \\
(x_1 \mathbf{e}_2, f_{15} &= x_1 x_3 x_4 x_7 + x_1 x_2 x_6 x_8), \\
(x_8 \mathbf{e}_1, f_{16} &= x_2 x_3 x_7 x_8 x_9 + x_3 x_4 x_5 x_7 + x_7 x_8), \\
(x_6 \mathbf{e}_1, f_{17} &= x_2 x_3 x_6 x_7 x_9 + x_1 x_2 x_5 x_6 + x_6 x_7), \\
(x_5 \mathbf{e}_1, f_{18} &= x_2 x_3 x_5 x_7 x_9 + x_1 x_2 x_5 x_6 + x_5 x_7), \\
(x_2 \mathbf{e}_1, f_{19} &= x_2 x_7 + x_7), \\
(x_1 \mathbf{e}_1, f_{20} &= x_1 x_2 x_3 x_7 x_9 + x_1 x_2 x_5 x_6 + x_1 x_7), \\
(x_2 x_3 x_8 x_9 \mathbf{e}_1, f_{21} &= x_3 x_4 x_5 x_7 + x_3 x_7 x_8 x_9 + x_7 x_8), \\
(x_2 x_3 x_6 x_9 \mathbf{e}_1, f_{22} &= x_3 x_6 x_7 x_9 + x_3 x_7 x_9 + x_6 x_7 + x_7), \\
(x_2 x_3 x_5 x_9 \mathbf{e}_1, f_{23} &= x_3 x_5 x_7 x_9 + x_3 x_7 x_9 + x_5 x_7 + x_7), \\
(x_1 x_2 x_3 x_9 \mathbf{e}_1, f_{24} &= x_1 x_3 x_7 x_9 + x_2 x_3 x_7 x_9 + x_1 x_7 + x_7).
\end{aligned}$$

During computations, many leading monomial of syzygies in \mathbf{M} are generated, among them the one $x_2 x_3 x_4 \mathbf{e}_1$ (obtained before f_{20}) is important, since it has been used to reject many other J-pairs.

So far, all J-pairs with degrees not bigger than 5 have been considered. It is easy to check $\{f_1, f_2, \dots, f_{24}\}$ is *not* a Gröbner basis of $\langle f_1, f_2, \dots, f_{11} \rangle$. However, for the same ideal, F4 algorithm with criteria from (Buchberger, 1979) can obtain a Gröbner basis without computing any critical pairs with degrees bigger than 5. Comparing GVW and F4 algorithm step by step, finally, we find the following J-pairs:

$$\begin{aligned}
&x_4(x_2 x_3 x_5 x_9 \mathbf{e}_1, f_{23}), & x_4(x_1 x_2 x_3 x_9 \mathbf{e}_1, f_{24}), \\
&x_4(x_2 x_3 x_6 x_9 \mathbf{e}_1, f_{22}), & x_1 x_5 x_6(x_2 \mathbf{e}_1, f_{19}), \\
&x_1 x_6 x_8(x_2 \mathbf{e}_1, f_{19}), & x_3(x_2 x_3 x_8 x_9 \mathbf{e}_1, f_{21}), \\
&x_4(x_2 x_3 x_8 x_9 \mathbf{e}_1, f_{21}), & x_3(x_1 x_2 x_3 x_9 \mathbf{e}_1, f_{24}), \\
&x_9(x_1 x_2 x_3 x_9 \mathbf{e}_1, f_{24}), & x_3(x_2 x_3 x_5 x_9 \mathbf{e}_1, f_{23}), \\
&x_9(x_2 x_3 x_5 x_9 \mathbf{e}_1, f_{23}), & x_3(x_2 x_3 x_6 x_9 \mathbf{e}_1, f_{22}), \\
&x_9(x_2 x_3 x_6 x_9 \mathbf{e}_1, f_{22}),
\end{aligned}$$

which are rejected by GVW's criteria but not rejected by Buchberger's criteria in F4.

Reducing these J-pairs, we get 9 polynomials with degree 3 and 4 polynomials with 4. These polynomials are computed in F4, and prevent F4 to deal with critical pairs with degree bigger than 5.

Next, we analyze why GVW is possible to reject J-pairs with lower degrees and prefer to reducing higher degree J-pairs.

Take J-pair $x_3(x_1 x_2 x_3 x_9 \mathbf{e}_1, f_{24})$ for example. Reducing this J-pair, we get

$$(x_1 x_2 x_3^2 x_9 \mathbf{e}_1, x_1 x_3 x_7 + x_1 x_7 + x_3 x_7 + x_7).$$

But this J-pair is rejected by $((x_3^2 + x_3) \mathbf{e}_1 - f_1 \mathbf{e}_5, 0) \in \mathbf{M}$ in GVW, which is the principal syzygy of f_1 and f_5 . While running GVW forward, we find the polynomial $x_1 x_3 x_7 + x_1 x_7 +$

$x_3x_7 + x_7$ is obtained from the J-pair $x_3(x_1\mathbf{e}_1, f_{20})$, which is a J-pair of degree 6. Combined with our experiences of proving F5 in (Sun and Wang, 2013), we have the following observation.

Remark 2.2. *GVW's criteria always reject J-pairs with higher signatures, and proceed some J-pairs with smaller signatures instead.*

When input systems are inhomogeneous, J-pairs with bigger signatures may have lower degrees than J-pairs with smaller signatures.

Consider the degree-5 J-pair $x_3(x_1x_2x_3x_9\mathbf{e}_1, f_{24})$ again. The syzygy $((x_3^2 + x_3)\mathbf{e}_1 - f_1\mathbf{e}_5, 0) \in \mathbf{M}$, which rejects this J-pair, corresponds to the equation

$$f_5f_1 - f_1f_5 = 0,$$

in which monomials with degree 6 appear. Thus, we believe that if we use the syzygy $((x_3^2 + x_3)\mathbf{e}_1 - f_1\mathbf{e}_5, 0)$ to reject this degree-5 J-pair, it is possible to deal with some J-pairs involving polynomials of degree 6 instead later. On seeing this, our basic idea is to prevent GVW rejecting J-pairs like $x_3(x_1x_2x_3x_9\mathbf{e}_1, f_{24})$ by using syzygy like $((x_3^2 + x_3)\mathbf{e}_1 - f_1\mathbf{e}_5, 0)$.

Analyzing all J-pairs we have listed earlier, we find they have two common properties:

1. All these J-pairs are rejected by Syzygy Criterion.
2. For any J-pair $t(x^\alpha\mathbf{e}_1, f_j)$ that is listed, we find that

$$\deg(x^\alpha) + \deg(f_1) > \deg(f_j).$$

The second property makes the degree of $x_3(x_1x_2x_3x_9\mathbf{e}_1, f_{24})$ lower than the degree of f_5f_1 . In order to prevent this J-pair to be rejected, there are two possible method: (1) treat the syzygy $(f_5\mathbf{e}_1 - f_1\mathbf{e}_5, 0)$ specially; and (2) treat the pair $(x_1x_2x_3x_9\mathbf{e}_1, f_{24})$ specially.

For the first method, we can store the degree of f_5f_1 together with the syzygy $(f_5\mathbf{e}_1 - f_1\mathbf{e}_5, 0)$ and prevent it to reject J-pairs that have lower degrees than $\deg(f_5f_1)$. But we do not use the first method in our implementation, because the second method seems to be simpler.

We find the pairs satisfying the property 2 are similar to mutant polynomials defined in (Ding et al., 2008), so we give the following definition.

Definition 2.3. *Let \mathbf{M} be an R -module generated by $\{(\mathbf{e}_1, f_1), \dots, (\mathbf{e}_m, f_m)\}$. A pair $(\mathbf{u}, f) \in \mathbf{M}$ with $\text{lm}(\mathbf{u}) = x^\alpha\mathbf{e}_i$ and $f \neq 0$, is called **mutant**, if $\deg(x^\alpha) + \deg(f_i) > \deg(f)$.*

Due to the existence of syzygy pairs, there are lots of mutant pairs in \mathbf{M} . But mutant pairs appearing in GVW are not so many, since the Syzygy Criterion is used.

2.3. The M-GVW algorithm

The basic idea of M-GVW is to append mutant pairs to the initial input system and assign new signatures to such pairs so that the J-pairs generated by mutant pairs will not be all rejected by GVW's Syzygy Criterion, and hence, the maximal degree of polynomials appearing in the computations will not become too high.

Specifically, let \mathbf{M} be generated by $\{(\mathbf{e}_1, f_1), \dots, (\mathbf{e}_m, f_m)\}$, and (\mathbf{u}, f) with $\text{lm}(\mathbf{u}) = x^\alpha \mathbf{e}_k$ be the first mutant pair that we meet during computations where $\mathbf{e}_i \in R^m$. Then we add a pair (\mathbf{e}_{m+1}, f) as a new generator and the module is expanded to the module generated by $\{(\mathbf{e}_1, f_1), \dots, (\mathbf{e}_m, f_m), (\mathbf{e}_{m+1}, f_{m+1} = f)\}$. Please note that dimensions of $\mathbf{e}_1, \dots, \mathbf{e}_m$ are enlarged to $m+1$ by appending 0's to last entry, and now $\mathbf{e}_i \in R^{m+1}$. We emphasize that, after appending $(\mathbf{e}_{m+1}, f_{m+1})$, we always require

$$x^\alpha \mathbf{e}_k \succ_s \mathbf{e}_{m+1}. \quad (1)$$

That is, signature of a new appended generator $(\mathbf{e}_{m+1}, f_{m+1})$ should be smaller than the signature of the mutant pair (\mathbf{u}, f) , such that $(\mathbf{e}_{m+1}, f_{m+1})$ will not be reduced to 0. Next, when the second mutant pair is obtained, we append it as the $(m+2)$ th generator, and so on. This appending method was mentioned in (Sun and Wang, 2009) by authors.

In order to ensure termination of this variant algorithm, when we meet a mutant polynomial (\mathbf{u}, f) , we usually do not append f as the k -th generator directly. Instead, we compute the remainder of f w.r.t. the previous $k-1$ existing generators $\{f_1, \dots, f_{k-1}\}$ by polynomial division first (defined in (Cox et al., 2006)) without consideration of signatures, and denote the remainder as f' . If $f' \neq 0$, then $\text{lm}(f')$ is not divisible by any $\text{lm}(f_i)$ where $1 \leq i < k$, and then we add (\mathbf{e}_k, f') as the k -th generator. Please note that f' is in the ideal generated by $\{f_1, \dots, f_{k-1}\}$.

Next we give M-GVW below. Function $\text{Rem}(f, F)$ computes a remainder of f w.r.t. F by polynomial division.

Theorem 2.4. *The M-GVW algorithm terminates in finite steps, if monomial orderings in R^m and R are compatible.*

Proof. At step 17-20 of M-GVW, a new generator is appended when $(tx^\alpha \mathbf{e}_i, h)$ is mutant and the remainder of h , say h' , w.r.t. $\{f_1, \dots, f_{\text{index}}\}$ is not 0. If $h' \neq 0$, the ideal $\langle \text{lm}(f_1), \dots, \text{lm}(f_{\text{index}}) \rangle$ is strictly smaller than $\langle \text{lm}(f_1), \dots, \text{lm}(f_{\text{index}}), \text{lm}(h') \rangle$. Ascending chain condition of ideals (Cox et al., 2006) implies M-GVW can only append finite many new generators. That is, after appending some generator (\mathbf{e}_l, f_l) , no more generators will be appended. In this case, M-GVW turns to be GVW, and the termination is ensured by Theorem 3.1 of (Gao et al., 2010). \square

Theorem 2.5. *The M-GVW algorithm is correct.*

Proof. Clearly, we have $f_{\text{index}+1} \in \langle f_1, \dots, f_{\text{index}} \rangle$ for $\text{index} \geq m$. Assume (\mathbf{e}_l, f_l) is the last generator appended in M-GVW. In this case, M-GVW turns to be GVW, and M-GVW computes a Gröbner basis for $\langle f_1, \dots, f_l \rangle = \langle f_1, \dots, f_m \rangle$ by Theorem 2.2 of (Gao et al., 2010). \square

There are some remarks on M-GVW.

1. Since we always make requirement like (1), we prefer \prec_s to be a *position over term extension* of \prec_p in M-GVW with $\mathbf{e}_1 \succ \mathbf{e}_2 \succ \dots \succ \mathbf{e}_m \succ \dots$.

Algorithm 2: The M-GVW algorithm

Input : $f_1, \dots, f_m \in R = K[x_1, \dots, x_n]$, monomial orderings for R and R^m .

Output: A Gröbner basis of $I = \langle f_1, \dots, f_m \rangle$.

```

1 begin
2    $H \leftarrow \{\text{lm}(f_j \mathbf{e}_i - f_i \mathbf{e}_j) \mid 1 \leq i, j \leq m\}$ 
3    $G \leftarrow \{(\text{lm}(\mathbf{e}_i), f_i) \mid 1 \leq i \leq m\}$ 
4    $\text{index} \leftarrow m$ 
5    $\text{JP} \leftarrow \{\text{all J-pairs of } G\}$ 
6   while  $\text{JP} \neq \emptyset$  do
7     Let  $t(x^\alpha \mathbf{e}_i, f) \in \text{JP}$ 
8      $\text{JP} \leftarrow \text{JP} \setminus \{t(x^\alpha \mathbf{e}_i, f)\}$ 
9     if  $tx^\alpha \mathbf{e}_i$  is divisible by monomials in  $H$  then
10      GotoStep5 (Syzygy Criterion)
11     if  $t(x^\alpha \mathbf{e}_i, f)$  is covered by  $G$  then
12      GotoStep5 (Rewriting Criterion)
13      $(tx^\alpha \mathbf{e}_i, h) \leftarrow \text{Regular top-reduce } t(x^\alpha \mathbf{e}_i, f) \text{ by } G.$ 
14     if  $h = 0$  then
15        $H \leftarrow H \cup \{tx^\alpha \mathbf{e}_i\}$ 
16       GotoStep5
17     if  $\deg(tx^\alpha) + \deg(f_i) > \deg(h)$  and  $\text{Rem}(h, \{f_1, \dots, f_{\text{index}}\}) \neq 0$  then
18        $f_{\text{index}+1} \leftarrow \text{Rem}(h, \{f_1, \dots, f_{\text{index}}\})$ 
19        $\text{index} \leftarrow \text{index} + 1$ 
20       Denote  $(\mathbf{e}_{\text{index}}, f_{\text{index}})$  as  $(x^\gamma \mathbf{e}_k, p)$ 
21     else
22       Denote  $(tx^\alpha \mathbf{e}_i, h)$  as  $(x^\gamma \mathbf{e}_k, p)$ 
23     for  $(x^\beta \mathbf{e}_j, g) \in G, \text{lm}(g)x^\gamma \mathbf{e}_k \neq \text{lm}(p)x^\beta \mathbf{e}_j$  do
24        $H \leftarrow H \cup \{\max(\text{lm}(g)x^\gamma \mathbf{e}_k, \text{lm}(p)x^\beta \mathbf{e}_j)\}$ 
25        $\text{JP} \leftarrow \text{JP} \cup \{\text{J-pair of } (x^\gamma \mathbf{e}_k, p) \text{ and } (x^\beta \mathbf{e}_j, g)\}$ 
26      $G \leftarrow G \cup \{(x^\gamma \mathbf{e}_k, p)\}$ 
27   return  $\{g \mid (x^\beta \mathbf{e}_j, g) \in G\}$ 

```

2. In practical implementation, we usually do not append all mutant pairs as new generators. Because appending generators with high degrees often make the implementation less efficient, and too many generators will also weaken the power of Syzygy Criterion. So we usually add a constraint “ $\deg(h) < \text{Deg-Limit}$ ” at Step 17, where Deg-Limit is a given constant.
3. Mutant pairs cannot be found in M-GVW when input systems are *homogeneous*. In this case, M-GVW is just the GVW algorithm.

3. An implementation with linear algebra over boolean polynomial rings

In this section, we give an implementation of M-GVW based on the dense matrix library M4RI, and show some details in our implementation.

The polynomial ring is specialized as $R = \mathbb{F}_2[x_1, x_2, \dots, x_n]$ with n variables over the Galois Field $GF(2)$. Polynomials $E = \{x_1^2 + x_1, \dots, x_n^2 + x_n\}$ are called field polynomials. Let $F = \{f_1, \dots, f_m\}$ be a subset of R . Then computing a Gröbner basis for the ideal generated by F over the boolean polynomial ring $R/\langle E \rangle$, is equivalent to computing a Gröbner basis for the ideal generated by $F \cup E$ over R . In our implementation, we aim to compute Gröbner bases for $F \cup E$ over R , so all the operations are done in R . In fact, since field polynomials have quite special forms, we do not need to store them in practical implementations, moreover, normal forms of polynomials in R w.r.t. E are also done automatically.

We specialize the monomial ordering \prec_p on R to be the *Graded Reverse Lexicographic ordering*. And monomial ordering \prec_s on modules is a *position over term extension* of \prec_p , such that $\mathbf{e}_1 \succ_s \mathbf{e}_2 \succ_s \dots$. Note that \mathbf{e}_j 's corresponding to field polynomials are always smaller than other non-field polynomials, even if new generators are appended, such that field polynomials can always be used for reductions.

In Subsection 3.1, we write M-GVW in a matrix style. In Subsection 3.2, we show how to do reductions efficiently based on matrices.

3.1. M-GVW in matrix style

The matrix version of M-GVW is quite similar to the F4 algorithm. The main function is given below.

Function *SymbolicProcess*($JPdeg', G$) will do three things. First, compute J-pairs from $JPdeg'$. Second, for each monomial that is not a leading monomial, search polynomials from G to reduce it. Third, sort all pairs according their signatures, and if there are several pairs having the same signature, retain only one of them. Denote $M(P)$ be the set of all monomials in h for any $(x^\gamma \mathbf{e}_k, h) \in P$.

This function is a bit different from Albrecht-Perry's version (Albrecht and Perry, 2010). First, any monomial m can be selected from $M(P) \setminus Done$, while in (Albrecht and Perry, 2010) the maximal one is selected each time. Second, for any selected monomial m , we do not need to know any signature information about it.

Function *Elimination*(P) will also do three things. First, write pairs in P as rows of a matrix. Second, compute the echelon form of this matrix. Third, read polynomials from rows of this matrix. In the first step, building matrices from boolean polynomials is different from building matrices from general polynomials, because the product of a monomial and a boolean polynomial should be reduced by field polynomials automatically. We report our method in (Sun et al., 2013) and omit details here. The second step is critical. We do not use naive Gaussian eliminations, and want to use efficient divide-and-conquer eliminating methods from M4RI to improve efficiencies. However, in signature-based algorithms, since rows with higher signatures can only be eliminated by rows with lower signatures, functions

Algorithm 3: M-GVW in matrix style

Input : $f_1, \dots, f_m \in R = K[x_1, \dots, x_n]$, monomial orderings for R and R^m .

Output: A Gröbner basis of $I = \langle f_1, \dots, f_m \rangle$.

```
1 begin
2    $H \leftarrow \{\text{lm}(f_j \mathbf{e}_i - f_i \mathbf{e}_j) \mid 1 \leq i, j \leq m\}$ 
3    $G \leftarrow \{(\text{lm}(\mathbf{e}_i), f_i) \mid 1 \leq i \leq m\}$ 
4    $\text{index} \leftarrow m$ 
5    $\text{JP} \leftarrow \{\text{all J-pairs of } G\}$ 
6   while  $\text{JP} \neq \emptyset$  do
7      $\text{deg} \leftarrow$  the minimal degree of J-pairs in JP
8      $\text{JPdeg} \leftarrow$  all J-pairs with degree  $\text{deg}$  in JP
9      $\text{JP} \leftarrow \text{JP} \setminus \text{JPdeg}$ 
10     $\text{JPdeg}' \leftarrow$  discard J-pairs that are rejected by Syzygy and Rewriting
        Criterion from JP
11     $P \leftarrow \text{SymbolicProcess}(\text{JPdeg}', G)$  (element in P has a form of  $(x^\alpha \mathbf{e}_i, f)$ )
12     $F \leftarrow \text{Elimination}(P)$  (element in F has a form of  $(x^\alpha \mathbf{e}_i, h)$ )
13     $F^+ \leftarrow F \setminus \{\text{pairs are super top-reducible by } G\}$ 
14    for each  $(x^\alpha \mathbf{e}_i, h) \in F^+$  s.t.  $h = 0$  do
15       $H \leftarrow H \cup \{x^\alpha \mathbf{e}_i\}$ 
16    for each  $(x^\alpha \mathbf{e}_i, h) \in F^+$  s.t.  $h \neq 0$  do
17      if  $\deg(tx^\alpha) + \deg(f_i) > \deg(h)$  and  $\deg(h) < \text{Deg-Limit}$  and
         $\text{Rem}(h, \{f_1, \dots, f_{\text{index}}\}) \neq 0$  then
18         $f_{\text{index}+1} \leftarrow \text{Rem}(h, \{f_1, \dots, f_{\text{index}}\})$ 
19         $\text{index} \leftarrow \text{index} + 1$ 
20        Denote  $(\mathbf{e}_{\text{index}}, f_{\text{index}})$  as  $(x^\gamma \mathbf{e}_k, p)$ 
21      else
22        Denote  $(tx^\alpha \mathbf{e}_i, h)$  as  $(x^\gamma \mathbf{e}_k, p)$ 
23      for  $(x^\beta \mathbf{e}_j, g) \in G$ ,  $\text{lm}(g)x^\gamma \mathbf{e}_k \neq \text{lm}(p)x^\beta \mathbf{e}_j$  do
24         $H \leftarrow H \cup \{\max(\text{lm}(g)x^\gamma \mathbf{e}_k, \text{lm}(h)x^\beta \mathbf{e}_j)\}$ 
25         $\text{JP} \leftarrow \text{JP} \cup \{\text{J-pair of } (x^\gamma \mathbf{e}_k, p), (x^\beta \mathbf{e}_j, g)\}$ 
26       $G \leftarrow G \cup \{(x^\gamma \mathbf{e}_k, p)\}$ 
27  return  $\{g \mid (x^\beta \mathbf{e}_j, g) \in G\}$ 
```

from M4RI can not be used directly. So we use a special kind of row swaps to replace original row swaps in M4RI, which will be discussed in the next subsection.

For doing criteria check, similarly as discussed in (Albrecht and Perry, 2010), we maintain two arrays of “rules” for Syzygy and Rewriting Criteria respectively. In “rules” of Rewriting Criterion, we sort pairs according to “ratios” of pairs, which is first introduced in (Roune and Stillman, 2012).

Algorithm 4: SymbolicProcess

Input : JP, a set of J-pairs, G , a set of pairs.

Output: P , element in P has a form of $(x^\alpha \mathbf{e}_i, f)$.

```
1 begin
2    $P \leftarrow \emptyset$ 
3   for each  $t(x^\alpha \mathbf{e}_i, f)$  in JP do
4      $P \leftarrow P \cup \{(tx^\alpha \mathbf{e}_i, tf)\}$ 
5    $\text{Done} \leftarrow \{\text{lm}(h) \mid (x^\gamma \mathbf{e}_k, h) \in P\}$ 
6   while  $M(P) \neq \text{Done}$  do
7      $m \leftarrow$  an element of  $M(P) \setminus \text{Done}$ 
8      $\text{Done} \leftarrow \text{Done} \cup \{m\}$ 
9     if  $\exists (x^\beta \mathbf{e}_j, g) \in G$  s.t. (1)  $\text{lm}(g) \mid m$ , and (2)  $t(x^\beta \mathbf{e}_j, g)$  are not rejected by
       Syzygy and Rewriting Criterion, where  $t = m/\text{lm}(g)$  then
10       $P \leftarrow P \cup \{t(x^\beta \mathbf{e}_j, g)\}$ 
11   Sort  $P$  by an increasing order on signatures, and if there are several pairs having
       the same signature, retain only one of them.
12 return  $P$ 
```

3.2. Elimination

Unlike eliminations in F4, eliminations in signature-based algorithm can only be done from one side. That is, each row of matrix has a signature, and rows with higher signatures can only be reduced by rows with lower signatures. Naive Gaussian eliminations can control eliminating directions easily. But to use efficient divide-and-conquer strategy as well as efficient implementation of matrices multiplications in the library M4RI (Albrecht and Bard, 2013), we allow eliminations to swap rows in a special manner. This strategy is a bit similar to the ideas in (Dumas et al., 2013).

Let A be a matrix with entries in \mathbb{F}_2 . Assume A has the following form:

$$\begin{array}{l} S_1 \\ S_2 \\ S_3 \\ S_4 \\ S_5 \\ S_6 \end{array} \begin{pmatrix} 0 & 1 & * & * & * & * \\ 0 & 0 & 0 & 1 & * & * \\ 0 & 0 & 1 & * & * & * \\ 0 & 1 & * & * & * & * \\ \textcolor{blue}{1} & * & * & * & * & * \\ 1 & * & * & * & * & * \end{pmatrix},$$

where “*” may be 1 or 0, S_i is the signature of each row, and we assume $S_1 \prec_s S_2 \prec_s \dots \prec_s S_6$.

To reduce A to row-echelon form, we first find the pivot entry in the first column. We must search the pivot entry from top to bottom (i.e. from lower signatures to higher signatures). Then we find the entry at row 5 and col 1 is a pivot. If we use general methods of elimination, we need to swap row 1 and row 5 directly, and clear entries at column 1 by

the row with signature S_5 . Next, when doing elimination in the second column, the row with signature S_4 is selected as pivot row, and needs to eliminate other rows. However, this will leads to errors in signature-based algorithms, because the row with signature S_1 has a smaller signature than S_4 and cannot be eliminated by the row with signature S_4 . So we cannot swap row 1 and row 5 directly.

So to make further eliminations correct, we swap row 1 and row 5 in a special manner. First, we pick up the row 5 with signature S_5 . Second, we move rows 4, 3, 2, and 1 to rows 5, 4, 3, and 2 respectively. At last, we put the row with signature S_5 at row 1. After this swap, matrix A becomes the following form.

$$\begin{matrix} S_5 \\ S_1 \\ S_2 \\ S_3 \\ S_4 \\ S_6 \end{matrix} \begin{pmatrix} 1 & * & * & * & * & * \\ 0 & 1 & * & * & * & * \\ 0 & 0 & 0 & 1 & * & * \\ 0 & 0 & 1 & * & * & * \\ 0 & 1 & * & * & * & * \\ 1 & * & * & * & * & * \end{pmatrix}.$$

Next, we use the row with S_5 to clear all entries at column 1 below this row, and then column 1 is done. For column 2, we find pivots from rows with S_1, \dots, S_4 and S_6 , and repeat the above processes. Elimination terminates when the matrix becomes an upper triangular form.

This swap makes eliminations correct in signature-based algorithm for the following reasons. On one hand, since pivot rows (e.g. row of S_5) are finding from low signatures to high signatures, rows with smaller signature (e.g. rows of S_1, \dots, S_4) cannot be reduced by pivot rows (e.g. row of S_5). On the other hand, after swaps, rows below pivot rows (e.g. rows of S_1, \dots, S_4 and S_6) are still in an increasing order on signatures.

Using this special swap, the echelon form of A is in an upper triangular form, such that divide-and-conquer methods of PLE decomposition (Albrecht and Pernet, 2011) can be used, and hence, the eliminations can be speeded up significantly.

In our implementation, we modify many subroutines of *mzd_ple()* in M4RI library to use this swap. The new function with the special swap is called *gvw_ple()*. We compare the efficiency of *mzd_ple()* and *gvw_ple()* in the next section. The results show both functions almost have the same efficiency.

4. Timings

M-GVW over boolean polynomial rings has been implemented in C++ and the library M4RI (version 20130416) is used (Albrecht and Bard, 2013). The codes will be available at <http://www.mmrc.iss.ac.cn/~dwang/software.html> sooner.

In Table 1, we test the efficiency of the function *gvw_ple()*, which is modified from *mzd_ple()* by using the new swap method. Examples with density $\approx 50\%$ are generated randomly by routines from M4RI. Since the densities of matrices in Gröbner basis computations are usually very small, we also generate some randomized matrices with density $\approx 3\%$.

The first column in Table 1 is the size of matrices, and the timings in this table are given by seconds.

Tests	density $\approx 50\%$		density $\approx 3\%$	
	mzd_ple()	gvw_ple()	mzd_ple()	gvw_ple()
$10,000 \times 10,000$	0.378	0.382	0.345	0.354
$10,000 \times 30,000$	1.342	1.301	1.268	1.262
$30,000 \times 10,000$	1.432	1.443	1.403	1.418
$30,000 \times 30,000$	7.661	7.655	7.604	7.577
$30,000 \times 60,000$	18.684	18.671	18.651	18.634
$60,000 \times 30,000$	19.396	19.296	19.282	19.298
$60,000 \times 60,000$	58.373	58.636	54.509	54.263
$60,000 \times 100,000$	123.321	123.298	119.479	122.523
$100,000 \times 60,000$	119.991	118.388	108.565	108.501
$100,000 \times 100,000$	266.817	267.191	237.401	237.560
$150,000 \times 150,000$	817.682	817.750	700.032	700.781

Table 1: mzd_ple() vs gvw_ple()

From the above table, we can see the function *mzd_ple()* and *gvw_ple()* almost have the same efficiency. So the new swapping method presented in the last section does not slow down the efficiency of elimination.

In Table 2, we compare our implementations of the algorithm GVW and M-GVW. The size of maximal matrices generated during the computation and the timings are given in details, and the numbers of mutants pairs are also listed. In both implementations, orderings of signatures are both position over term extensions of the Graded Reverse Lexicographic ordering. In M-GVW, the parameter Deg-Limit is set to 4. In the column of Exam., $n \times n$ means that the input polynomial system has n polynomials with n variables. These square polynomial systems were generated by Courtois in (Courtois, 2013). The left three HFE systems are from (Steel, 2004). The Computer we used is MacBook Pro with 2.6 GHz Intel Core i7, 16 GB memory.

Exam.	GVW		M-GVW		
	max mat.(deg)	time(sec)	max mat.(deg)	time(sec)	mutant pairs
16×16	$9378 \times 6861(5)$	0.560	$9378 \times 6861(5)$	0.543	0
17×17	$12012 \times 9354(5)$	0.893	$12012 \times 9354(5)$	0.895	0
18×18	$15240 \times 12569(5)$	1.556	$15240 \times 12569(5)$	1.588	0
19×19	$19043 \times 16613(5)$	2.742	$19043 \times 16613(5)$	2.728	0
20×20	$23478 \times 21640(5)$	4.676	$23478 \times 21640(5)$	4.664	0
21×21	$28718 \times 27839(5)$	14.991	$28718 \times 27839(5)$	8.226	924
22×22	$34777 \times 35383(5)$	28.947	$34777 \times 35383(5)$	28.840	0
HFE_25_96	$63341 \times 68298(5)$	131.806	$14271 \times 15222(4)$	3.418	300
HFE_30_96	$141708 \times 174303(5)$	1504.289	$22745 \times 31861(4)$	15.168	360
HFE_35_96	$248520 \times 383915(5)$	$> 1h$	$33929 \times 59410(4)$	57.988	420

Table 2: GVW vs M-GVW

From this table, we can find that the maximal size of the matrix generated during the computations are exactly the same for Courtois' examples except 21×21 , and the corresponding computing time are also almost the same. This is because we can not find mutant polynomials with degree lower than 4 for these examples. It is a little bit surprised that we find 924 mutant pairs with degree smaller than 4 in the example 21×21 . For the HFE examples, M-GVW performs much better than GVW because many mutant polynomials have been found in M-GVW and the maximal size of the matrix in M-GVW become much smaller than that in GVW, which leads that M-GVW cost less computing time.

We also test the same examples as in Table 2 for M-GVW and some intrinsic implementations on public softwares, including Gröbner basis functions on Maple (version 17, setting "method = fgb"), Singular (version 3-1-6), and Magma (version 2.12-16)³, and the computing times in seconds are listed in Table 3.

Exam.	Maple	Singular	Magma	M-GVW
16×16	4.088	5.210	0.484	0.543
17×17	9.891	12.886	0.874	0.895
18×18	22.340	31.590	1.513	1.588
19×19	48.314	84.771	2.792	2.728
20×20	107.064	265.325	5.226	4.664
21×21	218.479	724.886	10.468	8.226
22×22	839.067	$> 1h$	37.144	28.840
HFE_25_96	121.681	$> 1h$	7.675	3.418
HFE_30_96	619.745	$> 1h$	29.172	15.168
HFE_35_96	2229.239	$> 1h$	out mem.	57.988

Table 3: Maple, Singular and Magma vs M-GVW

³Magma 2.12-16 is an old version, and we are trying to buy the latest one.

From the above table, we can see that, due to the efficiency of routines from M4RI, our implementation of M-GVW is more efficient than some of functions from existing public softwares. However, since the matrices in large polynomial systems become quite sparse, our implementation may not perform very good for large systems at present.

5. Conclusions

In this paper, we present M-GVW to avoid criteria rejecting J-pairs with lower degrees. M-GVW is exactly the same as GVW when input systems are homogeneous, but have a better performance when input systems are inhomogeneous. Due to the efficient routines from M4RI, we also give an efficient implementation of M-GVW using linear algebra over boolean polynomial rings. We think our implementation can be optimized further, and we will try to use sparse linear algebra to improve the performance of M-GVW in the future.

References

- M. Albrecht and J. Perry. F4/5. Preprint, arXiv:1006.4933v2 [math.AC], 2010.
- M. Albrecht and C. Pernet. Efficient decomposition of dense matrices over GF(2). Arxiv.org: 1006.1744, 2011.
- M. Albrecht and G. Bard. The M4RI library – Version 20130416. 2013. <http://m4ri.sagemath.org>.
- A. Arri and J. Perry. The F5 criterion revised. J. Symb. Comput. vol 46, 1017-1029, 2011.
- B. Buchberger. Ein Algorithmus zum auffinden der Basiselemente des Restklassenringes nach einem nulldimensionalen Polynomideal. PhD thesis, 1965.
- B. Buchberger. A criterion for detecting unnecessary reductions in the construction of Gröbner basis. In Proceedings of EUROSAM’79, Lect. Notes in Comp. Sci., Springer, Berlin, vol. 72, 3-21, 1979.
- N. Courtois, A. Klimov, J. Patarin, and A. Shamir. Efficient algorithms for solving overdefined systems of multivariate polynomial equations. In proc. EUROCRYPT’00, Lect. Notes in Comp. Sci., Springer, Berlin, vol. 1807, 392-407, 2000.
- N. Courtois. Benchmarking algebraic, logical and constraint solvers and study of selected hard problems, 2013. <http://www.cryptosystem.net/aes/hardproblems.html>.
- D. Cox, J. Little, and D. O’Shea. Ideals, Varieties and Algorithms. Springer, New York, third edition, 2006.
- J. Ding, J. Buchmann, M.S.E. Mohamed, W.S.A.E. Mohamed, and R.-P. Weinmann. MutantXL. In Proceedings of the 1st international conference on Symbolic Computation and Cryptography (SCC08), Beijing, China, 16-22, 2008.
- J.-G. Dumas, C. Pernet, and Z. Sultan. Simultaneous computation of the row and column rank profiles. In Proc. In proc. ISSAC’13, ACM Press, New York, USA, 2013.
- C. Eder and J. Perry. F5C: a variant of Faugère’s F5 algorithm with reduced Gröbner bases. J. Symb. Comput., vol. 45(12), 1442-1458, 2010.
- C. Eder. An analysis of inhomogeneous signature-based Gröbner basis computations. J. Symb. Comput., vol 59, 21-35, 2013.
- C. Eder and B.H. Roune. Signature rewriting in Gröbner basis computation. In proc. ISSAC’13, ACM Press, New York, USA, 331-338, 2013.
- J.-C. Faugère. A new efficient algorithm for computing Gröbner bases (F_4). J. Pure Appl. Algebra, vol. 139(1-3), 61-88, 1999.
- J.-C. Faugère. A new efficient algorithm for computing Gröbner bases without reduction to zero (F_5). In proc. ISSAC’02, ACM Press, New York, USA, 75-82, 2002.
- J.-C. Faugère and A. Joux. Algebraic cryptanalysis of Hidden Field Equation (HFE) cryptosystems using Gröbner bases. In proc. CRYPTO’03, LNCS, vol. 2729, 44-60, springer Berlin/Heidelberg, 2003.

- J.-C. Faugère and S. Rahmany. Solving systems of polynomial equations with symmetries using SAGBI-Gröbner bases. In proc. ISSAC '09, ACM Press, New York, USA, 151-158, 2009.
- J.-C. Faugère and S. Lachartre. Parallel Gaussian elimination for Gröbner bases computations in finite fields. In proc. PASCO'10, ACM Press, 89-97, 2010.
- S.H. Gao, Y.H. Guan, and F. Volny. A new incremental algorithm for computing Gröbner bases. In proc. ISSAC'10, ACM Press, New York, USA, 13-19, 2010.
- S.H. Gao, F. Volny, and M.S. Wang. A new algorithm for computing Gröbner bases. Cryptology ePrint Archive, Report 2010/641, 2010. Latest version is given in July, 2013, and downloaded from <http://www.math.clemson.edu/~sgao/pub.html>.
- A. Hashemi and G. Ars. Extended F5 criteria. J. Symb. Comput., vol. 45(12), 1330-1340, 2010.
- D. Lazard. Gröbner bases, Gaussian elimination and resolution of systems of algebraic equations. In proc. EUROCAL'83, Lect. Notes in Comp. Sci., Springer, Berlin, vol. 162, 146-156, 1983.
- B.H. Roune and M. Stillman. Practical Gröbner basis computation. In proc. ISSAC'12, ACM Press, 2012.
- A. Steel. Allan Steel's Gröbner basis timings page. 2004. <http://magma.maths.usyd.edu.au/~allan/gb/>.
- Y. Sun and D.K. Wang. The implementation and complexity analysis of the branch Gröbner bases algorithm over Boolean ring. In proc. ASCM 2009, 191-200, 2009.
- Y. Sun and D.K. Wang. A generalized criterion for signature related Gröbner basis algorithms. In Proc. ISSAC'11, ACM Press, 337-344, 2011.
- Y. Sun, D.K. Wang, D.X. Ma, and Y. Zhang. A signature-based algorithm for computing Gröbner bases in solvable polynomial algebras. In Proc. ISSAC'12, ACM Press, 351-358, 2012.
- Y. Sun and D.K. Wang. A new proof for the correctness of the F5 algorithm. Sci. China Math., vol. 56(4), 745-756, 2013.
- Y. Sun, D.D. Lin, and D.K. Wang. On Implementing the Symbolic Preprocessing Function over Boolean Polynomial Rings in Gröbner Basis Algorithms Using Linear Algebra. Preprint, 2014.