

Stability of Influence Maximization

Xinran He ^{*} David Kempe [†]

March 3, 2022

Abstract

The present article serves as an erratum to our paper of the same title, which was presented and published in the KDD 2014 conference. In that article, we claimed falsely that the objective function defined in Section 1.4 is non-monotone submodular. We are deeply indebted to Debmalya Mandal, Jean Pouget-Abadie and Yaron Singer for bringing to our attention a counter-example to that claim.

Subsequent to becoming aware of the counter-example, we have shown that the objective function is in fact NP-hard to approximate to within a factor of $O(n^{1-\epsilon})$ for any $\epsilon > 0$.

In an attempt to fix the record, the present article combines the problem motivation, models, and experimental results sections from the original incorrect article with the new hardness result. We would like readers to only cite and use this version (which will remain an unpublished note) instead of the incorrect conference version.

arXiv:1501.04579v2 [cs.SI] 15 Apr 2015

^{*}Department of Computer Science, University of Southern California; xinranhe@usc.edu

[†]Department of Computer Science, University of Southern California; dkempe@usc.edu

1 Introduction

The processes and dynamics by which information and behaviors spread through social networks have long interested scientists within many areas. Understanding such processes has the potential to shed light on human social structure, and to impact the strategies used to promote behaviors or products. While the interest in the subject is long-standing, recent increased availability of social network and information diffusion data (through sites such as Facebook, Twitter, and LinkedIn) has raised the prospect of applying social network analysis at a large scale to positive effect. Consequently, the resulting algorithmic questions have received widespread interest in the computer science community.

Among the broad algorithmic domains, Influence Maximization has been repeatedly held up as having the potential to be of societal and financial value. The high-level hope is that based on observed data — such as social network information and past behavior — an algorithm could infer which individuals are likely to influence which others. This information could in turn be used to effect desired behavior, such as refraining from smoking, using superior crops, or purchasing a product. In the latter case, the goal of effecting desired behavior is usually termed *viral marketing*.

Consequently, both the problem of inferring the influence between individuals [11, 12, 13, 14, 23] and that of maximizing the spread of a desired behavior have been studied extensively. For the Influence Maximization problem, a large number of models have been proposed, along with many heuristics with and without approximation guarantees [5, 8, 9, 17, 18, 20, 22, 25, 26]. (See the monograph [7] for a recent overview of work in the area.)

However, one crucial aspect of the problem has — with very few exceptions discussed in Section 1.6 — gone largely unstudied. Contrary to many other algorithmic domains, *noise in social network data is not an exception, but the norm*. Indeed, one could argue that the very notion of a “social link” is not properly defined in the first place, so that any representation of a social network is only an approximation of reality. This issue is much more pronounced for a goal such as Influence Maximization. Here, the required data include, for every pair (u, v) of individuals, a numerical value for the strength of influence from u to v and vice versa. This influence strength will naturally depend on context (e.g., what exact product or behavior is being spread); furthermore, it cannot be observed directly, and must therefore be inferred from observed behavior or individuals’ reports; all of these are inherently very noisy.

When the inferred influence strength parameters differ from the actual ground truth, even an optimal algorithm is bound to return suboptimal solutions, for it will optimize the wrong objective function: a solution that appears good with respect to the incorrect parameters may be bad with respect to the actual ones. If relatively small errors in the inferred parameters could lead to highly suboptimal solutions, this would cast serious doubts on the practical viability of algorithmic influence maximization. *Therefore, in the present paper, we begin an in-depth study of the effect of noise on the performance of Influence Maximization algorithms.*

1.1 The Independent Cascade Model

We study this question under two widely adopted models for influence diffusion [17]: the *Independent Cascade (IC) Model* and the *Linear Threshold (LT) Model*. Both of these models fit in the following framework: The algorithm selects a *seed set* A_0 of k nodes, which begin *active* (having adopted the behavior). Starting with A_0 , the process proceeds in discrete time steps: in each time step, according to a probabilistic process, additional nodes may become active based on the influence from their neighbors. Active nodes never become inactive, and the process terminates when no new nodes become active in a time step. The goal is to maximize the expected number of active nodes when the process terminates; this expected number is denoted by $\sigma(A_0)$.

To illustrate the questions and approaches, we describe the IC model in this section. (A formal description of the LT model and general definitions of all concepts are given in Section 2.) Under the IC model, the probabilistic process is particularly simple and intuitive. When a node u becomes active in step t , it attempts to activate all currently inactive neighbors in step $t + 1$. For each neighbor v , it succeeds with a known probability $p_{u,v}$. If it succeeds, v becomes active; otherwise, v remains inactive. Once u has made all these attempts, it does not get to make further activation attempts at later times. It was shown in [17] that

the set of nodes active at the end can be characterized alternatively as follows: for each ordered pair (u, v) independently, insert the directed edge (u, v) with probability $p_{u,v}$. Then, the active nodes are exactly the ones reachable via directed paths from A_0 .

1.2 Can Instability Occur?

Suppose that we have inferred all parameters $p_{u,v}$, but are concerned that they may be slightly off: in reality, the influence probabilities are $p'_{u,v} \approx p_{u,v}$. Are there instances in which a seed set A_0 that is very influential with respect to the $p_{u,v}$ may be much less influential with respect to the $p'_{u,v}$? It is natural to suspect that this might not occur: when the objective function σ varies sufficiently smoothly with the input parameters (e.g., for linear objectives), small changes in the parameters only lead to small changes in the objective value; therefore, optimizing with respect to a perturbed input still leads to a near-optimal solution.

However, the objective σ of Influence Maximization does not depend on the parameters in a smooth way. To illustrate the issues at play, consider the following instance of the IC model. The social network consists of two disjoint bidirected cliques K_n , and $p_{u,v} = \hat{p}$ for all u, v in the same clique; in other words, for each directed edge, the same activation probability \hat{p} is observed. The algorithm gets to select exactly $k = 1$ node. Notice that because all nodes look the same, any algorithm essentially chooses an arbitrary node, which may as well be from Clique 1.

Let $\hat{p} = 1/n$ be the sharp threshold for the emergence of a giant component in the Erdős-Rényi Random Graph $G(n, p)$. It is well known [4, 10] that the largest connected component of $G(n, p)$ has size $O(\log n)$ for any $p \leq \hat{p} - \Omega(1/n)$, and size $\Omega(n)$ for any $p \geq \hat{p} + \Omega(1/n)$. Thus, if unbeknownst to the algorithm, all true activation probabilities in Clique 1 are $p \leq \hat{p} - \Omega(1/n)$, while all true activation probabilities in Clique 2 are $p \geq \hat{p} + \Omega(1/n)$, the algorithm only activates $O(\log n)$ nodes in expectation, while it could have reached $\Omega(n)$ nodes by choosing Clique 2. Hence, small adversarial perturbations to the input parameters can lead to highly suboptimal solutions from any algorithm.¹

1.3 Diagnosing Instability

The example of two cliques shows that there exist *unstable instances*, in which an optimal solution to the observed parameters is highly suboptimal when the observed parameters are slightly perturbed compared to the true parameters. Of course, not every instance of Influence Maximization is unstable: for instance, when the probability \hat{p} in the Two-Clique instance is bounded away from the critical threshold of $G(n, p)$, the objective function varies much more smoothly with \hat{p} . This motivates the following algorithmic question, which is the main focus of our paper: *Given an instance of Influence Maximization, can we diagnose efficiently whether it is stable or unstable?*

To make this question precise, we formulate a model of perturbations. We assume that for each edge (u, v) , in addition to the observed activation probability $p_{u,v}$, we are given an interval $I_{u,v} \ni p_{u,v}$ of values that the *actual probability* $p'_{u,v}$ could assume. The *true values* $p'_{u,v}$ are chosen from the intervals $I_{u,v}$ by an adversary; they induce an objective function σ' which the algorithm would like to maximize, while the observed values induce a different objective function σ which the algorithm actually has access to.

An instance $(p_{u,v}, I_{u,v})_{u,v}$ is *stable* if $|\sigma(S) - \sigma'(S)|$ is small for all objective functions σ' induced by legal probability settings, and for all seed sets S of size k . Here, “small” is defined relative to the objective function value $\sigma(A_0^*)$ of the optimum set.

When $|\sigma(S) - \sigma'(S)|$ is small compared to $\sigma(A_0^*)$ for all sets S , a user can have confidence that his optimization result will provide decent performance guarantees even if his input was perturbed. The converse

¹The example reveals a close connection between the stability of an IC instance and the question whether a uniform activation probability p lies close to the edge percolation threshold of the underlying graph. Characterizing the percolation threshold of families of graphs has been a notoriously hard problem. Successful characterizations have only been obtained for very few specific classes (such as d -dimensional grids [19] and d -regular expander graphs [2]). Therefore, it is unlikely that a clean characterization of stable and unstable instances can be obtained. The connection to percolation also reveals that the instability was not an artifact of having high node degrees. By the result of Alon et al. [2], the same behavior will be obtained if both components are d -regular expander graphs, since such graphs also have a sharp percolation threshold.

is of course not necessarily true: even in unstable instances, a solution that was optimal for the observed input *may* still be very good for the true input parameters.

1.4 Influence Difference Maximization

Trying to determine whether there are a function σ' and a set S for which $|\sigma(S) - \sigma'(S)|$ is large motivates the following optimization problem: Maximize $|\sigma(S) - \sigma'(S)|$ over all feasible functions σ' and all sets S . For any given set S , the objective is maximized either by making all probabilities (and thus $\sigma'(S)$) as small as possible, or by making all probabilities (and thus $\sigma'(S)$) as large as possible.² We denote the resulting two objective functions by σ^- and σ^+ , respectively. The following definition then captures the optimization goal.

Definition 1 (Influence Difference Maximization) *Given two instances with probabilities $p_{u,v} \geq p'_{u,v}$ for all u, v , let σ and σ' be their respective influence functions. Find a set S of size k maximizing $\delta(S) := \sigma(S) - \sigma'(S)$.*

In this generality, the Influence Difference Maximization problem subsumes the Influence Maximization problem, by setting $p'_{u,v} \equiv 0$ (and thus also $\sigma' \equiv 0$).

While Influence Difference Maximization subsumes Influence Maximization, whose objective function is monotone and submodular, the objective function of Influence Difference Maximization is in general neither. To see non-monotonicity, notice that $\delta(\emptyset) = \delta(V) = 0$, while generally $\delta(S) > 0$ for some sets S .

The function is also not in general submodular, a fact brought to our attention by Debmalya Mandal, Jean Pouget-Abadie and Yaron Singer, and in contrast to the main result claimed in a prior version of the present article. The following example shows non-submodularity for both the IC and LT Models.

The graph has four nodes $V = \{u, v, x, y\}$ and three edges $(u, v), (v, x), (x, y)$. The edges (v, x) and (x, y) are known to have an activation probability of 1, while the edge (u, v) has an adversarially chosen activation probability in the interval $[0, 1]$. With $S = \{u\}$ and $T = \{u, x\}$, we obtain that $\delta(S + v) - \delta(S) = |\emptyset| - |\{v, x, y\}| = -3$, while $\delta(T + v) - \delta(T) = |\emptyset| - |\{v\}| = -1$, which violates submodularity.

In fact, we establish a very strong hardness result here, in the form of the following theorem, whose proof is given in Section 3.

Theorem 1 *Under the Independent Cascade Model, the Influence Difference Maximization objective function $\delta(S)$ cannot be approximated better than $n^{1-\epsilon}$ for any $\epsilon > 0$ unless $NP \subseteq ZPP$.*

1.5 Experiments

Next, we investigate how pervasive instabilities are in real data. We evaluate frequently used synthetic models (2D grids, random regular graphs, small-world networks, and preferential attachment graphs) and real-world data sets (computer science theory collaborations and retweets about the Haiti earthquake). We focus on the Independent Cascade Model, and vary the influence strengths over a broad range of commonly studied values. We consider different relative perturbation levels Δ , ranging from 1% to 50%. The adversary can thus choose the actual activation probability to lie in the interval $[(1 - \Delta)p_{u,v}, (1 + \Delta)p_{u,v}]$.

To calculate a value for the maximum possible Influence Difference, we use the random greedy algorithm of Buchbinder et al. [6]. This choice of algorithm was motivated by the false belief that the objective function is submodular, in which case the algorithm would have provided a $1/e$ approximation. Notice, however, that the algorithm can only *underestimate* the maximum possible objective function value. Thus, when the Random Greedy algorithm finds a set with large influence difference, it suggests that the misestimations due to parameter misestimates may drown out the objective value, rendering Influence Maximization outputs very spurious. On the other hand, when the objective value obtained by the Random Greedy algorithm is small, no positive guarantees can be provided.

²This observation relies crucially on the fact that each $p_{u,v}$ can independently take on any value in $I_{u,v}$. If the adversary were constrained by the total absolute deviation or sum of squares of deviations of parameters, this would no longer be the case. This issue is discussed in Section 5.

Our experiments suggest that perturbations can have significantly different effects depending on the network structure and observed values. As a general rule of thumb, perturbations above 20% relative to the parameter values could significantly distort the optimum solution. For smaller errors (10% or less relative error), the values obtained by the algorithm are fairly small; however, as cautioned above, the actual deviations may still be large.

Since errors above 20% should be considered quite common for estimated social network parameters, our results suggest that practitioners exercise care in evaluating the stability of their problem instances, and treat the output of Influence Maximization algorithms with a healthy dose of skepticism.

1.6 Adversarial vs. Random Perturbations

One may question why we choose to study adversarial instead of random perturbations. This choice is for three reasons:

Theoretical: Worst-case analysis provides stronger guarantees, as it is not based on particular assumptions about the distribution of noise.

Practical: Most random noise models assume independence of noise across edges. However, we believe that in practice, both the techniques used for inferring model parameters as well as the data sources they are based on may well exhibit systematic bias, i.e., the noise will not be independent. For instance, a particular subpopulation may systematically underreport the extent to which they seek others’ advice, or may have fewer visible indicators (such as posts) revealing their behavior.

Modeling Interest: Perhaps most importantly, most natural random noise models do not add anything to the IC and LT models. As an illustration, consider the random noise models studied in recent work by Goyal, Bonchi and Lakshmanan [15] and Adiga et al. [1]. Goyal et al. assume that for each edge (u, v) , the value of $p_{u,v}$ is perturbed with uniformly random noise from a known interval. Adiga et al. assume that each edge (u, v) that was observed to be present is actually absent with some probability ϵ , while each edge that was not observed is actually present with probability ϵ ; in other words, each edge’s presence is independently flipped with probability ϵ .

The standard Independent Cascade Model subsumes both models straightforwardly. Suppose that a decision is to be made about whether u activates v . In the model of Goyal et al., we can first draw the actual (perturbed) value of $p'_{u,v}$ from its known distribution; subsequently, u activates v with probability $p'_{u,v}$; in total, u activates v with probability $\mathbb{E}[p'_{u,v}]$. Thus, we obtain an instance of the IC model in which all edge probabilities $p_{u,v}$ are replaced by $\mathbb{E}[p'_{u,v}]$. In the special case when the noise has mean 0, this expectation is exactly equal to $p_{u,v}$, which explains why Goyal et al. observed the noise to not affect the outcome at all.

In the model of Adiga et al., we first determine whether the edge is actually present; when it was observed present, this happens with probability $1 - \epsilon$; otherwise with probability ϵ . Subsequently, the activation succeeds with probability p . ([1] assumed uniform probabilities). Thus, the model is an instance of the IC model in which the activation probabilities on all observed edges are $p(1 - \epsilon)$, while those on unobserved edges are $p\epsilon$. This reduction explains the theoretical results obtained by Adiga et al.

More fundamentally, practically all “natural” random processes that independently affect edges of the graph can be “absorbed into” the activation probabilities themselves; as a result, random noise does not at all play the result of actual noise.

2 Models and Preliminaries

The social network is modeled by a directed graph $G = (V, E)$ on n nodes. All parameters for non-existing edges are assumed to be 0. We first describe models of influence diffusion, and then models of parameter perturbation.

2.1 Influence Diffusion Models

Most of the models for Influence Maximization have been based on the Independent Cascade Model (see Section 1.1) and Linear Threshold Model studied in [17] and their generalizations. Like the Independent Cascade Model, the Linear Threshold Model also proceeds in discrete rounds. Each edge (u, v) is equipped with a weight $c_{u,v} \in [0, 1]$, satisfying $\sum_{u \rightarrow v} c_{u,v} \leq 1$ for all nodes v . (By $u \rightarrow v$, we denote that there is a directed edge (u, v) .) Each node v initially draws a threshold ψ_v independently and uniformly at random from $[0, 1]$. A set A_0 of nodes is activated at time 0, and we use A_t to denote the set of nodes active at time t . In each discrete round t , each node v checks if $\sum_{u \in A_{t-1}, u \rightarrow v} c_{u,v} \geq \psi_v$. If so, v becomes active at time t , and remains active subsequently.

Any instance of the Influence Maximization problem is characterized by its parameters. For the LT model, the parameters are the n^2 edge weights $c_{u,v}$ for all edges (u, v) . Similarly, for the IC model, the parameters are the edge activation probabilities $p_{u,v}$ for all edges (u, v) . To unify notation, we write $\theta = (\theta_{u,v})_{(u,v) \in E}$ for the vector of all parameter values, where $\theta_{u,v}$ could be either $c_{u,v}$ or $p_{u,v}$.

Both the IC and LT model define random processes that continue until the diffusion process quiesces, i.e., no new activations occur. Let $\tau \leq n$ be the (random) time at which this happens. It is clear that $\tau \leq n$ always, since at least one more node becomes active in each round. We denote the stochastic process by $\mathbf{P}_\theta^{\text{Mod}}(A_0) = (A_t)_{t=0}^\tau$, with $\text{Mod} \in \{\text{IC}, \text{LT}\}$ denoting the model. The final set of active nodes is A_τ . We can now formally define the Influence Maximization problem:

Definition 2 (Influence Maximization) *The Influence Maximization problem consists of maximizing the objective $\sigma(A_0) := \mathbb{E}[|A_\tau|]$ (i.e., the expected number of active nodes in the end³), subject to a cardinality constraint $|A_0| \leq k$.*

The key insight behind most prior work on algorithmic Influence Maximization is that the objective function $\sigma(S)$ is a monotone and submodular function of S . This was proved for the IC and LT models in [17], and subsequently for a generalization called Generalized Threshold Model (proposed in [17]) by Mossel and Roch [22].

2.2 Models for Perturbations

To model adversarial input perturbations, we assume that for each of the edges (u, v) , we are given an interval $I_{u,v} = [\ell_{u,v}, r_{u,v}] \subseteq [0, 1]$ with $\theta_{u,v} \in I_{u,v}$. For the Linear Threshold Model, to ensure that the resulting activation functions are always submodular, we require that $\sum_{u \rightarrow v} r_{u,v} \leq 1$ for all nodes v . We write $\Theta = \times_{(u,v) \in E} I_{u,v}$ for the set of all allowable parameter settings. The adversary must guarantee that the ground truth parameter values satisfy $\theta' \in \Theta$; subject to this requirement, the adversary can choose the actual parameter values arbitrarily.

Together, the parameter values θ determine an instance of the Influence Maximization problem. We will usually be explicit about indicating the dependence of the objective function on the parameter setting. We write σ_θ for the objective function obtained with parameter values θ , and only omit the parameters when they are clear from the context. For a given setting of parameters, we will denote by $A_\theta^* \in \text{argmax}_S \sigma_\theta(S)$ a solution maximizing the expected influence under parameter values θ .

2.3 Influence Difference Maximization

In order to capture to what extent adversarial changes in the parameters can lead to misestimates of any set's influence, we are interested in the quantity

$$\max_S \max_{\theta' \in \Theta} |\sigma_\theta(S) - \sigma_{\theta'}(S)|, \tag{1}$$

³Our results carry over unchanged if we assign each node a non-negative value r_v , and the goal is to maximize $\sum_{v \in A_\tau} r_v$. We focus on the case of uniform values for notational convenience only.

where θ denotes the observed parameter values. For two parameter settings θ, θ' with $\theta \geq \theta'$ coordinate-wise, it is not difficult to show using a simple coupling argument that $\sigma_\theta(S) \geq \sigma_{\theta'}(S)$ for all S . Therefore, for any fixed set S , the maximum is attained either by making θ' as large as possible or as small as possible. Hence, solving the following problem is sufficient to maximize (1).

Definition 3 Given an influence model and two parameter settings θ, θ' with $\theta \geq \theta'$ coordinate-wise, define

$$\delta_{\theta, \theta'}(S) = \sigma_\theta(S) - \sigma_{\theta'}(S). \quad (2)$$

Given the set size k , the Influence Difference Maximization (IDM) problem is defined as follows:

$$\begin{aligned} & \text{Maximize} && \delta_{\theta, \theta'}(S) \\ & \text{subject to} && |S| = k. \end{aligned} \quad (3)$$

3 Approximation hardness

In this section, we prove Theorem 1.

Proof of Theorem 1. We establish the approximation hardness of Influence Difference Maximization without any constraint on the cardinality of the seed set A_0 . From this version, the hardness of the constrained problem is inferred easily as follows: if any better approximation could be obtained for the constrained problem, one could simply enumerate over all possible values of k from 1 to n , and retain the best solution, which would yield the same approximation guarantee for the unconstrained problem.

We give an approximation-preserving reduction from the MAXIMUM INDEPENDENT SET problem to the Influence Difference Maximization problem. It is well known that MAXIMUM INDEPENDENT SET cannot be approximated better than $O(n^{1-\epsilon})$ for any $\epsilon > 0$ unless $\text{NP} \subseteq \text{ZPP}$ [16].

Let $G = (V, E)$ be an instance of the MAXIMUM INDEPENDENT SET problem, with $|V| = n$. We construct from G a *directed* bipartite graph G' with vertex set $V' \cup V''$. For each node $v_i \in V$, there are nodes $v'_i \in V'$ and $v''_i \in V''$. The edge set is $E' \cup E''$, where $E' = \{(v'_i, v'_j) \mid (v_i, v_j) \in E\}$, and $E'' = \{(v'_i, v''_i) \mid v_i \in V\}$. All edges of E' are known to have an activation probability of 1, while all edges of E'' have an activation probability from the interval $[0, 1]$.

The difference is maximized by making all probabilities as large for one function (meaning that all edges in $E' \cup E''$ are present deterministically), while making them as small as possible for the other (meaning that exactly the edges in E' are present).

First, let S be an independent set in G . Consider the set $S' = \{v'_i \mid v_i \in S\}$. Each node v''_i with $v_i \in S$ is reachable from the corresponding v'_i in G' , but not in $(V' \cup V'', E')$, because S is independent. Hence, the objective function value obtained in Influence Difference Maximization is at least $|S|$.

Conversely, consider an optimal solution S' to the Influence Difference Maximization problem. Without loss of generality, we may assume that $S' \subseteq V'$: any node $v''_j \in V''$ can be removed from S' without lowering the objective value. Assume that $S := \{v_i \in V \mid v'_i \in S'\}$ is not independent, and that $(v_i, v_j) \in E$ for $v_i, v_j \in S$. Then, removing v'_j from S' cannot lower the Influence Difference Maximization objective value of S' : all of v'_j 's neighbors in V'' contribute 0, as they are reachable using E' already; furthermore, v''_j also does not contribute, as it is reachable using E' from v'_i . Thus, any node with a neighbor in S can be removed from S' , meaning that S is without loss of generality independent in G .

At this point, all the neighbors of S' contribute 0 to the Influence Difference Maximization objective function (because they are reachable under E' already), and the objective value of S' is exactly $|S'| = |S|$. ■

4 Experiments

While we saw in Section 1.2 that examples highly susceptible (with errors of magnitude $\Omega(n)$) to small perturbations exist, the goal of this section is to evaluate experimentally how widespread this behavior is for realistic social networks.

4.1 Experimental Setting

We carry out experiments under the Independent Cascade Model, for six classes of graphs — four synthetic and two real-world. In each case, the model/data give us a simple graph or multigraph. Multigraphs are converted to simple graphs by collapsing parallel edges to a single edge with weight c_e equal to the number of parallel edges; for simple graphs, all weights are $c_e = 1$. The observed probabilities for edges are $p_e = c_e \cdot p$; across experiments, we vary the base probability p to take on the values $\{0.01, 0.02, 0.05, 0.1\}$. The resulting parameter vector is denoted by θ .

The uncertainty interval for e is $I_e = [(1 - \Delta)p_e, (1 + \Delta)p_e]$; here, Δ is an uncertainty parameter for the estimation, which takes on the values $\{1\%, 5\%, 10\%, 20\%, 50\%\}$ in our experiments. The parameter vectors θ^+ and θ^- describe the settings in which all parameters are as large (as small, respectively) as possible.

4.2 Network Data

We run experiments on four synthetic networks and two real social networks. Synthetic networks provide a controlled environment in which to compare observed behavior to expectations, while real social networks may give us indications about the prevalence of vulnerability to perturbations in real networks that have been studied in the past.

Synthetic Networks. We generate synthetic networks according to four widely used network models. In all cases, we generate undirected networks with 400 nodes. The network models are: (1) the 2-dimensional grid, (2) random regular graphs, (3) the Watts-Strogatz Small-World (SW) Model [27] on a ring with each node connecting to the 5 closest nodes on each side initially, and a rewiring probability of 0.1. (4) The Barabási-Albert Preferential Attachment (PA) Model [3] with 5 outgoing edges per node. For all synthetic networks, we select $k = 20$ seed nodes.

Real Networks. We consider two real networks to evaluate the susceptibility of practical networks: one (*STOCFOCS*) is a co-authorship network of theoretical CS papers; the other (*Haiti*) is a Retweet network.

The co-authorship network, *STOCFOCS*, is a multigraph extracted from published papers in the conferences STOC and FOCS from 1964–2001. Each node in the network is a researcher with at least one publication in one of the conferences. For each multi-author paper, we add a complete undirected graph among the authors. As mentioned above, parallel edges are then compressed into a single edge with corresponding weight. The resulting graph has 1768 nodes and 10024 edges. Due to its larger size, we select 50 seed nodes.

The *Haiti* network is extracted from tweets of 274 users on the topic *Haiti Earthquake* in Twitter. For each tweet of user u that was retweeted by v , we add a directed edge (u, v) . We obtain a directed multigraph; after contracting parallel edges, the directed graph has 383 weighted edges. For this network, due to its smaller size, we select 20 seeds.

In all experiments, we work with uniform edge weights p , since — apart from edge multiplicities — we have no evidence on the strength of connections. It is a promising direction for future in-depth experiments to use influence strengths inferred from real-world cascade datasets by network inference methods such as [11, 14, 23].

4.3 Algorithms

Our experiments necessitate the solution of two algorithmic problems: Finding a set of size k of maximum influence, and finding a set of size k maximizing the *influence difference*. The former is a well-studied problem, with a monotone submodular objective function. We simply use the widely known $1 - 1/e$ approximation algorithm due to Nemhauser et al. [24], which is best possible unless $P=NP$.

For the goal of Influence Difference Maximization, we established (in Section 3) that the objective function is hard to approximate better than a factor $O(n^{1-\epsilon})$ for any $\epsilon > 0$. For experimental purposes, we use the *Random Greedy* algorithm of Buchbinder et al. [6], given as Algorithm 1 below. It is a natural generalization of the simple greedy algorithm of Nemhauser et al.: Instead of picking the *best* single element to add in each iteration, it first finds the set of the k individually best single elements (i.e., the elements which when added

to the current set give the largest, second-largest, third-largest, \dots , k^{th} -largest gain). Then, it picks one of these k elements uniformly at random and continues.

This particular choice of algorithm was motivated by an incorrect claim included in a prior version of this work, namely, that the Influence Difference Maximization objective is (non-monotone) submodular. For such functions, the Random Greedy algorithm guarantees at least an 0.266-approximation, and the guarantee improves to nearly $1/e$ when $k \ll n$. Furthermore, the Random Greedy algorithm is simpler and more efficient than other algorithms with slightly superior approximation guarantees. We stress that these guarantees are not obtained for our objective function, as submodularity does not hold.

Algorithm 1 Random Greedy Algorithm

- 1: Initialize: $S_0 \leftarrow \emptyset$
 - 2: **for** $i = 1, \dots, k$ **do**
 - 3: Let $M_i \subseteq V \setminus S_{i-1}$ be the subset of size k maximizing $\sum_{u \in M_i} g(S_{i-1} \cup \{u\}) - g(S_{i-1})$.
 - 4: Draw u_i uniformly at random from M_i .
 - 5: Let $S_i \leftarrow S_{i-1} \cup \{u_i\}$.
 - 6: **end for**
 - 7: Return S_k
-

The running time of the Random Greedy Algorithm is $O(kC|V|)$, where C is the time required to estimate $g(S \cup \{u\}) - g(S)$. In our case, the objective function is #P-hard to evaluate exactly [25, 9], but arbitrarily close approximations can be obtained by Monte Carlo simulation. Since each simulation takes time $O(|V|)$, if we run $M = 2000$ iterations of the Monte Carlo simulation in each iteration, the overall running time of the algorithm is $O(kM|V|^2)$.

A common technique for speeding up the greedy algorithm for maximizing a submodular function is the CELF heuristic of Leskovec et al. [21]. When the objective function is submodular, the standard greedy algorithm and CELF obtain the same result. However, when it is not, the results may be different. In the previous version of this article, we had used the CELF heuristic due to the incorrect belief that the objective function was submodular. In this revised version, we instead report the results from rerunning all the experiments without the use of the CELF heuristic. The single exception is the largest input, the STOCFOCS network. (Here, the greedy algorithm without CELF did not finish in a reasonable amount of time.) For all networks other than STOCFOCS, the results using CELF are not significantly different from the reported results without the CELF optimization. For STOCFOCS, we instead report the result including the CELF heuristic.

4.4 Results

In all our experiments, the results for the Grid and Small-World network are sufficiently similar that we omit the results for grids here. As a first sanity check, we empirically computed $\max_{S:|S|=1} \delta_{\theta^+, \theta^-}(S)$ for the *complete graph* on 200 nodes with $I_e = [1/200 \cdot (1 - \Delta), 1/200 \cdot (1 + \Delta)]$ and $k = 1$. According to the analysis in Section 1.2, we would expect extremely high instability. The results, shown in Table 1, confirm this expectation.

Δ	σ_{θ^+}	σ_{θ^-}
50%	66.529	1.955
20%	23.961	4.253
10%	15.071	6.204

Table 1: Instability for the clique K_{200} .

Next, Figure 1 shows the (approximately) computed values $\max_{S:|S|=k} \delta_{\theta^+, \theta^-}(S)$, and — for calibration purposes — $\max_{A_0:|A_0|=k} \sigma_{\theta}(A_0)$ for all networks and parameter settings. Notice that the result is obtained by running the Random Greedy algorithm without any approximation guarantee. However, as the algorithm’s




Figure 1: Comparison between Influence Difference Maximization and Influence Maximization results for four different networks. (The result of STOCFOCS network is obtained with CELF optimization.)




Figure 2: Ratio between the computed values of Influence Difference Maximization and Influence Maximization under random regular graphs with different degree.

output provides a lower bound on the maximum influence difference, a large value suggests that Influence Maximization could be unstable. On the other hand, small values *do not* guarantee that the instance is stable, as the algorithm provides no approximation guarantee.

While individual networks vary somewhat in their susceptibility, the overall trend is that larger estimates of baseline probabilities p make the instance more susceptible to noise, as do (obviously) larger uncertainty parameters Δ . In particular, for $\Delta \geq 20\%$, the noise (after scaling) dominates the Influence Maximization objective function value, meaning that optimization results should be used with care.

Next, we evaluate the dependence of the noise tolerance on the degrees of the graph, by experimenting with random d -regular graphs whose degrees vary from 5 to 25. It is known that such graphs are expanders with high probability, and hence have percolation thresholds of $1/d$ [2]. Accordingly, we set the base probability to $(1 + \alpha)/d$ with $\alpha \in \{-20\%, 0, 20\%\}$. We use the same setting for uncertainty intervals as in the previous experiments. Figure 2 shows the ratio between Influence Difference Maximization and Influence Maximization, i.e., $\frac{\max_S \delta_{\theta^+, \theta^-}(S)}{\max_S \sigma_{\theta}(S)}$, with $\alpha \in \{-20\%, 0, 20\%\}$. It indicates that for random regular graphs, the degree does not appear to significantly affect stability, and that again, noise around 20% begins to pose a significant challenge. Moreover, we observe that the ratio reaches its minimum when the edge activation probability is exactly at the percolation threshold $1/d$. This result is in line with percolation theory and also the analysis of Adiga et al. [1].

As a general takeaway message, for larger amounts of noise (even just a relative error of 20%) — which may well occur in practice — a lot of caution is advised in using the results of algorithmic Influence Maximization.

5 Discussion

We began a study of the stability of Influence Maximization when the input data are adversarially noisy. We showed that estimating the susceptibility of an instance to perturbations can be cast as an Influence Difference Maximization problem. Unfortunately, the Influence Difference Maximization problem under the Independent Cascade Model is as hard to approximate as the INDEPENDENT SET problem. While we do not at present have a comparable approximation hardness result for the Linear Threshold Model, we consider it unlikely that the Influence Difference Maximization objective could be much better approximated for that model.

We used the Random Greedy algorithm of Buchbinder et al. to gain an empirical understanding of the prevalence of instability on several synthetic and real networks. The results suggest that 20% relative error could lead to a significant risk of suboptimal outputs. Given the noise inherent in all estimates of social network data, this suggests applying extreme caution before relying heavily on results of algorithmic Influence Maximization.

The fact that our main theorem is negative (i.e., a strong approximation hardness result) is somewhat disappointing, in that it rules out reliably categorizing data sets as stable or unstable. This suggests searching for models which remain algorithmically tractable while capturing some notion of adversarially perturbed inputs. The issue of noise in social network data will not disappear, and it is necessary to understand its impact more fundamentally.

While we begin an investigation of how pervasive susceptibility to perturbations is in Influence Maximization data sets, our investigation is necessarily limited. Ground truth data are by definition impossible to obtain, and even good and reliable inferred data sets of actual influence probabilities are currently not available. The values we assigned for our experimental evaluation cover a wide range of parameter values studied in past work, but the community does not appear to have answered the question whether these ranges actually correspond to reality.

At an even more fundamental level, the *models* themselves have received surprisingly little thorough experimental validation, despite having served as models of choice for hundreds of papers over the last decade. In addition to verifying the susceptibility of models to parameter perturbations, it is thus a pressing task to verify how susceptible the optimization problems are to incorrect models. The verification or falsification of sociological models for collective behavior likely falls outside the expertise of the computer science community, but nonetheless needs to be undertaken before any significant impact of work on Influence Maximization can be truthfully claimed.

Acknowledgments

We are deeply indebted to Debmalya Mandal, Jean Pouget-Abadie and Yaron Singer for bringing to our attention a counter-example to a theorem incorrectly claimed in the previous version of this article.

Furthermore, we would like to thank Shaddin Dughmi for useful pointers and feedback, Shishir Bharathi and Mahyar Salek for useful discussions, and anonymous reviewers for useful feedback on prior versions. Xinran He was supported in part by the grant ONR MURI W911NF-11-1-0332 and DARPA SMISC W911NF-12-1-0034.

References

- [1] A. Adiga, C. J. Kuhlman, H. S. Mortveit, and A. K. S. Vullikanti. Sensitivity of diffusion dynamics to network uncertainty. In *Proc. 28th AAAI Conf. on Artificial Intelligence*, 2013.
- [2] N. Alon, I. Benjamini, and A. Stacey. Percolation on finite graphs and isoperimetric inequalities. *Annals of Probability*, 32:1727–1745, 2004.
- [3] A.-L. Barabási and R. Albert. Emergence of scaling in random networks. *Science*, 286:509–512, 1999.
- [4] B. Bollobás. *Random Graphs*. Cambridge University Press, second edition, 2001.

- [5] C. Borgs, M. Brautbar, J. T. Chayes, and B. Lucier. Maximizing social influence in nearly optimal time. In *Proc. 25th ACM-SIAM Symp. on Discrete Algorithms*, pages 946–957, 2014.
- [6] N. Buchbinder, M. Feldman, J. S. Naor, and R. Schwartz. Submodular maximization with cardinality constraints. In *Proc. 25th ACM-SIAM Symp. on Discrete Algorithms*, pages 1433–1452, 2014.
- [7] W. Chen, L. V. Lakshmanan, and C. Castillo. *Information and Influence Propagation in Social Networks*. Synthesis Lectures on Data Management. Morgan & Claypool, 2013.
- [8] W. Chen, Y. Wang, and S. Yang. Efficient influence maximization in social networks. In *Proc. 15th Intl. Conf. on Knowledge Discovery and Data Mining*, pages 199–208, 2009.
- [9] W. Chen, Y. Yuan, and L. Zhang. Scalable influence maximization in social networks under the linear threshold model. In *Proc. 10th Intl. Conf. on Data Mining*, pages 88–97, 2010.
- [10] P. Erdős and A. Rényi. On the evolution of random graphs. *Publ. Math. Inst. Hung. Acad. Sci.*, 5:17–61, 1960.
- [11] M. Gomez-Rodriguez, D. Balduzzi, and B. Schölkopf. Uncovering the temporal dynamics of diffusion networks. In *Proc. 28th Intl. Conf. on Machine Learning*, pages 561–568, 2011.
- [12] M. Gomez-Rodriguez, J. Leskovec, and A. Krause. Inferring networks of diffusion and influence. *ACM Transactions on Knowledge Discovery from Data (TKDD)*, 5(4), 2012.
- [13] M. Gomez-Rodriguez and B. Schölkopf. Submodular inference of diffusion networks from multiple trees. In *Proc. 29th Intl. Conf. on Machine Learning*, 2012.
- [14] A. Goyal, F. Bonchi, and L. V. S. Lakshmanan. Learning influence probabilities in social networks. In *Proc. 3rd ACM Intl. Conf. on Web Search and Data Mining*, pages 241–250, 2010.
- [15] A. Goyal, F. Bonchi, and L. V. S. Lakshmanan. A data-based approach to social influence maximization. *Proc. VLDB Endow.*, 5(1):73–84, Sept. 2011.
- [16] J. Håstad. Clique is hard to approximate within $n^{1-\epsilon}$. *Acta Mathematica*, 182:105–142, 1999.
- [17] D. Kempe, J. Kleinberg, and E. Tardos. Maximizing the spread of influence in a social network. In *Proc. 9th Intl. Conf. on Knowledge Discovery and Data Mining*, pages 137–146, 2003.
- [18] D. Kempe, J. Kleinberg, and E. Tardos. Influential nodes in a diffusion model for social networks. In *Proc. 32nd Intl. Colloq. on Automata, Languages and Programming*, pages 1127–1138, 2005.
- [19] H. Kesten. Asymptotics in high dimension for percolation. In G. Grimmett and D. Welsh, editors, *Disorder in Physical System*, pages 219–240. Oxford University Press, 1990.
- [20] S. Khanna and B. Lucier. Influence maximization in undirected networks. In *Proc. 25th ACM-SIAM Symp. on Discrete Algorithms*, pages 1482–1496, 2014.
- [21] J. Leskovec, A. Krause, C. Guestrin, C. Faloutsos, J. VanBriesen, and N. S. Glance. Cost-effective outbreak detection in networks. In *Proc. 13th Intl. Conf. on Knowledge Discovery and Data Mining*, pages 420–429, 2007.
- [22] E. Mossel and S. Roch. Submodularity of influence in social networks: From local to global. *SIAM J. Comput.*, 39(6):2176–2188, 2010.
- [23] S. A. Myers and J. Leskovec. On the convexity of latent social network inference. In *Proc. 22nd Advances in Neural Information Processing Systems*, pages 1741–1749, 2010.
- [24] G. L. Nemhauser, L. A. Wolsey, and M. L. Fisher. An analysis of the approximations for maximizing submodular set functions. *Mathematical Programming*, 14:265–294, 1978.

- [25] C. Wang, W. Chen, and Y. Wang. Scalable influence maximization for independent cascade model in large-scale social networks. *Data Mining and Knowledge Discovery Journal*, 25(3):545–576, 2012.
- [26] Y. Wang, G. Cong, G. Song, and K. Xie. Community-based greedy algorithm for mining top- k influential nodes in mobile social networks. In *Proc. 16th Intl. Conf. on Knowledge Discovery and Data Mining*, pages 1039–1048, 2010.
- [27] D. J. Watts and S. Strogatz. Collective dynamics of ‘small-world’ networks. *Nature*, 393:440–442, 1998.