Vincenzo Tamma 1,2 and Johannes ${\rm Seiler}^1$

¹Institut für Quantenphysik and Center for Integrated Quantum Science and Technology (IQST), Universität Ulm, D-89069 Ulm, Germany ²Author to whom any correspondence should be addressed.

E-mail: vincenzo.tamma@uni-ulm.de

Abstract. We theoretically demonstrate a counter-intuitive phenomenon in optical interferometry with a thermal source: the emergence of second-order interference between two pairs of correlated optical paths even if the time delay imprinted by each path in one pair with respect to each path in the other pair is much larger than the source coherence time. This fundamental effect could be useful for experimental simulations of small-scale quantum circuits and of 100%-visibility correlations typical of entangled states of a large number of qubits, with possible applications in high-precision metrology and imaging. As an example, we demonstrate the polarization-encoded simulation of the operation of the quantum logic gate known as controlled-NOT gate.

PACS numbers: 42.50.-p,42.50.Ar

Submitted to: New J. Phys.

Keywords:coherence theory, photon statistics, multiphoton correlations, multiphoton interference

1. Motivation

The Hanbury Brown and Twiss (HBT) effect [1, 2] discovered in 1956 was at the heart of the development of the field of quantum optics. Indeed, this discovery led to numerous remarkable multiphoton experiments which have not only deepened our fundamental understanding of multiphoton interference [3, 4, 5, 6, 7, 8, 9] but have also led to numerous applications in information processing [10, 11, 12, 13, 14, 15] and imaging [16, 17, 18, 19, 20, 21, 22].

The HBT effect fundamentally reveals the second-order coherence of a thermal source. For example, second-order temporal correlations can be measured after the interaction of multi-mode thermal radiation of given bandwidth $\Delta \omega$ with a beam splitter: two detectors at the beam splitter output ports have twice the chance to be triggered at equal times than with a relative time delay longer than the coherence time $1/\Delta \omega$ of the thermal field.

It is interesting to modify the described HBT scheme by adding two unbalanced Mach-Zehnder interferometers at the beam splitter output ports, the "control" port C and the "target" T, as depicted in figure 1(a). We further consider path lengths $L := L_C \cong L_T$ and $S := S_C \cong S_T$ such that the time |L - S| / c, with c the speed of light, is much larger than the coherence time of the source. Can we observe second order interference by performing correlation measurements at equal detection times at the output of the two Mach-Zehnder interferences?

Interestingly, in this paper we show that second-order interference between the two pairs (L_C, L_T) and (S_C, S_T) of optical paths (*multipath correlation interference*) can be observed even if the time delay |L - S| / c imprinted by each path in the pair (L_C, L_T) with respect to each path in the pair (S_C, S_T) is much beyond the source coherence time. Furthermore, we describe the similarities and differences between this secondorder interference effect and the one demonstrated by Franson [7] in 1989 by using a two-photon entangled source.

The fundamental interference phenomenon described here is also of interest in view of the recent studies of simulations of quantum logic operations and entanglement correlations using classical light [23, 24, 25, 26, 27, 28, 29, 30]. In particular, by considering the interferometric scheme in figure 1(b), we demonstrate how this interference effect is able to simulate the result of a controlled-NOT (CNOT) logic operation [10, 31, 32, 33, 34, 35, 36, 37].

The paper is outlined as following: we demonstrate how multipath correlation interference can be observed with a thermal source in section 2; we apply this novel phenomenon to the simulation of a CNOT gate operation in section 3; we show how this second-order interference effect can be generalized to interferometers based on arbitraryorder correlation measurements in section 4; and we conclude with discussions in section 5.



Figure 1. (a) Modified HBT interferometer with a thermal source where two unbalanced Mach-Zehnder interferometers are placed at the output channel of the first beam splitter and the correlation between the photon-number fluctuations is measured at the interferometer output. (b) Interferometer simulating a CNOT-gate operation: 1) The first transformation $\mathcal{U}_{\text{prep}}$ prepares the initial polarization state; 2) By using two unbalanced interferometers a polarization-dependent transformation \mathcal{P} is implemented; 3) At the interferometer output the polarization-dependent correlation between the photon-number fluctuations is measured.

2. Multipath Correlation Interference

We consider here the interferometer in figure 1(a). The interferometer has only one source, which generates in the input port A thermal light with a given horizontal polarization H. Therefore, the input state is described by [38, 39]

$$\hat{\rho}_{H} = \int \left[\prod_{\omega} \mathrm{d}^{2} \alpha_{\omega,H}\right] P_{\hat{\rho}_{H}}(\{\alpha_{\omega,H}\}) \bigotimes_{\omega} |\alpha_{\omega,H}\rangle_{A} \langle \alpha_{\omega,H}|, \qquad (1)$$

with the Glauber-Sudarshan probability distribution [3, 40]

$$P_{\hat{\rho}_H}(\{\alpha_{\omega,H}\}) = \prod_{\omega} \frac{1}{\pi \,\overline{n}_{\omega}} \exp\left(-\frac{|\alpha_{\omega,H}|^2}{\overline{n}_{\omega}}\right),$$

where \overline{n}_{ω} is the average photon number at frequency ω . For simplicity, but without losing generality, we consider a Gaussian frequency distribution [38]

$$\overline{n}_{\omega} = \overline{r} \frac{1}{\sqrt{2\pi}\Delta\omega} \exp\left\{-\frac{(\omega-\omega_0)^2}{2\Delta\omega^2}\right\},\,$$

with the mean photon rate \overline{r} , average frequency ω_0 and spectral width $\Delta \omega$.

At the interferometer output correlation measurements in the photon-number fluctuations

$$\Delta n_d = n_d - \langle n_d \rangle \tag{2}$$

at the detection time t_d around the mean value $\langle n_d \rangle$, with d = C, T, are performed by using either photon-number resolving detectors or single-photon detectors [41, 42] with integration time $\delta t \ll 1/\Delta \omega$, which are currently available (e.g. $\delta t \sim 10 - 100 ns$). The expectation value for the product of the photon-number fluctuations in (2) at the two output ports is [41, 42, 38]

$$\langle \Delta n_C \Delta n_T \rangle = \langle n_C n_T \rangle - \langle n_C \rangle \langle n_T \rangle \propto G^{(2)}(t_C, t_T) - G^{(1)}(t_C, t_C) G^{(1)}(t_T, t_T) = \left| G^{(1)}(t_C, t_T) \right|^2.$$
 (3)

Here we used the properties [38]

$$\langle n_C n_T \rangle \propto G^{(2)}(t_C, t_T),$$

with

$$G^{(2)}(t_C, t_T) = G^{(1)}(t_C, t_C)G^{(1)}(t_T, t_T) + \left|G^{(1)}(t_C, t_T)\right|^2 \tag{4}$$

and

$$\langle n_d \rangle \propto G^{(1)}(t_d, t_d)$$

where $G^{(1)}$ and $G^{(2)}$ are, respectively, the first and second-order correlation functions [38]. Therefore, the outcome (3) of the correlation measurement does not depend on the "background" term $G^{(1)}(t_C, t_C)G^{(1)}(t_T, t_T)$ in (4). As we will show, the only relevant term $|G^{(1)}(t_C, t_T)|^2$ characterizes the second-order interference occurring in the interferometer. Toward this end, we introduce the definition of the first-order correlation function

$$G^{(1)}(t_C, t_T) := \operatorname{tr} \left[\hat{\rho}_H \hat{E}_C^{(-)}(t_C) \hat{E}_T^{(+)}(t_T) \right].$$
(5)

Here, in the narrow bandwidth approximation,

$$\hat{E}_{d}^{(+)}(t_{d}) \propto \int d\omega \, \mathrm{e}^{-i\omega t_{d}} \left[\mathrm{e}^{\mathrm{i}\omega L_{d}/c} + \mathrm{e}^{\mathrm{i}\omega S_{d}/c} \right] \, \hat{a}_{A}^{(H)}(\omega) \tag{6}$$

is the electric field operator at the detector d = C, T in terms of the frequency-dependent annihilation operator $\hat{a}_A(\omega)$ at the only input port A where a source is placed; while $\hat{E}_d^{(-)}(t_d)$ is its respective Hermitian conjugate. The factors $e^{i\omega L_d/c}$ and $e^{i\omega S_d/c}$ describe the propagation through the paths L_d and S_d , respectively. By using (5) and (6), and defining the *effective* detection times

$$t_d^{(l_d)} \coloneqq t_d - \frac{l_d}{c},\tag{7}$$

with $l_d = L_d, S_d$, we show in Appendix A that the expectation value in (3) can be written as

$$\left\langle \Delta n_C \Delta n_T \right\rangle \propto \left| G^{(1)}(t_C, t_T) \right|^2 = \left| \sum_{l_C, l_T} G^{(l_C, l_T)}(t_C, t_T) \right|^2.$$
(8)

Here, each interfering term

$$G^{(l_C,l_T)}(t_C,t_T) = i \, a \, \overline{r} \, e^{i\omega_0 [t_C^{(l_C)} - t_T^{(l_T)}]} e^{-[t_C^{(l_C)} - t_T^{(l_T)}]^2 \Delta \omega^2/2}, \tag{9}$$

with a constant, describing the contribution of the corresponding path pair (l_C, l_T) , depends on the time delay $t_C^{(l_C)} - t_T^{(l_T)}$ between the detected photons in the two output ports before the propagation through the two paths l_C and l_T , respectively. In a standard HBT experiment only a fixed pair of paths can contribute to the measurement. Differently, here all the four possible pairs $(l_C, l_T) =$ $(L_C, L_T), (S_C, S_T), (L_C, S_T), (S_C, L_T)$ of paths can lead to a joint detection and, in principle, can interfere as in (8).

Now, we consider the following conditions for the delays between the effective detection times defined in (7):

$$\left| t_C^{(L_C)} - t_T^{(L_T)} \right| \ll 1/\Delta\omega, \qquad \left| t_C^{(S_C)} - t_T^{(S_T)} \right| \ll 1/\Delta\omega, \tag{10}$$

and

$$\left| t_C^{(L_C)} - t_T^{(S_T)} \right| \gg 1/\Delta\omega, \qquad \left| t_T^{(L_T)} - t_C^{(S_C)} \right| \gg 1/\Delta\omega, \tag{11}$$

which, by using (10), corresponds to differences between the path lengths in each Mach-Zehnder interferometer much larger than the coherence length $c/\Delta\omega$ of the source:

$$|L_C - S_C| \gg c/\Delta\omega, \qquad |L_T - S_T| \gg c/\Delta\omega.$$
 (12)

The conditions (10) can be simply achieved experimentally, for example, in the limit

$$t_C \cong t_T \Leftrightarrow |t_C - t_T| \ll 1/\Delta\omega$$
 (13)

of approximately equal detection times with respect to the coherence time $1/\Delta\omega$ and approximately equal paths

$$L := L_C \cong L_T \iff |L_C - L_T| \ll c/\Delta\omega, \qquad S := S_C \cong S_T \iff |S_C - S_T| \ll c/\Delta\omega$$
(14)

with respect to to the coherence length $c/\Delta\omega$. By using (14), the two conditions (12) reduce to the single condition

$$|L - S| \gg c/\Delta\omega. \tag{15}$$

In the conditions (11) and (10) and by using (9) the expression in (8) becomes

$$\langle \Delta n_C \Delta n_T \rangle \propto \left| G^{(1)}(t_C, t_T) \right|^2 \cong \left| G^{(L_C, L_T)}(t_C, t_T) + G^{(S_C, S_T)}(t_C, t_T) \right|^2$$

= $2a^2 \overline{r}^2 \left(1 + \cos \varphi_{L-S} \right),$ (16)

with the relative phase

$$\varphi_{L-S} := \omega_0 \left[\left(t_C^{(L_C)} - t_T^{(L_T)} \right) - \left(t_C^{(S_C)} - t_T^{(S_T)} \right) \right] = \frac{\omega_0}{c} \left[\left(L_C - L_T \right) - \left(S_C - S_T \right) \right], \quad (17)$$

where we used (7) in the second equality. The expectation value (16) depends now on the interference between *only* two contributions $G^{(L_C,L_T)}$ and $G^{(S_C,S_T)}$ associated with the pairs of optical paths (L_C, L_T) and (S_C, S_T) , respectively. The paths L_C and S_C in the interferometer are correlated with the paths L_T and S_T , respectively, and only the corresponding path pairs (L_C, L_T) and (S_C, S_T) interfere. This interference occurs even if the differences $|L_d - S_d|$, with d = C, T, between the path lengths in each Mach-Zehnder interferometer are much larger than the coherence length of the source (see (12)). Indeed, for a thermal source, the interfering contributions $G^{(L_C, L_T)}$ and $G^{(S_C, S_T)}$ (see (9)) do not depend on the relative path lengths in each Mach-Zehnder interferometer but only on the difference between the delays $t_C^{(L_C)} - t_T^{(L_T)}$ and $t_C^{(S_C)} - t_T^{(S_T)}$ between the detected photons in the two output ports before the propagation through the two pairs (L_C, L_T) and (S_C, S_T) of paths, respectively. Since these time delays are very small compared to the coherence time of the source (see (10)) both pairs (L_C, L_T) and (S_C, S_T) contribute to the observed second-order interference.

It is worthwhile to compare the interferometer described here with the famous Franson interferometer [7], where the state at the output of the beam splitter in figure 1(a) is substituted by a two-photon entangled state and the coincidence rate for detecting a photon at the same time in both output ports is measured. For a full comparison, we first determine the coincidence rate associated with the absorption of a single photon from the field at each of the two output ports of the interferometer in figure 1(a) considered here. This corresponds to measure the standard second-order correlation function [38] in (4) at approximately equal detection times $t_C \cong t_T$ (see (13)) and in the conditions (14) and (15) for the interferometric optical paths. In particular, by adding the product $G^{(1)}(t_C, t_C)G^{(1)}(t_T, t_T) = 4 a^2 \overline{r}^2$ of the intensities at the two output ports to the second-order interference term $|G^{(1)}(t_C, t_T)|^2$ found in (16), we obtain a second-order correlation function

$$G^{(2)}(t_C, t_T) \propto 3 + \cos \varphi_{L-S}$$

with visibility 1/3. This is a crucial difference between the interferometer described here and the Franson interferometer, where the second-order correlation function measured at the output at equal detection times manifests second-order interference with 100%visibility. Instead, in the interferometer in figure 1(a), 100%-visibility interference is only achieved by measuring the correlation (16) between the fluctuations in the number of detected photons, where the "background" constant term $G^{(1)}(t_C, t_C)G^{(1)}(t_T, t_T)$ is effectively "subtracted" from the second order correlation function. Therefore, the emergence of this interference effect is very different from the physics of two-photon interference based on energy-time entanglement in the Franson interferometer. Indeed, in the Franson interferometer the interference between the two pairs (L, L) and (S, S)of optical paths emerge from the fact that the two input entangled photons are emitted at the same time and the joint emission time is uncertain in the quantum sense. Therefore, 100%-visibility second-order interference can be observed even if the firstorder coherence length is much less than the difference L - S between the path lengths. In the interferometer described here, instead, neither an entangled source is used nor any entanglement process occurs. Therefore, coincidence events do not necessarily correspond to the absorption from the field of photons which entered the interferometer at the same time. In principle, the detected photons could have taken any of the four possible pairs of paths from the source to the two detectors. Nonetheless, the interference term $|G^{(1)}(t_C, t_T)|^2$ in the second-order correlation function, emerging from the measurement of the correlation (16) between the fluctuations in the number of detected photons as an average over all the possible experimental outcomes, contains only the contribution of two indistinguishable pairs (L_C, L_T) and (S_C, S_T) of correlated paths \ddagger . In particular, the interference pattern (16) depends on the *difference*

$$\varphi_{L-S} = \varphi_C - \varphi_T$$

in (17) between the relative phases $\varphi_d = \omega_0 (L_d - S_d)/c$, with d = C, T, in the two Mach-Zehnder interferometers. Differently, in the Franson interferometer the resulting interference pattern depends on the *sum* of the relative phases in the two Mach-Zehnder interferometers.

3. CNOT Gate Simulation

The interference phenomenon based on multipath correlations demonstrated in the previous section can be used to reproduce on-demand correlations in different degrees of freedom without the use of entanglement. Here, we address, for example, the simulation of a CNOT gate operation by encoding these multipath correlations in the polarization degree of freedom.

For this purpose, we consider the interferometer in figure 1(b). The source at the input port A is again described by (1). The H-polarized thermal light impinges on the balanced beam splitter BS1 and, by using half-wave plates, is prepared at the "control" port C and "target" port T in two general polarizations $\phi_{\mathcal{C}} = (\cos \phi_{\mathcal{C}} \quad \sin \phi_{\mathcal{C}})^T$ and $\phi_{\mathcal{T}} = (\cos \phi_{\mathcal{T}} \quad \sin \phi_{\mathcal{T}})^T$, respectively. Here, the H and V polarization directions are indicated by the vectors $(1 \quad 0)^T$ and $(0 \quad 1)^T$, respectively. Thereby, by introducing the polarization rotations

$$R_{\phi_{\mathcal{C},\mathcal{T}}} := \begin{pmatrix} \cos \phi_{\mathcal{C},\mathcal{T}} & \sin \phi_{\mathcal{C},\mathcal{T}} \\ \sin \phi_{\mathcal{C},\mathcal{T}} & -\cos \phi_{\mathcal{C},\mathcal{T}} \end{pmatrix},$$

the interferometer transformation associated with the first part of the interferometer connecting the input ports A, B with the ports C, T is given by

$$\mathcal{U}_{\text{prep}} := \begin{pmatrix} R_{\phi_{\mathcal{C}}} & 0\\ 0 & R_{\phi_{\mathcal{T}}} \end{pmatrix} \mathcal{U}_{\text{BS}} = \frac{1}{\sqrt{2}} \begin{pmatrix} R_{\phi_{\mathcal{C}}} & 0\\ 0 & R_{\phi_{\mathcal{T}}} \end{pmatrix} \begin{pmatrix} \text{i1} & 1\\ 1 & \text{i1} \end{pmatrix},$$
(18)

where we used the expression for the balanced beam-splitter transformation \mathcal{U}_{BS} , with 1 := diag(1, 1).

‡ Interestingly, there is, in principle, no upper bound to the difference |L - S| between the path lengths in (15) which limit this interference effect for an ideal stationary thermal source. This is of course not the case in "real world" experiments.

The second part of the interferometer consists of a "control" interferometer connecting the ports C and C and a "target" interferometer connecting the ports \mathcal{T} and T. Therefore, the global interferometric evolution is described by the two polarization-dependent transformations $\mathcal{P}_{C,C}$ and $\mathcal{P}_{T,\mathcal{T}}$ defining the diagonal matrix

$$\mathcal{P} := \operatorname{diag}\left(\mathcal{P}_{C,\mathcal{C}}, \mathcal{P}_{T,\mathcal{T}}\right). \tag{19}$$

In particular, in the control interferometer, the light in the polarization modes H and V at the output of the first polarizing beam splitter PBS1 acquires the time delays S_C/c and L_C/c , respectively, with c the speed of light, before being recombined at the output of the second polarizing beam splitter PBS2. This leads to the control transformation

$$\mathcal{P}_{C,\mathcal{C}} := \operatorname{diag}\left(\mathrm{e}^{\mathrm{i}\omega S_C/c},\mathrm{e}^{\mathrm{i}\omega L_C/c}\right)$$

On the other hand, the light in the target interferometer is coherently split into two different paths and recombined by the balanced beam splitters BS2 and BS3, respectively, independently of the polarization. The light polarization is unchanged in the path of length S_T . Instead, in the path of length L_T the polarization modes H and V are flipped ($H \leftrightarrow V$) by the NOT-gate operation $F := \operatorname{antidiag}(1, 1)$ implemented by a half-wave plate with axes rotated by $\pi/4$ with respect to the H and V axes. Thus the overall target evolution is described by the transformation

$$\mathcal{P}_{T,\mathcal{T}} := \frac{1}{2} \left(\mathrm{e}^{\mathrm{i}\omega L_T/c} F + \mathrm{e}^{\mathrm{i}\omega S_T/c} \mathbf{1} \right)$$

By using (18) and (19), we derive the total interferometer matrix

$$\mathcal{M}(\omega) := \mathcal{P} \cdot \mathcal{U}_{\text{prep}} = \frac{1}{\sqrt{2}} \begin{pmatrix} i \mathcal{P}_{C,\mathcal{C}} R_{\phi_{\mathcal{C}}} & \mathcal{P}_{C,\mathcal{C}} R_{\phi_{\mathcal{C}}} \\ \mathcal{P}_{T,\mathcal{T}} R_{\phi_{\mathcal{T}}} & i \mathcal{P}_{T,\mathcal{T}} R_{\phi_{\mathcal{T}}} \end{pmatrix}.$$
 (20)

We finally address the detection process, consisting of measuring the polarizationdependent correlation between the fluctuations in the number of photons $\Delta n_{\theta_C}(t_C)$ and $\Delta n_{\theta_T}(t_T)$ detected at the control and target ports d = C, T, respectively, with polarization $\boldsymbol{\theta}_d := (\cos \theta_d \quad \sin \theta_d)^T$ at time t_d . The expectation value for the product of the photon-number fluctuations at the two output ports is [41, 42, 38]

$$\left\langle \Delta n_{\theta_C} \Delta n_{\theta_T} \right\rangle \propto \left| G_{\theta_C, \theta_T}^{(1)}(t_C, t_T) \right|^2,$$
 (21)

where the first-order correlation function

$$G_{\theta_C,\theta_T}^{(1)}(t_C,t_T) := \operatorname{tr}\left[\hat{\rho}_H\left(\boldsymbol{\theta}_C \cdot \hat{\boldsymbol{E}}_C^{(-)}(t_C)\right)\left(\boldsymbol{\theta}_T \cdot \hat{\boldsymbol{E}}_T^{(+)}(t_T)\right)\right]$$

is now, differently from (5), polarization dependent. Here, in the narrow bandwidth approximation and in the (H, V)-polarization basis,

$$\hat{\boldsymbol{E}}_{d}^{(+)}(t_{d}) \propto \int d\omega \, \mathrm{e}^{-i\omega t_{d}} \mathcal{M}_{d,A}(\omega) \, \begin{pmatrix} \hat{a}_{A}^{(H)}(\omega) \\ \hat{a}_{A}^{(V)}(\omega) \end{pmatrix},$$

with the elements $\mathcal{M}_{d,A} = \mathcal{M}_{C,A}, \mathcal{M}_{T,A}$ in the first column of the total interferometer matrix (20), is the electric field operator at the detector d = C, T in terms of the frequency-dependent annihilation operators $\hat{a}_A^{(H)}(\omega)$ and $\hat{a}_A^{(V)}(\omega)$ at the only input port A where the source is placed, while $\hat{E}_d^{(-)}(t_d)$ is its respective Hermitian conjugate. In Appendix B we show, that, in the limits (11) and (10), (21) becomes

$$\langle \Delta n_{\theta_C} \Delta n_{\theta_T} \rangle \propto \left| G_{\theta_C \theta_T}^{(L_C, L_T)}(t_C, t_T) + G_{\theta_C \theta_T}^{(S_C, S_T)}(t_C, t_T) \right|^2$$

$$\propto \overline{r}^2 \left| \cos \phi_C \cos \theta_C \cos (\phi_T - \theta_T) + e^{i\varphi_{L-S}} \sin \phi_C \sin \theta_C \sin (\phi_T + \theta_T) \right|^2,$$

$$(22)$$

with φ_{L-S} defined in (17).

Here, similarly to a CNOT gate operation, the control path S_C associated with the polarization mode H is correlated with the target path S_T where the light polarization remains unchanged; instead, the control path L_C associated with the polarization mode V is correlated with the target path L_T where a NOT-gate operation occurs. Moreover, analogously to the scheme in figure 1(a), the two pairs (L_C, L_T) and (S_C, S_T) of optical paths interfere.

Let us fully compare now the interferometer in figure 1(b) with a genuine CNOT entangling operation on the two-qubit input state $|\phi_{\mathcal{C}}\rangle_{\mathcal{C}} |\phi_{\mathcal{T}}\rangle_{\mathcal{T}}$, where

$$|\phi_{\mathcal{C}}\rangle_{\mathcal{C}} := \cos \phi_{\mathcal{C}} |H\rangle_{\mathcal{C}} + \sin \phi_{\mathcal{C}} |V\rangle_{\mathcal{C}},$$

and

$$|\phi_{\mathcal{T}}\rangle_{\mathcal{T}} := \cos \phi_{\mathcal{T}} |H\rangle_{\mathcal{T}} + \sin \phi_{\mathcal{T}} |V\rangle_{\mathcal{T}}$$

are expressed as superpositions of the polarization states $|H\rangle$ and $|V\rangle$, corresponding to single-photon occupations of the H and V modes, respectively. A CNOT-gate operation on this input state leads to the output entangled state

$$\left|\psi\right\rangle_{C,T} = \cos\phi_{\mathcal{C}}\left|H\right\rangle_{C}\left|\phi_{\mathcal{T}}\right\rangle_{T} + \sin\phi_{\mathcal{C}}\left|V\right\rangle_{C}\left|\phi_{\mathcal{T}}^{(F)}\right\rangle_{T}$$

where

$$|\phi_{\mathcal{T}}^{(F)}\rangle_T := \sin \phi_{\mathcal{T}} |H\rangle_T + \cos \phi_{\mathcal{T}} |V\rangle_T.$$

Polarization-correlation measurements over the state $|\psi\rangle_{C,T}$ occur with a probability

$$P_{\text{CNOT}} := \left| \langle \theta_C, \theta_T | \psi \rangle_{C,T} \right|^2 = \left| \cos \phi_C \cos \theta_C \cos \left(\phi_T - \theta_T \right) + \sin \phi_C \sin \theta_C \sin \left(\phi_T + \theta_T \right) \right|^2.$$
(23)

Comparing (23) with (22) in the limit $\varphi_{L-S} \ll 1$, we obtain the expectation value

$$\langle \Delta n_{\theta_C} \Delta n_{\theta_T} \rangle \propto \overline{r}^2 P_{\text{CNOT}},$$
 (24)

which takes into account all the possible outcomes for the product of the photon-number fluctuations measured at the output of the interferometer in figure 1(b). We emphasize



Figure 2. N-order interference network with a thermal source based on: 1) Preparation of the N-channel initial state for arbitrary polarization angles ϕ_i (i = 1, ..., N) with a generalized transformation U_{prep} implemented by a symmetric 2Nport beam-splitter and N half-wave plates; 2) N-channel polarization-dependent evolution consisting of polarization rotations and \mathcal{P} -type transformations as in figure 1(b); 3) Polarization-dependent correlation measurements in the photon-number fluctuations at the output of the network.

that no entanglement process occurs in the interferometer; therefore the proposed scheme is not an entangling gate. Nonetheless, the measurement of the correlation (24) between the photon-number fluctuations at the two output ports allow us to simulate a CNOT-gate operation. As a "bonus", we find that the correlation signal can be enhanced on demand by increasing the square \bar{r}^2 of the source mean-photon rate, making it robust against technological losses.

As an example, if we fix the polarization angles $\phi_{\mathcal{C}} = \pi/4$ and $\phi_{\mathcal{T}} = 0$ in the setup in figure 1(b), the expectation value in (24) reads

$$\langle \Delta n_{\theta_C} \Delta n_{\theta_T} \rangle \propto \overline{r}^2 \cos^2\left(\theta_C - \theta_T\right),$$

simulating the 100%-visibility correlations typical of a Bell state $|\Phi^+\rangle = (|HH\rangle + |VV\rangle)/\sqrt{2}$ even if no Bell state is produced. Indeed, neither an entangled source is used, as for example in the experiment of Sanaka, Kawahara and Kuga [37], nor an entanglement process occurs in the interferometer as in a genuine CNOT gate operation. Nonetheless, an observer T can provide to a separate observer C the measured fluctuations Δn_{θ_C} in the number of photons for a polarization angle θ_C (in a given computational base) unknown to T, who can infer the value of θ_C only based on his/her corresponding measurements of Δn_{θ_T} (with θ_T in the same computational base). Interestingly, differently from a genuine Bell state, the correlation between the measurements of the two observers C and T emerge only from the expectation value of the product of the corresponding photon number fluctuations Δn_{θ_C} and Δn_{θ_T} .

4. N-order Interference Networks

One can finally generalize the second-order interference effect described in this paper to arbitrary orders N. For example, we consider an N-order interferometer as in figure 2 which generalizes the scheme in figure 1(b). For this purpose, we first prepare the N-channel initial polarization state: H-polarized thermal light impinges on a symmetric 2N-port beam-splitter (generalization of the balanced beam splitter BS1 in figure 1(b)); at each output port the polarization is then rotated, respectively, by arbitrary polarization angles ϕ_i , with i = 1, 2, ..., N, by using N half-wave plates. This prepared initial state propagates through a 2N-port polarization-dependent interferometer, consisting of polarization rotations and \mathcal{P} -type transformations as in figure 1 (b). Finally, the polarization-dependent correlation between the photon-number fluctuations is measured at the N output ports at approximately equal detection times.

We emphasize that for N = 2 one may also measure this correlation (24) by subtracting the product of the independent light intensities at the two detectors from the standard second-order correlation function. Differently, in higher order interferometric networks it may be useful to directly measure the correlation between the photonnumber fluctuations.

Experimentally, the precision in measuring the expectation value of the product of the photon-number fluctuations Δn_{θ_d} at each output port d = 1, 2, ..., N of a given network depends on the number n of performed measurements. For large numbers n of measurements the distribution of the measured mean values is normal around the expectation value with an indetermination given by the indetermination in the distribution of the measurement outcomes normalized by the root of n. Evidently, the indetermination in the distribution of the measurement outcomes depends intrinsically on the given N-order interference network. In general, a scaling in the number of resources typical of a quantum network with genuine entanglement cannot be achieved by the scheme described here. Nonetheless, an N-ordered interferometer as in figure 2 could be used to simulate experimentally 100%-visibility correlations typical of entangled states of N qubits [30], such as GHZ states, as well as small-scale quantum circuits and algorithms.

5. Discussion

We demonstrated a novel interference phenomenon emerging from the fundamental nature of multipath correlations with a thermal source. In particular, we introduced a novel interferometer (see figure 1(a)) where full correlations between the interferometric paths S_C and S_T (L_C and L_T) emerge at the interferometer output from measuring the correlation between the fluctuations in the number of detected photons at the two output ports. We showed how the interference between the two pairs (S_C , S_T) and (L_C , L_T) of correlated optical paths occurs even if the time delay imprinted by each path in one pair with respect to each path in the other pair is much larger than the source coherence time. We also pointed out the differences and the similarities between this interferometer and the well known Franson interferometer where an entangled two-photon source is used instead of a thermal source.

The interference effect demonstrated here can be easily observed experimentally: 1) It relies on one of the most natural sources which can be easily simulated in a laboratory by using laser light impinging on a fast rotating ground glass [43]; 2) The calibration of the interferometric paths and of the detection times (see (15), (14) and (13)) can

be easily achieved in the case of a thermal source, where the coherence time can range from the order of ns to μs . In an analogous way, multipath correlation interference can be also experimentally observed in the spatial domain with a spatial-mode dependent thermal source [44].

In conclusion, this interesting phenomenon provides a deeper fundamental understanding of the physics of coherence, multipath correlations and interference using a thermal source. Furthermore, it can be used to implement correlations in different degrees of freedom without recurring to entanglement processes. As an example, we demonstrated the polarization-encoded simulation of a CNOT logic operation. We also showed how this second-order interference effect can be extended to arbitrary orders N, leading to the interference of more general configurations of correlated paths. This could be used to simulate on-demand 100%-visibility correlations typical of entangled states of N qubits, with possible applications in high precision metrology and imaging [19, 21, 45, 22], and in the development of novel optical algorithms [46, 47, 48, 49, 50].

Acknowledgments

V.T. would like to thank M. Cassano, M. D'Angelo, P. Facchi, J. Fan, J. Franson, M. Freyberger, A. Garuccio, Y.-H. Kim, S. Laibacher, A. Migdall, S. Pascazio, T. Peng, T. Pittman, W.P. Schleich, and Y.H. Shih for fruitful conversations about the proposed scheme. V.T. is also grateful to M. Cassano, T. Peng and Y.H. Shih for discussions, during his visit at UMBC in 2014, about the experimental realization of this proposal in the spatial domain in Y.H. Shih's laboratory (paper in preparation).

V.T. acknowledges the support of the German Space Agency DLR with funds provided by the Federal Ministry of Economics and Technology (BMWi) under grant no. DLR 50 WM 1136.

Appendix A. Correlation between the photon-number fluctuations for the interferometer in figure 1(a)

We find here the explicit expression of the expectation value (in (3))

$$\langle \Delta n_C \Delta n_T \rangle \propto \left| G^{(1)}(t_C, t_T) \right|^2$$
 (A.1)

of the product of the photon-number fluctuations by calculating the first-order correlation function (in (5))

$$G^{(1)}(t_C, t_T) := \operatorname{tr} \left[\hat{\rho}_H \hat{E}_C^{(-)}(t_C) \hat{E}_T^{(+)}(t_T) \right], \qquad (A.2)$$

with the electric field operators

$$\hat{E}_C^{(-)}(t_C) = -\frac{K}{\sqrt{2}} \int d\omega \, \mathrm{e}^{i\omega t_C} \left[\mathrm{e}^{-\mathrm{i}\omega L_C/c} + \mathrm{e}^{-\mathrm{i}\omega S_C/c} \right] \, \hat{a}_A^{(H)\dagger}(\omega), \tag{A.3}$$

and

$$\hat{E}_T^{(+)}(t_T) = \frac{\mathrm{i}K}{\sqrt{2}} \int \mathrm{d}\omega \,\mathrm{e}^{-i\omega t_T} \left[\mathrm{e}^{\mathrm{i}\omega L_T/c} + \mathrm{e}^{\mathrm{i}\omega S_T/c}\right] \,\hat{a}_A^{(H)}(\omega),\tag{A.4}$$

where K is a constant. By inserting (A.3) and (A.4) into (A.2), and using the definition (in (7)) of the effective detection times

$$t_d^{(l_d)} = t_d - \frac{l_d}{c},$$

we obtain

$$G^{(1)}(t_C, t_T) = -\frac{\mathrm{i}K^2}{2} \left[\mathrm{tr} \left(\hat{\rho}_H \int \mathrm{d}\omega \int \mathrm{d}\omega' \mathrm{e}^{\mathrm{i}(\omega t_C^{(S_C)} - \omega' t_T^{(S_T)})} \hat{a}_A^{(H)\dagger}(\omega) \hat{a}_A^{(H)}(\omega') \right) \right. \\ \left. + \mathrm{tr} \left(\hat{\rho}_H \int \mathrm{d}\omega \int \mathrm{d}\omega' \mathrm{e}^{\mathrm{i}\omega t_C^{(S_C)} - \omega' t_T^{(L_T)})} \hat{a}_A^{(H)\dagger}(\omega) \hat{a}_A^{(H)}(\omega') \right) \right. \\ \left. + \mathrm{tr} \left(\hat{\rho}_H \int \mathrm{d}\omega \int \mathrm{d}\omega' \mathrm{e}^{\mathrm{i}(\omega t_C^{(L_C)} - \omega' t_T^{(S_T)})} \hat{a}_A^{(H)\dagger}(\omega) \hat{a}_A^{(H)}(\omega') \right) \right. \\ \left. + \mathrm{tr} \left(\hat{\rho}_H \int \mathrm{d}\omega \int \mathrm{d}\omega' \mathrm{e}^{\mathrm{i}(\omega t_C^{(L_C)} - \omega' t_T^{(S_T)})} \hat{a}_A^{(H)\dagger}(\omega) \hat{a}_A^{(H)}(\omega') \right) \right].$$

By using the property [9, 38]

$$\operatorname{tr}\left(\hat{\rho}_{H}\int \mathrm{d}\omega \int \mathrm{d}\omega' \mathrm{e}^{\mathrm{i}(\omega t_{1}-\omega' t_{2})} \hat{a}_{A}^{(H)\dagger}(\omega) \hat{a}_{A}^{(H)}(\omega')\right) = \overline{r} \mathrm{e}^{\mathrm{i}\omega_{0}(t_{1}-t_{2})} \mathrm{e}^{-(t_{1}-t_{2})^{2} \Delta \omega^{2}/2}$$

for the multimode thermal state $\hat{\rho}_H$ in (1), we obtain

$$G^{(1)}(t_C, t_T) = -\frac{\mathrm{i}K^2}{2} \overline{r} \left[\mathrm{e}^{\mathrm{i}\omega_0 [t_C^{(S_C)} - t_T^{(S_T)}]} \mathrm{e}^{-[t_C^{(S_C)} - t_T^{(S_T)}]^2 \Delta \omega^2 / 2} + \mathrm{e}^{\mathrm{i}\omega_0 [t_C^{(S_C)} - t_T^{(L_T)}]} \mathrm{e}^{-[t_C^{(S_C)} - t_T^{(L_T)}]^2 \Delta \omega^2 / 2} \right. \\ \left. + \mathrm{e}^{\mathrm{i}\omega_0 [t_C^{(L_C)} - t_T^{(S_T)}]} \mathrm{e}^{-[t_C^{(L_C)} - t_T^{(S_T)}]^2 \Delta \omega^2 / 2} + \mathrm{e}^{\mathrm{i}\omega_0 [t_C^{(L_C)} - t_T^{(L_T)}]} \mathrm{e}^{-[t_C^{(L_C)} - t_T^{(L_T)}]^2 \Delta \omega^2 / 2} \right],$$

which can be rewritten as

$$G^{(1)}(t_C, t_T) = \sum_{l_C, l_T} G^{(l_C, l_T)}(t_C, t_T),$$
(A.5)

with the contributions

$$G^{(l_C, l_T)}(t_C, t_T) = -\frac{\mathrm{i}K^2}{2} \overline{r} \mathrm{e}^{\mathrm{i}\omega_0 [t_C^{(l_C)} - t_T^{(l_T)}]} \mathrm{e}^{-[t_C^{(l_C)} - t_T^{(l_T)}]^2 \Delta \omega^2/2}$$

for all possible pairs $(l_C, l_T) = (L_C, L_T), (S_C, S_T), (L_C, S_T), (S_C, L_T)$ of optical paths. By substituting (A.5) in (A.1) we finally find the expression of $\langle \Delta n_C \Delta n_T \rangle$ in (8).

Appendix B. Polarization-dependent correlation between the photon-number fluctuations for the interferometer in figure 1(b)

We calculate here the expectation value (in (21))

$$\left\langle \Delta n_{\theta_C} \Delta n_{\theta_T} \right\rangle_{C,T} \propto \left| G^{(1)}_{\theta_C,\theta_T}(t_C,t_T) \right|^2$$
 (B.1)

for the product of the photon-number fluctuations, with the polarization-dependent first-order correlation function

$$G_{\theta_C,\theta_T}^{(1)}(t_C,t_T) := \operatorname{tr}\left[\hat{\rho}_H\left(\boldsymbol{\theta}_C \cdot \hat{\boldsymbol{E}}_C^{(-)}(t_C)\right)\left(\boldsymbol{\theta}_T \cdot \hat{\boldsymbol{E}}_T^{(+)}(t_T)\right)\right].$$
(B.2)

The electric field operator $\hat{E}_{d}^{(+)}(t_{d})$, with d = C, T, for direction of propagation perpendicular to the H-V plane is given in the narrow bandwidth approximation by the operator

$$\hat{\boldsymbol{E}}_{d}^{(+)}(t_{d}) = \mathrm{i}K \int \mathrm{d}\omega \, \mathrm{e}^{-i\omega t_{d}} \mathcal{M}_{d,A}(\omega) \, \begin{pmatrix} \hat{a}_{A}^{(H)}(\omega) \\ \hat{a}_{A}^{(V)}(\omega) \end{pmatrix}, \tag{B.3}$$

with a constant K, the elements $\mathcal{M}_{d,A} = \mathcal{M}_{C,A}, \mathcal{M}_{T,A}$ in the first column of the total interferometer matrix $\mathcal{M}(\omega)$ in (20), and the annihilation operators $\hat{a}_A^{(H)}(\omega)$ and $\hat{a}_A^{(V)}(\omega)$ at the only port A where a source is placed, while $\hat{E}_d^{(-)}(t_d)$ is its respective Hermitian conjugate.

By defining

$$A_C := (\cos \theta_C \quad \sin \theta_C) \ \mathcal{M}_{C,A}(\omega) \ \begin{pmatrix} 1\\ 0 \end{pmatrix} = \frac{\mathrm{i}}{\sqrt{2}} \left(\cos \theta_C \cos \phi_C \mathrm{e}^{\mathrm{i}\omega S_C/c} + \sin \theta_C \sin \phi_C \mathrm{e}^{\mathrm{i}\omega L_C/c} \right),$$

and

$$A_T := (\cos \theta_T \quad \sin \theta_T) \ \mathcal{M}_{T,A}(\omega) \begin{pmatrix} 1 \\ 0 \end{pmatrix}$$
$$= \frac{1}{2\sqrt{2}} \left[\cos \theta_T \left(\cos \phi_T \mathrm{e}^{\mathrm{i}\omega S_T/c} + \sin \phi_T \mathrm{e}^{\mathrm{i}\omega L_T/c} \right) + \sin \theta_T \left(\sin \phi_T \mathrm{e}^{\mathrm{i}\omega S_T/c} + \cos \phi_T \mathrm{e}^{\mathrm{i}\omega L_T/c} \right) \right],$$

it is useful to introduce the *effective* field operators

$$\hat{\mathcal{E}}_{d}^{(+)}(t_{d}) := \mathrm{i}K \int \mathrm{d}\omega \ A_{d} \ \mathrm{e}^{-i\omega t_{d}} \hat{a}_{A}^{(H)}(\omega), \tag{B.4}$$

with d = C, T. Indeed, given the fixed polarization H of the thermal light produced by the source in the port A, equation (B.2) can be rewritten by using (B.3) and (B.4) as

$$G_{\theta_C,\theta_T}^{(1)}(t_C,t_T) := \operatorname{tr}\left[\hat{\rho}_H\left(\hat{\mathcal{E}}_C^{(-)}(t_C)\right)\left(\hat{\mathcal{E}}_T^{(+)}(t_T)\right)\right].$$

By direct substitution and using again the definition (in (7)) of the effective detection times

$$t_d^{(l_d)} \coloneqq t_d - \frac{l_d}{c},\tag{B.5}$$

with $l_d = L_d, S_d$, we obtain

$$\begin{aligned} G_{\theta_{C},\theta_{T}}^{(1)}(t_{C},t_{T}) &= -\frac{\mathrm{i}K^{2}}{4} \left[\cos\theta_{C}\cos\phi_{\mathcal{C}}\left(\cos\theta_{T}\cos\phi_{\mathcal{T}}+\sin\theta_{T}\sin\phi_{\mathcal{T}}\right) \\ &\times \mathrm{tr}\left(\hat{\rho}_{H}\int\!\mathrm{d}\omega\!\int\!\mathrm{d}\omega'\mathrm{e}^{\mathrm{i}(\omega t_{C}^{(S_{C})}-\omega' t_{T}^{(S_{T})})}\hat{a}_{A}^{(H)\dagger}(\omega)\hat{a}_{A}^{(H)}(\omega')\right) \\ &+ \cos\theta_{C}\cos\phi_{\mathcal{C}}\left(\cos\theta_{T}\sin\phi_{\mathcal{T}}+\sin\theta_{T}\cos\phi_{\mathcal{T}}\right) \\ &\times \mathrm{tr}\left(\hat{\rho}_{H}\int\!\mathrm{d}\omega\!\int\!\mathrm{d}\omega'\mathrm{e}^{\mathrm{i}(\omega t_{C}^{(S_{C})}-\omega' t_{T}^{(L_{T})})}\hat{a}_{A}^{(H)\dagger}(\omega)\hat{a}_{A}^{(H)}(\omega')\right) \\ &+ \sin\theta_{C}\sin\phi_{\mathcal{C}}\left(\cos\theta_{T}\cos\phi_{\mathcal{T}}+\sin\theta_{T}\sin\phi_{\mathcal{T}}\right) \\ &\times \mathrm{tr}\left(\hat{\rho}_{H}\int\!\mathrm{d}\omega\!\int\!\mathrm{d}\omega'\mathrm{e}^{\mathrm{i}(\omega t_{C}^{(L_{C})}-\omega' t_{T}^{(S_{T})})}\hat{a}_{A}^{(H)\dagger}(\omega)\hat{a}_{A}^{(H)}(\omega')\right) \\ &+ \sin\theta_{C}\sin\phi_{\mathcal{C}}\left(\cos\theta_{T}\sin\phi_{\mathcal{T}}+\sin\theta_{T}\cos\phi_{\mathcal{T}}\right) \\ &\times \mathrm{tr}\left(\hat{\rho}_{H}\int\!\mathrm{d}\omega\!\int\!\mathrm{d}\omega'\mathrm{e}^{\mathrm{i}(\omega t_{C}^{(L_{C})}-\omega' t_{T}^{(L_{T})})}\hat{a}_{A}^{(H)\dagger}(\omega)\hat{a}_{A}^{(H)}(\omega')\right) \right]. \end{aligned}$$

By using again the property [9, 38]

$$\operatorname{tr}\left(\hat{\rho}_{H}\int \mathrm{d}\omega \int \mathrm{d}\omega' \mathrm{e}^{\mathrm{i}(\omega t_{1}-\omega' t_{2})} \hat{a}_{A}^{(H)\dagger}(\omega) \hat{a}_{A}^{(H)}(\omega')\right) = \overline{r} \mathrm{e}^{\mathrm{i}\omega_{0}(t_{1}-t_{2})} \mathrm{e}^{-(t_{1}-t_{2})^{2} \Delta \omega^{2}/2}$$

for the multimode thermal state $\hat{\rho}_H$ in (1), we obtain

$$G_{\theta_{C},\theta_{T}}^{(1)}(t_{C},t_{T}) = -\frac{\mathrm{i}K^{2}}{4}\overline{\tau} \left[\cos\theta_{C}\cos\phi_{\mathcal{C}}\cos\left(\theta_{T}-\phi_{\mathcal{T}}\right) \mathrm{e}^{\mathrm{i}\omega_{0}[t_{C}^{(S_{C})}-t_{T}^{(S_{T})}]} \mathrm{e}^{-[t_{C}^{(S_{C})}-t_{T}^{(S_{T})}]^{2}\Delta\omega^{2}/2} \right. \\ \left. + \cos\theta_{C}\cos\phi_{\mathcal{C}}\sin\left(\theta_{T}+\phi_{\mathcal{T}}\right) \mathrm{e}^{\mathrm{i}\omega_{0}[t_{C}^{(S_{C})}-t_{T}^{(L_{T})}]} \mathrm{e}^{-[t_{C}^{(S_{C})}-t_{T}^{(L_{T})}]^{2}\Delta\omega^{2}/2} \right. \\ \left. + \sin\theta_{C}\sin\phi_{\mathcal{C}}\cos\left(\theta_{T}-\phi_{\mathcal{T}}\right) \mathrm{e}^{\mathrm{i}\omega_{0}[t_{C}^{(L_{C})}-t_{T}^{(S_{T})}]} \mathrm{e}^{-[t_{C}^{(L_{C})}-t_{T}^{(S_{T})}]^{2}\Delta\omega^{2}/2} \right. \\ \left. + \sin\theta_{C}\sin\phi_{\mathcal{C}}\sin\left(\theta_{T}+\phi_{\mathcal{T}}\right) \mathrm{e}^{\mathrm{i}\omega_{0}[t_{C}^{(L_{C})}-t_{T}^{(L_{T})}]} \mathrm{e}^{-[t_{C}^{(L_{C})}-t_{T}^{(L_{T})}]^{2}\Delta\omega^{2}/2} \right] .$$
 (B.6)

Finally, by applying the conditions (in (11) and (10))

$$\begin{vmatrix} t_C^{(L_C)} - t_T^{(S_T)} \end{vmatrix} \Delta \omega \gg 1, \quad \begin{vmatrix} t_T^{(L_T)} - t_C^{(S_C)} \end{vmatrix} \Delta \omega \gg 1, \\ \begin{vmatrix} t_C^{(L_C)} - t_T^{(L_T)} \end{vmatrix} \Delta \omega \ll 1, \quad \begin{vmatrix} t_C^{(S_C)} - t_T^{(S_T)} \end{vmatrix} \Delta \omega \ll 1,$$

(B.6) reduces to

$$G_{\theta_C,\theta_T}^{(1)}(t_C, t_T) = G_{\theta_C,\theta_T}^{(L_C, L_T)}(t_C, t_T) + G_{\theta_C,\theta_T}^{(S_C, S_T)}(t_C, t_T),$$

with the two contributions

$$G_{\theta_C,\theta_T}^{(S_C,S_T)}(t_C,t_T) = -i\frac{K^2}{4}\overline{r}\cos\phi_{\mathcal{C}}\cos\theta_C\cos\left(\phi_{\mathcal{T}}-\theta_T\right)e^{i\omega_0\left[(t_C^{(S_C)}-t_T^{(S_T)}\right]},$$
$$G_{\theta_C,\theta_T}^{(L_C,L_T)}(t_C,t_T) = -i\frac{K^2}{4}\overline{r}\sin\phi_{\mathcal{C}}\sin\theta_C\sin\left(\phi_{\mathcal{T}}+\theta_T\right)e^{i\omega_0\left[(t_C^{(L_C)}-t_T^{(L_T)}\right]}.$$

Thereby, (B.1) reads

$$\left\langle \Delta n_{\theta_C} \Delta n_{\theta_T} \right\rangle_{C,T} \propto \left| G_{\theta_C \theta_T}^{(L_C, L_T)}(t_C, t_T) + G_{\theta_C \theta_T}^{(S_C, S_T)}(t_C, t_T) \right|^2,$$

which, by introducing the relative phase (in (17))

$$\varphi_{L-S} := \frac{\omega_0}{c} \left[\left(L_C - L_T \right) - \left(S_C - S_T \right) \right],$$

finally reduces to

 $\left\langle \Delta n_{\theta_C} \Delta n_{\theta_T} \right\rangle_{C,T} \propto \overline{r}^2 \left| \cos \phi_C \cos \theta_C \cos \left(\phi_T - \theta_T \right) + \mathrm{e}^{\mathrm{i}\varphi_{L-S}} \sin \phi_C \sin \theta_C \sin \left(\phi_T + \theta_T \right) \right|^2,$ as in (22).

References

- Brown R H and Twiss R Q 1956 Nature 177 27-29 ISSN 0028-0836 URL http://dx.doi.org/10.1038/177027a0
- [2] Hanbury Brown R and Twiss R Q 1956 Nature 178 1046-1048 URL http://dx.doi.org/10.1038/1781046a0
- [3] Glauber R J 1963 Phys. Rev. Lett. 10(3) 84-86 URL http://link.aps.org/doi/10.1103/PhysRevLett.10.84
- [4] Glauber R J 2006 Rev. Mod. Phys. 78 1267-1278 ISSN 1539-0756 URL http://dx.doi.org/10.1103/RevModPhys.78.1267
- [5] Alley C O and Shih Y H 1986 Proceedings of the Second International Symposium on Foundations of Quantum Mechanics in the Light of New Technology ed of Japan P S (Tokyo) pp 47 - 52 Shih Y H and Alley C O 1988 Phys. Rev. Lett. 61(26) 2921-2924 URL http://link.aps.org/doi/10.1103/PhysRevLett.61.2921
- [6] Hong C K, Ou Z Y and Mandel L 1987 Phys. Rev. Lett. 59(18) 2044-2046 URL http://link.aps.org/doi/10.1103/PhysRevLett.59.2044
- [7] Franson J D 1989 Phys. Rev. Lett. 62(19) 2205-2208 URL http://link.aps.org/doi/10.1103/PhysRevLett.62.2205
- [8] Tamma V and Laibacher S 2015 Phys. Rev. Lett. 114(24) 243601 URL http://link.aps.org/doi/10.1103/PhysRevLett.114.243601
- [9] Tamma V and Laibacher S 2014 Phys. Rev. A 90(6) 063836 URL http://link.aps.org/doi/10.1103/PhysRevA.90.063836
- [10] Nielsen M and Chuang I 2000 Quantum Computation and Quantum Information Cambridge Series on Information and the Natural Sciences (Cambridge University Press) ISBN 9780521635035 URL http://books.google.de/books?id=65FqEKQ0fP8C
- [11] Pan J W, Chen Z B, Lu C Y, Weinfurter H, Zeilinger A and Žukowski M 2012 Rev. Mod. Phys. 84(2) 777-838 URL http://link.aps.org/doi/10.1103/RevModPhys.84.777
- [12] Laibacher S and Tamma V 2015 Phys. Rev. Lett. 115(24) 243605 URL http://link.aps.org/doi/10.1103/PhysRevLett.115.243605
- [13] Tamma V 2014 International Journal of Quantum Information 12 1560017
- [14] Tamma V and Laibacher S 2015 Journal of Modern Optics 1-5 URL http://dx.doi.org/10.1080/09500340.2015.1088096
- [15] Tamma V and Laibacher S 2015 Quantum Inf. Process. 1-22 ISSN 1570-0755, 1573-1332 URL http://link.springer.com/10.1007/s11128-015-1177-8
- [16] Shih Y 2011 An Introduction to Quantum Optics (CRC Press Taylor and Francis group)

- [17] Pittman T B, Shih Y H, Strekalov D V and Sergienko A V 1995 Phys. Rev. A 52(5) R3429-R3432
 URL http://link.aps.org/doi/10.1103/PhysRevA.52.R3429
- [18] Bennink R S, Bentley S J and Boyd R W 2002 Phys. Rev. Lett. 89(11) 113601 URL http://link.aps.org/doi/10.1103/PhysRevLett.89.113601
- [19] Valencia A, Scarcelli G, D'Angelo M and Shih Y 2005 Phys. Rev. Lett. 94(6) 063601 URL http://link.aps.org/doi/10.1103/PhysRevLett.94.063601
- [20] Ferri F, Magatti D, Gatti A, Bache M, Brambilla E and Lugiato L A 2005 Phys. Rev. Lett. 94(18) 183602 URL http://link.aps.org/doi/10.1103/PhysRevLett.94.183602
- [21] Oppel S, Büttner T, Kok P and von Zanthier J 2012 Physical Review Letters 109 ISSN 1079-7114 URL http://dx.doi.org/10.1103/PhysRevLett.109.233603
- [22] Pearce M E, Mehringer T, von Zanthier J and Kok P 2015 Phys. Rev. A 92(4) 043831 URL http://link.aps.org/doi/10.1103/PhysRevA.92.043831
- [23] Cerf N J, Adami C and Kwiat P G 1998 Phys. Rev. A 57(3) R1477-R1480 URL http://link.aps.org/doi/10.1103/PhysRevA.57.R1477
- [24] Spreeuw R J C 2001 *Phys. Rev. A* **63**(6) 062302 URL http://link.aps.org/doi/10.1103/PhysRevA.63.062302
- [25] Lee K F and Thomas J E 2002 Physical Review Letters 88 097902 URL http://link.aps.org/doi/10.1103/PhysRevLett.88.097902
- [26] Lee K F and Thomas J E 2004 Phys. Rev. A 69 052311 URL http://link.aps.org/doi/10.1103/PhysRevA.69.052311
- [27] Fu J, Si Z, Tang S and Deng J 2004 Phys. Rev. A 70 042313 URL http://link.aps.org/doi/10.1103/PhysRevA.70.042313
- [28] Chen H, Peng T, Karmakar S and Shih Y 2011 New J. Phys. 13 083018 ISSN 1367-2630 URL http://dx.doi.org/10.1088/1367-2630/13/8/083018
- [29] Kagalwala K H, di Giuseppe G, Abouraddy A F and Saleh B E A 2013 Nature Photonics 7 72–78
- [30] Peng T and Shih Y 2015 EPL (Europhysics Letters) **112** 60006 URL http://stacks.iop.org/0295-5075/112/i=6/a=60006
- [31] Lomonaco S 2002 Quantum Computation: A Grand Mathematical Challenge for the Twenty-First Century and the Millennium (Proceedings of Symposia in Applied Mathematics) URL http://books.google.de/books?id=65FqEKQ0fP8C
- [32] Pittman T B, Fitch M J, Jacobs B C and Franson J D 2003 Phys. Rev. A 68(3) 032316 URL http://link.aps.org/doi/10.1103/PhysRevA.68.032316
- [33] O'Brien J L, Pryde G J, White A G, Ralph T C and Branning D 2003 Nature 426 264–267 ISSN 0028-0836 URL http://dx.doi.org/10.1038/nature02054
- [34] Gasparoni S, Pan J W, Walther P, Rudolph T and Zeilinger A 2004 Physical Review Letters 93 ISSN 1079-7114 URL http://dx.doi.org/10.1103/PhysRevLett.93.020504
- [35] Okamoto R, Hofmann H F, Takeuchi S and Sasaki K 2005 Physical Review Letters 95 ISSN 1079-7114 URL http://dx.doi.org/10.1103/PhysRevLett.95.210506
- [36] Okamoto R, O'Brien J L, Hofmann H F and Takeuchi S 2011 Proceedings of the National Academy of Sciences 108 10067-10071 ISSN 1091-6490 URL http://dx.doi.org/10.1073/pnas.1018839108
- [37] Sanaka K, Kawahara K and Kuga T 2002 Phys. Rev. A 66(4) 040301 URL http://link.aps.org/doi/10.1103/PhysRevA.66.040301
- [38] Glauber R J 2007 Quantum Theory of Optical Coherence: Selected Papers and Lectures (John Wiley and Sons) ISBN 978-3-527-40687-6
- [39] Mandel L and Wolf E 1995 Optical Coherence and Quantum Optics (Cambridge University Press) ISBN 9780521417112 URL http://books.google.de/books?id=FeBix14iM70C
- [40] Sudarshan E C G 1963 Phys. Rev. Lett. 10(7) 277-279 URL http://link.aps.org/doi/10.1103/PhysRevLett.10.277
- [41] Peng T, Chen H, Shih Y and Scully M O 2014 Phys. Rev. Lett. 112(18) 180401 URL http://link.aps.org/doi/10.1103/PhysRevLett.112.180401

- [42] Chen H, Peng T and Shih Y 2013 Phys. Rev. A 88(2) 023808 URL http://link.aps.org/doi/10.1103/PhysRevA.88.023808
- [43] Arecchi F, Gatti E and Sona A 1966 Physics Letters 20 27 29 ISSN 0031-9163 URL http://www.sciencedirect.com/science/article/pii/0031916366910341
- [44] Cassano M, D'Angelo M, Garuccio A, Peng T, Shih Y and Tamma V 2016 (Preprint 1601.05045)
- [45] Crespi A, Lobino M, Matthews J C F, Politi A, Neal C R, Ramponi R, Osellame R and O'Brien J L 2012 Applied Physics Letters 100 233704 URL http://scitation.aip.org/content/aip/journal/apl/100/23/10.1063/1.4724105
- [46] Tamma V 2015 Quantum Inf. Process. 11128:1190 URL http://link.springer.com/article/10.1007%2Fs11128-015-1190-y
- [47] Tamma V 2015 Quantum Inf. Process. **11128**:1189 URL http://link.springer.com/article/10.1007/s11128-015-1189-4
- [48] Tamma V, Zhang H, He X, Garuccio A, Schleich W P and Shih Y 2011 Phys. Rev. A 83(2) 020304 URL http://link.aps.org/doi/10.1103/PhysRevA.83.020304
- [49] Tamma V, Zhang H, He X, Garuccio A and Shih Y 2009 Journal of Modern Optics 56 2125–2132 URL http://dx.doi.org/10.1080/09500340903254700
- [50] Tamma V, Alley C O, Schleich W P and Shih Y H 2012 Found Phys 42 111–121 ISSN 1572-9516 URL http://dx.doi.org/10.1007/s10701-010-9522-3