

Explicit constructions of high-rate MDS array codes with optimal repair bandwidth

Min Ye

Alexander Barg

Abstract

Maximum distance separable (MDS) codes are optimal error-correcting codes in the sense that they provide the maximum failure-tolerance for a given number of parity nodes. Suppose that an MDS code with k information nodes and $r = n - k$ parity nodes is used to encode data in a distributed storage system. It is known that if h out of the n nodes are inaccessible and d surviving (helper) nodes are used to recover the lost data, then we need to download at least $h/(d + h - k)$ fraction of the data stored in each of the helper nodes (Dimakis et al., 2010 and Cadambe et al., 2013). If this lower bound is achieved for the repair of any h erased nodes from any d helper nodes, we say that the MDS code has the (h, d) -optimal repair property.

We study high-rate MDS array codes with the optimal repair property. Explicit constructions of such codes in the literature are only available for the cases where there are at most 3 parity nodes, and these existing constructions can only optimally repair a single node failure by accessing all the surviving nodes.

In this paper, given any r and n , we present two explicit constructions of MDS array codes with the (h, d) -optimal repair property for all $h \leq r$ and $k \leq d \leq n - h$ simultaneously. Codes in the first family can be constructed over any base field F as long as $|F| \geq sn$, where $s = \text{lcm}(1, 2, \dots, r)$. The encoding, decoding, repair of failed nodes, and update procedures of these codes all have low complexity. Codes in the second family have the optimal access property and can be constructed over any base field F as long as $|F| \geq n + 1$. Moreover, both code families have the optimal error resilience capability when repairing failed nodes. We also construct several other related families of MDS codes with the optimal repair property.

I. INTRODUCTION

Distributed storage systems, such as those run by Google [1] and Facebook [2], are widely used for data storage, with applications ranging from social networks to file and video sharing. Currently deployed systems are formed of thousands of individual drives (nodes), and drive failures occur on a daily basis. For this reason, companies utilizing or providing distributed storage solutions have increasingly turned to error-correcting coding for efficient recovery of data stored in the system. The coding method of choice used for data protection relies on MDS codes which provide the maximum failure tolerance for a given amount of storage overhead. The distributed nature of the system introduces new challenges in the code design that are related to the need to communicate data between the nodes during the repair of node failures. Efficient operation of the system requires minimizing the *repair bandwidth*, i.e., the amount of data that needs to be downloaded to repair the contents of the failed node(s). Therefore, recent research on MDS codes for distributed storage has focused on codes with minimum repair bandwidth.

In this paper, following the literature on codes for storage, we use the terminology motivated by storage applications: code's coordinates are called nodes, correcting erasures is referred to as repairing (or recovering) failed nodes, and the process of obtaining the information stored at some other nodes in the codeword to repair the failed node(s) is described as "downloading data from the helper nodes". As usual in distributed storage applications, we assume that an MDS code of length n formed of k information coordinates and $r = n - k$ parity coordinates is spread across n different nodes of the storage cluster. Each node of the cluster stores a coordinate of the code.

A. Notation and earlier results

Most studies of MDS codes with optimal repair bandwidth in the literature are concerned with a particular subclass of codes known as MDS *array codes* [3]. An (n, k, l) MDS array code has k information nodes and $r = n - k$ parity nodes in each codeword with the property that any k out of n nodes can recover the codeword. Every node is a column vector in F^l , where F is some finite field, reflecting the fact that the system views a large data block stored in one node as one coordinate of the codeword.

Suppose that $h \geq 1$ nodes become unavailable, and the system attempts to repair their contents by accessing $d \leq n - h$ surviving (helper) nodes. In this case, as shown in [4], [5], the recovery of failed nodes requires to download at least an $h/(d + h - k)$ fraction of the data stored in each of the helper nodes. More formally, given

The authors are with Dept. of ECE and ISR, University of Maryland, College Park, MD 20742. Emails: yeemmi@gmail.com and abarg@umd.edu. Research supported by NSF grants CCF1422955 and CCF1217245.

an (n, k, l) MDS array code \mathcal{C} and two disjoint subsets $\mathcal{F}, \mathcal{R} \subseteq [n]$ such that $|\mathcal{F}| \leq r$ and $|\mathcal{R}| \geq k$, we define $N(\mathcal{C}, \mathcal{F}, \mathcal{R})$ as the smallest number of symbols¹ of F one needs to download from the surviving nodes $\{C_i, i \in \mathcal{R}\}$ in order to recover the erased nodes $\{C_i, i \in \mathcal{F}\}$. (We use the notation $[n] = \{1, 2, \dots, n\}$.) Dimakis et. al. [4] showed that

$$N(\mathcal{C}, \mathcal{F}, \mathcal{R}) \geq \frac{|\mathcal{F}||\mathcal{R}|l}{|\mathcal{F}| + |\mathcal{R}| - k} \quad (1)$$

for any (n, k, l) MDS array code \mathcal{C} and any two disjoint subsets $\mathcal{F}, \mathcal{R} \subseteq [n]$ such that $|\mathcal{F}| = 1$ and $|\mathcal{R}| \geq k$. Cadambe et. al. [5] further proved that (1) holds for any two disjoint subsets $\mathcal{F}, \mathcal{R} \subseteq [n]$ such that $|\mathcal{F}| \leq r$ and $|\mathcal{R}| \geq k$. If (1) is achieved, we say that \mathcal{C} can *optimally repair* nodes $\{C_i, i \in \mathcal{F}\}$ using nodes $\{C_i, i \in \mathcal{R}\}$.

Given an (n, k, l) MDS array code \mathcal{C} , we define the (h, d) -repair bandwidth of \mathcal{C} as

$$\max_{\mathcal{F} \cap \mathcal{R} = \emptyset, |\mathcal{F}|=h, |\mathcal{R}|=d} N(\mathcal{C}, \mathcal{F}, \mathcal{R}).$$

If the (h, d) -repair bandwidth of \mathcal{C} is $\frac{hdl}{h+d-k}$, meeting the lower bound in (1), we say that \mathcal{C} has (h, d) -optimal repair property. We further say that the code has the d -optimal repair property if $h = 1$, omitting the reference to h , and say that the code has the optimal repair property if $h = 1$ and $d = n - 1$.

In [6], [7], the authors considered the *error resilience* capability in the repair process of a single node failure. We generalize this concept to the repair process of multiple node failures. Given an (n, k, l) MDS array code \mathcal{C} , a nonnegative integer t and two disjoint subsets $\mathcal{F}, \mathcal{R} \subseteq [n]$ such that $|\mathcal{F}| \leq r$ and $|\mathcal{R}| \geq k + 2t$, we define $N(\mathcal{C}, \mathcal{F}, \mathcal{R}, t)$ as the smallest number of symbols of F one needs to download from nodes $\{C_i, i \in \mathcal{R}\}$ such that the erased nodes $\{C_i, i \in \mathcal{F}\}$ can be recovered from these symbols as long as the number of erroneous nodes in $\{C_i, i \in \mathcal{R}\}$ is no larger than t . It is shown in [6], [7] that

$$N(\mathcal{C}, \mathcal{F}, \mathcal{R}, t) \geq \frac{|\mathcal{F}||\mathcal{R}|l}{|\mathcal{F}| + |\mathcal{R}| - 2t - k} \quad (2)$$

for any (n, k, l) MDS array code \mathcal{C} , any nonnegative integer t and any two disjoint subsets $\mathcal{F}, \mathcal{R} \subseteq [n]$ such that $|\mathcal{F}| = 1$ and $|\mathcal{R}| \geq k + 2t$. The method in [6], [7] can be straightforwardly generalized to show that (2) also holds for any \mathcal{F} such that $|\mathcal{F}| \leq r$. We say that an (n, k, l) MDS array code \mathcal{C} has the *universally error-resilient (UER)* (h, d) -optimal repair property if

$$N(\mathcal{C}, \mathcal{F}, \mathcal{R}, t) = \frac{h(d + 2t)l}{h + d - k}$$

for any nonnegative integer t and any two disjoint subsets $\mathcal{F}, \mathcal{R} \subseteq [n]$ such that $|\mathcal{F}| = h$ and $|\mathcal{R}| = d + 2t$. As above, when $h = 1$, we omit it from the notation.

In general, the downloaded data in the repair process can be some functions, e.g., linear combinations of the data stored in the helper nodes. As a result, even for codes with optimal repair property, we might still need to access a larger amount of data than the lower bounds in (1) and (2). We say that an (n, k, l) MDS array code \mathcal{C} has (h, d) -optimal access property if the repair of any h erased nodes using any d helper nodes can be accomplished by accessing the amount of data that meets the lower bound in (1). We define the *UER* (h, d) -optimal access property in a similar way.

For $k \leq (n + 1)/2$ (the low rate regime), MDS array codes with d -optimal repair property were constructed in [8]–[12], and MDS array codes with the UER d -optimal repair property were constructed in [7]. For arbitrary code rate, [5] proved that there exists a family of codes for which the bound (1) is asymptotically achieved when $l \rightarrow \infty$. For finite l and $k > (n + 1)/2$ (the high-rate regime) papers [13]–[17] showed that for large enough base field F there exist MDS array codes that can optimally repair any single systematic node failure using all the surviving nodes, and [18] showed the same for all rather than only systematic nodes.

Among the very recent additions to the literature, [19] showed existence of MDS array codes with d -optimal repair property for any single value of d in the range $k \leq d \leq n - 1$. Paper [20] showed existence of MDS array codes that can optimally repair any single systematic node failure by accessing any subset of the surviving nodes as long as the number of accessed nodes is no less than k . Finally [21] showed existence of MDS array codes which can optimally repair any h systematic node failures using all the $n - h$ surviving nodes for any single value of h in the range $1 \leq h \leq r$ (some special cases for $h = 2$ and 3 are discussed in [22]). These papers essentially rely on existential lemmas in large finite fields, e.g., the Schwartz-Zippel lemma or Combinatorial Nullstellensatz. At the same time, all the known explicit constructions in the high-rate regime are obtained only for the case of at most 3 parity nodes, and are further limited to repairing $h = 1$ failed node by accessing all the $n - 1$ surviving nodes; see [15]–[18], [23].

¹these symbols can be some functions of the contents of the nodes $\{C_i, i \in \mathcal{R}\}$.

B. Overview of the paper

In this paper, given any n and k , we present two explicit families of (n, k, l) MDS array codes. Codes in the first family have the UER (h, d) -optimal repair property for all $h \leq r$ and $k \leq d \leq n - h$ simultaneously, and the encoding, decoding, repair and update procedures of these codes all have low complexity. Codes in the second family have the UER (h, d) -optimal access property for all $h \leq r$ and $k \leq d \leq n - h$ simultaneously, and can be constructed over any base field F as long as $|F| \geq n + 1$.

The paper is organized as follows. In Sections III-VI we present the first code family and its variants. Sections VII-X are devoted to the second family and related results. Finally, in Sect. XI we present a new class of MDS array codes with optimal repair and smaller l than the other constructions. In the next few paragraphs we give a more detailed overview of our results.

In Section III, we present our first construction of $(n, k, l = r^n)$ MDS array codes with the optimal repair property using any field F of size $|F| \geq rn$. The encoding, decoding, and repair of a single failed node involve only simple operations with $r \times r$ matrices over F , and thus have low complexity. An additional property of the proposed codes is optimal update, i.e., the need to change only the minimum possible number of coordinates in the parity nodes if one coordinate in systematic node is updated. In our construction we rely on a (non-systematic) parity-check representation of the codes as opposed to the systematic generator form used in most earlier works. This representation does not distinguish between systematic nodes and parity nodes, and leads naturally to the optimal repair of all nodes. The parity-check form combined with the block Vandermonde structure [17] and the idea of using r -ary expansions [13], [16] makes the explicit construction for larger number of parity nodes possible. Note that exponentially large l is necessary for optimal repair bandwidth: Indeed, according to a result of [24], $l \geq 2^{\sqrt{k/(2r-1)}}$ is necessary for any code with the optimal repair property. It is further shown in [25] that $l \geq r^{(k-1)/r}$ for any code with the optimal access property.

In Section IV, we extend the construction of Section III to obtain (n, k, l) MDS array codes with the UER d -optimal repair property for any positive integers n, k, d, l such that $k \leq d < n, l = (d + 1 - k)^n$ using any field F of size $|F| \geq (d + 1 - k)n$. We first observe that we only need to know a $1/(d + 1 - k)$ fraction of data stored in each of the surviving nodes $C_j, j \neq i$ in order to recover the erased node C_i . We then use a novel method to prove that these data form an $(n - 1, d, l/(d + 1 - k))$ MDS array code, and thus establish the UER d -optimal repair property.

In Section V, we present another extension, constructing MDS codes with d -optimal repair property for several values of d simultaneously. Moreover, we show that (n, k, r^n) MDS array codes constructed in Section III will automatically have the d -optimal repair property for all d such that $(d + 1 - k) | (n - k)$. In Section VI we further extend our construction to obtain (n, k, l) MDS array codes with the UER (h, d) -optimal repair property for all $h \leq r$ and $k \leq d \leq n - h$ simultaneously, where $l = s^n, s = \text{lcm}(1, 2, \dots, r)$. These codes also have the optimal update property. Moreover, the encoding, decoding, and repair procedures only require operations with matrices of size not greater than $n \times n$.

In Section VII we develop the idea of using permutation matrices [13], [16] to obtain an explicit family of $(n, n - r, r^{n-1})$ MDS array codes with the optimal access property, which can be constructed over any base field F such that $|F| \geq n + 1$. In Sections VIII-X, we combine the ideas in Section VII and in Sections IV-VI to obtain an explicit family of (n, k, l) MDS array codes with the UER (h, d) -optimal access property for all $h \leq r$ and $k \leq d \leq n - h$ simultaneously, where $l = s^n, s = \text{lcm}(1, 2, \dots, r)$. These codes can be constructed over any base field F as long as $|F| \geq n + 1$.

In Section XI we introduce a new class of MDS array codes, *Generalized Reed-Solomon Array Codes*, and use their properties to extend the construction of Section VII to obtain MDS array codes with the d -optimal repair property for several values of d simultaneously. These codes also only require the underlying field size $|F| \geq n + 1$ as well as a smaller l compared to the other code families in this paper.

II. GENERAL CODE CONSTRUCTION

Let $\mathcal{C} \in F^{ln}$ be an (n, k, l) array code with nodes $C_i \in F^l, i = 1, \dots, n$, where each C_i is a column vector. Throughout this paper we consider codes defined in the following parity-check form:

$$\mathcal{C} = \{(C_1, C_2, \dots, C_n) : \sum_{i=1}^n A_{t,i} C_i = 0, t = 1, \dots, r\}, \quad (3)$$

where $A_{t,i}, t = 1, \dots, r, i = 1, \dots, n$ are $l \times l$ matrices over F .

Given positive integers r and n , define an $(n, k = n - r, l)$ array code \mathcal{C} by setting in (3)

$$A_{t,i} = A_i^{t-1}, t \in [r], i \in [n], \quad (4)$$

where A_1, A_2, \dots, A_n are some $l \times l$ matrices. (We use the convention $A^0 = I$.) The specific code families in Section III-XI are obtained by choosing different forms of the matrices A_1, A_2, \dots, A_n .

III. CONSTRUCTION OF MDS ARRAY CODES WITH OPTIMAL REPAIR PROPERTY

A. Code construction

Construction 1. Let F be a finite field of size $|F| \geq rn$, and let $l = r^n$. Let $\{\lambda_{i,j}\}_{i \in [n], j=0,1,\dots,r-1}$ be rn distinct elements in F . Consider the code family given by (3)-(4), where we take

$$A_i = \sum_{a=0}^{l-1} \lambda_{i,a_i} e_a e_a^T, \quad i = 1, \dots, n.$$

Here $\{e_a : a = 0, 1, \dots, l-1\}$ is the standard basis of F^l over F , and a_i is the i -th digit from the right in the representation of a in the r -ary form, $a = (a_n, a_{n-1}, \dots, a_1)$.

Since the $A_i, i = 1, \dots, n$ are diagonal matrices, we can write out the parity-check equations (3) coordinatewise. Let $c_{i,a}$ denote the a -th coordinate of the column vector C_i for all $a = 0, \dots, l-1$, i.e., $C_i = (c_{i,0}, c_{i,1}, \dots, c_{i,l-1})^T$. We have

$$\sum_{i=1}^n \lambda_{i,a_i}^t c_{i,a} = 0 \quad (5)$$

for all $t = 0, \dots, r-1$ and $a = 0, \dots, l-1$.

Theorem III.1. Codes given by Construction 1 attain optimal repair bandwidth for repairing any single failed node.

Proof: For $u = 0, 1, \dots, r-1$, let $a(i, u) := (a_n, \dots, a_{i+1}, u, a_{i-1}, \dots, a_1)$. We will show that for any $i \in [n]$ and $a = 0, 1, \dots, l-1$, the coordinates $\{c_{i,a(i,0)}, c_{i,a(i,1)}, \dots, c_{i,a(i,r-1)}\}$ in C_i are functions of the following set of $n-1$ elements of F :

$$\mu_{j,i}^{(a)} := \sum_{u=0}^{r-1} c_{j,a(i,u)}, \quad j \in [n] \setminus \{i\}. \quad (6)$$

In other words, each surviving node only needs to transmit one scalar in F to recover r coordinates in the failed node, so the optimal repair bandwidth is achieved. Replacing a with $a(i, u)$ in (5), we obtain

$$\lambda_{i,u}^t c_{i,a(i,u)} + \sum_{j \neq i} \lambda_{j,a_j}^t c_{j,a(i,u)} = 0. \quad (7)$$

Summing (7) over $u = 0, 1, \dots, r-1$ and then writing the result in matrix form, we get

$$\begin{bmatrix} 1 & 1 & \dots & 1 \\ \lambda_{i,0} & \lambda_{i,1} & \dots & \lambda_{i,r-1} \\ \vdots & \vdots & \ddots & \vdots \\ \lambda_{i,0}^{r-1} & \lambda_{i,1}^{r-1} & \dots & \lambda_{i,r-1}^{r-1} \end{bmatrix} \begin{bmatrix} c_{i,a(i,0)} \\ c_{i,a(i,1)} \\ \vdots \\ c_{i,a(i,r-1)} \end{bmatrix} = - \begin{bmatrix} \sum_{j \neq i} \mu_{j,i}^{(a)} \\ \sum_{j \neq i} \lambda_{j,a_j} \mu_{j,i}^{(a)} \\ \vdots \\ \sum_{j \neq i} \lambda_{j,a_j}^{r-1} \mu_{j,i}^{(a)} \end{bmatrix}. \quad (8)$$

By construction $\lambda_{i,0}, \dots, \lambda_{i,r-1}$ are distinct, so we can solve this system for $\{c_{i,a(i,0)}, c_{i,a(i,1)}, \dots, c_{i,a(i,r-1)}\}$ given the set of elements in (6). ■

The repair procedure of a single node has low complexity: indeed, according to (8), it can be accomplished by operations with $r \times r$ matrices (rather than much larger $l \times l$ matrices).

Theorem III.2. The code \mathcal{C} given by Construction 1 is MDS.

Proof: We write out the parity-check equations (3) coordinatewise. For all $a = 0, 1, \dots, l-1$, we have

$$\begin{bmatrix} 1 & 1 & \dots & 1 \\ \lambda_{1,a_1} & \lambda_{2,a_2} & \dots & \lambda_{n,a_n} \\ \vdots & \vdots & \ddots & \vdots \\ \lambda_{1,a_1}^{r-1} & \lambda_{2,a_2}^{r-1} & \dots & \lambda_{n,a_n}^{r-1} \end{bmatrix} \begin{bmatrix} c_{1,a} \\ c_{2,a} \\ \vdots \\ c_{n,a} \end{bmatrix} = 0 \quad (9)$$

Clearly every r columns of the parity-check matrix in (9) have rank r , so any k out of n elements in the set $\{c_{1,a}, c_{2,a}, \dots, c_{n,a}\}$ can recover the whole set. Since this holds for all $a = 0, 1, \dots, l-1$, we conclude that any k nodes of a codeword in \mathcal{C} can recover the whole codeword. ■

B. Complexity of encoding, decoding, and updates

The code given by Construction 1 can be efficiently transformed into systematic form. Without loss of generality we assume that the first k nodes are systematic (information) nodes. By (9), for all $a = 0, 1, \dots, l-1$, we have

$$\begin{bmatrix} 1 & 1 & \dots & 1 \\ \lambda_{k+1, a_{k+1}} & \lambda_{k+2, a_{k+2}} & \dots & \lambda_{k+r, a_{k+r}} \\ \vdots & \vdots & \vdots & \vdots \\ \lambda_{k+1, a_{k+1}}^{r-1} & \lambda_{k+2, a_{k+2}}^{r-1} & \dots & \lambda_{k+r, a_{k+r}}^{r-1} \end{bmatrix} \begin{bmatrix} c_{k+1, a} \\ c_{k+2, a} \\ \vdots \\ c_{k+r, a} \end{bmatrix} = - \begin{bmatrix} 1 & 1 & \dots & 1 \\ \lambda_{1, a_1} & \lambda_{2, a_2} & \dots & \lambda_{k, a_k} \\ \vdots & \vdots & \vdots & \vdots \\ \lambda_{1, a_1}^{r-1} & \lambda_{2, a_2}^{r-1} & \dots & \lambda_{k, a_k}^{r-1} \end{bmatrix} \begin{bmatrix} c_{1, a} \\ c_{2, a} \\ \vdots \\ c_{k, a} \end{bmatrix}. \quad (10)$$

Consequently, in the encoding process we do not need to invert an $rl \times rl$ matrix, instead, we only need to invert $r \times r$ matrices l times, gaining a factor of l^2 in complexity. Similarly, in the decoding process, if some r nodes are erased, then in order to recover them, we only need to invert $r \times r$ matrices l times.

Another useful parameter of codes is *update complexity* [3]. On account of the MDS property, in order to update the value of a stored element $c_{i,a}$ in an information node, one needs to update at least one coordinate in every parity node [25]. From (10) it is easy to see that for any $i \in [k]$ and $a = 0, \dots, l-1$, to update $c_{i,a}$, we only need to update $c_{k+1, a}, \dots, c_{k+r, a}$. Thus Construction 1 gives an optimal update code.

IV. EXPLICIT MDS ARRAY CODES WITH THE UER d -OPTIMAL REPAIR PROPERTY

The general construction in (3)-(4) can also be used to construct an $(n, k = n - r, l)$ MDS array code \mathcal{C} with the UER d -optimal repair property, $k \leq d \leq n - 1$.

Construction 2. Let F be a finite field of size $|F| \geq sn$, where $s = d + 1 - k$. Let $\{\lambda_{i,j}\}_{i \in [n], j=0,1,\dots,s-1}$ be sn distinct elements in F . Consider the code family given by (3)-(4), where $l = s^n$ and

$$A_i = \sum_{a=0}^{l-1} \lambda_{i, a_i} e_a e_a^T, \quad i = 1, \dots, n.$$

Here $\{e_a : a = 0, 1, \dots, l-1\}$ is the standard basis of F^l over F and a_i is the i -th digit from the right in the representation of a in the s -ary form, $a = (a_n, a_{n-1}, \dots, a_1)$.

Define $a(i, u)$ and $c_{i,a}$ in the same way as in Sect. III.

Theorem IV.1. The code \mathcal{C} given by Construction 2 is an MDS code. ■

Proof: Same as the proof of Theorem III.2. ■

By the same arguments as in the previous section, \mathcal{C} also has low-complexity encoding, decoding, and the optimal update property.

Let us show that the code \mathcal{C} has the UER d -optimal repair property. Recall the definition of Generalized Reed-Solomon codes.

Definition IV.2. A Generalized Reed-Solomon code $\text{GRS}(n, k, \Omega, v) \subseteq F^n$ of dimension k over F with evaluation points $\Omega = \{\omega_1, \omega_2, \dots, \omega_n\} \subseteq F$ is the set of vectors

$$\{(v_1 f(\omega_1), \dots, v_n f(\omega_n)) \in F^n : f \in F[x], \deg f \leq k - 1\}$$

where $v = (v_1, \dots, v_n) \in (F^*)^n$ are some nonzero coefficients. If $v = (1, \dots, 1)$, then the GRS code is called a Reed-Solomon code.

Remark IV.3. The minimum distance of the code $\text{GRS}(n, k, \Omega, v)$ is $n - k + 1$. Note that the projection of the GRS code on any subset of coordinates $\Omega' \subset \Omega$, $|\Omega'| \geq k$, is itself a GRS code. In particular, its distance equals $|\Omega'| - k + 1$.

Theorem IV.4. The code \mathcal{C} given by Construction 2 has the UER d -optimal repair property.

Proof: Without loss of generality, we consider the case of repairing C_1 . Let

$$\mu_{j,1}^{(a)} := \sum_{u=0}^{s-1} c_{j, a(1,u)}, \quad j \in \{2, 3, \dots, n\}. \quad (11)$$

Using arguments similar to those that lead to (8), we obtain

$$\begin{bmatrix} 1 & 1 & \cdots & 1 \\ \lambda_{1,0} & \lambda_{1,1} & \cdots & \lambda_{1,s-1} \\ \lambda_{1,0}^2 & \lambda_{1,1}^2 & \cdots & \lambda_{1,s-1}^2 \\ \vdots & \vdots & \ddots & \vdots \\ \lambda_{1,0}^{r-1} & \lambda_{1,1}^{r-1} & \cdots & \lambda_{1,s-1}^{r-1} \end{bmatrix} \begin{bmatrix} c_{1,a(1,0)} \\ c_{1,a(1,1)} \\ \vdots \\ c_{1,a(1,s-1)} \end{bmatrix} = - \begin{bmatrix} 1 & 1 & \cdots & 1 \\ \lambda_{2,a_2} & \lambda_{3,a_3} & \cdots & \lambda_{n,a_n} \\ \lambda_{2,a_2}^2 & \lambda_{3,a_3}^2 & \cdots & \lambda_{n,a_n}^2 \\ \vdots & \vdots & \ddots & \vdots \\ \lambda_{2,a_2}^{r-1} & \lambda_{3,a_3}^{r-1} & \cdots & \lambda_{n,a_n}^{r-1} \end{bmatrix} \begin{bmatrix} \mu_{2,1}^{(a)} \\ \mu_{3,1}^{(a)} \\ \vdots \\ \mu_{n,1}^{(a)} \end{bmatrix}. \quad (12)$$

Define polynomials $p_0(x) = \prod_{u=0}^{s-1} (x - \lambda_{1,u})$, and $p_i(x) = x^i p_0(x)$ for $i = 0, 1, \dots, r-s-1$. We have proved the case of $d = n-1$ in the previous section, so here we only consider the case when $d < n-1$, and so $r-s-1 \geq 0$. Since the degree of $p_i(x)$ is less than r for all $i = 0, 1, \dots, r-s-1$, we can write

$$p_i(x) = \sum_{j=0}^{r-1} p_{i,j} x^j.$$

Define the $(r-s) \times r$ matrix

$$P = \begin{bmatrix} p_{0,0} & p_{0,1} & \cdots & p_{0,r-1} \\ p_{1,0} & p_{1,1} & \cdots & p_{1,r-1} \\ \vdots & \vdots & \ddots & \vdots \\ p_{r-s-1,0} & p_{r-s-1,1} & \cdots & p_{r-s-1,r-1} \end{bmatrix}.$$

Since

$$P \begin{bmatrix} 1 & 1 & \cdots & 1 \\ \lambda_{1,0} & \lambda_{1,1} & \cdots & \lambda_{1,s-1} \\ \lambda_{1,0}^2 & \lambda_{1,1}^2 & \cdots & \lambda_{1,s-1}^2 \\ \vdots & \vdots & \ddots & \vdots \\ \lambda_{1,0}^{r-1} & \lambda_{1,1}^{r-1} & \cdots & \lambda_{1,s-1}^{r-1} \end{bmatrix} = \begin{bmatrix} p_0(\lambda_{1,0}) & p_0(\lambda_{1,1}) & \cdots & p_0(\lambda_{1,s-1}) \\ p_1(\lambda_{1,0}) & p_1(\lambda_{1,1}) & \cdots & p_1(\lambda_{1,s-1}) \\ \vdots & \vdots & \ddots & \vdots \\ p_{r-s-1}(\lambda_{1,0}) & p_{r-s-1}(\lambda_{1,1}) & \cdots & p_{r-s-1}(\lambda_{1,s-1}) \end{bmatrix} = 0,$$

together with (12), we have

$$P \begin{bmatrix} 1 & 1 & \cdots & 1 \\ \lambda_{2,a_2} & \lambda_{3,a_3} & \cdots & \lambda_{n,a_n} \\ \lambda_{2,a_2}^2 & \lambda_{3,a_3}^2 & \cdots & \lambda_{n,a_n}^2 \\ \vdots & \vdots & \ddots & \vdots \\ \lambda_{2,a_2}^{r-1} & \lambda_{3,a_3}^{r-1} & \cdots & \lambda_{n,a_n}^{r-1} \end{bmatrix} \begin{bmatrix} \mu_{2,1}^{(a)} \\ \mu_{3,1}^{(a)} \\ \vdots \\ \mu_{n,1}^{(a)} \end{bmatrix} = 0. \quad (13)$$

Note that

$$\begin{aligned} P \begin{bmatrix} 1 & 1 & \cdots & 1 \\ \lambda_{2,a_2} & \lambda_{3,a_3} & \cdots & \lambda_{n,a_n} \\ \lambda_{2,a_2}^2 & \lambda_{3,a_3}^2 & \cdots & \lambda_{n,a_n}^2 \\ \vdots & \vdots & \ddots & \vdots \\ \lambda_{2,a_2}^{r-1} & \lambda_{3,a_3}^{r-1} & \cdots & \lambda_{n,a_n}^{r-1} \end{bmatrix} &= \begin{bmatrix} p_0(\lambda_{2,a_2}) & p_0(\lambda_{3,a_3}) & \cdots & p_0(\lambda_{n,a_n}) \\ p_1(\lambda_{2,a_2}) & p_1(\lambda_{3,a_3}) & \cdots & p_1(\lambda_{n,a_n}) \\ \vdots & \vdots & \ddots & \vdots \\ p_{r-s-1}(\lambda_{2,a_2}) & p_{r-s-1}(\lambda_{3,a_3}) & \cdots & p_{r-s-1}(\lambda_{n,a_n}) \end{bmatrix} \\ &= \begin{bmatrix} p_0(\lambda_{2,a_2}) & p_0(\lambda_{3,a_3}) & \cdots & p_0(\lambda_{n,a_n}) \\ p_0(\lambda_{2,a_2})\lambda_{2,a_2} & p_0(\lambda_{3,a_3})\lambda_{3,a_3} & \cdots & p_0(\lambda_{n,a_n})\lambda_{n,a_n} \\ \vdots & \vdots & \ddots & \vdots \\ p_0(\lambda_{2,a_2})\lambda_{2,a_2}^{r-s-1} & p_0(\lambda_{3,a_3})\lambda_{3,a_3}^{r-s-1} & \cdots & p_0(\lambda_{n,a_n})\lambda_{n,a_n}^{r-s-1} \end{bmatrix}. \end{aligned}$$

Moreover, $p_0(\lambda_{2,a_2}), p_0(\lambda_{3,a_3}), \dots, p_0(\lambda_{n,a_n})$ are all nonzero. Thus $(\mu_{2,1}^{(a)}, \mu_{3,1}^{(a)}, \dots, \mu_{n,1}^{(a)})$ forms a Generalized Reed-Solomon code of length $n-1$ and dimension d . According to Remark IV.3, given a nonnegative integer t such that $d + 2t < n$, any $d + 2t$ out of $n-1$ elements in $\{\mu_{2,1}^{(a)}, \mu_{3,1}^{(a)}, \dots, \mu_{n,1}^{(a)}\}$ suffice to recover the whole set as long as the number of erroneous elements in the $d + 2t$ elements is not greater than t . Moreover, (12) implies that $\{c_{1,a(1,0)}, c_{1,a(1,1)}, \dots, c_{1,a(1,s-1)}\}$ can be determined by $\{\mu_{2,1}^{(a)}, \mu_{3,1}^{(a)}, \dots, \mu_{n,1}^{(a)}\}$. Consequently, we can recover C_1 by accessing any $d + 2t$ surviving nodes and downloading the total of $(d + 2t)l/s$ symbols of F from these nodes as long as the number of erroneous nodes among the helper nodes is not greater than t . This completes the proof. \blacksquare

V. MDS ARRAY CODES WITH THE UER d -OPTIMAL REPAIR PROPERTY FOR SEVERAL VALUES OF d SIMULTANEOUSLY

In the previous two sections, we constructed MDS array codes with the UER d -optimal repair property for a single value of d . In this section we give a simple extension of the previous constructions to make the code have the UER d -optimal repair property for several values of d simultaneously. Let $n, k, m, d_1, d_2, \dots, d_m$ be any positive integers such that $k \leq d_1, \dots, d_m < n$. We will show that by replacing s in Construction 2 with the value

$$s = \text{lcm}(d_1 + 1 - k, d_2 + 1 - k, \dots, d_m + 1 - k)$$

we obtain an $(n, k, l = s^n)$ MDS array code \mathcal{C} with the UER d_i -optimal repair property for all $i = 1, \dots, m$ simultaneously.

By Theorem IV.1, \mathcal{C} is an MDS array code. In the next theorem we establish results about the repair properties of the code \mathcal{C} .

Theorem V.1. *The code \mathcal{C} has the UER d_i -optimal repair property for any $i \in [m]$.*

Proof: Let $s_i = d_i + 1 - k$. Similarly to the proof of Theorem IV.4, we only prove the case of repairing C_1 . Since $s_i | s$, we can partition the set $\{0, 1, \dots, s - 1\}$ into s/s_i subsets $\mathcal{I}_1, \mathcal{I}_2, \dots, \mathcal{I}_{s/s_i}$, such that $|\mathcal{I}_j| = s_i$ for any $j \in [s/s_i]$, where $[s/s_i] = \{1, 2, \dots, s/s_i\}$. Following the proof of Theorem IV.4, we can show that for any $j \in [s/s_i], a \in \{0, 1, \dots, l - 1\}$, any nonnegative integer t such that $d_i + 2t < n$, and any $\mathcal{R} \subseteq \{2, 3, \dots, n\}$ of size $|\mathcal{R}| = d_i + 2t$, we can recover $\{c_{1,a(1,u)} : u \in \mathcal{I}_j\}$ by acquiring the set of values $\{\sum_{u \in \mathcal{I}_j} c_{v,a(1,u)} : v \in \mathcal{R}\}$ as long as the number of erroneous nodes in $\{C_i : i \in \mathcal{R}\}$ is not greater than t . Therefore, we can recover C_1 by accessing any $d_i + 2t$ surviving nodes and downloading the total of $(d_i + 2t)l/s_i$ symbols of F from these nodes as long as the number of erroneous nodes in the helper nodes is not greater than t . This completes the proof. \blacksquare

Corollary V.2. *The $(n, k, (n - k)^n)$ MDS array code given by Construction 1 has the UER d -optimal repair property if $(d + 1 - k) | (n - k)$.*

Example V.3. *A $(k + 4, k, 4^{k+4})$ MDS array code given by Construction 1 will automatically have the UER $(k + 1)$ -optimal repair property. A $(k + 6, k, 6^{k+6})$ MDS array code given by Construction 1 has both the UER $(k + 1)$ -optimal repair property and the UER $(k + 2)$ -optimal repair property.*

VI. EXPLICIT MDS ARRAY CODES WITH THE UER (h, d) -OPTIMAL REPAIR PROPERTY FOR ALL $h \leq r$ AND $k \leq d \leq n - h$ SIMULTANEOUSLY

Given integers n and r , we construct a family of $(n, k = n - r, l)$ MDS array codes with the UER (h, d) -optimal repair property for all $h \leq r$ and $k \leq d \leq n - h$ simultaneously.

Construction 3. *Let F be a finite field of size $|F| \geq sn$, where $s = \text{lcm}(1, 2, \dots, r)$. Let $\{\lambda_{i,j}\}_{i \in [n], j=0,1,\dots,s-1}$ be sn distinct elements in F . Let $l = s^n$. Consider the code family given by (3)-(4), where the matrices A_i are given by*

$$A_i = \sum_{a=0}^{l-1} \lambda_{i,a_i} e_a e_a^T, \quad i = 1, \dots, n. \quad (14)$$

Here $\{e_a : a = 0, 1, \dots, l - 1\}$ is the standard basis of F^l over F and a_i is defined in Construction 2.

Note that the difference between this construction and Construction 2 is in the choice of s . Define $a(i, u)$ and $c_{i,a}$ in the same way as in Sect. III.

Clearly, the code \mathcal{C} given by Construction 3 is an MDS array code.

Theorem VI.1. *The code \mathcal{C} given by Construction 3 has the UER (h, d) -optimal repair property for any $h \leq r$ and $k \leq d \leq n - h$.*

Proof: By Theorem V.1, \mathcal{C} has the UER d -optimal repair property for any $k \leq d \leq n - 1$. Now we show how to optimally repair h erasures. Without loss of generality, suppose that nodes $C_{\mathcal{F}} = \{C_1, C_2, \dots, C_h\}$ are erased and we access nodes $C_{\mathcal{R}} = \{C_{h+1}, C_{h+2}, \dots, C_{h+d+2t}\}$ to recover $C_{\mathcal{F}}$. Moreover, suppose that there are at most t erroneous nodes in $C_{\mathcal{R}}$.

To show the claim about the repair property of \mathcal{C} , we present a scheme that repairs the codes C_1, C_2, \dots, C_h one by one. More specifically, we first use $C_{\mathcal{R}}$ to repair C_1 , then use $C_{\mathcal{R}} \cup C_1$ to repair C_2 , then use $C_{\mathcal{R}} \cup C_1 \cup C_2$ to repair C_3, \dots , and finally use $C_{\mathcal{R}} \cup C_1 \cup C_2 \cup \dots \cup C_{h-1}$ to repair C_h . Let $s_i = i + d - k$.

When repairing C_i , we partition the set $\{0, 1, \dots, s - 1\}$ into s/s_i subsets $\mathcal{I}_1^{(i)}, \mathcal{I}_2^{(i)}, \dots, \mathcal{I}_{s/s_i}^{(i)}$, where $\mathcal{I}_j^{(i)} = \{(j - 1)s_i, (j - 1)s_i + 1, \dots, (j - 1)s_i + s_i - 1\}$ for $j \in [s/s_i]$. By the proof of Theorem IV.4, in order to recover

C_i it suffices to know the values $\{\sum_{u \in \mathcal{I}_j^{(i)}} c_{v,a(i,u)} : a_i = 0, j \in [s/s_i], v \in \mathcal{R} \cup [i-1]\}$. Since we have already recovered C_1, \dots, C_{i-1} , to recover C_i we only need to download the set of values

$$\left\{ \sum_{u \in \mathcal{I}_j^{(i)}} c_{v,a(i,u)} : a_i = 0, j \in [s/s_i], v \in \mathcal{R} \right\}$$

from $C_{\mathcal{R}}$. Thus, in order to recover $C_{\mathcal{F}}$, it suffices to know the values of elements in the set

$$\Lambda_h = \bigcup_{i=1}^h \left\{ \sum_{u \in \mathcal{I}_j^{(i)}} c_{v,a(i,u)} : a_i = 0, j \in [s/s_i], v \in \mathcal{R} \right\}.$$

In order to determine the values of these elements, we only need to download a spanning set for Λ_h over F from $C_{\mathcal{R}}$.

Define $\Omega_{i,v} = \{\sum_{u \in \mathcal{I}_j^{(i)}} c_{v,a(i,u)} : a_i = 0, j \in [s/s_i]\}$ for $i \in [h], v \in \mathcal{R}$ and $\Lambda_{1,v} = \Omega_{1,v}, \Lambda_{i,v} = \Lambda_{i-1,v} \cup \Omega_{i,v}$ for $i = 2, 3, \dots, h, v \in \mathcal{R}$. Given $a \in \{0, 1, \dots, l-1\}$ and $i \in [n]$, define the set $\Psi(a, i) = \{w : w \in [i-1], s_w | a_w\}$. For $i = 2, 3, \dots, h, q = 0, \dots, i-1$ define

$$\Gamma_{i,v,q} = \left\{ \sum_{u \in \mathcal{I}_j^{(i)}} c_{v,a(i,u)} : a_i = 0, |\Psi(a, i)| = q, j \in [s/s_i] \right\}.$$

Let $B_{1,v} = \Omega_{1,v}, B_{i,v} = B_{i-1,v} \cup \Gamma_{i,v,0}, i = 2, 3, \dots, h$. We use induction on i to show that $\Lambda_{i,v} \subseteq \text{span}(B_{i,v})$ for every $i \in [h]$ and $v \in \mathcal{R}$. Clearly this claim holds for $i = 1$. Now suppose that it holds for $i = m$ and consider the case $i = m+1$. By the induction hypothesis, $\Lambda_{m,v} \subseteq \text{span}(B_{m,v})$, so it suffices to prove that

$$\Lambda_{m,v} \cup \Omega_{m+1,v} \subseteq \text{span}(\Lambda_{m,v} \cup \Gamma_{m+1,v,0}).$$

Note that $\Omega_{m+1,v} = \bigcup_{q=0}^m \Gamma_{m+1,v,q}$. Thus we only need to prove that $\Gamma_{m+1,v,q} \subseteq \text{span}(\Lambda_{m,v} \cup \Gamma_{m+1,v,0})$ for all $q = 0, 1, \dots, m$. We prove this claim by induction on q . This claim trivially holds for $q = 0$. Now suppose that it holds for some $q \geq 1$ and consider the case $q+1$. Given any a satisfying that $a_{m+1} = 0$ and $|\Psi(a, m+1)| = q+1$, suppose that $w \in \Psi(a, m+1)$, namely, $s_w | a_w$, then $|\Psi(a(w, a_w + u), m+1)| = q$ for all $u \in [s_w - 1]$. By the induction hypothesis,

$$\sum_{u_2 \in \mathcal{I}_j^{(m+1)}} c_{v,a(w, m+1, a_w + u_1, u_2)} \in \text{span}(\Lambda_{m,v} \cup \Gamma_{m+1,v,0})$$

for all $u_1 \in [s_w - 1]$ and $j \in [s/s_{m+1}]$, where $a(i_1, i_2, u_1, u_2)$ is obtained from a by replacing a_{i_1} with u_1 and a_{i_2} with u_2 . Therefore,

$$\sum_{u_1=1}^{s_w-1} \sum_{u_2 \in \mathcal{I}_j^{(m+1)}} c_{v,a(w, m+1, a_w + u_1, u_2)} \in \text{span}(\Lambda_{m,v} \cup \Gamma_{m+1,v,0}). \quad (15)$$

Note that

$$\sum_{u_1=0}^{s_w-1} c_{v,a(w, m+1, a_w + u_1, u_2)} \in \Omega_{w,v} \subseteq \Lambda_{m,v}$$

for any $u_2 \in \{0, 1, \dots, s-1\}$. As a result,

$$\sum_{u_1=0}^{s_w-1} \sum_{u_2 \in \mathcal{I}_j^{(m+1)}} c_{v,a(w, m+1, a_w + u_1, u_2)} \in \text{span}(\Lambda_{m,v}). \quad (16)$$

Subtracting (15) from (16), we obtain

$$\sum_{u \in \mathcal{I}_j^{(m+1)}} c_{v,a(m+1,u)} \in \text{span}(\Lambda_{m,v} \cup \Gamma_{m+1,v,0})$$

for any $j \in [s/s_{m+1}]$. This establishes the induction step of the second induction and proves that $\Omega_{m+1,v} \subseteq \text{span}(\Lambda_{m,v} \cup \Gamma_{m+1,v,0})$. Therefore, $\Lambda_{m+1,v} \subseteq \text{span}(B_{m+1,v})$ for any $v \in \mathcal{R}$, and this completes the proof of the first induction.

Since $\Lambda_h = \bigcup_{v \in \mathcal{R}} \Lambda_{h,v}$ and $\Lambda_{h,v} \subseteq \text{span}(B_{h,v})$ for every $v \in \mathcal{R}$, to recover $C_{\mathcal{F}}$ we only need to download $\bigcup_{v \in \mathcal{R}} B_{h,v}$ from $C_{\mathcal{R}}$.

Finally, we find the size of the set $B_{h,v}$ for some fixed $v \in \mathcal{R}$. Since $B_{i,v} = B_{i-1,v} \cup \Gamma_{i,v,0}$, we have $|B_{i,v}| \leq |B_{i-1,v}| + |\Gamma_{i,v,0}|$. We will prove that $|B_{i,v}| \leq \frac{il}{s_i}$ by induction on i . By definition $|B_{1,v}| = |\Omega_{1,v}| = \frac{l}{s_1}$. Suppose that the claim holds for $i = m$ and consider the case $i = m + 1$. It is easy to see that

$$\begin{aligned} |\Gamma_{m+1,v,0}| &= \frac{s_1 - 1}{s_1} \frac{s_2 - 1}{s_2} \cdots \frac{s_m - 1}{s_m} \frac{l}{s_{m+1}} \\ &= \frac{d - k}{d + 1 - k} \frac{d + 1 - k}{d + 2 - k} \cdots \frac{d + m - 1 - k}{d + m - k} \frac{l}{d + m + 1 - k} \\ &= \frac{d - k}{d + m - k} \frac{l}{d + m + 1 - k}. \end{aligned}$$

By the induction hypothesis,

$$\begin{aligned} |B_{m+1,v}| &\leq |B_{m,v}| + |\Gamma_{m+1,v,0}| \\ &\leq \frac{ml}{d + m - k} + \frac{d - k}{d + m - k} \frac{l}{d + m + 1 - k} \\ &= \frac{(m + 1)l}{d + m + 1 - k} = \frac{(m + 1)l}{s_{m+1}}. \end{aligned}$$

This establishes the induction step and proves that $|B_{h,v}| \leq \frac{hl}{d+h-k}$ for any $v \in \mathcal{R}$. We obtain

$$\left| \bigcup_{v \in \mathcal{R}} B_{h,v} \right| \leq \frac{hl|\mathcal{R}|}{d + h - k} = \frac{h(d + 2t)l}{d + h - k}.$$

The proof is complete. \blacksquare

Since we set A_1, A_2, \dots, A_n to be diagonal matrices in Construction 3, the encoding and repair processes involve only operations with $r \times r$ matrices over F , and the code \mathcal{C} given by Construction 3 also has the optimal update property. Moreover, by the proof of Theorem IV.4 and Theorem VI.1, we can see that the repair process only requires operations with matrices of size no larger than $n \times n$.

VII. OPTIMAL-REPAIR MDS ARRAY CODES WITH OPTIMAL ACCESS PROPERTY OVER SMALL FIELDS

In this section we construct an explicit family of MDS array codes with optimal access property. As above, we rely on the general construction (3)-(4) to construct an $(n, k = n - r, l = r^{n-1})$ array code. However in this section we take A_n to be the identity matrix and take A_1, \dots, A_{n-1} to be permutation matrices rather than diagonal matrices. This choice is beneficial in two ways: first, we are able to reduce the field size from rn in earlier construction to any field F of size $|F| \geq n + 1$, while also obtaining the optimal access property.

Construction 4. Let F be a finite field of size $|F| \geq n + 1$ and let γ be its primitive element. Let $l = r^{n-1}$. Consider the code family given by (3)-(4), where the matrices A_1, A_2, \dots, A_n are given by

$$\begin{aligned} A_i &= \sum_{a=0}^{l-1} \lambda_{i,a_i} e_a e_a^T, \quad i = 1, 2, \dots, n - 1, \\ A_n &= I, \end{aligned}$$

where \oplus denotes addition modulo r , $\lambda_{i,0} = \gamma^i$ for all $i \in [n - 1]$ and $\lambda_{i,u} = 1$ for all $i \in [n - 1]$ and all $u \in \{1, 2, \dots, r - 1\}$. Here $\{e_a : a = 0, 1, \dots, l - 1\}$ is the standard basis of F^l over F , a_i is the i -th digit from the right in the representation of $a = (a_{n-1}, a_{n-2}, \dots, a_1)$ in the r -ary form, and $a(i, u)$ is defined in the same way as in Sect. III.

Remark VII.1. Since $\prod_{u=0}^{r-1} \lambda_{i,u} = \gamma^i$, we have

$$\begin{aligned} \prod_{u=0}^{r-1} \lambda_{i,u} &\neq \prod_{u=0}^{r-1} \lambda_{j,u} \text{ for any } i, j \in [n - 1], i \neq j. \\ \prod_{u=0}^{r-1} \lambda_{i,u} &\neq 1 \text{ for any } i \in [n - 1]. \end{aligned} \tag{17}$$

It will be clear from the proofs below that the values of $\{\lambda_{i,u} : i \in [n], u = 0, 1, \dots, r - 1\}$ in Construction 4 can be assigned arbitrarily as long as (17) is satisfied.

Clearly, for $t = 0, 1, \dots, r-1$ and $i \in [n-1]$, we have

$$A_i^t = \sum_{a=0}^{l-1} \beta_{i,a_i,t} e_a e_{a(i,a_i \oplus t)}^T,$$

where $\beta_{i,u,0} = 1$ and $\beta_{i,u,t} = \prod_{v=u}^{u \oplus (t-1)} \lambda_{i,v}$ for $t = 1, \dots, r-1$ and $u = 0, 1, \dots, r-1$.

Theorem VII.2. *The code \mathcal{C} given by Construction 4 has the optimal access property.*

Proof: Let us write out the parity-check equations (3) coordinatewise:

$$c_{n,a} + \sum_{i=1}^{n-1} \beta_{i,a_i,t} c_{i,a(i,a_i \oplus t)} = 0 \text{ for all } t = 0, 1, \dots, r-1 \text{ and } a = 0, \dots, l-1, \quad (18)$$

where $c_{i,a}$ is defined in Sect. III. First suppose we want to repair C_i for some $i \in [n-1]$. We will show that we only need to access the values in the set $\{c_{j,a} : a_i = 0\}$ from C_j for every $j \neq i$. Indeed, by (18), we have

$$\beta_{i,a_i,t} c_{i,a(i,a_i \oplus t)} = -c_{n,a} - \sum_{j \neq i,n} \beta_{j,a_j,t} c_{j,a(j,a_j \oplus t)}. \quad (19)$$

From (19) we see that the values $\{c_{i,a} : a_i = t\}$ can be determined by $\{c_{j,a} : j \neq i, a_i = 0\}$. Since (19) holds for every $t = 0, 1, \dots, r-1$, we see that for $i \in [n-1]$, C_i can be determined by the values $\{c_{j,a} : j \neq i, a_i = 0\}$.

Now consider the case when the failed node is C_n . By (18), we know that the values in the set $\{c_{n,a} : a_1 \oplus a_2 \oplus \dots \oplus a_{n-1} = r \ominus t\}$ can be determined by $\{c_{j,a} : j \neq n, a_1 \oplus a_2 \oplus \dots \oplus a_{n-1} = 0\}$, where \ominus denotes subtraction modulo r . Since (18) holds for every $t = 0, 1, \dots, r-1$, we conclude that C_n can be determined by $\{c_{j,a} : j \neq n, a_1 \oplus a_2 \oplus \dots \oplus a_{n-1} = 0\}$. This completes the proof. ■

Our next task is to establish the MDS property of \mathcal{C} . The code \mathcal{C} is MDS if and only if every $r \times r$ block submatrix of

$$\begin{bmatrix} I & I & \dots & I \\ A_1 & A_2 & \dots & A_n \\ \vdots & \vdots & \vdots & \vdots \\ A_1^{r-1} & A_2^{r-1} & \dots & A_n^{r-1} \end{bmatrix}$$

is invertible. A criterion for this is given in the following lemma.

Lemma VII.3 (Block Vandermonde matrix). *Let B_1, \dots, B_r be $l \times l$ matrices such that $B_i B_j = B_j B_i$ for all $i, j \in [r]$. The matrix*

$$M_r = \begin{bmatrix} I & I & \dots & I \\ B_1 & B_2 & \dots & B_r \\ \vdots & \vdots & \vdots & \vdots \\ B_1^{r-1} & B_2^{r-1} & \dots & B_r^{r-1} \end{bmatrix}$$

is invertible if and only if $B_i - B_j$ is invertible for all $i \neq j$.

Proof: Suppose that $B_i - B_j$ is invertible for any $i, j \in [r], i \neq j$. Clearly the claim holds for $r = 2$. Now suppose that it holds for $r = s$. Consider the matrix

$$M_{s+1} = \begin{bmatrix} I & I & \dots & I \\ B_1 & B_2 & \dots & B_{s+1} \\ \vdots & \vdots & \vdots & \vdots \\ B_1^s & B_2^s & \dots & B_{s+1}^s \end{bmatrix}.$$

For $i = s, s-1, \dots, 1$, multiply the i -th ‘‘row’’ on the left by B_1 and subtract from the $(i+1)$ -th row. Note that these operations do not change the rank of M_{s+1} since they leave its row space unchanged. Next, subtract the first column from all the other columns (this clears the first row without changing the column space and hence the rank of M_{s+1}) to obtain

$$M'_{s+1} = \begin{bmatrix} I & 0 & \dots & 0 \\ 0 & B_2 - B_1 & \dots & B_{s+1} - B_1 \\ \vdots & \vdots & \vdots & \vdots \\ 0 & (B_2 - B_1)B_2^{s-1} & \dots & (B_{s+1} - B_1)B_{s+1}^{s-1} \end{bmatrix}$$

$$= \begin{bmatrix} I & 0 & \cdots & 0 \\ 0 & B_2 - B_1 & \cdots & B_{s+1} - B_1 \\ \vdots & \vdots & \vdots & \vdots \\ 0 & B_2^{s-1}(B_2 - B_1) & \cdots & B_{s+1}^{s-1}(B_{s+1} - B_1) \end{bmatrix}$$

(here we relied on the commuting condition $B_i B_j = B_j B_i$). Since the matrices $B_i - B_1, i = 2, \dots, s+1$ are invertible, we can multiply the i -th column on the right by $(B_i - B_1)^{-1}$ without changing the rank. We conclude that the matrix

$$M''_{s+1} = \begin{bmatrix} I & 0 & \cdots & 0 \\ 0 & I & \cdots & I \\ \vdots & \vdots & \vdots & \vdots \\ 0 & B_2^{s-1} & \cdots & B_{s+1}^{s-1} \end{bmatrix}$$

has the same rank as M_{s+1} . By the induction hypothesis M''_{s+1} is invertible, and so is M_{s+1} . This completes the induction step.

Conversely, suppose that M_r is invertible. For $r = 2$ this implies that the matrix $B_1 - B_2$ is invertible. Now assume that the claim holds for $r = s$ and consider the case $r = s+1$. Since M_{s+1} is invertible, M'_{s+1} is also invertible. Assume that $B_i - B_1$ is singular for some $i \in \{2, 3, \dots, s+1\}$, then

$$\begin{bmatrix} 0 \\ B_i - B_1 \\ \vdots \\ B_i^{s-1}(B_i - B_1) \end{bmatrix} = \begin{bmatrix} 0 \\ I \\ \vdots \\ B_i^{s-1} \end{bmatrix} (B_i - B_1)$$

contains linearly dependent columns, and thus M'_{s+1} is singular, contradiction. Thus $B_i - B_1$ is invertible for any $i \neq 1$. Consequently M''_{s+1} is invertible. By the induction assumption we conclude that $B_i - B_j$ is invertible for any $i, j \in [s+1], i \neq j$. ■

Theorem VII.4. *The code \mathcal{C} given by Construction 4 is an MDS array code.*

Proof: On account of Lemma VII.3, the claim will follow if we prove that for any $i \neq j, A_i A_j = A_j A_i$ and that the matrices $A_i - A_j$ are invertible. The matrix $A_n = I$, so we need to verify that for any $i, j \in [n-1], i \neq j$,

$$A_i A_j = A_j A_i = \sum_{a=0}^{l-1} \lambda_{i,a_i} \lambda_{j,a_j} e_a e_a^T_{a(i,j,a_i \oplus 1, a_j \oplus 1)},$$

where $a(i, j, u, v)$ is obtained from a by replacing a_i with u and a_j with v . This establishes the commuting part.

Now suppose that $A_i x = A_j x$ for some $i, j \in [n-1], i \neq j$ and some vector $x \in F^l$. Let $x = \sum_{a=0}^{l-1} x_a e_a$, where $x_a \in F$. Then

$$\begin{aligned} A_i x &= \sum_{a=0}^{l-1} \lambda_{i,a_i} x_{a(i,a_i \oplus 1)} e_a, \\ A_j x &= \sum_{a=0}^{l-1} \lambda_{j,a_j} x_{a(j,a_j \oplus 1)} e_a. \end{aligned}$$

Therefore,

$$\lambda_{i,a_i} x_{a(i,a_i \oplus 1)} = \lambda_{j,a_j} x_{a(j,a_j \oplus 1)} \quad (20)$$

for every $a = 0, 1, \dots, l-1$. Since $\lambda_{i,u} \neq 0$ for all $i \in [n-1]$ and all $u = 0, 1, \dots, r-1$, we can write (20) as

$$x_a = \frac{\lambda_{j,a_j}}{\lambda_{i,a_i \oplus 1}} x_{a(i,j,a_i \oplus 1, a_j \oplus 1)}. \quad (21)$$

Repeating this step, we obtain

$$\begin{aligned} x_a &= \frac{\lambda_{j,a_j}}{\lambda_{i,a_i \oplus 1}} x_{a(i,j,a_i \oplus 1, a_j \oplus 1)} \\ &= \frac{\lambda_{j,a_j}}{\lambda_{i,a_i \oplus 1}} \frac{\lambda_{j,a_j \oplus 1}}{\lambda_{i,a_i \oplus 2}} x_{a(i,j,a_i \oplus 2, a_j \oplus 2)} \end{aligned}$$

$$\begin{aligned}
&= \dots = \frac{\lambda_{j,a_j}}{\lambda_{i,a_i \ominus 1}} \frac{\lambda_{j,a_j \oplus 1}}{\lambda_{i,a_i \ominus 2}} \dots \frac{\lambda_{j,a_j \oplus (r-1)}}{\lambda_{i,a_i \ominus r}} x_{a(i,j,a_i \ominus r, a_j \oplus r)} \\
&= \frac{\prod_{u=0}^{r-1} \lambda_{j,u}}{\prod_{u=0}^{r-1} \lambda_{i,u}} x_a
\end{aligned}$$

for every $a = 0, 1, \dots, l-1$. By (17), $x_a = 0$ for all $a = 0, \dots, l-1$. Thus $(A_i - A_j)x = 0$ implies that $x = 0$. We conclude that the matrices $A_i - A_j$ are invertible for all $i, j \in [n-1], i \neq j$.

Now suppose that $A_i x = A_n x = x$ for some $i \in [n-1]$ and some vector $x \in F^l$. Then we have

$$\lambda_{i,a_i} x_{a(i,a_i \oplus 1)} = x_a. \quad (22)$$

Thus

$$\begin{aligned}
x_a &= \lambda_{i,a_i} x_{a(i,a_i \oplus 1)} = \lambda_{i,a_i} \lambda_{i,a_i \oplus 1} x_{a(i,a_i \oplus 2)} \\
&= \dots = \lambda_{i,a_i} \lambda_{i,a_i \oplus 1} \dots \lambda_{i,a_i \oplus (r-1)} x_{a(i,a_i \oplus r)} \\
&= \left(\prod_{u=0}^{r-1} \lambda_{i,u} \right) x_a.
\end{aligned}$$

By (17), $x_a = 0$ for all $a = 0, \dots, l-1$. So $x = 0$ and $\ker(A_i - A_n) = 0$, or, in other words the matrix $A_i - A_n$ is invertible for all $i \in [n-1]$. This completes the proof. \blacksquare

A. Complexity of encoding and decoding

The encoding and decoding procedures solve the same problem, namely, determining the values of r nodes from the known values of k nodes. Without loss of generality, suppose that we want to determine C_{k+1}, \dots, C_{k+r} from C_1, C_2, \dots, C_k . Note that (18) contains rl equations and we have rl unknown elements here. Since the code is MDS, the unknown values are uniquely determined.

Now let us show that instead of inverting an $rl \times rl$ matrix, we only need to invert matrices of size $r^{r+1} \times r^{r+1}$. Observe that, given any $b_1, b_2, \dots, b_k \in \{0, 1, \dots, r-1\}$, the r^{r+1} unknown elements $\{c_{i,a} : i = k+1, k+2, \dots, k+r, a_1 = b_1, a_2 = b_2, \dots, a_k = b_k\}$ appear in exactly r^{r+1} equations in (18), and these r^{r+1} equations only contain these r^{r+1} unknown elements. For this reason, we can find these r^{r+1} unknown elements by inverting an $r^{r+1} \times r^{r+1}$ matrix.

VIII. EXPLICIT MDS ARRAY CODES WITH THE UER d -OPTIMAL ACCESS PROPERTY

Construction 5. Let F be a finite field of size $|F| \geq n+1$ and let γ be a primitive element in F . Let $s = d+k-1$ and $l = s^n$. Consider the code given by (3)-(4), where the matrices A_1, A_2, \dots, A_n are given by

$$A_i = \sum_{a=0}^{l-1} \lambda_{i,a_i} e_a e_{a(i,a_i \oplus 1)}^T, \quad i = 1, \dots, n,$$

where \oplus denotes addition modulo s , $\lambda_{i,0} = \gamma^i$ for all $i \in [n]$ and $\lambda_{i,u} = 1$ for all $i \in [n]$ and all $u \in [s-1]$. Here $\{e_a : a = 0, 1, \dots, l-1\}$ is the standard basis of F^l over F , a_i is the i -th digit from the right in the representation of $a = (a_n, a_{n-1}, \dots, a_1)$ in the s -ary form, and $a(i, u)$ is defined in the same way as in Sect. III.

Theorem VIII.1. The code \mathcal{C} given by Construction 5 is an MDS array code.

Proof: Paralleling the proof of Theorem VII.4, we can show that for any $i \neq j$, $A_i A_j = A_j A_i$ and that the matrix $A_i - A_j$ is invertible. Thus \mathcal{C} is an MDS array code. \blacksquare

Theorem VIII.2. The code \mathcal{C} given by Construction 5 has the UER d -optimal access property.

Proof: Suppose we want to repair C_i . By an argument similar to the proof of Theorem VII.2, we only need to know the values $\{c_{j,a} : a_i = 0\}$ from C_j for every $j \neq i$. Define a function $g : \{0, 1, \dots, l/s-1\} \rightarrow \{0, 1, \dots, l-1\}$ as $g(a) = (a_{n-1}, a_{n-2}, \dots, a_i, 0, a_{i-1}, a_{i-2}, \dots, a_1)$, where a is an element in $\{0, 1, \dots, l/s-1\}$ with the s -ary expansion $(0, a_{n-1}, a_{n-2}, \dots, a_1)$. Define the column vector $C_j^{(i)} \in F^{l/s}$ as $C_j^{(i)} = (c_{j,g(0)}, c_{j,g(1)}, \dots, c_{j,g(l/s-1)})^T$ for all $j \neq i$. In order to prove the theorem, we only need to prove that $(C_1^{(i)}, C_2^{(i)}, \dots, C_{i-1}^{(i)}, C_{i+1}^{(i)}, C_{i+2}^{(i)}, \dots, C_n^{(i)})$ forms an $(n-1, d, s^{n-1})$ MDS array code.

Notice that $A_j^s = \sum_{a=0}^{l-1} (\prod_{u=0}^{s-1} \lambda_{j,u}) e_a e_{a(j, a_j \oplus s)}^T = \gamma^j I$ for all $j \in [n]$. Note also that

$$\sum_{j=1}^n A_j^m C_j = 0, \quad \sum_{j=1}^n A_j^{m+s} C_j = 0$$

for all $m = 0, 1, \dots, r-s-1$. Multiplying the first equation by γ^i and then subtracting it from the second one, we obtain

$$\sum_{j \neq i} (\gamma^j - \gamma^i) A_j^m C_j = 0, \quad m = 0, 1, \dots, r-s-1. \quad (23)$$

Let $e_0^{(l/s)}, e_1^{(l/s)}, \dots, e_{l/s-1}^{(l/s)}$ be the standard basis vectors of $F^{l/s}$ over F . Define $l/s \times l/s$ matrix

$$B_j = \sum_{a=0}^{l/s-1} \lambda_{j, a_j} e_a^{(l/s)} (e_{a(j, a_j \oplus 1)}^{(l/s)})^T \text{ for } j \in [i-1],$$

$$B_j = \sum_{a=0}^{l/s-1} \lambda_{j+1, a_j} e_a^{(l/s)} (e_{a(j, a_j \oplus 1)}^{(l/s)})^T \text{ for } i \leq j < n,$$

It is easy to see that (23) implies

$$\sum_{j=1}^{i-1} (\gamma^j - \gamma^i) B_j^m C_j^{(i)} + \sum_{j=i}^{n-1} (\gamma^{j+1} - \gamma^i) B_j^m C_{j+1}^{(i)} = 0$$

for all $m = 0, 1, \dots, r-s-1$.

As in the proof of Theorem VII.4, we can show that for any $j_1, j_2 \in [n-1], j_1 \neq j_2$, $B_{j_1} B_{j_2} = B_{j_2} B_{j_1}$ and that the matrix $B_{j_1} - B_{j_2}$ is invertible. Moreover, $r-s = n-1-d$. Thus

$$\begin{bmatrix} I & I & \dots & I \\ B_1 & B_2 & \dots & B_{n-1} \\ \vdots & \vdots & \vdots & \vdots \\ B_1^{r-s-1} & B_2^{r-s-1} & \dots & B_{n-1}^{r-s-1} \end{bmatrix}$$

is a parity-check matrix of an $(n-1, d, s^{n-1})$ MDS array code. Multiplying each block column with a nonzero constant does not change the MDS property. As a result, the set of vectors $(C_1^{(i)}, C_2^{(i)}, \dots, C_{i-1}^{(i)}, C_{i+1}^{(i)}, C_{i+2}^{(i)}, \dots, C_n^{(i)})$ forms an $(n-1, d, s^{n-1})$ MDS array code. Therefore, if we access any $d+2t$ out of $n-1$ vectors in the set $(C_1^{(i)}, C_2^{(i)}, \dots, C_{i-1}^{(i)}, C_{i+1}^{(i)}, C_{i+2}^{(i)}, \dots, C_n^{(i)})$, we will be able to recover the whole set and further recover C_i as long as the number of erroneous nodes among the helper nodes is not greater than t . This completes the proof. ■

IX. AN MDS ARRAY CODE FAMILY WITH THE UER d -OPTIMAL ACCESS PROPERTY FOR SEVERAL VALUES OF d SIMULTANEOUSLY

In this section we present a simple extension of the code family in Construction 5 which gives MDS array codes with the UER d -optimal access property for several values of d simultaneously. More specifically, given any positive integers $n, k, m, d_1, d_2, \dots, d_m$ such that $k \leq d_1, \dots, d_m < n$, we will show that by replacing s in Construction 5 with the value

$$s = \text{lcm}(d_1 + 1 - k, d_2 + 1 - k, \dots, d_m + 1 - k)$$

we obtain an $(n, k, l = s^n)$ MDS array code \mathcal{C} with the UER d_i -optimal access property for all $i = 1, \dots, m$ simultaneously.

On account of Theorem VII.4, we already know that \mathcal{C} is an MDS array code. It remains to show that it has the UER d_i -optimal access property for any $i \in [m]$.

Theorem IX.1. *The code \mathcal{C} has the UER d_i -optimal access property for any $i \in [m]$.*

Proof: Given any $i \in [m]$, we show that \mathcal{C} has the UER d_i -optimal access property. Let $s_i = d_i + 1 - k$.

Without loss of generality, we only consider the case of repairing C_n . By an argument similar to the proof of Theorem VII.2, we only need to know the values $\{c_{j,a} : a_n = 0, s_i, 2s_i, \dots, (s/s_i - 1)s_i\}$ from C_j for every $j \in [n-1]$. Define a function

$$g : \{0, 1, \dots, l/s_i - 1\} \rightarrow \{0, 1, \dots, l-1\}$$

$$a \quad \mapsto (s_i a_n, a_{n-1}, a_{n-2}, \dots, a_1),$$

where a is an element in $\{0, 1, \dots, l/s_i - 1\}$ with s -ary expansion $(a_n, a_{n-1}, a_{n-2}, \dots, a_1)$. Define the column vector $C_j^{(n)} \in F^{l/s_i}$ as $C_j^{(n)} = (c_{j,g(0)}, c_{j,g(1)}, \dots, c_{j,g(l/s_i-1)})^T$ for all $j \in [n-1]$. As mentioned above, $\{C_j^{(n)} : j \in [n-1]\}$ contains the information we need to recover C_n . Let us prove that $(C_1^{(n)}, C_2^{(n)}, \dots, C_{n-1}^{(n)})$ forms an $(n-1, d, l/s_i)$ MDS array code.

Observe that

$$\sum_{j=1}^n A_j^m C_j = 0, \quad \sum_{j=1}^n A_j^{m+s_i} C_j = 0$$

for all $m = 0, 1, \dots, r - s_i - 1$. Multiplying the first equation on the left by $A_n^{s_i}$ and then subtracting it from the second one, we obtain

$$\sum_{j=1}^{n-1} (A_j^{s_i} - A_n^{s_i}) A_j^m C_j = 0, \quad m = 0, 1, \dots, r - s_i - 1. \quad (24)$$

Let $e_0^{(l/s_i)}, e_1^{(l/s_i)}, \dots, e_{l/s_i-1}^{(l/s_i)}$ be the standard basis vectors of F^{l/s_i} over F . Define $l/s_i \times l/s_i$ matrices

$$B_j = \sum_{a=0}^{l/s_i-1} \lambda_{j,a_j} e_a^{(l/s_i)} (e_{a(j,a_j \oplus 1)}^{(l/s_i)})^T \text{ for } j \in [n-1],$$

$$B_n = \sum_{a=0}^{l/s_i-1} \left(\prod_{q=s_i a_n}^{s_i a_n + s_i - 1} \lambda_{n,q} \right) e_a^{(l/s_i)} (e_{a(n, (s_i a_n \oplus s_i)/s_i)}^{(l/s_i)})^T.$$

It is easy to see that (24) implies the equality

$$\sum_{j=1}^{n-1} (B_j^{s_i} - B_n) B_j^m C_j^{(n)} = 0, \quad m = 0, 1, \dots, r - s_i - 1.$$

Now suppose that $B_j^{s_i} x = B_n x$ for some $j \in [n-1]$ and some vector $x \in F^{l/s_i}$. Let $x = \sum_{a=0}^{l/s_i-1} x_a e_a^{(l/s_i)}$, where $x_a \in F$. Then

$$B_j^{s_i} x = \sum_{a=0}^{l/s_i-1} \left(\prod_{q=a_j}^{a_j \oplus (s_i-1)} \lambda_{j,q} \right) x_{a(j, a_j \oplus s_i)} e_a^{(l/s_i)},$$

$$B_n x = \sum_{a=0}^{l/s_i-1} \left(\prod_{q=s_i a_n}^{s_i a_n + s_i - 1} \lambda_{n,q} \right) x_{a(n, (s_i a_n \oplus s_i)/s_i)} e_a^{(l/s_i)}.$$

Therefore,

$$\left(\prod_{q=a_j}^{a_j \oplus (s_i-1)} \lambda_{j,q} \right) x_{a(j, a_j \oplus s_i)} = \left(\prod_{q=s_i a_n}^{s_i a_n + s_i - 1} \lambda_{n,q} \right) x_{a(n, (s_i a_n \oplus s_i)/s_i)} \quad (25)$$

for every $a = 0, 1, \dots, l/s_i - 1$. Let us rewrite (25) as

$$x_a = \frac{\prod_{q=s_i a_n}^{s_i a_n + s_i - 1} \lambda_{n,q}}{\prod_{q=a_j \oplus s_i}^{a_j \oplus 1} \lambda_{j,q}} x_{a(j, n, a_j \oplus s_i, (s_i a_n \oplus s_i)/s_i)}.$$

Repeating this step, we obtain

$$\begin{aligned} x_a &= \frac{\prod_{q=s_i a_n}^{s_i a_n \oplus (s-1)} \lambda_{n,q}}{\prod_{q=a_j \oplus s}^{a_j \oplus 1} \lambda_{j,q}} x_{a(j, n, a_j \oplus s, (s_i a_n \oplus s)/s_i)} \\ &= \frac{\prod_{u=0}^{s-1} \lambda_{n,u}}{\prod_{u=0}^{s-1} \lambda_{j,u}} x_a \\ &= \frac{\gamma^n}{\gamma^j} x_a \end{aligned}$$

for every $a = 0, 1, \dots, l-1$. Since $\gamma^j \neq \gamma^n$ for any $j \in [n-1]$, we have $x_a = 0$ for all $a = 0, \dots, l-1$. Thus $(B_j^{s_i} - B_n)x = 0$ implies that $x = 0$. We conclude that the matrix $B_j^{s_i} - B_n$ is invertible for all $j \in [n-1]$.

Following the proof of Theorem VII.4, we can show that

$$\begin{bmatrix} I & I & \dots & I \\ B_1 & B_2 & \dots & B_{n-1} \\ \vdots & \vdots & \vdots & \vdots \\ B_1^{r-s_i-1} & B_2^{r-s_i-1} & \dots & B_{n-1}^{r-s_i-1} \end{bmatrix}$$

is the parity-check matrix of an $(n-1, d_i, l/s_i)$ MDS array code. Multiplying each block column with an invertible matrix does not change the MDS property. As a result, $(C_1^{(n)}, C_2^{(n)}, \dots, C_{n-1}^{(n)})$ forms an $(n-1, d_i, l/s_i)$ MDS array code. Therefore, if we access any $d_i + 2t$ out of $n-1$ vectors in the set $(C_1^{(n)}, C_2^{(n)}, \dots, C_{n-1}^{(n)})$, we will be able to recover the whole set and further recover C_n as long as the number of erroneous nodes among the helper nodes is not greater than t . This completes the proof. \blacksquare

X. EXPLICIT MDS ARRAY CODES WITH THE UER (h, d) -OPTIMAL ACCESS PROPERTY FOR ALL $h \leq r$ AND $k \leq d \leq n-h$ SIMULTANEOUSLY

Given integers n and r , we construct a family of $(n, k = n-r, l)$ MDS array codes with the UER (h, d) -optimal access property for all $h \leq r$ and $k \leq d \leq n-h$ simultaneously.

Construction 6. Let F be a finite field of size $|F| \geq n+1$ and let γ be its primitive element. Let $s = \text{lcm}(1, 2, \dots, r)$ and $l = s^n$. Consider the code family given by (3)-(4), where the matrices A_i are given by

$$A_i = \sum_{a=0}^{l-1} \lambda_{i,a_i} e_a e_{a(i,a_i \oplus 1)}^T, \quad i = 1, \dots, n,$$

where \oplus denotes addition modulo s , $\lambda_{i,0} = \gamma^i$ for all $i \in [n]$ and $\lambda_{i,u} = 1$ for all $i \in [n]$ and all $u \in [s-1]$. Here $\{e_a : a = 0, 1, \dots, l-1\}$ is the standard basis of F^l over F , a_i is the i -th digit from the right in the representation of $a = (a_n, a_{n-1}, \dots, a_1)$ in the s -ary form, and $a(i, u)$ is defined in the same way as in Sect. III.

Note that the difference between this construction and Construction 5 is in the choice of s .

Clearly, the code \mathcal{C} given by Construction 6 is an MDS array code.

Theorem X.1. The code \mathcal{C} given by Construction 6 has the UER (h, d) -optimal access property for all $h \leq r$ and $k \leq d \leq n-h$ simultaneously.

Proof: By Theorem IX.1, \mathcal{C} has the UER d -optimal access property for any $k \leq d \leq n-1$. Now we show how to optimally repair h erasures. Without loss of generality, suppose that nodes $C_{\mathcal{F}} = \{C_1, C_2, \dots, C_h\}$ are erased and we access nodes $C_{\mathcal{R}} = \{C_{h+1}, C_{h+2}, \dots, C_{h+d+2t}\}$ to recover $C_{\mathcal{F}}$. Moreover, suppose that there are at most t erroneous nodes in $C_{\mathcal{R}}$.

As before, we repair C_1, C_2, \dots, C_h one by one. More specifically, we first use $C_{\mathcal{R}}$ to repair C_1 , then $C_{\mathcal{R}} \cup C_1$ to repair C_2 , then $C_{\mathcal{R}} \cup C_1 \cup C_2$ to repair C_3, \dots , and finally we use $C_{\mathcal{R}} \cup C_1 \cup C_2 \cup \dots \cup C_{h-1}$ to repair C_h . Let $s_i = i + d - k$. When repairing C_i , according to the proof of Theorem IX.1, we only need to know the values $\{c_{v,a} : a_i = 0, s_i, 2s_i, \dots, (s/s_i - 1)s_i, v \in \mathcal{R} \cup [i-1]\}$. Since we have already recovered C_1, \dots, C_{i-1} , we need to access only the values $\{c_{v,a} : a_i = 0, s_i, 2s_i, \dots, (s/s_i - 1)s_i, v \in \mathcal{R}\}$ from $C_{\mathcal{R}}$ to recover C_i . Thus in order to recover $C_{\mathcal{F}}$, we need to access the set of elements $\Lambda_h = \bigcup_{i=1}^h \{c_{v,a} : a_i = 0, s_i, 2s_i, \dots, (s/s_i - 1)s_i, v \in \mathcal{R}\}$.

Consider the set

$$\Omega_{j,v} = \{c_{v,a} : a_j = 0, s_j, 2s_j, \dots, (s/s_j - 1)s_j\}$$

for $j \in [h]$ and $v \in \mathcal{R}$. Let $\Lambda_{1,v} = \Omega_{1,v}, \Lambda_{j+1,v} = \Lambda_{j,v} \cup \Omega_{j+1,v}, j = 1, \dots, h-1$. We prove by induction on j that $|\Lambda_{j,v}| = \frac{jl}{j+d-k}$. Clearly this is true for $j = 1$. Suppose that the claim is true for $j = m$ and consider the case $j = m+1$. By definition, we have $|\Lambda_{m+1,v}| = |\Lambda_{m,v}| + |\Omega_{m+1,v}| - |\Lambda_{m,v} \cap \Omega_{m+1,v}|$. By the induction hypothesis, $|\Lambda_{m,v}| = \frac{ml}{m+d-k}$. Therefore,

$$|\Lambda_{m,v} \cap \Omega_{m+1,v}| = \frac{ml}{m+d-k} \frac{1}{m+1+d-k}.$$

Thus

$$|\Lambda_{m+1,v}| = \frac{ml}{m+d-k} + \frac{l}{m+1+d-k} - \frac{ml}{m+d-k} \frac{1}{m+1+d-k}$$

$$= \frac{(m+1)l}{m+1+d-k}.$$

This concludes the induction step and proves that $|\Lambda_{h,v}| = \frac{hl}{d+h-k}$ for any $v \in \mathcal{R}$. Thus $|\Lambda_h| = |\mathcal{R}||\Lambda_{h,v}| = \frac{h(d+2t)l}{d+h-k}$. The proof is complete. \blacksquare

XI. GENERALIZED REED-SOLOMON ARRAY CODES AND d -OPTIMAL REPAIR PROPERTY

In this section we construct a family of MDS array codes with the d -optimal repair property that requires a smaller underlying field size compared to Construction 2 and a smaller l compared to both Construction 2 and Construction 5. The construction forms an extension of Construction 4. As a first step, we introduce a new class of MDS array codes.

A. Generalized Reed-Solomon Array Codes

Definition XI.1. Let $\mathcal{A} = \{A_1, A_2, \dots, A_n\}$ be a set of $l \times l$ matrices over F such that $A_i A_j = A_j A_i$ for all $i, j \in [n]$ and the matrices $A_i - A_j$ are invertible for all $i \neq j$. Let $\mathcal{V} = \{V_1, V_2, \dots, V_n\}$ be a set of $l \times l$ invertible matrices with entries in F such that $A_i V_j = V_j A_i$ for any $i, j \in [n]$. A Generalized Reed-Solomon array code $\text{GRSA}(n, k, \mathcal{A}, \mathcal{V})$ is defined as the (n, k, l) array code with the generator matrix

$$G = \begin{bmatrix} V_1 & V_2 & \dots & V_n \\ A_1 V_1 & A_2 V_2 & \dots & A_n V_n \\ A_1^2 V_1 & A_2^2 V_2 & \dots & A_n^2 V_n \\ \vdots & \vdots & \ddots & \vdots \\ A_1^{k-1} V_1 & A_2^{k-1} V_2 & \dots & A_n^{k-1} V_n \end{bmatrix}.$$

More specifically,

$$\begin{aligned} \text{GRSA}(n, k, \mathcal{A}, \mathcal{V}) &= \{(C_1, C_2, \dots, C_n) : [C_1^T C_2^T \dots C_n^T] \\ &= [M_1^T M_2^T \dots M_k^T] G \text{ for some } M_1, \dots, M_k \in F^l\}. \end{aligned} \quad (26)$$

If $V_1 = V_2 = \dots = V_n = I$, then we call this code a Reed-Solomon array code and denote it as $\text{RSA}(n, k, \mathcal{A})$.

Lemma VII.3 implies that GRSA codes have the MDS property. We need a description of its dual code, which is analogous to the scalar case (Theorem 10.4 in [26, p.304]).

Theorem XI.2. Given a Generalized Reed-Solomon array code $\text{GRSA}(n, k = n - r, \mathcal{A}, \mathcal{V})$ with \mathcal{A} and \mathcal{V} satisfying the conditions in Def. XI.1, there is a set $\mathcal{W} = \{W_1, W_2, \dots, W_n\}$ of $l \times l$ invertible matrices such that $A_i W_j = W_j A_i$ for any $i, j \in [n]$, and

$$\text{GRSA}(n, k, \mathcal{A}, \mathcal{V}) = \{(C_1, C_2, \dots, C_n) : H[C_1^T C_2^T \dots C_n^T]^T = 0\}, \quad (27)$$

where

$$H = \begin{bmatrix} W_1 & W_2 & \dots & W_n \\ A_1 W_1 & A_2 W_2 & \dots & A_n W_n \\ A_1^2 W_1 & A_2^2 W_2 & \dots & A_n^2 W_n \\ \vdots & \vdots & \ddots & \vdots \\ A_1^{r-1} W_1 & A_2^{r-1} W_2 & \dots & A_n^{r-1} W_n \end{bmatrix}.$$

This theorem follows from the following lemma.

Lemma XI.3. Let A_1, A_2, \dots, A_n be $l \times l$ matrices with entries in F such that $A_i A_j = A_j A_i$ for all $i, j \in [n]$ and the matrices $A_i - A_j$ are invertible for all $i \neq j$. The following equation holds:

$$\begin{bmatrix} I & I & \dots & I \\ A_1 & A_2 & \dots & A_n \\ A_1^2 & A_2^2 & \dots & A_n^2 \\ \vdots & \vdots & \ddots & \vdots \\ A_1^{n-2} & A_2^{n-2} & \dots & A_n^{n-2} \end{bmatrix} \begin{bmatrix} B_1 \\ B_2 \\ \vdots \\ B_n \end{bmatrix} = 0, \quad (28)$$

where $B_i = (\prod_{j \neq i} (A_j - A_i))^{-1}$, $i = 1, \dots, n$

Proof: Note that the theory of determinants as well as Cramer's rule extend with no extra effort over arbitrary commutative rings with identity [27, Sect. 11.4]. Let R be a commutative ring containing I, A_1, A_2, \dots, A_n . Given a square block matrix partitioned into $l \times l$ square submatrices in R , we view it as a square matrix with entries in R and define the determinant accordingly. Clearly, for any $i \in [n]$ and any nonnegative integer t , $A_i^t \in R$. We use Cramer's rule to solve the following equation

$$\begin{bmatrix} I & I & \dots & I \\ A_1 & A_2 & \dots & A_{n-1} \\ A_1^2 & A_2^2 & \dots & A_{n-1}^2 \\ \vdots & \vdots & \vdots & \vdots \\ A_1^{n-2} & A_2^{n-2} & \dots & A_{n-1}^{n-2} \end{bmatrix} \begin{bmatrix} X_1 \\ X_2 \\ \vdots \\ X_{n-1} \end{bmatrix} = - \begin{bmatrix} I \\ A_n \\ A_n^2 \\ \vdots \\ A_n^{n-2} \end{bmatrix}$$

The expression for the Vandermonde determinant also holds in commutative rings, and we can easily find that $X_i = (\prod_{j \neq n} (A_j - A_n)) (\prod_{j \neq i} (A_j - A_i))^{-1}$. Moving the right-hand side of the equation above to the left and then multiplying on the right by B_n , we obtain (28). ■

Proof of Theorem XI.2: Set $W_i = V_i^{-1} (\prod_{j \neq i} (A_j - A_i))^{-1}$. Notice the fact that if an $l \times l$ matrix A and an $l \times l$ invertible matrix B satisfy $AB = BA$, then $AB^{-1} = B^{-1}BAB^{-1} = B^{-1}ABB^{-1} = B^{-1}A$. Thus $W_i A_j = A_j W_i$ for any $i, j \in [n]$.

Denote the codes defined in (26) and (27) as \mathcal{C}_1 and \mathcal{C}_2 respectively. By (28), $HG^T = 0$. Thus $\mathcal{C}_1 \subseteq \mathcal{C}_2$. Since G and H both have full rank, \mathcal{C}_1 and \mathcal{C}_2 have the same dimension kl as a vector space over F . Consequently $\mathcal{C}_1 = \mathcal{C}_2$. This completes the proof. ■

B. A family of MDS array codes with the d -optimal repair property

In this section we use the results about GRSA codes to construct a family of $(n, k = n - r, l)$ MDS array codes with the d -optimal repair property.

Construction 7. Let F be a finite field of size $|F| \geq n + 1$ and let γ be a primitive element in F . Let $s = d + 1 - k$ and $l = s^{n-1}$. Consider the code family given by (3)-(4), where the matrices A_1, A_2, \dots, A_n are given by

$$A_i = \sum_{a=0}^{l-1} \lambda_{i,a_i} e_a e_{a(i,a_i \oplus 1)}^T, \quad i = 1, 2, \dots, n-1,$$

$$A_n = I,$$

where \oplus denotes addition modulo s , $\lambda_{i,0} = \gamma^i$ for all $i \in [n-1]$ and $\lambda_{i,u} = 1$ for all $i \in [n-1]$ and all $u \in \{1, 2, \dots, s-1\}$. Here $\{e_a : a = 0, 1, \dots, l-1\}$ is the standard basis of F^l over F , a_i is the i -th digit from the right in the representation of $a = (a_{n-1}, a_{n-2}, \dots, a_1)$ in the s -ary form, and $a(i, u)$ is defined in the same way as in Sect. III.

Theorem XI.4. The code \mathcal{C} given by Construction 7 is an MDS array code.

Proof: The proof parallels the proof of Theorem VII.4: we show that for any $i \neq j$, $A_i A_j = A_j A_i$ and that the matrix $A_i - A_j$ is invertible. Thus, \mathcal{C} is an MDS array code. ■

Theorem XI.5. The code \mathcal{C} given by Construction 7 has the d -optimal repair property.

Proof: By Theorem XI.2, $\mathcal{C} = \text{GRSA}(n, k, \mathcal{A}, \mathcal{V})$ with $\mathcal{A} = \{A_1, A_2, \dots, A_n\}$ and $\mathcal{V} = \{V_1, \dots, V_n\}$, where $V_i = (\prod_{j \neq i} (A_j - A_i))^{-1}$. Suppose that we want to use $C_{i_2}, C_{i_3}, \dots, C_{i_{d+1}}$ to repair C_{i_1} . Let $\Delta = \{i_1, i_2, \dots, i_{d+1}\}$. Clearly $(C_{i_1}, C_{i_2}, \dots, C_{i_{d+1}})$ is a Generalized Reed-Solomon Array code $\text{GRSA}(d+1, k, \mathcal{A}_\Delta, \mathcal{V}_\Delta)$, where $\mathcal{A}_\Delta = \{A_{i_1}, A_{i_2}, \dots, A_{i_{d+1}}\}$ and $\mathcal{V}_\Delta = \{V_{i_1}, V_{i_2}, \dots, V_{i_{d+1}}\}$. By Theorem XI.2, there is a set of $l \times l$ invertible matrices $W_\Delta = \{W_1, W_2, \dots, W_{d+1}\}$ such that

$$\begin{bmatrix} I & I & \dots & I \\ A_{i_1} & A_{i_2} & \dots & A_{i_{d+1}} \\ A_{i_1}^2 & A_{i_2}^2 & \dots & A_{i_{d+1}}^2 \\ \vdots & \vdots & \vdots & \vdots \\ A_{i_1}^{s-1} & A_{i_2}^{s-1} & \dots & A_{i_{d+1}}^{s-1} \end{bmatrix} \begin{bmatrix} W_1 C_{i_1} \\ W_2 C_{i_2} \\ \vdots \\ W_{d+1} C_{i_{d+1}} \end{bmatrix} = 0, \quad (29)$$

Using the same method as in the proof of Theorem VII.2, we can show that $W_1 C_{i_1}$ can be recovered by downloading a vector in $F^{l/s}$ from each of the nodes $C_{i_2}, C_{i_3}, \dots, C_{i_{d+1}}$. Since W_1 is invertible, C_{i_1} can be recovered by the same set of vectors. This shows that \mathcal{C} has the d -optimal repair property. ■

C. Extension to d -optimal repair property for several values of d simultaneously

Now we give a simple extension of the previous construction to make the code have d -optimal repair property for several values of d simultaneously. More specifically, give any positive integers $n, k, m, d_1, d_2, \dots, d_m$ such that $k \leq d_1, \dots, d_m < n$, we will show that by replacing s in Construction 7 with the value

$$s = \text{lcm}(d_1 + 1 - k, d_2 + 1 - k, \dots, d_m + 1 - k),$$

we will obtain an $(n, k, l = s^{n-1})$ MDS array code \mathcal{C} with d_i -optimal repair property for all $i = 1, \dots, m$ simultaneously.

By the proof of Theorem VII.4, we know that \mathcal{C} is an MDS array code. Now we prove that \mathcal{C} has d_i -optimal repair property for any $i \in [m]$.

Theorem XI.6. *The code \mathcal{C} has d_i -optimal repair property for any $i \in [m]$.*

Proof: Given any $i \in [m]$, we show that \mathcal{C} has d_i -optimal repair property. Let $s_i = d_i + 1 - k$. Without loss of generality, we only prove the case when we use $C_2, C_3, \dots, C_{d_i+1}$ to repair C_1 . (The proof below needs some slight modifications for the case of repairing C_n , we omit this special case here.) Following exactly the same steps in the proof of Theorem XI.5, we obtain

$$\begin{bmatrix} I & I & \dots & I \\ A_1 & A_2 & \dots & A_{d_i+1} \\ A_1^2 & A_2^2 & \dots & A_{d_i+1}^2 \\ \vdots & \vdots & \vdots & \vdots \\ A_1^{s_i-1} & A_2^{s_i-1} & \dots & A_{d_i+1}^{s_i-1} \end{bmatrix} \begin{bmatrix} W_1 C_1 \\ W_2 C_2 \\ \vdots \\ W_{d_i+1} C_{d_i+1} \end{bmatrix} = 0, \quad (30)$$

where $W_1, W_2, \dots, W_{d_i+1}$ are some $l \times l$ invertible matrices. Let $C'_i = W_i C_i$. Let $c'_{i,a}$ denote the a -th coordinate of the column vector C'_i for all $a = 0, \dots, l-1$. We can write out the parity-check equations (30) coordinatewise:

$$\sum_{i=1}^{d_i+1} \beta_{i,a_i,t} c'_{i,a(i,a_i \oplus t)} = 0 \quad (31)$$

for all $t = 0, 1, \dots, s_i - 1$ and $a = 0, \dots, l-1$,

where \oplus denotes addition modulo s , $\beta_{i,u,0} = 1$ and $\beta_{i,u,t} = \prod_{v=u}^{u \oplus (t-1)} \lambda_{i,v}$ for $t = 1, \dots, s_i - 1$. Clearly (31) indicates that for any $t = 0, 1, \dots, s-1$, the coordinates $\{c'_{1,a} : a_i = t, t \oplus 1, t \oplus 2, \dots, t \oplus (s_i - 1)\}$ can be determined by $\{c'_{j,a} : j = 2, 3, \dots, d_i + 1, a_i = t\}$. Thus C'_1 can be determined by $\{c'_{j,a} : j = 2, 3, \dots, d_i + 1, a_i = 0, s_i, 2s_i, 3s_i, \dots, s - s_i\}$. Since $s_i | s$, we conclude that C'_1 and thus C_1 itself can be recovered by downloading a vector in F^{l/s_i} from each of the nodes $C_2, C_3, \dots, C_{d_i+1}$. This completes the proof. \blacksquare

Corollary XI.7. *The $(n, k, (n-k)^{n-1})$ MDS array code given by Construction 4 has d -optimal repair property if $(d+1-k)|(n-k)$.*

XII. CONCLUSION

The main problems related to the construction of high-rate regenerating codes are concerned with finding explicit (non-probabilistic) code families over a field F of small size, with a small subpacketization value l , optimal access or repair bandwidth, and optimal error resilience. In this paper we present constructions of such codes over fields of size proportional to the code length n . The remaining open problems are constructing codes with similar properties over fields of constant size (independent of n) and with smaller values of l .

ACKNOWLEDGMENT

We are grateful to our colleague Itzhak Tamo for his help with the proof of Theorem X.1.

REFERENCES

- [1] S. Ghemawat, H. Gobioff, and S. Leung, "The Google file system," *ACM SIGOPS Operating Systems Review*, vol. 37, no. 5, pp. 29–43, 2003.
- [2] N. B. Ellison, C. Steinfield, and C. Lampe, "The benefits of Facebook friends: Social capital and college students use of online social network sites," *Journal of Computer-Mediated Communication*, vol. 12, no. 4, pp. 1143–1168, 2007.
- [3] M. Blaum, P. G. Farrell, and H. van Tilborg, "Array codes," in *Handbook of Coding Theory*, V. Pless and W. C. Huffman, Eds. Elsevier Science, 1998, vol. II, ch. 22, pp. 1855–1909.

- [4] A. G. Dimakis, P. B. Godfrey, Y. Wu, M. J. Wainwright, and K. Ramchandran, "Network coding for distributed storage systems," *IEEE Trans. Inform. Theory*, vol. 56, no. 9, pp. 4539–4551, 2010.
- [5] V. R. Cadambe, S. A. Jafar, H. Maleki, K. Ramchandran, and C. Suh, "Asymptotic interference alignment for optimal repair of MDS codes in distributed storage," *IEEE Trans. Inform. Theory*, vol. 59, no. 5, pp. 2974–2987, 2013.
- [6] S. Pawar, S. El Rouayheb, and K. Ramchandran, "Securing dynamic distributed storage systems against eavesdropping and adversarial attacks," *IEEE Trans. Inform. Theory*, vol. 57, no. 10, pp. 6734–6753, 2011.
- [7] K. V. Rashmi, N. B. Shah, K. Ramchandran, and P. Y. Kumar, "Regenerating codes for errors and erasures in distributed storage," in *Proc. 2012 IEEE Int. Sympos. Inform. Theory*, 2012, pp. 1202–1206.
- [8] K. V. Rashmi, N. B. Shah, and P. V. Kumar, "Optimal exact-regenerating codes for distributed storage at the MSR and MBR points via a product-matrix construction," *IEEE Trans. Inform. Theory*, vol. 57, no. 8, pp. 5227–5239, 2011.
- [9] —, "Methods and system for replacing a failed node in a distributed storage network," Jan. 14 2014, U.S. Patent 8,631,269.
- [10] N. Shah, K. Rashmi, P. Kumar, and K. Ramchandran, "Interference alignment in regenerating codes for distributed storage: Necessity and code constructions," *IEEE Trans. Inform. Theory*, vol. 58, no. 4, pp. 2134–2158, 2012.
- [11] C. Suh and K. Ramchandran, "Exact-repair MDS code construction using interference alignment," *IEEE Trans. Inform. Theory*, vol. 57, no. 3, pp. 1425–1442, 2011.
- [12] Y. Wu and A. Dimakis, "Reducing repair traffic for erasure coding-based storage via interference alignment," in *Proc. 2009 IEEE Int. Sympos. Inform. Theory*, 2009, pp. 2276–2280.
- [13] V. R. Cadambe, C. Huang, and J. Li, "Permutation code: Optimal exact-repair of a single failed node in MDS code based distributed storage systems," in *Proc. 2011 IEEE Int. Sympos. Inform. Theory*, 2011, pp. 1225–1229.
- [14] V. R. Cadambe, C. Huang, J. Li, and S. Mehrotra, "Polynomial length MDS codes with optimal repair in distributed storage," in *Proc. 45th Asilomar Conference on Signals, Systems and Computers*, 2011, pp. 1850–1854.
- [15] D. Papailiopoulos, A. Dimakis, and V. Cadambe, "Repair optimal erasure codes through Hadamard designs," *IEEE Trans. Inform. Theory*, vol. 59, no. 5, pp. 3021–3037, 2013.
- [16] I. Tamo, Z. Wang, and J. Bruck, "Zigzag codes: MDS array codes with optimal rebuilding," *IEEE Trans. Inform. Theory*, vol. 59, no. 3, pp. 1597–1616, 2013.
- [17] Z. Wang, I. Tamo, and J. Bruck, "Explicit MDS codes for optimal repair bandwidth," 2014, arXiv:1411.6328.
- [18] —, "On codes for optimal rebuilding access," in *Proceedings of the 49th Annual Allerton Conference on Communication, Control and Computing*, 2011, pp. 1374–1381.
- [19] A. S. Rawat, O. O. Koyluoglu, and S. Vishwanath, "Progress on high-rate MSR codes: Enabling arbitrary number of helper nodes," 2016, arXiv:1601.06362.
- [20] S. Goparaju, A. Fazeli, and A. Vardy, "Minimum storage regenerating codes for all parameters," 2016, arXiv:1602.04496.
- [21] Z. Wang, I. Tamo, and J. Bruck, "Optimal rebuilding of multiple erasures in MDS codes," 2016, arXiv:1603.01213.
- [22] A. S. Rawat, O. O. Koyluoglu, and S. Vishwanath, "Centralized repair of multiple node failures with applications to communication efficient secret sharing," 2016, arXiv:1603.04822.
- [23] N. Raviv, N. Silberstein, and T. Etzion, "Constructions of high-rate MSR codes over small fields," 2015, arXiv:1505.00919.
- [24] S. Goparaju, I. Tamo, and R. Calderbank, "An improved sub-packetization bound for minimum storage regenerating codes," *IEEE Trans. Inform. Theory*, vol. 60, no. 5, pp. 2770–2779, 2014.
- [25] I. Tamo, Z. Wang, and J. Bruck, "Access versus bandwidth in codes for storage," *IEEE Trans. Inform. Theory*, vol. 60, no. 4, pp. 2028–2037, 2014.
- [26] F. J. MacWilliams and N. J. A. Sloane, *The Theory of Error-Correcting Codes*. Elsevier, 1977.
- [27] D. S. Dummit and R. M. Foote, *Abstract Algebra*. Prentice Hall Englewood Cliffs, 1991.