arXiv:1604.00710v1 [cs.GT] 4 Apr 2016

Pure Nash Equilibrium and Coordination of Players in Ride Sharing Games

Tatsuya Iwase
Social Systems Research-Domain
Toyota Central R&D Labs., Inc.
tiwase@mosk.tytlabs.co.jp

Takahiro Shiga
Social Systems Research-Domain
Toyota Central R&D Labs., Inc.
t-shiga@mosk.tytlabs.co.jp

Abstract

In this study, we formulate positive and negative externalities caused by changes in the supply of shared vehicles as ride sharing games. The study aims to understand the price of anarchy (PoA) and its improvement via a coordination technique in ride sharing games. A critical question is whether ride sharing games exhibit a pure Nash equilibrium (pNE) since the PoA bound assumes it. Our result shows a sufficient condition for a ride sharing game to have a finite improvement property and a pNE similar to potential games. This is the first step to analyze PoA bound and its improvement by coordination in ride sharing games. We also show an example of coordinating players in ride sharing games using signaling and evaluate the improvement in the PoA.

1 Introduction

Congestion and effective resource allocation are traditional problems that game theory has been trying to solve. As populations are increasingly concentrated in big cities, the congestion problem becomes more critical. One practical way to solve the congestion problem is sharing of unused resources. For example, even during heavy traffic congestion, many vehicles have empty seats. Similarly, many empty vehicles occupy limited parking spaces in urban areas while people struggle to find an empty taxi. Besides the transportation field, we can find examples such as unused buildings, empty restaurants, and idle workers.

However, the sharing of unused resources is not realized unless there are matching demands of multiple users. Empty vehicle seats are shared among passengers only if they have a common part on their routes. A vehicle is shared only if the destination of a driver is equal to the origin of another driver. If people behave selfishly, the probability of matching the demand for sharing becomes small, leading to the problem of demand coordination and incentive design.

Particular to the sharing of vehicles is that positive and negative externalities of one player's route change are propagated to other players who do not choose the relevant routes via changes in vehicle supply. Consider a chain of vehicle sharing in which player 1 first drives a vehicle from A to B, then player 2 drives the same vehicle from B to C, and player 3 drives the vehicle from C to D. If player 1 quits to use the vehicle, player 2 and even 3 cannot use the vehicle even though player 3 does not share any part of his route with player 1. Because classical congestion games only focus on externalities among players who choose the same routes, it is necessary to consider alternative games that model externalities via vehicle supply to analyze coordination in vehicle sharing.

This study formulates ride sharing games that model the positive and negative externalities of choosing vehicles. We also consider how to coordinate players to improve the efficiency of sharing, i.e., maximizing the operation rate of otherwise unused vehicles by giving players an incentive. We mainly assume applications in transportation areas, such as carpooling and ride sharing.

1.1 Related work

Since Rosenthal introduced the congestion game [1], it has been applied to problems of congestion externalities in several areas such as transportation and communication networks [2]. In this game, players choose a combination of resources and the players' payoffs depend on the congestion level, i.e., the number of players using the same resources. The congestion game is a subclass of potential games, which feature the *finite improvement property* (FIP). This property guarantees that if each player updates his strategy in response to other players by turns, it will reduce his private cost and improve the common potential function, which eventually reaches a local minimum, the *pure Nash equilibrium* (pNE), where each player has a deterministic strategy. Because of this property, potential and congestion games

have been well studied and have wide applications [3].

The negative externalities in congestion games are also well studied. If players choose their routes selfishly in road networks, it causes loss of social welfare compared to socially optimal routing. The ratio of social cost in a selfish choice to the one in the social optimal is called the *price of anarchy* (PoA) and its bounds are well known, especially for affine cost functions [4]. Studies on PoA bound assume that a game has a pNE. Because of the property of always having a pNE, most PoA studies have focused on congestion games.

A major difference between vehicle sharing and traffic routing problems is vehicle supply. While players drive their own vehicles in traditional traffic routing problems, players must find shared vehicles before riding in sharing problems. In the case of a chain of vehicle sharing from player A via player B to player C, the choice of player A has externalities not only on player B but those also propagate to player C, who does not share any common part of route with player A. This kind of complicated externality is not considered in traditional routing problems and congestion games.

According to a review of sharing studies in transportation areas [5], there are few game theory studies on externalities and coordination of players' moves in vehicle sharing problems. Traditional studies on sharing include the optimization of vehicle routes for picking up all passengers (the *Dial-a-ride problem*), problems of splitting passengers' fares according to their riding distances, optimization of locations of carpool stations, and problems of relocation of carpool vehicles among stations. Those studies mainly focus on optimization problems under given moves (origins and destinations) of passengers and fixed drivers of vehicles, and therefore, do not analyze the PoA when passengers strategically choose their moves in response to the moves of other passengers and vehicles. The review states that there are no studies on coordination of players' moves to improve the efficiency of sharing or reduce the PoA.

There are several studies that examine the coordination of players in traditional traffic routing and congestion games. One promising technique for coordination is the mechanism design, which mainly provides monetary incentives for players to change their behavior in a coordinated manner. Christodoulou studied coordination mechanism in congestion games [6].

Another relatively new technique for coordination is signaling, in which a mediator provides information for players to control their beliefs on uncertain environments, and accordingly, the expected payoff and resulting choices when there is information asymmetry between the mediator and players [7–9]. Most recent studies are based on the *revelation principle*, which proved the existence of incentive compatible recommendations of choices equivalent to the raw information inducing the same choices [10]. Rogers applied differential privacy techniques originally from database security to traffic routing problems for mitigating congestions by sending noisy incentive compatible recommendations of routes [11]. Vasserman also applied recommendations to traffic routing and analyzed how the PoA improved [12].

1.2 Our contributions and paper structure

This study proposes ride sharing games as a formulation of positive and negative externalities caused by changes in the supply of shared vehicles. The study's objective is to understand the PoA and its improvement via a coordination technique in ride sharing games. A critical question is whether ride sharing games have a pNE since the PoA bound assumes it. Our result shows a sufficient condition for a ride sharing game to have a FIP and a pNE similar to potential games. This is the first step to analyze PoA bound and its improvement by coordination in ride sharing games. We also show an example of coordinating players in ride sharing games using signaling and evaluate the improvement in the PoA.

Section 2 provides a formulation of ride sharing games and other setups. Section 3 presents the main results on a condition of ride sharing games to have pNE and its proof. Section 4 presents graphic examples of ride sharing games and coordination of players by signaling.

2 The Models

2.1 Ride sharing games

A *ride sharing game* is defined as a tuple $G =< \mathcal{N}, \mathcal{M}, \mathcal{T}, \mathcal{G}, \mathcal{A}, \mu, c >$, where

- $\mathcal{N} = \{1, \ldots, N\}$ is a finite set of players. A player $i \in \mathcal{N}$ represents an user of shared vehicles. $-i$ represents all players except for i.
- $\mathcal{M} = \{1, \ldots, M\}$ is a finite set of vehicles. Each vehicle $m \in \mathcal{M}$ has a common seating capacity $w \in \mathbb{N}_{>0}$.
- $\mathcal{G} =< \mathcal{V}, \mathcal{E} >$ is a directed graph that has a finite set of nodes $\mathcal{V} = \{1, \ldots, V\}$ and a finite set of edges $\mathcal{E} = \{1, \ldots, E\}$. $\mathcal{G}$ is a simple graph but each node has a loop to itself. A node $v \in \mathcal{V}$ represents a place and an edge $e \in \mathcal{E}$ represents a road. Players and vehicles move on $\mathcal{G}$.
- $\mathcal{T} = \{1, \ldots, T\}$ is a finite set of time that partitions the day. Each player and vehicle is located on a node at time $t \in \mathcal{T}$ and finishes a move on an edge during period $(t, t+1)$.
- $\mathcal{R}$ is a set of all paths with length $T-1$ on $\mathcal{G}$. A path $r = (v_1, e_1, v_2, e_2, \ldots, e_{T-1}, v_T) \in \mathcal{R}$ represents a round trip of a player on a day. We denote $r_k \subseteq r$ if r_k is a induced path of r. $r - r_k$ is a complement of r_k which is also a induced path of r including all edges not in r_k. r is a common path $r = r_1 \bigcap r_2$ if and only if $r \subseteq r_1$ and $r \subseteq r_2$.
- $\mathcal{A}_i \subset \mathcal{R}$ is a set of strategies of player i. $\mathcal{A} = \underset{i \in \mathcal{N}}{\times} \mathcal{A}_i$ is a set of strategy profiles. $a_i \in \mathcal{A}_i$ is a round trip of player i and $\boldsymbol{a} \in \mathcal{A}$ is a strategy profile. $\boldsymbol{a}_{-i}$ represents a strategy profile of all players except for i. A strategy update is

denoted as $(\boldsymbol{a}, b_i, i)$ when a original strategy profile is $\boldsymbol{a}$ and player i update a strategy from a_i to b_i.

- $\mu(i, t, \boldsymbol{a}) :< \mathcal{N}, \mathcal{T}, \mathcal{A} >\rightarrow \mathcal{M}$ is a map that represents the allocation of player i to vehicle m during each period $(t, t+1)$ depending on strategy profile $\boldsymbol{a}$. In the case where no vehicle is allocated to player i, $\mu(i, t, \boldsymbol{a}) = \emptyset$. Each vehicle m moves together with allocated player i on the same edge where the player moves. $s_m(t, \boldsymbol{a})$ represents the number of players riding on vehicle m during period $(t, t+1)$ when the strategy profile is $\boldsymbol{a}$.

- $c_e(w, s_m) :< \mathbb{N}_{>0}, \mathbb{N}_{\geq 0} >\rightarrow \mathbb{R}_{\geq 0}$ is a cost function of a player riding on vehicle m on edge e. $c = \{c_e | e \in \mathcal{E}\}$ is a set of cost functions of all edges. The total cost of player i on a day is $c_i(\boldsymbol{a}) = \sum_{e_t \in a_i} c_e(w, s_{\mu(i,t,\boldsymbol{a})}(t, \boldsymbol{a}))$.

In this study, we consider one-shot games, where players simultaneously choose whole round trips $\boldsymbol{a}$ on the day. We assume that cost function c_e is monotone decreasing for s_m when $s_m < w$ and monotone increasing when $s_m \geq w$.

2.2 Basic notions of potential games

Here we prepare the basic concepts of potential games used in the rest of the paper. A *pure Nash equilibrium* (pNE) of game $G =< \mathcal{N}, \mathcal{A}, c >$ is defined as a deterministic strategy profile $\boldsymbol{a} \in \mathcal{A}$ if and only if no player can reduce his cost by updating his deterministic strategy from $\boldsymbol{a}$.

While not all games have a pNE, some games always have a pNE. In particular, the following property guarantees the existence of a pNE.

Definition 1 (Finite improvement property)**.** *A game has a finite improvement property (FIP) if a strategy profile of the game always converges to a pure Nash equilibrium by updating each player's strategy, by turns, finite times.*

When a game has an FIP, a pNE can be found by players updating their strategies one player at a step. Therefore, it is unnecessary to search the whole set of strategy profiles and the computational cost to find a pNE is reduced.

A potential game is game G which has a potential function Φ defined as follows [13].

Definition 2 ((Ordinal) potential game)**.** $\Phi : \mathcal{A} \rightarrow \mathbb{R}$ *is a (ordinal) potential function and G is a (ordinal) potential game if*

$$sgn(\Phi(b_i, \boldsymbol{a}_{-i}) - \Phi(a_i, \boldsymbol{a}_{-i})) = sgn(c_i(b_i, \boldsymbol{a}_{-i}) - c_i(a_i, \boldsymbol{a}_{-i})). \tag{1}$$

The following theorem guarantees that potential games have an FIP and then a pNE.

Theorem 1. *If a potential game has a potential function with a finite amount of values, the game has an FIP.*

Proof. Starting from an arbitrary strategy profile $\boldsymbol{a}$, each player updates their strategy by turns to minimize his cost. From the definition, it also reduces the value of the potential function until it reaches a local minimum. At that point, no player can reduce his cost and it is a pNE. From Definition 1, it also has an FIP. □

In applications such as transportation and communication networks, problems are often formulated as a minimization of a social cost, which is the total cost of all players. Normally, a social cost in a pNE is not the same as in the optimal. The ratio between the cost of a pNE and an optimal cost is called the *price of anarchy* (PoA) and is defined as follows [4].

Definition 3 (Price of anarchy)**.** *The price of anarchy $\rho(G)$ of game G is*

$$\rho(G) = \frac{C(\boldsymbol{a}^*)}{C(\boldsymbol{a}^{opt})} \tag{2}$$

where $C(\boldsymbol{a})$ is a social cost of strategy profile $\boldsymbol{a}$, $\boldsymbol{a}^*$ is pNE and $\boldsymbol{a}^{opt}$ is the social optimal.

Since the PoA assume a pNE, former studies on the PoA have focused on games with a pNE, such as congestion games.

2.3 Bayesian ride sharing games

We consider cases where players have incomplete information on vehicle allocations. A *Bayesian ride sharing game* is an extension of a ride sharing game and defined as $G_b =< \mathcal{N}, \mathcal{M}, \mathcal{T}, \mathcal{G}, \mathcal{A}, \mathcal{X}, \mathcal{P}, \mu, c >$ where

- $\mathcal{X}$ is a set of possible values of an exogenous variable $x \in \mathcal{X}$, which affects the allocation of vehicles μ.
- $\mu(i, t, \boldsymbol{a}|x)$ is the allocation of vehicles depending on x. Similarly, $s_m(t, \boldsymbol{a}|x)$ is the number of players on vehicle m depending on x and $c_i(\boldsymbol{a}|x)$ is the cost of player i depending on x.
- $p_i(x) : \mathcal{X} \to [0, 1]$ is a probability distribution on X of player i, which represents his belief. $\mathcal{P} = \{p_i | i \in N\}$ is a set of probability distributions of all players.
- Definitions of other elements of G_b are the same as those of ride sharing game G.

Examples of exogenous variable x are initial vehicle locations and traffic accidents. Each player chooses a_i to minimize his expected cost, which is $\mathbb{E}_{\mathcal{X}}[c_i] = \sum_{x \in \mathcal{X}} c_i(\boldsymbol{a}|x) p_i(x)$.

A pure Bayesian Nash equilibruim (pBNE) of a bayesian game is a similar concept to pNE of a deterministic game that is defined as a deterministic strategy profile $\boldsymbol{a} \in \mathcal{A}$ if and only if no player can reduce his expected cost by updating his deterministic strategy from $\boldsymbol{a}$.

2.4 Signaling on Bayesian ride sharing games

In this study, we use the *Bayes correlated equilibrium* (BCE) [8] as a signaling technique of a mediator to coordinate players. A BCE is a conditional distribution $\sigma(\hat{\boldsymbol{a}}|x)$ of a random recommendation $\hat{\boldsymbol{a}}$, which is *incentive compatible* (IC) as defined below.

Definition 4 (Incentive compatible)**.** *A recommendation policy $\sigma(\hat{\boldsymbol{a}}|x)$ is incentive compatible if*

$$\sum_{\hat{\boldsymbol{a}}_{-i},x} p_i(x)\sigma(\hat{\boldsymbol{a}}|x)c_i(\hat{a}_i,\hat{\boldsymbol{a}}_{-i}|x) \leq \sum_{\hat{\boldsymbol{a}}_{-i},x} p_i(x)\sigma(\hat{\boldsymbol{a}}|x)c_i(a_i,\hat{\boldsymbol{a}}_{-i}|x),\ \forall i \forall \hat{a}_i. \quad (3)$$

Given the cost function of the mediator $c_s(\boldsymbol{a}|x)$, the problem of the mediator is to design an optimal IC recommendation that makes players coordinate to minimize their cost. The problem is expressed as follows.

$$\begin{aligned} &\max_\sigma \mathbb{E}_x[c_s(\hat{\boldsymbol{a}}|x)] \\ &s.t.\ \textstyle\sum_{\hat{\boldsymbol{a}}_{-i},x} p_i(x)\sigma(\hat{\boldsymbol{a}}|x)c_i(\hat{a}_i,\hat{\boldsymbol{a}}_{-i}|x) \leq \sum_{\hat{\boldsymbol{a}}_{-i},x} p_i(x)\sigma(\hat{\boldsymbol{a}}|x)c_i(a_i,\hat{\boldsymbol{a}}_{-i}|x),\ \forall i \forall \hat{a}_i. \end{aligned} \quad (4)$$

3 Result

Here, we discuss when ride sharing games have a pNE in order to evaluate the PoA of a game and its improvement by coordination.

We first start with the following negative result in most general cases.

Theorem 2. *There exist ride sharing games that do not have an FIP.*

Proof. The example in Section 4.1 shows the case in which the strategy updates of players are caught in an infinite loop, which will not converge to any pNE. □

If all ride sharing games fall into this case, it is hard to apply theory of PoA. However, we found cases where ride sharing games have an FIP. Intuitively, cost functions c_e become monotone decreasing when $N \leq w$ and then ride sharing games have a structure of *increasing returns* and are *locked in* to a pNE [14]. Before proceeding, we introduce several notions here.

Let $M_{et}(\boldsymbol{a})$ and $N_{et}(\boldsymbol{a})$ be the number of vehicles and players on edge e during period $(t, t+1)$, respectively. The change in N_{et} by a strategy update $(\boldsymbol{a}, b_i, i)$ is defined as follows.

$$\Delta N_{et}(\boldsymbol{a}, b_i, i) = N_{et}(b_i, \boldsymbol{a}_{-i}) - N_{et}(\boldsymbol{a}). \tag{5}$$

Definition 5 (No-vehicle-loss update)**.** *A strategy update $(\boldsymbol{a}, b_i, i)$ is no-vehicle-loss if $M_{et}(b_i, \boldsymbol{a}_{-i}) \neq 0, \forall\{e_t : e_t \in b_i, M_{et}(\boldsymbol{a}) > 0\}$.*

An allocation map μ of a ride sharing game can be divided into *path allocation* μ_r and *seat allocation* μ_s. Path allocation determines the paths of vehicles. Once an edge on which a vehicle moves has been fixed, seat allocation determines the allocation of players to vehicles on the edge. The following path allocation assumes that the more demands there are on an edge, the more vehicles are allocated to it.

Definition 6 (Linear path allocation)**.** *A linear path allocation μ_r determines an allocation of M_{et} out of M vehicles on a node v to outgoing edge $e \in \mathcal{E}_v$ on which N_{et} players move at t so that*

$$M_{et} = floor(k * N_{et}) \tag{6}$$

where k is a constant that keeps $M = \sum_{e \in \mathcal{E}_v} k * N_{et}$. The remaining $M - \sum_{e_t \in \mathcal{E}_v} M_{et}$ vehicles are allocated to $\mathcal{E}_v$ in the order of $k * Net - M_{et}$.

Definition 7 (Allocated path)**.** *r is an allocated path if at least one vehicle is allocated on all edges in r.*

Seat allocation is a simple version of bin packing problem. If players are willing to share a vehicle to reduce their costs, it is natural to assume the first-fit algorithm [15] as follows.

Definition 8 (First-fit seat allocation)**.** *A seat allocation is first-fit if players are allocated to a vehicle with the smallest m on the edge until it becomes full.*

This definition immediately yields the following lemma.

Lemma 1. *If $N \leq w$ and μ_s is the first-fit seat allocation, all N_{et} players ride in the same vehicle if $M_{et} > 0$.*

Definition 9 (First fit linear allocation)**.** *An allocation μ is first-fit liner if it comprises a linear path allocation and a first-fit seat allocation.*

The following lemma states that copying the strategy of another player j always results in a cost less than c_j in some ride sharing games.

Lemma 2. $c_i(a_j, \boldsymbol{a}_{-i}) \leq c_j(\boldsymbol{a})$ *if*

H1: all players have a common set of actions $\mathcal{A}_0$,

H2: $N \leq w$,

H3: μ_s is the first-fit seat allocation, and

H4: strategy update $(\boldsymbol{a}, a_j, i)$ is no-vehicle-loss.

Proof. Let $\boldsymbol{a}$ be a current strategy profile. Now consider strategy update $(\boldsymbol{a}, a_j, i)$ which is always possible because of H1. Since all N_{et} players ride on a vehicle on the edge according to H2, H3 and Lemma1, the number of players sharing a car s_m now depends only on M_{et} and N_{et} as follows.

$$s_m(t, \boldsymbol{a}) = s_{et}(\boldsymbol{a}) = \begin{cases} N_{et}(\boldsymbol{a}) & \text{if } M_{et}(\boldsymbol{a}) \geq 1 \\ 0 & \text{if } M_{et}(\boldsymbol{a}) = 0. \end{cases} \tag{7}$$

Since player i joins in a_j and all other players' strategies remain the same,

$$\Delta N_{et}(\boldsymbol{a}, a_j, i) \geq 0, \forall e_t \in a_j. \tag{8}$$

Therefore, from H4 and Eq.7, we get

$$\Delta s_{et} = s_{et}(a_j, \boldsymbol{a}_{-i}) - s_{et}(\boldsymbol{a}) \geq 0, \forall e_t \in a_j. \tag{9}$$

From H2, cost functions c_e are monotone decreasing such that

$$c_e(w, s_{et}(a_j, \boldsymbol{a}_{-i})) \leq c_e(w, s_{et}(\boldsymbol{a})), \forall e_t \in a_j. \tag{10}$$

Then,

$$c_i(a_j, \boldsymbol{a}_{-i}) = \sum_{e_t \in a_j} c_e(w, s_{et}(a_j, \boldsymbol{a}_{-i})) \leq \sum_{e_t \in a_j} c_e(w, s_{et}(\boldsymbol{a})) = c_j(\boldsymbol{a}). \tag{11}$$

This completes the proof of Lemma 2. □

Definition 10 (Riding path)**.** *r is a riding path of player i if $r \subseteq a_i$ and r is an allocated path.*

Definition 11 (Necessary path)**.** *$r \in \mathcal{R}_n$ is a necessary path if*

$$c_i(a_i \supseteq r, \boldsymbol{a}_{-i}) \leq c_i(b_i \not\supseteq r, \boldsymbol{a}_{-i}), \forall i, \boldsymbol{a}_{-i} \tag{12}$$

when r is an allocated path.

Definition 12 (Sufficient path)**.** *$r \in \mathcal{R}_s$ is a sufficient path if r_c is a riding path of player i and*

$$c_i(r_c = r, \boldsymbol{a}_{-i}) \leq c_i(r_c \neq r, \boldsymbol{a}_{-i}), \forall i, \boldsymbol{a}_{-i}. \tag{13}$$

Definition 13 (Disjoint path set)**.** *A set of paths $\mathcal{R}$ is disjoint if*

$$r_i \bigcap r_j = \emptyset, \forall \{i \neq j : r_i, r_j \in \mathcal{R}\}. \tag{14}$$

Definition 14 (Driver and passener)**.** *Let r be a necessary path and $r_c \supseteq r$ is a riding path of player i. i is a driver if $r_c \supset r$. i is a passenger if $r_c = r$.*

Lemma 3. *Once a player update his strategy and becomes a driver, he cannot improve his cost by updating his strategy again if*

H1: all players have a common set of actions $\mathcal{A}_0$,

H2: $M = 1$,

H3: $N \leq w$,

H4: μ_s is the first-fit seat linear allocation, and

H5: G has a disjoint set of necessary and sufficient paths $\mathcal{R}_{ns}$.

Proof. Let i be a driver who has a riding path r_c including a necessary and sufficient path r. From H2, H5 and Definitions 12 and 14, all other players update their strategies to be passengers of r. Then the number of players on r increases compaired to the one when i lastly updated his strategy. Since $\mathcal{R}_{ns}$ is disjoint, the number of players on the other $r_{ns} \in \mathcal{R}_{ns}$ decreases. Then the cost for the part r stays minimal since cost functions are monotone decreasing. Meanwhile, i is a only player who is on $r_c - r$ since all other players are passengers of r. Then the cost for the part $a_i - r$ is independent of $\boldsymbol{a}_{-i}$ and stay minimal since when i updated strategy last time. Therefore, the cost of whole path a_i is minimal and then player i cannot update his strategy. □

The following theorem tells us there is a class of ride sharing games that has an FIP.

Theorem 3. *A ride sharing game G has an FIP if*

H1: all players have a common set of actions $\mathcal{A}_0$,

H2: $M = 1$,

H3: $N \leq w$,

H4: μ_s is the first-fit seat linear allocation, and

H5: G has a disjoint set of necessary and sufficient paths $\mathcal{R}_{ns}$.

Proof. Let Φ be a function defined as

$$\Phi(\boldsymbol{a}) = \min_k c_k(\boldsymbol{a}). \tag{15}$$

Let $\boldsymbol{a}$ be the current strategy profile, let j be a player who has the current minimum cost among all players, and let his current profile be a_j. Then, Φ becomes

$$\Phi(\boldsymbol{a}) = c_j(\boldsymbol{a}). \tag{16}$$

If j has no riding path, no player are allocated a vehicle because of Definition 11. In this case, player i can update his strategy to b_i, which has a necessary allocated path. From Definition 11, b_i updates the minimum cost and accordingly $\Phi(b_i, \boldsymbol{a}_{-i}) \leq \Phi(\boldsymbol{a})$.

If j has a riding path r_j, it must include a necessary path r because of Definition 11. If i is not a driver, he can copy the strategy of j as $b_i = a_j$ without reducing N_{et} for all $e_t \in r_j$ and from H4 the strategy update $(\boldsymbol{a}, a_j, i)$ is no-vehicle-loss. Then from Lemma 2, it updates the minimum cost and accordingly $\Phi(b_i, \boldsymbol{a}_{-i}) \leq \Phi(\boldsymbol{a})$.

If j has a riding path r_j and i is a driver, i cannot update his strategy according to Lemma 3.

Accordingly, if a player can update his strategy and reduce cost, it also reduces $\Phi(\boldsymbol{a})$ or a player cannot update his strategy. Then, $\Phi(\boldsymbol{a})$ satisfies Definition 2 and is a potential function. Consequently, from Theorem 1, game G has an FIP. This complete the proof of Theorem 3.

□

Although Theorem 3 has several assumptions and covers only a limited class of ride sharing games, the following theorem indicates a possibility of relaxation of the assumptions.

Theorem 4. *The assumptions in Theorem 3 are not necessary conditions.*

Proof. The example in Section 4.3 shows the case where a game has an FIP even though it does not satisfy all the assumptions in Theorem 3. □

4 Examples

In this section, we provide graphical examples of ride sharing games. In Sections 4.1 to 4.3 we assume the following games.

- $N = 3, T = 5, V = 4$.
- $\mathcal{G}$ is a complete graph but each node has a loop edge connected to itself to represent staying of players.
- Initial location of players is node 1 and that of vehicles is node 2.
- a_i must include nodes 3 and 4 for all players.
- μ is the first-fit linear allocation.

All edges have the same cost function, which is

$$c_e = \begin{cases} \frac{d}{s_m+1} & \text{if } s_m \leq w \\ d(1 - \frac{w^2}{s_m(w+1)}) & \text{if } s_m > w \end{cases} \tag{17}$$

where $d = 0$ for loop edges and $d = 1$ for others.

4.1 A case of non-FIP game

Here, we assume $M = 2$ and $w = 1$ and then G does not have an FIP. Figure 1 shows the initial state of this game. The numbers represent nodes v; a, b and c represent the players, and $*$ represents a vehicle. Figures 2 and 3 show how strategy updates make a loop and the FIP is broken. In Figure 2, there are two drivers (a and c) and b is the player with the minimum cost. However, in Figure 3, a updates his strategy to quit being a driver and become a passenger to reduce his cost, and b loses a vehicle and his cost increases. In this case, $w = 1 < N$ so that player b cannot reduce cost by copying another player's strategy according to Lemma 2. Then, b must choose the other vehicle to reduce his cost again as in Figure 4. This negative externality makes an infinite loop of this driver switching behavior and the game loses its FIP.




Figure 1: Initial strategy profile of non-FIP game

4.2 A case of FIP game

Here, we assume $M = 1$ and $w = 4$ and that G satisfies all the assumptions in Theorem 3 and has an FIP. In this case, the game immediately converges into a pNE as in Figure 5. The best update of player a is to pickup the vehicle and all other players because the vehicle has enough capacity.

4.3 Another case of FIP game

Here, we consider another case where $M = 2$ and $w = 4$ and the initial profile is the same as that in Figure 2. In this case, a updates the same strategy as that in




Figure 2: Two drivers

Figure 3 and increases the cost of player b. However, in this case, b does not have to pick up the other vehicle but can be a passenger as in Figure 6, and this is the same pNE as that in Figure 5. While this game does not satisfy H2 in Theorem 3, it has an FIP. This means that the assumptions in Theorem 3 are not necessary conditions.




Figure 3: Negative externality




Figure 4: A player's restarting update




Figure 5: A pNE of the FIP game




Figure 6: Same pNE of the FIP game

4.4 An example of signaling in ride sharing games

Here, we show how signaling can improve the efficiency of sharing by giving players an incentive to coordinate with each other in a Bayesian ride sharing game. Game G is defined as follows.

- $N = 2, V = 3, T = 4, M \leq 1$.
- $\mathcal{G}$ and initial locations are shown in Figure 7. All nodes have loop edges to themselves.
- a_i must include node 3 for all players.
- μ is the first-fit linear allocation.
- There is an uncertainty $x \in \mathcal{X} = \{0, 1\}$ regarding the existence of the vehicle. $x = 0$ means $M = 0$ and $x = 1$ means $M = 1$.
- All players have a common prior $p_i(x = 0) = 0.5, \forall i$.

For each x, this game satisfies the assumptions in Theorem 3. There are only two distinct options for each player that $\mathcal{A} = \{C, D\}$. $C = (1, 2, 3, 1)$ is a trip that visits nodes in this order. On the other hand, $D = (1, 1, 3, 1)$. All edges except for loop edges have the same cost function. If a player does not use the vehicle, the cost is 8. If a player drives alone, the cost is 6. If two players share the vehicle, the cost is 1. The cost of loop edges is zero. The cost matrices of this game are shown in Tables 1 and 2.




Figure 7: A Bayesian ride sharing game

The expected cost matrix is shown in Table 3. This matrix has the structure of a prisoner's dilemma and pBNE is $a = (D, D)$, which means no players share the vehicle.

Now we consider a system to coordinate players to share the unused vehicle by the BCE, as described in Section 2.4. A system cost can be denoted as $c_s(a|x) = \sum_{i \in \mathcal{N}} c_i(a|x)$. Then, the problem of the system is denoted as Eq.4, which is the search for an optimal recommendation policy $\sigma(\hat{\boldsymbol{a}}|x)$ as in Table 4. The problem becomes a linear programming and Table 5 presents a solution. This incentive compatible recommendation induces the coordination of players as a BCE, where

Table 1: $c_i(a_1, a_2|x = 0)$

	C	D
C	20,20	20,16
D	16,20	16,16

Table 2: $c_i(a_1, a_2|x = 1)$

	C	D
C	10,10	15,9
D	9,15	16,16

Table 3: $\mathbb{E}_x[c_i(a_1, a_2|x)]$

	C	D
C	15,15	17.5,12.5
D	12.5,17.5	16,16

Table 4: $\sigma(\hat{a}_1, \hat{a}_2|x)$

$\sigma(\hat{a}_1, \hat{a}_2\|0)$			$\sigma(\hat{a}_1, \hat{a}_2\|1)$		
	C	D		C	D
C	α_0	β_0	C	α_1	β_1
D	β_0	$1 - \alpha_0 - 2\beta_0$	D	β_1	$1 - \alpha_1 - 2\beta_1$

Table 5: Optimal $\sigma(\hat{a}_1, \hat{a}_2|x)$

$\sigma(\hat{a}_1, \hat{a}_2\|0)$			$\sigma(\hat{a}_1, \hat{a}_2\|1)$		
	C	D		C	D
C	0	0	C	0.06	0.47
D	0	1	D	0.47	0

$\mathbb{E}_x[c_s(\hat{\boldsymbol{a}}, x)] = 27.9$, which is better than the one of pBNE $\mathbb{E}_x[c_s(\boldsymbol{a}|x)] = 32$. Since $\mathbb{E}_x[c_s(\boldsymbol{a}|x)] = 26$ in social optimum, the PoA is improved from 1.23 of pBNE to 1.07 of BCE.

References

[1] R. W. Rosenthal, (1973). "A class of games possessing pure-strategy Nash equilibria," International Journal of Game Theory 2(1), 65.

[2] E. Altman, L. Wynter, (2004). "Equilibrium, games, and pricing in transportation and telecommunication networks," Networks and Spatial Economics 4(1), 7-21.

[3] W. H. Sandholm, (2010). "Population games and evolutionary dynamics," MIT press.

[4] T. Roughgarden, E. Tardos, (2002). "How bad is selfish routing?," Journal of the ACM (JACM) 49(2), 236.

[5] N. Agatz, (2012). "Optimization for dynamic ride-sharing: A review," European Journal of Operational Research 223(2), 295.

[6] G. Christodoulou, E. Koutsoupias, A. Nanavati, (2004). "Coordination mechanisms," Automata, Languages and Programming (pp. 345-357). Springer Berlin Heidelberg.

[7] M. Gentzkow, E. Kamenica, (2011). "Bayesian persuasion," American Economic Review 101(6), 2590.

[8] D. Bergemann, S. Morris, (2015). "Bayes correlated equilibrium and the comparison of information structures in games," Theoretical Economics.

[9] I. Kremer, Y. Mansour, M. Perry, (2014). "Implementing the wisdom of the crowd," Journal of Political Economy 122(5), 988.

[10] R. B. Myerson, (1979). "Incentive compatibility and the bargaining problem," Econometrica: journal of the Econometric Society 47(1), 61.

[11] R. M. Rogers, A. Roth, (2014). "Asymptotically truthful equilibrium selection in large congestion games," Proceedings of the fifteenth ACM conference on Economics and computation. ACM.

[12] S. Vasserman, M. Feldman, A. Hassidim, (2015). "Implementing the wisdom of waze," Proceedings of the Twenty-Fourth International Joint Conference on Artificial Intelligence (IJCAI 2015).

[13] D. Monderer, L. S. Shapley, (1996). "Potential games," Games and economic behavior 14(1), 124-143.

[14] W. B. Arthur, (1994). "Increasing returns and path dependence in the economy", University of Michigan Press.

[15] A. C. C. Yao, (1980). "New algorithms for bin packing," Journal of the ACM (JACM) 27(2), 207-227.