

Constructing Error-Correcting Binary Codes Using Transitive Permutation Groups

Antti Laaksonen, Patric Östergård

February 1, 2022

Abstract

Let $A_2(n, d)$ be the maximum size of a binary code of length n and minimum distance d . In this paper we present the following new lower bounds: $A_2(18, 4) \geq 5632$, $A_2(21, 4) \geq 40960$, $A_2(22, 4) \geq 81920$, $A_2(23, 4) \geq 163840$, $A_2(24, 4) \geq 327680$, $A_2(24, 10) \geq 136$, and $A_2(25, 6) \geq 17920$. The new lower bounds are a result of a systematic computer search over transitive permutation groups.

1 Introduction

A binary code C of length n is a set of binary vectors of length n . Each vector $w = (w_1, w_2, \dots, w_n)$ in the code is called a codeword. The minimum distance of C is the minimum of $d_H(a, b)$ where $a, b \in C$ and d_H is the Hamming distance, i.e., the number of coordinates where a and b differ. The size of C is the number of codewords that it contains.

Let $A_2(n, d)$ be the maximum size of a binary code of length n and minimum distance d . A long-standing problem in information theory has been to find lower and upper bounds for $A_2(n, d)$ values [1]. In this paper we present several improved lower bounds that are summarized in Table 1.

Our new lower bounds are a result of a systematic computer search over transitive permutation groups. We focus on codes that consist of orbits of codewords generated by a permutation group, and reduce the problem of finding a maximum size code into a maximum weight clique problem.

The motivation for the approach is that several existing codes have this kind of symmetric structure, which suggests that it is a good way to design codes. In addition, complete databases of transitive permutation groups are available, which makes an automatic computer search possible.

Table 1: New Lower Bounds for Code Sizes

Old Lower Bound	New Lower Bound
$A_2(18, 4) \geq 5312$ [6]	$A_2(18, 4) \geq 5632$
$A_2(21, 4) \geq 36864$ [1]	$A_2(21, 4) \geq 40960$
$A_2(22, 4) \geq 73728$ [1]	$A_2(22, 4) \geq 81920$
$A_2(23, 4) \geq 147456$ [1]	$A_2(23, 4) \geq 163840$
$A_2(24, 4) \geq 294912$ [1]	$A_2(24, 4) \geq 327680$
$A_2(24, 10) \geq 128$ [1]	$A_2(24, 10) \geq 136$
$A_2(25, 6) \geq 16384$ [1]	$A_2(25, 6) \geq 17920$

2 Code Construction

We represent a codeword w of length n as a doubleword x that is a binary vector $(x_1, x_2, \dots, x_{2n})$ of length $2n$. The first n elements of x correspond to the actual codeword, and the last n elements of x are the inverse of the codeword. More precisely, $x_i = w_i$ for $i = 1, 2, \dots, n$, and $x_i = 1 - w_{i-n}$ for $i = n + 1, n + 2, \dots, 2n$.

Let G be a permutation group of degree $2n$. For any doubleword x of length $2n$, we use the notation $G.x$ for the orbit of x , i.e., the set $G.x$ contains all doublewords that can be generated from x using the permutations in G . We construct codes that consist of one or more orbits, i.e., each code is of form $G.x_1 \cup G.x_2 \cup \dots \cup G.x_k$ where $x_1, x_2, \dots, x_k$ are the corresponding orbit representatives.

The benefit of using the doubleword representation is that permutations of both coordinates and coordinate values in the original codeword can be expressed as permutations of coordinates in the doubleword. To allow only this type of permutations, we require that for each permutation $p \in G$, $|p(i) - p(n + i)| = n$ for $i = 1, 2, \dots, n$.

The construction of a code of minimum distance d can be seen as a graph problem. Let $d_H(x)$ be the minimum distance of two codewords in $G.x$, and let $d_H(x, y)$ be the minimum distance of any codewords $a \in G.x$ and $b \in G.y$. Let us construct a graph whose nodes are the orbit representatives x such that $d_H(x) \geq d$, and there is an edge between nodes x and y if $d_H(x, y) \geq d$. Now any clique in the graph corresponds to a code of minimum distance d , and the weight of the clique is equal to the size of the code.

Using this approach, new codes can be discovered using a computer search. We constructed a large number of potential permutation groups based on databases of transitive permutation groups. All transitive permu-

tation groups up to degree 30 are available in GAP [5], and extensions up to degree 47 can be obtained from [3, 4].

After fixing the permutation group, the remaining problem is to select the orbits that will be included in the code. The problem of constructing a maximum size code is equal to the problem of finding a maximum weight clique in the corresponding graph. Even if the problem itself is NP-hard, heuristic methods can yield good results. We used the Cliquer [2] tool for searching for maximum weight cliques.

3 New Results

In this section we present the codes that correspond to the new lower bounds. For each code we give the generators of the permutation group, and the orbit representatives from which the code can be generated.

3.1 Lower Bound $A_2(18, 4) \geq 5632$

Let

$$G = \{ \begin{array}{l} (2\ 5\ 3\ 4\ 19\ 22\ 20\ 21)(6\ 34\ 7\ 33\ 23\ 17\ 24\ 16) \\ (8\ 15\ 9\ 14\ 25\ 32\ 26\ 31)(10\ 13\ 28\ 29\ 27\ 30\ 11\ 12), \\ (2\ 34\ 3\ 33\ 19\ 17\ 20\ 16)(4\ 14\ 22\ 32\ 21\ 31\ 5\ 15) \\ (6\ 12\ 7\ 13\ 23\ 29\ 24\ 30)(8\ 27\ 9\ 11\ 25\ 10\ 26\ 28), \\ (2\ 33\ 28\ 9\ 19\ 16\ 11\ 26)(3\ 34\ 27\ 8\ 20\ 17\ 10\ 25) \\ (4\ 15\ 13\ 7\ 21\ 32\ 30\ 24)(5\ 14\ 12\ 23\ 22\ 31\ 29\ 6), \\ (2\ 6\ 3\ 24\ 19\ 23\ 20\ 7)(4\ 34\ 22\ 16\ 21\ 17\ 5\ 33) \\ (8\ 29\ 26\ 30\ 25\ 12\ 9\ 13)(10\ 32\ 28\ 14\ 27\ 15\ 11\ 31) \end{array} \}$$

and

$$X = \{ \begin{array}{l} 10001111111111110111000000000000, \\ 0010011111111111111101100000000000, \\ 0100101111111111111101100000000000, \\ 101100111111111111110100110000000000, \\ 01110101111111111111000101000000000, \\ 010101101111111111110101001000000000, \\ 100111001111111111110100011000000000, \\ 111011001111111111110001001100000000, \\ 0000010011111111111111011000000000, \\ 010111010111111111110100010100000000, \\ 1000000001111111111111111100000000, \\ 1001011010111111111101001010000000, \\ 0011011010011111111100100101000000 \end{array} \}.$$

The group G has degree 34, coordinates 1 and 18 are fixed and other coordinates are permuted transitively. The code generated by G from X has length 17, size 5632 and minimum distance 3.

3.2 Lower Bound $A_2(24, 4) \geq 327680$

Let

$$G = \left\{ \begin{array}{l} (1\ 7\ 33\ 3\ 5\ 35\ 26\ 32\ 10\ 28\ 30\ 12) \\ (2\ 8\ 34\ 4\ 6\ 36\ 25\ 31\ 9\ 27\ 29\ 11) \\ (13\ 19\ 45\ 15\ 17\ 47\ 38\ 44\ 22\ 40\ 42\ 24) \\ (14\ 20\ 46\ 16\ 18\ 48\ 37\ 43\ 21\ 39\ 41\ 23), \\ (1\ 35)(2\ 36)(3\ 9\ 27\ 33)(4\ 34\ 28\ 10) \\ (5\ 8)(6\ 7)(11\ 25)(12\ 26)(13\ 47)(14\ 48) \\ (15\ 21\ 39\ 45)(16\ 46\ 40\ 22)(17\ 20)(18\ 19) \\ (24\ 38)(29\ 32)(30\ 31)(41\ 44)(42\ 43) \end{array} \right\}$$

and

$$X = \left\{ \begin{array}{l} 00010111111111111111111111111111010000000000000000000, \\ 00000001011111111111111111111111110100000000000000000, \\ 00110010011111111111111111111100110110000000000000000, \\ 1100001001111111111111111100111101100000000000000000, \\ 010110010101111111111111110100110101000000000000000, \\ 101010010101111111111111110101011010100000000000000, \\ 1111110111110111111111111000000100000100000000000000, \\ 001001011111011111111111110110100000100000000000000, \\ 100101001111011111111111011010110000100000000000000, \\ 011000110111011111111111110011001000100000000000000, \\ 0101000001110111111111111101011111000100000000000000, \\ 110101010011011111111111100101010110010000000000000, \\ 111010010011011111111111000101101100100000000000000, \\ 101001000011011111111111010110111100100000000000000, \\ 10000101010101111111111111010101010000000000000000, \\ 0000000000010111111111111111111111010000000000000 \end{array} \right\}.$$

The group G consists of two copies of a transitive permutation group of degree 24. The code generated by G from X has length 24, size 327680 and minimum distance 4. Since $A_2(n-1, d) \geq A_2(n, d)/2$, we also get lower bounds $A_2(23, 4) \geq 163840$, $A_2(22, 4) \geq 81920$, and $A_2(21, 4) \geq 40960$.

3.3 Lower Bound $A_2(24, 10) \geq 136$

Let

$$G = \{ \begin{array}{l} (1\ 27\ 30\ 12)(2\ 28\ 31\ 10)(3\ 6\ 36\ 25) \\ (4\ 7\ 34\ 26)(5\ 8\ 35\ 33)(9\ 29\ 32\ 11) \\ (13\ 39\ 42\ 24)(14\ 40\ 43\ 22)(15\ 18\ 48\ 37) \\ (16\ 19\ 46\ 38)(17\ 20\ 47\ 45)(21\ 41\ 44\ 23), \\ (1\ 36\ 26\ 33\ 11\ 31)(2\ 9\ 35\ 7\ 25\ 12) \\ (3\ 4\ 6\ 29\ 10\ 32)(5\ 34\ 8\ 27\ 28\ 30) \\ (13\ 48\ 38\ 45\ 23\ 43)(14\ 21\ 47\ 19\ 37\ 24) \\ (15\ 16\ 18\ 41\ 22\ 44)(17\ 46\ 20\ 39\ 40\ 42) \end{array} \}$$

and

$$X = \{ \begin{array}{l} 10010101001000011111111011010101101111000000000, \\ 001000101000100010011111110111010111011101100000, \\ 010011100100110011101111101100011011001100010000, \\ 000110101111000110101111111001010000111001010000, \\ 0010101100101011001001111110101001101010011011000, \\ 010010111001011101101101101101000110100010010010 \end{array} \}.$$

The group G consists of two copies of a transitive permutation group of degree 24. The code generated by G from X has length 24, size 136 and minimum distance 10.

3.4 Lower Bound $A_2(25, 6) \geq 17920$

Let

$$G = \{ \begin{array}{l} (1\ 26)(2\ 25)(3\ 4\ 27\ 28)(5\ 30\ 29\ 6) \\ (7\ 32)(8\ 31)(9\ 12\ 33\ 36)(10\ 35)(11\ 34) \\ (13\ 38)(14\ 37)(15\ 16\ 39\ 40)(17\ 42\ 41\ 18) \\ (19\ 44)(20\ 43)(21\ 24\ 45\ 48)(22\ 47)(23\ 46), \\ (1\ 31\ 12\ 25\ 7\ 36)(2\ 29\ 35)(3\ 32\ 10\ 27\ 8\ 34) \\ (4\ 6\ 33\ 28\ 30\ 9)(5\ 11\ 26)(13\ 43\ 24\ 37\ 19\ 48) \\ (14\ 41\ 47)(15\ 44\ 22\ 39\ 20\ 46) \\ (16\ 18\ 45\ 40\ 42\ 21)(17\ 23\ 38) \end{array} \}$$

and

$$X = \{ \begin{array}{l} 0001100001001111111111111111001111011000000000000, \\ 000110111101001111111111111110010000101100000000000, \\ 010011001001011111111111111101100110110100000000000, \\ 001101001110011111111111111100101100011000000000000, \\ 001001010110110111111111111101101010010010000000000, \\ 00000111100001111111111111111100001111000000000000, \\ 00001011001011011111111111111010011010010000000000, \\ 1011101111101111111111111111010001000001000000000000, \\ 1011011101110011111111111110100100010001100000000000, \\ 111001000010001111111111100011011110111100000000000, \\ 11111000011101111111111110000011110001000000000000, \\ 11001011000101111111111110011010011101000000000000, \\ 11001000101111011111111110011011101000010000000000, \\ 11110100110111011111111110000101100100010000000000, \\ 1101101001101101111111111001001011001001000000000 \}. \end{array}$$

The group G consists of two copies of a transitive permutation group of degree 24. The code generated by G from X has length 24, size 17920 and minimum distance 5.

References

- [1] M. Best, A. Brouwer, F. J. MacWilliams, A. M. Odlyzko, and N. J. A. Sloane. Bounds for binary codes of length less than 25. *IEEE Transactions on Information Theory*, 24(1):81–93, 1978.
- [2] S. Niskanen and P. R. J. Östergård. Cliquer User’s Guide, Version 1.0. Communications Laboratory, Helsinki University of Technology, Espoo, Finland, Tech. Rep. T48, 2003.
- [3] J. J. Cannon and D. F. Holt. The transitive permutation groups of degree 32. *Experimental Mathematics*, 17(3):307–314, 2008.
- [4] A. Huplke. Constructing transitive permutation groups. *Journal of Symbolic Computation*, 39(1):1–30, 2005.
- [5] GAP – Groups, Algorithms, Programming – a System for Computational Discrete Algebra, <http://www.gap-system.org/>
- [6] G. Cohen, I. Honkala, S. Litsyn, and A. Lobstein. *Covering codes*, North-Holland Mathematical Library, 1997.

- [7] P. R. J. Östergård and M. K. Kaikkonen. New single-error-correcting codes. *IEEE Transactions on Information Theory*, 42(4):1261–1262, 1996.