LEARNING ARBITRARY SUM-PRODUCT NETWORK LEAVES WITH EXPECTATION-MAXIMIZATION*

Mattia Desana^{1†} and Christoph Schnörr^{1,2}.

¹Heidelberg Collaboratory for Image Processing (HCI) ²Image and Pattern Analysis Group (IPA) Heidelberg University, Germany

Abstract

Sum-Product Networks with complex probability distribution at the leaves have been shown to be powerful tractable-inference probabilistic models. However, while learning the internal parameters has been amply studied, learning complex leaf distribution is an open problem with only few results available in special cases. In this paper we derive an efficient method to learn a very large class of leaf distributions with Expectation-Maximization. The EM updates have the form of simple weighted maximum likelihood problems, allowing to use any distribution that can be learned with maximum likelihood, even approximately. The algorithm has cost linear in the model size and converges even if only partial optimizations are performed. We demonstrate this approach with experiments on twenty real-life datasets for density estimation, using tree graphical models as leaves. Our model outperforms state-of-the-art methods for parameter learning despite using SPNs with much fewer parameters.

1 Introduction

Sum-Product Networks (SPNs, [Poon and Domingos, 2011]) are recently introduced probabilistic models that possess two crucial characteristics: firstly, inference in a SPN is always tractable; secondly, SPN enable to model tractably a larger class of distributions than for Graphical Models because they can model efficiently context specific dependences and determinism ([Boutilier et al., 1996]). Due to their ability to use exact inference in complex distributions SPNs are state-of-the-art models in density estimation (see e.g. [Gens and Domingos, 2013, Rahman and Gogate, 2016b]) and have been successfully used in computer vision ([Cheng et al., 2014], [Peharz et al., 2014], [Amer and Todorovic., 2015]).

SPNs are modelled by a directed acyclic graph with two sets of parameters: edge coefficients at internal sum nodes and probabilistic distributions at the leaves. Most SPN models use very simple leaf models in form of indicator variables. However, using leaf distributions with complex structure allows to create SPNs with high modelling power and flexibility, as shown for instance in [Rahman and Gogate, 2016a] using tree graphical models as leaves and in [Amer and Todorovic., 2015] using Bag-of-Words (example: fig. 1). While there are several methods to learn edge coefficients ([Gens and Domingos, 2012, Zhao et al., 2016b, Zhao et al., 2016a]), learning the leaf distribution parameters is still an open problem in the general case. The only method we are aware of is [Peharz et al., 2016], which works for the special case of univariate distribution in the exponential family (although the authors suggest it can be extended to the multivariate case).

The goal of this paper is to learn leaf distributions with complex structure in a principled way. To do so, we obtain a novel derivation of Expectation-Maximization for SPNs that allows to cover leaf distribution updates (section 4). The first step in this derivation is providing a new theoretical result relating the SPN and a subset of its encoded mixture (Proposition 2 in the following). Exploiting this new result EM for SPN leaves assumes the form of a *weighted maximum likelihood* problem, which is a slight modification of standard maximum likelihood and is well studied for a wide class of distributions. The algorithm has computational cost *linear* in the number of SPN edges.

^{*}Support of the German Science Foundation, grant GRK 1653, is gratefully acknowledged.

[†]Corresponding author. Email: mattia.desana@iwr.uni-heidelberg.de.



Figure 1: An example SPN with complex leaf distributions (in this case, probabilistic graphical models).

Convergence of the algorithm is guaranteed as long as the maximization is even *partially* performed. Therefore, any distribution where at least an approximate log-likelihood maximization method is available can be used as SPN leaf. This result allows to use a *very wide* family of leaf distributions and train them efficiently and straightforwardly. Particularly nice results hold when leaves belong to the exponential family, where the M-step has a single optimum and the maximization can often be performed efficiently in closed form.

To test the potential advantages of training complex leaves we perform experiments on a set of twenty widely used datasets for density estimation, using a SPN with tree graphical models as leaf distributions (section 6). We show that a simple SPN with tree graphical model leaves learned with EM state-of-theart methods for parameter learning while using much smaller models. These results suggests that much of the complexity of the SPN structure can be encoded in complex, trainable leaves rather than in a large number of edges, which is a promising direction for future research.

2 Sum-Product Networks

We start with the definition of SPN based on [Gens and Domingos, 2013]. Let X be a set of random variables, either continuous or discrete.

Definition 1. Sum-Product Network (SPN) :

- 1. A tractable distribution $\varphi(X)$ is a SPN S(X).
- 2. The product $\prod_k S_k(X_k)$ of SPNs $S_k(X_k)$ is a SPN $S(\bigcup_k X_k)$ if all sets X_k are disjoint.
- 3. The weighted sum $\sum_k w_k S_k(X)$ of SPNs $S_k(X)$ is a SPN S(X) if the weights $w_k \in \mathbb{R}$ are nonnegative (notice that X is in common for each SPN S_k).

By associating a node to each product, sum and tractable distribution and adding edges between an operator and its inputs, a SPN can be represented as a rooted Directed Acyclic Graph (DAG) $\mathcal{G}(\mathcal{V}, \mathcal{E})$ with sums and products as internal nodes and tractable distributions as leaves (example: fig. 2). This definition generalizes SPNs with indicator variables as leaves, since indicator variables are a special case of discrete distribution where the probability mass completely lies on a single variable state. A SPN is *normalized* if weights of outgoing edges of sum nodes sum to 1: $\sum_k w_k = 1$. We consider *only normalized SPNs*, without loss of generality ([Peharz, 2015]).

Notation. We use the following notation throughout the paper. Let X be a set of variables (either continuous or discrete depending on the context) and let x be an assignment of these variables. $S_q(X_q)$ denotes the sub-SPN rooted at a node q of S, with $X_q \subseteq X$. S(x) denotes the evaluation of S with assignment x (see below), and $\frac{\partial S(x)}{\partial S_q}$ is the derivative of S(x) w.r.t. node q. The term $\varphi_l(X_l)$ denotes the distribution of leaf node l. ch(q) and pa(q) denote the children and parents of q respectively, and



Figure 2: A SPN S(A, B) in which a subnetwork σ_c of S is highlighted. This subnetwork corresponds to a coefficient $\lambda_c = w_2^1 w_9^4$ and component $P_c(A, B) = \varphi_7(B) \varphi_9(A)$.

(q, i) indicates an edge between q and its child i, associated to a weight w_i^q if q is a sum node. Finally, let $\mathcal{E}(S)$, $\mathcal{V}(S)$ and $\mathcal{L}(S)$ denote respectively the set of edges, nodes and leaves in S.

Parameters. Let W denote the set of sum node weights and let θ denote the set of parameters governing the leaf distributions. We write $S(X|W,\theta)$ to explicitly express dependency of S on these parameters. Each leaf distribution φ_l is associated to a parameter set $\theta_l \subseteq \theta$. For instance, θ_l contains mean and covariance for Gaussian leaves, and tree structure and potentials for tree graphical model leaves.

Evaluation. The evaluation of S(X) for evidence x, written S(x), proceeds by first evaluating the leaf distributions with assignment x, then evaluating each internal node from the leaves to root and taking the value of the root. Evaluating any valid SPN corresponds to evaluating a probability distribution ([Poon and Domingos, 2011]). Computing S(x), the partition function and the quantities $S_q(x)$ and $\frac{\partial S(x)}{\partial S_q}$ for *each* node in S requires performing a single up-and-down pass over all network nodes and has a $O(|\mathcal{E}|)$ time and memory cost ([Poon and Domingos, 2011]).

3 SPNs as Mixture Models

This section discusses the interpretation of SPNs as a mixture model derived in [Dennis and Ventura, 2015] and [Zhao et al., 2016b], on which we will base our derivation of EM.

Definition 2. A subnetwork σ_c of S is a SPN constructed by first including the root of S in σ_c , then processing each node q included in σ_c as follows:

- 1. If q is a sum node, include in σ_c one child $i \in ch(q)$ with relative weight w_i^q . Process the included child.
- 2. If q is a product node, include in σ_c all the children ch(q). Process the included children.
- 3. If q is a leaf node, do nothing.

Example: fig. 2. Any subnetwork is a tree. Let $C = \sigma_1, \sigma_2, ..., \sigma_C$ be the number of different subnetworks obtainable from S for different choices of included sum node children. The number of subnetworks C can be exponentially larger than the number of edges $|\mathcal{E}|$.

Definition 3. For a subnetwork σ_c of $S(X|W, \theta)$ we define a mixture coefficient $\lambda_c = \prod_{(q,j) \in \mathcal{E}(\sigma_c)} w_j^q$ and a mixture component $P_c(X|\theta) = \prod_{l \in \mathcal{L}(\sigma_c)} \varphi_l(X_l|\theta_l)$.

Note that mixture coefficients are products of sum weights and mixture components are products of leaves in σ_c (fig. 2).

Proposition 1. $S|W, \theta(X)$ represents the following mixture model:

$$S(X|W,\theta) = \sum_{c=1}^{C} \lambda_c(W) P_c(X|\theta)$$
(1)

Proof: see [Dennis and Ventura, 2015]. Notice that since $C \gg |\mathcal{E}|$, it follows that a SPN encodes a mixture which can be intractably large if explicitly represented.

We now introduce a *new result* that is crucial for our derivation of EM, reporting it here rather than in the proofs section since it contributes to the set of analytical tools for SPNs.



Figure 3: Visualization of Proposition 2. The colored part is the set of edges traversed by all subnetworks crossing (q, i). The blue part represents S_i and the red part $\frac{\partial S(X)}{\partial S_q}$.

Proposition 2. Consider a SPN S(X), a sum node $q \in S$ and a node $i \in ch(q)$. The following relation holds:

$$\sum_{k:(q,i)\in\mathcal{E}(\sigma_k)}\lambda_k P_k\left(X\right) = w_i^q \frac{\partial S\left(X\right)}{\partial S_q} S_i\left(X\right)$$
(2)

where $\sum_{k:(q,i)\in \mathcal{E}(\sigma_k)}$ denotes the sum over all the subnetworks σ_k of S that include the edge (q,i).

Proof: in Appendix A.1. This result states that the value of each sub-mixture composed by all the subnetworks crossing (q, i), which has potentially intractable large size, can be evaluated in constant time after having evaluated and derivated S(x) once. This results is crucial in the derivation of EM (Appendix A) where we need to evaluate such subsets of solutions repeatedly. Note also that $\sum_{k:(q,i)\in \mathcal{E}(\sigma_k)} \lambda_k P_k(X)$ corresponds to the evaluation of a non-normalized SPN which is a subset of S - e.g. the colored part in fig. 3.

4 Expectation Maximization

In this section we obtain a novel derivation of Expectation-Maximization for SPNs by directly applying EM for mixture models to the exponentially large mixture encoded by a SPNs exploiting Proposition 2. We obtain a procedure to learn SPNs with a broad class of leaf distributions, and show that the algorithm converges under mild conditions.

Expectation Maximization is an elegant and widely used method for finding maximum likelihood solutions for models with latent variables (see e.g. [Murphy, 2012, 11.4]). Given a distribution $P(X) = \sum_{c=1}^{C} P(X, c|\pi)$ where c are latent variables and π are the distribution parameters our objective is to maximize the log likelihood $\sum_{n=1}^{N} \ln \sum_{c=1}^{C} P(x_n, c|\pi)$ over a dataset of observations $\{x_1, x_2, ..., x_N\}$. EM proceeds by updating the parameters iteratively starting from some initial configuration π_{old} . An update step consists in finding $\pi^* = \arg \max_{\pi} Q(\pi | \pi_{old})$, where

$$Q(\pi | \pi_{old}) = \sum_{n=1}^{N} \sum_{c=1}^{C} P(c | x_n, \pi_{old}) \ln P(c, x_n | \pi).$$

We want to apply EM to the mixture encoded by a SPN, which is in principle intractably large. First, using the relation between SPN and encoded mixture model in Proposition 1 we identify

$$P(c, x_n | \pi) = \lambda_c (W) P_c (x_n | \theta),$$

$$P(x_n | \pi_{old}) = S (x_n | W_{old}, \theta_{old}),$$

therefore:

$$P(c|x_n, \pi_{old}) = P(c, x_n | \pi_{old}) / P(x_n | \pi_{old}) = \lambda_c \left(W_{old} \right) P_c \left(x_n | \theta_{old} \right) / S \left(x_n | W_{old}, \theta_{old} \right).$$

Applying these substitutions and dropping the dependency on W_{old} , θ_{old} for compactness, $Q(W, \theta | W_{old}, \theta_{old})$ becomes:

$$Q(W,\theta) = \sum_{n=1}^{N} \sum_{c=1}^{C} \frac{\lambda_c P_c(x_n)}{S(x_n)} \ln \lambda_c(W) P_c(x_n|\theta)$$
(3)

which we maximize for W and θ in the following sections.

4.1 Edge Weights Update

We begin with EM updates for weights. Simplifying $Q(W, \theta)$ through the use of Proposition 2 (Appendix A.2) the objective function for W becomes:

$$W^* = \arg\max_{W} Q_W(W) \tag{4}$$

$$Q_W(W) = \sum_{q \in \mathcal{N}(S)} \sum_{i \in ch(q)} \beta_i^q \ln w_i^q$$

$$\beta_i^q = w_i^q - \sum_{i \in ch(q)}^N S_i(x_i)^{-1} \frac{\partial S(x_i)}{\partial S(x_i)} S_i(x_i)$$
(5)

$$\beta_i^q = w_{i,old}^q \sum_{n=1}^N S(x_n)^{-1} \frac{\partial S(x_n)}{\partial S_q} S_i(x_n)$$

The evaluation of terms β_i^q , which depend only on W_{old} , θ_{old} and are therefore constants in the optimization, is the *E step* of the EM algorithm. We now maximize $Q_W(W)$ subject to $\sum_i w_i^q = 1 \forall q \in \mathcal{N}(S)$ (*M step*).

Non shared weights. If weights at each node q are disjoint, then we can move the max inside the sum, obtaining separated maximizations each in the form $\arg \max_{w^q} \sum_{i \in ch(q)} \beta_i^q \ln w_i^q$, where w^q is the set of weights outgoing from q. Now, the same maximum is attained multiplying by $k = \frac{1}{\sum_i \beta_i^q}$. Then, defining $\bar{\beta}_i^q = k\beta_i^q$, we can equivalently find $\arg \max_{w^q} \sum_{i \in ch(q)} \bar{\beta}_i^q \ln w_i^q$, where $\bar{\beta}_i^q$ is positive and sums to 1 and therefore can be interpreted as a discrete distribution. This is then the maximum of the cross entropy $\arg \max_{w^q} \left(-\mathbb{H}\left(\bar{\beta}_i^q, w_i^q\right)\right)$ defined e.g. in [Murphy, 2012, 2.8.2], attained for $w_i^q = \bar{\beta}_i^q$, which corresponds to the following update:

$$w_j^{q*} = \beta_j^q / \sum_i \beta_i^q.$$
(6)

This is the same weight update obtained with radically different approaches in [Peharz et al., 2016, Zhao et al., 2016b].

Shared weights. Our derivation of weights updates allows a straightforward extension to the case of shared-weights nodes. Weights shared between different sum nodes appear for instance in convolutional SPNs (see e.g. [Cheng et al., 2014]). To keep notation simple let us consider only two nodes q_1, q_2 constrained to share weights, that is $w_i^{q_1} = w_i^{q_2} = \hat{w}$ for every child *i*, where \hat{w} is the set of shared weights. We then rewrite $Q_W(W)$ insulating the part depending on \hat{w} as $Q_W(W) = \sum_{i \in ch(q)} \beta_i^{q_1} \ln w_i^{q_1} + \sum_{i \in ch(q)} \beta_i^{q_2} \ln w_i^{q_2} + const$ (the constant includes terms not depending on w^q). Then, employing the weight sharing constraint, maximization of Q_W for \hat{w} becomes $\arg \max_{\hat{w}} \sum_{i \in ch(q)} (\beta_i^{q_1} + \beta_i^{q_2}) \ln \hat{w}$. As in the non-shared case, we end up maximizing the cross entropy $-\mathbb{H}(k(\beta_i^{q_1} + \beta_i^{q_2}), \hat{w}_i)$. Generalizing for an arbitrary set of nodes D such that any node $q \in D$ has shared weights \hat{w} , the weight update for \hat{w} is as follows:

$$\hat{w}_j^* = \frac{\sum_{q \in D} \beta_j^q}{\sum_i \sum_{q \in D} \beta_i^q}.$$
(7)

4.2 Leaf Distribution Updates

We now consider learning leaf distributions. Simplifying $Q(W, \theta)$ through the use of Proposition 2 (Appendix A.3), the objective function for θ becomes:

$$\theta^* = \arg\max_{\theta} Q_{\theta}\left(\theta\right) \tag{8}$$

$$Q_{\theta}(\theta) = \sum_{l \in \mathcal{L}(S)} \sum_{n=1}^{N} \alpha_{ln} \ln \varphi_l(x_n | \theta_l)$$

$$\alpha_{ln} = S(x_n)^{-1} \frac{\partial S(x_n)}{\partial S_l} S_l(x_n)$$
(9)

The evaluation of terms α_{ln} , which are constant coefficients in the optimization since they depend only on W_{old} , θ_{old} , is the *E* step and can be seen as computing the *responsibility* that leaf distribution φ_l assigns to the *n*-th data point, just as in EM for classical mixture models. Importantly, we note that the maximization eq. 8 is *concave* as long as $\ln \varphi_l (X_l | \theta)$ is concave, in which case there is an *unique* global optimum. Also note that normalizing α_l in eq. 9 dividing each α_{ln} by $\sum_n \alpha_{ln}$ we attain the same maximum and avoid numerical problems due to very small values.

Non shared parameters. Introducing the hypothesis that parameters θ_l are disjoint at each leaf l, we obtain separate maximizations in the form:

$$\theta_l^* = \arg \max_{\theta_l} \sum_{n=1}^N \alpha_{ln} \ln \varphi_l \left(x_n | \theta_l \right)$$
(10)

In this formulation one can recognize a *weighted maximum likelihood* problem, where each data sample n is weighted by a soft-count coefficient α_{ln} .

Shared parameters. Let us consider two leaf nodes k, j associated to distributions $\varphi_k(X_k|\theta_k), \varphi_j(X_j|\theta_j)$ respectively, such that $\theta_k = \theta_j = \hat{\theta}$ are shared parameters. Eq. 8 for k, j becomes

$$Q_{\theta}(\theta) = \sum_{n=1}^{N} \alpha_{kn} \ln \varphi_k(x_n | \hat{\theta}) + \sum_{n=1}^{N} \alpha_{jn} \ln \varphi_j(x_n | \hat{\theta}) + const(\hat{\theta})$$

Generalizing to an arbitrary set of leaves D such that each leaf $l \in D$ has a distribution $\varphi X_l | \theta$ and dropping the constant term, we obtain:

$$\hat{\theta}^* = \arg\max_{\hat{\theta}} \sum_{l \in D} \left(\sum_{n=1}^N \alpha_{ln} \ln \varphi_l(x_n | \hat{\theta}) \right).$$
(11)

The objective function now contains a sum of logarithms, therefore it cannot be maximized as separate problems over each leaf as in the non shared case. However, it is still *concave* in θ as long as $\ln \varphi_l (X_l | \theta)$ is concave, in which case there is an *unique global optimum* (this holds for exponential families, discussed next). Then, the optimal solution can be found with iterative methods such as gradient descent or second order methods.

Exponential Family Leaves. For distributions in the exponential family eq. 8 is *concave* and therefore a *global optimum* can be reached (see e.g. [Murphy, 2012, 11.3.2]). Additionally, the solution is often available efficiently in *closed form*. Let us consider two relevant examples. If $\varphi_l(X_l)$ is a *multivariate Gaussian* $\mathcal{N}(\mu_l, \Sigma_l)$, the solution of eq. 10 is obtained e.g. in [Murphy, 2012, 11.4.2] as $r_l = \sum_{n=1}^{N} \alpha_{ln}$, $\mu_l = \frac{\sum_{n=1}^{N} \alpha_{ln} x_n}{r_l}$ and $\Sigma_l = \frac{\sum_{n=1}^{N} \alpha_{ln} (x_n - \mu_l)(x_n - \mu_l)^T}{r_l}$. In this case, EM for SPNs generalizes EM for Gaussian mixture models. If $\varphi_l(X_l)$ is a *tree graphical model* over discrete variables, the solution of eq. 10 can be found with the Chow-Liu algorithm ([Chow and Liu, 1968]) adapted for weighted likelihood (see [Meila and Jordan, 2000]). The algorithm has a cost quadratic on the cardinality of X and allows to learn jointly the optimal tree structure and potentials.

5 Convergence for General Leaf Distributions

The EM algorithm proceeds by iterating E-and-M steps (pseudocode in Algorithm 2) until convergence. The training set log-likelihood is guaranteed not to decrease at each step as long as the M-step maximization can be done at least partially [Neal and Hinton, 1998]: namely, calling $\theta_{l,new}$ and $\theta_{l,old}$ the current and previous parameters of leaf *l*, this implies EM *converges* if the update at each leaf satisfies:

$$\sum_{n=1}^{N} \alpha_{ln} \ln \varphi_l \left(x_n | \theta_{l,new} \right) \ge \sum_{n=1}^{N} \alpha_{ln} \ln \varphi_l \left(x_n | \theta_{l,old} \right)$$
(12)

This condition is very non-constraining, as it simply requires that weighted log-likelihood can be at least approximately optimized. Note that weighted log-likelihood maximization requires minor modifications from standard maximum-likelihood. If approximate methods are used, a simple check on bound (12) ensures that the approximate learning procedure did not decrease the lower bound (Algorithm 2 row 8).

This allows a very *broad family* of distributions to be used as leaves: for instance, approximate maximum likelihood methods are available for intractable graphical models ([Wainwright and Jordan, 2008]), probabilistic Neural Networks ([?]), probabilistic Support Vector Machines ([Platt, 1999]) and several non parametric models (see e.g. [Geman and Hwang, 1982] and [Cule et al., 2010]). EM leaf distribution updates can be straightforwardly applied to each of these models. Note that depending on the tractability of the leaf distribution, some operations might not be tractable (e.q. exact marginalization in general graphical models) - whether to use certain distributions as leaves depends on the kind of queries one needs to answer and it is an application specific decision.

Cost. All the quantities required in a EM updates can be computed with a single forward-downward pass on the SPN, thus an EM iteration has cost *linear in the number of edges*. The cost of the maximization for each leaf depends on the leaf type, and it is an application specific problem. For instance, with Gaussian and tree graphical model leaves it is linear in the number of samples.

Algorithm 1 Compute α, β ($S, \{x_1, x_2, ..., \overline{x_N}\}$)

- 1: Input: SPN $S(W, \theta)$, samples $\{x_1, x_2, ..., x_N\}$
- 2: set $\beta_i^q = 0$ for each $(q, i) \in \mathcal{E}(S)$

3: for each sum node q in S and each node $i \in ch(q)$ do

```
4: for each leaf node l in S do
```

5: $\alpha_{ln} \leftarrow S(x_n)^{-1} \frac{\partial S(x_n)}{\partial S_l} S_l(x_n)$

6 Empirical Evaluation

The aim of this section is to evaluate the potential advantages of learning the parameters of complex leaf distributions in a density estimation setting.

Setup. As leaf distribution of choice we take tree graphical models in which the M-step can be solved exactly (section 4.2). First we need to fix the SPN structure. In order to keep the focus on parameter learning rather than structure learning we chose to use the simplest structure learning algorithm (Learn-SPN, [Gens and Domingos, 2013]), and augment it to use tree leaves by simply adding a fixed number of tree leaves to each generated sum node q. The tree leaves are initialized as a mixture model over the data that was used to learn the subnetwork rooted in q (see [Gens and Domingos, 2013] for details). To

```
Algorithm 2 EMstep(S, {x_1, x_2, ..., x_N})
```

- 1: Input: SPN $S(W, \theta)$, samples $\{x_1, x_2, ..., x_N\}$
- 2: $[\alpha, \beta] \leftarrow \text{Compute } \alpha, \beta (S, \{x_1, ..., x_N\})$
- 3: for each sum node q in S and each node $i \in ch(q)$ do
- 4: $w_i^q \leftarrow \beta_i^q / \sum_{i \in ch(q)} \beta_i^q$
- 5: for each leaf node l in S do
- 6: $\theta_l \leftarrow \arg \max_{\theta_l} \sum_{n=1}^N \alpha_{ln} \ln \varphi_l (x_n | \theta_l)$
- 7: if eq. 12 is not satisfied, discard the update

			Test LL			#edges	
Dataset	Nvars	train	TreeSPN	CCCP	CVI	TreeSPN	CCCP
NLTCS	16	16181	-6.01	-6.03	-6.08	2K	14K
MSNBC	17	291326	-6.04	-6.05	-6.29	13K	55K
KDDCup2K	64	180092	-2.14	-2.13	-2.14	50K	48K
Plants	69	17412	-12.30	-12.87	-12.86	60K	133K
Audio	100	15000	-39.76	-40.02	-40.6	93K	740K
Jester	100	9000	-52.59	-52.88	-53.84	93K	314K
Netflix	100	15000	-56.12	-56.78	-57.96	94K	162K
Accidents	111	12758	-29.86	-27.70	-29.55	100K	205K
Retail	135	22041	-10.95	-10.92	-10.91	116K	57K
Pumsb-star	163	12262	-23.71	-24.23	-25.93	105K	140K
DNA	180	1600	-79.90	-84.92	-86.73	167K	108K
Kosarek	190	33375	-10.75	-10.88	-10.70	149K	203K
MSWeb	294	29441	-10.03	-9.97	-9.89	186K	69K
Book	500	8700	-34.68	-35.01	-34.44	434K	191K
EachMovie	500	4524	-55.42	-52.56	-52.63	339K	523K
WebKB	839	2803	-167.8	-157.5	-161.5	713K	1.44M
Reuters-52	889	6532	-91.69	-84.63	-85.45	604K	2.21M
20Newsgrp.	910	11293	-156.8	-153.2	-155.6	848K	14.6M
BBC	1058	1670	-266.3	-248.6	-251.2	881K	1.88M
Ad	1556	2461	-16.88	-27.20	-19.00	364K	4.13M
#Wins/TotSize			11	8	1	5.41M	27.1M

Table 1: Experimental results. Note that TreeSPN performs better (11 wins) than both CCCP (9 wins) and CVI (1 win) while using much smaller SPNs (5.4M vs. 27M total edges).

keep the models small and the structure simple, we limit the depth to a fixed value. The number of added trees and the maximum depth are hyperparameters.

Methodology. We evaluate the model on 20 real-life datasets for density estimation, whose structure is described in table 1 (see [Gens and Domingos, 2013]). These datasets are binary, with a number of variables ranging from 16 to 1556, and have been widely used as benchmark for density estimation (e.g. in [Lowd and Domingos, 2012], [Gens and Domingos, 2013], [Rooshenas and Lowd, 2014], [Rahman and Gogate, 2016a]). We select the hyperparameters (described in [Gens and Domingos, 2013] for details) performing a grid search over independence thresholds (values $\{0.1, 0.01, 0.001\}$), number of tree leaves attached to sum nodes ($\{5, 20, 30\}$), and maximum depth 2, 4, 6. We train W, θ with EM until validation log-likelihood convergence.

Results. We compare against two state-of-the-art parameter learning methods: *Concave-Convex Procedure* (CCCP, [Zhao et al., 2016b]) and *Collapsed Variational Inference* (CVI, [Zhao et al., 2016a]) which employ LearnSPN for structure learning (like us, but without depth limit) then re-learn the edge parameters of the resulting SPN. The results of this experiment are shown in table 1. To perform a fair comparison, we also plot the network size as the number of edges in the network (table 1), and for each tree leaf node we also add to this count the number of edges which would be needed to represent the tree as a SPN. Our algorithm (column TreeSPN) *outperforms* CCCP and CVI in the majority of cases, despite the network size being *much smaller* (total number of edges is 5.41M vs. 27.1M). These results indicates that it can be convenient to use computational resources for modelling SPNs with complex structured leaves, learned with EM, rather than in just increasing the number of SPN edges. This new aspect should be explored in future work.

7 Conclusions

In this paper we derived the first parameter learning procedure for SPNs which allows to train jointly edge weights and a wide class of complex leaf distributions. Learning the leaf models corresponds to fitting models with weighted maximum, and the algorithm converges if this optimization is even partially performed. Experimental results on 20 datasets for density estimation showed that using complex SPN leaves trained with EM produced better results than state-of-the-art edge weights learning methods for

SPNs while using much smaller models, suggesting that learning complex SPN leaves is a promising direction for future research.

A Proofs

Preliminars. Consider some subnetwork σ_c of S including the edge (q, i) (fig. 3). Remembering that σ_c is a tree, we divide σ_c in three disjoint subgraphs: the edge (q, i), the tree $\sigma_{h(c)}^{d(i)}$ corresponding to "descendants" of i, and the remaining tree $\sigma_{g(c)}^{a(q)}$. Notice that g(c) could be the same for two different subnetworks σ_1 and σ_2 , meaning that the subtree $\sigma_{g(c)}^{a(q)}$ is in common (similarly for $\sigma_{h(c)}^{d(i)}$). We now observe that the the coefficient λ_c and component P_c (def. 3) factorize in terms corresponding to $\sigma_{g(c)}^{a(q)}$ and to $\sigma_{h(c)}^{d(i)}$ as follows: $\lambda_c = w_i^q \lambda_{h(c)}^{d(i)} \lambda_{g(c)}^{a(q)}$ and $P_c = P_{h(c)}^{d(i)} P_{g(c)}^{a(q)}$, where $\lambda_{h(c)}^{d(i)} = \prod_{(m,n) \in \mathcal{L}(\sigma_{h(c)}^{d(i)})} \varphi_l$ and similarly for a(q). With this notation, for *each* subnetwork σ_c including (q, i) we write:

$$\lambda_c P_c = w_i^q \left(\lambda_{g(c)}^{a(q)} P_{g(c)}^{a(q)} \right) \left(\lambda_{h(c)}^{d(i)} P_{h(c)}^{d(i)} \right)$$
(13)

Let us now consider the sum over *all* the subnetworks σ_c of S that include (q, i). The sum can be rewritten as two nested sums, the external one over all terms $\sigma_g^{a(q)}$ (red part, fig. 3) and the internal one over all subnets $\sigma_h^{d(i)}$ (blue part, fig. 3). This is intuitively easy to grasp: we can think of the sum over all trees σ_c as first keeping the subtree $\sigma_g^{a(q)}$ fixed and varying all possible subtrees $\sigma_h^{d(i)}$ below *i* (inner sum), then iterating this for choice of $\sigma_g^{a(q)}$ (outer sum). Exploiting the factorization 13 we obtain the following:

$$\sum_{c:(q,i)\in\mathcal{E}(\sigma_c)}\lambda_c P_c = w_i^q \sum_{g=1}^{C_{a(q)}} \lambda_g^{a(q)} P_g^{a(q)} \sum_{h=1}^{C_{d(i)}} \lambda_h^{d(i)} P_h^{d(i)}$$
(14)

where $C_{d(i)}$ and $C_{a(q)}$ denote the total number of different trees $\sigma_h^{d(i)}$ and $\sigma_g^{a(q)}$ in S.

Lemma 1. $\frac{\partial S(X)}{\partial S_q} = \sum_{g=1}^{C_{a(q)}} \lambda_g^{a(q)} P_g^{a(q)}$.

Proof. First let us separate the sum in eq. 1 in two sums, one over subnetworks including q and one over subnetworks not including q: $S(X) = \sum_{k:q\in\sigma_k} \lambda_k P_k + \sum_{l:q\notin\sigma_l} \lambda_l P_l$. The second sum does not involve node q so for $\frac{\partial S(X)}{\partial S_q}$ it is a constant \hat{k} . Then, $S = \sum_{k:q\in\sigma_k} \lambda_k P_k + \hat{k}$. As in eq. 14, we divide the sum $\sum_{k:q\in\sigma_k} (\cdot)$ in two nested sums acting over disjoint terms:

$$S = \left(\sum_{g=1}^{C_{a(q)}} \lambda_g^{a(q)} P_g^{a(q)}\right) \left(\sum_{h=1}^{C_{d(q)}} \lambda_h^{d(q)} P_h^{d(q)}\right) + \hat{k}$$

. We now notice that $\sum_{k=1}^{C_{d(q)}} \lambda_k^{d(q)} P_k^{d(q)} = S_q$ by Proposition 1, since $\lambda_k^{d(q)} P_k^{d(q)}$ refer to the subtree of σ_c rooted in i and the sum is taken over all such subtrees. Therefore: $S = \left(\sum_{g=1}^{C_{a(q)}} \lambda_g^{a(q)} P_g^{a(q)}\right) S_q + \hat{k}$. Taking the partial derivative leads to the result.

A.1 Proof of Proposition 2

We start by writing the sum on the left-hand side of eq. 2 as in eq. 14. Now, first we notice that $\sum_{k=1}^{C_{d(i)}} \lambda_k^{d(i)} P_k^{d(i)}$ equals $S_i(X)$ by Proposition 1, since $\lambda_k^{d(i)} P_k^{d(i)}$ refer to the subtree of σ_c rooted in *i* and the sum is taken over all such subtrees. Second, $\sum_{g=1}^{C_{a(q)}} \lambda_g^{a(q)} P_g^{a(q)} = \frac{\partial S(X)}{\partial S_q}$ for Lemma 1. Substituting in 14 we get the result.

A.2 M-step for Edge Weights

Starting from eq. 3 and collecting terms not depending on W in a constant, we obtain:

$$Q(W) = \sum_{n=1}^{N} \sum_{c=1}^{C} \frac{\lambda_c P_c(x_n)}{S(x_n)} \ln \lambda_c(W) + \text{const}$$
$$= \sum_{n=1}^{N} \sum_{c=1}^{C} \frac{\lambda_c P_c(x_n)}{S(x_n)} \sum_{(q,i) \in \mathcal{E}(\sigma_c)} \ln w_i^q + \text{const}$$

We now drop the constant and move out $\sum_{(q,i)\in\mathcal{E}(\sigma_c)}$ by introducing $\delta_{(q,i),c}$ s.t. $\delta_{(q,i),c} = 1$ if $(q,i) \in \mathcal{E}(\sigma_c)$ and 0 otherwise and summing over *all* edges $\mathcal{E}(S)$:

$$Q(W) = \sum_{n=1}^{N} \sum_{c=1}^{C} \frac{\lambda_c P_c(x_n)}{S(x_n)} \sum_{(q,i) \in \mathcal{E}(S)} \ln w_i^q \delta_{(q,i),c}$$
$$= \sum_{(q,i) \in \mathcal{E}(S)} \sum_{n=1}^{N} \frac{\sum_{c=1}^{C} \lambda_c P_c(x_n) \delta_{(q,i),c}}{S(x_n)} \ln w_i^q$$
$$= \sum_{(q,i) \in \mathcal{E}(S)} \sum_{n=1}^{N} \frac{\sum_{c:(q,i) \in \mathcal{E}(\sigma_c)} \lambda_c P_c(x_n)}{S(x_n)} \ln w_i^q$$

Applying Proposition 2 we get: $Q(W) = \sum_{(q,i)\in\mathcal{E}(S)} \left(\sum_{n=1}^{N} \frac{w_{i,old}^{q} \frac{\partial S(x_{n})}{\partial S_{q}} S_{i}(x_{n})}{S(x_{n})} \right) \ln w_{i}^{q}$, and defining $\beta_{i}^{q} = w_{i,old}^{q} \sum_{n=1}^{N} S(x_{n})^{-1} \frac{\partial S(x_{n})}{\partial S_{q}} S_{i}(x_{n})$ we write $Q(W) = \sum_{q\in\mathcal{N}(S)} \sum_{i\in ch(q)} \beta_{i}^{q} \ln w_{i}^{q}$. \Box

A.3 M-step for Leaf Distributions

Starting from eq. 3, as in A.2 we expand $\ln P_c$ as a sum of logarithms and obtain:

$$Q(\theta) = \sum_{n=1}^{N} \sum_{c=1}^{C} \frac{\lambda_c P_c(x_n)}{S(x_n)} \sum_{l \in \mathcal{L}(\sigma_c)} \ln \varphi_l(x_n | \theta_l) + const.$$

Introducing $\delta_{l,c}$ which equals 1 if $l \in \mathcal{L}(\sigma_c)$ and 0 otherwise, dropping the constant and performing the sum $\sum_{l \in \mathcal{L}(S)}$ over all leaves in S we get:

$$Q(\theta) = \sum_{n=1}^{N} \sum_{c=1}^{C} \frac{\lambda_c P_c(x_n)}{S(x_n)} \sum_{l \in \mathcal{L}(S)} \ln \varphi_l(x_n | \theta_l) \,\delta_{l,c}$$
$$= \sum_{l \in \mathcal{L}(S)} \sum_{n=1}^{N} \frac{\sum_{c=1}^{C} \lambda_c P_c(x_n)}{S(x_n)} \ln \varphi_l(x_n | \theta_l) \,\delta_{l,c}$$
$$= \sum_{l \in \mathcal{L}(S)} \sum_{n=1}^{N} \frac{\sum_{c:l \in \mathcal{L}(\sigma_c)} \lambda_c P_c(x_n)}{S(x_n)} \ln \varphi_l(x_n | \theta_l)$$
$$= \sum_{l \in \mathcal{L}(S)} \sum_{n=1}^{N} \alpha_{ln} \ln \varphi_l(x_n | \theta_l)$$

Where $\alpha_{ln} = S(x_n)^{-1} \sum_{c:l \in \mathcal{L}(\sigma_c)} \lambda_c P_c(x_n)$. To compute α_{ln} we notice that the term P_c in this sum always contains a factor φ_l (def. 3), and $\varphi_l = S_l$ by def. 1. Then, writing $P_{c \setminus l} = \left(\prod_{k \in \mathcal{L}(\sigma_c) \setminus l} \varphi_k\right)$ we obtain: $\alpha_{ln} = S(x_n)^{-1} S_l \left(\sum_{c:l \in \mathcal{L}(\sigma_c)} \lambda_c P_{c \setminus l}(x_n)\right)$. Finally, since $S = \sum_{c:l \in \mathcal{L}(\sigma_c)} \lambda_c P_c + \sum_{k:l \notin \mathcal{L}(\sigma_k)} \lambda_k P_k = S_l \sum_{c:l \in \mathcal{L}(\sigma_c)} \lambda_c P_{c \setminus l} + \hat{k}$ (where \hat{k} does not depend on S_l), taking the derivative we get $\frac{\partial S}{\partial S_l} = \sum_{c:l \in \mathcal{L}(\sigma_c)} \lambda_c P_{c \setminus l}$. Substituting we get: $\alpha_{ln} = S(x_n)^{-1} \frac{\partial S(X)}{\partial S_l} S_l(x_n)$.

References

- [Amer and Todorovic., 2015] Amer, M. and Todorovic., S. (2015). Sum Product Networks for Activity Recognition. *IEEE Transactions on Pattern Analysis and Machine Intelligence (TPAMI 2015)*.
- [Boutilier et al., 1996] Boutilier, C., Friedman, N., Goldszmidt, M., and Koller, D. (1996). Context-Specific Independence in Bayesian Networks. pages 115–123.
- [Cheng et al., 2014] Cheng, W.-C., Kok, S., Pham, H. V., Chieu, H. L., and Chai, K. M. (2014). Language Modeling with Sum-Product Networks. Annual Conference of the International Speech Communication Association 15 (INTERSPEECH 2014).
- [Chow and Liu, 1968] Chow, C. I. and Liu, C. N. (1968). Approximating discrete probability distributions with dependence trees. *IEEE Transactions on Information Theory*, 14:462–467.
- [Cule et al., 2010] Cule, M., Samworth, R., and Stewart, M. (2010). Maximum likelihood estimation of a multi-dimensional log-concave density. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 72(5):545–607.
- [Dennis and Ventura, 2015] Dennis, A. and Ventura, D. (2015). Greedy Structure Search for Sumproduct Networks. In *Proceedings of the 24th International Conference on Artificial Intelligence*, IJCAI'15, pages 932–938. AAAI Press.
- [Geman and Hwang, 1982] Geman, S. and Hwang, C.-R. (1982). Nonparametric maximum likelihood estimation by the method of sieves. *The Annals of Statistics*, 10:401–414.
- [Gens and Domingos, 2012] Gens, R. and Domingos, P. (2012). Discriminative Learning of Sum-Product Networks. In *NIPS*, pages 3248–3256.
- [Gens and Domingos, 2013] Gens, R. and Domingos, P. (2013). Learning the Structure of Sum-Product Networks. In ICML (3), pages 873–880.
- [Lowd and Domingos, 2012] Lowd, D. and Domingos, P. (2012). Learning Arithmetic Circuits. *CoRR*, abs/1206.3271.
- [Meila and Jordan, 2000] Meila, M. and Jordan, M. I. (2000). Learning with mixtures of trees. *Journal* of Machine Learning Research, 1:1–48.
- [Murphy, 2012] Murphy, K. P. (2012). Machine Learning: A Probabilistic Perspective. The MIT Press.
- [Neal and Hinton, 1998] Neal, R. and Hinton, G. E. (1998). A View Of The Em Algorithm That Justifies Incremental, Sparse, And Other Variants. In *Learning in Graphical Models*, pages 355–368. Kluwer Academic Publishers.
- [Peharz, 2015] Peharz, R. (2015). Foundations of Sum-Product Networks for Probabilistic Modeling. (PhD thesis). *Researchgate:273000973*.
- [Peharz et al., 2016] Peharz, R., Gens, R., Pernkopf, F., and Domingos, P. M. (2016). On the Latent Variable Interpretation in Sum-Product Networks. *CoRR*, abs/1601.06180.
- [Peharz et al., 2014] Peharz, R., Kapeller, G., Mowlaee, P., and Pernkopf, F. (2014). Modeling Speech with Sum-Product Networks: Application to Bandwidth Extension. In *ICASSP*, pages 3699 – 3703.
- [Platt, 1999] Platt, J. C. (1999). Probabilistic outputs for support vector machines and comparisons to regularized likelihood methods. In ADVANCES IN LARGE MARGIN CLASSIFIERS, pages 61–74. MIT Press.
- [Poon and Domingos, 2011] Poon, H. and Domingos, P. (2011). Sum-Product Networks: A New Deep Architecture. In UAI 2011, Proceedings of the Twenty-Seventh Conference on Uncertainty in Artificial Intelligence, Barcelona, Spain, July 14-17, 2011, pages 337–346.
- [Rahman and Gogate, 2016a] Rahman, T. and Gogate, V. (2016a). Learning Ensembles of Cutset Networks. In Proceedings of the Thirtieth AAAI Conference on Artificial Intelligence, February 12-17, 2016, Phoenix, Arizona, USA., pages 3301–3307.

- [Rahman and Gogate, 2016b] Rahman, T. and Gogate, V. (2016b). Merging Strategies for Sum-Product Networks: From Trees to Graphs. In Proceedings of the Thirty-Second Conference on Uncertainty in Artificial Intelligence, UAI 2016, June 25-29, 2016, New York City, NY, USA.
- [Rooshenas and Lowd, 2014] Rooshenas, A. and Lowd, D. (2014). Learning Sum-Product Networks with Direct and Indirect Variable Interactions. In Jebara, T. and Xing, E. P., editors, *Proceedings of the 31st International Conference on Machine Learning (ICML-14)*, pages 710–718. JMLR Workshop and Conference Proceedings.
- [Wainwright and Jordan, 2008] Wainwright, M. J. and Jordan, M. I. (2008). Graphical Models, Exponential Families, and Variational Inference. *Found. Trends Mach. Learn.*, 1(1-2):1–305.
- [Zhao et al., 2016a] Zhao, H., Adel, T., Gordon, G., and Amos, B. (2016a). Collapsed Variational Inference for Sum-Product Networks. In *Proceedings of the 33nd International Conference on Machine Learning, ICML 2016, New York City, NY, USA, June 19-24, 2016*, pages 1310–1318.
- [Zhao et al., 2016b] Zhao, H., Poupart, P., and Gordon, G. (2016b). A Unified Approach for Learning the Parameters of Sum-Product Networks. *Proceedings of the 29th Advances in Neural Information Processing Systems (NIPS 2016).*