

# Querying Temporal Drifts at Multiple Granularities

Sofia Kleisarchaki<sup>1</sup>, Sihem Amer-Yahia<sup>1</sup>, Ahlame Douzal Chouakria<sup>2</sup>,  
Vassilis Christophides<sup>2</sup>, and Ruben H. Zamar<sup>3</sup>

<sup>1</sup>*University Grenoble Alps, CNRS, France*

<sup>2</sup>*CSD, UoC, Greece & Inria, Paris-Rocquencourt, France*

<sup>3</sup>*Univ. of British Columbia, Canada*

## Abstract

There exists a large body of work on online drift detection with the goal of dynamically finding and maintaining changes in data streams. In this paper, we adopt a query-based approach to drift detection. Our approach relies on *a drift index*, a structure that captures drift at different time granularities and enables flexible *drift queries*. We formalize different drift queries that represent real-world scenarios and develop query evaluation algorithms that use different materializations of the drift index as well as strategies for online index maintenance. We describe a thorough study of the performance of our algorithms on real-world and synthetic datasets with varying change rates.

## 1 Introduction

Monitoring streaming content is a challenging big data analytics problem, given that very large datasets are rarely (if ever) stationary. In several real world monitoring applications (e.g., newsgroup discussions, network connections, etc.) we need to detect significant change points in the underlying data distribution (e.g., frequency of words, sessions, etc.) and track the evolution of those changes over time. These change points, depending on the research community, are referred to as *temporal evolution*, *non stationarity*, or *concept drift* and provide valuable insights on real world events (e.g. a discussion topic, an intrusion) to take a timely action. In this paper, we adopt *a query-based approach to drift detection* and address the question of processing *drift queries* over very large datasets. To the best of our knowledge, our work is the first to formalize flexible drift queries on streaming datasets with varying change rates.

In the problem of drift detection, given a number of  $m$  drifts ordered in time, we need no less than  $m + 1$  intervals to detect them. Thus, without any assumption on the underlying distribution, we are interested in exploring how to segment the input stream in order to find a reasonable tradeoff between true positives and false negatives. Existing methods rely on segmenting the input stream, mostly into smaller

fixed length intervals [3, 5, 9, 11, 14]. Although some works exist on partitioning the same stream into intervals of different granularities [2, 8, 15] they either adopt an offline analysis or they lack the ability of querying historical drifts in streams.

A granularity in this case is an interval of time (e.g., every hour) or a number of observed data points (e.g., every 200 points). A drift is then defined as a significant difference in data distributions between two consecutive intervals at the same granularity. To detect drifts either statistical tests are directly applied on the data of two intervals [6, 11] or on their summaries, as for instance provided by a clustering algorithm [1, 3, 4]. To this end, two parameters impact the accuracy and efficiency of drift detection: the granularity of the intervals at which the original data items are clustered and the drift significance threshold used to assess whether or not there is a drift between two consecutive clusterings. In fact, fine-grained intervals can be used to capture the evolution of frequently changing streams. However, they may induce computation overhead for slowly changing ones. In addition, they may cause false positives, i.e., detecting drifts that are too sudden and noisy, hence hurting precision. While a coarser granularity will improve precision, since more data is clustered in each interval, it may incur missing a drift that occurred at a finer granularity. Those misses will negatively affect recall. Moreover, the rate of change of a given dataset may vary over time thereby requiring to consider different clustering granularities and drift thresholds for the same dataset.

Understanding the tradeoff between precision (at higher segmentation granularities) and recall (at lower segmentation granularities), and the choice of thresholds to determine what constitutes a drift between two consecutive intervals of the same granularity, are the main objectives of this work. In this paper, we adopt an analytics approach in which we formalize drift queries over both fresh and historical data of arbitrary time granularities, in order to provide flexibility in tracking and analyzing drifts in evolving datasets. For this reason, we propose a flexible drift index to organize past data (or more precisely their summaries) at several granularities. Furthermore, we explore different creation strategies for this index relying on two common clustering approaches, namely independent [7, 12, 16] and cumulative [1, 4]. In independent clustering, data points belonging to a given interval are considered equally important and clustered independently. In cumulative clustering, data points in a given interval are clustered with all previously occurring points and fresher data is more important than older data. Moreover, we propose different materialization strategies in order to explore the tradeoff between index storage and query response time.

Unlike existing approaches [3, 5, 9, 11, 14] comparing only the last most recent intervals, we exploit this index in order to identify drifts at different granularities. In particular, we formalize three kinds of queries: unary, refinement and synthesis aiming to detect drifts against historical data. A unary query is used to extract all drifts detected at a given granularity. A refinement query explores drifts from a source granularity (e.g., 5,000 points) to a finer target granularity (e.g., 500 points), iteratively. Such a query is useful to provide a more detailed description of drifts that have been detected in a high granularity, resulting in better recall. Synthesis

queries, on the other hand, start from a relatively low granularity and summarize them into coarser ones. In this case, some of the particular details might be missed (low recall) in order to get drifts with higher precision. This flexibility in querying drifts allows us to explore, in a declarative fashion, precision and recall tradeoffs at different granularities. Also, it addresses a long standing concern in detecting and tracking drifts in streaming content, namely adaptability of drift detection to different drift arrival rates and types.

The evaluation of declarative drift queries relies on traversing the index of historical data summaries and, at each granularity, comparing its nodes pairwise to identify points where clusterings dissimilarity exceeds a threshold  $\theta$ . Rather than setting drift thresholds a-priori [5, 13], we learn a  $\theta$ -value for each dataset and at each granularity level in the index.

In summary, this paper makes the following contributions:

1. We introduce and formalize drift queries that provide high flexibility in analyzing precision and recall of drift detection for different time granularities.
2. We propose a drift index, a graph structure that captures change at different granularities and explore different materializations of the index that lead to the design of various index maintenance and query evaluation algorithms.
3. We propose learning algorithms for learning drift and clustering thresholds adaptively for different granularities and rates of change.
4. We perform a thorough study of proposed queries and indices using two real datasets, KDD Cup'99<sup>1</sup> and Usenet [10], and a synthetically generated dataset. On the effectiveness front, our study confirms the need for our refinement and synthesis queries, as demonstrated by the very good precision/recall results they attain. On the scalability front, it validates the need for different materializations of the drift index in order to achieve a trade-off between storage and query response time for datasets of varying change rates.

## 2 Drift Queries

The goal of drift queries is to compare drifts at different granularities and provide analysts with the ability to explore drift precision and recall across granularities. We study two kinds of queries, *refinement* and *synthesis*. Both kinds rely on a simpler *unary query* defined as follows.

**Definition 1 Unary Query.** A unary query  $UQ(D, g)$  returns the set of all drifts  $X^g$  detected at granularity  $g$  for a dataset  $D$ .

**Definition 2 Refinement Query.** A refinement query  $RQ(D, g_s, g_t)$  admits a source granularity  $g_s$  and a target one  $g_t$  s.t.  $g_t < g_s$ , and returns a set of pairs  $(x_i^{g_s}, x_j^{g_t})$

---

<sup>1</sup><https://archive.ics.uci.edu/ml/datasets/KDD+Cup+1999+Data>

where each drift  $x_i^{g_s} \in X^{g_s}$  at  $g_s$  is associated to the finest corresponding drift  $x_j^g \in X^g$  at a granularity  $g$  no finer than  $g_t$  as follows:

$$\begin{aligned} & \{x_j^g \in X^g, g_t \ll g \ll g_s \vee g = g_t \mid \\ & \exists x_i^{g_s} \in X^{g_s}, I_j^g \subseteq (I_i^{g_s} \cup I_{i+1}^{g_s}), \\ & \nexists x_k^{g'} \in X^{g'}, g_t \ll g' \ll g \vee g' = g_t, I_k^{g'} \subseteq (I_i^{g_s} \cup I_{i+1}^{g_s})\} \end{aligned}$$

$$\begin{aligned} & \text{where } I_i^{g_s} \cup I_{i+1}^{g_s} = [\min_{ts_j \in I_i^{g_s}}(ts_j), \max_{ts_k \in I_{i+1}^{g_s}}(ts_k)] \text{ and} \\ & I_j^g \subseteq (I_i^{g_s} \cup I_{i+1}^{g_s}) \text{ if } \min_{ts_j \in (I_i^{g_s} \cup I_{i+1}^{g_s})}(ts_j) \leq \min_{ts_k \in I_i^{g_s}}(ts_k) \text{ and } \max_{ts_k \in I_i^{g_s}}(ts_k) \leq \max_{ts_j \in (I_i^{g_s} \cup I_{i+1}^{g_s})}(ts_j) \end{aligned}$$

Refinement queries provide a detailed analysis of drifts iteratively. For instance, for a source granularity  $g_s = 1000$  connections on KDD Cup'99, selecting a granularity  $g_t = 500$  might result in missing a more insightful analysis occurring at granularity  $g_t = 100$ . On the other hand, selecting  $g_t = 100$  may result in retrieving false positives which could be avoided at  $g_t = 500$ . Therefore, the analyst will use the refinement query  $RQ(D, 1000, 100)$  to obtain details of each drift at  $g_s = 1000$  with a tradeoff between false negatives and false positives.

**Definition 3 Synthesis Query.** A synthesis query

$SQ(D, g_s, g_t)$  admits a source granularity  $g_s$  and a target one  $g_t$  s.t.  $g_s \ll g_t$ , and returns a set of pairs  $(x_i^{g_s}, x_j^g)$  where each drift  $x_i^{g_s} \in X^{g_s}$  at granularity  $g_s$  is associated to the coarsest corresponding drift  $x_j^g \in X^g$  at a granularity  $g$  no coarser than  $g_t$  as follows:

$$\begin{aligned} & \{x_j^g \in X^g, g_s \ll g \ll g_t \vee g = g_s \mid \\ & \exists x_i^{g_s} \in X^{g_s}, I_i^{g_s} \subseteq (I_j^g \cup I_{j+1}^g), \\ & \nexists x_k^{g'} \in X^{g'}, g \ll g' \ll g_t \vee g' = g_t, I_i^{g_s} \subseteq (I_k^{g'} \cup I_{k+1}^{g'})\} \end{aligned}$$

Synthesis queries provide a summary analysis of drifts iteratively. For instance, for a source granularity  $g_s = 100$  connections on KDD Cup'99, selecting a granularity  $g_t = 1000$  might result in missing a more precise synthesis occurring at  $g_t = 2000$ . On the other hand, selecting  $g_t = 2000$  can result in missing a summary of a drift, which could be obtained at  $g_t = 1000$ . Therefore, the analyst can use the synthesis query  $SQ(D, 100, 2000)$  to obtain a summary of each drift at  $g_s = 100$  with a tradeoff between false negatives and false positives.

### 3 References

- [1] C. C. Aggarwal, J. Han, J. Wang, and P. S. Yu. A framework for clustering evolving data streams. In Proc. of VLDB03 - Volume 29, pages 8192.
- [2] A. Bifet. Adaptive stream mining: Pattern learning and mining from evolving data streams. In Proc. of the 2010 Conference on Adaptive Stream Mining: Pattern

Learning and Mining from Evolving Data Streams, pages 1212, Amsterdam, The Netherlands, 2010. IOS Press.

[3] A. Bondu, B. Grossin, and M.-L. Picard. Density estimation on data streams : an application to change detection. In EGC10, pages 229240.

[4] F. Cao, M. Ester, W. Qian, and A. Zhou. Density-based clustering over an evolving data stream with noise. In SIAM CDM06, pages 328339.

[5] T. Dasu, S. Krishnan, S. Venkatasubramanian, and K. Yi. An information-theoretic approach to detecting changes in multi-dimensional data streams. In Proc. Symp. on the Interface of Statistics, Computing Science, and Applications, 2006.

[6] A. Dries and U. Rckert. Adaptive concept drift detection. Statistical Analysis and Data Mining, 2(5-6):311327, 2009.

[7] M. Ester, H.-P. Kriegel, J. S, and X. Xu. A density-based algorithm for discovering clusters in large spatial databases with noise. pages 226231. AAAI Press, 1996.

[8] J. Gama, P. Medas, G. Castillo, and P. Rodrigues. Learning with drift detection. In Advances in AI SBIA04, volume 3171 of Lecture Notes in Computer Science, pages 286295. Springer Berlin Heidelberg.

[9] N. Japkowicz, C. Myers, and M. Gluck. A novelty detection approach to classification. In Proc. of AI, pages 518523, 1995.

[10] I. Katakis, G. Tsoumakas, and I. Vlahavas. Dynamic feature space and incremental feature selection for the classification of textual data streams. In in ECML/PKDD-2006, page 107. Springer Verlag.

[11] D. Kifer, S. Ben-David, and J. Gehrke. Detecting change in data streams. In Proc. of VLDB04 - Volume 30, pages 180191.

[12] L. OCallaghan, N. Mishra, M. A., S. Guha, and R. Motwani. Streaming-data algorithms for high-quality clustering, 2001.

[13] R. Sebastiao and J. a. Gama. Change detection in learning histograms from data streams.

[14] P. Vorburger and A. Bernstein. Entropy-based concept shift detection. In ICDM06, pages 11131118. IEEE Computer Society.

[15] G. Widmer and M. Kubat. Learning in the presence of concept drift and hidden contexts. In ML, pages 69101, 1996.

[16] T. Zhang, R. Ramakrishnan, and M. Livny. Birch: an efficient data clustering method for very large databases. SIGMOD Rec., 25:103114, 1996.