

Revisiting Perceptron: Efficient and Label-Optimal Learning of Halfspaces

Songbai Yan
UC San Diego
La Jolla, CA
yansongbai@ucsd.edu

Chicheng Zhang*
Microsoft Research
New York, NY
chicheng.zhang@microsoft.com

Abstract

It has been a long-standing problem to efficiently learn a halfspace using as few labels as possible in the presence of noise. In this work, we propose an efficient Perceptron-based algorithm for actively learning homogeneous halfspaces under the uniform distribution over the unit sphere. Under the bounded noise condition [49], where each label is flipped with probability at most $\eta < \frac{1}{2}$, our algorithm achieves a near-optimal label complexity of $\tilde{O}\left(\frac{d}{(1-2\eta)^2} \ln \frac{1}{\epsilon}\right)^2$ in time $\tilde{O}\left(\frac{d^2}{\epsilon(1-2\eta)^3}\right)$. Under the adversarial noise condition [6, 45, 42], where at most a $\tilde{\Omega}(\epsilon)$ fraction of labels can be flipped, our algorithm achieves a near-optimal label complexity of $\tilde{O}\left(d \ln \frac{1}{\epsilon}\right)$ in time $\tilde{O}\left(\frac{d^2}{\epsilon}\right)$. Furthermore, we show that our active learning algorithm can be converted to an efficient passive learning algorithm that has near-optimal sample complexities with respect to ϵ and d .

1 Introduction

We study the problem of designing efficient noise-tolerant algorithms for actively learning homogeneous halfspaces in the streaming setting. We are given access to a data distribution from which we can draw unlabeled examples, and a noisy labeling oracle \mathcal{O} that we can query for labels. The goal is to find a computationally efficient algorithm to learn a halfspace that best classifies the data while making as few queries to the labeling oracle as possible.

Active learning arises naturally in many machine learning applications where unlabeled examples are abundant and cheap, but labeling requires human effort and is expensive. For those applications, one natural question is whether we can learn an accurate classifier using as few labels as possible. Active learning addresses this question by allowing the learning algorithm to sequentially select examples to query for labels, and avoid requesting labels which are less informative, or can be inferred from previously-observed examples.

There has been a large body of work on the theory of active learning, showing sharp distribution-dependent label complexity bounds [21, 11, 34, 27, 35, 46, 60, 41]. However, most of these general active learning algorithms rely on solving empirical risk minimization problems, which are computationally hard in the presence of noise [5].

On the other hand, existing computationally efficient algorithms for learning halfspaces [17, 29, 42, 45, 6, 23, 7, 8] are not optimal in terms of label requirements. These algorithms have different

*Work done while at UC San Diego.

²We use $\tilde{O}(f(\cdot)) := O(f(\cdot) \ln f(\cdot))$, and $\tilde{\Omega}(f(\cdot)) := \Omega(f(\cdot)/\ln f(\cdot))$. We say $f(\cdot) = \tilde{\Theta}(g(\cdot))$ if $f(\cdot) = \tilde{O}(g(\cdot))$ and $f(\cdot) = \tilde{\Omega}(g(\cdot))$.

degrees of noise tolerance (e.g. adversarial noise [6], malicious noise [43], random classification noise [3], bounded noise [49], etc), and run in time polynomial in $\frac{1}{\epsilon}$ and d . Some of them naturally exploit the utility of active learning [6, 7, 8], but they do not achieve the sharpest label complexity bounds in contrast to those computationally-inefficient active learning algorithms [10, 9, 60].

Therefore, a natural question is: is there any active learning halfspace algorithm that is computationally efficient, and has a minimum label requirement? This has been posed as an open problem in [50]. In the realizable setting, [26, 10, 9, 56] give efficient algorithms that have optimal label complexity of $\tilde{O}(d \ln \frac{1}{\epsilon})$ under some distributional assumptions. However, the challenge still remains open in the nonrealizable setting. It has been shown that learning halfspaces with agnostic noise even under Gaussian unlabeled distribution is hard [44]. Nonetheless, we give an affirmative answer to this question under two moderate noise settings: bounded noise and adversarial noise.

1.1 Our Results

We propose a Perceptron-based algorithm, ACTIVE-PERCEPTRON, for actively learning homogeneous halfspaces under the uniform distribution over the unit sphere. It works under two noise settings: bounded noise and adversarial noise. Our work answers an open question by [26] on whether Perceptron-based active learning algorithms can be modified to tolerate label noise.

In the η -bounded noise setting (also known as the Massart noise model [49]), the label of an example $x \in \mathbb{R}^d$ is generated by $\text{sign}(u \cdot x)$ for some underlying halfspace u , and flipped with probability $\eta(x) \leq \eta < \frac{1}{2}$. Our algorithm runs in time $\tilde{O}\left(\frac{d^2}{(1-2\eta)^3\epsilon}\right)$, and requires $\tilde{O}\left(\frac{d}{(1-2\eta)^2} \cdot \ln \frac{1}{\epsilon}\right)$ labels. We show that this label complexity is *nearly optimal* by providing an almost matching information-theoretic lower bound of $\Omega\left(\frac{d}{(1-2\eta)^2} \cdot \ln \frac{1}{\epsilon}\right)$. Our time and label complexities substantially improve over the state of the art result of [8], which runs in time $\tilde{O}(d^{O(\frac{1}{(1-2\eta)^4})} \frac{1}{\epsilon})$ and requires $\tilde{O}(d^{O(\frac{1}{(1-2\eta)^4})} \ln \frac{1}{\epsilon})$ labels.

Our main theorem on learning under bounded noise is as follows:

Theorem 2 (Informal). *Suppose the labeling oracle \mathcal{O} satisfies the η -bounded noise condition with respect to u , then for ACTIVE-PERCEPTRON, with probability at least $1 - \delta$: (1) The output halfspace v is such that $\mathbb{P}[\text{sign}(v \cdot X) \neq \text{sign}(u \cdot X)] \leq \epsilon$; (2) The number of label queries to oracle \mathcal{O} is at most $\tilde{O}\left(\frac{d}{(1-2\eta)^2} \cdot \ln \frac{1}{\epsilon}\right)$; (3) The number of unlabeled examples drawn is at most $\tilde{O}\left(\frac{d}{(1-2\eta)^3\epsilon}\right)$; (4) The algorithm runs in time $\tilde{O}\left(\frac{d^2}{(1-2\eta)^3\epsilon}\right)$.*

In addition, we show that our algorithm also works in a more challenging setting, the ν -adversarial noise setting [6, 42, 45].³ In this setting, the examples still come iid from a distribution, but the assumption on the labels is just that $\mathbb{P}[\text{sign}(u \cdot X) \neq Y] \leq \nu$ for some halfspace u . Under this assumption, the Bayes classifier may not be a halfspace. We show that our algorithm achieves an error of ϵ while tolerating a noise level of $\nu = \Omega\left(\frac{\epsilon}{\ln \frac{d}{\epsilon} + \ln \ln \frac{1}{\epsilon}}\right)$. It runs in time $\tilde{O}\left(\frac{d^2}{\epsilon}\right)$, and requires only $\tilde{O}\left(d \cdot \ln \frac{1}{\epsilon}\right)$ labels which is near-optimal. ACTIVE-PERCEPTRON has a label complexity bound that matches the state of the art result of [39]⁴, while having a lower running time.

Our main theorem on learning under adversarial noise is as follows:

Theorem 3 (Informal). *Suppose the labeling oracle \mathcal{O} satisfies the ν -adversarial noise condition with respect to u , where $\nu < \Theta(\frac{\epsilon}{\ln \frac{d}{\epsilon} + \ln \ln \frac{1}{\epsilon}})$. Then for ACTIVE-PERCEPTRON, with probability at least $1 - \delta$: (1) The output halfspace v is such that $\mathbb{P}[\text{sign}(v \cdot X) \neq \text{sign}(u \cdot X)] \leq \epsilon$; (2) The number of label queries to oracle \mathcal{O} is at most $\tilde{O}\left(d \cdot \ln \frac{1}{\epsilon}\right)$; (3) The number of unlabeled examples drawn is at most $\tilde{O}\left(\frac{d}{\epsilon}\right)$; (4) The algorithm runs in time $\tilde{O}\left(\frac{d^2}{\epsilon}\right)$.*

³Note that the adversarial noise model is not the same as that in online learning [18], where each example can be chosen adversarially.

⁴The label complexity bound is implicit in [39] by a refined analysis of the algorithm of [6] (See their Lemma 8 for details).

Table 1: A comparison of algorithms for active learning of halfspaces under the uniform distribution, in the η -bounded noise model.

Algorithm	Label Complexity	Time Complexity
[10, 9, 60]	$\tilde{O}(\frac{d}{(1-2\eta)^2} \ln \frac{1}{\epsilon})$	$\text{superpoly}(d, \frac{1}{\epsilon})$ ⁵
[8]	$\tilde{O}(d^{O(\frac{1}{(1-2\eta)^4})} \cdot \ln \frac{1}{\epsilon})$	$\tilde{O}(d^{O(\frac{1}{(1-2\eta)^4})} \cdot \frac{1}{\epsilon})$
Our Work	$\tilde{O}(\frac{d}{(1-2\eta)^2} \ln \frac{1}{\epsilon})$	$\tilde{O}(\frac{d^2}{(1-2\eta)^3} \frac{1}{\epsilon})$

Table 2: A comparison of algorithms for active learning of halfspaces under the uniform distribution, in the ν -adversarial noise model.

Algorithm	Noise Tolerance	Label Complexity	Time Complexity
[60]	$\nu = \Omega(\epsilon)$	$\tilde{O}(d \ln \frac{1}{\epsilon})$	$\text{superpoly}(d, \frac{1}{\epsilon})$
[39]	$\nu = \Omega(\epsilon)$	$\tilde{O}(d \ln \frac{1}{\epsilon})$	$\text{poly}(d, \frac{1}{\epsilon})$
Our Work	$\nu = \Omega(\frac{\epsilon}{\ln d + \ln \frac{1}{\epsilon}})$	$\tilde{O}(d \ln \frac{1}{\epsilon})$	$\tilde{O}(d^2 \cdot \frac{1}{\epsilon})$

Throughout the paper, ACTIVE-PERCEPTRON is shown to work if the unlabeled examples are drawn uniformly from the unit sphere. The algorithm and analysis can be easily generalized to any spherical symmetrical distributions, for example, isotropic Gaussian distributions. They can also be generalized to distributions whose densities with respect to uniform distribution are bounded away from 0.

In addition, we show in Section 6 that ACTIVE-PERCEPTRON can be converted to a passive learning algorithm, PASSIVE-PERCEPTRON, that has near optimal sample complexities with respect to ϵ and d under the two noise settings. We defer the discussion to the end of the paper.

2 Related Work

Active Learning. The recent decades have seen much success in both theory and practice of active learning; see the excellent surveys by [54, 37, 25]. On the theory side, many label-efficient active learning algorithms have been proposed and analyzed. An incomplete list includes [21, 11, 34, 27, 35, 46, 60, 41]. Most algorithms relies on solving empirical risk minimization problems, which are computationally hard in the presence of noise [5].

Computational Hardness of Learning Halfspaces. Efficient learning of halfspaces is one of the central problems in machine learning [22]. In the realizable case, it is well known that linear programming will find a consistent hypothesis over data efficiently. In the nonrealizable setting, however, the problem is much more challenging.

A series of papers have shown the hardness of learning halfspaces with agnostic noise [5, 30, 33, 44, 23]. The state of the art result [23] shows that under standard complexity-theoretic assumptions, there exists a data distribution, such that the best linear classifier has error $o(1)$, but no polynomial time algorithms can achieve an error at most $\frac{1}{2} - \frac{1}{d^c}$ for every $c > 0$, even with improper learning. [44] shows that under standard assumptions, even if the unlabeled distribution is Gaussian, any agnostic halfspace learning algorithm must run in time $(\frac{1}{\epsilon})^{\Omega(\ln d)}$ to achieve an excess error of ϵ . These results indicate that, to have nontrivial guarantees on learning halfspaces with noise in polynomial time, one has to make additional assumptions on the data distribution over instances and labels.

Efficient Active Learning of Halfspaces. Despite considerable efforts, there are only a few halfspace learning algorithms that are both computationally-efficient and label-efficient even under the uniform distribution. In the realizable setting, [26, 10, 9] propose computationally efficient active learning algorithms which have an optimal label complexity of $\tilde{O}(d \ln \frac{1}{\epsilon})$.

⁵The algorithm needs to minimize 0-1 loss, the best known method for which requires superpolynomial time.

Since it is believed to be hard for learning halfspaces in the general agnostic setting, it is natural to consider algorithms that work under more moderate noise conditions. Under the bounded noise setting [49], the only known algorithms that are both label-efficient and computationally-efficient are [7, 8]. [7] uses a margin-based framework which queries the labels of examples near the decision boundary. To achieve computational efficiency, it adaptively chooses a sequence of hinge loss minimization problems to optimize as opposed to directly optimizing the 0-1 loss. It works only when the label flipping probability upper bound η is small ($\eta \leq 1.8 \times 10^{-6}$). [8] improves over [7] by adapting a polynomial regression procedure into the margin-based framework. It works for any $\eta < 1/2$, but its label complexity is $O(d^{O(\frac{1}{(1-2\eta)^4})} \ln \frac{1}{\epsilon})$, which is far worse than the information-theoretic lower bound $\Omega(\frac{d}{(1-2\eta)^2} \ln \frac{1}{\epsilon})$. Recently [20] gives an efficient algorithm with a near-optimal label complexity under the membership query model where the learner can query on synthesized points. In contrast, in our stream-based model, the learner can only query on points drawn from the data distribution. We note that learning in the stream-based model is harder than in the membership query model, and it is unclear how to transform the DC algorithm in [20] into a computationally efficient stream-based active learning algorithm.

Under the more challenging ν -adversarial noise setting, [6] proposes a margin-based algorithm that reduces the problem to a sequence of hinge loss minimization problems. Their algorithm achieves an error of ϵ in polynomial time when $\nu = \Omega(\epsilon)$, but requires $\tilde{O}(d^2 \ln \frac{1}{\epsilon})$ labels. Later, [39] performs a refined analysis to achieve a near-optimal label complexity of $\tilde{O}(d \ln \frac{1}{\epsilon})$, but the time complexity of the algorithm is still an unspecified high order polynomial.

Tables 1 and 2 present comparisons between our results and results most closely related to ours in the literature. Due to space limitations, discussions of additional related work are deferred to Appendix A.

3 Definitions and Settings

We consider learning homogeneous halfspaces under uniform distribution. The instance space \mathcal{X} is the unit sphere in \mathbb{R}^d , which we denote by $\mathbb{S}^{d-1} := \{x \in \mathbb{R}^d : \|x\| = 1\}$. We assume $d \geq 3$ throughout this paper. The label space $\mathcal{Y} = \{+1, -1\}$. We assume all data points (x, y) are drawn i.i.d. from an underlying distribution D over $\mathcal{X} \times \mathcal{Y}$. We denote by $D_{\mathcal{X}}$ the marginal of D over \mathcal{X} (which is uniform over \mathbb{S}^{d-1}), and $D_{Y|X}$ the conditional distribution of Y given X . Our algorithm is allowed to draw unlabeled examples $x \in \mathcal{X}$ from $D_{\mathcal{X}}$, and to make queries to a labeling oracle \mathcal{O} for labels. Upon query x , \mathcal{O} returns a label y drawn from $D_{Y|X=x}$. The hypothesis class of interest is the set of homogeneous halfspaces $\mathcal{H} := \{h_w(x) = \text{sign}(w \cdot x) \mid w \in \mathbb{S}^{d-1}\}$. For any hypothesis $h \in \mathcal{H}$, we define its error rate $\text{err}(h) := \mathbb{P}_D[h(X) \neq Y]$. We will drop the subscript D in \mathbb{P}_D when it is clear from the context. Given a dataset $S = \{(X_1, Y_1), \dots, (X_m, Y_m)\}$, we define the empirical error rate of h over S as $\text{err}_S(h) := \frac{1}{m} \sum_{i=1}^m \mathbb{1}\{h(X_i) \neq Y_i\}$.

Definition 1 (Bounded Noise [49]). *We say that the labeling oracle \mathcal{O} satisfies the η -bounded noise condition for some $\eta \in [0, 1/2)$ with respect to u , if for any x , $\mathbb{P}[Y \neq \text{sign}(u \cdot x) \mid X = x] \leq \eta$.*

It can be seen that under η -bounded noise condition, h_u is the Bayes classifier.

Definition 2 (Adversarial Noise [6]). *We say that the labeling oracle \mathcal{O} satisfies the ν -adversarial noise condition for some $\nu \in [0, 1]$ with respect to u , if $\mathbb{P}[Y \neq \text{sign}(u \cdot X)] \leq \nu$.*

For two unit vectors v_1, v_2 , denote by $\theta(v_1, v_2) = \arccos(v_1 \cdot v_2)$ the angle between them. The following lemma gives relationships between errors and angles (see also Lemma 1 in [8]).

Lemma 1. *For any $v_1, v_2 \in \mathbb{S}^{d-1}$, $|\text{err}(h_{v_1}) - \text{err}(h_{v_2})| \leq \mathbb{P}[h_{v_1}(X) \neq h_{v_2}(X)] = \frac{\theta(v_1, v_2)}{\pi}$.*

Additionally, if the labeling oracle satisfies the η -bounded noise condition with respect to u , then for any vector v , $|\text{err}(h_v) - \text{err}(h_u)| \geq (1 - 2\eta)\mathbb{P}[h_v(X) \neq h_u(X)] = \frac{1-2\eta}{\pi}\theta(v, u)$.

Given access to unlabeled examples drawn from $D_{\mathcal{X}}$ and a labeling oracle \mathcal{O} , our goal is to find a polynomial time algorithm \mathcal{A} such that with probability at least $1 - \delta$, \mathcal{A} outputs a halfspace $h_v \in \mathcal{H}$ with $\mathbb{P}[\text{sign}(v \cdot X) \neq \text{sign}(u \cdot X)] \leq \epsilon$ for some target accuracy ϵ and confidence δ . (By Lemma 1, this guarantees that the excess error of h_v is at most ϵ , namely, $\text{err}(h_v) - \text{err}(h_u) \leq \epsilon$.) The desired algorithm should make as few queries to the labeling oracle \mathcal{O} as possible.

We say an algorithm \mathcal{A} achieves a *label complexity* of $\Lambda(\epsilon, \delta)$, if for any target halfspace $h_u \in \mathcal{H}$, with probability at least $1 - \delta$, \mathcal{A} outputs a halfspace $h_v \in \mathcal{H}$ such that $\text{err}(h_v) \leq \text{err}(h_u) + \epsilon$, and requests at most $\Lambda(\epsilon, \delta)$ labels from oracle \mathcal{O} .

4 Main Algorithm

Our main algorithm, ACTIVE-PERCEPTRON (Algorithm 1), works in epochs. It works under the bounded and the adversarial noise models, if its sample schedule $\{m_k\}$ and band width $\{b_k\}$ are set appropriately with respect to each noise model. At the beginning of each epoch k , it assumes an upper bound of $\frac{\pi}{2^k}$ on $\theta(v_{k-1}, u)$, the angle between current iterate v_{k-1} and the underlying halfspace u . As we will see, this can be shown to hold with high probability inductively. Then, it calls procedure MODIFIED-PERCEPTRON (Algorithm 2) to find a new iterate v_k , which can be shown to have an angle with u at most $\frac{\pi}{2^{k+1}}$ with high probability. The algorithm ends when a total of $k_0 = \lceil \log_2 \frac{1}{\epsilon} \rceil$ epochs have passed.

For simplicity, we assume for the rest of the paper that the angle between the initial halfspace v_0 and the underlying halfspace u is acute, that is, $\theta(v_0, u) \leq \frac{\pi}{2}$; Appendix F shows that this assumption can be removed with a constant overhead in terms of label and time complexities.

Algorithm 1 ACTIVE-PERCEPTRON

Input: Labeling oracle \mathcal{O} , initial halfspace v_0 , target error ϵ , confidence δ , sample schedule $\{m_k\}$, band width $\{b_k\}$.
Output: learned halfspace v .
1: Let $k_0 = \lceil \log_2 \frac{1}{\epsilon} \rceil$.
2: **for** $k = 1, 2, \dots, k_0$ **do**
3: $v_k \leftarrow \text{MODIFIED-PERCEPTRON}(\mathcal{O}, v_{k-1}, \frac{\pi}{2^k}, \frac{\delta}{k(k+1)}, m_k, b_k)$.
4: **end for**
5: **return** v_{k_0} .

Procedure MODIFIED-PERCEPTRON (Algorithm 2) is the core component of ACTIVE-PERCEPTRON. It sequentially performs a modified Perceptron update rule on the selected new examples (x_t, y_t) [51, 17, 26]:

$$w_{t+1} \leftarrow w_t - 2\mathbb{1}\{y_t w_t \cdot x_t < 0\} (w_t \cdot x_t) \cdot x_t \quad (1)$$

Define $\theta_t := \theta(w_t, u)$. Update rule (1) implies the following relationship between θ_{t+1} and θ_t (See Lemma 8 in Appendix E for its proof):

$$\cos \theta_{t+1} - \cos \theta_t = -2\mathbb{1}\{y_t w_t \cdot x_t < 0\} (w_t \cdot x_t) \cdot (u \cdot x_t) \quad (2)$$

This motivates us to take $\cos \theta_t$ as our measure of progress; we would like to drive $\cos \theta_t$ up to 1 (so that θ_t goes down to 0) as fast as possible.

To this end, MODIFIED-PERCEPTRON samples new points x_t under time-varying distributions $D_{\mathcal{X}}|_{R_t}$ and query for their labels, where $R_t = \left\{x \in \mathbb{S}^{d-1} : \frac{b}{2} \leq w_t \cdot x \leq b\right\}$ is a band inside the unit sphere. The rationale behind the choice of R_t is twofold:

1. We set R_t to have a probability mass of $\tilde{\Omega}(\epsilon)$, so that the time complexity of rejection sampling is at most $\tilde{O}(\frac{1}{\epsilon})$ per example. Moreover, in the adversarial noise setting, we set R_t large enough to dominate the noise of magnitude $\nu = \tilde{\Omega}(\epsilon)$.
2. Unlike the active Perceptron algorithm in [26] or other margin-based approaches (for example [55, 10]) where examples with small margin are queried, we query the label of the examples with a range of margin $[\frac{b}{2}, b]$. From a technical perspective, this ensures that θ_t decreases by a decent amount in expectation (see Lemmas 9 and 10 for details).

Following the insight of [32], we remark that the modified Perceptron update (1) on distribution $D_{\mathcal{X}}|_{R_t}$ can be alternatively viewed as performing stochastic gradient descent on a special non-convex loss function $\ell(w, (x, y)) = \min(1, \max(0, -1 - \frac{2}{b} y w \cdot x))$. It is an interesting open question

whether optimizing this new loss function can lead to improved empirical results for learning halfspaces.

Algorithm 2 MODIFIED-PERCEPTRON

Input: Labeling oracle \mathcal{O} , initial halfspace w_0 , angle upper bound θ , confidence δ , number of iterations m , band width b .

Output: Improved halfspace w_m .

- 1: **for** $t = 0, 1, 2, \dots, m - 1$ **do**
 - 2: Define region $R_t = \left\{x \in \mathbb{S}^{d-1} : \frac{b}{2} \leq w_t \cdot x \leq b\right\}$.
 - 3: Rejection sample $x_t \sim D_{\mathcal{X}}|_{R_t}$. In other words, draw x_t from $D_{\mathcal{X}}$ until x_t is in R_t . Query \mathcal{O} for its label y_t .
 - 4: $w_{t+1} \leftarrow w_t - 2\mathbb{1}\{y_t w_t \cdot x_t < 0\} \cdot (w_t \cdot x_t) \cdot x_t$.
 - 5: **end for**
 - 6: **return** w_m .
-

5 Performance Guarantees

We show that ACTIVE-PERCEPTRON works in the bounded and the adversarial noise models, achieving computational efficiency and near-optimal label complexities. To this end, we first give a lower bound on the label complexity under bounded noise, and then give computational and label complexity upper bounds under the two noise conditions respectively. We defer all proofs to the Appendix.

5.1 A Lower Bound under Bounded Noise

We first present an information-theoretic lower bound on the label complexity in the bounded noise setting under uniform distribution. This extends the distribution-free lower bounds of [53, 37], and generalizes the realizable-case lower bound of [47] to the bounded noise setting. Our lower bound can also be viewed as an extension of [59]’s Theorem 3; specifically it addresses the hardness under the α -Tsybakov noise condition where $\alpha = 0$ (while [59]’s Theorem 3 provides lower bounds when $\alpha \in (0, 1)$).

Theorem 1. *For any $d > 4$, $0 \leq \eta < \frac{1}{2}$, $0 < \epsilon \leq \frac{1}{4\pi}$, $0 < \delta \leq \frac{1}{4}$, for any active learning algorithm \mathcal{A} , there is a $u \in \mathbb{S}^{d-1}$, and a labeling oracle \mathcal{O} that satisfies η -bounded noise condition with respect to u , such that if with probability at least $1 - \delta$, \mathcal{A} makes at most n queries of labels to \mathcal{O} and outputs $v \in \mathbb{S}^{d-1}$ such that $\mathbb{P}[\text{sign}(v \cdot X) \neq \text{sign}(u \cdot X)] \leq \epsilon$, then $n \geq \Omega\left(\frac{d \log \frac{1}{\epsilon}}{(1-2\eta)^2} + \frac{\eta \log \frac{1}{\delta}}{(1-2\eta)^2}\right)$.*

5.2 Bounded Noise

We establish Theorem 2 in the bounded noise setting. The theorem implies that, with appropriate settings of input parameters, ACTIVE-PERCEPTRON efficiently learns a halfspace of excess error at most ϵ with probability at least $1 - \delta$, under the assumption that $D_{\mathcal{X}}$ is uniform over the unit sphere and \mathcal{O} has bounded noise. In addition, it queries at most $\tilde{O}\left(\frac{d}{(1-2\eta)^2} \ln \frac{1}{\epsilon}\right)$ labels. This matches the lower bound of Theorem 1, and improves over the state of the art result of [8], where a label complexity of $\tilde{O}\left(d^{O\left(\frac{1}{(1-2\eta)^4}\right)} \ln \frac{1}{\epsilon}\right)$ is shown using a different algorithm.

The proof and the precise setting of parameters (m_k and b_k) are given in Appendix C.

Theorem 2 (ACTIVE-PERCEPTRON under Bounded Noise). *Suppose Algorithm 1 has inputs labeling oracle \mathcal{O} that satisfies η -bounded noise condition with respect to halfspace u , initial halfspace v_0 such that $\theta(v_0, u) \in [0, \frac{\pi}{2}]$, target error ϵ , confidence δ , sample schedule $\{m_k\}$ where $m_k = \Theta\left(\frac{d}{(1-2\eta)^2} \left(\ln \frac{d}{(1-2\eta)^2} + \ln \frac{k}{\delta}\right)\right)$, band width $\{b_k\}$ where $b_k = \Theta\left(\frac{2^{-k}(1-2\eta)}{\sqrt{d \ln(km_k/\delta)}}\right)$. Then with probability at least $1 - \delta$:*

1. *The output halfspace v is such that $\mathbb{P}[\text{sign}(v \cdot X) \neq \text{sign}(u \cdot X)] \leq \epsilon$.*
2. *The number of label queries is $O\left(\frac{d}{(1-2\eta)^2} \cdot \ln \frac{1}{\epsilon} \cdot \left(\ln \frac{d}{(1-2\eta)^2} + \ln \frac{1}{\delta} + \ln \ln \frac{1}{\epsilon}\right)\right)$.*

3. The number of unlabeled examples drawn is

$$O\left(\frac{d}{(1-2\eta)^3} \cdot \left(\ln \frac{d}{(1-2\eta)^2} + \ln \frac{1}{\delta} + \ln \ln \frac{1}{\epsilon}\right)^2 \cdot \frac{1}{\epsilon} \ln \frac{1}{\epsilon}\right).$$

4. The algorithm runs in time $O\left(\frac{d^2}{(1-2\eta)^3} \cdot \left(\ln \frac{d}{(1-2\eta)^2} + \ln \frac{1}{\delta} + \ln \ln \frac{1}{\epsilon}\right)^2 \cdot \frac{1}{\epsilon} \ln \frac{1}{\epsilon}\right)$.

The theorem follows from Lemma 2 below. The key ingredient of the lemma is a delicate analysis of the dynamics of the angles $\{\theta_t\}_{t=0}^m$, where $\theta_t = \theta(w_t, u)$ is the angle between the iterate w_t and the halfspace u . Since x_t is randomly sampled and y_t is noisy, we are only able to show that θ_t decreases by a decent amount *in expectation*. To remedy the stochastic fluctuations, we apply martingale concentration inequalities to carefully control the upper envelope of sequence $\{\theta_t\}_{t=0}^m$.

Lemma 2 (MODIFIED-PERCEPTRON under Bounded Noise). *Suppose Algorithm 2 has inputs labeling oracle \mathcal{O} that satisfies η -bounded noise condition with respect to halfspace u , initial halfspace w_0 and angle upper bound $\theta \in (0, \frac{\pi}{2}]$ such that $\theta(w_0, u) \leq \theta$, confidence δ , number of iterations $m = \Theta(\frac{d}{(1-2\eta)^2}(\ln \frac{d}{(1-2\eta)^2} + \ln \frac{1}{\delta}))$, band width $b = \Theta\left(\frac{\theta(1-2\eta)}{\sqrt{d} \ln(m/\delta)}\right)$. Then with probability at least $1 - \delta$:*

1. The output halfspace w_m is such that $\theta(w_m, u) \leq \frac{\theta}{2}$.

2. The number of label queries is $O\left(\frac{d}{(1-2\eta)^2} \left(\ln \frac{d}{(1-2\eta)^2} + \ln \frac{1}{\delta}\right)\right)$.

3. The number of unlabeled examples drawn is $O\left(\frac{d}{(1-2\eta)^3} \cdot \left(\ln \frac{d}{(1-2\eta)^2} + \ln \frac{1}{\delta}\right)^2 \cdot \frac{1}{\theta}\right)$.

4. The algorithm runs in time $O\left(\frac{d^2}{(1-2\eta)^3} \cdot \left(\ln \frac{d}{(1-2\eta)^2} + \ln \frac{1}{\delta}\right)^2 \cdot \frac{1}{\theta}\right)$.

5.3 Adversarial Noise

We establish Theorem 3 in the adversarial noise setting. The theorem implies that, with appropriate settings of input parameters, ACTIVE-PERCEPTRON efficiently learns a halfspace of excess error at most ϵ with probability at least $1 - \delta$, under the assumption that $D_{\mathcal{X}}$ is uniform over the unit sphere and \mathcal{O} has an adversarial noise of magnitude $\nu = \Omega(\frac{\epsilon}{\ln d + \ln \ln \frac{1}{\epsilon}})$. In addition, it queries at most $\tilde{O}(d \ln \frac{1}{\epsilon})$ labels. Our label complexity bound is information-theoretically optimal [47], and matches the state of the art result of [39]. The benefit of our approach is computational: it has a running time of $\tilde{O}(\frac{d^2}{\epsilon})$, while [39] needs to solve a convex optimization problem whose running time is some polynomial over d and $\frac{1}{\epsilon}$ with an unspecified degree.

The proof and the precise setting of parameters (m_k and b_k) are given in Appendix C.

Theorem 3 (ACTIVE-PERCEPTRON under Adversarial Noise). *Suppose Algorithm 1 has inputs labeling oracle \mathcal{O} that satisfies ν -adversarial noise condition with respect to halfspace u , initial halfspace v_0 such that $\theta(v_0, u) \leq \frac{\pi}{2}$, target error ϵ , confidence δ , sample schedule $\{m_k\}$ where $m_k = \Theta(d(\ln d + \ln \frac{k}{\delta}))$, band width $\{b_k\}$ where $b_k = \Theta\left(\frac{2^{-k}}{\sqrt{d} \ln(km_k/\delta)}\right)$. Additionally $\nu \leq \Omega(\frac{\epsilon}{\ln \frac{d}{\delta} + \ln \ln \frac{1}{\epsilon}})$. Then with probability at least $1 - \delta$:*

1. The output halfspace v is such that $\mathbb{P}[\text{sign}(v \cdot X) \neq \text{sign}(u \cdot X)] \leq \epsilon$.

2. The number of label queries is $O\left(d \cdot \ln \frac{1}{\epsilon} \cdot \left(\ln d + \ln \frac{1}{\delta} + \ln \ln \frac{1}{\epsilon}\right)\right)$.

3. The number of unlabeled examples drawn is $O\left(d \cdot \left(\ln d + \ln \frac{1}{\delta} + \ln \ln \frac{1}{\epsilon}\right)^2 \cdot \frac{1}{\epsilon} \ln \frac{1}{\epsilon}\right)$.

4. The algorithm runs in time $O\left(d^2 \cdot \left(\ln d + \ln \frac{1}{\delta} + \ln \ln \frac{1}{\epsilon}\right)^2 \cdot \frac{1}{\epsilon} \ln \frac{1}{\epsilon}\right)$.

The theorem follows from Lemma 3 below, whose proof is similar to Lemma 2.

Lemma 3 (MODIFIED-PERCEPTRON under Adversarial Noise). *Suppose Algorithm 2 has inputs labeling oracle \mathcal{O} that satisfies ν -adversarial noise condition with respect to halfspace u , initial halfspace w_0 and angle upper bound $\theta \in (0, \frac{\pi}{2}]$ such that $\theta(w_0, u) \leq \theta$, confidence δ , number of iterations $m = \Theta(d(\ln d + \ln \frac{1}{\delta}))$, band width $b = \Theta\left(\frac{\theta}{\sqrt{d \ln(m/\delta)}}\right)$. Additionally $\nu \leq \Omega(\frac{\theta}{\ln(m/\delta)})$. Then with probability at least $1 - \delta$:*

1. *The output halfspace w_m is such that $\theta(w_m, u) \leq \frac{\theta}{2}$.*
2. *The number of label queries is $O\left(d \cdot (\ln d + \ln \frac{1}{\delta})\right)$.*
3. *The number of unlabeled examples drawn is $O\left(d \cdot (\ln d + \ln \frac{1}{\delta})^2 \cdot \frac{1}{\theta}\right)$.*
4. *The algorithm runs in time $O\left(d^2 \cdot (\ln d + \ln \frac{1}{\delta})^2 \cdot \frac{1}{\theta}\right)$.*

6 Implications to Passive Learning

ACTIVE-PERCEPTRON can be converted to a passive learning algorithm, PASSIVE-PERCEPTRON, for learning homogeneous halfspaces under the uniform distribution over the unit sphere. PASSIVE-PERCEPTRON has PAC sample complexities close to the lower bounds under the two noise models. We give a formal description of PASSIVE-PERCEPTRON in Appendix B. We give its formal guarantees in the corollaries below, which are immediate consequences of Theorems 2 and 3.

In the η -bounded noise model, the sample complexity of PASSIVE-PERCEPTRON improves over the state of the art result of [8], where a sample complexity of $\tilde{O}\left(\frac{d^{O(\frac{1}{(1-2\eta)^4})}}{\epsilon}\right)$ is obtained. The bound has the same dependency on ϵ and d as the minimax upper bound of $\tilde{\Theta}\left(\frac{d}{\epsilon(1-2\eta)}\right)$ by [49], which is achieved by a computationally inefficient ERM algorithm.

Corollary 1 (PASSIVE-PERCEPTRON under Bounded Noise). *Suppose PASSIVE-PERCEPTRON has inputs distribution D that satisfies η -bounded noise condition with respect to u , initial halfspace v_0 , target error ϵ , confidence δ , sample schedule $\{m_k\}$ where $m_k = \Theta\left(\frac{d}{(1-2\eta)^2} (\ln \frac{d}{(1-2\eta)^2} + \ln \frac{k}{\delta})\right)$, band width $\{b_k\}$ where $b_k = \Theta\left(\frac{2^{-k}(1-2\eta)}{\sqrt{d \ln(km_k/\delta)}}\right)$. Then with probability at least $1 - \delta$: (1) The output halfspace v is such that $\text{err}(h_v) \leq \text{err}(h_u) + \epsilon$; (2) The number of labeled examples drawn is $\tilde{O}\left(\frac{d}{(1-2\eta)^3 \epsilon}\right)$. (3) The algorithm runs in time $\tilde{O}\left(\frac{d^2}{(1-2\eta)^3 \epsilon}\right)$.*

In the ν -adversarial noise model, the sample complexity of PASSIVE-PERCEPTRON matches the minimax optimal sample complexity upper bound of $\tilde{\Theta}\left(\frac{d}{\epsilon}\right)$ obtained in [39]. Same as in active learning, our algorithm has a faster running time than [39].

Corollary 2 (PASSIVE-PERCEPTRON under Adversarial Noise). *Suppose PASSIVE-PERCEPTRON has inputs distribution D that satisfies ν -adversarial noise condition with respect to u , initial halfspace v_0 , target error ϵ , confidence δ , sample schedule $\{m_k\}$ where $m_k = \Theta\left(d(\ln d + \ln \frac{k}{\delta})\right)$, band width $\{b_k\}$ where $b_k = \Theta\left(\frac{2^{-k}}{\sqrt{d \ln(km_k/\delta)}}\right)$. Furthermore $\nu = \Omega\left(\frac{\epsilon}{\ln \ln \frac{1}{\epsilon} + \ln \frac{d}{\delta}}\right)$. Then with probability at least $1 - \delta$: (1) The output halfspace v is such that $\text{err}(h_v) \leq \text{err}(h_u) + \epsilon$; (2) The number of labeled examples drawn is $\tilde{O}\left(\frac{d}{\epsilon}\right)$. (3) The algorithm runs in time $\tilde{O}\left(\frac{d^2}{\epsilon}\right)$.*

Tables 3 and 4 present comparisons between our results and results most closely related to ours.

Acknowledgments. The authors thank Kamalika Chaudhuri for help and support, Hongyang Zhang for thought-provoking initial conversations, Jiapeng Zhang for helpful discussions, and the anonymous reviewers for their insightful feedback. Much of this work is supported by NSF IIS-1167157 and 1162581.

Table 3: A comparison of algorithms for PAC learning halfspaces under the uniform distribution, in the η -bounded noise model.

Algorithm	Sample Complexity	Time Complexity
[8]	$\tilde{O}\left(\frac{d^{O(\frac{1}{(1-2\eta)^4})}}{\epsilon}\right)$	$\tilde{O}\left(\frac{d^{O(\frac{1}{(1-2\eta)^4})}}{\epsilon}\right)$
ERM [49]	$\tilde{O}\left(\frac{d}{(1-2\eta)\epsilon}\right)$	superpoly($d, \frac{1}{\epsilon}$)
Our Work	$\tilde{O}\left(\frac{d}{(1-2\eta)^3\epsilon}\right)$	$\tilde{O}\left(\frac{d^2}{(1-2\eta)^3} \cdot \frac{1}{\epsilon}\right)$

Table 4: A comparison of algorithms for PAC learning halfspaces under the uniform distribution, in the ν -adversarial noise model where $\nu = \Omega(\frac{\epsilon}{\ln \ln \frac{1}{\epsilon} + \ln d})$.

Algorithm	Sample Complexity	Time Complexity
[39]	$\tilde{O}\left(\frac{d}{\epsilon}\right)$	poly($d, \frac{1}{\epsilon}$)
ERM [57]	$\tilde{O}\left(\frac{d}{\epsilon}\right)$	superpoly($d, \frac{1}{\epsilon}$)
Our Work	$\tilde{O}\left(\frac{d}{\epsilon}\right)$	$\tilde{O}\left(\frac{d^2}{\epsilon}\right)$

References

- [1] Alekh Agarwal. Selective sampling algorithms for cost-sensitive multiclass prediction. *ICML* (3), 28: 1220–1228, 2013.
- [2] Nir Ailon, Ron Begleiter, and Esther Ezra. Active learning using smooth relative regret approximations with applications. *Journal of Machine Learning Research*, 15(1):885–920, 2014.
- [3] Dana Angluin and Philip Laird. Learning from noisy examples. *Machine Learning*, 2 (4):343–370, Apr 1988. ISSN 1573-0565. doi: 10.1023/A:1022873112823. URL <https://doi.org/10.1023/A:1022873112823>.
- [4] Martin Anthony and Peter L Bartlett. *Neural network learning: Theoretical foundations*. Cambridge University Press, 2009.
- [5] Sanjeev Arora, László Babai, Jacques Stern, and Z Sweedyk. The hardness of approximate optima in lattices, codes, and systems of linear equations. In *Foundations of Computer Science, 1993. Proceedings., 34th Annual Symposium on*, pages 724–733. IEEE, 1993.
- [6] Pranjal Awasthi, Maria Florina Balcan, and Philip M Long. The power of localization for efficiently learning linear separators with noise. In *Proceedings of the 46th Annual ACM Symposium on Theory of Computing*, pages 449–458. ACM, 2014.
- [7] Pranjal Awasthi, Maria-Florina Balcan, Nika Haghtalab, and Ruth Uner. Efficient learning of linear separators under bounded noise. In *COLT*, pages 167–190, 2015.
- [8] Pranjal Awasthi, Maria-Florina Balcan, Nika Haghtalab, and Hongyang Zhang. Learning and 1-bit compressed sensing under asymmetric noise. In *Proceedings of The 28th Conference on Learning Theory, COLT 2016*, 2016.
- [9] M.-F. Balcan and P. M. Long. Active and passive learning of linear separators under log-concave distributions. In *COLT*, 2013.
- [10] M.-F. Balcan, A. Z. Broder, and T. Zhang. Margin based active learning. In *COLT*, 2007.
- [11] M.-F. Balcan, A. Beygelzimer, and J. Langford. Agnostic active learning. *J. Comput. Syst. Sci.*, 75(1): 78–89, 2009.
- [12] Maria-Florina Balcan and Vitaly Feldman. Statistical active learning algorithms. In *NIPS*, pages 1295–1303, 2013.
- [13] Maria-Florina Balcan and Hongyang Zhang. S-concave distributions: Towards broader distributions for noise-tolerant and sample-efficient learning algorithms. *arXiv preprint arXiv:1703.07758*, 2017.
- [14] Maria-Florina Balcan, Steve Hanneke, and Jennifer Wortman Vaughan. The true sample complexity of active learning. *Machine learning*, 80(2-3):111–139, 2010.

- [15] A. Beygelzimer, D. Hsu, J. Langford, and T. Zhang. Agnostic active learning without constraints. In *NIPS*, 2010.
- [16] Alina Beygelzimer, Sanjoy Dasgupta, and John Langford. Importance weighted active learning. In *Twenty-Sixth International Conference on Machine Learning*, 2009.
- [17] Avrim Blum, Alan M. Frieze, Ravi Kannan, and Santosh Vempala. A polynomial-time algorithm for learning noisy linear threshold functions. *Algorithmica*, 22(1/2):35–52, 1998.
- [18] Nicolo Cesa-Bianchi and Gábor Lugosi. *Prediction, learning, and games*. Cambridge university press, 2006.
- [19] Nicolò Cesa-Bianchi, Claudio Gentile, and erancesco Orabona. Robust bounds for classification via selective sampling. In *Proceedings of the 26th Annual International Conference on Machine Learning, ICML 2009, Montreal, Quebec, Canada, June 14-18, 2009*, pages 121–128, 2009.
- [20] Lin Chen, Hamed Hassani, and Amin Karbasi. Near-optimal active learning of halfspaces via query synthesis in the noisy setting. In *Thirty-First AAAI Conference on Artificial Intelligence*, 2017.
- [21] David A. Cohn, Les E. Atlas, and Richard E. Ladner. Improving generalization with active learning. *Machine Learning*, 15(2):201–221, 1994.
- [22] Nello Cristianini and John Shawe-Taylor. An introduction to support vector machines and other kernel-based learning methods. 2000.
- [23] Amit Daniely. Complexity theoretic limitations on learning halfspaces. *arXiv preprint arXiv:1505.05800*, 2015.
- [24] S. Dasgupta. Coarse sample complexity bounds for active learning. In *NIPS*, 2005.
- [25] Sanjoy Dasgupta. Two faces of active learning. *Theoretical computer science*, 412(19):1767–1781, 2011.
- [26] Sanjoy Dasgupta, Adam Tauman Kalai, and Claire Monteleoni. Analysis of perceptron-based active learning. In *Learning Theory, 18th Annual Conference on Learning Theory, COLT 2005, Bertinoro, Italy, June 27-30, 2005, Proceedings*, pages 249–263, 2005.
- [27] Sanjoy Dasgupta, Daniel Hsu, and Claire Monteleoni. A general agnostic active learning algorithm. In *Advances in Neural Information Processing Systems 20*, 2007.
- [28] Ofer Dekel, Claudio Gentile, and Karthik Sridharan. Selective sampling and active learning from single and multiple teachers. *Journal of Machine Learning Research*, 13(Sep):2655–2697, 2012.
- [29] John Dunagan and Santosh Vempala. A simple polynomial-time rescaling algorithm for solving linear programs. In *Proceedings of the thirty-sixth annual ACM symposium on Theory of computing*, pages 315–320. ACM, 2004.
- [30] Vitaly Feldman, Parikshit Gopalan, Subhash Khot, and Ashok Kumar Ponnuswami. New results for learning noisy parities and halfspaces. In *Foundations of Computer Science, 2006. FOCS'06. 47th Annual IEEE Symposium on*, pages 563–574. IEEE, 2006.
- [31] Y. Freund, H. S. Seung, E. Shamir, and N. Tishby. Selective sampling using the query by committee algorithm. *Machine Learning*, 28(2-3):133–168, 1997.
- [32] Andrew Guillory, Erick Chastain, and Jeff Bilmes. Active learning as non-convex optimization. In *International Conference on Artificial Intelligence and Statistics*, pages 201–208, 2009.
- [33] Venkatesan Guruswami and Prasad Raghavendra. Hardness of learning halfspaces with noise. *SIAM Journal on Computing*, 39(2):742–765, 2009.
- [34] S. Hanneke. A bound on the label complexity of agnostic active learning. In *ICML*, 2007.
- [35] S. Hanneke. *Theoretical Foundations of Active Learning*. PhD thesis, Carnegie Mellon University, 2009.
- [36] Steve Hanneke. Rates of convergence in active learning. *The Annals of Statistics*, 39(1):333–361, 2011.
- [37] Steve Hanneke. Theory of disagreement-based active learning. *Foundations and Trends® in Machine Learning*, 7(2-3):131–309, 2014.
- [38] Steve Hanneke and Liu Yang. Surrogate losses in passive and active learning. *arXiv preprint arXiv:1207.3772*, 2012.

- [39] Steve Hanneke, Varun Kanade, and Liu Yang. Learning with a drifting target concept. In *International Conference on Algorithmic Learning Theory*, pages 149–164. Springer, 2015.
- [40] D. Hsu. *Algorithms for Active Learning*. PhD thesis, UC San Diego, 2010.
- [41] Tzu-Kuo Huang, Alekh Agarwal, Daniel Hsu, John Langford, and Robert E. Schapire. Efficient and parsimonious agnostic active learning. *CoRR*, abs/1506.08669, 2015.
- [42] Adam Tauman Kalai, Adam R Klivans, Yishay Mansour, and Rocco A Servedio. Agnostically learning halfspaces. *SIAM Journal on Computing*, 37(6):1777–1805, 2008.
- [43] Michael Kearns and Ming Li. Learning in the presence of malicious errors. *SIAM Journal on Computing*, 22(4):807–837, 1993.
- [44] Adam Klivans and Pravesh Kothari. Embedding Hard Learning Problems Into Gaussian Space. In *APPROX/RANDOM 2014*, pages 793–809, 2014.
- [45] Adam R Klivans, Philip M Long, and Rocco A Servedio. Learning halfspaces with malicious noise. *Journal of Machine Learning Research*, 10(Dec):2715–2740, 2009.
- [46] V. Koltchinskii. Rademacher complexities and bounding the excess risk in active learning. *JMLR*, 2010.
- [47] Sanjeev R Kulkarni, Sanjoy K Mitter, and John N Tsitsiklis. Active learning using arbitrary binary valued queries. *Machine Learning*, 11(1):23–35, 1993.
- [48] Philip M Long. On the sample complexity of pac learning half-spaces against the uniform distribution. *IEEE Transactions on Neural Networks*, 6(6):1556–1559, 1995.
- [49] Pascal Massart and Élodie Nédélec. Risk bounds for statistical learning. *The Annals of Statistics*, pages 2326–2366, 2006.
- [50] Claire Monteleoni. Efficient algorithms for general active learning. In *International Conference on Computational Learning Theory*, pages 650–652. Springer, 2006.
- [51] TS Motzkin and IJ Schoenberg. The relaxation method for linear inequalities. *Canadian Journal of Mathematics*, 6(3):393–404, 1954.
- [52] Francesco Orabona and Nicolo Cesa-Bianchi. Better algorithms for selective sampling. In *Proceedings of the 28th international conference on Machine learning (ICML-11)*, pages 433–440, 2011.
- [53] Maxim Raginsky and Alexander Rakhlin. Lower bounds for passive and active learning. In *Advances in Neural Information Processing Systems*, pages 1026–1034, 2011.
- [54] Burr Settles. Active learning literature survey. *University of Wisconsin, Madison*, 52(55-66):11, 2010.
- [55] Simon Tong and Daphne Koller. Support vector machine active learning with applications to text classification. *Journal of machine learning research*, 2(Nov):45–66, 2001.
- [56] Christopher Tosh and Sanjoy Dasgupta. Diameter-based active learning. In *ICML*, pages 3444–3452, 2017.
- [57] Vladimir N. Vapnik and Alexey Ya. Chervonenkis. On the uniform convergence of relative frequencies of events to their probabilities. *Theory of Probability and Its Applications*, 16(2):264–280, 1971.
- [58] Liwei Wang. Smoothness, disagreement coefficient, and the label complexity of agnostic active learning. *Journal of Machine Learning Research*, 12(Jul):2269–2292, 2011.
- [59] Yining Wang and Aarti Singh. Noise-adaptive margin-based active learning and lower bounds under tsybakov noise condition. In *AAAI*, 2016.
- [60] Chicheng Zhang and Kamalika Chaudhuri. Beyond disagreement-based agnostic active learning. In *Advances in Neural Information Processing Systems 27: Annual Conference on Neural Information Processing Systems 2014, December 8-13 2014, Montreal, Quebec, Canada*, pages 442–450, 2014.
- [61] Yuchen Zhang, Percy Liang, and Moses Charikar. A hitting time analysis of stochastic gradient langevin dynamics. In *COLT*, pages 1980–2022, 2017.

A Additional Related Work

Active Learning. The recent decades have seen much success in both theory and practice of active learning; see the excellent surveys by [54, 37, 25]. On the theory side, many label-efficient active learning algorithms have been proposed and analyzed [21, 31, 24, 11, 34, 10, 27, 14, 16, 35, 46, 40, 15, 58, 36, 2, 60, 41]. Most algorithms are *disagreement-based* algorithms [37], and are not label-optimal due to the conservativeness of their label query policy. In addition, most of these algorithms require either explicit enumeration of classifiers in the hypothesis classes, or solving empirical 0-1 loss minimization problems on sets of examples. The former approach is easily seen to be computationally infeasible, while the latter is proven to be computationally hard as well [5]. The only exception in this family we are aware of is [38]. [38] considers active learning by sequential convex surrogate loss minimization. However, it assumes that the expected convex loss minimizer over all possible functions lies in a pre-specified real-valued function class, which is unlikely to hold in the bounded noise and the adversarial noise settings.

Some recent works [60, 41, 10, 9, 59] provide noise-tolerant active learning algorithms with improved label complexity over disagreement-based approaches. However, they are still computationally inefficient: [60] relies on solving a series of linear program with an exponential number of constraints, which are computationally intractable; [41, 10, 9, 59] relies on solving a series of empirical 0-1 loss minimization problems, which are also computationally hard in the presence of noise [5].

Efficient Learning of Halfspaces. A series of papers have shown the hardness of learning halfspaces with agnostic noise [5, 30, 33, 44, 23]. These results indicate that, to have nontrivial guarantees on learning halfspaces with noise in polynomial time, one has to make additional assumptions on the data distribution over instances and labels.

Many noise models, other than the bounded noise model and the adversarial noise model, has been studied in the literature. A line of work [19, 52, 28, 1] considers parameterized noise models. For instance, [28] gives an efficient algorithm for the setting that $\mathbb{E}[Y|X = x] = u \cdot x$ where u is the optimal classifier. [1] studies a generalization of the above linear noise model, where Y is a multiclass label, and there is a link function Φ such that $\mathbb{E}[Y|X = x] = \nabla\Phi(u \cdot x)$. Their analyses depend heavily on the noise models and it is unknown whether their algorithms can work with more general noise settings. [61] analyzes the problem of learning halfspaces under a new noise condition (as an application of their general analysis of stochastic gradient Langevin dynamics). They assume that the label flipping probability on every x is bounded by $\frac{1}{2} - c|u \cdot x|$, for some $c \in (0, \frac{1}{2}]$. It can be seen that the bounded noise condition implies the noise condition of [61], and it is an interesting open question whether it is possible to extend our algorithm and analysis to their setting.

Under the random classification noise condition [3], [17] gives the first efficient passive learning algorithm of learning halfspaces, by using a modification of Perceptron update (similar to Equation (1)) together with a boosting-type aggregation. [12] proposes an active statistical query algorithm for learning halfspaces. The algorithm proceeds by estimating the distance between the current halfspace and the optimal halfspace. However, it requires a suboptimal number of $\tilde{O}(\frac{d^2}{(1-2\eta)^2})$ labels. In addition, both results above rely on the uniformity over the random classification noise, and it is shown in [7] that this type of statistical query algorithms will fail in the heterogeneous noise setting (in particular the bounded noise setting and the adversarial noise setting).

In the adversarial noise model, we assume that there is a halfspace u with error at most ν over data. The goal is to design an efficient algorithm that outputting a classifier that disagrees with u with probability at most ϵ . [42] proposes an elegant averaging-based algorithm that tolerates an error of at most $\nu = \Omega(\frac{\epsilon}{\ln \frac{1}{\epsilon}})$ assuming that the unlabeled distribution is uniform. However it has a suboptimal label complexity of $\tilde{O}(\frac{d^2}{\epsilon^2})$. Under the assumption that the unlabeled distribution is log-concave or s -concave, the state of the art results [6, 13] give efficient margin-based algorithms that tolerates a noise of $\nu = \tilde{\Omega}(\epsilon)$. As discussed in the main text, such algorithms require a hinge loss minimization procedure that has a running time polynomial in d with an unspecified degree. Finally, [23] gives a PTAS that outputs a classifier with error $(1 + \mu)\nu + \epsilon$, in time $O(\text{poly}(d^{\tilde{O}(\frac{1}{\mu^2})}, \frac{1}{\epsilon}))$. Observe that in the case of $\nu = O(\epsilon)$, the running time is an unspecified high order polynomial in terms of d and $\frac{1}{\epsilon}$.

B Implications to Passive Learning

In this section, we formally describe PASSIVE-PERCEPTRON (Algorithm 3), a passive learning version of Algorithm 1. The algorithmic framework is similar to Algorithm 1, except that it calls Algorithm 4 rather than Algorithm 2.

Algorithm 3 PASSIVE-PERCEPTRON

Input: Initial halfspace v_0 , target error ϵ , confidence δ , sample schedule $\{m_k\}$, band width $\{b_k\}$.

Output: learned halfspace \hat{v} .

- 1: Let $k_0 = \lceil \log_2 \frac{1}{\epsilon} \rceil$.
 - 2: **for** $k = 1, 2, \dots, k_0$ **do**
 - 3: $v_k \leftarrow \text{PASSIVE-MODIFIED-PERCEPTRON}(\mathcal{O}, v_{k-1}, \frac{\pi}{2^k}, \frac{\delta}{k(k+1)}, m_k, b_k)$.
 - 4: **end for**
 - 5: **return** v_{k_0} .
-

Algorithm 4 is similar to Algorithm 2, except that it draws labeled examples from D directly, as opposed to performing label queries on unlabeled examples drawn.

Algorithm 4 PASSIVE-MODIFIED-PERCEPTRON

Input: Initial halfspace w_0 , angle upper bound θ , confidence δ , number of iterations m , band width b .

Output: Improved halfspace w_m .

- 1: **for** $t = 0, 1, 2, \dots, m - 1$ **do**
 - 2: Define region $C_t = \{(x, y) \in \mathbb{S}^{d-1} \times \{-1, +1\} : \frac{b}{2} \leq w_t \cdot x \leq b\}$.
 - 3: Rejection sample $(x_t, y_t) \sim D|_{C_t}$. In other words, repeat drawing example $(x_t, y_t) \sim D$ until it is in C_t .
 - 4: $w_{t+1} \leftarrow w_t - 2\mathbb{1}_{\{y_t w_t \cdot x_t < 0\}} \cdot (w_t \cdot x_t) \cdot x_t$.
 - 5: **end for**
 - 6: **return** w_m .
-

It can be seen that with the same input as ACTIVE-PERCEPTRON, PASSIVE-PERCEPTRON has exactly the same running time, and the number of labeled examples drawn in PASSIVE-PERCEPTRON is exactly the same as the number of unlabeled examples drawn in ACTIVE-PERCEPTRON. Therefore, Corollaries 1 and 2 are immediate consequences of Theorems 2 and 3.

C Proofs of Theorems 2 and 3

In this section, we give straightforward proofs that show Theorem 2 (resp. Theorem 3) are direct consequences of Lemma 2 (resp. Lemma 3). We defer the proofs of Lemmas 2 and 3 to Appendix D.

Theorem 4 (Theorem 2 Restated). *Suppose Algorithm 1 has inputs labeling oracle \mathcal{O} that satisfies η -bounded noise condition with respect to underlying halfspace u , initial halfspace v_0 such that $\theta(v_0, u) \leq \frac{\pi}{2}$, target error ϵ , confidence δ , sample schedule $\{m_k\}$ where $m_k = \lceil \frac{(3200\pi)^3 d}{(1-2\eta)^2} (\ln \frac{(3200\pi)^3 d}{(1-2\eta)^2} + \ln \frac{k(k+1)}{\delta}) \rceil$, band width $\{b_k\}$ where $b_k = \frac{1}{2(600\pi)^2 \ln \frac{m_k^2 k(k+1)}{\delta}} \frac{2^{-k} \pi (1-2\eta)}{\sqrt{d}}$.*

Then with probability at least $1 - \delta$:

1. *The output halfspace v is such that $\mathbb{P}[\text{sign}(v \cdot X) \neq \text{sign}(u \cdot X)] \leq \epsilon$.*
2. *The number of label queries is $O\left(\frac{d}{(1-2\eta)^2} \cdot \ln \frac{1}{\epsilon} \cdot \left(\ln \frac{d}{(1-2\eta)^2} + \ln \frac{1}{\delta} + \ln \ln \frac{1}{\epsilon}\right)\right)$.*
3. *The number of unlabeled examples drawn is $O\left(\frac{d}{(1-2\eta)^3} \cdot \left(\ln \frac{d}{(1-2\eta)^2} + \ln \frac{1}{\delta} + \ln \ln \frac{1}{\epsilon}\right)^2 \cdot \frac{1}{\epsilon} \ln \frac{1}{\epsilon}\right)$.*
4. *The algorithm runs in time $O\left(\frac{d^2}{(1-2\eta)^3} \cdot \left(\ln \frac{d}{(1-2\eta)^2} + \ln \frac{1}{\delta} + \ln \ln \frac{1}{\epsilon}\right)^2 \cdot \frac{1}{\epsilon} \ln \frac{1}{\epsilon}\right)$.*

Proof of Theorem 4. From Lemma 2, we know that for every k , there is an event E_k such that $\mathbb{P}(E_k) \geq 1 - \frac{\delta}{k(k+1)}$, and on event E_k , items 1 to 4 of Lemma 2 hold for input $w_0 = v_{k-1}$, output $w_m = v_k$, $\theta = \frac{\pi}{2^k}$, $\delta = \frac{\delta}{k(k+1)}$.

Define event $E = \cup_{k=1}^{k_0} E_k$. By union bound, $\mathbb{P}(E) \geq 1 - \delta$. We henceforth condition on event E happening.

1. By induction, the final output $v = v_{k_0}$ is such that $\theta(v, u) \leq 2^{-k_0} \pi \leq \epsilon \pi$, implying that $\mathbb{P}[\text{sign}(v \cdot X) \neq \text{sign}(u \cdot X)] \leq \epsilon$.
2. Define the number of label queries to oracle \mathcal{O} at iteration k as m_k . On event E_k , m_k is at most $O\left(\frac{d}{(1-2\eta)^2} \left(\ln \frac{d}{(1-2\eta)^2} + \ln \frac{k}{\delta}\right)\right)$. Thus, the total number of label queries to oracle \mathcal{O} is $\sum_{k=1}^{k_0} m_k$, which is at most

$$k_0 \cdot m_{k_0} = O\left(k_0 \cdot \frac{d}{(1-2\eta)^2} \left(\ln \frac{d}{(1-2\eta)^2} + \ln \frac{k_0}{\delta}\right)\right).$$

Item 2 is proved by noting that $k_0 \leq \log \frac{1}{\epsilon} + 1$.

3. Define the number of unlabeled examples drawn iteration k as n_k . On event E_k , n_k is at most $O\left(\frac{d}{(1-2\eta)^3} \cdot \left(\ln \frac{d}{(1-2\eta)^2} + \ln \frac{k}{\delta}\right)^2 \cdot \frac{1}{\epsilon}\right)$. Thus, the total number of unlabeled examples drawn is $\sum_{k=1}^{k_0} n_k$, which is at most

$$k_0 n_{k_0} = O\left(k_0 \cdot \frac{d}{(1-2\eta)^3} \cdot \left(\ln \frac{d}{(1-2\eta)^2} + \ln \frac{k_0}{\delta}\right)^2 \cdot \frac{1}{\epsilon}\right).$$

Item 3 is proved by noting that $k_0 \leq \log \frac{1}{\epsilon} + 1$.

4. Item 4 is immediate from Item 3 and the fact that the time for processing each example is at most $O(d)$. \square

Theorem 5 (Theorem 3 Restated). *Suppose Algorithm 1 has inputs labeling oracle \mathcal{O} that satisfies ν -adversarial noise condition with respect to underlying halfspace u , initial halfspace v_0 such that $\theta(v_0, u) \leq \frac{\pi}{2}$, target error ϵ , confidence δ , sample schedule $\{m_k\}$ where $m_k = \lceil (3200\pi)^3 d (\ln(3200\pi)^3 d + \ln \frac{k(k+1)}{\delta}) \rceil$, band width $\{b_k\}$ where $b_k = \frac{1}{2(600\pi)^2 \ln \frac{m_k^2 k(k+1)}{\delta}} \frac{2^{-k} \pi}{\sqrt{d}}$. Additionally $\nu \leq \frac{\epsilon}{384(600\pi)^4 (4 \ln((3200\pi)^3 d) + 8 \ln \frac{1}{\epsilon} + \ln \frac{1}{\delta})}$. Then with probability at least $1 - \delta$:*

1. The output halfspace v is such that $\mathbb{P}[\text{sign}(v \cdot X) \neq \text{sign}(u \cdot X)] \leq \epsilon$.
2. The number of label queries is $O\left(d \cdot \ln \frac{1}{\epsilon} \cdot \left(\ln d + \ln \frac{1}{\delta} + \ln \ln \frac{1}{\epsilon}\right)\right)$.
3. The number of unlabeled examples drawn is $O\left(d \cdot \left(\ln d + \ln \frac{1}{\delta} + \ln \ln \frac{1}{\epsilon}\right)^2 \cdot \frac{1}{\epsilon} \ln \frac{1}{\epsilon}\right)$.
4. The algorithm runs in time $O\left(d^2 \cdot \left(\ln d + \ln \frac{1}{\delta} + \ln \ln \frac{1}{\epsilon}\right)^2 \cdot \frac{1}{\epsilon} \ln \frac{1}{\epsilon}\right)$.

Proof of Theorem 5. From Lemma 3, we know that for every k , there is an event E_k such that $\mathbb{P}(E_k) \geq 1 - \frac{\delta}{k(k+1)}$, and on event E_k , items 1 to 4 of Lemma 3 hold for input $w_0 = v_k$, output $w_m = v_{k+1}$, $\theta = \frac{\pi}{2^k}$.

Define event $E = \cup_{k=1}^{k_0} E_k$. By union bound, $\mathbb{P}(E) \geq 1 - \delta$. We henceforth condition on event E happening.

1. By induction, the final output $v = v_{k_0}$ is such that that $\theta(v, u) \leq 2^{-k_0} \pi \leq \epsilon \pi$, implying that $\mathbb{P}[\text{sign}(v \cdot X) \neq \text{sign}(u \cdot X)] \leq \epsilon$.

2. Define the number of label queries to oracle \mathcal{O} at iteration k as m_k . On event E_k , m_k is at most $O\left(d\left(\ln d + \ln \frac{k}{\delta}\right)\right)$. Thus, the total number of label queries to oracle \mathcal{O} is $\sum_{k=1}^{k_0} m_k$, which is at most

$$k_0 \cdot m_{k_0} = O\left(k_0 \cdot d\left(\ln d + \ln \frac{k_0}{\delta}\right)\right).$$

Item 2 is proved by noting that $k_0 \leq \log \frac{1}{\epsilon} + 1$.

3. Define the number of unlabeled examples drawn iteration k as n_k . On event E_k , n_k is at most $O\left(d \cdot \left(\ln d + \ln \frac{k}{\delta}\right)^2 \cdot \frac{1}{\epsilon}\right)$. Thus, the total number of unlabeled examples drawn is $\sum_{k=1}^{k_0} n_k$, which is at most

$$k_0 n_{k_0} = O\left(k_0 \cdot d \cdot \left(\ln d + \ln \frac{k_0}{\delta}\right)^2 \cdot \frac{1}{\epsilon}\right).$$

Item 3 is proved by noting that $k_0 \leq \log \frac{1}{\epsilon} + 1$.

4. Item 4 is immediate from Item 3 and the fact that the time for processing each example is at most $O(d)$. \square

D Performance Guarantees of MODIFIED-PERCEPTRON

In this section, we prove Lemmas 2 and 3, which guarantees the shrinkage of θ_t . Two major building blocks of Lemma 2 (resp. Lemma 3) are Lemmas 7 and 9 (resp. Lemmas 7 and 10). In essence, Lemma 7 turns per-iteration in-expectation guarantees provided by Lemmas 9 and 10 into high probability upper bounds on the final θ_m . We present Lemma 7 and its proof in detail in this section, and defer Lemmas 9 and 10 to Appendix E.

Lemma 4 (Lemma 2 Restated). *Suppose Algorithm 2 has inputs labeling oracle \mathcal{O} that satisfies η -bounded noise condition with respect to underlying halfspace u , initial vector w_0 and angle upper bound $\theta \in (0, \frac{\pi}{2})$ such that $\theta(w_0, u) \leq \theta$, confidence δ , number of iterations $m = \lceil \frac{(3200\pi)^3 d}{(1-2\eta)^2} (\ln \frac{(3200\pi)^3 d}{(1-2\eta)^2} + \ln \frac{1}{\delta}) \rceil$, band width $b = \frac{1}{2(600\pi)^2 \ln \frac{m^2}{\delta}} \frac{\theta(1-2\eta)}{\sqrt{d}}$. then with probability at least $1 - \delta$:*

1. The output halfspace w_m is such that $\theta(w_m, u) \leq \frac{\theta}{2}$.
2. The number of label queries is $O\left(\frac{d}{(1-2\eta)^2} \left(\ln \frac{d}{(1-2\eta)^2} + \ln \frac{1}{\delta}\right)\right)$.
3. The number of unlabeled examples drawn is $O\left(\frac{d}{(1-2\eta)^3} \cdot \left(\ln \frac{d}{(1-2\eta)^2} + \ln \frac{1}{\delta}\right)^2 \cdot \frac{1}{\theta}\right)$.
4. The algorithm runs in time $O\left(\frac{d^2}{(1-2\eta)^3} \cdot \left(\ln \frac{d}{(1-2\eta)^2} + \ln \frac{1}{\delta}\right)^2 \cdot \frac{1}{\theta}\right)$.

Proof of Lemma 4. We show that each item holds with high probability respectively.

1. It can be verified that conditions for Lemma 7 are satisfied with $\zeta = 1 - 2\eta$ (item 3 in the condition follows from Lemma 9, and item 4 in the condition follows from Lemma 6). This shows that items 1 with probability at least $1 - \delta/2$.
2. By the definition of m , the number of label queries is $m = O\left(\frac{d}{(1-2\eta)^2} \log \frac{d}{\delta(1-2\eta)^2}\right)$.

3. As for the number of unlabeled examples drawn by the algorithm, at each iteration $t \in [0, m]$, it takes Z_t trials to hit an example in $[\frac{b}{2}, b]$, where Z_t is a $\text{Geometric}(p)$ random variable with $p = \mathbb{P}_{x \sim D_X}[w_t \cdot x \in [\frac{b}{2}, b]]$. From Lemma 18, $p \geq \frac{\sqrt{d}}{8\pi}b = \frac{\tilde{c}(1-2\eta)\theta}{8\pi} = \Omega(\frac{(1-2\eta)\theta}{\ln \frac{d}{\delta(1-2\eta)^2}})$.

Define event

$$E := \left\{ Z_1 + \dots + Z_m \leq \frac{2m}{p} \right\}$$

From Lemma 16 and the choice of m , $\mathbb{P}[E] \geq 1 - \frac{\delta}{2}$. Thus, on event E , the total number of unlabeled examples drawn is at most $\frac{2m}{p} = O(\frac{d}{(1-2\eta)^3} \log^2 \frac{d}{\delta(1-2\eta)^2} \frac{1}{\theta})$.

4. Observe that the time complexity for processing each example is at most $O(d)$. This shows that on event E , the total running time of the algorithm is at most $O(d \cdot \frac{2m}{p}) = O(\frac{d^2}{(1-2\eta)^3} \log^2 \frac{d}{\delta(1-2\eta)^2} \frac{1}{\theta})$.

Therefore, by a union bound, with probability at least $1 - \delta$, items 1 to 4 hold simultaneously. \square

Lemma 5 (Lemma 3 restated). *Suppose Algorithm 2 has inputs labeling oracle \mathcal{O} that satisfies ν -adversarial noise condition with respect to underlying halfspace u , initial vector w_0 and angle upper bound θ such that $\theta(w_0, u) \leq \theta$, confidence δ , number of iterations $m = \lceil (3200\pi)^3 d \ln \frac{(3200\pi)^3 d}{\delta} \rceil$, band width $b = \frac{1}{2(600\pi)^2 \ln \frac{m^2}{\delta}} \cdot \frac{\theta}{\sqrt{d}}$. Additionally $\nu \leq \frac{\theta}{384(600\pi)^4 \ln \frac{m^2}{\delta}}$. Then with probability at least $1 - \delta$:*

1. The output halfspace w_m is such that $\theta(w_m, u) \leq \frac{\theta}{2}$.
2. The number of label queries is $O\left(d \cdot (\ln d + \ln \frac{1}{\delta})\right)$.
3. The number of unlabeled examples drawn is $O\left(d \cdot (\ln d + \ln \frac{1}{\delta})^2 \cdot \frac{1}{\theta}\right)$.
4. The algorithm runs in time $O\left(d^2 \cdot (\ln d + \ln \frac{1}{\delta})^2 \cdot \frac{1}{\theta}\right)$.

Proof of Lemma 5. We show that each item holds with high probability respectively.

1. It can be verified that conditions for Lemma 7 are satisfied with $\zeta = 1$ (item 3 in the condition follows from Lemma 10, and item 4 in the condition follows from Lemma 6). This gives items 1 with probability at least $1 - \delta/2$.
2. By the definition of m , the number of label queries is $m = O\left(d \cdot (\ln d + \ln \frac{1}{\delta})\right)$.
3. The number of unlabeled examples drawn by the algorithm can be analyzed similarly as in the previous proof, which is at most $\frac{2m}{p} = O\left(d \cdot (\ln d + \ln \frac{1}{\delta})^2 \cdot \frac{1}{\theta}\right)$ with probability at least $1 - \delta/2$.
4. Observe that the time complexity for processing each example is at most $O(d)$. This gives that on event E , the total running time of the algorithm is at most $O(d \cdot \frac{2m}{p}) = O\left(d^2 \cdot (\ln d + \ln \frac{1}{\delta})^2 \cdot \frac{1}{\theta}\right)$.

Therefore, by a union bound, with probability at least $1 - \delta$, items 1 to 4 hold simultaneously. \square

Next we show a technical lemma used in the above proofs, coarsely bounding the difference between $\cos \theta_{t+1}$ and $\cos \theta_t$.

Lemma 6. Suppose $0 < \tilde{c}, \zeta < 1$, $b = \frac{\tilde{c}\zeta\theta}{\sqrt{d}} \leq 1$, and (x_t, y_t) is drawn from distribution $D|_{R_t}$ where $R_t = \left\{ (x, y) : x \cdot w_t \in [\frac{b}{2}, b] \right\}$. If unit vector w_t has angle θ_t with u such that $\theta_t \leq \frac{5}{3}\theta$, then update (5) has the following guarantee: $|\cos \theta_{t+1} - \cos \theta_t| \leq \frac{16\tilde{c}\zeta\theta^2}{3\sqrt{d}}$.

Proof. By Lemma 8,

$$\cos \theta_{t+1} - \cos \theta_t = -2\mathbb{1} \{y_t \neq \text{sign}(w_t \cdot x_t)\} (w_t \cdot x_t) \cdot (u \cdot x_t).$$

Firstly, note $|\cos \theta_{t+1} - \cos \theta_t| \leq 2|w_t \cdot x_t| |u \cdot x_t| \leq 2b|u \cdot x_t|$.

Observe that

$$\begin{aligned} & |u \cdot x_t| \\ & \leq |w_t \cdot x_t| + |(u - w_t) \cdot x_t| \\ & \leq b + 2 \sin \frac{\theta_t}{2} \\ & \leq b + \theta_t \end{aligned}$$

Thus, we have $|\cos \theta_{t+1} - \cos \theta_t| \leq 2b(b + \theta_t) = \frac{2\tilde{c}^2\zeta^2\theta^2}{d} + \frac{2\tilde{c}\zeta\theta\theta_t}{\sqrt{d}} \leq \frac{16\tilde{c}\zeta\theta^2}{3\sqrt{d}}$. \square

Lemma 7. Suppose $0 < \zeta < 1$, and the following conditions hold:

1. Initial unit vector w_0 has angle $\theta_0 = \theta(w_0, u) \leq \theta \leq \frac{27}{50}\pi$ with u ;
2. Integer $m = \lceil \frac{(3200\pi)^3 d}{\zeta^2} (\ln \frac{(3200\pi)^3 d}{\zeta^2} + \ln \frac{1}{\delta}) \rceil$ and $\tilde{c} = \frac{1}{2(600\pi)^2 \ln \frac{m^2}{\delta}}$;
3. For all t , if $\frac{1}{4}\theta \leq \theta_t \leq \frac{5}{3}\theta$, then $\mathbb{E}[\cos \theta_{t+1} - \cos \theta_t | \theta_t] \geq \frac{\tilde{c}}{100\pi} \frac{\zeta^2 \theta^2}{d}$;
4. For all t , if $\theta_t \leq \frac{5}{3}\theta$, then $|\cos \theta_{t+1} - \cos \theta_t| \leq \frac{16\tilde{c}\zeta\theta^2}{3\sqrt{d}}$ holds with probability 1.

Then with probability at least $1 - \delta/2$, $\theta_m \leq \frac{1}{2}\theta$.

Proof. Define random variable D_t as:

$$D_t := \left(\cos \theta_{t+1} - \cos \theta_t - \frac{\tilde{c}}{100\pi} \frac{\zeta^2 \theta^2}{d} \right) \mathbb{1} \left\{ \frac{1}{4}\theta \leq \theta_t \leq \frac{5}{3}\theta \right\}$$

Note that $\mathbb{E}[D_t | \theta_t] \geq 0$ and from Lemma 6, $|D_t| \leq |\cos \theta_{t+1} - \cos \theta_t| + \frac{\tilde{c}}{100\pi} \frac{\zeta^2 \theta^2}{d} \leq \frac{6\tilde{c}\zeta\theta^2}{\sqrt{d}}$. Therefore, $\{D_t\}$ is a bounded submartingale difference sequence. By Azuma's Inequality (see Lemma 15) and union bound, define event

$$E = \left\{ \text{for all } 0 \leq t_1 \leq t_2 \leq m, \sum_{s=t_1}^{t_2-1} D_s \geq -\frac{6\tilde{c}\zeta\theta^2}{\sqrt{d}} \sqrt{2(t_2 - t_1) \ln \frac{2m^2}{\delta}} \right\}$$

Then $\mathbb{P}(E) \geq 1 - \frac{\delta}{2}$.

We now condition on event E . We break the subsequent analysis into two parts: (1) Show that there exists some t such that θ_t goes below $\frac{1}{4}\theta$. (2) Show that θ_t must stay below $\frac{1}{2}\theta$ afterwards.

1. First, it can be checked by algebra that $m \geq \frac{200\pi d}{\zeta^2 \tilde{c}}$. We show the following claim.

Claim 1. There exists some $t \in [0, m]$, such that $\theta_t < \frac{1}{4}\theta$.

Proof. We first show that it is impossible for all $t \in [0, m]$ such that $\theta_t \in [\frac{1}{4}\theta, \frac{5}{3}\theta]$. To this end, assume this holds for the sake of contradiction. In this case, for all $t \in [0, m]$, $D_t = \cos \theta_{t+1} - \cos \theta_t - \frac{\tilde{c}}{100\pi} \frac{\zeta^2 \theta^2}{d}$. Therefore,

$$\begin{aligned} & \cos \theta_m - \cos \theta_0 \\ &= \sum_{s=0}^{m-1} D_s + \frac{\tilde{c}}{100\pi} \frac{\zeta^2 \theta^2}{d} m \\ &\geq \frac{\tilde{c}}{100\pi} \frac{\zeta^2 \theta^2}{d} m - \frac{6\tilde{c}\zeta\theta^2}{\sqrt{d}} \sqrt{2m \ln \frac{m^2}{\delta}} \\ &\geq \frac{\theta^2}{100\pi} \left[\frac{\tilde{c}\zeta^2 m}{d} - \sqrt{\frac{\tilde{c}\zeta^2 m}{d}} \right] \\ &\geq \theta^2 \end{aligned}$$

where the first inequality is from the definition of event E , the second inequality is from that $\tilde{c} = \frac{1}{2(600\pi)^2 \ln \frac{m^2}{\delta}}$, the third inequality is from that $\frac{\tilde{c}\zeta^2 m}{d} \geq 200\pi$.

Since $\cos \theta_0 \geq \cos \theta \geq 1 - \frac{1}{2}\theta^2$, this gives that $\cos \theta_m \geq 1 + \frac{1}{2}\theta^2 > 1$, contradiction.

Next, define $\tau := \min \left\{ t \geq 0 : \theta_t \notin [\frac{1}{4}\theta, \frac{5}{3}\theta] \right\}$. We now know that $\tau \leq m$ by the reasoning above. It suffices to show that $\theta_\tau < \frac{1}{4}\theta$, that is, the first time when θ_t goes outside the interval $[\frac{1}{4}\theta, \frac{5}{3}\theta]$, it must be crossing the left boundary as opposed to the right one.

By the definition of τ , for all $0 \leq t \leq \tau - 1$, $\theta_t \in [\frac{1}{4}\theta, \frac{5}{3}\theta]$. Thus,

$$\begin{aligned} & \cos \theta_\tau - \cos \theta_0 \\ &= \sum_{t=0}^{\tau-1} D_t + \frac{\tilde{c}}{100\pi} \frac{\zeta^2 \theta^2}{d} \tau \\ &\geq \frac{\tilde{c}}{100\pi} \frac{\zeta^2 \theta^2}{d} \tau - \frac{6\tilde{c}\zeta\theta^2}{\sqrt{d}} \sqrt{\tau \ln \frac{m^2}{\delta}} \\ &\geq -900\pi \ln \frac{m^2}{\delta} \tilde{c} \theta^2 \geq -\frac{1}{75} \theta^2 \end{aligned} \tag{3}$$

where the first inequality is by the definition of E ; the second inequality is by minimizing over $\tau \in [0, m]$; the last inequality is from the definition of \tilde{c} .

Now, if $\theta_\tau \geq \frac{5}{3}\theta$, then

$$\begin{aligned} \cos \theta_\tau - \cos \theta_0 &\leq \cos \frac{5}{3}\theta - \cos \theta \\ &\leq 1 - \frac{1}{5} \left(\frac{5}{3} \right)^2 \theta^2 - 1 + \frac{1}{2} \theta^2 \\ &< -\frac{1}{75} \theta^2 \end{aligned}$$

where the first inequality follows from $\theta_\tau \geq \frac{5}{3}\theta$ and $\theta_0 \leq \theta$, and the second inequality follows from Lemma 13. This contradicts with Inequality (3).

This gives that $\theta_\tau < \frac{5}{3}\theta$. Since $\theta_\tau \notin [\frac{1}{4}\theta, \frac{5}{3}\theta]$, it must be the case that $\theta_\tau < \frac{1}{4}\theta$. \square

2. We now show the following claim to conclude the proof.

Claim 2. θ_m , the angle in the last iteration, is at most $\frac{1}{2}\theta$.

Proof. Define $\sigma = \max \{ t \in [0, m] : \theta_t < \frac{1}{4}\theta \}$. by Claim 1, such σ is well-defined on event E . We now show that θ_t will not exceed $\frac{1}{2}\theta$ afterwards. Assume for the sake of contradiction that for some $t > \sigma$, $\theta_t > \frac{1}{2}\theta$.

Now define $\gamma := \min \{t > \sigma : \theta_t > \frac{1}{2}\theta\}$. We know by the definitions of σ and γ , for all $t \in [\sigma + 1, \gamma - 1]$, $\theta_t \in [\frac{1}{4}\theta, \frac{1}{2}\theta]$. Thus,

$$\begin{aligned}
& \cos \theta_\gamma - \cos \theta_{\sigma+1} \\
&= \sum_{t=\sigma+1}^{\gamma-1} D_t + \frac{\tilde{c}}{100\pi} \frac{\zeta^2 \theta^2}{d} (\gamma - \sigma - 1) \\
&\geq \frac{\tilde{c}}{100\pi} \frac{\zeta^2 \theta^2}{d} (\gamma - \sigma - 1) - \frac{6\tilde{c}\zeta\theta^2}{\sqrt{d}} \sqrt{(\gamma - \sigma - 1) \ln \frac{m^2}{\delta}} \\
&\geq -900\pi \ln \frac{m^2}{\delta} \tilde{c} \geq -\frac{1}{75} \theta^2
\end{aligned} \tag{4}$$

where the first inequality is by the definition of E ; the second inequality is by minimization over $\gamma - \sigma - 1 \in [0, m]$; the last inequality is from the definition of \tilde{c} .

On the other hand, $\theta_\gamma > \frac{1}{2}\theta$ and $\theta_\sigma < \frac{1}{4}\theta$. We have

$$\begin{aligned}
\cos \theta_\gamma - \cos \theta_{\sigma+1} &\leq \cos \theta_\gamma - \cos \theta_\sigma + \frac{6\tilde{c}\zeta\theta^2}{\sqrt{d}} \\
&\leq \cos \frac{\theta}{2} - \cos \frac{\theta}{4} + \frac{6\tilde{c}\zeta\theta^2}{\sqrt{d}} \\
&\leq 1 - \frac{1}{20}\theta^2 - 1 + \frac{1}{32}\theta^2 + \frac{6\tilde{c}\zeta\theta^2}{\sqrt{d}} \\
&< -\frac{1}{75}\theta^2
\end{aligned}$$

where the first inequality follows from Lemma 6, the third follows from Lemma 13, and the last follows from algebra. This contradicts with Inequality (4). \square

Thus, with probability at least $1 - \delta/2$, $\theta_m \leq \frac{1}{2}\theta$. \square

E Progress Measure Analysis

In this section, we prove two key lemmas on $\cos \theta_t$ (Lemmas 9 and 10), our measure of progress. We show that under the bounded noise model and the adversarial noise model, $\cos \theta_t$ increases by a decent amount in expectation at each iteration of MODIFIED-PERCEPTRON, with appropriate settings of bandwidth b .

We begin with a generic lemma that gives a recurrence of $\cos \theta_t$ when the modified Perceptron update rule (1) is applied to a new example.

Lemma 8. *Suppose $w_t \in \mathbb{R}^d$ is a unit vector, and (x_t, y_t) is an labeled example where $x_t \in \mathbb{R}^d$ is a unit vector and $y_t \in \{-1, +1\}$. Let $\theta_t = \theta(w_t, x_t)$. Then, update*

$$w_{t+1} \leftarrow w_t - 2\mathbb{1}\{y_t w_t \cdot x_t < 0\} (w_t \cdot x_t) \cdot x_t \tag{5}$$

gives an unit vector w_{t+1} such that

$$\cos \theta_{t+1} = \cos \theta_t - 2\mathbb{1}\{y_t w_t \cdot x_t < 0\} (w_t \cdot x_t) \cdot (u \cdot x_t) \tag{6}$$

Proof. We first show that w_{t+1} is still a unit vector. If $y_t = \text{sign}(w_t \cdot x_t)$, then $w_{t+1} = w_t$, thus it is still a unit vector; otherwise $w_{t+1} = w_t - 2(w_t \cdot x_t) \cdot x_t$. This gives that

$$\|w_{t+1}\|^2 = \|w_t\|^2 - 4(w_t \cdot x_t)(w_t \cdot x_t) + \|2(w_t \cdot x_t) \cdot x_t\|^2 = \|w_t\|^2 = 1.$$

This implies that $\cos \theta_t = w_t \cdot u$, and $\cos \theta_{t+1} = w_{t+1} \cdot u$. Now, taking inner products with u on both sides of Equation (5), we get

$$w_{t+1} \cdot u = w_t \cdot u - 2\mathbb{1}\{y_t w_t \cdot x_t < 0\} (w_t \cdot x_t) \cdot (u \cdot x_t)$$

which is equivalent to Equation (6). \square

E.1 Progress Measure under Bounded Noise

Lemma 9 (Progress Measure under Bounded Noise). *Suppose $0 < \tilde{c} < \frac{1}{288}$, $b = \frac{\tilde{c}(1-2\eta)\theta}{\sqrt{d}}$, $\theta \leq \frac{27}{50}\pi$, and (x_t, y_t) is drawn from $D|_{R_t}$, where $R_t = \{(x, y) : x \cdot w_t \in [\frac{b}{2}, b]\}$. Meanwhile, the oracle \mathcal{O} satisfies the η -bounded noise condition. If unit vector w_t has angle θ_t with u such that $\frac{1}{4}\theta \leq \theta_t \leq \frac{5}{3}\theta$, then update (5) has the following guarantee:*

$$\mathbb{E} [\cos \theta_{t+1} - \cos \theta_t \mid \theta_t] \geq \frac{\tilde{c}}{100\pi} \frac{(1-2\eta)^2 \theta^2}{d}.$$

Proof. Define random variable $\xi = x_t \cdot w_t$. By the tower property of conditional expectation, $\mathbb{E} [\cos \theta_{t+1} - \cos \theta_t \mid \theta_t] = \mathbb{E} [\mathbb{E} [\cos \theta_{t+1} - \cos \theta_t \mid \theta_t, \xi] \mid \theta_t]$. Thus, it suffices to show

$$\mathbb{E} [\cos \theta_{t+1} - \cos \theta_t \mid \theta_t, \xi] \geq \frac{\tilde{c}}{100\pi} \frac{(1-2\eta)^2 \theta^2}{d}$$

for all $\theta_t \in [\frac{1}{4}\theta, \frac{5}{3}\theta]$ and $\xi \in [\frac{1}{2}b, b]$.

By Lemma 8, we know that

$$\cos \theta_{t+1} - \cos \theta_t = -2\mathbb{1} \{y_t \neq \text{sign}(w_t \cdot x_t)\} (w_t \cdot x_t) \cdot (u \cdot x_t).$$

We simplify $\mathbb{E} [\cos \theta_{t+1} - \cos \theta_t \mid \theta_t, \xi]$ as follows:

$$\begin{aligned} & \mathbb{E} [\cos \theta_{t+1} - \cos \theta_t \mid \theta_t, \xi] \\ &= \mathbb{E} [-2\xi u \cdot x_t \mathbb{1} \{y_t = -1\} \mid \theta_t, \xi] \\ &= \mathbb{E} [-2\xi u \cdot x_t (\mathbb{1} \{u \cdot x_t > 0, y_t = -1\} + \mathbb{1} \{u \cdot x_t < 0, y_t = -1\}) \mid \theta_t, \xi] \\ &\geq \mathbb{E} [-2\xi u \cdot x_t (\eta \mathbb{1} \{u \cdot x_t > 0\} + (1-\eta) \mathbb{1} \{u \cdot x_t < 0\}) \mid \theta_t, \xi] \\ &= \mathbb{E} [-2\xi u \cdot x_t (\eta + (1-2\eta) \mathbb{1} \{u \cdot x_t < 0\}) \mid \theta_t, \xi] \\ &= -2\xi \left(\eta \mathbb{E} [u \cdot x_t \mid \theta_t, \xi] + (1-2\eta) \mathbb{E} [u \cdot x_t \mathbb{1} \{u \cdot x_t < 0\} \mid \theta_t, \xi] \right) \end{aligned} \quad (7)$$

where the second equality is from algebra, the first inequality is from that $\mathbb{P}[y_t = -1 \mid u \cdot x_t > 0] \leq \eta$ and $\mathbb{P}[y_t = -1 \mid u \cdot x_t < 0] \geq 1 - \eta$, the last two equalities are from algebra.

By Lemma 19 and that $0 \leq \theta_t \leq \frac{5}{3}\theta \leq \frac{9}{10}\pi$, $\mathbb{E}[u \cdot x_t \mid \theta_t, \xi] \leq \xi$ and $\mathbb{E}[u \cdot x_t \mathbb{1} \{u \cdot x_t < 0\} \mid \theta_t, \xi] \leq \xi - \frac{\theta_t}{36\sqrt{d}}$.

Thus,

$$\begin{aligned} & \mathbb{E} [\cos \theta_{t+1} - \cos \theta_t \mid \theta_t, \xi] \\ &\geq -2\xi \left(\xi \eta + \left(\xi - \frac{\theta_t}{36\sqrt{d}} \right) (1-2\eta) \right) \\ &\geq 2\xi \left(\frac{\theta_t}{36\sqrt{d}} (1-2\eta) - \xi \right) \\ &\geq b \frac{\theta_t}{72\sqrt{d}} (1-2\eta) \\ &\geq \frac{\tilde{c}}{100\pi} \frac{(1-2\eta)^2 \theta^2}{d} \end{aligned}$$

where the first and second inequalities are from algebra, the third inequality is from that $\xi \leq b \leq \frac{\theta(1-2\eta)}{288\sqrt{d}} \leq \frac{\theta_t(1-2\eta)}{72\sqrt{d}}$, and that $\xi \geq \frac{b}{2}$. the last inequality is by expanding $b = \frac{\tilde{c}(1-2\eta)\theta}{\sqrt{d}}$ and that $\theta_t \geq \frac{\theta}{4}$.

In conclusion, if $\frac{1}{4}\theta \leq \theta_t \leq \frac{5}{3}\theta$, then $\mathbb{E} [\cos \theta_{t+1} - \cos \theta_t \mid \theta_t, \xi] \geq \frac{\tilde{c}}{100\pi} \frac{(1-2\eta)^2 \theta^2}{d}$ for $\xi \in [\frac{b}{2}, b]$. The lemma follows. \square

E.2 Progress Measure under Adversarial Noise

Lemma 10 (Progress Measure under Adversarial Noise). *Suppose $0 \leq \tilde{c} \leq \frac{1}{100\pi}$, $b = \frac{\tilde{c}\theta}{\sqrt{d}}$, $\theta \leq \frac{27}{50}\pi$, and (x_t, y_t) is drawn from distribution $D|_{R_t}$ where $R_t = \{(x, y) : x \cdot w_t \in [\frac{b}{2}, b]\}$. Meanwhile, the oracle \mathcal{O} satisfies the ν -adversarial noise condition where $\nu \leq \frac{\tilde{c}\theta}{192(200\pi)^2}$. If unit vector w_t has angle θ_t with u such that $\frac{1}{4}\theta \leq \theta_t \leq \frac{5}{3}\theta$, then update (5) has the following guarantee:*

$$\mathbb{E} [\cos \theta_{t+1} - \cos \theta_t \mid \theta_t] \geq \frac{\tilde{c}}{100\pi} \frac{\theta^2}{d}.$$

Proof. Define random variable $\xi = x_t \cdot w_t$.

By Lemma 8, we know that

$$\cos \theta_{t+1} - \cos \theta_t = -2\mathbb{1}\{y_t \neq \text{sign}(w_t \cdot x_t)\} (w_t \cdot x_t) \cdot (u \cdot x_t).$$

We expand $\mathbb{E} [\cos \theta_{t+1} - \cos \theta_t \mid \theta_t]$ as follows.

$$\begin{aligned} & \mathbb{E} [\cos \theta_{t+1} - \cos \theta_t \mid \theta_t] \\ &= \mathbb{E} [-2(w_t \cdot x_t)(u \cdot x_t)\mathbb{1}\{y_t = -1\} \mid \theta_t] \\ &= \mathbb{E} [-2(w_t \cdot x_t)(u \cdot x_t)\mathbb{1}\{u \cdot x_t < 0\} \mid \theta_t] \\ &\quad + \mathbb{E} [2(w_t \cdot x_t)(u \cdot x_t)(\mathbb{1}\{y_t = +1, u \cdot x_t < 0\} - \mathbb{1}\{y_t = -1, u \cdot x_t > 0\}) \mid \theta_t] \end{aligned} \quad (8)$$

We bound the two terms separately. Firstly,

$$\begin{aligned} & \mathbb{E} [-2(w_t \cdot x_t)(u \cdot x_t)\mathbb{1}\{u \cdot x_t < 0\} \mid \theta_t] \\ &\geq -b\mathbb{E} [(u \cdot x_t)\mathbb{1}\{u \cdot x_t < 0\} \mid \theta_t] \\ &= -b\mathbb{E} [\mathbb{E} [(u \cdot x_t)\mathbb{1}\{u \cdot x_t < 0\} \mid \theta_t, b] \mid \theta_t] \\ &\geq b\left(\frac{\theta_t}{36\sqrt{d}} - b\right) \end{aligned} \quad (9)$$

where the first inequality is from that $-(u \cdot x_t)\mathbb{1}\{u \cdot x_t < 0\} \geq 0$ and $w_t \cdot x_t \geq \frac{b}{2}$, the equality is from the tower property of conditional expectation, the second inequality is from Lemma 19.

Secondly,

$$\begin{aligned} & \left| \mathbb{E} [2(w_t \cdot x_t)(u \cdot x_t)(\mathbb{1}\{y_t = +1, u \cdot x_t < 0\} - \mathbb{1}\{y_t = -1, u \cdot x_t > 0\}) \mid \theta_t] \right| \\ &\leq 2b\mathbb{E} [|u \cdot x_t|\mathbb{1}\{y_t \neq \text{sign}(u \cdot x_t)\} \mid \theta_t] \\ &\leq 2b\sqrt{\mathbb{E} [\mathbb{1}\{y_t \neq \text{sign}(u \cdot x_t)\} \mid \theta_t] \cdot \mathbb{E} [(u \cdot x_t)^2 \mid \theta_t]} \\ &= 2b\sqrt{\mathbb{P} [y_t \neq \text{sign}(u \cdot x_t) \mid \theta_t] \mathbb{E} [\mathbb{E} [(u \cdot x_t)^2 \mid \theta_t, \xi] \mid \theta_t]} \end{aligned} \quad (10)$$

where the first inequality is from that $|\mathbb{E}[X]| \leq \mathbb{E}|X|$, and $w_t \cdot x_t \leq b$, the second inequality is from Cauchy-Schwarz, the third equality is by algebra.

Now we look at the two terms inside the square root. First,

$$\begin{aligned} & \mathbb{P} [y_t \neq \text{sign}(u \cdot x_t) \mid \theta_t] \\ &= \mathbb{P}_{x \sim D|_{R_t}} [y \neq \text{sign}(u \cdot x)] \\ &\leq \frac{\mathbb{P}_{(x,y) \sim D} [y \neq \text{sign}(u \cdot x)]}{\mathbb{P}_{x \sim D} [x_1 \in [b/2, b]]} \\ &\leq \frac{8\pi\nu}{\tilde{c}\theta} \\ &\leq \frac{1}{16(200\pi)^2} \end{aligned}$$

where the first inequality is from that $\mathbb{P}[A|B] \leq \frac{\mathbb{P}[A]}{\mathbb{P}[B]}$, the second inequality is from Lemma 18 that $\mathbb{P}_{x \sim D} [x_1 \in [b/2, b]] \geq \frac{\sqrt{d}}{8\pi} b = \frac{\tilde{c}\theta}{8\pi}$, and the last inequality is by our assumption on ν .

Second, fix $\xi \in [\frac{b}{2}, b]$, $\xi \leq b \leq \frac{\theta_t}{4\sqrt{d}}$. Item 2 of Lemma 19 implies that $\mathbb{E}[(u \cdot x_t)^2 \mid \theta_t, \xi] \leq \frac{5\theta_t^2}{d}$.

By the tower property of conditional expectation, $\mathbb{E}[(u \cdot x_t)^2 \mid \theta_t] \leq \frac{5\theta_t^2}{d}$. Continuing Equation (10), we get

$$\left| \mathbb{E} [2(w_t \cdot x_t)(u \cdot x_t)(\mathbb{1}\{y_t = +1, u \cdot x_t < 0\} - \mathbb{1}\{y_t = -1, u \cdot x_t > 0\}) \mid \theta_t] \right| \leq b \frac{\theta_t}{100\pi\sqrt{d}}. \quad (11)$$

Continuing Equation (8), we have

$$\begin{aligned} & \mathbb{E} [\cos \theta_{t+1} - \cos \theta_t \mid \theta_t] \\ & \geq b \left(\frac{\theta_t}{36\sqrt{d}} - \frac{\theta_t}{100\pi\sqrt{d}} - b \right) \\ & \geq b \frac{\theta_t}{25\pi\sqrt{d}} \geq \frac{\tilde{c}}{100\pi} \frac{\theta^2}{d} \end{aligned}$$

where the first inequality is from Equations (9) and (11), the second inequality is from algebra and that $b \leq \frac{\theta_t}{100\pi\sqrt{d}}$, the third inequality is by expanding $b = \frac{\tilde{c}\theta}{\sqrt{d}}$ and $\theta_t \geq \frac{\theta}{4}$. \square

F Acute Initialization

We show in this section that the angle between the initial vector v_0 and the underlying halfspace u can be assumed to be acute under the two noise settings without loss of generality. To this end, we give two algorithms (Algorithms 5 and 6) that returns a halfspace that has angle at most $\frac{\pi}{4}$ with u , with constant overhead in label and time complexities. The techniques here are due to Appendix B of [6]. This fact, in conjunction with Theorems 2 and 3, yield an active learning algorithm that learns the target halfspace unconditionally with a constant overhead of label and time complexities.

For the bounded noise setting, we construct Algorithm 5 as an initialization procedure. It runs ACTIVE-PERCEPTRON twice, taking a vector v_0 and its opposite direction $-v_0$ as initializers. Then it performs hypothesis testing using $\tilde{O}(\frac{1}{(1-2\eta)^2})$ labeled examples to identify a halfspace that has angle at most $\frac{\pi}{4}$ with u .

Algorithm 5 Master Algorithm in the Bounded Noise Setting

Input: Labeling oracle \mathcal{O} , confidence δ , noise upper bound η , sample schedule $\{m_k\}$, band width $\{b_k\}$.

Output: a halfspace \hat{v} such that $\theta(\hat{v}, u) \leq \frac{\pi}{4}$.

- 1: $v_0 \leftarrow (1, 0, \dots, 0)$.
 - 2: $v_+ \leftarrow \text{ACTIVE-PERCEPTRON}(\mathcal{O}, v_0, \frac{(1-2\eta)}{16}, \frac{\delta}{3}, \{m_k\}, \{b_k\})$.
 - 3: $v_- \leftarrow \text{ACTIVE-PERCEPTRON}(\mathcal{O}, -v_0, \frac{(1-2\eta)}{16}, \frac{\delta}{3}, \{m_k\}, \{b_k\})$.
 - 4: Define region $R := \{x : \text{sign}(v_+ \cdot x) \neq \text{sign}(v_- \cdot x)\}$.
 - 5: $S \leftarrow \text{Draw } \frac{8}{(1-2\eta)^2} \ln \frac{6}{\delta} \text{ iid examples from } D|_R \text{ and query their labels.}$
 - 6: **if** $\text{err}_S(h_{v_+}) \leq \text{err}_S(h_{v_-})$ **then**
 - 7: **return** v_+
 - 8: **else**
 - 9: **return** v_-
 - 10: **end if**
-

Theorem 6. Suppose Algorithm 5 has inputs labeling oracle \mathcal{O} that satisfies η -bounded noise condition with respect to u , confidence δ , sample schedule $\{m_k\}$ where $m_k = \Theta\left(\frac{d}{(1-2\eta)^2} (\ln \frac{d}{(1-2\eta)^2} + \ln \frac{k}{\delta})\right)$, band width $\{b_k\}$ where $b_k = \tilde{\Theta}\left(\frac{2^{-k}(1-2\eta)}{\sqrt{d}}\right)$. Then, with probability at least $1 - \delta$, the output \hat{v} is such that $\theta(\hat{v}, u) \leq \frac{\pi}{4}$. Furthermore, (1) the total number of

label queries to oracle \mathcal{O} is at most $\tilde{O}\left(\frac{d}{(1-2\eta)^2}\right)$; (2) the total number of unlabeled examples drawn is $\tilde{O}\left(\frac{d}{(1-2\eta)^3}\right)$; (3) the algorithm runs in time $\tilde{O}\left(\frac{d^2}{(1-2\eta)^3}\right)$.

Proof. Note that one of $\theta(v_0, u)$, $\theta(-v_0, u)$ is at most $\frac{\pi}{2}$. From Theorem 2 and union bound, we know that with probability at least $1 - \frac{2\delta}{3}$, either $\theta(v_+, u) \leq \frac{(1-2\eta)\pi}{16}$, or $\theta(v_-, u) \leq \frac{(1-2\eta)\pi}{16}$.

Suppose without loss of generality, $\theta(v_+, u) \leq \frac{(1-2\eta)\pi}{16}$. We consider two cases.

Case 1: $\theta(v_+, v_-) \leq \pi/8$. By triangle inequality, $\theta(v_-, u) \leq \theta(v_+, u) + \theta(v_+, v_-) \leq \pi/4$. In this case, $\theta(v_+, u) \leq \frac{\pi}{4}$ and $\theta(v_-, u) \leq \frac{\pi}{4}$ holds simultaneously. Therefore, the returned vector \hat{v} satisfies $\theta(\hat{v}, u) \leq \frac{\pi}{4}$.

Case 2: $\theta(v_+, v_-) > \pi/8$. In this case, $\mathbb{P}[x \in R] \geq 1/8$, thus,

$$\mathbb{P}_R[\text{sign}(v_+ \cdot x) \neq \text{sign}(u \cdot x)] \leq \frac{\mathbb{P}[\text{sign}(v_+ \cdot x) \neq \text{sign}(u \cdot x)]}{\mathbb{P}[x \in R]} \leq \frac{1-2\eta}{8} = \frac{1}{4}\left(\frac{1}{2} - \eta\right).$$

Meanwhile, $\mathbb{P}_R[\text{sign}(v_+ \cdot x) \neq y] \leq \eta \mathbb{P}_R[\text{sign}(v_+ \cdot x) = \text{sign}(u \cdot x)] + \mathbb{P}_R[\text{sign}(v_+ \cdot x) \neq \text{sign}(u \cdot x)]$. Therefore,

$$\begin{aligned} & \frac{1}{2} - \mathbb{P}_R[\text{sign}(v_+ \cdot x) \neq y] \\ & \geq \left(\frac{1}{2} - \eta\right) \mathbb{P}_R[\text{sign}(v_+ \cdot x) = \text{sign}(u \cdot x)] - \frac{1}{2} \mathbb{P}_R[\text{sign}(v_+ \cdot x) \neq \text{sign}(u \cdot x)] \\ & \geq \left(\frac{1}{2} - \eta\right) \cdot \frac{1}{2} - \left(\frac{1}{2} - \eta\right) \cdot \frac{1}{4} \\ & \geq \frac{1}{4}\left(\frac{1}{2} - \eta\right) \end{aligned}$$

Since v_+ disagrees with v_- everywhere on R , $\mathbb{P}_R[\text{sign}(v_+ \cdot x) \neq y] + \mathbb{P}_R[\text{sign}(v_- \cdot x) \neq y] = 1$. Thus, $\text{err}_{D|R}(h_{v_+}) \leq \frac{1}{2} - \left(\frac{1}{2} - \eta\right)\frac{1}{4}$ and $\text{err}_{D|R}(h_{v_-}) \geq \frac{1}{2} + \left(\frac{1}{2} - \eta\right)\frac{1}{4}$. Therefore, by Hoeffding's Inequality, with probability at least $1 - \delta/3$,

$$\text{err}_S(v_+) < \frac{1}{2} < \text{err}_S(v_-)$$

therefore v_+ will be selected for \hat{v} . This shows that $\theta(\hat{v}, u) \leq \pi/4$.

In conclusion, by union bound, we have shown that with probability $1 - \delta$, $\theta(\hat{v}, u) \leq \frac{\pi}{4}$. The label complexity, unlabeled sample complexity, and time complexity of the algorithm follows immediately from Theorem 2. \square

For the adversarial noise setting, [6] outlines an algorithm that returns a vector that has angle at most $\frac{\pi}{4}$ with u . We state the algorithm in our context for completeness.

Theorem 7. Suppose Algorithm 6 has inputs labeling oracle \mathcal{O} that satisfies η -bounded noise condition with respect to u , confidence δ , sample schedule $\{m_k\}$ where $m_k = \Theta\left(d(\ln d + \ln \frac{k}{\delta})\right)$, and width $\{b_k\}$ where $b_k = \tilde{\Theta}\left(\frac{2^{-k}}{\sqrt{d}}\right)$. Then, with probability at least $1 - \delta$, the output \hat{v} is such that $\theta(\hat{v}, u) \leq \frac{\pi}{4}$. Furthermore, (1) the total number of label queries to oracle \mathcal{O} is at most $\tilde{O}(d)$; (2) the total number of unlabeled examples drawn is $\tilde{O}(d)$; (3) the algorithm runs in time $\tilde{O}(d^2)$.

The proof of this theorem is almost the same as Theorem 6 and is thus omitted.

G Basic Lemmas for the Upper Bounds

In this section, we present a few useful lemmas that serve as the basis of proving Theorems 2 and 3.

Algorithm 6 Master Algorithm in the Adversarial Noise Setting

Input: Labeling oracle \mathcal{O} , confidence δ **Output:** a halfspace \hat{v} such that $\theta(\hat{v}, u) \leq \frac{\pi}{4}$.

```

1:  $v_0 \leftarrow (1, 0, \dots, 0)$ .
2:  $v_+ \leftarrow \text{ACTIVE-PERCEPTRON}(\mathcal{O}, v_0, \frac{1}{16}, \frac{\delta}{3}, \{m_k\}, \{b_k\})$ .
3:  $v_- \leftarrow \text{ACTIVE-PERCEPTRON}(\mathcal{O}, -v_0, \frac{1}{16}, \frac{\delta}{3}, \{m_k\}, \{b_k\})$ .
4: Define region  $R := \{x : \text{sign}(v_+ \cdot x) \neq \text{sign}(v_- \cdot x)\}$ .
5:  $S \leftarrow \text{Draw } 8 \ln \frac{6}{\delta} \text{ iid examples from } D|_R \text{ and query their labels.}$ 
6: if  $\text{err}_S(h_{v_+}) \leq \text{err}_S(h_{v_-})$  then
7:   return  $v_+$ 
8: else
9:   return  $v_-$ 
10: end if

```

G.1 Basic Facts

We first collect a few useful facts for algebraic manipulations.

Lemma 11. *If $0 \leq x \leq 1 - \frac{1}{e}$, then for any $d \geq 1$, $(1 - \frac{x}{d})^{\frac{d}{2}} \geq e^{-x} \geq \frac{1}{2}$.*

Lemma 12. *Given $a \in (0, \pi)$, if $x \in [0, a]$, then $\frac{\sin a}{a} x \leq \sin x \leq x$.*

Lemma 13. *If $x \in [0, \pi]$, then $1 - \frac{x^2}{2} \leq \cos x \leq 1 - \frac{x^2}{5}$.*

Lemma 14. *Let $B(x, y) = \int_0^1 (1-t)^{x-1} t^{y-1} dt$ be the Beta function. Then $\frac{2}{\sqrt{d-1}} \leq B(\frac{1}{2}, \frac{d}{2}) \leq \frac{\pi}{\sqrt{d}}$.*

G.2 Probability Inequalities

Lemma 15 (Azuma's Inequality). *Let $\{Y_t\}_{t=1}^m$ be a bounded submartingale difference sequence, that is, $\mathbb{E}[Y_t | Y_1, \dots, Y_{t-1}] \geq 0$, and $|Y_t| \leq \sigma$. Then, with probability at least $1 - \delta$,*

$$\sum_{t=1}^m Y_t \geq -\sigma \sqrt{2m \ln \frac{1}{\delta}}$$

Lemma 16 (Concentration of Geometric Random Variables). *Suppose Z_1, \dots, Z_n are iid geometric random variables with parameter p . Then,*

$$\mathbb{P}[Z_1 + \dots + Z_n > \frac{2n}{p}] \leq \exp(-\frac{n}{4})$$

Proof. Since $Z_1 + \dots + Z_n > \frac{2n}{p}$ implies that $Z_1 + \dots + Z_n \geq \lceil \frac{2n}{p} \rceil$ (as $Z_1 + \dots + Z_n$ is an integer), the left hand side is at most $\mathbb{P}[Z_1 + \dots + Z_n \geq \lceil \frac{2n}{p} \rceil]$.

Let $X_1, \dots, X_{\lceil \frac{2n}{p} \rceil}$ be a sequence of iid Bernoulli(p) random variables. By standard relationship between Bernoulli random variables and geometric random variables, we have that

$$\mathbb{P}[Z_1 + \dots + Z_n \geq \lceil \frac{2n}{p} \rceil] = \mathbb{P}[X_1 + \dots + X_{\lceil \frac{2n}{p} \rceil - 1} \leq n - 1]$$

Note that $\mathbb{P}[X_1 + \dots + X_{\lceil \frac{2n}{p} \rceil - 1} \leq n - 1] \leq \mathbb{P}[X_1 + \dots + X_{\lceil \frac{2n}{p} \rceil} \leq n]$ since $X_{\lceil \frac{2n}{p} \rceil} \leq 1$. Applying Chernoff bound, the above probability is at most $\exp(-\lceil \frac{2n}{p} \rceil \cdot p \cdot \frac{1}{8}) \leq \exp(-\frac{n}{4})$. \square

G.3 Properties of the Uniform Distribution over the Unit Sphere

Lemma 17 (Marginal Density and Conditional Density). *If (x_1, x_2, \dots, x_d) is drawn from the uniform distribution over the unit sphere, then:*

1. (x_1, x_2) has a density function of $p(z_1, z_2)$, where $p(z_1, z_2) = \frac{(1-z_1^2-z_2^2)^{\frac{d-4}{2}}}{\frac{2\pi}{d-2}}$.

2. Conditioned on $x_2 = b$, x_1 has a density function of $p_b(z)$, where $p_b(z) = \frac{(1-b^2-z^2)^{\frac{d-4}{2}}}{(1-b^2)^{\frac{d-3}{2}} B(\frac{d-2}{2}, \frac{1}{2})}$.

3. x_1 has a density function of $p(z)$, where $p(z) = \frac{(1-z^2)^{\frac{d-3}{2}}}{B(\frac{d-1}{2}, \frac{1}{2})}$.

Lemma 18. Suppose x is drawn uniformly from the unit sphere, and $b \leq \frac{1}{10\sqrt{d}}$. Then,
 $\mathbb{P}\left[x_1 \in \left[\frac{b}{2}, b\right]\right] \geq \frac{\sqrt{d}}{8\pi}b$.

Proof.

$$\begin{aligned} & \mathbb{P}\left[x_1 \in \left[\frac{b}{2}, b\right]\right] \\ &= \frac{\int_{b/2}^b (1-t^2)^{\frac{d-3}{2}} dt}{B(\frac{d-1}{2}, \frac{1}{2})} \\ &\geq \frac{\frac{b}{2}(1-b^2)^{\frac{d-3}{2}}}{\frac{\pi}{\sqrt{d-1}}} \geq \frac{\sqrt{d}}{8\pi}b \end{aligned}$$

where the first equality is from item 3 of Lemma 17, giving the exact probability density function of x_1 , the first inequality is from that $(1-t^2)^{\frac{d-3}{2}} \geq (1-b^2)^{\frac{d-3}{2}}$ when $t \in [b/2, b]$, and Lemma 14 giving upper bound on $B(\frac{d-1}{2}, \frac{1}{2})$, and the second inequality is from Lemma 11 and that $d-1 \geq \frac{d}{2}$. \square

Lemma 19. Suppose x is drawn uniformly from unit sphere restricted to the region $\{x : v \cdot x = \xi\}$, and u, v are unit vectors such that $\theta(u, v) = \theta \in [0, \frac{9}{10}\pi]$ and $0 \leq \xi \leq \frac{\theta}{4\sqrt{d}}$. Then,

1. $\mathbb{E}[u \cdot x] \leq \xi$.
2. $\mathbb{E}[(u \cdot x)^2] \leq \frac{5\theta^2}{d}$.
3. $\mathbb{E}[(u \cdot x)\mathbb{1}\{u \cdot x < 0\}] \leq \xi - \frac{\theta}{36\sqrt{d}}$.

Proof. By spherical symmetry, without loss of generality, let $v = (0, 1, 0, \dots, 0)$, and $u = (\sin \theta, \cos \theta, 0, \dots, 0)$. Let $x = (x_1, \dots, x_d)$.

1.

$$\begin{aligned} & \mathbb{E}[u \cdot x] \\ &= \mathbb{E}[x_1 \sin \theta + x_2 \cos \theta | x_2 = \xi] \\ &= \mathbb{E}[x_1 | x_2 = \xi] \sin \theta + \xi \cos \theta \\ &\leq \xi \end{aligned}$$

where the first two equalities are by algebra, the inequality follows from $\cos \theta \leq 1$ and $\mathbb{E}[x_1 | x_2 = \xi] = 0$ since the conditional distribution of x_1 given $x_2 = \xi$ is symmetric around the origin.

2.

$$\begin{aligned}
& \mathbb{E}[(u \cdot x)^2] \\
&= \mathbb{E}[(x_1 \sin \theta + x_2 \cos \theta)^2 | x_2 = \xi] \\
&\leq \mathbb{E}[2x_1^2 \sin^2 \theta + 2x_2^2 \cos^2 \theta | x_2 = \xi] \\
&\leq 2\mathbb{E}[x_1^2 | x_2 = \xi] \sin^2 \theta + 2\xi^2 \\
&\leq 2\theta^2 \frac{\int_{-1}^1 z^2 (1 - z^2)^{\frac{d-4}{2}} dz}{B(\frac{d-2}{2}, \frac{1}{2})} + 2\xi^2 \\
&= 2\theta^2 \frac{B(\frac{d-2}{2}, \frac{3}{2})}{B(\frac{d-2}{2}, \frac{1}{2})} + 2\xi^2 \\
&\leq \frac{5\theta^2}{d}
\end{aligned}$$

where the first equality is by definition of u , the first inequality is from algebra that $(A + B)^2 \leq 2A^2 + 2B^2$, the second inequality is from that $|\cos \theta| \leq 1$, the third inequality is from item 2 of Lemma 17 and that $\sin \theta \leq \theta$, and the last inequality is from the fact that $\frac{B(\frac{d-2}{2}, \frac{3}{2})}{B(\frac{d-2}{2}, \frac{1}{2})} = \frac{1}{d-1} \leq \frac{2}{d}$, and $\xi^2 \leq \frac{\theta^2}{16d}$.

3.

$$\begin{aligned}
& \mathbb{E}[(u \cdot x) \mathbb{1}\{u \cdot x < 0\}] \\
&= \mathbb{E}[(x_1 \sin \theta + x_2 \cos \theta) \mathbb{1}\{x_1 < -\xi \cot \theta\} | x_2 = \xi] \\
&\leq \mathbb{E}[x_1 \mathbb{1}\{x_1 < -\xi \cot \theta\} | x_2 = \xi] \sin \theta + \xi \\
&= \xi + \sin \theta \int_{-\sqrt{1-\xi^2}}^{-\xi \cot \theta} \frac{(1 - \xi^2 - x_1^2)^{\frac{d-4}{2}} x_1}{(1 - \xi^2)^{\frac{d-3}{2}} B(\frac{d-2}{2}, \frac{1}{2})} dx_1 \\
&= \xi - \sin \theta \frac{\frac{2}{d-2} \left(1 - \left(\frac{\xi}{\sin \theta}\right)^2\right)^{\frac{d-2}{2}}}{(1 - \xi^2)^{\frac{d-3}{2}} B(\frac{d-2}{2}, \frac{1}{2})} \\
&\leq \xi - \sin \theta \frac{2}{\pi \sqrt{d-2}} \left(1 - \left(\frac{\xi}{\sin \theta}\right)^2\right)^{\frac{d-2}{2}} \\
&\leq \xi - \frac{\sin \theta}{\pi \sqrt{d}} \\
&\leq \xi - \frac{\theta}{36\sqrt{d}}
\end{aligned}$$

where the first inequality is by algebra and $|\cos \theta| \leq 1$, the second equality is by item 2 of Lemma 17, the third equality is by integration, the second inequality is from $(1 - \xi^2)^{\frac{d-3}{2}} \leq 1$ and Lemma 14 that $B(\frac{d-2}{2}, \frac{1}{2}) \leq \frac{\pi}{\sqrt{d-2}}$, the third inequality follows by Lemma 11 that $\left(1 - \left(\frac{\xi}{\sin \theta}\right)^2\right)^{\frac{d-2}{2}} \geq \frac{1}{2}$, since $\xi \leq \frac{\theta}{4\sqrt{d}}$, and the last inequality follows from Lemma 12 that $\sin \theta \geq \frac{5\theta}{18\pi}$ when $\theta \in [0, \frac{9}{10}\pi]$ and algebra.

□

H Proof of the Lower Bound

In this section, we give the proof of Theorem 1 (label complexity lower bound in the bounded noise setting). The proof follows from two key lemmas, Lemma 24 and Lemma 25. We start with some additional definitions.

Definition 3. Let \mathbb{P}, \mathbb{Q} be two probability measures on a common measurable space and \mathbb{P} is absolutely continuous with respect to \mathbb{Q} .

- The KL-divergence between \mathbb{P} and \mathbb{Q} is defined as $D_{KL}(\mathbb{P}, \mathbb{Q}) = \mathbb{E}_{X \sim \mathbb{P}} \ln \frac{\mathbb{P}(X)}{\mathbb{Q}(X)}$.
- We define $d_{KL}(p, q) = D_{KL}(\mathbb{P}, \mathbb{Q})$, where \mathbb{P}, \mathbb{Q} are distributions of a Bernoulli(p) and a Bernoulli(q) random variables respectively.
- For random variables X, Y, Z , define the mutual information between X and Y under \mathbb{P} as $I(X; Y) = D_{KL}(\mathbb{P}(X, Y), \mathbb{P}(X)\mathbb{P}(Y)) = \mathbb{E}_{X, Y} \ln \frac{\mathbb{P}(X, Y)}{\mathbb{P}(X)\mathbb{P}(Y)}$, and define the mutual information between X and Y conditioned on Z under \mathbb{P} as $I(X; Y | Z) = \mathbb{E}_{X, Y, Z} \ln \frac{\mathbb{P}(X, Y | Z)}{\mathbb{P}(X | Z)\mathbb{P}(Y | Z)}$.
- For a sequence of random variables X_1, X_2, \dots , denote by X^n the subsequence $\{X_1, X_2, \dots, X_n\}$.

We will use the following two folklore information-theoretic lower bounds.

Lemma 20. Let \mathcal{W} be a class of parameters, and $\{P_w : w \in \mathcal{W}\}$ be a class of probability distributions indexed by \mathcal{W} over some sample space \mathcal{X} . Let $d : \mathcal{W} \times \mathcal{W} \rightarrow \mathbb{R}$ be a semi-metric. Let $\mathcal{V} = \{w_1, \dots, w_M\} \subseteq \mathcal{W}$ such that $\forall i \neq j, d(w_i, w_j) \geq 2s > 0$. Let V be a random variable uniformly taking values from \mathcal{V} , and X be drawn from P_V . Then for any algorithm \mathcal{A} that given a sample X drawn from P_w outputs $\mathcal{A}(X) \in \mathcal{W}$, the following inequality holds:

$$\sup_{w \in \mathcal{W}} P_w(d(w, \mathcal{A}(X)) \geq s) \geq 1 - \frac{I(V; X) + \ln 2}{\ln M}$$

Proof. For any algorithm \mathcal{A} , define a test function $\hat{\Psi} : \mathcal{X} \rightarrow \{1, \dots, M\}$ such that

$$\hat{\Psi}(X) = \arg \min_{i \in \{1, \dots, M\}} d(\mathcal{A}(X), w_i)$$

We have

$$\sup_{w \in \mathcal{W}} P_w(d(w, \mathcal{A}(X)) \geq s) \geq \max_{w \in \mathcal{V}} P_w(d(w, \mathcal{A}(X)) \geq s) \geq \max_{i \in \{1, \dots, M\}} P_{w_i}(\hat{\Psi}(X) \neq i)$$

The desired result follows by classical Fano's Inequality:

$$\max_{i \in \{1, \dots, M\}} P_{w_i}(\hat{\Psi}(X) \neq i) \geq 1 - \frac{I(V; X) + \ln 2}{\ln M}$$

□

Lemma 21. [4, Lemma 5.1] Let $\gamma \in (0, 1)$, $\delta \in (0, \frac{1}{4})$, $p_0 = \frac{1-\gamma}{2}$, $p_1 = \frac{1+\gamma}{2}$. Suppose that $\alpha \sim \text{Bernoulli}(\frac{1}{2})$ is a random variable, ξ_1, \dots, ξ_m are i.i.d. (given α) Bernoulli(p_α) random variables. If $m \leq 2 \left\lfloor \frac{1-\gamma^2}{2\gamma^2} \ln \frac{1}{8\delta(1-2\delta)} \right\rfloor$, then for any function $f : \{0, 1\}^m \rightarrow \{0, 1\}$, $\mathbb{P}(f(\xi_1, \dots, \xi_m) \neq \alpha) > \delta$.

Next, we present two technical lemmas.

Lemma 22. [48, Lemma 6] For any $0 < \gamma \leq \frac{1}{2}$, $d \geq 1$, there is a finite set $\mathcal{V} \in \mathbb{S}^{d-1}$ such that the following two statements hold:

1. For any distinct $w_1, w_2 \in \mathcal{V}$, $\theta(w_1, w_2) \geq \pi\gamma$;

2. $|\mathcal{V}| \geq \frac{\sqrt{d}}{2} \left(\frac{1}{2\pi\gamma} \right)^{d-1} - 1$.

Lemma 23. If $p \in [0, 1]$ and $q \in (0, 1)$, then $d_{KL}(p, q) \leq \frac{(p-q)^2}{q(1-q)}$.

Proof.

$$\begin{aligned}
d_{\text{KL}}(p, q) &= p \ln \frac{p}{q} + (1-p) \ln \frac{1-p}{1-q} \\
&\leq p \left(\frac{p}{q} - 1 \right) + (1-p) \left(\frac{1-p}{1-q} - 1 \right) \\
&= \frac{(p-q)^2}{q(1-q)}
\end{aligned}$$

where the inequality follows by $\ln x \leq x - 1$. \square

Lemma 24. *For any $0 \leq \eta < \frac{1}{2}$, $d > 4$, $0 < \epsilon \leq \frac{1}{4\pi}$, $0 < \delta < \frac{1}{2}$, for any active learning algorithm \mathcal{A} , there is a $u \in \mathbb{S}^{d-1}$, and a labeling oracle \mathcal{O} that satisfies η -bounded noise condition with respect to u , such that if with probability at least $1 - \delta$, \mathcal{A} makes at most n queries to \mathcal{O} and outputs $v \in \mathbb{S}^{d-1}$ such that $\mathbb{P}[\text{sign}(v \cdot x) \neq \text{sign}(u \cdot x)] \leq \epsilon$, then $n \geq \frac{d \ln \frac{1}{\epsilon}}{16(1-2\eta)^2}$.*

Proof. We will prove this Lemma using Lemma 20.

First, we construct \mathcal{W} , \mathcal{V} , d , s , and P_θ . Let $\mathcal{W} = \mathbb{S}^{d-1}$. Let \mathcal{V} be the set in Lemma 22 with $\gamma = 2\epsilon$. For any $w_1, w_2 \in \mathcal{W}$, let $d(w_1, w_2) = \theta(w_1, w_2)$, $s = \pi\epsilon$. Fix any algorithm \mathcal{A} . For any $w \in \mathcal{W}$, any $x \in \mathcal{X}$, define $P_w[Y = 1|X = x] = \begin{cases} 1 - \eta, & w \cdot x \geq 0 \\ \eta, & w \cdot x < 0 \end{cases}$, and $P_w[Y = 0|X = x] = 1 - P_w[Y = 1|X = x]$. Define P_w^n to be the distribution of n examples $\{(X_i, Y_i)\}_{i=1}^n$ where Y_i is drawn from distribution $P_w(Y|X_i)$ and X_i is drawn by the active learning algorithm \mathcal{A} based solely on the knowledge of $\{(X_j, Y_j)\}_{j=1}^{i-1}$.

By Lemma 22, we have $M = |\mathcal{V}| \geq \frac{\sqrt{d}}{2} \left(\frac{1}{4\pi\epsilon} \right)^{d-1} - 1 \geq \frac{1}{4} \left(\frac{1}{4\pi\epsilon} \right)^{d-1}$, and $d(w_1, w_2) \geq 2\pi\epsilon = 2s$ for any distinct $w_1, w_2 \in \mathcal{V}$.

Clearly, for any $w \in \mathcal{W}$, if the optimal classifier is w , and the oracle \mathcal{O} responds according to $P_w(\cdot | X = x)$, then it satisfies η -bounded noise condition. Therefore, to prove the lemma, it suffices to show that if $n \leq \frac{d \ln \frac{1}{\epsilon}}{16(1-2\eta)^2}$, then

$$\sup_{w \in \mathcal{W}} P_w(d(w, \mathcal{A}(X^n, Y^n)) \geq s) \geq \frac{1}{2}.$$

Now, by Lemma 20,

$$\sup_{w \in \mathcal{W}} P_w^n(d(w, \mathcal{A}(X^n, Y^n)) \geq s) \geq 1 - \frac{I(V; X^n, Y^n) + \ln 2}{\ln M} \geq 1 - \frac{I(V; X^n, Y^n) + \ln 2}{(d-1) \ln \frac{1}{4\pi\epsilon} - \ln 4}.$$

It remains to show if $n = \frac{d \ln \frac{1}{\epsilon}}{16(1-2\eta)^2}$, then $I(V; X^n, Y^n) \leq \frac{1}{2} ((d-1) \ln \frac{1}{4\pi\epsilon} - \ln 4) - \ln 2$.

By the chain rule of mutual information, we have

$$I(V; X^n, Y^n) = \sum_{i=1}^n \left(I(V; X_i | X^{i-1}, Y^{i-1}) + I(V; Y_i | X^i, Y^{i-1}) \right)$$

First, we claim V and X_i are conditionally independent given $\{X^{i-1}, Y^{i-1}\}$, and thus $I(V; X_i | X^{i-1}, Y^{i-1}) = 0$. The proof for this claim is as follows. Since the selection of X_i only depends on algorithm \mathcal{A} and X^{i-1}, Y^{i-1} , for any $v_1, v_2 \in \mathcal{V}$, $\mathbb{P}(X_i | v_1, X^{i-1}, Y^{i-1}) =$

$\mathbb{P}(X_i | v_2, X^{i-1}, Y^{i-1})$. Thus,

$$\begin{aligned}
\mathbb{P}(X_i | X^{i-1}, Y^{i-1}) &= \sum_v \mathbb{P}(X_i, v | X^{i-1}, Y^{i-1}) \\
&= \sum_v \mathbb{P}(v) \mathbb{P}(X_i | v, X^{i-1}, Y^{i-1}) \\
&= \frac{1}{|\mathcal{V}|} \sum_v \mathbb{P}(X_i | v, X^{i-1}, Y^{i-1}) \\
&= \mathbb{P}(X_i | V, X^{i-1}, Y^{i-1})
\end{aligned}$$

Next, we show $I(V; Y_i | X^i, Y^{i-1}) \leq 5(1 - 2\eta)^2 \ln 2$. On one hand, since $Y_i \in \{-1, +1\}$, $I(V; Y_i | X^i, Y^{i-1}) \leq H(V | X^i, Y^{i-1}) \leq \ln 2$, where $H(\cdot | \cdot)$ is the conditional entropy.

On the other hand,

$$\begin{aligned}
&I(V; Y_i | X^i, Y^{i-1}) \\
&= \mathbb{E}_{X^i, Y^i, V} \left[\ln \frac{\mathbb{P}(V, Y_i | X^i, Y^{i-1})}{\mathbb{P}(V | X^i, Y^{i-1}) \mathbb{P}(Y_i | X^i, Y^{i-1})} \right] \\
&= \mathbb{E}_{X^i, Y^i, V} \left[\ln \frac{\mathbb{P}(Y_i | V, X^i, Y^{i-1})}{\mathbb{P}(Y_i | X^i, Y^{i-1})} \right] \\
&= \mathbb{E}_{X^i, Y^i, V} \left[\ln \frac{\mathbb{P}(Y_i | V, X^i, Y^{i-1})}{\mathbb{E}_{V'} \mathbb{P}(Y_i | V', X^i, Y^{i-1})} \right] \\
&\leq \mathbb{E}_{X^i, Y^i, V, V'} \left[\ln \frac{\mathbb{P}(Y_i | V, X^i, Y^{i-1})}{\mathbb{P}(Y_i | V', X^i, Y^{i-1})} \right] \\
&\leq \max_{x^i, y^{i-1}, v, v'} D_{\text{KL}} \left(\mathbb{P}(Y_i | x^i, y^{i-1}, v), \mathbb{P}(Y_i | x^i, y^{i-1}, v') \right) \\
&= \max_{x^i, y^{i-1}, v, v'} D_{\text{KL}} \left(\mathbb{P}(Y_i | x_i, v), \mathbb{P}(Y_i | x_i, v') \right) \\
&= \max_{x^i, v, v'} D_{\text{KL}} \left(P_v(Y_i | x_i), P_{v'}(Y_i | x_i) \right) \\
&\leq \frac{(1 - 2\eta)^2}{\eta(1 - \eta)}
\end{aligned}$$

where the first inequality follows from the convexity of KL-divergence, and the last inequality follows from Lemma 23.

Combining the two upper bounds, we get $I(V; Y_i | X^i, Y^{i-1}) \leq \min \left\{ \ln 2, \frac{(1-2\eta)^2}{\eta(1-\eta)} \right\} \leq 5(1 - 2\eta)^2 \ln 2$.

Therefore, $I(V; X^n, Y^n) \leq 5n(1 - 2\eta)^2 \ln 2$. If $n \leq \frac{d \ln \frac{1}{\epsilon}}{16(1-2\eta)^2} \leq \frac{\frac{1}{2}((d-1) \ln \frac{1}{4\pi\epsilon} - \ln 4) - \ln 2}{5(1-2\eta)^2 \ln 2}$, then $I(V; X^n, Y^n) \leq \frac{1}{2} \left((d-1) \ln \frac{1}{4\pi\epsilon} - \ln 4 \right) - \ln 2$. This concludes the proof. \square

Lemma 25. For any $d > 0$, $0 \leq \eta < \frac{1}{2}$, $0 < \epsilon < \frac{1}{3}$, $0 < \delta \leq \frac{1}{4}$, for any active learning algorithm \mathcal{A} , there is a $u \in \mathbb{S}^{d-1}$, and a labeling oracle \mathcal{O} that satisfies η -bounded noise condition with respect to u , such that if with probability at least $1 - \delta$, \mathcal{A} makes at most n queries to \mathcal{O} and outputs $v \in \mathbb{S}^{d-1}$ such that $\mathbb{P}[\text{sign}(v \cdot x) \neq \text{sign}(u \cdot x)] \leq \epsilon$, then $n \geq \Omega \left(\frac{\eta \ln \frac{1}{\epsilon}}{(1-2\eta)^2} \right)$.

Proof. We prove this result by reducing the hypothesis testing problem in Lemma 21 to our problem of learning halfspaces.

Fix $d, \epsilon, \delta, \eta$. Suppose \mathcal{A} is an algorithm that for any $u \in \mathbb{S}^{d-1}$, under η -bounded noise condition, with probability at least $1 - \delta$ outputs $v \in \mathbb{S}^{d-1}$ such that $\mathbb{P}[\text{sign}(v \cdot x) \neq \text{sign}(u \cdot x)] \leq \epsilon < \frac{1}{3}$, which implies $\theta(v, u) \leq \frac{\pi}{3}$ under bounded noise condition.

Let $p_0 = \eta, p_1 = 1 - \eta$. Suppose that $\alpha \sim \text{Bernoulli}(\frac{1}{2})$ is an unknown random variable. We are given a sequence of i.i.d. (given α) $\text{Bernoulli}(p_\alpha)$ random variables ξ_1, ξ_2, \dots , and would like to test if α equals 0 or 1.

Define $e = (1, 0, 0, \dots, 0) \in \mathbb{R}^d$. Construct a labeling oracle \mathcal{O} such that for the i -th query x_i , it returns $2\xi_i - 1$ if $x_i \cdot e \geq 0$, and $1 - 2\xi_i$ otherwise. Clearly, the oracle \mathcal{O} satisfies η -bounded noise condition with respect to underlying halfspace $u = (2\alpha - 1)e = (2\alpha - 1, 0, 0, \dots, 0) \in \mathbb{R}^d$.

Now, we run learning algorithm \mathcal{A} with oracle \mathcal{O} . Let m be the number of queries \mathcal{A} makes, and $\mathcal{A}(\xi_1, \dots, \xi_m)$ be the normal vector of the halfspace output by the learning algorithm. We define

$$f(\xi_1, \dots, \xi_m) = \begin{cases} 0 & \text{if } \mathcal{A}(\xi_1, \dots, \xi_m) \cdot e < 0 \\ 1 & \text{otherwise} \end{cases}.$$

By our assumption of \mathcal{A} and construction of \mathcal{O} , $\mathbb{P}\left(\theta(u, \mathcal{A}(\xi_1, \dots, \xi_m)) \leq \frac{1}{3}\pi\right) \geq 1 - \delta$, so $\mathbb{P}(f(\xi_1, \dots, \xi_m) = \alpha) \geq 1 - \delta$, implying $\mathbb{P}(f(\xi_1, \dots, \xi_m) \neq \alpha) \leq \delta$. By Lemma 21, $m \geq 2 \left\lceil \frac{4\eta(1-\eta)}{(1-2\eta)^2} \ln \frac{1}{8\delta(1-2\delta)} \right\rceil = \Omega\left(\frac{\eta \ln \frac{1}{\delta}}{(1-2\eta)^2}\right)$. \square