

Harnessing Correlations in Distributed Erasure-Coded Key-Value Stores

Ramy E. Ali and Viveck R. Cadambe

Abstract

Motivated by applications of distributed storage systems to key-value stores, the multi-version coding problem was formulated to efficiently store frequently updated data in asynchronous decentralized storage systems. Inspired by consistency requirements in distributed systems, the main goal in the multi-version coding problem is to ensure that the latest possible version of the data is decodable, even if the data updates have not reached some servers in the system. In this paper, we study the storage cost of ensuring consistency for the case where the data versions are correlated, in contrast to previous work where data versions were treated as being independent. We provide multi-version code constructions that show that the storage cost can be significantly smaller than the previous constructions depending on the degree of correlation, despite the asynchrony and the decentralized nature. Our achievability results are based on Reed-Solomon codes and random binning. Through an information-theoretic converse, we show that our multi-version codes are nearly-optimal, within a factor of 2, in certain interesting regimes.

I. INTRODUCTION

Distributed key-value stores are an important part of modern cloud computing infrastructure¹. Key-value stores are commonly used by several applications including reservation systems, financial transactions, collaborative text editing and multi-player gaming. Owing to their utility, there are numerous commercial and open-source cloud-based key-value store implementations such as Amazon Dynamo [2], Google Spanner [3] and Apache Cassandra [4]. Distributed data storage services including key-value stores commonly build fault tolerance and availability by replicating the data across multiple nodes. Unlike archival data storage services, in key-value stores, the data stored is updated frequently, and the time scales of data updates and access are often comparable to the time scale of dispersing the data to the nodes [2]. In fact, distributed key-value stores are commonly *asynchronous* as the time scale of data propagation is unpredictable and different nodes can receive the updates at different points in time. In such settings, ensuring that a client gets the latest version of the data requires careful and delicate protocol design.

Modern key-value stores depend on high-speed memory that is expensive as compared with hard drives to provide fast operations. Hence, the goal of efficiently using memory has motivated significant interest in erasure-coded key-value stores. In absence of consistency requirements,

Ramy E. Ali (email: ramy.ali@psu.edu) and Viveck R. Cadambe (email: viveck@engr.psu.edu) are with the School of Electrical Engineering and Computer Science, The Pennsylvania State University, University Park, PA 16802. This work is supported by NSF grant No. CCF 1553248 and is published in part in the Proceedings of the 2016 IEEE Information Theory Workshop [1].

¹A *read-write* key-value store is a shared database that supports *get* or read operations, and *put* or write operations.

erasure-coded “in-memory” storage systems can significantly improve latency as compared to replication-based counter parts [5]. Systems research related to erasure-coded consistent data stores also has received significant interest (See, e.g., [6] and also [7], which uses erasure coding for Microsoft’s data centers even for non-archival consistent data storage services). Delta coding [8] is another classical technique that improves memory efficiency in data storage systems, where it is desired to store older versions of the data. Delta coding relies on the idea of compressing differences between subsequent versions to improve the storage cost.

The main contribution of our paper is developing a coding-theoretic approach that combines erasure coding and delta coding to exploit correlations between subsequent updates and enable significant memory savings as compared to replication-based schemes and erasure coding approaches that do not exploit correlations. We begin by an overview of the consistent data storage algorithms, and then discuss the *multi-version coding* framework, which is an information-theoretic framework for distributed storage codes tailor-made for consistent key-value stores.

A. Overview of Key-Value Stores

The design principles of key-value stores are rooted in the distributed computing-theoretic abstraction known as *shared memory emulation* [9]. The goal of the *read-write* shared memory emulation problem is to implement a read-write variable over a distributed system. While there has been interest in archival data storage systems in coding theory, e.g. [10], [11], the shared memory emulation set up differs in the following aspects.

- 1) *Asynchrony*: a new version of the data may not arrive at all servers simultaneously.
- 2) *Decentralized nature*: there is no single encoder that is aware of all versions of the data simultaneously, and a server is not aware of which versions are received by other servers.

Shared memory emulation algorithms use *quorum-based* techniques to deal with the asynchrony. Specifically, in a system of n servers that tolerates f crash-stop server failures [9], a write operation sends a request to all servers and waits for the acknowledgments from any $c_W \leq n - f$ servers for the operation to be considered *complete*. Similarly, a read operation sends a request to all servers and waits for the response of any $c_R \leq n - f$ servers. This strategy ensures that, for every complete version, there are at least $c := c_W + c_R - n$ servers that received that version and responded to the read request. Shared memory emulation algorithms require that the *latest* complete version, or a later version, must be recoverable by the read operation. This requirement is referred to as consistency² in distributed systems [9].

In a replication-based protocol, where servers store an uncoded copy of the latest version that they receive, selecting c_W and c_R such that $c_W + c_R > n$ ensures consistency [2], [9]. Since for every complete write operation, there are c servers that store the value of that write operation and respond to a given read operation, it seems natural to use a maximum distance separable (MDS) code of dimension c to obtain storage cost savings over replication-based algorithms. However, the use of erasure coding in asynchronous distributed systems where consistency is

²More specifically, our decoding requirement is inspired by the consistency criterion known as *atomicity*, or *linearizability*.

important leads to interesting algorithmic and coding challenges. This is because, when erasure coding is used, no single server stores the data in its entirety; for instance, if an MDS code of dimension c is used, each server only stores a fraction of $1/c$ of the entire value. Therefore, for a read operation to get a version of the data, at least c servers must send the codeword symbols corresponding to this version. As a consequence, when a write operation updates the data, a server cannot delete the symbol corresponding to the old version before symbols corresponding to a new version propagate to a sufficient number of servers. That is, servers cannot simply store the latest version they receive; they have to store older versions as shown in Fig. 1. Given that storing multiple versions is inevitable in consistent erasure-coded systems [12]–[14],




Fig. 1: An erasure-coded algorithm where the servers only store the codeword symbol of the latest version is considered, where $n = 6$, $c_W = 5$ and $c_R = 5$. The old value of the variable is (x_1, x_2, x_3, x_4) and is updated to (y_1, y_2, y_3, y_4) . Since all servers may not receive the new codeword symbols simultaneously, a read operation may not be able to decode.

an important opportunity to improve memory efficiency is to exploit correlations between the various versions; this opportunity is the main motivation of our paper. We conduct our study through the *multi-version coding* framework [14].

B. Multi-Version Coding

The *multi-version coding* problem abstracts out algorithmic details of shared memory emulation while retaining the essence of consistent storage systems. Specifically, the multi-version coding problem [14] considers a decentralized storage system with n servers that tolerates f crash-stop failures, where the objective is storing a message (read-write variable) of length K bits with ν versions³. The versions are totally ordered; versions with higher ordering are referred to as later versions, and lower ordering as earlier versions. Each server receives an arbitrary subset

³We study the case where each version is K bits long; although certain applications might benefit from dynamic allocation, several important applications use a fixed size for various versions of the value. Furthermore, popular key-value stores expose a fixed-sized value to the client and do not expose “malloc”-type dynamic allocation.

of the ν versions, and encodes them. Because of the decentralized nature, a server is unaware of which versions are available at other servers. Inspired by the quorum-based protocols, we refer to any version that has reached at least c_W servers as a *complete* version. A decoder connects to any c_R servers, and must recover the latest complete version, or a later version.

In [14], it was shown that there is a storage cost inevitable price for maintaining consistency in asynchronous decentralized storage systems. In multi-version coding, for any complete version, for any decoder, there are at least c servers that have received that version and responded to the decoder. In the classical erasure coding model, where $\nu = 1$, the Singleton bound dictates that the storage cost per server is at least K/c . However for $\nu > 1$, a server cannot simply store the codeword symbol corresponding to one version. In the case where the versions are independent, it was shown in [14] that the storage cost per server is at least $\frac{\nu}{c+\nu-1}K - \Theta(1)$. Since, for $\nu < c$, we have $\frac{\nu}{c+\nu-1} \geq \frac{\nu}{2c}$, and since the per-server cost of storing a version is K/c , we may interpret the result as follows: when the versions are independent, to compensate for the asynchrony and maintain consistency, a server has to store an amount of data that is, from a cost perspective, tantamount to at least $\nu/2$ versions, each stored using an MDS code of dimension c .

Although the study of [14] focuses on coding-theoretic aspects, the insights obtained from this study have been incorporated into distributed algorithms [15] and a lower-bound was developed in [16] on the storage cost of any read-write memory emulation algorithm by creating a worst-case execution mimicking the converse of [14]. We believe that merging the coding-theoretic ideas in our paper and the algorithmic insights of [15] is an interesting area of future work.

C. Contributions

In this paper, we extend the scope of the multi-version coding problem to the case where the different versions are correlated. Specifically, we consider a decentralized storage system with n servers storing ν possibly correlated versions of a message. We assume that each message version is K bits long, and model the correlation between successive versions in terms of the bit-strings that represent them. Given a version, we assume that the subsequent version is uniformly distributed in the Hamming ball of radius $\delta_K K$ centered around that given version. Hence, this version can be represented using $\log \text{Vol}(\delta_K K, K)$ bits, where $\text{Vol}(\delta_K K, K)$ is the volume of the Hamming Ball of radius $\delta_K K$. We derive three main results for this system.

- 1) We first study the case where δ_K is not known and propose an effective scheme based on Reed-Solomon code with a per-server storage cost of $\frac{K}{c} + (\nu - 1)\delta_K K(\log K + o(\log K))$ bits. This scheme obtains the $1/c$ *erasure coding gain* for the first version and stores every subsequent version via delta coding with a cost of $\delta_K K(\log K + o(\log K))$ bits. Thus, this scheme is unable to simultaneously obtain the gains of both erasure and delta coding.
- 2) We then study the case where δ_K is known and derive a random binning based scheme with a per-server storage cost of $\frac{K}{c} + \frac{\nu-1}{c} \log \text{Vol}(\delta_K K, K) + o(\log K)$ bits. From a cost viewpoint, this scheme is tantamount to storing one version using erasure coding with a cost of K/c and performing delta and erasure coding for the subsequent versions leading to a cost of $\frac{\log \text{Vol}(\delta_K K, K)}{c}$ bits per version. This scheme outperforms our first scheme as it

simultaneously obtains the gains of both erasure coding and delta coding for subsequent versions. We also show the existence of linear codes that obtain this storage cost.

A cost of $\frac{K}{c} + \frac{\nu-1}{c} \log \text{Vol}(\delta_K K, K) + o(\log K)$ bits is readily achievable in a setting, where every server receives all the versions, and each server is aware that the other servers have indeed received all the versions. In such a setting, each server can store a fraction of $1/c$ of the first version it receives using an MDS code of dimension c . For a new version, each server can store $1/c$ of the compressed difference between this version and the old version using an MDS code of dimension c . However, this scheme would fail in our setting because of the decentralized asynchronous nature. For instance, a server which receives versions 1 and 3 needs to compress version 3 with respect to version 1 and then encodes it, but a different server that receives only versions 2 and 3 needs to compute the increment of version 3 with respect to version 2 and then encodes it; from a decoder's viewpoint, the erasure-coded symbols stored at the two servers are not compatible. Furthermore, the decentralized nature implies that the server that receives versions 1 and 3 must store some data that would enable successful decoding no matter what versions are received by the other servers. Handling the decentralized and asynchronous nature while achieving both the erasure and the delta coding gain is our main technical contribution.

- 3) We extend the lower bound of [14] to the case of correlated versions and show our random binning scheme is within a factor 2 of the information-theoretic optimum in certain regimes.

D. Related Work

The idea of exploiting the correlation to efficiently update, store or exchange data has a rich history of study starting from the classical Slepian-Wolf problem [17]–[21] for compressing correlated distributed sources. Encoding incremental updates efficiently is the motivation of the delta compression techniques used commonly in data storage. The notion of delta compression was refined in [22], [23] by modeling the data updates using the edit distance; in particular, these references develop schemes that synchronize a small number of edits between a client and a server efficiently. While we note that the edit distance is relevant to applications such as collaborative text editing, we focus on the classical Hamming metric used more widely in coding theory for the sake of fundamental understanding and other applications that view the data as a table as in Apache Cassandra [4], and the writes update only a few entries of the table.

Exploiting correlations to improve efficiency in *distributed* storage and caching settings has been of significant interest [24]–[30]. In [24] and [25], coding schemes were developed that use as input, the old and the new version of the data, and output a code that can be used to store both versions efficiently. Capacity-achieving *update-efficient* codes for binary symmetric and erasure channels were studied in [26], [27], where a small change in the message leads to a codeword which is close to the original codeword in Hamming distance. In [28], the problem of minimizing the communication cost of updating a “stale” server that did not get an updated message, by downloading data from already updated servers, was studied and constructions and tight bounds were developed. A side information problem is presented in [29], where the goal is to send an updated version to a remote entity that has as side information an arbitrary linear

transform of an old version. The reference shows that the optimal encoding function is related to a maximally recoverable subcode of the linear transform associated with the side information.

Although our problem has common ingredients with previous works, our setting differs as it captures the asynchrony, decentralized nature, and the consistency requirements. An important outcome of our study is that correlation can reduce storage costs despite these requirements.

Organization of the paper

This paper is organized as follows. Section II presents the multi-version coding problem and the main results of this paper. In Section III, we provide our code constructions. Section IV provides a lower bound on the storage cost. Finally, conclusions are discussed in Section V.

II. SYSTEM MODEL AND BACKGROUND OF MULTI-VERSION CODES

We start with some notation. We use boldface for vectors. In the n -dimensional space over a finite field \mathbb{F}_p , the standard basis column vectors are denoted by $\{\mathbf{e}_1, \mathbf{e}_2, \dots, \mathbf{e}_n\}$. We denote the Hamming weight of a vector \mathbf{x} by $w_H(\mathbf{x})$ and the Hamming distance between any two vectors \mathbf{x}_1 and \mathbf{x}_2 by $d_H(\mathbf{x}_1, \mathbf{x}_2)$. For a positive integer i , we denote by $[i]$ the set $\{1, 2, \dots, i\}$. For any set of ordered indices $S = \{s_1, s_2, \dots, s_{|S|}\} \subseteq \mathbb{Z}$, where $s_1 < s_2 < \dots < s_{|S|}$, and for any ensemble of variables $\{X_i : i \in S\}$, the tuple $(X_{s_1}, X_{s_2}, \dots, X_{s_{|S|}})$ is denoted by X_S . We use $\log(\cdot)$ to denote the logarithm to the base 2 and $H(\cdot)$ to denote the binary entropy function. We use the notation $[2^K]$ to denote the set of K -length binary strings. A *code* of length n and dimension k over alphabet \mathcal{A} consists of an injective mapping $\mathcal{C} : \mathcal{A}^k \rightarrow \mathcal{A}^n$. When \mathcal{A} is a finite field and the mapping \mathcal{C} is linear, then the code is referred to as a *linear code*. We refer to a linear code \mathcal{C} of length n and dimension k as an (n, k) code. An (n, k) linear code is called MDS if the mapping projected to *any* k co-ordinates is invertible.

A. Multi-version Codes (MVCs)

We now present a variant of the definition of the multi-version code [14], where we model the correlations. We consider a distributed storage system with n servers that can tolerate f crash-stop server failures. The system stores ν possibly correlated versions of a message where $\mathbf{W}_u \in [2^K]$ is the u -th version, $u \in [\nu]$, and K is the message length in bits. The versions are assumed to be totally ordered, i.e., if $u > l$, \mathbf{W}_u is interpreted as a *later* version with respect to \mathbf{W}_l . We assume that $\mathbf{W}_1 \rightarrow \mathbf{W}_2 \rightarrow \dots \rightarrow \mathbf{W}_\nu$ form a Markov chain. \mathbf{W}_1 is uniformly distributed over the set of K length binary vectors. Given \mathbf{W}_m , \mathbf{W}_{m+1} is uniformly distributed in a Hamming ball of radius $\delta_K K$, $B(\mathbf{W}_m, \delta_K K) = \{\mathbf{W} : d_H(\mathbf{W}, \mathbf{W}_m) \leq \delta_K K\}$, and the volume of the Hamming ball is given by

$$\text{Vol}(\delta_K K, K) = |B(\mathbf{W}_m, \delta_K K)| = \sum_{j=0}^{\delta_K K} \binom{K}{j}. \quad (1)$$

Given a correlation coefficient δ_K , we denote the set of possible tuples $(\mathbf{w}_1, \mathbf{w}_2, \dots, \mathbf{w}_\nu)$ under our correlation model by A_{δ_K} . We provide the formal definition next.

Definition 1 (δ_K -possible Set of Tuples). The set A_{δ_K} of δ_K -possible set of tuples $(\mathbf{w}_1, \mathbf{w}_2, \dots, \mathbf{w}_\nu)$ is defined as follows

$$A_{\delta_K}(\mathbf{W}_1, \mathbf{W}_2, \dots, \mathbf{W}_\nu) = \{(\mathbf{w}_1, \mathbf{w}_2, \dots, \mathbf{w}_\nu) : \mathbf{w}_1 \in [2^K], \mathbf{w}_2 \in B(\mathbf{w}_1, \delta_K K), \dots, \mathbf{w}_\nu \in B(\mathbf{w}_{\nu-1}, \delta_K K)\}. \quad (2)$$

We omit the dependency on the messages and simply write A_{δ_K} , when it is clear from the context. Similarly, we can also define the set of possible tuples \mathbf{w}_{F_1} given a particular tuple \mathbf{w}_{F_2} , $A_{\delta_K}(\mathbf{W}_{F_1} | \mathbf{w}_{F_2})$, where F_1, F_2 are two subsets of $[\nu]$.

Remark 1. Unlike the case of the twin binary symmetric source, in our model, the correlation coefficient δ_K is a function of K in general and is not necessarily a constant. The more familiar expressions that involve entropies can be obtained when δ_K is equal to a constant δ using Stirling's inequality [31]. Specifically, for $\delta < 1/2$, we have

$$KH(\delta) - o(K) \leq \log \text{Vol}(\delta K, K) \leq KH(\delta). \quad (3)$$

The i -th server receives an arbitrary subset of versions $\mathbf{S}(i) \subseteq [\nu]$ that denotes the *state* of that server. We denote the system state by $\mathbf{S} = \{\mathbf{S}(1), \mathbf{S}(2), \dots, \mathbf{S}(n)\} \in \mathcal{P}([\nu])^n$, where $\mathcal{P}([\nu])$ is the power set of $[\nu]$. For the i -th server with state $\mathbf{S}(i) = \{s_1, s_2, \dots, s_{|\mathbf{S}(i)|}\}$, where $s_1 < s_2 < \dots < s_{|\mathbf{S}(i)|}$, the server stores a codeword symbol generated by the encoding function $\varphi_{\mathbf{S}(i)}^{(i)}$ that takes an input $\mathbf{W}_{\mathbf{S}(i)}$ and outputs an element from the set $[q]$ that can be represented by $\log q$ bits. In state $\mathbf{S} \in \mathcal{P}([\nu])^n$, we denote the set of servers that have received \mathbf{W}_u by $\mathcal{A}_{\mathbf{S}}(u) = \{j \in [n] : u \in \mathbf{S}(j)\}$ and a version $u \in [\nu]$ is termed *complete* if $|\mathcal{A}_{\mathbf{S}}(u)| \geq c_W$, where $c_W \leq n - f$. The set of complete versions in state $\mathbf{S} \in \mathcal{P}([\nu])^n$ is given by $\mathcal{C}_{\mathbf{S}} = \{u \in [\nu] : |\mathcal{A}_{\mathbf{S}}(u)| \geq c_W\}$ and the latest among them is denoted by $L_{\mathbf{S}} := \max \mathcal{C}_{\mathbf{S}}$.

The goal of the multi-version coding problem is to devise encoders such that for every decoder that connects to any arbitrary set of $c_R \leq n - f$ servers, the latest complete version or a later version is decodable with probability of error that is at most ϵ while minimizing the per-server worst-case storage cost. We express this formally next.

Definition 2 (ϵ -error $(n, c_W, c_R, \nu, 2^K, q, \delta_K)$ multi-version code (MVC)). An ϵ -error $(n, c_W, c_R, \nu, 2^K, q, \delta_K)$ multi-version code (MVC) consists of the following

- encoding functions $\varphi_{\mathbf{S}(i)}^{(i)} : [2^K]^{|\mathbf{S}(i)|} \rightarrow [q]$, for every $i \in [n]$ and every state $\mathbf{S}(i) \subseteq [\nu]$
- decoding functions $\psi_{\mathbf{S}}^{(T)} : [q]^{c_R} \rightarrow [2^K] \cup \{\text{NULL}\}$,

that satisfy the following

$$\Pr \left[\psi_{\mathbf{S}}^{(T)} \left(\varphi_{\mathbf{S}(t_1)}^{(t_1)}, \dots, \varphi_{\mathbf{S}(t_{c_R})}^{(t_{c_R})} \right) = \mathbf{W}_m \text{ for some } m \geq L_{\mathbf{S}}, \text{ if } \mathcal{C}_{\mathbf{S}} \neq \emptyset \right] \geq 1 - \epsilon,$$

for every possible system state $\mathbf{S} \in \mathcal{P}([\nu])^n$ and every set of servers $T = \{t_1, t_2, \dots, t_{c_R}\} \subseteq [n]$, where the probability is computed over all possible tuples of the message versions.

We notice that set of possible tuples A_{δ_K} can be partitioned into disjoint sets as follows

$$A_{\delta_K} = A_{\delta_K,1} \cup A_{\delta_K,2}, \quad (4)$$

where $A_{\delta_K,1}$ is the set of tuples $(\mathbf{w}_1, \mathbf{w}_2, \dots, \mathbf{w}_\nu) \in A_{\delta_K}$ for which we can decode successfully for all $\mathbf{S} \in \mathcal{P}([\nu])^n$ and $A_{\delta_K,2}$ is the set of tuples where we cannot decode successfully at least for one state $\mathbf{S} \in \mathcal{P}([\nu])^n$.

Definition 3 (Storage Cost of a Multi-version Code). The storage cost of an ϵ -error $(n, c_W, c_R, \nu, 2^K, q, \delta_K)$ MVC is equal to $\alpha = \log q$ bits.

We next present an alternative decoding requirement that is shown in [14] to be equivalent to the multi-version coding problem defined above. For any set of servers $T \subseteq [n]$, note that $\max \cap_{i \in T} \mathbf{S}(i)$ denotes *the latest common version among* these servers. The alternate decoding requirement, which we refer to multi-version coding problem with Decoding Requirement A, replaces c_W, c_R by one parameter c . The decoding requirement requires that the decoder connects to any c servers and decodes the *latest common version* amongst those c servers, or a later version.

Definition 4 (ϵ -error $(n, c, \nu, 2^K, q, \delta_K)$ Multi-version code (MVC) with Decoding Requirement A). An ϵ -error $(n, c, \nu, 2^K, q, \delta_K)$ multi-version code (MVC) consists of the following

- encoding functions $\varphi_{\mathbf{S}(i)}^{(i)}: [2^K]^{|\mathbf{S}(i)|} \rightarrow [q]$, for every $i \in [n]$ and every state $\mathbf{S}(i) \subseteq [\nu]$
- decoding functions $\psi_{\mathbf{S}}^{(T)}: [q]^c \rightarrow [2^K] \cup \{NULL\}$,

that satisfy the following

$$\Pr \left[\psi_{\mathbf{S}}^{(T)} \left(\varphi_{\mathbf{S}(t_1)}^{(t_1)}, \dots, \varphi_{\mathbf{S}(t_c)}^{(t_c)} \right) = \mathbf{W}_m, \text{ for some } m \geq \max \cap_{i \in T} \mathbf{S}(i), \text{ if } \cap_{i \in T} \mathbf{S}(i) \neq \emptyset \right] \geq 1 - \epsilon,$$

for every possible system state $\mathbf{S} \in \mathcal{P}([\nu])^n$ and every set of servers $T = \{t_1, t_2, \dots, t_c\} \subseteq [n]$, where the probability is computed over all possible tuples of the message versions.

In this paper, we present our achievability results for decoding requirement A and Lemma 1 [14] establishes the connection between the two decoding requirements.

Lemma 1. Consider any positive integers n, c_W, c_R, c such that $c = c_W + c_R - n$. An ϵ -error $(n, c, \nu, 2^K, q, \delta_K)$ MVC with decoding requirement A exists if and only if an ϵ -error $(n, c_W, c_R, \nu, 2^K, q, \delta_K)$ MVC exists.

We now make some remarks interpreting the multi-version coding problem in terms of the underlying system and algorithm that it aims to model.

Remark 2.

- The system model has an implicit failure tolerance of f , as long as the quorum sizes c_W, c_R are chosen such that $c_W, c_R \leq n - f$. This is because, for a version to be complete, a writer must contact c_W servers, and for a reader, it must obtain responses from c_R servers - choosing $c_W, c_R \leq n - f$ ensures that write and read operations complete provided that the number of failed servers is no larger than f (see [9], [32] for more details).
- The parameter ν can be interpreted as a measure of the number of concurrent writes in the system [12]–[14], [16]. In distributed algorithms, the ordering among the various

write operations is determined by carefully constructed protocols usually through the use of *Lamport timestamps* (also known as logical timestamps) [33]. For instance, several protocols (e.g., [12], [13], [32]) involve a separate round of communication for a write to figure out the lamport clock (i.e., version number) before proceeding with dispersing the data. The mult-version coding problem abstracts out these protocol details into the version number. However, it is worth noting that a “later version” is not necessarily arriving to the system after an earlier version - they can be concurrent, and can in fact arrive at different nodes at different orders (e.g., see [14], [16]). A later version may simply be viewed as one that could receive a higher Lamport timestamp in a protocol execution.

- C. Unlike the study of [14] which considers 0-error MVCs, we allow the probability of error to be at most ϵ . See also Remark 4 for more details.

B. Background - Replication and Simple Erasure Coding

Replication and simple MDS codes provide two natural MVC constructions. Suppose that the state of the i -th server is $\mathbf{S}(i) = \{s_1, s_2, \dots, s_{|\mathbf{S}(i)|}\}$, where $s_1 < s_2 < \dots < s_{|\mathbf{S}(i)|}$.

- *Replication-based MVCs*: In this scheme, each server only stores the latest version it receives. The encoding function is $\varphi_{\mathbf{S}(i)}^{(i)}(\mathbf{W}_{\mathbf{S}(i)}) = \mathbf{W}_{s_{|\mathbf{S}(i)|}}$, hence the storage cost is K .
- *Simple MDS codes based MVC (MDS-MVC)*: In this scheme, an (n, c) MDS code is used to encode each version separately. Specifically, suppose that $\mathcal{C} : [2^K] \rightarrow [2^{K/c}]^n$ is an (n, c) MDS code over alphabet $[2^{K/c}]$, and denote the i -th co-ordinate of the output of \mathcal{C} by $\mathcal{C}^{(i)} : [2^K] \rightarrow [2^{K/c}]$. The encoding function is constructed as $\varphi_{\mathbf{S}(i)}^{(i)}(\mathbf{W}_{\mathbf{S}(i)}) = (\mathcal{C}^{(i)}(\mathbf{W}_{s_1}), \mathcal{C}^{(i)}(\mathbf{W}_{s_2}), \dots, \mathcal{C}^{(i)}(\mathbf{W}_{s_{|\mathbf{S}(i)|}}))$. That is, each server stores one codeword symbol for each version it receives and the storage cost is $\nu \frac{K}{c}$.

An important outcome of the study of [14] is that, when the different versions are independent, i.e., if $\delta_K = 1$, then the storage cost is at least $\frac{\nu K}{\nu+c-1} - \Theta(1)$. In particular, because $\frac{\nu}{\nu+c-1} \geq \frac{1}{2} \min(\frac{\nu}{c}, 1)$, the best possible MVC scheme is, for large K , at most twice as cost-efficient as the better among replication and simple erasure coding. In this paper, we show that replication and simple erasure coding are significantly inefficient if the different versions are correlated. Our schemes resemble simple erasure codes in their construction; however, we exploit the correlation between the versions to store fewer bits per server.

C. Summary of Results

In order to explain the significance of our results, summarized in Table I, we begin with a simple motivating scheme. Consider the MDS-MVC scheme of Section II-B. Assume that we use a Reed-Solomon code over a field \mathbb{F}_p of binary characteristic. The generator matrix of a Reed-Solomon code is usually expressed over \mathbb{F}_p . However, every element in \mathbb{F}_p is a vector over \mathbb{F}_2 , and a multiplication over the extension field \mathbb{F}_p is a linear transformation over \mathbb{F}_2 . Therefore, the generator matrix of the Reed-Solomon code can be equivalently expressed over \mathbb{F}_2 as follows

$$G = (G^{(1)}, G^{(2)}, \dots, G^{(n)}),$$

Scheme	Worst-case Storage Cost	Regime
Replication	K	oblivious to δ_K , $\epsilon = 0$
Simple erasure codes	$\nu \frac{K}{c}$	outperforms replication if $\nu < c$, oblivious to δ_K , $\epsilon = 0$
Theorem 2 [Reed-Solomon update-efficient code]	$\frac{K}{c} + (\nu - 1)\delta_K K(\log K + o(\log K))$	asymptotically outperforms the above schemes for $\nu < c$ and $\delta_K = o(1/\log K)$, oblivious to δ_K , $\epsilon = 0$
Motivating scheme of Section II-C	$\frac{K}{c} + (\nu - 1)\log \text{Vol}(\delta_K K, K)$	not oblivious to δ_K , $\epsilon = 0$
Theorem 3 [Random binning]	$\frac{K}{c} + \frac{\nu-1}{c}\log \text{Vol}(\delta_K K, K) + o(\log K)$	asymptotically outperforms the above schemes for $\nu < c$, not oblivious to δ_K , $\epsilon = 1/\log K$
Theorem 4 [Lower bound]	$\frac{K}{c+\nu-1} + \frac{\nu-1}{c+\nu-1}\log \text{Vol}(K, \delta_K K) - \Theta(1)$	applicable for all δ_K

TABLE I: Storage cost.

where G is a $K \times nK/c$ binary generator matrix, and $G^{(i)}$ has dimension $K \times K/c$. Because Reed-Solomon codes can tolerate $n-c$ erasures, every matrix of the form $(G^{(t_1)}, G^{(t_2)}, \dots, G^{(t_c)})$, where t_1, t_2, \dots, t_c are distinct elements of $[n]$, has a full rank of K over \mathbb{F}_2 .

We now describe a simple scheme that extends the MDS-MVC by exploiting the correlations and requires the knowledge of δ_K . Suppose that the i -th server receives the set of versions $\mathbf{S}(i) = \{s_1, s_2, \dots, s_{|\mathbf{S}(i)|}\}$, where $s_1 < s_2 < \dots < s_{|\mathbf{S}(i)|}$. The server encodes \mathbf{W}_{s_1} using the binary code as $\mathbf{W}_{s_1}^T G^{(i)}$. For \mathbf{W}_{s_m} , where $m > 1$, the server finds a difference vector $\mathbf{y}_{s_m, s_{m-1}}^{(i)}$ that satisfies the following

- 1) $\mathbf{y}_{s_m, s_{m-1}}^{(i)T} G^{(i)} = (\mathbf{W}_{s_m} - \mathbf{W}_{s_{m-1}})^T G^{(i)}$ and
- 2) $w_H(\mathbf{y}_{s_m, s_{m-1}}^{(i)}) \leq (s_m - s_{m-1})\delta_K K$.

Although it is not necessary that $\mathbf{y}_{s_m, s_{m-1}}^{(i)} = \mathbf{W}_{s_m} - \mathbf{W}_{s_{m-1}}$, the fact that $\mathbf{W}_{s_m} - \mathbf{W}_{s_{m-1}}$ satisfies these two conditions implies that the encoder can find at least one vector $\mathbf{y}_{s_m, s_{m-1}}^{(i)}$ satisfying these conditions. Since $w_H(\mathbf{y}_{s_m, s_{m-1}}^{(i)}) \leq (s_m - s_{m-1})\delta_K K$, an encoder aware of δ_K can represent $\mathbf{y}_{s_m, s_{m-1}}^{(i)}$ by $\log \text{Vol}((s_m - s_{m-1})\delta_K K, K)$ bits. The first condition implies that a decoder that connects to the i -th server can obtain $\mathbf{W}_{s_m}^T G^{(i)}$ by applying $\mathbf{W}_{s_1}^T G^{(i)} + \sum_{\ell=2}^m \mathbf{y}_{s_\ell, s_{\ell-1}}^{(i)T} G^{(i)} = \mathbf{W}_{s_m}^T G^{(i)}$. Therefore, from any subset $\{t_1, t_2, \dots, t_c\}$ of c servers, for any common version s_m among these servers, a decoder can recover $\mathbf{W}_{s_m}^T G^{(t_1)}, \mathbf{W}_{s_m}^T G^{(t_2)}, \dots, \mathbf{W}_{s_m}^T G^{(t_c)}$ from these servers and can therefore recover \mathbf{W}_{s_m} .

The worst-case storage cost of this scheme is obtained when each server receives all the ν versions, which results in a storage cost of $\frac{K}{c} + (\nu - 1)\log \text{Vol}(\delta_K K, K)$. Intuitively, the above scheme stores the first version using erasure coding - K/c bits - and the remaining $(\nu - 1)$ versions using delta coding, which adds a storage cost of $\log \text{Vol}(\delta_K K, K)$ bits per version. The scheme we described above motivates the following two questions.

Q1: Can we obtain a MVC construction that is oblivious to the parameter δ_K with a storage cost of $\frac{K}{c} + (\nu - 1)\log \text{Vol}(\delta_K K, K)$?

Q2: Can we use erasure coding to achieve a storage cost of $\frac{K}{c} + \frac{\nu-1}{c} \log \text{Vol}(\delta_K K, K)$?

In Section III-A, we provide Theorem 2 that answers Q1 by developing a 0-error Reed-Solomon based scheme that does not require the knowledge of δ_K and obtains the erasure coding gain of $1/c$ for the first version available at a server and stores the subsequent versions via delta coding.

In Section III-B, we provide Theorem 3 that gives a positive answer to Q2 by showing the existence of an ϵ -error storage efficient scheme that obtains the erasure coding factor of $1/c$, not only for the first version, but also for the subsequent versions. Moreover, the scheme is able to harness the delta compression gain.

Finally, in Section IV, Theorem 4 provides a lower bound on the per-server storage cost which implies that for $\nu < c$, constant $\delta_K = \delta$ and $\epsilon = 2^{-o(K)}$, the achievable scheme of Theorem 3 is asymptotically at most twice the lower bound. We notice that the regime where $\nu < c$ is interesting as the degree of asynchrony is typically limited as pointed out in [34].

III. CODE CONSTRUCTIONS (THEOREM 2 AND THEOREM 3)

In this section, we provide our code constructions. We study the case where δ_K is not known and present a MVC based on Reed-Solomon code in Section III-A. Later on in this section, we study the case where δ_K is known and propose a random binning argument in Section III-B.

A. Update-efficient Multi-version Codes

We develop simple multi-version coding scheme that exploits the correlation between the different versions and have smaller storage cost as compared with [14]. In this scheme, the servers do not know the correlation degree δ_K in advance. We begin by recalling the definition of the update efficiency of a code from [26].

Definition 5 (Update efficiency). For a code \mathcal{C} of length N and dimension K with encoder $\mathcal{C} : \mathbb{F}^K \rightarrow \mathbb{F}^N$, the update efficiency of the code is the maximum number of codeword symbols that must be updated when a single message symbol is changed and is expressed as follows

$$t = \max_{\substack{\mathbf{W}, \mathbf{W}' \in \mathbb{F}^K: \\ d_H(\mathbf{W}, \mathbf{W}')=1}} d_H(\mathcal{C}(\mathbf{W}), \mathcal{C}(\mathbf{W}')). \quad (5)$$

An (N, K) code \mathcal{C} is referred to as update-efficient code if it has an update efficiency of $o(N)$.

Definition 6 (Update efficiency of a server). Suppose that $\mathcal{C}^{(i)} : \mathbb{F}^K \rightarrow \mathbb{F}^{N/n}$ denotes the i -th co-ordinate of the output of \mathcal{C} stored by the i -th server. The update efficiency of the i -th server is the maximum number of codeword symbols that must be updated in this server when a single message symbol is changed and is expressed as follows

$$t^{(i)} = \max_{\substack{\mathbf{W}, \mathbf{W}' \in \mathbb{F}^K: \\ d_H(\mathbf{W}, \mathbf{W}')=1}} d_H(\mathcal{C}^{(i)}(\mathbf{W}), \mathcal{C}^{(i)}(\mathbf{W}')). \quad (6)$$

Suppose that $G = (G^{(1)}, G^{(2)}, \dots, G^{(n)})$ is the generator matrix of a linear code \mathcal{C} , where $G^{(i)}$ is a $K \times N/n$ matrix that corresponds to the i -th server. The update efficiency of the i -th server is the maximum row weight of $G^{(i)}$.

Definition 7 (The per-server maximum update efficiency). The per-server maximum update efficiency is the maximum number of codeword symbols that must be updated in any server when a single message symbol is changed and is given by

$$t_s = \max_{i \in [n]} t^{(i)}. \quad (7)$$

We next present an update-efficient MVC construction, illustrated in Fig. 2, that is based on Reed-Solomon code and has a maximum update efficiency per-server $t_s = 1$.

Construction 1 (Reed-Solomon Update-Efficient MVC). Suppose that the i -th server receives the versions $\mathbf{S}(i) = \{s_1, s_2, \dots, s_{|\mathbf{S}(i)|}\}$, where $s_1 < s_2 < \dots < s_{|\mathbf{S}(i)|}$. A version \mathbf{W}_{s_j} is divided into $\frac{K}{c \log n_p}$ blocks of length $c \log n_p$, where $n_p = 2^{\lceil \log_2 n \rceil}$. In each block, every consecutive string of $\log n_p$ bits is represented by a symbol in \mathbb{F}_{n_p} . The representation of \mathbf{W}_{s_j} over \mathbb{F}_{n_p} is denoted by $\overline{\mathbf{W}}_{s_j}$. Each block is then encoded by an (n, c) Reed-Solomon code with a generator matrix \tilde{G} that is given by

$$\tilde{G} = \begin{pmatrix} 1 & 1 & \dots & 1 \\ \lambda_1 & \lambda_2 & \dots & \lambda_n \\ \lambda_1^2 & \lambda_2^2 & \dots & \lambda_n^2 \\ \vdots & \vdots & \vdots & \vdots \\ \lambda_1^{c-1} & \lambda_2^{c-1} & \dots & \lambda_n^{c-1} \end{pmatrix}, \quad (8)$$

where $\Lambda = \{\lambda_1, \lambda_2, \dots, \lambda_n\} \subset \mathbb{F}_{n_p}$ is a set of distinct elements. For \mathbf{W}_{s_1} , the i -th server stores $\overline{\mathbf{W}}_{s_1}^T G^{(i)}$, where $G^{(i)}$ is a $\frac{K}{\log n_p} \times \frac{K}{c \log n_p}$ matrix that is given by

$$G^{(i)} = \begin{pmatrix} \tilde{G} \mathbf{e}_i & 0 & \dots & 0 & 0 \\ 0 & \tilde{G} \mathbf{e}_i & \dots & 0 & 0 \\ \vdots & \vdots & \vdots & \vdots & \vdots \\ 0 & 0 & \dots & 0 & \tilde{G} \mathbf{e}_i \end{pmatrix}, \quad (9)$$

where \mathbf{e}_i is i -th standard basis vector over \mathbb{F}_{n_p} . For \mathbf{W}_{s_m} , where $m > 1$, the server may only store the updated symbols from the old version $\overline{\mathbf{W}}_{s_{m-1}}$ or store $\overline{\mathbf{W}}_{s_m}^T G^{(i)}$.

Theorem 2. [Reed-Solomon Update-Efficient MVC] Construction 1 is a 0-error $(n, c, \nu, 2^K, q, \delta_K)$ multi-version code with a worst-case storage that is at most

$$\frac{K}{c} + (\nu - 1) \min\left(\delta_K K \log \left(\frac{K n_p}{c \log n_p} \right), K/c\right), \quad (10)$$

where $n_p = 2^{\lceil \log_2 n \rceil}$.

Proof of Theorem 2. We observe that Construction 1 is a valid multi-version code as the latest common version is recoverable from any c servers by the MDS property of Reed-Solomon code. In order to characterize the worst-case storage cost, we observe that the update efficiency of the i -th server is equal to the maximum row weight of $G^{(i)}$ which is equal to 1, $\forall i \in [n]$. Thus, the per-server maximum update efficiency t_s is also equal to 1.




Fig. 2: Illustration of Construction 1. A bit that changes in the message leads at most to one updated codeword symbol in the i -th server, $\forall i \in [n]$, hence $t_s = 1$.

The worst-case storage cost corresponds to the case where a server receives all versions. In this case, the server stores $\overline{\mathbf{W}}_1^T G^{(i)}$ for the first version. For \mathbf{W}_u , where $u > 2$, the server may only store the updated symbols from the old version $\overline{\mathbf{W}}_{u-1}$ or store $\overline{\mathbf{W}}_u^T G^{(i)}$. Storing the index of an updated symbol requires $\log(\frac{K}{c \log n_p})$ bits and storing the value requires $\log n_p$. Therefore, the per-server storage cost is upper-bounded as follows

$$\begin{aligned}
\alpha &\leq \frac{K}{c} + \sum_{u=2}^{\nu} \min(d_H(\mathbf{W}_u, \mathbf{W}_{u-1}) \log\left(\frac{K n_p}{c \log n_p}\right), K/c) \\
&\leq \frac{K}{c} + \sum_{u=2}^{\nu} \min(d_H(\mathbf{W}_u, \mathbf{W}_{u-1}) \log\left(\frac{K n_p}{c \log n_p}\right), K/c) \\
&\leq \frac{K}{c} + (\nu - 1) \min(\delta_K K \log\left(\frac{K n_p}{c \log n_p}\right), K/c).
\end{aligned}$$

□

B. Random Binning Based Multi-version Codes

We next introduce a random binning argument showing the existence of a multi-version code that can harness both of the erasure and the delta coding gains for all versions for the case where δ_K is known. Recall that Slepian-Wolf coding [17], [35] is a distributed data compression technique for correlated sources that are drawn in independent and identical manner according to a given distribution. In the Slepian-Wolf setting, the decoder is interested in decoding the data of all sources. In the multi-version coding problem, the decoder is interested in decoding the latest common version, or a later version, among any set of c servers.

We notice that our model differs from the Slepian-Wolf setting as we do not aspire to decode all the versions. The lossless source coding problem with a helper [36]–[38] may also seem related to our approach, since the side information of the older versions may be interpreted as helpers. In the optimal strategy for the helper setting, the helper side information is encoded

via a joint typicality encoding scheme, whereas the random binning is used for the message. However, in the multi-version coding setting, a version that may be a side information for one state may be required to be decoded in another state. For this reason, a random binning scheme for all versions leads to schemes with a near-optimal storage cost. We next present the code construction that is inspired by Cover's random binning proof of the Slepian-Wolf problem [38].

Construction 2 (Random binning multi-version code). Suppose that the i -th server receives the versions $\mathbf{S}(i) = \{s_1, s_2, \dots, s_{|\mathbf{S}(i)|}\} \subseteq [\nu]$, where $s_1 < s_2 < \dots < s_{|\mathbf{S}(i)|}$.

- *Random code generation*: At the i -th server, for a version s_j the encoder assigns an index at random from $\{1, 2, \dots, 2^{R_{s_j}^{(i)}/c}\}$ uniformly and independently to each vector of length K bits, where $R_{s_j}^{(i)}/c$ is the rate assigned by the i -th server to version s_j .
- *Encoding*: The server stores the corresponding index to each version that it receives and the decoder is also aware of this mapping. The encoding function of the i -th server is given by

$$\varphi_{\mathbf{S}(i)}^{(i)} = (\varphi_{s_1}^{(i)}, \varphi_{s_2}^{(i)}, \dots, \varphi_{s_{|\mathbf{S}(i)|}}^{(i)}), \quad (11)$$

where $\varphi_{s_j}^{(i)}: [2^K] \rightarrow \{1, 2, \dots, 2^{KR_{s_j}^{(i)}/c}\}$ and we choose the rates as follows

$$KR_{s_1}^{(i)} = K + (s_1 - 1) \log \text{Vol}(\delta_K K, K) + (s_1 - 1) - \log \epsilon 2^{-\nu n}, \quad (12)$$

$$KR_{s_j}^{(i)} = (s_j - s_{j-1}) \log \text{Vol}(\delta_K K, K) + (s_j - 1) - \log \epsilon 2^{-\nu n}, j \in \{2, 3, \dots, |\mathbf{S}(i)|\}. \quad (13)$$

Consider a state $\mathbf{S} \in \mathcal{P}([\nu])^n$ and suppose that the decoder connects to the servers $T = \{t_1, t_2, \dots, t_c\} \subseteq [n]$. Suppose that a version s_j is received by a set of servers $\{i_1, i_2, \dots, i_r\} \subseteq T$, then the bin index corresponding to this version is given by

$$\varphi_{s_j} = (\varphi_{s_j}^{(i_1)}, \varphi_{s_j}^{(i_2)}, \dots, \varphi_{s_j}^{(i_r)}). \quad (14)$$

In this case, the rate of version s_j is given by

$$R_{s_j} = \frac{1}{c} \sum_{i \in \{i_1, i_2, \dots, i_r\}} R_{s_j}^{(i)}. \quad (15)$$

Decoding: The decoder employs the *possible set decoding* strategy as follows. Assume that \mathbf{W}_{u_L} is the latest common version in \mathbf{S} and that the versions $\mathbf{W}_{u_1}, \mathbf{W}_{u_2}, \dots, \mathbf{W}_{u_{L-1}}$ are the older versions such that each of them is received by at least one server out of those c servers. We denote this set of versions by \mathbf{S}_T and define it formally as follows

$$\mathbf{S}_T = \{u_1, u_2, \dots, u_L\} = \left(\bigcup_{t \in T} \mathbf{S}(t) \right) \setminus \{u_L + 1, u_L + 2, \dots, \nu\}, \quad (16)$$

where $u_1 < u_2 < \dots < u_L$. Given the bin indices $(b_{u_1}, b_{u_2}, \dots, b_{u_L})$, the decoder finds all tuples $(\mathbf{w}_{u_1}, \mathbf{w}_{u_2}, \dots, \mathbf{w}_{u_L}) \in A_{\delta_K}$ such that $(\varphi_{u_1}(\mathbf{w}_{u_1}) = b_{u_1}, \varphi_{u_2}(\mathbf{w}_{u_2}) = b_{u_2}, \dots, \varphi_{u_L}(\mathbf{w}_{u_L}) = b_{u_L})$. If all of these tuples have the same latest common version \mathbf{w}_{u_L} , the decoder declares \mathbf{w}_{u_L} to be the estimate of the latest common version $\hat{\mathbf{W}}_{u_L}$. Otherwise, it declares an error.

Theorem 3. [Random Binning MVC] There exists an ϵ -error $(n, c, \nu, 2^K, q, \delta_K)$ multi-version code whose worst-case storage cost is at most

$$\frac{K}{c} + \frac{(\nu - 1) \log \text{Vol}(\delta_K K, K)}{c} + \frac{\nu(\nu - 1)/2 - \nu \log \epsilon 2^{-\nu n}}{c}. \quad (17)$$

Proof of Theorem 3. We show that Construction 2 is an ϵ -error multi-version code.

We denote the error event by E and express it as follows

$$E = \{\exists (\mathbf{w}'_{u_1}, \mathbf{w}'_{u_2}, \dots, \mathbf{w}'_{u_L}) \in A_{\delta_K} : \mathbf{w}'_{u_L} \neq \mathbf{W}_{u_L} \text{ and } \varphi_u(\mathbf{w}'_u) = \varphi_u(\mathbf{W}_u), \forall u \in \mathbf{S}_T\}. \quad (18)$$

The error event in decoding can be equivalently expressed as follows

$$E = \bigcup_{\mathcal{I} \subseteq \mathbf{S}_T : u_L \in \mathcal{I}} E_{\mathcal{I}} \quad (19)$$

where

$$E_{\mathcal{I}} = \{\exists \mathbf{w}'_u \neq \mathbf{W}_u, \forall u \in \mathcal{I} : \varphi_u(\mathbf{w}'_u) = \varphi_u(\mathbf{W}_u), \forall u \in \mathcal{I} \text{ and } (\mathbf{w}'_{\mathcal{I}}, \mathbf{W}_{\mathbf{S}_T \setminus \mathcal{I}}) \in A_{\delta_K}\}, \quad (20)$$

for $\mathcal{I} \subseteq \mathbf{S}_T$ such that $u_L \in \mathcal{I}$. By the union bound, we have

$$P_e(\mathbf{S}, T) := P(E) = P\left(\bigcup_{\mathcal{I} \subseteq \mathbf{S}_T : u_L \in \mathcal{I}} E_{\mathcal{I}}\right) \leq \sum_{\mathcal{I} \subseteq \mathbf{S}_T : u_L \in \mathcal{I}} P(E_{\mathcal{I}}), \quad (21)$$

and we require that $P_e(\mathbf{S}, T) \leq \epsilon 2^{-\nu n}$. Thus, for every $\mathcal{I} \subseteq \mathbf{S}_T$ such that $u_L \in \mathcal{I}$, it suffices to show that $P(E_{\mathcal{I}}) \leq \epsilon 2^{-(L-1)} 2^{-\nu n}$.

We now proceed in a case by case manner as shown in Fig. 3. We first consider the case where




Fig. 3: Illustration of the error analysis of Construction 2.

$u_{L-1} \notin \mathcal{I}$, later we consider the case where $u_{L-1} \in \mathcal{I}$. For the case where $u_{L-1} \notin \mathcal{I}$, we have

$$E_{\mathcal{I}} \subset \tilde{E}_{u_{L-1}} := \{\exists \mathbf{w}'_{u_L} \neq \mathbf{W}_{u_L} : \varphi_{u_L}(\mathbf{w}'_{u_L}) = \varphi_{u_L}(\mathbf{W}_{u_L}) \text{ and } (\mathbf{W}_{u_{L-1}}, \mathbf{w}'_{u_L}) \in A_{\delta_K}\}. \quad (22)$$

Consequently, we have

$$P(E_{\mathcal{I}}) \leq P(\tilde{E}_{u_{L-1}}) = \sum_{(\mathbf{w}_{u_{L-1}}, \mathbf{w}_{u_L})} p(\mathbf{w}_{u_{L-1}}, \mathbf{w}_{u_L})$$

$$\begin{aligned}
& P(\exists \mathbf{w}'_{u_L} \neq \mathbf{w}_{u_L} : \varphi_{u_L}(\mathbf{w}'_{u_L}) = \varphi_{u_L}(\mathbf{w}_{u_L}) \text{ and } (\mathbf{w}_{u_{L-1}}, \mathbf{w}'_{u_L}) \in A_{\delta_K}) \\
& \stackrel{(a)}{\leq} \sum_{(\mathbf{w}_{u_{L-1}}, \mathbf{w}_{u_L})} p(\mathbf{w}_{u_{L-1}}, \mathbf{w}_{u_L}) \sum_{\substack{\mathbf{w}'_{u_L} \neq \mathbf{w}_{u_L} \\ (\mathbf{w}_{u_{L-1}}, \mathbf{w}'_{u_L}) \in A_{\delta_K}}} P(\varphi_{u_L}(\mathbf{w}'_{u_L}) = \varphi_{u_L}(\mathbf{w}_{u_L})) \\
& \stackrel{(b)}{=} \sum_{(\mathbf{w}_{u_{L-1}}, \mathbf{w}_{u_L})} p(\mathbf{w}_{u_{L-1}}, \mathbf{w}_{u_L}) \sum_{\substack{\mathbf{w}'_{u_L} \neq \mathbf{w}_{u_L} \\ (\mathbf{w}_{u_{L-1}}, \mathbf{w}'_{u_L}) \in A_{\delta_K}}} \prod_{i=1}^c P(\varphi_{u_L}^{(t_i)}(\mathbf{w}'_{u_L}) = \varphi_{u_L}^{(t_i)}(\mathbf{w}_{u_L})) \\
& \leq \sum_{(\mathbf{w}_{u_{L-1}}, \mathbf{w}_{u_L})} p(\mathbf{w}_{u_{L-1}}, \mathbf{w}_{u_L}) |A_{\delta_K}(\mathbf{W}_{u_L} | \mathbf{w}_{u_{L-1}})| \prod_{i=1}^c 2^{-KR_{u_L}^{(t_i)}/c} \\
& \stackrel{(c)}{=} \sum_{(\mathbf{w}_{u_{L-1}}, \mathbf{w}_{u_L})} p(\mathbf{w}_{u_{L-1}}, \mathbf{w}_{u_L}) |A_{\delta_K}(\mathbf{W}_{u_L} | \mathbf{w}_{u_{L-1}})| 2^{-KR_{u_L}} \\
& = \sum_{(\mathbf{w}_{u_{L-1}}, \mathbf{w}_{u_L})} p(\mathbf{w}_{u_{L-1}}, \mathbf{w}_{u_L}) 2^{-(KR_{u_L} - \log \text{Vol}((u_L - u_{L-1})\delta_K K, K))} \\
& = 2^{-(KR_{u_L} - \log \text{Vol}((u_L - u_{L-1})\delta_K K, K))}, \tag{23}
\end{aligned}$$

where (a) follows by the union bound, (b) follows since each server assigns an index independently from the other servers and (c) follows from (15). Choosing R_{u_L} to satisfy

$$KR_{u_L} \geq \log \text{Vol}((u_L - u_{L-1})\delta_K K, K) + (L - 1) - \log \epsilon 2^{-\nu n}$$

ensures that $P(E_{\mathcal{I}}) \leq \epsilon 2^{-(L-1)} 2^{-\nu n}$.

Now, we consider the case where $u_{L-1} \in \mathcal{I}$. In this case, we consider the following two cases. First, we consider the case where $u_{L-2} \notin \mathcal{I}$, later we consider the case where $u_{L-2} \in \mathcal{I}$. For the case where $u_{L-2} \notin \mathcal{I}$, we have

$$\begin{aligned}
E_{\mathcal{I}} \subseteq \tilde{E}_{u_{L-2}} &:= \{\exists \mathbf{w}'_{u_{L-1}} \neq \mathbf{W}_{u_{L-1}}, \mathbf{w}'_{u_L} \neq \mathbf{W}_{u_L} : \varphi_{u_{L-1}}(\mathbf{w}'_{u_{L-1}}) = \varphi_{u_{L-1}}(\mathbf{W}_{u_{L-1}}), \\
&\varphi_{u_L}(\mathbf{w}'_{u_L}) = \varphi_{u_L}(\mathbf{W}_{u_L}) \text{ and } (\mathbf{W}_{u_{L-2}}, \mathbf{w}'_{u_{L-1}}, \mathbf{w}'_{u_L}) \in A_{\delta_K}\}. \tag{24}
\end{aligned}$$

Therefore, we have

$$\begin{aligned}
P(E_{\mathcal{I}}) &< P(\tilde{E}_{u_{L-2}}) \leq \sum_{(\mathbf{w}_{u_{L-2}}, \mathbf{w}_{u_{L-1}}, \mathbf{w}_{u_L})} p(\mathbf{w}_{u_{L-2}}, \mathbf{w}_{u_{L-1}}, \mathbf{w}_{u_L}) \\
&\sum_{\substack{\mathbf{w}'_{u_{L-1}} \neq \mathbf{w}_{u_{L-1}} \\ \mathbf{w}'_{u_L} \neq \mathbf{w}_{u_L} \\ (\mathbf{w}_{u_{L-2}}, \mathbf{w}'_{u_{L-1}}, \mathbf{w}'_{u_L}) \in A_{\delta_K}}} P(\varphi(\mathbf{w}'_{u_{L-1}}) = \varphi(\mathbf{w}_{u_{L-1}})) P(\varphi_{u_L}(\mathbf{w}'_{u_L}) = \varphi(\mathbf{w}_{u_L})) \\
&\leq \sum_{(\mathbf{w}_{u_{L-2}}, \mathbf{w}_{u_{L-1}}, \mathbf{w}_{u_L})} p(\mathbf{w}_{u_{L-2}}, \mathbf{w}_{u_{L-1}}, \mathbf{w}_{u_L}) 2^{-K(R_{u_{L-1}} + R_{u_L})} |A_{\delta_K}(\mathbf{W}_{u_{L-1}}, \mathbf{W}_{u_L} | \mathbf{w}_{u_{L-2}})| \\
&= \sum_{(\mathbf{w}_{u_{L-2}}, \mathbf{w}_{u_{L-1}}, \mathbf{w}_{u_L})} p(\mathbf{w}_{u_{L-2}}, \mathbf{w}_{u_{L-1}}, \mathbf{w}_{u_L}) 2^{-K(R_{u_{L-1}} + R_{u_L})}
\end{aligned}$$

$$2^{\log \text{Vol}((u_L - u_{L-1})\delta_K K, K) + \log \text{Vol}((u_{L-1} - u_{L-2})\delta_K K, K)}. \quad (25)$$

In this case, we choose the rates as follows

$$K(R_{u_{L-1}} + R_{u_L}) \geq \sum_{j=L-1}^L \log \text{Vol}((u_j - u_{j-1})\delta_K K, K) + (L-1) - \log \epsilon 2^{-\nu n}.$$

We next consider the other case where $u_{L-2} \in \mathcal{I}$. In this case, we also have two cases based on whether u_{L-3} is in \mathcal{I} or not. By applying the above argument repeatedly, we obtain the following conditions for the overall probability of error to be upper bounded by $\epsilon 2^{-\nu n}$.

$$\begin{aligned} K \sum_{j=i}^L R_{u_j} &\geq \sum_{j=i}^L \log \text{Vol}((u_j - u_{j-1})\delta_K K, K) + (L-1) - \log \epsilon 2^{-\nu n}, \forall i \in \{2, 3, \dots, L\}, \\ K \sum_{j=1}^L R_{u_j} &\geq K + \sum_{j=2}^L \log \text{Vol}((u_j - u_{j-1})\delta_K K, K) + (L-1) - \log \epsilon 2^{-\nu n}. \end{aligned} \quad (26)$$

Since $\log \text{Vol}(m\delta_K K, K) \leq m \log \text{Vol}(\delta_K K, K), \forall m \in \mathbb{Z}^+$, it suffices if the rates satisfy

$$\begin{aligned} K \sum_{j=i}^L R_{u_j} &\geq \sum_{j=i}^L (u_j - u_{j-1}) \log \text{Vol}(\delta_K K, K) + (L-1) - \log \epsilon 2^{-\nu n}, \forall i \in \{2, 3, \dots, L\}, \\ K \sum_{j=1}^L R_{u_j} &\geq K + \sum_{j=2}^L (u_j - u_{j-1}) \log \text{Vol}(\delta_K K, K) + (L-1) - \log \epsilon 2^{-\nu n}. \end{aligned} \quad (27)$$

The rates chosen in (12), (13) satisfy the above inequalities, therefore our construction has a probability of error bounded by $\epsilon 2^{-\nu n}$. Moreover, as in [39, Chapter 7], it follows that there exists a deterministic code that has a probability of error bounded by ϵ . The worst-case storage cost is when a server receives all versions and is given by

$$\frac{K - \log \epsilon 2^{-\nu n}}{c} + \frac{(\nu - 1)(\log \text{Vol}(\delta_K K, K) - \log \epsilon 2^{-\nu n} + \nu/2)}{c}.$$

□

Motivated by the fact that linear codes have lower complexity, in the Appendix, we show that linear codes exist that achieve the storage cost of Theorem 3. Our proof is inspired by [18].

Remark 3. The proof of Theorem 3 uses simultaneous non-unique decoding ideas [40] used in several multi-user scenarios. In particular, with our non-unique decoding approach to decode \mathbf{W}_{u_L} , the decoder picks the unique \mathbf{w}_{u_L} such that $(\mathbf{w}_{u_1}, \mathbf{w}_{u_2}, \dots, \mathbf{w}_{u_L}) \in A_{\delta_K}$ for *some* $\mathbf{w}_{u_1}, \mathbf{w}_{u_2}, \dots, \mathbf{w}_{u_{L-1}}$, which are consistent with the bin indices. We use this strategy since unlike the Slepian-Wolf problem where all the messages are to be decoded, we are only required to decode the latest common version. In contrast, the *unique decoding* approach employed by Slepian-Wolf coding would require the decoder to obtain for some subset $S \subseteq \{u_1, u_2, \dots, u_L\}$ such that $u_L \in S$, the unique \mathbf{w}_S in the possible set that is consistent with the bin-indices; unique decoding, for instance, would not allow for correct decoding if there are multiple possible tuples even if they happen to have the same latest common version \mathbf{w}_{u_L} . The discussion in [41], which

examined the necessity of non-unique decoding, motivates the following question: Can we use the decoding ideas of Slepian-Wolf - where all the messages are decoded - however, for an appropriately chosen subset of versions and have the same rates? In other words, if we take the union of the unique decoding rate regions over all possible subsets of $\{\mathbf{W}_{u_1}, \mathbf{W}_{u_2}, \dots, \mathbf{W}_{u_L}\}$, does the rate allocation of (12), (13) lie in this region? The answer of this question is that non-unique decoding provides better rates than unique decoding in our case as we explain in Example 1.

Example 1. We consider the case where $\delta_K = \delta$, $c = 2$ and $\nu = 3$. Consider the state where server 2 does not receive \mathbf{W}_1 . Then, the storage allocation of our scheme is given by Table II. We use KR_u to denote the total number of bits stored for version $u \in [\nu]$ in Table II.

Version	Server 1	Server 2
\mathbf{W}_1	$\frac{K+o(K)}{2}$	-
\mathbf{W}_2	$\frac{KH(\delta)+o(K)}{2}$	$\frac{K+KH(\delta)+o(K)}{2}$
\mathbf{W}_3	$\frac{KH(\delta)+o(K)}{2}$	$\frac{KH(\delta)+o(K)}{2}$

TABLE II: Storage Allocation of Example 1.

We first examine unique decoding based decoders that aim to recover \mathbf{W}_3 . It is clear that the decoder cannot recover the K bits of \mathbf{W}_3 without using side information, since the total number of bits of \mathbf{W}_3 stored is only $KH(\delta) + o(K)$.

We next consider the case where a unique decoding based decoder uses the subset $\{\mathbf{W}_1, \mathbf{W}_3\}$. The rates $(R_1^{(unique, \mathbf{W}_1, \mathbf{W}_3)}, R_3^{(unique, \mathbf{W}_1, \mathbf{W}_3)})$ for a vanishing probability of error must satisfy

$$KR_3^{(unique, \mathbf{W}_1, \mathbf{W}_3)} \geq KH(\delta * \delta) + o(K),$$

$$K(R_1^{(unique, \mathbf{W}_1, \mathbf{W}_3)} + R_3^{(unique, \mathbf{W}_1, \mathbf{W}_3)}) \geq K + KH(\delta * \delta) + o(K),$$

where $\delta * \delta = 2\delta(1 - \delta)$. However, $KR_3 = KH(\delta) + o(K) < KR_3^{(unique, \mathbf{W}_1, \mathbf{W}_3)}$.

We next consider the case where a unique decoding based decoder uses $\{\mathbf{W}_2, \mathbf{W}_3\}$ for decoding. In this case, the decoder requires

$$KR_3^{(unique, \mathbf{W}_2, \mathbf{W}_3)} \geq KH(\delta) + o(K),$$

$$K(R_2^{(unique, \mathbf{W}_2, \mathbf{W}_3)} + R_3^{(unique, \mathbf{W}_2, \mathbf{W}_3)}) \geq K + KH(\delta) + o(K)$$

We notice $K(R_2 + R_3) = K/2 + 2KH(\delta) + o(K) < K(R_2^{(unique, \mathbf{W}_2, \mathbf{W}_3)} + R_3^{(unique, \mathbf{W}_2, \mathbf{W}_3)})$, for $\delta < H^{-1}(0.5)$.

Finally, consider the case where a unique decoding based decoder uses all three messages $\{\mathbf{W}_1, \mathbf{W}_2, \mathbf{W}_3\}$. In this case, the rate tuples $(R_1^{(unique, \mathbf{W}_1, \mathbf{W}_2, \mathbf{W}_3)}, R_3^{(unique, \mathbf{W}_1, \mathbf{W}_2, \mathbf{W}_3)})$ have to satisfy seven inequalities, including the following inequality

$$K(R_1^{(unique, \mathbf{W}_1, \mathbf{W}_2, \mathbf{W}_3)} + R_3^{(unique, \mathbf{W}_1, \mathbf{W}_2, \mathbf{W}_3)}) \geq K + KH(\delta * \delta) + o(K)$$

Clearly $K(R_1 + R_3) < K(R_1^{(\text{unique}, \mathbf{W}_1, \mathbf{W}_2, \mathbf{W}_3)} + R_3^{(\text{unique}, \mathbf{W}_1, \mathbf{W}_2, \mathbf{W}_3)})$. Thus, the union of the unique decoding rate regions for vanishing error probabilities, taken over all possible subsets of $\{\mathbf{W}_1, \mathbf{W}_2, \mathbf{W}_3\}$, does not include the rate tuple of Table II.

Remark 4. The result of Theorem 3 allows for erroneous decoding with probability at most ϵ . A natural question is to ask whether a similar storage cost can be obtained if we want the probability of error to be 0, i.e., if we want our decoder to correctly decode for *every* possible message tuple. The answer to this question in general is connected to the question of whether 0-error rate region and ϵ -error rate region are identical for our setting. There are several instances in network information theory where, even though there is no noise in the network the ϵ -error capacity is still larger than the zero error capacity, (e.g., multiple access [31]). For some networks, the answer to this question is unknown and involves deep connections to other related questions [42]. Note also for distributed source coding setups such as our problem, the determination of the 0-error capacity is more complicated and involves the use of graph entropy [43]. In this paper, we leave the question of whether the 0-error and ϵ -error rate regions are the same, open.

IV. LOWER BOUND ON THE STORAGE COST (THEOREM 4)

In this section, we extend the lower bound on the per-server storage cost of [14] for the case where we have correlated versions, and we require the probability of error to be at most ϵ .

Theorem 4. [Storage Cost Lower Bound] An ϵ -error $(n, c, \nu, 2^K, q, \delta_K)$ multi-version code with correlated versions such that $\mathbf{W}_1 \rightarrow \mathbf{W}_2 \rightarrow \dots \rightarrow \mathbf{W}_\nu$ form a Markov chain, $\mathbf{W}_m \in [2^K]$ and given \mathbf{W}_m , \mathbf{W}_{m+1} is uniformly distributed in a Hamming ball of radius $\delta_K K$ centered around \mathbf{W}_m must satisfy

$$\log q \geq \frac{K + (\nu - 1) \log \text{Vol}(\delta_K K, K)}{c + \nu - 1} + \frac{\log(1 - \epsilon 2^{\nu n}) - \log \binom{c + \nu - 1}{\nu} \nu!}{c + \nu - 1}, \quad (28)$$

where $\epsilon < 1/2^{\nu n}$.

Proof of Theorem 4 for $\nu = 2$. Consider any ϵ -error $(n, c, 2, 2^K, q, \delta_K)$ multi-version code, and consider the first c servers, $T = [c]$, for decoding. We recall that the set of possible tuples A_{δ_K} is partitioned into disjoint sets as follows

$$A_{\delta_K} = A_{\delta_K,1} \cup A_{\delta_K,2},$$

where $A_{\delta_K,1}$ is the set of tuples $(\mathbf{w}_1, \mathbf{w}_2) \in A_{\delta_K}$ for which we can decode successfully for all $\mathbf{S} \in \mathcal{P}([\nu])^n$ and $A_{\delta_K,2}$ is the set of tuples where we cannot decode successfully at least for one state $\mathbf{S} \in \mathcal{P}([\nu])^n$, which can be expressed as follows

$$A_{\delta_K,2} = \bigcup_{\mathbf{S} \in \mathcal{P}([\nu])^n} A_{\delta_K,2}^{(\mathbf{S})}, \quad (29)$$

where $A_{\delta_K,2}^{(\mathbf{S})}$ is the set of tuples for which we cannot decode successfully given a particular state $\mathbf{S} \in \mathcal{P}([\nu])^n$. Consequently, we have

$$|A_{\delta_K,2}| \leq \sum_{\mathbf{S} \in \mathcal{P}([\nu])^n} |A_{\delta_K,2}^{(\mathbf{S})}|. \quad (30)$$

For any state $\mathbf{S} \in \mathcal{P}([\nu])^n$, we require the probability of error, P_e , to be at most ϵ . Since all tuples in the set A_{δ_K} are equiprobable, we have

$$P_e = \frac{|A_{\delta_K,2}^{(\mathbf{S})}|}{|A_{\delta_K}|} \leq \epsilon. \quad (31)$$

Therefore, we have

$$\begin{aligned} |A_{\delta_K,1}| &= |A_{\delta_K}| - |A_{\delta_K,2}| \\ &\geq |A_{\delta_K}| - \sum_{\mathbf{S} \in \mathcal{P}([\nu])^n} |A_{\delta_K,2}^{(\mathbf{S})}| \\ &\geq |A_{\delta_K}| - \sum_{\mathbf{S} \in \mathcal{P}([\nu])^n} \epsilon |A_{\delta_K}| \\ &\geq |A_{\delta_K}|(1 - \epsilon 2^{\nu n}). \end{aligned} \quad (32)$$

Suppose that $(\mathbf{W}_1, \mathbf{W}_2) \in A_{\delta_K,1}$. Because of the decoding requirements, if \mathbf{W}_1 is available at all servers, the decoder must be able to obtain \mathbf{W}_1 and if \mathbf{W}_2 is available at all servers, the decoder must return \mathbf{W}_2 . Hence, as shown in [14], there exist $\mathbf{S}_1, \mathbf{S}_2 \in \mathcal{P}([\nu])^n$ such that

- \mathbf{S}_1 and \mathbf{S}_2 differ only in the state of one server indexed by $B \in [c]$, and
- \mathbf{W}_1 can be recovered from the first c servers in state \mathbf{S}_1 and \mathbf{W}_2 can be recovered from the first c servers in \mathbf{S}_2 .

Therefore both \mathbf{W}_1 and \mathbf{W}_2 are decodable from the c codeword symbols of the first c servers in state \mathbf{S}_1 , and the codeword symbol of the B -th server in state \mathbf{S}_2 . Thus, we require the following

$$\begin{aligned} c q^{c+1} &\geq |A_{\delta_K,1}| \\ &\geq |A_{\delta_K}|(1 - \epsilon 2^{\nu n}). \end{aligned} \quad (33)$$

We also have $|A_{\delta_K}| = 2^K \text{Vol}(\delta_K K, K)$. Therefore, the storage cost is lower-bounded as follows

$$\log q \geq \frac{K + \log \text{Vol}(\delta_K K, K)}{c + 1} + \frac{\log(1 - \epsilon 2^{\nu n}) - \log c}{c + 1}. \quad (34)$$

□

We now provide a proof sketch for the case where $\nu \geq 3$.

Proof sketch of Theorem 4 for $\nu \geq 3$. Consider any ϵ -error $(n, c, \nu, 2^K, q, \delta_K)$ multi-version code, and consider the first $c \leq n$ servers, $T = [c]$, for decoding. Suppose we have ν versions $\mathbf{W}_{[\nu]} = (\mathbf{W}_1, \mathbf{W}_2, \dots, \mathbf{W}_\nu)$. Suppose that $\mathbf{W}_{[\nu]} \in A_{\delta_K,1}$. We construct auxiliary variables $Y_{[c-1]}, Z_{[\nu]}, B_{[\nu]}$, where $Y_i, Z_j \in [q], i \in [c-1], j \in [\nu]$, $1 \leq B_1 \leq \dots \leq B_\nu \leq c$ and a permutation $\Pi : [\nu] \rightarrow [\nu]$, such that there is a bijection mapping from these variables to $A_{\delta_K,1}$. In order to construct these auxiliary variables, we use the algorithm of [14]. Therefore, we have

$$\begin{aligned} q^{c+\nu-1} \binom{c+\nu-1}{\nu} \nu! &\geq |A_{\delta_K,1}| \\ &> |A_{\delta_K}|(1 - \epsilon 2^{\nu n}), \end{aligned} \quad (35)$$

where the first inequality follows since $Y_i, Z_j \in [q]$, there are at most $\binom{c+\nu-1}{\nu}$ possibilities of $B_{[\nu]}$ and at most $\nu!$ possible permutations. We also have $|A_{\delta_K}| = 2^K \text{Vol}(\delta_K K, K)^{(\nu-1)}$. Therefore, the storage cost is lower-bounded as follows

$$\log q \geq \frac{K + (\nu - 1) \log \text{Vol}(\delta_K K, K)}{c + \nu - 1} + \frac{\log(1 - \epsilon 2^{\nu n}) - \log \binom{c+\nu-1}{\nu} \nu!}{c + \nu - 1}. \quad (36)$$

□

ACKNOWLEDGEMENT

The authors would like to thank A. Tulino and J. Llorca for their helpful comments.

V. CONCLUSION

In this paper, we have proposed multi-version codes to efficiently store correlated updates of data in a decentralized asynchronous storage system. These constructions are based on Reed-Solomon codes and random binning. An outcome of our results is that the correlation between versions can be used to reduce storage costs in asynchronous decentralized systems, even if there is no single server or client node who is aware of all data versions, in applications where consistency is important. In addition, our converse result shows that these constructions are within a factor of 2 from the information-theoretic optimum in certain interesting regimes. The development of practical coding schemes for the case where δ_K is known a priori is an open research question, which would require non-trivial generalizations of previous code constructions for the Slepian-Wolf problem [19], [20].

APPENDIX

In this appendix, we show that there exist *linear* codes that achieve the storage cost of Theorem 3. The proof uses linear binning instead of random binning, but mirrors the random binning proof in other respects and we focus on the key differences here.

Lemma 5. Let G be an $N \times M$ matrix whose entries are chosen according to Bernoulli(p) independently of each other. Let \mathbf{u} be any non-zero $N \times 1$ vector. We have

$$\mathbb{P}(\mathbf{u}^T G = 0) = ((1 + (1 - 2p)^{w_H(\mathbf{u})})/2)^M. \quad (37)$$

Proof. Consider k Bernoulli trials where the probability of success of each trial is p . It can be shown that an even number of successes among the k trials occurs with probability $(1 + (1 - 2p)^k)/2$. Therefore, we have $\mathbb{P}(\mathbf{u}^T G = 0) = ((1 + (1 - 2p)^{w_H(\mathbf{u})})/2)^M$. □

We next explain the code construction and provide an alternate proof for Theorem 3.

Construction 3 (Random Linear binning multi-version code). Suppose that the i -th server receives the versions $\mathbf{S}(i) = \{s_1, s_2, \dots, s_{|\mathbf{S}(i)|}\} \subseteq [\nu]$, where $s_1 < s_2 < \dots < s_{|\mathbf{S}(i)|}$.

- *Random code generation:* At the i -th server, for version s_j the encoder creates a random binary matrix $G_{s_j}^{(i)}$ with K rows and $(K + (\nu - 1) \log \text{Vol}(\delta_K K, K) + (\nu - 1) - \log \epsilon 2^{-\nu n})/c$

columns, where each entry is chosen as Bernoulli(1/2) independently of all the other entries in the matrix and all other matrices. We denote by $G_{s_j, m}^{(i)}$ the first m columns of $G_{s_j}^{(i)}$.

- *Encoding*: The server stores $\mathbf{W}_{s_j}^T G_{s_j, KR_{s_j}^{(i)}/c}^{(\ell)}$ for version s_j , where $R_{s_j}^{(i)}/c$ is the rate assigned by the i -th server to version s_j . The decoder is also aware of the matrix $G_{s_j}^{(i)}$ a priori. The encoding function of the i -th server is defined as follows

$$\varphi_S^{(i)} = (\mathbf{W}_{s_1}^T G_{s_1, KR_{s_1}^{(i)}/c}^{(i)}, \mathbf{W}_{s_2}^T G_{s_2, KR_{s_2}^{(i)}/c}^{(i)}, \dots, \mathbf{W}_{s_{|\mathbf{S}^{(i)}|}}^T G_{s_{|\mathbf{S}^{(i)}|}, KR_{s_{|\mathbf{S}^{(i)}|}}^{(i)}/c}^{(i)}), \quad (38)$$

where we choose the rates as given by (12), (13).

- *Decoding*: Consider a state $\mathbf{S} \in \mathcal{P}([\nu])^n$ and assume that the decoder connects to the servers $T = \{t_1, t_2, \dots, t_c\}$. Let \mathbf{W}_{u_L} be the latest common version among these servers and that the versions $\mathbf{W}_{u_1}, \mathbf{W}_{u_2}, \dots, \mathbf{W}_{u_{L-1}}$ are the older versions such that each is received by at least one server out of those c servers. This set of versions is denoted by \mathbf{S}_T and defined in (16). Given the bin indices $(b_{u_1}, b_{u_2}, \dots, b_{u_L})$, the decoder finds all tuples $(\mathbf{w}_{u_1}, \mathbf{w}_{u_2}, \dots, \mathbf{w}_{u_L}) \in A_{\delta_K}$ such that $(\varphi_{u_1}(\mathbf{w}_{u_1}) = b_{u_1}, \varphi_{u_2}(\mathbf{w}_{u_2}) = b_{u_2}, \dots, \varphi_{u_L}(\mathbf{w}_{u_L}) = b_{u_L})$. If all tuples have the same latest common version \mathbf{w}_{u_L} , the decoder declares \mathbf{w}_{u_L} to be the estimate of the latest common version $\hat{\mathbf{W}}_{u_L}$. Otherwise, the decoder declares an error.

Proof of Theorem 3 using linear binning. The probability of error in decoding the latest common version among the c servers is upper-bounded as follows

$$P_e(\mathbf{S}, T) = P(E) = P\left(\bigcup_{\mathcal{I} \subseteq \mathbf{S}_T: u_L \in \mathcal{I}} E_{\mathcal{I}}\right) \leq \sum_{\mathcal{I} \subseteq \mathbf{S}_T: u_L \in \mathcal{I}} P(E_{\mathcal{I}}),$$

and we require that $P_e(\mathbf{S}, T) \leq \epsilon 2^{-\nu n}$. We proceed in a case by case manner and first consider the case where $u_{L-1} \notin \mathcal{I}$, later we consider the case where $u_{L-1} \in \mathcal{I}$. For the case where $u_{L-1} \notin \mathcal{I}$, we have the following

$$E_{\mathcal{I}} \subset \tilde{E}_{u_{L-1}} := \{\exists \mathbf{w}'_{u_L} \neq \mathbf{w}_{u_L} : \mathbf{w}_{u_L}^T G_{u_L, KR_{u_L}^{(t_i)}/c}^{(t_i)} = \mathbf{w}'_{u_L}^T G_{u_L, KR_{u_L}^{(t_i)}/c}^{(t_i)}, \forall i \in [c] \text{ and } (\mathbf{W}_{u_{L-1}}, \mathbf{w}'_{u_L}) \in A_{\delta_K}\}. \quad (39)$$

Consequently, we have $P(E_{\mathcal{I}}) < P(\tilde{E}_{u_{L-1}})$, and we can upper-bound $P(\tilde{E}_{u_{L-1}})$ as follows

$$\begin{aligned} P(\tilde{E}_{u_{L-1}}) &= \sum_{(\mathbf{w}_{u_{L-1}}, \mathbf{w}_{u_L})} p(\mathbf{w}_{u_{L-1}}, \mathbf{w}_{u_L}) \\ &P\left(\exists \mathbf{w}'_{u_L} \neq \mathbf{w}_{u_L} : \mathbf{w}_{u_L}^T G_{u_L, KR_{u_L}^{(t_i)}/c}^{(t_i)} = \mathbf{w}'_{u_L}^T G_{u_L, KR_{u_L}^{(t_i)}/c}^{(t_i)}, \forall i \in [c], (\mathbf{w}_{u_{L-1}}, \mathbf{w}'_{u_L}) \in A_{\delta_K}\right) \\ &\stackrel{(a)}{\leq} \sum_{(\mathbf{w}_{u_{L-1}}, \mathbf{w}_{u_L})} p(\mathbf{w}_{u_{L-1}}, \mathbf{w}_{u_L}) \sum_{\substack{\mathbf{w}'_{u_L} \neq \mathbf{w}_{u_L} \\ (\mathbf{w}_{u_{L-1}}, \mathbf{w}'_{u_L}) \in A_{\delta_K}}} \prod_{i=1}^c P\left((\mathbf{w}'_{u_L} + \mathbf{w}_{u_L})^T G_{u_L, KR_{u_L}^{(t_i)}/c}^{(t_i)} = 0\right) \\ &\stackrel{(b)}{=} \sum_{(\mathbf{w}_{u_{L-1}}, \mathbf{w}_{u_L})} p(\mathbf{w}_{u_{L-1}}, \mathbf{w}_{u_L}) \text{Vol}((u_L - u_{L-1})\delta_K K, K) \prod_{i=1}^c 2^{-KR_{u_L}^{(t_i)}/c} \end{aligned} \quad (40)$$

$$= 2^{-(KR_{u_L} - \log \text{Vol}((u_L - u_{L-1})\delta_K K, K))}. \quad (41)$$

where (a) follows since the matrices $G^{(t_1)}, G^{(t_2)}, \dots, G^{(t_c)}$ are chosen independently and (b) follows from Lemma 5. Choosing R_{u_L} to satisfy $KR_{u_L} \geq \log \text{Vol}((u_L - u_{L-1})\delta_K K, K) + (L - 1) - \log \epsilon 2^{-\nu n}$ ensures that $P(E_{\mathcal{I}}) \leq \epsilon 2^{-(L-1)} 2^{-\nu n}$.

Now, we consider the case where $u_{L-1} \in \mathcal{I}$. In this case, we consider the following two cases. First, we consider the case where $u_{L-2} \notin \mathcal{I}$, later we consider the case where $u_{L-2} \in \mathcal{I}$. For the case where $u_{L-2} \notin \mathcal{I}$, we have

$$E_{\mathcal{I}} \subseteq \tilde{E}_{u_{L-2}} := \{\exists \mathbf{w}'_{u_{L-1}} \neq \mathbf{W}_{u_{L-1}}, \mathbf{w}'_{u_L} \neq \mathbf{W}_{u_L} : \mathbf{w}_{u_{L-1}}'^T G_{u_{L-1}, KR_{u_{L-1}}/c}^{(t_i)} = \mathbf{W}_{u_{L-1}}^T G_{u_{L-1}, KR_{u_{L-1}}/c}^{(t_i)}, \\ \mathbf{w}_{u_L}'^T G_{u_L, KR_{u_L}/c}^{(t_i)} = \mathbf{W}_{u_L}^T G_{u_L, KR_{u_L}/c}^{(t_i)} \text{ and } (\mathbf{W}_{u_{L-2}}, \mathbf{w}'_{u_{L-1}}, \mathbf{w}'_{u_L}) \in A_{\delta_K}\}. \quad (42)$$

In this case, we choose the rates to satisfy $K(R_{u_{L-1}} + R_{u_L}) \geq \sum_{j=L-1}^L \log \text{Vol}((u_j - u_{j-1})\delta_K K, K) + (L - 1) - \log \epsilon 2^{-\nu n}$. By applying the above argument repeatedly, we obtain the region in (26). \square

REFERENCES

- [1] R. E. Ali and V. R. Cadambe, “Consistent distributed storage of correlated data updates via multi-version coding,” in *Information Theory Workshop (ITW), 2016, IEEE*, pp. 176–180.
- [2] G. DeCandia, D. Hastorun, M. Jampani, G. Kakulapati, A. Lakshman, A. Pilchin, S. Sivasubramanian, P. Voshall, and W. Vogels, “Dynamo: Amazon’s highly available key-value store,” in *SOSP*, vol. 7, 2007, pp. 205–220.
- [3] J. C. Corbett *et al.*, “Spanner: Googles globally distributed database,” *ACM Transactions on Computer Systems (TOCS)*, vol. 31, no. 3, p. 8, 2013.
- [4] E. Hewitt, *Cassandra: the definitive guide*. O’Reilly Media, Inc., 2010.
- [5] K. Rashmi, M. Chowdhury, J. Kosaian, I. Stoica, and K. Ramchandran, “Ec-cache: Load-balanced, low-latency cluster caching with online erasure coding,” in *OSDI*, 2016, pp. 401–417.
- [6] K. Taranov, G. Alonso, and T. Hoefler, “Fast and strongly-consistent per-item resilience in key-value stores,” in *Proceedings of the Thirteenth EuroSys Conference*. ACM, 2018, p. 39.
- [7] Y. L. Chen, S. Mu, J. Li, C. Huang, J. Li, A. Ogus, and D. Phillips, “Giza: Erasure coding objects across global data centers,” in *Proc. USENIX Annu. Tech. Conf.(USENIX ATC)*, 2017.
- [8] R. J. Morris, “System and method for reducing storage requirement in backup subsystems utilizing segmented compression and differencing,” Sep. 22 1998, uS Patent 5,813,017.
- [9] N. A. Lynch, *Distributed Algorithms*. San Francisco, CA, USA: Morgan Kaufmann Publishers Inc., 1996.
- [10] A. G. Dimakis, P. B. Godfrey, Y. Wu, M. J. Wainwright, and K. Ramchandran, “Network coding for distributed storage systems,” *IEEE Transactions on Information Theory*, vol. 56, no. 9, pp. 4539–4551, 2010.
- [11] I. Tamo and A. Barg, “A family of optimal locally recoverable codes,” *IEEE Transactions on Information Theory*, vol. 60, no. 8, pp. 4661–4676, 2014.
- [12] V. R. Cadambe, N. Lynch, M. Medard, and P. Musial, “A coded shared atomic memory algorithm for message passing architectures,” in *2014 IEEE International Symposium on Network Computing and Applications*. IEEE, pp. 253–260.
- [13] P. Dutta, R. Guerraoui, and R. R. Levy, “Optimistic erasure-coded distributed storage,” in *Distributed Computing*. Springer, 2008, pp. 182–196.
- [14] Z. Wang and V. R. Cadambe, “Multi-version coding—an information-theoretic perspective of consistent distributed storage,” *IEEE Transactions on Information Theory*, vol. 64, no. 6, pp. 4540–4561, June 2018.
- [15] M. Zorghi, R. Mateescu, F. Blagojevic, C. Guyot, and Z. Wang, “Storage-efficient shared memory emulation,” *arXiv preprint arXiv:1803.01098*, 2018.
- [16] V. R. Cadambe, Z. Wang, and N. Lynch, “Information-theoretic lower bounds on the storage cost of shared memory emulation,” in *Proceedings of the ninth annual ACM symposium on Principles of distributed computing*, ser. PODC ’16. ACM, 2016, pp. 305–314.

- [17] D. Slepian and J. K. Wolf, "Noiseless coding of correlated information sources," *IEEE Transactions on Information theory*, vol. 19, no. 4, pp. 471–480, 1973.
- [18] A. Wyner, "Recent results in the shannon theory," *IEEE Transactions on information Theory*, vol. 20, no. 1, pp. 2–10, 1974.
- [19] S. S. Pradhan and K. Ramchandran, "Distributed source coding using syndromes (discus): Design and construction," *IEEE Transactions on Information Theory*, vol. 49, no. 3, pp. 626–643, 2003.
- [20] D. Schonberg, K. Ramchandran, and S. S. Pradhan, "Distributed code constructions for the entire slepian-wolf rate region for arbitrarily correlated sources," in *Data Compression Conference Proceedings (DCC)*, IEEE, 2004, pp. 292–301.
- [21] D. H. Schonberg, *Practical distributed source coding and its application to the compression of encrypted data*. University of California, Berkeley, 2007.
- [22] Q. Wang, V. Cadambe, S. Jaggi, M. Schwartz, and M. Médard, "File updates under random/arbitrary insertions and deletions," in *IEEE Information Theory Workshop (ITW)*, 2015, pp. 1–5.
- [23] N. Ma, K. Ramchandran, and D. Tse, "A compression algorithm using mis-aligned side-information," in *IEEE International Symposium on Information Theory Proceedings (ISIT)*, 2012, pp. 16–20.
- [24] J. Harshan, F. Oggier, and A. Datta, "Sparsity exploiting erasure coding for resilient storage and efficient I/O access in delta based versioning systems," *IEEE 35th International Conference on Distributed Computing Systems*, 2015, pp. 798–799.
- [25] S. El Rouayheb, S. Goparaju, H. M. Kiah, and O. Milenkovic, "Synchronization and deduplication in coded distributed storage networks," *IEEE/ACM Transactions on Networking*, vol. 24, no. 5, pp. 3056–3069, 2016.
- [26] N. P. Anthapadmanabhan, E. Soljanin, and S. Vishwanath, "Update-efficient codes for erasure correction," in *Allerton Conference on Communication, Control, and Computing*, 2010. IEEE, pp. 376–382.
- [27] A. Mazumdar, V. Chandar, and G. W. Wornell, "Update-efficiency and local repairability limits for capacity approaching codes," *IEEE Journal on Selected Areas in Communications*, vol. 32, no. 5, pp. 976–988, 2014.
- [28] P. Nakkiran, N. B. Shah, and K. Rashmi, "Fundamental limits on communication for oblivious updates in storage networks," in *Global Communications Conference (GLOBECOM)*, 2014, IEEE, pp. 2363–2368.
- [29] N. Prakash and M. Médard, "Communication cost for updating linear functions when message updates are sparse: Connections to maximally recoverable codes," *IEEE Transactions on Information Theory*, 2018.
- [30] P. Hassanzadeh, A. M. Tulino, J. Llorca, and E. Erkip, "On coding for cache-aided delivery of dynamic correlated content," *IEEE Journal on Selected Areas in Communications*, 2018.
- [31] T. M. Cover and J. A. Thomas, *Elements of information theory*. John Wiley & Sons, 2012.
- [32] H. Attiya, A. Bar-Noy, and D. Dolev, "Sharing memory robustly in message-passing systems," *J. ACM*, vol. 42, no. 1, pp. 124–142, Jan. 1995.
- [33] L. Lamport, "Time, clocks, and the ordering of events in a distributed system," *Communications of the ACM*, vol. 21, no. 7, pp. 558–565, 1978.
- [34] Y. L. Chen, S. Mu, J. Li, C. Huang, J. Li, A. Ogus, and D. Phillips, "Giza: Erasure coding objects across global data centers," in *Proc. USENIX Annu. Tech. Conf.(USENIX ATC)*, 2017.
- [35] J. K. Wolf, "Data reduction for multiple correlated sources," in *Proc. 5th Colloquium Microwave Communication*, 1973, pp. 287–295.
- [36] R. Ahlswede and J. Körner, "Source coding with side information and a converse for degraded broadcast channels," *IEEE Transactions on Information Theory*, vol. 21, no. 6, pp. 629–637, 1975.
- [37] A. Wyner, "On source coding with side information at the decoder," *IEEE Transactions on Information Theory*, vol. 21, no. 3, pp. 294–300, 1975.
- [38] T. Cover, "A proof of the data compression theorem of slepian and wolf for ergodic sources (corresp.)," *IEEE Transactions on Information Theory*, vol. 21, no. 2, pp. 226–228, 1975.
- [39] A. El Gamal and Y.-H. Kim, *Network information theory*. Cambridge university press, 2011.
- [40] B. Bandemer, A. El Gamal, and Y.-H. Kim, "Simultaneous nonunique decoding is rate-optimal," in *Communication, Control, and Computing (Allerton)*, 2012 50th Annual Allerton Conference on. IEEE, 2012, pp. 9–16.
- [41] S. S. Bidokhti and V. M. Prabhakaran, "Is non-unique decoding necessary?" *IEEE Transactions on Information Theory*, vol. 60, no. 5, pp. 2594–2610, 2014.
- [42] M. Langberg and M. Effros, "Network coding: Is zero error always possible?" in *2011 49th Annual Allerton Conference on Communication, Control, and Computing (Allerton)*. IEEE, 2011, pp. 1478–1485.
- [43] J. Körner, "Coding of an information source having ambiguous alphabet and the entropy of graphs," in *6th Prague conference on information theory*, 1973, pp. 411–425.