Making 3D Movies of Northern Lights

Eric Hivon¹, Jean Mouette¹, Thierry Legault^{2,3}

¹ Sorbonne Universités, UPMC Univ. Paris 6 & CNRS (UMR7095): Institut d'Astrophysique de Paris, 98bis Bd Arago, F-75014, Paris, France

² Astrophotography (http://www.astrophoto.fr)

³ THALES, 19 Avenue Morane Saulnier, F-78140 Vélizy Villacoublay, France

Received 4 June 2017 / Accepted 16 August 2017

ABSTRACT

We describe the steps necessary to create three-dimensional (3D) movies of Northern Lights or Aurorae Borealis out of real-time images taken with two distant high-resolution fish-eye cameras. Astrometric reconstruction of the visible stars is used to model the optical mapping of each camera and correct for it in order to properly align the two sets of images. Examples of the resulting movies can be seen at http://www.iap.fr/aurora3d.

Key words. Aurora / visualisation / technical / image processing / algorithm

1. Introduction

Aurorae borealis have always fascinated humans, who have long tried to report their observations by the best means available at the time. If the earliest known record of an Aurora was written on a clay tablet 567BC in Babylon (Stephenson et al., 2004), they have since been filmed in color with specially designed high sensitivity cameras¹ in the mid-1980s (Hallinan et al., 1985), and filmed in 3D for the first time in 2008².

In this paper we detail the steps taken to generate 3D movies Aurorae Borealis shot with high resolution wide field cameras, generating movies fit for projection on hemispheric planetariums. To our knowledge, these 3D movies are the first ones showing Northern Lights ever produced thanks to post-shooting astrometric reconstruction. Since they are produced from realtime movie images instead of the usual time-lapsed sequences, they can be used for education and public outreach and give a glimpse at the rich and rapidly moving three-dimensional structure of the Auroras. While they are close to the real-world sensations of Aurora watching in terms of colors, saturation, speed of evolution, and sheer size on the sky (if seen in a planetarium), such movies add the extra information of the stereoscopy, which is inaccessible to a single human observer on the field. Now that such movies are made available, they will hopefully prompt the interest of scientists studying the Aurorae properties, who would like to use them, or build upon them, in their work.

The image taking procedure and camera synchronisation is described in Sect. 2. The image processing steps allowing a good rendition of the stereoscopy is described in Sect. 3, while Sect. 4 shows how such 3D images and movies can be viewed. Section 5 is devoted to a conclusion and perspectives.

2. Observational setup

Observations are made from Norway at the approximate latitudes and longitudes of 69.3°N and 20.3°E, with two cameras separated by either 6 or 9km, depending on the local weather conditions. Since the Aurorae mostly happen in the upper atmosphere at ~ 100km above the ground, their parallax is expected to be large enough between the two cameras to construct their 3D rendering via binocular vision. As much as possible, the cameras point to the zenith, and are then rotated around the vertical so that the Northern Star is in the lower part of the image, aligning the long axis of the image with the West-East direction, as shown in Fig. 1 for one of the cameras. Their positions are measured by GPS receivers. In what follows, the western and eastern cameras are respectively dubbed *left* and *right*.

2.1. The cameras

Each of the two cameras used is a Sony α 7s, on which is mounted a Canon Fisheye lens of focal length f=15mm with an aperture of f/2.8. In order to further enlarge the field of view, and allow the use of a Canon lens on the Sony E-mount camera, it is coupled to a Metabones Speed Booster that reduces the focal length by a factor of 0.71. The camera sensor is a full-frame CMOS

Send offprint requests to: hivon@iap.fr

http://auroraalive.com/multimedia/autoformat/get_ swf.php?videoSite=aurora&videoFile=aa_aurora_on_tv. swf++&videoTitle=Aurora+on+TV

² https://www.newscientist.com/article/dn15147-

northern-lights-captured-in-3d-for-the-first-time/

4240x2832 pixel RGBG Bayer matrix³, with half of the pixels being sensitive to green and the other half spread evenly between red and blue. ISO is set to 12800, representing a good compromise between noise and sensitivity. A video signal is produced at 25 or 30 frames per second (fps), in Ultra High Definition format (3840x2160 pixels, ratio 16:9), and recorded on an external video recorder, with Apple ProRes HQ codec (approximately 800 Mbits/sec). As we will see in Sect. 3, the field of view is 220°x110°, covering 48% of the sphere, with a resolution at the center of the image of 2.94'/pixel.

2.2. Cameras synchronization

In order to achieve a good stereoscopy out of the movies produced, we first have to make sure that their images are properly synchronized during their processing and visualisation. Keeping, on the field, the two distant cameras and/or their recorders synchronized thanks to a common absolute GPS-based time signal would have been ideal, but out of reach of this project. Instead, to achieve a good relative synchronization of the two movies, we first made sure that the internal clocks of the two recorders agreed to one second or less before starting every observing nights; we then flashed a light in front of the two cameras put side by side and connected to their turned-on recorder before setting up the cameras at their respective distant location. This gives us a good estimate of the offset and possible drift in time between the internal clocks of the two recorders as they write a time-code in the images metadata. Finally, in post-production, but before starting the 3D reconstruction pipeline, we look in the filmed sequences for the occurence of bright, thin and fast moving Auroras structures, and compare closely their evolution from frame to frame between the two cameras, in order to find the best matching pair of frames. This provides the residual time offset between the two series of recorded time-stamps, and allows us to re-synchronize the two movies at a level compatible with the image rate (25 or 30 fps), assuming the relative time drift to be negligible over the duration of a sequence (a few minutes).

3. Image processing

Time-lapsed stereoscopic observations of aurorae are described for wide field cameras in Kataoka et al. (2013), and for fast narrow field cameras in Kataoka et al. (2016), following in either cases the procedure described in Mori et al. (2013). We are implementing a similar astrometric method: since the actual pointing, orientation and relative position of the two cameras are only known with limited accuracy, and because each camera can distord the image differently, the positional astrometry of bright stars identified in the images is used to determine and characterize the cameras geometrical settings and optical responses, in order to properly realign the *left* and *right* set of images.



Fig. 1. The observation is done from colatitude θ_0 and longitude ϕ_0 , in the Earth-bound *xyz* referential. A camera-bound referential is defined, with the Z axis along the camera boresight (roughly towards the zenith), the Y axis along the shorter dimension of the camera image, approximately pointing North, and the X axis along the longer dimension of the camera image, pointing East

3.1. Finding the stars

The 5th edition of the Kitt Peak National Observatory (KNPO) catalog⁴, adapted from the Yale catalog⁵, lists the J2000 equatorial coordinates and magnitude of more than 9000 stars of magnitude ≤ 6.5 . After setting correctly the minus sign on the magnitude of its four brightest stars, it was used as a catalog of bright stars potentially seen in the *left* and *right* images.

Candidate stars in the images are identified as follows. Since the Aurorae filmed here are mostly green in color, a red channel frame is expected to be less exposed to them than the other channels, and is used to detect stars. We checked that using the green channel, expected to have a better intrisic resolution, did not change much the final result, while it increased slightly the risk of false detection. The chosen image is convolved (via Fast Fourier Transform operations) with a difference of Gaussians (DoG) filter, defined in pixel space as

$$F(x,y) = \frac{\exp\left(-\frac{x^2 + y^2}{2\sigma_1^2}\right)}{2\pi\sigma_1^2} - \frac{\exp\left(-\frac{x^2 + y^2}{2\sigma_2^2}\right)}{2\pi\sigma_2^2}$$
(1)

where x, y are integer pixel indices, $\sigma_1 = 1$ and $\sigma_2 = 1.6$, and one then looks for local maxima in the filtered image. The value of $\sigma_2/\sigma_1 = 1.6$ picked here is generally recommended as a good approximation of the Mexican hat or Marr wavelet (Marr and

³ http://www.imaging-resource.com/PRODS/sonya7s/sony-a7sDAT.HTM

⁴ http://www-kpno.kpno.noao.edu/Info/Caches/Catalogs/ BSC5/catalog5.html

⁵ http://tdc-www.harvard.edu/catalogs/bsc5.html

Hildreth, 1980), often used to look for point sources in astrophysics (Coupinot et al., 1992), but values as large as $\sigma_2/\sigma_1 = 3$ gave almost identical results.

For practical reasons, we keep our cameras in focus during the totally of the shooting sequences. As a consequence, the Airy diameter of the optical system (~ 3μ m) is smaller than the pixels physical size of the CMOS sensor ($8.40\mu m$), and the observed stars generally won't be resolved. We tried three different techniques to determine the position of a star on the frame: (a) that of the locally brightest pixel of the DoG filtered map, or the centroid of the filtered map on a (b) 3x3 or (c) 5x5 patch of pixels centered on that same brightest pixel. For reasons that will detailled in Sect. 3.3, the option (b) which provides sub-pixel accuracy was preferred. Since it is difficult to estimate exactly the error made on determining the star position, especially since we start from a (red) image interpolated with proprietary algorithms from the RGBG detector matrix, we will simply assume the error in position in (b) to be the same as in the discretization scheme (a) and determined by the nominal pixel size of the image, as described in Sect. **B**. Note that over-estimating by a factor 10 the error bar on each star position won't change the numerical value of any parameter in the multi-dimensional fit being done, it will only increase by a factor 10 the error bar associated to each parameter.

The $N_b \simeq 40$ brightest sources found by this procedure are compared to the $N_s \simeq 40$ brightest stars in the Northern hemisphere, as listed in the input catalog described above.

3.2. Modeling the projection

3.2.1. 3D rotation of the sky

At a time t, a star (j) having the colatitude⁶ and longitude $(\delta_E^{(j)}, \alpha_E^{(j)})$ in Equatorial coordinates, will have the angular coordinates $(\delta_c^{(j)}, \alpha_c^{(j)})$ in a camera-bound referential, such as the one illustrated in Fig. 1, so that the respective 3D coordinate vectors are

$$\mathbf{r}_{i}^{(j)} \equiv \begin{pmatrix} x_{i}^{(j)} \\ y_{i}^{(j)} \\ z_{i}^{(j)} \end{pmatrix} = \begin{pmatrix} \sin \delta_{i}^{(j)} \cos \alpha_{i}^{(j)} \\ \sin \delta_{i}^{(j)} \sin \alpha_{i}^{(j)} \\ \cos \delta_{i}^{(j)} \end{pmatrix},$$
(2a)

for i = E or c. This change of coordinates is a rotation parameterized by the three (time dependent) Euler angles ψ, θ, φ

$$\mathbf{r}_{c}^{(j)} = \mathbf{R}(\psi, \theta, \varphi) \, \mathbf{r}_{E}^{(j)}, \tag{2b}$$

with

$$\mathbf{R}(\psi,\theta,\varphi) \equiv$$

$$\begin{pmatrix} \cos\psi & -\sin\psi & 0\\ \sin\psi & \cos\psi & 0\\ 0 & 0 & 1 \end{pmatrix} \cdot \begin{pmatrix} \cos\theta & 0 & \sin\theta\\ 0 & 1 & 0\\ -\sin\theta & 0 & \cos\theta \end{pmatrix} \cdot \begin{pmatrix} \cos\varphi & -\sin\varphi & 0\\ \sin\varphi & \cos\varphi & 0\\ 0 & 0 & 1 \end{pmatrix}.$$
(2c)

The solid-body rotation of the sky described in Eq. (2) is an approximation that ignores subtle distortions like the atmospheric

refraction, which will be discussed later on, or the relativistic aberration due to the yearly Earth motion around the Sun. The latter is fairly small, with an apparent displacement of the source varying between 0 and ~ 20.5" across the sky, and will affect almost identically the two cameras since they observe the same area of the sky. It should therefore not affect the relative alignment of the images provided by the two cameras. For a camera located at a time *t* at the Earth-bound colatitude θ_0 and longitude ϕ_0 , pointing exactly to the zenith and rotated by ψ_0 around the vertical (with $\psi_0 = 0$ in the current configuration), then, ignoring the Earth nutation,

$$\psi = -90 - \psi_0, \tag{3a}$$

$$\theta = -\theta_0, \tag{3b}$$

$$\varphi = -(\varphi_0 + 15 S(t) \mod 360),$$
 (3c)

where S(t) is the Greenwich Mean Sidereal Time of observation, expressed in hours, which parameterizes the rotation of the Earth with respect to the distant stars:

$$S(t) = 18.697374558 + 24.06570982441933 (J(t) - J_{2000})$$
(4)

with J(t) the Julian day of observation and $J_{2000} = 2451545$ is the Julian day starting at 12:00:00 UTC on Jan 1, 2000 (Meeus, 1991). However, as noted previously, the limited accuracy on the actual shooting time, position and orientation of the cameras will impact these parameters. The values recovered for (ψ, θ, φ) , as described in Sect. 3.3, are well within 1° of those expected from Eq. (3), with the larger discrepancy affecting the harder to set-up azimuthal angle ψ .

3.2.2. Radial distortion of the optics

A source located at an angular distance δ_c of the camera boresight will appear on the imaging CMOS sensor at a distance *r* of the focal point, as illustrated in Fig. 2 and we model this distance as

$$r^{(j)} = f_1 r_{ES}(\delta_c^{(j)}) + f_a r_{ES}^a(\delta_c^{(j)}) + f_b r_{ES}^b(\delta_c^{(j)}),$$
(5a)

where

$$r_{ES}(\delta_c) \equiv 2\sin(\delta_c/2),$$
 (5b)

is the Equisolid radius *ideally* expected for the fisheye and reducer lenses being used, f_1 is the combined focal length of the fisheye and focal reducer, and f_a and f_b model any non-linear departure from the expected projection, for the integer numbers aand b. We found the combination (a, b) = (3, 5) to be slightly better than (2, 3), by requiring smaller amplitude of the corrections ie, $f_3/f_1 \approx -0.008$ and $f_5/f_1 \approx 0.004$, instead of $f_2/f_1 \approx -0.02$ and $f_3/f_1 \approx 0.01$, in the range probed by the stars ($\delta_c < 90^\circ$ and $r_{ES} < 1.41$), and by returning slightly smaller residual in the comparison of the model with the observations.

Since the optics is pointing toward the zenith, these nonlinear terms can result from both radial non-idealities of the optics and, as suggested by Mori et al. (2013), the atmospheric refraction of the incoming light, which increases with the camerabound colatitude of the source. However, as shown in Sect. A and in Fig. 2, atmospheric refraction is too small in amplitude to explain the distortions seen, since we would then get $f_3/f_1 = 2f_5/f_1 \simeq -8.24 \, 10^{-5}$.

⁶ In what follows, and unless stated otherwise, the angles will be expressed in degrees; and we will prefer the colatitude δ measured southward from the North pole to the usual latitude δ' measured northward from the equator, the two being related by $\delta + \delta' = 90^{\circ}$.



Fig. 2. Radial mapping of the camera, relating the camera-bound colatitude δ_c of a sky object, and its projected radial distance *r* on the camera image, measured in pixels. In the case of stars (red diamonds) the measured radial distance comes with the discretization error bar of size $\pm 1/\sqrt{12} \approx \pm 0.2887$ (see Sect. B) more visible on the lower panel. The black dots show a simple equidistant mapping $r \propto \delta_c$. The magenta dashes show the equisolid projection of Eq. (5b) expected for the fisheye and focal reducer lenses used here; the green solid line show the best fit distorted radial model of Eq. (5a); while the blue dotted-dashed line illustrate the impact of atmospheric refraction on observations with a perfect equisolid optical system (see Sect. A). The upper panel shows the raw radial distance *r*, while the lower panel shows the difference between *r* and the equisolid model.

3.2.3. 2D offset of the camera sensor

Finally, the geometric center of the camera sensor, identified as (x, y) = (0, 0) may not match exactly the optics focal point, and we allow for the shifts Δ_x , Δ_y , so that a source *j* will appear on the sensor at the location

$$x^{(j)} = r^{(j)} \cos \alpha_c^{(j)} + \Delta_x, \tag{6a}$$

$$y^{(j)} = r^{(j)} \sin \alpha_c^{(j)} + \Delta_y,$$
 (6b)

measured in units of pixels, from the nominal CMOS sensor center. As listed in Table 1, we find these shifts to be respectively $|\Delta_x| \sim 20$ and $|\Delta_y| \sim 5$ pixels, depending on the camera considered, and the conditions of observation.

3.3. Fitting the parameters

Combining Eqs. (2), (5) and (6), the position of a star on the camera sensor is related to its Equatorial coordinates via

$$\begin{pmatrix} x^{(j)} \\ y^{(j)} \end{pmatrix} = D\left(\psi, \theta, \varphi, f_1, f_a, f_b, \Delta_x, \Delta_y; \begin{pmatrix} \delta_E^{(j)} \\ \alpha_E^{(j)} \end{pmatrix} \right), \tag{7}$$

where the eight parameters $(\psi, \theta, \varphi, f_1, f_a, f_b, \Delta_x, \Delta_y)$ are assumed unrelated between the two cameras.

In order to determine these parameters for a camera, we begin by setting the angles (ψ, θ, φ) to the values given in Eq. (3), and letting all the other parameters to 0, except for f_1 which is set to the nominal focal length of the optical system. Applying Eq. (7) to the N_s brightest stars of the catalog, we find that for each of a handful of them (N_m) , the computed location is within a few pixels of a bright source identified on the image. Assuming the star

E. Hivon, J. Mouette & T. Legault: Making 3D Movies of Northern Lights

Camera	N _m	f_1	$1000f_3/f_1$	$1000f_5/f_1$	Δ_x	Δ_{v}	mean discr.	max discr.
& run		[mm]			[pixels]	[pixels]	[pixels]	[pixels]
L1	22	9.811 ± 0.003	-6.1 ± 0.5	3.8 ± 0.3	-17.7 ± 0.5	6.0 ± 0.4	0.30	0.71
L2	28	9.815 ± 0.003	-7.0 ± 0.4	4.4 ± 0.2	-19.8 ± 0.4	-0.1 ± 0.4	0.29	0.68
L3	27	9.817 ± 0.003	-7.4 ± 0.4	4.5 ± 0.2	-19.0 ± 0.4	-0.0 ± 0.4	0.34	0.66
L4	25	9.819 ± 0.003	-8.2 ± 0.4	5.0 ± 0.3	-21.2 ± 0.4	0.3 ± 0.4	0.31	0.58
L5	22	9.818 ± 0.003	-6.6 ± 0.5	4.0 ± 0.3	-7.7 ± 0.5	2.0 ± 0.3	0.41	1.07
L6	23	9.859 ± 0.004	-5.6 ± 0.6	3.0 ± 0.4	-10.2 ± 0.4	4.3 ± 0.3	0.33	0.98
R1	23	9.890 ± 0.003	-5.8 ± 0.5	3.8 ± 0.3	14.0 ± 0.5	5.0 ± 0.4	0.21	0.42
R2	25	9.891 ± 0.003	-5.3 ± 0.5	2.9 ± 0.3	13.9 ± 0.4	5.3 ± 0.5	0.26	0.58
R3	23	9.893 ± 0.003	-6.7 ± 0.4	4.3 ± 0.3	14.1 ± 0.5	4.8 ± 0.5	0.22	0.44
R4	23	9.885 ± 0.004	-3.7 ± 0.6	1.9 ± 0.5	14.2 ± 0.4	4.9 ± 0.5	0.26	0.55
R5	25	9.897 ± 0.003	-8.3 ± 0.4	5.6 ± 0.2	8.1 ± 0.5	0.4 ± 0.3	0.28	0.53
R6	22	9.888 ± 0.004	-5.3 ± 0.6	3.4 ± 0.3	20.5 ± 0.4	8.8 ± 0.3	0.33	0.85

Table 1. Parameters of the camera response, for frames taken from six different shooting sequences with the *left* (rows L1 to L6) and *right* (rows R1 to R6) cameras. All runs were shot on consecutive nights, except for #2 to 4 which were produced on the same night, and #6 obtained four months later. Figures 2 and 3 correspond to row R2. The focal length f_1 was converted from pixels to mm assuming a pixel size of 8.40 μ m. The errors quoted on the parameters $f_1, f_3, f_5, \Delta_x, \Delta_y$ are those returned by the non-linear fitting procedure, based on the assumed discretization error on star location. The two rightmost columns show the mean and maximum discrepancy between the measured and modelled positions of the N_m stars found in the frame.

and the close bright pixel to be the same object, we then look for the set of parameters that minimize the $2N_m$ discrepancies in (x, y) coordinates. To do this non-linear fitting, we tried and compared two different IDL implementations of the Levenberg-Marquardt algorithm (Marquardt, 1963; Press et al., 1992): the curvefit⁷ routine included in the standard IDL library, and its drop-in replacement mpcurvefit⁸ by Markwardt (2009) based on the MINPACK algorithm of Moré (1978). We found the best fit parameter values to be nearly identical, but only the latter routine returned meaningful error bars on those parameters. Injecting these new parameters in Eq. (7), the number of coincidences N_m is increased, and we again look for a new estimate of the parameters minimizing the $2N_m$ discrepancies. The process is repeated a few times, rapidly converging toward a stable number of matches $(22 \le N_m \le 28$ depending on the image being treated), and providing a stable set of fitted parameters.

Figure 3 compares the measured position of the bright sources and the computed position of their matching stars in the best fit model of the camera response, for one specific image. Their discrepancies, shown as magenta arrows (after multiplication by 200) seem fairly randomly distributed and do not exhibit any clear trend. The residual distances have a mean value of 0.29 (in pixel units), with a worst case of 0.68. The mean residual found is compatible with the error created by assigning an integer value to the star coordinate in the image, which is ≈ 0.3826 , as shown in Sect. B.

As shown in Table 1, the same reconstruction procedure was applied, for each of the two cameras, on images extracted from six different shooting sequences, filmed on four different nights spread over a four month period. The optics related parameters $(f_1, f_3, f_5, \Delta_x, \Delta_y)$ and the level of residual discrepancies in position, were found to be quite stable for each camera, with the largest relative changes affecting Δ_x, Δ_y when the lenses were un-

mounted and remounted between observations performed on different nights. The relatively large changes of f_3 and f_5 between runs may be due to a partial (anti-)correlation between these two parameters, which also shows on the fact that the combination $f_3 + f_5$ varies less between runs than either f_3 or f_5 . However, this degeneracy does not hamper the modelling of Eq. (7) as long as f_3 and f_5 are treated together, and not considered separately. This suggests however that any more sophisticated modelling of the optical response, and in particular of the radial distortion, would require either the use of a basis of orthogonal polynomials, or a physically motivated set of parameters.

In each case, the mean residual error in position is compatible or below what is expected from quantization error of the star coordinates (0.3826 pixels), and we note that the *right* camera seems to perform a bit better than the *left* one on this respect. This may be due to the slightly lesser sharpness of the images produced by the *right* camera, maybe due to its optics, which by bluring lightly the stars makes the sub-pixel determination of their position easier.

As mentioned in Sect. 3.1, different options were considered to determine the stars position on the camera frame. Using the centroid on a 5x5 patch (so-called option (c)) instead of 3x3 used here made no significant difference on the parameter values and did not improve the residual discrepancies compared to those listed in Table 1. As expected, using instead a discrete pixel location (option (*a*)) lead to different parameter values, with a shift compatible with the quoted error bars, and larger mean and worst case discrepancies (by ~30% and ~20% respectively). However, for the 12 images tested, the sky to pixel mappings of Eq. (7) resulting from options (*a*) and (*b*) respectively differed by quite less than one pixel in the region of interest, ie, everywhere above the horizon, making the resulting processed images and movies of Auroras nearly indistinguishable.

The 8-parameter mapping model considered here therefore seems to generate smaller reconstruction errors than the 6parameter model considered in Mori et al. (2013), which ig-

⁷ https://harrisgeospatial.com/docs/CURVEFIT.html

⁸ http://purl.com/net/mpfit



Fig. 3. Comparison of the bright sources location and the position computed with the optical model, for one frame of one of the cameras. The bright pixels detected in the camera image are shown as black circles, while the expected position of the associated stars, computed by Eq. (7) with the eight camera parameters obtained in Sect. 3.3, are shown as red stars. The residual discrepancies between the two, *multiplied by 200*, are shown as magenta arrows. The thick black dots outline the approximate landscape horizon on the image; the black cross close to the image center shows the optics focal point; and the cyan lines represent the Equatorial graticule, with a spacing of 10° in (Equatorial) colatitude and 45° in longitude. The Northern Star is marked NS, while the "dipper" part of *Ursa Major*, in the North-East quadrant, is outlined in grey.

nores the non-linear radial distortions (f_a and f_b). On the other hand, in the framework of meteors and transient objects detection, Borovička et al. (1995) proposed a model containing 13 (12 independent) parameters for the modelling of all sky cameras equiped with photographic plates featuring a measurement uncertainty of ~1 arcmin. With hour-long exposures and ~100 stars for calibration, they reached a residual modelling error of ~1 arcmin too. We did not investigate how such a model would have performed in our case. Even though adding more parameters is not problematic in itself for the non-linear fitting procedure, it may lead to further degeneracies between parameters, unless they are carefuly designed to be orthogonal, especially if the number of constraints (here, the identified stars) is not large enough to correctly probe each of them. Moreover, inspection of Figs. 2 and 3 does not suggest the need for more degrees of freedom.

3.4. Aligning the images

Once the parameters are determined for each of the *left* and *right* images, with respect to the absolute Equatorial coordinates, one can map the two images (or set of images) onto a common projection of our choice, so that the stars match exactly for the *left* and *right* "eyes", while the structures of the aurorae will be offset

according to their parallax. We chose for instance, for flat screen viewing, and for Figs. 4 and 5, to deproject the *right* image by inverting Eq. (7) for the *right* camera parameters, and projected it again by applying that same equation with the *left* camera parameters. Other choices are possible, such as mappinng the two images onto a common equidistant projection, as required by the Dome Master format⁹ used in planetariums.

Apart from the angle φ , which includes the apparent motion of the sky due to Earth rotation, the parameters are not expected to vary during the typical duration of a filmed sequence (2 to 3 minutes). We chose to determine these two sets of parameters on the first image of the *left* and *right* movies respectively and apply the mappings based on them, one frame at a time, to the whole span of each of the two movies, meaning that the stars will appear to slowly rotate on the sky, as they would for a human observer with a very wide field of view.

An extra twist is that the two cameras do not sit on the same latitude, even though the long axis of the images they generate are along the East-West axis. It is therefore necessary to rotate the two sets of images by (almost) the same angle so that the direction of parallax matches the horizontal axis of the screen on which they will be projected.

⁹ www.mayaskies.net/production_tools/articles/ Introducing_the_dome_master.pdf



Fig. 4. Anaglyph rendition of an Aurora snapshot, before (upper panel) and after (lower panel) alignment of the images produced by the *left* and *right* cameras

Figure 4 illustrates the impact of the images alignment and rotation.

4. 3D viewing

4.1. Stereoscopic techniques

The 3D images generated above have been tested with different stereoscopic techniques, which are listed below in the order of increasing hardware requirement and quality of the rendition.

4.1.1. Free-viewing and cross-eye

The *left* and *right* images are shown side by side, either at their respective location and watching far beyond the screen, in the so-called free-viewing technique, as shown in Fig. 5, or after swaping their position (ie *left* image on the right side and vice-versa), and crossing the eyes, in the aptly named cross-eye technique. These techniques, requiring no material, are by far the cheapest and most accessible ones, but take some time to master, and are limited to very small images.

4.1.2. Anaglyphs

Since the Auroras are mostly green in color, a single composite image of the realigned observations is made in which the red

channel is the green component of the *left* image, and the blue channel is made out of the *right* image. This is looked at with anaglyph glasses in the which the left glass is red, and the right one is blue. This technique, available on screen and in print, as illustrated in Fig. 4, is extremely cheap, with the drawback of loosing color information and reducing luminosity.

4.1.3. Passively polarized screen and glasses

On an ad hoc screen, the odd lines, polarized vertically, show every second line of the *left* image while the even lines, polarized horizontally, do the same for the *right* image. The left and right lenses of a pair of glasses are polarized vertically and horizontally respectively. More recent models of screens and glasses use circular polarization instead. This technique, used on some 3D TV screens, is affordable and preserves the colors, but has a resolution cut in half.

4.1.4. Time multiplexing and active glasses

The *left* and *right* images are shown alternatively on a LCD screen polarized at 45° and supporting high frequency refreshment rate, and the left and right glasses become alternatively opaque and transparent to that polarization, thanks to rotating liquid crystals, with a shutter system operating in synch with the screen. This technique, preferred for computer video games, requires specific glasses and proprietary software and video card. Like all techniques based on linear polarization, it is limited to small or medium size screens.

4.1.5. Other techniques

Other techniques that we were not able to test with our Aurorae images, but are extremely suitable for very large screens, include time multiplexing of circularly polarized images, shown in alternance, with circularly polarized passive glasses, very widespread in 3D movie theaters, or wavelength multiplexing, where the *left* and *right* images use differents red, green and blue wavelength bands, to which the left and right dichroic lenses are respectively transparent, and which is mostly used in planetariums.

Yet another pathway is the use of virtual reality glasses, allowing the immersion of the viewer in a outdoor scene illuminated by 3D Northern Lights. However, for maximum efficiency this requires a heavier observational set-up providing two different views of, at least, the whole hemispheric sky. Set-up that we are only starting to implement.

4.2. Depth of images

In all the techniques listed above, the stars, which after the image processing of Sect. 3 match exactly on the *left* and *right* images, will appear to be on the plan of the paper or of the screen, with the Aurora floating in front of them. Depending on the technique used and the size of the image, and in order to improve the feeling of immersion, it may be necessary to move the whole 3D image closer to or further from the viewer. This can be achieved by

shifting, for instance, the *left* image toward the right or the left respectively.

5. Conclusion

In this paper we present the image processing pipeline implemented to produce real time 3D movies of Aurorae Borealis out of images produced by two distant high resolution fish-eye cameras. A model of the camera optical response is proposed, and for each camera, its eight numerical parameters are constrained using the positional astrometric information of the two dozen bright stars it observed. Each frame of the filmed rushes can be then corrected from this response in order to properly superpose the images, and produce 3D movies with a good stereoscopy. Samples of minutes-long movies produced by this pipeline are available for download at http://www.iap.fr/aurora3d, and can be watched on monitors or projection screens adapted for 3D vision, as described in Sect. 4, and probably in virtual reality headsets. The IDL source code of the pipeline, and its fish-eye projection model, will be made available at the same location, after it has been properly cleaned-up and documented.

We are now applying the same techniques to images and films produced with two pairs of camera, separated by ~6km as previously, and the cameras in each pair set up so that the whole hemispheric sky is observed at once by each pair. After careful stitching of the images, this provides higher quality 3D movies suitable for hemispherical screens, such as planetariums, or for virtual reality glasses, at the cost of heavier observational setup and logistics.

We hope that the existing movies, and the forthcoming ones, will be of interest to the general public raptured by the spectacle of Northern Lights, as well as to scientists studying the phenomenon.

Acknowledgements. We thank François Sèvre and Stéphane Colombi for insightful discussions, François Bouchet for funding this article publication charges, Inge Petter Amlien and Elisabeth Nygård for their hospitality and friendship in the far North, as well as Urpo and Tarja Taskinen for their cozy welcome on the Arctic polar circle.

The authors and the editor thank two anonymous referees for their very constructive comments and suggestions, which helped improving this paper and for their assistance in evaluating it.

Appendix A: Impact of atmospheric refraction

The atmospheric refraction makes astronomical objects appear higher above the horizon (ie, at smaller *local* colatitude, measured from the zenith) than they actually are, with an offset increasing with the colatitude. In the simplest model, in which the atmosphere is approximated as a uniform and flat slab of gas, a source of actual colatitude δ will appear at a colatitude δ_a shifted by

$$R_{\text{atm.}} = \delta - \delta_a = R_{45} \tan(\delta_a) \approx R_{45} \tan(\delta),$$
 (A.1)

and Comstock (1890) proposed that the amplitude of refraction, parameterized by its value at 45°, R_{45} , expressed in arcsec, depends on the observational conditions via

$$R_{45} = \frac{21.5 \, P}{273 + T},\tag{A.2}$$

with *P* and *T* the atmospheric pressure and temperature, in mmHg and $^{\circ}C$ respectively. One then notes that, for small values of *R*_{atm.}, the apparent equisolid radial distance is

=

$$r_{ES}(\delta - R_{\text{atm.}}) \simeq r_{ES} - R_{\text{atm.}} \cos \delta/2,$$
 (A.3a)

$$r_{ES} - R_{45} \frac{r_{ES}}{1 - \frac{r_{ES}^2}{4 - r_{ES}^2}},$$
 (A.3b)

$$= (1 - R_{45})r_{ES} - R_{45} \sum_{p \ge 1} \frac{r_{ES}^{2p+1}}{2^{p+1}}.$$
 (A.3c)

At sea level, for high pressure (P = 800mmHg = 107kPa) and low temperature ($T = -20^{\circ}C$), $R_{45} = 68'' = 3.3 \, 10^{-4}$ rad, and the apparent location of a source seen through a fisheye of focal fwith perfect equisolid projection would be

$$r(\delta)/f = 0.99967r_{ES} - 8.24 \, 10^{-5} r_{ES}^3 - 4.12 \, 10^{-5} r_{ES}^5 + \dots$$
 (A.4)

Of course, Eq. (A.1) is very crude model of atmospheric refraction, but for sources 10° or more above the horizon, it only differs by a few arcsec at most from more accurate and complex models. Moreover, this model most likely over-estimates the refraction close to the horizon since it diverges at $\delta = 90^\circ$, leading us to consider that the actual refraction will be smaller than the one estimated above.

Appendix B: Discretization error

Since the projection of the optics is close to equisolid, as illustrated in Fig. 2, it preserves the areas and therefore the surface densities. If the distribution of stars is assumed uniform on the sky, it will also be uniform on the image. When assigning a star position (x, y) to the closest pixel of integer indices (i, j) the error made is (dx, dy) = (x - i, y - j), where dx and dy both have a probability density of 1 on the interval] - 1/2, 1/2]. Therefore, the means and variances of these errors are $\langle dx \rangle = \langle dy \rangle = 0$ and $\langle (dx)^2 \rangle = \langle (dy)^2 \rangle = 1/12$. Defining the actual and approximate radial distances as $r \equiv (x^2 + y^2)^{1/2}$ and $r' \equiv (i^2 + j^2)^{1/2}$ respectively, then their difference

$$dr = r - r', \tag{B.1a}$$

$$\simeq \frac{(dx)^2 + (dy)^2}{2r'} + \frac{idx + jdy}{r'} \quad \text{for } r' \gg 1, \qquad (B.1b)$$

has for mean value $\langle dr \rangle = 1/(12r')$ and for standard deviation

$$\sigma_{dr} = 1/\sqrt{12} \simeq 0.28867.$$
 (B.2)

One also notes that $s \equiv (dx)^2$ has the density $\rho_s = 1/\sqrt{s}$ for $0 \le s \le 1/4$, and therefore

$$e^2 \equiv (dx)^2 + (dy)^2$$
 (B.3)

has the density

$$\rho_{e^2} = \pi \qquad \text{for } 0 \le e^2 \le 1/4, \tag{B.4a}$$

$$= 2 \arcsin(\frac{1}{2e^2} - 1) \quad \text{for } 1/4 < e^2 \le 1/2, \tag{B.4b}$$

$$= 0$$
 otherwise. (B.4c)

8



Fig. 5. *Left* and *right* images of an Aurora, cropped to a 4:3 aspect ratio, for 3D free-viewing, as described in Sect. 4. The cross-eye technique, where the *left* and *right* images are swapped, can be tried by turning the image up-side down

It implies

$$\langle e\rangle = \left(\sqrt{2} + \ln\left(1 + \sqrt{2}\right)\right)/6 \simeq 0.3826, \tag{B.5}$$

and

$$\sigma_e = (1/6 - \langle e \rangle^2)^{1/2} \simeq 0.14242.$$
 (B.6)

References

- J. Borovička, P. Spurný, and J. Keclíková. A new positional astrometric method for all-sky cameras. Astron. Astrophys. Suppl., 112: 173–178, July 1995. URL http://cdsads.u-strasbg.fr/abs/ 1995A&AS..112..173B. 3.3
- C. Comstock. A Simple Approximate Formula for the Refraction. Sidereal Messenger, 9:185–190, Apr. 1890. URL http://cdsads. u-strasbg.fr/abs/1890SidM....9..185. A
- G. Coupinot, J. Hecquet, M. Auriere, and R. Futaully. Photometric analysis of astronomical images by the wavelet transform. *Astronomy and Astrophysics*, 259:701–710, June 1992. URL http://cdsads.ustrasbg.fr/abs/1992A&A...259..701C. 3.1
- T. J. Hallinan, H. C. Stenbaek Nielsen, and C. S. Deehr. Enhanced aurora. Journal of Geophysical Research: Space Physics, 90(A9): 8461–8475, Sept. 1985. URL http://onlinelibrary.wiley. com/doi/10.1029/JA090iA09p08461/abstract. 1
- R. Kataoka, Y. Miyoshi, K. Shigematsu, D. Hampton, Y. Mori, T. Kubo, A. Yamashita, M. Tanaka, T. Takahei, T. Nakai, H. Miyahara, and K. Shiokawa. Stereoscopic determination of all-sky altitude map of aurora using two ground-based Nikon DSLR cameras. *Annales Geophysicae*, 31:1543–1548, sep 2013. URL http://cdsads.ustrasbg.fr/abs/2013AnGeo..31.1543K. 3
- R. Kataoka, Y. Fukuda, H. A. Uchida, H. Yamada, Y. Miyoshi, Y. Ebihara, H. Dahlgren, and D. Hampton. High-speed stereoscopy of aurora. *Annales Geophysicae*, 34(1):41–44, 2016. URL http://www.ann-geophys.net/34/41/2016/angeo-34-41-2016-supplement.zip. 3
- C. B. Markwardt. Non-linear Least-squares Fitting in IDL with MPFIT. In D. A. Bohlender, D. Durand, and P. Dowler, editors, Astronomical Data Analysis Software and Systems XVIII, volume 411

of Astronomical Society of the Pacific Conference Series, page 251, Sept. 2009. URL https://arxiv.org/abs/0902.2850. 3.3

- D. W. Marquardt. An algorithm for least-squares estimation of nonlinear parameters. *Journal of the society for Industrial and Applied Mathematics*, 11(2):431–441, 1963. 3.3
- D. Marr and E. Hildreth. Theory of edge detection. Proceedings of the Royal Society of London. Series B, Biological Sciences, 207(1167): 187-217, 1980. ISSN 00804649. URL http://www.jstor.org/ stable/35407. 3.1
- J. Meeus. Astronomical Algorithms. Willmann-Bell, Richmond, 1991. ISBN 9780943396354. URL https://books.google.fr/books? id=1smAQgAACAAJ. 3.2.1
- J. J. Moré. The Levenberg-Marquardt algorithm: Implementation and theory, pages 105–116. Springer, Berlin Heidelberg, 1978. ISBN 978-3-540-35972-2. URL http://dx.doi.org/10.1007/ BFb0067700. 3.3
- Y. Mori, A. Yamashita, M. Tanaka, R. Kataoka, T. Miyoshi, M. Okutomi, and H. Asama. Calibration of Fish-Eye Stereo Camera for Aurora Observation. *Proceedings of the International Workshop* on Advanced Image Technology (IWAIT2013), pages 729–734, Jan. 2013. URL http://www.robot.t.u-tokyo.ac.jp/asamalab/ publications/files/848.pdf. 3, 3.2.2, 3.3
- W. Press, S. Teukolsky, W. Vetterling, and B. Flannery. Numerical Recipes in Fortran: The Art of Scientific Computing, 2nd Edition. Cambridge University Press, New York, 1992. ISBN 052143064X. 3.3
- F. R. Stephenson, D. M. Willis, and T. J. Hallinan. The earliest datable observation of the aurora borealis. Astronomy & Geophysics, 45(6):6.15–6.17, Dec. 2004. URL https://academic.oup. com/astrogeo/article-lookup/doi/10.1046/j.1468-4004.2003.45615.x. 1