

A NEW CODING/DECODING ALGORITHM USING FIBONACCI NUMBERS

NİHAL TAŞ*, SÜMEYRA UÇAR, NİHAL YILMAZ ÖZGÜR,
AND ÖZNUR ÖZTUNÇ KAYMAK

ABSTRACT. In this paper we present a new method of coding/decoding algorithms using Fibonacci Q -matrices. This method is based on the blocked message matrices. The main advantage of our model is the encryption of each message matrix with different keys. Our approach will not only increase the security of information but also has high correct ability.

1. INTRODUCTION AND BACKGROUND

It is well known that the Fibonacci sequence is defined by

$$F_n = F_{n-1} + F_{n-2} \text{ with } n \geq 2, \quad (1.1)$$

with the initial terms $F_0 = 0$, $F_1 = 1$. The Fibonacci Q -matrix is defined in [2] and [3] as follows:

$$Q = \begin{pmatrix} 1 & 1 \\ 1 & 0 \end{pmatrix}.$$

From [5] and [7], we known that the n .th power of the Fibonacci Q -matrix is of the following form:

$$Q^n = \begin{pmatrix} F_{n+1} & F_n \\ F_n & F_{n-1} \end{pmatrix}.$$

In recent days information security becomes a more important matter in terms of data transfer over communication channel. So coding/decoding algorithms are of great importance to help in improving information security. Especially, Fibonacci coding theory has been considered in many aspects (see [1], [4], [6],

2010 *Mathematics Subject Classification.* 68P30, 11B39.

Key words and phrases. Coding/decoding algorithm, Fibonacci Q -matrix.

*Corresponding author: N. TAŞ

Balıkesir University, Department of Mathematics, 10145 Balıkesir, TURKEY
e-mail: nihaltas@balikesir.edu.tr.

[7], [8] and [9] for more details). For example, in [7], it was given a new coding theory using the generalization of the Cassini formula for Fibonacci p -numbers and Q_p -matrices.

In this study we present a new coding/decoding algorithm using Fibonacci Q -matrices. The main idea of our method depend on dividing the message matrix into the block matrices of size 2×2 . We use different numbered alphabet for each message, so we get a more reliable coding method. The alphabet is determined by the number of block matrices of the message matrix. Our approach will not only increase the security of information but also has high correct ability for data transfer over communication channel.

2. THE BLOCKING ALGORITHM

At first, we put our message in a matrix of even size adding zero between two words and end of the message until we obtain the size of the message matrix is even. Dividing the message square matrix M of size $2m$ into the matrices, named B_i ($1 \leq i \leq m^2$) of size 2×2 , from left to right, we construct a new coding method.

Now we explain the symbols of our coding method. Assume that matrices B_i , E_i and Q^n are of the following forms:

$$B_i = \begin{pmatrix} b_1^i & b_2^i \\ b_3^i & b_4^i \end{pmatrix}, E_i = \begin{pmatrix} e_1^i & e_2^i \\ e_3^i & e_4^i \end{pmatrix} \text{ and } Q^n = \begin{pmatrix} q_1 & q_2 \\ q_3 & q_4 \end{pmatrix}.$$

The number of the block matrices B_i is denoted by b . According to b , we choose the number n as follows:

$$n = \begin{cases} 3 & , \quad b \leq 3 \\ b & , \quad b > 3 \end{cases}.$$

Using the choosen n , we write the following letter table according to $mod27$ (this table can be extended according to the used characters in the message matrix). We begin the “ n ” for the first character.

A	B	C	D	E	F	G	H	I	J
n	$n + 1$	$n + 2$	$n + 3$	$n + 4$	$n + 5$	$n + 6$	$n + 7$	$n + 8$	$n + 9$
K	L	M	N	O	P	Q	R	S	T
$n + 10$	$n + 11$	$n + 12$	$n + 13$	$n + 14$	$n + 15$	$n + 16$	$n + 17$	$n + 18$	$n + 19$
U	V	W	X	Y	Z	0			
$n + 20$	$n + 21$	$n + 22$	$n + 23$	$n + 24$	$n + 25$	$n + 26$			

Now we explain the following new coding and decoding algorithms.

Coding Algorithm (Fibonacci Blocking Algorithm)

Step 1. Divide the matrix M into blocks B_i ($1 \leq i \leq m^2$).

Step 2. Choose n .

Step 3. Determine b_j^i ($1 \leq j \leq 4$).

Step 4. Compute $\det(B_i) \rightarrow d_i$.

Step 5. Construct $F = [d_i, b_k^i]_{k \in \{1,2,4\}}$.

Step 6. End of algorithm.

Decoding Algorithm

Step 1. Compute Q^n .

Step 2. Determine q_j ($1 \leq j \leq 4$).

Step 3. Compute $q_1 b_1^i + q_3 b_2^i \rightarrow e_1^i$ ($1 \leq i \leq m^2$).

Step 4. Compute $q_2 b_1^i + q_4 b_2^i \rightarrow e_2^i$.

Step 5. Solve $(-1)^n d_i = e_1^i (q_2 x_i + q_4 b_4^i) - e_2^i (q_1 x_i + q_3 b_4^i)$.

Step 6. Substitute for $x_i = b_3^i$.

Step 7. Construct B_i .

Step 8. Construct M .

Step 9. End of algorithm.

In the following examples we give applications of the above algorithm for $b > 3$ and $b \leq 3$, respectively.

Example 2.1. Let us consider the message matrix for the message text “NIHAL HELLO”:

$$M = \begin{pmatrix} N & I & H & A \\ L & 0 & H & E \\ L & L & O & 0 \\ 0 & 0 & 0 & 0 \end{pmatrix}_{4 \times 4}.$$

Coding Algorithm:

Step 1. We can divide the message matrix M of size 4×4 into the matrices, named B_i ($1 \leq i \leq 4$), from left to right, each of size is 2×2 :

$$B_1 = \begin{pmatrix} N & I \\ L & 0 \end{pmatrix}, B_2 = \begin{pmatrix} H & A \\ H & E \end{pmatrix}, B_3 = \begin{pmatrix} L & L \\ 0 & 0 \end{pmatrix} \text{ and } B_4 = \begin{pmatrix} O & 0 \\ 0 & 0 \end{pmatrix}.$$

Step 2. Since $b = 4 \geq 3$, we choose $n = 4$. For $n = 4$, we use the following “letter table” for the message matrix M :

N	I	H	A	L	0	H	E	L	L	O
17	12	11	4	15	3	11	8	15	15	18

Step 3. We have the elements of the blocks B_i ($1 \leq i \leq 4$) as follows:

$b_1^1 = 17$	$b_2^1 = 12$	$b_3^1 = 15$	$b_4^1 = 3$
$b_1^2 = 11$	$b_2^2 = 4$	$b_3^2 = 11$	$b_4^2 = 8$
$b_1^3 = 15$	$b_2^3 = 15$	$b_3^3 = 3$	$b_4^3 = 3$
$b_1^4 = 18$	$b_2^4 = 3$	$b_3^4 = 3$	$b_4^4 = 3$

Step 4. Now we calculate the determinants d_i of the blocks B_i :

$d_1 = \det(B_1) = -129$
$d_2 = \det(B_2) = 44$
$d_3 = \det(B_3) = 0$
$d_4 = \det(B_4) = 45$

Step 5. Using Step 3 and Step 4 we obtain the following matrix F :

$$F = \begin{pmatrix} -129 & 17 & 12 & 3 \\ 44 & 11 & 4 & 8 \\ 0 & 15 & 15 & 3 \\ 45 & 18 & 3 & 3 \end{pmatrix}.$$

Step 6. End of algorithm.

Decoding algorithm:

Step 1. It is known that

$$Q^4 = \begin{pmatrix} 5 & 3 \\ 3 & 2 \end{pmatrix}.$$

Step 2. The elements of Q^4 are denoted by

$$q_1 = 5, q_2 = 3, q_3 = 3 \text{ and } q_4 = 2.$$

Step 3. We compute the elements e_1^i to construct the matrix E_i :

$$e_1^1 = 121, e_1^2 = 67, e_1^3 = 120 \text{ and } e_1^4 = 99.$$

Step 4. We compute the elements e_2^i to construct the matrix E_i :

$$e_2^1 = 75, e_2^2 = 41, e_2^3 = 75 \text{ and } e_2^4 = 60.$$

Step 5. We calculate the elements x_i :

$$\begin{aligned} (-1)^4(-129) &= 121(3x_1 + 6) - 75(5x_1 + 9) \\ \Rightarrow x_1 &= 15. \end{aligned}$$

$$\begin{aligned} (-1)^444 &= 67(3x_2 + 16) - 41(5x_2 + 24) \\ \Rightarrow x_2 &= 11. \end{aligned}$$

$$\begin{aligned} (-1)^40 &= 120(3x_3 + 6) - 75(5x_3 + 9) \\ \Rightarrow x_3 &= 3. \end{aligned}$$

$$\begin{aligned} (-1)^445 &= 99(3x_4 + 6) - 60(5x_4 + 9) \\ \Rightarrow x_4 &= 3. \end{aligned}$$

Step 6. We rename x_i as follows:

$$x_1 = b_3^1 = 15, x_2 = b_3^2 = 11, x_3 = b_3^3 = 3 \text{ and } x_4 = b_3^4 = 3.$$

Step 7. We construct the block matrices B_i :

$$B_1 = \begin{pmatrix} 17 & 12 \\ 15 & 3 \end{pmatrix}, B_2 = \begin{pmatrix} 11 & 4 \\ 11 & 8 \end{pmatrix}, B_3 = \begin{pmatrix} 15 & 15 \\ 3 & 3 \end{pmatrix} \text{ and } B_4 = \begin{pmatrix} 18 & 3 \\ 3 & 3 \end{pmatrix}.$$

Step 8. We obtain the message matrix M :

$$M = \begin{pmatrix} 17 & 12 & 11 & 4 \\ 15 & 3 & 11 & 8 \\ 15 & 15 & 18 & 3 \\ 3 & 3 & 3 & 3 \end{pmatrix} = \begin{pmatrix} N & I & H & A \\ L & 0 & H & E \\ L & L & O & 0 \\ 0 & 0 & 0 & 0 \end{pmatrix}.$$

Step 9. End of algorithm.

Example 2.2. Let us consider the message matrix for the message text “MATH”:

$$M = \begin{pmatrix} M & A \\ T & H \end{pmatrix}_{2 \times 2}.$$

Coding Algorithm:

Step 1. Since the size of message matrix M is 2×2 , we have only one block matrix $B_1 = M$.

Step 2. Since $b = 1 < 3$, we choose $n = 3$. For $n = 3$, we use the following “letter table” for the message matrix M :

M	A	T	H
15	3	22	10

Step 3. We have the elements of the blocks B_1 as follows:

$$\boxed{b_1^1 = 15 \mid b_2^1 = 3 \mid b_3^1 = 22 \mid b_4^1 = 10}.$$

Step 4. Now we calculate the determinant d_1 of the block matrix B_1 :

$$\boxed{d_1 = \det(B_1) = 84}.$$

Step 5. Using Step 3 and Step 4 we obtain the following matrix F :

$$F = \begin{pmatrix} 84 & 15 & 3 & 10 \end{pmatrix}.$$

Step 6. End of algorithm.

Decoding algorithm:

Step 1. It is known that

$$Q^3 = \begin{pmatrix} 3 & 2 \\ 2 & 1 \end{pmatrix}.$$

Step 2. The elements of Q^3 are denoted by

$$q_1 = 3, q_2 = 2, q_3 = 2 \text{ and } q_4 = 1.$$

Step 3. We compute the element e_1^1 to construct the matrix E_1 :

$$e_1^1 = q_1 b_1^1 + q_3 b_2^1 = 51.$$

Step 4. We compute the element e_2^1 to construct the matrix E_1 :

$$e_2^1 = q_2 b_1^1 + q_4 b_2^1 = 33.$$

Step 5. We calculate the element x_1 :

$$\begin{aligned} (-1)^3(84) &= 51(2x_1 + 10) - 33(3x_1 + 20) \\ \Rightarrow x_1 &= 22. \end{aligned}$$

Step 6. We rename x_1 as follows:

$$x_1 = b_3^1 = 22.$$

Step 7. We construct the block matrix B_i :

$$B_1 = \begin{pmatrix} 15 & 3 \\ 22 & 10 \end{pmatrix}.$$

Step 8. We obtain the message matrix M :

$$M = \begin{pmatrix} 15 & 3 \\ 22 & 10 \end{pmatrix} = \begin{pmatrix} M & A \\ T & H \end{pmatrix}.$$

Step 9. End of algorithm.

3. A COMPUTER APPLICATION

To determine the verification of our coding method, in this section we construct a computer algorithm. We create the MATLAB codes for the examples given in the previous section. So our blocking algorithm is checked for $n = 2$ and $n = 4$ for different message texts, respectively. It can be seen that the algorithm works errorless. Moreover, complex message texts are solved correctly thanks to these algorithms. By a similar way, this algorithm can be extended for convenient n . At first we define the Fibonacci numbers in the algorithm then we give the following code segments for $n = 2$ (see Table 1).

The second algorithm seen in Table 2 provides more faster solution for complex text. The readers can verify these algorithms for varied values of n .

4. CONCLUSION

The main idea of our method depends on dividing the message matrix into the block matrices of size 2×2 . We give an algorithm using Fibonacci numbers and the numbers corresponding to each letter in used alphabet changes for each new message matrix. We verify our new algorithm with illustrative examples. Also our method is supported by a code in MATLAB programme for $n = 2$ and $n = 4$. This algorithm can be improved for any n in the light of similar arguments.

REFERENCES

- [1] M. Basu, B. Prasad, *The generalized relations among the code elements for Fibonacci coding theory*, Chaos Solitons Fractals 41 (2009), no. 5, 2517–2525.
- [2] H. W. Gould, *A history of the Fibonacci Q-matrix and a higher-dimensional problem*, Fibonacci Quart. 19 (1981), no. 3, 250–257.
- [3] V. E. Hoggat, *Fibonacci and Lucas Numbers*, Houghton-Mifflin, Palo Alto (1969).
- [4] S. Prajapat, A. Jain, R. S. Thakur, *A Novel Approach For Information Security With Automatic Variable Key Using Fibonacci Q-Matrix*, IJCCT 3 (2012), no. 3, 54–57.
- [5] A. P. Stakhov, *A generalization of the Fibonacci Q-matrix*, Rep. Natl. Acad. Sci. Ukraine 9 (1999), 46–49.
- [6] A. Stakhov, V. Massingue, A. Sluchenko, *Introduction into Fibonacci Coding and Cryptography*, Osnova, Kharkov (1999).
- [7] A. P. Stakhov, *Fibonacci matrices, a generalization of the Cassini formula and a new coding theory*, Chaos Solitons Fractals 30 (2006), no. 1, 56–66.
- [8] B. S. Tarle, G. L. Prajapati, *On the information security using Fibonacci series*, International Conference and Workshop on Emerging Trends in Technology (ICWET 2011)-TCET, Mumbai, India.
- [9] F. Wang, J. Ding, Z. Dai, Y. Peng, *An application of mobile phone encryption based on Fibonacci structure of chaos*, 2010 Second WRI World Congress on Software Engineering.

BALIKESIR UNIVERSITY, DEPARTMENT OF MATHEMATICS, 10145 BALIKESIR, TURKEY
E-mail address: nihaltas@balikesir.edu.tr

BALIKESIR UNIVERSITY, DEPARTMENT OF MATHEMATICS, 10145 BALIKESIR, TURKEY
E-mail address: sumeyraucar@balikesir.edu.tr

BALIKESIR UNIVERSITY, DEPARTMENT OF MATHEMATICS, 10145 BALIKESIR, TURKEY
E-mail address: nihali@balikesir.edu.tr

BALIKESIR UNIVERSITY, 10145 BALIKESIR, TURKEY
E-mail address: oztunc@balikesir.edu.tr

TABLE 1. The Algorithm for $n = 2$

```

a=input('a='); b=input('b= '); c=input('c= '); d=input('d= ');
A= [a, b; c, d];
F=[det(A), a; c, d];%End of Coding Algorithm
fibf(1) = 1; fibf(2) = 1; p=3;
while fibf(p - 1) < 1000 fibf(p)=fibf(-1)+fibf(p-2); p=p+1; end
Q = [fibf(n+1), fibf(n); fibf(n), fibf(n-1)];
e1= fibf(n+1)*a+fibf(n)*b; e2= fibf(n)*a+fibf(n-1)*b;
x = sym('x');
eqn = (-1)^n*det(A) == (e1*(fibf(n)*x+fibf(n-1)*d))-(e2*(fibf(n+1)*x+fibf(n)*d));
solx = solve(eqn,'x');
E =[a,b;solx,d] %End of Decoding Algorithm

```

TABLE 2. The Algorithm for $n = 4$

```

a=input('a='); b=input('b= '); c=input('c= '); d=input('d= ');
e=input('e = '); f=input('f= '); g=input('g = '); h=input('h = ');
i=input('i= '); j=input('j = '); k=input('k = '); l=input('l = ');
m=input('m = '); n=input('n = '); p=input('p = '); r=input('r = ');
A = [a, b, c, d; e, f, g, h; i, j, k, l; m, n, p, r];
M = [a, b; e, f]; N = [c, d; g, h]; O = [i, j; m, n]; P = [k, l; p, r];
d1=det(M); d2=det(N); d3=det(O); d4=det(P);
F=[d1, a, b, f; d2, c, d, h; d3, i, j, n; d4, k, l, r]%End of Coding Algorithm
fibf(1) = 1; fibf(2) = 1; p=3;
while fibf(p-1) < 1000 fibf(p) = fibf(p-1)+fibf(p-2); ;
    p=p+1;end
de11=fibf(s+1)*a+fibf(s)*b;
e12= fibf(s+1)*c+fibf(s)*d;
e13= fibf(s+1)*i+fibf(s)*j;
e14= fibf(s+1)*k+fibf(s)*l;
e21= fibf(s)*a+fibf(s-1)*b;
e22= fibf(s)*c+fibf(s-1)*d;
e23= fibf(s)*i+fibf(s-1)*j;
e24= fibf(s)*k+fibf(s-1)*l; x = sym('x');
eqn1 = (-1)^s*d1 == (e11*(fibf(s)*x+fibf(s-1)*f))-(e21*(fibf(s+1)*x+fibf(s)*f));
eqn2 = (-1)^s*d2 == (e12*(fibf(s)*x+fibf(s-1)*h))-(e22*(fibf(s+1)*x+fibf(s)*h));
eqn3 = (-1)^s*d3 == (e13*(fibf(s)*x+fibf(s-1)*n))-(e23*(fibf(s+1)*x+fibf(s)*n));
eqn4 = (-1)^s*d4 == (e14*(fibf(s)*x+fibf(s-1)*r))-(e24*(fibf(s+1)*x+fibf(s)*r));
solx1 = solve(eqn1,'x'); solx2 = solve(eqn2,'x');
solx3 = solve(eqn3,'x'); solx4 = solve(eqn4,'x');
B1 = [a, b; solx1, f]; B2 = [c, d; solx2, h]; B3 = [i, j; solx3, n]; B4 = [k, l; solx4, r];
M=[a, b, c, d; solx1, f, solx2, h; i, j, k, l; solx3, n, solx4, r]%End of Decoding Algorithm

```