arXiv:1812.10431v1 [cs.DS] 26 Dec 2018

Applying Predicate Detection to the Constrained Optimization Problems

Vijay K. Garg, The University of Texas at Austin, Department of Electrical and Computer Engineering, Austin, TX 78712, USA

Abstract-We present a method to design parallel algorithms for constrained combinatorial optimization problems. Our method solves and generalizes many classical combinatorial optimization problems including the stable marriage problem, the shortest path problem and the market clearing price problem. These three problems are solved in the literature using Gale-Shapley algorithm, Dijkstra's algorithm, and Demange, Gale, Sotomayor algorithm. Our method solves all these problems by casting them as searching for an element that satisfies an appropriate predicate in a distributive lattice. Moreover, it solves generalizations of all these problems - namely finding the optimal solution satisfying additional constraints called latticelinear predicates. For stable marriage problems, an example of such a constraint is that Peter's regret is less than that of Paul. For shortest path problems, an example of such a constraint is that cost of reaching vertex v_1 is at least the cost of reaching vertex v_2 . For the market clearing price problem, an example of such a constraint is that $item_1$ is priced at least as much as *item*₂. In addition to finding the optimal solution, our method is useful in enumerating all constrained stable matchings, and all constrained market clearing price vectors.

Index Terms—Stable Matching, lattice-linear Predicates, Distributive Lattices

I. INTRODUCTION

We present a method called *lattice-linear predicate detection* that can solve many combinatorial optimization problems. We use this method to solve generalization of three of the most fundamental problems in combinatorial optimization — the stable marriage problem [9], the shortest path problem [8], and the assignment problem [14]. Due to the importance and applications of these problems, each one of them has been the subject of numerous books and thousands of papers. The classical algorithms to solve these problems are Gale-Shapley algorithm for the shortest path problem [8], and Kuhn's Hungarian method to solve the assignment problem [14] (or equivalently, Demange, Gale, Sotomayor auction-based algorithm [6] for market clearing prices). Could there be a single efficient algorithm that solves all of these problems?

In this paper, we describe a technique that solves not only these problems but more *general* versions of each of the above problems. We seek the optimal solution for these problems that satisfy additional constraints modeled using a *lattice-linear* predicate [3]. When the set of constraints is empty, we get back the classical problems.

Our technique requires the underlying search space to be viewed as a distributive lattice [2], [5]. Common to all these seemingly disparate combinatorial optimization problems is the structure of the *feasible* solution space. The set of all stable matchings, the set of all feasible rooted trees for the shortest path problem, and the set of all market clearing prices are all closed under the meet operation of the lattice. If the order is appropriately defined, then finding the optimal solution (the man-optimal stable marriage, the shortest path cost vector, the minimum market clearing price vector) is equivalent to finding the infimum of all feasible solutions in the lattice.

We note here that it is well-known that the set of stable matching and the set of market clearing price vectors form distributive lattices. The set of stable matchings forms a distributive lattice is given in [11] where the result is attributed to Conway. The set of market clearing price vectors forms a distributive lattice is given in [15]. However, the algorithms to find the man-optimal stable matching and the minimum market clearing price vectors are not derived from the lattice property. In our method, once the lattice-linearity of the feasible solution space is established, the algorithm to find the optimal solution falls out as a consequence. To the best of our knowledge, this is the first paper to derive Gale-Shapley's algorithm, Dijkstra's algorithm and Demange-Gale-Sotomayor's algorithm from a single algorithm by exploiting a lattice property.

The lattice-linear predicate detection method to solve the combinatorial optimization problem is as follows. The first step is to define a lattice of vectors L such that each vector is assigned a point in the search space. For the stable matching problem, the vector corresponds to the assignment of men to women (or equivalently, the choice number for each man). For the shortest path problem, the vector assigns a cost to each node. For the market clearing price problem, the vector assigns a price to each item. The comparison operation (\leq) is defined on the set of vectors such that the least vector, if feasible, is the extremal solution of interest. For example, in the stable marriage problem if each man orders women according to his preferences and every man is assigned the first woman in the list, then this solution is the man-optimal solution whenever the assignment is a matching and has no blocking pair. Similarly, in the shortest path problem and the minimum market clearing price problem, the zero vector would be optimal if it were

Supported by NSF CNS-1812349, CNS-1563544, and the Cullen Trust for Higher Education Endowed Professorship

feasible.

The second step in our method is to define a boolean predicate B that models feasibility of the vector. For the stable matching problem, an assignment is feasible iff it is a matching and there is no blocking pair. For the shortest path problem, an assignment is feasible iff there exists a rooted spanning tree at the source vertex such that the cost of each vertex is greater than the cost of traversing the path in the rooted tree. For the minimum market clearing price problem, a price vector is feasible iff it is a market clearing price vector.

The third step is to show that the feasibility predicate is a lattice-linear predicate [3]. Lattice-linearity property allows one to search for a feasible solution efficiently. If any point in the search space is not feasible, it allows one to make progress towards the optimal feasible solution without any need for exploring multiple paths in the lattice. Moreover, multiple processes can make progress towards the feasible solution independently. In a finite distributive lattice, it is clear that the maximum number of such advancement steps before one finds the optimal solution or reaches the top element of the lattice is equal to the height of the lattice. Once this step is done, we get the following outcomes.

First, by applying the lattice-linear predicate detection algorithm to unconstrained problems, we get Gale-Shapley algorithm for the stable matching problem, Dijkstra's algorithm for the shortest path problem and Demange, Gale, Sotomayor's algorithm for the minimum market clearing price. In fact, the lattice-linear predicate detection method yields a parallel version of these algorithms and by restricting these to their sequential counterparts, we get these classical sequential algorithms.

Second, we get optimal solutions for the constrained version of each of these problems, whenever the constraints are lattice-linear. We solve the Constrained Stable Matching Problem where in addition to men's preferences and women's preferences, there may be a set of lattice-linear constraints. For example, we may require that Peter's regret [10] should be less than that of Paul, where the *regret* of a man in a matching is the choice number he is assigned. We note here that some special cases of the constrained stable marriage problems have been studied. Dias et al [4], [7] study the stable marriage problem with restricted pairs. A restricted pair is either a *forced* pair which is required to be in the matching, or a *forbidden* pair which must not be in the matching. Both of these constraints are lattice-linear and therefore can be modeled in our system. The constrained shortest path problem asks for a rooted tree at the source node with the smallest cost at each vertex that satisfies additional constraints of the form "the cost of reaching node x is at least the cost of reaching node y", "the cost of reaching x must be equal to the cost of reaching y, and "the cost of reaching x must be within δ of the cost of reaching y". For the market clearing price problem, we consider constraints on the clearing prices of the form that item i must be priced at least as much as item j, or the difference in prices for item i and j must not exceed δ .

Third, by applying a constructive version of Birkhoff's

theorem on finite distributive lattices [2], [5], we give an algorithm that outputs a succinct representation of all feasible solutions. In particular, the join-irreducible elements [5] of the feasible sublattice can be determined efficiently (in polynomial time). For the constrained stable matching problem, we get a concise representation of all stable matchings that satisfy given constraints. Thus, our method yields a more general version of rotation posets [10] to represent all *constrained* stable matchings. Analogously, we get a concise representation of all constrained integral market clearing price vectors.

The paper is organized as follows. Section II defines latticelinear predicates and gives a simple parallel algorithm called LLP (Lattice-Linear Predicate detection algorithm). Section III uses LLP to solve the constrained stable matching problem. Section IV solves the constrained single source shortest path problem, and Section V solves the constrained market clearing prices problem. Section VI gives a concise representation of all feasible solutions for the constrained stable matching and market clearing price problem. Finally, Section VII gives conclusions and future work.

II. LATTICE-LINEAR PREDICATES

Let L be the lattice of all n-dimensional vectors of reals greater than or equal to zero vector and less than or equal to a given vector T where the order on the vectors is defined by the component-wise natural \leq . The minimum element of this lattice is the zero vector. The lattice is used to model the search space of the combinatorial optimization problem. For simplicity, we are considering the lattice of vectors of nonnegative reals; later we show that our results are applicable to any distributive lattice. The combinatorial optimization problem is modeled as finding the minimum element in L that satisfies a boolean *predicate* B, where B models *feasible* (or acceptable solutions). We are interested in parallel algorithms to solve the combinatorial optimization problem with n processes. We will assume that the systems maintains as its state the current candidate vector $G \in L$ in the search lattice, where G[i] is maintained at process i. We call G, the global state, and G[i], the state of process *i*.

Finding an element in lattice that satisfies the given predicate B, is called the *predicate detection* problem. Finding the *minimum* element that satisfies B (whenever it exists) is the combinatorial optimization problem. We now define *lattice-linearity* which enables efficient computation of this minimum element. Lattice-linearity is first defined in [3] in the context of detecting global conditions in a distributed system where it is simply called linearity. We use the term *lattice-linearity* to avoid confusion with the standard usage of linearity.

A key concept in deriving an efficient predicate detection algorithm is that of a *forbidden* state. Given a predicate B, and a vector $G \in L$, a state G[i] is *forbidden* (or equivalently, the index i is forbidden) if for any vector $H \in L$, where $G \leq H$, if H[i] equals G[i], then B is false for H. Formally,

Definition 1 (Forbidden State [3]). *Given any distributive lattice* L *of* n*-dimensional vectors of* $\mathbf{R}_{\geq 0}$ *, and a predicate* B*,*

we define forbidden $(G, i, B) \equiv \forall H \in L : G \leq H : (G[i] = H[i]) \Rightarrow \neg B(H).$

We define a predicate B to be *lattice-linear* with respect to a lattice L if for any global state G, B is false in G implies that G contains a *forbidden state*. Formally,

Definition 2 (lattice-linear Predicate [3]). A boolean predicate B is lattice-linear with respect to a lattice L iff $\forall G \in L : \neg B(G) \Rightarrow (\exists i : \text{forbidden}(G, i, B)).$

We now give some examples of lattice-linear predicates. Our first example relates to scheduling of n jobs. Each job j requires time t_j for completion and has a set of prerequisite jobs, denoted by pre(j), such that it can be started only after all its prerequisite jobs have been completed. Our goal is to find the minimum completion time for each job. We let our lattice L be the set of all possible completion times. A completion vector $G \in L$ is feasible iff $B_{jobs}(G)$ holds where $B_{jobs}(G) \equiv \forall j : (G[j] \geq t_j) \land (\forall i \in pre(j) : G[j] \geq G[i] + t_j)$. B_{jobs} is lattice-linear because if it is false, then there exists j such that either $G[j] < t_j$ or $\exists i \in pre(j) : G[j] < G[i] + t_j$. We claim that forbidden (G, i, B_{jobs}) . Indeed, any vector $H \geq G$ cannot be feasible with G[j] equal to H[j]. The minimum of all vectors that satisfy feasibility corresponds to the minimum completion time.

Our second example relates to (exclusive) prefix sum of an array A with non-negative reals. We are required to output an array G such that G[j] equals sum of all entries in A from 0 to j-1. We define G to be feasible iff B_{prefix} holds where $B_{prefix} \equiv (\forall j > 0) : (G[j] \ge G[j-1] + A[j-1])$. Again, it is easy to verify that B_{prefix} is lattice-linear. The minimum vector G that satisfies B_{prefix} corresponds to the exclusive prefix sum of the array A.

As an example of a predicate that is not lattice-linear, consider the predicate $B \equiv \sum_j G[j] \ge 1$ defined on the space of two dimensional vectors. Consider the vector G equal to (0,0). The vector G does not satisfy B. For B to be lattice-linear either the first index or the second index should be forbidden. However, none of the indices are forbidden in (0,0). The index 0 is not forbidden because the vector H = (0,1) is greater than G, has H[0] equal to G[0] but it still satisfies B. The index 1 is also not forbidden because H = (1,0) is greater than G, has H[1] equal to G[1] but it satisfies B.

The following Lemma is useful in proving lattice-linearity of predicates.

Lemma 1. Let *B* be any boolean predicate defined on a lattice *L* of vectors.

(a) Let $f : L \to \mathbf{R}_{\geq 0}$ be any monotone function defined on the lattice L of vectors of $\mathbf{R}_{\geq 0}$. Consider the predicate $B \equiv G[i] \geq f(G)$ for some fixed *i*. Then, B is lattice-linear. (b) Let L_B be the subset of the lattice L of the elements that satisfy B. Then, B is lattice-linear iff L_B is closed under meets.

(c) If B_1 and B_2 are lattice-linear then $B_1 \wedge B_2$ is also lattice-linear.

Proof. (a) Suppose B is false for G. This implies that G[i] < f(G). Consider any vector $H \ge G$ such that H[i] is equal to G[i]. Since G[i] < f(G), we get that H[i] < f(G). The monotonicity of f implies that H[i] < f(H) which shows that $\neg B(H)$.

(b) This is shown in [3]. Assume that B is not lattice-linear. This implies that there exists a global state G such that $\neg B(G)$, and $\forall i : \exists H_i \geq G : (G[i] = H_i[i])$ and $B(H_i)$. Consider $Y = \bigcup_i \{H_i\}$. All elements of $Y \in L_B$. However, inf Y which is in G is not an element of L_B . This implies that L_B is not closed under the infimum operation. Conversely, let $Y = \{H_1, H_2, \ldots, H_k\}$ be any subset of L_B such that its infimum G does not belong to L_B . Since G is the infimum of Y, for any i, there exists $j \in \{1 \dots k\}$ such that $G[i] = H_j[i]$. Since $B(H_j)$ is true for all j, it follows that there exists a G for which lattice-linearity does not hold.

(c) Follows from the equivalence of meet-closed predicates with lattice-linearity and that meet-closed predicates are closed under conjunction. For a more direct proof, suppose that $\neg(B_1 \land B_2)$. This implies that one of the conjuncts is false and therefore from the lattice-linearity of that conjunct, a forbidden state exists.

For the job scheduling example, we can define B_j as $G[j] \geq max(t_j, max\{G[i] + t_j \mid i \in pre(j)\})$. Since $f_j(G) = max(t_j, max\{G[i] + t_j \mid i \in pre(j)\})$ is a monotone function, it follows from Lemma 1(a) that B_j is lattice-linear. The predicate $B_{jobs} \equiv \forall j : B_j$ is lattice-linear due to Lemma 1(c). Also note that the problem of finding the minimum vector that satisfies B_{jobs} is well-defined due to Lemma 1(b).

We now discuss detection of lattice-linear predicates which requires an additional assumption called the *efficient advancement property* [3] — there exists an efficient (polynomial time) algorithm to determine the forbidden state. This property holds for all the problems considered in this paper. Once we determine j such that forbidden(G, j, B), we also need to determine how to advance along index j. To that end, we extend the definition of forbidden as follows.

Definition 3 (α -forbidden). Let *B* be any boolean predicate on the lattice *L* of all assignment vectors. For any *G*, *j* and positive real $\alpha > G[j]$, we define forbidden (G, j, B, α) iff

$$\forall H \in L : H \ge G : (H[j] < \alpha) \Rightarrow \neg B(H).$$

Given any lattice-linear predicate B, suppose $\neg B(G)$. This means that G must be advanced on all indices jsuch that forbidden(G, j, B). We use a function $\alpha(G, j, B)$ such that forbidden(G, j, B). We use a function $\alpha(G, j, B)$ such that forbidden $(G, j, B, \alpha(G, j, B))$ holds whenever forbidden(G, j, B) is true. With the notion of $\alpha(G, j, B)$, we have the algorithm LLP shown in Fig. 1. The algorithm LLPhas two inputs — the predicate B and the top element of the lattice T. It returns the least vector G which is less than or equal to T and satisfies B (if it exists). Whenever B is not true in the current vector G, the algorithm advances on all forbidden indices j in parallel. This simple parallel algorithm can be used to solve a large variety of combinatorial optimization problems by instantiating different forbidden(G, j, B) and $\alpha(G, j, B)$. vector function getLeastFeasible(T: vector, B: predicate) var G: vector of reals initially $\forall i : G[i] = 0$; while $\exists j$: forbidden(G, j, B) do for all j such that forbidden(G, j, B) in parallel: if ($\alpha(G, j, B) > T[j]$) then return null; else $G[j] := \alpha(G, j, B)$; endwhile; return G; // the optimal solution

Fig. 1. Parallel Algorithm LLP to find the minimum vector less than or equal to T that satisfies B

Theorem 1. Suppose there exists a fixed constant $\delta > 0$ such that $\alpha(G, j, B) - G[j] \ge \delta$ whenever forbidden(G, j, B). Then, the parallel algorithm LLP finds the least vector $G \le T$ that satisfies B, if one exists.

Proof. Since G[j] increases by at least δ for at least one forbidden j in every iteration of the *while* loop, the algorithm terminates in at most $\sum_i [T[i]/\delta]$ number of steps.

We show that the algorithm maintains the invariant (I1) that for all indices j, any vector V such that V[j] is less than G[j]cannot satisfy B. Formally, the invariant (I1) is

$$\forall j : (\forall V \in L : (V[j] < G[j]) \Rightarrow \neg B(V)).$$

Initially, the invariant holds trivially because G is initialized to 0. Suppose forbidden(G, j, B). Then, we increase G[j] to $\alpha(G, j, B)$. We need to show that this change maintains the invariant. Pick any V such that $V[j] < \alpha(G, j, B)$. We now do a case analysis. If $V \ge G$, then $\neg B(V)$ holds from the definition of $\alpha(G, j, B)$. Otherwise, there exists some k such that V[k] < G[k]. In this case $\neg B(V)$ holds due to (11).

We can now show Theorem 1 using the invariant. First, suppose that the algorithm LLP terminates because $\alpha(G, j, B) > T[j]$. In this case, there is no feasible vector in L due to the invariant (because the predicate B is false for all values of G[j]). Now suppose that the algorithm terminates because there does not exist any j such that forbidden(G, j, B). This implies that G satisfies B due to lattice-linearity of B. It is also the least vector that satisfies B due to the invariant (I1).

For the job scheduling example, we get a parallel algorithm to find the minimum completion time by using forbidden $(G, j, B_{jobs}) \equiv (G[j] < t_j) \lor (\exists i \in pre(j) : G[j] < G[i] + t_j)$, and $\alpha(G, j, B_{jobs}) = \max\{t_j, \max\{G[i] + t_j | i \in pre(j)\}\}$.

For the prefix sum example, we get a parallel algorithm by using forbidden $(G, j, B_{prefix}) \equiv (G[j] < G[j-1] + A[j-1])$ and $\alpha(G, j, B_{prefix}) = G[j-1] + A[j-1]$ for all j > 0.

We now show, on account of Lemma 1(c), that if we have a parallel algorithm for a problem, then we also have one for the constrained version of that problem.

Lemma 2. Let LLP be the parallel algorithm to find the least vector G that satisfies B_1 if one exists. Then, LLP can be adapted to find the least vector G that satisfies $B_1 \wedge B_2$ for any lattice-linear predicate B_2 .

Proof. The algorithm *LLP* can be used with the following changes: forbidden $(G, j, B_1 \land B_2) \equiv$ forbidden $(G, j, B_1) \lor$ forbidden (G, j, B_2) , and $\alpha(G, j, B_1 \land B_2) = \max\{\alpha(G, j, B_1), \alpha(G, j, B_2)\}.$

For example, suppose that we want the minimum completion time of jobs with the additional lattice-linear constraint that $B_2(G) \equiv (G[1] = G[2])$. B_2 is latticelinear with forbidden $(G, 1, B_2) \equiv (G[1] < G[2])$ and forbidden $(G, 2, B_2) \equiv (G[2] < G[1])$. By applying, Lemma 2, we get a parallel algorithm for the constrained version.

The job scheduling problem and the prefix sum problem are special cases of the following optimization problem: minimize G such that $\forall i : G_i \ge f_i(G)$ where each of f_i is a monotone function on the lattice of reals. When the predicate B is of the form $\forall i : G_i \ge f_i(G)$, the problem is closely related to finding the least fixed point in a lattice using Knaster-Tarski's fixed point theorem [12], [16].

The algorithm in Fig. 1 can be viewed as repeated iteration of a monotone function on the bottom element of a lattice similar to a constructive version of Knaster-Tarski's theorem. In particular, let L be any lattice with the bottom element \perp , the top element \top and f a monotone function from L to $\mathbf{R}_{\geq 0}$. Consider the set $F \subseteq L$ defined as $\{x \mid x \geq f(x)\}$. If there exists k such that $f^k(\perp) = f^{k+1}(\perp)$, then $x^* = f^k(\perp)$ is the minimum element in L that satisfies the predicate $(x \ge f(x))$. Our work differs from such earlier work in many respects. First, B may not have the form $\forall i: G_i > f_i(G)$; instead we only require B to be closed under meets. Second, Knaster-Tarski's fixed point theorem (and many variants) requires the function to be from the lattice L to itself. In that case, the solution to the equation x > f(x) always exists for a complete lattice because $\top \geq f(\top)$. We do not assume that the range of the function is the lattice itself. Therefore, there is no guarantee of the existence of the fixed point. Indeed, for the job scheduling example, if the prerequisites have a cycle and weights are positive, then there is no solution and the algorithm LLP returns null. Third, the goal of this paper is to develop techniques to reach the fixed point with an efficient parallel algorithm and to show that many standard and nonstandard parallel algorithms for combinatorial optimization can be derived in this framework.

Note that the straightforward application of LLP may not give the most time-efficient parallel algorithm. The efficiency of the algorithm may depend upon $\alpha(G, j, B)$ chosen for the predicate B. We will later show such optimizations for the shortest path algorithm.

III. CONSTRAINED STABLE MATCHING PROBLEM

We now show that our technique is applicable when the search space is any distributive lattice rather than lattice of nonnegative real vectors. We illustrate this by applying predicate detection to the stable matching problem. Traditionally, a stable matching problem is modeled as a bipartite graph consisting of two sets of vertices for men and women. We use a different model to exploit predicate detection techniques - instead of the underlying set of vertices being men and women, it is the set of proposals E that can be made by men to women. We call these proposals, *events*, which are executed by n processes corresponding to n men denoted by $\{P_1 \dots P_n\}$. An event is denoted by a tuple (i, j) that corresponds to the proposal made by man i to woman j. Women are also numbered 1..nand denoted by $\{w_1 \dots w_n\}$. We now impose a partial order \rightarrow_p on E to model the order in which these proposals can be made. In the standard stable matching problem (SMP), every man P_i has his preference list mpref[i] such that mpref[i][k]gives the k^{th} most preferred woman for P_i . We model mpref using \rightarrow_p order on the set of events. If P_i prefers woman j to woman k, then there is an edge from the event (i, j) to the event (i, k). As in SMP, we assume that every man gives a total order on all women. Each process makes proposals to women in the decreasing order of preferences (similar to the Gale-Shapley algorithm).

In the standard stable matching problem, there are no constraints on the order of proposals made by different men, and \rightarrow_p can be visualized as a partial order (E, \rightarrow_p) with n disjoint chains. In the constrained SMP, \rightarrow_p can relate proposals made by different men and therefore \rightarrow_p forms a general poset (E, \rightarrow_p) . For example, the constraint that Peter's regret is less than or equal to John can be modeled by adding \rightarrow_p edges as follows. For any regret r, we add an \rightarrow_p edge from the proposal by John with regret r to the proposal by Peter with regret r. The constraint that Peter and John have the same regret can be modeled as a conjunction of Peter's regret being less than that of John and vice-versa. We draw \rightarrow_p edges in solid (blue) edges as shown in Fig. 3.

Let $G \subseteq E$ denote the global state of the system. A global state G is simply the subset of events executed in the computation such that it preserves the order of events within each P_i . Since all events executed by a process P_i are totally ordered, it is sufficient to record the number of events executed by each process in a global state. Let G[i] be the number of proposal made by P_i . Initially, G[i] is 0 for all men. If P_i has made G[i] > 0 proposals, then mpref[i][G[i]] gives the identity of the woman last proposed by P_i . We let event(i, G[i]) denote the event in which P_i makes a proposal to mpref[i][G[i]]. We also use succ(event(i, G[i])) to denote the next proposal made by P_i , if any.

For the constrained SMP, we have \rightarrow_p edges that relate proposals of different processes. The second graph in Fig. 3 shows an example of using \rightarrow_p edges in the constrained SMP. For this problem, we work with *consistent global states* (or order ideals [5]).

Definition 4 (Consistent Global State). A global state $G \subseteq E$ is consistent if $\forall e, f \in E : (e \rightarrow_p f) \land (f \in G) \Rightarrow (e \in G)$.

In the context of constrained SMP, it is easy to verify that G is consistent iff for all j, there does not exist i such that $succ(event(j, G[j])) \rightarrow_p event(i, G[i])$ (otherwise, by letting e = succ(event(j, G[j])) and f = event(i, G[i]), we get a contradiction to consistency).

mpref					wpref				
P_1	w_4	w_1	w_2	w_3	w_1	P_4	P_1	P_3	P_2
P_2	w_2	w_3	w_1	w_4	w_2	P_1	P_4	P_2	P_3
P_3	w_3	w_1	w_4	w_2	w_3	P_1	P_2	P_4	P_3
P_4	w_2	w_4	w_3	w_1	w_4	P_3	P_1	P_4	P_2

Fig. 2. Stable Matching Problem with men preference list (mpref) and women preference list (wpref).

It is well known that the set of all consistent global states of a finite poset forms a finite distributive lattice [5]. We use the lattice of all consistent global states as L for the predicate detection.

In the standard SMP, women's preferences are specified by preference lists wpref such that wpref[i][k] gives the k^{th} most preferred man for woman *i*. It is also convenient to define rank such that rank[i][j] gives the choice number k for which wpref[i][k] equals j, i.e., wpref[i][k] = j iff rank[i][j] = k. We model these preferences using edges on the computation graph as follows. If an event e corresponds to a proposal by P_i to woman q and she prefers P_j , then we add a dashed (green) edge from e to the event f that corresponds to P_j proposing to woman q. The set E along with the dashed edges also forms a partial order (E, \rightarrow_w) where $e \rightarrow_w f$ iff both proposals are to the same woman and that woman prefers the proposal fto e. It is important to note that the definition of a consistent global state only refers to \rightarrow_p . The relation \rightarrow_w is used only to define the feasible predicate later. With $((E, \rightarrow_p), \rightarrow_w)$ we can model any SMP specified using mpref and wpref as shown in Fig. 2. The first graph in Figure 3 gives an example of a standard SMP. To avoid cluttering the figure, we have shown preferences of all men but preferences of only the woman w_1 . The woman w_1 has highest preference for P_4 , followed by P_1 , P_3 and P_2 . Note that an arrow in \rightarrow_p for the same man goes from the more preferred woman to the less preferred woman, but an arrow in \rightarrow_w for the same woman goes from the less preferred man to the more preferred man.

The second graph in Fig 3 gives a constrained SMP. Since both \rightarrow_p and \rightarrow_w are transitive relations, we draw only the transitively reduced diagrams.




Fig. 3. The first graph models the standard SMP problem. Men's preferences are shown in blue solid edges. Preferences of women 1 and 2 are shown in dashed green edges. The second constrained SMP Graph corresponds to constraint that the *regret* for P_2 is less than or equal to that of P_1 . It also shows the preference of w_3 of P_4 over P_3 .

The above discussion motivates the following definition.

Definition 5 (Constrained SMP Graph). Let $E = \{(i, j) | i \in [1..n] \text{ and } j \in [1..n]\}$. A Constrained SMP Graph $((E, \rightarrow_p), \rightarrow_w)$ is a directed graph on E with two sets of edges \rightarrow_p and

 \rightarrow_w with the following properties: (1) (E, \rightarrow_p) is a poset such that the set $P_i = \{(i, j) | j \in [1..n]\}$ is a chain for all *i*, and (2) (E, \rightarrow_w) is a poset such that the set $Q_j = \{(i, j) | i \in [1..n]\}$ is a chain for all *j* and there is no \rightarrow_w edge between proposals to different women, i.e., for all $i, j, k, l : (i, j) \rightarrow_w (k, l) \Rightarrow$ (j = l).

Given a global state G, we define the *frontier* of G as the set of maximal events executed by any process. The frontier includes only the last event executed by P_i (if any). Formally, frontier $(G) = \{e \in G \mid \forall f \in G \text{ such that} f \neq e, f \text{ and } e \text{ are executed by } P_i \text{ implies } f \rightarrow_p e \}$. We call the events in G that are not in frontier(G)as pre-frontier events. For example, suppose that $G = \{(P_1, w_4), (P_1, w_1), (P_2, w_2), (P_3, w_3), (P_3, w_1), (P_4, w_2)\}$ in Fig. 3. Then,

frontier(G) = {
$$(P_1, w_1), (P_2, w_2), (P_3, w_1), (P_4, w_2)$$
}

and pre-frontier $(G) = \{(P_1, w_4), (P_3, w_3)\}.$

We now define the feasible predicate on global states as follows.

Definition 6 (feasibility for marriage). A global state G is feasible for marriage iff (1) every man has made at least one proposal (2) G is a consistent global state, and (3) there is no green edge (\rightarrow_w) from a frontier event to any event of G(frontier or pre-frontier). Formally, $B_{marriage}(G) \equiv$ $(\forall i : G[i] > 0) \land consistent(G) \land (\forall e \in frontier(G), \forall g \in$ $G : \neg(e \rightarrow_w g).$

A green edge from a frontier event (i, j) to another frontier event (k, l) would imply that j is equal to l and both men i and k are assigned the same woman which violates the matching property. For example, in Fig. 3, (P_3, w_3) and (P_4, w_3) cannot both be frontier events of an feasible global state. A green edge from a frontier event (i, j) to a pre-frontier event (k, l)in a global state G implies that woman j prefers man k to her partner i and man k prefers j to his partner in G. For example, in Fig. 3, (P_3, w_3) and (P_4, w_1) cannot both be frontier events of an feasible global state because there is a green edge from (P_3, w_3) to a pre-frontier event (P_4, w_3) .

It is easy to verify that the problem of finding a stable matching is the same as finding a global state that satisfies the predicate $B_{marriage}$ which is defined purely in graph-theoretic terms on the constrained SMP graph. The next task is to show that $B_{marriage}$ is lattice-linear.

Theorem 2. For any global state G that is not a constrained stable matching, there exists a j such that forbidden $(G, j, B_{marriage})$.

Proof. First suppose that some process j has not made any proposal (i.e., G[j] = 0), then clearly unless process j is advanced, the predicate $B_{marriage}$ cannot hold. Now suppose that G is not a consistent global state. This means that there exists an event e, say on P_j , such that $e \rightarrow_p f$ for some event $f \in G$, but $e \notin G$. Again, unless G is advanced on P_j , the global state cannot become consistent and hence j

is forbidden in G. Finally, suppose that there exists a green edge from a frontier event of G, G[j] to another event $g \in G$. Consider H such that $G \subseteq H$ and G[j] = H[j]. We now have that H[j] is a frontier event and it has a green edge to g. Since g is an event in G, it is also included in all global states greater than G. Hence, H is also not feasible. Therefore, forbidden(G, j, B).

We now apply the detection of lattice-linear global predicates for the constrained stable matching.

Fig. 4. An efficient algorithm to find the man-optimal constrained stable matching less than or equal to T

 $\alpha(G, j, B_{marriage}) = (G[j] + 1);$

The algorithm to find the man-optimal constrained stable marriage is shown in Fig. 4. From the proof of Theorem 2, we get the following implementation of forbidden $(G, j, B_{marriage})$ in Fig. 4. The first disjunct in the function forbidden holds when the assignment for G is null with respect to j. The second disjunct holds when the woman z assigned to man j is such that there exists a man i who is either (1) currently assigned to z and woman z prefers man i, or (2) is currently assigned to another woman but he prefers z to the current assignment. The first case holds when k = G[i] and the second case holds when k < G[i]. The first case is equivalent to checking is a green edge exists from (j, z) to a frontier event. The second case is equivalent to checking if a green edge exists to a pre-frontier event. The third disjunct checks that the assignment for G satisfies all external constraints with respect to j.

Our algorithm generalizes the Gale-Shapley algorithm in that it allows specification of external constraints. It is easy to see that the third disjunct $(\exists i : succ(event(j, G[j])) \rightarrow_p event(i, G[i]))$ is not necessary when there are no external constraints. It can also be shown that the second disjunct can be simplified to $(\exists i : (z = mpref[i][G[i]]) \land (rank[z][i] < rank[z][j]))$ in the absence of external constraints. On removing the third disjunct and simplifying the second disjunct, we get the Gale-Shapley algorithm as a special case of our algorithm. In every iteration of *LLP*, we need to find *j* such that forbidden(*G*, *j*, *B*) holds. By keeping a list of *j* such that G[j] is equal to 0, finding *j* that satisfies the first disjunct can be done in O(1) time. By keeping the rank of the most preferred man that has proposed to any woman with the woman, and the list of men that have been rejected, finding *j* that satisfies the second disjunct can also be done in O(1) time. For the standard matching problem, these two disjuncts are sufficient and we get the overall time complexity of $O(n^2)$ which is identical to that of the Gale-Shapley algorithm.

We note here that existence of a stable matching via Tarski's theorem is shown by Adachi [1]. Our interest is not in the existence (and occasionally there may not be any solution to the constrained stable marriage problem), but the computation of the constrained stable marriage whenever it exists.

IV. CONSTRAINED SINGLE SOURCE SHORTEST PATH Algorithm

In this section, we first model the traditional shortest path problem and later generalize it to incorporate constraints. Consider a weighted directed graph with n vertices numbered 0 to n-1. We assume that all edge weights are *strictly positive*. We are required to find the minimum cost of a path from a distinguished *source* vertex v_0 to all other vertices where the cost of a path is defined as the sum of edge weights along that path. For any vertex v, let pre(v) be the set of vertices usuch that (u, v) is an edge in the graph. To avoid trivialities, assume that every vertex v (except possibly the source vertex v_0) has nonempty pre(v).

As the first step of the predicate detection algorithm, we define the lattice for the search space. We assign to each vertex v_i , $G[i] \in \mathbf{R}_{\geq 0}$ with the interpretation that G[i] is the cost of reaching vertex v_i . We call G, the *assignment* vector. The invariant maintained by our algorithm is: for all i, the cost of any path from v_0 to v_i is greater than or equal to G[i].




Fig. 5. (a) A Weighted Directed Graph (b) The parent structure for G = (0, 2, 3, 5, 8) (c) The parent structure for G = (0, 10, 3, 14, 8). Since every non-source node has at least one parent, G is feasible.

The second step in the predicate detection algorithm is to define an appropriate *feasibility* predicate. The vector G only gives the lower bound on the cost of a path and there may not be any path to vertex v_i with cost G[i]. To capture that an assignment is feasible, we define *feasibility* which requires the notion of a *parent*. We say that v_i is a parent of v_j in G (denoted by the predicate parent(j, i, G)) iff there is a direct edge from v_i to v_j and G[j] is at least (G[i] + w[i, j]), i.e.,

 $(i \in pre(j)) \land (G[j] \ge G[i] + w[i, j])$. In Fig. 5, let G be the vector (0, 2, 3, 5, 8). Then, v_0 is a parent of v_2 because G[2] is greater than G[0] plus $w[0, 2](i.e., 3 \ge 0 + 2)$. Similarly, v_1 is a parent of v_4 because $G[4] \ge G[1] + 2$. A node may have multiple parents. The node v_2 is also a parent of v_4 because $G[4] \ge G[2] + 5$. Since w[i, j] are strictly positive, there cannot be a cycle in the parent relation. Now, feasibility can be defined as follows.

Definition 7 (feasible for paths). An assignment G is feasible for paths iff every node except the source node has a parent. Formally, $B_{path}(G) \equiv \forall j \neq 0 : (\exists i : parent(j, i, G)).$

Hence, an assignment G is feasible iff one can go from any non-source node to the source node by following any of the parent edges. In Fig. 5, the vector G = (0, 10, 3, 14, 8) is feasible because every non-source node has at least one parent. One can go from v_3 to v_0 either via v_1 or v_2 .

As the third step of our method, we now show that feasibility satisfies lattice-linearity.

Lemma 3. For any assignment vector G that is not feasible, $\exists j : \text{forbidden}(G, j, B_{path}(G)).$

Proof. Suppose G is not feasible. Then, there exists $j \neq v_0$ such that v_j does not have a parent, i.e., $\forall i \in pre(j) : G[j] < G[i] + w[i, j]$. Of all nodes that do not have any parent, let j be such that it has the least value of G[j]. If there are multiple j with the same value of G[j], then we choose any j. We show that forbidden $(G, j, B_{path}(G))$ holds. Pick any H such that $H \geq G$. Since for any $i \in pre(j)$, $H[i] \geq G[i]$, G[j] < G[i] + w[i, j] implies that G[j] < H[i] + w[i, j]. Therefore, whenever H[j] = G[j], v_j does not have a parent.

Remark. Since B_{path} is a lattice-linear predicate, it follows from Lemma 1(c), that the set of feasible assignment vectors are closed under meets (the component-wise min operation). Unlike the constrained stable matching problem, the set of feasible assignment vectors are not closed under the join operation. In Fig. 5, the vectors (0, 10, 3, 14, 8) and (0, 9, 10, 12, 11) are feasible, but their join (0, 10, 10, 14, 11) is not feasible.

Lemma 4. Suppose $\neg B_{path}(G)$. Then, $(\forall i : \neg parent(j, i, G)) \Rightarrow$ forbidden $(G, j, B_{path}, \alpha(G, j))$ for any $j \neq 0$, where $\alpha(G, j, B_{path}) = \min\{G[i] + w[i, j] \mid i \in pre(j)\}.$

Proof. It is sufficient to observe that $\alpha(G, j)$ is the minimum amount that G[j] must increase to have a parent.

Use Algorithm <i>LLP</i> with
$T = (M, M, \dots, M)$, where $M = n * \max_{i,j:i \in pre(j)} w[i, j]$
$parent(j, i, G) \equiv (i \in pre(j)) \land (G[j] \ge G[i] + w[i, j])$
$forbidden(G, j, B_{path}) \equiv \forall i : \neg parent(j, i, G)$
$\alpha(G, j, B_{path}) = \min\{G[i] + w[i, j] \mid i \in pre(j)\}$

Fig. 6. Algorithm $ShortestPath_a$ to find the minimum cost assignment vector less than or equal to T

We now have our first algorithm for computing the cost of the shortest path from a source vertex. The algorithm called Shortest Path_a (Lattice-Linear Shortest Path) shown in Fig. 6 finds the minimum cost assignment vector G less than or equal to T that is feasible. We note that the algorithm returns null if any vertex in the graph is not reachable from the source vertex because there is no assignment vector less than or equal to T that is feasible. If one wants the algorithm to find the shortest path to a specific target vertex, then the algorithm can be modified to delete the unreachable vertex from the graph (and the corresponding component from G array) and then continue until either the desired target vertex is deleted or there exists no forbidden vertex. If there is no forbidden vertex in G, then any component j of G has the cost of the shortest path from the source vertex to j.

For an unweighted graph (i.e., each edge has weight equal to 1), the above parallel algorithm requires time equal to the distance of the farthest node from the root. However, for a weighted graph, it may take non-polynomial time in the number of nodes because the advancement along a forbidden process may be small.

We now give an alternative feasible predicate that results in an algorithm that takes bigger steps. We first define a node j to be *fixed* in G if either it is the source node or it has a parent that is a fixed node, i.e., $fixed(j,G) \equiv (j=0) \lor (\exists i : parent(j,i,G) \land fixed(i,G)).$

Observe that node v_0 is always fixed. Any node v_j such that one can reach from v_j to v_0 using parent relation is also fixed. We now define another feasible predicate called B_{rooted} , as

$$B_{rooted}(G) \equiv \forall j : fixed(j,G).$$

Even though it may first seem that the predicate B_{rooted} is strictly stronger than B_{path} , the following Lemma shows otherwise.

Lemma 5.
$$B_{path}(G)$$
 iff $B_{rooted}(G)$.

Proof. If G satisfies B_{rooted} , then every node other than v_0 has at least one parent by definition of fixed, hence $B_{path}(G)$. Conversely, suppose that every node except v_0 has a parent. Since parent edges cannot form a cycle, by following the parent edges, we can go from any node to v_0 .

It follows that the predicate B_{rooted} is also lattice-linear. An advantage of the predicate B_{rooted} is that it allows us to define a different α for advancement whenever the assignment vector G is not B_{rooted} . Suppose that $\neg B_{rooted}(G)$. Then, the following threshold $\beta(G)$ is well-defined whenever the set of edges from the fixed vertices to non-fixed vertices is nonempty.

$$\beta(G) = \min_{(i,j):i \in pre(j)} \{G[i] + w[i,j] \mid fixed(i,G), \neg fixed(j,G)\}$$

If the set of such edges is empty then no non-fixed vertex is reachable from the source.

We now have the following result in advancement of G.

Lemma 6. Suppose $\neg B_{rooted}(G)$. Then, $\neg fixed(j,G) \Rightarrow$ forbidden $(G, j, B_{rooted}, \beta(G))$.

Proof. Consider any assignment vector H such that $H \ge G$ and $H[j] < \beta(G)$. We show that H is not B_{rooted} . In particular,

we show that j is not fixed in H. Suppose j is fixed in H. This implies that there is a path W from v_0 to v_j such that all nodes in that path are fixed. Let the path be the sequence of vertices $w_0, w_1, \ldots, w_{m-1}$, where $w_0 = v_0$ and $w_{m-1} = v_j$. Let $w_l = v_k$ be the first node in the path that is not fixed in G. Such a node exists because w_{m-1} is not fixed in G. Since w_0 is fixed, we know that $1 \le l \le m - 1$. The predecessor of w_l in that path, w_{l-1} is well-defined because $l \ge 1$. Let $w_{l-1} = v_i$.

We show that $H[k] \ge \beta(G)$ which contradicts $H[j] < \beta(G)$ because $H[k] \le H[j]$ as the cost can only increase going from k to j along the path W. We have $H[k] \ge H[i] + w[i, k]$ because i is a parent of k in H. Therefore, $H[k] \ge G[i] + w[i, k]$ because $H[i] \ge G[i]$. Since i is fixed in G and k is not fixed in G, from the definition of $\beta(G)$, we get that $\beta(G) \le$ G[i] + w[i, k]. Hence, $H[k] \ge \beta(G)$.

By combining the advancement Lemma 6 with Lemma 4, we get the algorithm $ShortestPath_b$ shown in Fig. 7. In this algorithm, in every iteration of the while loop we find an edge going from a fixed node *i* to a non-fixed node *j* that minimizes G[i]+w[i, j]. All nodes are advanced to $\alpha(G, j)$ that combines $\beta(G)$ with $\alpha(G, j)$ of the algorithm $ShortestPath_a$ as shown in Fig. 7. Note that if a node is fixed, its parent is fixed and therefore any algorithm that advances G[j] only for non-fixed nodes *j* maintain that once a node becomes fixed it stays fixed.

In the graph of Fig. 5, G is initially (0,0,0,0,0). After the first iteration, $\beta(G) = 2$ and $\alpha(1,G) = 9, \alpha(2,G) = 2, \alpha(3,G) = 3, \alpha(4,G) = 2$. Therefore, G becomes (0,9,2,3,2). At this point, nodes v_0, v_1 and v_2 are fixed. In the second iteration, $\beta(G) = 7$, $\alpha(3,G) = \max(7,\min(12,8,10)) = 8$ and $\alpha(4,G) = \max(7,\min(11,7)) = 7$. Hence, G = (0,9,2,8,7). At this point, all nodes are fixed and the algorithm terminates.

We first note that by removing certain steps, we get Dijkstra's algorithm from the algorithm $ShortestPath_b$. It is clear that the algorithm stays correct if $\alpha(G, j)$ uses just $\beta(G)$ instead of $\max\{\beta(G), \min\{G[i] + w[i, j] \mid i \in pre(j)\}\}$. Secondly, the algorithm stays correct if we advance G only on the node j such that $(i, j) \in E'$ minimizes G[i] + w[i, j]. Finally, to determine such a node and $\beta(G)$, it is sufficient to maintain a min-heap of all non-fixed nodes j, along with the label that equals $\min_{i \in pre(j), fixed(i,G)} G[i] + w[i, j]$. On making all these changes to $ShortestPath_b$, we get Dijkstra's algorithm (modified to run with a heap).

The $ShortestPath_b$ algorithm and indeed all the algorithms $\}$. in this paper have a single variable G. All other predicates and functions are defined using this variable.

We now consider the generalization of the shortest path algorithm with constraints. We assume that all constraints specified are lattice-linear. For example, consider the following constraints:

 Find the minimum cost vector such that cost of vertex *i* is at most cost of vertex *j*. The predicate B ≡ G[*j*] ≥ G[*i*] is easily seen to be lattice-linear. If any cost vector G violates Use Algorithm *LLP* with $T = (M, M, \dots, M), \text{ where } M = n * \max_{i,j} w[i, j]$ $parent(j, i, G) \equiv (i \in pre(j)) \land (G[j] \ge G[i] + w[i, j])$ $fixed(j, G) \equiv (j = 0) \lor (\exists i : parent(j, i, G) \land fixed(i, G))$ $forbidden(G, j) \equiv \neg fixed(j, G)$ $E' := \{ (i, k) \mid i \in pre(k) \land fixed(i, G) \land \neg fixed(k, G) \};$ $\beta(G) = \min\{G[i] + w[i, j] \mid (i, j) \in E'\}$ $\alpha(G, j) = \max\{\beta(G), \min\{G[i] + w[i, j] \mid i \in pre(j)\}\}$

Fig. 7. Algorithm $ShortestPath_b$ to find the minimum cost assignment vector less than or equal to T.

B, then the component j is forbidden (with $\alpha(G, j)$ equal to G[i]).

- The predicate (G[i] = G[j]) is lattice-linear because it can be written as a conjunction of two lattice-linear predicates (G[i] ≥ G[j]) and (G[j] ≥ G[i]).
- The predicate B ≡ (G[i] ≥ k) ⇒ (G[j] ≥ m) is also lattice-linear. If any cost vector violates B, then we have (G[i] ≥ k) ∧ (G[j] < m). In this case, the component j is forbidden with α(G, j) equal to m.
- The predicate $B \equiv (\forall i : G[i] \ge F[i])$ for any fixed vector F is lattice-linear. It is sufficient to show that $(G[i] \ge F[i])$ is lattice-linear. If the predicate $(G[i] \ge F[i])$ is false, then the component i is forbidden with $\alpha(G, j)$ equal to F[i].

Again, from Lemma 2, the algorithm LLP can be used to solve the constrained shortest path algorithm by combining forbidden and α for constraints with B_{rooted} .

An example of a predicate that is not lattice-linear is $B \equiv G[i] + G[j] \geq k$. If the predicate is false for G, then we have G[i] + G[j] < k. However, neither i nor j may be forbidden. The component i is not forbidden because if G[i] is fixed but G[j] is increased, the predicate B can become true. Similarly, j is also not forbidden.

V. CONSTRAINED MARKET CLEARING PRICE

In this section, we apply our technique to the problem of finding a market clearing price with constraints. Let I be a set of indivisible n items, and U, a set of n bidders. Every item $i \in I$ is given a valuation $v_{b,i}$ by each bidder $b \in U$. The valuation of any item i is a number between 0 and T[i]. Each item i is given a price G[i] which is also a number between 0 and T[i]. We are assuming integral costs for simplicity — the algorithm is easily extensible to real costs.

Given a price vector G, we define the bipartite graph (I, U, E(G)) as

$$(j,b) \in E(G) \equiv \forall i : (v_{b,j} - G[j]) \ge (v_{b,i} - G[i]).$$

Informally, an edge exists between item i and bidder b if the payoff for the bidder (the bid minus the price) is maximized with that item. Given any set $U' \subseteq U$, let N(U', G) denote all the items that are adjacent to the vertices in U' in the graph (I, U, E(G)). A price vector G is a market clearing price, denoted by $B_{clearingPrice}(G)$ if the bipartite graph (I, U, E(G)) has a perfect matching. We now generalize the problem of finding a market clearing price to that of


finding a constrained market clearing price. Given any set of valuations, and a boolean predicate B that is a conjunction of lattice-linear constraints, a price vector G is a *constrained* market clearing price, denoted by *constrainedClearing*(G) iff clearing(G) $\land B(G)$. From Lemma 2, it is sufficient to give an algorithm for clearing(G).

We now claim that

Lemma 7. The predicate $B_{clearingPrice}(G)$ is a lattice-linear predicate on the lattice of price vectors.

Proof. From $\neg B_{clearingPrice}(G)$, we get that (I, U, E(G)) does not have a perfect matching. From Hall's theorem, there exists a *minimal* set of over-demanded items J, i.e., there exists a set of bidders U' with item set J = N(U', G) such that the size of J is smaller than U' and no proper subset of J is over-demanded. It can be shown that any item $j \in J$ satisfies forbidden $(j, G, B_{clearingPrice})$ (from the proof of Theorem 1 in [6]).

Use Algorithm LLP with
$\forall i: T[i] = \max_b v_{b,i}$
$E(G) = \{(i,b) \mid \forall j : (v_{b,i} - G[i]) \ge (v_{b,j} - G[j])\}$
$overDemanded(J,G) \equiv \exists U' \subseteq U : (J = N(U',G))$
$\wedge (J < U')$
$minimalOverDemanded(J,G) \equiv overDemanded(J,G)$
$\land \forall J' \subseteq J : overDemanded(J', G) \Rightarrow (J' = J)$
forbidden $(G, j, B_{clearingPrice}) \equiv$
$\exists J: minimalOverDemanded(J,G) \land (j \in J)$
$\alpha(G, j, B_{clearingPrice}) = (G[j] + 1);$



It follows that the set of constrained market clearing price vectors is closed under meets. By applying the lattice-linear predicate detection, we get an algorithm to compute the least constrained market clearing price shown in Fig. 8. In conjunction with Lemma 2, we get a generalization of Demange, Gale and Sotomayor's exact auction mechanism [6] to incorporate lattice-linear constraints on the market clearing price.

In Fig. 8, we have used $\alpha(G, j)$ as simply one unit of price. For any item j that is part of a minimal over-demanded set of items, we can increase its price by the minimum amount to ensure that some bidder b can switch to her second most preferred item.

VI. COMPUTING ALL CONSTRAINED STABLE MATCHINGS

We now consider the problem of computing all constrained stable matchings. Since the number of stable matchings may be exponential in n, instead of keeping all matchings in explicit form, we would like a concise representation of polynomial size that can be used to enumerate all constrained stable matchings. In SMP literature, rotation posets are used to capture all stable matchings. We give a method based on a constructive version of Birkhoff's Theorem that can be used to capture all stable matchings that satisfy external constraints [2], [13]. A rotation poset [10] is a special case of our method when the set of external constraints is empty.

We first define the dual concept of a lattice-linear predicate. Just as a lattice-linear predicate allows us to start with the bottom element of the lattice and advance in the forward direction, its dual allows us to start with the top element and advance in the backward direction. Given any distributive lattice L of n-dimensional vectors, and any predicate B, we say reverse-forbidden $(G, i, B) \equiv \forall H \in L : H \leq G : (G[i] = H[i]) \Rightarrow \neg B(H)$. Observe that for *forbidden*, we considered $H \geq G$, whereas for reverse-forbidden, we consider $H \leq G$. We define a predicate B to be *post-lattice-linear* if for any $G \in L$, B is false in G implies that G contains a *reverse-forbidden state*. Formally, A boolean predicate B is *post-lattice-linear* iff: $\forall G \in L : \neg B(G) \Rightarrow \exists i : reverse-forbidden(G, i, B)$ It can be shown that $B_{marriage}$ is not only lattice-linear but

also post-lattice-linear.

Since constrained stable matching is a post-lattice-linear predicate, from the dual of Lemma 1(b) it follows that the *feasible set*, the set of assignments satisfying $B_{marriage}$, is also closed under joins. Therefore, the feasible set forms a sublattice of the lattice of all assignments. Since a sublattice of a distributive lattice is also distributive, the set of assignments that satisfy constrained stable marriage forms a finite distributive lattice. From Birkhoff's theorem [5] we know that a finite distributive lattice can be equivalently represented using the poset of its join-irreducible elements. We now show that joinirreducible elements of the feasible sublattice can be constructed efficiently (i.e. without constructing the sublattice which may be exponential in n in its size). The set of all elements of L satisfying B can be generated as the order ideals of the following poset $(\{J(B,e)|e \in E\}, \subseteq)$ where J(B,e) is the minimum order ideal of (E, \leq) that satisfies B and contains e. It can be verified that J(B, e) is a join-irreducible element and that every join-irreducible element is of this form. Interested readers can find details in [13]. The poset $(\{J(B, e) | e \in E\}, \subseteq)$ is called a *slice* in [13].

Hence, to compute the slice, it is sufficient to give a procedure to compute J(B, e). To determine J(B, e) it is sufficient to use the algorithm for detecting a lattice-linear predicate by using the following predicate for every $e: B_e(G) \equiv B(G) \land (e \in G)$. Since B is a lattice-linear predicate, and the predicate $e \in G$ is also lattice-linear, $B_e(G)$ is also lattice-linear. Therefore, by using the algorithm for the constrained stable marriage introduced in this paper, we also get an algorithm to compute the slice.

We illustrate this procedure by computing $J(B, (P_1, w_2))$. We start with $[w_1, w_3, w_4, w_2]$ since $J(B, (P_1, w_1)) = [w_1, w_3, w_4, w_2]$. On changing the assignment of P_1 to w_2 , we get $[w_2, w_3, w_4, w_2]$. Since w_2 prefers P_1 to P_4 , we advance on P_4 to get $[w_2, w_3, w_4, w_4]$. Since w_4 prefers P_3 , we advance again on P_4 to get $[w_2, w_3, w_4, w_3]$. Since w_3 prefers P_2 , we advance on P_4 to get $[w_2, w_3, w_4, w_3]$. Since w_3 prefers P_2 , we advance on P_4 to get $[w_2, w_3, w_4, w_3]$. This is a constrained stable matching.

By computing the set $\{J(B, e) | e \in E\}$, in this manner, we can compute the slice for any constrained SMP graph.

An analogous method can be used to compute a concise representation of all constrained market clearing prices when the prices are integral.

VII. CONCLUSIONS AND FUTURE WORK

We have shown that many combinatorial optimization problems can be solved by applying our lattice-linear predicate algorithm LLP. Specifically, we have shown that more general versions of the stable matching problem, the single source shortest path problem and the market clearing prices problem can be solved using LLP.

There are many future directions for this work. Are there efficient lattice-linear predicate detection based parallel algorithms for the max-flow problem? Can the properties of the lattices be exploited to speed up the computation? Are there efficient methods when the feasibility predicate is not lattice-linear?

VIII. ACKNOWLEDGEMENTS.

I thank Calvin Ly and Rohan Garg for many discussions on this topic. I also thank Calvin Ly for implementing a version of LLP algorithm in Java.

REFERENCES

- Hiroyuki Adachi. On a characterization of stable matchings. *Economics Letters*, 68(1):43–49, 2000.
- [2] G. Birkhoff. Lattice Theory. Providence, R.I., 1967. third edition.
- [3] Craig M Chase and Vijay K Garg. Detection of global predicates: Techniques and their limitations. *Distributed Computing*, 11(4):191–201, 1998.
- [4] Agnes Cseh and David F. Manlove. Stable marriage and roommates problems with restricted edges: Complexity and approximability. *Discrete Optimization*, 20:62 – 89, 2016.
- [5] B. A. Davey and H. A. Priestley. Introduction to Lattices and Order. Cambridge University Press, Cambridge, UK, 1990.
- [6] Gabrielle Demange, David Gale, and Marilda Sotomayor. Multi-item auctions. Journal of Political Economy, 94(4):863–872, 1986.
- [7] Vnia M.F. Dias, Guilherme D. da Fonseca, Celina M.H. de Figueiredo, and Jayme L. Szwarcfiter. The stable marriage problem with restricted pairs. *Theoretical Computer Science*, 306(1):391 – 405, 2003.
- [8] E. W. Dijkstra. A note on two problems in connexion with graphs. Numerische Mathematik, 1(1):269–271, Dec 1959. URL: https://doi.org/ 10.1007/BF01386390, doi:10.1007/BF01386390.
- [9] David Gale and Lloyd S Shapley. College admissions and the stability of marriage. *The American Mathematical Monthly*, 69(1):9–15, 1962.
- [10] Dan Gusfield and Robert W Irving. The stable marriage problem: structure and algorithms. MIT press, 1989.
- [11] Donald Ervin Knuth. Stable marriage and its relation to other combinatorial problems: An introduction to the mathematical analysis of algorithms, volume 10. American Mathematical Soc., 1997.
- [12] J-L. Lassez, V. L. Nguyen, and E. A. Sonenberg. Fixed point theorems and semantics: a folk tale. *Information Processing Letters*, 14(3):112–116, 1982.
- [13] Neeraj Mittal and Vijay K Garg. Computation slicing: Techniques and theory. In *International Symposium on Distributed Computing*, pages 78–92. Springer, 2001.
- [14] James Munkres. Algorithms for the assignment and transportation problems. *Journal of the society for industrial and applied mathematics*, 5(1):32–38, 1957.
- [15] Lloyd S Shapley and Martin Shubik. The assignment game i: The core. International Journal of game theory, 1(1):111–130, 1971.
- [16] Alfred Tarski. A lattice-theoretic fixed point theorem and its applications. *Pacific J Math*, 5:285–309, 1955.