

ON THE SUPERSINGULAR GPST ATTACK

ANDREA BASSO AND FABIEN PAZUKI

ABSTRACT. We explain why the first Galbraith-Petit-Shani-Ti attack on the Supersingular Isogeny Diffie-Hellman and the Supersingular Isogeny Key Encapsulation fails in some cases.

Keywords: Isogenies, Supersingular elliptic curves, Modular invariants.

Mathematics Subject Classification: 14H52, 14K02, 11T71, 94A60, 81P94, 65P25.

1. INTRODUCTION

In 2011, De Feo and Jao [DFJ11] introduced Supersingular Isogeny Diffie-Hellman (SIDH), a post-quantum key exchange protocol that mimics the Diffie-Hellman protocol in the settings of isogenies between supersingular curves. In 2014, Jao, De Feo and Plüt [DFJP14] built upon SIDH to obtain a key encapsulation scheme called Supersingular Isogeny Key Encapsulation (SIKE).

We recently carried out a study of one of the most relevant attacks against SIDH and SIKE, namely the first attack presented in [GPST16]. We call it the Galbraith-Petit-Shani-Ti attack, or GPST. It is an active attack where the attacker impersonates one of the two parties and can recover the static key of the other party in about as many interactions as the number of bits of the key. We will show in Section 2 that the attack may fail in some precise circumstances.

Preliminaries. For an elliptic curve E defined over a field k , we denote the base point of the elliptic curve by \mathcal{O} and the modular invariant of E by $j(E)$. The invariant is an element of k that characterizes the \bar{k} -isomorphism class of E . For $P \in E(k)$ rational over k , we denote by $\langle P \rangle$ the subgroup of $E(k)$ generated by P .

The parameters of the SIDH protocol, in the form and notation of [GPST16], are the following:

- A prime $p = 2^n 3^m f - 1$, where n, m, f are natural numbers, f is small and $2^n \approx 3^m$.
- A supersingular elliptic curve E_0 defined over \mathbb{F}_{p^2} .
- Points $P_A, Q_A \in E_0$ which form a basis of $E_0[2^n]$ and points $P_B, Q_B \in E_0$ which form a basis of $E_0[3^m]$.

We refer the reader to the original paper [GPST16] for the presentation of the attack. We introduce here the two assumptions that are required for the GPST attack to take place:

Both authors thank Christophe Petit and Christophe Ritzenthaler for interesting feedback. The second author is a member of the project ANR-17-CE40-0012 Flair.

- (a) Alice uses a static key (a_1, a_2) . The values a_1, a_2 are elements of $\mathbb{Z}/2^n\mathbb{Z}$, not both divisible by 2.
- (b) The attacker has access to an oracle O such that, if E, E' denote supersingular elliptic curves defined over \mathbb{F}_{p^2} and R, S denote any two points on E ,

$$(1) \quad O(E, R, S, E') = \begin{cases} \text{true}, & \text{if } j(E/\langle [a_1]R + [a_2]S \rangle) = j(E'), \\ \text{false}, & \text{otherwise.} \end{cases}$$

Such an oracle can be realized in practice by having a mechanism in place that ensures the two parties obtain the same shared key.

The attacker does not need any additional information, which makes the GPST attack one of the most powerful attacks known in the literature.

2. ATTACKING THE ATTACK

Alice's static key (a_1, a_2) is always equivalent (*i.e.* it leads to the same key exchange) to a key of the form $(1, \alpha)$ or $(\alpha, 1)$, where α is again an element of $\mathbb{Z}/2^n\mathbb{Z}$ [GPST16, Lemma 2.1]. Without loss of generality, we may assume we are in the former case.

Each iteration of the GPST attack relies on the following implication, used in the paragraph *First step of the attack* of [GPST16]:

$$(2) \quad \left(j(E/\langle T_1 \rangle) = j(E/\langle T_2 \rangle) \right) \Rightarrow \left(\langle T_1 \rangle = \langle T_2 \rangle \right)$$

to recover a single bit of the key. In particular, the oracle query (1) is used to recover whether $\langle R' + \alpha S' \rangle$ is equal to $\langle R + \alpha S \rangle$, where R, S, R', S' are points on an elliptic curve computed by the attacker. The points R' and S' are chosen such that $\langle R' + \alpha S' \rangle = \langle R + \alpha S \rangle$ implies the i -th bit α_i of the key is a zero-bit. Thus, if the oracle returns *true*, then $\alpha_i = 0$, otherwise $\alpha_i = 1$.

However, implication (2) is not correct, because there exist pairs of elliptic curves E_1, E_2 with multiple isogenies between them. Thus, if ϕ_1 and ϕ_2 are distinct cyclic isogenies between E_1 and E_2 and K_1 and K_2 are their respective kernels, we have that E_1/K_1 is isomorphic to E_1/K_2 because they are both isomorphic to E_2 , but K_1 and K_2 may not be equal and need not even be isomorphic. Over \mathbb{Q} , a classical example can be found in [Sil94, page 110], namely the pair (E, E) , where E is the curve defined over \mathbb{Q} with $j(E) = 8000$, which is given by the affine Weierstrass equation $y^2 = x^3 + 4x^2 + 2x$. This curve E admits a rational 2-isogeny φ to itself (hence cyclic, and given explicitly in *loc. cit.*), and one computes $j(E/\ker \varphi) = 8000 = j(E)$, hence E and $E/\ker \varphi$ are in fact $\overline{\mathbb{Q}}$ -isomorphic, but clearly $\ker \varphi \neq \{O\}$.

Over a finite field of characteristic $p > 0$, if one starts with a supersingular elliptic curve E , then for any prime $\ell \neq p$, for any positive integer m and for any cyclic subgroup G of order ℓ^m , the elliptic curve E/G will also be supersingular, because there are still no points of order p on E/G . As there are only finitely many supersingular curves over $\overline{\mathbb{F}}_p$ (see for instance [Sil86, Theorem 4.1, pages 148-149]), there exist pairs of cyclic groups (G_1, G_2) where G_1 and G_2 are not isomorphic and such that E/G_1 is isomorphic to E/G_2 . This argument is used to compute the endomorphism ring of supersingular elliptic curves in [Sil86, page 146] (see also [Hus04, page 267]).

Let us give now a detailed example where the Galbraith-Petit-Shani-Ti attack fails to recover the private key of a SIDH key exchange.

Example 1. Let $p = 2^5 3^3 - 1 = 863$ be a prime and k be the finite field \mathbb{F}_{p^2} , considered as $\mathbb{F}_p(\beta)$, where β satisfies the quadratic equation $\beta^2 - \beta + 5 = 0$. Let E_0 be the supersingular elliptic curve with affine Weierstrass model $y^2 = x^3 + (531\beta + 538)x + (720\beta + 375)$ over k . Consider the points

$$\begin{aligned} P_A &= (834\beta + 726, 642\beta + 130), & Q_A &= (583\beta + 276, 180\beta + 854), \\ P_B &= (254\beta + 697, 516\beta + 268), & Q_B &= (753\beta + 317, 234\beta + 532). \end{aligned}$$

The points P_A, Q_A form a basis of $E_0[2^5]$, and P_B, Q_B form a basis of $E_0[3^3]$. Let Alice's key be of the form $(1, \alpha)$, with $\alpha = 10$ (written in base ten). The value α can also be expressed in bits as 1010 (written in base two). From now on, by a slight abuse of notation we refer to α as the key.

Let us now carry on the Galbraith-Petit-Shani-Ti attack. Assume the randomly generated values b_1, b_2 are $b_1 = 1, b_2 = 6$ (for simplicity, we assume b_1 and b_2 stay constant across iterations, but we only need $b_1 = 1, b_2 = 6$ in the second round for the attack to fail). Let ϕ_A be the isogeny with kernel $K_A = \langle P_A + [\alpha]Q_A \rangle$. Then $E_A = E_0/K_A$ has affine Weierstrass model $y^2 = x^3 + (40\beta + 535)x + (720\beta + 768)$. Let us begin the attack and let ϕ_B be the isogeny with kernel $K_B = \langle P_B + [6]Q_B \rangle$. Thus $E_B = E_0/K_B$ has affine Weierstrass model $y^2 = x^3 + 105x + 254$. Furthermore, we have

$$\begin{aligned} R &= \phi_B(P_A) = (151\beta + 257, 594\beta + 2), \\ S &= \phi_B(Q_A) = (98\beta + 386, 286\beta + 58). \end{aligned}$$

Note that since the degree of ϕ_B is coprime with the order of P_A and Q_A , the points R and S have also order 2^5 .

The first iteration of the attack starts by computing

$$\begin{aligned} \theta_0 &= \sqrt{(1 + 2^4)^{-1}} \pmod{2^5} = 7, \\ R'_0 &= [\theta_0]R = (527\beta + 129, 700\beta + 163), \\ S'_0 &= [\theta_0][1 + 2^4]S = (164\beta + 377, 566\beta + 641). \end{aligned}$$

It then proceeds by querying the oracle with $O(E_B, R'_0, S'_0, E_{AB}) = E_B / \langle \phi_A(P_B) + [6]\phi_A(Q_B) \rangle$. The curve $E_{AB} : y^2 = x^3 + 698x + (516\beta + 605)$ has j -invariant 117. The curve $E_B / \langle R'_0 + [\alpha]S'_0 \rangle$ also has j -invariant 117, thus the oracle response is true and the first (rightmost) bit of the key is a zero-bit. Hence the attack correctly obtains the first bit of the key.

For the second round, the attacker computes

$$\begin{aligned} \theta_1 &= \sqrt{(1 + 2^3)^{-1}} \pmod{2^5} = 5, \\ R'_1 &= [\theta_1]R = (97\beta + 261, 795\beta + 545), \\ S'_1 &= [\theta_1][1 + 2^3]S = (718\beta + 214, 450\beta + 844), \end{aligned}$$

and queries the oracle on $O(E_B, R'_1, S'_1, E_{AB})$. As before, the curves E_{AB} and $E_B / \langle R'_1 + [\alpha]S'_1 \rangle$ both have j -invariant 117, thus the oracle responds true. Hence this time the attacker incorrectly deduces the second bit (reading from right to left) of the key to be zero.

Brute-forcing the remaining bits does not yield any solution, since there is no key α ending with two zero-bits (00) such that $E_0 / \langle P_A + [\alpha]Q_A \rangle$ is isomorphic to E_A .

The previous example establishes that there exist cases where the attack fails. The following are sufficient conditions (when considered together) for the attack to fail at the i -th iteration

of the attack, for $1 \leq i < n - 3$ (the attack brute-forces the last three bits of the key and thus cannot fail after $n - 3$):

- (i) There exist two distinct isogenies ϕ_1 and ϕ_2 between E_B and E_{AB} .
- (ii) One has $R + [\alpha]S = P_1$ and $R'_i + [\alpha]S'_i = P_2$, where P_1 and P_2 are generators of the kernel of ϕ_1 and ϕ_2 , respectively.
- (iii) The i -th key bit α_i is 1.

Determining whether condition (i) is satisfied is computationally hard since it is generally hard to compute isogenies between two given curves. Moreover, the points P_1 and P_2 are dependent on the key α and thus unknown to the attacker. Hence, while the attacker influences the points P_1 and P_2 by choosing ϕ_B , they cannot know whether his choice of ϕ_B would cause the attack to fail.

Condition (ii) ensures that the attack is taking place in the case where the points R and S give rise to the isogenies considered in the first condition. Given the points P_1, P_2 , we have

$$\begin{cases} P_1 = R + [\alpha]S, \\ P_2 = R'_i + [\alpha]S'_i = [\theta_i]R + [\theta_i][\alpha + \alpha_i 2^{n-i-1}]S, \end{cases}$$

thus $[\theta_i]P_1 - P_2 = [\theta_i][2^{n-i-1}][\alpha_i]S = [\theta_i][2^{n-i-1}]S$ (because of condition (iii)). If a θ_i exists such that the previous equation is satisfied, then suitable points R and S also exist.

Condition (iii) is necessary because the attack fails by incorrectly deducing a zero-bit instead of a one-bit.

These conditions appear to be quite rare. If it could be shown that the number of cases where the attack fails is polylogarithmic in the security parameter, the attacker could simply retry the attack with different choices of ϕ_B until it succeeds. The attack would still be efficient.

Let us add a remark. Each iteration of the attack depends on the previous one since the modified value R'_i of iteration $i + 1$ relies on K_i , whose last bit is obtained in the i^{th} iteration. To see how the error propagates, assume the attack fails at iteration i . Thus α_i , the i^{th} bit of the key, is a one-bit but the attacker deduces it to be a zero-bit. It follows that $K_i = K_{i-1}$ for the attacker since prepending zero-bits does not affect the value of K . The attacker then computes the points

$$R'_i = [\theta]R - [\theta][2^{n-i-1}K_{i-1}]S, \quad S'_i = [\theta][1 + 2^{n-i-1}]S$$

and queries the oracle on $O(E_B, R'_i, S'_i, E_{AB})$.

Thus, omitting θ since it does not affect the subgroup, we have

$$\begin{aligned} & \langle R'_i + [\alpha]S'_i \rangle \\ &= \langle R + [-2^{n-i-1}K_{i-1} + \alpha(1 + 2^{n-i-1})]S \rangle \\ &= \langle R + [\alpha]S + [-2^{n-i-1}K_{i-1} + 2^{n-i-1}(K_{i-1} + 2^{i-1} + 2^i\alpha_i + 2^{i+1}\alpha')]S \rangle \\ &= \langle R + [\alpha]S + [2^{n-2} + 2^{n-1}\alpha_i]S \rangle \\ &\neq \langle R + [\alpha]S \rangle, \end{aligned}$$

To see why the inequality in the last line holds, consider that if the two cyclic subgroups are the same, their generators must be multiples of each other. Assume then $R + [\alpha]S + [2^{n-2} + 2^{n-1}\alpha_i]S = [m](R + [\alpha]S)$. The linear independence of R and S implies that $R = [m]R$, which means $m \equiv 1 \pmod{2^n}$. Thus, the equality on S implies that $[2^{n-2} + 2^{n-1}\alpha_i]S = \mathcal{O}$, which is impossible because $\alpha_i \in \{0, 1\}$ and $0 \not\equiv 2^{n-2} \not\equiv -2^{n-1} \pmod{2^n}$. This means that the oracle

will return *false* (unless the two subgroups, $\langle R + [\alpha]S \rangle$ and $\langle R'_i + [\alpha]S'_i \rangle$, give rise again to two isogenies with isomorphic codomain).

The subsequent iterations further propagate the error and the oracle will respond *false* to every further query (unless, again, the isogenies with different kernels have the same codomain, which is believed to be a rare occurrence). Thus, if the attack fails at the i^{th} iteration, all the following key bits are deduced to be a one-bit. This allows the attacker to approximately identify the part of the key that has been correctly deduced and target, with a different choice of ϕ_B , only the remaining part.

3. SAGE IMPLEMENTATION

In this section, we report the source code of a SAGE [S⁺09] implementation that shows the attack failing in the case detailed in Example 1.

```
def oracle(E, R, S, Ep):
    EAp = E.isogeny(R + alpha*S).codomain()
    return EAp.j_invariant() == Ep.j_invariant()

## Performs the GPST attack, assuming that Alice's key
## is of the form (1, alpha).
def attack(n, m, E0, PA, QA, PB, QB, EA, phiAPB, phiAQB):
    K = 0

    for i in range(n - 3):
        alpha = 0

        b1 = 1
        b2 = 6

        KB = b1*PB + b2*QB
        phiB = E0.isogeny(KB)
        EB = phiB.codomain()

        R = phiB(PA)
        S = phiB(QA)
        EAB = EA.isogeny(b1*phiAPB + b2*phiAQB).codomain()

        FF = IntegerModRing(2^n)
        theta = Integer(FF((1 + 2^(n - i - 1))^-1).sqrt())
        Rprime = theta * (R - (2^(n - i - 1) * K) * S)
        Sprime = theta * (1 + 2^(n - i - 1)) * S

        response = oracle(EB, Rprime, Sprime, EAB)

        if response == False:
            alpha = 1
```

```

    K += alpha*2^i

found = False

## Bruteforcing the rest of the key
for i in range(2):
    for j in range(2):
        for k in range(2):
            key = K
            key += i*2^(n-3) + j*2^(n-2) + k*2^(n-1)

            EAprime = E0.isogeny(PA + key*QA).codomain()

            if EAprime.j_invariant() == EA.j_invariant():
                solution = (1, key % 2^n)
                found = True
                break

if found:
    return solution
else:
    return "Key not found"

## Setup
lA = 2
lB = 3
eA = 5
eB = 3
f = 1

p = lA^eA*lB^eB*f - 1 #p in Primes() returns True
F.<x> = GF(p^2)

# E0: y^2 = x^3 + (531\beta + 538)x + 720\beta + 375
# E0 is supersingular, as shown by E0.is_supersingular()
E0 = EllipticCurve(F, [531*x + 538, 720*x + 375])

PA = E0(834*x + 726, 642*x + 130)
QA = E0(583*x + 276, 180*x + 854) #PA and QA form a basis of E0[2^5]
PB = E0(254*x + 697, 516*x + 268)
QB = E0(753*x + 317, 234*x + 532) #PB and QB form a basis of E0[3^3]

mA = 1
nA = alpha = 10

KA = mA*PA + nA*QA

```

```

phiA = E0.isogeny(KA)
EA = phiA.codomain()

phiAPB = phiA(PB)
phiAQB = phiA(QB)

alphaprime = attack(eA, eB, E0, PA, QA, PB, QB, EA, phiAPB, phiAQB)
print("The key is: %s" % str(alphaprime))

```

REFERENCES

- [DFJ11] JAO, D. AND DE FEO, L., *Towards Quantum-resistant Cryptosystems from Supersingular Elliptic Curve Isogenies*. Proceedings of the 4th International Conference on Post-Quantum Cryptography **PQCrypto'11**, Berlin, Heidelberg, Springer-Verlag (2011), 19–34.
- [DFJP14] DE FEO, L., JAO, D., AND PLÜT, J., *Towards Quantum-Resistant Cryptosystems from Supersingular Elliptic Curve Isogenies*. J. Math. Cryptol. **8.3** (2014), 209–247.
- [GPST16] GALBRAITH, S., PETIT, C., SHANI, B., AND TI, Y.B., *On the Security of Supersingular Isogeny Cryptosystems*. Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics) **10031** (2016), 63–91.
- [Hus04] HUSEMÖLLER, D., *Elliptic curves*. Second edition. GTM **111** (2004).
- [S⁺09] STEIN, W. A. ET AL., *Sage Mathematics Software (Version 7.5.1)*, The Sage Development Team, (2017), <http://www.sagemath.org>.
- [Sil86] SILVERMAN, J., *The Arithmetic of Elliptic Curves*. Second edition. GTM **106** (1986).
- [Sil94] SILVERMAN, J., *Advanced topics in the arithmetic of elliptic curves*. GTM **151** (1994).

ANDREA BASSO. UNIVERSITY OF BIRMINGHAM, UNIVERSITY RD W, BIRMINGHAM B15 2TT, UNITED KINGDOM.

E-mail address: a.basso@cs.bham.ac.uk

FABIEN PAZUKI. UNIVERSITY OF COPENHAGEN, INSTITUTE OF MATHEMATICS, UNIVERSITETSPARKEN 5, 2100 COPENHAGEN, DENMARK, AND UNIVERSITÉ DE BORDEAUX, IMB, 351, COURS DE LA LIBÉRATION, 33400 TALENCE, FRANCE.

E-mail address: fpazuki@math.ku.dk