

Sampling of globally depolarized random quantum circuit

Tomoyuki Morimae,^{1,2,*} Yuki Takeuchi,^{3,†} and Seiichiro Tani^{3,‡}

¹*Yukawa Institute for Theoretical Physics, Kyoto University,
Kitashirakawa Oiwakecho, Sakyo-ku, Kyoto 606-8502, Japan*

²*JST, PRESTO, 4-1-8 Honcho, Kawaguchi, Saitama, 332-0012, Japan*

³*NTT Communication Science Laboratories,
NTT Corporation, 3-1 Morinosato Wakamiya,
Atsugi, Kanagawa 243-0198, Japan*

(Dated: March 2, 2022)

Abstract

The recent paper [F. Arute et al. Nature **574**, 505 (2019)] considered exact classical sampling of the output probability distribution of the globally depolarized random quantum circuit. In this paper, we show three results. First, we consider the case when the fidelity F is constant. We show that if the distribution is classically sampled in polynomial time within a constant multiplicative error, then $\text{BQP} \subseteq \text{SBP}$, which means that BQP is in the second level of the polynomial-time hierarchy. We next show that for any $F \leq 1/2$, the distribution is classically trivially sampled by the uniform distribution within the multiplicative error $F2^{n+2}$, where n is the number of qubits. We finally show that for any F , the distribution is classically trivially sampled by the uniform distribution within the additive error $2F$. These last two results show that if we consider realistic cases, both $F \sim 2^{-m}$ and $m \gg n$, or at least $F \sim 2^{-m}$, where m is the number of gates, quantum supremacy does not exist for approximate sampling even with the exponentially-small errors. We also argue that if $F \sim 2^{-m}$ and $m \gg n$, the standard approach will not work to show quantum supremacy even for exact sampling.

* tomoyuki.morimae@yukawa.kyoto-u.ac.jp

† yuki.takeuchi.yt@hco.ntt.co.jp

‡ seiichiro.tani.cs@hco.ntt.co.jp

I. INTRODUCTION

Several sub-universal quantum computing models are shown to be hard to classically simulate. For example, output probability distributions of the depth-four model [1], the Boson Sampling model [2], the IQP model [3, 4], the one-clean qubit model [5–9], and the random circuit model [10, 11] cannot be classically sampled in polynomial time unless some conjectures in classical complexity theory (such as the infiniteness of the polynomial-time hierarchy) are refuted. Impossibilities of exponential-time classical simulations of sub-universal quantum computing models have also been shown recently based on classical fine-grained complexity theory [12–16].

Let p_z be the probability that an n -qubit ideal random quantum circuit outputs the n -bit string $z \in \{0, 1\}^n$. Ref. [17] considered the globally depolarized version where the probability p'_z that the output is $z \in \{0, 1\}^n$ is written as

$$p'_z = Fp_z + \frac{1 - F}{2^n},$$

where $0 < F < 1$ is the fidelity.

In this paper, we show the following three results:

Theorem 1 Assume that F is constant. Then, if the probability distribution $\{p'_z\}_{z \in \{0, 1\}^n}$ is sampled in classical $\text{poly}(n)$ time within a constant multiplicative error $\epsilon < 1$, then $\text{BQP} \subseteq \text{SBP}$.

Theorem 2 For any $F \leq \frac{1}{2}$, $\{p'_z\}_{z \in \{0, 1\}^n}$ is classically sampled by the uniform distribution within the multiplicative error $F2^{n+2}$.

Theorem 3 For any F , $\{p'_z\}_{z \in \{0, 1\}^n}$ is classically sampled by the uniform distribution within the additive error $2F$.

Proofs are given in the later sections. In the rest of this section, we provide several remarks.

First, the class SBP [18] is defined as follows.

Definition 1 A language L is in SBP if and only if there exist a polynomial s and a classical polynomial-time probabilistic algorithm such that if $x \in L$ then $p_{acc} \geq 2^{-s(|x|)}$, and if $x \notin L$ then $p_{acc} \leq 2^{-s(|x|)-1}$. Here, p_{acc} is the acceptance probability.

Note that the class SBP remains unchanged even when the two thresholds, $2^{-s(|x|)}$ and $2^{-s(|x|)-1}$, are replaced with $\alpha 2^{-s(|x|)}$ and $\beta 2^{-s(|x|)}$, respectively, for any constants α and β satisfying $0 \leq \beta < \alpha \leq 1$. It is known that SBP is in AM, and therefore $\text{BQP} \subseteq \text{SBP}$ means that BQP is in the second level of the polynomial-time hierarchy. The containment of BQP in the polynomial-time hierarchy is not believed. (For example, there is an oracle separation [19].)

Second, note that quantum supremacy for the globally depolarized circuits was previously studied in Ref. [20] for the one-clean qubit model.

Third, Theorem 1 holds for a broader class of quantum circuits than the globally depolarized random circuit. In particular, we can replace our random gate application with the coherent one. In this paper, however, we concentrate on the globally depolarized random circuit for the simplicity. Theorem 2 and Theorem 3 hold for the output probability distribution $\{p_z\}_z$ of any quantum circuit.

Finally, in Ref. [17], it was claimed that if the exact polynomial-time classical sampling of $\{p'_z\}_z$ is possible, then estimating $|\langle 0^n | U | 0^n \rangle|^2$ for an n -qubit unitary U can be done by an Arthur-Merlin protocol with the F^{-1} -time Arthur. However, if we consider the realistic case, $F \sim 2^{-m}$ and $m \gg n$, where m is the number of gates, the time-complexity of Arthur is $\sim 2^m$. (On the other hand, the exact computation of $|\langle 0^n | U | 0^n \rangle|^2$ can be done in time $\sim 2^n$.) Moreover, although Ref. [17] considered exact sampling of $\{p'_z\}_z$, what a realistic quantum computer can do is approximately sampling $\{p'_z\}_z$. Theorem 2 shows that if we consider the realistic case, $F \sim 2^{-m}$ and $m \gg n$, quantum supremacy does not exist for approximate sampling of $\{p'_z\}_z$ even with the exponentially-small multiplicative error $\sim 2^{-(m-n)}$. Theorem 3 shows that if we consider the realistic case, $F \sim 2^{-m}$, quantum supremacy does not exist for approximate sampling of $\{p'_z\}_z$ even with the exponentially-small additive error $\sim 2^{-m}$.

II. DISCUSSION

Our theorems show that if $F \sim 2^{-m}$ and $m \gg n$, or at least $F \sim 2^{-m}$, quantum supremacy does not exist for approximate sampling of $\{p'_z\}_z$. In this section, we argue that if $F \sim 2^{-m}$ and $m \gg n$, the standard approach will not work to show quantum supremacy for exact sampling of $\{p'_z\}_z$.

In the standard proof of quantum supremacy [1–3, 6, 8, 9], we first consider the following promise problem: given the classical description of an n -qubit m -size quantum circuit U , and parameters a and b , decide $p_{acc} \geq a$ or $p_{acc} \leq b$, where p_{acc} is the acceptance probability. In the standard proof of quantum supremacy, we take the promise problem as the complete problem of a “strong” quantum class, such as postBQP , SBQP , or NQP .

We next assume that $p'_{acc} \equiv Fp_{acc} + \frac{1-F}{2^n}$ is exactly classically sampled. It means that there exists a polynomial-time classical probabilistic algorithm that accepts with probability q_{acc} such that $q_{acc} = p'_{acc}$.

If the answer of the promise problem is yes, then $q_{acc} \geq Fa + \frac{1-F}{2^n} \equiv \alpha$. If the answer of the promise problem is no, then $q_{acc} \leq Fb + \frac{1-F}{2^n} \equiv \beta$. In the standard proof of quantum supremacy, we then conclude that the promise problem is in a “weaker” class (such as postBPP , SBP , or NP) that leads to an unlikely consequence in complexity theory, such as $\text{postBQP} \subseteq \text{postBPP}$, $\text{SBQP} \subseteq \text{SBP}$, or $\text{NQP} \subseteq \text{NP}$. However, deciding $q_{acc} \geq \alpha$ or $q_{acc} \leq \beta$ seems to be “more difficult” than the original promise problem: the original promise problem can be solved in time $\sim 2^n$, while deciding $q_{acc} \geq \alpha$ or $q_{acc} \leq \beta$ will not be solved in that time because $\alpha - \beta = F(a - b) = O(2^{-m})$, and $m \gg n$. Therefore we will not have any unlikely consequence in this approach.

Although the above argument does not exclude the existence of a completely new supremacy proof for the exact sampling of $\{p'_z\}_z$ that works even when $F \sim 2^{-m}$ and $m \gg n$, we can also argue that even if the realistic quantum computer exactly samples $\{p'_z\}_z$, it is “effectively” classically samplable by the uniform distribution when $F \sim 2^{-m}$ unless we can access exponentially many samples.

To see this, let us consider the task of distinguishing $\rho_0 \equiv \frac{I^{\otimes n}}{2^n}$ and $\rho_1 \equiv F\rho + (1-F)\frac{I^{\otimes n}}{2^n}$, where ρ is any n -qubit state. Assume that we can measure k copies of ρ_0 or ρ_1 . Let Π_0 (Π_1) be the POVM element that we conclude that the actual state is $\rho_0^{\otimes k}$ ($\rho_1^{\otimes k}$), where

$\Pi_0 + \Pi_1 = I^{\otimes nk}$. The probability $p_{correct}$ that we make the correct decision is

$$\begin{aligned}
p_{correct} &\equiv \frac{1}{2}\text{Tr}(\Pi_0\rho_0^{\otimes k}) + \frac{1}{2}\text{Tr}(\Pi_1\rho_1^{\otimes k}) \\
&= \frac{1}{2} + \frac{1}{2}\left[\text{Tr}(\Pi_0\rho_0^{\otimes k}) - \text{Tr}(\Pi_0\rho_1^{\otimes k})\right] \\
&\leq \frac{1}{2} + \frac{1}{4}\|\rho_0^{\otimes k} - \rho_1^{\otimes k}\|_1 \\
&\leq \frac{1}{2} + \frac{k}{4}\|\rho_0 - \rho_1\|_1 \\
&= \frac{1}{2} + \frac{k}{4}\left\|\frac{I^{\otimes n}}{2^n} - \left[F\rho + (1-F)\frac{I^{\otimes n}}{2^n}\right]\right\|_1 \\
&= \frac{1}{2} + \frac{kF}{4}\left\|\rho - \frac{I^{\otimes n}}{2^n}\right\|_1 \\
&\leq \frac{1}{2} + \frac{kF}{2}.
\end{aligned}$$

If $F \sim 2^{-m}$ and $k = o(2^m)$, $p_{correct} \rightarrow \frac{1}{2}$.

III. PROOF OF THEOREM 1

Assume that a language L is in BQP. Then for any polynomial r , there exists a polynomial-time uniformly generated family $\{V_x\}_x$ of quantum circuits such that if $x \in L$ then $p_{acc} \geq 1 - 2^{-r(|x|)}$, and if $x \notin L$ then $p_{acc} \leq 2^{-r(|x|)}$. Here

$$p_{acc} \equiv \langle 0^w | V_x | 0^w \rangle$$

with $w = \text{poly}(|x|)$ is the acceptance probability.

Let m be the number of elementary gates in V_x , i.e., $V_x = w_m w_{m-1} \dots w_2 w_1$, where each w_j is an elementary gate (such as H , $CNOT$, and T , etc.). Let us consider the following random quantum circuit on $n \equiv w + m$ qubits:

1. The initial state is $|0^w\rangle \otimes |0^m\rangle$, where we call the first w -qubit register the main register, and the second m -qubit register the ancilla register.
2. For each $j = 1, 2, \dots, m$, apply $w_j \otimes I$ or $\eta_j \otimes X$ with probability $1/2$, where η_j is any elementary gate, w_j and η_j act on the main register, and I and X act on the j th qubit of the ancilla register. Thus obtained the final state is

$$\frac{1}{2^m} \sum_{\alpha \in \{0,1\}^m} \xi_m^{\alpha_m} \dots \xi_1^{\alpha_1} |0^w\rangle \langle 0^w| (\xi_1^{\alpha_1})^\dagger \dots (\xi_m^{\alpha_m})^\dagger \otimes |\alpha\rangle \langle \alpha|, \quad (1)$$

where $\alpha \equiv (\alpha_1, \dots, \alpha_m) \in \{0,1\}^m$ is an m -bit string, $\xi_j^0 = w_j$, and $\xi_j^1 = \eta_j$.

3. Measure all n qubits in the computational basis. If all results are 0, accept. Otherwise, reject.

If we consider the globally depolarized version, the state of Eq. (1) is replaced with

$$\frac{F}{2^m} \sum_{\alpha \in \{0,1\}^m} \xi_m^{\alpha_m} \dots \xi_1^{\alpha_1} |0^w\rangle \langle 0^w| (\xi_1^{\alpha_1})^\dagger \dots (\xi_m^{\alpha_m})^\dagger \otimes |\alpha\rangle \langle \alpha| + (1-F) \frac{I^{\otimes n}}{2^n}.$$

The acceptance probability p'_{acc} is

$$p'_{acc} = \frac{F p_{acc}^2}{2^m} + \frac{1-F}{2^n}.$$

Assume that there exists a classical $poly(n)$ -time probabilistic algorithm that accepts with probability q_{acc} such that $|p'_{acc} - q_{acc}| \leq \epsilon p'_{acc}$, where $\epsilon < 1$ is a constant. Then, if $x \in L$,

$$\begin{aligned} q_{acc} &\geq (1-\epsilon) p'_{acc} \\ &= (1-\epsilon) \left(\frac{F p_{acc}^2}{2^m} + \frac{1-F}{2^n} \right) \\ &\geq (1-\epsilon) F 2^{-m} (1-2^{-r})^2, \end{aligned}$$

and if $x \notin L$,

$$\begin{aligned} q_{acc} &\leq (1+\epsilon) p'_{acc} \\ &= (1+\epsilon) \left(\frac{F p_{acc}^2}{2^m} + \frac{1-F}{2^n} \right) \\ &\leq (1+\epsilon) \left(F 2^{-2r-m} + \frac{1-F}{2^n} \right) \\ &= 2^{-m} (1+\epsilon) F \left(2^{-2r} + \frac{1-F}{F 2^w} \right). \end{aligned}$$

If r and w are sufficiently large, L is in SBP. \square

Note that although here we have considered constant F , the same result also holds for other “not so small” F such as $F = \frac{1}{poly(m)}$.

IV. PROOF OF THEOREM 2

Let us take $\epsilon = F 2^{n+2}$. For any $z \in \{0,1\}^n$,

$$\left| p'_z - \frac{1}{2^n} \right| = \left| \left(F p_z + \frac{1-F}{2^n} \right) - \frac{1}{2^n} \right| \leq F \left(1 + \frac{1}{2^n} \right) < \epsilon p'_z,$$

where in the last inequality, we have used

$$\begin{aligned}
\epsilon p'_z - F\left(1 + \frac{1}{2^n}\right) &= \epsilon\left(Fp_z + \frac{1-F}{2^n}\right) - F\left(1 + \frac{1}{2^n}\right) \\
&\geq \frac{\epsilon(1-F)}{2^n} - F\left(1 + \frac{1}{2^n}\right) \\
&= \frac{F2^{n+2}(1-F)}{2^n} - F\left(1 + \frac{1}{2^n}\right) \\
&= 4F(1-F) - F\left(1 + \frac{1}{2^n}\right) \\
&> 0.
\end{aligned}$$

□

V. PROOF OF THEOREM 3

$$\sum_{z \in \{0,1\}^n} \left| p'_z - \frac{1}{2^n} \right| = F \sum_{z \in \{0,1\}^n} \left| p_z - \frac{1}{2^n} \right| \leq 2F.$$

□

ACKNOWLEDGMENTS

TM is supported by MEXT Quantum Leap Flagship Program (MEXT Q-LEAP) Grant Number JPMXS0118067394, JST PRESTO No.JPMJPR176A, and the Grant-in-Aid for Young Scientists (B) No.JP17K12637 of JSPS. YT is supported by MEXT Quantum Leap Flagship Program (MEXT Q-LEAP) Grant Number JPMXS0118067394.

-
- [1] B. M. Terhal and D. P. DiVincenzo, Adaptive quantum computation, constant depth quantum circuits and Arthur-Merlin games. *Quant. Inf. Comput.* **4**, 134 (2004).
 - [2] S. Aaronson and A. Arkhipov, The computational complexity of linear optics. *Theory of Computing* **9**, 143 (2013).
 - [3] M. J. Bremner, R. Jozsa, and D. J. Shepherd, Classical simulation of commuting quantum computations implies collapse of the polynomial hierarchy. *Proc. R. Soc. A* **467**, 459 (2011).

- [4] M. J. Bremner, A. Montanaro, and D. J. Shepherd, Average-case complexity versus approximate simulation of commuting quantum computations. *Phys. Rev. Lett.* **117**, 080501 (2016).
- [5] E. Knill and R. Laflamme, Power of one bit of quantum information. *Phys. Rev. Lett.* **81**, 5672 (1998).
- [6] T. Morimae, K. Fujii, and J. F. Fitzsimons, Hardness of classically simulating the one clean qubit model. *Phys. Rev. Lett.* **112**, 130502 (2014).
- [7] T. Morimae, Hardness of classically sampling one clean qubit model with constant total variation distance error. *Phys. Rev. A* **96**, 040302(R) (2017).
- [8] K. Fujii, H. Kobayashi, T. Morimae, H. Nishimura, S. Tamate, and S. Tani, Impossibility of classically simulating one-clean-qubit model with multiplicative error. *Phys. Rev. Lett.* **120**, 200502 (2018).
- [9] K. Fujii, H. Kobayashi, T. Morimae, H. Nishimura, S. Tamate, and S. Tani, Power of quantum computation with few clean qubits. *Proceedings of 43rd International Colloquium on Automata, Languages, and Programming (ICALP 2016)*, pp.13:1-13:14 (2016).
- [10] A. Bouland, B. Fefferman, C. Nirkhe, and U. Vazirani, Quantum supremacy and the complexity of random circuit sampling. *Nature Phys.* **15**, 159 (2019).
- [11] R. Movassagh, Cayley path and quantum computational supremacy: a proof of average-case $\#P$ -hardness of random circuit sampling with quantified robustness. [arXiv:1909.06210](https://arxiv.org/abs/1909.06210)
- [12] A. M. Dalzell, A. W. Harrow, D. E. Koh, and R. L. La Placa, How many qubits are needed for quantum computational supremacy? [arXiv:1805.05224](https://arxiv.org/abs/1805.05224)
- [13] A. M. Dalzell, Bachelor thesis, MIT (2017).
- [14] C. Huang, M. Newman, and M. Szegedy, Explicit lower bounds on strong quantum simulation. [arXiv:1804.10368](https://arxiv.org/abs/1804.10368)
- [15] C. Huang, M. Newman, and M. Szegedy, Explicit lower bounds on strong simulation of quantum circuits in terms of T -gate count. [arXiv:1902.04764](https://arxiv.org/abs/1902.04764)
- [16] T. Morimae and S. Tamaki, Fine-grained quantum computational supremacy. *Quant. Inf. Comput.* **19**, 1089 (2019).
- [17] F. Arute et al. Quantum supremacy using a programmable superconducting processor. *Nature* **574**, 505 (2019).
- [18] E. Böhrer, C. Glaßer, and D. Meister, Error-bounded probabilistic computations between MA and AM. *J. Comput. Syst. Sci.* **72**, 1043 (2006).

- [19] R. Raz and A. Tal, Oracle separation of BQP and PH. Proceedings of the 51st Annual ACM SIGACT Symposium on Theory of Computing (STOC 2019), pp.13-23 (2019).
- [20] T. Morimae, K. Fujii, and H. Nishimura, Power of one nonclean qubit. Phys. Rev. A **95**, 042336 (2017).