

# Maxwell's derivation of the Lorentz force from Faraday's law

Arthur D. Yaghjian

## Abstract

In a brief but brilliant derivation that can be found in Maxwell's 1861 and 1865 papers as well as in his *Treatise*, he derives the force on a moving electric charge subject to electric and magnetic fields from his mathematical expression of Faraday's law for a moving circuit. Maxwell's derivation of this force, which is usually referred to today as the Lorentz force, is given in detail in the present paper using Maxwell's same procedure but with more modern notation.

## I. INTRODUCTION

In Article 603 of his *Treatise* [1], [2], Maxwell derives the force density  $\mathbf{F}_J$  exerted by a magnetic field  $\mathbf{B}$  on a current density  $\mathbf{J}$  as

$$\mathbf{F}_J = \mathbf{J} \times \mathbf{B}. \quad (1)$$

His derivation is based on the mutual induction between two current carrying circuits that represent magnetic shells and nowhere in his *Treatise* does he express  $\mathbf{J}$  as  $\rho\mathbf{v}$ , where  $\rho$  is the electric charge density and  $\mathbf{v}$  is the velocity of the charge density. Therefore, the credit for the force  $q\mathbf{v} \times \mathbf{B}$  on an electric charge  $q$  moving in a magnetic field is generally given to Heaviside [3] and credit for the total force  $q(\mathbf{E} + \mathbf{v} \times \mathbf{B})$  on a moving charge in electric and magnetic fields is generally given to Lorentz [4], [5, app. 7].

Nonetheless, it was Maxwell who first determined the general force equation on a moving unit electric charge, namely

$$\mathbf{F}_1 = \mathbf{E} + \mathbf{v} \times \mathbf{B} \quad (2)$$

in a remarkable derivation from the general equation for Faraday's law that he deduced from Faraday's experiments [6].<sup>1</sup> It is the main purpose of this paper to document and reproduce in modern notation this impressive derivation of Maxwell that can be found in both his 1861 [7] and 1865 [8] papers as well as his *Treatise* [1], [2].<sup>2</sup>

## II. FARADAY'S LAW

In Articles 530–541 of his *Treatise* [1], Maxwell explains some of Faraday's experiments by means of “primary” and “secondary” circuits that allow him to summarize in Article 541 the “true law of magneto-electric induction [Faraday's law of induced electromotive force]” as follows: “The total electromagnetic force acting round a circuit at any instant is measured by the rate of decrease of the number of lines of magnetic force [field] which pass through it.” In Chapter IV of Part IV of the *Treatise*, he explains that Faraday's experiments with a single solenoidal circuit also demonstrate a self-induced electromotive force.

Maxwell begins the formulation of time-varying electromagnetic-field equations per se with Chapter VII, “Theory of Electric Circuits,” in Part IV of the *Treatise*. In this chapter as well as the following Chapter VIII, specifically in Articles 578–592, he culminates a lengthy argument based on the experimental results of Ampère and Faraday with a mathematical formulation of these results in a form we recognize today as Maxwell's first equation. It is most noteworthy that, although Maxwell does not include his equation for Faraday's law explicitly in his summary of equations in Article 619 because, evidently, he decided finally to emphasize the vector and scalar potential representations of his equations,<sup>3</sup> he first wrote down the integral form of Faraday's law in Articles 579 and 595 as

$$E(t) = -\frac{d}{dt}p(t) \quad (3)$$

<sup>1</sup>Faraday did not write any equations in his *Experimental Researches* [6]. The clearest concise statement that I could find in Faraday's writings on electromagnetic induction (Faraday's law) is in Paragraph 3087 of his *Experimental Researches* [6], namely, “The first practical result produced by the apparatus described, in respect of magneto-electric induction generally, is, that a piece of metal or conducting matter which moves across lines of magnetic force, has, or tends to have, a current of electricity produced in it.” Following this statement, Faraday continues with a more detailed explanation of the “full effect” of the experimentally observed magneto-electric induction.

<sup>2</sup>A shortened version of the derivation in the present paper is given in [2] but it contains an error pointed out by Redžić [9]. Redžić's treatment in [9] of Maxwell's derivation of the force on a moving charge differs from Maxwell's original derivation in that it requires differentiation of the differential of the position vector as well as an involved mathematical proof that the time derivative can be brought inside the line integral of the vector potential for a moving curve.

<sup>3</sup>Physicists often note that quantum field theory is indebted to Maxwell's emphasis on the vector and scalar potentials in his final summary of equations in Article 619.

where  $E(t)$  is the line integral of the dynamic electromotive force per unit electric charge in a closed circuit that can be moving (and deforming). For a stationary circuit,  $E$  has been given in Article 69 as  $\int_C \mathbf{E} \cdot d\mathbf{c}$ , where  $\mathbf{E}$  is the electric field. For a moving circuit,  $E$  can be written in terms of a vector  $\mathbf{E}_v$  as [1, art. 598, eq. (6)], [2, sec. 6.1]

$$E(t) = \oint_{C(t)} \mathbf{E}_v(\mathbf{r}, t) \cdot d\mathbf{c} \quad (4)$$

where  $C(t)$  denotes the curve of the moving closed circuit and  $\mathbf{E}_v(\mathbf{r}, t)$  is the *unknown* force per unit electric charge moving with each point  $\mathbf{r}$  of the circuit. The vector form of the line integral in (4) is given in equation (6) of Art. 598 [1]. (It should be noted that in Article 579,  $E$  represents the “impressed” voltage produced by a battery in the circuit so that  $E - IR$  in Article 579 equals  $-\oint_{C(t)} \mathbf{E}_v \cdot d\mathbf{c}$  and thus in Article 579 Maxwell writes  $E - IR = dp/dt$ .)

The  $p(t)$  in (3) is given in Article 591 as

$$p(t) = \oint_{C(t)} \mathbf{A}(\mathbf{r}, t) \cdot d\mathbf{c} = \int_{S(t)} \mathbf{B}(\mathbf{r}, t) \cdot \hat{\mathbf{n}} dS \quad (5)$$

with  $S(t)$  any open surface bounded by the closed curve  $C(t)$ . The vector forms of the line and surface integrals in (5) are given in equation (7) of Art. 590 and equation (12) of Art. 591 [1]. With (4) and (5) inserted into (3), we see that Maxwell has obtained the most general integral form of Faraday’s law

$$\oint_{C(t)} \mathbf{E}_v(\mathbf{r}, t) \cdot d\mathbf{c} = -\frac{d}{dt} \oint_{C(t)} \mathbf{A}(\mathbf{r}, t) \cdot d\mathbf{c} = -\frac{d}{dt} \int_{S(t)} \mathbf{B}(\mathbf{r}, t) \cdot \hat{\mathbf{n}} dS. \quad (6)$$

When he writes (3) in Article 595, however, he has not yet shown for moving circuits that the electromotive intensity or force ( $\mathbf{E}_v$ ) on a moving unit charge is equal to what now is generally called the Lorentz force  $\mathbf{E} + \mathbf{v} \times \mathbf{B}$  per moving unit electric charge, where  $\mathbf{v}$  is the velocity of the moving charge.

For stationary circuits, he confirms toward the end of Article 598 that, as in Article 69

$$E(t) = \oint_C \mathbf{E}(\mathbf{r}, t) \cdot d\mathbf{c} \quad (7)$$

where  $\mathbf{E}$  is the electric field on a fixed unit electric charge defined in Article 68. Consequently, Maxwell has obtained the integral form of Faraday’s law for stationary circuits, namely

$$\oint_C \mathbf{E}(\mathbf{r}, t) \cdot d\mathbf{c} = -\oint_C \frac{\partial}{\partial t} \mathbf{A}(\mathbf{r}, t) \cdot d\mathbf{c} = -\int_S \frac{\partial}{\partial t} \mathbf{B}(\mathbf{r}, t) \cdot \hat{\mathbf{n}} dS. \quad (8)$$

Application of Stoke’s theorem to (8) yields the differential form of Faraday’s law

$$\nabla \times \mathbf{E}(\mathbf{r}, t) = -\nabla \times \frac{\partial}{\partial t} \mathbf{A}(\mathbf{r}, t) = -\frac{\partial}{\partial t} \mathbf{B}(\mathbf{r}, t). \quad (9)$$

However, Maxwell does not write this differential form of Faraday’s law in his *Treatise* nor in his 1865 paper [8] which contain only the integral form of Faraday’s law.<sup>4</sup> The first equation in (8) or (9) implies that

$$\mathbf{E}(\mathbf{r}, t) = -\frac{\partial}{\partial t} \mathbf{A}(\mathbf{r}, t) - \nabla \psi_e(\mathbf{r}, t) \quad (10)$$

where  $\psi_e(\mathbf{r}, t)$  is a time-dependent as well as a spatially dependent scalar potential function. In Article 598 Maxwell says that  $\psi_e(\mathbf{r}, t)$  “represents, according to a certain definition, the *electric potential*,” which he later says in Article 783 “is proportional to the volume charge density of free electricity [ $\rho_e(\mathbf{r}, t)$ ].”

### III. DERIVATION OF THE LORENTZ FORCE ON A MOVING UNIT ELECTRIC CHARGE

Returning to Maxwell’s general integral form of Faraday’s law for moving circuits in (3), expressed more fully in (6), we find in Article 598 Maxwell’s ingenious evaluation of  $-(d/dt) \oint_{C(t)} \mathbf{A}(\mathbf{r}, t) \cdot d\mathbf{c}$  to prove that  $\mathbf{E}_v(\mathbf{r}, t) = \mathbf{E}(\mathbf{r}, t) + \mathbf{v}(\mathbf{r}, t) \times \mathbf{B}(\mathbf{r}, t)$ , where  $\mathbf{v}(\mathbf{r}, t)$  is the velocity at each point  $\mathbf{r}$  of the moving circuit  $C(t)$ . He thus completes the mathematical formulation of Faraday’s integral law for moving circuits and in so doing derives the force exerted on a moving unit electric charge by the magnetic induction  $\mathbf{B}$ . Maxwell accomplishes this feat as follows.

<sup>4</sup>We know that Maxwell deliberately chose to emphasize the integral form of Faraday’s law in his *Treatise* and 1865 paper [8] since he had deduced the differential form of this law from his “theory of molecular vortices” that he used in his 1861 paper [7] to explain Faraday’s experimental results [10]. In Part 2 of that paper, which contained no integrals, he wrote the scalar version of  $\nabla \times \mathbf{E} = -\mu \partial \mathbf{H} / \partial t (= -\partial \mathbf{B} / \partial t)$  as equation (54). Maxwell’s mathematical formulation of Faraday’s law is not contained in Maxwell’s earlier 1856 paper [11] in either the integral or differential form.

He writes  $\mathbf{A}(\mathbf{r}, t) \cdot d\mathbf{c}$  in rectangular coordinates as

$$\mathbf{A}(\mathbf{r}, t) \cdot d\mathbf{c} = A_x \frac{\partial x}{\partial c} dc + A_y \frac{\partial y}{\partial c} dc + A_z \frac{\partial z}{\partial c} dc \quad (11)$$

where  $dc = |d\mathbf{c}| = |d\mathbf{r}|$  is the scalar element of length on the closed curve  $C(t)$  at a fixed time  $t$ . The  $x$ ,  $y$ , and  $z$  components of the position vector  $\mathbf{r} = x\hat{\mathbf{x}} + y\hat{\mathbf{y}} + z\hat{\mathbf{z}}$  are functions of time  $t$  and length  $c$  along the curve  $C(t)$ , that is

$$\mathbf{r}(t, c) = x(t, c)\hat{\mathbf{x}} + y(t, c)\hat{\mathbf{y}} + z(t, c)\hat{\mathbf{z}}. \quad (12)$$

If we consider the integral

$$\oint_{C(t)} \mathbf{A}(\mathbf{r}, t) \cdot d\mathbf{c} = \oint_{C(t)} \left( A_x \frac{\partial x}{\partial c} + A_y \frac{\partial y}{\partial c} + A_z \frac{\partial z}{\partial c} \right) dc \quad (13)$$

one can change the scalar integration variable  $c$  to  $c' = c/c_{max}$  at each time  $t$ , where  $c_{max}$  is the total length of the closed curve  $C(t)$  at the time  $t$ , and (13) becomes

$$\oint_{C(t)} \mathbf{A}(\mathbf{r}, t) \cdot d\mathbf{c} = \int_0^1 \left( A_x \frac{\partial x}{\partial c'} + A_y \frac{\partial y}{\partial c'} + A_z \frac{\partial z}{\partial c'} \right) dc' \quad (14)$$

and thus the integration variable  $c'$  need not change with time  $t$ . Since  $C(t)$  is a closed curve,  $c' = 0$  and  $c' = 1$  refer to the same point on  $C(t)$ .

Taking the time derivative of this equation, we can bring the time derivative of the right-hand side under the integral sign (because the limits of integration do not depend on time) to get

$$\begin{aligned} \frac{d}{dt} \oint_{C(t)} \mathbf{A}(\mathbf{r}, t) \cdot d\mathbf{c} &= \int_0^1 \frac{d}{dt} \left[ A_x[\mathbf{r}(t, c), t] \frac{\partial x}{\partial c} + A_y[\mathbf{r}(t, c), t] \frac{\partial y}{\partial c} + A_z[\mathbf{r}(t, c), t] \frac{\partial z}{\partial c} \right] dc \\ &= \oint_{C(t)} \left[ \frac{\partial A_x(\mathbf{r}, t)}{\partial t} \frac{\partial x}{\partial c} + \frac{\partial A_y(\mathbf{r}, t)}{\partial t} \frac{\partial y}{\partial c} + \frac{\partial A_z(\mathbf{r}, t)}{\partial t} \frac{\partial z}{\partial c} \right. \\ &\quad + \left( \frac{\partial A_x}{\partial x} \frac{\partial x}{\partial c} + \frac{\partial A_y}{\partial x} \frac{\partial y}{\partial c} + \frac{\partial A_z}{\partial x} \frac{\partial z}{\partial c} \right) \frac{\partial x}{\partial t} \\ &\quad + \left( \frac{\partial A_x}{\partial y} \frac{\partial x}{\partial c} + \frac{\partial A_y}{\partial y} \frac{\partial y}{\partial c} + \frac{\partial A_z}{\partial y} \frac{\partial z}{\partial c} \right) \frac{\partial y}{\partial t} \\ &\quad + \left( \frac{\partial A_x}{\partial z} \frac{\partial x}{\partial c} + \frac{\partial A_y}{\partial z} \frac{\partial y}{\partial c} + \frac{\partial A_z}{\partial z} \frac{\partial z}{\partial c} \right) \frac{\partial z}{\partial t} \\ &\quad \left. + \left( A_x(\mathbf{r}, t) \frac{\partial^2 x}{\partial c \partial t} + A_y(\mathbf{r}, t) \frac{\partial^2 y}{\partial c \partial t} + A_z(\mathbf{r}, t) \frac{\partial^2 z}{\partial c \partial t} \right) \right] dc \quad (15) \end{aligned}$$

where the superfluous prime on the integration variable  $c'$  has been dropped. The partial derivatives with respect to  $c$  are taken holding  $t$  fixed. The partial derivatives of  $(x, y, z)$  with respect to  $t$  are taken holding  $c$  fixed. The partial derivatives of  $\mathbf{A}(\mathbf{r}, t)$  with respect to  $x$ ,  $y$ , or  $z$  are taken holding  $t$  fixed and with respect to  $t$  holding  $(x, y, z)$  fixed. To obtain (15), use has been made of the chain rules

$$\frac{d\mathbf{A}(\mathbf{r}, t)}{dt} = \frac{\partial \mathbf{A}(\mathbf{r}, t)}{\partial t} + \frac{\partial \mathbf{A}(\mathbf{r}, t)}{\partial x} \frac{dx}{dt} + \frac{\partial \mathbf{A}(\mathbf{r}, t)}{\partial y} \frac{dy}{dt} + \frac{\partial \mathbf{A}(\mathbf{r}, t)}{\partial z} \frac{dz}{dt} \quad (16)$$

$$\frac{dx(t, c)}{dt} = \frac{\partial x(t, c)}{\partial t} + \frac{\partial x(t, c)}{\partial c} \frac{dc}{dt} = \frac{\partial x(t, c)}{\partial t} = v_x \quad (17a)$$

$$\frac{dy(t, c)}{dt} = \frac{\partial y(t, c)}{\partial t} = v_y \quad (17b)$$

$$\frac{dz(t, c)}{dt} = \frac{\partial z(t, c)}{\partial t} = v_z \quad (17c)$$

as well as the variable  $c$  being independent of time ( $dc/dt = 0$ ). The chain rule in (16) holds for any  $dx$ ,  $dy$ , and  $dz$  so we can choose  $[x, y, z]$  to be the coordinates  $[x(t, c), y(t, c), z(t, c)]$  of the curve  $C(t)$ .

If we proceed as Maxwell did, using  $\mathbf{B} = \nabla \times \mathbf{A}$  to substitute  $\partial A_y/\partial x = \partial A_x/\partial y + B_z$  and  $\partial A_z/\partial x = \partial A_x/\partial z - B_y$  into the third line of (15), we get for that line

$$\oint_{C(t)} \left( B_z \frac{\partial y}{\partial c} - B_y \frac{\partial z}{\partial c} + \frac{\partial A_x}{\partial x} \frac{\partial x}{\partial c} + \frac{\partial A_x}{\partial y} \frac{\partial y}{\partial c} + \frac{\partial A_x}{\partial z} \frac{\partial z}{\partial c} \right) \frac{\partial x}{\partial t} dc = \oint_{C(t)} \left( B_z \frac{\partial y}{\partial c} - B_y \frac{\partial z}{\partial c} + \frac{\partial A_x}{\partial c} \right) \frac{\partial x}{\partial t} dc. \quad (18)$$

Since

$$\frac{\partial A_x}{\partial c} \frac{\partial x}{\partial t} + A_x \frac{\partial^2 x}{\partial c \partial t} = \frac{\partial}{\partial c} \left( A_x \frac{\partial x}{\partial t} \right) \quad (19)$$

is a perfect differential, its integral around the closed curve  $C(t)$  is zero. Thus, (18), along with the similar expressions for the fourth and fifth lines in (15), reduce (15) to

$$\begin{aligned} \frac{d}{dt} \oint_{C(t)} \mathbf{A}(\mathbf{r}, t) \cdot d\mathbf{c} &= \oint_{C(t)} \left[ \left( \frac{\partial A_x(\mathbf{r}, t)}{\partial t} + B_y \frac{\partial z}{\partial t} - B_z \frac{\partial y}{\partial t} \right) \frac{\partial x}{\partial c} \right. \\ &\quad + \left( \frac{\partial A_y(\mathbf{r}, t)}{\partial t} + B_z \frac{\partial x}{\partial t} - B_x \frac{\partial z}{\partial t} \right) \frac{\partial y}{\partial c} \\ &\quad \left. + \left( \frac{\partial A_z(\mathbf{r}, t)}{\partial t} + B_x \frac{\partial y}{\partial t} - B_y \frac{\partial x}{\partial t} \right) \frac{\partial z}{\partial c} \right] dc \\ &= \oint_{C(t)} \left[ \frac{\partial}{\partial t} \mathbf{A}(\mathbf{r}, t) - \mathbf{v}(\mathbf{r}, t) \times \mathbf{B}(\mathbf{r}, t) \right] \cdot d\mathbf{c} \end{aligned} \quad (20)$$

where  $\mathbf{v} = \partial x / \partial t \hat{\mathbf{x}} + \partial y / \partial t \hat{\mathbf{y}} + \partial z / \partial t \hat{\mathbf{z}}$ . Consequently, Maxwell has proven that

$$\oint_{C(t)} \mathbf{E}_v(\mathbf{r}, t) \cdot d\mathbf{c} = - \oint_{C(t)} \left[ \frac{\partial}{\partial t} \mathbf{A}(\mathbf{r}, t) - \mathbf{v}(\mathbf{r}, t) \times \mathbf{B}(\mathbf{r}, t) \right] \cdot d\mathbf{c} \quad (21)$$

and, thus, he concludes that

$$\mathbf{E}_v(\mathbf{r}, t) = - \frac{\partial}{\partial t} \mathbf{A}(\mathbf{r}, t) - \nabla \psi_e(\mathbf{r}, t) + \mathbf{v}(\mathbf{r}, t) \times \mathbf{B}(\mathbf{r}, t) \quad (22)$$

or in accordance with (10)

$$\mathbf{E}_v(\mathbf{r}, t) = \mathbf{E}(\mathbf{r}, t) + \mathbf{v}(\mathbf{r}, t) \times \mathbf{B}(\mathbf{r}, t) \quad (23)$$

since  $\mathbf{E}_v$  in (22) with  $\mathbf{v} = 0$  has to equal  $\mathbf{E}$  in (10). It should be emphasized that Maxwell uses his mathematical formulation of Faraday's law to obtain (23) and not the current force  $\mathbf{J} \times \mathbf{B}$  in (1) that he has found from the force on a magnetic-shell model of circulating electric current.

Thus, Maxwell has been able to represent Faraday's experimental results in a general mathematical form of Faraday's law given in (6) with  $\mathbf{E}_v$  given in (23) [1, arts. 598–599]. *In one magnificent synthesis of mathematical and physical insight, he has not only put Faraday's law on a solid mathematical foundation but he has also derived the "Lorentz force" for a moving electric charge.* (As explained in [2, sec.3], Maxwell uses the same boldface German letter  $\mathfrak{E}$  for both the symbols  $\mathbf{E}_v$  and  $\mathbf{E}$  that we use here, and when Maxwell denotes  $\mathbf{E}_v$  by  $\mathfrak{E}$  he expects the reader to know from the context that  $\mathfrak{E}$  with  $\mathbf{v} = 0$  is the electric field defined in Articles 44 and 68 and given here as  $\mathbf{E}$  in equation (10).)

It is also possible to prove (6) and (22)–(23) from (8) using the Helmholtz transport theorem [12, ch. 6] of vector calculus, but Maxwell does not do this even though he mentions Helmholtz's work with moving circuits in Article 544. Effectively, he proves the Helmholtz transport theorem for the electromagnetic fields in his mathematical formulation of Faraday's law as part of his derivation reproduced above in (13)–(23).

After deriving (23) from (6) in Article 598, he says that  $\mathbf{E}_v$  in (23) is the most general form of the electromotive force on a moving unit point electric charge, "being the force which would be experienced by a [moving] unit of positive charge at that point." It follows from linearity that the force on an electric charge  $q$  in external fields  $[\mathbf{E}, \mathbf{B}]$  is given by

$$\mathbf{F} = q(\mathbf{E} + \mathbf{v} \times \mathbf{B}) \quad (24)$$

what we refer to today as the Lorentz force.<sup>5</sup>

<sup>5</sup>Redžić argues that Maxwell's charged "particle" is not what we mean today as a charged particle but an "infinitesimal portion of a medium". It is true that Maxwell did not believe that charge came in discrete amounts but was always a fluid, which could nevertheless coat a small body to produce a charged particle. He says near the end of Art. 598 that "The electromotive intensity [electric field] has already been defined in Art. 68. It is also called the resultant electrical intensity, being the force which would be experienced by a unit of positive electricity [a word Maxwell used interchangeably with electric charge] placed at that point. We have not obtained the most general value of this quantity [force on a unit of positive electric charge] in the case of a body [which could be a small particle] moving in a magnetic field due to a variable electric system." He continues in Art. 599 with, "The electromotive intensity [force on a unit electrically charged particle], the components of which are defined by equations (B) [(22) above], depends on three circumstances. The first of these is the motion of the *particle* [emphasis mine] through the magnetic field  $[\mathbf{B}]$ . The part of the force depending on this motion is expressed by the first two terms on the right of each equation  $[\mathbf{v} \times \mathbf{B}$  in (22) above]." From this and similar statements in his *Treatise*, it seems unequivocal that Maxwell realized that he had derived the force excited by the external electric and magnetic fields on an electrically charged particle moving in the ether. Moreover, if Maxwell had thought that the force in (22) or (23) (his equations (B)) did not apply to an isolated moving particle carrying unit electric charge (electricity), then these equations would not apply to a particle carrying unit electric charge when  $\mathbf{v} = 0$ . This would be an obvious denial of Maxwell's definition in Art. 68, that he used throughout his *Treatise*, of the electric field at a point being the force on an isolated unit charged particle placed at that point. Finally, even if we suppose that Maxwell did not have exactly the same concept of a moving charged particle as we do today, he nevertheless derived the force in (23) on what he called a "moving unit of positive electricity" that he said was the same as the small stationary charged body that experienced the electric force used to define the electric field in Arts. 44 and 68.

#### IV. CONCLUSION

From the experiments of Faraday, Maxwell infers that the integral of the electromotive force around a moving closed circuit  $C(t)$  is given by the negative time derivative of the magnetic flux through any open surface  $S(t)$  bounded by the closed curve  $C(t)$ . Using this generalized mathematical formulation of Faraday's law given in (6), Maxwell effectively derives a Helmholtz transport theorem for the electromagnetic fields to prove that the electromagnetic force on a moving electric charge is given by the "Lorentz force" in (24). This remarkable derivation found in Maxwell's *Treatise* can be traced back to his 1861 paper [7], which was written about 30 years before Heaviside [3] and Lorentz [4] expressed the force on a moving electric charge.

#### ACKNOWLEDGMENT

This work was supported in part under the U.S. Air Force Office of Scientific Research Contract # FA9550-19-1-0097 through Dr. Arje Nachman.

#### REFERENCES

- [1] J.C. Maxwell, *A Treatise on Electricity and Magnetism, 3rd Edition*, New York: Dover, 1954. The Dover edition is an unabridged, slightly altered, republication of the third edition, published by the Clarendon Press in 1891. All additions to the *Treatise* made by W.D. Niven and J.J. Thomson are ignored in [2] and in the present paper so as to concentrate on Maxwell's original contributions.
- [2] A.D. Yaghjian, "Reflections on Maxwell's Treatise," *PIER*, **149**, pp. 217–249, November 2014; see also "An overview of Maxwell's Treatise," *FERMAT*, **11**, Sept.-Oct. 2015.
- [3] O. Heaviside, "On the electromagnetic effects due to the motion of electrification through a dielectric," *Phil. Mag. and J. Sci.*, fifth series, **27**, pp. 324–339, 1889.
- [4] H.A. Lorentz, "Le theorie electromagnetique de Maxwell et son application aux corps mouvants," *Archives Neerlandaises des Sciences Exactes et Naturelles*, **25**, pp. 363–552, 1892.
- [5] J.D. Buchwald, *From Maxwell to Microphysics*, Chicago: University of Chicago Press, 1985.
- [6] M. Faraday, *Experimental Researches in Electricity*, New York: Dover, 2004; Originally published in three volumes by J.E. Taylor: London, 1839–1855.
- [7] J.C. Maxwell, "On physical lines of force, Part 2" *Phil. Mag. and J. Sci.*, fourth series, **21**, pp. 282–349, March 1861.
- [8] J.C. Maxwell, "A dynamical theory of the electromagnetic field" *Phil. Trans. Roy. Soc. Lond.*, **155**, pp. 459–512, 1865.
- [9] D.V. Redžić, "Maxwell's inductions from Faraday's induction law," *Eur. J. Phys.*, **39**, 025205 (16pp), February 2018.
- [10] O.M. Bucci, "The genesis of Maxwell's equations," ch. 4 in *History of Wireless*, Hoboken, NJ: Wiley, 2006.
- [11] J.C. Maxwell, "On Faraday's lines of force," *Trans. Cambridge Phil. Soc.*, **10**, pp. 27–83, 1856.
- [12] C.-T. Tai, *Generalized Vector and Dyadic Analysis*, New York: IEEE/Wiley, 1997.