

Simultaneous Neural Machine Translation using Connectionist Temporal Classification

Katsuki Chousa, Katsuhito Sudoh, Satoshi Nakamura
Nara Institute of Science and Technology

Abstract

Simultaneous machine translation is a variant of machine translation that starts the translation process before the end of an input. This task faces a trade-off between translation accuracy and latency. We have to determine when we start the translation for observed inputs so far, to achieve good practical performance. In this work, we propose a neural machine translation method to determine this timing in an adaptive manner. The proposed method introduces a special token ‘<wait>’, which is generated when the translation model chooses to read the next input token instead of generating an output token. It also introduces an objective function to handle the ambiguity in wait timings that can be optimized using an algorithm called Connectionist Temporal Classification (CTC). The use of CTC enables the optimization to consider all possible output sequences including ‘<wait>’ that are equivalent to the reference translations and to choose the best one adaptively. We apply the proposed method into simultaneous translation from English to Japanese and investigate its performance and remaining problems.

1 Introduction

Simultaneous translation is a translation task where the translation process starts before the end of an input. It helps real-time spoken language communications such as human conversations and public talks. A usual machine translation system works in the sentence level and starts its translation process after it reads the end of a sentence. It would not be appropriate for spoken languages due to roughly two issues: (1) sentence boundaries are not clear and (2) a large latency occurs for a long input.

Previous studies tackled this problem by an incremental process, in order to reduce the translation latency for a given input. Fujita et al. (2013)

proposed a phrase-based approach to the simultaneous translation based on phrasal reordering probabilities. Oda et al. (2015) proposed a syntax-based method to determine when to start translation of observed inputs. Such an approach faces a trade-off between speed and accuracy; reducing the translation latency using very limited context information also causes the loss in the translation accuracy. This becomes more serious especially in a syntactically-distant language pair such as English and Japanese, where we sometimes have to wait a latter part of a source language to determine the corresponding former part in a target language.

Recent neural machine translation (NMT) studies tried an incremental processing for the simultaneous translation. Gu et al. (2017) proposed a reinforcement learning approach to determine *when to translate* based on two different actions: READ to take one input token and WRITE to generate one output token. While they reported some latency reduction without the loss of translation accuracy, the NMT model itself is trained independently from this incremental manner and is not fully optimized for simultaneous translation. Ma et al. (2018) proposed a very simple incremental method called *Wait- k* , where the decoder starts to generate output tokens after the encoder reads k tokens and then works token-by-token. Here, some required inputs may not be observed by the encoder; however, the decoder has to predict the next output token even in that case. This approach enables a simple end-to-end simultaneous NMT with implicit anticipation of unobserved inputs. It showed high translation accuracy with small latency on some common English-to-German and Chinese-to-English datasets. The latency hyperparameter k can be used to control the speed-accuracy trade-off, but it has to be large enough for a distant language pair like English-Japanese. We observed a problem in translating a phrase longer

than k tokens in our pilot study on English-to-Japanese translation.

In this work, we propose a novel incremental NMT method that uses a special token $\langle \text{wait} \rangle$ in the target language which is generated when the translation model chooses to read the next input token instead of generating an output token. The proposed method uses Connectionist Temporal Classification (CTC) (Graves et al., 2006) to handle ambiguities in possible positions inserting $\langle \text{wait} \rangle$ in the training time. CTC is applied to sequential model training such as automatic speech recognition, where we have a reference word sequence but do not have the corresponding segmentation or alignment in an acoustic signal. We conduct experiments in English-to-Japanese simultaneous translation with the proposed and baseline methods and show the proposed method achieves a good translation performance with relatively small latency. The proposed method can determine when to wait or translate in an adaptive manner and is useful in simultaneous translation tasks.

2 Simultaneous machine translation by Wait- k model

First, we review a general NMT model following the formulation by Luong et al. (2015) and the “Wait- k ” model (Ma et al., 2018) that is the baseline model for simultaneous NMT.

Given a source sentence X and a target sentence Y as follows:

$$\begin{aligned} X &= \{\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_I\}, \\ Y &= \{\mathbf{y}_1, \mathbf{y}_2, \dots, \mathbf{y}_J\}, \end{aligned}$$

where $\mathbf{x}_i \in \mathbb{R}^{S \times 1}$ is a one-hot vector of the i -th input word, I is the length of the input sentence X , $\mathbf{y}_i \in \mathbb{R}^{T \times 1}$ is a one-hot vector of the i -th output word, and J is the length of the output sentence Y .

The problem of translation from the source to the target language can be solved by finding the best target language sentence $\hat{Y}$ that maximizes the conditional probability

$$\hat{Y} = \arg \max_Y p(Y|X). \quad (1)$$

In general NMT manner, the conditional probability is decomposed by the product of conditional generation probabilities of $\mathbf{y}_j$ given the source sen-

tence X and preceding target words $\mathbf{y}_{<j}$:

$$p(Y|X) = \prod_{j=1}^J p_{\theta}(\mathbf{y}_j | \mathbf{y}_{<j}, X), \quad (2)$$

where $\mathbf{y}_{<j}$ represents the target words up to position j , and θ indicates the model parameters. In contrast, the model for simultaneous translation has to output translated words given only prefix words of the source sentence. Therefore, the conditional probability is decomposed as follows:

$$p(Y|X) = \prod_{j=1}^J p_{\theta}(\mathbf{y}_j | \mathbf{y}_{<j}, \mathbf{x}_{<g(j)}), \quad (3)$$

where $\mathbf{x}_{<g(j)}$ are the target words up to position $g(j)$ and $g(j)$ represents the number of encoded source tokens when the model outputs j words. In the “Wait- k ” model, $g(j)$ is defined as follows:

$$g(j) = \begin{cases} k + j - 1 & (j < I - k) \\ I & (\text{otherwise}) \end{cases} \quad (4)$$

Here, k is the hyperparameter which indicates the target sentence generation is k tokens behind the source sentence input and it takes a constant value in the “Wait- k ” model.

The model is composed of an encoder (§2.1) and a decoder with the attention mechanism (§2.2) that are both implemented using recurrent neural networks (RNNs); the encoder converts source words into a sequence of vectors, and the decoder generates target language words one-by-one with the attention mechanism based on the conditional probability shown in the equation 2 and 3. The details are described below.

2.1 Encoder

The encoder takes a sequence of a source sentence X as inputs and returns forward hidden vectors $\vec{\mathbf{h}}_i (1 \leq i \leq I)$ of the forward RNNs:

$$\vec{\mathbf{h}}_i = \text{RNN}(\vec{\mathbf{h}}_{i-1}, \mathbf{x}_i). \quad (5)$$

In the general NMT model, they also calculate backward hidden vectors of backward RNNs from a reversed source sentence. However, we only use forward hidden vectors because we cannot use the information of the whole sentence on the simultaneous translation task.

2.2 Decoder with Attention

The decoder takes source hidden vectors as inputs and returns target language words one-by-one with the attention mechanism. The decoder RNNs recurrently generates target words using its hidden state and an output context. The conditional generation probability of the target word $\mathbf{y}_i$ defined as follows:

$$p_\theta(\mathbf{y}_j|\mathbf{y}_{<j}, \mathbf{x}_{\leq g(j)}) = \text{softmax}(\mathbf{W}_s \tilde{\mathbf{b}}_j), \quad (6)$$

$$\tilde{\mathbf{b}}_j = \tanh(\mathbf{W}_c[\mathbf{c}_j; \mathbf{d}_j]), \quad (7)$$

$$\mathbf{d}_j = \text{RNN}(\mathbf{d}_{j-1}, \mathbf{y}_{j-1}). \quad (8)$$

Here, $\mathbf{W}_c, \mathbf{W}_p$ are trainable parameters and $\mathbf{c}_j$ is a context vector to retrieve source language inputs in forms of a weighted sum of the source hidden vectors $\mathbf{h}_j$, defined as follows.

$$\mathbf{c}_j = \sum_{t=1}^{g(j)} \alpha_{ij} \vec{\mathbf{h}}_i, \quad (9)$$

$$\alpha_{ij} = \frac{\exp(\text{score}(\mathbf{d}_j^T, \vec{\mathbf{h}}_i))}{\sum_{t'=1}^{g(j)} \exp(\text{score}(\mathbf{d}_j^T, \vec{\mathbf{h}}_{t'}))}. \quad (10)$$

The *score* function above can be defined in some different ways as discussed by Luong et al. (2015). In this paper, we use *dot* attention for this *score* function.

3 Proposed Method

In this work, we proposed the method to decide the output timing adaptively. The proposed method introduces a special token $\langle \text{wait} \rangle$ which is output instead of delaying translation to target-side vocabulary.

In this section, we first review a standard objective function, softmax cross-entropy and show the problem that occurs when this function is applied to $\langle \text{wait} \rangle$ (§3.1). After that, we introduce an objective function, called Connectionist Temporal Classification, to handle this problem (§3.2). Finally, we propose a new objective function to adjust a trade-off between translation accuracy and latency (§3.3) and explain how to combine these objective functions (§3.4).

3.1 Softmax Cross-Entropy

Softmax Cross-Entropy (SCE) is a commonly used token-level objective function for multi-class classification including word generation in NMT,

defined as follows:

$$\ell_{ent} = - \sum_{j=1}^J \sum_{k=1}^K \mathbf{y}_{jk} \log p_\theta(\mathbf{y}_{jk}|\mathbf{y}_{<j}, \mathbf{x}_{<g(j)}), \quad (11)$$

where $\mathbf{y}_{ij}$ is a j -th element of the one-hot vector corresponding to the i -th words of the reference sentence and $p(\mathbf{y}_{jk}|\cdot)$ is the generation probability of $\mathbf{y}_{jk}$.

A correct sequence that corresponds to an output sequence one-by-one is necessary to use SCE as an objective function for NMT. However, in the proposed method, we cannot simply use SCE because we don't know when we should cause delay. To avoid this problem, we set the loss for delay tokens to 0 during the time step t ($t \leq g(I)$) which the model can output $\langle \text{wait} \rangle$, or while a source sentence is inputted.

3.2 Connectionist Temporal Classification

As we mentioned in the previous section, we set the loss value for $\langle \text{wait} \rangle$ to 0, but this causes the problem that it does not optimize about generating $\langle \text{wait} \rangle$. Against this problem, we use an objective function called Connectionist Temporal Classification (CTC) (Graves et al., 2006) for sequence-level optimization.

CTC extends output sequence, called Path $\pi = \Omega(\mathbf{y})$, to the length T by allowing token repetitions and outputting $\langle \text{wait} \rangle$. Conversely, we can obtain an original output sequence $\mathbf{y} = \Omega^{-1}(\pi)$ by removing $\langle \text{wait} \rangle$ and all token repetitions. The objective function is defined the sum of the probabilities of all possible paths $\pi \in \Omega(\mathbf{y})$ by using the forward-backward algorithm, as follows:

$$\begin{aligned} \ell_{ctc} &= \sum_{\pi \in \Omega(\mathbf{y})} p(\pi|X) \\ &= \sum_{\pi \in \Omega(\mathbf{y})} \prod_{t=1}^T p(\pi_t|\pi_{<t}, \mathbf{x}_{g(t)}), \end{aligned} \quad (12)$$

where π_t is a t -th element of π .

3.3 Delay Penalty

Furthermore, we introduce a new objective function, called Delay Penalty, to control latency. We use this function only when an output token causes the delay; that is, when the model outputs $\langle \text{wait} \rangle$ or the same token as a previous one. Delay Penalty is defined by a negative log-likelihood of the prob-

abilities for non-delayed tokens, as follows:

$$\ell_{def} = - \sum_{t=1}^T \log(1 - w_t), \quad (13)$$

$$w_t = \begin{cases} p(\langle \text{wait} \rangle | \mathbf{y}_{<t}, \mathbf{x}_{<g(t)}) & (\mathbf{y}_t = \langle \text{wait} \rangle) \\ p(\mathbf{y}_{t-1} | \mathbf{y}_{<t}, \mathbf{x}_{<g(t)}) & (\mathbf{y}_t = \mathbf{y}_{t-1}) \\ 0 & (\text{otherwise}) \end{cases} \quad (14)$$

3.4 Objective Function

For optimization, we combine three objective functions introduced so far, as follows:

$$\ell = \ell_{ent} + \ell_{ctc} + \alpha \ell_{del}. \quad (15)$$

Here, α is a hyperparameter to adjust the amount of latency directly.

4 Experiments

We conducted simultaneous translation experiments from English to Japanese and discussed accuracy, latency, and issues for translation results.

4.1 Settings

All models were implemented as described in the previous sections using PyTorch¹. Both the encoders and the decoders were two-layered unidirectional LSTM (Hochreiter and Schmidhuber, 1997), and the decoder used input feeding (Luong et al., 2015). The number of dimensions in word embeddings and hidden vectors was set to 512, and the minibatch size was 64. We use Adam (Kingma and Ba, 2015) for optimization with the default parameters. The learning rate was set to 10^{-1} , and gradient clipping was set to 5. The dropout probability was set to 0.3. The learning rate was adjusted by a decay factor of $1/\sqrt{2}$ when the validation loss was larger than that in the previous epoch. Then, we chose the best parameter/model with the smallest validation loss for evaluation.

We used two different corpora for the experiments: small_parallel_enja² and Asian Scientific Paper Excerpt Corpus (ASPEC) (Nakazawa et al., 2016). small_parallel_enja is a small-scale corpus that consists of sentences filtered sentence length 4 to 16 words, and ASPEC is a mid-scale corpus of the scientific paper domain. Table 1 shows their detailed statistics.

¹<https://pytorch.org>

²https://github.com/odashi/small_parallel_enja

Table 1: Number of sentences for each corpus used in the experiments.

Corpus	Number of Sentence		
	Train	Valid.	Test
small_parallel_enja	50k	500	500
ASPEC	964k	1790	1812

All datasets were tokenized into subword unit (Sennrich et al., 2016; Kudo and Richardson, 2018) by using Sentencepiece³. The source and target language vocabularies were independent, and their size was set to 4000 tokens for small_parallel_enja and 8000 tokens for ASPEC, respectively. We filtered out the sentence whose number of tokens was more than 60 tokens, or the length ratio was more than 9 from the training set.

We used “Wait-k” models and general NMT models as baseline models. General NMT models were attention-based encoder-decoder and it translated sentences from full-length source sentences (called **Full Sentence**). For evaluation metrics, we used BLEU (Papineni et al., 2002) and RIBES (Isozaki et al., 2010) to measure translation accuracy, and token-level delay to measure latency. We used Kytea (Neubig et al., 2011) as a tokenize method for evaluations of Japanese translation accuracy.

4.2 Experiments with Small-scale Corpus

We conducted small-scale experiments using small_parallel_enja. We compared different hyperparameters: $k = \{3, 5\}$ and $\alpha = \{0, 0.01, 0.03, 0.05\}$.

Table 2 shows the results in latency and automatic evaluation scores on small_parallel_enja. The full sentence scores are upper bounds of incremental methods. The proposed method reduced the average latency in more than 50% from the full sentence baseline with some loss in BLEU and RIBES. The BLEU and RIBES results by the proposed method were worse than those by Wait-k. This would be due to some degradation in smaller latency parts that were determined adaptively by the proposed methods while Wait-k keeps the fixed latency.

³<https://github.com/google/sentencepiece>

Table 2: Latency and automatic evaluation scores with small_parallel_enja. Latencies are shown by averages and standard deviations (in parentheses) in the number of tokens.

Method		Latency (#tokens)	BLEU	RIBES
Full sentence		9.75 ($\pm$ 2.69)	34.53	84.03
Wait-k (Ma et al., 2018)	k=3	3.00 ($\pm$ 0.00)	31.06	82.46
	k=5	5.00 ($\pm$ 0.00)	33.29	83.45
Ours	$\alpha=0.00$	4.32 ($\pm$ 3.14)	28.01	81.78
	$\alpha=0.01$	4.29 ($\pm$ 3.16)	30.42	82.60
	$\alpha=0.03$	2.88 ($\pm$ 2.95)	26.47	80.51
	$\alpha=0.05$	0.80 ($\pm$ 1.96)	22.60	77.86

4.3 Experiments with Mid-scale Corpus

We investigated the performance on longer and more complex sentences by the experiments using ASPEC. We compared different hyperparameters: $k = \{5, 7\}$ and $\alpha = \{0.03, 0.05, 0.1\}$.

Table 3 shows the results in latency and automatic evaluation scores on ASPEC. We can see the proposed method showed much larger latency than Wait-k. This is probably due to many long and complex phrases used in scientific articles in ASPEC. Wait-k has to translate such a long phrase without sufficient input observations due to its strict fixed latency strategy. On the other hand, the proposed method can wait for more input tokens adaptively by generating <wait> at the cost of large latency.

4.4 Discussion

In the experimental results above, the proposed method determined the translation latency adaptively, short delay for short and simple inputs as in small_parallel_enja and long delay for long and complex inputs as in ASPEC. Here we discuss our results in detail using some examples.

Table 4 shows translation examples on small_parallel_enja. In the first example, the proposed method gives a correct translation result by adaptive waits. Wait-k generated unrelated words 野球 (*baseball*) and 飲み (*drink*) due to the poor input observations with its small fixed latency. The proposed method waited until a subword *swim* was observed and successfully generate a word 泳ぐ (*swim*).

However, the proposed method sometimes generated consecutive <wait> symbols until the end of input, as shown in the second example. This is probably due to our training strategy; the latency penalty would not be large enough to choose small latency translation at the cost of some in-

crease in SCE- and CTC-based loss. The translation data in the experiments are not from simultaneous interpretation but standard translation, so the current task does not match with the proposed approach. The use of specialized data for simultaneous translation would be important in practice, such as *monotonic translations* like simultaneous translation.

5 Conclusion

In this paper, we proposed an adaptive latency control method for simultaneous neural machine translation in syntactically distant language pairs. We introduced a meta token <wait> to wait until the observation of the next input token. We proposed a CTC-based loss function to perform optimization using bilingual data without appropriate positions of <wait>, which is used along with the latency penalty and a standard word prediction loss. The experimental results suggest the proposed method determines when to translate or when to wait in an adaptive manner. Future work includes further analyses on translation accuracy in different latency conditions and time-based latency evaluation instead of the token-based one.

Acknowledgments

A part of this work is supported by JSPS Kakenhi JP17H06101.

References

- Tomoki Fujita, Graham Neubig, Sakriani Sakti, Tomoki Toda, and Satoshi Nakamura. 2013. Simple, lexicalized choice of translation timing for simultaneous speech translation. In *InterSpeech*, pages 3487–3491, Lyon, France.
- Alex Graves, Santiago Fernández, Faustino Gomez, and Jürgen Schmidhuber. 2006. Connectionist

Table 3: Latency and automatic evaluation scores with ASPEC.

Method		Latency (#tokens)	BLEU	RIBES
Full sentence		29.81 ($\pm$ 14.30)	32.22	80.17
Wait-k (Ma et al., 2018)	k=5	5.00 ($\pm$ 0.00)	21.53	71.40
	k=7	7.00 ($\pm$ 0.00)	23.20	73.21
Ours	$\alpha=0.03$	23.03 ($\pm$ 14.08)	24.86	72.59
	$\alpha=0.05$	21.96 ($\pm$ 13.88)	22.45	70.60
	$\alpha=0.1$	17.13 ($\pm$ 12.69)	23.66	72.27

Table 4: Translation examples in small-parallel-enja. *w* shows the generation of <wait> token.

Example (1)

Source	he	did	n	'	t	care	for	swimm	ing	.
Reference	彼	は	水泳	が	得意	で	は	な	かつ	た。
Wait-k ($k=3$)	<i>w</i>	<i>w</i>	<i>w</i>	彼	は	野球	を	飲	み	ま
(gross)	<i>He did not drink baseball.</i>									
Proposed ($\alpha=0.03$)	彼	は	<i>w</i>	<i>w</i>	<i>w</i>	<i>w</i>	<i>w</i>	泳	ぐ	の
(gross)	<i>He did not like swimming.</i>									

Example (2)

Source	it	'	s	business	.
Reference	それ	が	仕事	で	す。
Proposed ($\alpha=0.03$)	<i>w</i>	<i>w</i>	<i>w</i>	<i>w</i>	<i>w</i>
(gross)	<i>It's business.</i>				

temporal classification: labelling unsegmented sequence data with recurrent neural networks. In *Proceedings of the 23rd international conference on Machine learning*, pages 369–376. ACM.

Jiatao Gu, Graham Neubig, Kyunghyun Cho, and Victor OK Li. 2017. Learning to translate in real-time with neural machine translation. In *Proceedings of EACL*, volume 1, pages 1053–1062.

Sepp Hochreiter and Jürgen Schmidhuber. 1997. Long short-term memory. *Neural computation*, 9(8):1735–1780.

Hideki Isozaki, Tsutomu Hirao, Kevin Duh, Katsuhito Sudoh, and Hajime Tsukada. 2010. Automatic evaluation of translation quality for distant language pairs. In *Proceedings of the 2010 Conference on Empirical Methods in Natural Language Processing*, pages 944–952, Cambridge, MA. Association for Computational Linguistics.

Diederik P. Kingma and Jimmy Lei Ba. 2015. Adam: a method for stochastic optimization. In *Proceedings of ICLR2016*.

Taku Kudo and John Richardson. 2018. Sentence-Piece: A simple and language independent subword tokenizer and detokenizer for neural text processing. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 66–71, Brussels, Belgium. Association for Computational Linguistics.

Thang Luong, Hieu Pham, and Christopher D. Manning. 2015. Effective approaches to attention-based neural machine translation. In *Proceedings of EMNLP*, pages 1412–1421.

Mingbo Ma, Liang Huang, Hao Xiong, Kaibo Liu, Chuanqiang Zhang, Zhongjun He, Hairong Liu, Xing Li, and Haifeng Wang. 2018. Stacl: Simultaneous translation with integrated anticipation and controllable latency. *arXiv preprint arXiv:1810.08398*.

Toshiaki Nakazawa, Manabu Yaguchi, Kiyotaka Uchimoto, Masao Utiyama, Eiichiro Sumita, Sadao Kurohashi, and Hitoshi Isahara. 2016. Aspec: Asian scientific paper excerpt corpus. In *Proceedings of LREC 2016*, pages 2204–2208, Portorož, Slovenia.

Graham Neubig, Yosuke Nakata, and Shinsuke Mori. 2011. Pointwise prediction for robust, adaptable Japanese morphological analysis. In *Proceedings of the 49th Annual Meeting of the Association for Computational Linguistics: Human Language Technologies*, pages 529–533, Portland, Oregon, USA. Association for Computational Linguistics.

Yusuke Oda, Graham Neubig, Sakriani Sakti, Tomoki Toda, and Satoshi Nakamura. 2015. Syntax-based simultaneous translation through prediction of unseen syntactic constituents. In *Proceedings of the 53rd Annual Meeting of the Association for Computational Linguistics and the 7th International Joint Conference on Natural Language Processing*

(Volume 1: Long Papers), pages 198–207, Beijing, China. Association for Computational Linguistics.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. 2002. Bleu: a method for automatic evaluation of machine translation. In Proceedings of ACL, pages 311–318, Philadelphia, Pennsylvania, USA.

Rico Sennrich, Barry Haddow, and Alexandra Birch. 2016. Neural Machine Translation of Rare Words with Subword Units. In Proceedings of ACL, pages 1715–1725, Berlin, Germany.