

An Optimal Streaming Algorithm for Submodular Maximization with a Cardinality Constraint*

Naor Alaluf[†] Alina Ene[‡] Moran Feldman[§] Huy L. Nguyen[¶] Andrew Suh^{||}

December 31, 2021

Abstract

We study the problem of maximizing a *non-monotone* submodular function subject to a cardinality constraint in the streaming model. Our main contribution is a single-pass (semi-) streaming algorithm that uses roughly $O(k/\varepsilon^2)$ memory, where k is the size constraint. At the end of the stream, our algorithm post-processes its data structure using *any offline algorithm* for submodular maximization, and obtains a solution whose approximation guarantee is $\frac{\alpha}{1+\alpha} - \varepsilon$, where α is the approximation of the offline algorithm. If we use an exact (exponential time) post-processing algorithm, this leads to $\frac{1}{2} - \varepsilon$ approximation (which is nearly optimal). If we post-process with the algorithm of [8], that achieves the state-of-the-art offline approximation guarantee of $\alpha = 0.385$, we obtain 0.2779-approximation in polynomial time, improving over the previously best polynomial-time approximation of 0.1715 due to [25]. It is also worth mentioning that our algorithm is combinatorial and deterministic, which is rare for an algorithm for non-monotone submodular maximization, and enjoys a fast update time of $O(\frac{\log k + \log(1/\alpha)}{\varepsilon^2})$ per element.

*An earlier version of this paper appeared in IICALP 2020 [1].

[†]Department of Mathematics and Computer Science, Open University of Israel, naoralaluf@gmail.com.

[‡]Department of Computer Science, Boston University, aene@bu.edu.

[§]Department of Computer Science, University of Haifa, moranfe@cs.haifa.ac.il.

[¶]Khoury College of Computer and Information Science, Northeastern University, hlnghuyen@cs.princeton.edu.

^{||}Department of Computer Science, Boston University, asuh9@bu.edu.

1 Introduction

In this paper, we study the problem of maximizing a *non-monotone* submodular function subject to a cardinality (size) constraint in the streaming model. This problem captures problems of interest in a wide-range of domains, such as machine learning, data mining, combinatorial optimization, algorithmic game theory, social networks, and many others. A representative application is data summarization, where the goal is to select a small subset of the data that captures the salient features of the overall dataset [4]. One can model these problems as submodular maximization with a cardinality constraint: the submodular objective captures how informative the summary is, as well as other considerations such as how diverse the summary is, and the cardinality constraint ensures that the summary is small. Obtaining such a summary is very beneficial when working with massive data sets, that may not even fit into memory, since it makes it possible to analyze the data using algorithms that would be prohibitive to run on the entire dataset.

There have been two main approaches to deal with the large size of modern data sets: the *distributed* computation approach partitions the data across many machines and uses local computation on the machines and communication across the machines in order to perform the analysis, and the *streaming* computation approach processes the data in a stream using only a small amount of memory and (ideally) only a single pass over the data. Classical algorithms for submodular maximization, such as the Greedy algorithm, are not suitable in these settings since they are centralized and require many passes over the data. Motivated by the applications as well as theoretical considerations, there has been a significant interest in studying submodular maximization problems both in the distributed and the streaming setting, leading to many new results and insights [33, 40, 4, 14, 17, 37, 6, 39, 5, 21, 38, 25, 44].

Despite this significant progress, several fundamental questions remain open both in the streaming and distributed setting. In the streaming setting, which is the main focus of this paper, submodular maximization is fairly well understood when the objective function is additionally *monotone*—i.e., we have $f(A) \leq f(B)$ whenever $A \subseteq B$. For example, the Greedy approach, which obtains an optimal $(1 - 1/e)$ -approximation in the centralized setting when the function is monotone [41], can be adapted to the streaming model [33, 4]. This yields the single-threshold Greedy algorithm: make a single pass over the data and select an item if its marginal gain exceeds a suitably chosen threshold. If the threshold is chosen to be $\frac{1}{2} \frac{f(\text{OPT})}{k}$, where $f(\text{OPT})$ is the value of the optimal solution and k is the cardinality constraint, then the single-threshold Greedy algorithm is guaranteed to achieve $\frac{1}{2}$ -approximation. Although the value of the optimal solution is unknown, it can be estimated based on the largest singleton value even in the streaming setting [4]. The algorithm uses the maximum singleton value to make $O(\varepsilon^{-1} \log k)$ guesses for $f(\text{OPT})$ and, for each guess, it runs the single-threshold Greedy algorithm; which leads to $(\frac{1}{2} - \varepsilon)$ -approximation. Remarkably, this approximation guarantee is optimal in the streaming model even if we allow unbounded computational power: Feldman *et al.* [27] showed that any algorithm for this problem that achieves an approximation better than $\frac{1}{2}$ requires $\Omega\left(\frac{n}{k^3}\right)$ memory, where n is the length of the stream. Additionally, the single-threshold Greedy algorithm enjoys a fast update time of $O(\varepsilon^{-1} \log k)$ marginal value computations per item and uses only $O(\varepsilon^{-1} k \log k)$ space.¹

In contrast, the general problem with a *non-monotone* objective has proved to be considerably more challenging. Even in the centralized setting, the Greedy algorithm fails to achieve any constant approximation guarantee when the objective is non-monotone. Thus, several approaches have been developed for handling non-monotone objectives in this setting, including local search [22, 35, 34], continuous optimization [26, 20, 8] and sampling [11, 24]. The currently best approximation

¹A variant of the algorithm due to [31] has an even better space complexity of $O(k/\varepsilon)$.

guarantee is 0.385 [8], the strongest inapproximability is 0.491 [29], and it remains a long-standing open problem to settle the approximability of submodular maximization subject to a cardinality constraint.

Adapting the above techniques to the streaming setting is challenging, and the approximation guarantees are weaker. The main approach for non-monotone maximization in the streaming setting has been to extend the local search algorithm of Chakrabarti and Kale [14] from monotone to non-monotone objectives. This approach was employed in a sequence of works [17, 25, 38], leading to the currently best approximation of $\frac{1}{3+2\sqrt{2}} \approx 0.1715$.² This naturally leads to the following questions.

- *What is the optimal approximation ratio achievable for submodular maximization in the streaming model? In particular, is it possible to achieve $\frac{1}{2} - \varepsilon$ approximation using an algorithm that uses only $\text{poly}(k, 1/\varepsilon)$ space?*
- *Is there a good streaming algorithm for non-monotone functions based on the single-threshold Greedy algorithm that works so well for monotone functions?*
- *Can we exploit existing heuristics for the offline problem in the streaming setting?*

Our contributions. In this work, we give an affirmative answer to all of the above questions. Specifically, we give a streaming algorithm³ that performs a single pass over the stream and outputs sets of size $O(k/\varepsilon)$ that can be post-processed using *any offline algorithm* for submodular maximization. The post-processing is itself quite straightforward: we simply run the offline algorithm on the output set to obtain a solution of size at most k . We show that, if the offline algorithm achieves α -approximation, then we obtain $(\frac{\alpha}{1+\alpha} - \varepsilon)$ -approximation. One can note that if we post-process using an exact (exponential time) algorithm, we obtain $(\frac{1}{2} - \varepsilon)$ -approximation. This matches the inapproximability result proven by [27] for the special case of a monotone objective function. Furthermore, we show that in the non-monotone case any streaming algorithm guaranteeing $(\frac{1}{2} + \varepsilon)$ -approximation for some positive constant ε must use in fact $\Omega(n)$ space.⁴ Thus, we essentially settle the approximability of the problem if exponential-time computation is allowed.

The best (polynomial-time) approximation guarantee that is currently known in the offline setting is $\alpha = 0.385$ [8]. If we post-process using this algorithm, we obtain 0.2779-approximation in polynomial time, improving over the previously best polynomial-time approximation of 0.1715 due to [25]. The offline algorithm of [8] is based on the multilinear extension, and thus is quite slow. One can obtain a more efficient overall algorithm by using the combinatorial random Greedy algorithm of [11] that achieves $\frac{1}{e}$ -approximation. Furthermore, any existing heuristic for the offline problem can be used for post-processing, exploiting their effectiveness beyond the worst case.

Variants of our algorithm. Essentially, every algorithm for non-monotone submodular maximization includes a randomized component. Oftentimes this component is explicit, but in some cases it takes more subtle forms such as maintaining multiple solutions that are viewed as the support of a distribution [7, 24] or using the multilinear extensions (which is defined via expecta-

²Chekuri et al. [17] claimed an improved approximation ratio of $\frac{1}{2+\varepsilon} - \varepsilon$ for a cardinality constraint, but an error was later found in the proof of this improved ratio [16]. See Appendix A for more details.

³Formally, all the algorithms we present are semi-streaming algorithms, i.e., their space complexity is nearly linear in k . Since this is unavoidable for algorithms designed to output an approximate solution (as opposed to just estimating the value of the optimal solution), we ignore the difference between streaming and semi-streaming algorithms in this paper and use the two terms interchangeably.

⁴This result is a simple adaptation of a result due to Buchbinder et al. [12]. For completeness, we include the proof in Appendix B.

tions) [26, 8]. We present in this work three variants of our algorithm based on the above three methods of introducing a randomized component into the algorithm.

Perhaps the most straightforward way to introduce a randomized component into the single-threshold Greedy algorithm is to use the multilinear extension as the objective function and include only fractions of elements in the solution (which corresponds to including the elements in the solution only with some bounded probability). This has the advantage of keeping the algorithm almost deterministic (in fact, completely deterministic when the multilinear extension can be evaluated deterministically), which allows for a relatively simple analysis of the algorithm and a low space complexity of $O(k \log \alpha^{-1}/\varepsilon^2)$. However, the time complexity of an algorithm obtained via this approach depends on the complexity of evaluating the multilinear extension, which in general can be quite high. In Appendix C, we describe and analyze a variant of our algorithm (named `STREAMPROCESSEXTENSION`) which is based on the multilinear extension.

To avoid the multilinear extension, and its associated time complexity penalty, one can use true randomization, and pass every arriving element to single-threshold Greedy only with a given probability. However, analyzing such a combination of single-threshold Greedy with true randomization is difficult because it requires delicate care of the event that the single-threshold Greedy algorithm fills up the budget. In particular, this was the source of the subtle error mentioned above in one of the results of [17]. Our approach for handling this issue is to consider two cases depending on the probability that the budget is filled up in a run (this is a good event since the resulting solution has good value). If this probability is sufficiently large (at least ε), we repeat the basic algorithm $O(\ln(1/\varepsilon)/\varepsilon)$ times in parallel to boost the probability of this good event to $1 - \varepsilon$. Otherwise, the probability that the budget is not filled up in a run is at least $1 - \varepsilon$, and conditioning on this event changes the probabilities by only a $1 - \varepsilon$ factor. Another issue with true randomness is that some elements can be randomly discarded despite being highly desirable. Following ideas from distributed algorithms [37, 6, 5], this issue can also be solved by running multiple copies of the algorithm in parallel since such a run guarantees that with high probability every desirable element is processed by some copy. Using this approach we get a variant of our algorithm named `STREAMPROCESSRANDOMIZED` which can be found in Appendix D. `STREAMPROCESSRANDOMIZED` is combinatorial and fast (it has an update time of $\tilde{O}(\varepsilon^{-2})$ marginal value computations per element), but due to the heavy use of parallel runs, it has a slightly worse space complexity of $\tilde{O}(k/\varepsilon^3)$.

The two above discussed variants of our algorithm appeared already in an earlier conference version of this paper [1]. Our main result, however, is a new variant of our algorithm (named `STREAMPROCESS`) based on the technique of maintaining multiple solutions and treating them as the support of a distribution. In retrospect, creating a variant based on this technique is natural since it combines the advantages of the two previous approaches. Specifically, we get an algorithm which is deterministic and combinatorial, has a relatively simple analysis and enjoys a low space complexity of $O(k\varepsilon^{-2} \log \alpha^{-1})$ and a low update time of $O(\varepsilon^{-2} \log(k/\alpha))$ marginal value computations per element.

While the last variant of our algorithm has the best time and space guarantees, we give also the two earlier variants for two reasons. The first reason is that they demonstrate the first use of techniques such as continuous extensions and random partitions in the context of streaming algorithms for submodular maximization, and thus, greatly expand the toolkit available in this context. These techniques have proved to be quite versatile in the sequential and distributed settings, and we hope that they will lead to further developments in the streaming setting as well. The second reason is that, while the asymptotic approximation guarantees of all three variants of our algorithm are identical given a black box offline α -approximation algorithm, they might differ when the offline algorithm has additional properties. For example, the approximation ratio of the offline algorithm might depend on the ratio between k and the number of elements in its

input (see [11] for an example of such an algorithm). Given such an offline algorithm, it might be beneficial to set the parameters controlling the number of elements passed to the offline algorithm so that only a moderate number of elements is passed, which is a regime in which the three variants of our algorithm produce different approximation guarantees. Hence, one of the first two variants of our algorithm might end up having a better approximation guarantee than that of the last variant if future research yields offline algorithms with relevant properties.

1.1 Additional related work

The problem of maximizing a non-negative monotone submodular function subject to a cardinality or a matroid constraint was studied (in the offline model) already in the 1970's. In 1978, Nemhauser et al. [43] and Fisher et al. [28] showed that a natural greedy algorithm achieves an approximation ratio of $1 - 1/e \approx 0.632$ for this problem when the constraint is a cardinality constraint and an approximation ratio of $1/2$ for matroid constraints. The $1 - 1/e$ approximation ratio for cardinality constraints was shown to be optimal already on the same year by Nemhauser and Wolsey [42], but the best possible approximation ratio for matroid constraints was open for a long time. Only a decade ago, Calinescu et al. [13] managed to show that a more involved algorithm, known as “continuous greedy”, can achieve $(1 - 1/e)$ -approximation for this type of constraint, which is tight since matroid constraints generalize cardinality constraints.

Unlike the natural greedy algorithm, continuous greedy is a randomized algorithm, which raised an interesting question regarding the best possible approximation ratio for matroid constraints that can be achieved by a deterministic algorithm. Very recently, Buchbinder et al. [10] made a slight step towards answering this question. Specifically, they described a deterministic algorithm for maximizing a monotone submodular function subject to a matroid constraint whose approximation ratio is 0.5008. This algorithm shows that the $1/2$ -approximation of the greedy algorithm is not the right answer for the above mentioned question.

Many works have studied also the offline problem of maximizing a non-negative (not necessarily monotone) submodular function subject to a cardinality or matroid constraint [8, 11, 19, 20, 23, 26]. The most recent of these works achieves an approximation ratio of 0.385 for both cardinality and matroid constraints [8]. In contrast, it is known that no polynomial time algorithm can achieve an approximation ratio of 0.497 for cardinality constraints or 0.478 for matroid constraints, respectively [29].

The study of streaming algorithms for submodular maximization problems is related to the study of online algorithms for such problems. A partial list of works on algorithms of the last kind includes [3, 9, 12, 15, 30, 32].

2 Preliminaries

Basic notation. Let V denote a finite ground set of size $n := |V|$. We occasionally assume without loss of generality that $V = \{1, 2, \dots, n\}$, and use, e.g., $x = (x_1, x_2, \dots, x_n)$ to denote a vector in \mathbb{R}^V . For two vectors $x, y \in \mathbb{R}^V$, we let $x \vee y$ and $x \wedge y$ be the vectors such that $(x \vee y)_e = \max\{x_e, y_e\}$ and $(x \wedge y)_e = \min\{x_e, y_e\}$ for all $e \in V$. For a set $S \subseteq V$, we let $\mathbf{1}_S$ denote the indicator vector of S , i.e., the vector that has 1 in every coordinate $e \in S$ and 0 in every coordinate $e \in V \setminus S$. Given an element $e \in V$, we use $\mathbf{1}_e$ as a shorthand for $\mathbf{1}_{\{e\}}$. Furthermore, if S is a random subset of V , we use $\mathbb{E}[\mathbf{1}_S]$ to denote the vector p such that $p_e = \Pr[e \in S]$ for all $e \in V$ (i.e., the expectation is applied coordinate-wise).

Submodular functions. In this paper, we consider the problem of maximizing a non-negative submodular function subject to a cardinality constraint. A set function $f: 2^V \rightarrow \mathbb{R}$ is submodular

if $f(A) + f(B) \geq f(A \cap B) + f(A \cup B)$ for all subsets $A, B \subseteq V$. Additionally, given a set $S \subseteq V$ and an element $e \in V$, we use $f(e \mid S)$ to denote the marginal contribution of e to S with respect to the set function f , i.e., $f(e \mid S) = f(S \cup \{e\}) - f(S)$.

Continuous extensions. We make use of two standard continuous extensions of submodular functions. The first of these extensions is known as the *multilinear extension*. To define this extension, we first need to define the random set $\mathbf{R}(x)$. For every vector $x \in [0, 1]^V$, $\mathbf{R}(x)$ is defined as a random subset of V that includes every element $e \in V$ with probability x_e , independently. The multilinear extension F of f is now defined for every $x \in [0, 1]^V$ by

$$F(x) = \mathbb{E}[f(\mathbf{R}(x))] = \sum_{A \subseteq V} f(A) \cdot \Pr[\mathbf{R}(x) = A] = \sum_{A \subseteq V} \left(f(A) \cdot \prod_{e \in A} x_e \cdot \prod_{e \notin A} (1 - x_e) \right).$$

One can observe from the definition that F is indeed a multilinear function of the coordinates of x , as suggested by its name. Thus, if we use the shorthand $\partial_e F(x)$ for the first partial derivative $\frac{\partial F(x)}{\partial x_e}$ of the multilinear extension F , then $\partial_e F(x) = F(x \vee \mathbf{1}_e) - F(x \wedge \mathbf{1}_{V \setminus \{e\}})$.

The second extension we need is known as the *Lovász extension*. Unlike the multilinear extension that explicitly appears in one of the variants of our algorithm, the Lovász extension is not part of any of these variants. However, it plays a central role in the analyses of two of them. The Lovász extension $\hat{f}: [0, 1]^V \rightarrow \mathbb{R}$ is defined as follows. For every $x \in [0, 1]^V$, $\hat{f}(x) = \mathbb{E}_{\theta \sim [0, 1]}[f(\{e \in V : x_e \geq \theta\})]$, where we use the notation $\theta \sim [0, 1]$ to denote a value chosen uniformly at random from the interval $[0, 1]$. The Lovász extension \hat{f} of a non-negative submodular function has the following properties: (1) convexity: $c\hat{f}(x) + (1 - c)\hat{f}(y) \geq \hat{f}(cx + (1 - c)y)$ for all $x, y \in [0, 1]^V$ and all $c \in [0, 1]$ [36]; (2) restricted scale invariance: $\hat{f}(cx) \geq c\hat{f}(x)$ for all $x \in [0, 1]^V$ and all $c \in [0, 1]$; (3) it lower bounds the multilinear extension, i.e., $F(x) \geq \hat{f}(x)$ for every $x \in [0, 1]^V$ [45, Lemma A.4].

3 Simplified Algorithm

The properties of our main algorithm (STREAMPROCESS—the third variant discussed above) are summarized by the following theorem.

Theorem 1. *Assume there exists an α -approximation offline algorithm OFFLINEALG for maximizing a non-negative submodular function subject to a cardinality constraint whose space complexity is nearly linear in the size of the ground set. Then, for every constant $\varepsilon \in (0, 1]$, there exists an $(\frac{\alpha}{1+\alpha} - \varepsilon)$ -approximation semi-streaming algorithm for maximizing a non-negative submodular function subject to a cardinality constraint. The algorithm stores $O(k\varepsilon^{-2})$ elements and makes $O(\varepsilon^{-2} \log k)$ marginal value computations while processing each arriving element.⁵ Furthermore, if OFFLINEALG is deterministic, then so is the algorithm that we get.*

In this section, we introduce a simplified version of the algorithm used to prove Theorem 1. This simplified version (given as Algorithm 1) captures our main new ideas, but makes the simplifying assumption that it has access to an estimate τ of $f(\text{OPT})$ obeying $(1 - \varepsilon/2) \cdot f(\text{OPT}) \leq \tau \leq f(\text{OPT})$. Such an estimate can be produced using well-known techniques, at the cost of a slight increase in the space complexity and update time of the algorithm. More specifically, in Section 4 we formally show that one such technique due to [31] can be used for that purpose, and that it increases the space

⁵Formally, the number of elements stored by the algorithm and the number of marginal value computations also depend on $\log \alpha^{-1}$. Since α is typically a positive constant, or at least lower bounded by a positive constant, we omit this dependence from the statement of the theorem.

complexity and update of the algorithm only by factors of $O(\varepsilon^{-1} \log \alpha^{-1})$ and $O(\varepsilon^{-1} \log(k/\alpha))$, respectively.

Algorithm 1 gets two parameters: the approximation ratio α of OFFLINEALG and an integer $p \geq 1$. The algorithm maintains p solutions S_1, S_2, \dots, S_p . All these solutions start empty, and the algorithm may add each arriving element to at most one of them. Specifically, when an element e arrives, the algorithm checks whether there exists a solution S_i such that (1) S_i does not already contain k elements, and (2) the marginal contribution of e with respect to S_i exceeds the threshold of $c\tau/k$ for $c = \alpha/(1+\alpha)$. If there is such a solution, the algorithm adds e to it (if there are multiple such solutions, the algorithm adds e to an arbitrary one of them); otherwise, the algorithm discards e . After viewing all of the elements, Algorithm 3 generates one more solution S_o by executing OFFLINEALG on the union of the p solutions S_1, S_2, \dots, S_p . The output of the algorithm is then the best solution among the $p+1$ generated solutions.

Algorithm 1: STREAMPROCESS (simplified) (p, α)

- 1 Let $c \leftarrow \frac{\alpha}{1+\alpha}$.
 - 2 **for** $i = 1$ **to** p **do** Let $S_i \leftarrow \emptyset$.
 - 3 **for** *each arriving element* e **do**
 - 4 **if** *there exists an integer* $1 \leq i \leq p$ *such that* $|S_i| < k$ *and* $f(e \mid S_i) \geq \frac{c\tau}{k}$ **then**
 - 5 Update $S_i \leftarrow S_i \cup \{e\}$ (if there are multiple options for i , pick an arbitrary one).
 - 6 Find another feasible solution $S_o \subseteq \bigcup_{i=1}^p S_i$ by running OFFLINEALG with $\bigcup_{i=1}^p S_i$ as the ground set.
 - 7 **return** the solution maximizing f among S_o and the p solutions S_1, S_2, \dots, S_p .
-

Since Algorithm 1 stores elements only in the $p+1$ solutions it maintains, and all these solutions are feasible (and thus, contain only k elements), we immediately get the following observation. Note that this observation implies (in particular) that Algorithm 1 is a semi-streaming algorithm for a constant p when the space complexity of OFFLINEALG is nearly linear.

Observation 2. *Algorithm 1 stores at most $O(pk)$ elements, and makes at most p marginal value calculations while processing each arriving element.*

We now divert our attention to analyzing the approximation ratio of Algorithm 1. Let us denote by \hat{S}_i the final set S_i (i.e., the content of this set when the stream ends), and consider two cases. The first (easy) case is when at least one of the solutions S_1, S_2, \dots, S_p reaches a size of k . The next lemma analyzes the approximation guarantee of Algorithm 1 in this case.

Lemma 3. *If there is an integer $1 \leq i \leq p$ such that $|\hat{S}_i| = k$, then the output of Algorithm 1 has value of at least $\frac{\alpha\tau}{1+\alpha}$.*

Proof. Denote by e_1, e_2, \dots, e_k the elements of \hat{S}_i in the order of their arrival. Using this notation, the value of $f(\hat{S}_i)$ can be written as follows.

$$f(\hat{S}_i) = f(\emptyset) + \sum_{j=1}^k f(e_j \mid \{e_1, e_2, \dots, e_{j-1}\}) \geq \sum_{i=1}^k \frac{\alpha\tau}{(1+\alpha)k} = \frac{\alpha\tau}{1+\alpha} ,$$

where the inequality holds since the non-negativity of f implies $f(\emptyset) \geq 0$ and Algorithm 1 adds an element e_j to S_i only when $f(e_j \mid \{e_1, e_2, \dots, e_{j-1}\}) \geq \frac{c\tau}{k} = \frac{\alpha\tau}{(1+\alpha)k}$. The lemma now follows since the solution outputted by Algorithm 1 is at least as good as S_i . \square

Consider now the case in which no set S_i reaches the size of k . In this case our objective is to show that at least one of the solutions computed by Algorithm 1 has a large value. Lemmata 5 and 6 lower bound the value of the average solution among S_1, S_2, \dots, S_p and the solution S_o , respectively. The proof of Lemma 5 uses the following known lemma.

Lemma 4 (Lemma 2.2 from [11]). *Let $f: 2^V \rightarrow \mathbb{R}_{\geq 0}$ be a non-negative submodular function. Denote by $A(p)$ a random subset of A where each element appears with probability at most p (not necessarily independently). Then, $\mathbb{E}[f(A(p))] \geq (1 - p) \cdot f(\emptyset)$.*

Let $O = \text{OPT} \setminus \bigcup_{i=1}^p \hat{S}_i$, and let $b = |O|/k$.

Lemma 5. *If $|\hat{S}_i| < k$ for every integer $1 \leq i \leq p$, then, for every fixed set $A \subseteq V$, $p^{-1} \cdot \sum_{i=1}^p f(\hat{S}_i \cup A) \geq (1 - p^{-1}) \cdot f(O \cup A) - \alpha b \tau / (1 + \alpha)$.*

Proof. The elements in O were rejected by Algorithm 1. Since no set S_i reaches a size of k , this means that the marginal contribution of the elements of O with respect to every set S_i at the time of their arrival was smaller than $c\tau/k$. Moreover, since Algorithm 1 only adds elements to its solutions during its execution, the submodularity of f guarantees that the marginals of the elements of O are below this threshold also with respect to $\hat{S}_1 \cup A, \hat{S}_2 \cup A, \dots, \hat{S}_p \cup A$. More formally, we get

$$f(e \mid \hat{S}_i \cup A) < \frac{c\tau}{k} = \frac{\alpha\tau}{k(1+\alpha)} \quad \forall e \in O \text{ and integer } 1 \leq i \leq p .$$

Using the submodularity of f again, this implies that for every integer $1 \leq i \leq p$

$$f(\hat{S}_i \cup O \cup A) \leq f(\hat{S}_i \cup A) + \sum_{e \in O} f(e \mid \hat{S}_i \cup A) \leq f(\hat{S}_i \cup A) + |O| \cdot \frac{\alpha\tau}{k(1+\alpha)} = f(\hat{S}_i \cup A) + \frac{\alpha b \tau}{1+\alpha} .$$

Adding up the above inequalities (and dividing by p), we get

$$p^{-1} \cdot \sum_{i=1}^p f(\hat{S}_i \cup A) \geq p^{-1} \cdot \sum_{i=1}^p f(\hat{S}_i \cup O \cup A) - \frac{\alpha b \tau}{1+\alpha} .$$

We now note that $p^{-1} \cdot \sum_{i=1}^p f(\hat{S}_i \cup O \cup A)$ can be viewed as the expected value of a non-negative submodular function $g(S) = f(S \cup O \cup A)$ over a random set S that is equal to every one of the sets $\hat{S}_1, \hat{S}_2, \dots, \hat{S}_p$ with probability $1/p$. Since the sets $\hat{S}_1, \hat{S}_2, \dots, \hat{S}_p$ are disjoint, S contains every element with probability at most $1/p$, and thus, by Lemma 4,

$$p^{-1} \cdot \sum_{i=1}^p f(\hat{S}_i \cup O \cup A) = \mathbb{E}[g(S)] \geq (1 - p^{-1}) \cdot g(\emptyset) = (1 - p^{-1}) \cdot f(O \cup A) .$$

The lemma now follows by combining the last two inequalities. \square

As mentioned above, our next step is to get a lower bound on the value of $f(S_o)$. One easy way to get such a lower bound is to observe that $\text{OPT} \setminus O$ is a subset of $\bigcup_{i=1}^p \hat{S}_i$ of size at most k , and thus, is a feasible solution for the instance faced by the algorithm OFFLINEALG used to find S_o ; which implies $\mathbb{E}[f(S_o)] \geq \alpha \cdot f(\text{OPT} \setminus O)$ since OFFLINEALG is an α -approximation algorithm. The following lemma proves a more involved lower bound by considering the vectors $(b\mathbf{1}_{\hat{S}_i}) \vee \mathbf{1}_{\text{OPT} \setminus O}$ as feasible fractional solutions for the same instance (using rounding methods such as Pipage Rounding or Swap Rounding [13, 18], such feasible fractional solutions can be converted into integral feasible solutions of at least the same value).

Lemma 6. *If $|\hat{S}_i| < k$ for every integer $1 \leq i \leq p$, then $\mathbb{E}[f(S_o)] \geq \alpha b \tau (1 - p^{-1} - \alpha b / (1 + \alpha)) + \alpha(1 - b) \cdot f(\text{OPT} \setminus O)$.*

Proof. Fix some integer $1 \leq i \leq p$, and consider the vector $(b\mathbf{1}_{\hat{S}_i}) \vee \mathbf{1}_{\text{OPT} \setminus O}$. Clearly,

$$\|(b\mathbf{1}_{\hat{S}_i}) \vee \mathbf{1}_{\text{OPT} \setminus O}\|_1 \leq b \cdot |\hat{S}_i| + |\text{OPT} \setminus O| \leq |O| + |\text{OPT} \setminus O| = |\text{OPT}| \leq k ,$$

where the second inequality holds by the definition of b since $|\hat{S}_i| < k$. Given the last property of the vector $(b\mathbf{1}_{\hat{S}_i}) \vee \mathbf{1}_{\text{OPT} \setminus O}$, standard rounding techniques such as Pipage Rounding [13] and Swap Rounding [18] can be used to produce from this vector a set $A_i \subseteq \hat{S}_i \cup (\text{OPT} \setminus O) \subseteq \bigcup_{i=1}^p \hat{S}_i$ of size at most k such that $f(A_i) \geq F((b\mathbf{1}_{\hat{S}_i}) \vee \mathbf{1}_{\text{OPT} \setminus O})$. Since S_o is produced by the algorithm OFFLINEALG whose approximation ratio is α and A_i is one possible output for this algorithm, this implies $\mathbb{E}[f(S_o)] \geq \alpha \cdot f(A_i) \geq \alpha \cdot F((b\mathbf{1}_{\hat{S}_i}) \vee \mathbf{1}_{\text{OPT} \setminus O})$. Furthermore, by averaging this equation over all the possible values of i , we get

$$\begin{aligned} \mathbb{E}[f(S_o)] &\geq \alpha p^{-1} \cdot \sum_{i=1}^p F((b\mathbf{1}_{\hat{S}_i}) \vee \mathbf{1}_{\text{OPT} \setminus O}) \\ &\geq \alpha p^{-1} \cdot \left[(1 - b) \cdot \sum_{i=1}^p f(\text{OPT} \setminus O) + b \cdot \sum_{i=1}^p f(\hat{S}_i \cup (\text{OPT} \setminus O)) \right] \\ &\geq \alpha(1 - b) \cdot f(\text{OPT} \setminus O) + \alpha b [(1 - p^{-1}) \cdot f(\text{OPT}) - \alpha b \tau / (1 + \alpha)] , \end{aligned}$$

where the second inequality holds since the submodularity of f implies that $F((t \cdot \mathbf{1}_{\hat{S}_i}) \vee \mathbf{1}_{\text{OPT} \setminus O})$ is a concave function of t within the range $[0, 1]$ (and b falls inside this range), and the last inequality holds by Lemma 5 (for $A = \text{OPT} \setminus O$). The lemma now follows by recalling that $f(\text{OPT}) \geq \tau$. \square

Combining the guarantees of the last two lemmata we can now obtain a lower bound on the value of the solution of Algorithm 1 in the case that $|\hat{S}_i| < k$ for every integer $1 \leq i \leq p$ which is independent of b .

Corollary 7. *If $|\hat{S}_i| < k$ for every integer $1 \leq i \leq p$, then the output of Algorithm 1 has value of at least $\left(\frac{\alpha}{\alpha+1} - 2p^{-1}\right) \tau$.*

Proof. The corollary follows immediately from the non-negativity of f when $p = 1$. Thus, we may assume $p \geq 2$ in the rest of the proof.

Since Algorithm 1 outputs the best solution among the $p + 1$ solutions it creates, we get by Lemma 5 (for $A = \emptyset$) and Lemma 6 that the value of the solution it outputs is at least

$$\begin{aligned} \max \left\{ p^{-1} \sum_{i=1}^p f(\hat{S}_i), f(S_o) \right\} &\geq \max \{ (1 - p^{-1}) \cdot f(O) - \alpha b \tau / (1 + \alpha), \\ &\quad \alpha b \tau (1 - p^{-1} - \alpha b / (1 + \alpha)) + \alpha(1 - b) \cdot f(\text{OPT} \setminus O) \} \\ &\geq \frac{\alpha(1 - b)}{\alpha(1 - b) + 1 - p^{-1}} \cdot \left[(1 - p^{-1}) \cdot f(O) - \alpha b \tau / (1 + \alpha) \right] \\ &\quad + \frac{1 - p^{-1}}{\alpha(1 - b) + 1 - p^{-1}} \cdot \left[\alpha b \tau (1 - p^{-1} - \alpha b / (1 + \alpha)) + \alpha(1 - b) \cdot f(\text{OPT} \setminus O) \right] . \end{aligned}$$

Note now that the submodularity and non-negativity of f guarantee together $f(O) + f(\text{OPT} \setminus O) \geq f(\text{OPT}) \geq \tau$. Using this fact and the non-negativity of f , the previous inequality yields

$$\begin{aligned} \frac{\max \left\{ p^{-1} \sum_{i=1}^p f(\hat{S}_i), f(S_o) \right\}}{\alpha \tau} &\geq \\ &\max \left\{ 0, \frac{(1-b)(1-p^{-1}) - \alpha b(1-b)/(1+\alpha) + b(1-p^{-1})(1-p^{-1} - \alpha b/(1+\alpha))}{\alpha(1-b) + 1 - p^{-1}} \right\} \\ &\geq \max \left\{ 0, \frac{(1-b)(1-p^{-1}) - \alpha b(1-b)/(1+\alpha) + b(1-p^{-1})(1-p^{-1} - \alpha b/(1+\alpha))}{\alpha(1-b) + 1} \right\} \\ &\geq \frac{(1-b) - \alpha b(1-b)/(1+\alpha) + b(1 - \alpha b/(1+\alpha))}{\alpha(1-b) + 1} - 2p^{-1}, \end{aligned}$$

where the last two inequalities hold since $\alpha \in (0, 1]$, $b \in [0, 1]$ and $p \geq 2$. Simplifying the last inequality, we get

$$\begin{aligned} \frac{\max \left\{ p^{-1} \sum_{i=1}^p f(\hat{S}_i), f(S_o) \right\}}{\alpha \tau} &\geq \frac{(1-b)(1+\alpha) - \alpha b(1-b) + b(1+\alpha - \alpha b)}{(1+\alpha)[\alpha(1-b) + 1]} - 2p^{-1} \\ &= \frac{1 + \alpha(1-b)}{(1+\alpha)[\alpha(1-b) + 1]} - 2p^{-1} = \frac{1}{1+\alpha} - 2p^{-1}. \end{aligned}$$

The corollary now follows by rearranging this inequality (and recalling that $\alpha \in (0, 1]$). \square

Note that the guarantee of Corollary 7 (for the case it considers) is always weaker than the guarantee of Lemma 3. Thus, we can summarize the results we have proved so far using the following proposition.

Proposition 8. *Algorithm 1 stores $O(pk)$ elements, makes at most p marginal value calculations while processing each arriving element and its output set has an expected value of at least $\left(\frac{\alpha}{\alpha+1} - 2p^{-1}\right) \tau$.*

Using the last proposition, we can now prove the following theorem. As discussed at the beginning of the section, in Section 4 we explain how the assumption that τ is known can be dropped at the cost of a slight increase in the number of elements stored by the algorithm and its update time, which yields Theorem 1.

Theorem 9. *Assume there exists an α -approximation offline algorithm OFFLINEALG for maximizing a non-negative submodular function subject to cardinality constraint whose space complexity is nearly linear in the size of the ground set. Then, for every constant $\varepsilon \in (0, 1]$, there exists a semi-streaming algorithm that assumes access to an estimate τ of $f(\text{OPT})$ obeying $(1 - \varepsilon/2) \cdot f(\text{OPT}) \leq \tau \leq f(\text{OPT})$ and provides $(\frac{\alpha}{1+\alpha} - \varepsilon)$ -approximation for the problem of maximizing a non-negative submodular function subject to cardinality constraint. This algorithm stores $O(k\varepsilon^{-1})$ elements and calculates $O(\varepsilon^{-1})$ marginal values while processing each arriving element.*

Proof. Consider the algorithm obtained from Algorithm 1 by setting $p = \lceil 4/\varepsilon \rceil$. By Proposition 8 and the non-negativity of f , this algorithm stores only $O(pk) = O(k\varepsilon^{-1})$ elements, calculates only $p = O(\varepsilon^{-1})$ marginal values while processing each arriving element, and the expected value of its output set is at least

$$\max \left\{ 0, \left(\frac{\alpha}{\alpha+1} - 2p^{-1} \right) \tau \right\} \geq \left(\frac{\alpha}{\alpha+1} - \frac{\varepsilon}{2} \right) \cdot (1 - \varepsilon/2) \cdot f(\text{OPT}) \geq \left(\frac{\alpha}{\alpha+1} - \varepsilon \right) \cdot f(\text{OPT}),$$

where the first inequality holds since $p \geq 4/\varepsilon$ and τ obeys, by assumption, $\tau \geq (1 - \varepsilon/2) \cdot f(\text{OPT})$. \square

4 Complete Algorithm

In this section, we explain how one can drop the assumption from Section 3 that the algorithm has access to an estimate τ of $f(\text{OPT})$. This completes the proof of Theorem 1.

Technically, we analyze in this section the variant of Algorithm 1 given as Algorithm 2. It gets the same two parameters α and p received by Algorithm 1 plus an additional parameter $\varepsilon' \in (0, 1)$ controlling the guaranteed quality of the output. The algorithm is based on a technique originally due to Kazemi et al. [31]. Throughout its execution, Algorithm 2 tracks in m a lower bound on the value of $f(\text{OPT})$. The algorithm also maintains a set $T = \{(1+\varepsilon')^i \mid m/(1+\varepsilon') \leq (1+\varepsilon')^i \leq mk/c\}$ of values that, given the current value of the lower bound m , are (1) possible estimates for $f(\text{OPT})$ at the current point and (2) are not so large that they dwarf this lower bound (of course, T includes only a subset of the possible estimates obeying these requirements). For every estimate τ in T , the algorithm maintains p sets $S_1^\tau, S_2^\tau, \dots, S_p^\tau$. We note that the set of solutions maintained is updated every time that T is updated (which happens after every update of m). Specifically, whenever a new value τ is added to T , the algorithm instantiate p new sets $S_1^\tau, S_2^\tau, \dots, S_p^\tau$, and whenever a value τ is dropped from T , the algorithm deletes $S_1^\tau, S_2^\tau, \dots, S_p^\tau$.

While a value τ remains in T , Algorithm 2 maintains the sets $S_1^\tau, S_2^\tau, \dots, S_p^\tau$ in exactly the same way that Algorithm 1 maintains its sets S_1, S_2, \dots, S_p given this value τ as an estimate for $f(\text{OPT})$. Moreover, we show below that if τ remains in T when the algorithm terminates, then the contents of $S_1^\tau, S_2^\tau, \dots, S_p^\tau$ when the algorithm terminates are equal to the contents of the sets S_1, S_2, \dots, S_p when Algorithm 1 terminates after executing with this τ as the estimate for $f(\text{OPT})$. Thus, one can view Algorithm 2 as parallel execution of Algorithm 1 for many estimates of $f(\text{OPT})$ at the same time. After viewing the last element, Algorithm 2 calculates for every $\tau \in T$ an output set \bar{S}_τ based on the sets $S_1^\tau, S_2^\tau, \dots, S_p^\tau$ in the same way Algorithm 1 does that, and then outputs the best output set computed for any $\tau \in T$.

Algorithm 2: STREAMPROCESS $(p, \alpha, \varepsilon')$

```

1 Let  $c \leftarrow \frac{\alpha}{1+\alpha}$ .
2 Let  $m \leftarrow f(\emptyset)$  and  $T \leftarrow \{(1+\varepsilon')^h \mid m/(1+\varepsilon') \leq (1+\varepsilon')^h \leq mk/c\}$ .
3 for each arriving element  $e$  do
4   Let  $m' \leftarrow \max\{f(\{e\}), \max_{\tau \in T, 1 \leq i \leq p} f(S_i^\tau)\}$ .
5   if  $m < m'$  then
6     Update  $m \leftarrow m'$ , and then  $T \leftarrow \{(1+\varepsilon')^h \mid m/(1+\varepsilon') \leq (1+\varepsilon')^h \leq mk/c\}$ .
7     Delete  $S_1^\tau, S_2^\tau, \dots, S_p^\tau$  for every value  $\tau$  removed from  $T$  in Line 6.
8     Initialize  $S_i^\tau \leftarrow \emptyset$  for every value  $\tau$  added to  $T$  in Line 6 and integer  $1 \leq i \leq p$ .
9   for every  $\tau \in T$  do
10    if there exists an integer  $1 \leq i \leq p$  such that  $|S_i^\tau| < k$  and  $f(e \mid S_i^\tau) \geq \frac{c\tau}{k}$  then
11      Update  $S_i^\tau \leftarrow S_i^\tau \cup \{e\}$  (if there are multiple options for  $i$ , pick an arbitrary one).
12 for every  $\tau \in T$  do
13   Find another feasible solution  $S_o^\tau \subseteq \bigcup_{i=1}^p S_i^\tau$  by running OFFLINEALG with  $\bigcup_{i=1}^p S_i^\tau$  as
      the ground set.
14   Let  $\bar{S}_\tau$  be the better solution among  $S_o^\tau$  and the  $p$  solutions  $S_1^\tau, S_2^\tau, \dots, S_p^\tau$ .
15 return the best solution among  $\{\bar{S}_\tau\}_{\tau \in T}$ , or the empty set if  $T = \emptyset$ .
```

We begin the analysis of Algorithm 2 by providing a basic lower bound on the value of each set

S_i^τ . This lower bound can be viewed as a generalized counterpart of Lemma 3.

Lemma 10. *At every point during the execution of the algorithm, for every $\tau \in T$ and $1 \leq i \leq p$ it holds that $f(S_i^\tau) \geq \frac{\alpha\tau \cdot |S_i^\tau|}{(1+\alpha)k}$.*

Proof. Denote by $e_1, e_2, \dots, e_{|S_i^\tau|}$ the elements of S_i^τ in the order of their arrival. Using this notation, the value of $f(S_i^\tau)$ can be written as follows.

$$f(S_i^\tau) = f(\emptyset) + \sum_{j=1}^{|S_i^\tau|} f(e_j \mid \{e_1, e_2, \dots, e_{j-1}\}) \geq \sum_{i=1}^{|S_i^\tau|} \frac{\alpha\tau}{(1+\alpha)k} = \frac{\alpha\tau \cdot |S_i^\tau|}{(1+\alpha)k} ,$$

where the inequality holds since the non-negativity of f implies $f(\emptyset) \geq 0$ and Algorithm 2 adds an element e_j to S_i^τ only when $f(e_j \mid \{e_1, e_2, \dots, e_{j-1}\}) \geq \frac{c\tau}{k} = \frac{\alpha\tau}{(1+\alpha)k}$. \square

Using the last lemma we can now prove the following observation, which upper bounds the size of each set S_i^τ maintained by Algorithm 2, and thus, serves as a first step towards bounding the space complexity of this algorithm.

Observation 11. *At the end of the every iteration of Algorithm 2, the size of the set S_i^τ is at most $mk/(c\tau) + 1$ for every $\tau \in T$ and integer $1 \leq i \leq p$.*

Proof. Let \bar{S}_i^τ denote the content of the set S_i^τ at the beginning of the iteration. Since at most a single element is added to S_i^τ during the iteration, we get via Lemma 10 that the value of the set \bar{S}_i^τ is at least

$$\frac{\alpha\tau \cdot |\bar{S}_i^\tau|}{(1+\alpha)k} \geq \frac{\alpha\tau \cdot (|S_i^\tau| - 1)}{(1+\alpha)k} = \frac{c\tau \cdot (|S_i^\tau| - 1)}{k} .$$

The way in which Algorithm 2 updates m guarantees that immediately after the update of m at the beginning of the iteration, the value of m was at least as large as the value of \bar{S}_i^τ , and thus, we get

$$m \geq \frac{c\tau \cdot (|S_i^\tau| - 1)}{k} ,$$

which implies the observation. \square

We are now ready to bound the space complexity and update time of Algorithm 2.

Lemma 12. *Algorithm 2 can be implemented so that it stores $O(pk(\varepsilon')^{-1} \log \alpha^{-1})$ elements and makes only $O(p(\varepsilon')^{-1} \log(k/\alpha))$ marginal value calculations when processing each arriving element.*

Proof. We begin the proof with two technical calculations. First, note that the number of estimates in T is upper bounded at all times by

$$1 + \log_{1+\varepsilon'} \left(\frac{km/c}{m/(1+\varepsilon')} \right) = 2 + \frac{\ln k - \ln c}{\ln(1+\varepsilon')} \leq 2 + \frac{\ln k - \ln c}{2\varepsilon'/3} = O((\varepsilon')^{-1}(\log k - \log c)) .$$

Second, note that

$$\begin{aligned} \sum_{\tau \in T} \sum_{i=1}^p (|S_i^\tau| - 1) &\leq \sum_{\tau \in T} \min \left\{ pk, \frac{pmk}{c\tau} \right\} \leq \sum_{\substack{h \in \mathbb{Z} \\ (1+\varepsilon')^{h+1} \geq m}} \min \left\{ pk, \frac{pmk}{c(1+\varepsilon')^h} \right\} \\ &\leq pk \cdot \left| \left\{ h \in \mathbb{Z} \mid \frac{m}{1+\varepsilon'} \leq (1+\varepsilon')^h < m/c \right\} \right| + \sum_{h=0}^{\infty} \frac{pk}{(1+\varepsilon')^h} \\ &\leq pk \cdot \left(\log_{1+\varepsilon'} \left(\frac{m/c}{m} \right) + 2 \right) + \frac{pk}{1 - 1/(1+\varepsilon')} \leq \frac{pk \cdot (\ln c^{-1} + 2)}{\ln(1+\varepsilon')} + \frac{pk(1+\varepsilon')}{\varepsilon'} \\ &= O(pk(\varepsilon')^{-1} \log c^{-1}) + O(pk(\varepsilon')^{-1}) = O(pk(\varepsilon')^{-1} \log c^{-1}) , \end{aligned}$$

where the first inequality follows from Observation 11 and the fact that all the sets maintained by Algorithm 2 are of size at most k ; and the second inequality follows from the definition of T .

We now observe that, while processing each arriving element, Algorithm 2 makes p marginal value calculations in association with every value $\tau \in T$ and another set of $O(p)$ such calculations that are not associated with any value of T . Thus, the total number of marginal value calculations made by the algorithm during the processing of an arriving element is

$$p \cdot |T| + O(p) = p \cdot O((\varepsilon')^{-1}(\log k - \log c)) + O(p) = O(p(\varepsilon')^{-1}(\log k - \log c)) = O(p(\varepsilon')^{-1} \log(k/c)) .$$

We also note that Algorithm 2 has to store only the elements belonging to S_i^τ for some $\tau \in T$ and integer $1 \leq i \leq p$. Thus, in all these sets together the algorithm stores $O(pk(\varepsilon')^{-1} \log c^{-1})$ elements since

$$\begin{aligned} \sum_{\tau \in T} \sum_{i=1}^p |S_i^\tau| &= \sum_{\tau \in T} \sum_{i=1}^p (|\text{supp}(S_i^\tau)| - 1) + p|T| \\ &= O(pk(\varepsilon')^{-1} \log c^{-1}) + p \cdot O((\varepsilon')^{-1}(\log k - \log c)) = O(pk(\varepsilon')^{-1} \log c^{-1}) . \end{aligned}$$

To complete the proof of the lemma, it remains to note that $c = \alpha/(1 + \alpha) \geq \alpha/2$. \square

A this point we divert our attention to analyzing the approximation guarantee of Algorithm 2. Let us denote by \hat{m} and \hat{T} the final values of m and T , respectively.

Observation 13. $c \in (0, 1/2]$, and thus, \hat{T} is not empty unless $\hat{m} = 0$.

Proof. Since $\alpha \in (0, 1]$ and $\alpha/(\alpha + 1)$ is an increasing function of α ,

$$c = \frac{\alpha}{\alpha + 1} \in \left(\frac{0}{0 + 1}, \frac{1}{1 + 1} \right] = (0, 1/2] . \quad \square$$

The last observation immediately implies that when \hat{T} is empty, all the singletons have zero values, and the same must be true for every other non-empty set by the submodularity and non-negativity of f . Thus, $\text{OPT} = \emptyset$, which makes the output of Algorithm 2 optimal in the rare case in which \hat{T} is empty. Hence, we can assume from now on that $\hat{T} \neq \emptyset$. The following lemma shows that \hat{T} contains a good estimate for $f(\text{OPT})$ in this case.

Lemma 14. *The set \hat{T} contains a value $\hat{\tau}$ such that $(1 - \varepsilon') \cdot f(\text{OPT}) \leq \hat{\tau} \leq f(\text{OPT})$.*

Proof. Observe that $\hat{m} \geq \max\{f(\emptyset), \max_{e \in V} \{f(\{e\})\}\}$. Thus, by the submodularity of f ,

$$f(\text{OPT}) \leq f(\emptyset) + \sum_{e \in \text{OPT}} [f(\{e\}) - f(\emptyset)] \leq \max \left\{ f(\emptyset), \sum_{e \in \text{OPT}} f(\{e\}) \right\} \leq k\hat{m} \leq \frac{k\hat{m}}{c} .$$

In contrast, one can note that m is equal to the value of f for some feasible solution, and thus, $f(\text{OPT}) \geq \hat{m}$. Since \hat{T} contains all the values of the form $(1 + \varepsilon')^i$ in the range $[\hat{m}/(1 + \varepsilon'), k\hat{m}/c]$, the above inequalities imply that it contains in particular the largest value of this form that is still not larger than $f(\text{OPT})$. Let us denote this value by $\hat{\tau}$. By definition, $\hat{\tau} \leq f(\text{OPT})$. Additionally,

$$\hat{\tau} \cdot (1 + \varepsilon') \geq f(\text{OPT}) \Rightarrow \hat{\tau} \geq \frac{f(\text{OPT})}{1 + \varepsilon'} \geq (1 - \varepsilon') \cdot f(\text{OPT}) . \quad \square$$

Let us now concentrate on the value $\hat{\tau}$ whose existence is guaranteed by Lemma 14, and let $\hat{S}_1, \hat{S}_2, \dots, \hat{S}_p$ denote the sets maintained by Algorithm 1 when it gets $\hat{\tau}$ as the estimate for $f(\text{OPT})$. Additionally, let us denote by e_1, e_2, \dots, e_n the elements of V in the order of their arrival, and let e_j be the element whose arrival made Algorithm 2 add $\hat{\tau}$ to T (i.e., $\hat{\tau}$ was added to T by Algorithm 2 while processing e_j). If $\hat{\tau}$ belonged to T from the very beginning of the execution of Algorithm 2, then we define $j = 1$.

Lemma 15. *All the sets $\hat{S}_1, \hat{S}_2, \dots, \hat{S}_p$ maintained by Algorithm 1 are empty immediately prior to the arrival of e_j .*

Proof. If $j = 1$, then lemma is trivial. Thus, we assume $j > 1$ in the rest of this proof. Prior to the arrival of e_j , $\hat{\tau}$ was not part of T . Nevertheless, since $\hat{\tau} \in \hat{T}$, we must have at all times

$$\hat{\tau} \geq \frac{\hat{m}}{1 + \varepsilon'} \geq \frac{m}{1 + \varepsilon'} ,$$

where the second inequality holds since the value m only increases over time. Therefore, the reason that $\hat{\tau}$ did not belong to T prior to the arrival of e_j must have been that m was smaller than $c\hat{\tau}/k$. Since m is at least as large as the value of any singleton containing an element already viewed by the algorithm we get, for every two integers $1 \leq t \leq j - 1$ and $1 \leq i \leq p$,

$$\frac{c\hat{\tau}}{k} > f(\{e_t\}) \geq f(\{e_t\} \mid \emptyset) \geq f(e_t \mid \hat{S}_i \wedge \mathbf{1}_{\{e_1, e_2, \dots, e_{t-1}\}}) ,$$

where the second inequality follows from the non-negativity of f and the last from its submodularity. Thus, e_t is not added by Algorithm 1 to any one of the sets $\hat{S}_1, \hat{S}_2, \dots, \hat{S}_p$, which implies that all these sets are empty at the moment e_j arrives. \square

According to the above discussion, from the moment $\hat{\tau}$ gets into T , Algorithm 2 updates the sets $S_1^{\hat{\tau}}, S_2^{\hat{\tau}}, \dots, S_p^{\hat{\tau}}$ in the same way that Algorithm 1 updates $\hat{S}_1, \hat{S}_2, \dots, \hat{S}_p$ (note that, once $\hat{\tau}$ gets into T , it remains there for good since $\hat{\tau} \in \hat{T}$). Together with the previous lemma which shows that $\hat{S}_1, \hat{S}_2, \dots, \hat{S}_p$ are empty just like $S_1^{\hat{\tau}}, S_2^{\hat{\tau}}, \dots, S_p^{\hat{\tau}}$ at the moment e_j arrives, this implies that the final contents of $S_1^{\hat{\tau}}, S_2^{\hat{\tau}}, \dots, S_p^{\hat{\tau}}$ are equal to the final contents of $\hat{S}_1, \hat{S}_2, \dots, \hat{S}_p$, respectively. Since the set $\bar{S}_{\hat{\tau}}$ is computed based on the final contents of $S_1^{\hat{\tau}}, S_2^{\hat{\tau}}, \dots, S_p^{\hat{\tau}}$ in the same way that the output of Algorithm 1 is computed based on the final contents of $\hat{S}_1, \hat{S}_2, \dots, \hat{S}_p$, we get the following corollary.

Corollary 16. *If it is guaranteed that the approximation ratio of Algorithm 1 is at least β when $(1 - \varepsilon') \cdot f(\text{OPT}) \leq \tau \leq f(\text{OPT})$ for some choice of the parameters α and p , then the approximation ratio of Algorithm 2 is at least β as well for this choice of α and p .*

We are now ready to prove Theorem 1.

Theorem 1. *Assume there exists an α -approximation offline algorithm OFFLINEALG for maximizing a non-negative submodular function subject to a cardinality constraint whose space complexity is nearly linear in the size of the ground set. Then, for every constant $\varepsilon \in (0, 1]$, there exists an $(\frac{\alpha}{1+\alpha} - \varepsilon)$ -approximation semi-streaming algorithm for maximizing a non-negative submodular function subject to a cardinality constraint. The algorithm stores $O(k\varepsilon^{-2} \log \alpha^{-1})$ elements and makes $O(\varepsilon^{-2} \log(k/\alpha))$ marginal value computations while processing each arriving element. Furthermore, if OFFLINEALG is deterministic, then so is the algorithm that we get.*

Proof. The proof of Theorem 9 shows that Algorithm 1 achieves an approximation guarantee of $\frac{\alpha}{1+\alpha} - \varepsilon$ when it has access to a value τ obeying $(1 - \varepsilon/2) \cdot f(\text{OPT}) \leq \tau \leq f(\text{OPT})$ and its parameter p is set to $\lceil 4/\varepsilon \rceil$. According to Corollary 16, this implies that by setting the parameter p of Algorithm 2 in the same way and setting ε' to $\varepsilon/2$, we get an algorithm whose approximation ratio is at least $\frac{\alpha}{1+\alpha} - \varepsilon$ and does not assume access to an estimate τ of $f(\text{OPT})$.

It remains to bound the space requirement and update time of the algorithm obtained in this way. Plugging the equalities $p = \lceil 4/\varepsilon \rceil$ and $\varepsilon' = \varepsilon/2$ into the guarantee of Lemma 12, we get that the algorithm we have obtained stores $O(k\varepsilon^{-2} \log \alpha^{-1})$ elements and makes $O(\varepsilon^{-2} \log(k/\alpha))$ marginal value calculations while processing each arriving element. \square

References

- [1] Naor Alaluf, Alina Ene, Moran Feldman, Huy L. Nguyen, and Andrew Suh. Optimal streaming algorithms for submodular maximization with cardinality constraints. In *ICALP*, pages 6:1–6:19, 2020. URL: <https://doi.org/10.4230/LIPIcs.ICALP.2020.6>, doi:10.4230/LIPIcs.ICALP.2020.6.
- [2] Naor Alaluf, Alina Ene, Moran Feldman, Huy L. Nguyen, and Andrew Suh. Optimal streaming algorithms for submodular maximization with cardinality constraints. *CoRR*, abs/1911.12959v2, 2020. URL: <https://arxiv.org/pdf/1911.12959v2.pdf>.
- [3] Yossi Azar, Iftah Gamzu, and Ran Roth. Submodular max-sat. In *ESA*, pages 323–334, 2011. URL: https://doi.org/10.1007/978-3-642-23719-5_28, doi:10.1007/978-3-642-23719-5_28.
- [4] Ashwinkumar Badanidiyuru, Baharan Mirzasoleiman, Amin Karbasi, and Andreas Krause. Streaming submodular maximization: Massive data summarization on the fly. In *Proceedings of the 20th ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 671–680. ACM, 2014.
- [5] Rafael da Ponte Barbosa, Alina Ene, Huy L. Nguyen, and Justin Ward. A new framework for distributed submodular maximization. In *IEEE Foundations of Computer Science (FOCS)*, pages 645–654, 2016.
- [6] Rafael D.P. Barbosa, Alina Ene, Huy L. Nguyen, and Justin Ward. The power of randomization: Distributed submodular maximization on massive datasets. In *International Conference on Machine Learning (ICML)*, 2015.
- [7] Niv Buchbinder and Moran Feldman. Deterministic algorithms for submodular maximization problems. *ACM Trans. Algorithms*, 14(3):32:1–32:20, 2018. URL: <https://doi.org/10.1145/3184990>, doi:10.1145/3184990.
- [8] Niv Buchbinder and Moran Feldman. Constrained submodular maximization via a non-symmetric technique. *Mathematics of Operations Research*, 44(3):988–1005, 2019.
- [9] Niv Buchbinder, Moran Feldman, Yuval Filmus, and Mohit Garg. Online submodular maximization: Beating $1/2$ made simple. In *Integer Programming and Combinatorial Optimization - 20th International Conference, IPCO 2019, Ann Arbor, MI, USA, May 22-24, 2019, Proceedings*, pages 101–114, 2019. URL: https://doi.org/10.1007/978-3-030-17953-3_8, doi:10.1007/978-3-030-17953-3_8.
- [10] Niv Buchbinder, Moran Feldman, and Mohit Garg. Deterministic $(1/2 + \varepsilon)$ -approximation for submodular maximization over a matroid. In *SODA*, pages 241–254, 2019. URL: <https://doi.org/10.1137/1.9781611975482.16>, doi:10.1137/1.9781611975482.16.
- [11] Niv Buchbinder, Moran Feldman, Joseph Naor, and Roy Schwartz. Submodular maximization with cardinality constraints. In *SODA*, pages 1433–1452, 2014. URL: <https://doi.org/10.1137/1.9781611973402.106>, doi:10.1137/1.9781611973402.106.
- [12] Niv Buchbinder, Moran Feldman, and Roy Schwartz. Online submodular maximization with preemption. *ACM Trans. Algorithms*, 15(3):30:1–30:31, 2019. URL: <https://doi.org/10.1145/3309764>, doi:10.1145/3309764.

- [13] Gruia Călinescu, Chandra Chekuri, Martin Pál, and Jan Vondrák. Maximizing a monotone submodular function subject to a matroid constraint. *SIAM J. Comput.*, 40(6):1740–1766, 2011. URL: <https://doi.org/10.1137/080733991>, doi:10.1137/080733991.
- [14] Amit Chakrabarti and Sagar Kale. Submodular maximization meets streaming: Matchings, matroids, and more. *Mathematical Programming*, 154(1-2):225–247, 2015.
- [15] T.-H. Hubert Chan, Zhiyi Huang, Shaofeng H.-C. Jiang, Ning Kang, and Zhihao Gavin Tang. Online submodular maximization with free disposal. *ACM Trans. Algorithms*, 14(4):56:1–56:29, 2018. URL: <https://doi.org/10.1145/3242770>, doi:10.1145/3242770.
- [16] Chandra Chekuri. Personal communication, 2018.
- [17] Chandra Chekuri, Shalmoli Gupta, and Kent Quanrud. Streaming algorithms for submodular function maximization. In *International Colloquium on Automata, Languages and Programming (ICALP)*, pages 318–330. Springer, 2015.
- [18] Chandra Chekuri, Jan Vondrák, and Rico Zenklusen. Dependent randomized rounding via exchange properties of combinatorial structures. In *FOCS*, pages 575–584, 2010. URL: <https://doi.org/10.1109/FOCS.2010.60>, doi:10.1109/FOCS.2010.60.
- [19] Chandra Chekuri, Jan Vondrák, and Rico Zenklusen. Submodular function maximization via the multilinear relaxation and contention resolution schemes. *SIAM J. Comput.*, 43(6):1831–1879, 2014. URL: <https://doi.org/10.1137/110839655>, doi:10.1137/110839655.
- [20] Alina Ene and Huy L Nguyen. Constrained submodular maximization: Beyond $1/e$. In *IEEE Foundations of Computer Science (FOCS)*, pages 248–257. IEEE, 2016.
- [21] Alessandro Epasto, Vahab Mirrokni, and Morteza Zadimoghaddam. Bicriteria distributed submodular maximization in a few rounds. In *PACM Symposium on Parallelism in Algorithms and Architectures (SPAA)*, pages 25–33, 2017.
- [22] Uriel Feige, Vahab S Mirrokni, and Jan Vondrák. Maximizing non-monotone submodular functions. *SIAM Journal on Computing*, 40(4):1133–1153, 2011.
- [23] Moran Feldman. Maximizing symmetric submodular functions. *ACM Trans. Algorithms*, 13(3):39:1–39:36, 2017. URL: <https://doi.org/10.1145/3070685>, doi:10.1145/3070685.
- [24] Moran Feldman, Christopher Harshaw, and Amin Karbasi. Greed is good: Near-optimal submodular maximization via greedy optimization. In *Proceedings of the 30th Conference on Learning Theory, COLT 2017, Amsterdam, The Netherlands, 7-10 July 2017*, pages 758–784, 2017. URL: <http://proceedings.mlr.press/v65/feldman17b.html>.
- [25] Moran Feldman, Amin Karbasi, and Ehsan Kazemi. Do less, get more: Streaming submodular maximization with subsampling. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 732–742, 2018.
- [26] Moran Feldman, Joseph (Seffi) Naor, and Roy Schwartz. A unified continuous greedy algorithm for submodular maximization. In *Proceedings of the 52nd IEEE Foundations of Computer Science (FOCS)*, pages 570–579. IEEE Computer Society, 2011.
- [27] Moran Feldman, Ashkan Norouzi-Fard, Ola Svensson, and Rico Zenklusen. The one-way communication complexity of submodular maximization with applications to streaming and robustness. In *STOC*, pages 1363–1374, 2020.

- [28] M. L. Fisher, G. L. Nemhauser, and L. A. Wolsey. An analysis of approximations for maximizing submodular set functions—II. *Mathematical Programming Studies*, 8:73–87, 1978.
- [29] Shayan Oveis Gharan and Jan Vondrák. Submodular maximization by simulated annealing. In *ACM-SIAM Symposium on Discrete Algorithms (SODA)*, 2011.
- [30] Michael Kapralov, Ian Post, and Jan Vondrák. Online submodular welfare maximization: Greedy is optimal. In *SODA*, pages 1216–1225, 2013. URL: <https://doi.org/10.1137/1.9781611973105.88>, doi:10.1137/1.9781611973105.88.
- [31] Ehsan Kazemi, Marko Mitrovic, Morteza Zadimoghaddam, Silvio Lattanzi, and Amin Karbasi. Submodular streaming in all its glory: Tight approximation, minimum memory and low adaptive complexity. In *ICML*, pages 3311–3320, 2019. URL: <http://proceedings.mlr.press/v97/kazemi19a.html>.
- [32] Nitish Korula, Vahab S. Mirrokni, and Morteza Zadimoghaddam. Online submodular welfare maximization: Greedy beats 1/2 in random order. *SIAM J. Comput.*, 47(3):1056–1086, 2018. URL: <https://doi.org/10.1137/15M1051142>, doi:10.1137/15M1051142.
- [33] Ravi Kumar, Benjamin Moseley, Sergei Vassilvitskii, and Andrea Vattani. Fast greedy algorithms in mapreduce and streaming. In *PACM Symposium on Parallelism in Algorithms and Architectures (SPAA)*, pages 1–10, 2013.
- [34] Jon Lee, Vahab S Mirrokni, Viswanath Nagarajan, and Maxim Sviridenko. Non-monotone submodular maximization under matroid and knapsack constraints. In *ACM Symposium on Theory of Computing (STOC)*, pages 323–332, 2009.
- [35] Jon Lee, Maxim Sviridenko, and Jan Vondrák. Submodular maximization over multiple matroids via generalized exchange properties. *Mathematics of Operations Research*, 35(4):795–806, 2010.
- [36] László Lovász. Submodular functions and convexity. In *Mathematical Programming The State of the Art, Xith International Symposium on Mathematical Programming, Bonn, Germany, August 23-27, 1982*, pages 235–257, 1982. URL: https://doi.org/10.1007/978-3-642-68874-4_10, doi:10.1007/978-3-642-68874-4_10.
- [37] Vahab Mirrokni and Morteza Zadimoghaddam. Randomized composable core-sets for distributed submodular maximization. In *ACM Symposium on Theory of Computing (STOC)*, 2015.
- [38] Baharan Mirzasoleiman, Stefanie Jegelka, and Andreas Krause. Streaming non-monotone submodular maximization: Personalized video summarization on the fly. In *Thirty-second AAAI conference on artificial intelligence*, 2018.
- [39] Baharan Mirzasoleiman, Amin Karbasi, Ashwinkumar Badanidiyuru, and Andreas Krause. Distributed submodular cover: Succinctly summarizing massive data. In *Advances in Neural Information Processing Systems*, pages 2881–2889, 2015.
- [40] Baharan Mirzasoleiman, Amin Karbasi, Rik Sarkar, and Andreas Krause. Distributed submodular maximization: Identifying representative elements in massive data. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 2049–2057, 2013.

- [41] G. L. Nemhauser, L. A. Wolsey, and M. L. Fisher. An analysis of approximations for maximizing submodular set functions—I. *Mathematical Programming*, 14(1):265–294, 1978.
- [42] George L. Nemhauser and Laurence A. Wolsey. Best algorithms for approximating the maximum of a submodular set function. *Math. Oper. Res.*, 3(3):177–188, 1978. URL: <https://doi.org/10.1287/moor.3.3.177>, doi:10.1287/moor.3.3.177.
- [43] George L. Nemhauser, Laurence A. Wolsey, and Marshall L. Fisher. An analysis of approximations for maximizing submodular set functions—I. *Math. Program.*, 14(1):265–294, 1978. URL: <https://doi.org/10.1007/BF01588971>, doi:10.1007/BF01588971.
- [44] Ashkan Norouzi-Fard, Jakub Tarnawski, Slobodan Mitrovic, Amir Zandieh, Aidasadat Mousavifar, and Ola Svensson. Beyond 1/2-approximation for submodular maximization on massive data streams. In *International Conference on Machine Learning*, pages 3826–3835, 2018.
- [45] Jan Vondrák. Symmetry and approximability of submodular maximization problems. *SIAM J. Comput.*, 42(1):265–304, 2013. URL: <https://doi.org/10.1137/110832318>, doi:10.1137/110832318.

A Details about the Error in a Previous Work

As mentioned above, Chekuri et al. [17] described a semi-streaming algorithm for the problem of maximizing a non-negative (not necessarily monotone) submodular function subject to a cardinality constraint, and claimed an approximation ratio of roughly 0.212 for this algorithm. However, an error was later found in the proof of this result [16] (the error does not affect the other results of [17]). For completeness, we briefly describe in this appendix the error found.

In the proof presented by Chekuri et al. [17], the output set of their algorithm is denoted by \tilde{S} . As is standard in the analysis of algorithms based on single-threshold Greedy, the analysis distinguishes between two cases: one case in which $\tilde{S} = k$, and a second case in which $\tilde{S} < k$. To argue about the second case, the analysis then implicitly uses the inequality

$$\mathbb{E}[f(\tilde{S} \cup \text{OPT}) \mid |S| < k] \geq (1 - \max_{e \in V} \Pr[e \in \tilde{S}]) \cdot f(\text{OPT}) . \quad (1)$$

It is claimed by [17] that this inequality follows from Lemma 4 (originally due to [11]). However, this lemma can yield only the inequalities

$$\mathbb{E}[f(\tilde{S} \cup \text{OPT})] \geq (1 - \max_{e \in V} \Pr[e \in \tilde{S}]) \cdot f(\text{OPT})$$

and

$$\mathbb{E}[f(\tilde{S} \cup \text{OPT}) \mid |S| < k] \geq (1 - \max_{e \in V} \Pr[e \in \tilde{S} \mid |S| < k]) \cdot f(\text{OPT}) ,$$

which are similar to (1), but do not imply it.

B Inapproximability

In this appendix, we prove an inapproximability result for the problem of maximizing a non-negative submodular function subject to cardinality constraint in the data stream model. This result is given by the next theorem. The proof of the theorem is an adaptation of a proof given by Buchbinder et al. [12] for a similar result applying to an online variant of the same problem.

Theorem 17. *For every constant $\varepsilon > 0$, no data stream algorithm for maximizing a non-negative submodular function subject to cardinality constraint is $(1/2 + \varepsilon)$ -competitive, unless it uses $\Omega(|V|)$ memory.*

Proof. Let $k \geq 1$ and $h \geq 1$ be two integers to be chosen later, and consider the non-negative submodular function $f: 2^V \rightarrow \mathbb{R}^+$, where $V = \{u_i\}_{i=1}^{k-1} \cup \{v_i\}_{i=1}^h \cup \{w\}$, defined as follows.

$$f(S) = \begin{cases} |S| & \text{if } w \notin S , \\ k + |S \cap \{u_i\}_{i=1}^{k-1}| & \text{if } w \in S . \end{cases}$$

It is clear that f is non-negative. One can also verify that the marginal value of each element in V is non-increasing, and hence, f is submodular.

Let ALG be an arbitrary data stream algorithm for the problem of maximizing a non-negative submodular function subject to a cardinality constraint, and let us consider what happens when we give this algorithm the above function f as input, the last element of V to arrive is the element w and we ask the algorithm to pick a set of size at most k . One can observe that, before the arrival of w , ALG has no way to distinguish between the other elements of V . Thus, if we denote by M the set of elements stored by ALG immediately before the arrival of w and assume that the elements

of $V \setminus \{w\}$ arrive at a random order, then every element of $V \setminus \{w\}$ belongs to M with the same probability of $\mathbb{E}[|M|]/|V \setminus \{w\}|$. Hence, there must exist some arrival order for the elements of $V \setminus \{w\}$ guaranteeing that

$$\mathbb{E}[|M \cap \{u_i\}_{i=1}^{k-1}|] = \sum_{i=1}^{k-1} \Pr[u_i \in M] \leq \frac{k \cdot \mathbb{E}[|M|]}{|V \setminus \{w\}|}.$$

Note now that the above implies that the expected value of the output set produced by ALG given the above arrival order is at most

$$k + \frac{k \cdot \mathbb{E}[|M|]}{|V \setminus \{w\}|}.$$

In contrast, the optimal solution is the set $\{u_i\}_{i=1}^{k-1} \cup \{w\}$, whose value is $2k - 1$. Therefore, the competitive ratio of ALG is at most

$$\frac{k + k \cdot \mathbb{E}[|M|]/|V \setminus \{w\}|}{2k - 1} = \frac{1 + \mathbb{E}[|M|]/|V \setminus \{w\}|}{2 - 1/k} \leq \frac{1}{2} + \frac{1}{k} + \frac{\mathbb{E}[|M|]}{|V \setminus \{w\}|}.$$

To prove the theorem we need to show that, when the memory used by ALG is $o(|V|)$, we can choose large enough values for k and h that will guarantee that the rightmost side of the last inequality is at most $1/2 + \varepsilon$. We do so by showing that the two terms $1/k$ and $\mathbb{E}[|M|]/|V \setminus \{w\}|$ can both be upper bounded by $\varepsilon/2$ when the integers k and h are large enough, respectively. For the term $1/k$ this is clearly the case when k is larger than $2/\varepsilon$. For the term $\mathbb{E}[|M|]/|V \setminus \{w\}|$ this is true because increasing h can make V as large as want, and thus, can make the ratio $\mathbb{E}[|M|]/|V \setminus \{w\}|$ as small as necessary due to our assumption that the memory used by ALG (which includes M) is $o(|V|)$. \square

C Multilinear extension based algorithm

The properties of the multilinear extension based variant of our algorithm are summarized by the following theorem.

Theorem 18. *Assume there exists an α -approximation offline algorithm OFFLINEALG for maximizing a non-negative submodular function subject to cardinality constraint whose space complexity is nearly linear in the size of the ground set. Then, for every constant $\varepsilon \in (0, 1]$, there exists an $(\frac{\alpha}{1+\alpha} - \varepsilon)$ -approximation semi-streaming algorithm for maximizing a non-negative submodular function subject to a cardinality constraint. The algorithm stores at most $O(k\varepsilon^{-2} \log \alpha^{-1})$ elements.*

For ease of the reading, we present below only a simplified version of the multilinear extension based variant of our algorithm. This simplified version (given as Algorithm 3) captures our main new ideas, but makes two simplifying assumptions that can be avoided using standard techniques.

- The first assumption is that Algorithm 3 has access to an estimate τ of $f(\text{OPT})$ obeying $(1 - \varepsilon/8) \cdot f(\text{OPT}) \leq \tau \leq f(\text{OPT})$. Such an estimate can be produced using well-known techniques, such as a technique of [31] used in Section 4, at the cost of increasing the space complexity of the algorithm only by a factor of $O(\varepsilon^{-1} \log \alpha^{-1})$.
- The second assumption is that Algorithm 3 has value oracle access to the multilinear extension F . If the time complexity of Algorithm 3 is not important, then this assumption is of no

consequence since a value oracle query to F can be emulated using an exponential number of value oracle queries to f . However, the assumption becomes problematic when we would like to keep the time complexity of the algorithm polynomial and we only have value oracle access to f , in which case this assumption can be dropped using standard sampling techniques (such as the one used in [13]). Interestingly, the rounding step of the algorithm and the sampling technique are the only parts of the extension based algorithm that employ randomness. Since the rounding can be made deterministic given either exponential time or value oracle access to F , we get the following observation.

Observation 19. *If OFFLINEALG is deterministic, then our multilinear extension based algorithm is also deterministic when it is allowed either exponential computation time or value oracle access to F .*

A more detailed discussion of the techniques for removing the above assumptions can be found in an earlier version of this paper (available in [2]) that had this variant of our algorithm as one of its main results.

Algorithm 3 has two constant parameters $p \in (0, 1)$ and $c > 0$ and maintains a fractional solution $x \in [0, 1]^V$. This fractional solution starts empty, and the algorithm adds to it fractions of elements as they arrive. Specifically, when an element e arrives, the algorithm considers its marginal contribution with respect to the current fractional solution x . If this marginal contribution exceeds the threshold of $c\tau/k$, then the algorithm tries to add to x a p -fraction of e , but might end up adding a smaller fraction of e if adding a full p -fraction of e to x will make x an infeasible solution, i.e., make $\|x\|_1 > k$ (note that $\|x\|_1$ is the sum of the coordinates of x).

After viewing all of the elements, Algorithm 3 uses the fractional solution x to generate two sets S_1 and S_2 that are feasible (integral) solutions. The set S_1 is generated by rounding the fractional solution x . As mentioned in Section 3, two rounding procedures, named Pipage Rounding and Swap Rounding, were suggested for this task in the literature [13, 18]. Both procedures run in polynomial time and guarantee that the output set S_1 of the rounding is always feasible, and that its expected value with respect to f is at least the value $F(x)$ of the fractional solution x . The set S_2 is generated by applying OFFLINEALG to the support of the vector x , which produces a feasible solution that (approximately) maximizes f among all subsets of the support whose size is at most k . After computing the two feasible solutions S_1 and S_2 , Algorithm 3 simply returns the better one of them.

Algorithm 3: STREAMPROCESSEXTENSION (simplified) (p, c)

- 1 Let $x \leftarrow \mathbf{1}_\emptyset$.
 - 2 **for** each arriving element e **do**
 - 3 **if** $\partial_e F(x) \geq \frac{c\tau}{k}$ **then** $x \leftarrow x + \min\{p, k - \|x\|_1\} \cdot \mathbf{1}_e$.
 - 4 Round the vector x to yield a feasible solution S_1 such that $\mathbb{E}[f(S_1)] \geq F(x)$.
 - 5 Find another feasible solution $S_2 \subseteq \text{supp}(x)$ by running OFFLINEALG with $\text{supp}(x)$ as the ground set.
 - 6 **return** the better solution among S_1 and S_2 .
-

Let us denote by \hat{x} the final value of the fractional solution x (i.e., its value when the stream ends). We begin the analysis of Algorithm 3 with the following useful observation. In the statement of observation, and in the rest of the section, we denote by $\text{supp}(x)$ the support of vector x , i.e., the set $\{e \in V \mid x_e > 0\}$.

Observation 20. *If $\|\hat{x}\|_1 < k$, then $\hat{x}_e = p$ for every $e \in \text{supp}(\hat{x})$. Otherwise, $\|\hat{x}\|_1 = k$, and the first part of the observation is still true for every element $e \in \text{supp}(\hat{x})$ except for maybe a single element.*

Proof. For every element e added to the support of x by Algorithm 3, the algorithm sets x_e to p unless this will make $\|x\|_1$ exceed k , in which case the algorithm set x_e to be the value that will make $\|x\|_1$ equal to k . Thus, after a single coordinate of x is set to a value other than p (or the initial 0), $\|x\|_1$ becomes k and Algorithm 3 stops changing x . \square

Using the last observation we can now bound the space complexity of Algorithm 3, and show (in particular) that it is a semi-streaming algorithm for a constant p when the space complexity of OFFLINEALG is nearly linear.

Observation 21. *Algorithm 3 can be implemented so that it stores at most $O(k/p)$ elements.*

Proof. To calculate the sets S_1 and S_2 , Algorithm 3 needs access only to the elements of V that appear in the support of x . Thus, the number of elements it needs to store is $O(|\text{supp}(\hat{x})|) = O(k/p)$, where the equality follows from Observation 20. \square

We now divert our attention to analyzing the approximation ratio of Algorithm 3. The first step in this analysis is lower bounding the value of $F(\hat{x})$, which we do by considering two cases, one when $\|\hat{x}\|_1 = k$, and the other when $\|\hat{x}\|_1 < k$. The following lemma bounds the value of $F(\hat{x})$ in the first of these cases. Intuitively, this lemma holds since $\text{supp}(\hat{x})$ contains many elements, and each one of these elements must have increased the value of $F(x)$ significantly when added (otherwise, Algorithm 3 would not have added this element to the support of x).

Lemma 22. *If $\|\hat{x}\|_1 = k$, then $F(\hat{x}) \geq c\tau$.*

Proof. Denote by e_1, e_2, \dots, e_ℓ the elements in the support of \hat{x} , in the order of their arrival. Using this notation, the value of $F(\hat{x})$ can be written as follows.

$$\begin{aligned} F(\hat{x}) &= F(\mathbf{1}_\emptyset) + \sum_{i=1}^{\ell} \left(F(\hat{x} \wedge \mathbf{1}_{\{e_1, e_2, \dots, e_i\}}) - F(\hat{x} \wedge \mathbf{1}_{\{e_1, e_2, \dots, e_{i-1}\}}) \right) \\ &= F(\mathbf{1}_\emptyset) + \sum_{i=1}^{\ell} \left(\hat{x}_{e_i} \cdot \partial_{e_i} F(\hat{x} \wedge \mathbf{1}_{\{e_1, e_2, \dots, e_{i-1}\}}) \right) \\ &\geq F(\mathbf{1}_\emptyset) + \frac{c\tau}{k} \cdot \sum_{i=1}^{\ell} \hat{x}_{e_i} = F(\mathbf{1}_\emptyset) + \frac{c\tau}{k} \cdot \|\hat{x}\|_1 \geq c\tau, \end{aligned}$$

where the second equality follows from the multilinearity of F , and the first inequality holds since Algorithm 3 selects an element e_i only when $\partial_{e_i} F(\hat{x} \wedge \mathbf{1}_{\{e_1, e_2, \dots, e_{i-1}\}}) \geq \frac{c\tau}{k}$. The last inequality holds since f (and thus, also F) is non-negative and $\|\hat{x}\|_1 = k$ by the assumption of the lemma. \square

Consider now the case in which $\|\hat{x}\|_1 < k$. Recall that our objective is to lower bound $F(\hat{x})$ in this case as well. To do that, we need to a tool for upper bounding the possible increase in the value of $F(x)$ when some of the indices of x are zeroed. The next lemma provides such an upper bound.

Lemma 23. *Let $f: 2^V \rightarrow \mathbb{R}_{\geq 0}$ be a non-negative submodular function, let p be a number in the range $[0, 1]$ and let x, y be two vectors in $[0, 1]^V$ such that*

- $\text{supp}(x) \cap \text{supp}(y) = \emptyset$,

- and $y_e \leq p$ for every $e \in V$.

Then, the multilinear extension F of f obeys $F(x + y) \geq (1 - p) \cdot F(x)$.

Proof. Let us define the function $G_x(S) = \mathbb{E}[f(\mathbf{R}(x) \cup S)]$. It is not difficult to verify that G_x is non-negative and submodular, and that $G_x(\emptyset) = F(x)$. Additionally, since $\text{supp}(x) \cap \text{supp}(y) = \emptyset$, $\mathbf{R}(x + y)$ has the same distribution as $\mathbf{R}(x) \cup \mathbf{R}(y)$, and therefore,

$$\begin{aligned} F(x + y) &= \mathbb{E}[f(\mathbf{R}(x + y))] = \mathbb{E}[f(\mathbf{R}(x) \cup \mathbf{R}(y))] \\ &= \mathbb{E}[G_x(\mathbf{R}(y))] \geq (1 - p) \cdot G_x(\emptyset) = (1 - p) \cdot F(x) , \end{aligned}$$

where the inequality follows from Lemma 4. \square

Using the last lemma, we now prove two lemmata proving upper and lower bounds the expression $F(\hat{x} + \mathbf{1}_{\text{OPT} \setminus \text{supp}(\hat{x})})$.

Lemma 24. *If $\|\hat{x}\|_1 < k$, then $F(\hat{x} + \mathbf{1}_{\text{OPT} \setminus \text{supp}(\hat{x})}) \geq (1 - p) \cdot [p \cdot f(\text{OPT}) + (1 - p) \cdot f(\text{OPT} \setminus \text{supp}(\hat{x}))]$.*

Proof. Since $\|\hat{x}\|_1 < k$, Observation 20 guarantees that $\hat{x}_e = p$ for every $e \in \text{supp}(\hat{x})$. Thus $\hat{x} = p \cdot \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})} + p \cdot \mathbf{1}_{\text{supp}(\hat{x}) \setminus \text{OPT}}$, and therefore,

$$\begin{aligned} F(\hat{x} + \mathbf{1}_{\text{OPT} \setminus \text{supp}(\hat{x})}) &= F(p \cdot \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})} + p \cdot \mathbf{1}_{\text{supp}(\hat{x}) \setminus \text{OPT}} + \mathbf{1}_{\text{OPT} \setminus \text{supp}(\hat{x})}) \\ &\geq (1 - p) \cdot F(p \cdot \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})} + \mathbf{1}_{\text{OPT} \setminus \text{supp}(\hat{x})}) \\ &\geq (1 - p) \cdot \hat{f}(p \cdot \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})} + \mathbf{1}_{\text{OPT} \setminus \text{supp}(\hat{x})}) \\ &= (1 - p) \cdot [p \cdot f(\text{OPT}) + (1 - p) \cdot f(\text{OPT} \setminus \text{supp}(\hat{x}))] , \end{aligned}$$

where the first inequality follows from Lemma 23, the second inequality holds since the Lovász extension lower bounds the multilinear extension, and the last equality follows from the definition of the Lovász extension. \square

In the following lemma, and the rest of the section, we use the notation $b = k^{-1} \cdot |\text{OPT} \setminus \text{supp}(\hat{x})|$. Intuitively, the lemma holds since the fact that the elements of $\text{OPT} \setminus \text{supp}(\hat{x})$ were not added to the support of x by Algorithm 3 implies that their marginal contribution is small.

Lemma 25. *If $\|\hat{x}\|_1 < k$, then $F(\hat{x} + \mathbf{1}_{\text{OPT} \setminus \text{supp}(\hat{x})}) \leq F(\hat{x}) + bc\tau$.*

Proof. The elements in $\text{OPT} \setminus \text{supp}(\hat{x})$ were rejected by Algorithm 3, which means that their marginal contribution with respect to the fractional solution x at the time of their arrival was smaller than $c\tau/k$. Since the fractional solution x only increases during the execution of the algorithm, the submodularity of f guarantees that the same is true also with respect to \hat{x} . More formally, we get

$$\partial_e F(\hat{x}) < \frac{c\tau}{k} \quad \forall e \in \text{OPT} \setminus \text{supp}(\hat{x}) .$$

Using the submodularity of f again, this implies

$$F(\hat{x} + \mathbf{1}_{\text{OPT} \setminus \text{supp}(\hat{x})}) \leq F(\hat{x}) + \sum_{e \in \text{OPT} \setminus \text{supp}(\hat{x})} \partial_e F(\hat{x}) \leq F(\hat{x}) + |\text{OPT} \setminus \text{supp}(\hat{x})| \cdot \frac{c\tau}{k} = F(\hat{x}) + bc\tau . \quad \square$$

Combining the last two lemmata immediately yields the promised lower bound on $F(\hat{x})$. To understand the second inequality in the following corollary, recall that $\tau \leq f(\text{OPT})$.

Corollary 26. *If $\|\hat{x}\|_1 < k$, then $F(\hat{x}) \geq (1-p) \cdot \left[p \cdot f(\text{OPT}) + (1-p) \cdot f(\text{OPT} \setminus \text{supp}(\hat{x})) \right] - bc\tau \geq [p(1-p) - bc]\tau + (1-p)^2 \cdot f(\text{OPT} \setminus \text{supp}(\hat{x}))$.*

Our next step is to get a lower bound on the expected value of $f(S_2)$. One easy way to get such a lower bound is to observe that $\text{OPT} \cap \text{supp}(\hat{x})$ is a subset of the support of \hat{x} of size at most k , and thus, is a feasible solution for `OFFLINEALG` to return; which implies $\mathbb{E}[f(S_2)] \geq \alpha \cdot f(\text{OPT} \cap \text{supp}(\hat{x}))$ since the algorithm `OFFLINEALG` used to find S_2 is an α -approximation algorithm. The following lemma proves a more involved lower bound by considering the vector $(b\hat{x}) \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})}$ as a fractional feasible solution (using the rounding methods discussed above it, it can be converted into an integral feasible solution of at least the same value). The proof of the lemma lower bounds the value of the vector $(b\hat{x}) \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})}$ using the concavity of the function $F((t \cdot \hat{x}) \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})})$ as well as ideas used in the proofs of the previous claims.

Lemma 27. *If $\|\hat{x}\|_1 < k$, then $\mathbb{E}[f(S_2)] \geq \alpha b(1-p-cb)\tau + \alpha(1-b) \cdot f(\text{OPT} \cap \text{supp}(\hat{x}))$.*

Proof. Consider the vector $(b\hat{x}) \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})}$. Clearly,

$$\begin{aligned} \|(b\hat{x}) \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})}\|_1 &\leq b \cdot \|\hat{x}\|_1 + \|\mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})}\|_1 \\ &\leq |\text{OPT} \setminus \text{supp}(\hat{x})| + |\text{OPT} \cap \text{supp}(\hat{x})| = |\text{OPT}| \leq k, \end{aligned}$$

where the second inequality holds by the definition of b since $\|\hat{x}\|_1 < k$. Thus, due to the existence of the rounding methods discussed in the beginning of the section, there must exist a set S of size at most k obeying $f(S) \geq F((b\hat{x}) \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})})$. Since S_2 is produced by `OFFLINEALG`, whose approximation ratio is α , this implies $\mathbb{E}[f(S_2)] \geq \alpha \cdot F((b\hat{x}) \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})})$. Thus, to prove the lemma it suffices to show that $F((b\hat{x}) \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})})$ is always at least $b(1-p-cb)\tau + (1-b) \cdot f(\text{OPT} \cap \text{supp}(\hat{x}))$.

The first step towards proving the last inequality is getting a lower bound on $F(\hat{x} \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})})$. Recall that we already showed in the proof of Lemma 25 that

$$\partial_e F(\hat{x}) < \frac{c\tau}{k} \quad \forall e \in \text{OPT} \setminus \text{supp}(\hat{x}).$$

Thus, the submodularity of f implies

$$\begin{aligned} F(\hat{x} \vee \mathbf{1}_{\text{OPT}}) &\leq F(\hat{x} \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})}) + \sum_{e \in \text{OPT} \setminus \text{supp}(\hat{x})} \partial_e F(\hat{x}) \\ &\leq F(\hat{x} \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})}) + \frac{c\tau \cdot |\text{OPT} \setminus \text{supp}(\hat{x})|}{k} = F(\hat{x} \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})}) + cb\tau. \end{aligned}$$

Rearranging this inequality yields

$$F(\hat{x} \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})}) \geq F(\hat{x} \vee \mathbf{1}_{\text{OPT}}) - cb\tau \geq (1-p) \cdot f(\text{OPT}) - cb\tau \geq (1-p-cb)\tau,$$

where the second inequality holds by Lemma 23 since Observation 20 guarantees that every coordinate of \hat{x} is either 0 or p . This gives us the promised lower bound on $F(\hat{x} \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})})$.

We now note that the submodularity of f implies that $F((t \cdot \hat{x}) \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})})$ is a concave function of t within the range $[0, 1]$. Since b is inside this range,

$$\begin{aligned} F((b\hat{x}) \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})}) &\geq b \cdot F(\hat{x} \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})}) + (1-b) \cdot f(\text{OPT} \cap \text{supp}(\hat{x})) \\ &\geq b(1-p-cb)\tau + (1-b) \cdot f(\text{OPT} \cap \text{supp}(\hat{x})), \end{aligned}$$

which completes the proof of the lemma. \square

Using the last two claims we can now obtain a lower bound on the value of the solution of Algorithm 3 in the case of $\|\hat{x}\|_1 < k$ which is a function of α , τ and p alone. We note that both the guarantees of Corollary 26 and Lemma 27 are lower bounds on the expected value of the output of the algorithm in this case since $\mathbb{E}[f(S_1)] \geq F(\hat{x})$. Thus, any convex combination of these guarantees is also such a lower bound, and the proof of the following corollary basically proves a lower bound for one such convex combination—for the specific value of c stated in the corollary.

Corollary 28. *If $\|\hat{x}\|_1 < k$ and c is set to $\frac{\alpha(1-p)}{\alpha+1}$, then $\mathbb{E}[\max\{f(S_1), f(S_2)\}] \geq \frac{(1-p)\alpha\tau}{\alpha+1}$.*

Proof. The corollary follows immediately from the non-negativity of f when $p = 1$. Thus, we may assume $p < 1$ in the rest of the proof.

By the definition of S_1 , $\mathbb{E}[f(S_1)] \geq F(\hat{x})$. Thus, by Corollary 26 and Lemma 27,

$$\begin{aligned} \mathbb{E}[\max\{f(S_1), f(S_2)\}] &\geq \max\{\mathbb{E}[f(S_1)], \mathbb{E}[f(S_2)]\} \\ &\geq \max\{[p(1-p) - bc]\tau + (1-p)^2 \cdot f(\text{OPT} \setminus \text{supp}(\hat{x})), \\ &\quad \alpha b(1-p - cb)\tau + \alpha(1-b) \cdot f(\text{OPT} \cap \text{supp}(\hat{x}))\} \\ &\geq \frac{\alpha(1-b)}{\alpha(1-b) + (1-p)^2} \cdot [p(1-p) - bc]\tau + (1-p)^2 \cdot f(\text{OPT} \setminus \text{supp}(\hat{x})) \\ &\quad + \frac{(1-p)^2}{\alpha(1-b) + (1-p)^2} \cdot [\alpha b(1-p - cb)\tau + \alpha(1-b) \cdot f(\text{OPT} \cap \text{supp}(\hat{x}))] . \end{aligned}$$

To keep the following calculations short, it will be useful to define $q = 1 - p$ and $d = 1 - b$. Using this notation and the fact that the submodularity and non-negativity of f guarantee together $f(\text{OPT} \setminus \text{supp}(\hat{x})) + f(\text{OPT} \cap \text{supp}(\hat{x})) \geq f(\text{OPT}) \geq \tau$, the previous inequality implies

$$\begin{aligned} \frac{\mathbb{E}[\max\{f(S_1), f(S_2)\}]}{\alpha\tau} &\geq \frac{(1-b)[p(1-p) - bc] + b(1-p)^2(1-p - bc) + (1-b)(1-p)^2}{\alpha(1-b) + (1-p)^2} \\ &= \frac{d[q(1-q) - (1-d)c] + q^2(1-d)[q - (1-d)c] + dq^2}{\alpha d + q^2} \\ &= \frac{d[q - (1-d)c] + q^2(1-d)[q - (1-d)c]}{\alpha d + q^2} = \frac{[d + q^2(1-d)][q - (1-d)c]}{\alpha d + q^2} \\ &= \frac{q[d + q^2(1-d)](d\alpha + 1)}{(\alpha + 1)(d\alpha + q^2)} = \frac{d^2\alpha + d\alpha q^2 - d^2\alpha q^2 + d + q^2 - dq^2}{d\alpha + q^2} \cdot \frac{q}{\alpha + 1} , \end{aligned} \tag{2}$$

where the fourth equality holds by plugging in the value we assume for c .

The second fraction in the last expression is independent of the value of d , and the derivative of the first fraction in this expression as a function of d is

$$\begin{aligned} &\frac{(2d\alpha + \alpha q^2 - 2d\alpha q^2 + 1 - q^2)[d\alpha + q^2] - \alpha(d^2\alpha + d\alpha q^2 - d^2\alpha q^2 + d + q^2 - dq^2)}{[d\alpha + q^2]^2} \\ &= \frac{1 - q^2}{[d\alpha + q^2]^2} \cdot [q^2(1 - \alpha) + d\alpha(d\alpha + 2q^2)] , \end{aligned}$$

which is always non-negative since both q and α are numbers between 0 and 1. Thus, we get that the minimal value of the expression (2) is obtained for $d = 0$ for any choice of q and α . Plugging this value into d yields

$$\mathbb{E}[\max\{f(S_1), f(S_2)\}] \geq \frac{q\alpha\tau}{\alpha + 1} = \frac{(1-p)\alpha\tau}{\alpha + 1} . \quad \square$$

Note that Lemma 22 and Corollary 28 both prove the same lower bound on the expectation $\mathbb{E}[\max\{f(S_1), f(S_2)\}]$ when c is set to the value it is set to in Corollary 28 (because $\mathbb{E}[\max\{f(S_1), f(S_2)\}] \geq \mathbb{E}[f(S_1)] \geq F(\hat{x})$). Thus, we can summarize the results we have proved so far using the following proposition.

Proposition 29. *Algorithm 3 is a semi-streaming algorithm storing $O(k/p)$ elements. Moreover, for the value of the parameter c given in Corollary 28, the output set produced by this algorithm has an expected value of at least $\frac{\alpha\tau(1-p)}{\alpha+1}$.*

Using the last proposition, we can now prove the following theorem. As discussed at the beginning of the section, the assumption that τ is known can be dropped at the cost of a slight increase in the number of elements stored by the algorithm, which yields Theorem 18.

Theorem 30. *For every constant $\varepsilon \in (0, 1]$, there exists a semi-streaming algorithm that assumes access to an estimate τ of $f(\text{OPT})$ obeying $(1 - \varepsilon/8) \cdot f(\text{OPT}) \leq \tau \leq f(\text{OPT})$ and provides $(\frac{\alpha}{1+\alpha} - \varepsilon)$ -approximation for the problem of maximizing a non-negative submodular function subject to cardinality constraint. This algorithm stores at most $O(k\varepsilon^{-1})$ elements.*

Proof. Consider the algorithm obtained from Algorithm 3 by setting $p = \varepsilon/2$ and c as is set in Corollary 28. By Proposition 29, this algorithm stores only $O(k/p) = O(k\varepsilon^{-1})$ elements, and the expected value of its output set is at least

$$\frac{\alpha\tau(1-p)}{\alpha+1} \geq \frac{\alpha(1-\varepsilon/8)(1-\varepsilon/2)}{\alpha+1} \cdot f(\text{OPT}) \geq \frac{\alpha(1-\varepsilon)}{\alpha+1} \cdot f(\text{OPT}) \geq \left(\frac{\alpha}{\alpha+1} - \varepsilon\right) \cdot f(\text{OPT}) ,$$

where the first inequality holds since τ obeys, by assumption, $\tau \geq (1 - \varepsilon/8) \cdot f(\text{OPT})$. \square

D Algorithm with true randomization

The variant of our algorithm that involves true randomization is shown in Algorithm 4. For simplicity, we describe the algorithm assuming the knowledge of an estimate of the value of the optimal solution, $f(\text{OPT})$. To remove this assumption, we use the standard technique introduced by [4]. The basic idea is to use the maximum singleton value $v = \max_e f(\{e\})$ as a k -approximation of $f(\text{OPT})$. Given this approximation, one can guess a $1 + \varepsilon$ approximation of $f(\text{OPT})$ from a set of $O(\log(k/\alpha)/\varepsilon)$ values ranging from v to kv/α (recall that α is the approximation guarantee of the offline algorithm OFFLINEALG that we use in the post-processing step). The final streaming algorithm is simply $O(\log(k/\alpha)/\varepsilon)$ copies of the basic algorithm running in parallel with different guesses. As new elements appear in the stream, the value $v = \max_e f(\{e\})$ also increases over time and thus, existing copies of the basic algorithm with small guesses are dropped and new copies with higher guesses are added. An important observation is that when we introduce a new copy with a large guess, starting it from mid-stream has exactly the same outcome as if we started it from the beginning of the stream: all previous elements have marginal gain much smaller than the guess and smaller than the threshold so they would have been rejected anyway. We refer to [4] for the full details.

Theorem 31. *There is a streaming algorithm STREAMPROCESSRANDOMIZED for non-negative, non-monotone submodular maximization with the following properties ($\varepsilon > 0$ is any desired accuracy and it is given as input to the algorithm):*

- *The algorithm makes a single pass over the stream.*

- The algorithm uses $O\left(\frac{k \log(k/\alpha) \log(1/\varepsilon)}{\varepsilon^3}\right)$ space.
- The update time per item is $O\left(\frac{\log(k/\alpha) \log(1/\varepsilon)}{\varepsilon^2}\right)$ marginal gain computations.

At the end of the stream, we post-process the output of `STREAMPROCESSRANDOMIZED` using any offline algorithm `OFFLINEALG` for submodular maximization. The resulting solution is a $\frac{\alpha}{1+\alpha} - \varepsilon$ approximation, where α is the approximation of `OFFLINEALG`.

Algorithm 4: Streaming algorithm for $\max_{|S| \leq k} f(S)$. `POSTPROCESS` uses any offline algorithm `OFFLINEALG` with approximation α . Lines shown in blue are comments. The algorithm does **not** store the sets $V_{i,j}$, they are defined for analysis purposes only.

```

1   $f: 2^V \rightarrow \mathbb{R}_{\geq 0}$ : submodular and non-negative
2   $k$ : cardinality constraint
3   $\varepsilon \in (0, 1]$ : accuracy parameter
4   $\kappa$ : threshold
5  STREAMPROCESSRANDOMIZED( $f, k, \varepsilon, \kappa$ )
6   $r \leftarrow \Theta(\ln(1/\varepsilon)/\varepsilon)$ 
7   $m \leftarrow 1/\varepsilon$ 
8   $S_{i,j} \leftarrow \emptyset$  for all  $i \in [r], j \in [m]$ 
9   $V_{i,j} \leftarrow \emptyset$  for all  $i \in [r], j \in [m]$  // not stored, defined for analysis purposes only
10 for each arriving element  $e$  do
11   for  $i = 1$  to  $r$  do
12     choose an index  $j \in [m]$  uniformly and independently at random
13      $V_{i,j} \leftarrow V_{i,j} \cup \{e\}$  // not stored, defined for analysis purposes only
14     if  $f(S_{i,j} \cup \{e\}) - f(S_{i,j}) \geq \kappa$  and  $|S_{i,j}| < k$  then
15        $S_{i,j} \leftarrow S_{i,j} \cup \{e\}$ 
16 return  $\{S_{i,j} : i \in [r], j \in [m]\}$ 
17 POSTPROCESS( $f, k, \varepsilon$ )
18 Assumes an estimate for  $f(\text{OPT})$ , see text on how to remove this assumption
19 Uses any offline algorithm OFFLINEALG with approximation  $\alpha$ 
20  $\kappa \leftarrow \frac{\alpha}{1+\alpha} \cdot \frac{1}{k} \cdot f(\text{OPT})$  // threshold
21  $\{S_{i,j}\} \leftarrow \text{STREAMPROCESSRANDOMIZED}(f, k, \varepsilon, \kappa)$ 
22 if  $|S_{i,j}| = k$  for some  $i$  and  $j$  then
23   return  $S_{i,j}$ 
24 else
25    $U \leftarrow \bigcup_{i,j} S_{i,j}$ 
26    $T \leftarrow \text{OFFLINEALG}(f, k, U)$ 
27   return  $\arg \max \{f(S_{1,1}), f(T)\}$ 

```

In the remainder of this section, we analyze Algorithm 4 and show that it achieves a $\frac{\alpha}{1+\alpha} - \varepsilon$ approximation, where α is the approximation guarantee of the offline algorithm `OFFLINEALG`.

We divide the analysis into two cases, depending on the probability of the event that a set $S_{i,1}$ (for some $i \in [r]$) constructed by `STREAMPROCESSRANDOMIZED` has size k . For every $i \in [r]$, let \mathcal{F}_i be the event that $|S_{i,1}| = k$. Since each of the r repetitions (iterations of the for loop of

Algorithm 5: Single threshold Greedy algorithm. The algorithm processes the elements in the order in which they arrive in the stream, and it uses the same threshold κ as STREAMPROCESSRANDOMIZED.

```

1 STGREEDY( $f, N, k, \kappa$ ):
2  $S \leftarrow \emptyset$ 
3 for each  $e \in N$  in the stream order do
4   if  $f(S \cup \{e\}) - f(S) \geq \kappa$  and  $|S| < k$  then
5      $S \leftarrow S \cup \{e\}$ 
6 return  $S$ 

```

STREAMPROCESSRANDOMIZED) use independent randomness to partition V , the events $\mathcal{F}_1, \dots, \mathcal{F}_r$ are independent. Additionally, the events $\mathcal{F}_1, \dots, \mathcal{F}_r$ have the same probability. We divide the analysis into two cases, depending on whether $\Pr[\mathcal{F}_1] \geq \varepsilon$ or $\Pr[\mathcal{F}_1] < \varepsilon$. In the first case, since we are repeating $r = \Theta(\ln(1/\varepsilon)/\varepsilon)$ times, the probability that there is a set $S_{i,j}$ of size k is at least $1 - \varepsilon$, and we obtain the desired approximation since $f(S_{i,j}) \geq \kappa |S_{i,j}| = \kappa k = \frac{\alpha}{1+\alpha} f(\text{OPT})$. In the second case, we have $\Pr[\overline{\mathcal{F}_1}] \geq 1 - \varepsilon$ and we argue that $\bigcup_{i,j} S_{i,j}$ contains a good solution. We now give the formal argument for each of the cases.

D.1 The case $\Pr[\mathcal{F}_1] \geq \varepsilon$

As noted earlier, the events $\mathcal{F}_1, \dots, \mathcal{F}_r$ are independent and have the same probability. Thus,

$$\Pr[\overline{\mathcal{F}_1 \cup \dots \cup \mathcal{F}_r}] \leq (1 - \varepsilon)^r \leq \exp(-\varepsilon r) \leq \varepsilon$$

since $r = \Theta(\ln(1/\varepsilon)/\varepsilon)$. Thus $\Pr[\mathcal{F}_1 \cup \dots \cup \mathcal{F}_r] \geq 1 - \varepsilon$.

Conditioned on the event $\mathcal{F}_1 \cup \dots \cup \mathcal{F}_r$, we obtain the desired approximation due to the following lemma. The lemma follows from the fact that the marginal gain of each selected element is at least κ .

Lemma 32. *We have $f(S_{i,j}) \geq \kappa |S_{i,j}|$ for all $i \in [r]$, $j \in [m]$.*

Proof. To simplify notation, let $S = S_{i,j}$. Let $e_1, \dots, e_{|S|}$ be the elements of S in the order in which they were added to S . Let $S^{(t)} = \{e_1, \dots, e_t\}$. We have $f(S^{(t)}) - f(S^{(t-1)}) = f(S^{(t-1)} \cup \{e_t\}) - f(S^{(t-1)}) \geq \kappa$ and thus

$$f(S) - f(\emptyset) = \sum_{t=1}^{|S|} (f(S^{(t)}) - f(S^{(t-1)})) \geq \kappa |S|$$

□

We can combine the two facts and obtain the desired approximation as follows. Let \mathcal{S} be the random variable equal to the solution returned by POSTPROCESS. We have

$$\mathbb{E}[f(\mathcal{S})] \geq \mathbb{E}[f(\mathcal{S}) | \mathcal{F}_1 \cup \dots \cup \mathcal{F}_r] \Pr[\mathcal{F}_1 \cup \dots \cup \mathcal{F}_r] \geq (1 - \varepsilon) \kappa k = (1 - \varepsilon) \frac{\alpha}{1 + \alpha} f(\text{OPT}) .$$

D.2 The case $\Pr[\mathcal{F}_1] < \varepsilon$

In this case, we show that the solution $\arg \max \{f(T), f(S_{1,1})\}$, which is returned on the last line of POSTPROCESS, has good value in expectation. Our analysis borrows ideas and techniques from the work of Barbosa *et al.* [5]: the probabilities p_e defined below are analogous to the probabilities used in that work; the division of OPT into two sets based on these probabilities is analogous to the division employed in Section 7.3 in that work; Lemma 34 shows a consistency property for the single threshold greedy algorithm that is analogous to the consistency property shown for the standard greedy algorithm and other algorithms by Barbosa *et al.* We emphasize that Barbosa *et al.* use these concepts in a different context (specifically, *monotone* maximization in the *distributed* setting). When applied to our context—*non-monotone* maximization in the *streaming* setting—the framework of Barbosa *et al.* requires $\Omega(\sqrt{nk})$ memory if used with a single pass (alternatively, they use $\Omega(\min\{k, 1/\varepsilon\})$ passes) and achieves worse approximation guarantees.

Notation and definitions. For analysis purposes only, we make use of the Lovasz extension \hat{f} . We fix an optimal solution $\text{OPT} \in \arg \max \{f(A) : A \subseteq V, |A| \leq k\}$. Let $\mathcal{V}(1/m)$ be the distribution of $1/m$ -samples of V , where a $1/m$ -sample of V includes each element of V independently at random with probability $1/m$. Note that $V_{i,j} \sim \mathcal{V}(1/m)$ for every $i \in [r]$, $j \in [m]$ (see STREAMPROCESSRANDOMIZED). Additionally, for each $i \in [r]$, $V_{i,1}, \dots, V_{i,m}$ is a partition of V into $1/m$ -samples.

For a subset $N \subseteq V$, we let $\text{STGREEDY}(N)$ be the output of the single threshold greedy algorithm when run as follows (see also Algorithm 5 for a formal description of the algorithm): the algorithm processes the elements of N *in the order in which they arrive in the stream* and it uses the same threshold κ as STREAMPROCESSRANDOMIZED; starting with the empty solution and continuing until the size constraint of k is reached, the algorithm adds an element to the current solution if its marginal gain is above the threshold. Note that $S_{i,j} = \text{STGREEDY}(V_{i,j})$ for all $i \in [r], j \in [m]$. For analysis purposes only, we also consider $\text{STGREEDY}(N)$ for sets N that do not correspond to any set $V_{i,j}$.

For each $e \in V$, we define

$$p_e = \begin{cases} \Pr_{X \sim \mathcal{V}(1/m)} [e \in \text{STGREEDY}(X \cup \{e\})] & \text{if } e \in \text{OPT} \\ 0 & \text{otherwise} \end{cases}.$$

We partition OPT into two sets:

$$\begin{aligned} O_1 &= \{e \in \text{OPT} : p_e \geq \varepsilon\} \\ O_2 &= \text{OPT} \setminus O_1. \end{aligned}$$

We also define the following subset of O_2 :

$$O'_2 = \{e \in O_2 : e \notin \text{STGREEDY}(V_{1,1} \cup \{e\})\}.$$

Note that (O_1, O_2) is a deterministic partition of OPT, whereas O'_2 is a random subset of O_2 . The role of the sets O_1, O_2, O'_2 will become clearer in the analysis. The intuition is that, using the repetition, we can ensure that each element of O_1 ends up in the collected set $U = \bigcup_{i,j} S_{i,j}$ with good probability: each iteration $i \in [r]$ ensures that an element $e \in O_1$ is in $S_{i,1} \cup \dots \cup S_{i,m}$ with probability $p_e \geq \varepsilon$ and, since we repeat $r = \Theta(\ln(1/\varepsilon)/\varepsilon)$ times, we will ensure that $\mathbb{E}[\mathbf{1}_{O_1 \cap U}] \geq (1 - \varepsilon)\mathbf{1}_{O_1}$. We also have that $\mathbb{E}[\mathbf{1}_{O'_2}] \geq (1 - \varepsilon)\mathbf{1}_{O_2}$: an element $e \in O_2 \setminus O'_2$ ends up being picked by STGREEDY when run on input $V_{1,1} \cup \{e\}$, which is a low probability event for the elements in O_2 ; more precisely, the probability of this event is equal to p_e (since $V_{1,1} \sim \mathcal{V}(1/m)$) and $p_e \leq \varepsilon$ (since $e \in O_2$). Thus

$\mathbb{E}[\mathbf{1}_{(O_1 \cap U) \cup O'_2}] \geq (1 - \varepsilon)\mathbf{1}_{\text{OPT}}$, which implies that the expected value of $(O_1 \cap U) \cup O'_2$ is at least $(1 - \varepsilon)f(\text{OPT})$. However, whereas $O_1 \cap U$ is available in the post-processing phase, elements of O'_2 may not be available and they may account for most of the value of O_2 . The key insight is to show that $S_{1,1}$ makes up for the lost value from these elements.

We start the analysis with two helper lemmas, which follow from standard arguments that have been used in previous works. The first of these lemmas follows from an argument based on the Lovasz extension and its properties.

Lemma 33. *Let $0 \leq u \leq v \leq 1$. Let $S \subseteq V \setminus \text{OPT}$ and $O \subseteq \text{OPT}$ be random sets such that $\mathbb{E}[\mathbf{1}_S] \leq u\mathbf{1}_{V \setminus \text{OPT}}$ and $\mathbb{E}[\mathbf{1}_O] \geq v\mathbf{1}_{\text{OPT}}$. Then $\mathbb{E}[f(S \cup O)] \geq (v - u)f(\text{OPT})$.*

Proof. Let \hat{f} be the Lovasz extension of f . Using the fact that \hat{f} is an extension and it is convex, we obtain

$$\mathbb{E}[f(S \cup O)] = \mathbb{E}[\hat{f}(\mathbf{1}_{S \cup O})] \geq \hat{f}(\mathbb{E}[\mathbf{1}_{S \cup O}]) = \hat{f}(\mathbb{E}[\mathbf{1}_S] + \mathbb{E}[\mathbf{1}_O])$$

Let $\mathbf{x} := \mathbb{E}[\mathbf{1}_S] + \mathbb{E}[\mathbf{1}_O]$. Note that

$$x_e = \begin{cases} \Pr[e \in S] \leq u & \text{if } e \in V \setminus \text{OPT} \\ \Pr[e \in O] \geq v & \text{if } e \in \text{OPT} \end{cases}.$$

Thus, we have

$$\hat{f}(\mathbf{x}) = \int_0^1 f(\{e \in V : x_e \geq \theta\}) d\theta \geq \int_u^v f(\{e \in V : x_e \geq \theta\}) d\theta = (v - u)f(\text{OPT}).$$

The first equality is the definition of \hat{f} . The inequality is by the non-negativity of f . The second equality is due to the fact that, for $u < \theta \leq v$, we have $\{e \in V : x_e \geq \theta\} = \text{OPT}$. \square

The following lemma establishes a consistency property for the STGREEDY algorithm, analogous to the consistency property shown and used by Barbosa *et al.* for algorithms such as the standard Greedy algorithm. The proof is also very similar to the proof shown by Barbosa *et al.*

Lemma 34. *Conditioned on the event $|S_{1,1}| < k$, $\text{STGREEDY}(V_{1,1} \cup O'_2) = \text{STGREEDY}(V_{1,1}) = S_{1,1}$.*

Proof. To simplify notation, we let $V_1 = V_{1,1}$ and $S_1 = S_{1,1}$. Let $X = \text{STGREEDY}(V_1 \cup O'_2)$. Suppose for contradiction that $S_1 \neq X$. Let $e_1, e_2, \dots, e_{|V_1 \cup O'_2|}$ be the elements of $V_1 \cup O'_2$ in the order in which they arrived in the stream. Let i be the smallest index such that $\text{STGREEDY}(\{e_1, \dots, e_i\}) \neq \text{STGREEDY}(\{e_1, \dots, e_i\} \cap V_1)$. By the choice of i , we have

$$\text{STGREEDY}(\{e_1, \dots, e_{i-1}\}) = \text{STGREEDY}(\{e_1, \dots, e_{i-1}\} \cap V_1) := A.$$

Note that $|A| < k$, since $A \subseteq S_1$ and $|S_1| < k$ by assumption. Since $\text{STGREEDY}(\{e_1, \dots, e_i\}) \neq \text{STGREEDY}(\{e_1, \dots, e_i\} \cap V_1)$, we must have $e_i \notin V_1$ (and thus $e_i \in O'_2 \setminus V_1$) and $f(A \cup \{e_i\}) - f(A) \geq \kappa$. The latter implies that $e_i \in \text{STGREEDY}(V_1 \cup \{e_i\})$: after processing all of the elements of V_1 that arrived before e_i , the partial greedy solution is A ; when e_i arrives, it is added to the solution since $|A| < k$ and $f(A \cup \{e_i\}) - f(A) \geq \kappa$. But then $e_i \notin O'_2$, which is a contradiction. \square

We now proceed with the main analysis. Recall that POSTPROCESS runs OFFLINEALG on U to obtain a solution T , and returns the better of the two solutions $S_{1,1}$ and T . In the following lemma, we show that the value of this solution is proportional to $f(S_{1,1} \cup (O_1 \cap U))$. Note that $S_{1,1} \cup (O_1 \cap U)$ may not be feasible, since we could have $|S_{1,1}| > |O_2|$, and hence the scaling based on $\frac{|O_2|}{k}$.

Lemma 35. We have $\max \{f(S_{1,1}), f(T)\} \geq \frac{\alpha}{1+\alpha\left(1-\frac{|O_2|}{k}\right)} f(S_{1,1} \cup (O_1 \cap U))$.

Proof. To simplify notation, we let $S_1 = S_{1,1}$. Let $b = |O_2|$. First, we analyze $f(T)$. Let $X \subseteq S_1$ be a random subset of S_1 such that $|X| \leq b$ and $\mathbb{E}[\mathbf{1}_X] = \frac{b}{k} \mathbf{1}_{S_1}$. We can select such a subset as follows: we first choose a permutation of S_1 uniformly at random, and let \tilde{X} be the first $s := \min \{b, |S_1|\}$ elements in the permutation. For each element of \tilde{X} , we add it to X with probability $p := |S_1|b/(sk)$.

Since $X \cup ((O_1 \cap U) \setminus S_1)$ is a feasible solution contained in U and OFFLINEALG achieves an α -approximation, we have

$$f(T) \geq \alpha f(X \cup ((O_1 \cap U) \setminus S_1)) .$$

By taking expectation over X only (more precisely, the random sampling that we used to select X) and using that \hat{f} is a convex extension, we obtain:

$$\begin{aligned} f(T) &\geq \alpha \mathbb{E}_X [f(X \cup ((O_1 \cap U) \setminus S_1))] = \alpha \mathbb{E}_X [\hat{f}(\mathbf{1}_{X \cup ((O_1 \cap U) \setminus S_1)})] \\ &\geq \alpha \hat{f}(\mathbb{E}_X [\mathbf{1}_{X \cup ((O_1 \cap U) \setminus S_1)}]) = \alpha \hat{f}\left(\frac{b}{k} \mathbf{1}_{S_1} + \mathbf{1}_{(O_1 \cap U) \setminus S_1}\right) . \end{aligned}$$

Next, we lower bound $\max \{f(S_1), f(T)\}$ using a convex combination $(1 - \theta)f(S_1) + \theta f(T)$ with coefficient $\theta = 1/(1 + \alpha(1 - \frac{b}{k}))$. Note that $1 - \theta = \theta\alpha(1 - \frac{b}{k})$. By taking this convex combination, using the previous inequality lower bounding $f(T)$, and the convexity and restricted scale invariance of \hat{f} , we obtain:

$$\begin{aligned} \max \{f(S_1), f(T)\} &\geq (1 - \theta)f(S_1) + \theta f(T) = \theta\alpha \left(1 - \frac{b}{k}\right) f(S_1) + \theta f(T) \\ &\geq \theta\alpha \left(1 - \frac{b}{k}\right) \hat{f}(\mathbf{1}_{S_1}) + \theta\alpha \hat{f}\left(\frac{b}{k} \mathbf{1}_{S_1} + \mathbf{1}_{(O_1 \cap U) \setminus S_1}\right) \\ &= \theta\alpha \left(2 - \frac{b}{k}\right) \left(\frac{1 - \frac{b}{k}}{2 - \frac{b}{k}} \hat{f}(\mathbf{1}_{S_1}) + \frac{1}{2 - \frac{b}{k}} \hat{f}\left(\frac{b}{k} \mathbf{1}_{S_1} + \mathbf{1}_{(O_1 \cap U) \setminus S_1}\right)\right) \\ &\geq \theta\alpha \left(2 - \frac{b}{k}\right) \hat{f}\left(\frac{1 - \frac{b}{k}}{2 - \frac{b}{k}} \mathbf{1}_{S_1} + \frac{1}{2 - \frac{b}{k}} \left(\frac{b}{k} \mathbf{1}_{S_1} + \mathbf{1}_{(O_1 \cap U) \setminus S_1}\right)\right) \\ &= \theta\alpha \left(2 - \frac{b}{k}\right) \hat{f}\left(\frac{1}{2 - \frac{b}{k}} \mathbf{1}_{S_1 \cup (O_1 \cap U)}\right) \geq \frac{\alpha}{1 + \alpha\left(1 - \frac{b}{k}\right)} f(S_1 \cup (O_1 \cap U)) . \quad \square \end{aligned}$$

Next, we analyze the expected value of $f(S_{1,1} \cup (O_1 \cap U))$. We do so in two steps: first we analyze the marginal gain of O'_2 on top of $S_{1,1}$ and show that it is suitably small, and then we analyze $f(S_{1,1} \cup (O_1 \cap U) \cup O'_2)$ and show that its expected value is proportional to $f(\text{OPT})$. We use the notation $f(A \mid B)$ to denote the marginal gain of set A on top of set B , i.e., $f(A \mid B) = f(A \cup B) - f(B)$.

Lemma 36. We have $\mathbb{E}[f(O'_2 \mid S_{1,1})] \leq \kappa b + \varepsilon f(\text{OPT})$.

Proof. As before, to simplify notation, we let $S_1 = S_{1,1}$ and $V_1 = V_{1,1}$. We break down the expectation using the law of total expectation as follows:

$$\begin{aligned} &\mathbb{E}[f(O'_2 \mid S_1)] \\ &= \mathbb{E}[f(O'_2 \mid S_1) \mid |S_1| < k] \cdot \underbrace{\Pr[|S_1| < k]}_{\leq 1} + \underbrace{\mathbb{E}[f(O'_2 \mid S_1) \mid |S_1| = k]}_{\leq f(\text{OPT})} \cdot \underbrace{\Pr[|S_1| = k]}_{\leq \varepsilon} \\ &\leq \mathbb{E}[f(O'_2 \mid S_1) \mid |S_1| < k] + \varepsilon f(\text{OPT}) . \end{aligned}$$

Above, we have used that $f(O'_2 \mid S_1) \leq f(O'_2) \leq f(\text{OPT})$, where the first inequality follows by submodularity. We have also used that $\Pr[|S_1| = k] = \Pr[\mathcal{F}_1] \leq \varepsilon$. Thus, it only remains to show that $\mathbb{E}[f(O'_2 \mid S_1) \mid |S_1| < k] \leq \kappa b$.

We condition on the event $|S_1| < k$ for the remainder of the proof. By Lemma 34, we have $\text{STGREEDY}(V_1 \cup O'_2) = S_1$. Since $|S_1| < k$, each element of $O'_2 \setminus S_1$ was rejected because its marginal gain was below the threshold when it arrived in the stream. This, together with submodularity, implies that

$$f(O'_2 \mid S_1) \leq \kappa |O'_2| \leq \kappa b. \quad \square$$

Lemma 37. *We have $\mathbb{E}[f(S_{1,1} \cup (O_1 \cap U) \cup O'_2)] \geq (1 - 2\varepsilon)f(\text{OPT})$.*

Proof. We apply Lemma 33 to the following sets:

$$\begin{aligned} S &= S_{1,1} \setminus \text{OPT} \\ O &= (S_{1,1} \cap \text{OPT}) \cup (O_1 \cap U) \cup O'_2. \end{aligned}$$

We show below that $\mathbb{E}[\mathbf{1}_S] \leq \varepsilon \mathbf{1}_{V \setminus \text{OPT}}$ and $\mathbb{E}[\mathbf{1}_O] \geq (1 - \varepsilon) \mathbf{1}_{\text{OPT}}$. Assuming these bounds, we can take $u = \varepsilon$ and $v = 1 - \varepsilon$ in Lemma 33, which gives the desired result.

Since $S \subseteq S_{1,1} \subseteq V_{1,1}$ and $V_{1,1}$ is a $(1/m)$ -sample of V , we have $\mathbb{E}[\mathbf{1}_S] \leq \frac{1}{m} \mathbf{1}_{V \setminus \text{OPT}} = \varepsilon \mathbf{1}_{V \setminus \text{OPT}}$. Thus it only remains to show that, for each $e \in \text{OPT}$, we have $\Pr[e \in O] \geq 1 - \varepsilon$. Since $(O_1 \cap U) \cup O'_2 \subseteq O$, it suffices to show that $\Pr[e \in (O_1 \cap U) \cup O'_2] \geq 1 - \varepsilon$, or equivalently that $\Pr[e \in (O_1 \setminus U) \cup (O_2 \setminus O'_2)] \leq \varepsilon$.

Recall that (O_1, O_2) is a deterministic partition of OPT . Thus e belongs to exactly one of O_1 and O_2 and we consider each of these cases in turn.

Suppose that $e \in O_1$. A single iteration of the for loop of `STREAMPROCESSRANDOMIZED` ensures that e is in $S_{i,1} \cup \dots \cup S_{i,m}$ with probability $p_e \geq \varepsilon$. Since we perform $r = \Theta(\ln(1/\varepsilon)/\varepsilon)$ independent iterations, we have $\Pr[e \notin U] \leq (1 - \varepsilon)^r \leq \exp(-\varepsilon r) \leq \varepsilon$.

Suppose that $e \in O_2$. We have

$$\Pr[e \in O_2 \setminus O'_2] = \Pr[e \in \text{STGREEDY}(V_{1,1} \cup \{e\})] = p_e \leq \varepsilon,$$

where the first equality follows from the definition of O'_2 , the second equality follows from the definition of p_e and the fact that $V_{1,1} \sim \mathcal{V}(1/m)$, and the inequality follows from the definition of O_2 . \square

Lemmas 36 and 37 immediately imply the following:

Lemma 38. *We have $\mathbb{E}[f(S_{1,1} \cup (O_1 \cap U))] \geq (1 - 3\varepsilon)f(\text{OPT}) - \kappa b$.*

Proof. Recall that we use the notation $f(A \mid B) = f(A \cup B) - f(B)$. We have

$$\begin{aligned} f(S_{1,1} \cup (O_1 \cap U)) &= f(S_{1,1} \cup (O_1 \cap U) \cup O'_2) - f(O'_2 \mid S_{1,1} \cup (O_1 \cap U)) \\ &\geq f(S_{1,1} \cup (O_1 \cap U) \cup O'_2) - f(O'_2 \mid S_{1,1}), \end{aligned}$$

where the inequality is by submodularity.

By taking expectation and using Lemmas 36 and 37, we obtain the desired result. \square

Finally, Lemmas 35 and 38 give the approximation guarantee:

Lemma 39. *We have $\mathbb{E}[\max\{f(S_{1,1}), f(T)\}] \geq \left(\frac{\alpha}{1+\alpha} - 3\varepsilon\right)f(\text{OPT})$.*

Proof. By Lemmas 35 and 38, we have

$$\begin{aligned}
\mathbb{E}[\max \{f(S_{1,1}), f(T)\}] &\geq \frac{\alpha}{1 + \alpha \left(1 - \frac{b}{k}\right)} \mathbb{E}[f(S_{1,1} \cup (O_1 \cap U))] \\
&\geq \frac{\alpha}{1 + \alpha \left(1 - \frac{b}{k}\right)} ((1 - 3\varepsilon)f(\text{OPT}) - \kappa b) \\
&= \frac{\alpha}{1 + \alpha \left(1 - \frac{b}{k}\right)} \left((1 - 3\varepsilon)f(\text{OPT}) - \frac{\alpha}{1 + \alpha} \frac{b}{k} f(\text{OPT}) \right) \\
&\geq \left(\frac{\alpha}{1 + \alpha} - 3\varepsilon \right) f(\text{OPT}) . \quad \square
\end{aligned}$$