

Optimal Streaming Algorithms for Submodular Maximization with Cardinality Constraints

Naor Alaluf* Alina Ene† Moran Feldman‡ Huy L. Nguyen§ Andrew Suh¶

February 21, 2020

Abstract

We study the problem of maximizing a *non-monotone* submodular function subject to a cardinality constraint in the streaming model. Our main contributions are two single-pass (semi-)streaming algorithms that use $\tilde{O}(k) \cdot \text{poly}(1/\varepsilon)$ memory, where k is the size constraint. At the end of the stream, both our algorithms post-process their data structures using *any offline algorithm* for submodular maximization, and obtain a solution whose approximation guarantee is $\frac{\alpha}{1+\alpha} - \varepsilon$, where α is the approximation of the offline algorithm. If we use an exact (exponential time) post-processing algorithm, this leads to $\frac{1}{2} - \varepsilon$ approximation (which is nearly optimal). If we post-process with the algorithm of [5], that achieves the state-of-the-art offline approximation guarantee of $\alpha = 0.385$, we obtain 0.2779-approximation in polynomial time, improving over the previously best polynomial-time approximation of 0.1715 due to [22]. One of our algorithms is combinatorial and enjoys fast update and overall running times. Our other algorithm is based on the multilinear extension, enjoys an improved space complexity, and can be made deterministic in some settings of interest.

1 Introduction

In this paper, we study the problem of maximizing a *non-monotone* submodular function subject to a cardinality (size) constraint in the streaming model. This problem captures problems of interest in a wide-range of domains, such as machine learning, data mining, combinatorial optimization, algorithmic game theory, social networks, and many others. A representative application is data summarization, where the goal is to select a small subset of the data that captures the salient features of the overall dataset [2]. One can model these problems as submodular maximization with a cardinality constraint: the submodular objective captures how informative the summary is, as well as other considerations such as how diverse the summary is, and the cardinality constraint ensures that the summary is small. Obtaining such a summary is very beneficial when working with massive data sets, that may not even fit into memory, since it makes it possible to analyze the data using algorithms that would be prohibitive to run on the entire dataset.

There have been two main approaches to deal with the large size of modern data sets: the *distributed* computation approach partitions the data across many machines and uses local computation on the machines and communication across the machines in order to perform the analysis,

*Department of Mathematics and Computer Science, Open University of Israel, naoralaluf@gmail.com.

†Department of Computer Science, Boston University, aene@bu.edu.

‡Department of Computer Science, University of Haifa, moranfe@cs.haifa.ac.il.

§Khoury College of Computer and Information Science, Northeastern University, hlnghuyen@cs.princeton.edu.

¶Department of Computer Science, Boston University, asuh9@bu.edu.

and the *streaming* computation approach processes the data in a stream using only a small amount of memory and (ideally) only a single pass over the data. Classical algorithms for submodular maximization, such as the Greedy algorithm, are not suitable in these settings since they are centralized and require many passes over the data. Motivated by the applications as well as theoretical considerations, there has been a significant interest in studying submodular maximization problems both in the distributed and the streaming setting, leading to many new results and insights [30, 37, 2, 11, 14, 34, 4, 36, 3, 18, 35, 22, 41].

Despite this significant progress, several fundamental questions remain open both in the streaming and distributed setting. In the streaming setting, which is the main focus of this paper, submodular maximization is fairly well understood when the objective function is additionally *monotone*—i.e., we have $f(A) \leq f(B)$ whenever $A \subseteq B$. For example, the Greedy approach, which obtains an optimal $(1 - 1/e)$ -approximation in the centralized setting when the function is monotone [38], can be adapted to the streaming model [30, 2]. This yields the single-threshold Greedy algorithm: make a single pass over the data and select an item if its marginal gain exceeds a suitably chosen threshold. If the threshold is chosen to be $\frac{1}{2} \frac{f(\text{OPT})}{k}$, where $f(\text{OPT})$ is the value of the optimal solution and k is the cardinality constraint, then the single-threshold Greedy algorithm is guaranteed to achieve $\frac{1}{2}$ -approximation. Although the value of the optimal solution is unknown, it can be estimated based on the largest singleton value even in the streaming setting [2]. The algorithm uses the maximum singleton value to make $O(\varepsilon^{-1} \log k)$ guesses for $f(\text{OPT})$ and, for each guess, it runs the single-threshold Greedy algorithm; which leads to $(\frac{1}{2} - \varepsilon)$ -approximation. Remarkably, this approximation guarantee is optimal in the streaming model even if we allow unbounded computational power: Feldman *et al.* [24] showed that any algorithm for monotone submodular maximization that achieves an approximation better than $\frac{1}{2}$ requires $\Omega\left(\frac{n}{k^3}\right)$ memory, where n is the length of the stream. Additionally, the single-threshold Greedy algorithm enjoys a fast update time of $O(\varepsilon^{-1} \log k)$ marginal value computations per item, and it uses $O(\varepsilon^{-1} k \log k)$ space.

In contrast, the general problem with a *non-monotone* objective has proved to be considerably more challenging. Even in the centralized setting, the Greedy algorithm fails to achieve any approximation guarantee when the objective is non-monotone. Thus, several approaches have been developed for handling non-monotone objectives in this setting, including local search [19, 32, 31], continuous optimization [23, 17, 5] and sampling [8, 21]. The currently best approximation guarantee is 0.385 [5], and the strongest inapproximability is 0.491 [26], and it remains a long-standing open problem to settle the approximability of submodular maximization subject to a cardinality constraint.

Adapting the above techniques to the streaming setting is challenging, and the approximation guarantees are weaker. The main approach for non-monotone maximization in the streaming setting has been to extend the local search algorithm of Chakrabarti and Kale [11] from monotone to non-monotone objectives. This approach was employed in a sequence of works [14, 22, 35], leading to the currently best approximation of $\frac{1}{3+2\sqrt{2}} \approx 0.1715$.¹ This naturally leads to the following questions.

- *What is the optimal approximation ratio achievable for submodular maximization in the streaming model? Is it possible to achieve $\frac{1}{2} - \varepsilon$ approximation using an algorithm that uses only $\text{poly}(k, 1/\varepsilon)$ space?*
- *Is there a good streaming algorithm for non-monotone functions based on the single-threshold Greedy algorithm that works so well for monotone functions?*
- *Can we exploit existing heuristics for the offline problem in the streaming setting?*

¹Chekuri *et al.* [14] claimed an improved approximation ratio of $\frac{1}{2+e} - \varepsilon$ for a cardinality constraint, but an error was later found in the proof of this improved ratio [13]. See Appendix A for more details.

1.1 Our contributions

In this work, we give an affirmative answer to all of the above questions. Specifically, we give streaming algorithms² that perform a single pass over the stream and output a set of size $k \cdot \text{poly}(1/\varepsilon)$ that can be post-processed using *any offline algorithm* for submodular maximization. The post-processing is itself quite straightforward: we simply run the offline algorithm on the output set to obtain a solution of size at most k . We show that, if the offline algorithm achieves α -approximation, then we obtain $\left(\frac{\alpha}{1+\alpha} - \varepsilon\right)$ -approximation.

Our main result implies that if we post-process using an exact (exponential time) algorithm, we obtain $(\frac{1}{2} - \varepsilon)$ -approximation. This matches the inapproximability result proven by [24] for the special case of a monotone function. Furthermore, we show that in the non-monotone case any streaming algorithm guaranteeing $(\frac{1}{2} + \varepsilon)$ -approximation for some positive constant ε must use in fact $\Omega(n)$ space.³ Thus, we essentially settle the approximability of the problem if exponential-time computation is allowed.

The best (polynomial-time) approximation guarantee that is currently known in the offline setting is $\alpha = 0.385$ [5]. If we post-process using this algorithm, we obtain 0.2779-approximation in polynomial time, improving over the previously best polynomial-time approximation of 0.1715 due to [22]. The offline algorithm of [5] is based on the multilinear extension, and thus is quite slow. One can obtain a more efficient overall algorithm by using the combinatorial random Greedy algorithm of [8] that achieves $\frac{1}{e}$ -approximation. Furthermore, any existing heuristic for the offline problem can be used for post-processing, exploiting their effectiveness beyond the worst case.

1.2 Our techniques

Prior to our work, the toolkit for submodular maximization in the streaming setting was comprised largely of local search techniques. We greatly expand this toolkit to include techniques such as continuous extensions and random partitions. These techniques have proved to be quite versatile in the sequential and distributed settings, and we hope that they will lead to further developments in the streaming setting as well.

The two streaming algorithms that we present enjoy the same approximation guarantee, but differ in other properties. Our first algorithm (STREAMPROCESS) is a combinatorial algorithm that achieves very fast update time and overall running time. STREAMPROCESS takes inspiration both from the single-threshold Greedy algorithm for *monotone* maximization and distributed algorithms that randomly partition the data [34, 4, 3]: it randomly partitions the elements into $1/\varepsilon$ parts as they arrive in the stream and runs the single-threshold Greedy algorithm on each part; this process is repeated independently and in parallel $O(\ln(1/\varepsilon)/\varepsilon)$ times. Since the main engine behind our algorithm is the very efficient and practical single-threshold Greedy algorithm, our STREAMPROCESS algorithm inherits its very efficient update time and practical potential. Compared to the optimal streaming algorithm for monotone maximization discussed above, our algorithm is quite similar: the monotone algorithm runs $O(\log k/\varepsilon)$ instances of single-threshold Greedy, each of which processes all n items; STREAMPROCESS runs $O(\ln(1/\varepsilon)/\varepsilon^2) \cdot O(\log k/\varepsilon)$ instances of single-threshold Greedy, each of which processes $O(\varepsilon \cdot n)$ items with high probability.

²Formally, our algorithms are semi-streaming algorithms, i.e., their space complexity is nearly linear in k . Since this is unavoidable for algorithms designed to output an approximate solution (as opposed to just estimating the value of the optimal solution), we ignore the difference between streaming and semi-streaming algorithms in this paper and use the two terms interchangeably.

³This result is a simple adaptation of a result due to Buchbinder et al. [9]. For completeness, we include the proof in Appendix B.

Our second algorithm (STREAMPROCESSEXTENSION) is based on the multilinear extension of the submodular function. This algorithm is similar to the single-threshold Greedy algorithm, but adds fractions of elements rather than whole elements to the solution it maintains. The extension based approach of this algorithm allows us to save on the space usage. Furthermore, when the multilinear extension can be evaluated deterministically, this approach leads to a deterministic algorithm. However, the time complexity of this approach depends on the complexity of evaluating the multilinear extension, which is quite high if we are only given value oracle access to f . Thus, given such restricted access, this approach leads to higher update and overall running time.

We note that combining the single-threshold Greedy with randomization is difficult because it requires delicate care of the event that the single-threshold Greedy algorithm fills up the budget. In particular, this was the source of the subtle error mentioned above in one of the results of [14]. Our approach here for handling this issue is simple in retrospect. In our combinatorial algorithm, we consider two cases depending on the probability that the budget is filled up in a run (this is a good event since the resulting solution has good value). If this probability is sufficiently large (at least ε), we repeat the basic algorithm $O(\ln(1/\varepsilon)/\varepsilon)$ times to boost the probability of this good event to $1 - \varepsilon$. Otherwise, the probability that the budget is not filled up in a run is at least $1 - \varepsilon$, and conditioning on this event changes the probabilities by only a $1 - \varepsilon$ factor.

In our extension based algorithm, the decisions of the algorithm are based on the values taken by derivatives of the extension, which are values of expectations over appropriately chosen distributions. On the one hand, this allows our algorithm to include a random component, which is a component that appears (at least implicitly) in all of the known algorithms for non-monotone submodular maximization. On the other hand, since expectations have deterministic values, the algorithm we get is deterministic enough that it suffices for us to consider at each time only one of two possible cases: the case in which the budget fills up, and the case in which it does not.

1.3 Additional related work

The problem of maximizing a non-negative monotone submodular function subject to a cardinality or a matroid constraint was studied (in the offline model) already in the 1970's. In 1978, Nemhauser et al. [40] and Fisher et al. [25] showed that a natural greedy algorithm achieves an approximation ratio of $1 - 1/e \approx 0.632$ for this problem when the constraint is a cardinality constraint and an approximation ratio of $1/2$ for matroid constraints. The $1 - 1/e$ approximation ratio for cardinality constraints was shown to be optimal already on the same year by Nemhauser and Wolsey [39], but the best possible approximation ratio for matroid constraints was open for a long time. Only a decade ago, Calinescu et al. [10] managed to show that a more involved algorithm, known as “continuous greedy”, can achieve $(1 - 1/e)$ -approximation for this type of constraint, which is tight since matroid constraints generalize cardinality constraints.

Unlike the natural greedy algorithm, continuous greedy is a randomized algorithm, which raised an interesting question regarding the best possible approximation ratio for matroid constraints that can be achieved by a deterministic algorithm. Very recently, Buchbinder et al. [7] made a slight step towards answering this question. Specifically, they described a deterministic algorithm for maximizing a monotone submodular function subject to a matroid constraint whose approximation ratio is 0.5008. This algorithm shows that the $1/2$ -approximation of the greedy algorithm is not the right answer for the above mentioned question.

Many works have studied also the offline problem of maximizing a non-negative (not necessarily monotone) submodular function subject to a cardinality or matroid constraint [5, 8, 16, 17, 20, 23]. The most recent of these works achieves an approximation ratio of 0.385 for both cardinality and matroid constraints [5]. In contrast, it is known that no polynomial time algorithm can

achieve an approximation ratio of 0.497 for cardinality constraints or 0.478 for matroid constraints, respectively [26].

The study of streaming algorithms for submodular maximization problems is related to the study of online algorithms for such problems. A partial list of works on algorithms of the last kind includes [1, 6, 9, 12, 27, 29].

Paper structure. In Section 2, defines the notation that we use and presents some known lemmata. Section 3 presents and analyzes our combinatorial algorithm (STREAMPROCESS). Finally, in Section 4, we present and analyze our extension based algorithm.

2 Preliminaries

Basic notation. Let V denote a finite ground set of size $n := |V|$. We occasionally assume without loss of generality that $V = \{1, 2, \dots, n\}$, and use, e.g., $x = (x_1, x_2, \dots, x_n)$ to denote a vector in \mathbb{R}^V . For two vectors $x, y \in \mathbb{R}^V$, we let $x \vee y$ and $x \wedge y$ be the vectors such that $(x \vee y)_e = \max\{x_e, y_e\}$ and $(x \wedge y)_e = \min\{x_e, y_e\}$ for all $e \in V$. For a set $S \subseteq V$, we let $\mathbf{1}_S$ denote the indicator vector of S , i.e., the vector that has 1 in every coordinate $e \in S$ and 0 in every coordinate $e \in V \setminus S$. Given an element $e \in V$, we use $\mathbf{1}_e$ as a shorthand for $\mathbf{1}_{\{e\}}$. Furthermore, if S is a random subset of V , we use $\mathbb{E}[\mathbf{1}_S]$ to denote the vector p such that $p_e = \Pr[e \in S]$ for all $e \in V$ (i.e., the expectation is applied coordinate-wise).

Submodular functions. In this paper, we consider the problem of maximizing a non-negative submodular function subject to a cardinality constraint. A set function $f: 2^V \rightarrow \mathbb{R}$ is submodular if $f(A) + f(B) \geq f(A \cap B) + f(A \cup B)$ for all subsets $A, B \subseteq V$.

Continuous extensions. We make use of two standard continuous extensions of submodular functions. The first of these extensions is known as the *multilinear extension*. To define this extension, we first need to define the random set $\mathbf{R}(x)$. For every vector $x \in [0, 1]^V$, $\mathbf{R}(x)$ is defined as a random subset of V that includes every element $e \in V$ with probability x_e , independently. The multilinear extension F of f is now defined for every vector $x \in [0, 1]^V$ by

$$F(x) = \mathbb{E}[f(\mathbf{R}(x))] = \sum_{A \subseteq V} f(A) \cdot \Pr[\mathbf{R}(x) = A] = \sum_{A \subseteq V} \left(f(A) \cdot \prod_{e \in A} x_e \cdot \prod_{e \notin A} (1 - x_e) \right).$$

One can observe from the definition that F is indeed a multilinear function of the coordinates of x , as suggested by its name. Thus, if we use the shorthand $\partial_e F(x)$ for the first partial derivative $\frac{\partial F(x)}{\partial x_e}$ of the multilinear extension F , then $\partial_e F(x) = F(x \vee \mathbf{1}_e) - F(x \wedge \mathbf{1}_{V \setminus \{e\}})$.

In the analysis of our extension based algorithm, we need an upper bound on the possible increase in the value of $F(x)$ when some of the indices of x are zeroed. Corollary 2 provides such an upper bound. It readily follows from the following known lemma by Buchbinder et al. [8] (see Appendix C.1 for the formal proof).

Lemma 1 (Lemma 2.2 from [8]). *Let $f: 2^V \rightarrow \mathbb{R}_{\geq 0}$ be a non-negative submodular function. Denote by $A(p)$ a random subset of A where each element appears with probability at most p (not necessarily independently). Then, $\mathbb{E}[f(A(p))] \geq (1 - p) \cdot f(\emptyset)$.*

In the statement of Corollary 2, and in the rest of the paper, we denote by $\text{supp}(x)$ the support of vector x , i.e., the set $\{e \in V \mid x_e > 0\}$.

Corollary 2. *Let $f: 2^V \rightarrow \mathbb{R}_{\geq 0}$ be a non-negative submodular function, let p be a number in the range $[0, 1]$ and let x, y be two vectors in $[0, 1]^V$ such that*

- $\text{supp}(x) \cap \text{supp}(y) = \emptyset$,
- and $y_e \leq p$ for every $e \in V$.

Then, the multilinear extension F of f obeys $F(x + y) \geq (1 - p) \cdot F(x)$.

The analyses of both our algorithms make use of the *Lovász extension* \hat{f} of f . The Lovász extension $\hat{f}: [0, 1]^V \rightarrow \mathbb{R}$ is defined as follows. For every $x \in [0, 1]^V$, $\hat{f}(x) = \mathbb{E}_{\theta \sim [0, 1]}[f(\{e \in V: x_e \geq \theta\})]$, where we use the notation $\theta \sim [0, 1]$ to denote a value chosen uniformly at random from the interval $[0, 1]$. The Lovász extension \hat{f} of a non-negative submodular function has the following properties: (1) convexity: $c\hat{f}(x) + (1 - c)\hat{f}(y) \geq \hat{f}(cx + (1 - c)y)$ for all $x, y \in [0, 1]^V$ and all $c \in [0, 1]$ [33]; (2) restricted scale invariance: $\hat{f}(cx) \geq c\hat{f}(x)$ for all $x \in [0, 1]^V$ and all $c \in [0, 1]$; (3) it lower bounds the multilinear extension, i.e., $F(x) \geq \hat{f}(x)$ for every $x \in [0, 1]^V$ [42, Lemma A.4].

3 Combinatorial Algorithm

Our combinatorial streaming algorithm is shown in Algorithm 1. For simplicity, we describe the algorithm assuming the knowledge of an estimate of the value of the optimal solution, $f(\text{OPT})$. To remove this assumption, we use the standard technique introduced by [2]. The basic idea is to use the maximum singleton value $v = \max_e f(\{e\})$ as a k -approximation of $f(\text{OPT})$. Given this approximation, one can guess a $1 + \varepsilon$ approximation of $f(\text{OPT})$ from a set of $O(\log(k/\alpha)/\varepsilon)$ values ranging from v to kv/α (α is the approximation guarantee of the offline algorithm OFFLINEALG that we use in the post-processing step). The final streaming algorithm is simply $O(\log(k/\alpha)/\varepsilon)$ copies of the basic algorithm running in parallel with different guesses. As new elements appear in the stream, the value $v = \max_e f(\{e\})$ also increases over time and thus, existing copies of the basic algorithm with small guesses are dropped and new copies with higher guesses are added. An important observation is that when we introduce a new copy with a large guess, starting it from mid-stream has exactly the same outcome as if we started it from the beginning of the stream: all previous elements have marginal gain much smaller than the guess and smaller than the threshold so they would have been rejected anyway. We refer to [2] for the full details.

Theorem 3. *There is a streaming algorithm STREAMPROCESS for non-negative, non-monotone submodular maximization with the following properties ($\varepsilon > 0$ is any desired accuracy and it is given as input to the algorithm):*

- The algorithm makes a single pass over the stream.
- The algorithm uses $O\left(\frac{k \log(k/\alpha) \log(1/\varepsilon)}{\varepsilon^3}\right)$ space.
- The update time per item is $O\left(\frac{\log(k/\alpha) \log(1/\varepsilon)}{\varepsilon^2}\right)$ marginal gain computations.

At the end of the stream, we post-process the output of STREAMPROCESS using any offline algorithm OFFLINEALG for submodular maximization. The resulting solution is a $\frac{\alpha}{1+\alpha} - \varepsilon$ approximation, where α is the approximation of OFFLINEALG.

In the remainder of this section, we analyze Algorithm 1 and show that it achieves a $\frac{\alpha}{1+\alpha} - \varepsilon$ approximation, where α is the approximation guarantee of the offline algorithm OFFLINEALG.

We divide the analysis into two cases, depending on the probability of the event that a set $S_{i,1}$ (for some $i \in [r]$) constructed by STREAMPROCESS has size k . For every $i \in [r]$, let \mathcal{F}_i be the event that $|S_{i,1}| = k$. Since each of the r repetitions (iterations of the for loop of STREAMPROCESS)

Algorithm 1: Streaming algorithm for $\max_{|S| \leq k} f(S)$. POSTPROCESS uses any offline algorithm OFFLINEALG with approximation α . Lines shown in blue are comments. The algorithm does **not** store the sets $V_{i,j}$, they are defined for analysis purposes only.

```

1 STREAMPROCESS( $f, k, \varepsilon, \kappa$ )
2  $r \leftarrow \Theta(\ln(1/\varepsilon)/\varepsilon)$ 
3  $m \leftarrow 1/\varepsilon$ 
4  $S_{i,j} \leftarrow \emptyset$  for all  $i \in [r], j \in [m]$ 
5  $V_{i,j} \leftarrow \emptyset$  for all  $i \in [r], j \in [m]$  // not stored, defined for analysis purposes only
6 for each arriving element  $e$  do
7   for  $i = 1$  to  $r$  do
8     choose an index  $j \in [m]$  uniformly and independently at random
9      $V_{i,j} \leftarrow V_{i,j} \cup \{e\}$  // not stored, defined for analysis purposes only
10    if  $f(S_{i,j} \cup \{e\}) - f(S_{i,j}) \geq \kappa$  and  $|S_{i,j}| < k$  then
11       $S_{i,j} \leftarrow S_{i,j} \cup \{e\}$ 
12 return  $\{S_{i,j} : i \in [r], j \in [m]\}$ 
13 POSTPROCESS( $f, k, \varepsilon$ )
14 Assumes an estimate for  $f(\text{OPT})$ , see text on how to remove this assumption
15  $\kappa \leftarrow \frac{\alpha}{1+\alpha} \cdot \frac{1}{k} \cdot f(\text{OPT})$  // threshold
16  $\{S_{i,j}\} \leftarrow \text{STREAMPROCESS}(f, k, \varepsilon, \kappa)$ 
17 if  $|S_{i,j}| = k$  for some  $i$  and  $j$  then
18   return  $S_{i,j}$ 
19 else
20    $U \leftarrow \bigcup_{i,j} S_{i,j}$ 
21    $T \leftarrow \text{OFFLINEALG}(f, k, U)$ 
22   return  $\arg \max \{f(S_{1,1}), f(T)\}$ 

```

use independent randomness to partition V , the events $\mathcal{F}_1, \dots, \mathcal{F}_r$ are independent. Additionally, the events $\mathcal{F}_1, \dots, \mathcal{F}_r$ have the same probability. We divide the analysis into two cases, depending on whether $\Pr[\mathcal{F}_1] \geq \varepsilon$ or $\Pr[\mathcal{F}_1] < \varepsilon$. In the first case, since we are repeating $r = \Theta(\ln(1/\varepsilon)/\varepsilon)$ times, the probability that there is a set $S_{i,j}$ of size k is at least $1 - \varepsilon$, and we obtain the desired approximation since $f(S_{i,j}) \geq \kappa |S_{i,j}| = \kappa k = \frac{\alpha}{1+\alpha} f(\text{OPT})$. In the second case, we have $\Pr[\overline{\mathcal{F}_1}] \geq 1 - \varepsilon$ and we argue that $\bigcup_{i,j} S_{i,j}$ contains a good solution. We now give the formal argument for each of the cases.

3.1 The case $\Pr[\mathcal{F}_1] \geq \varepsilon$

As noted earlier, the events $\mathcal{F}_1, \dots, \mathcal{F}_r$ are independent and have the same probability. Thus,

$$\Pr[\overline{\mathcal{F}_1 \cup \dots \cup \mathcal{F}_r}] \leq (1 - \varepsilon)^r \leq \exp(-\varepsilon r) \leq \varepsilon$$

since $r = \Theta(\ln(1/\varepsilon)/\varepsilon)$. Thus $\Pr[\mathcal{F}_1 \cup \dots \cup \mathcal{F}_r] \geq 1 - \varepsilon$.

Conditioned on the event $\mathcal{F}_1 \cup \dots \cup \mathcal{F}_r$, we obtain the desired approximation due to the following lemma. The lemma follows from the fact that the marginal gain of each selected element is at least κ .

Algorithm 2: Single threshold Greedy algorithm. The algorithm processes the elements in the order in which they arrive in the stream, and it uses the same threshold κ as STREAMPROCESS.

```

1 STGREEDY( $f, N, k, \kappa$ ):
2  $S \leftarrow \emptyset$ 
3 for each  $e \in N$  in the stream order do
4   if  $f(S \cup \{e\}) - f(S) \geq \kappa$  and  $|S| < k$  then
5      $S \leftarrow S \cup \{e\}$ 
6 return  $S$ 

```

Lemma 4. We have $f(S_{i,j}) \geq \kappa |S_{i,j}|$ for all $i \in [r], j \in [m]$.

We can combine the two facts and obtain the desired approximation as follows. Let \mathcal{S} be the random variable equal to the solution returned by POSTPROCESS. We have

$$\mathbb{E}[f(\mathcal{S})] \geq \mathbb{E}[f(\mathcal{S}) | \mathcal{F}_1 \cup \dots \cup \mathcal{F}_r] \Pr[\mathcal{F}_1 \cup \dots \cup \mathcal{F}_r] \geq (1 - \varepsilon) \kappa k = (1 - \varepsilon) \frac{\alpha}{1 + \alpha} f(\text{OPT})$$

3.2 The case $\Pr[\mathcal{F}_1] < \varepsilon$

In this case, we show that the solution $\arg \max \{f(T), f(S_{1,1})\}$, which is returned on the last line of POSTPROCESS, has good value in expectation. Our analysis borrows ideas and techniques from the work of Barbosa *et al.* [3]: the probabilities p_e defined below are analogous to the probabilities used in that work; the division of OPT into two sets based on these probabilities is analogous to the division employed in Section 7.3 in that work; Lemma 6 shows a consistency property for the single threshold greedy algorithm that is analogous to the consistency property shown for the standard greedy algorithm and other algorithms by Barbosa *et al.* We emphasize that Barbosa *et al.* use these concepts in a different context (specifically, *monotone* maximization in the *distributed* setting). When applied to our context—*non-monotone* maximization in the *streaming* setting—the framework of Barbosa *et al.* requires $\Omega(\sqrt{nk})$ memory if used with a single pass (alternatively, they use $\Omega(\min\{k, 1/\varepsilon\})$ passes) and achieves worse approximation guarantees.

Notation and definitions. For analysis purposes only, we make use of the Lovasz extension \hat{f} . We fix an optimal solution $\text{OPT} \in \arg \max \{f(A) : A \subseteq V, |A| \leq k\}$. Let $\mathcal{V}(1/m)$ be the distribution of $1/m$ -samples of V , where a $1/m$ -sample of V includes each element of V independently at random with probability $1/m$. Note that $V_{i,j} \sim \mathcal{V}(1/m)$ for every $i \in [r], j \in [m]$ (see STREAMPROCESS). Additionally, for each $i \in [r]$, $V_{i,1}, \dots, V_{i,m}$ is a partition of V into $1/m$ -samples.

For a subset $N \subseteq V$, we let $\text{STGREEDY}(N)$ be the output of the single threshold greedy algorithm when run as follows (see also Algorithm 2 for a formal description of the algorithm): the algorithm processes the elements of N in the order in which they arrive in the stream and it uses the same threshold κ as STREAMPROCESS; starting with the empty solution and continuing until the size constraint of k is reached, the algorithm adds an element to the current solution if its marginal gain is above the threshold. Note that $S_{i,j} = \text{STGREEDY}(V_{i,j})$ for all $i \in [r], j \in [m]$. For analysis purposes only, we also consider $\text{STGREEDY}(N)$ for sets N that do not correspond to any set $V_{i,j}$.

For each $e \in V$, we define

$$p_e = \begin{cases} \Pr_{X \sim \mathcal{V}(1/m)} [e \in \text{STGREEDY}(X \cup \{e\})] & \text{if } e \in \text{OPT} \\ 0 & \text{otherwise} \end{cases}.$$

We partition OPT into two sets:

$$\begin{aligned} O_1 &= \{e \in \text{OPT} : p_e \geq \varepsilon\} \\ O_2 &= \text{OPT} \setminus O_1. \end{aligned}$$

We also define the following subset of O_2 :

$$O'_2 = \{e \in O_2 : e \notin \text{STGREEDY}(V_{1,1} \cup \{e\})\}.$$

Note that (O_1, O_2) is a deterministic partition of OPT, whereas O'_2 is a random subset of O_2 . The role of the sets O_1, O_2, O'_2 will become clearer in the analysis. The intuition is that, using the repetition, we can ensure that each element of O_1 ends up in the collected set $U = \bigcup_{i,j} S_{i,j}$ with good probability: each iteration $i \in [r]$ ensures that an element $e \in O_1$ is in $S_{i,1} \cup \dots \cup S_{i,m}$ with probability $p_e \geq \varepsilon$ and, since we repeat $r = \Theta(\ln(1/\varepsilon)/\varepsilon)$ times, we will ensure that $\mathbb{E}[\mathbf{1}_{O_1 \cap U}] \geq (1 - \varepsilon)\mathbf{1}_{O_1}$. We also have that $\mathbb{E}[\mathbf{1}_{O'_2}] \geq (1 - \varepsilon)\mathbf{1}_{O_2}$: an element $e \in O_2 \setminus O'_2$ ends up being picked by STGREEDY when run on input $V_{1,1} \cup \{e\}$, which is a low probability event for the elements in O_2 ; more precisely, the probability of this event is equal to p_e (since $V_{1,1} \sim \mathcal{V}(1/m)$) and $p_e \leq \varepsilon$ (since $e \in O_2$). Thus $\mathbb{E}[\mathbf{1}_{(O_1 \cap U) \cup O'_2}] \geq (1 - \varepsilon)\mathbf{1}_{\text{OPT}}$, which implies that the expected value of $(O_1 \cap U) \cup O'_2$ is at least $(1 - \varepsilon)f(\text{OPT})$. However, whereas $O_1 \cap U$ is available in the post-processing phase, elements of O'_2 may not be available and they may account for most of the value of O_2 . The key insight is to show that $S_{1,1}$ makes up for the lost value from these elements.

We start the analysis with two helper lemmas, which follow from standard arguments that have been used in previous works (we give the proofs in Appendix C.2 for completeness). The first of these lemmas follows from an argument based on the Lovasz extension and its properties.

Lemma 5. *Let $0 \leq u \leq v \leq 1$. Let $S \subseteq V \setminus \text{OPT}$ and $O \subseteq \text{OPT}$ be random sets such that $\mathbb{E}[\mathbf{1}_S] \leq u\mathbf{1}_{V \setminus \text{OPT}}$ and $\mathbb{E}[\mathbf{1}_O] \geq v\mathbf{1}_{\text{OPT}}$. Then $\mathbb{E}[f(S \cup O)] \geq (v - u)f(\text{OPT})$.*

The following lemma establishes a consistency property for the STGREEDY algorithm, analogous to the consistency property shown and used by Barbosa *et al.* for algorithms such as the standard Greedy algorithm. The proof is also very similar to the proof shown by Barbosa *et al.*

Lemma 6. *Conditioned on the event $|S_{1,1}| < k$, $\text{STGREEDY}(V_{1,1} \cup O'_2) = \text{STGREEDY}(V_{1,1}) = S_{1,1}$.*

We now proceed with the main analysis. Recall that POSTPROCESS runs OFFLINEALG on U to obtain a solution T , and returns the better of the two solutions $S_{1,1}$ and T . In the following lemma, we show that the value of this solution is proportional to $f(S_{1,1} \cup (O_1 \cap U))$. Note that $S_{1,1} \cup (O_1 \cap U)$ may not be feasible, since we could have $|S_{1,1}| > |O_2|$, and hence the scaling based on $\frac{|O_2|}{k}$.

Lemma 7. *We have $\max\{f(S_{1,1}), f(T)\} \geq \frac{\alpha}{1 + \alpha \left(1 - \frac{|O_2|}{k}\right)} f(S_{1,1} \cup (O_1 \cap U))$.*

Proof. To simplify notation, we let $S_1 = S_{1,1}$. Let $b = |O_2|$. First, we analyze $f(T)$. Let $X \subseteq S_1$ be a random subset of S_1 such that $|X| \leq b$ and $\mathbb{E}[\mathbf{1}_X] = \frac{b}{k}\mathbf{1}_{S_1}$. We can select such a subset as follows: we first choose a permutation of S_1 uniformly at random, and let \tilde{X} be the first $s := \min\{b, |S_1|\}$ elements in the permutation. For each element of \tilde{X} , we add it to X with probability $p := |S_1|b/(sk)$.

Since $X \cup ((O_1 \cap U) \setminus S_1)$ is a feasible solution contained in U and OFFLINEALG achieves an α -approximation, we have

$$f(T) \geq \alpha f(X \cup ((O_1 \cap U) \setminus S_1))$$

By taking expectation over X only (more precisely, the random sampling that we used to select X) and using that \hat{f} is a convex extension, we obtain:

$$\begin{aligned} f(T) &\geq \alpha \mathbb{E}_X [f(X \cup ((O_1 \cap U) \setminus S_1))] = \alpha \mathbb{E}_X \left[\hat{f} \left(\mathbf{1}_{X \cup ((O_1 \cap U) \setminus S_1)} \right) \right] \\ &\geq \alpha \hat{f} \left(\mathbb{E}_X \left[\mathbf{1}_{X \cup ((O_1 \cap U) \setminus S_1)} \right] \right) = \alpha \hat{f} \left(\frac{b}{k} \mathbf{1}_{S_1} + \mathbf{1}_{(O_1 \cap U) \setminus S_1} \right) \end{aligned}$$

Next, we lower bound $\max \{f(S_1), f(T)\}$ using a convex combination $(1 - \theta)f(S_1) + \theta f(T)$ with coefficient $\theta = 1/(1 + \alpha(1 - \frac{b}{k}))$. Note that $1 - \theta = \theta\alpha(1 - \frac{b}{k})$. By taking this convex combination, using the previous inequality lower bounding $f(T)$, and the convexity and restricted scale invariance of \hat{f} , we obtain:

$$\begin{aligned} \max \{f(S_1), f(T)\} &\geq (1 - \theta)f(S_1) + \theta f(T) = \theta\alpha \left(1 - \frac{b}{k} \right) f(S_1) + \theta f(T) \\ &\geq \theta\alpha \left(1 - \frac{b}{k} \right) \hat{f}(\mathbf{1}_{S_1}) + \theta\alpha \hat{f} \left(\frac{b}{k} \mathbf{1}_{S_1} + \mathbf{1}_{(O_1 \cap U) \setminus S_1} \right) \\ &= \theta\alpha \left(2 - \frac{b}{k} \right) \left(\frac{1 - \frac{b}{k}}{2 - \frac{b}{k}} \hat{f}(\mathbf{1}_{S_1}) + \frac{1}{2 - \frac{b}{k}} \hat{f} \left(\frac{b}{k} \mathbf{1}_{S_1} + \mathbf{1}_{(O_1 \cap U) \setminus S_1} \right) \right) \\ &\geq \theta\alpha \left(2 - \frac{b}{k} \right) \hat{f} \left(\frac{1 - \frac{b}{k}}{2 - \frac{b}{k}} \mathbf{1}_{S_1} + \frac{1}{2 - \frac{b}{k}} \left(\frac{b}{k} \mathbf{1}_{S_1} + \mathbf{1}_{(O_1 \cap U) \setminus S_1} \right) \right) \\ &= \theta\alpha \left(2 - \frac{b}{k} \right) \hat{f} \left(\frac{1}{2 - \frac{b}{k}} \mathbf{1}_{S_1 \cup (O_1 \cap U)} \right) \geq \frac{\alpha}{1 + \alpha \left(1 - \frac{b}{k} \right)} f(S_1 \cup (O_1 \cap U)) \quad \square \end{aligned}$$

Next, we analyze the expected value of $f(S_{1,1} \cup (O_1 \cap U))$. We do so in two steps: first we analyze the marginal gain of O'_2 on top of $S_{1,1}$ and show that it is suitably small, and then we analyze $f(S_{1,1} \cup (O_1 \cap U) \cup O'_2)$ and show that its expected value is proportional to $f(\text{OPT})$. We use the notation $f(A|B)$ to denote the marginal gain of A on top of B , i.e., $f(A|B) = f(A \cup B) - f(B)$.

Lemma 8. *We have $\mathbb{E}[f(O'_2|S_{1,1})] \leq \kappa b + \varepsilon f(\text{OPT})$.*

Proof. As before, to simplify notation, we let $S_1 = S_{1,1}$ and $V_1 = V_{1,1}$. We break down the expectation using the law of total expectation as follows:

$$\begin{aligned} \mathbb{E}[f(O'_2|S_1)] &= \mathbb{E}[f(O'_2|S_1) \mid |S_1| < k] \cdot \underbrace{\Pr[|S_1| < k]}_{\leq 1} + \underbrace{\mathbb{E}[f(O'_2|S_1) \mid |S_1| = k]}_{\leq f(\text{OPT})} \cdot \underbrace{\Pr[|S_1| = k]}_{\leq \varepsilon} \\ &\leq \mathbb{E}[f(O'_2|S_1) \mid |S_1| < k] + \varepsilon f(\text{OPT}) \end{aligned}$$

Above, we have used that $f(O'_2|S_1) \leq f(O'_2) \leq f(\text{OPT})$, where the first inequality follows by submodularity. We have also used that $\Pr[|S_1| = k] = \Pr[\mathcal{F}_1] \leq \varepsilon$. Thus it only remains to show that $\mathbb{E}[f(O'_2|S_1) \mid |S_1| < k] \leq \kappa b$.

We condition on the event $|S_1| < k$ for the remainder of the proof. By Lemma 6, we have $\text{STGREEDY}(V_1 \cup O'_2) = S_1$. Since $|S_1| < k$, each element of $O'_2 \setminus S_1$ was rejected because its marginal gain was below the threshold when it arrived in the stream. This, together with submodularity, implies that

$$f(O'_2|S_1) \leq \kappa |O'_2| \leq \kappa b \quad \square$$

Lemma 9. *We have $\mathbb{E}[f(S_{1,1} \cup (O_1 \cap U) \cup O'_2)] \geq (1 - 2\varepsilon)f(\text{OPT})$.*

Proof. We apply Lemma 5 to the following sets:

$$\begin{aligned} S &= S_{1,1} \setminus \text{OPT} \\ O &= (S_{1,1} \cap \text{OPT}) \cup (O_1 \cap U) \cup O'_2 \end{aligned}$$

We show below that $\mathbb{E}[\mathbf{1}_O] \leq \varepsilon \mathbf{1}_{V \setminus \text{OPT}}$ and $\mathbb{E}[\mathbf{1}_O] \geq (1 - \varepsilon) \mathbf{1}_{\text{OPT}}$. Assuming these bounds, we can take $u = \varepsilon$ and $v = 1 - \varepsilon$ in Lemma 5, which gives the desired result.

Since $S \subseteq S_{1,1} \subseteq V_{1,1}$ and $V_{1,1}$ is a $(1/m)$ -sample of V , we have $\mathbb{E}[\mathbf{1}_S] \leq \frac{1}{m} \mathbf{1}_{V \setminus \text{OPT}} = \varepsilon \mathbf{1}_{V \setminus \text{OPT}}$. Thus it only remains to show that, for each $e \in \text{OPT}$, we have $\Pr[e \in O] \geq 1 - \varepsilon$. Since $(O_1 \cap U) \cup O'_2 \subseteq O$, it suffices to show that $\Pr[e \in (O_1 \cap U) \cup O'_2] \geq 1 - \varepsilon$, or equivalently that $\Pr[e \in (O_1 \setminus U) \cup (O_2 \setminus O'_2)] \leq \varepsilon$.

Recall that (O_1, O_2) is a deterministic partition of OPT . Thus e belongs to exactly one of O_1 and O_2 and we consider each of these cases in turn.

Suppose that $e \in O_1$. A single iteration of the for loop of `STREAMPROCESS` ensures that e is in $S_{i,1} \cup \dots \cup S_{i,m}$ with probability $p_e \geq \varepsilon$. Since we perform $r = \Theta(\ln(1/\varepsilon)/\varepsilon)$ independent iterations, we have $\Pr[e \notin U] \leq (1 - \varepsilon)^r \leq \exp(-\varepsilon r) \leq \varepsilon$.

Suppose that $e \in O_2$. We have

$$\Pr[e \in O_2 \setminus O'_2] = \Pr[e \in \text{STGREEDY}(V_{1,1} \cup \{e\})] = p_e \leq \varepsilon$$

where the first equality follows from the definition of O'_2 , the second equality follows from the definition of p_e and the fact that $V_{1,1} \sim \mathcal{V}(1/m)$, and the inequality follows from the definition of O_2 . \square

Lemmas 8 and 9 immediately imply the following:

Lemma 10. *We have $\mathbb{E}[f(S_{1,1} \cup (O_1 \cap U))] \geq (1 - 3\varepsilon)f(\text{OPT}) - \kappa b$.*

Proof. Recall that we use the notation $f(A|B) = f(A \cup B) - f(B)$. We have

$$\begin{aligned} f(S_{1,1} \cup (O_1 \cap U)) &= f(S_{1,1} \cup (O_1 \cap U) \cup O'_2) - f(O'_2|S_{1,1} \cup (O_1 \cap U)) \\ &\geq f(S_{1,1} \cup (O_1 \cap U) \cup O'_2) - f(O'_2|S_{1,1}) \end{aligned}$$

where the inequality is by submodularity.

By taking expectation and using Lemmas 8 and 9, we obtain the desired result. \square

Finally, Lemmas 7 and 10 give the approximation guarantee:

Lemma 11. *We have $\mathbb{E}[\max\{f(S_{1,1}), f(T)\}] \geq \left(\frac{\alpha}{1+\alpha} - 3\varepsilon\right) f(\text{OPT})$.*

Proof. By Lemmas 7 and 10, we have

$$\begin{aligned} \mathbb{E}[\max\{f(S_{1,1}), f(T)\}] &\geq \frac{\alpha}{1 + \alpha \left(1 - \frac{b}{k}\right)} \mathbb{E}[f(S_{1,1} \cup (O_1 \cap U))] \\ &\geq \frac{\alpha}{1 + \alpha \left(1 - \frac{b}{k}\right)} ((1 - 3\varepsilon)f(\text{OPT}) - \kappa b) \\ &= \frac{\alpha}{1 + \alpha \left(1 - \frac{b}{k}\right)} \left((1 - 3\varepsilon)f(\text{OPT}) - \frac{\alpha}{1 + \alpha} \frac{b}{k} f(\text{OPT}) \right) \\ &\geq \left(\frac{\alpha}{1 + \alpha} - 3\varepsilon \right) f(\text{OPT}) \end{aligned} \quad \square$$

4 Extension based algorithm

Using our extension based algorithm, we prove the following theorem.

Theorem 12. *Assume there exists an α -approximation offline algorithm OFFLINEALG for maximizing a non-negative submodular function subject to cardinality constraint whose space complexity is nearly linear in the size of the ground set. Then, for every constant $\varepsilon \in (0, 1]$, there exists an $(\frac{\alpha}{1+\alpha} - \varepsilon)$ -approximation semi-streaming algorithm for maximizing a non-negative submodular function subject to a cardinality constraint. The algorithm stores at most $O(k\varepsilon^{-2})$ elements.⁴*

In this section, we introduce a simplified version of the algorithm used to prove Theorem 12. This simplified version (given as Algorithm 3) captures our main new ideas, but makes two simplifying assumptions that can be avoided using standard techniques.

- The first assumption is that Algorithm 3 has access to an estimate τ of $f(\text{OPT})$ obeying $(1 - \varepsilon/8) \cdot f(\text{OPT}) \leq \tau \leq f(\text{OPT})$. Such an estimate can be produced using well-known techniques, at the cost of a slight increase in the space complexity of the algorithm. More specifically, in Appendix D we formally show that one such technique due to [28] can be used for that purpose, and that it increases the space complexity of the algorithm only by a factor of $O(\varepsilon^{-1} \log \alpha^{-1})$.
- The second assumption is that Algorithm 3 has value oracle access to the multilinear extension F . If the time complexity of Algorithm 3 is not important, then this assumption is of no consequence since a value oracle query to F can be emulated using an exponential number of value oracle queries to f . However, the assumption becomes problematic when we would like to keep the time complexity of the algorithm polynomial and we only have value oracle access to f . Thus, we explain in Appendix E how to drop this assumption. Interestingly, the rounding step and the technique used in Appendix E are the only parts of the extension based algorithm that employ randomness. Since the rounding can be made deterministic given either exponential time or value oracle access to F , we get the following observation.

Observation 13. *If OFFLINEALG is deterministic, then the algorithm whose existence is guaranteed by Theorem 12 is also deterministic when it is allowed either exponential computation time or value oracle access to F .*

Algorithm 3 has two constant parameters $p \in (0, 1)$ and $c > 0$ and maintains a fractional solution $x \in [0, 1]^V$. This fractional solution starts empty, and the algorithm adds to it fractions of elements as they arrive. Specifically, when an element e arrives, the algorithm considers its marginal contribution with respect to the current fractional solution x . If this marginal contribution exceeds the threshold of $c\tau/k$, then the algorithm tries to add to x a p -fraction of e , but might end up adding a smaller fraction of e if adding a full p -fraction of e to x will make x an infeasible solution, i.e., make $\|x\|_1 > k$ (note that $\|x\|_1$ is the sum of the coordinates of x).

After viewing all of the elements, Algorithm 3 uses the fractional solution x to generate two sets S_1 and S_2 that are feasible (integral) solutions. The set S_1 is generated by rounding the fractional solution x . Two rounding procedures, named Pipage Rounding and Swap Rounding, were suggested for this task in the literature [10, 15]. Both procedures run in polynomial time and guarantee that the output set S_1 of the rounding is always feasible, and that its expected value

⁴Formally, the number of elements stored by the algorithm also depends on $\log \alpha^{-1}$. Since α is typically a positive constant, or at least lower bounded by a positive constant, we omit this dependence from the statement of the theorem.

with respect to f is at least the value $F(x)$ of the fractional solution x . The set S_2 is generated by applying OFFLINEALG to the support of the vector x , which produces a feasible solution that (approximately) maximizes f among all subsets of the support whose size is at most k . After computing the two feasible solutions S_1 and S_2 , Algorithm 3 simply returns the better one of them.

Algorithm 3: STREAMPROCESSEXTENSION (simplified) (p, c)

- 1 Let $x \leftarrow \mathbf{1}_\emptyset$.
 - 2 **for** each arriving element e **do**
 - 3 **if** $\partial_e F(x) \geq \frac{c\tau}{k}$ **then** $x \leftarrow x + \min\{p, k - \|x\|_1\} \cdot \mathbf{1}_e$.
 - 4 Round the vector x to yield a feasible solution S_1 such that $\mathbb{E}[f(S_1)] \geq F(x)$.
 - 5 Find another feasible solution $S_2 \subseteq \text{supp}(x)$ by running OFFLINEALG with $\text{supp}(x)$ as the ground set.
 - 6 **return** the better solution among S_1 and S_2 .
-

Let us denote by \hat{x} the final value of the fractional solution x (i.e., its value when the stream ends). We begin the analysis of Algorithm 3 with the following useful observation.

Observation 14. *If $\|\hat{x}\|_1 < k$, then $\hat{x}_e = p$ for every $e \in \text{supp}(\hat{x})$. Otherwise, this is still true for every element $e \in \text{supp}(\hat{x})$ except for maybe a single element.*

Proof. For every element e added to the support of x by Algorithm 3, the algorithm sets x_e to p unless this will make $\|x\|_1$ exceed k , in which case the algorithm set x_e to be the value that will make $\|x\|_1$ equal to k . Thus, after a single coordinate of x is set to a value other than p (or the initial 0), $\|x\|_1$ becomes k and Algorithm 3 stops changing x . \square

Using the last observation we can now bound the space complexity of Algorithm 3, and show (in particular) that it is a semi-streaming algorithm for a constant p when the space complexity of OFFLINEALG is nearly linear.

Observation 15. *Algorithm 3 can be implemented so that it stores at most $O(k/p)$ elements.*

Proof. To calculate the sets S_1 and S_2 , Algorithm 3 needs access only to the elements of V that appear in the support of x . Thus, the number of elements it needs to store is $O(|\text{supp}(\hat{x})|) = O(k/p)$, where the equality follows from Observation 14. \square

We now divert our attention to analyzing the approximation ratio of Algorithm 3. The first step in this analysis is lower bounding the value of $F(\hat{x})$, which we do by considering two cases, one when $\|\hat{x}\|_1 = k$, and the other when $\|\hat{x}\|_1 < k$. The following lemma bounds the value of $F(\hat{x})$ in the first of these cases. Intuitively, this lemma holds since $\text{supp}(\hat{x})$ contains many elements, and each one of these elements must have increased the value of $F(x)$ significantly when added (otherwise, Algorithm 3 would not have added this element to the support of x).

Lemma 16. *If $\|\hat{x}\|_1 = k$, then $F(\hat{x}) \geq c\tau$.*

Proof. Denote by e_1, e_2, \dots, e_ℓ the elements in the support of \hat{x} , in the order of their arrival. Using

this notation, the value of $F(\hat{x})$ can be written as follows.

$$\begin{aligned}
F(\hat{x}) &= F(\mathbf{1}_\emptyset) + \sum_{i=1}^{\ell} \left(F(\hat{x} \wedge \mathbf{1}_{\{e_1, e_2, \dots, e_i\}}) - F(\hat{x} \wedge \mathbf{1}_{\{e_1, e_2, \dots, e_{i-1}\}}) \right) \\
&= F(\mathbf{1}_\emptyset) + \sum_{i=1}^{\ell} \left(\hat{x}_{e_i} \cdot \partial_{e_i} F(\hat{x} \wedge \mathbf{1}_{\{e_1, e_2, \dots, e_{i-1}\}}) \right) \\
&\geq F(\mathbf{1}_\emptyset) + \frac{c\tau}{k} \cdot \sum_{i=1}^{\ell} \hat{x}_{e_i} = F(\mathbf{1}_\emptyset) + \frac{c\tau}{k} \cdot \|\hat{x}\|_1 \geq c\tau,
\end{aligned}$$

where the second equality follows from the multilinearity of F , and the first inequality holds since Algorithm 3 selects an element e_i only when $\partial_{e_i} F(\hat{x} \wedge \mathbf{1}_{\{e_1, e_2, \dots, e_{i-1}\}}) \geq \frac{c\tau}{k}$. The last inequality holds since f (and thus, also F) is non-negative and $\|\hat{x}\|_1 = k$ by the assumption of the lemma. \square

Consider now the case in which $\|\hat{x}\|_1 < k$. Recall that our objective is to lower bound $F(\hat{x})$ in this case as well. Towards this goal, we bound the expression $F(\hat{x} + \mathbf{1}_{\text{OPT} \setminus \text{supp}(\hat{x})})$ from below and above in the following two lemmata.

Lemma 17. *If $\|\hat{x}\|_1 < k$, then $F(\hat{x} + \mathbf{1}_{\text{OPT} \setminus \text{supp}(\hat{x})}) \geq (1-p) \cdot [p \cdot f(\text{OPT}) + (1-p) \cdot f(\text{OPT} \setminus \text{supp}(\hat{x}))]$.*

Proof. Since $\|\hat{x}\|_1 < k$, Observation 14 guarantees that $\hat{x}_e = p$ for every $e \in \text{supp}(\hat{x})$. Thus $\hat{x} = p \cdot \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})} + p \cdot \mathbf{1}_{\text{supp}(\hat{x}) \setminus \text{OPT}}$, and therefore,

$$\begin{aligned}
F(\hat{x} + \mathbf{1}_{\text{OPT} \setminus \text{supp}(\hat{x})}) &= F(p \cdot \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})} + p \cdot \mathbf{1}_{\text{supp}(\hat{x}) \setminus \text{OPT}} + \mathbf{1}_{\text{OPT} \setminus \text{supp}(\hat{x})}) \\
&\geq (1-p) \cdot F(p \cdot \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})} + \mathbf{1}_{\text{OPT} \setminus \text{supp}(\hat{x})}) \\
&\geq (1-p) \cdot \hat{f}(p \cdot \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})} + \mathbf{1}_{\text{OPT} \setminus \text{supp}(\hat{x})}) \\
&= (1-p) \cdot [p \cdot f(\text{OPT}) + (1-p) \cdot f(\text{OPT} \setminus \text{supp}(\hat{x}))],
\end{aligned}$$

where the first inequality follows from Corollary 2, the second inequality holds since the Lovász extension lower bounds the multilinear extension, and the last equality follows from the definition of the Lovász extension. \square

In the following lemma, and the rest of the section, we use the notation $b = k^{-1} \cdot |\text{OPT} \setminus \text{supp}(\hat{x})|$. Intuitively, the lemma holds since the fact that the elements of $\text{OPT} \setminus \text{supp}(\hat{x})$ were not added to the support of x by Algorithm 3 implies that their marginal contribution is small.

Lemma 18. *If $\|\hat{x}\|_1 < k$, then $F(\hat{x} + \mathbf{1}_{\text{OPT} \setminus \text{supp}(\hat{x})}) \leq F(\hat{x}) + bc\tau$.*

Proof. The elements in $\text{OPT} \setminus \text{supp}(\hat{x})$ were rejected by Algorithm 3, which means that their marginal contribution with respect to the fractional solution x at the time of their arrival was smaller than $c\tau/k$. Since the fractional solution x only increases during the execution of the algorithm, the submodularity of f guarantees that this is true also with respect to \hat{x} . More formally, we get

$$\partial_e F(\hat{x}) < \frac{c\tau}{k} \quad \forall e \in \text{OPT} \setminus \text{supp}(\hat{x}).$$

Using the submodularity of f again, this implies

$$F(\hat{x} + \mathbf{1}_{\text{OPT} \setminus \text{supp}(\hat{x})}) \leq F(\hat{x}) + \sum_{e \in \text{OPT} \setminus \text{supp}(\hat{x})} \partial_e F(\hat{x}) \leq F(\hat{x}) + |\text{OPT} \setminus \text{supp}(\hat{x})| \cdot \frac{c\tau}{k} = F(\hat{x}) + bc\tau. \quad \square$$

Combining the last two lemmata immediately yields the promised lower bound on $F(\hat{x})$. To understand the second inequality in the following corollary, recall that $\tau \leq f(\text{OPT})$.

Corollary 19. *If $\|\hat{x}\|_1 < k$, then $F(\hat{x}) \geq (1-p) \cdot \left[p \cdot f(\text{OPT}) + (1-p) \cdot f(\text{OPT} \setminus \text{supp}(\hat{x})) \right] - bc\tau \geq [p(1-p) - bc]\tau + (1-p)^2 \cdot f(\text{OPT} \setminus \text{supp}(\hat{x}))$.*

Proof. The elements in $\text{OPT} \setminus \text{supp}(\hat{x})$ were rejected by Algorithm 3, which means that their marginal contribution with respect to the fractional solution x at the time of their arrival was smaller than $c\tau/k$. Since the fractional solution x only increases during the execution of the algorithm, the submodularity of f guarantees that this is true also with respect to \hat{x} . More formally, we get

$$\partial_e F(\hat{x}) < \frac{c\tau}{k} \quad \forall e \in \text{OPT} \setminus \text{supp}(\hat{x}) .$$

Using the submodularity of f again, this implies

$$F(\hat{x} + \mathbf{1}_{\text{OPT} \setminus \text{supp}(\hat{x})}) \leq F(\hat{x}) + \sum_{e \in \text{OPT} \setminus \text{supp}(\hat{x})} \partial_e F(\hat{x}) \leq F(\hat{x}) + |\text{OPT} \setminus \text{supp}(\hat{x})| \cdot \frac{c\tau}{k} = F(\hat{x}) + bc\tau . \quad \square$$

Our next step is to get a lower bound on the expected value of $f(S_2)$. One easy way to get such a lower bound is to observe that $\text{OPT} \cap \text{supp}(\hat{x})$ is a subset of the support of \hat{x} of size at most k , and thus, is a candidate to be OPT ; which implies $\mathbb{E}[f(S_2)] \geq \alpha \cdot f(\text{OPT} \cap \text{supp}(\hat{x}))$ since the algorithm `OFFLINEALG` used to find S_2 is an α -approximation algorithm. The following lemma proves a more involved lower bound by considering the vector $(b\hat{x}) \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})}$ as a fractional candidate to be OPT (using the rounding methods discussed above it, it can be converted into an integral candidate of at least the same value). The proof of the lemma lower bounds the value of the vector $(b\hat{x}) \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})}$ using the concavity of the function $F((t \cdot \hat{x}) \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})})$ as well as ideas used in the proofs of the previous claims.

Lemma 20. *If $\|\hat{x}\|_1 < k$, then $\mathbb{E}[f(S_2)] \geq \alpha b(1-p-cb)\tau + \alpha(1-b) \cdot f(\text{OPT} \cap \text{supp}(\hat{x}))$.*

Proof. Consider the vector $(b\hat{x}) \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})}$. Clearly,

$$\begin{aligned} \left\| (b\hat{x}) \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})} \right\|_1 &\leq b \cdot \|\hat{x}\|_1 + \left\| \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})} \right\|_1 \\ &\leq |\text{OPT} \setminus \text{supp}(\hat{x})| + |\text{OPT} \cap \text{supp}(\hat{x})| = |\text{OPT}| \leq k , \end{aligned}$$

where the second inequality holds by the definition of b since $\|\hat{x}\|_1 < k$. Thus, due to the existence of the rounding methods discussed in Section 4, there must exist a set S of size at most k obeying $f(S) \geq F((b\hat{x}) \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})})$. Since S_2 is produced by `OFFLINEALG`, whose approximation ratio is α , this implies $\mathbb{E}[f(S_2)] \geq \alpha \cdot F((b\hat{x}) \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})})$. Thus, to prove the lemma it suffices to show that $F((b\hat{x}) \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})})$ is always at least $b(1-p-cb)\tau + (1-b) \cdot f(\text{OPT} \cap \text{supp}(\hat{x}))$.

The first step towards proving the last inequality is getting a lower bound on $F(\hat{x} \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})})$. Recall that we already showed in the proof of Lemma 18 that

$$\partial_e F(\hat{x}) < \frac{c\tau}{k} \quad \forall e \in \text{OPT} \setminus \text{supp}(\hat{x}) .$$

Thus, the submodularity of f implies

$$\begin{aligned} F(\hat{x} \vee \mathbf{1}_{\text{OPT}}) &\leq F(\hat{x} \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})}) + \sum_{e \in \text{OPT} \setminus \text{supp}(\hat{x})} \partial_e F(\hat{x}) \\ &\leq F(\hat{x} \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})}) + \frac{c\tau \cdot |\text{OPT} \setminus \text{supp}(\hat{x})|}{k} = F(\hat{x} \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})}) + cb\tau . \end{aligned}$$

Rearranging this inequality yields

$$F(\hat{x} \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})}) \geq F(\hat{x} \vee \mathbf{1}_{\text{OPT}}) - cb\tau \geq (1-p) \cdot f(\text{OPT}) - cb\tau \geq (1-p-cb)\tau ,$$

where the second inequality holds by Corollary 2 since Observation 14 guarantees that every coordinate of \hat{x} is either 0 or p . This gives us the promised lower bound on $F(\hat{x} \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})})$.

We now note that the submodularity of f implies that $F((t \cdot \hat{x}) \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})})$ is a concave function of t within the range $[0, 1]$. Since b is inside this range,

$$\begin{aligned} F((b\hat{x}) \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})}) &\geq b \cdot F(\hat{x} \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})}) + (1-b) \cdot f(\text{OPT} \cap \text{supp}(\hat{x})) \\ &\geq b(1-p-cb)\tau + (1-b) \cdot f(\text{OPT} \cap \text{supp}(\hat{x})) , \end{aligned}$$

which completes the proof of the lemma. \square

Using the last two claims we can now obtain a lower bound on the value of the solution of Algorithm 3 in the case of $\|\hat{x}\|_1 < k$ which is a function of α , τ and p alone. We note that both the guarantees of Corollary 19 and Lemma 20 are lower bounds on the expected value of the output of the algorithm in this case since $\mathbb{E}[f(S_1)] \geq F(\hat{x})$. Thus, any convex combination of these guarantees is also such a lower bound, and the proof of the following corollary basically proves a lower bound for one such convex combination—for the specific value of c stated in the corollary.

Corollary 21. *If $\|\hat{x}\|_1 < k$ and c is set to $\frac{\alpha(1-p)}{\alpha+1}$, then $\mathbb{E}[\max\{f(S_1), f(S_2)\}] \geq \frac{(1-p)\alpha\tau}{\alpha+1}$.*

Proof. The corollary follows immediately from the non-negativity of f when $p = 1$. Thus, we may assume $p < 1$ in the rest of the proof.

By the definition of S_1 , $\mathbb{E}[f(S_1)] \geq F(\hat{x})$. Thus, by Corollary 19 and Lemma 20,

$$\begin{aligned} \mathbb{E}[\max\{f(S_1), f(S_2)\}] &\geq \max\{\mathbb{E}[f(S_1)], \mathbb{E}[f(S_2)]\} \\ &\geq \max\{[p(1-p) - bc]\tau + (1-p)^2 \cdot f(\text{OPT} \setminus \text{supp}(\hat{x})), \\ &\quad \alpha b(1-p-cb)\tau + \alpha(1-b) \cdot f(\text{OPT} \cap \text{supp}(\hat{x}))\} \\ &\geq \frac{\alpha(1-b)}{\alpha(1-b) + (1-p)^2} \cdot [p(1-p) - bc]\tau + (1-p)^2 \cdot f(\text{OPT} \setminus \text{supp}(\hat{x})) \\ &\quad + \frac{(1-p)^2}{\alpha(1-b) + (1-p)^2} \cdot [\alpha b(1-p-cb)\tau + \alpha(1-b) \cdot f(\text{OPT} \cap \text{supp}(\hat{x}))] . \end{aligned}$$

To keep the following calculations short, it will be useful to define $q = 1 - p$ and $d = 1 - b$. Using this notation and the fact that the submodularity and non-negativity of f guarantee together $f(\text{OPT} \setminus \text{supp}(\hat{x})) + f(\text{OPT} \cap \text{supp}(\hat{x})) \geq f(\text{OPT}) \geq \tau$, the previous inequality implies

$$\begin{aligned} \frac{\mathbb{E}[\max\{f(S_1), f(S_2)\}]}{\alpha\tau} &\geq \frac{(1-b)[p(1-p) - bc] + b(1-p)^2(1-p-cb) + (1-b)(1-p)^2}{\alpha(1-b) + (1-p)^2} \\ &= \frac{d[q(1-q) - (1-d)c] + q^2(1-d)[q - (1-d)c] + dq^2}{\alpha d + q^2} \\ &= \frac{d[q - (1-d)c] + q^2(1-d)[q - (1-d)c]}{\alpha d + q^2} = \frac{[d + q^2(1-d)][q - (1-d)c]}{\alpha d + q^2} \\ &= \frac{q[d + q^2(1-d)](d\alpha + 1)}{(\alpha + 1)(d\alpha + q^2)} = \frac{d^2\alpha + d\alpha q^2 - d^2\alpha q^2 + d + q^2 - dq^2}{d\alpha + q^2} \cdot \frac{q}{\alpha + 1} , \end{aligned} \tag{1}$$

where the fourth equality holds by plugging in the value we assume for c .

The second fraction in the last expression is independent of the value of d , and the derivative of the first fraction in this expression as a function of d is

$$\begin{aligned} & \frac{(2d\alpha + \alpha q^2 - 2d\alpha q^2 + 1 - q^2)[d\alpha + q^2] - \alpha(d^2\alpha + d\alpha q^2 - d^2\alpha q^2 + d + q^2 - dq^2)}{[d\alpha + q^2]^2} \\ &= \frac{1 - q^2}{[d\alpha + q^2]^2} \cdot [q^2(1 - \alpha) + d\alpha(d\alpha + 2q^2)] , \end{aligned}$$

which is always non-negative since both q and α are numbers between 0 and 1. Thus, we get that the minimal value of the expression (1) is obtained for $d = 0$ for any choice of q and α . Plugging this value into d yields

$$\mathbb{E}[\max\{f(S_1), f(S_2)\}] \geq \frac{q\alpha\tau}{\alpha + 1} = \frac{(1 - p)\alpha\tau}{\alpha + 1} . \quad \square$$

Note that Lemma 16 and Corollary 21 both prove the same lower bound on the expectation $\mathbb{E}[\max\{f(S_1), f(S_2)\}]$ when c is set to the value it is set to in Corollary 21 (because $\mathbb{E}[\max\{f(S_1), f(S_2)\}] \geq \mathbb{E}[f(S_1)] \geq F(\hat{x})$). Thus, we can summarize the results we have proved so far using the following proposition.

Proposition 22. *Algorithm 3 is a semi-streaming algorithm storing $O(k/p)$ elements. Moreover, for the value of the parameter c given in Corollary 21, the output set produced by this algorithm has an expected value of at least $\frac{\alpha\tau(1-p)}{\alpha+1}$.*

Using the last proposition, we can now prove the following theorem. As discussed at the beginning of the section, in Appendix D we explain how the assumption that τ is known can be dropped at the cost of increasing of a slight increase in the number of elements stored by the algorithm, which yields Theorem 12.

Theorem 23. *For every constant $\varepsilon \in (0, 1]$, there exists a semi-streaming algorithm that assumes access to an estimate τ of $f(\text{OPT})$ obeying $(1 - \varepsilon/8) \cdot f(\text{OPT}) \leq \tau \leq f(\text{OPT})$ and provides $(\frac{\alpha}{1+\alpha} - \varepsilon)$ -approximation for the problem of maximizing a non-negative submodular function subject to cardinality constraint. This algorithm stores at most $O(k\varepsilon^{-1})$ elements.*

Proof. Consider the algorithm obtained from Algorithm 3 by setting $p = \varepsilon/2$ and c as is set in Corollary 21. By Proposition 22, this algorithm stores only $O(k/p) = O(k\varepsilon^{-1})$ elements, and the expected value of its output set is at least

$$\frac{\alpha\tau(1-p)}{\alpha+1} \geq \frac{\alpha(1-\varepsilon/8)(1-\varepsilon/2)}{\alpha+1} \cdot f(\text{OPT}) \geq \frac{\alpha(1-\varepsilon)}{\alpha+1} \cdot f(\text{OPT}) \geq \left(\frac{\alpha}{\alpha+1} - \varepsilon\right) \cdot f(\text{OPT}) ,$$

where the first inequality holds since τ obeys, by assumption, $\tau \geq (1 - \varepsilon/8) \cdot f(\text{OPT})$. \square

Before concluding this section, we would like to further discuss the value that should be assigned to the parameter p of Algorithm 3. In the proof of Theorem 23, we chose p to be very small. This makes sense whenever α is independent of p since the formula given by Proposition 22 for the guaranteed value of the output is non-increasing in p . However, for some choices of OFFLINEALG the value of α might depend on p , and thus, it might be beneficial to choose a value for p which is not very small. To see why α might depend on p , note that the input passed to OFFLINEALG by Algorithm 3 is of size at most $\lceil k/p \rceil$ due to Observation 14; and therefore, the ratio between the size of the ground set and k in this input is roughly $1/p$. Hence, α depends on p if the approximation ratio of OFFLINEALG depends on the above ratio; which is the case, e.g., for one of the algorithms described in [8].

References

- [1] Yossi Azar, Iftah Gamzu, and Ran Roth. Submodular max-sat. In *ESA*, pages 323–334, 2011. URL: https://doi.org/10.1007/978-3-642-23719-5_28, doi:10.1007/978-3-642-23719-5_28.
- [2] Ashwinkumar Badanidiyuru, Baharan Mirzasoleiman, Amin Karbasi, and Andreas Krause. Streaming submodular maximization: Massive data summarization on the fly. In *Proceedings of the 20th ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 671–680. ACM, 2014.
- [3] Rafael da Ponte Barbosa, Alina Ene, Huy L Nguyen, and Justin Ward. A new framework for distributed submodular maximization. In *IEEE Foundations of Computer Science (FOCS)*, pages 645–654, 2016.
- [4] Rafael D.P. Barbosa, Alina Ene, Huy L. Nguyen, and Justin Ward. The power of randomization: Distributed submodular maximization on massive datasets. In *International Conference on Machine Learning (ICML)*, 2015.
- [5] Niv Buchbinder and Moran Feldman. Constrained submodular maximization via a non-symmetric technique. *Mathematics of Operations Research*, 44(3):988–1005, 2019.
- [6] Niv Buchbinder, Moran Feldman, Yuval Filmus, and Mohit Garg. Online submodular maximization: Beating $1/2$ made simple. In *Integer Programming and Combinatorial Optimization - 20th International Conference, IPCO 2019, Ann Arbor, MI, USA, May 22-24, 2019, Proceedings*, pages 101–114, 2019. URL: https://doi.org/10.1007/978-3-030-17953-3_8, doi:10.1007/978-3-030-17953-3_8.
- [7] Niv Buchbinder, Moran Feldman, and Mohit Garg. Deterministic $(1/2 + \epsilon)$ -approximation for submodular maximization over a matroid. In *SODA*, pages 241–254, 2019. URL: <https://doi.org/10.1137/1.9781611975482.16>, doi:10.1137/1.9781611975482.16.
- [8] Niv Buchbinder, Moran Feldman, Joseph Naor, and Roy Schwartz. Submodular maximization with cardinality constraints. In *SODA*, pages 1433–1452, 2014. URL: <https://doi.org/10.1137/1.9781611973402.106>, doi:10.1137/1.9781611973402.106.
- [9] Niv Buchbinder, Moran Feldman, and Roy Schwartz. Online submodular maximization with preemption. *ACM Trans. Algorithms*, 15(3):30:1–30:31, 2019. URL: <https://doi.org/10.1145/3309764>, doi:10.1145/3309764.
- [10] Gruia Călinescu, Chandra Chekuri, Martin Pál, and Jan Vondrák. Maximizing a monotone submodular function subject to a matroid constraint. *SIAM J. Comput.*, 40(6):1740–1766, 2011. URL: <https://doi.org/10.1137/080733991>, doi:10.1137/080733991.
- [11] Amit Chakrabarti and Sagar Kale. Submodular maximization meets streaming: Matchings, matroids, and more. *Mathematical Programming*, 154(1-2):225–247, 2015.
- [12] T.-H. Hubert Chan, Zhiyi Huang, Shaofeng H.-C. Jiang, Ning Kang, and Zhihao Gavin Tang. Online submodular maximization with free disposal. *ACM Trans. Algorithms*, 14(4):56:1–56:29, 2018. URL: <https://doi.org/10.1145/3242770>, doi:10.1145/3242770.
- [13] Chandra Chekuri. Personal communication, 2018.

- [14] Chandra Chekuri, Shalmoli Gupta, and Kent Quanrud. Streaming algorithms for submodular function maximization. In *International Colloquium on Automata, Languages and Programming (ICALP)*, pages 318–330. Springer, 2015.
- [15] Chandra Chekuri, Jan Vondrák, and Rico Zenklusen. Dependent randomized rounding via exchange properties of combinatorial structures. In *FOCS*, pages 575–584, 2010. URL: <https://doi.org/10.1109/FOCS.2010.60>, doi:10.1109/FOCS.2010.60.
- [16] Chandra Chekuri, Jan Vondrák, and Rico Zenklusen. Submodular function maximization via the multilinear relaxation and contention resolution schemes. *SIAM J. Comput.*, 43(6):1831–1879, 2014. URL: <https://doi.org/10.1137/110839655>, doi:10.1137/110839655.
- [17] Alina Ene and Huy L Nguyen. Constrained submodular maximization: Beyond 1/e. In *IEEE Foundations of Computer Science (FOCS)*, pages 248–257. IEEE, 2016.
- [18] Alessandro Epasto, Vahab Mirrokni, and Morteza Zadimoghaddam. Bicriteria distributed submodular maximization in a few rounds. In *PACM Symposium on Parallelism in Algorithms and Architectures (SPAA)*, pages 25–33, 2017.
- [19] Uriel Feige, Vahab S Mirrokni, and Jan Vondrák. Maximizing non-monotone submodular functions. *SIAM Journal on Computing*, 40(4):1133–1153, 2011.
- [20] Moran Feldman. Maximizing symmetric submodular functions. *ACM Trans. Algorithms*, 13(3):39:1–39:36, 2017. URL: <https://doi.org/10.1145/3070685>, doi:10.1145/3070685.
- [21] Moran Feldman, Christopher Harshaw, and Amin Karbasi. Greed is good: Near-optimal submodular maximization via greedy optimization. In *Proceedings of the 30th Conference on Learning Theory, COLT 2017, Amsterdam, The Netherlands, 7-10 July 2017*, pages 758–784, 2017. URL: <http://proceedings.mlr.press/v65/feldman17b.html>.
- [22] Moran Feldman, Amin Karbasi, and Ehsan Kazemi. Do less, get more: Streaming submodular maximization with subsampling. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 732–742, 2018.
- [23] Moran Feldman, Joseph (Seffi) Naor, and Roy Schwartz. A unified continuous greedy algorithm for submodular maximization. In *Proceedings of the 52nd IEEE Foundations of Computer Science (FOCS)*, pages 570–579. IEEE Computer Society, 2011.
- [24] Moran Feldman, Ashkan Norouzi-Fard, Ola Svensson, and Rico Zenklusen. The one-way communication complexity of submodular maximization with applications to streaming and robustness, 2020. To appear in STOC 2020.
- [25] M L Fisher, G L Nemhauser, and L A Wolsey. An analysis of approximations for maximizing submodular set functions—II. *Mathematical Programming Studies*, 8:73–87, 1978.
- [26] Shayan Oveis Gharan and Jan Vondrák. Submodular maximization by simulated annealing. In *ACM-SIAM Symposium on Discrete Algorithms (SODA)*, 2011.
- [27] Michael Kapralov, Ian Post, and Jan Vondrák. Online submodular welfare maximization: Greedy is optimal. In *SODA*, pages 1216–1225, 2013. URL: <https://doi.org/10.1137/1.9781611973105.88>, doi:10.1137/1.9781611973105.88.

- [28] Ehsan Kazemi, Marko Mitrovic, Morteza Zadimoghaddam, Silvio Lattanzi, and Amin Karbasi. Submodular streaming in all its glory: Tight approximation, minimum memory and low adaptive complexity. In *ICML*, pages 3311–3320, 2019. URL: <http://proceedings.mlr.press/v97/kazemi19a.html>.
- [29] Nitish Korula, Vahab S. Mirrokni, and Morteza Zadimoghaddam. Online submodular welfare maximization: Greedy beats 1/2 in random order. *SIAM J. Comput.*, 47(3):1056–1086, 2018. URL: <https://doi.org/10.1137/15M1051142>, doi:10.1137/15M1051142.
- [30] Ravi Kumar, Benjamin Moseley, Sergei Vassilvitskii, and Andrea Vattani. Fast greedy algorithms in mapreduce and streaming. In *PACM Symposium on Parallelism in Algorithms and Architectures (SPAA)*, pages 1–10, 2013.
- [31] Jon Lee, Vahab S Mirrokni, Viswanath Nagarajan, and Maxim Sviridenko. Non-monotone submodular maximization under matroid and knapsack constraints. In *ACM Symposium on Theory of Computing (STOC)*, pages 323–332, 2009.
- [32] Jon Lee, Maxim Sviridenko, and Jan Vondrák. Submodular maximization over multiple matroids via generalized exchange properties. *Mathematics of Operations Research*, 35(4):795–806, 2010.
- [33] László Lovász. Submodular functions and convexity. In *Mathematical Programming The State of the Art, XIth International Symposium on Mathematical Programming, Bonn, Germany, August 23-27, 1982*, pages 235–257, 1982. URL: https://doi.org/10.1007/978-3-642-68874-4_10, doi:10.1007/978-3-642-68874-4_10.
- [34] Vahab Mirrokni and Morteza Zadimoghaddam. Randomized composable core-sets for distributed submodular maximization. In *ACM Symposium on Theory of Computing (STOC)*, 2015.
- [35] Baharan Mirzasoleiman, Stefanie Jegelka, and Andreas Krause. Streaming non-monotone submodular maximization: Personalized video summarization on the fly. In *Thirty-second AAAI conference on artificial intelligence*, 2018.
- [36] Baharan Mirzasoleiman, Amin Karbasi, Ashwinkumar Badanidiyuru, and Andreas Krause. Distributed submodular cover: Succinctly summarizing massive data. In *Advances in Neural Information Processing Systems*, pages 2881–2889, 2015.
- [37] Baharan Mirzasoleiman, Amin Karbasi, Rik Sarkar, and Andreas Krause. Distributed submodular maximization: Identifying representative elements in massive data. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 2049–2057, 2013.
- [38] G. L. Nemhauser, L. A. Wolsey, and M. L. Fisher. An analysis of approximations for maximizing submodular set functions—I. *Mathematical Programming*, 14(1):265–294, 1978.
- [39] George L. Nemhauser and Laurence A. Wolsey. Best algorithms for approximating the maximum of a submodular set function. *Math. Oper. Res.*, 3(3):177–188, 1978. URL: <https://doi.org/10.1287/moor.3.3.177>, doi:10.1287/moor.3.3.177.
- [40] George L. Nemhauser, Laurence A. Wolsey, and Marshall L. Fisher. An analysis of approximations for maximizing submodular set functions—I. *Math. Program.*, 14(1):265–294, 1978. URL: <https://doi.org/10.1007/BF01588971>, doi:10.1007/BF01588971.

- [41] Ashkan Norouzi-Fard, Jakub Tarnawski, Slobodan Mitrovic, Amir Zandieh, Aidasadat Mousavifar, and Ola Svensson. Beyond $1/2$ -approximation for submodular maximization on massive data streams. In *International Conference on Machine Learning*, pages 3826–3835, 2018.
- [42] Jan Vondrák. Symmetry and approximability of submodular maximization problems. *SIAM J. Comput.*, 42(1):265–304, 2013. URL: <https://doi.org/10.1137/110832318>, doi:10.1137/110832318.

A Details about the Error in a Previous Work

As mentioned above, Chekuri et al. [14] described a semi-streaming algorithm for the problem of maximizing a non-negative (not necessarily monotone) submodular function subject to a cardinality constraint, and claimed an approximation ratio of roughly 0.212 for this algorithm. However, an error was later found in the proof of this result [13] (the error does not affect the other results of [14]). For completeness, we briefly describe in this appendix the error found.

In the proof presented by Chekuri et al. [14], the output set of their algorithm is denoted by \tilde{S} . As is standard in the analysis of algorithms based on Sieve-Streaming, the analysis distinguishes between two cases: one case in which $\tilde{S} = k$, and a second case in which $\tilde{S} < k$. To argue about the second case, the analysis then implicitly uses the inequality

$$\mathbb{E}[f(\tilde{S} \cup \text{OPT}) \mid |S| < k] \geq (1 - \max_{u \in V} \Pr[u \in \tilde{S}]) \cdot f(\text{OPT}) . \quad (2)$$

It is claimed by [14] that this inequality follows from a lemma due to [8]. However, the lemma of [8] can yield only the inequalities

$$\mathbb{E}[f(\tilde{S} \cup \text{OPT})] \geq (1 - \max_{u \in V} \Pr[u \in \tilde{S}]) \cdot f(\text{OPT})$$

and

$$\mathbb{E}[f(\tilde{S} \cup \text{OPT}) \mid |S| < k] \geq (1 - \max_{u \in V} \Pr[u \in \tilde{S} \mid |S| < k]) \cdot f(\text{OPT}) ,$$

which are similar to (2), but do not imply it.

B Inapproximability

In this appendix, we prove an inapproximability result for the problem of maximizing a non-negative submodular function subject to cardinality constraint in the data stream model. This result is given by the next theorem. The proof of the theorem is an adaptation of a proof given by Buchbinder et al. [9] for a similar result applying to an online variant of the same problem.

Theorem 24. *For every constant $\varepsilon > 0$, no data stream algorithm for maximizing a non-negative submodular function subject to cardinality constraint is $(1/2 + \varepsilon)$ -competitive, unless it uses $\Omega(|V|)$ memory.*

Proof. Let $k \geq 1$ and $h \geq 1$ be two integers to be chosen later, and consider the non-negative submodular function $f: 2^V \rightarrow \mathbb{R}^+$, where $V = \{u_i\}_{i=1}^{k-1} \cup \{v_i\}_{i=1}^h \cup \{w\}$, defined as follows.

$$f(S) = \begin{cases} |S| & \text{if } w \notin S , \\ k + |S \cap \{u_i\}_{i=1}^{k-1}| & \text{if } w \in S . \end{cases}$$

It is clear that f is non-negative. One can also verify that the marginal value of each element in V is non-increasing, and hence, f is submodular.

Let ALG be an arbitrary data stream algorithm for the problem of maximizing a non-negative submodular function subject to a cardinality constraint, and let us consider what happens when we give this algorithm the above function f as input, the last element of V to arrive is the element w and we ask the algorithm to pick a set of size at most k . One can observe that, before the arrival of w , ALG has no way to distinguish between the other elements of V . Thus, if we denote by M the set of elements stored by ALG immediately before the arrival of w and assume that the elements

of $V \setminus \{w\}$ arrive at a random order, then every element of $V \setminus \{w\}$ belongs to M with the same probability of $\mathbb{E}[|M|]/|V \setminus \{w\}|$. Hence, there must exist some arrival order for the elements of $V \setminus \{w\}$ guaranteeing that

$$\mathbb{E}\left[|M \cap \{u_i\}_{i=1}^{k-1}|\right] = \sum_{i=1}^{k-1} \Pr[u_i \in M] \leq \frac{k \cdot \mathbb{E}[|M|]}{|V \setminus \{w\}|}.$$

Note now that the above implies that the expected value of the output set produced by ALG given the above arrival order is at most

$$k + \frac{k \cdot \mathbb{E}[|M|]}{|V \setminus \{w\}|}.$$

In contrast, the optimal solution is the set $\{u_i\}_{i=1}^{k-1} \cup \{w\}$, whose value is $2k - 1$. Therefore, the competitive ratio of ALG is at most

$$\frac{k + k \cdot \mathbb{E}[|M|]/|V \setminus \{w\}|}{2k - 1} = \frac{1 + \mathbb{E}[|M|]/|V \setminus \{w\}|}{2 - 1/k} \leq \frac{1}{2} + \frac{1}{k} + \frac{\mathbb{E}[|M|]}{|V \setminus \{w\}|}.$$

To prove the theorem we need to show that, when the memory used by ALG is $o(|V|)$, we can choose large enough values for k and h that will guarantee that the rightmost side of the last inequality is at most $1/2 + \varepsilon$. We do so by showing that the two terms $1/k$ and $\mathbb{E}[|M|]/|V \setminus \{w\}|$ can both be upper bounded by $\varepsilon/2$ when the integers k and h are large enough, respectively. For the term $1/k$ this is clearly the case when k is larger than $2/\varepsilon$. For the term $\mathbb{E}[|M|]/|V \setminus \{w\}|$ this is true because increasing h can make V as large as want, and thus, can make the ratio $\mathbb{E}[|M|]/|V \setminus \{w\}|$ as small as necessary due to our assumption that the memory used by ALG (which includes M) is $o(|V|)$. \square

C Omitted proofs

C.1 Omitted Proof of Section 2

Corollary 2. *Let $f: 2^V \rightarrow \mathbb{R}_{\geq 0}$ be a non-negative submodular function, let p be a number in the range $[0, 1]$ and let x, y be two vectors in $[0, 1]^V$ such that*

- $\text{supp}(x) \cap \text{supp}(y) = \emptyset$,
- and $y_e \leq p$ for every $e \in V$.

Then, the multilinear extension F of f obeys $F(x + y) \geq (1 - p) \cdot F(x)$.

Proof. Let us define the function $G_x(S) = \mathbb{E}[f(\mathbf{R}(x) \cup S)]$. It is not difficult to verify that G_x is non-negative and submodular, and that $G_x(\emptyset) = F(x)$. Additionally, since $\text{supp}(x) \cap \text{supp}(y) = \emptyset$, $\mathbf{R}(x + y)$ has the same distribution as $\mathbf{R}(x) \cup \mathbf{R}(y)$, and therefore,

$$\begin{aligned} F(x + y) &= \mathbb{E}[f(\mathbf{R}(x + y))] = \mathbb{E}[f(\mathbf{R}(x) \cup \mathbf{R}(y))] \\ &= \mathbb{E}[G_x(\mathbf{R}(y))] \geq (1 - p) \cdot G_x(\emptyset) = (1 - p) \cdot F(x), \end{aligned}$$

where the inequality follows from Lemma 1. \square

C.2 Omitted Proofs of Section 3

Lemma 4. *We have $f(S_{i,j}) \geq \kappa |S_{i,j}|$ for all $i \in [r]$, $j \in [m]$.*

Proof. To simplify notation, let $S = S_{i,j}$. Let $e_1, \dots, e_{|S|}$ be the elements of S in the order in which they were added to S . Let $S^{(t)} = \{e_1, \dots, e_t\}$. We have $f(S^{(t)}) - f(S^{(t-1)}) = f(S^{(t-1)} \cup \{e_t\}) - f(S^{(t-1)}) \geq \kappa$ and thus

$$f(S) - f(\emptyset) = \sum_{t=1}^{|S|} (f(S^{(t)}) - f(S^{(t-1)})) \geq \kappa |S| \quad \square$$

Lemma 5. *Let $0 \leq u \leq v \leq 1$. Let $S \subseteq V \setminus \text{OPT}$ and $O \subseteq \text{OPT}$ be random sets such that $\mathbb{E}[\mathbf{1}_S] \leq u \mathbf{1}_{V \setminus \text{OPT}}$ and $\mathbb{E}[\mathbf{1}_O] \geq v \mathbf{1}_{\text{OPT}}$. Then $\mathbb{E}[f(S \cup O)] \geq (v - u)f(\text{OPT})$.*

Proof. Let \hat{f} be the Lovasz extension of f . Using the fact that \hat{f} is an extension and it is convex, we obtain

$$\mathbb{E}[f(S \cup O)] = \mathbb{E}[\hat{f}(\mathbf{1}_{S \cup O})] \geq \hat{f}(\mathbb{E}[\mathbf{1}_{S \cup O}]) = \hat{f}(\mathbb{E}[\mathbf{1}_S] + \mathbb{E}[\mathbf{1}_O])$$

Let $\mathbf{x} := \mathbb{E}[\mathbf{1}_S] + \mathbb{E}[\mathbf{1}_O]$. Note that

$$x_e = \begin{cases} \Pr[e \in S] \leq u & \text{if } e \in V \setminus \text{OPT} \\ \Pr[e \in O] \geq v & \text{if } e \in \text{OPT} \end{cases}$$

Thus, we have

$$\hat{f}(\mathbf{x}) = \int_0^1 f(\{e \in V : x_e \geq \theta\}) d\theta \geq \int_u^v f(\{e \in V : x_e \geq \theta\}) d\theta = (v - u)f(\text{OPT})$$

The first equality is the definition of \hat{f} . The inequality is by the non-negativity of f . The second equality is due to the fact that, for $u < \theta \leq v$, we have $\{e \in V : x_e \geq \theta\} = \text{OPT}$. \square

Lemma 6. *Conditioned on the event $|S_{1,1}| < k$, $\text{STGREEDY}(V_{1,1} \cup O'_2) = \text{STGREEDY}(V_{1,1}) = S_{1,1}$.*

Proof. To simplify notation, we let $V_1 = V_{1,1}$ and $S_1 = S_{1,1}$. Let $X = \text{STGREEDY}(V_1 \cup O'_2)$. Suppose for contradiction that $S_1 \neq X$. Let $e_1, e_2, \dots, e_{|V_1 \cup O'_2|}$ be the elements of $V_1 \cup O'_2$ in the order in which they arrived in the stream. Let i be the smallest index such that $\text{STGREEDY}(\{e_1, \dots, e_i\}) \neq \text{STGREEDY}(\{e_1, \dots, e_i\} \cap V_1)$. By the choice of i , we have

$$\text{STGREEDY}(\{e_1, \dots, e_{i-1}\}) = \text{STGREEDY}(\{e_1, \dots, e_{i-1}\} \cap V_1) := A.$$

Note that $|A| < k$, since $A \subseteq S_1$ and $|S_1| < k$ by assumption. Since $\text{STGREEDY}(\{e_1, \dots, e_i\}) \neq \text{STGREEDY}(\{e_1, \dots, e_i\} \cap V_1)$, we must have $e_i \notin V_1$ (and thus $e_i \in O'_2 \setminus V_1$) and $f(A \cup \{e_i\}) - f(A) \geq \kappa$. The latter implies that $e_i \in \text{STGREEDY}(V_1 \cup \{e_i\})$: after processing all of the elements of V_1 that arrived before e_i , the partial greedy solution is A ; when e_i arrives, it is added to the solution since $|A| < k$ and $f(A \cup \{e_i\}) - f(A) \geq \kappa$. But then $e_i \notin O'_2$, which is a contradiction. \square

D Estimating the Optimal Value

In this appendix, we explain how one can drop the assumption from Section 4 that the algorithm has access to an estimate τ of $f(\text{OPT})$. This completes the proof of Theorem 12.

Technically, we analyze in this section the variant of Algorithm 3 given as Algorithm 4. It gets the same two parameters p and c received by Algorithm 3 plus an additional parameter $\varepsilon' \in (0, 1)$ controlling the guaranteed quality of the output. The algorithm is based on a technique originally due to Kazemi et al. [28]. Throughout its execution, Algorithm 4 tracks in m a lower bound on the value of $f(\text{OPT})$. The algorithm also maintains a set $T = \{(1+\varepsilon')^i \mid m/(1+\varepsilon') \leq (1+\varepsilon')^i \leq mk/c\}$ of values that, given the current value of the lower bound m , are (1) possible estimates for $f(\text{OPT})$ at the current point and (2) are not so large that they dwarf this lower bound (of course, T includes only a subset of the possible estimates obeying these requirements). For every estimate τ in T , the algorithm maintains a fractional solution x_τ . We note that the set of fractional solutions maintained is updated every time that T is updated (which happens after every update of m). Specifically, whenever a new value τ is added to T , the algorithm instantiate a new vector x_τ , and whenever a value τ is dropped from T , the algorithm deletes x_τ .

While a value τ remains in T , Algorithm 4 maintains the fractional solution x_τ in exactly the same way that Algorithm 3 maintains its fractional solution given this value τ as an estimate for $f(\text{OPT})$. Moreover, we show below that if τ remains in T when the algorithm terminates, then the value of x_τ when the algorithm terminates is equal to the value of the vector x when Algorithm 3 terminates after executing with this τ as the estimate for $f(\text{OPT})$. Thus, one can view Algorithm 4 as parallel execution of Algorithm 3 for many estimates of $f(\text{OPT})$ at the same time. After viewing the last element, Algorithm 4 calculates for every $\tau \in T$ an output set \hat{S}_τ based on the fractional solution \hat{x}_τ in the same way Algorithm 3 does that, and then outputs the best output set computed for any $\tau \in T$.

Algorithm 4: STREAMPROCESSEXTENSION (with value oracle access to F) (p, c, ε')

```

1 Let  $m \leftarrow f(\emptyset)$  and  $T \leftarrow \{(1 + \varepsilon')^h \mid m/(1 + \varepsilon') \leq (1 + \varepsilon')^h \leq mk/c\}$ .
2 for each arriving element  $e$  do
3   Let  $m' \leftarrow \max\{f(\{e\}), \max_{\tau \in T} \|x_\tau\|_1 \cdot c\tau/k\}$ .
4   if  $m < m'$  then
5     Update  $m \leftarrow m'$  and then  $T \leftarrow \{(1 + \varepsilon')^h \mid m/(1 + \varepsilon') \leq (1 + \varepsilon')^h \leq mk/c\}$ .
6     Delete  $x_\tau$  for every value  $\tau$  removed from  $T$  in Line 5.
7     Initialize  $x_\tau \leftarrow \mathbf{1}_\emptyset$  for every value  $\tau$  added to  $T$  in Line 5.
8   for every  $\tau \in T$  do
9     if  $\partial_e F(x_\tau) \geq \frac{c\tau}{k}$  then  $x_\tau \leftarrow x_\tau + \min\{p, k - \|x_\tau\|_1\} \cdot \mathbf{1}_e$ .
10 for every  $\tau \in T$  do
11   Round the vector  $x_\tau$  to yield a feasible solution  $S_1^\tau$  such that  $\mathbb{E}[f(S_1^\tau)] \geq F(x_\tau)$ .
12   Find another feasible solution  $S_2^\tau \subseteq \text{supp}(x_\tau)$  by running OFFLINEALG with  $\text{supp}(x_\tau)$  as
    the ground set.
13   Let  $\hat{S}_\tau$  be the better solution among  $S_1^\tau$  and  $S_2^\tau$ .
14 return the best solution among  $\{\hat{S}_\tau\}_{\tau \in T}$ , or the empty set if  $T = \emptyset$ .
```

We begin the analysis of Algorithm 4 by bounding its space complexity. The following observation is a first step towards this goal. It upper bounds the size of the support of each vector x_τ

maintained by this algorithm.

Observation 25. *At the end of the every iteration of Algorithm 4, the size of the support of x_τ is at most $mk/(pc\tau) + 2$ for every $\tau \in T$.*

Proof. The way in which Algorithm 4 updates m guarantees that immediately after the update of m at the beginning of the iteration, it was true that m is at least

$$\|x_\tau\|_1 \cdot c\tau/k \geq p(|\text{supp}(x_\tau)| - 1) \cdot c\tau/k ,$$

where the inequality holds since Observation 14 applies to x_τ (because Algorithm 4 updates x_τ in the same way in which Algorithm 3 maintains its solution). Since at most a single element is added to the support of x_τ in each iteration, at the end of the iteration considered we still have the slightly weaker inequality

$$m \geq p(|\text{supp}(x_\tau)| - 2) \cdot c\tau/k ,$$

which implies the observation. \square

We are now ready to bound the space complexity of Algorithm 4.

Lemma 26. *Algorithm 4 can be implemented so that it stores at most $O(kp^{-1}(\varepsilon')^{-1} \ln c^{-1})$ elements.*

Proof. We begin the proof with two technical calculations. First, note that the number of estimates in T is upper bounded at all times by

$$1 + \log_{1+\varepsilon'} \left(\frac{km/c}{m/(1+\varepsilon')} \right) = 1 + \frac{1 + \ln k - \ln c}{\ln(1+\varepsilon')} \leq 1 + \frac{1 + \ln k - \ln c}{2\varepsilon'/3} = O((\varepsilon')^{-1}(\log k - \log c)) .$$

Second, note that

$$\begin{aligned} \sum_{\tau \in T} (|\text{supp}(x_\tau)| - 2) &\leq \sum_{\tau \in T} \min \left\{ \frac{k}{p}, \frac{mk}{pc\tau} \right\} \leq \sum_{\substack{h \in \mathbb{Z} \\ (1+\varepsilon')^{h+1} \geq m}} \min \left\{ \frac{k}{p}, \frac{mk}{pc(1+\varepsilon')^h} \right\} \\ &\leq \frac{k}{p} \cdot \left| \left\{ h \in \mathbb{Z} \mid \frac{m}{1+\varepsilon'} \leq (1+\varepsilon')^h < m/c \right\} \right| + \sum_{h=0}^{\infty} \frac{k}{p(1+\varepsilon')^h} \\ &\leq \frac{k}{p} \cdot \left(\log_{1+\varepsilon'} \left(\frac{m/c}{m} \right) + 2 \right) + \frac{k/p}{1 - 1/(1+\varepsilon')} \leq \frac{k \cdot (\ln c^{-1} + 2)}{p \cdot \ln(1+\varepsilon')} + \frac{k(1+\varepsilon')}{p\varepsilon'} \\ &= O(kp^{-1}(\varepsilon')^{-1} \log c^{-1}) + O(kp^{-1}(\varepsilon')^{-1}) = O(kp^{-1}(\varepsilon')^{-1} \log c^{-1}) , \end{aligned}$$

where the first inequality follows from Observations 14 and 25, and the second inequality follows from the definition of T .

We now observe that Algorithm 4 has to store the elements in the support of the vector x_τ for every $\tau \in T$. Thus, for all the values in T together the algorithm stores $O(kp^{-1}(\varepsilon')^{-1} \log c^{-1})$ elements since

$$\begin{aligned} \sum_{\tau \in T} |\text{supp}(x_\tau)| &= \sum_{\tau \in T} (|\text{supp}(x_\tau)| - 2) + 2|T| \\ &= O(kp^{-1}(\varepsilon')^{-1} \log c^{-1}) + O((\varepsilon')^{-1}(\log k - \log c)) = O(kp^{-1}(\varepsilon')^{-1} \log c^{-1}) . \quad \square \end{aligned}$$

Our next objective is to prove some properties of m . For that purpose, we need the following observation.

Observation 27. *At every point during the execution of Algorithm 4, we have $F(x_\tau) \geq \|x_\tau\|_1 \cdot c\tau/k$ for every $\tau \in T$.*

Proof. Denote by e_1, e_2, \dots, e_ℓ the elements belonging to the support of x_τ at this point, in the order of their arrival. Using this notation, the value of $F(x_\tau)$ can be written as follows.

$$\begin{aligned} F(x_\tau) &= F(\mathbf{1}_\emptyset) + \sum_{i=1}^{\ell} \left(F(x_\tau \wedge \mathbf{1}_{\{e_1, e_2, \dots, e_i\}}) - F(x_\tau \wedge \mathbf{1}_{\{e_1, e_2, \dots, e_{i-1}\}}) \right) \\ &= F(\mathbf{1}_\emptyset) + \sum_{i=1}^{\ell} \left((x_\tau)_{e_i} \cdot \partial_{e_i} F(x_\tau \wedge \mathbf{1}_{\{e_1, e_2, \dots, e_{i-1}\}}) \right) \\ &\geq F(\mathbf{1}_\emptyset) + \frac{c\tau}{k} \cdot \sum_{i=1}^{\ell} (x_\tau)_{e_i} = F(\mathbf{1}_\emptyset) + \frac{c\tau}{k} \cdot \|x_\tau\|_1 \quad , \end{aligned}$$

where the second equality follows from the multilinearity of F , and the inequality holds since Algorithm 4 adds e_i to the support of x_τ only when $\partial_{e_i} F(x_\tau \wedge \mathbf{1}_{\{e_1, e_2, \dots, e_{i-1}\}}) \geq \frac{c\tau}{k}$. \square

Corollary 28. *The value of m only increases during the execution of Algorithm 4, and it always remains a lower bound on $f(\text{OPT})$.*

Proof. The first part of the corollary follows immediately from the fact that each iteration of Algorithm 4 changes the value of m to m' if and only if $m' > m$.

Let us now prove that the second part of the corollary also holds. To do so, we need to show that the original value of m is at most $f(\text{OPT})$, and that the value m' calculated in every iteration of Algorithm 4 is also upper bounded by $f(\text{OPT})$. The first claim holds since the original value of m is $f(\emptyset)$, which is a lower bound on $f(\text{OPT})$ since \emptyset is a feasible solution. Thus, it remains to consider an arbitrary iteration of Algorithm 4 and show that the value m' calculated in this iteration is at most $f(\text{OPT})$.

Recall that m' is the maximum between $f(\{e\})$ and $\max_{\tau \in T} \|x_\tau\|_1 \cdot c\tau/k$. Clearly, $f(\{e\}) \leq f(\text{OPT})$ because $\{e\}$ is a feasible solution. Additionally, for every $\tau \in T$ we have

$$\|x_\tau\|_1 \cdot c\tau/k \leq F(x_\tau) \leq f(\text{OPT}) \quad ,$$

where the first inequality follows from Observation 27, and the second inequality holds since the fact that $\|x_\tau\|_1 \leq k$ implies that the rounding techniques discussed in Section 4 can be used to round x_τ into a feasible solution whose expected value is at least $F(x_\tau)$. \square

Let us denote now by \hat{m} and \hat{T} the final values of m and T , respectively. We assume in the rest of this section that c is set to the value given in Corollary 21—the value $\frac{\alpha(1-p)}{\alpha+1}$. Recall that this is the value required to make Proposition 22 hold. Using this choice of c allows us to easily bound the approximation guarantee of Algorithm 4 in the rare case in which \hat{T} is empty.

Observation 29. *$c \in (0, 1/2)$, and thus, \hat{T} is not empty unless $\hat{m} = 0$.*

Proof. Since $\alpha \in (0, 1]$ and $p \in (0, 1)$,

$$c = \frac{\alpha(1-p)}{\alpha+1} \in \left(0, \frac{\alpha}{\alpha+1} \right) \subseteq (0, 1/2) \quad . \quad \square$$

The last observation immediately implies that when \hat{T} is empty, all the singletons have zero values, and the same must be true for every other non-empty set by the submodularity and non-negativity of f . Thus, $\text{OPT} = \emptyset$, which makes the output of Algorithm 4 optimal in this case. Hence, we can assume from now on that $\hat{T} \neq \emptyset$. The following lemma shows that \hat{T} contains a good estimate for $f(\text{OPT})$ in this case.

Lemma 30. *The set \hat{T} contains a value $\hat{\tau}$ such that $(1 - \varepsilon') \cdot f(\text{OPT}) \leq \hat{\tau} \leq f(\text{OPT})$.*

Proof. Observe that $\hat{m} \geq \max\{f(\emptyset), \max_{u \in V}\{f(\{u\})\}\}$. Thus, by the submodularity of f ,

$$f(\text{OPT}) \leq f(\emptyset) + \sum_{u \in \text{OPT}} [f(\{u\}) - f(\emptyset)] \leq \max\left\{f(\emptyset), \sum_{u \in \text{OPT}} f(\{u\})\right\} \leq k\hat{m} \leq \frac{k\hat{m}}{c} .$$

In contrast, by Corollary 28, $f(\text{OPT}) \geq \hat{m}$. Since \hat{T} contains all the values of the form $(1 + \varepsilon')^i$ in the range $[\hat{m}/(1 + \varepsilon'), k\hat{m}/c]$, the above inequalities imply that it contains in particular the largest value of this form that is still not larger than $f(\text{OPT})$. Let us denote this value by $\hat{\tau}$. By definition, $\hat{\tau} \leq f(\text{OPT})$. Additionally,

$$\hat{\tau} \cdot (1 + \varepsilon') \geq f(\text{OPT}) \Rightarrow \hat{\tau} \geq \frac{f(\text{OPT})}{1 + \varepsilon'} \geq (1 - \varepsilon') \cdot f(\text{OPT}) . \quad \square$$

Let us now concentrate on the value $\hat{\tau}$ whose existence is guaranteed by Lemma 30, and let \bar{x} denote the fractional solution maintained by Algorithm 3 when it gets $\hat{\tau}$ as the estimate for $f(\text{OPT})$. Additionally, let us denote by e_1, e_2, \dots, e_n the elements of V in the order of their arrival, and let e_j the element whose arrival made Algorithm 4 add $\hat{\tau}$ to T (i.e., $\hat{\tau}$ was added to T by Algorithm 4 while processing e_j). If $\hat{\tau}$ belonged to T from the very beginning of the execution of Algorithm 4, then we define $j = 1$

Lemma 31. *The fractional solution \bar{x} of Algorithm 3 is empty immediately prior to the arrival of e_j .*

Proof. If $j = 1$, then lemma is trivial. Thus, we assume $j > 1$ in the rest of this proof. Prior to the arrival of e_j , $\hat{\tau}$ was not part of T . Nevertheless, since $\hat{\tau} \in \hat{T}$, we must have at all times

$$\hat{\tau} \geq \frac{\hat{m}}{1 + \varepsilon'} \geq \frac{m}{1 + \varepsilon'} ,$$

where the second inequality holds by Corollary 28. Therefore, the reason that $\hat{\tau}$ did not belong to T prior to the arrival of e_j must have been that m was smaller than $c\hat{\tau}/k$. Since m is at least as large as the value of any singleton containing an element already viewed by the algorithm we get, for every integer $1 \leq t \leq j - 1$,

$$\frac{c\hat{\tau}}{k} > f(\{e_t\}) \geq f(\{e_t\}) - f(\emptyset) = \partial_{e_t} F(\mathbf{1}_{\emptyset}) \geq \partial_{e_t} F(\bar{x} \wedge \mathbf{1}_{\{e_1, e_2, \dots, e_{t-1}\}}) ,$$

where the second inequality follows from the non-negativity of f and the last from its submodularity. Thus, no fraction of e_t is added to \bar{x} , which implies that \bar{x} is empty at the moment e_j arrives. \square

According to the above discussion, from the moment $\hat{\tau}$ gets into T , Algorithm 4 updates the fractional solution $x_{\hat{\tau}}$ in the same way that Algorithm 3 updates \bar{x} (note that, once $\hat{\tau}$ gets into T , it remains there for good since $\hat{\tau} \in \hat{T}$). Together with the previous lemma which shows that \bar{x} is empty just like $x_{\hat{\tau}}$ at the moment e_j arrives, this implies that the final value of $x_{\hat{\tau}}$ is equal to the final value of \bar{x} . Since the set $\hat{S}_{\hat{\tau}}$ is computed based on the final value of $x_{\hat{\tau}}$ in the same way that the output of Algorithm 3 is computed based on the final value of \bar{x} , we get the following corollary.

Corollary 32. *If it is guaranteed that the approximation ratio of Algorithm 3 is at least β when $(1 - \varepsilon') \cdot f(\text{OPT}) \leq \tau \leq f(\text{OPT})$ for some choice of the parameters p and c , then the approximation ratio of Algorithm 4 is at least β as well for this choice of p and c .*

We are now ready to prove Theorem 12.

Theorem 12. *Assume there exists an α -approximation offline algorithm OFFLINEALG for maximizing a non-negative submodular function subject to cardinality constraint whose space complexity is nearly linear in the size of the ground set. Then, for every constant $\varepsilon \in (0, 1]$, there exists an $(\frac{\alpha}{1+\alpha} - \varepsilon)$ -approximation semi-streaming algorithm for maximizing a non-negative submodular function subject to a cardinality constraint. The algorithm stores at most $O(k\varepsilon^{-2} \log \alpha^{-1})$ elements.*

Proof. The proof of Theorem 23 shows that Algorithm 3 achieves an approximation guarantee of $\frac{\alpha}{1+\alpha} - \varepsilon$ when it has access to a value τ obeying $(1 - \varepsilon/8) \cdot f(\text{OPT}) \leq \tau \leq f(\text{OPT})$ and its parameters are set to $p = \varepsilon/2$ and $c = \frac{\alpha(1-p)}{\alpha+1}$. According to Corollary 32, this implies that by setting the parameters p and c of Algorithm 4 in the same way and setting ε' to $\varepsilon/8$, we get an algorithm whose approximation ratio is at least $\frac{\alpha}{1+\alpha} - \varepsilon$ and does not assume access to an estimate τ of $f(\text{OPT})$.

It remains to bound the space requirement of the algorithm obtained in this way. Observe that

$$c = \frac{\alpha(1-p)}{\alpha+1} = \frac{\alpha(1-\varepsilon/2)}{\alpha+1} \geq \frac{\alpha}{4} .$$

Plugging this bound and the equalities $p = \varepsilon/2$ and $\varepsilon' = \varepsilon/8$ into the guarantee of Lemma 26, we get that the algorithm we have obtained stores $O(k\varepsilon^{-2} \log \alpha^{-1})$ elements. \square

E Approximating the Multilinear Extension

In this appendix we show that Theorem 12 can be proved also by an algorithm that runs in polynomial time (except for the time required for OFFLINEALG) and does not assume value oracle access to F .⁵ The algorithm we use for this purpose is given as Algorithm 5. The differences between this algorithm and Algorithm 4 are as following.

- The elements in Algorithm 5 are denoted by e_1, e_2, \dots, e_n in the order of their arrival.
- Algorithm 5 maintains in r_i the value of $\max\{f(\emptyset), \max_{e_j | 1 \leq j \leq i} f(\{e_j\})\}$. We note that the indexing of r_i by i is for analysis purposes only, and an implementation of the algorithm need not keep in memory more than one such value at any given time.
- The exact formula used to calculate m' is slightly different in the two algorithms.
- Algorithm 5 uses estimates for the partial derivatives of F instead of the actual values of these derivatives (which are difficult to compute in polynomial time without value oracle access to F). These estimates are calculated in Line 10 of the algorithm.

We begin the analysis of Algorithm 5 with the following observation, which is a counterpart of Observation 25 from Appendix D.

Observation 33. *At the end of every iteration of Algorithm 5, the size of the support of x_τ is at most $2mk/(p\tau) + 2$ for every $\tau \in T$.*

⁵Recall that value access to F is equivalent to value access to f for algorithms that are allowed unbounded computational time.

Algorithm 5: STREAMPROCESSEXTENSION (p, c, ε')

```

1 Let  $r_0 \leftarrow f(\emptyset)$  and  $T \leftarrow \{(1 + \varepsilon')^h \mid m/(1 + \varepsilon') \leq (1 + \varepsilon')^h \leq mk/c\}$ .
2 for each arriving element  $e_i$  do
3   Let  $r_i \leftarrow \max\{f(\{e_i\}), r_{i-1}\}$ .
4   Let  $m' \leftarrow \max\{f(\{e_i\}), \max_{\tau \in T} \|x_\tau\|_1 \cdot c(\tau - \varepsilon' r_i/20)/k\}$ .
5   if  $m < m'$  then
6     Update  $m \leftarrow m'$  and then  $T \leftarrow \{(1 + \varepsilon')^h \mid m/(1 + \varepsilon') \leq (1 + \varepsilon')^h \leq mk/c\}$ .
7     Delete  $x_\tau$  for every value  $\tau$  removed from  $T$  in Line 6.
8     Initialize  $x_\tau \leftarrow \mathbf{1}_\emptyset$  for every value  $\tau$  added to  $T$  in Line 6.
9   for every  $\tau \in T$  do
10    Let  $\bar{\partial}_{e_i}^\tau F(x_\tau)$  be an approximation of
        
$$\partial_{e_i} F(x_\tau) = F(x_\tau \vee \mathbf{1}_{e_i}) - F(x_\tau \wedge \mathbf{1}_{V \setminus e_i}) = \mathbb{E}[f(\mathbb{R}(x_\tau) \cup \{e_i\}) - f(\mathbb{R}(x_\tau))]$$

        obtained by averaging  $\ell = \left\lceil \frac{4800(k/p+1)^2 k^2}{c^2 [\varepsilon'(1-\varepsilon')]^2} \cdot \ln \left( \frac{160i^2(2+\ln(k/c))}{(\varepsilon')^2} \right) \right\rceil$  samples.
11    if  $\bar{\partial}_{e_i}^\tau F(x_\tau) \geq \frac{c\tau}{k}$  then  $x_\tau \leftarrow x_\tau + \min\{p, k - \|x_\tau\|_1\} \cdot \mathbf{1}_{e_i}$ .
12 for every  $\tau \in T$  do
13   Round the vector  $x_\tau$  to yield a feasible solution  $S_1^\tau$  such that  $\mathbb{E}[f(S_1^\tau)] \geq F(x_\tau)$ .
14   Find another feasible solution  $S_2^\tau \subseteq \text{supp}(x_\tau)$  by running OFFLINEALG with  $\text{supp}(x_\tau)$  as
        the ground set.
15   Let  $\hat{S}_\tau$  be the better solution among  $S_1^\tau$  and  $S_2^\tau$ .
16 return the best solution among  $\{\hat{S}_\tau\}_{\tau \in T}$ , or the empty set if  $T = \emptyset$ .

```

Proof. The way in which Algorithm 5 updates m guarantees that immediately after the update of m at the beginning of the iteration in which Algorithm 5 process e_i , it was true that m is at least

$$\begin{aligned} \|x_\tau\|_1 \cdot c(\tau - \varepsilon' r_i/20)/k &\geq p(|\text{supp}(x_\tau)| - 1) \cdot c(\tau - \varepsilon' r_i/20)/k \\ &\geq p(|\text{supp}(x_\tau)| - 1) \cdot c(\tau - \varepsilon' m/20)/k, \end{aligned}$$

where the first inequality holds since Observation 14 applies to x_τ (because Algorithm 5 updates x_τ in the same way in which Algorithm 3 maintains its solution), and the second inequality holds since m is the maximum over all the values r_i is a maximum over and more. Since at most a single element is added to the support of x_τ in each iteration, at the end of the iteration considered we still have the slightly weaker inequality

$$m \geq p(|\text{supp}(x_\tau)| - 2) \cdot c(\tau - \varepsilon' m/20)/k \Rightarrow |\text{supp}(x_\tau)| \leq \frac{mk}{pc(\tau - \varepsilon' m/20)} + 2.$$

The observation now follows since the fact that $\tau \in T$ implies $m \leq (1 + \varepsilon')\tau$, and thus,

$$\tau - \varepsilon' m/20 \geq \tau - (1 + \varepsilon')\varepsilon'\tau/20 \geq \tau(1 - \varepsilon'/10) \geq \tau/2. \quad \square$$

Using Observation 33 instead of Observation 25 in the proof of Lemma 26 we get that Lemma 26 applies also to Algorithm 5, which completes the analysis of the number of elements stored by this algorithm. Thus, we concentrate in the rest of this section on analyzing the approximation guarantee of Algorithm 5.

Let us denote now by \mathcal{E} the event that every estimate $\bar{\partial}_{e_i}^\tau F(x_\tau)$ that is calculated by Algorithm 5 differs from $\partial_{e_i}^\tau F(x_\tau)$ by at most $\frac{c\varepsilon'(1-\varepsilon')}{20k} \cdot r_i$. In the next few claims we show that \mathcal{E} is a high probability event. We first need the following known Chernoff-like lemma.

Lemma 34 (Lemma B.3 from [9]). *Let X_1, X_2, \dots, X_ℓ be independent random variables such that for each i , $X_i \in [-1, 1]$. Let $X = \frac{1}{\ell} \sum_{i=1}^\ell X_i$ and $\mu = \mathbb{E}[X]$. Then*

$$\Pr[X > \mu + \alpha] \leq e^{-\frac{\alpha^2 \ell}{12}} \quad \text{and} \quad \Pr[X < \mu - \alpha] \leq e^{-\frac{\alpha^2 \ell}{8}}$$

for every $\alpha > 0$.

In the next lemma we show that each individual estimate that Algorithm 5 calculates is not likely to be too far away from the true value that it estimates.

Lemma 35. *Given that Algorithm 5 calculates an estimate $\bar{\partial}_{e_i}^\tau(x)$ of the value of $\partial_{e_i}^\tau(x)$ for some value τ , element e_i and vector x that has a positive probability to be equal to x_τ upon the arrival of e_i ,*

$$\Pr \left[|\bar{\partial}_{e_i}^\tau F(x) - \partial_{e_i}^\tau(x)| > \frac{c\varepsilon'(1-\varepsilon')}{20k} \cdot r_i \right] \leq \frac{(\varepsilon')^2}{80i^2(2 + \ln(k/c))} .$$

Proof. The algorithm calculates the estimate $\bar{\partial}_{e_i}^\tau F(x)$ by averaging ℓ samples of $f(\mathbf{R}(x) \cup \{u_i\}) - f(\mathbf{R}(x))$. Let Y_t be the t -th such sample. Note that the expected value of Y_t for every $1 \leq t \leq \ell$ is exactly $\partial_{e_i}^\tau F(x)$ because e_i cannot be in the support of x . Later in this proof, we will show that the value of Y_t always falls within the range $[-(k/p + 1) \cdot r_i, r_i]$. However, before doing so, let us prove that the lemma follows from this property.

Consider the random variables $Y_1/[(k/p + 1) \cdot r_i], Y_2/[(k/p + 1) \cdot r_i], \dots, Y_\ell/[(k/p + 1) \cdot r_i]$. Due to the above property, the values of these random variables always fall within the range $[-1, 1]$, therefore, by Lemma 34,

$$\begin{aligned} & \Pr \left[|\bar{\partial}_{e_i}^\tau F(x) - \partial_{e_i}^\tau F(x)| > \frac{c\varepsilon'(1-\varepsilon')}{20k} \cdot r_i \right] \\ &= \Pr \left[\left| \frac{1}{\ell} \cdot \sum_{t=1}^\ell Y_t - \mathbb{E} \left[\frac{1}{\ell} \cdot \sum_{t=1}^\ell Y_t \right] \right| > \frac{c\varepsilon'(1-\varepsilon')}{20k} \cdot r_i \right] \\ &= \Pr \left[\left| \frac{1}{\ell} \cdot \sum_{t=1}^\ell \frac{Y_t}{(k/p + 1) \cdot r_i} - \mathbb{E} \left[\frac{1}{\ell} \cdot \sum_{t=1}^\ell \frac{Y_t}{(k/p + 1) \cdot r_i} \right] \right| > \frac{c\varepsilon'(1-\varepsilon')}{20k(k/p + 1)} \right] \\ &\leq 2e^{-\frac{\ell \left[\frac{c\varepsilon'(1-\varepsilon')}{20k(k/p + 1)} \right]^2}{12}} \leq 2e^{-\ln \left(\frac{160i^2(2 + \ln(k/c))}{(\varepsilon')^2} \right)} = \frac{(\varepsilon')^2}{80i^2(2 + \ln(k/c))} . \end{aligned}$$

It only remains to prove that, for every $1 \leq t \leq \ell$, the sample Y_t is contained within the range $[-(k/p + 1) \cdot r_i, r_i]$. Since f is submodular,

$$Y_t \geq -f(\mathbf{R}(x)) \geq -f(\emptyset) - \sum_{e \in \mathbf{R}(x)} [f(\{e\}) - f(\emptyset)] \geq -(k/p + 1) \cdot r_i$$

because x contains at most $\lceil k/p \rceil$ non-zero entries due to Observation 14 (which applies to Algorithm 5 as well). In contrast, the submodularity of f also implies

$$Y_t = f(\mathbf{R}(x) \cup \{u_i\}) - f(\mathbf{R}(x)) \leq f(\{u_i\}) - f(\emptyset) \leq f(\{u_i\}) \leq r_i . \quad \square$$

Lemma 35 implies the following corollary.

Corollary 36. $\Pr[\mathcal{E}] \geq 1 - \varepsilon'/20$.

Proof. Following the arrival of each element e_i , Algorithm 5 performs one estimate for each value in T . The number of values in T is at most

$$\log_{1+\varepsilon'} \left(\frac{mk/c}{m/(1+\varepsilon')} \right) + 1 = \frac{1 + \ln(k/c)}{\ln(1+\varepsilon')} + 1 \leq \frac{1 + \ln(k/c)}{2\varepsilon'/3} + 1 \leq \frac{2[2 + \ln(k/c)]}{\varepsilon'}.$$

Thus, by Lemma 35 and the union bound, the probability that any of these estimates is off by more than $\frac{c\varepsilon'(1-\varepsilon')}{20k} \cdot r_i$ is at most

$$\frac{2[2 + \ln(k/c)]}{\varepsilon'} \cdot \frac{(\varepsilon')^2}{80i^2(2 + \ln(k/c))} = \frac{\varepsilon'}{40i^2}.$$

Using the union bound again over all the values of i , we get

$$1 - \Pr[\mathcal{E}] \leq \sum_{i=1}^n \frac{\varepsilon'}{40i^2} \leq \frac{\varepsilon'}{40} + \frac{\varepsilon'}{40} \int_1^n \frac{1}{x^2} dx = \frac{\varepsilon'}{40} - \frac{\varepsilon'}{40} \left[\frac{1}{x} \right]_1^n = \frac{\varepsilon'}{40} - \frac{\varepsilon'}{40n} + \frac{\varepsilon'}{40} \leq \frac{\varepsilon'}{20}. \quad \square$$

Our next objective is to show that, given that the event \mathcal{E} happens, the approximation ratio of Algorithm 5 is good. We begin with the following counterpart of Observation 27 from Appendix D.

Observation 37. *Assuming \mathcal{E} holds, at the point in which m' is calculated at the beginning of the processing of e_i by Algorithm 5, we have $F(x_\tau) \geq \|x_\tau\|_1 \cdot c(\tau - \varepsilon'r_i/20)/k$ for every $\tau \in T$.*

Proof. Denote by e'_1, e'_2, \dots, e'_h the elements belonging to the support of x_τ at this point, in the order of their arrival. Using this notation, the value of $F(x_\tau)$ can be written as follows.

$$\begin{aligned} F(x_\tau) &= F(\mathbf{1}_\emptyset) + \sum_{j=1}^h \left(F(x_\tau \wedge \mathbf{1}_{\{e'_1, e'_2, \dots, e'_j\}}) - F(x_\tau \wedge \mathbf{1}_{\{e'_1, e'_2, \dots, e'_{j-1}\}}) \right) \\ &= F(\mathbf{1}_\emptyset) + \sum_{j=1}^h (x_\tau)_{e'_j} \cdot \partial_{e'_j} F(x_\tau \wedge \mathbf{1}_{\{e'_1, e'_2, \dots, e'_{j-1}\}}) \\ &\geq F(\mathbf{1}_\emptyset) + \sum_{j=1}^h (x_\tau)_{e'_j} \cdot \left(\bar{\partial}_{e'_j} F(x_\tau \wedge \mathbf{1}_{\{e'_1, e'_2, \dots, e'_{j-1}\}}) - \frac{c\varepsilon'(1-\varepsilon')}{20k} \cdot r_i \right) \\ &\geq F(\mathbf{1}_\emptyset) + \sum_{i=1}^h (x_\tau)_{e'_i} \cdot \left(\frac{c\tau}{k} - \frac{c\varepsilon'r_i}{20k} \right) = F(\mathbf{1}_\emptyset) + \frac{c}{k} \cdot \left(\tau - \frac{\varepsilon'r_i}{20} \right) \cdot \|x_\tau\|_1, \end{aligned}$$

where the second equality follows from the multilinearity of F , the first inequality follows from the definition of \mathcal{E} and the fact that $r_i \geq r_j$ for every $j < i$, and the second inequality holds since Algorithm 4 adds e'_j to the support of x_τ only when $\bar{\partial}_{e'_j} F(x_\tau \wedge \mathbf{1}_{\{e'_1, e'_2, \dots, e'_{j-1}\}}) \geq \frac{c\tau}{k}$. \square

From this point on we assume that the parameter c is set to $\frac{\alpha(1-p)}{1+\alpha}$. Given this value of c , the proofs of Observation 29 and Lemmata 30 and 31 can be made to work also for Algorithm 5 by simply replacing every use of Observation 27 with a use of Observation 37. Since the last observation is conditioned on the assumption that the event \mathcal{E} happens, we get that Observation 29 and Lemmata 30 and 31 apply to Algorithm 5 under the assumption that the event \mathcal{E} happens. Similarly to the case in Appendix D, this implies the following. Given that \mathcal{E} happens, then

- Algorithm 5 outputs an optimal solution if the final set T (which we denote by \hat{T}) is empty.
- If \hat{T} is not empty, then there exists a value $\hat{\tau}$ and integer $1 \leq j \leq n$ such that
 - $\hat{\tau}$ enters T when e_j arrives (unless $\hat{\tau}$ belongs to T from the very beginning of the algorithm, in which case $j = 1$),
 - once $\hat{\tau}$ enters into T , it remains there until the algorithm terminates,
 - for every $1 \leq t < j$, $\partial_{e_t} F(\tilde{x} \wedge \mathbf{1}_{\{e_1, e_2, \dots, e_{t-1}\}}) < c\hat{\tau}/k$, where \tilde{x} denotes the final value of fractional solution $x_{\hat{\tau}}$,
 - and $(1 - \varepsilon') \cdot f(\text{OPT}) \leq \hat{\tau} \leq f(\text{OPT})$.

It is important to observe also that the value of $x_{\hat{\tau}}$ when the element e_i arrives is $\tilde{x} \wedge \mathbf{1}_{\{e_1, e_2, \dots, e_{i-1}\}}$.

The next few claims repeat arguments from Section 4 to lower bound the approximation guarantee of Algorithm 5 under the assumptions that \mathcal{E} happens and \hat{T} is non-empty. We first consider the case in which $\|\tilde{x}\|_1 = k$. The following lemma corresponds to Lemma 16 and bounds the value of $F(\tilde{x})$ from below in this case.

Lemma 38. *Assuming \mathcal{E} holds and \hat{T} is not empty, if $\|\tilde{x}\|_1 = k$, then $F(\tilde{x}) \geq \hat{\tau} \cdot (c - \varepsilon'/20)$.*

Proof. Note that since \tilde{x} contains a zero fraction of every element that arrived before e_j , the value of $F(\tilde{x})$ can also be written as

$$\begin{aligned} F(\tilde{x}) &= F(\mathbf{1}_\emptyset) + \sum_{i=j}^n \left(F(\tilde{x} \wedge \mathbf{1}_{\{e_1, e_2, \dots, e_i\}}) - F(\tilde{x} \wedge \mathbf{1}_{\{e_1, e_2, \dots, e_{i-1}\}}) \right) \\ &= F(\mathbf{1}_\emptyset) + \sum_{i=j}^n \left(\tilde{x}_{e_i} \cdot \partial_{e_i} F(\tilde{x} \wedge \mathbf{1}_{\{e_1, e_2, \dots, e_{i-1}\}}) \right), \end{aligned}$$

where the second equality follows from the multilinearity of F . Since we assume that the event \mathcal{E} happened, for every $j \leq i \leq n$ it holds that

$$\begin{aligned} \bar{\partial}_{e_i}^{\hat{\tau}}(\tilde{x} \wedge \mathbf{1}_{\{e_1, e_2, \dots, e_{i-1}\}}) &\leq \partial_{e_i}(\tilde{x} \wedge \mathbf{1}_{\{e_1, e_2, \dots, e_{i-1}\}}) + \frac{c\varepsilon'(1 - \varepsilon')}{20k} \cdot r_i \\ &\leq \partial_{e_i}(\tilde{x} \wedge \mathbf{1}_{\{e_1, e_2, \dots, e_{i-1}\}}) + \hat{\tau} \cdot \frac{\varepsilon'}{20k}, \end{aligned}$$

where the second inequality follows since $(1 - \varepsilon') \cdot r_i \leq (1 - \varepsilon') \cdot f(\text{OPT}) \leq \hat{\tau}$ because r_i the maximum of the value of f over a collection of feasible sets. Combining this with the observation that Algorithm 5 selects e_i only if $\bar{\partial}_{e_i}^{\hat{\tau}} F(\tilde{x} \wedge \mathbf{1}_{\{e_1, e_2, \dots, e_{i-1}\}}) \geq c\hat{\tau}/k$, we get

$$\begin{aligned} F(\tilde{x}) &\geq F(\mathbf{1}_\emptyset) + \sum_{i=j}^n \left[\tilde{x}_{e_i} \cdot \left(\bar{\partial}_{e_i}^{\hat{\tau}} F(\tilde{x} \wedge \mathbf{1}_{\{e_1, e_2, \dots, e_{i-1}\}}) - \hat{\tau} \cdot \frac{\varepsilon'}{20k} \right) \right] \\ &\geq F(\mathbf{1}_\emptyset) + \hat{\tau} \cdot \left(\frac{c}{k} - \frac{\varepsilon'}{20k} \right) \cdot \sum_{i=j}^n \tilde{x}_{e_i} = F(\mathbf{1}_\emptyset) + \hat{\tau} \cdot \left(\frac{c}{k} - \frac{\varepsilon'}{20k} \right) \cdot \|\tilde{x}\|_1 \geq \hat{\tau} \cdot \left(c - \frac{\varepsilon'}{20} \right), \end{aligned}$$

where the last equality holds since \tilde{x} contains a zero fraction of every element arriving before e_j by the definition of j , and the last inequality holds since F is non-negative and we assumed that $\|\tilde{x}\|_1 = k$. \square

Let $b = |\text{OPT} \setminus \text{supp}(\tilde{x})|/k$. In the following lemma we bound the value of $F(\tilde{x})$ when $\|\tilde{x}\|_1 < k$. To prove this lemma we use the same steps used in Section 4 to derive Corollary 19. Note that the bound we get here on $F(\tilde{x})$ is equal up to a small error term to the bound in this corollary.

Lemma 39. *Assuming \mathcal{E} holds and \hat{T} is non-empty, if $\|\tilde{x}\|_1 < k$, then $F(\tilde{x}) \geq (1-p) \cdot \left[p \cdot f(\text{OPT}) + (1-p) \cdot f(\text{OPT} \setminus \text{supp}(\tilde{x})) \right] - \hat{\tau}bc \cdot (1 + \varepsilon'/20) \geq [(1-p)p - bc]\hat{\tau} + (1-p)^2 \cdot f(\text{OPT} \setminus \text{supp}(\tilde{x})) - \varepsilon'\hat{\tau}/20$.*

Proof. As done in the proofs of Lemmata 17 and 18 (which are used to prove Corollary 19 in Section 4), we find in this proof lower and upper bounds for $F(\tilde{x} + \mathbf{1}_{\text{OPT} \setminus \text{supp}(\tilde{x})})$. Since Algorithms 3 and 5 both handle the scenario of an arriving element getting past the threshold for acceptance similarly, Lemma 17 applies to \tilde{x} , and thus,

$$F(\tilde{x} + \mathbf{1}_{\text{OPT} \setminus \text{supp}(\tilde{x})}) \geq (1-p) \cdot \left[p \cdot f(\text{OPT}) + (1-p) \cdot f(\text{OPT} \setminus \text{supp}(\tilde{x})) \right] . \quad (3)$$

Moreover, for every element $e_i \in \text{OPT} \setminus \text{supp}(\tilde{x})$ it holds that, if $i < j$, then $\partial_{e_i} F(\tilde{x}) \leq \partial_{e_i} F(\tilde{x} \wedge \mathbf{1}_{e_1, e_2, \dots, e_{i-1}}) < c\hat{\tau}/k$ by the definition of j , and if $i \geq j$, then

$$\partial_{e_i} F(\tilde{x}) - \hat{\tau} \cdot \frac{c\varepsilon'}{20k} \leq \partial_{e_i} F(\tilde{x}) - \frac{c\varepsilon'(1-\varepsilon')}{20k} \cdot r_i \leq \bar{\partial}_{e_i}^{\hat{\tau}} F(\tilde{x}) < \frac{c\hat{\tau}}{k} ,$$

where the first inequality follows from the definitions of r_i and $\hat{\tau}$, the second inequality follows from the assumption that the event \mathcal{E} happens, and the last inequality follows since the elements in $\text{OPT} \setminus \text{supp}(\tilde{x})$ were rejected by Algorithm 5 and f is submodular. The submodularity of f also implies

$$\begin{aligned} F(\tilde{x} + \mathbf{1}_{\text{OPT} \setminus \text{supp}(\tilde{x})}) &\leq F(\tilde{x}) + \sum_{e \in \text{OPT} \setminus \text{supp}(\tilde{x})} \partial_e F(\tilde{x}) \leq F(\tilde{x}) + |\text{OPT} \setminus \text{supp}(\tilde{x})| \cdot \hat{\tau} \cdot \left(\frac{c}{k} + \frac{c\varepsilon'}{20k} \right) \\ &= F(\tilde{x}) + \hat{\tau}bc \cdot \left(1 + \frac{\varepsilon'}{20} \right) , \end{aligned} \quad (4)$$

where the last equality follows from the definition of b . The lemma now follows by combining Inequalities (3) and (4). \square

We now lower bound the value of the set $S_2^{\hat{\tau}}$. The following lemma corresponds to Lemma 20 from Section 5.

Lemma 40. *Assuming \mathcal{E} holds and \hat{T} is non-empty, if $\|\hat{x}\|_1 < k$, then $\mathbb{E}[f(S_2)] \geq \alpha b[1-p-cb(1+\varepsilon'/20)]\hat{\tau} + \alpha(1-b) \cdot f(\text{OPT} \cap \text{supp}(\hat{x})) \geq \alpha b(1-p-cb)\hat{\tau} + \alpha(1-b) \cdot f(\text{OPT} \cap \text{supp}(\hat{x})) - \varepsilon'\hat{\tau}/20$.*

Proof. Using the same arguments as in the proof of Lemma 20, we get that it suffices to prove $F(\tilde{x} \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})}) \geq 1-p-cb(1+\varepsilon'/20)$, which is our objective in the rest of this proof. Recall that we already showed in the proof of Lemma 39 that

$$\partial_e F(\tilde{x}) < \frac{c\hat{\tau}}{k} + \hat{\tau} \cdot \frac{c\varepsilon'}{20k} \quad \forall e \in \text{OPT} \setminus \text{supp}(\tilde{x}) .$$

Thus, the submodularity of f implies

$$\begin{aligned} F(\tilde{x} \vee \mathbf{1}_{\text{OPT}}) &\leq F(\tilde{x} \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})}) + \sum_{e \in \text{OPT} \setminus \text{supp}(\hat{x})} \partial_e F(\tilde{x}) \\ &\leq F(\tilde{x} \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})}) + \frac{c\hat{\tau} \cdot |\text{OPT} \setminus \text{supp}(\hat{x})| \cdot (1 + \varepsilon'/20)}{k} \\ &= F(\tilde{x} \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\hat{x})}) + cb\hat{\tau}(1 + \varepsilon'/20) . \end{aligned}$$

Rearranging this inequality yields

$$\begin{aligned} F(\tilde{x} \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\tilde{x})}) &\geq F(\tilde{x} \vee \mathbf{1}_{\text{OPT}}) - cb\hat{\tau}(1 + \varepsilon'/20) \\ &\geq (1 - p) \cdot f(\text{OPT}) - cb\hat{\tau}(1 + \varepsilon'/20) \geq (1 - p - cb(1 + \varepsilon'/20))\hat{\tau} \ , \end{aligned}$$

where the second inequality holds by Corollary 2 since Observation 14 guarantees that every coordinate of \tilde{x} is either 0 or p . This gives us the promised lower bound on $F(\tilde{x} \vee \mathbf{1}_{\text{OPT} \cap \text{supp}(\tilde{x})})$. \square

The guarantees of Lemmata 39 and 40 differ from the guarantees of Corollary 19 and Lemma 20 from Section 4 only by the subtraction of the error term $\varepsilon'\hat{\tau}/20$. Corollary 21 gives an expression lower bounding the maximum of the guarantees of Corollary 19 and Lemma 20. Thus, this expression also lower bounds the maximum of the guarantees of Lemmata 39 and 40 if the error term $\varepsilon'\hat{\tau}/20$ is subtracted from it. This leads to the following corollary.⁶

Corollary 41. *Assuming \mathcal{E} holds and \hat{T} is non-empty, if $\|\tilde{x}\|_1 < k$, then*

$$\mathbb{E}[\max\{f(S_1^{\hat{\tau}}), f(S_2^{\hat{\tau}})\}] \geq \frac{(1-p)\alpha\hat{\tau}}{\alpha+1} - \frac{\varepsilon'\hat{\tau}}{20} \ .$$

The following proposition summarizes the above claims and proves the approximation guarantee of Algorithm 5.

Proposition 42. *When c is set to $\frac{\alpha(1-p)}{\alpha}$, the expected value of the output set of Algorithm 5 is at least $\left(\frac{(1-p)\alpha}{1+\alpha} - 2\varepsilon'\right) \cdot f(\text{OPT})$.*

Proof. Let us denote by R be the output set of Algorithm 5. We begin the proof by noting that the guarantee of Corollary 41 holds also when $\|\tilde{x}\|_1 = k$ due to Lemma 38 and the inequality $\mathbb{E}[f(S_1^{\hat{\tau}})] \geq F(x_{\hat{\tau}})$. Thus, we get $\mathbb{E}[f(R) \mid \mathcal{E}, \hat{T} \neq \emptyset] \geq \frac{(1-p)\alpha\hat{\tau}}{\alpha+1} - \frac{\varepsilon'\hat{\tau}}{20}$. Using the non-negativity of f and the properties of $\hat{\tau}$, this implies

$$\mathbb{E}[f(R) \mid \mathcal{E}, \hat{T} \neq \emptyset] \geq \left[\frac{(1-p)\alpha}{\alpha+1} - \frac{\varepsilon'}{20}\right] \cdot (1 - \varepsilon') \cdot f(\text{OPT}) \ .$$

Using now the law of total expectation and the non-negativity of f , we get

$$\begin{aligned} \mathbb{E}[f(R)] &\geq \Pr[\mathcal{E}] \cdot \mathbb{E}[f(R) \mid \mathcal{E}] \\ &\geq \Pr[\mathcal{E}] \cdot \left\{ \Pr[\hat{T} = \emptyset \mid \mathcal{E}] \cdot \mathbb{E}[f(R) \mid \mathcal{E}, \hat{T} = \emptyset] + \Pr[\hat{T} \neq \emptyset \mid \mathcal{E}] \cdot \mathbb{E}[f(R) \mid \mathcal{E}, \hat{T} \neq \emptyset] \right\} \\ &\geq \Pr[\mathcal{E}] \cdot \left\{ \Pr[\hat{T} = \emptyset \mid \mathcal{E}] \cdot f(\text{OPT}) + \Pr[\hat{T} \neq \emptyset \mid \mathcal{E}] \cdot \left[\frac{(1-p)\alpha}{\alpha+1} - \frac{\varepsilon'}{20}\right] (1 - \varepsilon') f(\text{OPT}) \right\} \ , \end{aligned}$$

where the last inequality holds since Algorithm 5 outputs an optimal solution when \mathcal{E} happens and \hat{T} is empty. Since $1 \geq \left[\frac{(1-p)\alpha}{\alpha+1} - \frac{\varepsilon'}{20}\right] \cdot (1 - \varepsilon')$, the last inequality implies

$$\begin{aligned} \mathbb{E}[f(R)] &\geq \Pr[\mathcal{E}] \cdot \left[\frac{(1-p)\alpha}{\alpha+1} - \frac{\varepsilon'}{20}\right] \cdot (1 - \varepsilon') \cdot f(\text{OPT}) \\ &\geq \left(1 - \frac{\varepsilon'}{20}\right) \cdot \left[\frac{(1-p)\alpha}{\alpha+1} - \frac{\varepsilon'}{20}\right] \cdot (1 - \varepsilon') \cdot f(\text{OPT}) \geq \left(\frac{(1-p)\alpha}{\alpha+1} - 2\varepsilon'\right) \cdot f(\text{OPT}) \ , \end{aligned}$$

where the second inequality follows from Corollary 36. \square

⁶We note that c is missing from the expression proved by this corollary since the proof of the corollary replaces it with the value we assume for it.

We are now ready to prove the main result of this section.

Theorem 43. *It can be assumed that the algorithm whose existence is guaranteed by Theorem 12 runs in polynomial time (assuming OFFLINEALG runs in such time).*

Proof. Consider the algorithm obtained from Algorithm 5 by setting $p = \varepsilon/2$, $\varepsilon' = \varepsilon/4$ and c as in as in Proposition 42. By Proposition 42, the approximation ratio of this algorithm is at least

$$\frac{\alpha(1-p)}{\alpha+1} - 2\varepsilon' \geq \frac{\alpha(1-\varepsilon/2)}{\alpha+1} - \frac{\varepsilon}{2} \geq \frac{\alpha}{\alpha+1} - \varepsilon .$$

It remains to bound the space requirement of the algorithm obtained in this way. Observe that

$$c = \frac{\alpha(1-p)}{\alpha+1} = \frac{\alpha(1-\varepsilon/2)}{\alpha+1} \geq \frac{\alpha}{4} .$$

Plugging this bound and the equalities $p = \varepsilon/2$ and $\varepsilon' = \varepsilon/4$ into the guarantee of Lemma 26, we get that the algorithm we have obtained stores $O(k\varepsilon^{-2} \log \alpha^{-1})$ elements. \square