

A Hidden Variables Approach to Multilabel Logistic Regression

Jaemoon Lee and Hoda Shajari*

Abstract

Multilabel classification is an important problem in a wide range of domains such as text categorization and music annotation. In this paper, we present a probabilistic model, Multilabel Logistic Regression with Hidden variables (MLRH), which extends the standard logistic regression by introducing hidden variables. Hidden variables make it possible to go beyond the conventional multiclass logistic regression by relaxing the one-hot-encoding constraint. We define a new joint distribution of labels and hidden variables which enables us to obtain one classifier for multilabel classification. Our experimental studies on a set of benchmark datasets demonstrate that the probabilistic model can achieve competitive performance compared with other multilabel learning algorithms.

1 Introduction

Classification is one of the most widespread and classical supervised learning problems in machine learning. Classification problems exist quite extensively in many domains and research areas. In single-label classification tasks, it is assumed that each instance belongs to one and only one class and therefore is assigned a single label. The goal is to learn a mapping from given data (training data) to their respective labels which is able to predict the label of unseen instances (test data). There have been a number of approaches to tackle multiclass classification tasks, including bayesian and probabilistic approaches, support vector machines, and artificial neural networks.

Although multiclass classification has pervasive applications and has been applied successfully to many real-world problems, there exist learning tasks which do not fit in multiclass learning framework. In contrast to multiclass (single-label) classification, in multilabel setting an instance could belong to multiple classes simultaneously and therefore, more than one label needs to be assigned to each instance. For example, a news document could be categorized as both *politics* and *economics* labels simultaneously. In fact, a multilabel classification problem can be decomposed into a number of independent binary classification problems. However, it might not be optimal to solve binary classification problems independently since some labels might be correlated to each other. Therefore, multilabel classification is more challenging. Some of these challenges include exponential growth of possible number of label combinations, label dependencies and structured output spaces [1], unbalanced datasets [2], and computational cost of developing and training these models. Multilabel classification is related to many real-world applications such as text categorization [3, 4, 5, 6, 7], image and scene classification [8, 9], and multimedia automatic annotation and suggestion systems.

Logistic regression (LR) is one of the most common and well-known approaches to solve the multiclass classification tasks and has proven its value in the statistics and machine learning community. Standard LR assumes that only one elements of a label vector is 1 and others are 0 (one-hot-encoding) since it uses a multinoulli distribution [10]. Thus, it naturally fits the multiclass setting. We estimate the parameters of LR based on maximum likelihood estimate and predict a label of an instance in a probabilistic way. However, in multilabel setting, one-hot encoding is the core difficulty for extending LR to a multilabel classification framework. The reason is that we can not assign multiple 1s to a label simultaneously because the multinoulli distribution is no longer a valid probability distribution. In spite of this limitation of LR, a number of approaches using LR for multilabel classification has been proposed in the literature. Those approaches used independent binary LR and combined other methods such as k -nearest neighbor (KNN) to

*The authors are with the Department of Computer and Information Science and Engineering, University of Florida, Gainesville, FL, USA. E-mail: j.lee1,shajaris@ufl.edu.

consider correlations among labels. Despite all the existing approaches for multilabel logistic regression, no framework has been proposed for training the classifiers within one model.

In this paper, we propose Multilabel Logistic Regression with Hidden variables (MLRH), which extends standard LR by introducing hidden variables. A hidden variable or a latent variable is a variable which is not directly observable and affects the response variable. Hidden variables are sometimes used to explain observed variables or relationships between variables. We propose a novel joint probability model of hidden variables and labels to go beyond the conventional classification tasks.

The rest of this paper is organized as follows: Related work is discussed in Section 2. Our MLRH method is then described in Section 3. We briefly discuss the optimization algorithm in Section 4 and related experiments are described in Section 5. The paper ends with a conclusion and future work in Section 6. Some of detailed derivations of our method are discussed in Appendices A.

2 Related Work

As it was mentioned, there have been approaches in the past which extend LR for multilabel classification. Cheng and H  cellermeier [11] proposed an approach to combine both logistic regression and instance-based learning. Their IBLR model basically uses binary LR for each class. In addition, to consider correlations among labels, labels of neighboring instances are weighted by KNN and combined with the parameter of each LR. In other words, their model uses the labels of neighboring instances as extra attributes in a logistic regression scheme and train one classifier for each label. Bian et al. [12] presented the CorrLog model, which explicitly model pairwise correlation between labels and combine it with independent LR for each class. In the CorrLog model, pairwise correlation is defined as weighted sum of products between labels and is added to the parameter of each LR. Li et al. [13] combined the CorrLog model with elastic-net regularization. Liu et al. [14] proposed MLSLR model, in which independent LR are combined with elastic-net regularization for each class and then they are trained. However, the MLSLR do not consider possible label dependencies among labels. Teisseyre [15] propose similar approaches to the MLSLR model, but Teisseyre considers label dependencies by suggesting chaining rule of probabilities of each label. These approaches and some other approaches [16, 17] are based on using separate LR for each class.

Our approach is based on a hidden variable model explained in details in the next section for extending multiclass logistic regression to multilabel case. There also have been models based on hidden variables in logistic regression which are mainly concerned with conventional multiclass (single-label) classification problem. Memisevic et al. [18] proposed the Gated Softmax model, which adopt mixture model and predicts labels by summing over all possible configurations of hidden variables. In the Gated Softmax model, hidden variables are combined with each input feature quadratically. Xu et al. [19, 20] proposed Multinomial Latent Logistic Regression (MLLR) model. The MLLR model also associates hidden variables with each input feature. These approaches basically stem from the idea that the probability $\Pr(y | \mathbf{x}, \mathbf{W})$, which we want to estimate, can be obtained from a joint probability of hidden variables and labels by marginalizing over all possible configurations of hidden variables, i.e.,

$$\Pr(y | \mathbf{x}, \mathbf{W}) = \sum_{\mathbf{h}} \Pr(y, \mathbf{h} | \mathbf{x}, \mathbf{W}). \quad (1)$$

The Gated Softmax and MLLR model use the following conditional probability,

$$\Pr(y, \mathbf{h} | \mathbf{x}, \mathbf{W}) = \frac{\exp\{f(y, \mathbf{h}, \mathbf{x}, \mathbf{W})\}}{\sum_{y, \mathbf{h}} \exp\{f(y, \mathbf{h}, \mathbf{x}, \mathbf{W})\}}. \quad (2)$$

Our model is also based on the conditional probability (Eq. 2). However, in contrast to the previous approaches, we will suggest a new joint conditional probability that can be applied to both multiclass and multilabel setting.

3 Multilabel Logistic Regression with Hidden Variables

In this section, we briefly review multiclass logistic regression and then propose our joint probability model of hidden variables and labels for multilabel logistic regression. We demonstrate that multiclass logistic

regression can be obtained from this joint probability model and show that multilabel logistic regression can also be achieved from the joint probability model.

3.1 Multiclass Logistic Regression

In the multiclass classification problem with K classes ($K \geq 2$), we are given N training data $\{(\mathbf{x}_i, \mathbf{y}_i)\}_{i=1}^N$ with $\mathbf{x}_i \in \mathbb{R}^D$ and $\mathbf{y}_i \in \{0, 1\}^K$, where $\sum_{k=1}^K y_{ik} = 1$ for each i (one-hot-encoding). The goal is to learn a model from the training data such that given a new test input $\mathbf{x}_t$, it can predict the label vector $\mathbf{y}_t$. Logistic regression is one of the well-known approaches for this task. Logistic regression originates from the idea of applying regression model to classification by setting the log-odds to be linear function of parameters and features [10], i.e.,

$$\text{log-odds} = \log \frac{\Pr(y_{k'} = 1 \mid \mathbf{x}, \mathbf{W})}{\Pr(y_K = 1 \mid \mathbf{x}, \mathbf{W})} = \mathbf{w}_{k'}^T \mathbf{x}, \quad k' \in \{1, 2, \dots, K-1\} \quad (3)$$

where $\mathbf{w}$ is a weight vector or decision surface between classes. Using the fact that sum of all the K possibilities is 1 and if $\Pr(y_K = 1 \mid \mathbf{x}, \mathbf{W})$ is chosen to be the reference, we can obtain the probabilities for each class,

$$\Pr(y_k = 1 \mid \mathbf{x}, \mathbf{W}) = \frac{\exp(\mathbf{w}_k^T \mathbf{x})}{\sum_l \exp(\mathbf{w}_l^T \mathbf{x})}, \quad k \in \{1, 2, \dots, K\} \quad (4)$$

where $\mathbf{W} = (\mathbf{w}_1, \mathbf{w}_2, \dots, \mathbf{w}_K) \in \mathbb{R}^{D \times K}$ and $\mathbf{w}_k$ is the weight vector of k -th class. (Eq. 4) is known as the *softmax* function.

The linear function of parameters and features, $\mathbf{w}_k^T \mathbf{x}$, can also view as a score function, or an activation function [21], i.e.,

$$s_k(\mathbf{x}; \mathbf{W}) = \mathbf{w}_k^T \mathbf{x}. \quad (5)$$

We can also obtain the posterior probabilities $\Pr(\mathbf{y} \mid \mathbf{x})$ (Eq. 4) by exponentiating and normalizing (Eq. 5). Note that a bias term b can be added easily by augmenting an extra dimension to $\mathbf{W}$ and $\mathbf{x}$. In the multiclass logistic regression, the assumption is that every feature vector $\mathbf{x}$ belongs to one and only one class. Then, the probability of the training set is

$$\Pr(\{\mathbf{y}_i\} \mid \{\mathbf{x}_i\}, \mathbf{W}) = \prod_{i=1}^N \prod_{k=1}^K \mu_{ik}^{y_{ik}}, \quad (6)$$

where $\mu_{ik} = \Pr(y_{ik} = 1 \mid \mathbf{x}_i, \mathbf{W})$. Note that each instance $\mathbf{x}_i$ is drawn from an independent multinomial distribution (but not identical). The optimal parameters of multiclass logistic regression are obtained by minimizing the negative log-likelihood,

$$\mathbf{W}^* = \arg \min_{\mathbf{W}} \{-\log \Pr(\{\mathbf{y}_i\} \mid \{\mathbf{x}_i\}, \mathbf{W})\}. \quad (7)$$

For a test instance $\mathbf{x}_t$, we assign the k -th label, y_k , to be 1, if the posterior probability $\Pr(y_{tk} = 1 \mid \mathbf{x}_t, \mathbf{W})$ has the maximum value (winner-take-all).

3.2 Hidden Variables

Hidden variables, as described in Section 1, can be used to explain relationships between variables. A hidden variable model is a model that learns a relationships between a set of observable variables and a set of hidden variables. Many hidden variable models have been proposed in the literature, and thus have a long history [22, 23, 24, 25]. As we will see, a hidden variable approach is a sufficient condition to derive the standard logistic regression. Furthermore, hidden variables enable us to go beyond multiclass setting by relaxing single label constraint (one-hot-encoding) and accommodating logistic regression to multi-label framework. We will derive the standard logistic regression from first principles with hidden variables. Then, we discuss its inherent problem and suggest our Multilabel Logistic Regression with Hidden variables (MLRH) model. We introduce binary hidden variables $\mathbf{h}$,

$$\mathbf{h} = [h_1, h_2, \dots, h_K], \quad h_k \in \{0, 1\}, \quad (8)$$

into the *softmax* function (Eq. 4). Since we consider the multiclass setting, we put the one-hot encoding setting to the hidden variables $\mathbf{h}$,

$$\sum_k h_k = 1. \quad (9)$$

The joint probability model of hidden variables $\mathbf{h}$ and labels $\mathbf{y}$ is

$$\Pr(\mathbf{y}, \mathbf{h} \mid \mathbf{x}, \mathbf{W}) = \frac{1}{Z(\mathbf{x}, \mathbf{W})} \exp \left[\sum_{k'} \{y_{k'} \log h_{k'} + h_{k'} \mathbf{w}_{k'}^T \mathbf{x}\} \right], \quad (10)$$

where

$$Z(\mathbf{x}, \mathbf{W}) = \sum_{\mathbf{y}, \mathbf{h}} \exp \left[\sum_{k'} \{y_{k'} \log h_{k'} + h_{k'} \mathbf{w}_{k'}^T \mathbf{x}\} \right]. \quad (11)$$

This joint probability distribution is actually same with the joint model (Eq. 2) we discussed in Section 2. By defining $0 \times \log 0$ to be 1, we can get back the standard logistic regression model. We compute marginal probability $\Pr(\mathbf{y} \mid \mathbf{x}, \mathbf{W})$ over all the possible configurations of hidden variables $\mathbf{h}$,

$$\Pr(\mathbf{y} \mid \mathbf{x}, \mathbf{W}) = \sum_{\mathbf{h}} \Pr(\mathbf{y}, \mathbf{h} \mid \mathbf{x}, \mathbf{W}). \quad (12)$$

For example, assume the number of classes is two ($K = 2$). After some algebra, we can easily obtain the following set of probabilities which are identical to the softmax function (Eq. 4),

$$\Pr(y_1 = 1, y_2 = 0 \mid \mathbf{x}, \mathbf{W}) = \frac{1}{Z(\mathbf{x}, \mathbf{W})} \exp(\mathbf{w}_1^T \mathbf{x}) = \frac{\exp(\mathbf{w}_1^T \mathbf{x})}{\exp(\mathbf{w}_1^T \mathbf{x}) + \exp(\mathbf{w}_2^T \mathbf{x})}, \quad (13)$$

$$\Pr(y_1 = 0, y_2 = 1 \mid \mathbf{x}, \mathbf{W}) = \frac{1}{Z(\mathbf{x}, \mathbf{W})} \exp(\mathbf{w}_2^T \mathbf{x}) = \frac{\exp(\mathbf{w}_2^T \mathbf{x})}{\exp(\mathbf{w}_1^T \mathbf{x}) + \exp(\mathbf{w}_2^T \mathbf{x})}. \quad (14)$$

Therefore, we proved that the joint probability model (Eq. 10) of hidden variables and labels works well in the multiclass setting.

However, there exists an inherent problem related to *log* term in the joint probability, which we call as a *mismatch* problem. Consider the two-class case. The joint probability (Eq. 10) can be simplified as

$$\Pr(\mathbf{y}, \mathbf{h} \mid \mathbf{x}, \mathbf{W}) = \frac{1}{Z(\mathbf{x}, \mathbf{W})} h_1^{y_1} \exp(h_1 \mathbf{w}_1^T \mathbf{x}) h_2^{y_2} \exp(h_2 \mathbf{w}_1^T \mathbf{x}). \quad (15)$$

In multiclass setting, $h_1^{y_1} \times h_2^{y_2}$ produce 1 if both h_k and y_k have same value (e.g. $0^0 \times 1^1 = 1$), otherwise it becomes 0. In other words, if h_k and y_k do not *match*, the joint probability (Eq. 10) becomes 0. However, in the multilabel setting we should relax the one-hot encoding setting of labels $\mathbf{y}$,

$$1 \leq \sum_k y_k \leq K, \quad (16)$$

where K is the number of classes. To go beyond multiclass setting, the constraint of hidden variables 9 is also relaxed,

$$\sum_k h_k \leq K. \quad (17)$$

This relaxation causes the *mismatch* problem to $h_k^{y_k}$. Table 1 shows an example of the mismatch problem. Regardless of values of labels $\mathbf{y}$, $h_k^{y_k}$ always produces 1 when every component of $\mathbf{h}$ is 1. Thus, an extra exponential term is always added in the joint probability (Eq. 10) when every hidden variable is 1, and thus hidden variables do not reflect the information of labels correctly.

Table 1: Mismatch problem in $h_k^{y_k}$

y_2	y_1	h_2	h_1	$h_1^{y_1} \times h_2^{y_2}$	$\exp \left[\sum_{k'} \left\{ y_{k'} \log h_{k'} + h_{k'} \mathbf{w}_{k'}^T \mathbf{x} \right\} \right]$
0	1	0	0	0	0
		0	1	1	$\exp \mathbf{w}_1^T \mathbf{x}$
		1	0	0	0
		1	1	1	$\exp (\mathbf{w}_1 + \mathbf{w}_2)^T \mathbf{x}$
1	0	0	0	0	0
		0	1	0	0
		1	0	1	$\exp \mathbf{w}^T \mathbf{x}$
		1	1	1	$\exp (\mathbf{w}_1 + \mathbf{w}_2)^T \mathbf{x}$

Therefore, we modified the joint probability model (Eq. 10) to resolve the mismatch problem. Instead of the exponential scheme of h_k and y_k , we introduce the multiplication scheme of h_k and y_k , i.e.,

$$\Pr(\mathbf{y}, \mathbf{h} \mid \mathbf{x}, \mathbf{W}) = \frac{1}{Z(\mathbf{x}, \mathbf{W})} \prod_k \left\{ \frac{r_k + 1}{2} \exp(h_k \mathbf{w}_k^T \mathbf{x}) \right\}, \quad (18)$$

where

$$r_k = (2h_k - 1)(2y_k - 1), \quad (19)$$

and the normalization constant $Z(\cdot)$ is computed as

$$Z(\mathbf{x}, \mathbf{W}) = \sum_{\mathbf{y}, \mathbf{h}} \left[\prod_k \left\{ \frac{r_k + 1}{2} \exp(h_k \mathbf{w}_k^T \mathbf{x}) \right\} \right]. \quad (20)$$

Note that hidden variables $\mathbf{h}$ and $\mathbf{y}$ are mapped to $\{-1, 1\}$ space in (Eq. 19). This prevents the result multiplication scheme to be 0 because even one 0 can make entire result be 0. Now their product r_k produces 1 if h_k and y_k are match, otherwise it becomes -1 , and therefore hidden variables reflect the information of labels correctly. The multiplication scheme resolves the mismatch problem and prevents the previous joint probability model (Eq. 10) to produce biased results. In the modified joint probability model (Eq. 18), we remape the space of r_k from $\{-1, 1\}$ to $\{0, 1\}$ to ensure that all the probabilities are always greater than or equal to 0. Since the modified joint probability model is essentially same as the previous model (Eq. 10) in multiclass setting, we can get back the standard logistic regression by marginalizing the joint probability (Eq. 18) over hidden variables.

3.3 Multilabel Logistic Regression with Hidden Variables

In the multilabel classification with K classes ($K \geq 2$), we are given N training data $\{(\mathbf{x}_i, \mathbf{y}_i)\}_{i=1}^N$ with $\mathbf{x}_i \in \mathbb{R}^D$ and $\mathbf{y}_i \in \{0, 1\}^K$. But instead of $\sum_{k=1}^K y_{ik} = 1$, y_{ik} can have multiple 1s. Since logistic regression stems from multinoulli distribution, multiclass logistic regression can not be naturally extended to solve the multi-label problem by having multiple 1s in label $\mathbf{y}$ because it will not be a valid probability distribution. However, hidden variables enables to relax the one-hot-encoding setting and thus allows us to go beyond multiclass problems. We first consider a two-class multilabel classification problem, and then later consider the general case. We enumerate all the possible configurations of hidden variables $\mathbf{h}$ in the joint probability model (Eq. 18). Table 2 shows that from equation 20, the partition function $Z(\mathbf{x}, \mathbf{W})$ becomes

$$Z(\mathbf{x}, \mathbf{W}) = \exp(\mathbf{w}_1^T \mathbf{x}) + \exp(\mathbf{w}_2^T \mathbf{x}) + \exp\{(\mathbf{w}_1 + \mathbf{w}_2)^T \mathbf{x}\}. \quad (21)$$

y_2	y_1	h_2	h_1	$s(\mathbf{h}, \mathbf{x}, \mathbf{W})$	y_2	y_1	h_2	h_1	$s(\mathbf{h}, \mathbf{x}, \mathbf{W})$	y_2	y_1	h_2	h_1	$s(\mathbf{h}, \mathbf{x}, \mathbf{W})$
		0	0	0			0	0	0			0	0	0
0	1	0	1	$\exp(\mathbf{w}_1^T \mathbf{x})$	1	0	0	1	0	1	1	0	1	0
		1	0	0			1	0	$\exp(\mathbf{w}_2^T \mathbf{x})$			1	0	0
		1	1	0			1	1	0			1	1	$\exp(\mathbf{w}_1 + \mathbf{w}_2)^T \mathbf{x}$

Table 2: Summing over all configuration set of $\mathbf{h}$. Note that $s(\mathbf{h}, \mathbf{x}, \mathbf{W})$ is $\prod_k \left\{ \frac{r_k+1}{2} \exp(h_k \mathbf{w}_k^T \mathbf{x}) \right\}$

Then the marginal probabilities $\Pr(\mathbf{y} | \mathbf{x}, \mathbf{W})$ are

$$\Pr(y_1 = 1, y_2 = 0 | \mathbf{x}, \mathbf{W}) = \frac{1}{Z(\mathbf{x}, \mathbf{W})} \exp(\mathbf{w}_1^T \mathbf{x}), \quad (22)$$

$$\Pr(y_1 = 0, y_2 = 1 | \mathbf{x}, \mathbf{W}) = \frac{1}{Z(\mathbf{x}, \mathbf{W})} \exp(\mathbf{w}_2^T \mathbf{x}), \quad (23)$$

$$\Pr(y_1 = 1, y_2 = 1 | \mathbf{x}, \mathbf{W}) = \frac{1}{Z(\mathbf{x}, \mathbf{W})} \exp\left\{(\mathbf{w}_1 + \mathbf{w}_2)^T \mathbf{x}\right\}. \quad (24)$$

Note that the joint probability model $\Pr(\mathbf{y}, \mathbf{h} | \mathbf{x}, \mathbf{W})$ is valid in the multilabel setting since

$$\sum_{\mathbf{y}} \sum_{\mathbf{h}} \Pr(\mathbf{y}, \mathbf{h} | \mathbf{x}_i, \mathbf{W}) = \sum_{\mathbf{h}} \sum_{\mathbf{y}} \Pr(\mathbf{y}, \mathbf{h} | \mathbf{x}_i, \mathbf{W}) = 1. \quad (25)$$

The observation is that if $y_k = 1$, then $\exp(\mathbf{w}_k^T \mathbf{x})$ term is included in the marginal probability. We can obtain a new probability distribution over label $\mathbf{y}$ with hidden variables

$$\Pr(\mathbf{y} | \mathbf{x}, \mathbf{W}) = \frac{1}{Z(\mathbf{x}, \mathbf{W})} \exp(y_1 \mathbf{w}_1^T \mathbf{x}) \exp(y_2 \mathbf{w}_2^T \mathbf{x}). \quad (26)$$

Then, the probability of the training set becomes

$$\Pr(\{\mathbf{y}_i\} | \{\mathbf{x}_i\}, \mathbf{W}) = \prod_i \left\{ \frac{1}{Z(\mathbf{x}_i, \mathbf{W})} \exp(y_{i1} \mathbf{w}_1^T \mathbf{x}_i) \exp(y_{i2} \mathbf{w}_2^T \mathbf{x}_i) \right\}. \quad (27)$$

Our objective function is the negative log-likelihood of (Eq. 27),

$$\begin{aligned} \ell(\mathbf{W}) &= \sum_i -\log \Pr(\{\mathbf{y}_i\} | \{\mathbf{x}_i\}, \mathbf{W}) \\ &= \sum_i [\log Z(\mathbf{x}_i, \mathbf{W}) - y_{i1} \mathbf{w}_1^T \mathbf{x}_i - y_{i2} \mathbf{w}_2^T \mathbf{x}_i]. \end{aligned} \quad (28)$$

Note that the objective function (Eq. 28) is convex since the Hessian of $\ell(\mathbf{W})$ is positive definite (proof in Appendix A.3).

3.3.1 Generalization to K classes

We now consider the general multi-label problem with $K > 2$ classes. We consider the maximum number of labels that a training instance can belongs to, i.e.,

$$\sum_k y_{ik} \leq M, \quad M \leq K. \quad (29)$$

That means, we observe that a feature vector $\mathbf{x}_i$ can belong to at most M classes simultaneously in training set. Therefore, we restrict the label space when training. This restriction reduces the computational complexity. The generalized multilabel logistic regression model is

$$\Pr(\mathbf{y} | \mathbf{x}, \mathbf{W}) = \frac{1}{Z(\mathbf{x}, \mathbf{W})} \prod_{k'=1}^K \{\exp(y_{k'} \mathbf{w}_{k'}^T \mathbf{x})\}, \quad (30)$$

where the partition function $Z(\mathbf{x}, \mathbf{W})$ is

$$Z(\mathbf{x}, \mathbf{W}) = \sum_{a_1} \exp(\mathbf{w}_{a_1}^T \mathbf{x}) + \sum_{a_1} \sum_{a_2 > a_1} \exp\{(\mathbf{w}_{a_1} + \mathbf{w}_{a_2})^T \mathbf{x}\} + \cdots + \sum_{a_1} \cdots \sum_{a_M > a_{M-1}} \exp\{(\mathbf{w}_{a_1} + \cdots + \mathbf{w}_{a_M})^T \mathbf{x}\}. \quad (31)$$

Detailed derivation for the generalized model is presented in Appendix A.1. The probability of the training set and its negative log-likelihood are

$$\Pr(\{\mathbf{y}_i\} | \{\mathbf{x}_i\}, \mathbf{W}) = \prod_i \left[\frac{1}{Z(\mathbf{x}_i, \mathbf{W})} \left\{ \prod_{k'=1}^K (\exp(y_{ik'} \mathbf{w}_{k'}^T \mathbf{x}_i)) \right\} \right], \quad (32)$$

and

$$\begin{aligned} \ell(\mathbf{W}) &= \sum_i -\log \Pr(\{\mathbf{y}_i\} | \{\mathbf{x}_i\}, \mathbf{W}) \\ &= \sum_i \left[\log Z(\mathbf{x}_i, \mathbf{W}) - \sum_{k'=1}^K (y_{ik'} \mathbf{w}_{k'}^T \mathbf{x}_i) \right]. \end{aligned} \quad (33)$$

It is worth mentioning that regularization terms could also be added to objective function 33 to prevent overfitting and a trade off could be found between regularization terms and error terms.

3.3.2 Extension to Hilbert Spaces and Kernels

Logistic regression framework were developed based on the assumption of linear separability between classes. However, this assumption is not always the case since there are many problems in which features are not linearly separable. To address this issue, Kernels were introduced to map a non-separable dataset into an implicit higher dimensional reproducing kernel Hilbert space (RKHS) $\mathcal{H}$ known as feature space where mapped data are linearly separable. Via kernels, it is possible to compute the inner products of mapped features without explicitly computing the features in the feature space (Kernel trick) [26]. If $\phi: X \rightarrow \mathcal{H}$ is a mapping from the original space to a feature space, then a kernel is defined as a function $\kappa: X \times X \rightarrow \mathbb{R}$, such that for every $x_i, x_j \in X$,

$$\kappa(x_i, x_j) = \langle \phi(x_i), \phi(x_j) \rangle, \quad (34)$$

By representer theorem [27], each weight vector w_k can be written as a linear combination of all projected patterns $\phi(x_i) := \kappa(\cdot, x_i)$ in RKHS as

$$w_k = \sum_{i=1}^N \alpha_{ki} \phi(x_i) \quad k \in \{1, \dots, K\}. \quad (35)$$

With (Eq. 34), (Eq. 35), and the following notation

$$\boldsymbol{\alpha}_k = [\alpha_{k1}, \alpha_{k2}, \dots, \alpha_{kn}]^T, \quad (36)$$

$$K_i = [\kappa(x_1, x_i), \kappa(x_2, x_i), \dots, \kappa(x_n, x_i)]^T, \quad (37)$$

The objective function (Eq. 33) becomes

$$\ell(\mathbf{W}) = \sum_i \left[\log Z(\mathbf{x}_i, \mathbf{W}) - \sum_{k'=1}^K \{y_{ik'} \boldsymbol{\alpha}_{k'}^T K_i\} \right], \quad (38)$$

where

$$Z(\mathbf{x}, \mathbf{W}) = \sum_{a_1=1}^K \exp(\boldsymbol{\alpha}_{a_1}^T K_i) + \sum_{a_1=1}^K \sum_{a_2 > a_1}^K \exp\{(\boldsymbol{\alpha}_{a_1} + \boldsymbol{\alpha}_{a_2})^T \mathbf{x}\} + \cdots + \sum_{a_1=1}^K \sum_{a_2 > a_1}^K \cdots \sum_{a_M > a_{M-1}}^K \exp\{(\boldsymbol{\alpha}_{a_1} + \cdots + \boldsymbol{\alpha}_{a_M})^T \mathbf{x}\} \quad (39)$$

3.4 Prediction

In this section, we discuss two different test strategy for the prediction. The first strategy is the winner-take-all (WTA) method and the second strategy is the marginal probability method.

The WTA method is conventional decision criterion. In the WTA scheme, a test pattern is assigned to the class with maximum discriminant function value. We can apply the WTA method to our MLRH model since we can compute probabilities for each configuration set of labels (see, e.g., Eq. 22, 23, and 24). The weakness of the WTA method is that the maximum number of labels which can be assigned to a test instance is restricted by the maximum number of labels that a training instance belongs to.

To overcome the weakness of the WTA approach, we employ the marginal probability method. The marginal probability method enables us to assign arbitrary number of labels to a test instance by computing the marginal probability for each label. Therefore, each label can be assigned independently and probabilistically. Moreover, we can reduce computation complexity by removing all the comparison procedure of the WTA method.

3.4.1 Winner-Take-All

As discussed previously, the WTA method can also be used for our multilabel logistic regression model. In this test scheme, a test instance $\mathbf{x}_t$ is assigned the label configuration $\mathbf{y}_t$ with maximum posterior probability $\Pr(\mathbf{y}_t | \mathbf{x}_t, \mathbf{W})$. The label configurations are restricted to have at most M labels (Eq. 29). For example, if the number $M = 3$ in K classes, we will assign at most 3 labels to a test instance $\mathbf{x}_t$ simultaneously. We discuss the WTA method in detail in Appendix A.2.

3.4.2 Marginal Probability

For the second strategy, we use a marginal probability approach to predict test labels. Assume the number of classes is 2 ($K = 2$). We can compute the marginal probability by using (Eq. 22, 23, and 24)

$$\Pr(y_{t1} = 1 | \mathbf{x}_t, \mathbf{W}) = \frac{1}{Z(\mathbf{x}, \mathbf{W})} \left[\exp(\mathbf{w}_1^T \mathbf{x}_t) + \exp\{(\mathbf{w}_1 + \mathbf{w}_2)^T \mathbf{x}_t\} \right], \quad (40)$$

and

$$\Pr(y_{t2} = 1 | \mathbf{x}_t, \mathbf{W}) = \frac{1}{Z(\mathbf{x}, \mathbf{W})} \left[\exp(\mathbf{w}_2^T \mathbf{x}_t) + \exp\{(\mathbf{w}_1 + \mathbf{w}_2)^T \mathbf{x}_t\} \right]. \quad (41)$$

We will assign each label separately based on the marginal probabilities. Thresholds for assigning a label would be 0.5 or they can be also be obtained by cross validation. We do not put any constraint on the number of labels that a test instance $\mathbf{x}_t$ can belong to simultaneously. Therefore, the benefit of this test scheme is that we can assign labels in a probabilistic way, even if there are unobserved label configurations during training.

4 Majorization-Minimization

In this section, we briefly discuss the Majorization-Minimization (MM) optimization scheme [28]. MM is an optimization framework for both convex and non-convex functions. An MM procedure operates by iteratively optimizing a surrogate function that majorizes the objective function. A function $g(\theta \mid \theta^m)$ is said to majorize a real-valued function $f(\theta)$ at θ^m if

$$g(\theta \mid \theta^m) \geq f(\theta) \quad \text{for all } \theta, \quad (42)$$

$$g(\theta^m \mid \theta^m) = f(\theta^m). \quad (43)$$

The surface $\theta \mapsto g(\theta \mid \theta^m)$ lies above the surface $f(\theta)$ and touches $f(\theta)$ at point $\theta = \theta^m$. Therefore, minimizing or descending on $g(\theta \mid \theta^m)$ is guaranteed to be a descent step on $f(\theta)$. If θ^{m+1} is the minimizer of $g(\theta \mid \theta^m)$, then we establish $f(\theta^{m+1}) = g(\theta^{m+1} \mid \theta^m)$ and descend on $g(\theta \mid \theta^{m+1})$. This MM algorithm forces $f(\theta)$ downhill [28].

Hunter and Lange [28] also presented majorization via a quadratic upper bound, which can apply to logistic regression. If a convex function $\kappa(\theta)$ is twice differentiable and has bounded curvature, by the mean value theorem, we can majorize $\kappa(\theta)$ by

$$\kappa(\theta) \leq \kappa(\theta^m) + \nabla \kappa(\theta^m)^T (\theta - \theta^m) + \frac{1}{2} (\theta - \theta^m)^T M (\theta - \theta^m), \quad (44)$$

where M is a positive definite matrix such that $M - \nabla^2 \kappa(\theta)$ is nonnegative definite for all θ . Although this quadratic majorization is not sharp, we can achieve the global minimum since $\kappa(\theta)$ is convex. We will show that the quadratic majorization works reasonably in logistic regression by comparing to the existing libraries, and then majorize the objective function (Eq. 33).

4.1 MM Algorithm for Multiclass Logistic Regression

In multiclass logistic regression, the objective function is the negative log-likelihood of the probability of training set (Eq. 6),

$$\ell(\mathbf{W}) = \sum_{i=1}^N \left[- \sum_{k'=1}^K y_{ik'} \mathbf{w}_{k'}^T \mathbf{x}_i + \log \sum_{k'=1}^K \exp(\mathbf{w}_{k'}^T \mathbf{x}_i) \right]. \quad (45)$$

The gradient and Hessian of $\ell(\mathbf{W})$ with respect to w_k are

$$\mathbf{g}(\mathbf{w}_k) = \nabla_{\mathbf{w}_k} \ell(\mathbf{W}) = \sum_{i=1}^N \left[y_{ik} + \frac{\exp(\mathbf{w}_k^T \mathbf{x}_i)}{\sum_{k'=1}^K \exp(\mathbf{w}_{k'}^T \mathbf{x}_i)} \right] \mathbf{x}_i, \quad (46)$$

and

$$\mathbf{H}(\mathbf{w}_k) = \nabla_{\mathbf{w}_k} \nabla_{\mathbf{w}_k}^T \ell(\mathbf{W}) = \sum_{i=1}^N \left[\frac{\exp(\mathbf{w}_k^T \mathbf{x}_i)}{\sum_{k'=1}^K \exp(\mathbf{w}_{k'}^T \mathbf{x}_i)} \left(1 - \frac{\exp(\mathbf{w}_k^T \mathbf{x}_i)}{\sum_{k'=1}^K \exp(\mathbf{w}_{k'}^T \mathbf{x}_i)} \right) \right] \mathbf{x}_i \mathbf{x}_i^T. \quad (47)$$

Let $\mathbf{X}$ and α be $[\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_N]^T$ and $\exp(\mathbf{w}_k^T \mathbf{x}_i) / \sum_{k'=1}^K \exp(\mathbf{w}_{k'}^T \mathbf{x}_i)$ respectively. Since $0 \leq \alpha(1 - \alpha) \leq 1/4$, the Hessian $\mathbf{H}(\mathbf{w}_k)$ is positive definite and thus $\frac{1}{4} \mathbf{X}^T \mathbf{X} - \mathbf{H}(\mathbf{w}_k)$ is nonnegative definite. The corresponding MM algorithm becomes

$$\mathbf{w}_k^{m+1} \leftarrow \mathbf{w}_k^m - 4 \left(\mathbf{X}^T \mathbf{X} \right)^{-1} \mathbf{g}(\mathbf{w}_k^m). \quad (48)$$

4.1.1 Validity of the MM Algorithm

We compare the results of the MM algorithm in logistic regression to those of scikit-learn [29] and statsmodels [30] libraries. We use Iris and Wine datasets for the experiments. Table 3 shows that the MM algorithm (Eq. 48) works well comparing to existing libraries.

Table 3: Accuracy on Iris and Wine datasets (%) in 4-fold cross validation

	<i>Iris</i>	<i>Wine</i>
MM algorithm	98.02	96.08
Scikit-learn	97.22	96.11
Statsmodels	97.38	95.55

4.2 MM Algorithm for Multilabel Logistic Regression

Derivation of the MM algorithm for the MLRH model is same as described in Section 4.1. The detailed derivation is presented in Appendix A.3. The MM algorithm for the MLRH model is

$$\mathbf{w}_k^{m+1} \leftarrow \mathbf{w}_k^m - 4 \left(\mathbf{X}^T \mathbf{X} \right)^{-1} \mathbf{g}(\mathbf{w}_k^m),$$

where $\mathbf{g}(\mathbf{w}_k^m)$ is given by

$$\mathbf{g}(\mathbf{w}_k) = \nabla_{\mathbf{w}_k} \ell(\mathbf{W}) = \sum_{i=1}^N \left[\frac{\nabla_{\mathbf{w}_k} Z(\mathbf{x}, \mathbf{W})}{Z(\mathbf{x}, \mathbf{W})} - y_{ik} \right] \mathbf{x}_i,$$

with the partition function $Z(\mathbf{x}, \mathbf{W})$ (Eq. 31).

5 Experimental Results

This section is devoted to experimental studies that we conducted to evaluate the performance of our MLRH model. Before presenting and discussing our experimental results, we briefly discuss some learning algorithms as baseline methods, and give some information about datasets and evaluation metrics.

5.1 Learning Algorithms - Binary Relevance and Label Powerset

Multilabel classification can be converted into a number of binary (single-label) problems in a straightforward manner. In *binary relevance* (BR) learning, a multilabel classification problem is decomposed into a number of independent binary classification problems. Since in BR, each binary classifier is trained independently, the correlation among labels is ignored. Nevertheless, BR usually serves as benchmark to other multilabel approaches [31]. For assigning a label to a test pattern, it is possible to come up with a probabilistic scheme for confidence levels and consider a threshold for scores for which each value or probability above threshold gives rise to a label. We used BR with Support Vector Machine (SVM) [32] as a benchmark.

In Label Powerset (LP) learning, a multilabel classification problem with K classes is transformed to a multiclass problem with 2^K classes. A standard multiclass technique can then be applied to solve the problem. It is shown that such an approach can give the best empirical results [33]. One of the drawbacks of this approach is that there might be no training patterns corresponding to one or more combinations of labels and no classifier is learned for them during training and therefore these label combinations can not be recognized during testing. We solved transformed LP via multiclass logistic regression.

5.2 Dataset

We tested our MLRH model on two benchmark multilabel datasets, scene [34] and emotions [35]. Overview of these datasets is given in Table 4.

Table 4: Statistics for Scene and Emotions datasets. Max Labels is the maximum number of labels that an instance can belong to simultaneously.

Dataset	Domain	# Instances	# Attributes	# Labels	# Max Labels
Scene	Image	2407	294	6	3
Emotions	Music	593	72	6	3

5.3 Evaluation Metrics for Multilabel case

We use the following evaluation metric:

- Exact Match Ratio is simply the ratio of correctly classified instances to all instances. The predicted label of an instance is correct if it is exactly same as the actual (true) label of the instance.

$$\text{Exact Match Ratio} = \frac{1}{N} \sum_{i=1}^N I(\tilde{Y}_i = Y_i),$$

- Hamming loss [36] is defined as the fraction of incorrectly predicted labels to the total number of labels averaged over all instances and normalized by number of classes,

$$\text{Hamming loss} = \frac{1}{NK} \sum_{i=1}^N |\tilde{Y}_i \Delta Y_i|,$$

where Δ denotes symmetric difference of two sets.

5.4 Results

We used 5-fold cross validation for training the classifiers. We tuned the hyperparameters in such a way that BR-SVM performs at its best. As shown in Table 5, our MLRH model with WTA test scheme tends to outperforms other methods in terms of Exact Match Ratio since our model considers each possibilities of label sets. In marginal probability test scheme, we simply set the thresholds for each class to be 0.5. Therefore, the marginal probability test scheme can be improved by setting optimal thresholds via cross validation, which is one of our future works.

Table 5: Experimental results in terms of different evaluation measures via 5-fold cross validation. MLRH stands for Multilabel Logistic Regression with Hidden Variables model. Winner-take-all (WTA) and marginal probability (MP) are the test schemes of the MLRH model. RBF denotes RBF kernels. Exact Match Ratio are in %.

Dataset	Scene		Emotions	
	Exact Match Ratio	Hamming Loss	Exact Match Ratio	Hamming Loss
MLRH-WTA (RBF)	72.61	0.079	33.37	0.188
MLRH-MP(RBF)	54.22	0.096	31.03	0.189
BR-SVM (RBF)	64.90	0.075	33.20	0.178
LP-Multiclass LR	65.33	0.111	24.59	0.228

6 Conclusion and Future Work

In this paper, we proposed a multilabel logistic regression model via defining a joint distribution of hidden and observed variables. To our knowledge, it is the first approach to extend the standard logistic regression by introducing hidden variables. We derived logistic regression for multiclass from first principles by using hidden variables and then obtained multilabel logistic regression using the joint probability distribution. We also proved that our objective function (negative log-likelihood) is convex, and thus employ a simple optimization scheme, majorization-minimization. For the objective function, weight regularization can be used if needed. The experimental results show that the proposed multilabel logistic regression model can be competitive comparing to a set of baseline methods for multilabel learning. For future work, we will apply our model to different multilabel tasks and compare other learning algorithms. We will compute the optimal thresholds of the marginal probability test scheme via cross-validation. We are considering to deploy the objective function 33 as a loss in the last layer of a neural network for training multilabel classifiers.

References

- [1] Christoph H. Lampert. Maximum margin multi-label structured prediction. In *Proceedings of the 24th International Conference on Neural Information Processing Systems*, NIPS’11, pages 289–297. Curran Associates Inc., 2011.
- [2] Francisco Charte, Antonio J Rivera, María J del Jesus, and Francisco Herrera. Addressing imbalance in multilabel classification: Measures and random resampling algorithms. *Neurocomputing*, 163:3–16, 2015.
- [3] Thorsten Joachims. Text categorization with support vector machines: Learning with many relevant features. In *Machine Learning: ECML-98*, pages 137–142. Springer Berlin Heidelberg, 1998.
- [4] Andrew Kachites McCallum. Multi-label text classification with a mixture model trained by em. In *AAAI 99 Workshop on Text Learning*, 1999.
- [5] Robert E. Schapire and Yoram Singer. Boostexter: A boosting-based system for text categorization. *Machine Learning*, 39(2):135–168, May 2000.
- [6] Hideto Kazawa, Tomonori Izumitani, Hirotoshi Taira, and Eisaku Maeda. Maximal margin labeling for multi-topic text categorization. In *Proceedings of the 17th International Conference on Neural Information Processing Systems*, NIPS’04, pages 649–656, Cambridge, MA, USA, 2004. MIT Press.
- [7] Juho Rousu, Craig Saunders, Sandor Szedmak, and John Shawe-Taylor. Kernel-based learning of hierarchical multilabel classification models. *J. Mach. Learn. Res.*, 7:1601–1626, December 2006.
- [8] Matthew R. Boutell, Jiebo Luo, Xipeng Shen, and Christopher M. Brown. Learning multi-label scene classification, 2004.
- [9] Mei Wang, Xiangdong Zhou, and Tat-Seng Chua. Automatic image annotation via local multi-label classification. In *CIVR*, 2008.
- [10] Kevin P. Murphy. *Machine Learning: A Probabilistic Perspective*. The MIT Press, 2012.
- [11] Weiwei Cheng and Eyke Hüllermeier. Combining instance-based learning and logistic regression for multilabel classification. *Machine Learning*, 76(2):211–225, Sep 2009.
- [12] Wei Bian, Bo Xie, and Dacheng Tao. Corlog: Correlated logistic models for joint prediction of multiple labels. In Neil D. Lawrence and Mark Girolami, editors, *Proceedings of the Fifteenth International Conference on Artificial Intelligence and Statistics*, volume 22 of *Proceedings of Machine Learning Research*, pages 109–117, La Palma, Canary Islands, 21–23 Apr 2012. PMLR.
- [13] Q. Li, B. Xie, J. You, W. Bian, and D. Tao. Correlated logistic model with elastic net regularization for multilabel image classification. *IEEE Transactions on Image Processing*, 25(8):3801–3813, Aug 2016.

- [14] Huawen Liu, Shichao Zhang, and Xindong Wu. Mlslr: Multilabel learning via sparse logistic regression. *Information Sciences*, 281:310 – 320, 2014. Multimedia Modeling.
- [15] Pawel Teisseyre. Ccnet: Joint multi-label classification and feature selection using classifier chains and elastic net regularization. *Neurocomputing*, 235:98 – 111, 2017.
- [16] Akinori Fujino and Hideki Isozaki. Multi-label classification using logistic regression models for ntcir-7 patent mining task. In *NTCIR*, 2008.
- [17] Shibiao Wan, Man-Wai Mak, and Sun-Yuan Kung. mplr-loc: An adaptive decision multi-label classifier based on penalized logistic regression for protein subcellular localization prediction. *Analytical biochemistry*, 473:14–27, 2015.
- [18] Roland Memisevic, Christopher Zach, Marc Pollefeys, and Geoffrey E Hinton. Gated softmax classification. In *Advances in Neural Information Processing Systems 23*, pages 1603–1611. Curran Associates, Inc., 2010.
- [19] Zhe Xu, Dacheng Tao, Ya Zhang, Junjie Wu, and Ah Chung Tsoi. Architectural style classification using multinomial latent logistic regression. In *European Conference on Computer Vision*, pages 600–615. Springer, 2014.
- [20] Z. Xu, Z. Hong, Y. Zhang, J. Wu, A. C. Tsoi, and D. Tao. Multinomial latent logistic regression for image understanding. *IEEE Transactions on Image Processing*, 25(2):973–987, Feb 2016.
- [21] Christopher M. Bishop. *Pattern Recognition and Machine Learning (Information Science and Statistics)*. Springer-Verlag, 2006.
- [22] David M. Blei, Andrew Y. Ng, and Michael I. Jordan. Latent dirichlet allocation. *J. Mach. Learn. Res.*, 3:993–1022, 2003.
- [23] Susan T. Dumais. Latent semantic analysis. *Annual Review of Information Science and Technology*, 38(1):188–230, 2004.
- [24] Ariadna Quattoni, Sybor Wang, Louis-Philippe Morency, Michael Collins, and Trevor Darrell. Hidden conditional random fields. *IEEE Trans. Pattern Anal. Mach. Intell.*, 29(10):1848–1852, 2007.
- [25] D.J. Bartholomew, M. Knott, and I. Moustaki. *Latent variable models and factor analysis: A unified approach*, volume 899. Wiley, 2011.
- [26] Vladimir N. Vapnik. *The Nature of Statistical Learning Theory*. Springer-Verlag, Berlin, Heidelberg, 1995.
- [27] George Kimeldorf and Grace Wahba. Some results on tchebycheffian spline functions. *Journal of Mathematical Analysis and Applications*, 33(1):82 – 95, 1971.
- [28] David R Hunter and Kenneth Lange. A tutorial on mm algorithms. *The American Statistician*, 58(1):30–37, 2004.
- [29] F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12:2825–2830, 2011.
- [30] Skipper Seabold and Josef Perktold. Statsmodels: Econometric and statistical modeling with python. In *9th Python in Science Conference*, 2010.
- [31] Oscar Luaces, Jorge Díez, José Barranquero, Juan José del Coz, and Antonio Bahamonde. Binary relevance efficacy for multilabel classification. *Progress in Artificial Intelligence*, 1(4):303–313, Dec 2012.
- [32] Alex J. Smola and Bernhard Schölkopf. A tutorial on support vector regression. *Statistics and Computing*, 14(3):199–222, Aug 2004.

- [33] Grigorios Tsoumakas and Ioannis Katakis. Multi-label classification: An overview. *Int J Data Warehousing and Mining*, 2007:1–13, 2007.
- [34] Matthew R. Boutell, Jiebo Luo, Xipeng Shen, and Christopher M. Brown. Learning multi-label scene classification, 2004.
- [35] Konstantinos Trohidis, Grigorios Tsoumakas, George Kalliris, and Ioannis P. Vlahavas. Multi-label classification of music into emotions. In *ISMIR*, pages 325–330, 2008.
- [36] Robert E. Schapire and Yoram Singer. Improved boosting algorithms using confidence-rated predictions. *Machine Learning*, 37(3):297–336, Dec 1999.

A Appendices

A.1 Generalizing to Multiple Classes

In general case, we have K classes in multi-label setting. Let M be the maximum number of classes that a feature vector $\mathbf{x}$ can belong to simultaneously. We will discuss a simple case, where $K = 3$ and $M = 2$, and figure out the general model. We have the joint probability model

$$\Pr(\mathbf{y}, \mathbf{h} \mid \mathbf{x}, \mathbf{W}) = \frac{1}{Z(\mathbf{x}, \mathbf{W})} \prod_k \left\{ \frac{r_k + 1}{2} \exp(h_k \mathbf{w}_k^T \mathbf{x}) \right\}, \quad (49)$$

where the normalization constant $Z(\mathbf{x}, \mathbf{W})$ can be computed as

$$Z(\mathbf{x}, \mathbf{W}) = \sum_{\mathbf{y}, \mathbf{h}} \prod_k \left\{ \frac{r_k + 1}{2} \exp(h_k \mathbf{w}_k^T \mathbf{x}) \right\}. \quad (50)$$

Let us enumerate all the possible configurations of hidden variables $\mathbf{h}$ and labels $\mathbf{y}$ in the joint probability.

y_3	y_2	y_1	h_3	h_2	h_1	$s(\mathbf{h}, \mathbf{x}, \mathbf{W})$
0	0	1	0	0	1	$\exp(\mathbf{w}_1^T \mathbf{x})$
			$\vdots$	$\vdots$	$\vdots$	$\vdots$
			1	1	1	0
0	1	0	0	1	0	$\exp(\mathbf{w}_2^T \mathbf{x})$
			$\vdots$	$\vdots$	$\vdots$	$\vdots$
			1	1	1	0
1	0	0	1	0	0	$\exp(\mathbf{w}_3^T \mathbf{x})$
			$\vdots$	$\vdots$	$\vdots$	$\vdots$
			1	1	1	0

y_3	y_2	y_1	h_3	h_2	h_1	$s(\mathbf{h}, \mathbf{x}, \mathbf{W})$
0	1	1	0	1	1	$\exp(\mathbf{w}_1 + \mathbf{w}_2)^T \mathbf{x}$
			$\vdots$	$\vdots$	$\vdots$	$\vdots$
			1	1	1	0
1	0	1	1	0	1	$\exp(\mathbf{w}_1 + \mathbf{w}_3)^T \mathbf{x}$
			$\vdots$	$\vdots$	$\vdots$	$\vdots$
			1	1	1	
1	1	0	1	1	0	$\exp(\mathbf{w}_2 + \mathbf{w}_3)^T \mathbf{x}$
			$\vdots$	$\vdots$	$\vdots$	$\vdots$
			1	1	1	0

Table 6: Summing over all configuration set of $\mathbf{h}$. $s(\mathbf{h}, \mathbf{x}, \mathbf{W})$ is $\prod_{k'=1}^3 \left\{ \frac{h_{k'}(2y_{k'}-1)+1}{2} \exp\left(\frac{h_{k'}+1}{2} \mathbf{w}_{k'}^T \mathbf{x}\right) \right\}$.

Then, the partition function $Z(\mathbf{x}, \mathbf{W})$ becomes

$$\begin{aligned} Z(\mathbf{x}, \mathbf{W}) = & \exp(\mathbf{w}_1^T \mathbf{x}) + \exp(\mathbf{w}_2^T \mathbf{x}) + \exp(\mathbf{w}_3^T \mathbf{x}) + \exp\left\{(\mathbf{w}_1 + \mathbf{w}_2)^T \mathbf{x}\right\} \\ & + \exp\left\{(\mathbf{w}_1 + \mathbf{w}_3)^T \mathbf{x}\right\} + \exp\left\{(\mathbf{w}_2 + \mathbf{w}_3)^T \mathbf{x}\right\}. \end{aligned} \quad (51)$$

And some examples of the posterior probabilities $\Pr(\mathbf{y} \mid \mathbf{x}, \mathbf{W})$ are

$$\Pr(y_1 = 1, y_2 = 0, y_3 = 0 \mid \mathbf{x}, \mathbf{W}) = \frac{1}{Z(\mathbf{x}, \mathbf{W})} \exp(\mathbf{w}_1^T \mathbf{x}), \quad (52)$$

$$\Pr(y_1 = 1, y_2 = 1, y_3 = 0 \mid \mathbf{x}, \mathbf{W}) = \frac{1}{Z(\mathbf{x}, \mathbf{W})} \exp\left\{(\mathbf{w}_1 + \mathbf{w}_2)^T \mathbf{x}\right\}. \quad (53)$$

As we discussed in Section 3.3, we can observe that if $y_k = 1$, then $\exp(\mathbf{w}_k^T \mathbf{x})$ term is always included in the posterior probability. With this observation, we can generalize our Multi-label Logistic Regression with Hidden variables model

$$\Pr(\mathbf{y} \mid \mathbf{x}, \mathbf{W}) = \frac{1}{Z(\mathbf{x}, \mathbf{W})} \prod_{k'=1}^K \{\exp(y_{k'} \mathbf{w}_{k'}^T \mathbf{x})\}, \quad (54)$$

where the partition function $Z(\mathbf{x}, \mathbf{W})$ is

$$Z(\mathbf{x}, \mathbf{W}) = \sum_{a_1=1}^K \exp(\mathbf{w}_{a_1}^T \mathbf{x}) + \sum_{a_1=1}^K \sum_{a_2 > a_1}^K \exp\left\{(\mathbf{w}_{a_1} + \mathbf{w}_{a_2})^T \mathbf{x}\right\} + \dots + \sum_{a_1=1}^K \dots \sum_{a_M > a_{M-1}}^K \frac{\exp\left\{(\mathbf{w}_{a_1} + \dots + \mathbf{w}_{a_M})^T \mathbf{x}\right\}}{M!}. \quad (55)$$

A.2 Winner-Take-All

In this test scheme, we restrict the test label space based on the observed label space in the training set. For a test instance $\mathbf{x}_t$, we predict the label with maximum posterior probability. For example, let us consider the posterior probabilities in two classes

$$\Pr(y_{t1} = 1, y_{t2} = 0 \mid \mathbf{x}_t, \mathbf{W}) = \frac{1}{Z(\mathbf{x}_t, \mathbf{W})} \exp(\mathbf{w}_1^T \mathbf{x}_t), \quad (56)$$

$$\Pr(y_{t1} = 0, y_{t2} = 1 \mid \mathbf{x}_t, \mathbf{W}) = \frac{1}{Z(\mathbf{x}_t, \mathbf{W})} \exp(\mathbf{w}_2^T \mathbf{x}_t), \quad (57)$$

$$\Pr(y_{t1} = 1, y_{t2} = 1 \mid \mathbf{x}_t, \mathbf{W}) = \frac{1}{Z(\mathbf{x}_t, \mathbf{W})} \exp\left\{(\mathbf{w}_1 + \mathbf{w}_2)^T \mathbf{x}_t\right\}, \quad (58)$$

where

$$Z(\mathbf{x}, \mathbf{W}) = \exp(\mathbf{w}_1^T \mathbf{x}) + \exp(\mathbf{w}_2^T \mathbf{x}) + \exp\left\{(\mathbf{w}_1 + \mathbf{w}_2)^T \mathbf{x}\right\}. \quad (59)$$

Therefore, we will assign a label set according to the posterior probabilities. For instance, $y_{t1} = 1$ and $y_{t2} = 1$ are assigned if $\exp\left\{(\mathbf{w}_1 + \mathbf{w}_2)^T \mathbf{x}_t\right\}$ is the maximum. Note that in this test scheme, we do not need to consider the partition function $Z(\mathbf{x}_t, \mathbf{W})$ since it is the normalization constant of $\Pr(\mathbf{y}_t \mid \mathbf{x}_t, \mathbf{W})$. This test scheme can be simplified. Assume the case that $y_{t1} = 1$ and $y_{t2} = 1$ are assigned. That means

$$\exp\left\{(\mathbf{w}_1 + \mathbf{w}_2)^T \mathbf{x}_i\right\} \geq \exp(\mathbf{w}_1^T \mathbf{x}_i) \quad (60)$$

$$\begin{aligned} &\Rightarrow \exp(\mathbf{w}_1^T \mathbf{x}_i) \exp(\mathbf{w}_2^T \mathbf{x}_i) \geq \exp(\mathbf{w}_1^T \mathbf{x}_i) \\ &\Rightarrow \exp(\mathbf{w}_2^T \mathbf{x}_i) \geq 1 \\ &\Rightarrow \mathbf{w}_2^T \mathbf{x}_i \geq 0 \end{aligned} \quad (61)$$

In this way, we can simplify the WTA method. For example, $y_{t1} = 1$ and $y_{t2} = 1$ are assigned if $\mathbf{w}_1^T \mathbf{x}_i \geq 0$ and $\mathbf{w}_2^T \mathbf{x}_i \geq 0$.

A.3 MM Algorithm for MLHR model

From the objective function (Eq. 33), the gradient of $\ell(W)$ with respect to w_k are

$$\mathbf{g}(\mathbf{w}_k) = \nabla_{\mathbf{w}_k} \ell(\mathbf{W}) = \sum_{i=1}^N \left[\frac{\nabla_{\mathbf{w}_k} Z(\mathbf{x}, \mathbf{W})}{Z(\mathbf{x}, \mathbf{W})} - y_{ik} \right] \mathbf{x}_i. \quad (62)$$

Let α be equal to $\nabla_{\mathbf{w}_k} Z(\mathbf{x}, W) / Z(\mathbf{x}, W)$. Then Hessian is

$$\begin{aligned} \mathbf{H}(\mathbf{w}_k) &= \nabla_{\mathbf{w}_k} \nabla_{\mathbf{w}_k^T} \ell(\mathbf{W}) = \sum_{i=1}^N [\alpha(1-\alpha)] \mathbf{x}_i \mathbf{x}_i^T \\ &= \mathbf{X}^T \mathbf{S} \mathbf{X} \end{aligned} \quad (63)$$

where $\mathbf{X} = [\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_N]^T$, $\mathbf{S} = \text{diag}[\alpha(1-\alpha)]$, and $Z(x, W)$ is given by (Eq. 31). The Hessian $\mathbf{H}(\mathbf{w}_k)$ is positive definite since

$$\mathbf{u}^T \mathbf{H}(\mathbf{w}_k) \mathbf{u} = \mathbf{u}^T \mathbf{X}^T \mathbf{S} \mathbf{X} \mathbf{u} = (\mathbf{X} \mathbf{u})^T \mathbf{S} (\mathbf{X} \mathbf{u}) > 0, \quad \forall \alpha \neq 0. \quad (64)$$

Therefore, our objective function (Eq. 33) is convex. Furthermore, $\frac{1}{4} \mathbf{X}^T \mathbf{X} - \mathbf{H}(\mathbf{w}_k)$ is nonnegative definite since $\mathbf{H}(\mathbf{w}_k) \leq \frac{1}{4} \mathbf{X}^T \mathbf{X}$. The corresponding MM algorithm becomes

$$\mathbf{w}_k^{m+1} \leftarrow \mathbf{w}_k^m - 4 \left(\mathbf{X}^T \mathbf{X} \right)^{-1} \mathbf{g}(\mathbf{w}_k^m). \quad (65)$$