

Efficient Deterministic Distributed Coloring with Small Bandwidth

Philipp Bamberger · philipp.bamberger@cs.uni-freiburg.de · University of Freiburg

Fabian Kuhn · kuhn@cs.uni-freiburg.de · University of Freiburg

Yannic Maus¹ · yannic.maus@campus.technion.ac.il · Technion

Abstract. We show that the $(\text{degree} + 1)$ -list coloring problem can be solved deterministically in $O(D \cdot \log n \cdot \log^2 \Delta)$ rounds in the **CONGEST** model, where D is the diameter of the graph, n the number of nodes, and Δ the maximum degree. Using the recent polylogarithmic-time deterministic network decomposition algorithm by Rozhoň and Ghaffari [STOC 2020], this implies the first efficient (i.e., poly $\log n$ -time) deterministic **CONGEST** algorithm for the $(\Delta + 1)$ -coloring and the $(\text{degree} + 1)$ -list coloring problem. Previously the best known algorithm required $2^{O(\sqrt{\log n})}$ rounds and was not based on network decompositions.

Our techniques also lead to deterministic $(\text{degree} + 1)$ -list coloring algorithms for the congested clique and the massively parallel computation (MPC) model. For the congested clique, we obtain an algorithm with time complexity $O(\log \Delta \cdot \log \log \Delta)$, for the MPC model, we obtain algorithms with round complexity $O(\log^2 \Delta)$ for the linear-memory regime and $O(\log^2 \Delta + \log n)$ for the sublinear memory regime.

¹Supported by the European Union's Horizon 2020 Research And Innovation Programme under grant agreement no. 755839.

1 Introduction

In the distributed message passing model, a communication network is abstracted as an n -node graph $G = (V, E)$. The nodes of G host processors that communicate with each other through the edges of the graph. In the context of distributed graph algorithms, the objective is to solve some graph problem on G by a distributed message passing algorithm. One of the most important and most extensively studied problems in the area is the *distributed graph coloring problem*, where we need to compute a proper (vertex) coloring of the communication graph G . Typically, at the beginning of an algorithm, the nodes of G do not know anything about G , except maybe the names of their immediate neighbors and at the end of an algorithm, each node of G needs to know its local part of the solution of the given graph problem (e.g., for distributed coloring, at the end, each node must know its own color). The two classic models in which distributed graph algorithms have been studied are the LOCAL and the CONGEST model [Lin92, Pel00]. In both models, time is divided into synchronous rounds and in each round, each node can perform arbitrary internal computations and send a message to each of its neighbors. The time complexity of an algorithm is the number of rounds required for the algorithm to terminate. In the LOCAL model, messages can be of arbitrary size, whereas in the CONGEST model, all messages have to be of size $O(\log n)$ bits.

Distributed Graph Coloring. Computing a coloring with the optimal number of colors $\chi(G)$ was one of the first problems known to be NP-complete [Kar72]. In the distributed setting, one therefore aims for a more relaxed goal and the usual objective is to color a given graph G with $\Delta + 1$ colors, where Δ is the maximum degree of G [BE13]. Note that any graph admits such a coloring and it can be computed by a simple sequential greedy algorithm. Despite the simplicity of the sequential algorithm, the question of determining the distributed complexity of computing a $(\Delta + 1)$ -coloring has been an extremely challenging question. In particular, while $O(\log n)$ -time randomized distributed $(\Delta + 1)$ -coloring algorithms have been known for more than 30 years, the question whether a similarly efficient (i.e., polylogarithmic time) *deterministic* distributed coloring algorithm exists remained one of the most important open problems in the area [BE13, GKM17] until it was resolved very recently by Rozhoň and Ghaffari [RG19]. In [RG19] the question was answered in the affirmative for the LOCAL model by designing an efficient deterministic distributed method to decompose the communication graph into a logarithmic number of subgraphs consisting of connected components (clusters) of polylogarithmic (weak) diameter, a structure known as a *network decomposition* [AGLP89]. It was known before that an efficient deterministic algorithm for network decomposition would essentially imply efficient deterministic LOCAL algorithms for all problems for which efficient randomized algorithms exist [Lin92, AGLP89, BE13, GKM17, GHK18].

Note that due to the unbounded message size any (solvable) problem can be solved in *diameter* time in the LOCAL model by simply collecting the whole graph topology at one node, solving the problem locally (potentially using unbounded computational power), and redistributing the solution to the nodes. Thus the small diameter components of a network decomposition almost immediately give rise to an efficient $(\Delta + 1)$ -coloring algorithm in the LOCAL model. In light of the breakthrough by Rozhoň and Ghaffari [RG19], which implies that a polylogarithmic-time deterministic $(\Delta + 1)$ -coloring algorithm exists in the LOCAL model, it is natural to ask whether a polylogarithmic-time deterministic algorithm also exists in the more restricted, but seemingly also more realistic CONGEST model. As the main result of this paper, we answer this question in the affirmative.

1.1 Our Contributions in CONGEST

The main technical contribution of this work is to provide an efficient deterministic CONGEST model algorithm for the $(\Delta + 1)$ -coloring problem, and more generally the $(\text{degree} + 1)$ -list coloring problem in time proportional to the diameter of the graph. By using the network decomposition algorithm by Rozhoň and Ghaffari [RG19], the result also implies efficient CONGEST algorithms for general graphs even if the diameter is large.

Given a graph $G = (V, E)$, a *color space* $[C]$ and color lists $L(v) \subseteq [C]$ for each $v \in V$, a *list-coloring* of G is a proper C -coloring such that each node is colored with a color from its list. In this paper we consider the $(\text{degree} + 1)$ -list coloring problem, where the list sizes are $|L(v)| = \deg(v) + 1$. Throughout the paper we assume that each color from each node's list fits in $O(1)$ messages in the CONGEST model, i.e., we only

consider list-coloring instances with $C = \text{poly } n$. Whenever we do not explicitly mention the color space we assume $C = \text{poly } \Delta$. Note that just as the $(\Delta + 1)$ -coloring problem the $(\text{degree} + 1)$ -list coloring problem admits a simple sequential greedy algorithm.

While in the LOCAL model, the diameter of the graph is a trivial upper bound on the time needed to solve any graph problem, it is not clear per se whether a small diameter also helps for solving problems in the CONGEST model. So far, there are a few examples where a small diameter helps in the CONGEST model. In particular, the problems of computing a maximal independent set, a sparse spanner, and an $(1 + \epsilon) \log \Delta$ -approximation of a minimum dominating set can all be solved deterministically in time $D \cdot \text{polylog } n$ [CPS17, GK18, DKM19]. Other problems cannot profit from small diameter, e.g., verifying or computing a minimum spanning tree requires $\tilde{\Omega}(D + \sqrt{n})$ CONGEST rounds [DHK⁺11] and solving many optimization problems exactly (minimum dominating set, vertex cover, chromatic number) or almost exactly (maximum independent set) requires $\tilde{\Omega}(n^2)$ CONGEST rounds even if the diameter of the graph is constant [CKP17, BCD⁺19].

We prove the following theorem (when assuming $C \leq \text{poly } \Delta$).

Theorem 1.1 (simplified). *There is a deterministic CONGEST algorithm that solves the list-coloring problem for instances $G = (V, E)$ with $|L(v)| \geq \deg(v) + 1$ in time $O(D \cdot \log n \cdot \log^2 \Delta)$.*

The algorithm to obtain Theorem 1.1 is based on a similar basic strategy as the algorithms in [CPS17, GK18, DKM19], which achieve similar time complexities for other graph problems. More specifically, the proof of Theorem 1.1 relies on designing a 0-round randomized process that in expectation colors a constant fraction of the vertices. Then, we derandomize this process and iterate $O(\log n)$ times until all nodes are colored. In Section 1.4 we elaborate on the challenges that occur with this approach and how we approach them.

The most important implication of the result in Theorem 1.1 is that it can be lifted to an efficient, i.e., $\text{polylog } n$ time algorithm for general graphs, even for graphs with large diameter.

Corollary 1.2. *There is a deterministic $O(\log^8 n)$ -round CONGEST algorithm for the $(\text{degree} + 1)$ -list-coloring problem.*

The proof of Corollary 1.2 is based on iterating through the color classes of a *suitable network decomposition* and applying Theorem 1.1 on the clusters of the same color [AGLP89, RG19]. Many network decomposition algorithms, in particular the one in [RG19], only compute so-called *weak-diameter network decompositions* in which the diameter of components is only small if edges and vertices outside the component can be used for communication. One needs additional care to use these decompositions in the CONGEST model. For more details on the definition of a suitable network decomposition we refer to Section 3 and [RG19]. We want to point out that improvements in computing such network decompositions immediately carry over to Corollary 1.2.

Corollary 1.2 is a drastic improvement over the state of the art even for the standard $(\Delta + 1)$ -coloring problem: Surprisingly until the beginning of 2019 the best deterministic CONGEST algorithm for the $(\Delta + 1)$ -coloring problem was the $O(\Delta^{3/4} + \log^* n)$ algorithm by Barenboim [Bar15, BEG18]. Even though the objective of [Bar15] was to optimize the runtime mainly as a function of the maximum degree Δ , the paper also provided the fastest known algorithm if the runtime is solely expressed as a function of the number of nodes, i.e., it provided an $O(n^{3/4})$ round CONGEST algorithm. Very recently, the runtime for $(\text{degree} + 1)$ -list coloring was improved to $2^{O(\sqrt{\log \Delta})} \cdot \log n = 2^{O(\sqrt{\log n})}$ rounds [Kuh20]. The algorithm in [Kuh20] does work in the CONGEST model but it does not rely on network decompositions. Hence its runtime does not improve with the recent breakthrough result by Rozhoň and Ghaffari [RG19].

1.2 Our Contributions in the CONGESTED CLIQUE and MPC

The techniques of Theorem 1.1 can also be adapted in an almost direct way to yield simple deterministic algorithms in the CONGESTED CLIQUE and the MPC model. By using the additional power in those models, we can speed up some parts of our derandomization. Because the main focus of our paper is on the CONGEST model algorithm, the limited space in the main body of the paper is used for our CONGEST results and all the proofs for the CONGESTED CLIQUE and the MPC model are moved to Section 4.

The CONGESTED CLIQUE model [LPPP03]: The CONGESTED CLIQUE model differs from the CONGEST model in the way that the input graph might be different from the communication network. Given an input graph $G = (V, E)$ consisting of n nodes, in each round, each node $u \in V$ can send a message of size $O(\log n)$ to each other node $v \in V$ in the graph (i.e., although G might be an arbitrary graph, the communication graph is a complete graph on the nodes V). Initially, each node only knows its neighbors in G . More specifically, we consider the UNICAST CONGESTED CLIQUE model, in which nodes are allowed to send a different message to each other node in each round.

We prove the following result.

Theorem 1.3 (CONGESTED CLIQUE). *There is a deterministic CONGESTED CLIQUE algorithm that solves the $(\text{degree} + 1)$ -list-coloring problem in time $O(\log \Delta \log \log \Delta)$.*

The runtime of Theorem 1.3 is faster than the runtime of Theorem 1.1 due to the following reasons. First, due to all-to-all communication, we can avoid the diameter term in the runtime. Further, the $O(\log n)$ factor can be turned into a $O(\log \Delta)$ factor as we can send a subgraph to a single vertex of the clique and solve the problem locally as soon as the subgraph consists of at most n/Δ vertices which is achieved after $O(\log \Delta)$ rounds. In fact, this can even be achieved within $O(\log \log \Delta)$ rounds because with each phase in which a constant fraction of the nodes is colored, the routing capabilities compared to the number of remaining nodes is increased, accelerating the process of choosing a color for each node. Finally, $\Omega(\log \Delta)$ rounds of our derandomization procedure can be compressed into $O(1)$ rounds in the CONGESTED CLIQUE using the routing capabilities of the model.

We emphasize that while Theorem 1.3 provides the best known deterministic CONGESTED CLIQUE algorithm for $(\text{degree} + 1)$ -list-coloring, it does not improve the state of the art for the slightly weaker $(\Delta + 1)$ -list coloring problem. In [Par18b, Par18a], Parter provides a $O(\log \Delta)$ -round deterministic algorithm CONGESTED CLIQUE algorithm for this problem.² Although Theorem 1.3 only improves the state of the art for a very special case, we still like to mention it, as the result almost immediately follows from our CONGEST algorithm.

The MPC model [KSV10, ANOY14]: In the MPC model, an input graph $G = (V, E)$ is distributed in a worst case manner among $M = \tilde{O}\left(\frac{|V|+|E|}{S}\right)$ machines, each having a memory of S words. S is a parameter of the model, a word consists of $O(\log |V|)$ bits and $\tilde{O}$ hides poly $\log |V|$ factors that can be chosen arbitrarily by the designer of an algorithm. Time progresses in synchronous rounds in which machines exchange messages. In one round, every machine is allowed to send a (different) message to each other machine such that the size of all messages sent and received by a machine does not exceed its local memory. Additionally, each machine can perform an arbitrary local computation on its stored data. At the end of computation, each machine outputs a part of the solution which may not exceed its local memory. So for the coloring problem each machine is responsible for the output of some of the nodes and has to output their colors. The complexity of a deterministic MPC algorithm is the number of synchronous rounds until the problem is solved. We say that the MPC model works with *linear memory* if $S = \tilde{O}(|V|)$ and with *sublinear memory* if there exists some constant $0 < \alpha < 1$ and $S = \tilde{O}(n^\alpha)$.

The algorithm of Theorem 1.3 can also be implemented in the deterministic MPC model with linear memory, but without the additional improvement of turning the $\log \Delta$ into a $\log \log \Delta$ factor. However, additional care is needed to reason that none of the steps of the algorithm ever exceeds the memory of a machine, i.e., a machine never sends, receives nor stores more than $S = \tilde{O}(n)$ words.

Theorem 1.4 (MPC, linear memory). *There is a deterministic MPC algorithm that solves the $(\text{degree} + 1)$ -list-coloring problem in $O(\log^2 \Delta)$ rounds with linear memory.*

For the sublinear memory regime we obtain the following result. The basic algorithm is the same as the one for the linear memory regime. Since in the sublinear memory regime, the neighborhood of a single node might not fit on a single machine, we have to use and adapt some standard MPC for handling operations like aggregation of a function over a single neighborhood or updating the color lists of all nodes after a partial coloring step (e.g., the last problem corresponds to designing an MPC algorithm to compute the

²A bug in the deterministic CONGESTED CLIQUE algorithm in the conference version [Par18b] has been fixed in [Par18a].

intersection between two sets of size N , if machines with a local memory of N^ϵ are available). These basic MPC computations appear in Section 5.

Theorem 1.5 (MPC, sublinear memory). *There is a deterministic MPC algorithm that solves the $(\text{degree} + 1)$ -list-coloring problem in $O(\log^2 \Delta + \log n)$ rounds with sublinear memory.*

We remark that in independent work, Czumaj, Davies, and Parter [CDP19] have developed another deterministic $(\text{degree} + 1)$ -list coloring algorithm for the sublinear memory MPC model. The algorithm of [CDP19] achieves a time complexity of $O(\log \Delta + \log \log n)$ and it thus is significantly faster than our algorithm. In order to achieve this faster running time, the authors of [CDP19] have to make the assumption that even if the graph is sparse and consists of only $n^{1+o(1)}$ or even $\tilde{O}(n)$ edges, the MPC algorithm needs at total memory of $\Omega(n^{1+\alpha})$ for some constant $\alpha > 0$. In our results, the total memory is of order $\tilde{O}(m + n)$, if m denotes the number of edges of G . We also believe that our algorithm is of interest because in our opinion, both our algorithm and the analysis are substantially simpler than the algorithm and analysis of [CDP19].

1.3 Related Work

We continue with a short overview on the most important distributed graph coloring algorithms in the LOCAL and CONGEST model. For a more detailed discussion of previous work on distributed graph coloring we refer to [BE13, Kuh20] for deterministic algorithms and [CLP18] for randomized algorithms.

Deterministic Distributed Coloring: The work on distributed coloring started more than 30 years ago with work on several symmetry breaking problems in the parallel setting [ABI86, CV86, GPS88, Lub86] and a seminal paper by Linial [Lin92] that introduced the LOCAL model for solving graph problems in a distributed setting. Linial showed that a graph can be colored (deterministically) in $O(\log^* N)$ rounds with $O(\Delta^2)$ colors and that $\Omega(\log^* N)$ rounds are necessary even for graphs of degree 2 where N is the size of the identifier space.³ Even though these algorithms and lower bounds were devised for the LOCAL model, all of them also directly apply to the CONGEST model. If randomization is allowed, already the early works imply that a $(\Delta + 1)$ -coloring can always be computed in $O(\log n)$ rounds, even in the CONGEST model [ABI86, Lub86, Lin92, Joh99].

The focus of our current work is to express the complexity of distributed graph coloring in the CONGEST model as a function of n , i.e, the number of nodes of the network. Despite ample attention to the problem in the LOCAL model, the $2^{O(\sqrt{\log n})}$ -time solution of [PS95] has been the state of the art until the recent breakthrough by Rozhoň and Ghaffari [RG19], which provided the first polylog n -time algorithm. However, to the best of our knowledge and somewhat surprisingly there are no published results on the $(\Delta + 1)$ -coloring problem in the CONGEST model, when runtime is expressed solely as a function of n . But there has been extensive work on determining the problem's round complexity in terms of the maximum degree Δ and most of these algorithms also work in CONGEST: A simple single-round color elimination scheme combined with Linial's $O(\Delta^2)$ -coloring algorithm provided an $O(\Delta \log \Delta + \log^* n)$ algorithm [SV93, KW06]. This was improved to $O(\Delta + \log^* n)$ rounds by using a divide-and-conquer approach based on defective colorings [BE09, Kuh09]. The first and only sublinear in Δ algorithm in the for $(\Delta + 1)$ -coloring was obtained by Barenboim and used $O(\Delta^{3/4} + \log^* n)$ rounds [Bar15, BEG18]. The current state of the art in the LOCAL model uses $\tilde{O}(\sqrt{\Delta} + \log^* n)$ rounds, but it does not extend to CONGEST [FHK16, BEG18]. There are faster algorithms if the final coloring can use more than $\Delta + 1$ colors: [BE10] shows that coloring with $O(\Delta^{1+\epsilon}) \gg \Delta + 1$ colors for some constant $\epsilon > 0$ can be done in $O(\log \Delta \log n)$ rounds. If one desires to reduce the allowed communication from $O(\log n)$ bits per round to a single bit per round, Barenboim, Elkin and Goldenberg provided algorithm that uses $O(\Delta + \log n + \log^* n)$ rounds and colors with $O(\Delta)$ colors [BEG18]. In its original version the algorithm computes an $O(\Delta)$ -coloring in $O(\Delta + \log^* n)$ rounds in the standard CONGEST model.

While there has been extensive progress on upper bounds, the original $\Omega(\log^* n)$ lower bound by Linial is still the best known lower bound on the $(\Delta + 1)$ -coloring problem. It was recently shown that in a weak

³The function $\log^* x$ denotes the number of iterated logarithms needed to obtain a value at most 1, that is, $\forall x \leq 1 : \log^* x = 0$, $\forall x > 1 : \log^* x = 1 + \log^* \log x$. As most results in the area assume that the identifier space N is of size $\text{poly}(n)$ Linial's lower bound and upper bounds are usually used as $\Omega(\log^* n)$ and $O(\log^* n)$; we do the same.

version of the LOCAL model (called the SET-LOCAL model), the $(\Delta + 1)$ -coloring problem has a lower bound of $\Omega(\Delta^{1/3})$ [HMKS16].

Randomized Distributed Coloring: There has also been a lot of work on understanding the randomized complexity of the distributed coloring problem [KSOS06, SW10, BEPS12, PS13, HSS16, GHKM18, CLP18]. Most of the work focuses on the LOCAL model and a particularly important contribution was provided by Barenboim, Elkin, Pettie, and Schneider [BEPS12], who introduced the so-called graph shattering technique to the theory of distributed graph algorithms. The paper shows that a $(\Delta + 1)$ -coloring can be computed in time $O(\log \Delta) + 2^{O(\sqrt{\log \log n})}$ in the LOCAL model. [Gha19] showed that the same can be done in the CONGEST model and in both algorithms the $2^{O(\sqrt{\log \log n})}$ term can most likely be reduced with the result from [RG19]. The state of the art for randomized $(\Delta + 1)$ -coloring in the LOCAL model is the graph shattering based poly log log n algorithm by Chang et al. [CLP18, RG19] that does not translate to the CONGEST model.

$(\Delta + 1)$ -Coloring in the CONGESTED CLIQUE and MPC: In the special case of $\Delta = O(n^{1/3})$ the MIS algorithm in [CPS17] combined with a well-known reduction from the $(\Delta + 1)$ -coloring problem to the MIS problem [Lub86, Lin92] can be used to deterministically compute a $(\Delta + 1)$ -coloring in $O(\log \Delta)$ rounds. Building up on the result from [CPS17] Parter provided an $O(\log \Delta)$ deterministic algorithm [Par18b]. All other results in the CONGESTED CLIQUE and the MPC model are randomized: [CFG⁺19] provides a $O(1)$ -round algorithm in the CONGESTED CLIQUE and a $O(\sqrt{\log \log n})$ round randomized algorithm for the MPC model with sublinear memory. Previously Assadi et al. [ACK19] provided an $O(1)$ randomized algorithm in the MPC model in the linear memory regime, i.e., with memory $\tilde{O}(n)$.

Derandomization in the CONGEST Model: As pointed out earlier [CPS17, GK18, DKM19] use a similar derandomization strategy for other graph problems. [CPS17] computes an MIS in $\tilde{O}(D)$ rounds and uses the same strategy to obtain deterministic algorithms for spanners. [GK18] computes a $O(\log^2 n)$ approximation for the minimum dominating set problems and [DKM19] computes a $(1 + \epsilon) \log \Delta$ -approximation for the minimum dominating set problem for any constant $\epsilon > 0$. We cite [CPS17]:

This work opens a window to many additional intriguing questions. First, we would like to see many more local problems being derandomized despite congestion restrictions.

Despite the fact that [CPS17, GK18, DKM19] and the current paper use the same derandomization strategy, applying it to further graph problems is unfortunately non-black-box.

Kawarabayashi and Schwartzman [KS18] also use the concept of derandomization in the CONGEST model. Their approach relies on iterating through the color classes of a given coloring; by only considering a suitably chosen subgraphs and defective colorings they obtain several algorithms for various cut problems including a deterministic $O(\epsilon^{-2} \log \Delta + \log^* n)$ round algorithm for an $(1/2 - \epsilon)$ -approximation of the *max cut problem*.

1.4 Our Derandomization in a Nutshell

General derandomization strategy. We use the general derandomization strategy as recently introduced by Censor-Hillel, Parter, and Schwartzman in [CPS17] and afterwards also used in [GK18, DKM19]. We start with a simple and efficient randomized algorithm that is guaranteed to make good progress in expectation. By using the method of conditional expectations (see e.g., [MU05, Chapter 6.3]), we then turn this randomized algorithm into a deterministic CONGEST algorithm with a time complexity of $D \cdot \text{polylog } n$. Finally, in combination with the new polylogarithmic-time network decomposition algorithm of [RG19], the running time of the algorithm can be reduced from $D \cdot \text{polylog } n$ to only $\text{polylog } n$.

A bit more specifically, assume that we have a random variable X_v that measures the progress of each node $v \in V$ in our given randomized algorithm such that $X := \sum_{v \in V} X_v$ measures the global progress of the algorithm. Assume for example that a small value of X implies fast progress, whereas a large X implies slow progress (in the context of coloring X could for example measure the number of conflicts in a single random coloring step). Assume further that we can reasonably upper bound the expected value $E[X]$ of X even if the random choices of the nodes in the randomized algorithm are only k -wise independent for some $k = \text{polylog } n$ (i.e., for any subset of k nodes, the choices are independent). It is well-known that a

set of n polylog n -wise independent random bits can be generated from only polylog n independent random bits [Vad12]. The algorithm can therefore be implemented with a shared random seed of polylog n bits and we can use the method of conditional expectations to *deterministically* find an assignment to these polylog n shared bits for which the value of X is not larger than its expectation. When implementing the algorithm in the CONGEST model, we deterministically fix the polylog n bits of the random seed one-by-one, where fixing a single bit involves a global aggregation for computing the conditional expectations of $E[X]$ based on setting the bit to 0 or 1. One bit of the random seed can therefore be fixed in $O(D)$ time in the CONGEST model.

Computing a partial coloring. The arguably most natural distributed random coloring algorithm is to let each node choose a color from its list uniformly at random [Joh99]. For the expected number of conflicts X_v of a node v we have

$$E[X_v] = \sum_{u \in \Gamma_v} \frac{|L(u) \cap L(v)|}{|L(u)| \cdot |L(v)|} \leq \sum_{u \in \Gamma_v} \frac{|L(u)|}{|L(u)| \cdot |L(v)|} = \deg(v) \cdot \frac{1}{|L(v)|} < 1. \quad (1)$$

Note that for (1) to hold, we need only pairwise independent choices of the colors. It follows that the expected number of conflicts is $\sum_{v \in V} E[X_v] < n$. The derandomization by the method of conditional expectations would then choose a color for each node such that $\sum_{v \in V} X_v \leq \sum_{v \in V} E[X_v] < n$, i.e., the number of conflicts is upper bounded by its expectation which is at most n . It follows that at least half of the nodes have $X_v \leq 1$, i.e., at most one neighbor that has chosen the same color and thus at least half of these nodes can keep their color. The whole process can then be repeated for $O(\log n)$ iterations to color all vertices. However, in order to compute the conditional expectation of X_v , v needs to know the lists of its neighbors which is too expensive to acquire in the CONGEST model.

Computing Conditional Expectations. Therefore we choose another approach which is inspired by the algorithm of [Kuh20]: Let the global color space be $[C]$ for some integer C (i.e., for each $v \in V$, we have $L(v) \subseteq [C]$). Each color thus has a binary representation of $\log C$ bits. We define a process where we fix each node's color bit-by-bit, i.e., we run $\log C$ phases where in each phase, each node fixes the next bit of its color. Each time a node v has fixed a bit, its list $L(v)$ is reduced to the subset of colors which have the sequence of bits that we have fixed so far as prefix and as soon as all bits have been fixed, each node has picked a candidate color. We show that if the color prefixes are extended with the correct probabilities, this process colors a constant fraction of the vertices in expectation. One can also view it as a slowed down version of directly taking a color from the list uniformly at random. Now we apply the aforementioned derandomization technique only to the zero-round algorithm of choosing a single bit of the color prefix. The benefit of this approach is that it admits a pessimistic estimator of Equation (1) that allows the efficient computation of conditional expectations.

Shorter Random Seeds. In [CPS17, GK18, DKM19] the length of the shared random seed is polylog n . As the seed length appears as a factor in the runtime of the resulting deterministic algorithms, one wishes to keep it as short as possible. In our algorithms we manage to reduce the seed length to $O(\log \Delta + \log \log C)$ bits; in particular the seed length is independent of n . The main ingredient for a shorter seed length is the observation that pairwise independent random coins for adjacent nodes are sufficient in our randomized algorithms and these coins can be produced from a random seed whose length does not depend on n . This observation might be helpful for derandomizing other algorithms.

2 Degree+1 List Coloring in Diameter Time

Throughout, let D denote the diameter of a graph. Often we run algorithms on subgraphs of a graph; however, all our algorithms can be implemented such that D always refers to the diameter of the original communication graph. For $C \in \mathbb{N}$ we introduce the notation $[C] := \{0, \dots, C-1\}$. Given a graph $G = (V, E)$, a *color space* $[C]$ and *color lists* $L(v) \subseteq [C]$ for each $v \in V$, a *list-coloring* $\phi : V \rightarrow [C]$ of G is a proper C -coloring such that each node is colored with a color from its list, i.e, for any edge $\{u, v\} \in E$ we have

$\phi(u) \neq \phi(v)$ and for all $v \in V$ we have $\phi(v) \in L(v)$. In this paper we consider the $(\text{degree} + 1)$ -list-coloring problem, where $|L(v)| = \deg(v) + 1$ for each $v \in V$.

As our main technical contribution, we show that we can list-color a constant fraction of the nodes of a graph.

Lemma 2.1. *There is a deterministic CONGEST algorithm that given a list-coloring instance $G = (V, E)$ with color space $[C]$, lists $L(v) \subseteq [C]$ for which $|L(v)| \geq \deg(v) + 1$ holds for all $v \in V$ and an initial K -coloring of G , list-colors a $1/8$ fraction of the nodes in $O(D \cdot \log C \cdot (\log \Delta + \log K + \log \log C))$ rounds.*

When the result is applied to a subgraph of a communication graph G , $\deg(v)$ refers to the degree of v in the subgraph and Δ to the maximum degree of the subgraph, but the diameter D refers to the diameter of G .

Before we explain the algorithm of Lemma 2.1 we show that it directly implies the following theorem.

Theorem 1.1 *There is a deterministic CONGEST algorithm that solves the list-coloring problem for instances $G = (V, E)$ with $L(v) \subseteq [C]$ and $|L(v)| \geq \deg(v) + 1$ in time $O(D \cdot \log n \cdot \log C \cdot (\log \Delta + \log \log C))$.*

Proof. First we use Linial's coloring algorithm ([Lin92]) to compute a $K = O(\Delta^2)$ coloring of the graph in $O(\log^* n)$ rounds. This coloring is used as the input coloring to $O(\log n)$ iterations of Lemma 2.1. In each iteration $i = 0, \dots, O(\log n)$ we color a constant fraction of the still uncolored vertices and after the iteration each still uncolored vertex removes the colors of newly colored neighbors from its list. As a node only removes a color from its list if also its 'uncolored degree' drops, the residual graph G_i that is induced by the still uncolored nodes after iteration i forms a feasible instance for Lemma 2.1, i.e., it satisfies the condition $|L(v)| \geq \deg_{G_i}(v) + 1$ for all $v \in V(G_i)$. Thus after $O(\log n)$ iterations each vertex is colored with a color from its initial list and the total runtime is

$$O(D \cdot \log n \cdot \log C \cdot (\log \Delta + \log K + \log \log C)) = O(D \cdot \log n \cdot \log C \cdot (\log \Delta + \log \log C)) \quad \square$$

In the introduction we presented a simplified version of Theorem 1.1 by setting $C = \text{poly } \Delta$.

Remark. When applying Theorem 1.1 to disconnected subgraphs the diameter term in the runtime can be substituted by the maximum diameter of the connected components.

We now continue by explaining the ideas of the algorithm of Lemma 2.1; the formal proof of Lemma 2.1 appears at the very end of Section 2. Note that the given initial K -coloring is only used for symmetry breaking purposes and does not relate to the lists of the nodes.

General Algorithmic Idea: In the algorithm of Lemma 2.1, every node deterministically (and tentatively) selects a color from its list such that a constant fraction of nodes can permanently keep their selected color. We now describe this selection process in more detail: Given a list-coloring instance $G = (V, E)$ with color space $[C]$, each color is represented by a bitstring of length $\lceil \log C \rceil$ (e.g., color 2 is represented as the bit string 0...010 and not just as the bit string 10). Our algorithm operates in $\lceil \log C \rceil$ phases and in each phase we determine one further bit of each node's color. That is, each $u \in V$ maintains a bitstring $s(u)$ with the property that $s(u)$ is the prefix of some color(s) in $L(u)$, starting with $s(u) = s_0(u)$ being the empty string and successively extending the prefix $s(u)$ by one bit per phase. We write $s_\ell(u)$ for the bitstring that node u has chosen after phase ℓ . The string $s_{\lceil \log C \rceil}(u)$ corresponds to the tentative color that u selects. For $\ell = 1, \dots, \lceil \log C \rceil$ we define

$$L_\ell(u) := \{x \in L(u) \mid \text{prefix of } x \text{ is } s_\ell(u)\}$$

as the set of u 's *candidate colors* at the end of phase ℓ , i.e., the set of colors in $L(u)$ that start with $s_\ell(u)$. We note that our algorithm chooses all prefixes $s_\ell(u)$ in such a way that $L_\ell(u)$ is always non-empty for all ℓ and $u \in V$. We further define the remaining *conflict graph* after iteration ℓ as

$$G_\ell := (V, E_\ell), \text{ where } E_\ell := \{\{u, v\} \in E \mid s_\ell(u) = s_\ell(v)\},$$

and the remaining *conflict degree* $\deg_\ell(u) := \deg_{G_\ell}(u)$. That is, in graph G_ℓ any edge of G is considered as deleted as soon as its nodes choose different prefixes. To ensure that a constant fraction of the vertices can keep their selected color we need a suitable measure of progress for the extension of prefixes, that is,

we need a potential function that captures the ‘*usefulness*’ of the prefixes for our purpose. Informally, the potential relates (but does not equal!) to the expected number of monochromatic edges if each node chooses a random candidate color from its list, i.e., a random color that is consistent with its current prefix. We define the following **potential function**

$$\Phi_\ell(u) := \frac{\deg_\ell(u)}{|L_\ell(u)|}.$$

At the beginning, when all prefixes are empty, we have $\Phi_0(u) < 1$ for all $u \in V$ and thus $\sum_{u \in V} \Phi_0(u) < n$. We will give an algorithm that extends all prefixes bitwise while keeping the overall increase of the potential small such that when all $\ell = \lceil \log C \rceil$ bits are fixed, we still have $\sum_{u \in V} \Phi_\ell(u) \leq 2n$. It follows that a constant fraction of the nodes u have $\Phi_\ell(u) < 4$. At this stage all nodes have selected a single candidate color, i.e., $|L_\ell(u)| = 1$ for all $u \in V$. Thus $\Phi_\ell(u)$ equals the number of neighbors v of u with the same candidate color. Hence a constant fraction of the vertices has at most 3 neighbors that have the same selected color which is sufficient to permanently color a constant fraction of the vertices of G .

In Section 2.1 we show that using biased coin flips to determine the next bit of the prefix yields a 0-round randomized algorithm that, *in expectation*, has no increase in the potential even if the nodes only use pairwise independent coin flips (Lemma 2.2). In the same section we show that the expected increase of the potential is small if the probabilities of the coin flips are chosen slightly inaccurate (Lemma 2.3).

In Section 2.2 we show that such biased coin flips can be deterministically produced from a short random seed (Lemma 2.5). Thus, over the randomness of the seed, the expected potential increase is small. In the following we use the method of conditional expectation and a BFS tree to derandomize this algorithm, i.e., we *deterministically* pick a *good* random seed that incurs only a small increase in the potential (Lemma 2.6).

2.1 Extending Prefixes: Zero Round Randomized Algorithms

To fix bit ℓ of all prefixes (that we describe by Algorithm 1) each node flips a coin to determine its ℓ -th bit. The bit and also the coin equals 1 with probability $p_u := \frac{k_1(u)}{|L_{\ell-1}(u)|}$ where $L_{\ell-1}(u)$ is the list of current candidate colors and $k_1(u) := |\{x \in L_{\ell-1}(u) \mid x[\ell] = 1\}|$ is the number of candidate colors whose ℓ -th bit equals 1. Thus p_u is the fraction of candidate colors whose ℓ -th bit equals 1. This process can be seen as a slowed down version of selecting a color from the initial list uniformly at random as iterating this process for $\lceil \log C \rceil$ times yields the same probability for each color to be selected. However, we do not know how to immediately derandomize the non slowed down process.

Algorithm 1 Randomized One Bit Prefix Extension

Input: Bitstring $s_{\ell-1}(u)$ of length $\ell - 1$ for all $u \in V$

for each node u in parallel **do**

$p_u := \frac{k_1(u)}{|L_{\ell-1}(u)|}$ where $k_1(u) := |\{x \in L_{\ell-1}(u) \mid x[\ell] = 1\}|$

Coin Flip: Set $s_\ell(u) = s_{\ell-1}(u) \circ 1$ with probability p_u and $s_\ell(u) = s_{\ell-1}(u) \circ 0$ otherwise
($\circ$ represents the concatenation of strings)

Lemma 2.2. *Let $\ell \leq \lceil \log C \rceil$ and assume the prefixes $s_{\ell-1}(v)$ are fixed for all nodes v . Let all nodes choose the ℓ -th bit according to Algorithm 1. Then we obtain*

$$E \left[\sum_{v \in V} \Phi_\ell(v) \right] \leq \sum_{v \in V} \Phi_{\ell-1}(v) \quad (2)$$

if the coin flips in Algorithm 1 of adjacent nodes are independent. Furthermore, the list of candidate colors of each node never becomes empty.

Proof. We can write the sum of the potentials of all nodes as

$$\sum_{v \in V} \Phi_\ell(v) = \sum_{\{u, v\} \in E_\ell} \left(\frac{1}{|L_\ell(u)|} + \frac{1}{|L_\ell(v)|} \right).$$

For each edge $e = \{u, v\} \in E_{\ell-1}$ we introduce a random variable

$$X_e = \mathbb{1}_{e \in E_\ell} \left(\frac{1}{|L_\ell(u)|} + \frac{1}{|L_\ell(v)|} \right)$$

which can be seen as the contribution of e to the potential. Edge e survives the ℓ -th phase if either both endpoints choose 1 as their ℓ -th bit, which happens with probability $p_u p_v$ due to the pairwise independence of the bit-choice, or if both choose 0 as their ℓ -th bit, which happens with probability $(1 - p_u)(1 - p_v)$. In the first case we obtain $|L_\ell(u)| = p_u |L_{\ell-1}(u)|$ and $|L_\ell(v)| = p_u |L_{\ell-1}(v)|$ and in the second case $|L_\ell(u)| = (1 - p_u) |L_{\ell-1}(u)|$ and $|L_\ell(v)| = (1 - p_u) |L_{\ell-1}(v)|$. To compute $E[X_e]$ we hence define

$$A := \begin{cases} p_u p_v \left(\frac{1}{p_u |L_{\ell-1}(u)|} + \frac{1}{p_v |L_{\ell-1}(v)|} \right) & \text{if } p_u, p_v > 0 \\ 0 & \text{else} \end{cases}$$

$$B := \begin{cases} (1 - p_u)(1 - p_v) \left(\frac{1}{(1 - p_u) |L_{\ell-1}(u)|} + \frac{1}{(1 - p_v) |L_{\ell-1}(v)|} \right) & \text{if } p_u, p_v < 1 \\ 0 & \text{else} \end{cases}$$

and obtain

$$\begin{aligned} E[X_e] &= A + B \leq p_u p_v \left(\frac{1}{p_u |L_{\ell-1}(u)|} + \frac{1}{p_v |L_{\ell-1}(v)|} \right) + (1 - p_u)(1 - p_v) \left(\frac{1}{(1 - p_u) |L_{\ell-1}(u)|} + \frac{1}{(1 - p_v) |L_{\ell-1}(v)|} \right) \\ &= \frac{p_v}{|L_{\ell-1}(u)|} + \frac{p_u}{|L_{\ell-1}(v)|} + \frac{(1 - p_v)}{|L_{\ell-1}(u)|} + \frac{(1 - p_u)}{|L_{\ell-1}(v)|} = \frac{1}{|L_{\ell-1}(u)|} + \frac{1}{|L_{\ell-1}(v)|} . \end{aligned}$$

It follows

$$E \left[\sum_{v \in V} \Phi_\ell(v) \right] = E \left[\sum_{e \in E_{\ell-1}} X_e \right] \leq \sum_{\{u, v\} \in E_{\ell-1}} \left(\frac{1}{|L_{\ell-1}(u)|} + \frac{1}{|L_{\ell-1}(v)|} \right) = \sum_{v \in V} \Phi_{\ell-1}(v) .$$

The lists of candidate colors never becomes empty as vertices only choose to extend their prefix by 0 (or 1 respectively) if they also have a candidate color with the respective extension; for this property to hold we merely need that the probabilities $p_v \in \{0, 1\}$ are exactly represented. $\square$

We will not immediately derandomize the described procedure but a very similar one where nodes produce their biased random coins to represent the probabilities p_v from a common short random seed. Then, in the derandomization process, we will find a *good* seed from which nodes can determine the values of their coins. Producing biased coins from the common random seed implies that not all probabilities can be produced, in fact, instead of having a coin that equals 1 with an arbitrary probability p_v we can only produce probabilities of the type $k/2^b$ for some large enough b that we will chose later. That is, each p_v can only be approximated up to some $\varepsilon = \Theta(2^{-b})$. The next lemma shows that the expected increase of the potential can be kept small with these inaccurate probabilities.

Lemma 2.3. *Let $\ell \leq \lceil \log C \rceil$ and assume the prefixes $s_{\ell-1}(v)$ are fixed for all nodes v . Let all nodes choose the ℓ -th bit according to Algorithm 1, but with the following adjustment: For each node v , if $p_v = 0$ or $p_v = 1$, then v chooses 1 as its ℓ -th bit with probability 0 or 1 respectively. For all other values of p_v , v chooses 1 as its ℓ -th bit with some probability in the interval $[\max\{0, p_v - \varepsilon\}, \min\{1, p_v + \varepsilon\}]$ for some $0 \leq \varepsilon < 1$. Then we obtain*

$$E \left[\sum_{v \in V} \Phi_\ell(v) \right] \leq \sum_{v \in V} \Phi_{\ell-1}(v) + 10\varepsilon \Delta n \quad (3)$$

if the coin flips of adjacent nodes are independent. Furthermore, the list of candidate colors of each node never becomes empty.

Proof. For an edge $e = \{u, v\}$ we define X_e as in Lemma 2.2 and

$$A := \begin{cases} (p_u + \varepsilon)(p_v + \varepsilon) \left(\frac{1}{p_u |L_{\ell-1}(u)|} + \frac{1}{p_v |L_{\ell-1}(v)|} \right) & \text{if } p_u, p_v > 0 \\ 0 & \text{else} \end{cases}$$

$$B := \begin{cases} (1 - p_u + \varepsilon)(1 - p_v + \varepsilon) \left(\frac{1}{(1-p_u) |L_{\ell-1}(u)|} + \frac{1}{(1-p_v) |L_{\ell-1}(v)|} \right) & \text{if } p_u, p_v < 1 \\ 0 & \text{else} \end{cases}$$

We obtain

$$A \leq \frac{p_v}{|L_{\ell-1}(u)|} + \frac{p_u}{|L_{\ell-1}(v)|} + \frac{\varepsilon}{|L_{\ell-1}(u)|} + \frac{\varepsilon}{|L_{\ell-1}(v)|} + \frac{\varepsilon p_v}{p_u |L_{\ell-1}(u)|} + \frac{\varepsilon p_u}{p_v |L_{\ell-1}(v)|} + \frac{\varepsilon^2}{p_u |L_{\ell-1}(u)|} + \frac{\varepsilon^2}{p_v |L_{\ell-1}(v)|}.$$

As we have $p_u \geq 1/|L_{\ell-1}(u)|$ and $p_v \geq 1/|L_{\ell-1}(v)|$ if $p_u, p_v > 0$ (cf. the definition of p_u in Algorithm 1), we obtain

$$A \leq \frac{p_v}{|L_{\ell-1}(u)|} + \frac{p_u}{|L_{\ell-1}(v)|} + \frac{\varepsilon}{|L_{\ell-1}(u)|} + \frac{\varepsilon}{|L_{\ell-1}(v)|} + \varepsilon p_v + \varepsilon p_u + 2\varepsilon^2$$

and analogously

$$B \leq \frac{1 - p_v}{|L_{\ell-1}(u)|} + \frac{1 - p_u}{|L_{\ell-1}(v)|} + \frac{\varepsilon}{|L_{\ell-1}(u)|} + \frac{\varepsilon}{|L_{\ell-1}(v)|} + \varepsilon(1 - p_v) + \varepsilon(1 - p_u) + 2\varepsilon^2.$$

It follows

$$E[X_e] = A + B \leq \frac{1}{|L_{\ell-1}(u)|} + \frac{1}{|L_{\ell-1}(v)|} + \frac{2\varepsilon}{|L_{\ell-1}(u)|} + \frac{2\varepsilon}{|L_{\ell-1}(v)|} + 2\varepsilon + 4\varepsilon^2 \leq \frac{1}{|L_{\ell-1}(u)|} + \frac{1}{|L_{\ell-1}(v)|} + 10\varepsilon$$

and thus

$$E \left[\sum_{v \in V} \Phi_{\ell}(v) \right] = E \left[\sum_{e \in E_{\ell-1}} X_e \right] \leq \sum_{\{u, v\} \in E_{\ell-1}} \left(\frac{1}{|L_{\ell-1}(u)|} + \frac{1}{|L_{\ell-1}(v)|} + 10\varepsilon \right) \leq \sum_{v \in V} \Phi_{\ell-1}(v) + 10\varepsilon \Delta n.$$

Because nodes can represent the probabilities 0 and 1 exactly, the proof that the list of candidate colors of each node never becomes empty goes along similar lines as in Lemma 2.2. $\square$

2.2 Extending Prefixes Deterministically through Derandomization

To fix the ℓ -th bit of all prefixes deterministically we produce the nodes' coins for Algorithm 1 from a short random seed, such that (1) the coins of each two adjacent nodes are independent, (2) the coins can represent the probabilities p_v with a sufficient accuracy and (3) the common random seed is short enough to find a good seed deterministically and efficiently in the CONGEST model. To this end, we need the following result on how to compute biased coins from a random seed.

Definition 2.1 ([Vad12]). For $N, M, k \in \mathbb{N}$ such that $k \leq N$, a family of functions $\mathcal{H} = \{h : [N] \rightarrow [M]\}$ is k -wise independent if for all distinct $x_1, \dots, x_k \in [N]$, the random variables $h(x_1), \dots, h(x_k)$ are independent and uniformly distributed in $[M]$ when h is chosen uniformly at random from $\mathcal{H}$.

Theorem 2.4 ([Vad12]). For every a, b, k , there is a family of k -wise independent hash functions $\mathcal{H} = \{h : \{0, 1\}^a \rightarrow \{0, 1\}^b\}$ such that choosing a random function from $\mathcal{H}$ takes $k \cdot \max\{a, b\}$ random bits.

We can use Theorem 2.4 to produce biased random coins for the vertices of a graph such that adjacent vertices' coins are independent.

Lemma 2.5. Given a graph $G = (V, E)$, an integer $b > 0$, probabilities $(p_v)_{v \in V}$ and a K -coloring $\psi : V \rightarrow [K]$ one can efficiently compute random coins $(C_v, p_v)_{v \in V}$ from a seed of length $2 \max\{\log K, b\}$ with the following properties:

- C_v equals 1 with probability $p_v \pm 2^{-b}$ if $p_v \notin \{0, 1\}$
- C_v equals 1 with probability p_v if $p_v \in \{0, 1\}$
- the coins of adjacent vertices are independent.

Proof. Set $a = \log K$. By Theorem 2.4, one can efficiently select a function $h_S : [K] \rightarrow [2^b]$ from a uniformly chosen random seed S of length $2 \cdot \max\{a, b\} = O(\max\{\log K, b\})$. Here, for all $i \in [K]$ the random variable $h_S(i)$ (over the randomness of the random seed) is uniformly distributed in $[2^b]$; further the random variables $h_S(0), \dots, h_S(K-1)$ are pairwise independent. We obtain the desired biased coins, i.e., random variables over the randomness of the seed by defining

$$C_v = \begin{cases} 1, & \text{if } \frac{h_S(\psi(v))}{2^b} < p_v \\ 0, & \text{otherwise} \end{cases} \quad (4)$$

As $h_S(\psi(v))$ only assumes values in $[2^b]$, we always have $\frac{h_S(\psi(v))}{2^b} < 1$ and never $\frac{h_S(\psi(v))}{2^b} < 0$. Hence, if $p_v = 0$ or $p_v = 1$, then C_v equals 1 with probability 0 or 1, respectively. Generally, as $h_S(\psi(v))$ is uniformly distributed in $[2^b]$, we have $\Pr(C_v = 1) = i/2^b$ with $i = |\{k \in [2^b] \mid k/2^b < p_v\}|$. That is, $\Pr(C_v = 1)$ equals p_v rounded up to the next multiple of $1/2^b$, i.e.,

$$p_v \leq \Pr(C_v = 1) \leq p_v + 2^{-b}.$$

Note that although we use the same random variable $h_S(i)$ for all nodes that have input color i in ψ , the probabilities of their coins are not equal. However, two adjacent vertices have distinct input colors $i \neq j$ for which we use the independent random variables $h_S(i)$ and $h_S(j)$ and hence their coins are independent. $\square$

The next lemma shows how to use the method of conditional expectation to find a good random seed that only incurs a small increase of the potential.

Lemma 2.6. *There is a deterministic CONGEST algorithm that given a K -coloring of the graph, fixes the ℓ -th bit of all prefixes in time $O(D \cdot (\log K + \log \Delta + \log \log C))$ such that*

$$\sum_{u \in V} \Phi_\ell(u) \leq \sum_{u \in V} \Phi_{\ell-1}(u) + \frac{n}{\lceil \log C \rceil} \quad (5)$$

and the list of candidate colors of each node does not become empty for $\ell \leq \lceil \log C \rceil$.

Proof. Assume that prefixes of length $\ell-1$ are already fixed. For each $v \in V$ we define $p_v := k_1(v)/|L_{\ell-1}(v)|$ and apply Lemma 2.5 with $b = \lceil \log 10\Delta \lceil \log C \rceil \rceil$ to obtain biased coins $\{(C_v, p_v) \mid v \in V\}$ from a seed of length $d = O(\log K + \log \Delta + \log \log C)$ that are independent for adjacent nodes of G and where C_v equals 1 with probability $p_v \pm 2^{-b}$ if $p_v \notin \{0, 1\}$ and where C_v equals 1 with probability 0 or 1 if p_v equals 0 or 1, respectively. Define a variant of Algorithm 1 executed with the coins $\{(C_v, p_v) \mid v \in V\}$, that is, node v fixes the ℓ -th bit of its prefix to the value of C_v . Note that this algorithm per se is not a distributed algorithm but uses shared randomness in the form of the shared random seed. The described random process satisfies all properties needed to apply Lemma 2.3, with $\varepsilon = \frac{1}{2^b} = \frac{1}{10\Delta \lceil \log C \rceil}$ and we can bound the expected increase of the sum of all potentials by

$$E \left[\sum_{v \in V} \Phi_\ell(v) \right] \leq \sum_{v \in V} \Phi_{\ell-1}(v) + \frac{n}{\lceil \log C \rceil}. \quad (6)$$

Next, we derandomize this process with the method of conditional expectation to find a seed that only incurs a small increase of the potential.

Derandomization: For $j \in \{1, \dots, d\}$, let R_j be the random variable that describes the value of the j -th bit of the random seed. To derandomize the aforementioned algorithm we iterate through the bits of the random seed and deterministically fix a *good bit* r_j for each R_j using the method of conditional expectation—we will later define the notion of a *good bit*. The computed *good seed* $s = r_1, \dots, r_d$ will be such that the potential does not increase by much if coins are flipped and prefixes are extended according to the seed s . We use a BFS tree with a designated root as a leader that gathers all the necessary information to find and distribute good bits for the seed. We obtain a deterministic distributed algorithm to extend the prefixes by one bit without increasing the potential by much. The runtime to find a single good bit for some R_j will be $O(D)$ due to communication over the BFS tree. The total runtime of extending prefixes by one bit is $O(D \cdot \text{seedlength}) = O(D \cdot d) = O(D \cdot (\log K + \log \Delta + \log \log C))$.

Finding a good bit for R_j : Assume we already chose good values $R_1 = r_1, \dots, R_{j-1} = r_{j-1}$ for a $1 \leq j \leq b$ and we want to find a good bit r_j for R_j . By the law of total expectation there must be an $r_j \in \{0, 1\}$ such that

$$E \left[\sum_{v \in V} \Phi_\ell(v) \mid R_1 = r_1, \dots, R_j = r_j \right] \leq E \left[\sum_{v \in V} \Phi_\ell(v) \mid R_1 = r_1, \dots, R_{j-1} = r_{j-1} \right], \quad (7)$$

where the randomness is over the non-determined random bits of $R_{j+1}, \dots, R_d$ and $R_j, \dots, R_d$ of the random seed, respectively. We call a value r_j satisfying Equation (7) a *good bit*; note that the property of r_j being good depends on the choice of $r_1, \dots, r_{j-1}$.

To let the leader of the BFS tree find a good bit r_j , each node $v \in V$ computes

$$x_v^0 = E[\Phi_\ell(v) \mid R_1 = r_1, \dots, R_{j-1} = r_{j-1}, R_j = 0] \quad \text{and} \quad x_v^1 = E[\Phi_\ell(v) \mid R_1 = r_1, \dots, R_{j-1} = r_{j-1}, R_j = 1].$$

In order to compute x_u^0 and x_u^1 , u needs to know $\Pr(\{u, v\} \in G_\ell \mid R_1 = r_1, \dots, R_{j-1} = r_{j-1}, R_j = i)$ for $i \in \{0, 1\}$ for all its neighbors v in $G_{\ell-1}$. The event $\{u, v\} \in G_\ell$ only depends on the values of C_u and C_v . Therefore, u learns $k_1(v)$ (the number of colors in $L_{\ell-1}(v)$ with 1 as the ℓ -th bit) and $\psi(v)$ from all its neighbors v in $G_{\ell-1}$ in one CONGEST round. This is sufficient to compute C_v for any seed S as the initial color $\psi(v)$ determines which random variable v uses to produce C_v and all nodes know how to generate the random variable $h_S(t)$ for any color $t \in [K]$ from S . Note that each node u is aware of its neighbors in $G_{\ell-1}$ when nodes always exchange the latest chosen bit of their prefix each time a new prefix bit is fixed.

Next step, we aggregate $\sum_{v \in V} x_v^0$ and $\sum_{v \in V} x_v^1$ at the leader, choose

$$r_j := \arg \min_{i \in \{0, 1\}} \sum_{v \in V} x_v^i$$

and broadcast r_j to all nodes. r_j is a good bit, as we know there is a bit which fulfills (7) and r_j is chosen as the bit which minimizes the left hand side in (7).

After d iterations, we found a good seed $r_1, \dots, r_d$. By iteratively applying (7) we obtain

$$E \left[\sum_{v \in V} \Phi_\ell(v) \mid R_1 = r_1, \dots, R_d = r_d \right] \leq E \left[\sum_{v \in V} \Phi_\ell(v) \right] \stackrel{(6)}{\leq} \sum_{v \in V} \Phi_{\ell-1}(v) + \frac{n}{\lceil \log C \rceil}. \quad (8)$$

As we have fixed the complete random seed as $s = r_1 \circ \dots \circ r_d$, the left hand side of Equation (8) does not contain any randomness. The claim of the lemma (Equation (5)) follows if each node deterministically extends its prefix by one bit according to s .

In the same way as in Lemma 2.3 we can show that by applying our randomized algorithm, the list of candidate colors of each node does not become empty (this holds for *any* possible outcome of the algorithm, i.e., for any choice of the random seed). Hence, this also holds for our deterministic algorithm as its output equals one possible outcome of the randomized one. $\square$

Proof of Lemma 2.1. Initially, for each node v we have $|L(v)| \geq \deg(v) + 1$ and thus $\sum_{v \in V} \Phi_0(v) = \sum_{v \in V} \frac{\deg(v)}{|L(v)|} \leq n$. We apply the algorithm from Lemma 2.6 $\ell = \lceil \log C \rceil$ times and obtain

$$\sum_{v \in V} \Phi_\ell(v) \leq \sum_{v \in V} \Phi_0(v) + \frac{n}{\lceil \log C \rceil} \cdot \lceil \log C \rceil \leq 2n.$$

It follows that at least half of the nodes u have $\Phi_\ell(u) < 4$. Denote the set of these nodes by $V_{<4}$. As all nodes have chosen prefixes of length $\ell = \lceil \log C \rceil$ and all lists never become empty we obtain $|L(u)| = 1$ for all $u \in V$. Hence for any $u \in V$ the value $\Phi_\ell(u) = \frac{\deg_\ell(u)}{|L(u)|} = \deg_\ell(u)$ equals the number of neighbors that have selected the same candidate color, i.e., the number of neighbors v with $s_\ell(u) = s_\ell(v)$. So the graph $G_\ell[V_{<4}]$ has maximum degree at most $\Delta_\ell = 3$. We compute an MIS on $G_\ell[V_{<4}]$ in $O(\log^* K)$ rounds: The given K -coloring of G induces a K -coloring of $G_\ell[V_{<4}]$ which we can transform to an $O(\Delta_\ell^2) = O(1)$ coloring in $O(\log^* K)$ rounds with Linial's algorithm [Lin92]. Then we compute an MIS on $G_\ell[V_{<4}]$ by iterating through the color classes. Each node $u \in V_{<4}$ that is contained in the MIS colors itself permanently with $s_\ell(u)$; all nodes not in the MIS forget their candidate color and remain uncolored. Due to the maximum degree of $G_\ell[V_{<4}]$ the MIS has size at least $|V_{<4}|/4 \geq n/8$, that is, at least a $1/8$ fraction of all nodes get colored.

The runtime equals the time needed for $\lceil \log C \rceil$ iterations of the algorithm from Lemma 2.6 (plus $O(\log^* K)$ rounds for computing the MIS), i.e., $O(\log C \cdot D \cdot (\log K + \log \Delta + \log \log C))$. $\square$

3 Efficient $(\text{degree} + 1)$ -List Coloring in CONGEST

For solving the $(\text{degree} + 1)$ -list-coloring problem deterministically in $\text{poly log } n$ rounds in CONGEST, we first compute an (α, β) -network decomposition with $\alpha, \beta = \text{poly log } n$ (see Definition 3.1), that is, a decomposition of the network graph into $\text{poly log } n$ color classes such that connected components (*clusters*) in each color class have *small diameter*, i.e., diameter $\text{poly log } n$. Then we iterate through the $\text{poly log } n$ classes and apply the algorithm from Theorem 1.1 on the small diameter clusters of one class in parallel. The concept of network decomposition was introduced in [AGLP89] and was later differentiated into weak and strong decompositions [LS93]. However, both concepts are not suitable for our purpose. In a weak decomposition, when solving the list-coloring on a cluster, it might be necessary to communicate also via edges outside the cluster. Hence, it is not possible to run the algorithm from Theorem 1.1 on $\omega(\log n)$ clusters in parallel as there might be an edge being involved in all these computations. In contrast, a strong decomposition would be sufficient, however, we do not know how to compute it in $\text{poly log } n$ rounds in CONGEST. We therefore introduce a slightly more general definition of a network decomposition, which also includes a congestion parameter κ . A similar definition was for example used previously in [GK19].

Definition 3.1 (Network decomposition with congestion). An (α, β) -network decomposition with congestion κ of a graph $G = (V, E)$ is a partition of V into clusters $C_1, \dots, C_p$ together with associated subtrees $T_1, \dots, T_p$ of G and a color $\gamma_i \in \{1, \dots, \alpha\}$ for each cluster C_i such that

- (i) the tree T_i of cluster C_i contains all nodes of C_i (but it might contain other nodes as well)
- (ii) each tree T_i has diameter at most β
- (iii) clusters that are connected by an edge of G are assigned different colors
- (iv) each edge of G is contained in at most κ trees of the same color

When we assume to have a network decomposition on a graph, we require that each node knows the color of the cluster it belongs to and for each of its incident edges e the set of associated trees e is contained in. Note that a decomposition according to this definition has weak diameter β and a strong network decomposition is a decomposition with congestion 1 where the tree T_i of each cluster C_i contains exactly the nodes in C_i .

Theorem 3.1 ([RG19]). *There is a deterministic algorithm that computes an $(O(\log n), O(\log^3 n))$ -network decomposition with congestion $O(\log n)$ in $O(\log^8 n)$ rounds in the CONGEST model.⁴*

⁴In on-going unpublished work [RGG19] it is shown that diameter and runtime can be improved. These improvements carry over to our results.

We use Theorem 3.1 and Theorem 1.1 to list-color graphs efficiently in the CONGEST model.

Corollary 1.2 *There is a deterministic CONGEST algorithm that solves the list-coloring problem for instances $G = (V, E)$ with $L(v) \subseteq [C]$ and $|L(v)| \geq \deg(v) + 1$ in $O(\log^8 n)$ rounds.*

Proof. Given a graph G , we compute an $(O(\log n), O(\log^3 n))$ -network decomposition with congestion $O(\log n)$ in $O(\log^8 n)$ rounds using the algorithm from Theorem 3.1. To list-color G we iterate through the color classes of the network decomposition. When handling a single color class we need to solve a list-coloring problem on each cluster which is done by applying Theorem 1.1 on all clusters of the color class in parallel. We continue with a detailed description and runtime analysis of the process: Let $L_G(v)$ be the initial list of $v \in V$ in G . Assume all clusters with colors $1, \dots, k-1$ are already list-colored. To list-color the clusters of color k , every node in such a cluster $\mathcal{C}$ updates its list, i.e., it deletes all colors from its list $L_G(v)$ taken by already colored neighbors in G and obtains a new list $L_{\mathcal{C}}(v)$. Let $\deg_{\mathcal{C}}(v)$ denote the degree of v in the graph induced by the nodes in cluster $\mathcal{C}$ and $\deg_G(v)$ the degree of v in G . We obtain $|L_{\mathcal{C}}(v)| \geq \deg_{\mathcal{C}}(v) + 1$ because initially we have $|L_G(v)| \geq \deg_G(v) + 1 = \deg_{\mathcal{C}}(v) + |\Gamma_G(v) \setminus \mathcal{C}| + 1$ and we remove at most one color from $|L_G(v)|$ for each neighbor in $|\Gamma_G(v) \setminus \mathcal{C}|$.

Thus we can apply the algorithm from Theorem 1.1 for each cluster $\mathcal{C}$ of color k in parallel where all aggregation and broadcast in the derandomization part is done over the associated tree of the cluster. This tree has diameter $O(\log^3 n)$ (note that n is the size of G and not of the tree). Messages over edges that are contained in more than one tree are pipelined and as each edge of G is contained in at most $O(\log n)$ trees of the same color, the number of rounds to list-color all clusters of color k is at most $O(\log n)$ times the number of rounds required to list-color a single cluster (without pipelining) which is $O(\log^4 n \cdot \log C \cdot (\log \Delta + \log \log C))$ according to Theorem 1.1. So in total $O(\log^5 n \cdot \log C \cdot (\log \Delta + \log \log C))$ rounds are needed to list-color a single color class of the network decomposition. After iterating through all $O(\log n)$ colors, each node chose a color from its list and has no conflict with a neighbor. Hence we computed a $(\text{degree} + 1)$ -list-coloring of G in time $O(\log^8 n + \log^6 n \cdot \log C \cdot (\log \Delta + \log \log C)) = O(\log^8 n)$. $\square$

4 List Coloring in the CONGESTED CLIQUE and MPC

In this section we show how to adapt the algorithm from Theorem 1.1 to obtain faster algorithms in the CONGESTED CLIQUE and MPC model. As in these models we have direct communication between the nodes/machines, the derandomization from Lemma 2.1 can be sped up in three ways: (1) Communication with a leader can be done directly, removing the dependence on the diameter in the runtime; (2) due to the large routing capabilities of the respective models, we can derandomize $\log n$ bits of the seed in constant time (as described in the following proofs), reducing the influence of the seed-length in the runtime to a constant factor. Sometimes we can even change the base of the bit representation of the colors to get further speedups; (3) once the graph is sparse enough we can send it to one machine (node) and solve it locally in that machine. Thus the $\log n$ -factor that is due to coloring a constant fraction of the vertices in each iteration can be turned into a $\log \Delta$ -factor.

In essence, using the algorithm from Section 2 but choosing several bits of the random seeds at once and gradually adapting the base of the bit representation of the colors to the current routing capabilities—the fewer uncolored vertices remain, the larger the routing capabilities become compared to the number of uncolored nodes—imply the following result.

Theorem 1.3 *There is a deterministic CONGESTED CLIQUE algorithm that solves the $(\text{degree} + 1)$ -list-coloring problem for instances $G = (V, E)$ with $L(v) \subseteq [C]$ and $|L(v)| \geq \deg(v) + 1$ in time $O(\log \log \Delta \log C)$.*

Proof. We use the same algorithm as in Theorem 1.1 but speed up the derandomization step (cf. Lemma 2.6) by fixing $\Omega(\log n)$ bits of the random seed in $O(1)$ rounds. That is, we fix one bit of each node's candidate color in a constant number of rounds. Assume the bits $\{1, \dots, \ell - 1\}$ are already fixed and we want to fix the ℓ -th bit. Instead of first using Linial's algorithm to compute an $O(\Delta^2)$ coloring we simply use the unique Ids of the nodes as an input coloring which yields a seed length of $O(\log n)$. To fix the ℓ -th bit of all prefixes, we split the seed into $O(1)$ segments of length $\lambda \leq \log n$ and choose a *partial seed* $S \in \{0, 1\}^\lambda$ for each segment. For the first segment, a leader chooses a subset $V' \subseteq V$ of size 2^λ and a bijection $\mathcal{R} : V' \rightarrow \{0, 1\}^\lambda$ and

sends $\mathcal{R}(v)$ to node v . We say that v is responsible for $\mathcal{R}(v)$. The nodes exchange the tuples $(v, \mathcal{R}(v))$ such that each node knows which node is responsible for which partial seed. Next, each $u \in V$ learns $k_0(v)$ (the number of colors in $L_{\ell-1}(v)$ starting with 0) and $k_1(v)$ from each of its neighbors v . With this information, u can compute $E[\phi_\ell(u) \mid R_1 \circ \dots \circ R_\lambda = \mathcal{R}(v)]$ for any $v \in V'$ and sends this value to v . Now each node $u \in V'$ can compute $\sum_{v \in V} E[\phi_\ell(v) \mid R_1 \circ \dots \circ R_\lambda = \mathcal{R}(u)]$ and sends it to the leader. The leader chooses the partial seed minimizing this sum and broadcasts it to every node. This way we proceed with all other segments and thus the derandomization of the whole seed is done in $O(1)$ rounds. It follows that coloring a constant fraction of the nodes (cf. proof of Lemma 2.1) can be done in $O(\log C)$ rounds.

After a constant number of iterations of this procedure, i.e., after $O(\log C)$ rounds, at least half of the nodes are colored. This implies that we can speed up the following iterations by fixing *two* bits of each node's candidate color in $O(1)$ rounds. More generally, if the number of uncolored nodes is at most $\frac{n}{2^i}$, we can fix i bits of each node's candidate color in $O(1)$ rounds and thus color a constant fraction of the nodes in time $O\left(\frac{\log C}{i}\right)$. This follows from the fact that if at most $\frac{n}{2^i}$ nodes are left, we have $\Delta \leq \frac{n}{2^i}$ (n is the number of nodes in the original communication network and Δ the maximum degree in the subgraph induced by the uncolored nodes) and by using Lenzen's routing algorithm, each node can send $n/\Delta \geq 2^i$ values to each of its neighbors in $O(1)$ rounds. E.g., for $i = 2$, each node u sends $k_{00}(u)$ (the number of colors in $L_{\ell-1}(u)$ starting with 00), $k_{01}(u)$, $k_{10}(u)$ and $k_{11}(u)$ to each of its neighbors. By adapting the derandomization process in Lemma 2.6 in a straightforward fashion, we can fix the next two bits of each node's candidate color.

As a result, it takes

$$O\left(\sum_{i=1}^{\log \Delta} \frac{\log C}{i}\right) = O(\log \log \Delta \log C)$$

rounds until the number of uncolored nodes is reduced to n/Δ . Then we can use Lenzen's routing algorithm [Len13] to send in $O(1)$ rounds the subgraph of uncolored nodes to a leader which locally solves the problem. $\square$

Next, we turn to coloring in the MPC model and we first formally explain how a $(\text{degree} + 1)$ -list-coloring instance is given in the MPC model.

$(\text{degree} + 1)$ -list-coloring instance in MPC. Given a graph with n nodes and m edges, we assume that each machine has a local memory of $S = \Theta(n^\alpha)$ for some constant $\alpha > 0$ and we have $\Theta\left(\frac{m+n}{S}\right)$ machines.⁵ Each edge $\{u, v\}$ is stored as $\{\text{Id}_u, \text{Id}_v\}$ on some machine. For the $(\text{degree} + 1)$ -list-coloring problem, for each u and each color c from u 's list there is a *list entry* (Id_u, c) stored on some machine. Both, edges and list entries, can be distributed adversarially on the machines.

In the following theorems, we further assume that we have directed edges (u, v) and (v, u) for each edge $\{u, v\} \in E$ stored on the machines and the edges and list entries are sorted in lexicographic order (cf. Definition 5.1). Further we assume that the machine storing (u, v) knows on which machine (v, u) is stored. This can be achieved in $O(1)$ in the following way: If machine i stores an edge $\{u, v\}$, it replaces the edge by the triples (u, v, i) and (v, u, i) . We sort these triples as well as the list entries (u, c) in lexicographic order in $O(1)$ rounds using the algorithm from Lemma 5.1. Assume that after the sorting, (u, v, i) is stored on machine j and (v, u, i) is stored on machine k . Via communication over machine i , machine j learns that (v, u, i) is stored on machine k and vice versa. In Section 5 we formally show that seemingly trivial procedures such as deleting colors chosen by a neighbor from a list that is stored in a distributed manner can be performed in $O(1)$ rounds in the MPC model. We also provide communication primitives such as aggregation trees for the nodes of the graph and we freely use these in our proofs without explicitly mentioning them. For the details we refer to Section 5.

Observation 4.1. We can reduce the $(\Delta + 1)$ -coloring problem where initially no color lists are given to the $(\text{degree} + 1)$ -list-coloring problem in the following way: Let $v_1, \dots, v_{\deg(u)}$ be u 's neighbors sorted by increasing Id. Each machine storing an edge (u, v) learns v 's position within the list of u 's neighbors, i.e., the $i \in \{1, \dots, \deg(u)\}$ for which $v = v_i$, in $O(1)$ rounds (cf. Corollary 5.2) and writes the list entry (u, i) to its memory (w.l.o.g. we may assume that so far, each machine only used half of its memory). The machine storing $(u, v_{\deg(u)})$ produces both list entries $(u, \deg(u))$ and $(u, \deg(u) + 1)$. This way we produced a color

⁵The constant α cannot be chosen by the algorithm designer but is determined by the system. However, the algorithm designer can choose the constant in the $\Theta(\cdot)$ for S and for the number of machines.

list $L(u) \subseteq [\Delta + 1]$ of size $\deg(u) + 1$ for each node u . Thus all our $(\text{degree} + 1)$ -list-coloring results also apply to the standard $(\Delta + 1)$ -coloring problem.

The algorithm in Lemma 2.1 computes an MIS on constant degree subgraphs when every node has chosen a candidate color. To keep our MPC coloring algorithm self-contained and independent from the implementation of an MIS algorithm we explain how to avoid the computation of an MIS.

How to Avoid MIS. We adapt the algorithm from Lemma 2.1 such that it is not necessary to compute an MIS at the end. To this end, we produce the coins in Lemma 2.6 with higher accuracy. Concretely, we choose $\varepsilon = \frac{1}{10\Delta(\Delta+1)\lceil\log C\rceil}$, i.e., we add a $1/(\Delta + 1)$ factor in the accuracy. It follows that after fixing one color-bit of all nodes, the sum of all potentials increased by at most $10\varepsilon\Delta n = \frac{n}{(\Delta+1)\lceil\log C\rceil}$ (cf. Lemma 2.3 and Lemma 2.6—increasing the accuracy this way increases the runtime in Lemma 2.6 only by a constant factor). As initially we have

$$\sum_{v \in V} \Phi_0(v) = \sum_{v \in V} \frac{\deg(v)}{|L(v)|} < \sum_{v \in V} \frac{|L(v)| - 1}{|L(v)|} \stackrel{(*)}{\leq} n - \frac{n}{\Delta + 1}, \quad (9)$$

it follows that after fixing all $\ell = \lceil \log C \rceil$ bits we have

$$\sum_{v \in V} \Phi_\ell(v) \leq \sum_{v \in V} \Phi_0(v) + \frac{n}{\Delta + 1} < n. \quad (10)$$

For the last inequality in 9 (marked by $(*)$) we used $|L(v)| \leq \Delta + 1$. To ensure this property for each node v at each stage of the algorithm, we must delete colors from v 's list as soon as v 's degree decreased by more than v 's list size. This deletion can be done in $O(1)$ rounds in the MPC model with similar techniques as in Observation 4.1.

We obtain that at least half of the nodes have $\Phi_\ell < 2$, i.e., $\Phi_\ell \leq 1$ which means that at least half of the nodes have at most one neighbor that chose the same candidate color. Computing an MIS on the graph induced by these nodes can be done in 1 round by letting the vertex with the larger Id join the MIS; then all MIS nodes keep their color permanently.

We first show how to solve $(\text{degree} + 1)$ -list-coloring with linear memory and afterwards move to the more involved sublinear memory regime.

Theorem 1.4 *There is a deterministic MPC algorithm that solves the $(\text{degree} + 1)$ -list-coloring problem in $O(\log \Delta \log C)$ rounds with linear memory.*

Proof. We proceed similarly as in the CONGESTED CLIQUE model, i.e., we fix one bit of each node's candidate color in a constant number of rounds by fixing $\Omega(\log n)$ bits of the random seed in $O(1)$ rounds in the derandomization. Assume the bits $\{1, \dots, \ell - 1\}$ are already fixed and we want to fix the ℓ -th bit. We use the Ids of the nodes as an input coloring which yields a seed length of $O(\log n)$. As all edges (u, v) for $v \in \Gamma(u)$ and list entries (u, c) fit on one machine, we can achieve that they are stored on the same machine which we name $\mathcal{M}_u$ (note that $\mathcal{M}_u = \mathcal{M}_v$ for $u \neq v$ is possible).

For the derandomization, we split the seed into $O(1)$ segments of length $\lambda \leq \frac{\log n}{2}$. If $\mathcal{M}_u$ stores the edge (u, v) , it sends the values $k_1(u)$ and $|L_{\ell-1}(u)|$ to $\mathcal{M}_v$. We obtain that each machine $\mathcal{M}_u$ knows the values $k_1(v)$ and $|L_{\ell-1}(v)|$ for all $v \in \Gamma(u)$ and hence can compute a vector $\mathcal{V}_u$ of length $2^\lambda \leq \sqrt{n}$ with entries $E[\Phi_\ell(u) \mid R_1 \circ \dots \circ R_\lambda = \mathcal{R}]$ for any partial seed $\mathcal{R} \in \{0, 1\}^\lambda$ (we assume each machine knows how to compute a node's coin from a seed, cf. Equation (4)). For derandomizing the first segment of the seed, we need to compute $\sum_v \mathcal{V}_v$ (where we sum the vectors componentwise) and then choose the partial seed whose entry is the smallest. For this purpose we build an aggregation tree with degree $\sqrt{n}$ and depth $O(1)$ (cf. Lemma 5.1). Each machine sums up the vectors it has and sends it to its parent. As a machine has at most $\sqrt{n}$ children each sending a vector of length at most $\sqrt{n}$, a machine receives at most n values. Finally, the root machine learns $\sum \mathcal{V}_v$, chooses the partial seed with minimum entry and broadcasts it to each machine. Afterwards we proceed with the next seed segment.

After fixing all $\log C$ bits, each node has chosen a candidate color and a constant fraction of the nodes can keep their color permanently. If node u has permanently chosen a color, $\mathcal{M}_u$ informs $\mathcal{M}_v$ about it (for each $v \in \Gamma(u)$) which updates v 's color list.

After $O(\log \Delta)$ iterations of this procedure, i.e., after $O(\log \Delta \log C)$ rounds, there are at most n/Δ^2 uncolored nodes left. It follows that the graph induced by the uncolored nodes has at most n/Δ edges, which means that it fits on a single machine together with all remaining color lists (with length $O(\Delta)$ each). Thus all machines can send their edges and color lists to a leader machine which locally list-colors the remaining graph. $\square$

Theorem 1.5 *There is a deterministic MPC algorithm that solves the $(\text{degree} + 1)$ -list-coloring problem in $O(\log \Delta \log C + \log n)$ rounds with sublinear memory.*

Proof. We proceed similarly as in the linear memory regime, i.e., we fix one bit of each node's candidate color in a constant number of rounds. We take the Ids of the nodes as input coloring and obtain a seed length of $O(\log n)$. With sublinear memory it is not possible to store all edges incident of a node u together with all colors in u 's list on a single machine, but we store it on a set of machines that are connected via an aggregation tree. We call a machine storing an edge (u, v) for a $v \in \Gamma(u)$ or a list entry (u, c) for a $c \in L(u)$ a u -machine. For each node u we build an aggregation tree with degree $\sqrt{n}$ and depth $O(\alpha^{-1})$ with the u -machines as leafs (cf. Lemma 5.1).

Next we describe the derandomization. Assume the bits $\{1, \dots, \ell - 1\}$ are already fixed and we want to fix the ℓ -th bit. We split the seed into $O(1/c)$ parts of length $\lambda \leq c \log n$ for a sufficiently small constant $c < \alpha$. We do an edge-based computation of the sum of all potentials. As in Lemma 2.2 we have

$$E \left[\sum_{v \in V} \Phi_\ell(v) \right] = E \left[\sum_{e \in E_{\ell-1}} X_e \right] \quad \text{with} \quad X_e = \mathbb{1}_{e \in E_\ell} \left(\frac{1}{|L_\ell(u)|} + \frac{1}{|L_\ell(v)|} \right).$$

Each u -machine learns the values $k_1(u)$ and $|L_{\ell-1}(u)|$ in $O(1)$ rounds via communication over the aggregation tree. If a machine stores the edge (u, v) it sends $k_1(u)$ and $|L_{\ell-1}(u)|$ to the machine storing (v, u) . We obtain that the machine storing the edge $e = (u, v)$ has the values $k_1(u)$, $|L_{\ell-1}(u)|$, $k_1(v)$ and $|L_{\ell-1}(v)|$ and hence can compute a vector $\mathcal{V}_e$ of length $2^\lambda \leq n^c$ with entries $E[X_e \mid R_1 \circ \dots \circ R_\lambda = \mathcal{R}]$ for any partial seed $\mathcal{R} \in \{0, 1\}^\lambda$. We connect the aggregation trees of the nodes to one tree with degree $\sqrt{S}$ and depth $O(\alpha^{-1})$. Via aggregation over this tree the root machine learns $\sum_{e \in E_{\ell-1}} \mathcal{V}_e$, chooses the partial seed with minimum entry and broadcasts it to each machine. Afterwards we proceed with the next seed segment. After fixing all $\log C$ bits, each node has chosen a candidate color and a constant fraction of the nodes can keep their color permanently. Afterwards, the machines update their color lists. That is, using the set difference algorithm from Lemma 5.1, the machine storing (u, c) can learn whether c has been taken by one of u 's neighbors and deletes it if this is the case.

If $\Delta > n^{\alpha/2}$, we apply this $O(\log C)$ rounds procedure $O(\log n)$ times, each time coloring a constant fraction of the nodes, yielding an $O(\log n \log C) = O(\log \Delta \log C)$ algorithm. If $\Delta < n^{\alpha/2}$, we apply this procedure $O(\log \Delta)$ times, taking $O(\log \Delta \log C)$ rounds. Afterwards, the number of uncolored nodes is reduced to n/Δ^2 and we can list-color the remaining nodes in $O(\log n)$ rounds using Lemma 4.2. $\square$

Lemma 4.2. *Consider the sublinear memory regime of the MPC model where each machine has memory $S = \Theta(n^\alpha)$ for some $\alpha > 0$. Let G be a graph with $\Delta < n^{\alpha/2}$ and assume we have a total memory of $\Omega(n\Delta^2)$. Then we can solve list-coloring on G in $O(\log n)$ rounds.*

Proof. We take again the node Ids as initial coloring and obtain a seed length of $O(\log n)$. However, in the given setting, it is not necessary to fix each nodes candidate color bitwise. Instead each node directly chooses a color from its list uniformly at random if the seed is chosen uniformly at random. Expressed in the framework of Lemma 2.6 this means that given a random seed, each node chooses a color from its list by choosing one bit after another, producing the coins for each bit from the seed as before. The derandomization of this process goes along similar lines as the proof of Theorem 1.5. That is, we have

$$E \left[\sum_{v \in V} \Phi_{\lceil \log C \rceil}(v) \right] = E \left[\sum_{e \in E} X_e \right] \quad \text{with} \quad X_e = \mathbb{1}_{e \in E_{\lceil \log C \rceil}}.$$

To compute $E[X_e]$ for $e = (u, v)$ conditioned on some partly chosen seed, the machine storing e needs the color lists of u and v . We have at most $n\Delta$ edges and $\Delta < n^{\alpha/2}$. As we have a global memory of $\Omega(n\Delta^2)$

and each machine has memory $\Theta(n^\alpha)$, we can achieve that there is only one u -machine for each node u (that is, all edges outgoing from u and the colors from $L(u)$ are on one machine) and each machine has $\Omega(\Delta)$ extra space for each edge it stores. The machine storing edge (u, v) can therefore send $L(u)$ (which has size $O(\Delta)$) to the machine storing (v, u) . Now each machine knows the color lists $L(u)$ and $L(v)$ for each edge $e = (u, v)$ it stores and can compute $E[X_e]$. The procedure of finding a good seed goes along similar lines as described in the proof of Theorem 1.5.

The increase of the potential can be upper bounded as given in Equation (10) and hence a constant fraction of the nodes can keep their candidate color. The procedure described so far runs in $O(1)$ rounds and hence the list-coloring takes $O(\log n)$ rounds. $\square$

5 Basic MPC Tools

In this section, we provide a set of basic algorithms and constructions that can be carried out deterministically in constant time in the sublinear MPC model. The algorithms are used as subroutines in our sublinear memory MPC algorithms. In the following, when we say that an MPC algorithm is given a set or a multiset of N values, we assume that each of the values is initially given to an arbitrary machine. Throughout this section, we further assume that there is a parameter $S = N^\alpha$ for some constant $\alpha > 0$ such that every machine has space for $c \cdot S$ values for a sufficiently large constant $c > 0$. We will assume that each machine stores at most S values such that there is enough space on the machine to store a constant amount of additional data per stored value during a computation. We note that in the MPC model, it is standard to assume that the global memory is by a sufficiently large constant factor $c > 0$ larger than the total size of the input. We can then always store the input in such a way that only a (sufficiently small) constant fraction of each machine is occupied. We will therefore also generally assume that the number of available machines is $c' \cdot N/S$ for a sufficiently large constant c' . We consider the following three basic problems.

Definition 5.1 (Sorting). Assume that an MPC algorithm receives a multiset of N values from a totally ordered set as input. The MPC algorithm is said to sort the input values if at the end machine $i \in \{1, \dots, \lceil N/S \rceil\}$ stores the input values with ranks $(i-1)S+1, \dots, iS$ in the sorted order of all the N input values.

Definition 5.2 (Prefix Sums). Assume that an MPC algorithm receives a set X of N values from a totally ordered set $\mathcal{X}$ as input. Assume further that there is an associative binary operation $\oplus : \mathcal{X} \times \mathcal{X} \rightarrow \mathcal{X}$. Assume that x_i is the value of the input value with rank i in the sorted order of X . The MPC algorithm is said to solve the prefix sums problem w.r.t. $\oplus$ if at the end for every $i \in \{1, \dots, N\}$, the machine holding value x_i also holds the value $s_i := \bigoplus_{j=1}^i x_j$.

Definition 5.3 (Set Difference). Assume that an MPC algorithm receives a collection of sets $A_1, \dots, A_k$ and a collection of multisets $B_1, \dots, B_k$ as inputs. The MPC algorithm is said to solve the set difference problem if at the end for every $i \in \{1, \dots, k\}$ and for every $a \in A_i$, the machine holding a knows if a is contained in B_i .

The last problem defines a tree structure that is useful to carry out computations on a set or on a collection of sets.

Definition 5.4 (Aggregation Tree Structure). Assume that an MPC algorithm receives a collection of sets $A_1, \dots, A_k$ with elements from a totally ordered domain as input. In an *aggregation tree structure* for $A_1, \dots, A_k$, the elements of $A_1, \dots, A_k$ are stored in lexicographically sorted order (they are primarily sorted by the number $i \in \{1, \dots, k\}$ and within each set A_i they are sorted increasingly). For each $i \in \{1, \dots, k\}$ such that the elements of A_i appear on at least 2 different machines, there is a tree of constant depth containing the machines that store elements of A_i as leafs and where each inner node of the tree has at most $\sqrt{S}$ children. The tree is structured such that it can be used as a search tree for the elements in A_i (i.e., such that an in-order traversal of the tree visits the leaves in sorted order). Each inner node of these trees is handled by a separate additional machine. In addition, there is a constant-depth aggregation tree of degree at most $\sqrt{S}$ connecting all the machines that store elements of $A_1, \dots, A_k$.

Lemma 5.1. *There are constant-time MPC algorithms to solve the sorting, prefix-sums, and set difference problems, as well as to compute an aggregation tree structure for a given collection of input sets.*

Proof. The constant-time sorting algorithm follows directly from the constant-time sorting algorithm in the MapReduce model that is described by Goodrich et al. [GSZ11]. In [GSZ11], the authors consider an I/O-bound MapReduce model, which can be simulated efficiently by the MPC model (the two models are essentially equivalent). Theorem 3.1 in [GSZ11] gives an efficient simulation of BSP algorithms in the I/O-bound MapReduce model. In combination with the BSP sorting algorithm in [Goo99], this yields the desired sorting algorithm in the MapReduce and thus also in the MPC model.

The constant-time prefix-sums algorithm also follows from [GSZ11]. In [GSZ11], it is described how to compute the prefix sums in constant time if each machine only has one value. Note however that if we first locally compute the sum of all values of each machine and afterwards compute the prefix sums of these values, the prefix sums for all the elements can easily be derived in a constant number of additional rounds.

As the third part of the proof, we show how to construct an aggregation tree structure in constant time. We first sort the elements of the sets $A_1, \dots, A_k$ lexicographically (first by the set index $i \in \{1, \dots, k\}$ and then within each set A_i). As described above, this can be done in $O(1)$ time in the MPC model. As a next step, for every $i \in \{1, \dots, k\}$ and each element $a \in A_i$, we make sure that the machine storing a learns the cardinality $|A_i|$ of the set A_i and that the machine learns the position of a within the sorted order of the elements of A_i . Note that as soon as this is done, every machine that stores elements of a set A_i knows exactly where the other elements of A_i are stored and therefore building the aggregation trees for each A_i is straightforward.

To compute the positions of the elements within the sets A_i , we use the prefix sums algorithm discussed above. Assume that all the elements of A_i are from a globally ordered domain $\mathcal{X}$. We first define an associative binary relation $\oplus : (\mathbb{N} \times \mathcal{X}) \times (\mathbb{N} \times \mathcal{X}) \rightarrow (\mathbb{N} \times \mathcal{X})$ as follows. For $a_1, a_2 \in \mathbb{N}$ and $x_1, x_2 \in \mathcal{X}$, we define

$$(a_1, x_1) \oplus (a_2, x_2) := \begin{cases} (a_1, x_1 + x_2) & \text{if } a_1 = a_2 \\ (a_1, x_1) & \text{if } a_1 > a_2 \\ (a_2, x_2) & \text{if } a_2 > a_1 \end{cases}.$$

It is easy to check that the binary operation $\oplus$ is associative. For each element $a \in A_i$, we now build the tuple (i, a) (on the machine where a is stored) and we apply the prefix sums discussed above to these tuples w.r.t. the binary operation $\oplus$. Because the elements of all the sets $A_1 \cup \dots \cup A_k$ are sorted by increasing set index $i \in \{1, \dots, k\}$, this prefix sums operation gives exactly what we need. For each set A_i , it numbers the elements in sorted order from 1 to $|A_i|$. To determine the size of each A_i , we can use an analogous algorithm to number the elements of each set A_i in the reverse direction. If an element $a \in A_i$ knows its position in A_i from both sides, it also directly knows the size of A_i . This therefore shows that the aggregation trees for each set can be computed in constant time in the MPC model. The aggregation tree connecting all the machines that store elements of $A_1, \dots, A_k$ can be done in the same way by treating the collection of the elements of all the sets as one large set.

It remains to show that also the set difference operation can be carried out in $O(1)$ MPC rounds. First note that we can w.l.o.g. assume that $k = 1$. That is, we are only given a single set A and a single multiset B for each $a \in A$, we need to determine whether $a \in B$. To reduce the general problem to the problem with a single set A and a single multiset B , we define $A := \bigcup_{i=1}^k \bigcup_{a \in A_i} (i, a)$ and $B := \bigcup_{i=1}^k \bigcup_{b \in B_i} (i, b)$. As a next step, we compute an aggregation tree structure for A and B . Note that while B is a multiset, formally the aggregation tree structure is only defined for sets. For the construction, we can easily turn B into a set by arbitrarily (but uniquely) labeling the elements of B (e.g., by only using a single copy of each element of B per machine and adding the machine number as a label to the elements). Further, after building the aggregation tree for B , we can efficiently (i.e., in constant time) remove all except one copy for each element in B so that in the following, we can w.l.o.g. assume that B is a set. In the following, we will refer to the aggregation tree for set A as the A -tree and we similarly refer to the aggregation tree for set B as the B -tree.

Note that because of the search tree property of the aggregation trees of A and B , for a given element of $a \in A$ it is straightforward to determine in constant time if $a \in B$ and similarly for an element $b \in B$ one can easily check in constant time if $b \in A$. The challenge is to efficiently do these searches for all elements in parallel. To describe this parallel search, we first define some notation. Let $\mathcal{M}_A$ be the set of machines that participate in the A -tree (i.e., the machines storing the elements of A and the machines handling the inner nodes of the aggregation tree). Similarly, let $\mathcal{M}_B$ be the set of machines that participate in the B -tree. For simplicity, assume that both aggregation trees have height exactly h for some $h = O(1)$ and that all the leaf

nodes (i.e., the machines storing the elements of A and B) are on level h of the respective tree. This is easy to guarantee by adding some dummy nodes where necessary. For every $\ell \in \{0, \dots, h\}$, let $\mathcal{M}_A^{(\ell)} \subseteq \mathcal{M}_A$ and $\mathcal{M}_B^{(\ell)}$ be the subsets of the machines in $\mathcal{M}_A$ and $\mathcal{M}_B$ that are on level ℓ of the respective tree (where level 0 consists of the root nodes of the two trees). For each machine M in $\mathcal{M}_A$ or $\mathcal{M}_B$, let $x_{\min}(M)$ and $x_{\max}(M)$ be the smallest and largest elements stored in the subtree of M .

As a first step, we compute $M_B[M_A] \in \mathcal{M}_B \cup \{\perp\}$ for each machine $M_A \in \mathcal{M}_A$ in such a way that if $M_B[M_A] = \perp$, there are no elements of $A \cap B$ stored in the subtree of M_A of the A -tree and otherwise, (among other things) the subtree of $M_B[M_A]$ of the B -tree contains all the values of $A \cap B$ that are stored in the subtree of M_A of the A -tree. For a fixed $M_A \in \mathcal{M}_A$, the machine $M_B[M_A]$ is determined by using the following iterative process. We initially set $M_B[M_A] \in \mathcal{M}_B^{(0)}$ to be the root machine of the B -tree. Assume that we have currently set $M_B[M_A]$ such that $M_B[M_A] \in \mathcal{M}_B^{(\ell)}$ for some $\ell \in \{0, \dots, h\}$. If $\ell = h$ (i.e., $M_B[M_A]$ is a leaf machine), we assign $M_B[M_A]$ to M_A . Otherwise, let $M_{B,1}, \dots, M_{B,k} \in \mathcal{M}_B^{(\ell+1)}$ be the direct children of $M_B[M_A]$ in the B -tree. If there is exactly one such child machine $M_{B,i}$ such that the value ranges of $M_{B,i}$ and M_A intersect (i.e., such that $x_{\max}(M_A) \geq x_{\min}(M_{B,i})$ and $x_{\min}(M_A) \leq x_{\max}(M_{B,i})$), we set $M_B[M_A] := M_{B,i}$ and continue. Otherwise, if there is no machine $M_{B,i}$ for which the ranges of M_A and $M_{B,i}$ intersect, we define $M_B[M_A] := \perp$ and if there are at least 2 child machines $M_{B,i}$ for which the value range intersects with the value range of M_A , we assign $M_B[M_A]$ to M_A . Note that the construction of $M_B[M_A]$ immediately implies that all the values of $B \cap A$ that are stored in the subtree of M_A in the A -tree are stored in the subtree of $M_B[M_A]$ in the B -tree (and if $M_B[M_A] = \perp$, it implies that the intersection of the values stored in the subtree of M_A and B is empty).

We next show that the machines $M_B[M_A]$ for all machines $M_A \in \mathcal{M}_A$ can be done in constant time in the MPC model. Clearly, if M'_A is a machine in the subtree of M_A (in the A -tree) then also $M_B[M_A]$ is a machine in the subtree of $M_B[M_A]$ (in the B -tree). The assignment can therefore be computed in a top-down fashion. It remains to show that the computation does not exceed the communication budget of each MPC machine. In addition to computing the assignment, we make sure that for each machine $M_A \in \mathcal{M}_A$, if $M_B[M_A]$ is not a leaf machine of the B -tree, M_A also learns the complete state of $M_B[M_A]$. Note that since the degree of both trees is at most $\sqrt{S}$, the state of $M_B[M_A]$ consists of $\sqrt{S}$ values (the information about the $\sqrt{S}$ children and their value ranges). Therefore, when moving down the A -tree from a node M to its at most $\sqrt{S}$ children, the information about $M_B[M]$ can be copied to the children of M in a single MPC round. Hence, when computing the machine $M_B[M_A]$ assigned to M_A , we can assume that M_A already knows the state of the machine $M_B[M]$ for the parent machine M of M_A (if M_A is not the root node of the A -tree). If M_A is the root machine of the A -tree, it is clear that it can compute the machine $M_B[M_A]$ and learn its state in constant time. Otherwise, since M_A already knows the state of $M_B[M]$, it can then locally check if there is exactly one subtree of $M_B[M]$ that intersects with the value range of M_A . If this is not the case, we have $M_B[M_A] = \perp$ or $M_B[M_A] = M_B[M]$ and we are done. Otherwise, let $M_{B,i}$ be this unique subtree of $M_B[M]$ that intersects with the range of M_A . Machine M_A then asks machine $M_{B,i}$ for its state. In order to show that we do not exceed the bandwidth requirement, we have to show that the state of each machine $M_{B,i}$ is required by at most $O(\sqrt{S})$ different A -tree machines. In the following, assume that M_B is the parent machine of $M_{B,i}$. Assume that $M_A \in \mathcal{M}_A^{(\ell)}$ for some level $\ell \geq 1$. Machine M_A only asks for the state of $M_{B,i}$ if the range of the parent machine $M \in \mathcal{M}_A^{(\ell-1)}$ of M_A intersects with $M_{B,i}$ and with at least one other subtree $M_{B,j}$ of M_B (i.e., it either also intersects with $M_{B,i-1}$ or with $M_{B,i+1}$). Note however that there can be at most one machine in $\mathcal{M}_A^{(\ell-1)}$ for which the value range intersects with $M_{B,i-1}$ and with $M_{B,i+1}$ and there can be at most one such machine for which the value range intersects with $M_{B,i}$ and with $M_{B,i-1}$. Only the $O(\sqrt{S})$ children machines of these two machines can ask for the state of $M_{B,i}$. The assignment $M_B[M_A]$ for all $M_A \in \mathcal{M}_A$ can therefore be computed in constant time in the MPC model.

We next show how we can use the assignment $M_B[M_A]$ to the machines $M_A \in \mathcal{M}_A$ to determine the intersection of A and B . Recall that each leaf machine $M_A \in \mathcal{M}_A^{(h)}$ needs to determine which of its at most S stored values of A are contained in B . Consider some machine $M_A \in \mathcal{M}_A^{(h)}$. If $M_B[M_A] = \perp$, we M_A knows that there is no intersection between the values of A it stores and B . Let us therefore assume that $M_B[M_A] \neq \perp$. We first consider the case where $M_B[M_A]$ is an inner node of the B -tree (i.e., $M_B[M_A] \in \mathcal{M}_B^{(\ell)}$ for some $\ell < h$). Let $M_{B,1}, \dots, M_{B,k}$ be the direct children of $M_B[M_A]$ in the B -tree. Recall that M_A knows the state of $M_B[M_A]$ and it thus knows $M_{B,1}, \dots, M_{B,k}$ and $x_{\min}(M_{B,i})$ and $x_{\max}(M_{B,i})$

for each $i \in \{1, \dots, k\}$. We also know that the value range of M_A intersects with the ranges of at least two of the machines $M_{B,1}, \dots, M_{B,k}$ as otherwise, we would have set $M_B[M_A]$ differently. Therefore, for each $M_{B,i}$, there are at most 2 leaf machines $M_A \in \mathcal{M}_A^{(h)}$ of the A -tree for which the value range intersects with the value range of $M_{B,i}$. The machine M_A can therefore send all its stored elements of A that fall within the range of machine $M_{B,i}$ for each $i \in \{1, \dots, k\}$. Note that while M_A might have to communicate with up to $\sqrt{S}$ different machines, the total number of values it has to send is at most S . Since each such machine $M_{B,i}$ is contacted by at most 2 machines from the A -tree, it can in constant time determine which of the elements it receives are stored in its subtree and report this information back to the respective A -tree machines. Hence, if $M_B[M_A]$ is an inner node of the B -tree, M_A can efficiently learn its part of $A \cap B$. It therefore remains to consider the case where $M_B[M_A]$ is a leaf machine of the B -tree. Now, all the elements in the intersection between the elements stored at M_A and the elements in B are stored on machine $M_B[M_A]$ in the B -tree. However, we cannot bound the number of leaf machines M_A that are assigned the same B machine $M_B[M_A]$. The intersection between the elements stored at M_A and the elements stored at $M_B[M_A]$ can therefore not be computed by direct communication between the two machines. Instead, we delegate this task up the A -tree. Let M be the highest (i.e., closest to the root) ancestor of M_A in the A -tree for which $M_B[M] = M_B[M_A]$. Instead of M_A , machine M asks machine M_B for its elements in the range between $x_{\min}(M)$ and $x_{\max}(M)$. After receiving these values, M can efficiently propagate them down the A -tree by always only forwarding the values that fall within the range of each particular child. Thus, after M knows the values of M_B in the range between $x_{\min}(M)$ and $x_{\max}(M)$, M_A can efficiently learn its intersection with B . In order to show that the algorithm works, it only remains to show that the leaf machine M_B of the B -tree does not get too many requests from machines $M' \in \mathcal{M}_A$ for which $M_B[M'] = M_B$. Note however that on each level ℓ (i.e., in each set $\mathcal{M}_A^{(\ell)}$, there can be at most $O(\sqrt{S})$ machines M' for which $M_B[M'] = M_B$ and such that for the parent M'' of M' , we have $M_B[M''] \neq M_B$. This concludes the proof. $\square$

In the construction of the aggregation tree structure, we proved the following as an intermediate result:

Corollary 5.2. *There is a constant-time MPC algorithm that given a collection of sets $A_1, \dots, A_k$ with elements from a totally ordered domain, for all $i \in \{1, \dots, k\}$ and $a \in A_i$ the machine storing a learns the rank of a within A_i .*

References

- [ABI86] Noga Alon, László Babai, and Alon Itai. A fast and simple randomized parallel algorithm for the maximal independent set problem. *J. of Algorithms*, 7(4):567–583, 1986.
- [ACK19] Sepehr Assadi, Yu Chen, and Sanjeev Khanna. Sublinear algorithms for $(\Delta + 1)$ vertex coloring. In *Proc. 30th ACM-SIAM Symp. on Discrete Algorithms (SODA)*, pages 767–786, 2019.
- [AGLP89] Baruch Awerbuch, Andrew V. Goldberg, Michael Luby, and Serge A. Plotkin. Network decomposition and locality in distributed computation. In *Proc. 30th Symp. on Foundations of Computer Science (FOCS)*, pages 364–369, 1989.
- [ANOY14] Alexandr Andoni, Aleksandar Nikolov, Krzysztof Onak, and Grigory Yaroslavtsev. Parallel algorithms for geometric graph problems. *CoRR*, abs/1401.0042, 2014.
- [Bar15] Leonid Barenboim. Deterministic $(\Delta + 1)$ -coloring in sublinear (in Δ) time in static, dynamic and faulty networks. In *Proc. 34th Symp. on Principles of Distributed Computing (PODC)*, pages 345–354, 2015.
- [BCD⁺19] Nir Bachrach, Keren Censor-Hillel, Michal Dory, Yuval Efron, Dean Leitersdorf, and Ami Paz. Hardness of distributed optimization. In *Proc. 38th ACM Symp. on Principles of Distributed Computing (PODC)*, pages 238–247, 2019.
- [BE09] Leonid Barenboim and Michael Elkin. Distributed $(\Delta+1)$ -coloring in linear (in Δ) time. In *Proc. 41st ACM Symp. on Theory of Computing (STOC)*, pages 111–120, 2009.

- [BE10] Leonid Barenboim and Michael Elkin. Deterministic distributed vertex coloring in polylogarithmic time. In *Proc. 29th Symp. on Principles of Distributed Computing (PODC)*, 2010.
- [BE13] Leonid Barenboim and Michael Elkin. *Distributed Graph Coloring: Fundamentals and Recent Developments*. Morgan & Claypool Publishers, 2013.
- [BEG18] Leonid Barenboim, Michael Elkin, and Uri Goldenberg. Locally-iterative distributed $(\Delta + 1)$ -coloring below Szegedy-Vishwanathan barrier, and applications to self-stabilization and to restricted-bandwidth models. In *Proc. 37th ACM Symp. on Principles of Distr. Comp. (PODC)*, pages 436–446, 2018.
- [BEPS12] Leonid Barenboim, Michael Elkin, Seth Pettie, and Johannes Schneider. The locality of distributed symmetry breaking. In *Proc. 53th Symp. on Foundations of Computer Science (FOCS)*, 2012.
- [CDP19] Artur Czumaj, Peter Davies, and Merav Parter. Graph sparsification for derandomizing massively parallel computation with low space. *CoRR*, abs/1912.05390, 2019.
- [CFG⁺19] Yi-Jun Chang, Manuela Fischer, Mohsen Ghaffari, Jara Uitto, and Yufan Zheng. The complexity of $(\Delta+1)$ coloring in congested clique, massively parallel computation, and centralized local computation. In *Proc. 38th ACM Symp. on Principles of Distr. Comp. (PODC)*, pages 471–480, 2019.
- [CKP17] Keren Censor-Hillel, Seri Khoury, and Ami Paz. Quadratic and near-quadratic lower bounds for the CONGEST model. In *31st International Symposium on Distributed Computing, DISC 2017, October 16-20, 2017, Vienna, Austria*, pages 10:1–10:16, 2017.
- [CLP18] Yi-Jun Chang, Wenzheng Li, and Seth Pettie. An optimal distributed $(\Delta+1)$ -coloring algorithm? In *Proc. 50th ACM Symp. on Theory of Computing (STOC)*, pages 445–456, 2018.
- [CPS17] Keren Censor-Hillel, Merav Parter, and Gregory Schwartzman. Derandomizing local distributed algorithms under bandwidth restrictions. In *Proc. 31st Symp. on Distributed Computing (DISC)*, pages 11:1–11:16, 2017.
- [CV86] Richard Cole and Uzi Vishkin. Deterministic coin tossing with applications to optimal parallel list ranking. *Information and Control*, 70(1):32–53, 1986.
- [DHK⁺11] Atish Das Sarma, Stephan Holzer, Liah Kor, Amos Korman, Danupon Nanongkai, Gopal Pandurangan, David Peleg, and Roger Wattenhofer. Distributed verification and hardness of distributed approximation. In *Proc. 43rd ACM Symp. on Theory of Computing (STOC)*, pages 363–372, 2011.
- [DKM19] Janosch Deurer, Fabian Kuhn, and Yannic Maus. Deterministic distributed dominating set approximation in the CONGEST model. In *Proc. 38th ACM Symp. on Principles of Distributed Computing (PODC)*, pages 94–103, 2019.
- [FHK16] Pierre Fraigniaud, Marc Heinrich, and Adrian Kosowski. Local conflict coloring. In *Proc. 57th Symp. on Foundations of Computer Science (FOCS)*, 2016.
- [Gha19] Mohsen Ghaffari. Distributed maximal independent set using small messages. In *Proc. 30th ACM-SIAM Symp. on Discrete Algorithms (SODA)*, pages 805–820, 2019.
- [GHK18] Mohsen Ghaffari, David G. Harris, and Fabian Kuhn. On derandomizing local distributed algorithms. In *Proc. 59th Symp. on Foundations of Computer Science (FOCS)*, pages 662–673, 2018.
- [GHKM18] Mohsen Ghaffari, Juho Hirvonen, Fabian Kuhn, and Yannic Maus. Improved distributed Delta-coloring. In *Proc. 37th ACM Symp. on Principles of Distributed Computing (PODC)*, pages 427–436, 2018.

- [GK18] Mohsen Ghaffari and Fabian Kuhn. Derandomizing distributed algorithms with small messages: Spanners and dominating set. In *Proc. 32nd Symp. on Distributed Computing (DISC)*, pages 29:1–29:17, 2018.
- [GK19] Mohsen Ghaffari and Fabian Kuhn. On the use of randomness in local distributed graph algorithms. In *Proc. ACM Symp. on Principles of Distributed Computing (PODC)*, pages 290–299, 2019.
- [GKM17] Mohsen Ghaffari, Fabian Kuhn, and Yannic Maus. On the complexity of local distributed graph problems. In *Proc. 49th ACM Symp. on Theory of Computing (STOC)*, pages 784–797, 2017.
- [Goo99] Michael T. Goodrich. Communication-efficient parallel sorting. *SIAM Journal on Computing*, 29(2):416–432, 1999.
- [GPS88] Andrew V. Goldberg, Serge A. Plotkin, and Gregory E. Shannon. Parallel symmetry-breaking in sparse graphs. *SIAM J. on Discrete Mathematics*, 1(4):434–446, 1988.
- [GSZ11] Michael T. Goodrich, Nodari Sitchinava, and Qin Zhang. Sorting, searching, and simulation in the mapreduce framework. In *Proc. 22nd Int. Symp. on Algorithms and Computation (ISAAC)*, pages 374–383, 2011.
- [HMKS16] Dan Hefetz, Yannic Maus, Fabian Kuhn, and Angelika Steger. A polynomial lower bound for distributed graph coloring in a weak LOCAL model. In *Proc. 30th Symp. on Distributed Computing (DISC)*, pages 99–113, 2016.
- [HSS16] David G. Harris, Johannes Schneider, and Hsin-Hao Su. Distributed $(\delta + 1)$ -coloring in sublogarithmic rounds. In *Proc. 48th ACM Symp. on Theory of Computing (STOC)*, pages 465–478, 2016.
- [Joh99] Öjvind Johansson. Simple distributed $\Delta+1$ -coloring of graphs. *Inf. Process. Lett.*, 70(5):229–232, 1999.
- [Kar72] Richard M. Karp. Reducibility among combinatorial problems. In *Symposium on Complexity of Computer Computations*, pages 85–103, 1972.
- [KS18] Ken-ichi Kawarabayashi and Gregory Schwartzman. Adapting local sequential algorithms to the distributed setting. In *32nd International Symposium on Distributed Computing, DISC 2018, New Orleans, LA, USA, October 15-19, 2018*, pages 35:1–35:17, 2018.
- [KSOS06] Kishore Kothapalli, Christian Scheideler, Melih Onus, and Christian Schindelhauer. Distributed coloring in $\tilde{O}(\sqrt{\log n})$ bit rounds. In *Proc. 20th Int. Parallel and Distributed Processing Symposium (IPDPS)*, 2006.
- [KSV10] Howard J. Karloff, Siddharth Suri, and Sergei Vassilvitskii. A model of computation for mapreduce. In *Proc. 21st ACM-SIAM Symp. on Discrete Algorithms (SODA)*, pages 938–948, 2010.
- [Kuh09] Fabian Kuhn. Local weak coloring algorithms and implications on deterministic symmetry breaking. In *Proc. of 21st ACM Symp. on Parallelism in Algorithms and Architectures (SPAA)*, 2009.
- [Kuh20] Fabian Kuhn. Faster deterministic distributed coloring through recursive list coloring. pages 1244–1259, 2020.
- [KW06] Fabian Kuhn and Roger Wattenhofer. On the complexity of distributed graph coloring. In *Proc. 25th ACM Symp. on Principles of Distributed Computing (PODC)*, pages 7–15, 2006.
- [Len13] Christoph Lenzen. Optimal deterministic routing and sorting on the congested clique. In *Proc. 32nd ACM Symp. on Principles of Distributed Computing (PODC)*, pages 42–50, 2013.
- [Lin92] Nathan Linial. Locality in distributed graph algorithms. *SIAM J. Comput.*, 21(1):193–201, 1992.

- [LPPP03] Zvi Lotker, Elan Pavlov, Boaz Patt-Shamir, and David Peleg. MST construction in $o(\log \log n)$ communication rounds. In *Proc. 15th ACM Symp. on Parallelism in Algorithms and Architectures (SPAA)*, pages 94–100, 2003.
- [LS93] Nathan Linial and Michael E. Saks. Low diameter graph decompositions. *Combinatorica*, 13(4):441–454, 1993.
- [Lub86] Michael Luby. A simple parallel algorithm for the maximal independent set problem. *SIAM J. on Computing*, 15:1036–1053, 1986.
- [MU05] Michael Mitzenmacher and Eli Upfal. *Probability and Computing: Randomized Algorithms and Probabilistic Analysis*. Cambridge University Press, New York, NY, USA, 2005.
- [Par18a] Merav Parter. $(\Delta+1)$ coloring in the congested clique model. *CoRR*, abs/1805.02457v2, 2018.
- [Par18b] Merav Parter. $(\delta+1)$ coloring in the congested clique model. In *Proc. 45th Int. Coll. on Automata, Languages, and Programming (ICALP)*, pages 160:1–160:14, 2018.
- [Pel00] David Peleg. Distributed computing. *SIAM Monographs on discrete mathematics and applications*, 5, 2000.
- [PS95] Alessandro Panconesi and Aravind Srinivasan. On the complexity of distributed network decomposition. *J. of Alg.*, 20(2):581–592, 1995.
- [PS13] Seth Pettie and Hsin-Hao Su. Fast distributed coloring algorithms for triangle-free graphs. In *Proc. 40th Int. Coll. on Automata, Languages, and Programming (ICALP)*, pages 681–693, 2013.
- [RG19] Václav Rozhoň and Mohsen Ghaffari. Polylogarithmic-time deterministic network decomposition and distributed derandomization. *CoRR*, abs/1907.10937, 2019.
- [RGG19] Václav Rozhoň, Mohsen Ghaffari, and Christoph Grunau. Personal communication, 2019.
- [SV93] Mario Szegedy and Sundar Vishwanathan. Locality based graph coloring. In *Proc. 25th ACM Symp. on Theory of Computing (STOC)*, pages 201–207, 1993.
- [SW10] Johannes Schneider and Roger Wattenhofer. A new technique for distributed symmetry breaking. In *Proc. 29th ACM Symp. on Principles of Distributed Computing (PODC)*, pages 257–266, 2010.
- [Vad12] Salil P. Vadhan. Pseudorandomness. *Foundations and Trends in Theoretical Computer Science*, 7(1-3):1–336, 2012.