# Efficient Decremental Learning Algorithms for Broad Learning System

Hufei Zhu

Abstract—The decremental learning algorithms are required in machine learning, to prune redundant nodes and remove obsolete inline training samples. In this paper, an efficient decremental learning algorithm to prune redundant nodes is deduced from the incremental learning algorithm 1 proposed in [9] for added nodes, and two decremental learning algorithms to remove training samples are deduced from the two incremental learning algorithms proposed in [10] for added inputs. The proposed decremental learning algorithm for reduced nodes utilizes the inverse Cholesky factor of the Hermitian matrix in the ridge inverse, to update the output weights recursively, as the incremental learning algorithm 1 for added nodes in [9], while that inverse Cholesky factor is updated with an unitary transformation. The proposed decremental learning algorithm 1 for reduced inputs updates the output weights recursively with the inverse of the Hermitian matrix in the ridge inverse, and updates that inverse recursively, as the incremental learning algorithm 1 for added inputs in [10]. Moreover, the proposed decremental learning algorithm 2 for reduced inputs updates the output weights recursively with the inverse Cholesky factor of the Hermitian matrix in the ridge inverse, and updates that inverse Cholesky factor recursively by multiplying it with an upper-triangular intermediate matrix, as the incremental learning algorithm 2 for added inputs in [10]. In numerical experiments, all the proposed 3 decremental learning algorithms for reduced nodes or inputs always achieve the testing accuracy of the standard ridge solution. When some nodes or training samples are removed, the standard ridge solution by (2) and (3) requires high computational complexity to retrain the whole network from the beginning, while the proposed decremental learning algorithms update the output weights easily for reduced nodes or inputs without a retraining process.

*Index Terms*—Broad learning system (BLS), decremental learning, prune nodes, remove training samples, matrix inversion lemma, random vector functional-link neural networks (RVFLNN), single layer feedforward neural networks (SLFN), efficient algorithms, partitioned matrix, inverse Cholesky factorization, ridge inverse, ridge solution.

## I. INTRODUCTION

In Single layer feedforward neural networks (SLFN) with the universal approximation capability [1]–[3], traditional Gradient-descent-based learning algorithms [4], [5] can be utilized, which suffer from the time-consuming training process. To avoid the long training process, the random vector functional-link neural network (RVFLNN) was proposed [2], which is a universal approximation for continuous functions on compact sets. The rapid incremental learning algorithm proposed in [6] updates the output weights of the RVFLNN easily for a new added node or input, which can be applied to model time-variety data with moderate size. To deal with timevariety big data with high dimension, the scheme in [6] was improved into Broad Learning System (BLS) [7], which can update the output weights easily for any number of new added nodes or inputs. In [8], the universal approximation capability of BLS was proved mathematically, and several BLS variants were proposed, which include cascade, recurrent, and broaddeep combination structures.

Efficient incremental learning BLS algorithms for new added nodes and inputs have been proposed in [9] and [10], respectively, to reduce the computational complexities of the original BLS algorithms in [7]. Moreover, the original BLS algorithms [7] utilize the ridge regression approximation of the generalized inverse, while the BLS algorithms proposed in [9], [10] are based on the ridge inverse and the corresponding ridge solution [11]. In [7], the ridge parameter  $\lambda \rightarrow 0$  is assumed in the ridge inverse [11] to approximate the generalized inverse, while in [9], [10],  $\lambda$  can be any positive real number since the assumption of  $\lambda \rightarrow 0$  is no longer required.

In machine learning, usually the decremental learning algorithms are also required to prune redundant nodes [12]-[17] and remove obsolete inline training samples [18]–[20]. Thus in this paper, we propose efficient decremental learning algorithms to remove nodes and training samples, respectively. As the incremental learning algorithm 1 for added nodes proposed in [9], the proposed decremental learning algorithm for reduced nodes also computes the ridge solution (i.e, the output weights) from the inverse Cholesky factor of the Hermitian matrix in the ridge inverse. Moreover, the proposed decremental learning algorithm for reduced nodes updates the inverse Cholesky factor by an unitary transformation. On the other hand, as the incremental learning algorithms for added inputs proposed in [10], the proposed two decremental learning algorithms for reduced inputs also compute the ridge solution from the inverse and the inverse Cholesky factor of the Hermitian matrix in the ridge inverse, respectively.

This paper is organized as follows. Section II introduces BLS and the efficient incremental learning algorithms proposed in [9], [10]. In Section III, we propose 1 decremental learning algorithm for reduced nodes and 2 decremental learning algorithms for reduced inputs. Then Section IV evaluates the proposed decremental learning algorithms by numerical experiments. Finally, conclusions are given in Section V.

## II. BROAD LEARNING SYSTEM AND INCREMENTAL LEARNING ALGORITHMS PROPOSED IN [9], [10]

BLS transforms the original input  $\mathbf{X}$  into "mapped features" in "feature nodes" by some feature mappings. The feature nodes are then enhanced as the enhancement nodes with random weights. All the feature nodes and the enhancement

nodes form the expanded input matrix **A**. The expanded input matrix **A** can be denoted as  $\mathbf{A}_k$  or  $\mathbf{A}_{\bar{l}}$ , where the subscript k denotes the column number and the total number of nodes, and the subscript  $\bar{l}$  denotes the row number and the number of training samples. The connections of all the feature nodes and the enhancement nodes in **A** are fed into the output by

$$\hat{\mathbf{Y}} = \mathbf{A}\mathbf{W},\tag{1}$$

where  $\mathbf{W}$  is the output weight matrix. The ridge solution [11] of (1) is

$$\mathbf{W} = \mathbf{A}^{\dagger} \mathbf{Y},\tag{2}$$

where  $\mathbf{A}^{\dagger}$  is the ridge inverse [11] of  $\mathbf{A}$  that satisfies

$$\mathbf{A}^{\dagger} = \left(\mathbf{A}^T \mathbf{A} + \lambda \mathbf{I}\right)^{-1} \mathbf{A}^T.$$
(3)

The incremental learning algorithms were proposed in [7] to add q enhancement nodes and p input training samples to the network, respectively. The q enhancement nodes are added to the input matrix  $\mathbf{A}_{k-q}$  by

$$\mathbf{A}_{k} = \begin{bmatrix} \mathbf{A}_{k-q} | \mathbf{H} \end{bmatrix},\tag{4}$$

where **H** include q columns. On the other hand, the additional p input training samples can be denoted as  $\mathbf{X}_a$ , and the incremental feature nodes and enhancement nodes corresponding to  $\mathbf{X}_a$  can be denoted as the matrix  $\mathbf{A}_x$  with p rows. Accordingly the expanded input matrix  $\mathbf{A}_{\bar{l}-\bar{v}}$  should be updated into

$$\mathbf{A}_{\bar{l}} = \begin{bmatrix} \mathbf{A}_{\bar{l}-\bar{p}} \\ \mathbf{A}_x \end{bmatrix}.$$
(5)

The incremental learning algorithms in [7] are based on the Greville's method [21], which can only compute the generalized inverse of the partitioned matrices (4) and (5). Correspondingly the ridge parameter  $\lambda$  in (3) should be set to a very small positive real number, e.g.,  $10^{-8}$ , and then  $\lambda \rightarrow 0$ can be assumed in (3) to approximate the generalized inverse.

The incremental learning algorithm 1 proposed in [9] and the two incremental learning algorithms proposed in [10] no longer need to assume  $\lambda \to 0$ , which are all based on the ridge inverse, and always achieve the testing accuracy of the standard ridge solution in numerical experiments. However, usually the BLS algorithms in [7] achieve worse testing accuracy than the standard ridge solution in numerical experiments, when the assumption of  $\lambda \to 0$  is not satisfied (i.e.,  $\lambda$  is not very small). The rest of this section will give a brief introduction to the above-mentioned algorithms proposed in [9], [10].

## A. Incremental Learning for Added Nodes

The incremental learning algorithm 1 proposed in [9] for added nodes computes the ridge solution (i.e, the output weights) from the inverse Cholesky factor of the Hermitian matrix in the ridge inverse, and updates the inverse Cholesky factor efficiently by extending the inverse Cholesky factorization in [22].

Let

$$\mathbf{R}_k = \mathbf{A}_k^T \mathbf{A}_k + \lambda \mathbf{I},\tag{6}$$

and then (4) can be substituted into (6) to obtain

$$\mathbf{R}_{k} = \begin{bmatrix} \mathbf{R}_{k-q} & \mathbf{A}_{k-q}^{T} \mathbf{H} \\ \mathbf{H}^{T} \mathbf{A}_{k-q} & \mathbf{H}^{T} \mathbf{H} + \lambda \mathbf{I} \end{bmatrix}.$$
 (7)

The inverse Cholesky factor [22] of  $\mathbf{R}_k$  is the upper-triangular  $\mathbf{F}_k$  that satisfies

$$\mathbf{F}_k \mathbf{F}_k^T = \mathbf{R}_k^{-1} = (\mathbf{A}_k^T \mathbf{A}_k + \lambda \mathbf{I})^{-1}.$$
 (8)

In [9],  $\mathbf{F}_k$  is computed from  $\mathbf{F}_{k-q}$  by

$$\mathbf{F}_{k} = \begin{bmatrix} \mathbf{F}_{k-q} & \mathbf{T} \\ \mathbf{0} & \mathbf{G} \end{bmatrix}$$
(9)

where

$$\begin{cases} \mathbf{G}\mathbf{G}^{T} = \begin{pmatrix} \mathbf{H}^{T}\mathbf{H} + \lambda\mathbf{I} - \mathbf{H}^{T} \times \\ \mathbf{A}_{k-q}\mathbf{F}_{k-q}\mathbf{F}_{k-q}^{T}\mathbf{A}_{k-q}^{T}\mathbf{H} \end{pmatrix}^{-1} \quad (10a) \end{cases}$$

$$\mathbf{T} = -\mathbf{F}_{k-q}\mathbf{F}_{k-q}^T\mathbf{A}_{k-q}^T\mathbf{H}\mathbf{G}.$$
 (10b)

In (10a), the upper-triangular **G** is the inverse Cholesky factor of  $\mathbf{H}^T \mathbf{H} + \lambda \mathbf{I} - \mathbf{H}^T \mathbf{A}_{k-q} \mathbf{F}_{k-q} \mathbf{F}_{k-q}^T \mathbf{A}_{k-q}^T \mathbf{H}$ .

The output weight matrix

$$\mathbf{W}_k = \mathbf{F}_k \mathbf{F}_k^T \mathbf{A}_k^T \mathbf{Y}$$
(11)

is computed from  $\mathbf{W}_{k-q}$  by

$$\mathbf{W}_{k} = \begin{bmatrix} \mathbf{W}_{k-q} + \mathbf{T}\mathbf{G}^{T} \left(\mathbf{H}^{T}\mathbf{Y} - \mathbf{H}^{T}\mathbf{A}_{k-q}\mathbf{W}_{k-q}\right) \\ \mathbf{G}\mathbf{G}^{T} \left(\mathbf{H}^{T}\mathbf{Y} - \mathbf{H}^{T}\mathbf{A}_{k-q}\mathbf{W}_{k-q}\right) \end{bmatrix}.$$
 (12)

## B. Incremental Learning for Added Inputs

The two incremental learning algorithms for added inputs proposed in [10] compute the ridge solution (i.e., the output weights) from the inverse or the inverse Cholesky factor of the Hermitian matrix in the ridge inverse. The algorithm 1 proposed in [10] updates the inverse of the Hermitian matrix by the matrix inversion lemma [23], while the algorithm 2 proposed in [10] updates the upper-triangular inverse Cholesky factor of the Hermitian matrix by multiplying that inverse Cholesky factor with an upper-triangular intermediate matrix, which is computed by a Cholesky factorization or an inverse Cholesky factorization.

Let  $\mathbf{Y}$  and  $\mathbf{Y}_a$  denote the output labels corresponding to the input  $\mathbf{X}$  and the added input  $\mathbf{X}_a$ , respectively, and write

$$\mathbf{Y}_{\bar{l}} = \begin{bmatrix} \mathbf{Y} \\ \mathbf{Y}_a \end{bmatrix}.$$
 (13)

Then the output weights (2) can be written as

$$\mathbf{W}_{\bar{l}} = \mathbf{Q}_{\bar{l}} \mathbf{A}_{\bar{l}}^T \mathbf{Y}_{\bar{l}},\tag{14}$$

where

$$\mathbf{Q}_{\bar{l}} = \left(\mathbf{A}_{\bar{l}}^T \mathbf{A}_{\bar{l}} + \lambda \mathbf{I}\right)^{-1}.$$
 (15)

Substitute (5) into (15) to obtain

$$\mathbf{Q}_{\bar{l}} = \left( \left( \mathbf{A}_{\bar{l}-\bar{p}}^T \mathbf{A}_{\bar{l}-\bar{p}} + \lambda \mathbf{I} \right) - \mathbf{A}_x^T (-\mathbf{A}_x) \right)^{-1}.$$
 (16)

Based on (16), the matrix inversion lemma [23, equation (1a)] and the inverse of a sum of matrices [24, equation (20)] were applied to to deduce the algorithm 1 in [10], i.e.,

$$\begin{pmatrix}
p \leq k : \begin{cases}
\mathbf{B} = \mathbf{Q}_{\bar{l}-\bar{p}} \mathbf{A}_x^T (\mathbf{I} + \mathbf{A}_x \mathbf{Q}_{\bar{l}-\bar{p}} \mathbf{A}_x^T)^{-1} \\
\mathbf{Q}_{\bar{l}} = \mathbf{Q}_{\bar{l}-\bar{p}} - \mathbf{B} \mathbf{A}_x \mathbf{Q}_{\bar{l}-\bar{p}}
\end{cases}, \quad (17a)$$

$$\begin{pmatrix}
p \ge k : \begin{cases}
\mathbf{Q}_{\bar{l}} = (\mathbf{I} + \mathbf{Q}_{\bar{l}-\bar{p}}\mathbf{A}_x^T\mathbf{A}_x)^{-1}\mathbf{Q}_{\bar{l}-\bar{p}} \\
\mathbf{B} = \mathbf{Q}_{\bar{l}}\mathbf{A}_x^T
\end{cases}, \quad (17b)$$

and

$$\mathbf{W}_{\bar{l}} = \mathbf{W}_{\bar{l}-\bar{p}} + \mathbf{B} \left( \mathbf{Y}_a - \mathbf{A}_x \mathbf{W}_{\bar{l}-\bar{p}} \right).$$
(18)

The inverse Cholesky Factor [7] of  $\mathbf{R}_{\bar{l}} = \mathbf{A}_{\bar{l}}^T \mathbf{A}_{\bar{l}} + \lambda \mathbf{I}$  is the upper-triangular  $\mathbf{F}_{\bar{l}}$  satisfying

$$\mathbf{F}_{\bar{l}}\mathbf{F}_{\bar{l}}^{T} = (\mathbf{A}_{\bar{l}}^{T}\mathbf{A}_{\bar{l}} + \lambda \mathbf{I})^{-1} = \mathbf{Q}_{\bar{l}}.$$
(19)

Instead of updating the inverse  $\mathbf{Q}_{\bar{l}}$  by (17), the algorithm 2 proposed in [10] computes the inverse Cholesky factor  $\mathbf{F}_{\bar{l}}$  from  $\mathbf{F}_{\bar{l}-\bar{\nu}}$  by

$$\mathbf{F}_{\bar{l}} = \mathbf{F}_{\bar{l}-\bar{p}} \mathbf{V},\tag{20}$$

where the upper-triangular V satisfies

$$\mathbf{V}\mathbf{V}^{T} = \begin{cases} \mathbf{I} - \mathbf{S}^{T} (\mathbf{I} + \mathbf{S}\mathbf{S}^{T})^{-1} \mathbf{S} & if \ p \le k \\ (\mathbf{I} + \mathbf{S}^{T}\mathbf{S})^{-1} & if \ p \ge k, \end{cases}$$
(21a)

and S in 
$$(21)$$
 is computed by

$$\mathbf{S} = \mathbf{A}_x \mathbf{F}_{\bar{l}-\bar{p}}.\tag{22}$$

Then the algorithm 2 in [10] computes  $\mathbf{W}_{\bar{l}}$  from  $\mathbf{W}_{\bar{l}-\bar{p}}$  and  $\mathbf{F}_{\bar{l}}$  by

$$\mathbf{W}_{\bar{l}} = \mathbf{W}_{\bar{l}-\bar{p}} + (\mathbf{F}_{\bar{l}}\mathbf{F}_{\bar{l}}^T\mathbf{A}_x^T) \left(\mathbf{Y}_a - \mathbf{A}_x\mathbf{W}_{\bar{l}-\bar{p}}\right).$$
(23)

To reduce the computational complexity, a smaller inverse and inverse Cholesky factorization are chosen in (17) and (21), respectively, according to the size of the  $p \times k$  matrix  $\mathbf{A}_x$ . Moreover, the upper-triangular inverse Cholesky factor in (19) and (21) can be computed by the inverse Choleksy factorization [22], or by inverting and transposing the traditional lowertriangular Cholesky factor [25].

## III. PROPOSED DECREMENTAL LEARNING ALGORITHMS

## A. Proposed Decremental Learning Algorithm for Reduced Nodes

Assume the  $\rho$  nodes corresponding to the columns  $i_1, i_2, \cdots, i_{\rho}$  ( $i_1 < i_2 < \cdots < i_{\rho}$ ) in  $\mathbf{A}_k$  needs to be removed. Then let us permute the columns  $i_1, i_2, \cdots, i_{\rho}$  in  $\mathbf{A}_k$  to be the last  $1^{st}, 2^{nd}, \cdots, \rho^{th}$  columns, respectively, and the permuted  $\mathbf{A}_k$  can be written as

$$\mathbf{A}_{k} = \left[\mathbf{A}_{k-\rho} | \mathbf{A}_{\rho}\right],\tag{24}$$

where  $\mathbf{A}_{\rho}$  includes the  $\rho$  columns to be removed. Accordingly we need to permute the rows  $i_1, i_2, \dots, i_{\rho}$  in  $\mathbf{F}_k$  and  $\mathbf{W}_k$  to be the last  $1^{st}, 2^{nd}, \dots, \rho^{th}$  rows, respectively, as can be seen from (8) and (2). The permuted  $\mathbf{F}_k$  can be block-triangularized by an unitary transformation  $\Sigma$ , i.e.,

$$\mathbf{F}_{k}\boldsymbol{\Sigma} = \begin{bmatrix} \mathbf{F}_{k-\rho} & \mathbf{T}_{\rho} \\ \mathbf{0} & \mathbf{G}_{\rho} \end{bmatrix}, \qquad (25)$$

where  $\mathbf{T}_{\rho}$  includes  $\rho$  columns, and  $\mathbf{G}_{\rho}$  is  $\rho \times \rho$ . The submatrix  $\mathbf{F}_{k-\rho}$  in (25) is the "square-root" matrix [22], [26] of  $\mathbf{Q}_{k-\rho} = \mathbf{R}_{k-\rho}^{-1}$  that satisfies  $\mathbf{F}_{k-\rho}\mathbf{F}_{k-\rho}^{T} = \mathbf{Q}_{k-\rho} = \mathbf{R}_{k-\rho}^{-1}$ , as can be seen by comparing (25) with (9). From the permuted  $\mathbf{W}_{k}$ , the output weights  $\mathbf{W}_{k-\rho}$  for the remaining  $k-\rho$  nodes can be computed by

$$\mathbf{W}_{k-\rho} = \mathbf{W}_{k}^{1:(k-\rho),:} - \mathbf{T}_{\rho}\mathbf{G}_{\rho}^{-1}\mathbf{W}_{k}^{(k-\rho+1):k,:}, \qquad (26)$$

where  $\mathbf{W}_{k}^{i:j,:}$  denotes the sub-matrix in  $\mathbf{W}_{k}$  from the  $i^{th}$  row to the  $j^{th}$  row. The derivation of (26) is in Appendix A.

The unitary transformation  $\Sigma$  in (25) can be formed by a sequence of Givens rotations [22]. Assume k = 6 and the rows 2 and 4 in  $\mathbf{F}_6$  are permuted to be the last  $1^{st}$  and  $2^{nd}$  rows, respectively. The effect of the sequence of Givens rotations to triangularize the permuted  $\mathbf{F}_6$  can be shown as

where  $\Omega_{m,n}^{i}$  is the Givens rotation that zeroes the  $m^{th}$  entry in the  $i^{th}$  row and rotates the  $m^{th}$  and  $n^{th}$  entries in each row of  $\mathbf{F}_{k}$ , and \* denotes the non-zero entries rotated by the current Givens rotation. It can be seen that the sequence of Givens rotations obtain the upper-triangular  $\mathbf{F}_{k-\rho}$  and  $\mathbf{G}_{\rho}$ .

In (25), the unitary transformation  $\Sigma$  can also be formed by several Householder reflections [25] or a block Householder transformation [27]. When  $\Sigma$  is formed by a block Householder transformation, usually  $\mathbf{F}_{k-\rho}$  and  $\mathbf{G}_{\rho}$  in (25) are no longer upper-triangular. Moreover, since there are many zeros in  $\mathbf{F}_k$ , we can use a smaller block Householder transformation to reduce the computational complexity. For example, assume the permuted  $\mathbf{F}_6$  is

$$\mathbf{F}_{6} = \begin{vmatrix} x & x & x & x & x & x \\ 0 & x & x & x & x & x \\ 0 & 0 & 0 & x & x & x \\ 0 & 0 & 0 & 0 & 0 & x & x \\ 0 & 0 & 0 & x & x & x & x \\ 0 & 0 & x & x & x & x & x \end{vmatrix},$$

and then we can set  $\Sigma = \begin{bmatrix} I_2 & 0 \\ 0 & \Theta \end{bmatrix}$ , where  $I_2$  is the  $2 \times 2$  identity matrix, and  $\Theta$  is a block Householder transformation.

## B. Proposed Decremental Learning Algorithms for Reduced Inputs

Permute the rows in  $\mathbf{A}_{\bar{l}}$  to put the training samples to be removed into the sub-matrix  $\mathbf{A}_{\bar{\delta}}$  with the last  $\delta$  rows, i.e.,

$$\mathbf{A}_{\bar{l}} = \begin{bmatrix} \mathbf{A}_{\bar{l}-\bar{\delta}} \\ \mathbf{A}_{\bar{\delta}} \end{bmatrix}, \qquad (27)$$

and permute the rows in  $\mathbf{Y}_{\bar{l}}$  accordingly to obtain

$$\mathbf{Y}_{\bar{l}} = \begin{bmatrix} \mathbf{Y}_{\bar{l}-\bar{\delta}} \\ \mathbf{Y}_{\bar{\delta}} \end{bmatrix}.$$
 (28)

The proposed decremental learning algorithm 1 for reduced inputs computes  $Q_{\bar{l}-\bar{\delta}}$  by

$$\mathbf{Q}_{ar{l}-ar{\delta}} = \mathbf{ ilde{B}} \mathbf{Q}_{ar{l}}$$

(29)

where

$$\tilde{\mathbf{B}} = \begin{cases} \mathbf{I} + \mathbf{Q}_{\bar{l}} \mathbf{A}_{\bar{\delta}}^T (\mathbf{I} - \mathbf{A}_{\bar{\delta}} \mathbf{Q}_{\bar{l}} \mathbf{A}_{\bar{\delta}}^T)^{-1} \mathbf{A}_{\bar{\delta}} & if \ \delta \le k \quad (30a) \\ \left( \mathbf{I} - \mathbf{Q}_{\bar{l}} \mathbf{A}_{\bar{\delta}}^T \mathbf{A}_{\bar{\delta}} \right)^{-1} & if \ \delta \ge k, \quad (30b) \end{cases}$$

and compute the output weights by

$$\mathbf{W}_{\bar{l}-\bar{\delta}} = \tilde{\mathbf{B}}(\mathbf{W}_{\bar{l}} - \mathbf{Q}_{\bar{l}}\mathbf{A}_{\bar{\delta}}^T\mathbf{Y}_{\bar{\delta}}). \tag{31}$$

The derivation of (29), (30) and (31) is in Appendix B.

The proposed decremental learning algorithm 2 for reduced inputs updates  $\mathbf{F}_{\bar{l}}$  satisfying (19) by

$$\mathbf{F}_{\bar{l}-\bar{\delta}} = \mathbf{F}_{\bar{l}} \mathbf{V},\tag{32}$$

and the upper-triangular V in (32) is computed by

$$\mathbf{V}\mathbf{V}^{T} = \begin{cases} \mathbf{I} + \mathbf{S}^{T} (\mathbf{I} - \mathbf{S}\mathbf{S}^{T})^{-1} \mathbf{S} & if \ \delta \leq k \qquad (33a) \\ \left(\mathbf{I} - \mathbf{S}^{T}\mathbf{S}\right)^{-1} & if \ \delta \geq k, \qquad (33b) \end{cases}$$

$$\mathbf{S} = \mathbf{A}_{\bar{\delta}} \mathbf{F}_{\bar{l}}.\tag{34}$$

Moreover, the proposed decremental learning algorithm 2 for reduced inputs computes the output weights  $\mathbf{W}_{\bar{l}-\bar{\delta}}$  by

$$\mathbf{W}_{\bar{l}-\bar{\delta}} = \mathbf{F}_{\bar{l}-\bar{\delta}} \mathbf{V}^T \mathbf{F}_{\bar{l}}^{-1} \mathbf{W}_{\bar{l}} - \mathbf{F}_{\bar{l}-\bar{\delta}} \mathbf{F}_{\bar{l}-\bar{\delta}}^T \mathbf{A}_{\bar{\delta}}^T \mathbf{Y}_{\bar{\delta}}.$$
 (35)

The derivation of (33) and (35) is also in Appendix B.

To compute (33a), firstly compute the inverse Cholesky factor of  $\mathbf{I} - \mathbf{SS}^T$ , i.e., the upper-triangular  $\tilde{\mathbf{F}}$  satisfying

$$\tilde{\mathbf{F}}\tilde{\mathbf{F}}^{T} = \left(\mathbf{I} - \mathbf{S}\mathbf{S}^{T}\right)^{-1}.$$
(36)

Then we need to compute the upper-triangular V satisfying

$$\mathbf{V}\mathbf{V}^T = \mathbf{I} + (\mathbf{S}^T\tilde{\mathbf{F}})(\mathbf{S}^T\tilde{\mathbf{F}})^T, \qquad (37)$$

where the upper-triangular Cholesky factor V is different from the traditional lower-triangular Cholesky factor [25].

#### **IV. NUMERICAL EXPERIMENTS**

We compare the proposed decremental learning algorithms for BLS with the standard ridge solution for BLS (by (2) and (3)), by the simulations on MATLAB software platform under a Microsoft-Windows Server with 128 GB of RAM. We give the experimental results on the Modified National Institute of Standards and Technology (MNIST) dataset [28] with 60000 training images and 10000 testing images. For the enhancement nodes, the weights  $\mathbf{W}_{h_j}$  and the biases  $\beta_{h_j}$  ( $j = 1, 2, \dots, m$ ) are drawn from the standard uniform distributions on the interval  $\begin{bmatrix} -1 & 1 \end{bmatrix}$ , and the sigmoid function is chosen.

In Table I, we give the testing accuracy of the standard ridge solution (by (2) and (3)) and the proposed decremental learning algorithm for reduced nodes, which are abbreviated as "Standard" and "Proposed", respectively. We set the initial network as  $10 \times 10$  feature nodes and 11000 enhancement nodes. Then the enhancement nodes are dynamically decreased from 11000 to 7000, and  $\rho = 1000$  enhancement nodes are

TABLE I SNAPSHOT RESULTS OF TESTING ACCURACY FOR THE BLS ALGORITHMS

Number of	$\lambda = 10^{-3}$							
Enhancement	Testing Ac	curacy (%)	Testing Accuracy (%)					
Nodes	Standard	Proposed	Standard	Proposed				
11000	97.23	97.23	96.95	96.95				
$11000\rightarrow10000$	97.18	97.18	96.92	96.92				
$10000 \rightarrow 9000$	97.05	97.05	96.78	96.78				
$9000 \rightarrow 8000$	96.99	96.99	96.74	96.74				
$8000 \rightarrow 7000$	96.79	96.79	96.59	96.59				

removed in each update. The snapshot results of each update are shown in Table I, where the ridge parameter  $\lambda$  is set to  $10^{-3}$ . As observed from Table I, the proposed decremental learning algorithm for reduced nodes always achieves the testing accuracy of the standard ridge solution.

We also simulate the decremental BLS on reduced inputs. We set the network as  $10 \times 10$  feature nodes and 5000 enhancement nodes, and then the total node number is k = 5100. In Table II, we train the initial network under the first l = 60000training samples, and decrease  $\delta = 10000 > k$  training samples in each update, until only 10000 training samples are fed. On the other hand, in Table III, we train the initial network under the first l = 60000 training samples, and decrease  $\delta = 1000 < k$  training samples in each update, until only 55000 training samples are fed. The snapshot results of each update are shown in Tables II and III, where the ridge parameter  $\lambda$  is set to  $10^{-3}$  and  $10^{-1}$ . In Tables II and III, "Standard" is the abbreviation of the standard ridge solution, while "Alg. 1" and "Alg. 2" are the abbreviations of the proposed decremental learning algorithms 1 and 2 for reduced inputs, respectively. As can be seen from Table II and Table III, the proposed decremental learning algorithms 1 and 2 for reduced inputs always achieve the testing accuracy of the standard ridge solution.

## V. CONCLUSION

The decremental learning algorithms are required in machine learning, to prune redundant nodes [12]–[17] and remove obsolete inline training samples [18]–[20]. In this paper, an efficient decremental learning algorithm to prune redundant nodes is deduced from the incremental learning algorithm 1 proposed in [9] for added nodes, and two decremental learning algorithms to remove training samples are deduced from the two incremental learning algorithms proposed in [10] for added inputs.

The proposed decremental learning algorithm for reduced nodes utilizes the inverse Cholesky factor of the Hermitian matrix in the ridge inverse, to update the output weights recursively by (26), as the incremental learning algorithm 1 for added nodes in [9], while that inverse Cholesky factor is updated with an unitary transformation by (25). The proposed decremental learning algorithm 1 for reduced inputs updates the output weights recursively with the inverse of the Hermitian matrix in the ridge inverse, and updates that inverse recursively, as the incremental learning algorithm 1 for added

Number of	$\lambda = 10^{-3}$						$\lambda = 10^{-1}$						
Input	Training Accuracy (%)			Testing Accuracy (%)			Training Accuracy (%)			Testing Accuracy (%)			
Patterns	Standard	Alg. 1	Alg. 2	Standard	Alg. 1	Alg. 2	Standard	Alg. 1	Alg. 2	Standard	Alg. 1	Alg. 2	
60000	96.87	96.87	96.87	96.77	96.77	96.77	92.58	92.58	92.58	93.05	93.05	93.05	
→ <b>50000</b>	96.84	96.84	96.84	96.67	96.67	96.67	92.47	92.47	92.47	92.75	92.75	92.75	
$\xrightarrow[10000]{}$ 40000	96.76	96.76	96.76	96.59	96.59	96.59	92.22	92.22	92.22	92.54	92.54	92.54	
$\xrightarrow[10000]{}$ 30000	96.58	96.58	96.58	96.34	96.34	96.34	91.82	91.82	91.82	92.23	92.23	92.23	
$\xrightarrow[10000]{}$ 20000	96.41	96.41	96.41	96.11	96.11	96.11	91.47	91.47	91.47	91.61	91.61	91.61	
$\xrightarrow[10000]{}$ 10000	96.19	96.19	96.19	95.62	95.62	95.62	90.54	90.54	90.54	90.71	90.71	90.71	

TABLE II SNAPSHOT RESULTS OF TESTING ACCURACY FOR 4 BLS ALGORITHMS WITH p = 10000 > k = 5100

TABLE III SNAPSHOT RESULTS OF TESTING ACCURACY FOR 4 BLS ALGORITHMS WITH p = 1000 < k = 5100

Number of	$\lambda = 10^{-3}$						$\lambda = 10^{-1}$					
Input	Training Accuracy (%)			Testing Accuracy (%)			Training Accuracy (%)			Testing Accuracy (%)		
Patterns	Standard	Alg. 1	Alg. 2	Standard	Alg. 1	Alg. 2	Standard	Alg. 1	Alg. 2	Standard	Alg. 1	Alg. 2
60000	96.34	96.34	96.34	96.21	96.21	96.21	92.83	92.83	92.83	93.24	93.24	93.24
$\xrightarrow[1000]{}$ 59000	96.34	96.34	96.34	96.23	96.23	96.23	92.82	92.82	92.82	93.22	93.22	93.22
$\xrightarrow[1000]{}$ 58000	96.31	96.31	96.31	96.26	96.26	96.26	92.81	92.81	92.81	93.15	93.15	93.15
$\xrightarrow[1000]{}$ 57000	96.31	96.31	96.31	96.22	96.22	96.22	92.81	92.81	92.81	93.11	93.11	93.11
$\xrightarrow[1000]{}$ 56000	96.33	96.33	96.33	96.19	96.19	96.19	92.81	92.81	92.81	93.09	93.09	93.09
$\xrightarrow[1000]{}$ 55000	96.32	96.32	96.32	96.22	96.22	96.22	92.78	92.78	92.78	93.07	93.07	93.07

inputs in [10]. Moreover, the proposed decremental learning algorithm 2 for reduced inputs updates the output weights recursively with the inverse Cholesky factor of the Hermitian matrix in the ridge inverse, and updates that inverse Cholesky factor recursively by multiplying it with an upper-triangular intermediate matrix, as the incremental learning algorithm 2 for added inputs in [10].

In numerical experiments, all the proposed 3 decremental learning algorithms for reduced nodes or inputs always achieve the testing accuracy of the standard ridge solution. When some nodes or training samples are removed, the standard ridge solution by (2) and (3) requires high computational complexity to retrain the whole network from the beginning, while the proposed decremental learning algorithms update the output weights easily for reduced nodes or inputs without a retraining process.

## APPENDIX A Derivation of (26)

From (11) we can deduce  $\mathbf{W}_k = \mathbf{F}_k \mathbf{\Sigma} (\mathbf{F}_k \mathbf{\Sigma})^T \mathbf{A}_k^T \mathbf{Y}$ , into which we substitute (25) and (24) to obtain

$$\mathbf{W}_{k} = \begin{bmatrix} \mathbf{F}_{k-\rho} & \mathbf{T}_{\rho} \\ \mathbf{0} & \mathbf{G}_{\rho} \end{bmatrix} \begin{bmatrix} \mathbf{F}_{k-\rho} & \mathbf{T}_{\rho} \\ \mathbf{0} & \mathbf{G}_{\rho} \end{bmatrix}^{T} \begin{bmatrix} \mathbf{A}_{k-\rho} | \mathbf{A}_{\rho} \end{bmatrix}^{T} \mathbf{Y}, \quad (38)$$

i.e.,

$$\begin{split} \mathbf{W}_{k} &= \\ \begin{bmatrix} \mathbf{F}_{k-\rho} \mathbf{F}_{k-\rho}^{T} \mathbf{A}_{k-\rho}^{T} \mathbf{Y} + \mathbf{T}_{\rho} (\mathbf{T}_{\rho}^{T} \mathbf{A}_{k-\rho}^{T} \mathbf{Y} + \mathbf{G}_{\rho}^{T} \mathbf{A}_{\rho}^{T} \mathbf{Y}) \\ \mathbf{G}_{\rho} (\mathbf{T}_{\rho}^{T} \mathbf{A}_{k-\rho}^{T} \mathbf{Y} + \mathbf{G}_{\rho}^{T} \mathbf{A}_{\rho}^{T} \mathbf{Y}) \end{bmatrix}, \end{split}$$

into which substitute (11) to obtain

$$\begin{cases} \mathbf{W}_{k}^{1:(k-\rho),:} = \mathbf{W}_{k-\rho} + \mathbf{T}_{\rho}(\mathbf{T}_{\rho}^{T}\mathbf{A}_{k-\rho}^{T}\mathbf{Y} + \mathbf{G}_{\rho}^{T}\mathbf{A}_{\rho}^{T}\mathbf{Y}) (39a) \\ \mathbf{W}_{k}^{(k-\rho+1):k,:} = \mathbf{G}_{\rho}(\mathbf{T}_{\rho}^{T}\mathbf{A}_{k-\rho}^{T}\mathbf{Y} + \mathbf{G}_{\rho}^{T}\mathbf{A}_{\rho}^{T}\mathbf{Y}) \qquad (39b) \end{cases}$$
  
From (39b) we deduce  $\mathbf{T}_{\rho}^{T}\mathbf{A}_{k-\rho}^{T}\mathbf{Y} + \mathbf{G}_{\rho}^{T}\mathbf{A}_{\rho}^{T}\mathbf{Y} = \mathbf{G}_{\rho}^{-1}\mathbf{W}_{k}^{(k-\rho+1):k,:},$  which is then substituted into (39a) to obtain (26).

## APPENDIX B DERIVATION OF (33), (29), (30), (31) AND (35)

From (27) and (15), we can deduce

$$\mathbf{Q}_{\bar{l}-\bar{\delta}} = \left( \left( \mathbf{A}_{\bar{l}}^T \mathbf{A}_{\bar{l}} + \lambda \mathbf{I} \right) - \mathbf{A}_{\bar{\delta}}^T \mathbf{A}_{\bar{\delta}} \right)^{-1}.$$
 (40)

Obviously we can replace  $\mathbf{Q}_{\bar{l}}$ ,  $\mathbf{A}_{\bar{l}-\bar{p}}^T$ ,  $\mathbf{A}_{\bar{l}-\bar{p}}^T$ ,  $\mathbf{A}_x^T$  and  $-\mathbf{A}_x$  in (16) with  $\mathbf{Q}_{\bar{l}-\bar{\delta}}$ ,  $\mathbf{A}_{\bar{l}}^T$ ,  $\mathbf{A}_{\bar{l}}$ ,  $\mathbf{A}_{\bar{\delta}}^T$  and  $\mathbf{A}_{\bar{\delta}}$ , respectively, to obtain (40), and then we can make the same replacement in (21) and (17), to obtain (33) and

$$\left\{ \begin{array}{l} \delta \leq k : \left\{ \begin{array}{l} \mathbf{B} = \mathbf{Q}_{\bar{l}} \mathbf{A}_{\bar{\delta}}^T (\mathbf{I} - \mathbf{A}_{\bar{\delta}} \mathbf{Q}_{\bar{l}} \mathbf{A}_{\bar{\delta}}^T)^{-1} \\ \mathbf{Q}_{\bar{l}-\bar{\delta}} = \mathbf{Q}_{\bar{l}} + \mathbf{B} \mathbf{A}_{\bar{\delta}} \mathbf{Q}_{\bar{l}} \end{array} \right. , \qquad (41a)$$

$$\delta \geq k : \begin{cases} \mathbf{Q}_{\bar{l}-\bar{\delta}} = \left(\mathbf{I} - \mathbf{Q}_{\bar{l}}\mathbf{A}_{\bar{\delta}}^T\mathbf{A}_{\bar{\delta}}\right)^{-1}\mathbf{Q}_{\bar{l}} \\ \mathbf{B} = \mathbf{Q}_{\bar{l}-\bar{\delta}}\mathbf{A}_{\bar{\delta}}^T \end{cases} , \qquad (41b)$$

respectively. From (41) we can deduce (29) and (30).

From (14) we can obtain  $\mathbf{W}_{\bar{l}-\bar{\delta}} = \mathbf{Q}_{\bar{l}-\bar{\delta}} \mathbf{A}_{\bar{l}-\bar{\delta}}^T \mathbf{Y}_{\bar{l}-\bar{\delta}}$ , into which we substitute (29) to obtain

$$\mathbf{W}_{\bar{l}-\bar{\delta}} = \tilde{\mathbf{B}} \mathbf{Q}_{\bar{l}} \mathbf{A}_{\bar{l}-\bar{\delta}}^T \mathbf{Y}_{\bar{l}-\bar{\delta}}.$$
 (42)

On the other hand, let us substitute (27) and (28) into (14) to obtain  $\mathbf{W}_{\bar{l}} = \mathbf{Q}_{\bar{l}} \begin{bmatrix} \mathbf{A}_{\bar{l}-\bar{\delta}} \end{bmatrix}^T \begin{bmatrix} \mathbf{Y}_{\bar{l}-\bar{\delta}} \end{bmatrix}$ , i.e.,

$$\mathbf{Q}_{\bar{l}} - \mathbf{Q}_{\bar{l}} \begin{bmatrix} \mathbf{A}_{\bar{\delta}} \end{bmatrix} \begin{bmatrix} \mathbf{Y}_{\bar{\delta}} \end{bmatrix}, \text{ Ic.},$$
$$\mathbf{Q}_{\bar{l}} \mathbf{A}_{\bar{l}-\bar{\delta}}^T \mathbf{Y}_{\bar{l}-\bar{\delta}} = \mathbf{W}_{\bar{l}} - \mathbf{Q}_{\bar{l}} \mathbf{A}_{\bar{\delta}}^T \mathbf{Y}_{\bar{\delta}}. \tag{43}$$

Finally we can substitute (43) into (42) to obtain (31).

Substitute (32) into (19) to obtain  $\mathbf{Q}_{\bar{l}-\bar{\delta}} = \mathbf{F}_{\bar{l}-\bar{\delta}} \mathbf{V}^T \mathbf{F}_{\bar{l}}^T$ , which is then substituted into (42) to obtain

$$\mathbf{W}_{\bar{l}-\bar{\delta}} = \mathbf{F}_{\bar{l}-\bar{\delta}} \mathbf{V}^T \mathbf{F}_{\bar{l}}^T \mathbf{A}_{\bar{l}-\bar{\delta}}^T \mathbf{Y}_{\bar{l}-\bar{\delta}}, \tag{44}$$

i.e.,

$$\mathbf{W}_{\bar{l}-\bar{\delta}} = \mathbf{F}_{\bar{l}-\bar{\delta}} \mathbf{V}^{T} \mathbf{F}_{\bar{l}}^{-1} \mathbf{F}_{\bar{l}} \mathbf{F}_{\bar{l}}^{1} \mathbf{A}_{\bar{l}-\bar{\delta}}^{1} \mathbf{Y}_{\bar{l}-\bar{\delta}}.$$
 (45)

Then substitute (19) into (45) to obtain

$$\mathbf{W}_{\bar{l}-\bar{\delta}} = \mathbf{F}_{\bar{l}-\bar{\delta}} \mathbf{V}^T \mathbf{F}_{\bar{l}}^{-1} \mathbf{Q}_{\bar{l}-\bar{\delta}} \mathbf{A}_{\bar{l}-\bar{\delta}}^T \mathbf{Y}_{\bar{l}-\bar{\delta}}, \tag{46}$$

into which substitute (43) to obtain

$$\mathbf{W}_{\bar{l}-\bar{\delta}} = \mathbf{F}_{\bar{l}-\bar{\delta}} \mathbf{V}^T \mathbf{F}_{\bar{l}}^{-1} (\mathbf{W}_{\bar{l}} - \mathbf{Q}_{\bar{l}} \mathbf{A}_{\bar{\delta}}^T \mathbf{Y}_{\bar{\delta}}).$$
(47)

Finally let us substitute (19) into (47) to obtain

 $\mathbf{W}_{\bar{l}-\bar{\delta}} = \mathbf{F}_{\bar{l}-\bar{\delta}} \mathbf{V}^T \mathbf{F}_{\bar{l}}^{-1} (\mathbf{W}_{\bar{l}} - \mathbf{F}_{\bar{l}} \mathbf{F}_{\bar{l}}^T \mathbf{A}_{\bar{\delta}}^T \mathbf{Y}_{\bar{\delta}}), \text{ i.e.,}$ 

$$\mathbf{W}_{\bar{l}-\bar{\delta}} = \mathbf{F}_{\bar{l}-\bar{\delta}} \mathbf{V}^T \mathbf{F}_{\bar{l}}^{-1} \mathbf{W}_{\bar{l}} - \mathbf{F}_{\bar{l}-\bar{\delta}} \mathbf{V}^T \mathbf{F}_{\bar{l}}^T \mathbf{A}_{\bar{\delta}}^T \mathbf{Y}_{\bar{\delta}}, \qquad (48)$$

into which we can substitute (32) to obtain (35).

#### REFERENCES

- M. Leshno, V. Y. Lin, A. Pinkus, and S. Schocken, "Multilayer feedforward networks with a nonpolynomial activation function can approximate any function," *Neural Netw.*, vol. 6, no. 6, pp. 861-867.
- [2] Y.-H. Pao and Y. Takefuji, "Functional-link net computing: Theory, system architecture, and functionalities," *Computer*, vol. 25, no. 5, pp. 76-79, May 1992.
- [3] Y.-H. Pao, G.-H. Park, and D. J. Sobajic, "Learning and generalization characteristics of the random vector functional-link net," *Neurocomputing*, vol. 6, no. 2, pp. 163-180, 1994.
- [4] Y. LeCun et al., "Handwritten digit recognition with a back-propagation network," Proc. Neural Inf. Process. Syst. (NIPS), 1990, pp. 396-404.
- [5] J. S. Denker et al., "Neural network recognizer for hand-written zip code digits," Advances in Neural Information Processing Systems, D. S. Touretzky, Ed. San Francisco, CA, USA: Morgan Kaufmann, 1989, pp. 323-331.
- [6] C. L. Philip Chen and J. Z. Wan, "A rapid learning and dynamic stepwise updating algorithm for flat neural networks and the application to timeseries prediction", *IEEE Trans. Syst., Man, Cybern. B, Cybern.*, vol. 29, no. 1, pp. 62-72, Feb. 1999.
- [7] C. L. Philip Chen, and Z. Liu, "Broad Learning System: An Effective and Efficient Incremental Learning System Without the Need for Deep Architecture", *IEEE Transactions on Neural Networks and Learning Systems*, vol. 29, no. 1, Jan. 2018.
- [8] C. L. Philip Chen, Z. Liu, and S. Feng, "Universal Approximation Capability of Broad Learning System and Its Structural Variations", *IEEE Transactions on Neural Networks and Learning Systems*, vol. 30, no. 4, April 2019.
- [9] H. Zhu and C. Wei, "Efficient Ridge Solution for the Incremental Broad Learning System on Added Nodes by Inverse Cholesky Factorization of a Partitioned Matrix", arXiv preprint arXiv: 1911.04872(2019).
- [10] H. Zhu and C. Wei, "Efficient Ridge Solutions for the Incremental Broad Learning System on Added Inputs by Updating the Inverse or the Inverse Cholesky Factor of the Hermitian matrix in the Ridge Inverse", arXiv preprint arXiv: 1911.07292(2019).
- [11] Donald W. Marquaridt, "Generalized Inverses, Ridge Regression, Biased Linear Estimation, and Nonlinear Estimation", *Technometrics*, vol. 12, no. 3, Aug. 1970.
- [12] E. D. Karnin, "A simple procedure for pruning back-propagation trained neural networks", *IEEE Trans. Neural Netw.*, vol. 1, no. 2, pp. 239C242, Jun. 1990.

- [13] G. Castellano, A. M. Fanelli, and M. Pelillo, "An iterative pruning algorithm for feedforward neural networks", *IEEE Trans. Neural Netw.*, vol. 8, no. 3, pp. 519C531, May 1997.
  [14] X. Zeng and D. S. Yeung, "Hidden neuron pruning of multilayer
- [14] X. Zeng and D. S. Yeung, "Hidden neuron pruning of multilayer perceptrons using a quantified sensitivity measure", *Neurocomputing*, vol. 69, no. 7C9, pp. 825C837, 2006.
- [15] H.-J. Rong, Y.-S. Ong, A.-H. Tan, and Z. Zhu, "A fast pruned-extreme learning machine for classification problem", *Neurocomputing*, vol. 72, nos. 1C3, pp. 359C366, 2008.
- [16] Y. Miche, A. Sorjamaa, P. Bas, O. Simula, C. Jutten, and A. Lendasse, "OP-ELM: Optimally pruned extreme learning machine", *IEEE Trans. Neural Netw.*, vol. 21, no. 1, pp. 158C162, Jan. 2010.
- [17] X. Xie, H. Zhang, J. Wang, Q. Chang, J. Wang, and N. R. Pal, "Learning Optimized Structure of Neural Networks by Hidden Node Pruning With L<sub>1</sub> Regularization", *IEEE Transactions on Cybernetics*, Early Access Article, 2019.
- [18] G. Cauwenberghs and T. Poggio, "Incremental and Decremental Support Vector Machine Learning", Adv. Neural Information Processing Systems (NIPS\*2000), Cambridge MA: MIT Press, vol. 13, 2001.
- [19] M. Karasuyama and I. Takeuchi, "Multiple Incremental Decremental Learning of Support Vector Machines", *IEEE Transactions on Neural Networks*, vol. 21, no. 7, 2010.
- [20] L. Zhu, S. Pang, A. Sarrafzadeh, T. Ban, and D. Inoue, "Incremental and Decremental Max-Flow for Online Semi-Supervised Learning", *IEEE Transactions on Knowledge and Data Engineering*, vol. 28, no. 8, 2016.
- [21] A. Ben-Israel and T. Greville, *Generalized Inverses: Theory and Applications*, New York, USA, Wiley, 1974.
- [22] H. Zhu, W. Chen, B. Li, and F. Gao, "An Improved Square-Root Algorithm for V-BLAST Based on Efficient Inverse Cholesky Factorization", *IEEE Trans. Wireless Commun.*, vol. 10, no. 1, Jan. 2011.
- [23] D.J. Tylavsky and G.R.L. Sohie, "Generalization of the matrix inversion lemma", *Proceedings of the IEEE*, pp. 1050-1052, vol. 74, no. 7, 1986.
- [24] H. V. Henderson and S. R. Searle, "On Deriving the Inverse of a Sum of Matrices", *SIAM Review*, vol. 23, no. 1, January 1981.
- [25] G. H. Golub and C. F. Van Loan, *Matrix Computations*, third ed. Baltimore, MD: Johns Hopkins Univ. Press, 1996.
- [26] H. Zhu, Z. Lei, and F. P. S. Chin, "An improved square-root algorithm for BLAST," *IEEE Signal Process. Lett.*, vol. 11, no. 9, pp. 772-775, Sept. 2004.
- [27] F.Rotella, I.Zambettakis, "Block Householder transformation for parallel QR factorization," *Applied Mathematics Letters*, vol. 12, no. 4, pp. 29-34, May 1999.
- [28] Y. LeCun, L. Bottou, Y. Bengio, and P. Haffner, "Gradient-based learning applied to document recognition", *Proc. IEEE*, vol. 86, no. 11, pp. 2278-2324, Nov. 1998.