

On Optimal Load-Memory Tradeoff of Cache-Aided Scalar Linear Function Retrieval

Kai Wan, *Member, IEEE*, Hua Sun, *Member, IEEE*, Mingyue Ji, *Member, IEEE*,
Daniela Tuninetti, *Senior Member, IEEE*, and Giuseppe Caire, *Fellow, IEEE*

Abstract

Coded caching has the potential to greatly reduce network traffic by leveraging the cheap and abundant storage available in end-user devices so as to create multicast opportunities in the delivery phase. In the seminal work by Maddah-Ali and Niesen (MAN), the shared-link coded caching problem was formulated, where each user demands one file (i.e., single file retrieval). This paper generalizes the MAN problem so as to allow users to request *scalar linear functions* of the files. This paper proposes a novel coded delivery scheme that, based on MAN uncoded cache placement, is shown to allow for the decoding of arbitrary scalar linear functions of the files (on arbitrary finite fields). Interestingly, and quite surprisingly, it is shown that the load for cache-aided scalar linear function retrieval depends on the number of linearly independent functions that are demanded, akin to the cache-aided single-file retrieval problem where the load depends on the number of distinct file requests. The proposed scheme is optimal under the constraint of uncoded cache placement, in terms of worst-case load, and within a factor 2 otherwise. The key idea of this paper can be extended to all scenarios which the original MAN scheme has been extended to, including demand-private and/or device-to-device settings.

A short version of this paper was submitted to the IEEE 2020 International Symposium on Information Theory, Los Angeles, California, USA.

K. Wan and G. Caire are with the Electrical Engineering and Computer Science Department, Technische Universität Berlin, 10587 Berlin, Germany (e-mail: kai.wan@tu-berlin.de; caire@tu-berlin.de). The work of K. Wan and G. Caire was partially funded by the European Research Council under the ERC Advanced Grant N. 789190, CARENET.

H. Sun is with the Department of Electrical Engineering, University of North Texas, Denton, TX 76203 (email: hua.sun@unt.edu).

M. Ji is with the Electrical and Computer Engineering Department, University of Utah, Salt Lake City, UT 84112, USA (e-mail: mingyue.ji@utah.edu). The work of M. Ji was supported in part by NSF Awards 1817154 and 1824558.

D. Tuninetti is with the Electrical and Computer Engineering Department, University of Illinois at Chicago, Chicago, IL 60607, USA (e-mail: danielat@uic.edu). The work of D. Tuninetti was supported in part by NSF Award 1910309.

Index Terms

Coded caching; uncoded cache placement; linear scalar function retrieval.

I. INTRODUCTION

Information theoretic coded caching was originally proposed by Maddah-Ali and Niesen (MAN) in [1] for the shared-link caching systems containing a server with a library of N equal-length files, which is connected to K users through a noiseless shared-link. Each user can store M files in their local cache. Two phases are included in the MAN caching system: i) cache placement phase: content is pushed into each cache without knowledge of future demands; ii) delivery phase: each user demands one file, and according to the cache contents, the server broadcasts coded packets to all the users. The objective is to minimize the transmitted load (i.e., number of transmitted bits normalized by the length of a single file) to satisfy the all the user' demands.

The MAN coded caching scheme proposed in [1], uses a combinatorial design in the placement phase (referred to as MAN cache placement), such that in the delivery phase binary multicast messages (referred to as MAN multicast messages) can simultaneously satisfy the demands of users. Under the constraint of uncoded cache placement (i.e., each user directly caches a subset of the library bits), the MAN scheme can achieve the minimum worst-case load among all possible demands when $N \geq K$ [2]. On the observation that if there are files demanded multiple times, some MAN multicast messages can be obtained as a binary linear combination of other MAN multicast messages, Yu, Maddah-Ali, and Avestimehr (YMA) proposed an improved delivery scheme in [3]. The YMA delivery, with MAN placement, achieves the minimum worst-case load under the constraint of uncoded cache placement. The cost of uncoded cache placement compared to coded cache placement was proved in [4] to be at most 2.

MAN coded caching [1] has been extended to numerous models, such as Device-to-Device (D2D) caching systems [5], private coded caching [6], [7], coded distributed computing [8], and coded data shuffling [9]–[11] – just to name a few. A common point of these models is that each user requests one file – some allow for users to request (the equivalent of) multiple files [8]–[13] which however does not change much the nature of the problem. In general, linear and multivariate polynomial operations are widely used fundamental primitives for building the complex queries that support on-line analytics and data mining procedures. For example,

linear operations are critical in modern deep learning and artificial intelligence algorithms, where matrix-matrix or matrix-vector multiplications are at the core of iterative optimization algorithms; while algebraic polynomial queries naturally arise in engineering problems such as those described by differential equations and distributed machine learning algorithms [14], [15]. In those scenarios, it may be too resource-consuming (in terms of bandwidth, or execution time, or storage space) to download locally all the input variables in order to compute the desired output value. Instead, it is desirable to directly download the result of the desired output function. This paper studies the fundamental tradeoff between local storage and network load when users are interested in retrieving a function of the dataset available at the server.

The question we ask in this paper is, compared to the original MAN caching problem, whether the optimal worst-case load is increased when the users are allowed to request *scalar linear functions of the files* – the first non-trivial extension of the MAN single-file-retrieval problem, on the way to understand the problem of retrieving general functions. The original MAN shared-link caching problem in [1] where each user request one file is a special case of the formulated shared-link cache-aided scalar linear function retrieval problem.

In addition to the novel problem formulation, our main results are as follows:

- *Achievable scheme for demanded functions on the binary field.* We start by considering the case of scalar linear functions on $\mathbb{F}_2$. Based on the YMA delivery, which uses an “interference cancellation” idea on $\mathbb{F}_2$, we propose a novel delivery scheme whose key idea is to deliver only the largest set of linearly independent functions, while the remaining ones can be reconstructed by proper linear combinations of those already retrieved. This can be thought of as the generalization of the idea to only deliver the files requested by the “leader users” in the YMA delivery.
- *Generalization to demanded functions on arbitrary finite field.* We then generalize the proposed scheme to the case where the demands are scalar linear functions on an arbitrary finite field $\mathbb{F}_q$. To the best of our knowledge, even for the originally MAN coded caching problem, no caching scheme is known in the literature for arbitrary finite fields. Compared to the YMA delivery scheme, we use different encoding (based on a finite field interference alignment idea) and decoding procedures that work on an arbitrary finite field.

Interestingly, the achieved load by the proposed scheme only depends on the number of linearly independent functions that are demanded, akin to the YMA’s cache-aided single-file retrieval scheme where the load depends on the number of distinct file requests.

- *Optimality.* On observation that the converse bound for the original MAN caching problem in [2], [3] is also a converse in the considered cache-aided function retrieval problem, we prove that the proposed scheme achieves the optimal worst-cast load under the constraint of uncoded cache placement. Moreover, the achieved worst-case load of the proposed scheme is also proved to be order optimal in general within a factor of 2.

From the results in this paper, we can answer the question we asked at the beginning of this paper: *the optimal worst-case load under the constraint of uncoded cache placement is not increased when the users are allowed to request scalar linear functions of the files.*

A. Paper Organization

The rest of this paper is organized as follows. Section II formulates the cache-aided function retrieval problem and introduces some related results in the literature. Section III provides and discusses the main results in this paper. Section IV and Section V describe the proposed achievable caching schemes on the binary field and on arbitrary finite field, respectively. Section VI concludes the paper. Some of the proofs are given in the Appendices.

B. Notation Convention

Calligraphic symbols denote sets, bold symbols denote vectors, and sans-serif symbols denote system parameters. We use $|\cdot|$ to represent the cardinality of a set or the length of a vector; $[a : b] := \{a, a + 1, \dots, b\}$ and $[n] := [1, 2, \dots, n]$; $\oplus$ represents bit-wise XOR; $\mathbb{E}[\cdot]$ represents the expectation value of a random variable; $[a]^+ := \max\{a, 0\}$; $a! = a \times (a - 1) \times \dots \times 1$ represents the factorial of a ; $\mathbb{F}_q$ represents a finite field with order q ; $\text{rank}_q(\mathbb{A})$ represents the rank of matrix $\mathbb{A}$ on field $\mathbb{F}_q$; $\det(\mathbb{A})$ represents the determinant matrix $\mathbb{A}$; $\mathbb{A}_{\mathcal{S}, \mathcal{V}}$ represents the sub-matrix of $\mathbb{A}$ by selecting from $\mathbb{A}$, the rows with indices in $\mathcal{S}$ and the columns with indices in $\mathcal{V}$. we let $\binom{x}{y} = 0$ if $x < 0$ or $y < 0$ or $x < y$. In this paper, for each set of integers $\mathcal{S}$, we sort the elements in $\mathcal{S}$ in an increasing order and denote the i^{th} smallest element by $\mathcal{S}(i)$, i.e., $\mathcal{S}(1) < \dots < \mathcal{S}(|\mathcal{S}|)$.

II. SYSTEM MODEL AND RELATED RESULTS

A. System Model

A (K, N, M, q) shared-link cache-aided scalar linear function retrieval problem is defined as follows. A central server has access to a library of N files. The files are denoted as $F_1, \dots, F_N$.

Each file has B independent and uniformly distributed symbols over a finite field $\mathbb{F}_q$, for some prime-power q . The central server is connected to K users through an error-free shared-link. Each user is equipped with a cache that can store up to MB symbols, where $M \in [0, N]$.

The system operates in two phases.

Cache Placement Phase. During the cache placement phase, each user stores information about the N files in its local cache without knowledge of future users' demands, that is, there exist placement functions ϕ_k , $k \in [K]$, such that

$$\phi_k : [\mathbb{F}_q]^{BN} \rightarrow [\mathbb{F}_q]^{BM}, \quad (1)$$

We denote the content in the cache of user $k \in [K]$ by $Z_k = \phi_k(F_1, \dots, F_N)$.

Delivery Phase. During the delivery phase, each user requests one scalar linear function of the files. The demand of user $k \in [K]$ is represented by the row vector $\mathbf{y}_k = (y_{k,1}, \dots, y_{k,N}) \in [\mathbb{F}_q]^N$, which means that user k wants to retrieve $y_{k,1}F_1 + \dots + y_{k,N}F_N$. We denote the demand matrix of all users by

$$\mathbb{D} = [\mathbf{y}_1; \dots; \mathbf{y}_K] \in [\mathbb{F}_q]^{KN}. \quad (2)$$

Given the demand matrix $\mathbb{D}$, the server broadcasts the message $X = \psi(\mathbb{D}, F_1, \dots, F_N)$ to each user $k \in [K]$, where the encoding function ψ is such that

$$\psi : [\mathbb{F}_q]^{KN} \times [\mathbb{F}_q]^{BN} \rightarrow [\mathbb{F}_q]^{BR}, \quad (3)$$

for some non-negative R .

Decoding. Each user $k \in [K]$ decode its desired function from $(\mathbb{D}, Z_k, X)$. In other words, there exist decoding functions ξ_k , $k \in [K]$, such that

$$\xi_k : [\mathbb{F}_q]^{KN} \times [\mathbb{F}_q]^{BM} \times [\mathbb{F}_q]^{BR} \rightarrow [\mathbb{F}_q]^B, \quad (4)$$

$$\xi_k(\mathbb{D}, Z_k, X) = y_{k,1}F_1 + \dots + y_{k,N}F_N. \quad (5)$$

Objective. For a given memory size $M \in [0, N]$, our objective is to determine the *minimum worst-case load* among all possible demands, defined as the smallest R such that there exist placement functions $\phi_k, k \in [K]$, encoding function ψ , and decoding functions $\xi_k, k \in [K]$, satisfying all the above constraints. The optimal load is denoted as R^* .

If each user directly copies some symbols of the N files into its cache, the cache placement is said to be *uncoded*. The minimum worst-case load under the constraint of uncoded cache placement is denoted by R_u^* .

B. Review of the MAN [1] and YMA [3] Coded Caching Schemes

In the following, we review the MAN and YMA coded caching schemes, which are on the binary field $\mathbb{F}_2$, for the shared-link caching problem, where each user requests one file.

MAN Scheme: File Split. Let $t \in [0 : K]$. Partition each file $F_i, i \in [N]$, into $\binom{K}{t}$ equal-length subfiles denoted as

$$F_i = \{F_{i,\mathcal{W}} : \mathcal{W} \subseteq [K], |\mathcal{W}| = t\}. \quad (6)$$

Placement Phase. User $k \in [K]$ caches $F_{i,\mathcal{W}}, i \in [N]$, if $k \in \mathcal{W}$. Hence, each user caches $N\binom{K-1}{t-1}$ subfiles, each of which contains $\frac{B}{\binom{K}{t}}$ symbols, which requires

$$M = \frac{Nt}{K}. \quad (7)$$

Delivery Phase. User $k \in [K]$ requests the file with index $d_k \in [N]$. The server then broadcasts the following *MAN multicast messages*: for each $\mathcal{S} \subseteq [K]$ where $|\mathcal{S}| = t + 1$, the server sends

$$W_{\mathcal{S}} = \bigoplus_{k \in \mathcal{S}} F_{d_k, \mathcal{S} \setminus \{k\}}. \quad (8)$$

Decoding. The multicast message $W_{\mathcal{S}}$ in (8) is useful to each user $k \in \mathcal{S}$, since this user caches all subfiles contained by $W_{\mathcal{S}}$ except for the desired subfile $F_{d_k, \mathcal{S} \setminus \{k\}}$. Considering all multicast messages, each user can recover all uncached subfiles and thus recover its demanded file.

Load. The achieved memory-load tradeoff of the MAN scheme is the lower convex envelop of the following points

$$(M, R) = \left(\frac{Nt}{K}, \frac{\binom{K}{t+1}}{\binom{K}{t}} \right), \forall t \in [0 : K]. \quad (9)$$

YMA Scheme: File splitting and cache placement are as for the MAN scheme.

Delivery Phase. The main idea of the YMA delivery is that, when a file is demanded by multiple users, some MAN multicast messages in (8) can be obtained as a linear combinations of others. Thus the load of the MAN scheme in (9) can be further reduced by removing the redundant MAN multicast messages. More precisely, for each demanded file, randomly choose one user among all users demanding this file and designate it as the “leader user” for this file. Let $\mathcal{D} := \cup_{k \in [K]} \{d_k\}$ be the set of all distinct files that are demanded, and $\mathcal{L}$ be the set of $|\mathcal{D}|$ leader users. The server only sends those multicast message $W_{\mathcal{S}}$ in (8) that are useful for the leader users, that is, if $\mathcal{S} \cap \mathcal{L} \neq \emptyset$, thus saving $\binom{K-|\mathcal{D}|}{t+1}$ transmissions.

Decoding. Clearly, all leaders users can decode their demanded files as per the MAN scheme. The non-leader users appear to miss the multicast message $W_{\mathcal{A}}$ for each $\mathcal{A} \subseteq [K]$ where $\mathcal{A} \cap \mathcal{L} = \emptyset$ and $|\mathcal{A}| = t + 1$. It was proved in [3] that

$$\bigoplus_{\mathcal{F} \in \mathcal{F}_{\mathcal{B}}} W_{\mathcal{B} \setminus \mathcal{F}} = 0, \quad (10)$$

where $\mathcal{B} = \mathcal{A} \cup \mathcal{L}$, and $\mathcal{F}_{\mathcal{B}}$ is the family of subsets $\mathcal{F} \subseteq \mathcal{B}$, where each file in $\mathcal{D}$ is requested by exactly one user in $\mathcal{F}$. The key observation is that in $\bigoplus_{\mathcal{F} \in \mathcal{F}_{\mathcal{B}}} W_{\mathcal{B} \setminus \mathcal{F}}$ each involved subfile appears exactly twice (i.e., contained into two MAN multicast messages)¹, whose contribution on $\mathbb{F}_2$ is thus zero. From (10), we have

$$W_{\mathcal{A}} = \bigoplus_{\mathcal{F} \in \mathcal{F}_{\mathcal{B}}: \mathcal{F} \neq \mathcal{L}} W_{\mathcal{B} \setminus \mathcal{F}}. \quad (11)$$

In other words, the multicast message $W_{\mathcal{A}}$ can be reconstructed by all users from the delivery phase.

Load. The YMA scheme requires the load of

$$\frac{\binom{K}{t+1} - \binom{K-|\mathcal{D}|}{t+1}}{\binom{K}{t}}, \quad (12)$$

if the set of the demanded files is $\mathcal{D}$. The worst-case load is attained for $|\mathcal{D}| = \min(N, K)$, thus the achieved memory-load tradeoff of the YMA scheme is the lower convex envelop of the following points

$$(M, R) = \left(\frac{Nt}{K}, \frac{\binom{K}{t+1} - \binom{K-\min(N,K)}{t+1}}{\binom{K}{t}} \right), \forall t \in [0 : K]. \quad (13)$$

III. MAIN RESULTS AND DISCUSSION

In this section, we summarize the main results in this paper.

The proposed caching scheme in Section IV (for $q = 2$) and Section V (for general prime-power q), achieves the following load.

¹ In this paper, A ‘appears’ in a linear combination means that in the linear combination, there exists some term in the linear combination including A . A linear combination ‘contains’ B means that in the linear combination, the total coefficient of B is not 0. For example, we say A appears in the linear combination $(A \oplus B) \oplus (A \oplus C)$, but the linear combination does not contain A .

Theorem 1 (Achievability). *For the (K, N, M, q) shared-link cache-aided scalar linear function retrieval problem, the YMA load in (13) is an achievable worst-case load. More precisely, for cache size $M = \frac{Nt}{K}$, with $t \in [0 : K]$, and for demand matrix $\mathbb{D}$, the load*

$$R(\mathbb{D}) := \frac{\binom{K}{t+1} - \binom{K - \text{rank}_q(\mathbb{D})}{t+1}}{\binom{K}{t}} \quad (14)$$

is achievable. The worst-case load is attained by $\text{rank}_q(\mathbb{D}) = \min(N, K)$. $\square$

Remark 1 (Dependence on the rank of the demand matrix). The load in (14) is a generalization of the load in (12) achieved by the YMA scheme. More precisely, if each user $k \in [K]$ requests one file (i.e., $\mathbf{y}_k \in [0 : 1]^N$ with a unit norm), $\text{rank}_q(\mathbb{D})$ is exactly the number of demanded files, and thus the proposed scheme achieves the load in (12) as the YMA scheme. Interestingly, the load of the proposed scheme only depends on the rank of the demand matrix of all users, instead of on the specifically demanded functions. $\square$

Remark 2 (High-level ideas to derive the load in Theorem 1). We partition the “symbol positions” set $[B]$ as follows

$$[B] = \{\mathcal{I}_{\mathcal{W}} : \mathcal{W} \subseteq [K], |\mathcal{W}| = t\} \text{ such that } |\mathcal{I}_{\mathcal{W}}| = B / \binom{K}{t}. \quad (15)$$

Then, with a Matlab-inspired notation, we let

$$F_{i,\mathcal{W}} = F_i(\mathcal{I}_{\mathcal{W}}), \quad \forall \mathcal{W} \subseteq [K] : |\mathcal{W}| = t, \quad \forall i \in [N], \quad (16)$$

representing the set of symbols of F_i whose position is in $\mathcal{I}_{\mathcal{W}}$. As in the MAN placement, user $k \in [K]$ caches $F_{i,\mathcal{W}}$ if $k \in \mathcal{W}$. By doing so, any scalar linear function is naturally partitioned into “blocks” as follows

$$y_{k,1}F_1 + \dots + y_{k,N}F_N = \left\{ \underbrace{y_{k,1}F_1(\mathcal{I}_{\mathcal{W}}) + \dots + y_{k,N}F_N(\mathcal{I}_{\mathcal{W}})}_{:= B_{k,\mathcal{W}} \text{ is the } \mathcal{W}\text{-th block of the } k\text{-th demanded function}} : \mathcal{W} \subseteq [K], |\mathcal{W}| = t \right\}. \quad (17)$$

Some blocks of the demanded functions can thus be computed based on the cache content available at each user while the remaining ones need to be delivered by the server. With this specific file split (and corresponding MAN cache placement), **we operate the MAN delivery scheme over the blocks instead of over the subfiles**; more precisely, instead of (8) we transmit

$$W_{\mathcal{S}} = \sum_{k \in \mathcal{S}} \alpha_{\mathcal{S},k} B_{k,\mathcal{S} \setminus \{k\}}, \quad \forall \mathcal{S} \subseteq [K] : |\mathcal{S}| = t + 1, \quad (18)$$

for some $\alpha_{\mathcal{S},k} \in \mathbb{F}_q \setminus \{0\}$ and where $B_{k,\mathcal{W}}$ was defined in (17). Clearly, this scheme achieves the same load as in (9) (and works on any finite field and any $\alpha_{\mathcal{S},k} \in \mathbb{F}_q \setminus \{0\}$).

The question is, whether with (18) we can do something similar to the YMA delivery scheme. More specifically,

- 1) what is a suitable definition of the leader user set $\mathcal{L}$;
- 2) what is a suitable choice of $\alpha_{\mathcal{S},k}$'s in (18); and
- 3) assuming we only send the multicast messages in (18) that are useful for the leader users (i.e., $W_{\mathcal{S}}$ where $\mathcal{S} \subseteq [K]$, $|\mathcal{S}| = t + 1$, and $\mathcal{S} \cap \mathcal{L} \neq \emptyset$), what is the counterpart of (11); here for each $\mathcal{A} \subseteq [K]$ where $|\mathcal{A}| = t + 1$ and $\mathcal{A} \cap \mathcal{L} = \emptyset$, we seek

$$W_{\mathcal{A}} = \sum_{\mathcal{S} \subseteq [K]: |\mathcal{S}|=t+1, \mathcal{S} \cap \mathcal{L} \neq \emptyset} \beta_{\mathcal{A},\mathcal{S}} W_{\mathcal{S}}. \quad (19)$$

The novelty of our scheme lays in the answers to these questions as follows:

- 1) we first choose $\text{rank}_q(\mathbb{D})$ leaders (the set of leader users is denoted by $\mathcal{L}$), where the demand matrix of the leaders is full-rank.
- 2) When $q = 2$ (i.e., on the binary field), let $\alpha_{\mathcal{S},k} = 1$. When q is a prime-power, the proposed scheme in Section V separates the demanded blocks by the leaders and non-leaders in $W_{\mathcal{S}}$ in (18) as

$$\sum_{k \in \mathcal{S}} \alpha_{\mathcal{S},k} B_{k,\mathcal{S} \setminus \{k\}} = \sum_{k_1 \in \mathcal{S} \cap \mathcal{L}} \alpha_{\mathcal{S},k_1} B_{k_1,\mathcal{S} \setminus \{k_1\}} + \sum_{k_2 \in \mathcal{S} \setminus \mathcal{L}} \alpha_{\mathcal{S},k_2} B_{k_2,\mathcal{S} \setminus \{k_2\}}; \quad (20)$$

we then alternate the coefficients of the desired blocks by the leaders (i.e., users in $\mathcal{S} \cap \mathcal{L}$) between $+1$ and -1 , i.e., the coefficient of the desired block of the first leader is $+1$, the coefficient of the desired block of the second leader is -1 , the coefficient of the desired block of the third leader is $+1$, etc; similarly, we alternate the coefficients of the desired blocks by the non-leaders (i.e., users in $\mathcal{S} \setminus \mathcal{L}$) between $+1$ and -1 .²

- 3) With the above encoding scheme, we can compute the decoding coefficients (as $\beta_{\mathcal{A},\mathcal{S}}$ in (19)) such that (19) holds for each $\mathcal{A} \subseteq [K]$ where $|\mathcal{A}| = t + 1$ and $\mathcal{A} \cap \mathcal{L} = \emptyset$. In other words, each user can recover all multicast messages $W_{\mathcal{S}}$ where $\mathcal{S} \subseteq [K]$ and $|\mathcal{S}| = t + 1$, and thus it can recover its desired function.

² This type of code was originally proposed in [16] for the private function retrieval problem, where there is a memory-less user aiming to retrieve a scalar linear function of the files in the library from multiple servers (each server can access to the whole library), while preserving the demand of this user from each server.

□

Since the setting where each user demands one file is a special case of the considered cache-aided scalar linear function retrieval problem, the converse bounds in [2]–[4] for the original shared-link coded caching problem is also a converse in our considered problem, thus we have:

Theorem 2 (Optimality). *For the (K, N, M, q) shared-link cache-aided scalar linear function retrieval problem, under the constraint of uncoded cache placement, the optimal worst-case load-memory tradeoff is the lower convex envelop of*

$$(M, R_u^*) = \left(\frac{Nt}{K}, \frac{\binom{K}{t+1} - \binom{K - \min\{K, N\}}{t+1}}{\binom{K}{t}} \right), \quad \forall t \in [0 : K]. \quad (21)$$

Moreover, the achieved worst-case load in (21) is optimal within a factor of 2 in general. □

Remark 3 (Extensions). We discuss three extensions of the proposed caching scheme in Theorem 1 in the following.

Optimal average load under uncoded and symmetric cache placement. We define *uncoded and symmetric* cache placement as follows, which is a generalization of file split in (15)–(16). We partition the “symbol positions” set $[B]$ as

$$[B] = \{\mathcal{I}_{\mathcal{W}} : \mathcal{W} \subseteq [K]\}, \quad (22)$$

and let $F_{i, \mathcal{W}} = F_i(\mathcal{I}_{\mathcal{W}})$ as in (16). Each user $k \in [K]$ caches $F_{i, \mathcal{W}}$ if $k \in \mathcal{W}$.

Hence, in the delivery phase, user k needs to recover $B_{k, \mathcal{W}}$ (defined in (17)) where $\mathcal{W} \subseteq [K] \setminus \{k\}$. By directly using [4, Lemma 2] in the caching converse bound under uncoded cache placement in [2], [3], we can prove that the proposed caching scheme in Theorem 1 achieves the minimum average load over uniform demand distribution under the constraint of uncoded and symmetric cache placement cross files.

Corollary 1. *[Optimal average load] For the (K, N, M, q) shared-link cache-aided scalar linear function retrieval problem, under the constraint of uncoded and symmetric cache placement, the minimum average load over uniform demand distribution is the lower convex envelop of*

$$(M, R) = \left(\frac{Nt}{K}, \mathbb{E}_{\mathbb{D}} \left[\frac{\binom{K}{t+1} - \binom{K - \text{rank}_q(\mathbb{D})}{t+1}}{\binom{K}{t}} \right] \right), \quad \forall t \in [0 : K]. \quad (23)$$

Notice that an uncoded and asymmetric cache placement can be treated as a special case of the inter-file coded cache placement in the originally MAN caching problem. It is one of the

on-going works to derive the converse bound under the constraints of uncoded cache placement for the considered cache-aided function retrieval problem.

Device-to-Device (D2D) cache-aided scalar linear function retrieval. Coded caching was originally used in Device-to-Device networks in [5], where in the delivery phase each user broadcasts packets as functions of its cached content and the users' demands, to all other users. The authors in [17] extended the YMA scheme to D2D networks by dividing the D2D networks into K shared-link networks, and used the YMA scheme in each shared-link network. Hence, when users request scalar linear functions, we can use the same method as in [17] to divide the D2D networks into K shared-link networks, and then use the proposed caching scheme in Theorem 1 in each shared-link network.

Corollary 2. *[D2D cache-aided scalar linear function retrieval] For the (K, N, M, q) D2D cache-aided scalar linear function retrieval problem, the minimum worse-case load is upper bounded by the lower convex envelop of*

$$(M, R) = \left(\frac{Nt}{K}, \max_{\mathbb{D}} \frac{\binom{K-1}{t} - \frac{1}{K} \sum_{k \in [K]} \binom{K-1 - \text{rank}_q(\mathbb{D}_{[K] \setminus \{k\}})}{t}}{\binom{K-1}{t-1}} \right), \quad \forall t \in [K]. \quad (24)$$

Cache-aided private scalar linear function retrieval. For the successful decoding of the proposed scheme in Theorem 1, users need to be aware of the demands of other users, which is not private. To preserve the privacy of the demand of each user against other users, we can generate virtual users as in [6], such that each of all possible demanded functions (the total number of possible demanded functions is $N' := \frac{q^N - 1}{q - 1}$) is demanded exactly K times. Thus there are totally $N'K$ real or virtual users in the system. Then the proposed scheme in Theorem 1 can be used to satisfy the demands of all real or virtual users. Since each user cannot distinguish other real users from virtual users, the resulting scheme does not leak any information on the demands of real users.

Corollary 3. *[Cache-aided private scalar linear function retrieval] For the (K, N, M, q) D2D cache-aided scalar linear function retrieval problem, the minimum load is upper bounded by the lower convex envelop of*

$$(M, R) = \left(\frac{t}{N'K} N, \frac{\binom{N'K}{t+1} - \binom{N'K-N}{t+1}}{\binom{N'K}{t}} \right), \quad \forall t \in [N'K]. \quad (25)$$

□

IV. ACHIEVABLE SCHEME IN THEOREM 1 FOR $q = 2$

In the following, we describe the proposed scheme when the demands are scalar linear functions on $\mathbb{F}_2$. We start with the following example.

A. Example

Consider the $(K, N, M, q) = (6, 3, 1, 2)$ shared-link cache-aided scalar linear function retrieval problem, where $t = KM/N = 2$. In the cache placement, each file is partitioned into $\binom{K}{t} = 15$ equal-length subfiles. We use the file split in (15)-(16), resulting in the demand split in (17).

In the delivery phase, we assume that

user 1 demands F_1 ;

user 2 demands F_2 ;

user 3 demands F_3 ;

user 4 demands $F_1 \oplus F_2$;

user 5 demands $F_1 \oplus F_3$;

user 6 demands $F_1 \oplus F_2 \oplus F_3$;

i.e., the demand matrix is

$$\mathbb{D} = \begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \\ 1 & 1 & 0 \\ 1 & 0 & 1 \\ 1 & 1 & 1 \end{bmatrix}. \quad (26)$$

On the observation that $\text{rank}_2(\mathbb{D}) = 3$, we choose 3 users as leaders, where the demand matrix of these 3 leaders is also full-rank. Here, we choose $\mathcal{L} = [3]$.

Encoding. For each set $\mathcal{S} \subseteq [K]$ where $|\mathcal{S}| = t + 1 = 3$, we generate a multicast message with $\alpha_{\mathcal{S},k} = 1$ in (18). Hence, we have

$$W_{\{1,2,3\}} = F_{1,\{2,3\}} \oplus F_{2,\{1,3\}} \oplus F_{3,\{1,2\}}; \quad (27a)$$

$$W_{\{1,2,4\}} = F_{1,\{2,4\}} \oplus F_{2,\{1,4\}} \oplus (F_{1,\{1,2\}} \oplus F_{2,\{1,2\}}); \quad (27b)$$

$$W_{\{1,2,5\}} = F_{1,\{2,5\}} \oplus F_{2,\{1,5\}} \oplus (F_{1,\{1,2\}} \oplus F_{3,\{1,2\}}); \quad (27c)$$

$$W_{\{1,2,6\}} = F_{1,\{2,6\}} \oplus F_{2,\{1,6\}} \oplus (F_{1,\{1,2\}} \oplus F_{2,\{1,2\}} \oplus F_{3,\{1,2\}}); \quad (27d)$$

$$W_{\{1,3,4\}} = F_{1,\{3,4\}} \oplus F_{3,\{1,4\}} \oplus (F_{1,\{1,3\}} \oplus F_{2,\{1,3\}}); \quad (27e)$$

$$W_{\{1,3,5\}} = F_{1,\{3,5\}} \oplus F_{3,\{1,5\}} \oplus (F_{1,\{1,3\}} \oplus F_{3,\{1,3\}}); \quad (27f)$$

$$W_{\{1,3,6\}} = F_{1,\{3,6\}} \oplus F_{3,\{1,6\}} \oplus (F_{1,\{1,3\}} \oplus F_{2,\{1,3\}} \oplus F_{3,\{1,3\}}); \quad (27g)$$

$$W_{\{1,4,5\}} = F_{1,\{4,5\}} \oplus (F_{1,\{1,5\}} \oplus F_{2,\{1,5\}}) \oplus (F_{1,\{1,4\}} \oplus F_{3,\{1,4\}}); \quad (27h)$$

$$W_{\{1,4,6\}} = F_{1,\{4,6\}} \oplus (F_{1,\{1,6\}} \oplus F_{2,\{1,6\}}) \oplus (F_{1,\{1,4\}} \oplus F_{2,\{1,4\}} \oplus F_{3,\{1,4\}}); \quad (27i)$$

$$W_{\{1,5,6\}} = F_{1,\{5,6\}} \oplus (F_{1,\{1,6\}} \oplus F_{3,\{1,6\}}) \oplus (F_{1,\{1,5\}} \oplus F_{2,\{1,5\}} \oplus F_{3,\{1,5\}}); \quad (27j)$$

$$W_{\{2,3,4\}} = F_{2,\{3,4\}} \oplus F_{3,\{2,4\}} \oplus (F_{1,\{2,3\}} \oplus F_{2,\{2,3\}}); \quad (27k)$$

$$W_{\{2,3,5\}} = F_{2,\{3,5\}} \oplus F_{3,\{2,5\}} \oplus (F_{1,\{2,3\}} \oplus F_{3,\{2,3\}}); \quad (27l)$$

$$W_{\{2,3,6\}} = F_{2,\{3,6\}} \oplus F_{3,\{2,6\}} \oplus (F_{1,\{2,3\}} \oplus F_{2,\{2,3\}} \oplus F_{3,\{2,3\}}); \quad (27m)$$

$$W_{\{2,4,5\}} = F_{2,\{4,5\}} \oplus (F_{1,\{2,5\}} \oplus F_{2,\{2,5\}}) \oplus (F_{1,\{2,4\}} \oplus F_{3,\{2,4\}}); \quad (27n)$$

$$W_{\{2,4,6\}} = F_{2,\{4,6\}} \oplus (F_{1,\{2,6\}} \oplus F_{2,\{2,6\}}) \oplus (F_{1,\{2,4\}} \oplus F_{2,\{2,4\}} \oplus F_{3,\{2,4\}}); \quad (27o)$$

$$W_{\{2,5,6\}} = F_{2,\{5,6\}} \oplus (F_{1,\{2,6\}} \oplus F_{3,\{2,6\}}) \oplus (F_{1,\{2,5\}} \oplus F_{2,\{2,5\}} \oplus F_{3,\{2,5\}}); \quad (27p)$$

$$W_{\{3,4,5\}} = F_{3,\{4,5\}} \oplus (F_{1,\{3,5\}} \oplus F_{2,\{3,5\}}) \oplus (F_{1,\{3,4\}} \oplus F_{3,\{3,4\}}); \quad (27q)$$

$$W_{\{3,4,6\}} = F_{3,\{4,6\}} \oplus (F_{1,\{3,6\}} \oplus F_{2,\{3,6\}}) \oplus (F_{1,\{3,4\}} \oplus F_{2,\{3,4\}} \oplus F_{3,\{3,4\}}); \quad (27r)$$

$$W_{\{3,5,6\}} = F_{3,\{5,6\}} \oplus (F_{1,\{3,6\}} \oplus F_{3,\{3,6\}}) \oplus (F_{1,\{3,5\}} \oplus F_{2,\{3,5\}} \oplus F_{3,\{3,5\}}); \quad (27s)$$

$$W_{\{4,5,6\}} = (F_{1,\{5,6\}} \oplus F_{2,\{5,6\}}) \oplus (F_{1,\{4,6\}} \oplus F_{3,\{4,6\}}) \oplus (F_{1,\{4,5\}} \oplus F_{2,\{4,5\}} \oplus F_{3,\{4,5\}}). \quad (27t)$$

Delivery. The server broadcasts $W_{\mathcal{S}}$ for each $\mathcal{S} \subseteq [K]$ where $|\mathcal{S}| = t + 1 = 3$ and $\mathcal{S} \cap \mathcal{L} \neq \emptyset$. In other words, the server broadcasts all the multicast messages in (27) except for $W_{\{4,5,6\}}$.

Decoding. We show that the untransmitted multicast message $W_{\{4,5,6\}}$ can be reconstructed by the transmitted multicast messages. For each set of users $\mathcal{B} \subseteq [K]$, we define $\mathcal{V}_{\mathcal{B}}$ as the family of subsets $\mathcal{V} \subseteq \mathcal{B}$, where $|\mathcal{V}| = |\mathcal{L}|$ and $\text{rank}_2(\mathbb{D}_{\mathcal{V}}) = |\mathcal{L}|$. It can be seen that $\mathcal{V}_{\mathcal{B}}$ is the generalization of $\mathcal{F}_{\mathcal{B}}$ defined in the YMA scheme described in Section II-B. When $\mathcal{B} = \mathcal{L} \cup \{4, 5, 6\} = [6]$, we have

$$\begin{aligned} \mathcal{V}_{[6]} = \big\{ & \{1, 2, 3\}, \{1, 2, 5\}, \{1, 2, 6\}, \{1, 3, 4\}, \{1, 3, 6\}, \{1, 4, 5\}, \{1, 4, 6\}, \{1, 5, 6\}, \\ & \{2, 3, 4\}, \{2, 3, 5\}, \{2, 3, 6\}, \{2, 4, 5\}, \{2, 4, 6\}, \{3, 4, 5\}, \{3, 5, 6\}, \{4, 5, 6\} \big\}. \end{aligned} \quad (28)$$

From the above definition, we focus on the following sum of multicast messages

$$\bigoplus_{\mathcal{V} \in \mathcal{V}_{[6]}} W_{[6] \setminus \mathcal{V}} = 0, \quad (29)$$

where (29) is because on the LHS of (29), among all subfiles $F_{i,\mathcal{W}}$ where $i \in [3]$, $\mathcal{W} \subseteq [6]$, and $|\mathcal{W}| = 2$, the coefficient of each of $F_{2,\{2,4\}}$, $F_{2,\{2,6\}}$, $F_{2,\{4,6\}}$, $F_{3,\{3,5\}}$, $F_{3,\{3,6\}}$, $F_{3,\{5,6\}}$ is 0, $F_{1,\{2,3\}}$ appears 4 times and other subfiles appear 2 times. Hence, the sum is equivalent to 0 on $\mathbb{F}_2$. Notice that in the YMA delivery scheme, the coefficient of each subfile appearing in the sum $\bigoplus_{\mathcal{F} \in \mathcal{F}_{\mathcal{B}}} W_{\mathcal{B} \setminus \mathcal{F}}$ is 2.

We can write (29) as

$$W_{\{4,5,6\}} = \bigoplus_{\mathcal{V} \in \mathcal{V}_{[6]}: \mathcal{V} \neq \mathcal{L}} W_{[6] \setminus \mathcal{V}}. \quad (30)$$

In other words, the untransmitted multicast message $W_{\{4,5,6\}}$ can be reconstructed by the transmitted multicast messages. Thus each user can recover all the multicast messages in (27), and then recover its desired function.

Performance. In total we transmit $\binom{K}{t+1} - \binom{K - \text{rank}_2(\mathbb{D})}{t+1} = \binom{6}{3} - \binom{3}{3} = 19$ multicast messages, each of which contains $\frac{B}{20}$ bits. Hence, the transmitted load is $\frac{19}{20}$, which coincides with the optimal worst-case load in Theorem 2.

B. General Description

We use the file split in (15)-(16), resulting in the demand split in (17).

In the delivery phase, the demand matrix $\mathbb{D}$ is revealed where each element in $\mathbb{D}$ is either 0 or 1. Among the K users we first choose $\text{rank}_2(\mathbb{D})$ leaders (assume the set of leaders is $\mathcal{L} = \{\mathcal{L}(1), \dots, \mathcal{L}(|\mathcal{L}|)\}$), where

$$|\mathcal{L}| = \text{rank}_2(\mathbb{D}_{\mathcal{L}}) = \text{rank}_2(\mathbb{D}). \quad (31)$$

Encoding. We focus on each set $\mathcal{S} \subseteq [K]$ where $|\mathcal{S}| = t + 1$, and generate the multicast message in (18) with $\alpha_{\mathcal{S},k} = 1$.

Delivery. The server broadcasts $W_{\mathcal{S}}$ for each $\mathcal{S} \subseteq [K]$ where $|\mathcal{S}| = t + 1$ and $\mathcal{S} \cap \mathcal{L} \neq \emptyset$.

Decoding. For each set of users $\mathcal{B} \subseteq [K]$, recall that $\mathcal{V}_{\mathcal{B}}$ is the family of subsets $\mathcal{V} \subseteq \mathcal{B}$, where $|\mathcal{V}| = |\mathcal{L}|$ and $\text{rank}_2(\mathbb{D}_{\mathcal{V}}) = |\mathcal{L}|$. We now consider each set $\mathcal{A} \subseteq [K]$ where $|\mathcal{A}| = t + 1$ and $\mathcal{A} \cap \mathcal{L} = \emptyset$, and focus on the binary sum

$$\bigoplus_{\mathcal{V} \in \mathcal{V}_{\mathcal{B}}} W_{\mathcal{B} \setminus \mathcal{V}}, \quad (32)$$

where $\mathcal{B} = \mathcal{L} \cup \mathcal{A}$. A subfile $F_{i,\mathcal{W}}$ appears in the sum (32) if and only if $\mathcal{W} \subseteq \mathcal{B}$ and there exists some user $k \in \mathcal{B} \setminus \mathcal{W}$ such that $\text{rank}_2(\mathbb{D}_{\mathcal{B} \setminus (\mathcal{W} \cup \{k\})}) = |\mathcal{L}|$ (i.e., $\mathbb{D}_{\mathcal{B} \setminus (\mathcal{W} \cup \{k\})}$ is full-rank) and $y_{k,i} \neq 0$. We then provide the following Lemma, proved in Appendix A.

Lemma 1. *If $F_{i,\mathcal{W}}$ appears in the sum (32), the number of multicast messages in the sum which contains $F_{i,\mathcal{W}}$ is even.*³ $\square$

From Lemma 1, it can be seen that each subfile in the sum (32) appears an even number of times, and thus the coefficient of this subfile in the sum is 0, which leads to

$$W_{\mathcal{A}} = \bigoplus_{\mathcal{V} \in \mathcal{V}_{\mathcal{B}}: \mathcal{V} \neq \mathcal{L}} W_{\mathcal{B} \setminus \mathcal{V}}. \quad (33)$$

In other words, $W_{\mathcal{A}}$ can be reconstructed by the transmitted multicast messages.

As a result, each user k can recover each multicast message $W_{\mathcal{S}}$ where $\mathcal{S} \subseteq [\mathsf{K}]$ and $|\mathcal{S}| = t+1$, and thus it can decode its desired function.

Performance. In total, we transmit $\binom{\mathsf{K}}{t+1} - \binom{\mathsf{K} - \text{rank}_2(\mathbb{D})}{t+1}$ multicast messages, each of which contains $\frac{\mathsf{B}}{\binom{\mathsf{K}}{t}}$ bits. Hence, the transmitted load is

$$\frac{\binom{\mathsf{K}}{t+1} - \binom{\mathsf{K} - \text{rank}_2(\mathbb{D})}{t+1}}{\binom{\mathsf{K}}{t}}. \quad (34)$$

For the worst-case demands where $\text{rank}_2(\mathbb{D})$ is full-rank, we have $\text{rank}_2(\mathbb{D}) = \min\{\mathsf{K}, \mathsf{N}\}$, and we achieve the worst-case load in (21).

V. ACHIEVABLE SCHEME IN THEOREM 1 FOR GENERAL PRIME-POWER q

In the following, we generalize the proposed caching scheme in Section IV to the case where the demands are scalar linear functions on arbitrary finite field $\mathbb{F}_q$. All the operations in the proposed scheme are on $\mathbb{F}_q$. We again start with an example.

A. Example

Consider the $(\mathsf{K}, \mathsf{N}, \mathsf{M}, q) = (5, 3, 3/5, q)$ shared-link cache-aided scalar linear function retrieval problem, where q is a prime-power. In this case, we have $t = \mathsf{KM}/\mathsf{N} = 1$. Hence, in the cache placement, each file is partitioned into $\binom{\mathsf{K}}{t} = 5$ equal-length subfiles. We use the file split in (15)-(16), resulting in the demand split in (17).

³ Notice that in the YMA scheme for the original MAN caching problem, each subfile in (10) is contained by two multicast messages in (10). Hence, Lemma 1 is also a generalization of [3, Lemma 1] for the YMA scheme.

In the delivery phase, we assume that

- user 1 demands F_1 ;
- user 2 demands F_2 ;
- user 3 demands F_3 ;
- user 4 demands $y_{4,1}F_1 + y_{4,2}F_2 + y_{4,3}F_3$;
- user 5 demands $y_{5,1}F_1 + y_{5,2}F_2 + y_{5,3}F_3$;

i.e., the demand matrix is

$$\mathbb{D} = \begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \\ y_{4,1} & y_{4,2} & y_{4,3} \\ y_{5,1} & y_{5,2} & y_{5,3} \end{bmatrix} \in [\mathbb{F}_q]^{5 \times 3}. \quad (35)$$

We choose the set of leaders $\mathcal{L} = [3]$, since $\text{rank}_q(\mathbb{D}_{[3]}) = 3$.

Each user $k \in [K]$ should recover each block $B_{k,\mathcal{W}} = y_{k,1}F_{1,\mathcal{W}} + y_{k,2}F_{2,\mathcal{W}} + y_{k,3}F_{3,\mathcal{W}}$ in the delivery phase, where $\mathcal{W} \in [5] \setminus \{k\}$ and $|\mathcal{W}| = 1$.

Encoding. For each set $\mathcal{S} \subseteq [K]$ where $|\mathcal{S}| = t + 1 = 2$, recall that the multicast messages are given in (18) and we separate it as

$$W_{\mathcal{S}} = \sum_{k_1 \in \mathcal{S} \cap \mathcal{L}} \alpha_{\mathcal{S},k_1} B_{k_1,\mathcal{S} \setminus \{k_1\}} + \sum_{k_2 \in \mathcal{S} \setminus \mathcal{L}} \alpha_{\mathcal{S},k_2} B_{k_2,\mathcal{S} \setminus \{k_2\}}. \quad (36)$$

We first alternate the coefficients (either 1 or -1) of the desired blocks of the leaders in $\mathcal{S}$, and then alternate the coefficients (either 1 or -1) of the desired blocks of the non-leaders in $\mathcal{S}$. For example, if $\mathcal{S} = \{1, 2\}$, we have $W_{\{1,2\}} = F_{1,\{2\}} - F_{2,\{1\}}$; if $\mathcal{S} = \{1, 4\}$, we have $W_{\{1,4\}} = F_{1,\{4\}} + (y_{4,1}F_{1,\{1\}} + y_{4,2}F_{2,\{1\}} + y_{4,3}F_{3,\{1\}})$; if $\mathcal{S} = \{4, 5\}$, we have $W_{\{4,5\}} = (y_{4,1}F_{1,\{5\}} + y_{4,2}F_{2,\{5\}} + y_{4,3}F_{3,\{5\}}) - (y_{5,1}F_{1,\{4\}} + y_{5,2}F_{2,\{4\}} + y_{5,3}F_{3,\{4\}})$. With this, we can list all the multicast messages as

$$W_{\{1,2\}} = F_{1,\{2\}} - F_{2,\{1\}}; \quad (37a)$$

$$W_{\{1,3\}} = F_{1,\{3\}} - F_{3,\{1\}}; \quad (37b)$$

$$W_{\{1,4\}} = F_{1,\{4\}} + (y_{4,1}F_{1,\{1\}} + y_{4,2}F_{2,\{1\}} + y_{4,3}F_{3,\{1\}}); \quad (37c)$$

$$W_{\{1,5\}} = F_{1,\{5\}} + (y_{5,1}F_{1,\{1\}} + y_{5,2}F_{2,\{1\}} + y_{5,3}F_{3,\{1\}}); \quad (37d)$$

$$W_{\{2,3\}} = F_{2,\{3\}} - F_{3,\{2\}}; \quad (37e)$$

$$W_{\{2,4\}} = F_{2,\{4\}} + (y_{4,1}F_{1,\{2\}} + y_{4,2}F_{2,\{2\}} + y_{4,3}F_{3,\{2\}}); \quad (37f)$$

$$W_{\{2,5\}} = F_{2,\{5\}} + (y_{5,1}F_{1,\{2\}} + y_{5,2}F_{2,\{2\}} + y_{5,3}F_{3,\{2\}}); \quad (37g)$$

$$W_{\{3,4\}} = F_{3,\{4\}} + (y_{4,1}F_{1,\{3\}} + y_{4,2}F_{2,\{3\}} + y_{4,3}F_{3,\{3\}}); \quad (37h)$$

$$W_{\{3,5\}} = F_{3,\{5\}} + (y_{5,1}F_{1,\{3\}} + y_{5,2}F_{2,\{3\}} + y_{5,3}F_{3,\{3\}}); \quad (37i)$$

$$W_{\{4,5\}} = (y_{4,1}F_{1,\{5\}} + y_{4,2}F_{2,\{5\}} + y_{4,3}F_{3,\{5\}}) - (y_{5,1}F_{1,\{4\}} + y_{5,2}F_{2,\{4\}} + y_{5,3}F_{3,\{4\}}). \quad (37j)$$

Delivery. The server broadcasts $W_{\mathcal{S}}$ for each $\mathcal{S} \subseteq [K]$ where $|\mathcal{S}| = t + 1 = 2$ and $\mathcal{S} \cap \mathcal{L} \neq \emptyset$. In other words, the server broadcasts all the multicast messages in (37) except for $W_{\{4,5\}}$.

Decoding. We first show the untransmitted multicast message $W_{\{4,5\}}$ can be reconstructed by the transmitted multicast messages. More precisely, we aim to choose the decoding coefficients $\beta_{\{4,5\},\mathcal{S}} \in \mathbb{F}_q$ for each $\mathcal{S} \subseteq [K]$ where $|\mathcal{S}| = t + 1$ and $\mathcal{S} \cap \mathcal{L} \neq \emptyset$, such that

$$W_{\{4,5\}} = \sum_{\mathcal{S} \subseteq [K]: |\mathcal{S}|=t+1, \mathcal{S} \cap \mathcal{L} \neq \emptyset} \beta_{\{4,5\},\mathcal{S}} W_{\mathcal{S}}. \quad (38)$$

Since on the RHS of (38) $F_{1,\{4\}}$ only appears in $W_{\{1,4\}}$ and on the LHS of (38) the coefficient of $F_{1,\{4\}}$ is $-y_{5,1}$, in order to have the same coefficient of $F_{1,\{4\}}$ on both sides of (38), we let

$$\beta_{\{4,5\},\{1,4\}} = -y_{5,1} = -\det([y_{5,1}]). \quad (39)$$

Similarly, we let

$$\beta_{\{4,5\},\{2,4\}} = -y_{5,2} = -\det([y_{5,2}]), \quad (40)$$

such that the coefficients of $F_{2,\{4\}}$ on both sides of (38) are the same; let

$$\beta_{\{4,5\},\{3,4\}} = -y_{5,3} = -\det([y_{5,3}]), \quad (41)$$

such that the coefficients of $F_{3,\{4\}}$ on both sides of (38) are the same; let

$$\beta_{\{4,5\},\{1,5\}} = y_{4,1} = \det([y_{4,1}]), \quad (42)$$

such that the coefficients of $F_{1,\{5\}}$ on both sides of (38) are the same; let

$$\beta_{\{4,5\},\{2,5\}} = y_{4,2} = \det([y_{4,2}]), \quad (43)$$

such that the coefficients of $F_{2,\{5\}}$ on both sides of (38) are the same; let

$$\beta_{\{4,5\},\{3,5\}} = y_{4,3} = \det([y_{4,3}]), \quad (44)$$

such that the coefficients of $F_{3,\{5\}}$ on both sides of (38) are the same.

Next we focus $F_{1,\{1\}}$, which appears in $W_{\{1,4\}}$ and $W_{\{1,5\}}$. Since $\beta_{\{4,5\},\{1,4\}} = -y_{5,1}$ and $\beta_{\{4,5\},\{1,5\}} = y_{4,1}$, the coefficient of $F_{1,\{1\}}$ on the RHS of (38) is

$$y_{4,1}\beta_{\{4,5\},\{1,4\}} + y_{5,1}\beta_{\{4,5\},\{1,5\}} = 0. \quad (45)$$

Similarly, the coefficient of $F_{2,\{2\}}$ on the RHS of (38), which appears in $W_{\{2,4\}}$ and $W_{\{2,5\}}$, is 0. The coefficient of $F_{3,\{3\}}$ on the RHS of (38), which appears in $W_{\{3,4\}}$ and $W_{\{3,5\}}$, is 0,

Now we focus on $F_{1,\{2\}}$, which appears in $W_{\{1,2\}}$, $W_{\{2,4\}}$, and $W_{\{2,5\}}$. Since $\beta_{\{4,5\},\{2,4\}} = -y_{5,2}$ and $\beta_{\{4,5\},\{2,5\}} = y_{4,2}$, in order to let the coefficient of $F_{1,\{2\}}$ on the RHS of (38) be 0, we let

$$\beta_{\{4,5\},\{1,2\}} = y_{4,1}y_{5,2} - y_{5,1}y_{4,2} = \det([y_{4,1}, y_{4,2}; y_{5,1}, y_{5,2}]). \quad (46)$$

In addition, $F_{2,\{1\}}$ appears in $W_{\{1,2\}}$, $W_{\{1,4\}}$, and $W_{\{1,5\}}$. The coefficient of $F_{2,\{1\}}$ on the RHS of (38) is

$$-\beta_{\{4,5\},\{1,2\}} + y_{4,2}\beta_{\{4,5\},\{1,4\}} + y_{5,2}\beta_{\{4,5\},\{1,5\}} = 0. \quad (47)$$

Similarly, we let

$$\beta_{\{4,5\},\{1,3\}} = y_{4,1}y_{5,3} - y_{5,1}y_{4,3} = \det([y_{4,1}, y_{4,3}; y_{5,1}, y_{5,3}]), \quad (48)$$

such that the coefficients of $F_{1,\{3\}}$ and $F_{3,\{1\}}$ on the RHS of (38) are 0. We let

$$\beta_{\{4,5\},\{2,3\}} = y_{4,2}y_{5,3} - y_{5,2}y_{4,3} = \det([y_{4,2}, y_{4,3}; y_{5,2}, y_{5,3}]), \quad (49)$$

such that the coefficients of $F_{2,\{3\}}$ and $F_{3,\{2\}}$ on the RHS of (38) are 0.

With the above choice of decoding coefficients, on the RHS of (38), the coefficients of all the subfiles which is not contained by $W_{\{4,5\}}$ are 0. In addition, the coefficients of each subfile contained by $W_{\{4,5\}}$ are the same on both sides of (38). Thus we prove (38). In conclusion, each user can recover all multicast messages in (37), and then recover its demanded function.

Performance. In total we transmit $\binom{K}{t+1} - \binom{K - \text{rank}_q(\mathbb{D})}{t+1} = \binom{5}{2} - \binom{2}{2} = 9$ multicast messages, each of which contains $\frac{B}{5}$ symbols. Hence, the transmitted load is $\frac{9}{5}$, which coincides with the optimal worst-case load in Theorem 2.

B. General Description

We use the file split in (15)-(16), resulting in the demand split in (17).

In the delivery phase, after the demand matrix $\mathbb{D}$ is revealed, among the K users we first choose $\text{rank}_q(\mathbb{D})$ leaders (assume the set of leaders is $\mathcal{L} = \{\mathcal{L}(1), \dots, \mathcal{L}(|\mathcal{L}|)\}$), where

$$|\mathcal{L}| = \text{rank}_q(\mathbb{D}_{\mathcal{L}}) = \text{rank}_q(\mathbb{D}). \quad (50)$$

For each $i \in [|\mathcal{L}|]$, we also define that the *leader index* of leader $\mathcal{L}(i)$ is i .

From (50), we can represent the demands of non-leaders by the linear combinations of the demands of leaders. More precisely, we define

$$F'_i := y_{\mathcal{L}(i),1}F_1 + \dots + y_{\mathcal{L}(i),N}F_N, \quad \forall i \in [|\mathcal{L}|], \quad (51)$$

and represent the demand of each user $k \in [K]$ by

$$y_{k,1}F_1 + \dots + y_{k,N}F_N = x_{k,1}F'_1 + \dots + x_{k,|\mathcal{L}|}F'_{|\mathcal{L}|}. \quad (52)$$

Clearly, for each leader $\mathcal{L}(i)$ where $i \in [|\mathcal{L}|]$, $\mathbf{x}_{\mathcal{L}(i)}$ is an $|\mathcal{L}|$ -dimension unit vector where the i^{th} element is 1. The transformed demand matrix $\mathbb{D}'$ is defined as follows,

$$\mathbb{D}' = [x_{1,1}, \dots, x_{1,|\mathcal{L}|}; \dots; x_{K,1}, \dots, x_{K,|\mathcal{L}|}]. \quad (53)$$

In addition, for each $i \in [|\mathcal{L}|]$ and each $\mathcal{W} \subseteq [K]$ where $|\mathcal{W}| = t$, we define

$$F'_{i,\mathcal{W}} := y_{\mathcal{L}(i),1}F_{1,\mathcal{W}} + \dots + y_{\mathcal{L}(i),N}F_{N,\mathcal{W}}, \quad (54)$$

refer $F'_{i,\mathcal{W}}$ to as a *transformed subfile*, and refer

$$B'_{k,\mathcal{W}} = x_{k,1}F'_{1,\mathcal{W}} + \dots + x_{k,|\mathcal{L}|}F'_{|\mathcal{L}|,\mathcal{W}}$$

to as a *transformed block*.

Encoding. For each $\mathcal{S} \subseteq [K]$, we denote the set of leaders in $\mathcal{S}$ by

$$\mathcal{L}_{\mathcal{S}} := \mathcal{S} \cap \mathcal{L}, \quad (55)$$

and the set of non-leaders in $\mathcal{S}$ by

$$\mathcal{N}_{\mathcal{S}} := \mathcal{S} \setminus \mathcal{L}. \quad (56)$$

We also denote the leader indices of leaders in $\mathcal{S}$ by

$$\text{Ind}_{\mathcal{S}} := \{i \in [|\mathcal{L}|] : \mathcal{L}(i) \in \mathcal{S}\}, \quad (57)$$

For example, if $\mathcal{L} = \{2, 4, 5\}$ and $\mathcal{S} = \{1, 2, 5\}$, we have $\mathcal{L}_{\mathcal{S}} = \{2, 5\}$, $\mathcal{N}_{\mathcal{S}} = \{1\}$, and $\text{Ind}_{\mathcal{S}} = \{1, 3\}$.

Now we focus on each set $\mathcal{S} \subseteq [K]$ where $|\mathcal{S}| = t + 1$, and generate the multicast message

$$W_{\mathcal{S}} = \sum_{i \in [\mathcal{L}_{\mathcal{S}}]} (-1)^{i-1} B'_{\mathcal{L}_{\mathcal{S}}(i), \mathcal{S} \setminus \{\mathcal{L}_{\mathcal{S}}(i)\}} + \sum_{j \in [\mathcal{N}_{\mathcal{S}}]} (-1)^{j-1} B'_{\mathcal{N}_{\mathcal{S}}(j), \mathcal{S} \setminus \{\mathcal{N}_{\mathcal{S}}(j)\}}. \quad (58)$$

The construction of $W_{\mathcal{S}}$ can be explained as follows.

- The coefficient of each transformed block in $W_{\mathcal{S}}$ is either 1 or -1 .
- We divide the transformed blocks in $W_{\mathcal{S}}$ into two groups, demanded by leaders and non-leaders, respectively. We alternate the sign (i.e., the coefficient 1 or -1) of each transformed block demanded by leaders, and alternate the sign of each transformed block demanded by non-leaders, respectively. We then sum the resulting summations of these two groups.
- For each $i \in [\mathcal{L}_{\mathcal{S}}]$, by the construction in (51), we have

$$B'_{\mathcal{L}_{\mathcal{S}}(i), \mathcal{S} \setminus \{\mathcal{L}_{\mathcal{S}}(i)\}} = F'_{\text{Ind}_{\mathcal{S}}(i), \mathcal{S} \setminus \{\mathcal{L}_{\mathcal{S}}(i)\}}.$$

Delivery. The server broadcasts $W_{\mathcal{S}}$ for each $\mathcal{S} \subseteq [K]$ where $|\mathcal{S}| = t + 1$ and $\mathcal{S} \cap \mathcal{L} \neq \emptyset$.

Decoding. We consider each set $\mathcal{A} \subseteq [K]$ where $|\mathcal{A}| = t + 1$ and $\mathcal{A} \cap \mathcal{L} = \emptyset$.

We define that the *non-leader index* of non-leader $\mathcal{A}(i)$ is i , where $i \in [t + 1]$. For each $\mathcal{S} \subseteq \mathcal{A} \cup \mathcal{L}$, recall that $\text{Ind}_{\mathcal{S}}$ defined in (57) represents the leader indices of leaders in $\mathcal{S}$ and that $\mathcal{N}_{\mathcal{S}}$ defined in (56) represents the set of non-leaders in $\mathcal{S}$. By definition, we have $\mathcal{N}_{\mathcal{S}} \subseteq \mathcal{A}$. In addition, with a slight abuse of notation we denote the non-leader indices of non-leaders in $\mathcal{A} \setminus \mathcal{S}$ by

$$\overline{\text{Ind}}_{\mathcal{S}} = \{i \in [t + 1] : \mathcal{A}(i) \notin \mathcal{S}\}. \quad (59)$$

For example, if $\mathcal{A} = \{4, 5, 6\}$ and $\mathcal{S} = \{1, 2, 5\}$, we have $\overline{\text{Ind}}_{\mathcal{S}} = \{1, 3\}$.

For any set $\mathcal{X}$ and any number y , we define $\text{Tot}(\mathcal{X})$ as the sum of the elements in $\mathcal{X}$, i.e.,

$$\text{Tot}(\mathcal{X}) := \sum_{i \in [\mathcal{X}]} \mathcal{X}(i);. \quad (60)$$

For example, if $\mathcal{X} = \{1, 3, 4, 5\}$, we have $\text{Tot}(\mathcal{X}) = 1 + 3 + 4 + 5 = 13$.

Recall that $\mathbb{A}_{\mathcal{S}, \mathcal{V}}$ represents the sub-matrix of $\mathbb{A}$ by selecting from $\mathbb{A}$, the rows with indices in $\mathcal{S}$ and the columns with indices in $\mathcal{V}$. It will be proved in Appendix B that

$$W_{\mathcal{A}} = \sum_{\mathcal{S} \subseteq \mathcal{A} \cup \mathcal{L} : |\mathcal{S}| = t+1, \mathcal{S} \neq \mathcal{A}} \beta_{\mathcal{A}, \mathcal{S}} W_{\mathcal{S}}, \quad (61)$$

$$\beta_{\mathcal{A},\mathcal{S}} = (-1)^{1+\text{Tot}(\overline{\text{Ind}}_{\mathcal{S}})} \det(\mathbb{D}'_{\mathcal{A} \setminus \mathcal{S}, \text{Ind}_{\mathcal{S}}}). \quad (62)$$

In other words, each user $k \in [\mathsf{K}]$ can recover all messages $W_{\mathcal{S}}$ where $\mathcal{S} \subseteq [\mathsf{K}]$ and $|\mathcal{S}| = t + 1$. For each desired transformed block $B'_{k,\mathcal{W}}$, where $\mathcal{W} \subseteq ([\mathsf{K}] \setminus \{k\})$ and $|\mathcal{W}| = t$, user k can recover it in $W_{\mathcal{W} \cup \{k\}}$, because it knows all the other transformed blocks in $W_{\mathcal{W} \cup \{k\}}$. Hence, user k can recover $x_{k,1}F'_1 + \dots + x_{k,|\mathcal{L}|}F'_{|\mathcal{L}|}$, which is identical to its demand.

Performance. In total, we transmit $\binom{\mathsf{K}}{t+1} - \binom{\mathsf{K}-\text{rank}_{\mathsf{q}}(\mathbb{D})}{t+1}$ multicast messages, each of which contains $\frac{\mathsf{B}}{\binom{\mathsf{K}}{t}}$ symbols. Hence, the transmitted load is

$$\frac{\binom{\mathsf{K}}{t+1} - \binom{\mathsf{K}-\text{rank}_{\mathsf{q}}(\mathbb{D})}{t+1}}{\binom{\mathsf{K}}{t}}. \quad (63)$$

For the worst-case demands where $\text{rank}_{\mathsf{q}}(\mathbb{D})$ is full-rank, we have $\text{rank}_{\mathsf{q}}(\mathbb{D}) = \min\{\mathsf{K}, \mathsf{N}\}$, and we achieve the worst-case load in (21).

VI. CONCLUSIONS

In this paper, we introduced a novel problem, cache-aided function retrieval, which is a generalization of the classic coded caching problem and allows users to request scalar linear functions of files. We proposed a novel scheme for the demands functions on arbitrary finite field. The proposed scheme was proved to be optimal under the constraint of uncoded cache placement. In addition, for any demand, the achieved load only depends on the rank of the demand matrix. From the results in this paper, we showed that compared to the original MAN caching problem, the optimal worst-case load of coded caching under the constraint of uncoded cache placement, is not increased when users request scalar linear functions.

Further works include the extension of the proposed caching scheme to the case where the demanded functions are non-linear or vectorial, and finding novel caching schemes for the cache-aided function retrieval problem with coded cache placement.

APPENDIX A

PROOF OF LEMMA 1

To prove Lemma 1, it is equivalent to prove that the number of users $k \in \mathcal{B} \setminus \mathcal{W}$ satisfying the following constraints is even,

- 1) Constraint 1: $\text{rank}_2(\mathbb{D}_{\mathcal{B} \setminus (\mathcal{W} \cup \{k\})}) = |\mathcal{L}|$;
- 2) Constraint 2: $y_{k,i} \neq 0$.

We assume that user k_1 satisfies the above constraints. Hence, $\mathbb{D}_{\mathcal{B} \setminus (\mathcal{W} \cup \{k_1\})}$ is full-rank, and $y_{k_1,i} \neq 0$. We let $\mathcal{Y} = \{\mathcal{Y}(1), \dots, \mathcal{Y}(|\mathcal{L}|)\} = \mathcal{B} \setminus (\mathcal{W} \cup \{k_1\})$.

In the following, we operate a linear space transformation. More precisely, we let

$$G_j = \mathbf{y}_{\mathcal{Y}(j)}[F_1; \dots; F_N], \quad \forall j \in [|\mathcal{L}|]. \quad (64)$$

From (64), we can re-write the demand of each user $\mathcal{Y}(j)$ as

$$G_j = \mathbf{y}'_j[G_1; \dots; G_{|\mathcal{L}|}],$$

where $\mathbf{y}'_j$ is the $|\mathcal{L}|$ -dimension unit vector whose j^{th} element is 1. The transformed demand matrix of the users in $\mathcal{Y}$ is

$$\mathbb{D}'_{\mathcal{Y}} = [\mathbf{y}'_1; \dots; \mathbf{y}'_{|\mathcal{L}|}],$$

which is an identity matrix.

In addition, we can also re-write the demand of user k_1 as

$$\mathbf{y}'[G_1; \dots; G_{|\mathcal{L}|}],$$

where $\mathbf{y}'$ is an $|\mathcal{L}|$ -dimension vector on $\mathbb{F}_2$. Notice that if the p^{th} element in $\mathbf{y}'$ is 1 and G_p contains F_i , F_i appears one time in $\mathbf{y}'[G_1; \dots; G_{|\mathcal{L}|}]$. Since $y_{k_1,i} \neq 0$, it can be seen that $\mathbf{y}'[G_1; \dots; G_{|\mathcal{L}|}]$ contains F_i . Hence, the number of $p \in [|\mathcal{L}|]$ where the p^{th} element in $\mathbf{y}'$ is 1 and G_p contains F_i , is odd. For each of such p , if we replace the p^{th} row of $\mathbb{D}'_{\mathcal{Y}}$ by $\mathbf{y}'$, the resulting matrix is still full-rank, because the p^{th} element in $\mathbf{y}'$ is 1. Since the resulting matrix is full-rank, it can be seen that $\mathbb{D}_{\mathcal{B} \setminus (\mathcal{W} \cup \{\mathcal{Y}(p)\})}$ is also full-rank. In addition, since G_p contains F_i , we can see that $y_{\mathcal{Y}(p),i} \neq 0$. Hence, user $\mathcal{Y}(p)$ also satisfies the two constraints. Moreover, for any $s \in [|\mathcal{L}|]$, if the s^{th} element in $\mathbf{y}'$ is not 1, user $\mathcal{Y}(s)$ does not satisfy Constraint 1; if G_s does not contain F_s , user $\mathcal{Y}(s)$ does not satisfy Constraint 2.

As a result, besides user k_1 , the number of users in $\mathcal{B} \setminus \mathcal{W}$ satisfying the two constraints is odd. In conclusion, by taking user k_1 into consideration, the number of users in $\mathcal{B} \setminus \mathcal{W}$ satisfying the two constraints is even. Thus Lemma 1 is proved.

APPENDIX B

PROOF OF (61)

We focus on one set of non-leaders $\mathcal{A} \subseteq [K]$ where $|\mathcal{A}| = t + 1$ and $\mathcal{A} \cap \mathcal{L} = \emptyset$.

For any positive integer n , $\text{Perm}(n)$ represents the set of all permutations of $[n]$. For any set $\mathcal{X}$ and any number y , we define $\text{Card}(\mathcal{X}, y)$ as the number of elements in $\mathcal{X}$ which is smaller than y , i.e.,

$$\text{Card}(\mathcal{X}, y) := |\{i \in \mathcal{X} : i < y\}|. \quad (65)$$

For example, if $\mathcal{X} = \{1, 3, 4, 5\}$ and $y = 4$, we have $\text{Card}(\mathcal{X}, y) = |\{1, 3\}| = 2$.

Our objective is to prove

$$W_{\mathcal{A}} = \sum_{\mathcal{S} \subseteq \mathcal{A} \cup \mathcal{L}; |\mathcal{S}|=t+1, \mathcal{S} \neq \mathcal{A}} \beta_{\mathcal{A}, \mathcal{S}} W_{\mathcal{S}}, \quad (66)$$

$$\beta_{\mathcal{A}, \mathcal{S}} = \sum_{\substack{\mathbf{u}=(u_1, \dots, u_{|\text{Ind}_{\mathcal{S}}|}) \\ \in \text{Perm}(|\text{Ind}_{\mathcal{S}}|)}} (-1)^{1+\text{Tot}(\overline{\text{Ind}}_{\mathcal{S}}) + \sum_{i_1 \in |\text{Ind}_{\mathcal{S}}|} \text{Card}(|\text{Ind}_{\mathcal{S}}| \setminus \{u_1, \dots, u_{i_1}\}, u_{i_1})} \prod_{i_2 \in |\text{Ind}_{\mathcal{S}}|} x_{\mathcal{A}(\overline{\text{Ind}}_{\mathcal{S}}(u_{i_2})), \text{Ind}_{\mathcal{S}}(i_2)}, \quad (67)$$

where (67) is obtained from expand the determinant in (62). Let us go back to the illustrated example in Section V-A, where we choose $\mathcal{L} = [3]$. When $\mathcal{A} = \{4, 5\}$ and $\mathcal{S} = \{1, 2\}$, from the definition in (57) we have $\text{Ind}_{\mathcal{S}} = [2]$ and from the definition in (59) we have $\overline{\text{Ind}}_{\mathcal{S}} = [2]$. In addition, $\text{Perm}(|\text{Ind}_{\mathcal{S}}|) = \text{Perm}(2)\{(1, 2), (2, 1)\}$. Hence, when $\mathbf{u} = (u_1, u_2) = (1, 2)$, in (67) we have the term

$$\begin{aligned} & (-1)^{1+\text{Tot}([2]) + \text{Card}([2] \setminus \{1\}, 1) + \text{Card}([2] \setminus \{1, 2\}, 2)} x_{4,1} x_{5,2} \\ &= (-1)^{1+\text{Tot}([2]) + \text{Card}([2] \setminus \{1\}, 1) + \text{Card}([2] \setminus \{1, 2\}, 2)} y_{4,1} y_{5,2} \\ &= y_{4,1} y_{5,2}, \end{aligned} \quad (68)$$

where (68) is because in the example we have $F_i = F'_i$ for each $i \in [\mathbf{N}]$, and thus $\mathbf{x}_k = \mathbf{y}_k$ for each $k \in [\mathbf{K}]$. Similarly, when $\mathbf{u} = (2, 1)$, in (67) we have the term

$$\begin{aligned} & (-1)^{1+\text{Tot}([2]) + \text{Card}([2] \setminus \{2\}, 2) + \text{Card}([2] \setminus \{1, 2\}, 1)} x_{5,1} x_{4,2} \\ &= (-1)^{1+\text{Tot}([2]) + \text{Card}([2] \setminus \{2\}, 2) + \text{Card}([2] \setminus \{1, 2\}, 1)} y_{5,1} y_{4,2} \\ &= -y_{5,1} y_{4,2}. \end{aligned} \quad (69)$$

Hence, in (67) we have $\beta_{\{4,5\}, \{1,2\}} = y_{4,1} y_{5,2} - y_{5,1} y_{4,2}$, which coincides (46) in the illustrated example.

By the definition of $W_{\mathcal{S}}$ in (58), it is obvious to check that in (66), there only exist the transformed subfiles $F_{i, \mathcal{W}}$ where $i \in [\mathbf{N}]$, $|\mathcal{W}| \subseteq (\mathcal{A} \cup \mathcal{L})$, and $|\mathcal{W}| = t$. Now we divide such

transformed subfiles into hierarchies, where we say a transformed subfile $F'_{i,\mathcal{W}}$ appearing in (66) is in Hierarchy $h \in [0 : t]$, if $|\mathcal{W} \cap \mathcal{L}| = h$. In addition, on the LHS of (66), only transformed subfiles in Hierarchy 0 exist.

We consider the following three cases,

- 1) Case 1: $F'_{i,\mathcal{W}}$ is in Hierarchy 0. In Appendix B-A, we will prove that the coefficient of $F'_{i,\mathcal{W}}$ on the RHS of (66) is equal to the coefficient of $F'_{i,\mathcal{W}}$ on the LHS of (66).
- 2) Case 2: $F'_{i,\mathcal{W}}$ is in Hierarchy $h > 0$ and $\mathcal{L}(i) \in \mathcal{W}$. In Appendix B-B, we will prove that the coefficient of $F'_{i,\mathcal{W}}$ on the RHS of (66) is 0.
- 3) Case 3: $F'_{i,\mathcal{W}}$ is in Hierarchy $h > 0$ and $\mathcal{L}(i) \notin \mathcal{W}$. In Appendix B-C, we will prove that the coefficient of $F'_{i,\mathcal{W}}$ on the RHS of (66) is 0.

Hence, after proving the above three cases, (66) can be directly derived.

In the illustrated example in Section V-A, since $F_i = F'_i$ for each $i \in [N]$, it can be seen that $F'_{i,\mathcal{W}} = F_{i,\mathcal{W}}$ for each $i \in [N]$, $|\mathcal{W}| \subseteq [K]$, and $|\mathcal{W}| = t$. For each subfile $F_{i,\mathcal{W}}$, it is in one of the following three cases,

- 1) Case 1: $F_{i,\mathcal{W}}$ is in Hierarchy 0. In this case, we have the subfiles $F_{i,\{4\}}, F_{i,\{5\}}$ for $i \in [3]$.
- 2) Case 2: $F_{i,\mathcal{W}}$ is in Hierarchy 1 and $\mathcal{L}(i) \in \mathcal{W}$. In this case, we have the subfiles $F_{i,\{i\}}$ for $i \in [3]$.
- 3) Case 3: $F_{i,\mathcal{W}}$ is in Hierarchy 1 and $\mathcal{L}(i) \notin \mathcal{W}$. In this case, we have the subfiles $F_{i,\{j\}}$ for $i \in [3]$ and $j \in [3] \setminus \{i\}$.

A. Case 1

If $F'_{i,\mathcal{W}}$ is in Hierarchy 0, we have $\mathcal{W} \subseteq \mathcal{A}$. Since $|\mathcal{A}| - |\mathcal{W}| = 1$, we assume that $\{\mathcal{A}(k)\} = \mathcal{A} \setminus \mathcal{W}$. On the LHS of (66), $F'_{i,\mathcal{W}}$ appears in $W_{\mathcal{A}}$, where from (58) we have

$$W_{\mathcal{A}} = \sum_{j \in [t+1]} (-1)^{j-1} (x_{\mathcal{A}(j),1} F'_{1,S \setminus \{\mathcal{A}(j)\}} + \dots + x_{\mathcal{A}(j),|\mathcal{L}|} F'_{|\mathcal{L}|,S \setminus \{\mathcal{A}(j)\}}). \quad (70)$$

Hence, the coefficient of $F'_{i,\mathcal{W}}$ in $W_{\mathcal{A}}$ is $(-1)^{k-1} x_{\mathcal{A}(k),i}$.

Let us then focus on the RHS of (66). $F'_{i,\mathcal{W}}$ appears in $W_{\mathcal{W} \cup \{\mathcal{L}(i)\}}$. Since $\mathcal{L}(i)$ is the only leader in $\mathcal{W} \cup \{\mathcal{L}(i)\}$ (i.e., $\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}} = \{i\}$), the coefficient of $F'_{i,\mathcal{W}}$ in $W_{\mathcal{W} \cup \{\mathcal{L}(i)\}}$ is $(-1)^{1-1} = 1$. In addition, by computing $\overline{\text{Ind}}_{\mathcal{W} \cup \{\mathcal{L}(i)\}} = \{k\}$, we have

$$\beta_{\mathcal{A},\mathcal{W} \cup \{\mathcal{L}(i)\}} = (-1)^{1+k+0} x_{\mathcal{A}(k),i} = (-1)^{k+1} x_{\mathcal{A}(k),i} = (-1)^{k-1} x_{\mathcal{A}(k),i}. \quad (71)$$

Hence, the coefficient of $F'_{i,\mathcal{W}}$ on the RHS of (66) (i.e., in $\beta_{\mathcal{A},\mathcal{W}\cup\{\mathcal{L}(i)\}}W_{\mathcal{W}\cup\{\mathcal{L}(i)\}}$) is

$$(-1)^{k-1}x_{\mathcal{A}(k),i} \times 1 = (-1)^{k-1}x_{\mathcal{A}(k),i}, \quad (72)$$

which is the same as the coefficient of $F'_{i,\mathcal{W}}$ on the LHS of (66).

B. Case 2

Now we focus on one transformed subfile $F'_{i,\mathcal{W}}$ in Hierarchy $h > 0$ where $\mathcal{L}(i) \in \mathcal{W}$. By definition, we have $|\mathcal{W} \cap \mathcal{L}| = h$. On the RHS of (66), since $\mathcal{L}(i) \in \mathcal{W}$, $F'_{i,\mathcal{W}}$ only appears in $W_{\mathcal{W}\cup\{\mathcal{A}(k)\}}$, where $k \in \overline{\text{Ind}}_{\mathcal{W}}$. We define that

$$\text{the } \left(\overline{\text{Ind}}_{\mathcal{W}}^{-1}(k)\right)^{\text{th}} \text{ smallest element in } \overline{\text{Ind}}_{\mathcal{W}} \text{ is } k. \quad (73)$$

We focus on one $k \in \overline{\text{Ind}}_{\mathcal{W}}$. $\mathcal{A}(k)$ is the k^{th} element in $\mathcal{A}$, and in $\mathcal{A} \setminus \mathcal{W}$ there are $\overline{\text{Ind}}_{\mathcal{W}}^{-1}(k) - 1$ elements smaller than $\mathcal{A}(k)$. Hence, in $\mathcal{N}_{\mathcal{W}\cup\{\mathcal{A}(k)\}}$ there are $k-1 - \left(\overline{\text{Ind}}_{\mathcal{W}}^{-1}(k) - 1\right) = k - \overline{\text{Ind}}_{\mathcal{W}}^{-1}(k)$ elements smaller than $\mathcal{A}(k)$. So from (58), it can be seen that the coefficient of $F'_{i,\mathcal{W}}$ in $W_{\mathcal{W}\cup\{\mathcal{A}(k)\}}$ is

$$(-1)^{k - \overline{\text{Ind}}_{\mathcal{W}}^{-1}(k)} x_{\mathcal{A}(k),i}. \quad (74)$$

In addition, we have

$$\begin{aligned} \beta_{\mathcal{A},\mathcal{W}\cup\{\mathcal{A}(k)\}} &= \sum_{\substack{\mathbf{u}=(u_1,\dots,u_{|\text{Ind}_{\mathcal{W}\cup\{\mathcal{A}(k)\}}|}) \\ \in \text{Perm}(|\text{Ind}_{\mathcal{W}\cup\{\mathcal{A}(k)\}}|)}} (-1)^{1+\text{Tot}(\overline{\text{Ind}}_{\mathcal{W}\cup\{\mathcal{A}(k)\}})+\sum_{i_1 \in [|\text{Ind}_{\mathcal{W}\cup\{\mathcal{A}(k)\}}|]} \text{Card}([|\text{Ind}_{\mathcal{W}\cup\{\mathcal{A}(k)\}}|] \setminus \{u_1,\dots,u_{i_1}\}, u_{i_1})} \\ &\quad \prod_{i_2 \in [|\text{Ind}_{\mathcal{W}\cup\{\mathcal{A}(k)\}}|]} x_{\mathcal{A}(\overline{\text{Ind}}_{\mathcal{W}\cup\{\mathcal{A}(k)\}}(u_{i_2})), \text{Ind}_{\mathcal{W}\cup\{\mathcal{A}(k)\}}(i_2)} \end{aligned} \quad (75a)$$

$$\begin{aligned} &= \sum_{\substack{\mathbf{u}=(u_1,\dots,u_{|\text{Ind}_{\mathcal{W}}|}) \\ \in \text{Perm}(|\text{Ind}_{\mathcal{W}}|)}} (-1)^{1+(\text{Tot}(\overline{\text{Ind}}_{\mathcal{W}})-k)+\sum_{i_1 \in [|\text{Ind}_{\mathcal{W}}|]} \text{Card}([|\text{Ind}_{\mathcal{W}}|] \setminus \{u_1,\dots,u_{i_1}\}, u_{i_1})} \\ &\quad \prod_{i_2 \in [|\text{Ind}_{\mathcal{W}}|]} x_{\mathcal{A}(\overline{\text{Ind}}_{\mathcal{W}\cup\{\mathcal{A}(k)\}}(u_{i_2})), \text{Ind}_{\mathcal{W}}(i_2)}. \end{aligned} \quad (75b)$$

From (74) and (75b), the coefficient of $F'_{i,\mathcal{W}}$ in $\beta_{\mathcal{A},\mathcal{W}\cup\{\mathcal{A}(k)\}}W_{\mathcal{W}\cup\{\mathcal{A}(k)\}}$ is $(-1)^{k - \overline{\text{Ind}}_{\mathcal{W}}^{-1}(k)} x_{\mathcal{A}(k),i} \beta_{\mathcal{A},\mathcal{W}\cup\{\mathcal{A}(k)\}}$.

In the following, we will prove

$$\sum_{k \in \overline{\text{Ind}}_{\mathcal{W}}} (-1)^{k - \overline{\text{Ind}}_{\mathcal{W}}^{-1}(k)} x_{\mathcal{A}(k),i} \beta_{\mathcal{A},\mathcal{W}\cup\{\mathcal{A}(k)\}} = 0, \quad (76)$$

such that the coefficient of $F'_{i,\mathcal{W}}$ on the RHS of (66) is 0.

Let us focus on one $k \in \overline{\text{Ind}}_{\mathcal{W}}$ and one permutation $\mathbf{u} = (u_1, \dots, u_{|\text{Ind}_{\mathcal{W}}|}) \in \text{Perm}(|\text{Ind}_{\mathcal{W}}|)$. The term in (76) caused by k and $\mathbf{u}$ is

$$(-1)^{k - \overline{\text{Ind}}_{\mathcal{W}}^{-1}(k)} x_{\mathcal{A}(k), i} \left\{ (-1)^{1 + (\text{Tot}(\overline{\text{Ind}}_{\mathcal{W}}) - k) + \sum_{i_1 \in [|\text{Ind}_{\mathcal{W}}|]} \text{Card}([\text{Ind}_{\mathcal{W}}] \setminus \{u_1, \dots, u_{i_1}\}, u_{i_1})} \prod_{i_2 \in [|\text{Ind}_{\mathcal{W}}|]} x_{\mathcal{A}(\overline{\text{Ind}}_{\mathcal{W} \cup \{\mathcal{A}(k)\}}(u_{i_2})), \text{Ind}_{\mathcal{W}}(i_2)} \right\} \quad (77a)$$

$$= (-1)^{-\overline{\text{Ind}}_{\mathcal{W}}^{-1}(k) + 1 + \text{Tot}(\overline{\text{Ind}}_{\mathcal{W}}) + \sum_{i_1 \in [|\text{Ind}_{\mathcal{W}}|]} \text{Card}([\text{Ind}_{\mathcal{W}}] \setminus \{u_1, \dots, u_{i_1}\}, u_{i_1})} \left\{ x_{\mathcal{A}(k), i} \prod_{i_2 \in [|\text{Ind}_{\mathcal{W}}|]} x_{\mathcal{A}(\overline{\text{Ind}}_{\mathcal{W} \cup \{\mathcal{A}(k)\}}(u_{i_2})), \text{Ind}_{\mathcal{W}}(i_2)} \right\}. \quad (77b)$$

Notice that in the product

$$x_{\mathcal{A}(k), i} \prod_{i_2 \in [|\text{Ind}_{\mathcal{W}}|]} x_{\mathcal{A}(\overline{\text{Ind}}_{\mathcal{W} \cup \{\mathcal{A}(k)\}}(u_{i_2})), \text{Ind}_{\mathcal{W}}(i_2)}, \quad (78)$$

there is one term whose second subscript is i' for each $i' \in \text{Ind}_{\mathcal{W}} \setminus \{i\}$, and there are two terms whose second subscript is i . We define that

$$\text{the } (\text{Ind}_{\mathcal{W}}^{-1}(i))^{\text{th}} \text{ smallest element in } \text{Ind}_{\mathcal{W}} \text{ is } i. \quad (79)$$

Hence, the two terms in (78) whose second subscript is i are $x_{\mathcal{A}(k), i}$ and $x_{\mathcal{A}(k'), i}$, where $k' := \overline{\text{Ind}}_{\mathcal{W} \cup \{\mathcal{A}(k)\}}(u_{\text{Ind}_{\mathcal{W}}^{-1}(i)})$.

In addition, the combination k' and $\mathbf{u}' = (u'_1, \dots, u'_{|\text{Ind}_{\mathcal{W}}|})$ also causes a term in (76) which has the product

$$x_{\mathcal{A}(k'), i} \prod_{i_2 \in [|\text{Ind}_{\mathcal{W}}|]} x_{\mathcal{A}(\overline{\text{Ind}}_{\mathcal{W} \cup \{\mathcal{A}(k')\}}(u'_{i_2})), \text{Ind}_{\mathcal{W}}(i_2)}. \quad (80)$$

The products in (78) and (80) are identical if $\mathbf{u}'$ is as follows,

- for $j \in [|\text{Ind}_{\mathcal{W}}|] \setminus \{\text{Ind}_{\mathcal{W}}^{-1}(i)\}$, we have

$$\mathcal{A}(\overline{\text{Ind}}_{\mathcal{W} \cup \{\mathcal{A}(k')\}}(u'_j)) = \mathcal{A}(\overline{\text{Ind}}_{\mathcal{W} \cup \{\mathcal{A}(k)\}}(u_j)); \quad (81)$$

such that

$$x_{\mathcal{A}(\overline{\text{Ind}}_{\mathcal{W} \cup \{\mathcal{A}(k')\}}(u'_j)), \text{Ind}_{\mathcal{W}}(j)} = x_{\mathcal{A}(\overline{\text{Ind}}_{\mathcal{W} \cup \{\mathcal{A}(k)\}}(u_j)), \text{Ind}_{\mathcal{W}}(j)}; \quad (82)$$

- for $j = \text{Ind}_{\mathcal{W}}^{-1}(i)$, we have

$$\mathcal{A}(\overline{\text{Ind}}_{\mathcal{W} \cup \{\mathcal{A}(k')\}}(u'_j)) = \mathcal{A}(k); \quad (83)$$

such that

$$x_{\mathcal{A}(\overline{\text{Ind}}_{\mathcal{W} \cup \{\mathcal{A}(k')\}}(u'_j)), \text{Ind}_{\mathcal{W}}(j)} = x_{\mathcal{A}(k), i}. \quad (84)$$

It is obvious to check that there does not exist any other combination of $k'' \in \overline{\text{Ind}}_{\mathcal{W}}$ and $\mathbf{u}'' \in \text{Perm}(|\text{Ind}_{\mathcal{W}}|)$, causing a term on the LHS of (76) which has the product in (78), except the two above combinations.

In Appendix C, we will prove that

$$\begin{aligned} & (-1)^{-\overline{\text{Ind}}_{\mathcal{W}}^{-1}(k)+1+\text{Tot}(\overline{\text{Ind}}_{\mathcal{W}})+\sum_{i_1 \in [|\text{Ind}_{\mathcal{W}}|]} \text{Card}([|\text{Ind}_{\mathcal{W}}|] \setminus \{u_1, \dots, u_{i_1}\}, u_{i_1})} \\ & (-1)^{-\overline{\text{Ind}}_{\mathcal{W}}^{-1}(k')+1+\text{Tot}(\overline{\text{Ind}}_{\mathcal{W}})+\sum_{i'_1 \in [|\text{Ind}_{\mathcal{W}}|]} \text{Card}([|\text{Ind}_{\mathcal{W}}|] \setminus \{u'_1, \dots, u'_{i'_1}\}, u'_{i'_1})} = 0, \end{aligned} \quad (85)$$

such that the coefficient of the product in (78) on the LHS of (76) is 0. In other words, for each combination of k and $\mathbf{u}$ on the LHS of (76), there is exactly one term caused by the combination of k' and $\mathbf{u}'$, such that the sum of these two caused terms is 0. Thus (76) is proved.

C. Case 3

Lastly we focus on one transformed subfile $F'_{i, \mathcal{W}}$ in Hierarchy $h > 0$ where $\mathcal{L}(i) \notin \mathcal{W}$. By definition, we have $|\mathcal{W} \cap \mathcal{L}| = h$. On the RHS of (66), since $\mathcal{L}(i) \notin \mathcal{W}$, $F'_{i, \mathcal{W}}$ appears in $W_{\mathcal{W} \cup \{\mathcal{L}(i)\}}$. In addition, $F'_{i, \mathcal{W}}$ also appears in $W_{\mathcal{W} \cup \{\mathcal{A}(k)\}}$, where $k \in \overline{\text{Ind}}_{\mathcal{W}}$.

Let us first focus on $W_{\mathcal{W} \cup \{\mathcal{L}(i)\}}$. Recall that the $(\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i))^{\text{th}}$ element in $\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}$ is i . From (58), it can be seen that the coefficient of $F'_{i, \mathcal{W}}$ in $W_{\mathcal{W} \cup \{\mathcal{L}(i)\}}$ is

$$(-1)^{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)-1}. \quad (86)$$

In addition, we have

$$\begin{aligned} \beta_{\mathcal{A}, \mathcal{W} \cup \{\mathcal{L}(i)\}} &= \sum_{\substack{\mathbf{u}=(u_1, \dots, u_{|\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}|}) \\ \in \text{Perm}(|\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}|)}} (-1)^{1+\text{Tot}(\overline{\text{Ind}}_{\mathcal{W} \cup \{\mathcal{L}(i)\}})+\sum_{i_1 \in [|\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}|]} \text{Card}([|\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}|] \setminus \{u_1, \dots, u_{i_1}\}, u_{i_1})} \\ &\quad \prod_{i_2 \in [|\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}|]} x_{\mathcal{A}(\overline{\text{Ind}}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}(u_{i_2})), \text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}(i_2)} \end{aligned} \quad (87a)$$

$$\begin{aligned} &= \sum_{\substack{\mathbf{u}=(u_1, \dots, u_{|\text{Ind}_{\mathcal{W}}|+1}) \\ \in \text{Perm}(|\text{Ind}_{\mathcal{W}}|+1)}} (-1)^{1+\text{Tot}(\overline{\text{Ind}}_{\mathcal{W}})+\sum_{i_1 \in [|\text{Ind}_{\mathcal{W}}|+1]} \text{Card}([|\text{Ind}_{\mathcal{W}}|+1] \setminus \{u_1, \dots, u_{i_1}\}, u_{i_1})} \prod_{i_2 \in [|\text{Ind}_{\mathcal{W}}|+1]} x_{\mathcal{A}(\overline{\text{Ind}}_{\mathcal{W}}(u_{i_2})), \text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}(i_2)} \end{aligned} \quad (87b)$$

Let us then focus on $W_{\mathcal{W} \cup \{\mathcal{A}(k)\}}$, where $k \in \overline{\text{Ind}}_{\mathcal{W}}$. It was proved in (74) that the coefficient of $F'_{i,\mathcal{W}}$ in $W_{\mathcal{W} \cup \{\mathcal{A}(k)\}}$ is

$$(-1)^{k - \overline{\text{Ind}}_{\mathcal{W}}^{-1}(k)} x_{\mathcal{A}(k),i}. \quad (88)$$

In addition, it was proved in (75b) that

$$\beta_{\mathcal{A}, \mathcal{W} \cup \{\mathcal{A}(k)\}} = \sum_{\substack{\mathbf{u} = (u_1, \dots, u_{|\text{Ind}_{\mathcal{W}}|}) \\ \in \text{Perm}(|\text{Ind}_{\mathcal{W}}|)}} (-1)^{1 + (\text{Tot}(\overline{\text{Ind}}_{\mathcal{W}}) - k) + \sum_{i_1 \in [|\text{Ind}_{\mathcal{W}}|]} \text{Card}([|\text{Ind}_{\mathcal{W}}|] \setminus \{u_1, \dots, u_{i_1}\}, u_{i_1})} \prod_{i_2 \in [|\text{Ind}_{\mathcal{W}}|]} x_{\mathcal{A}(\overline{\text{Ind}}_{\mathcal{W} \cup \{\mathcal{A}(k)\}}(u_{i_2})), \text{Ind}_{\mathcal{W}}(i_2)}. \quad (89)$$

In the following, we will prove

$$(-1)^{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i) - 1} \beta_{\mathcal{A}, \mathcal{W} \cup \{\mathcal{L}(i)\}} + \sum_{k \in \overline{\text{Ind}}_{\mathcal{W}}} (-1)^{k - \overline{\text{Ind}}_{\mathcal{W}}^{-1}(k)} x_{\mathcal{A}(k),i} \beta_{\mathcal{A}, \mathcal{W} \cup \{\mathcal{A}(k)\}} = 0, \quad (90)$$

such that the coefficient of $F'_{i,\mathcal{W}}$ on the RHS of (66) is 0. Notice that there are $t - |\text{Ind}_{\mathcal{W}}|$ non-leaders in $\mathcal{W}$. Since there are totally $t + 1$ non-leaders in $\mathcal{A}$, we have

$$|\overline{\text{Ind}}_{\mathcal{W}}| = t + 1 - (t - |\text{Ind}_{\mathcal{W}}|) = |\text{Ind}_{\mathcal{W}}| + 1. \quad (91)$$

Let us focus on one permutation $\mathbf{u} = (u_1, \dots, u_{|\text{Ind}_{\mathcal{W}}|+1}) \in \text{Perm}(|\text{Ind}_{\mathcal{W}}| + 1)$ in $\beta_{\mathcal{A}, \mathcal{W} \cup \{\mathcal{L}(i)\}}$. The term in (90) caused by $\mathbf{u}$ is

$$(-1)^{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i) - 1} \left\{ (-1)^{1 + \text{Tot}(\overline{\text{Ind}}_{\mathcal{W}}) + \sum_{i_1 \in [|\text{Ind}_{\mathcal{W}}|+1]} \text{Card}([|\text{Ind}_{\mathcal{W}}|+1] \setminus \{u_1, \dots, u_{i_1}\}, u_{i_1})} \prod_{i_2 \in [|\text{Ind}_{\mathcal{W}}|+1]} x_{\mathcal{A}(\overline{\text{Ind}}_{\mathcal{W}}(u_{i_2})), \text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}(i_2)} \right\} \quad (92a)$$

$$= (-1)^{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i) + \text{Tot}(\overline{\text{Ind}}_{\mathcal{W}}) + \sum_{i_1 \in [|\text{Ind}_{\mathcal{W}}|+1]} \text{Card}([|\text{Ind}_{\mathcal{W}}|+1] \setminus \{u_1, \dots, u_{i_1}\}, u_{i_1})} \left\{ \prod_{i_2 \in [|\text{Ind}_{\mathcal{W}}|+1]} x_{\mathcal{A}(\overline{\text{Ind}}_{\mathcal{W}}(u_{i_2})), \text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}(i_2)} \right\}. \quad (92b)$$

We can rewrite the product term in (92b) as follows (recall again that the $(\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i))^{\text{th}}$ element in $\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}$ is i),

$$\begin{aligned} & \prod_{i_2 \in [|\text{Ind}_{\mathcal{W}}|+1]} x_{\mathcal{A}(\overline{\text{Ind}}_{\mathcal{W}}(u_{i_2})), \text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}(i_2)} \\ &= x_{\mathcal{A}(\overline{\text{Ind}}_{\mathcal{W}}(u_{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)})), i} \prod_{i_2 \in [|\text{Ind}_{\mathcal{W}}|+1] \setminus \{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)\}} x_{\mathcal{A}(\overline{\text{Ind}}_{\mathcal{W}}(u_{i_2})), \text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}(i_2)} \end{aligned} \quad (93a)$$

$$= x_{\mathcal{A}(\tilde{k}), i} \prod_{i_2 \in [|\text{Ind}_{\mathcal{W}}|+1] \setminus \{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)\}} x_{\mathcal{A}(\overline{\text{Ind}}_{\mathcal{W}}(u_{i_2})), \text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}(i_2)}, \quad (93b)$$

where we define $\tilde{k} := \overline{\text{Ind}}_{\mathcal{W}}(u_{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)})$.

Hence, on the LHS of (90), besides $(-1)^{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)-1} \beta_{\mathcal{A}, \mathcal{W} \cup \{\mathcal{L}(i)\}}$, only the caused term by the combination of $\tilde{k}$ and $\tilde{\mathbf{u}} = (\tilde{u}_1, \dots, \tilde{u}_{|\text{Ind}_{\mathcal{W}}|})$ has the product in (93b), where

$$\tilde{\mathbf{u}} = (g(u_1), \dots, g(u_{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)-1}), g(u_{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)+1}), \dots, g(u_{|\text{Ind}_{\mathcal{W}}|+1})), \quad (94a)$$

$$g(u_j) := \begin{cases} u_j, & \text{if } u_j < u_{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)} \\ u_j - 1 & \text{if } u_j > u_{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)} \end{cases}. \quad (94b)$$

In Appendix D, we will prove that

$$\begin{aligned} & (-1)^{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i) + \text{Tot}(\overline{\text{Ind}}_{\mathcal{W}}) + \sum_{i_1 \in [|\text{Ind}_{\mathcal{W}}|+1]} \text{Card}([|\text{Ind}_{\mathcal{W}}|+1] \setminus \{u_1, \dots, u_{i_1}\}, u_{i_1})} \\ & (-1)^{-\overline{\text{Ind}}_{\mathcal{W}}^{-1}(\tilde{k}) + 1 + \text{Tot}(\overline{\text{Ind}}_{\mathcal{W}}) + \sum_{\tilde{i}_1 \in [|\text{Ind}_{\mathcal{W}}|]} \text{Card}([|\text{Ind}_{\mathcal{W}}|] \setminus \{\tilde{u}_1, \dots, \tilde{u}_{\tilde{i}_1}\}, \tilde{u}_{\tilde{i}_1})} = 0, \end{aligned} \quad (95)$$

such that the coefficient of the product in (93b) on the LHS of (90) is 0. Hence, for each permutation $\mathbf{u} \in \text{Perm}(|\text{Ind}_{\mathcal{W}}| + 1)$, there is exactly one term caused by the combination of $\tilde{k} \in \overline{\text{Ind}}_{\mathcal{W}}$ and $\tilde{\mathbf{u}} \in \text{Perm}(|\text{Ind}_{\mathcal{W}}|)$, such that the sum of these two caused terms are 0.

In addition, on the LHS of (90), there are $(|\text{Ind}_{\mathcal{W}}| + 1)!$ terms in $(-1)^{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)-1} \beta_{\mathcal{A}, \mathcal{W} \cup \{\mathcal{L}(i)\}}$. Recall that in (91), we proved $|\overline{\text{Ind}}_{\mathcal{W}}| = |\text{Ind}_{\mathcal{W}}| + 1$. Hence, on the LHS of (90), there are $|\text{Ind}_{\mathcal{W}}|! \times (|\text{Ind}_{\mathcal{W}}| + 1) = (|\text{Ind}_{\mathcal{W}}| + 1)!$ terms in $\sum_{k \in \overline{\text{Ind}}_{\mathcal{W}}} (-1)^{k - \overline{\text{Ind}}_{\mathcal{W}}^{-1}(k)} x_{\mathcal{A}(k), i} \beta_{\mathcal{A}, \mathcal{W} \cup \{\mathcal{A}(k)\}}$. In conclusion, we prove (90).

APPENDIX C

PROOF OF (85)

To prove (85), it is equivalent to prove

$$(-1)^{-\overline{\text{Ind}}_{\mathcal{W}}^{-1}(k) - \overline{\text{Ind}}_{\mathcal{W}}^{-1}(k') + \sum_{i_1 \in [|\text{Ind}_{\mathcal{W}}|]} \text{Card}([|\text{Ind}_{\mathcal{W}}|] \setminus \{u_1, \dots, u_{i_1}\}, u_{i_1}) + \sum_{i'_1 \in [|\text{Ind}_{\mathcal{W}}|]} \text{Card}([|\text{Ind}_{\mathcal{W}}|] \setminus \{u'_1, \dots, u'_{i'_1}\}, u'_{i'_1})} = -1. \quad (96)$$

Let us focus on $\sum_{i_1 \in [|\text{Ind}_{\mathcal{W}}|]} \text{Card}([|\text{Ind}_{\mathcal{W}}|] \setminus \{u_1, \dots, u_{i_1}\}, u_{i_1})$. By the definition of the function $\text{Card}(\cdot)$ in (65), we have

$$\begin{aligned} & \sum_{i_1 \in [|\text{Ind}_{\mathcal{W}}|]} \text{Card}([|\text{Ind}_{\mathcal{W}}|] \setminus \{u_1, \dots, u_{i_1}\}, u_{i_1}) \\ &= \sum_{i_1 \in [|\text{Ind}_{\mathcal{W}}|] : i_1 \neq \text{Ind}_{\mathcal{W}}^{-1}(i)} \text{Card}([|\text{Ind}_{\mathcal{W}}|] \setminus \{u_{\text{Ind}_{\mathcal{W}}^{-1}(i)}\}) \setminus \{u_1, \dots, u_{\text{Ind}_{\mathcal{W}}^{-1}(i)-1}, u_{\text{Ind}_{\mathcal{W}}^{-1}(i)+1}, \dots, u_{i_1}\}, u_{i_1}) \\ &+ |\{i_2 \in [\text{Ind}_{\mathcal{W}}^{-1}(i) - 1] : u_{\text{Ind}_{\mathcal{W}}^{-1}(i)} < u_{i_2}\}| + |\{i_3 \in [\text{Ind}_{\mathcal{W}}^{-1}(i) + 1 : |\text{Ind}_{\mathcal{W}}|] : u_{i_3} < u_{\text{Ind}_{\mathcal{W}}^{-1}(i)}\}| \end{aligned} \quad (97a)$$

$$\begin{aligned}
&= \sum_{i_1 \in [\text{Ind}_{\mathcal{W}}] : i_1 \neq \text{Ind}_{\mathcal{W}}^{-1}(i)} \text{Card}([\text{Ind}_{\mathcal{W}}] \setminus \{u_{\text{Ind}_{\mathcal{W}}^{-1}(i)}\}) \setminus \{u_1, \dots, u_{\text{Ind}_{\mathcal{W}}^{-1}(i)-1}, u_{\text{Ind}_{\mathcal{W}}^{-1}(i)+1}, \dots, u_{i_1}\}, u_{i_1}) \\
&+ (\text{Ind}_{\mathcal{W}}^{-1}(i) - 1 - |\{i_2 \in [\text{Ind}_{\mathcal{W}}^{-1}(i) - 1] : u_{i_2} < u_{\text{Ind}_{\mathcal{W}}^{-1}(i)}\}|) + |\{i_3 \in [\text{Ind}_{\mathcal{W}}^{-1}(i) + 1 : \text{Ind}_{\mathcal{W}}] : u_{i_3} < u_{\text{Ind}_{\mathcal{W}}^{-1}(i)}\}| \\
&\quad (97b)
\end{aligned}$$

$$\begin{aligned}
&= \sum_{i_1 \in [\text{Ind}_{\mathcal{W}}] : i_1 \neq \text{Ind}_{\mathcal{W}}^{-1}(i)} \text{Card}([\text{Ind}_{\mathcal{W}}] \setminus \{u_{\text{Ind}_{\mathcal{W}}^{-1}(i)}\}) \setminus \{u_1, \dots, u_{\text{Ind}_{\mathcal{W}}^{-1}(i)-1}, u_{\text{Ind}_{\mathcal{W}}^{-1}(i)+1}, \dots, u_{i_1}\}, u_{i_1}) \\
&+ (\text{Ind}_{\mathcal{W}}^{-1}(i) - 1 - |\{i_2 \in [\text{Ind}_{\mathcal{W}}^{-1}(i) - 1] : u_{i_2} < u_{\text{Ind}_{\mathcal{W}}^{-1}(i)}\}|) \\
&+ \text{Card}([\text{Ind}_{\mathcal{W}}], u_{\text{Ind}_{\mathcal{W}}^{-1}(i)}) - |\{i_2 \in [\text{Ind}_{\mathcal{W}}^{-1}(i) - 1] : u_{i_2} < u_{\text{Ind}_{\mathcal{W}}^{-1}(i)}\}|. \quad (97c)
\end{aligned}$$

Similarly, for $\sum_{i'_1 \in [\text{Ind}_{\mathcal{W}}]} \text{Card}([\text{Ind}_{\mathcal{W}}] \setminus \{u'_1, \dots, u'_{i'_1}\}, u'_{i'_1})$, from the same derivation as (97c), we have

$$\begin{aligned}
&\sum_{i'_1 \in [\text{Ind}_{\mathcal{W}}]} \text{Card}([\text{Ind}_{\mathcal{W}}] \setminus \{u'_1, \dots, u'_{i'_1}\}, u'_{i'_1}) \\
&= \sum_{i'_1 \in [\text{Ind}_{\mathcal{W}}] : i'_1 \neq \text{Ind}_{\mathcal{W}}^{-1}(i)} \text{Card}([\text{Ind}_{\mathcal{W}}] \setminus \{u'_{\text{Ind}_{\mathcal{W}}^{-1}(i)}\}) \setminus \{u'_1, \dots, u'_{\text{Ind}_{\mathcal{W}}^{-1}(i)-1}, u'_{\text{Ind}_{\mathcal{W}}^{-1}(i)+1}, \dots, u'_{i'_1}\}, u'_{i'_1}) \\
&+ (\text{Ind}_{\mathcal{W}}^{-1}(i) - 1 - |\{i'_2 \in [\text{Ind}_{\mathcal{W}}^{-1}(i) - 1] : u'_{i'_2} < u'_{\text{Ind}_{\mathcal{W}}^{-1}(i)}\}|) \\
&+ \text{Card}([\text{Ind}_{\mathcal{W}}], u'_{\text{Ind}_{\mathcal{W}}^{-1}(i)}) - |\{i'_2 \in [\text{Ind}_{\mathcal{W}}^{-1}(i) - 1] : u'_{i'_2} < u'_{\text{Ind}_{\mathcal{W}}^{-1}(i)}\}|. \quad (98)
\end{aligned}$$

In addition, from (81), it can be seen that

$$\begin{aligned}
&\sum_{i_1 \in [\text{Ind}_{\mathcal{W}}] : i_1 \neq \text{Ind}_{\mathcal{W}}^{-1}(i)} \text{Card}([\text{Ind}_{\mathcal{W}}] \setminus \{u_{\text{Ind}_{\mathcal{W}}^{-1}(i)}\}) \setminus \{u_1, \dots, u_{\text{Ind}_{\mathcal{W}}^{-1}(i)-1}, u_{\text{Ind}_{\mathcal{W}}^{-1}(i)+1}, \dots, u_{i_1}\}, u_{i_1}) \\
&= \sum_{i'_1 \in [\text{Ind}_{\mathcal{W}}] : i'_1 \neq \text{Ind}_{\mathcal{W}}^{-1}(i)} \text{Card}([\text{Ind}_{\mathcal{W}}] \setminus \{u'_{\text{Ind}_{\mathcal{W}}^{-1}(i)}\}) \setminus \{u'_1, \dots, u'_{\text{Ind}_{\mathcal{W}}^{-1}(i)-1}, u'_{\text{Ind}_{\mathcal{W}}^{-1}(i)+1}, \dots, u'_{i'_1}\}, u'_{i'_1}). \quad (99)
\end{aligned}$$

From (97c)-(99), and the fact that $(-1)^{2a} = (-1)^0$ for any integer a , we have

$$\begin{aligned}
&(-1)^{\sum_{i_1 \in [\text{Ind}_{\mathcal{W}}]} \text{Card}([\text{Ind}_{\mathcal{W}}] \setminus \{u_1, \dots, u_{i_1}\}, u_{i_1}) + \sum_{i'_1 \in [\text{Ind}_{\mathcal{W}}]} \text{Card}([\text{Ind}_{\mathcal{W}}] \setminus \{u'_1, \dots, u'_{i'_1}\}, u'_{i'_1})} \\
&= (-1)^{\text{Card}([\text{Ind}_{\mathcal{W}}], u_{\text{Ind}_{\mathcal{W}}^{-1}(i)}) + \text{Card}([\text{Ind}_{\mathcal{W}}], u'_{\text{Ind}_{\mathcal{W}}^{-1}(i)})}. \quad (100)
\end{aligned}$$

Without loss of generality, we assume $k < k'$. Recall that $\overline{\text{Ind}}_{\mathcal{W} \cup \{\mathcal{A}(k)\}}(u_{\text{Ind}_{\mathcal{W}}^{-1}(i)}) = k'$. By the definition in (73), we can see that in $\overline{\text{Ind}}_{\mathcal{W}}$, there are $\overline{\text{Ind}}_{\mathcal{W}}^{-1}(k') - 1$ elements smaller than k' . By the assumption, $k < k'$. Hence, in $\overline{\text{Ind}}_{\mathcal{W} \cup \{\mathcal{A}(k)\}}$, there are $\overline{\text{Ind}}_{\mathcal{W}}^{-1}(k') - 2$ elements smaller than k' . In other words,

$$u_{\text{Ind}_{\mathcal{W}}^{-1}(i)} = \overline{\text{Ind}}_{\mathcal{W}}^{-1}(k') - 1, \quad (101)$$

which leads to

$$\text{Card}(\{u_1, \dots, u_{|\text{Ind}_{\mathcal{W}}|}\}, u_{\text{Ind}_{\mathcal{W}}^{-1}(i)}) = \overline{\text{Ind}}_{\mathcal{W}}^{-1}(k') - 2. \quad (102)$$

Similarly, recall that $\overline{\text{Ind}}_{\mathcal{W} \cup \{\mathcal{A}(k')\}}(u'_{\text{Ind}_{\mathcal{W}}^{-1}(i)}) = k$. In $\overline{\text{Ind}}_{\mathcal{W}}$, there are $\overline{\text{Ind}}_{\mathcal{W}}^{-1}(k) - 1$ elements smaller than k . By the assumption, $k < k'$. Hence, in $\overline{\text{Ind}}_{\mathcal{W} \cup \{\mathcal{A}(k')\}}$, there are $\overline{\text{Ind}}_{\mathcal{W}}^{-1}(k) - 1$ elements smaller than k . In other words,

$$u'_{\text{Ind}_{\mathcal{W}}^{-1}(i)} = \overline{\text{Ind}}_{\mathcal{W}}^{-1}(k), \quad (103)$$

which leads to

$$\text{Card}(\{u'_1, \dots, u'_{|\text{Ind}_{\mathcal{W}}|}\}, u'_{\text{Ind}_{\mathcal{W}}^{-1}(i)}) = \overline{\text{Ind}}_{\mathcal{W}}^{-1}(k) - 1. \quad (104)$$

We take (102) and (104) into (100) to obtain,

$$\begin{aligned} & (-1)^{\sum_{i_1 \in [|\text{Ind}_{\mathcal{W}}|]} \text{Card}([|\text{Ind}_{\mathcal{W}}|] \setminus \{u_1, \dots, u_{i_1}\}, u_{i_1}) + \sum_{i'_1 \in [|\text{Ind}_{\mathcal{W}}|]} \text{Card}([|\text{Ind}_{\mathcal{W}}|] \setminus \{u'_1, \dots, u'_{i'_1}\}, u'_{i'_1})} \\ &= (-1)^{\overline{\text{Ind}}_{\mathcal{W}}^{-1}(k') - 2 + \overline{\text{Ind}}_{\mathcal{W}}^{-1}(k) - 1} \end{aligned} \quad (105a)$$

$$= (-1)^{\overline{\text{Ind}}_{\mathcal{W}}^{-1}(k') + \overline{\text{Ind}}_{\mathcal{W}}^{-1}(k) + 1}. \quad (105b)$$

Finally, we have

$$\begin{aligned} & (-1)^{-\overline{\text{Ind}}_{\mathcal{W}}^{-1}(k) - \overline{\text{Ind}}_{\mathcal{W}}^{-1}(k') + \sum_{i_1 \in [|\text{Ind}_{\mathcal{W}}|]} \text{Card}([|\text{Ind}_{\mathcal{W}}|] \setminus \{u_1, \dots, u_{i_1}\}, u_{i_1}) + \sum_{i'_1 \in [|\text{Ind}_{\mathcal{W}}|]} \text{Card}([|\text{Ind}_{\mathcal{W}}|] \setminus \{u'_1, \dots, u'_{i'_1}\}, u'_{i'_1})} \\ &= (-1)^{-\overline{\text{Ind}}_{\mathcal{W}}^{-1}(k) - \overline{\text{Ind}}_{\mathcal{W}}^{-1}(k') + \overline{\text{Ind}}_{\mathcal{W}}^{-1}(k') + \overline{\text{Ind}}_{\mathcal{W}}^{-1}(k) + 1} \end{aligned} \quad (106a)$$

$$= -1, \quad (106b)$$

which proves (96).

APPENDIX D

PROOF OF (95)

To prove (95), it is equivalent to prove

$$\begin{aligned} & (-1)^{1 + \text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i) - \overline{\text{Ind}}_{\mathcal{W}}^{-1}(\tilde{k}) + \sum_{i_1 \in [|\text{Ind}_{\mathcal{W}}| + 1]} \text{Card}([|\text{Ind}_{\mathcal{W}}| + 1] \setminus \{u_1, \dots, u_{i_1}\}, u_{i_1}) + \sum_{\tilde{i}_1 \in [|\text{Ind}_{\mathcal{W}}|]} \text{Card}([|\text{Ind}_{\mathcal{W}}|] \setminus \{\tilde{u}_1, \dots, \tilde{u}_{\tilde{i}_1}\}, \tilde{u}_{\tilde{i}_1})} \\ &= -1. \end{aligned} \quad (107)$$

Let us focus on $\sum_{i_1 \in [|\text{Ind}_{\mathcal{W}}| + 1]} \text{Card}([|\text{Ind}_{\mathcal{W}}| + 1] \setminus \{u_1, \dots, u_{i_1}\}, u_{i_1})$. By the definition of the function $\text{Card}(\cdot)$ in (65), we have

$$\sum_{i_1 \in [|\text{Ind}_{\mathcal{W}}| + 1]} \text{Card}([|\text{Ind}_{\mathcal{W}}| + 1] \setminus \{u_1, \dots, u_{i_1}\}, u_{i_1})$$

$$\begin{aligned}
&= \sum_{\substack{i_1 \in [|\text{Ind}_{\mathcal{W}}| + 1]: \\ i_1 \neq \text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)}} \text{Card}(([\text{Ind}_{\mathcal{W}}| + 1] \setminus \{u_{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)}\}) \setminus \{u_1, \dots, u_{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)-1}, u_{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)+1}, \dots, u_{i_1}\}, u_{i_1}) \\
&+ |\{i_2 \in [\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i) - 1] : u_{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)} < u_{i_2}\}| \\
&+ |\{i_3 \in [\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i) + 1 : |\text{Ind}_{\mathcal{W}}| + 1] : u_{i_3} < u_{|\text{Ind}_{\mathcal{W}}| + 1}\}| \tag{108a}
\end{aligned}$$

$$\begin{aligned}
&= \sum_{\substack{i_1 \in [|\text{Ind}_{\mathcal{W}}| + 1]: \\ i_1 \neq \text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)}} \text{Card}(([\text{Ind}_{\mathcal{W}}| + 1] \setminus \{u_{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)}\}) \setminus \{u_1, \dots, u_{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)-1}, u_{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)+1}, \dots, u_{i_1}\}, u_{i_1}) \\
&+ \text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i) - 1 - |\{i_2 \in [\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i) - 1] : u_{i_2} < u_{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)}\}| \\
&+ \text{Card}([\text{Ind}_{\mathcal{W}}| + 1], u_{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)}) - |\{i_2 \in [\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i) - 1] : u_{i_2} < u_{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)}\}| \tag{108b}
\end{aligned}$$

From the construction of $\tilde{\mathbf{u}}$ in (94a), we have

$$\begin{aligned}
&\sum_{\substack{i_1 \in [|\text{Ind}_{\mathcal{W}}| + 1]: \\ i_1 \neq \text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)}} \text{Card}(([\text{Ind}_{\mathcal{W}}| + 1] \setminus \{u_{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)}\}) \setminus \{u_1, \dots, u_{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)-1}, u_{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)+1}, \dots, u_{i_1}\}, u_{i_1}) \\
&= \sum_{\tilde{i}_1 \in [|\text{Ind}_{\mathcal{W}}|]} \text{Card}([\text{Ind}_{\mathcal{W}}|] \setminus \{\tilde{u}_1, \dots, \tilde{u}_{\tilde{i}_1}\}, \tilde{u}_{\tilde{i}_1}). \tag{109}
\end{aligned}$$

From (108b) and (109), and the fact that $(-1)^{2a} = (-1)^0$ for any integer a , we have

$$\begin{aligned}
&(-1)^{1 + \text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i) - \overline{\text{Ind}}_{\mathcal{W}}^{-1}(\tilde{k}) + \sum_{i_1 \in [|\text{Ind}_{\mathcal{W}}| + 1]} \text{Card}([\text{Ind}_{\mathcal{W}}| + 1] \setminus \{u_1, \dots, u_{i_1}\}, u_{i_1}) + \sum_{\tilde{i}_1 \in [|\text{Ind}_{\mathcal{W}}|]} \text{Card}([\text{Ind}_{\mathcal{W}}|] \setminus \{\tilde{u}_1, \dots, \tilde{u}_{\tilde{i}_1}\}, \tilde{u}_{\tilde{i}_1})} \\
&= (-1)^{-\overline{\text{Ind}}_{\mathcal{W}}^{-1}(\tilde{k}) + \text{Card}([\text{Ind}_{\mathcal{W}}| + 1], u_{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)})} \tag{110a}
\end{aligned}$$

$$= -1, \tag{110b}$$

where (110b) comes from that $\tilde{k} := \overline{\text{Ind}}_{\mathcal{W}}(u_{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)})$, and thus $u_{\text{Ind}_{\mathcal{W} \cup \{\mathcal{L}(i)\}}^{-1}(i)} = \overline{\text{Ind}}_{\mathcal{W}}^{-1}(\tilde{k})$.

REFERENCES

- [1] M. A. Maddah-Ali and U. Niesen, "Fundamental limits of caching," *IEEE Trans. Infor. Theory*, vol. 60, no. 5, pp. 2856–2867, May 2014.
- [2] K. Wan, D. Tuninetti, and P. Piantanida, "On the optimality of uncoded cache placement," in *IEEE Infor. Theory Workshop*, Sep. 2016.
- [3] Q. Yu, M. A. Maddah-Ali, and S. Avestimehr, "The exact rate-memory tradeoff for caching with uncoded prefetching," *IEEE Trans. Infor. Theory*, vol. 64, pp. 1281 – 1296, Feb. 2018.
- [4] Q. Yu, M. A. Maddah-Ali, and A. S. Avestimehr, "Characterizing the rate-memory tradeoff in cache networks within a factor of 2," *IEEE Trans. Infor. Theory*, vol. 65, no. 1, pp. 647–663, Jan. 2019.

- [5] M. Ji, G. Caire, and A. Molisch, "Fundamental limits of caching in wireless d2d networks," *IEEE Trans. Inf. Theory*, vol. 62, no. 1, pp. 849–869, 2016.
- [6] K. Wan and G. Caire, "On coded caching with private demands," *arXiv:1908.10821*, Aug. 2019.
- [7] K. Wan, H. Sun, M. Ji, D. Tuninetti, and G. Caire, "Device-to-device private caching with trusted server," *arXiv:1909.12748*, Sep. 2019.
- [8] S. Li, M. A. Maddah-Ali, Q. Yu, and A. S. Avestimehr, "A fundamental tradeoff between computation and communication in distributed computing," *IEEE Trans. Inf. Theory*, vol. 64, no. 1, pp. 109–128, Jan. 2018.
- [9] M. A. Attia and R. Tandon, "Near optimal coded data shuffling for distributed learning," vol. 65, no. 11, pp. 7325–7349, Nov. 2019.
- [10] A. Elmahdy and S. Mohajer, "On the fundamental limits of coded data shuffling for distributed learning systems," *arXiv:1807.04255*, a preliminary version is in *IEEE Int. Symp. Inf. Theory 2018*, Jul. 2018.
- [11] K. Wan, D. Tuninetti, M. Ji, G. Caire, and P. Piantanida, "Fundamental limits of decentralized data shuffling," *arXiv:1807.00056*, Jun. 2018.
- [12] M. Ji, A. Tulino, J. Llorca, and G. Caire, "Caching-aided coded multicasting with multiple random requests," in *Proc. IEEE Inf. Theory Workshop (ITW)*, May. 2015.
- [13] A. Sengupta and R. Tandon, "Improved approximation of storage-rate tradeoff for caching with multiple demands," *IEEE Trans. Commun.*, vol. 65, no. 5, pp. 1940–1955, May. 2017.
- [14] J. So, B. Guler, A. S. Avestimehr, and P. Mohassel, "Codedprivateml: A fast and privacy-preserving framework for distributed machine learning," *arXiv:1902.00641*, Feb. 2019.
- [15] M. Aliasgari, O. Simeone, and J. Kliewer, "Private and secure distributed matrix multiplication with flexible communication load," *arXiv:1909.00407*, Sep. 2019.
- [16] H. Sun and S. A. Jafar, "The capacity of private computation," *IEEE Trans. Inf. Theory*, vol. 65, no. 5, pp. 3880–3897, Jun. 2019.
- [17] C. Yapar, K. Wan, R. F. Schaefer, and G. Caire, "On the optimality of d2d coded caching with uncoded cache placement and one-shot delivery," in *IEEE Int. Symp. Inf. Theory*, Jul. 2019.