

Fast Complete Algorithm for Multiplayer Nash Equilibrium

Sam Ganzfried
Ganzfried Research
sam@ganzfriedresearch.com

Abstract

We describe a new complete algorithm for computing Nash equilibrium in multiplayer general-sum games, based on a quadratically-constrained feasibility program formulation. We demonstrate that the algorithm runs significantly faster than the prior fastest complete algorithm on several game classes previously studied and that its runtimes even outperform the best incomplete algorithms.

1 Introduction

Nash equilibrium is the central solution concept in game theory. While a Nash equilibrium can be computed in polynomial time for two-player zero-sum games, it is PPAD-hard for two-player general-sum and multiplayer games and widely believed that no efficient algorithms exist [7, 8, 9]. Furthermore, even if we were able to compute an equilibrium for these game classes, it would have no performance guarantee. In a two-player zero-sum game, every Nash equilibrium guarantees at least the value of the game in expectation in the worst case. Therefore, if players alternate roles, a Nash equilibrium would guarantee a win or tie in expectation regardless of the strategy used by the opponent. However, for non-zero-sum and multiplayer games, an equilibrium would have no performance guarantee. There can be multiple equilibria with different values, and if the opponents play strategies from a different equilibrium than ours then the resulting strategies may not be in equilibrium.

Despite these computational and conceptual challenges, we must still create agents with strong strategies for these settings, and Nash equilibrium is a compelling starting point. It was shown that an exact Nash equilibrium strategy defeated a variety of agents submitted for a class project in 3-player Kuhn poker [11]. Recently an agent was created for 6-player no-limit Texas hold 'em that defeated strong human players by attempting to approximate Nash equilibrium strategies [6]. The core equilibrium-finding technique used by this agent was based on the counterfactual regret minimization algorithm, an iterative self-play procedure [23]. It has been demonstrated that counterfactual regret minimization does in fact converge to an ϵ -Nash equilibrium (a strategy profile in which no player can gain more than ϵ by deviating) for small ϵ in three-player Kuhn poker, while it does not converge to equilibrium in the larger game of three-player Leduc hold 'em [1]. These results show that Nash equilibrium strategies (or their approximations) can be successful in practice despite the fact that they do not have a performance guarantee.

Several algorithms have been developed for computing Nash equilibrium in multiplayer games; however, many of them are incomplete, slow, and/or produce solutions with poor approximation quality (i.e., high ϵ). An algorithm is *complete* if it always finds a solution when one exists (which is the case for Nash equilibrium because one is guaranteed to exist in all finite games [18]). We present a new algorithm that is complete and runs significantly faster than prior complete algorithms, and even runs faster than the best incomplete algorithms. Our algorithm is based on a novel quadratically-constrained mixed-integer program formulation that utilizes a technique from the newest Gurobi release [14]. We run experiments on uniform random games with a variety of players and strategy sizes, as well as several games produced from the GAMUT generator [19]. We compare our algorithm against the best prior algorithms, which includes several complete methods as well as faster incomplete methods available on the GAMBIT software suite [17].

2 Notation

A strategic-form game consists of a finite set of players $N = \{1, \dots, n\}$, a finite set of pure strategies S_i for each player $i \in N$, and a real-valued utility for each player for each strategy vector (aka *strategy profile*), $u_i : \times_i S_i \rightarrow \mathbb{R}$. We will assume that the sets S_i are disjoint, and for simplicity assume that all S_i have the same cardinality. For $s_j \in S_i$ define the *player* function to be $P(s_j) = i$ (which is well-defined under the assumption that the S_i are disjoint). Suppose that $s_{j_k} \in S_{i_k}$ for $k = 1 \dots n$, and suppose that the $i_k \in N$ are all distinct. Then for $w \in N$ define $\hat{u}_w(s_{j_1}, \dots, s_{j_n}) = u_w(s_{m_1}, \dots, s_{m_n})$, where m_q equals the j_k such that $P(j_k) = q$ (and therefore that $s_{m_q} \in S_q$). That is, in the event that the s_{j_k} are not in order of increasing value of the player $P(s_{j_k})$, the \hat{u} function will compute the utility assuming that the vector of strategies is listed in the order of increasing players so that u can be properly applied. For example, suppose that $s_1 \in S_1, s_2 \in S_2, s_3 \in S_3$. Then $\hat{u}_w(s_2, s_3, s_1) = u_w(s_1, s_2, s_3)$, for $w \in N$. This notation will be useful in order to provide more concise representations of our optimization formulations.

A *mixed strategy* σ_i for player i is a probability distribution over pure strategies, where $\sigma_i(s_{i'})$ is the probability that player i plays pure strategy $s_{i'} \in S_i$ under σ_i . Let Σ_i denote the full set of mixed strategies for player i . A strategy profile $\sigma^* = (\sigma_1^*, \dots, \sigma_n^*)$ is a *Nash equilibrium* if $u_i(\sigma_i^*, \sigma_{-i}^*) \geq u_i(\sigma_i, \sigma_{-i}^*)$ for all $\sigma_i \in \Sigma_i$ for all $i \in N$, where σ_{-i}^* denotes the vector of the components of strategy σ^* for all players excluding player i . For a given candidate strategy profile σ^* , define $\epsilon = \epsilon(\sigma^*) = \max_i \max_{\sigma_i \in \Sigma_i} [u_i(\sigma_i, \sigma_{-i}^*) - u_i(\sigma_i^*, \sigma_{-i}^*)]$.

3 Algorithm

We first describe a linear mixed-integer feasibility program formulation for computing Nash equilibrium in two-player general-sum games [21]. That work presented four different formulations each using a different objective function and set of constraints, and demonstrated that the first one significantly outperformed the other three. The first formulation was a feasibility program with no objective function, in which the set of Nash equilibria correspond exactly to feasible solutions. We use this formulation as a starting point for our new multiplayer formulations.

3.1 Linear mixed-integer feasibility formulation for two-player Nash equilibrium

We quote from the original description of the program formulation for two-player Nash equilibrium, and present the formulation below:

In our first formulation, the feasible solutions are exactly the equilibria of the game. For every pure strategy s_i , there is binary variable b_{s_i} . If this variable is set to 1, the probability placed on the strategy must be 0. If it is set to 0, the strategy is allowed to be in the support, but the regret of the strategy must be 0. The formulation has the following variables other than the b_{s_i} . For each player, there is a variable u_i indicating the highest possible expected utility that that player can obtain given the other player's mixed strategy. For every pure strategy s_i , there is a variable p_{s_i} indicating the probability placed on that strategy, a variable u_{s_i} indicating the expected utility of playing that strategy (given the other player's mixed strategy), and a variable r_{s_i} indicating the regret of playing s_i . The constant U_i indicates the maximum difference between two utilities in the game for player i : $U_i = \max_{s_i^h, s_i^l \in S_i, s_{1-i}^h, s_{1-i}^l \in S_{1-i}} [u_i(s_i^h, s_{1-i}^h) - u_i(s_i^l, s_{1-i}^l)]$. The formulation follows below [21].

Find $p_{s_i}, u_i, u_{s_i}, r_{s_i}, b_{s_i}$ such that:

$$\sum_{s_i \in S_i} p_{s_i} = 1 \text{ for all } i \quad (1)$$

$$u_{s_i} = \sum_{s_{1-i} \in S_{1-i}} p_{s_{1-i}} u_i(s_i, s_{1-i}) \text{ for all } i, s_i \in S_i \quad (2)$$

$$u_i \geq u_{s_i} \text{ for all } i, s_i \in S_i \quad (3)$$

$$r_{s_i} = u_i - u_{s_i} \text{ for all } i, s_i \in S_i \quad (4)$$

$$p_{s_i} \leq 1 - b_{s_i} \text{ for all } i, s_i \in S_i \quad (5)$$

$$r_{s_i} \leq U_i b_{s_i} \text{ for all } i, s_i \in S_i \quad (6)$$

$$p_{s_i} \geq 0 \text{ for all } i, s_i \in S_i \quad (7)$$

$$u_i \geq 0 \text{ for all } i \quad (8)$$

$$u_{s_i} \geq 0 \text{ for all } i, s_i \in S_i \quad (9)$$

$$r_{s_i} \geq 0 \text{ for all } i, s_i \in S_i \quad (10)$$

$$b_{s_i} \text{ binary in } \{0, 1\} \text{ for all } i, s_i \in S_i \quad (11)$$

The first four constraints ensure that the p_{s_i} values constitute a valid probability distribution and define the regret of a strategy. Constraint 5 ensures that b_{s_i} can be set to 1 only when no probability is placed on s_i . On the other hand, Constraint 6 ensures that the regret of a strategy equals 0, unless $b_{s_i} = 1$, in which case the constraint is vacuous because the regret can never exceed U_i . (Technically, Constraint 3 is redundant as it follows from Constraints 4 and 10.) [21]

For clarity, we will rewrite the system with the redundant Constraint 3 removed, as our extensions will be based on this formulation.

Find $p_{s_i}, u_i, u_{s_i}, r_{s_i}, b_{s_i}$ such that:

$$\sum_{s_i \in S_i} p_{s_i} = 1 \text{ for all } i$$

$$u_{s_i} = \sum_{s_{1-i} \in S_{1-i}} p_{s_{1-i}} u_i(s_i, s_{1-i}) \text{ for all } i, s_i \in S_i$$

$$r_{s_i} = u_i - u_{s_i} \text{ for all } i, s_i \in S_i$$

$$p_{s_i} \leq 1 - b_{s_i} \text{ for all } i, s_i \in S_i$$

$$r_{s_i} \leq U_i b_{s_i} \text{ for all } i, s_i \in S_i$$

$$p_{s_i} \geq 0 \text{ for all } i, s_i \in S_i$$

$$u_i \geq 0 \text{ for all } i$$

$$u_{s_i} \geq 0 \text{ for all } i, s_i \in S_i$$

$$r_{s_i} \geq 0 \text{ for all } i, s_i \in S_i$$

$$b_{s_i} \text{ binary in } \{0, 1\} \text{ for all } i, s_i \in S_i$$

3.2 New formulation for three-player Nash equilibrium

We now describe an extension of the previous two-player formulation to three players. To do this, we introduce new variables, p_{s_i, s_j} , which denote the product of the variables p_{s_i} and p_{s_j} . Note that these new product constraints are now quadratic (while all other constraints remain linear).

Find $p_{s_i}, u_i, u_{s_i}, r_{s_i}, b_{s_i}, p_{s_i, s_j}$ such that:

$$\begin{aligned}
\sum_{s_i \in S_i} p_{s_i} &= 1 \text{ for all } i \\
u_{s_i} &= \sum_{s_j \in S_2} \sum_{s_k \in S_3} p_{s_j, s_k} u_1(s_i, s_j, s_k) \text{ for all } s_i \in S_1 \\
u_{s_j} &= \sum_{s_i \in S_1} \sum_{s_k \in S_3} p_{s_i, s_k} u_2(s_i, s_j, s_k) \text{ for all } s_j \in S_2 \\
u_{s_k} &= \sum_{s_i \in S_1} \sum_{s_j \in S_2} p_{s_i, s_j} u_3(s_i, s_j, s_k) \text{ for all } s_k \in S_3 \\
p_{s_i, s_j} &= p_{s_i} \cdot p_{s_j} \text{ for all } i, j, s_i \in S_1, s_j \in S_2 \\
p_{s_i, s_j} &= p_{s_i} \cdot p_{s_j} \text{ for all } i, j, s_i \in S_1, s_j \in S_3 \\
p_{s_i, s_j} &= p_{s_i} \cdot p_{s_j} \text{ for all } i, j, s_i \in S_2, s_j \in S_3 \\
r_{s_i} &= u_i - u_{s_i} \text{ for all } i, s_i \in S_i \\
p_{s_i} &\leq 1 - b_{s_i} \text{ for all } i, s_i \in S_i \\
r_{s_i} &\leq U_i b_{s_i} \text{ for all } i, s_i \in S_i \\
p_{s_i} &\geq 0 \text{ for all } i, s_i \in S_i \\
u_i &\geq 0 \text{ for all } i \\
u_{s_i} &\geq 0 \text{ for all } i, s_i \in S_i \\
r_{s_i} &\geq 0 \text{ for all } i, s_i \in S_i \\
b_{s_i} &\text{ binary in } \{0, 1\} \text{ for all } i, s_i \in S_i
\end{aligned}$$

We can simplify the presentation by condensing the constraints for u_{s_i} and for the product variables p_{s_i, s_j} , using the notation for \hat{u} defined in Section 2.

Find $p_{s_i}, u_i, u_{s_i}, r_{s_i}, b_{s_i}, p_{s_i, s_j}$ such that:

$$\begin{aligned}
\sum_{s_i \in S_i} p_{s_i} &= 1 \text{ for all } i \\
u_{s_i} &= \sum_{s_j \in S_J} \sum_{s_k \in S_K} p_{s_j, s_k} \hat{u}_{P(s_i)}(s_i, s_j, s_k) \text{ for all } I, J \neq I, K \neq I, J < K, s_i \in S_I \\
p_{s_i, s_j} &= p_{s_i} \cdot p_{s_j} \text{ for all } I, J \in N, I < J, s_i \in S_I, s_j \in S_J \\
r_{s_i} &= u_i - u_{s_i} \text{ for all } i, s_i \in S_i \\
p_{s_i} &\leq 1 - b_{s_i} \text{ for all } i, s_i \in S_i \\
r_{s_i} &\leq U_i b_{s_i} \text{ for all } i, s_i \in S_i \\
p_{s_i} &\geq 0 \text{ for all } i, s_i \in S_i \\
u_i &\geq 0 \text{ for all } i \\
u_{s_i} &\geq 0 \text{ for all } i, s_i \in S_i \\
r_{s_i} &\geq 0 \text{ for all } i, s_i \in S_i \\
b_{s_i} &\text{ binary in } \{0, 1\} \text{ for all } i, s_i \in S_i
\end{aligned}$$

3.3 New formulation for four-player Nash equilibrium

We further extend our 3-player formulation to 4 players by introducing new variables p_{s_i, s_j, s_k} . We still retain the p_{s_i, s_j} variables as before, and include additional constraints of the form $p_{s_i, s_j, s_k} = p_{s_i} \cdot p_{s_j, s_k}$. Thus,

despite the expected utilities being cubic in the original variables p_{s_i} , we are able to obtain a formulation that only has linear and quadratic constraints.

Find $p_{s_i}, u_i, u_{s_i}, r_{s_i}, b_{s_i}, p_{s_i, s_j}, p_{s_i, s_j, s_k}$ such that:

$$\begin{aligned}
& \sum_{s_i \in S_i} p_{s_i} = 1 \text{ for all } i \\
& u_{s_i} = \sum_{s_j \in S_2, s_k \in S_3, s_m \in S_4} p_{s_j, s_k, s_m} u_1(s_i, s_j, s_k, s_m) \text{ for all } s_i \in S_1 \\
& u_{s_j} = \sum_{s_i \in S_1, s_k \in S_3, s_m \in S_4} p_{s_i, s_k, s_m} u_2(s_i, s_j, s_k, s_m) \text{ for all } s_j \in S_2 \\
& u_{s_k} = \sum_{s_i \in S_1, s_j \in S_2, s_m \in S_4} p_{s_i, s_j, s_m} u_3(s_i, s_j, s_k, s_m) \text{ for all } s_k \in S_3 \\
& u_{s_m} = \sum_{s_i \in S_1, s_j \in S_2, s_k \in S_3} p_{s_i, s_j, s_k} u_4(s_i, s_j, s_k, s_m) \text{ for all } s_m \in S_4 \\
& p_{s_i, s_j} = p_{s_i} \cdot p_{s_j} \text{ for all } s_i \in S_1, s_j \in S_2 \\
& p_{s_i, s_j} = p_{s_i} \cdot p_{s_j} \text{ for all } s_i \in S_1, s_j \in S_3 \\
& p_{s_i, s_j} = p_{s_i} \cdot p_{s_j} \text{ for all } s_i \in S_1, s_j \in S_4 \\
& p_{s_i, s_j} = p_{s_i} \cdot p_{s_j} \text{ for all } s_i \in S_2, s_j \in S_3 \\
& p_{s_i, s_j} = p_{s_i} \cdot p_{s_j} \text{ for all } s_i \in S_2, s_j \in S_4 \\
& p_{s_i, s_j} = p_{s_i} \cdot p_{s_j} \text{ for all } s_i \in S_3, s_j \in S_4 \\
& p_{s_i, s_j, s_k} = p_{s_i} \cdot p_{s_j, s_k} \text{ for all } s_i \in S_1, s_j \in S_2, s_k \in S_3 \\
& p_{s_i, s_j, s_k} = p_{s_i} \cdot p_{s_j, s_k} \text{ for all } s_i \in S_1, s_j \in S_2, s_k \in S_4 \\
& p_{s_i, s_j, s_k} = p_{s_i} \cdot p_{s_j, s_k} \text{ for all } s_i \in S_1, s_j \in S_3, s_k \in S_4 \\
& p_{s_i, s_j, s_k} = p_{s_i} \cdot p_{s_j, s_k} \text{ for all } s_i \in S_2, s_j \in S_3, s_k \in S_4 \\
& r_{s_i} = u_i - u_{s_i} \text{ for all } i, s_i \in S_i \\
& p_{s_i} \leq 1 - b_{s_i} \text{ for all } i, s_i \in S_i \\
& r_{s_i} \leq U_i b_{s_i} \text{ for all } i, s_i \in S_i \\
& p_{s_i} \geq 0 \text{ for all } i, s_i \in S_i \\
& u_i \geq 0 \text{ for all } i \\
& u_{s_i} \geq 0 \text{ for all } i, s_i \in S_i \\
& r_{s_i} \geq 0 \text{ for all } i, s_i \in S_i \\
& b_{s_i} \text{ binary in } \{0, 1\} \text{ for all } i, s_i \in S_i
\end{aligned}$$

As for the 3-player version we can simplify the presentation by condensing constraints and utilizing \hat{u} .

Find $p_{s_i}, u_i, u_{s_i}, r_{s_i}, b_{s_i}, p_{s_i, s_j}, p_{s_i, s_j, s_k}$ such that:

$$\begin{aligned}
& \sum_{s_i \in S_i} p_{s_i} = 1 \text{ for all } i \\
& u_{s_i} = \sum_{s_j \in S_J} \sum_{s_k \in S_K} \sum_{s_m \in S_M} p_{s_j, s_k, s_m} \hat{u}_{P(s_i)}(s_i, s_j, s_k, s_m) \text{ for all } I, J \neq I, K \neq I, M \neq I, J < K < M, s_i \in S_I \\
& p_{s_i, s_j} = p_{s_i} \cdot p_{s_j} \text{ for all } I, J \in N, I < J, s_i \in S_I, s_j \in S_J \\
& p_{s_i, s_j, s_k} = p_{s_i} \cdot p_{s_j, s_k} \text{ for all } I, J, K \in N, I < J < K, s_i \in S_I, s_j \in S_J, s_k \in S_K \\
& r_{s_i} = u_i - u_{s_i} \text{ for all } i, s_i \in S_i \\
& p_{s_i} \leq 1 - b_{s_i} \text{ for all } i, s_i \in S_i \\
& r_{s_i} \leq U_i b_{s_i} \text{ for all } i, s_i \in S_i \\
& p_{s_i} \geq 0 \text{ for all } i, s_i \in S_i \\
& u_i \geq 0 \text{ for all } i \\
& u_{s_i} \geq 0 \text{ for all } i, s_i \in S_i \\
& r_{s_i} \geq 0 \text{ for all } i, s_i \in S_i \\
& b_{s_i} \text{ binary in } \{0, 1\} \text{ for all } i, s_i \in S_i
\end{aligned}$$

3.4 Five-player Nash equilibrium

We can create a similar extension for 5 players that again only uses linear and quadratic constraints.

Find $p_{s_i}, u_i, u_{s_i}, r_{s_i}, b_{s_i}, p_{s_i, s_j}, p_{s_i, s_j, s_k}, p_{s_i, s_j, s_k, s_m}$ such that:

$$\begin{aligned}
& \sum_{s_i \in S_i} p_{s_i} = 1 \text{ for all } i \\
& u_{s_i} = \sum_{s_j \in S_J} \sum_{s_k \in S_K} \sum_{s_m \in S_M} \sum_{s_o \in S_O} p_{s_j, s_k, s_m, s_o} \hat{u}_{P(s_i)}(s_i, s_j, s_k, s_m, s_o) \forall I, \{J, K, M, O\} \neq I, J < K < M < O, s_i \in S_I \\
& p_{s_i, s_j} = p_{s_i} \cdot p_{s_j} \text{ for all } I, J \in N, I < J, s_i \in S_I, s_j \in S_J \\
& p_{s_i, s_j, s_k} = p_{s_i} \cdot p_{s_j, s_k} \text{ for all } I, J, K \in N, I < J < K, s_i \in S_I, s_j \in S_J, s_k \in S_K \\
& p_{s_i, s_j, s_k, s_m} = p_{s_i} \cdot p_{s_j, s_k, s_m} \text{ for all } I, J, K, M \in N, I < J < K < M, s_i \in S_I, s_j \in S_J, s_k \in S_K, s_m \in S_M \\
& r_{s_i} = u_i - u_{s_i} \text{ for all } i, s_i \in S_i \\
& p_{s_i} \leq 1 - b_{s_i} \text{ for all } i, s_i \in S_i \\
& r_{s_i} \leq U_i b_{s_i} \text{ for all } i, s_i \in S_i \\
& p_{s_i} \geq 0 \text{ for all } i, s_i \in S_i \\
& u_i \geq 0 \text{ for all } i \\
& u_{s_i} \geq 0 \text{ for all } i, s_i \in S_i \\
& r_{s_i} \geq 0 \text{ for all } i, s_i \in S_i \\
& b_{s_i} \text{ binary in } \{0, 1\} \text{ for all } i, s_i \in S_i
\end{aligned}$$

3.5 New formulation for n-player Nash equilibrium

One can easily see how our formulation can be generalized to one for n players that has only linear and quadratic constraints. There will be $m^k \binom{n}{k}$ of the $p_{s_{i_1}, \dots, s_{i_k}}$ terms of length k for each $1 \leq k \leq n-1$, where $m = |S_i|$. So the total number of the p terms will be

$$\sum_{k=1}^{n-1} m^k \binom{n}{k} \leq \sum_{k=1}^{n-1} m^{n-1} \binom{n}{k} = m^{n-1} \sum_{k=1}^{n-1} \binom{n}{k} = m^{n-1} (2^n - 2) = O((2m)^{n-1}).$$

3.6 Computation of Nash equilibrium from new quadratic program formulation

While we have been able to formulate the problem of computing a Nash equilibrium for $n \geq 3$ players as a quadratically-constrained program (QCP), unfortunately the constraint matrix is not positive semidefinite making the overall program non-convex and more challenging to solve. The best commercial solvers could previously solve convex QCPs but not non-convex QCPs, and the best approach was to approximate products of variables by using piecewise linear approximations [4]; however, this approach introduces a large number of new variables and constraints and a layer of approximation error, leading to large runtimes. Recently Gurobi has released an approach that is able to solve non-convex programs with quadratic objective and/or constraints [14]. The solver allows for both continuous and integral variables, and so can handle mixed-integer quadratically-constrained programs (MIQCPs), which is what we are interested in. The new method addresses non-convex bilinear constraints using an analogue of the simplex algorithm with McCormick envelopes for constructing relaxations with new approaches for cutting planes and spatial branching.

4 Experiments

For our first set of experiments, we generated games with payoffs uniformly random in $[0,1]$ for a variety of number of players n and number of pure strategies m . We used the same parameter values as those used for previous experiments for complete algorithms [3]. For each set of parameter values (n, m) , we generated 1,000 random games as the prior work had done (with the exception of the largest game $n = 5, m = 3$ for which we generated 100 games). We set a time limit of 900 seconds for the random game experiments as the prior work had done.

For all experiments with our algorithm we used Gurobi’s non-convex MIQCP solver, with feasibility tolerance parameter set to 0.0001. We used an Intel Core i7-8550U at 1.80 GHz with 16 GB of RAM under 64-bit Windows 10 (8 threads). Prior experiments had been done with similar hardware: Intel Core i7-6500U at 2.50 GHz with 16 GB of RAM under 64-bit Windows 7 [3].

The results from experiments with our MIQCP algorithm on random games are shown in Table 1. For all games other than the largest class ($n = 5, m = 3$) the algorithm had very fast runtimes (in most cases averaging a fraction of a second), with zero runs over the time limit. For the largest class the algorithm hit the time limit in 58% of instances. Analogous results for the best prior complete algorithms are shown in Table 2. Other than for the $n = 5, m = 3$ games, our algorithm outperformed both other algorithms by orders of magnitude in runtime.

n	m	Avg. time(s)	Median time(s)	OverTime%
3	2	0.00707	0.0	0
3	3	0.02342	0.02901	0
3	5	0.85763	0.26544	0
4	2	0.02598	0.03124	0
4	3	1.35334	0.40505	0
5	2	0.11873	0.09373	0
5	3	607.68524	900.0	58

Table 1: Results of new MIQCP algorithm for random games.

The Exclusion Method algorithm is a complete tree-search-based method that has the best upper bound with respect to the number of players n [3]. The algorithm divides the search space into smaller regions and examines whether an equilibrium can exist in the region. The k -Uniform Search algorithm is based on an improvement to a prior exhaustive complete method [2] where a search is performed over the space of k -

		Exclusion Method			k -Uniform Search		
n	m	Avg. time(s)	Median time(s)	OverTime%	k	Avg. time(s)	OverTime%
3	2	0.04	0.02	0	2/180	49	1
3	3	26	1.2	1	3/18	191	29
3	5	900	900	100	5	94	33
4	2	99	0.48	8	2/40	23	15
4	3	352	87	30	3/8	85	33
5	2	125	2.7	10	2/8	1.0	30
5	3	520	589	46	3	7.9	36

Table 2: Results of prior complete algorithms for random games [3].

uniform strategies for incrementally increasing k . (A k -uniform strategy is a strategy where all probabilities are integer multiples of $\frac{1}{k}$.) This approach was used as a benchmark in prior work [3].

We next experimented on several games produced from the GAMUT generator [19]. We used the same games and parameter settings as used in prior work [3]. In particular, we used the variants with 3 players and 3 actions per player. For the congestion game class we used 2 for the number of facilities parameter, and for the covariant game we used $r = -0.5$. All other parameters were generated randomly (as the prior experiments had done). We generated 1,000 games from each class using these distributions. We did not use any time limit for these experiments.

Results for our new MIQCP algorithm over the GAMUT games are shown in Table 3. We noticed that several of the games generated had coefficients with very large absolute magnitude, which can lead to numerical stability issues for optimization algorithms. So we normalized all payoffs to be in $[0,1]$ (by subtracting the smallest payoff from all the payoffs and then dividing all payoffs by the difference between the max and min payoff). Note that linear transformations of the payoffs exactly preserve Nash equilibria, so this normalization would theoretically have no effect on the solutions (aside from numerical stability issues). For one of the instances of the Bertrand oligopoly games we noticed that the game generated had NaN values for some payoffs which led to an error when performing normalization, so we did not perform the normalization for that class. We can see that our algorithm ran very quickly for all game classes. We note that in addition to the Bertrand oligopoly instance with NaN payoffs, there was also one instance from the Random graphical game class where our algorithm incorrectly output that the program was infeasible due to numerical instability. Despite the completeness of the algorithm, there can always be certain specific games constructed that can lead to numerical issues for optimization solvers that deal with floating-point arithmetic with certain feasibility tolerances. However, our algorithm correctly solved all instances with the exception of these two.

Analogous results for the prior best complete algorithms for these same game classes are in Table 4. We can see again that our algorithm typically runs orders of magnitude faster than the others. Note that for these results the NotSolved% column refers to the percentage of runs where the ϵ of the computed strategies exceeded 0.001 (this was the criterion from prior work [3]).

Table 5 shows results for these same game classes using the best algorithms from the GAMBIT software suite [17]. The numbers are the average computation times for the algorithms (in seconds) and the parentheses show the percentage of instances that were not solved (code got stuck, empty output, or accuracy not within the given $\epsilon = 0.001$). All of these methods are incomplete, and in many cases the NotSolved% was quite large. The runtimes of our algorithm are still about one order of magnitude better than these methods, while also correctly solving all instances (except for two exceptions noted above).

The algorithms are the homotopy method [12] (gnm), its modification using iterated polymatrix approximation [13] (ipa), an algorithm based on solving a polynomial system of equations (enumpoly), the

Game class	Avg. time(s)	# NotSolved
Bertrand oligopoly	0.00119	1
Bidirectional LEG	0.00600	0
Collaboration	0.01133	0
Congestion	0.00613	0
Covariant	0.02678	0
Polymatrix	0.00976	0
Random graphical	0.01737	1
Random LEG	0.00640	0
Uniform LEG	0.00550	0

Table 3: Results of new MIQCP algorithm for GAMUT games.

Game class	Exclusion Method		k -Uniform Search	
	Avg. time(s)	NotSolved%	Avg. time(s)	NotSolved%
Bertrand oligopoly	13.7	0	0.01	0
Bidirectional LEG	159	0	0.013	0
Collaboration	2.8	0	0.0009	0
Congestion	29	0	0.027	0
Covariant	95	0	80	16
Polymatrix	172	0	27.2	7
Random graphical	35000	0	0.05	0
Random LEG	880	0	0.02	0
Uniform LEG	793	0	0.02	0

Table 4: Results of prior complete algorithms for GAMUT games [3].

Game class	gnm	ipa	enumpoly	simpdiv	liap	logit
Bertrand oligopoly	0.05 (30)	0.05 (75)	0.04 (50)	0.05	0.24 (99)	0.06
Bidirectional LEG	0.09 (0.3)	0.05 (58)	0.84 (1)	0.06 (0.1)	0.24 (99)	0.06 (0.1)
Collaboration	0.24 (0.1)	0.04	3.3 (50)	0.05	0.34 (99)	0.06 (0.3)
Congestion	0.05 (0.2)	0.05 (85)	0.05 (0.6)	0.05 (0.1)	0.21 (100)	0.05
Covariant	0.13 (3)	0.05 (94)	36	0.67 (2.8)	0.31 (100)	0.05 (1)
Polymatrix	0.06 (1)	0.04 (79)	0.04 (50)	0.07 (0.3)	0.3 (92)	0.05 (0.4)
Random graphical	0.08 (3)	0.04 (96)	6.3 (6)	0.17 (3)	0.31 (99)	0.06 (0.3)
Random LEG	0.05 (1)	0.04 (59)	8.1 (2)	0.05 (0.6)	0.24 (99)	0.06
Uniform LEG	0.07 (0.4)	0.05 (55)	0.04 (17)	0.05	0.23 (99)	0.06

Table 5: Computation times in seconds for the GAMBIT algorithms and percentage of instances not solved [3].

simplicial subdivision method [15] (simpdiv), a function minimization approach (liap), and the quantal response method [16, 22] (logit).¹

Our final comparison is with two recently popular algorithms, counterfactual regret minimization [23] and fictitious play [5, 20]. These are iterative self-play procedures that have been proven to converge to Nash

¹These experiments were performed using GAMBIT version 15.0 (except 16.0 for simpdiv as it had a bug in 15.0; only simpdiv changed from 15.0 to 16.0, so only that algorithm was rerun with version 16.0) [3].

equilibrium in two-player zero-sum games, but not for more than two players. However, they can both be run for more than two players, and have been demonstrated to obtain strong empirical performance in certain large extensive-form imperfect-information games. For example, an agent that utilized counterfactual regret minimization (CFR) recently defeated strong humans in 6-player no limit Texas hold 'em [6]. Both CFR and fictitious play (FP) can be extremely effective at quickly approximating Nash equilibrium strategies, particularly in large games. However, they can also lead to strategies with extremely high ϵ , even for very small games. So if the goal is to compute an exact Nash equilibrium in multiplayer games, CFR and FP are ineffective. Table 6 shows recent results of CFR and FP for games with uniform random payoffs in $[0,1]$ [10]. We can see that in several cases the average values of ϵ are quite large, and in all cases it exceeds the value of 0.001 that had been previously designated as a benchmark [3].

n	m	# games	# algorithm iterations	Avg. CFR ϵ	Avg. FP ϵ
3	3	100,000	10,000	0.00768	0.00749
3	5	100,000	10,000	0.02312	0.02244
3	10	10,000	10,000	0.05963	0.05574
4	3	100,000	10,000	0.01951	0.01950
4	5	10,000	10,000	0.05121	0.04635
4	10	10,000	10,000	0.08315	0.06661
5	3	10,000	10,000	0.13622	0.03285
5	5	10,000	10,000	0.12286	0.05334
5	10	10,000	1,000	0.07621	0.04325

Table 6: Results of counterfactual regret minimization and fictitious play in random games [10].

5 Conclusion

We presented a new complete algorithm for computing Nash equilibrium in multiplayer games based on a mixed-integer quadratically-constrained feasibility program formulation. Our algorithm outperforms the previously best complete algorithms by orders of magnitude for all but the largest game class we considered. Our algorithm even has significantly smaller runtimes than the best prior incomplete methods (which also frequently fail to compute a solution). We also demonstrated that recently popular iterative algorithms have significant approximation error and are unsatisfactory for the goal of computing an exact Nash equilibrium. Our algorithm clearly outperforms all prior approaches on small games, though its scalability may be limited due to the large number of variables and constraints (exponential in the number of players).

References

- [1] Nick Abou Risk and Duane Szafron. Using counterfactual regret minimization to create competitive multiplayer poker agents. In *Proceedings of the International Conference on Autonomous Agents and Multi-Agent Systems (AAMAS)*, pages 159–166, Toronto, Canada, 2010. International Foundation for Autonomous Agents and Multiagent Systems.
- [2] Yakov Babichenko, Siddharth Barman, and Ron Peretz. Simple approximate equilibria in large games. In *Proceedings of the Fifteenth ACM Conference on Economics and Computation*, pages 753–770, New York, NY, USA, 2014. Association for Computing Machinery.

- [3] Kimmo Berg and Tuomas Sandholm. Exclusion method for finding Nash equilibrium in multiplayer games. In *Proceedings of the AAAI Conference on Artificial Intelligence (AAAI)*, pages 383–389, San Francisco, California, USA, 2017. AAAI Press.
- [4] Johannes Bisschop. *AIMMS—Optimization Modeling*. AIMMS Inc., Bellevue, Washington, USA, 2006.
- [5] George W. Brown. Iterative solutions of games by fictitious play. In Tjalling C. Koopmans, editor, *Activity Analysis of Production and Allocation*, pages 374–376. John Wiley & Sons, New York, New York, 1951.
- [6] Noam Brown and Tuomas Sandholm. Superhuman AI for multiplayer poker. *Science*, 365(6456):885–890, 2019.
- [7] Xi Chen and Xiaotie Deng. 3-Nash is PPAD-complete. *Electronic Colloquium on Computational Complexity*, Report No. 134:1–12, 2005.
- [8] Xi Chen and Xiaotie Deng. Settling the complexity of 2-player Nash equilibrium. In *Proceedings of the Annual Symposium on Foundations of Computer Science (FOCS)*, pages 261–272, Berkeley, California, USA, 2006. IEEE Computer Society.
- [9] Constantinos Daskalakis, Paul Goldberg, and Christos Papadimitriou. The complexity of computing a Nash equilibrium. *SIAM Journal on Computing*, 1(39):195–259, 2009.
- [10] Sam Ganzfried. Fictitious Play Outperforms Counterfactual Regret Minimization, Jan 2020. arXiv:2001.11165 [cs.GT].
- [11] Sam Ganzfried, Austin Nowak, and Joannier Pinales. Successful Nash equilibrium agent for a 3-player imperfect-information game. *Games*, 9(33):1–8, 2018.
- [12] Srihari Govindan and Robert Wilson. A global Newton method to compute Nash equilibria. *Journal of Economic Theory*, 110:65–86, 2003.
- [13] Srihari Govindan and Robert Wilson. Computing Nash equilibria by iterated polymatrix approximation. *Journal of Economic Dynamics and Control*, 28:1229–1241, 2004.
- [14] LLC Gurobi Optimization. Gurobi optimizer reference manual, 2019.
- [15] G. Van Der Laan, A. J. J. Talman, and L. Van Der Heyden. Simplicial variable dimension algorithms for solving the nonlinear complementarity problem on a product of unit simplices using a general labelling. *Mathematics of Operations Research*, 12(3):377–397, 1987.
- [16] Richard McKelvey and Thomas Palfrey. Quantal response equilibria for normal form games. *Games and Economic Behavior*, 10:6–38, 07 1995.
- [17] Richard D. McKelvey, Andrew M. McLennan, and Theodore L. Turocy. Gambit: Software tools for game theory, version 0.97.1.5, 2004.
- [18] John Nash. *Non-cooperative games*. PhD thesis, Princeton University, 1950.
- [19] Eugene Nudelman, Jennifer Wortman, Kevin Leyton-Brown, and Yoav Shoham. Run the GAMUT: A comprehensive approach to evaluating game-theoretic algorithms. In *Proceedings of the International Conference on Autonomous Agents and Multi-Agent Systems (AAMAS)*, pages 880–887, New York, NY, 2004. International Foundation for Autonomous Agents and Multiagent Systems.

- [20] Julia Robinson. An iterative method of solving a game. *Annals of Mathematics*, 54:296–301, 1951.
- [21] Tuomas Sandholm, Andrew Gilpin, and Vincent Conitzer. Mixed-integer programming methods for finding Nash equilibria. In *Proceedings of the National Conference on Artificial Intelligence (AAAI)*, pages 495–501, Pittsburgh, Pennsylvania, USA, 2005. AAAI Press.
- [22] Theodore Turocy. A dynamic homotopy interpretation of the logistic quantal response equilibrium correspondence. *Games and Economic Behavior*, 51:243–263, 05 2005.
- [23] Martin Zinkevich, Michael Bowling, Michael Johanson, and Carmelo Piccione. Regret minimization in games with incomplete information. In *Proceedings of the Annual Conference on Neural Information Processing Systems (NIPS)*, pages 1729–1736, Vancouver, British Columbia, Canada, 2007. Curran Associates, Inc.