

An improved quantum-inspired algorithm for linear regression

András Gilyén*

Zhao Song[†]Ewin Tang[‡]

Abstract

We give a classical algorithm for linear regression analogous to the quantum matrix inversion algorithm [Harrow, Hassidim, and Lloyd, Physical Review Letters'09] for low-rank matrices [Wossnig et al., Physical Review Letters'18], when the input matrix A is stored in a data structure applicable for QRAM-based state preparation.

Namely, given an $A \in \mathbb{C}^{m \times n}$ with minimum singular value σ and which supports certain efficient ℓ_2 -norm importance sampling queries, along with a $b \in \mathbb{C}^m$, we can output a description of an $x \in \mathbb{C}^n$ such that $\|x - A^+b\| \leq \varepsilon \|A^+b\|$ in $\tilde{O}\left(\frac{\|A\|_F^6 \|A\|^2}{\sigma^8 \varepsilon^4}\right)$ time, improving on previous “quantum-inspired” algorithms in this line of research by a factor of $\frac{\|A\|_F^{14}}{\sigma^{14} \varepsilon^2}$ [Chia et al., STOC'20]. The algorithm is stochastic gradient descent, and the analysis bears similarities to those of optimization algorithms for regression in the usual setting [Gupta and Sidford, NeurIPS'18]. Unlike earlier works, this is a promising avenue that could lead to feasible implementations of classical regression in a quantum-inspired setting, for comparison against future quantum computers.

*agilyen@caltech.edu. Caltech. Formerly at QuSoft, CWI and University of Amsterdam.

[†]zhaos@ias.edu. Columbia University, Princeton University and Institute for Advanced Study.

[‡]ewint@cs.washington.edu. University of Washington.

1 Introduction

An important question for the future of quantum computing is whether we can use quantum computers to speed up machine learning [Pre18]. Answering this question is a topic of active research [Chi09, Aar15, BWP⁺17]. One potential avenue to an affirmative answer is through quantum linear algebra algorithms, which can perform sparse linear regression [HHL09] (and compute similar linear algebra expressions [GSLW19]) in time poly-logarithmic in input dimension. However, in machine learning it is often natural to assume that the input is close to being low-rank [KP17], in which case the above quantum algorithms typically require that the input is given in a manner allowing efficient quantum state preparation. Such proposals are usually based on quantum random access memory (QRAM) and a corresponding efficient data structure¹ [GLM08, Pra14], which also allows classical algorithms to perform the same tasks as the quantum algorithms with only a polynomial slowdown [CGL⁺20], meaning that here quantum computers do not give the exponential speedup in dimension that one might hope for. However, current results do not rule out large polynomial quantum speedups.

This paper focuses on this question of polynomial speedup for the particular case of linear regression (finding an approximate solution to $\min_x \|Ax - b\|_2^2$) for low-rank $A \in \mathbb{C}^{m \times n}$. Since Harrow, Hassidim, and Lloyd’s algorithm (HHL) for sparse A [HHL09, DHM⁺18], linear regression has been an influential primitive for quantum machine learning [BWP⁺17], and the corresponding variant for low-rank A also commonly appears [WZP18, RML14], typically manifesting in algorithms depending on $\|A\|_F$, the Frobenius norm of A . In the low-rank scenario, assuming the aforementioned data structure, current state-of-the-art quantum algorithms can produce a state ε -close to $|A^+b\rangle^2$ in ℓ_2 -norm given A and b in QRAM in $\mathcal{O}^*\left(\frac{\|A\|_F \|A\|}{\|A\| \sigma}\right)$ time [CGJ19].³ We think about this runtime as depending polynomially on (square root of) stable rank $\frac{\|A\|_F}{\|A\|}$ and condition number $\frac{\|A\|}{\sigma}$. Note that being able to produce quantum states $|x\rangle = \frac{1}{\|x\|} \sum_i x_i |i\rangle$ corresponding to a desired vector x is akin to a classical sampling problem, and is different from outputting x itself. The prior best analogous algorithm can produce the same result classically in $\tilde{\mathcal{O}}^*\left(\left(\frac{\|A\|_F}{\|A\|}\right)^6 \left(\frac{\|A\|}{\sigma}\right)^{28}\right)$ time [CGL⁺20]. This 1-to-28 separation suggests that classical techniques may be significantly slower, though not exponentially slower asymptotically.⁴

Our main result tightens this gap, giving an algorithm running in $\mathcal{O}^*\left(\left(\frac{\|A\|_F}{\|A\|}\right)^6 \left(\frac{\|A\|}{\sigma}\right)^8\right)$ time. Further, this runtime simply follows from an analysis of stochastic gradient descent (SGD), making it potentially more practical to implement and use as a benchmark against future scalable quantum computers. This result suggests that other tasks that can be solved

¹In this paper, we always use QRAM in combination with a data structure used for efficiently preparing states $|0\rangle \rightarrow \sum_i \frac{x_i}{\|x\|} |i\rangle$ corresponding to vectors $x \in \mathbb{C}^n$.

² A^+ denotes the pseudoinverse of A , also called the Moore-Penrose inverse of A .

³We define \mathcal{O}^* to be big O notation, hiding polynomial dependence on ε and poly-logarithmic dependence on dimension. Note that the precise exponent on $\log(mn)$ depends on the choice of word size in our RAM models. Since quantum and classical algorithms have different conventions for this choice, we will elide it for simplicity.

⁴The ε dependence for the quantum algorithm is $\log \frac{1}{\varepsilon}$, compared to the classical algorithm which gets $\frac{1}{\varepsilon^6}$. While this suggests an exponential speedup in ε , it appears to only hold for sampling problems, such as measuring $|A^+b\rangle$ in the computational basis. Learning information from the output quantum state $|A^+b\rangle$ generally requires $\text{poly}\left(\frac{1}{\varepsilon}\right)$ samples, preventing the exponential separation.

through iterative methods may have quantum-classical gaps that are smaller than existing quantum-inspired results suggest.

Our choice of stochastic gradient is similar to the one in the regression algorithm of Gupta and Sidford [GS18], though made mildly weaker to be efficient with the quantum-inspired data structure (instead of the bespoke data structure they design for their algorithm). In some sense, this work gives a version of their algorithm that trades runtime for weaker, more quantum-like input assumptions. To elaborate, if we include the cost of putting the raw input into the required data structure (an additional $\mathcal{O}(\text{nnz}(A))$ time) and require the output to be x in full, then the time needed to solve regression via our main result Theorem 1.1, $\mathcal{O}^*(\text{nnz}(A) + \frac{\|A\|_F^6 \|A\|^2}{\sigma^8} + \frac{\|A\|_F^2 \|A\|^2}{\sigma^4} n)$, is worse than Gupta and Sidford’s $\tilde{\mathcal{O}}^*(\text{nnz}(A) + \frac{\|A\|_F}{\sigma} \text{nnz}(A)^{\frac{2}{3}} n^{\frac{1}{6}})$ time (shown here after naively bounding numerical sparsity by n).⁵ However, our work demonstrates a *more general barrier* to quantum speedups: one could imagine that, for sufficiently quantum-like problems, the input satisfies quantum-inspired assumptions (say, we could prepare states corresponding to input), so quantum linear algebra algorithms are efficient, and yet the input is too large to re-format into a data structure of our choice, preventing classical results like Gupta and Sidford’s from giving a comparable runtime, while our work is still applicable and gives comparable runtimes.

1.1 Our model

Current QML algorithms for low-rank regression require input to be stored in an efficient data structure in QRAM [CGJ19].⁶ Many quantum machine learning (QML) algorithms require such assumptions [WZP18, RML14, Pra14, BWP⁺17, Pre18, CHI⁺18], especially those that achieve runtimes polylogarithmic in dimension. So, our comparison classical algorithms must also assume that input is stored in this “quantum-inspired” data structure, which supports several fully-classical operations. We first define the quantum-inspired data structure for vectors.

Definition (Vector-based data-structure, $\text{SQ}(v)$ and $\text{Q}(v)$). For any vector $v \in \mathbb{C}^n$, let $\text{SQ}(v)$ denote a data-structure that supports the following operations:

1. $\text{SAMPLE}()$. It outputs the entry i with probability $|v_i|^2 / \|v\|^2$.
2. $\text{QUERY}(i)$. The input of this function is an $i \in [n]$, the output is v_i .
3. $\text{NORM}()$. The output of this function is $\|v\|$.⁷

⁵This is comparable to the runtime of the quantum algorithm for outputting x , since one would need to run it $\mathcal{O}^*(n)$ times for state tomography, resulting in a total runtime of $\tilde{\mathcal{O}}^*(\text{nnz}(A) + \frac{\|A\|_F}{\sigma} n)$. The use of state tomography would also bring in polynomial dependence on ε^{-1} similarly to the quantum-inspired algorithm, while Gupta and Sidford’s algorithm has only logarithmic dependence on ε^{-1} .

⁶Although current QRAM proposals suggest that quantum hardware implementing QRAM may be realizable with essentially only logarithmic overhead in the runtime [GLM08], an actual physical implementation would require substantial advances in quantum technology in order to maintain coherence for a long enough time [AGJO⁺15].

⁷When we claim that we can call $\text{NORM}()$ on output vectors, we will mean that we can output a constant approximation: a number in $[0.9\|v\|, 1.1\|v\|]$.

Let $\mathcal{T}(v)$ denote the max time it takes for the data structure to respond to any query. If we only allow the QUERY operation, the data-structure is called $Q(v)$.

Notice that the SAMPLE function is the classical analogue of quantum state preparation, since the distribution being sampled is identical to the one attained by measuring $|v\rangle$ in the computational basis. We now extend our notion of quantum-inspired data structure to matrices.

Definition (Matrix-based data-structure, $SQ(A)$). For any matrix $A \in \mathbb{C}^{m \times n}$, let $SQ(A)$ denote a data-structure that supports the following operations:

1. $SAMPLE1()$. It outputs i with probability $\|A_{i,*}\|^2/\|A\|_F^2$.
2. $SAMPLE2(i)$. The input of this function is an $i \in [m]$. This function will output the entry j with probability $|A_{i,j}|^2/\|A_{i,*}\|^2$.
3. $QUERY(i, j)$. The input are $i \in [m]$ and $j \in [n]$, the output is $A_{i,j}$.
4. $NORM(i)$. The input is $i \in [m]$. The output is $\|A_{i,*}\|$.
5. $NORM()$. It outputs $\|A\|_F$.

Let $\mathcal{T}(A)$ denote the max time the data structure takes to respond to any query.

For the sake of simplicity, we will assume all input SQ data structures respond to queries in $\mathcal{O}(1)$ time. There are data structures that can do this in the word RAM model [CGL⁺20, Remark 2.15]. The dynamic data structures that commonly appear in the QML literature [KP17] respond to queries in $\mathcal{O}(\log(mn))$ time, so using such versions only increases our runtime by a logarithmic factor.

More formally, assumptions about QRAM and its data structures can be replaced by a specific form of *state preparation assumption*: the assumption that quantum states corresponding to input data can be prepared in time polylogarithmic in dimension. QML algorithms typically work with any state preparation assumption. However, to the authors' knowledge, all models admitting efficient protocols that take v stored in the standard way as input and output the quantum state $|v\rangle$ also admit corresponding efficient classical sample and query operations that can replace the data structure described above [CGL⁺20, Remark 2.15]. So, our results on the size of the speedup that quantum low-rank matrix inversion with QRAM achieves appears robust to changing quantum input models.

1.2 Our results

We start by defining some common notation. For a vector $v \in \mathbb{C}^n$, $\|v\|$ denotes ℓ_2 norm. For a matrix $A \in \mathbb{C}^{m \times n}$, A^\dagger , A^+ , $\|A\|$, and $\|A\|_F$ denote the conjugate transpose, pseudoinverse, operator norm, and Frobenius norm of A , respectively. $A_{i,*}$ and $A_{*,j}$ denote the i -th row and j -th column of A . $f \lesssim g$ denotes $f = \mathcal{O}(g)$, and respectively with \gtrsim and \asymp .

We solve the following problem.

Problem (Regression with regularization). Given $A \in \mathbb{C}^{m \times n}$, $b \in \mathbb{C}^m$, and a regularization parameter $\lambda \geq 0$, we define function $f : \mathbb{C}^n \rightarrow \mathbb{R}$ as

$$f(x) := \frac{1}{2}(\|Ax - b\|^2 + \lambda\|x\|^2).$$

Let $x^* := \arg \min_{x \in \mathbb{C}^n} f(x) = (A^\dagger A + \lambda I)^+ A^\dagger b$.

We will manipulate vectors by manipulating their *sparse descriptions*, defined as follows:

Definition. We say we have an s -sparse description of $x \in \mathbb{C}^d$ if we have an s -sparse $v \in \mathbb{C}^d$ such that $x = A^\dagger v$. We use the convention that any s -sparse description is also a t -sparse description for all $t \geq s$.

Our main result is that we can solve regression efficiently, assuming SQ(A).

Theorem 1.1. *Suppose we are given SQ(A) $\in \mathbb{C}^{m \times n}$ and Q(b) $\in \mathbb{C}^n$. Denote $\sigma := \|A^+\|^{-1}$ and consider $f(x)$ for $\lambda = \mathcal{O}(\|A\|^2)$. Let $\varepsilon \lesssim (\log \frac{\|A\|_{\mathbb{F}}^2}{\sigma^2 + \lambda})^{-\frac{1}{2}}$. There is an algorithm that takes*

$$\mathcal{O}\left(\frac{\|A\|_{\mathbb{F}}^6 \|A\|^2}{(\sigma^2 + \lambda)^4 \varepsilon^4} \left(\frac{\|b\|^2}{\|AA^+b\|^2} + \log \frac{1}{\varepsilon}\right) \log \frac{1}{\varepsilon}\right)$$

time and outputs a $\mathcal{O}\left(\frac{\|A\|_{\mathbb{F}}^2 \|A\|^2}{(\sigma^2 + \lambda)^2 \varepsilon^2} \left(\frac{\|b\|^2}{\|AA^+b\|^2} + \log \frac{1}{\varepsilon}\right)\right)$ -sparse description of an x such that $\|x - x^\| \leq \varepsilon \|x^*\|$ with probability ≥ 0.9 . This description admits SQ(x) for*

$$\mathcal{T}(x) = \tilde{\mathcal{O}}\left(\frac{\|A\|_{\mathbb{F}}^6 \|A\|^6}{(\sigma^2 + \lambda)^6 \varepsilon^4} \log^2 \frac{1}{\varepsilon} \left(\frac{\|b\|^4}{\|AA^+b\|^4} + \log^2 \frac{1}{\varepsilon}\right)\right).$$

Note that the runtime stated for $\mathcal{T}(x)$ corresponds to the runtime of SAMPLE and NORM; the runtime of QUERY is the sparsity of the description, $\mathcal{O}\left(\frac{\|A\|_{\mathbb{F}}^2 \|A\|^2}{(\sigma^2 + \lambda)^2 \varepsilon^2} \left(\frac{\|b\|^2}{\|AA^+b\|^2} + \log \frac{1}{\varepsilon}\right)\right)$. So, unlike previous quantum-inspired algorithms, it may be the case that the runtime of the SQ query dominates, though it's conceivable that this runtime bound is an artifact of our analysis. The parameter $\frac{\|AA^+b\|^2}{\|b\|^2}$ corresponds to the fraction of b 's mass that is in the row space of A , thinking of AA^+ as the orthogonal projector on the row space of A . Factors of $\frac{\|b\|^2}{\|AA^+b\|^2}$ arise because sampling error is additive with respect to $\|b\|$, and need to be rescaled relative to $\|x^*\|$; the quantum algorithm must also pay such a factor.

As mentioned previously, we use stochastic gradient descent to solve this problem, for $T := \mathcal{O}\left(\frac{\|A\|_{\mathbb{F}}^2 \|A\|^2}{(\sigma^2 + \lambda)^2 \varepsilon^2} \log \frac{1}{\varepsilon}\right)$ iterations. Such optimization algorithms are standard for solving regression in this setting [GS18]: the idea is that, instead of computing a pseudoinverse to explicitly compute the minimizer to f , one can start at $x^{(0)} = \vec{0}$ and iteratively find $x^{(t+1)}$ from $x^{(t)}$ such that the sequence $\{f(x^{(t)})\}_{t \in \mathbb{N}}$ converges to $f(x^*)$. Since f is convex, updating $x^{(t)}$ by nudging it in the gradient direction produces such a sequence, even when we only compute decent (stochastic) estimators of the gradient [Bub15].

Though the idea of SGD for regression is simple and well-understood, we note that some standard analyses fail in our setting, so some care is needed in analysing SGD correctly. First, our stochastic gradient (Eq. (1)) has variance that depends on the norm of the current

iterate, and projection onto the ball of vectors of bounded norm is too costly, so our analyses cannot assume a uniform bound on the second moment of our stochastic gradient. Second, we want a bound for the final iterate $x^{(T)}$, not merely a bound on averaged iterates as is common for SGD analyses, since using an averaging scheme would complicate the analysis in Section 2.3. Third, we want a bound on the output x of our algorithm of the form $\|x - x^*\| \leq \varepsilon \|x^*\|$. We could have chosen to aim for the typical bound in the optimization literature of $f(x) - f(x^*) \leq \varepsilon (f(x^{(0)}) - f(x^*))$, but our choice is common in the QML literature, and it only makes sense to have $\text{SQ}(x)$ when x is indeed close to x^* up to multiplicative error. Finally, note that acceleration via methods like the accelerated proximal point algorithm (APPA) [FGKS15] framework cannot be used in this setting, since we cannot pay the linear time in dimension necessary to recenter gradients. The SGD analysis of Moulines and Bach [MB11] meets all of our criteria: the bulk of our result comes from simply combining this analysis with our choice of stochastic gradient (Eq. (1)).

The runtime of SGD is only good for our choice of gradient when b is sparse, but through a sketching matrix we can reduce to the case where b has $\mathcal{O}\left(\frac{\|A\|_{\text{F}}^2 \|A\|^2}{\sigma^4 \varepsilon^2} \frac{\|b\|^2}{\|AA^\dagger + b\|^2}\right)$ non-zero entries. Additional analysis is necessary to argue that we have efficient sample and query access to the output, since we need to rule out the possibility that our output x is given as a description $A^\dagger \tilde{x}$ such that \tilde{x} is much larger than x , in which case computing, say, $\|x\|$ via rejection sampling would be intractable.

2 Proofs

2.1 Stochastic gradient bounds

Because we are using SGD to minimize $f(x)$, we need a stochastic approximation to $\nabla f(x) = A^\dagger Ax - A^\dagger b + \lambda x$. Our choice of stochastic gradient comes from observing that $A^\dagger Ax = \sum_{r=1}^m \sum_{c=1}^n A_r^\dagger A_{rc} x_c$, so we can estimate this by sampling one of the summands.

Let r be drawn from the distribution that is r with probability $\frac{\|A_{r,*}\|^2}{\|A\|_{\text{F}}^2}$ and let c_1, \dots, c_C be drawn i.i.d. from the distribution that is c with probability $\frac{|A_{r,c}|^2}{\|A_{r,*}\|^2}$. Define

$$\nabla g(x) = \frac{\|A\|_{\text{F}}^2}{\|A_{r,*}\|^2} \left(\sum_{j=1}^C \frac{\|A_{r,*}\|^2}{C |A_{r,c_j}|^2} A_{r,c_j} x_{c_j} \right) (A_{r,*})^\dagger - A^\dagger b + \lambda x, \quad (1)$$

and this will be our estimator for $\nabla f(x)$. Notice that the first term of this expression is the average of copies of

$$\frac{\|A\|_{\text{F}}^2}{|A_{r,c}|^2} A_{r,c} x_c (A_{r,*})^\dagger \quad \text{with probability } \frac{|A_{r,c}|^2}{\|A\|_{\text{F}}^2}$$

Lemma 2.1. *Consider $\nabla g(x)$ as in Eq. (1) as an estimator of $\nabla f(x)$.*

1. $\mathbb{E}[\nabla g(x)] = \nabla f(x)$
2. $\text{Var}[\nabla g(x)] = \frac{1}{C} \|A\|_{\text{F}}^4 \|x\|^2 + \left(1 - \frac{1}{C}\right) \|A\|_{\text{F}}^2 \|Ax\|^2 - \|A^\dagger Ax\|^2$
3. $\mathbb{E}[\|\nabla g(x) - \nabla g(y)\|_2^2] = \|(A^\dagger A + \lambda I)(x - y)\|^2 + \text{Var}[\nabla g(x - y)]$

Proof. Part 1. We have

$$\begin{aligned}
\mathbb{E}[\nabla g(x)] &= \frac{1}{C} \sum_{j=1}^C \mathbb{E} \left[\frac{\|A\|_{\mathbb{F}}^2}{\|A_{r,*}\|^2} \frac{\|A_{r,*}\|^2}{|A_{r,c_j}|^2} A_{r,c_j} x_{c_j} (A_{r,*})^\dagger \right] - A^\dagger b + \lambda x \\
&= \mathbb{E} \left[\frac{\|A\|_{\mathbb{F}}^2}{|A_{r,c_1}|^2} A_{r,c_1} x_{c_1} (A_{r,*})^\dagger \right] - A^\dagger b + \lambda x \\
&= \left(\sum_{r,c_1} \frac{|A_{r,c_1}|^2}{\|A\|_{\mathbb{F}}^2} \frac{\|A\|_{\mathbb{F}}^2}{|A_{r,c_1}|^2} A_{r,c_1} x_{c_1} (A_{r,*})^\dagger \right) - A^\dagger b + \lambda x \\
&= A^\dagger A x - A^\dagger b + \lambda x = \nabla f(x).
\end{aligned}$$

Part 2. Now variance.

$$\begin{aligned}
\text{Var}[\nabla g(x)] &= \mathbb{E}[\|\nabla g(x) - \mathbb{E}[\nabla g(x)]\|^2] \\
&= \text{Var} \left[\frac{\|A\|_{\mathbb{F}}^2}{\|A_{r,*}\|^2} \left(\sum_{j=1}^C \frac{\|A_{r,*}\|^2}{C|A_{r,c_j}|^2} A_{r,c_j} x_{c_j} \right) (A_{r,*})^\dagger \right] \\
&= \text{Var} \left[\left(\sum_{j=1}^C \frac{\|A\|_{\mathbb{F}}^2}{C|A_{r,c_j}|^2} A_{r,c_j} x_{c_j} \right) (A_{r,*})^\dagger \right] \\
&= \mathbb{E} \left[\left\| \left(\sum_{j=1}^C \frac{\|A\|_{\mathbb{F}}^2}{C|A_{r,c_j}|^2} A_{r,c_j} x_{c_j} \right) (A_{r,*})^\dagger \right\|^2 \right] - \|A^\dagger A x\|^2.
\end{aligned}$$

Then, we can bound the first term of the above equation as follows:

$$\begin{aligned}
&\mathbb{E} \left[\left\| \left(\sum_{j=1}^C \frac{\|A\|_{\mathbb{F}}^2}{C|A_{r,c_j}|^2} A_{r,c_j} x_{c_j} \right) (A_{r,*})^\dagger \right\|^2 \right] \\
&= \sum_{i=1}^m \frac{\|A_{i,*}\|^2}{\|A\|_{\mathbb{F}}^2} \frac{\|A\|_{\mathbb{F}}^4 \|A_{i,*}\|^2}{\|A_{i,*}\|^4} \mathbb{E} \left[\left(\sum_{j=1}^C \frac{\|A_{i,*}\|^2}{C|A_{i,c_j}|^2} A_{i,c_j} x_{c_j} \right)^2 \right] \\
&= \|A\|_{\mathbb{F}}^2 \sum_{i=1}^m \mathbb{E} \left[\left(\sum_{j=1}^C \frac{\|A_{i,*}\|^2}{C|A_{i,c_j}|^2} A_{i,c_j} x_{c_j} \right)^2 \right] \\
&= \|A\|_{\mathbb{F}}^2 \sum_{i=1}^m \left(\frac{1}{C} \text{Var} \left[\frac{\|A_{i,*}\|^2}{|A_{i,c_j}|^2} A_{i,c_j} x_{c_j} \right] + (A_{i,*} x)^2 \right) \\
&= \|A\|_{\mathbb{F}}^2 \sum_{i=1}^m \left(\frac{1}{C} (\|A_{i,*}\|^2 \|x\|^2 - (A_{i,*} x)^2) + (A_{i,*} x)^2 \right) \\
&= \frac{1}{C} \|A\|_{\mathbb{F}}^4 \|x\|^2 + \left(1 - \frac{1}{C} \right) \|A\|_{\mathbb{F}}^2 \|A x\|^2
\end{aligned}$$

Note that if $C \leq \frac{\|A\|_{\mathbb{F}}^2 \|x\|^2}{\|A x\|^2}$ (as is the case for our eventual value of C , $\frac{\|A\|_{\mathbb{F}}^2}{\|A\|^2}$), this variance can be bounded as $\frac{1}{C} \|A\|_{\mathbb{F}}^4 \|x\|^2$.

Part 3. Finally, the expression for $\mathbb{E}[\|\nabla g(x) - \nabla g(y)\|^2]$ follows from the observation that $\nabla g(x) - \nabla g(y)$ is simply $\nabla g(x - y)$ when b and $x^{(0)}$ are zero vectors. \square

2.2 Analyzing stochastic gradient descent for sparse b

The algorithm we use to solve regression is stochastic gradient descent (SGD): consider a differentiable random function $g : \mathcal{X} \rightarrow \mathbb{R}$, and consider the following recursion, starting from $x^{(0)} \in \mathcal{X}$:

$$x^{(t)} = x^{(t-1)} - \eta_t \nabla g(x^{(t-1)}), \quad (2)$$

where $(\eta_t)_{k \geq 1}$ is a deterministic sequence of positive scalars. We will take ∇g to be as in Eq. (1), and $x^{(0)} = \vec{0}$.

We can make some simple observations about the computational complexity of this gradient step when b is sparse (that is, the number of non-zero entries of b , $\|b\|_0$, is small).

Lemma 2.2. *Given $\text{SQ}(A)$, we can output $x^{(t)}$ as a $(t + \|b\|_0)$ -sparse description in time*

$$\mathcal{O}(Ct(t + \|b\|_0)).$$

Proof. First, suppose we are given $x^{(t)}$ as an s -sparse description, and wish to output a sparse description for the next iterate $x^{(t+1)}$, which from Eq. (1), satisfies

$$\begin{aligned} x^{(t+1)} &= x^{(t)} - \eta_{t+1} \nabla g(x^{(t)}) \\ &= x^{(t)} - \eta_{t+1} \cdot \left(\frac{\|A\|_F^2}{\|A_{r,*}\|^2} \left(\sum_{j=1}^C \frac{\|A_{r,*}\|^2}{C|A_{r,c_j}|^2} A_{r,c_j} x_{c_j}^{(t)} \right) (A_{r,*})^\dagger - A^\dagger b + \lambda x^{(t)} \right). \end{aligned}$$

The r and c_j 's are drawn from distributions, and $\text{SQ}(A)$ can produce such samples with its `SAMPLE` queries, taking $\mathcal{O}(C)$ time.

From inspection of the above equation, if we have $x^{(t)}$ in terms of its description as $A^\dagger v^{(t)}$, then we can write $x^{(t+1)}$ as a description $A^\dagger v^{(t+1)}$ where $v^{(t+1)}$ satisfies

$$v^{(t+1)} = v^{(t)} - \eta_{t+1} \cdot \left(\frac{\|A\|_F^2}{\|A_{r,*}\|^2} \left(\sum_{j=1}^C \frac{\|A_{r,*}\|^2}{C|A_{r,c_j}|^2} A_{r,c_j} (A_{*,c_j})^\dagger v^{(t)} \right) e_r - b + \lambda v^{(t)} \right). \quad (3)$$

Here, e_r is the vector that is one in the r th entry and zero otherwise. So, if $v^{(t)}$ is s -sparse, and has a support that includes the support of b , then $v^{(t+1)}$ is $(s+1)$ -sparse. Furthermore, by exploiting the sparsity of $v^{(t)}$, computing $v^{(t+1)}$ takes $\mathcal{O}(Cs)$ time (including the time taken to use $\text{SQ}(A)$ to query A for all of the relevant norms and entries).

So, if we wish to compute $x^{(t)}$, we begin with $x^{(0)}$, which we have trivially as an $\|b\|_0$ -sparse decomposition ($v^{(0)} = \vec{0}$). It is sparser, but if we consider $x^{(0)}$ as having the same support as b , by the argument described above, we can then compute $x^{(1)}$ as an $(\|b\|_0 + 1)$ -sparse description in $\mathcal{O}(C\|b\|_0)$ time.

By iteratively computing $v^{(i+1)}$ from $v^{(i)}$ in $\mathcal{O}(C(\|b\|_0 + i))$ time, we can output $x^{(t)}$ as a $(t + \|b\|_0)$ -sparse description in

$$\mathcal{O}\left(\sum_{i=0}^t C(\|b\|_0 + i)\right) = \mathcal{O}(Ct(t + \|b\|_0))$$

time as desired. □

We will take $C = \|A\|_{\mathbb{F}}^2/\|A\|^2$, which is the largest value we can set C to before it stops having an effect on the variance of ∇g . It's good to scale C up to be as large as possible, since it means a corresponding linear decrease in the number of iterations, which our algorithm runtime depends on quadratically. We eventually take $T = \mathcal{O}\left(\frac{\|A\|^2\|A\|_{\mathbb{F}}^2}{\sigma^4\varepsilon^2} \log \frac{1}{\varepsilon}\right)$ and, giving a runtime of

$$\Theta\left(s \frac{\|A\|_{\mathbb{F}}^4}{\sigma^4\varepsilon^2} \log \frac{1}{\varepsilon} + \frac{\|A\|^2\|A\|_{\mathbb{F}}^6}{\sigma^8\varepsilon^4} \log^2 \frac{1}{\varepsilon}\right)$$

For simplicity we assume knowledge of $\|A\|$ exactly, despite that our $\text{SQ}(A)$ only gives us access to $\|A\|_{\mathbb{F}}$. One can get a constant approximation to $\|A\|$ in $\mathcal{O}\left(\frac{\|A\|_{\mathbb{F}}^6}{\|A\|^6}\right)$ time [CGL⁺20, Lemma 3.9], though, which suffices for our purposes. Now, we must show that performing SGD for T many iterations gives an x sufficiently close to x^* .

Proposition 2.3. *Let $A \in \mathbb{C}^{m \times n}$ and $b \in \mathbb{C}^n$. Let $\sigma := \|A^+\|^{-1}$. Let $C := \frac{\|A\|_{\mathbb{F}}^2}{\|A\|^2}$. We choose $\varepsilon := \mathcal{O}\left(\frac{\|A\|_{\mathbb{F}}\|A\|}{\|A\|_{\mathbb{F}}\|A\|+\lambda} (\log \frac{\|A\|_{\mathbb{F}}\|A\|}{\sigma^2+\lambda})^{-\frac{1}{2}}\right)$ and $T := \Theta\left(\frac{\|A\|_{\mathbb{F}}^2\|A\|^2}{(\sigma^2+\lambda)^2\varepsilon^2} \log \frac{1}{\varepsilon}\right)$. Let $x^{(T)}$ be defined as Eq. (2), with $x^{(0)} = \vec{0}$ and $\eta_t := \frac{\varepsilon(12 \log(1/\varepsilon)/t)^{1/2}}{\|A\|_{\mathbb{F}}\|A\|}$. Then we have*

$$\mathbb{E}[\|x^{(T)} - x^*\|^2] \leq \varepsilon^2 \|x^*\|^2.$$

In particular, by Markov's inequality, with probability ≥ 0.9 , $\|x^{(T)} - x^*\| \lesssim \varepsilon \|x^*\|$.

Stochastic gradient descent is known to require a number of iterations linear in (something like the) second moment of the stochastic gradient. To analyze SGD, we apply the following theorem.

Theorem 2.4 ([MB11, Theorem 1]). *Suppose the following assumptions hold:*

1. Let $(\mathcal{F}_n)_{n \geq 0}$ be an increasing family of σ -fields. x_0 is \mathcal{F}_0 -measurable, and for each $x \in \mathcal{X}$, the random variable $g'(x)$ is square-integrable, \mathcal{F}_n -measurable, and

$$\forall x \in \mathcal{X}, \quad \mathbb{E}[g'(\theta) \mid \mathcal{F}_{n-1}] = f'(x), \text{ w.p. } 1.$$

2. g is almost surely convex, differentiable, and:

$$\forall x, y \in \mathcal{X}. \mathbb{E}[\|g'(x) - g'(y)\|^2 \mid \mathcal{F}_{n-1}] \leq L^2 \|x - y\|^2, \text{ w.p. } 1.$$

3. f is μ -strongly convex with respect to the norm $\|\cdot\|$.

4. There exists $G^2 \in \mathbb{R}_+$ such that $\mathbb{E}[\|g'(x^*)\|^2 \mid \mathcal{F}_{n-1}] \leq G^2$.

Denote $\delta_t := \mathbb{E}[\|x^{(t)} - x^*\|^2]$, $\varphi_\alpha(t) = \frac{t^\alpha}{\alpha}$ for $\alpha \neq 0$ and $\varphi_0(t) = \log(t)$. Let $\eta \in (0, 1)$ denote a parameter, and for each t , set $\eta_t = \eta \cdot t^{-\alpha}$. We have, for $\alpha \in [0, 1]$:

$$\delta_t \leq \begin{cases} 2 \exp(4L^2\eta^2\varphi_{1-2\alpha}(t) - \mu\eta t^{1-\alpha}/4) \cdot (\delta_0 + G^2/L^2) + 4\eta G^2/(\mu t^\alpha) & \alpha \in [0, 1) \\ \exp(2L^2\eta^2) \cdot n^{-\mu\eta} \cdot (\delta_0 + G^2/L^2) + 2G^2\eta^2 \cdot \varphi_{\mu\eta/2-1}(n) \cdot n^{-\mu\eta/2} & \alpha = 1 \end{cases}$$

Now, we apply this theorem to our stochastic gradient $\nabla g(x)$ as in Eq. (1), for $C = \|A\|_{\mathbb{F}}^2/\|A\|^2$ as discussed, to show that $\delta_t \leq \varepsilon^2\|x^*\|^2$, thereby proving Proposition 2.3. By Lemma 2.1 we can take

$$\begin{aligned} L^2 &= (\|A\|^2 + \lambda)^2 + \frac{1}{C}\|A\|_{\mathbb{F}}^4 \leq 3(\|A\|_{\mathbb{F}}^2\|A\|^2 + \lambda^2) & G^2 &= \frac{1}{C}\|A\|_{\mathbb{F}}^4\|x^*\|^2, \\ \mu &= \sigma^2 + \lambda, & \delta_0 &= \|x^*\|^2. \end{aligned}$$

Claim 2.5. *If we take $\alpha = \frac{1}{2}$, $\eta^2 = \frac{12\varepsilon^2}{\|A\|_{\mathbb{F}}^2\|A\|^2} \log \frac{1}{\varepsilon}$, and assume $\varepsilon \lesssim \frac{\|A\|_{\mathbb{F}}\|A\|}{\|A\|_{\mathbb{F}}\|A\| + \lambda} (\log \frac{\|A\|_{\mathbb{F}}\|A\|}{\sigma^2 + \lambda})^{-\frac{1}{2}}$, then for $T = \frac{\eta^2\|A\|_{\mathbb{F}}^4\|A\|^4}{(\sigma^2 + \lambda)^2\varepsilon^4} = 12\frac{\|A\|_{\mathbb{F}}^2\|A\|^2}{(\sigma^2 + \lambda)^2\varepsilon^2} \log \frac{1}{\varepsilon}$,*

$$\delta_T \leq \varepsilon^2\|x^*\|^2.$$

The particular values in this claim (in particular, η , T , and ε) are chosen to give the eventual bound of $\delta_T \leq \varepsilon^2\|x^*\|^2$.

Proof. It happens that $\alpha = \frac{1}{2}$ gives the best bound on δ_t (as we expect, since SGD in this setting gives a $\frac{1}{\sqrt{t}}$ rate). For this choice of α , substituting in our values for L^2 , G^2 , μ , and δ_0 , we get

$$\begin{aligned} \delta_T &\leq 2 \exp(4L^2\eta^2 \log(T) - \mu\eta\sqrt{T}/4)(\delta_0 + G^2/L^2) + \frac{4\eta G^2}{\mu\sqrt{T}} \\ &\leq \left(4 \exp\left(12(\|A\|_{\mathbb{F}}^2\|A\|^2 + \lambda^2)\eta^2 \log(T) - (\sigma^2 + \lambda)\eta\sqrt{T}/4\right) + \frac{4\eta\|A\|_{\mathbb{F}}^2\|A\|^2}{(\sigma^2 + \lambda)\sqrt{T}}\right)\|x^*\|^2. \end{aligned}$$

Dividing by $\|x^*\|^2$ on both sides and substituting in T , we get

$$\begin{aligned} \frac{\delta_T}{\|x^*\|^2} &\leq 4 \exp\left(12(\|A\|_{\mathbb{F}}^2\|A\|^2 + \lambda^2)\eta^2 \log\left(\frac{\eta^2\|A\|_{\mathbb{F}}^4\|A\|^4}{(\sigma^2 + \lambda)^2\varepsilon^4}\right) - \frac{\eta^2\|A\|_{\mathbb{F}}^2\|A\|^2}{4\varepsilon^2}\right) + 4\varepsilon^2 \\ &= 4 \exp(-C_1 \log(1/\varepsilon)) + 4\varepsilon^2 \\ &= 4\varepsilon^{C_1} + 4\varepsilon^2 \leq 8\varepsilon^2. \end{aligned}$$

The first step follows from substituting in η and defining

$$C_1 := 3 - 144 \frac{(\|A\|_{\mathbb{F}}^2\|A\|^2 + \lambda^2)\varepsilon^2}{\|A\|_{\mathbb{F}}^2\|A\|^2} \log\left(\frac{12\|A\|_{\mathbb{F}}^2\|A\|^2}{(\sigma^2 + \lambda)^2\varepsilon^2} \log \frac{1}{\varepsilon}\right), \quad (4)$$

and the final inequality follows because the bound on ε in the statement of the claim implies that $C_1 \geq 2$. \square

2.3 Accessing the output

After performing SGD, we have a $x^{(T)}$ that is close to x^* as desired, and it is given as a sparse description $A^\dagger v^{(T)}$. We want to say that we have $\text{SQ}(x^{(T)})$ from its description. Our goal is to invoke a result originally from [Tan19] about length-square sampling a vector that is a linear-combination of length-square accessible vectors.

Lemma 2.6 ([CGL⁺20, Lemmas 2.9 and 2.10]). *Suppose we have $\text{SQ}(M^\dagger)$ for $M \in \mathbb{C}^{n \times d}$ and $Q(x) \in \mathbb{C}^d$. Denote $\Delta := \sum_{i=1}^d \|M_{*,i}\|^2 x_i^2 / \|y\|_2^2$. Then we can implement $\text{SQ}(y) \in \mathbb{C}^n$ for $y := Mx$ with $\mathcal{T}(y) = \mathcal{O}(d^2 \Delta \log(1/\delta) \cdot \mathcal{T}(M))$, where queries succeed with probability $\geq 1 - \delta$. Namely, we can:*

- (a) query for entries with complexity $\mathcal{O}(d \cdot \mathcal{T}(M))$;
- (b) sample from y with runtime $\mathcal{T}_{\text{SAMPLE}}(y)$ satisfying

$$\mathbb{E}[\mathcal{T}_{\text{SAMPLE}}(y)] = \mathcal{O}(d^2 \Delta \cdot \mathcal{T}(M))$$

and

$$\Pr[\mathcal{T}_{\text{SAMPLE}}(y) = \mathcal{O}(d^2 \Delta \cdot \log(1/\delta))] \geq 1 - \delta.$$

- (c) estimate $\|y\|$ to $(1 \pm \varepsilon)$ multiplicative error with success probability at least $1 - \delta$ in complexity

$$\mathcal{O}\left(\frac{d^2 \Delta}{\varepsilon^2} \mathcal{T}(M) \cdot \log(1/\delta)\right).$$

So we care about the quantity $\Delta = \frac{1}{\|A^\dagger v^{(t)}\|^2} \sum_{i=1}^m \|A_{i,*}\|^2 |v_i^{(t)}|^2$, with $t = T$, where $v^{(t)}$ follows the recurrence according to Eq. (3) (recalling from before that r and c_1, \dots, c_C are sampled randomly and independently each iteration):

$$v^{(t+1)} = v^{(t)} - \eta_{t+1} \cdot \underbrace{\left(\frac{\|A\|_F^2}{\|A_{r,*}\|^2} \left(\sum_{j=1}^C \frac{\|A_{r,*}\|^2}{C|A_{r,c_j}|^2} A_{r,c_j} (A_{*,c_j})^\dagger v^{(t)} \right) e_r - b + \lambda v^{(t)} \right)}_{\nabla \tilde{g}(v^{(t)})}.$$

Roughly speaking, Δ encodes the amount of cancellation that could occur in the product $A^\dagger v^{(t)}$. We will consider it as a norm: $\Delta = \frac{\|v^{(t)}\|_D^2}{\|x^{(t)}\|^2}$, for D a diagonal matrix with $D_{ii} = \|A_{i,*}\|$, where $\|v\|_D := \sqrt{v^\dagger D^\dagger D v}$. From now on, we will consider $x^{(t)}$ to be the version of SGD as in Proposition 2.3, e.g. $C = \frac{\|A\|_F^2}{\|A\|^2}$.

First, notice that we can show similar moment bounds for $\nabla \tilde{g}(v^{(t)})$ in the D norm as those in Lemma 2.1. The mean is what we expect it to be:

$$\begin{aligned} \mathbb{E}[\nabla \tilde{g}(v)] &= \mathbb{E} \left[\frac{\|A\|_F^2}{\|A_{r,*}\|^2} \left(\sum_{j=1}^C \frac{\|A_{r,*}\|^2}{C|A_{r,c_j}|^2} A_{r,c_j} (A_{*,c_j})^\dagger v^{(t)} \right) e_r - b + \lambda v \right] \\ &= \sum_{r=1}^m \mathbb{E} \left[\sum_{j=1}^C \frac{\|A_{r,*}\|^2}{C|A_{r,c_j}|^2} A_{r,c_j} (A_{*,c_j})^\dagger v^{(t)} \right] e_r - b + \lambda v \\ &= \sum_{r=1}^m \sum_{c=1}^n A_{r,c} ((A_{*,c})^\dagger v^{(t)}) e_r - b + \lambda v \\ &= AA^\dagger v - b + \lambda v. \end{aligned}$$

The variance in the D norm is identical to the variance of ∇g :

$$\begin{aligned}\mathbb{E}[\|\nabla\tilde{g}(v) - \mathbb{E}[\nabla\tilde{g}(v)]\|_D^2] &= \text{Var} \left[D \frac{\|A\|_F^2}{\|A_{r,*}\|_F^2} \left(\sum_{j=1}^C \frac{\|A_{r,*}\|_F^2}{C|A_{r,c_j}|^2} A_{r,c_j} (A_{*,c_j})^\dagger v^{(t)} \right) e_r \right] \\ &= \mathbb{E} \left[\left\| A_{r,*} \right\|^2 \left| \sum_{j=1}^C \frac{\|A\|_F^2}{C|A_{r,c_j}|^2} A_{r,c_j} (A_{*,c_j})^\dagger v^{(t)} \right|^2 \right] - \|AA^\dagger v\|_D^2\end{aligned}$$

From here, the variance computation is identical to the one in Lemma 2.1.

$$\begin{aligned}&= \frac{1}{C} \|A\|_F^2 \|A^\dagger v\|^2 + \left(1 - \frac{1}{C}\right) \|A\|_F^2 \|AA^\dagger v\|^2 - \|AA^\dagger v\|_D^2 \\ &\leq 2\|A\|_F^2 \|A\|^2 \|A^\dagger v\|^2.\end{aligned}$$

To bound Δ , we will show a recurrence. Note that

$$\begin{aligned}\mathbb{E}[\|v^{(t+1)}\|_D \mid v^{(t)}] &\leq \|v^{(t)}\|_D (1 - \eta_{t+1}\lambda) + \eta_{t+1} \mathbb{E}[\|\nabla\tilde{g}(v^{(t)}) - \lambda v^{(t)}\| \mid v^{(t)}] && \text{by triangle inequality} \\ &\leq \|v^{(t)}\|_D + \eta_{t+1} \sqrt{\mathbb{E}[\|\nabla\tilde{g}(v^{(t)}) - \lambda v^{(t)}\|_D^2 \mid v^{(t)}]} && \text{by } \mathbb{E}[Z]^2 \leq \mathbb{E}[Z^2] \\ &\leq \|v^{(t)}\|_D + \eta_{t+1} \sqrt{\|AA^\dagger v^{(t)} - b\|_D^2 + 2\|A\|_F^2 \|A\|^2 \|A^\dagger v^{(t)}\|^2} && \text{by } \mathbb{E}[Z^2] = \mathbb{E}[Z]^2 + \text{Var}[Z] \\ &\lesssim \|v^{(t)}\|_D + \eta_{t+1} (\|b\|_D + \|A\|_F \|A\| \|x^{(t)}\|). && \text{by } x^{(t)} = A^\dagger v^{(t)} \text{ and } \|D\| \leq \|A\|\end{aligned}$$

Taking the expectation of both sides, we have

$$\mathbb{E}[\|v^{(t+1)}\|_D] \leq \mathbb{E}[\|v^{(t)}\|_D] + \eta_{t+1} (\|b\|_D + \|A\|_F \|A\| \mathbb{E}[\|x^{(t)}\|]),$$

so since $v^{(0)} = \vec{0}$, we can solve this recurrence to get

$$\mathbb{E}[\|v^{(T)}\|_D] \lesssim \sum_{t=1}^T \frac{\eta}{\sqrt{t}} (\|b\|_D + \|A\|_F \|A\| \mathbb{E}[\|x^{(t)}\|]). \quad (5)$$

Further, for $t \leq T$,

$$\mathbb{E}[\|x^{(t)}\|] \leq \|x^*\| + \sqrt{\mathbb{E}[\|x^{(t)} - x^*\|^2]} \leq \|x^*\| + \sqrt{\delta_t} \lesssim \|x^*\| \left(1 + \sqrt{\frac{\varepsilon \|A\|_F \|A\|}{(\sigma^2 + \lambda)\sqrt{t}} \sqrt{\log \frac{1}{\varepsilon}}}\right),$$

where the last line uses the analysis from the proof of Claim 2.5:

$$\begin{aligned}\delta_t &\leq \|x^*\|^2 \left(4 \exp \left(12(\|A\|_F^2 \|A\|^2 + \lambda^2)\eta^2 \log(t) - (\sigma^2 + \lambda)\eta\sqrt{t}/4\right) + \frac{4\eta\|A\|_F^2 \|A\|^2}{(\sigma^2 + \lambda)\sqrt{t}}\right) \\ &\leq \|x^*\|^2 \left(4 \exp \left(12(\|A\|_F^2 \|A\|^2 + \lambda^2)\eta^2 \log(T)\right) + \frac{4\eta\|A\|_F^2 \|A\|^2}{(\sigma^2 + \lambda)\sqrt{t}}\right) \\ &\lesssim \|x^*\|^2 \left(1 + \frac{\varepsilon \|A\|_F \|A\|}{(\sigma^2 + \lambda)\sqrt{t}} \sqrt{\log \frac{1}{\varepsilon}}\right).\end{aligned}$$

The last line of the above equation follows from a similar reasoning to Eq. (4): after plugging in $\eta^2 = \frac{12\varepsilon^2}{\|A\|_{\mathbb{F}}^2\|A\|^2} \log \frac{1}{\varepsilon}$ and $T = 12\frac{\|A\|_{\mathbb{F}}^2\|A\|^2}{(\sigma^2+\lambda)^2\varepsilon^2} \log \frac{1}{\varepsilon}$, our upper bound on ε implies that the expression in the exponential is at most one. Returning to Eq. (5), we have

$$\begin{aligned}
\mathbb{E}[\|v^{(T)}\|_D] &\lesssim \sum_{t=1}^T \frac{\eta}{\sqrt{t}} (\|b\|_D + \|A\|_{\mathbb{F}}\|A\| \mathbb{E}[\|x^{(t)}\|]) \\
&\lesssim \eta\sqrt{T}\|b\|_D + \sum_{t=1}^T \frac{\eta}{\sqrt{t}} \|A\|_{\mathbb{F}}\|A\| \mathbb{E}[\|x^{(t)}\|] \\
&\lesssim \eta\sqrt{T}\|b\|_D + \sum_{t=1}^T \|x^*\| \frac{\varepsilon}{\sqrt{t}} \sqrt{\log \frac{1}{\varepsilon}} \left(1 + \sqrt{\frac{\varepsilon\|A\|_{\mathbb{F}}\|A\|}{(\sigma^2+\lambda)\sqrt{t}} \sqrt{\log \frac{1}{\varepsilon}}}\right) \\
&\lesssim \eta\sqrt{T}\|b\|_D + \|x^*\| \varepsilon \sqrt{T \log \frac{1}{\varepsilon}} + \|x^*\| \sqrt{\frac{\varepsilon^3\|A\|_{\mathbb{F}}\|A\|\sqrt{T}}{(\sigma^2+\lambda)}} \left(\log \frac{1}{\varepsilon}\right)^{\frac{3}{2}} \\
&\lesssim \frac{\|b\|_D}{\sigma^2+\lambda} \log \frac{1}{\varepsilon} + \|x^*\| \frac{\|A\|_{\mathbb{F}}\|A\|}{\sigma^2+\lambda} \log \frac{1}{\varepsilon} + \|x^*\| \frac{\varepsilon\|A\|_{\mathbb{F}}\|A\|}{\sigma^2+\lambda} \log \frac{1}{\varepsilon} \\
&\lesssim \|b\|_D \frac{1}{\sigma^2+\lambda} \log \frac{1}{\varepsilon} + \|x^*\| \frac{\|A\|_{\mathbb{F}}\|A\|}{\sigma^2+\lambda} \log \frac{1}{\varepsilon}. \tag{6}
\end{aligned}$$

So, we can bound our cancellation constant. By union bounding, we have that with probability ≥ 0.9 , $\|x^{(T)} - x^*\| \leq \varepsilon\|x^*\|$ and the above bound on $\|v^{(T)}\|_D$ holds up to constant factors. When both those bounds hold, we have

$$\begin{aligned}
\Delta = \frac{\|v^{(T)}\|_D^2}{\|x^{(T)}\|^2} &\leq \frac{\|v^{(T)}\|_D^2}{\|x^*\|^2(1-\varepsilon)^2} \lesssim \frac{1}{\|x^*\|^2} \left(\|b\|_D^2 \frac{1}{(\sigma^2+\lambda)^2} \log^2 \frac{1}{\varepsilon} + \|x^*\|^2 \frac{\|A\|_{\mathbb{F}}^2\|A\|^2}{(\sigma^2+\lambda)^2} \log^2 \frac{1}{\varepsilon} \right) \\
&= \frac{\|b\|_D^2}{\|x^*\|^2} \frac{1}{(\sigma^2+\lambda)^2} \log^2 \frac{1}{\varepsilon} + \frac{\|A\|_{\mathbb{F}}^2\|A\|^2}{(\sigma^2+\lambda)^2} \log^2 \frac{1}{\varepsilon}. \tag{7}
\end{aligned}$$

To translate the $\frac{\|b\|_D^2}{\|x^*\|^2}$ in the output to a more intuitive parameter, we use that $\|b\|_D^2 = \|Db\|^2 \leq \|D\|^2\|b\|^2 \leq \|A\|^2\|b\|^2$ and that

$$\|x^*\| = \|(A^\dagger A + \lambda I)^{-1} A^\dagger (AA^+ b)\| \geq \frac{\|A\|}{\|A\|^2 + \lambda} \|AA^+ b\| = \Theta\left(\frac{1}{\|A\|} \|AA^+ b\|\right)$$

to conclude that

$$\Delta \lesssim \frac{\|A\|_{\mathbb{F}}^2\|A\|^2}{(\sigma^2+\lambda)^2} \log^2 \frac{1}{\varepsilon} + \frac{\|A\|^4}{(\sigma^2+\lambda)^2} \frac{\|b\|^2}{\|AA^+ b\|^2} \log^2 \frac{1}{\varepsilon}. \tag{8}$$

2.4 Extending to non-sparse b : Proof of Theorem 1.1

In previous sections, we have shown how to solve our regularized regression problem for sparse b : from Proposition 2.3, performing SGD for $T \asymp \frac{\|A\|_{\mathbb{F}}^2\|A\|^2}{(\sigma^2+\lambda)^2\varepsilon^2} \log \frac{1}{\varepsilon}$ iterations outputs an x with the desired error bound; from Lemma 2.2, it takes $\mathcal{O}\left(\frac{\|A\|_{\mathbb{F}}^2}{\|A\|^2} T(T + \|b\|_0)\right)$ time to

output x as a sparse description; and from Section 2.3, we have sample and query access to that output x given its sparse description.

Now, all that remains is to extend this work to the case that b is non-sparse. In this case, we will simply replace b with a sparse \hat{b} that behaves similarly, and show that running SGD with this value of \hat{b} gives all the same results. The sparsity of \hat{b} will be $\mathcal{O}\left(\frac{\|A\|_F^2 \|A\|^2}{\sigma^4 \varepsilon^2} \frac{\|b\|^2}{\|AA+b\|^2}\right)$, giving a total runtime of

$$\mathcal{O}\left(\frac{\|A\|_F^6 \|A\|^2}{(\sigma^2 + \lambda)^4 \varepsilon^4} \left(\frac{\|b\|^2}{\|AA+b\|^2} + \log \frac{1}{\varepsilon}\right) \log \frac{1}{\varepsilon}\right)$$

The crucial observation for sparsifying b is that we can use importance sampling to approximate the matrix product $A^\dagger b$, which suffices to approximate the solution x^* .⁸

Lemma 2.7 (Matrix multiplication to Frobenius norm error, [DKM06, Lemma 4]). *Consider $X \in \mathbb{C}^{m \times n}$, $Y \in \mathbb{C}^{m \times p}$, and let $S \in \mathbb{C}^{s \times m}$ be an importance sampling matrix for X . That is, let each $S_{i,*}$ be independently sampled to be $\frac{\|X\|_F^2}{s \|X_{i,*}\|^2} e_i$ with probability $\frac{\|X_{i,*}\|^2}{\|X\|_F^2}$. Then*

$$\begin{aligned} \mathbb{E}[\|X^\dagger S^\dagger S Y - X^\dagger Y\|_F^2] &\leq \frac{1}{s} \|X\|_F^2 \|Y\|_F^2 \text{ and} \\ \mathbb{E}\left[\sum_{i=1}^s \|[SX]_{i,*}\|^2 \|[SY]_{i,*}\|^2\right] &\leq \frac{1}{s} \|X\|_F^2 \|Y\|_F^2. \end{aligned}$$

We have $\text{SQ}(A)$, so we can use Lemma 2.7 with $s \leftarrow \frac{\|A\|_F^2 \|A\|^2}{(\sigma^2 + \lambda)^2 \varepsilon^2} \frac{\|b\|^2}{\|AA+b\|^2}$, $X \leftarrow A$, and $Y \leftarrow b$, to find an S in $\mathcal{O}(s)$ time that satisfies the guarantees

$$\|A^\dagger S^\dagger S b - A^\dagger b\| \leq \frac{(\sigma^2 + \lambda) \varepsilon \|AA+b\|}{\|A\|_F \|A\| \|b\|} \|A\|_F \|b\| \lesssim \varepsilon (\sigma^2 + \lambda) \|x^*\| \text{ and} \quad (9)$$

$$\sum_{i=1}^s \|[SA]_{i,\cdot}\|^2 \|[Sb]_{i,\cdot}\|^2 \leq \frac{(\sigma^2 + \lambda)^2 \varepsilon^2 \|AA+b\|^2}{\|A\|_F^2 \|A\|^2 \|b\|^2} \|A\|_F^2 \|b\|^2 \lesssim \varepsilon^2 (\sigma^2 + \lambda)^2 \|x^*\|^2 \quad (10)$$

with probability ≥ 0.99 . (Above, we used that, since $x^* = (A^\dagger A + \lambda I)^+ A^\dagger b$, $\|x^*\| \geq \frac{\|A\|}{\|A\|^2 + \lambda} \|AA+b\|$, and that $\lambda \lesssim \|A\|^2$.) Assuming this holds, we can perform SGD as in Proposition 2.3 on $\hat{b} := S^\dagger S b$ (which is s -sparse) to find an x such that $\|x - \hat{x}^*\| \leq \varepsilon \|\hat{x}^*\|$, where \hat{x}^* is the optimum $(A^\dagger A + \lambda I)^{-1} A^\dagger \hat{b}$. This implies that $\|x - x^*\| \lesssim \varepsilon \|x^*\|$, since

$$\|\hat{x}^* - x^*\| = \|(A^\dagger A + \lambda I)^+ A^\dagger (\hat{b} - b)\| \leq \frac{1}{\sigma^2 + \lambda} \|A^\dagger (\hat{b} - b)\| \lesssim \varepsilon \|x^*\|. \quad (11)$$

To bound the runtimes of $\text{SQ}(x)$, we modify the analysis of Δ from Section 2.3: recalling from Eq. (7), we have that, with probability ≥ 0.9 ,

$$\Delta \lesssim \frac{\|A\|_F^2 \|A\|^2}{(\sigma^2 + \lambda)^2} \log^2 \frac{1}{\varepsilon} + \frac{\|\hat{b}\|_D^2}{\|\hat{x}^*\|^2} \frac{1}{(\sigma^2 + \lambda)^2} \log^2 \frac{1}{\varepsilon}.$$

⁸It is straightforward to apply the tool in \mathbb{R} to \mathbb{C} via doubling the size of the dimension.

Notice that, by Eqs. (10) and (11),

$$\frac{\|\hat{b}\|_D^2}{\|\hat{x}^*\|^2} \leq \frac{\|\hat{b}\|_D^2}{\|x^*\|^2(1-\varepsilon)^2} = \frac{\sum_{i=1}^m \|A_{i,*}\|^2 |\hat{b}_i|^2}{\|x^*\|^2(1-\varepsilon)^2} \lesssim \frac{\varepsilon^2(\sigma^2 + \lambda)^2 \|x^*\|^2}{\|x^*\|^2(1-\varepsilon)^2} \lesssim \varepsilon^2(\sigma^2 + \lambda)^2,$$

so

$$\Delta \lesssim \frac{\|A\|_F^2 \|A\|^2}{(\sigma^2 + \lambda)^2} \log^2 \frac{1}{\varepsilon} + \varepsilon^2 \log^2 \frac{1}{\varepsilon} \lesssim \frac{\|A\|_F^2 \|A\|^2}{(\sigma^2 + \lambda)^2} \log^2 \frac{1}{\varepsilon}.$$

Using Lemma 2.6, the time it takes to respond to a query to $\text{SQ}(x^{(T)})$ is $(T + \|\hat{b}\|_0)^2 \Delta$, which gives the runtime in Theorem 1.1.

Acknowledgments

E.T. thanks Kevin Tian immensely for discussions integral to these results.

A.G. acknowledges funding provided by Samsung Electronics Co., Ltd., for the project “The Computational Power of Sampling on Quantum Computers”, and additional support by the Institute for Quantum Information and Matter, an NSF Physics Frontiers Center (NSF Grant PHY-1733907), as well as support by ERC Consolidator Grant QPROGRESS and by QuantERA project QuantAlgo 680-91-034. Z.S. was partially supported by Schmidt Foundation and Simons Foundation. E.T. is supported by the National Science Foundation Graduate Research Fellowship Program under Grant No. DGE-1762114.

References

- [Aar15] Scott Aaronson. [Read the fine print](#). *Nature Physics*, 11(4):291, 2015.
- [AGJO⁺15] Srinivasan Arunachalam, Vlad Gheorghiu, Tomas Jochym-O’Connor, Michele Mosca, and Priyaa Varshinee Srinivasan. [On the robustness of bucket brigade quantum RAM](#). *New Journal of Physics*, 17(12):123010, 2015. arXiv: [1502.03450](#)
- [Bub15] Sébastien Bubeck. [Convex optimization: Algorithms and complexity](#). *Foundations and Trends in Machine Learning*, 8(3–4):231–357, 2015. arXiv: [1405.4980](#)
- [BWP⁺17] Jacob Biamonte, Peter Wittek, Nicola Pancotti, Patrick Rebentrost, Nathan Wiebe, and Seth Lloyd. [Quantum machine learning](#). *Nature*, 549:195–202, 2017. arXiv: [1611.09347](#)
- [CGJ19] Shantanav Chakraborty, András Gilyén, and Stacey Jeffery. [The power of block-encoded matrix powers: improved regression techniques via faster Hamiltonian simulation](#). In *Proceedings of the 46th International Colloquium on Automata, Languages, and Programming (ICALP)*, pages 33:1–33:14, 2019. arXiv: [1804.01973](#)

- [CGL⁺20] Nai-Hui Chia, András Gilyén, Tongyang Li, Han-Hsuan Lin, Ewin Tang, and Chunhao Wang. [Sampling-based sublinear low-rank matrix arithmetic framework for dequantizing quantum machine learning](#). In *Proceedings of the 52nd ACM Symposium on the Theory of Computing (STOC)*, page 387–400, 2020. arXiv: [1910.06151](#)
- [Chi09] Andrew M Childs. [Equation solving by simulation](#). *Nature Physics*, 5(12):861–861, 2009.
- [CHI⁺18] Carlo Ciliberto, Mark Herbster, Alessandro Davide Ialongo, Massimiliano Pontil, Andrea Rocchetto, Simone Severini, and Leonard Wossnig. [Quantum machine learning: a classical perspective](#). *Proceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences*, 474(2209):20170551, 2018. arXiv: [1707.08561](#)
- [DHM⁺18] Danial Dervovic, Mark Herbster, Peter Mountney, Simone Severini, Nairi Usher, and Leonard Wossnig. [Quantum linear systems algorithms: a primer](#). arXiv: [1802.08227](#), 2018.
- [DKM06] Petros Drineas, Ravi Kannan, and Michael W Mahoney. [Fast Monte Carlo algorithms for matrices II: Computing a low-rank approximation to a matrix](#). *SIAM Journal on computing*, 36(1):158–183, 2006.
- [FGKS15] Roy Frostig, Rong Ge, Sham Kakade, and Aaron Sidford. [Un-regularizing: approximate proximal point and faster stochastic algorithms for empirical risk minimization](#). In *International Conference on Machine Learning*, pages 2540–2548, 2015. arXiv: [1506.07512](#)
- [GLM08] Vittorio Giovannetti, Seth Lloyd, and Lorenzo Maccone. [Quantum random access memory](#). *Physical Review Letters*, 100(16):160501, 2008. arXiv: [0708.1879](#)
- [GS18] Neha Gupta and Aaron Sidford. [Exploiting numerical sparsity for efficient learning: faster eigenvector computation and regression](#). In *Advances in Neural Information Processing Systems*, pages 5269–5278, 2018. arXiv: [1811.10866](#)
- [GSLW19] András Gilyén, Yuan Su, Guang Hao Low, and Nathan Wiebe. [Quantum singular value transformation and beyond: exponential improvements for quantum matrix arithmetics](#). In *Proceedings of the 51st ACM Symposium on the Theory of Computing (STOC)*, pages 193–204, 2019. arXiv: [1806.01838](#)
- [HHL09] Aram W. Harrow, Avinatan Hassidim, and Seth Lloyd. [Quantum algorithm for linear systems of equations](#). *Physical Review Letters*, 103(15):150502, 2009. arXiv: [0811.3171](#)
- [KP17] Iordanis Kerenidis and Anupam Prakash. [Quantum recommendation systems](#). In *Proceedings of the 8th Innovations in Theoretical Computer Science Conference (ITCS)*, pages 49:1–49:21, 2017. arXiv: [1603.08675](#)

- [MB11] Eric Moulines and Francis R. Bach. [Non-asymptotic analysis of stochastic approximation algorithms for machine learning](#). In *Advances in Neural Information Processing Systems*, pages 451–459, 2011.
- [Pra14] Anupam Prakash. [Quantum Algorithms for Linear Algebra and Machine Learning](#). PhD thesis, University of California at Berkeley, 2014.
- [Pre18] John Preskill. [Quantum Computing in the NISQ era and beyond](#). *Quantum*, 2:79, 2018. arXiv: [1801.00862](#)
- [RML14] Patrick Rebentrost, Masoud Mohseni, and Seth Lloyd. [Quantum support vector machine for big data classification](#). *Physical Review Letters*, 113(13):130503, 2014. arXiv: [1307.0471](#)
- [Tan19] Ewin Tang. [A quantum-inspired classical algorithm for recommendation systems](#). In *Proceedings of the 51st ACM Symposium on the Theory of Computing (STOC)*, pages 217–228, 2019. arXiv: [1807.04271](#)
- [WZP18] Leonard Wossnig, Zhikuan Zhao, and Anupam Prakash. [Quantum linear system algorithm for dense matrices](#). *Physical Review Letters*, 120(5):050502, 2018. arXiv: [1704.06174](#)