

Near-Optimal Decremental Approximate Multi-Source Shortest Paths

Jakub Łącki
Google Research
jłacki@google.com

Yasamin Nazari
Johns Hopkins University*
ynazari@jhu.edu

Abstract

We provide new algorithms for maintaining approximate distances in a weighted undirected graph $G = (V, E)$ subject to edge deletions. Our first result is an algorithm that maintains $(1 + \epsilon)$ -approximate distances from a set of s sources in $\tilde{O}(sm)$ total update time, assuming that $s = n^{\Omega(1)}$, $\epsilon = \Omega(1)$ and $|E| = n^{1+\Omega(1)}$. This matches the best known static algorithm, up to polylogarithmic factors for a wide range of settings. The currently best known algorithm for the problem is obtained by running the single-source algorithm of [Henzinger, Krinninger and Nanongkai, FOCS'14] independently from each source. Our result improves over the update time bound of this solution by removing a $2^{\tilde{O}(\log^{3/4} n)}$ factor. Additionally, we can maintain a $(1 + \epsilon)$ -approximate single-source shortest paths with amortized update time of $2^{\tilde{O}(\sqrt{\log n})}$, when $0 < \epsilon < 1$ is a constant and $|E| = n2^{\tilde{O}(\sqrt{\log n})}$. This improves over the best known update time of $2^{\tilde{O}(\log^{3/4} n)}$ by [Henzinger, Krinninger and Nanongkai, FOCS'14].

Furthermore, for any integer $k \geq 1$ we give an algorithm for maintaining $(2k - 1)(1 + \epsilon)$ -approximate all-pairs-shortest-paths, in $\tilde{O}(mn^{1/k})$ total update time and $O(k)$ query time¹. This improves over the result of [Chechik, FOCS'18] in a twofold way. Namely, we improve the total update time bound by removing an $n^{o(1)}$ factor and reduce the query time from $O(\log \log(nW))$ to $O(k)$.

Our results are based on a new decremental hopset construction that may be of independent interest.

*This work was conducted in part while the author was an intern at Google.

¹Throughout this paper we use the notation $\tilde{O}(f(n))$ to hide factors of $O(\text{polylog}(f(n)))$.

1 Introduction

A graph algorithm is called dynamic if it supports answering *queries* about a graph which is undergoing modifications, or, as we say in the following, *updates*. Each update is an edge deletion, insertion, or a weight change. In this paper, we are interested in designing *decremental* algorithms for distance problems in weighted graphs. In a decremental setting, the updates are only edge deletions or weight increases. This is as opposed to an *incremental* setting in which edges can be inserted, or a *fully dynamic* setting, in which we have both insertions and deletions.

We study the fundamental problem of maintaining shortest paths from a fixed set S of multiple sources (MSSP), which is a generalization of the all-pairs shortest path problem (APSP). In particular, given a weighted graph $G = (V, E, w)$, we need to support the following operations: DELETE((u, v)), where $(u, v) \in E$, which removes the edge (u, v) , DISTANCE(s, u), which returns an (approximate) distance between a source s and any $u \in V$, and INCREASE($(u, v), \delta$), which increases the weight of the edge (u, v) by $\delta > 0$.

The best known algorithm for maintaining exact distances under deletions takes $O(mn)$ total update time [SE81, Kin99], even if we limit ourselves to unweighted and undirected graphs. In fact, this bound matches a widely believed conditional lower bound [HKNS15]. Hence a large body of work [Ber09, BR11, Che18, HKN14a, RZ12, HKN14b, HKN17] focused on maintaining *approximate* distances. Allowing approximate distances enabled significant speedups in the running time. Following this line of work, we provide efficient decremental algorithms for maintaining $(1 + \epsilon)$ -approximate SSSP and MSSP and $(2k - 1)(1 + \epsilon)$ -approximate APSP in *weighted undirected graphs*.

MSSP. Our first result is an algorithm for multi-source shortest paths.

Theorem 1 (MSSP). *There is a data structure which given a weighted undirected graph $G = (V, E)$ explicitly maintains $(1 + \epsilon)$ -approximate distances from a set of s sources in G under edge deletions. Assuming that $|E| = n^{1 + \Omega(1)}$ and $s = n^{\Omega(1)}$, the total expected update time is $\tilde{O}(sm)$.*

Note that the total update time matches (up to polylogarithmic factors) the running time of the best known static algorithm for computing reachability from s sources, as long as $m \cdot s$ is smaller than the time needed to multiply two $n \times n$ matrices, that is $ms = n^\delta$ where δ is a constant such that $1 < \delta < 2.37$. Our algorithm also improves upon a solution obtained by running the algorithm of Henzinger, Krinninger and Nanongkai [HKN14a] independently from each source by removing a $n^{o(1)}$ factor from the total update time bound.

We note that in the general case, i.e., for sparse graphs, the update bound of our algorithm is $O(sm n^{o(1)})$, which is similar to the bound obtained in [HKN14a].

SSSP. Our next result is an algorithm for single-source shortest paths with an improved amortized update time in comparison to the state-of-the-art result of [HKN16]. In particular, we have,

Theorem 2. *Given an undirected and weighted graph $G = (V, E)$, there is data structure for maintaining $(1 + \epsilon)$ -approximate distances from a source $s_0 \in V$ under edge deletions, where $0 < \epsilon < 1$ is a constant and $|E| = n \cdot 2^{\tilde{\Omega}(\sqrt{\log n})}$, with the total update time of $\tilde{O}(m \cdot 2^{\tilde{O}(\sqrt{\log n})})$, and with $O(1)$ query time.*

Note that in this theorem and in our other results we maintain a data structure that is randomized and works against an *oblivious adversary*. The amortized update time of our algorithm over all m deletions is $2^{\tilde{O}(\sqrt{\log n})}$, which is a *super-polynomial* improvement over the best currently known algorithm of [HKN16], whose amortized update time is $2^{\tilde{O}(\sqrt{\log n})}$. Observe that for any constant $c > 0$, $2^{\tilde{O}(\sqrt{\log n})} = o((2^{\tilde{O}(\log^{3/4} n)})^c)$.

APSP. In Section 4.2, we will show that by maintaining both a hopset and a Thorup-Zwick distance oracle we can get the following tradeoffs for approximating distance between any pair of nodes:

Theorem 3 (Approximate APSP). *For any integer $k \geq 1$, there is a data structure which can answer $(2k - 1)(1 + \epsilon)$ -approximate distance queries in a given a weighted undirected graph $G = (V, E, w)$ subject to edge deletions. The total expected update time over any sequence of edge deletions is $\tilde{O}(mn^{1/k})$ and the expected size of the data structure is $\tilde{O}(m + n^{1+1/k})$. Each query for the distance between two vertices is answered in $O(k)$ worst-case time.*

The best known bounds for approximating APSP with the similar stretch before this work is due to [Che18]. The total update time in [Che18] is $\tilde{O}(mn^{1/k+o(1)})$, and the query time is $O(\log \log(nW))$, where W is the largest weight. Our update time improves over this bound by a factor of $n^{o(1)}$. In addition, the query time of our algorithm is independent of n or the weights. Prior to [Che18], Roditty and Zwick [RZ04] gave an algorithm for maintaining Thorup-Zwick distance oracles in total time $\tilde{O}(mn)$, stretch $(2k - 1)(1 + \epsilon)$ and $O(k)$ query time for *unweighted graphs*. Later on, Bernstein and Roditty [BR11] gave a decremental algorithm for maintaining Thorup-Zwick distance oracles in $O(n^{2+1/k+o(1)})$ time using emulators also only for *unweighted graphs*.

1.1 Hopsets

One fundamental tool that we utilize for obtaining these bound is a hopset with small hopbound. Hopsets, which were originally defined by [Coh00], are widely used in distance related problems in various settings, such as parallel shortest path computation [Coh00, MPVX15, EGN19, EN19b], distributed shortest path computation [EN19a, Nan14], routing tables [EN18] and distance sketches [EN18, DN19]. Given a weighted undirected graph $G = (V, E, w)$, a $(\beta, 1 + \epsilon)$ -hopset H with *hopbound* β , is a set of edges added to G such that for any pair of nodes $u, v \in V$, there is a path with at most β hops in $G \cup H$ with length within $(1 + \epsilon)$ of the shortest path between u and v in G (see Definition 1 for a formal statement). The approximation ratio is also referred to as the *stretch*. Once the hopset edges are computed, they can be used in speeding up approximate distance computation in a time that is dependent on the hopbound. That is why we are generally interested in a small hopbound, ideally polylogarithmic. We would also like to avoid adding too many edges.

Most of previous work on dynamic distance computation are based on algorithms constructing a sparse *emulator* (e.g. [Ber09, BR11, Che18]). For a graph $G = (V, E)$, an emulator $H' = (V, E')$ is a graph such that for any pair of nodes $x, y \in V$, there is a path in H' that approximates the distance between x and y on G (possibly with both multiplicative and additive factors). While some of the previous work implicitly use a hopbounded structure on their emulator for improved running time [Ber09, Che18], with the exception of the work by [HKN14a] hopsets are not explicitly studied in dynamic settings. Therefore their true power in these settings is not very well-understood.

Our algorithms are based on hopsets of [EN19b], and they cover a wide range of hopbound/running time/size tradeoffs. By efficiently maintaining hopsets with a small (polylogarithmic) hopbound, we are able to get near-optimal bounds for $(1 + \epsilon)$ -approximate MSSP and $(2k - 1)(1 + \epsilon)$ -approximate APSP. Our decremental hopset algorithm is summarized in the following result.

Theorem 4. *Given an undirected graph $G = (V, E)$ with polynomial weights², subject to edge deletions, we can maintain a $(\beta, 1 + \epsilon)$ -hopset with total update time $\tilde{O}(\frac{\beta}{\epsilon} \cdot (m + n^{1+1/2^k-1})n^\rho)$, where $\beta = O(\frac{\log n}{\epsilon} \cdot (k + 1/\rho))^{k+1/\rho+1}$, $0 < \epsilon < 1$ and $\frac{2}{2^k-1} < \rho < 1$.*

²If weights are not polynomial a factor the $\log n$ factor will be replace with $\log W$, and a factor of $\log W$ will be added to the update time.

As we shall see the hopsets of [EN19b] and emulators of [TZ06] are similar in the clustering procedure, but their analysis is different. More importantly, the efficient *dynamic algorithms* for maintaining emulators and hopsets have some significant differences. At a high-level, an emulator approximates distances without using the original graph edges and hence we can restrict the computation to a sparser graph, whereas for using and maintaining hopsets we need to use the edges in the original graph as well. On the other hand, hopsets allows for faster computation because we can restrict our attention to a *bounded hop neighborhood*. One challenge in the decremental implementation of both of these objects is the fact by definition we have to *insert* edges. How we handle such insertions is also different for these two objects. In case of emulators, one would need to argue that the overall decrease in distances (think of a potential function) after each update is bounded. This is harder to argue for hopsets since we are not only considering a sparse graph. Instead, in our decremental hopset, we use an idea similar to the monotone ES tree idea by [HKN14a] to handle the insertions.

1.2 Preliminaries and Notation

Given a weighted undirected graph $G = (V, E, w)$, and a pair $u, v \in V$ we denote the (weighted) shortest path distance by $d_G(u, v)$. We denote by $d_G^{(h)}(u, v)$ the length of the shortest path between u and v among the paths that use at most h -hops, and call this the h -hop limited distance between u and v .

Definition 1. Let $G = (V, E, w)$ be a weighted undirected graph. Fix $d, \epsilon > 0$ and an integer $\beta \geq 1$. A $(d, \beta, 1 + \epsilon)$ -hopset is a graph $H = (V, E(H), w_H)$, such that:

- For each $(u, v) \in E(H)$, $w_H(u, v) \geq d_G(u, v)$.
- For each $u, v \in V$, such that $d_G(u, v) \leq d$, we have $d_{G \cup H}^{(\beta)}(u, v) \leq (1 + \epsilon)d_G(u, v)$.

We say that β is the *hopbound* of the hopset and $1 + \epsilon$ is the *stretch* of the hopset. We also use $(\beta, 1 + \epsilon)$ -hopset to denote a $(\infty, \beta, 1 + \epsilon)$ -hopset. Finally, for any finite d , we say that a $(d, \beta, 1 + \epsilon)$ -hopset is a *d -restricted hopset*.

In analyzing dynamic algorithms we sometimes also use a time subscript t to denote a distance (or a weight) after the first t updates. In particular we use $d_{t,G}(u, v)$ to denote the distance between u and v after t updates, and similarly use $d_{t,G}^{(h)}(u, v)$ to denote h -hop limited distance between u and v at time t .

2 Overview of Our Algorithms

Our algorithms for maintaining approximate distances under edge deletions are obtained by decrementally maintaining a hopset with a polylogarithmic hopbound. In the following we first describe a technique borrowed from distributed/parallel models (e.g. [Coh00, EN19a]). We will then explain how this can be combined with various dynamic tools in order to obtain an efficient hopset construction.

Our algorithm maintains a sequence of graphs $H_1, \dots, H_{\log W}$ with the following property. For each $1 \leq j \leq \log W$, $H_1 \cup \dots \cup H_j$ is a $(2^j, \beta, (1 + \epsilon)^j)$ -hopset of G . Note that for $1 \leq j \leq \log \beta$ we can set $H_j = \emptyset$, since G covers these scales (the edge weights in G are at least 1, so if $d_G(u, v) \leq \beta$, there is a shortest path between u and v of at most β hops).

Instead of computing each H_j separately, we use $G \cup \bigcup_{r=\log \beta}^{j-1} H_r$ to construct H_j . Note that by our assumption it suffices if H_j is a hopset for paths of length $\in [2^{j-1}, 2^j]$, since shorter paths are already taken care of by H_1, \dots, H_{j-1} . The important observation is that each path π of length $\in [2^{j-1}, 2^j]$ in G can be approximated (within a $(1 + \epsilon)^{j-1}$ factor) by a path of $2\beta + 1$ hops in $G \cup \bigcup_{r=\log \beta}^{j-1} H_r$. This follows from the fact that any such π can be obtained by concatenating paths π_1, π_2 and π_3 , where π_1 and π_3 have length at most 2^{j-1} (so we can apply the property of a 2^{j-1} -restricted hopset) and π_2 consists of a single edge.

Hence, the basic subproblem that we need to solve for each distance scale $[2^{j-1}, 2^j]$ is computing a hopset for distances between $[2^{j-1}, 2^j]$, knowing that the length of each such shortest path in G can be approximated by a path in $G \cup \bigcup_{r=\log \beta}^{j-1} H_r$ consisting of at most $2\beta + 1$ hops. Extending this idea to dynamic settings requires using specific properties of these hopsets and the scaling procedure. Formally, we show the following.

Lemma 5. *Consider a graph $G = (V, E, w)$ subject to edge deletions. Assume that $\bar{H}_j := H_1, \dots, H_j$ is a $(2^j, \beta, (1 + \epsilon)^j)$ -hopset of G , which is updated dynamically, as the edges of G are deleted.*

Then, there is a data structure, which, given the sequence of changes to G and $\bar{H}_j := H_1 \cup \dots \cup H_j$, maintains a graph H_{j+1} , such that $\bar{H}_j \cup H_{j+1}$ is a $(2^{j+1}, \beta, (1 + \epsilon)^{j+1})$ -hopset of G .

The data structure can be maintained in $\tilde{O}((m + \Delta)n^\rho \cdot \frac{\beta}{\epsilon})$ total time, where m is the initial size of G and Δ is the total number of edges inserted to \bar{H}_j over all updates, and $\beta = (\frac{1}{\epsilon \cdot \rho})^{O(1/\rho)}$, and $\rho < 1$ is a constant.

While this *path-doubling* idea has been used in parallel and distributed hopset constructions (e.g. [Coh00, EN19a, EN19b]), to the best of our knowledge this is their first application in dynamic settings. However for obtaining efficient decremental algorithms, we need to combine this idea with various tools. There are few technicalities in applying this idea in dynamic settings. One idea is using a scaling algorithm widely used in dynamic settings (e.g. [Ber09, BR11, HKN14a]) *repeatedly and iteratively* during the process of adding hopset edges.

We now describe the high-level idea behind the data structure. We first apply the following scaling scheme due to Klein and Subramanian [KS97], which, roughly speaking, says that finding shortest paths of length $\in [2^{j-1}, 2^j]$ and at most ℓ hops, can be (approximately) reduced to finding paths of length at most $O(\ell)$ in a graph with integral weights. This is done by a rounding procedure that adds a small additive factor $\frac{\epsilon_0 w(e)}{\ell}$ to each edge e . Then for a path of ℓ hops the overall stretch will be $(1 + \epsilon_0)$.

Lemma 6 ([KS97]). *Let $G = (V, E, w)$ be a weighted undirected graph. Let $R \geq 0$ and $l \geq 1$ be integers and $\epsilon_0 > 0$. We define the scaled graph to be a graph $\text{SCALE}(G, R, \epsilon_0, \ell) := (V, E, \hat{w})$, such that $\hat{w}(e) = \lceil \frac{w(e)}{\eta(R, \ell)} \rceil$, where $\eta(R, \ell) = \frac{\epsilon_0 R}{\ell}$.*

Then, for each edge $e \in E$ we have $\hat{w}(e) \leq w(e) + \epsilon_0 R$, and for any path π in G such that π has at most ℓ hops and weight $R \leq w(\pi) \leq 2R$, we have

- $\hat{w}(\pi) \leq \lceil 2\ell/\epsilon_0 \rceil$,
- $w(\pi) \leq \eta(R, \ell) \cdot \hat{w}(\pi) \leq (1 + \epsilon_0)w(\pi)$.

By using the above scaling in the construction of the data structure of Lemma 5, we can effectively reduce the problem that the data structure is solving to the problem of maintaining a $O(\beta)$ -restricted hopset in a graph with integral weights in a dynamic setting. Note that we set $\beta = \text{poly log } n$. Since there are edge insertion into the hopset, and hence each scale graph there are further technicalities in how these ideas can be combined in decremental settings. We will explain

later that for handling edge insertion we need to use another data structure called the monotone ES tree ([HKN16]). We need to show that by combining the estimates from these different data structures we still get a hopset with the desired properties.

We first describe the static hopset construction, and will then explain modifications needed for improving the update time.

2.1 Static Hopset Construction

In this section we outline the (static) hopset construction of Elkin and Neiman [EN19b] (which is similar to [HP19]). The construction is based on Thorup-Zwick emulators [TZ06]. We will later show how to use the construction in a dynamic setting.

Given a weighted graph $G = (V, E, w)$, and a parameter k , we first show the construction a hopset of size $O(n^{1+\frac{1}{2^k-1}})$ and hopbound $O((k/\epsilon)^k)$. We then show how to modify this algorithm in order to get a better running time at the cost of a worse stretch.

We define sets $V = A_0 \supseteq A_1 \supseteq \dots \supseteq A_k = \emptyset$. Let $\nu = \frac{1}{2^k-1}$. Each set A_{i+1} is obtained by sampling each element from A_i with probability $q_i = n^{-2^i \cdot \nu}$. Hence it can be shown that $E[|A_i|] = n^{1-2^{i-1}\nu}$.

For every vertex $u \in A_i \setminus A_{i+1}$, let $p(u) \in A_{i+1}$ be the closest node to set A_{i+1} . We define a *bunch* of u to be a set $B(u) := \{v \in A_i : d(u, v) < d(u, A_{i+1})\} \cup \{p(u)\}$. Also, we define a set $C(v)$, called the *cluster* of v such that if $v \in B(u)$ then $u \in C(v)$. It can easily be shown that clusters are *connected* in a sense that if a node $v \in C(u)$ then any node z on the shortest path between v and u is also in $C(u)$. As we will see, this property is important for bounding the running time. The hopset is obtained by adding edges (u, v) where $v \in B(u)$, and setting the weight to be $d(u, v)$.

The algorithm described will lead to a $((k/\epsilon)^k, 1 + \epsilon)$ -hopset, but the running time can be as large $O(mn)$. In order to resolve this, [EN19b] proposed an algorithm using modified sampling probabilities of $q_i = \max(n^{-2^i \cdot \nu}, n^{-\rho})$. Using this approach, the number of iterations becomes $k + 1/\rho + 1$, but this also increases the hopbound to $O((k + 1/\rho + 1)^{k+1/\rho+1})$.

Theorem 7 ([EN19b]). *There is an algorithm that given a weighted and undirected graph $G = (V, E)$, and $2 \leq k \leq \log \log n - 2$, $\frac{2}{2^k-1} < \rho < 1$ computes a $(\beta, 1 + \epsilon)$ -hopset of size $O(n^{1+\frac{1}{2^k-1}})$, where $\beta = O((\frac{k+1/\rho}{\epsilon})^{k+1/\rho+1})$. It runs in $O(\frac{n^\rho}{\rho}(m + n \log n))$ expected time.*

We use these properties as a black-box, but for completeness we sketch a proof for the hopset properties in Appendix A. One important component of this algorithm is the *modified Dijkstra's algorithm* that we will also utilize in our dynamic algorithms, that we will briefly review. This algorithm was presented by Thorup-Zwick [TZ05] and it allows us to construct the bunches and clusters for level i in $O((m+n \log n)/q_i)$ (expected) time. At a high-level this is done by making a modification to Dijkstra. In the original Dijkstra for each source $u \in A_i \setminus A_{i+1}$, at each iteration we consider an unvisited vertex v , and relax each incident edge (v, z) by setting $d(u, z) := \min\{d(u, z), d(u, v) + w(v, z)\}$. But in the modified algorithm this is done only if $d(u, v) + w(v, z) < d(z, A_{i+1})$. In other words each node z only "participates" in a shortest-path exploration from a source u only if $z \in B(u)$. Note that if $z \in B(u)$, all the nodes on the shortest path between u and z are considered. This will let us bound the running time by expected size of $B(u)$.

2.2 Maintaining d -Restricted Hopset Dynamically

In order to maintain a d -restricted hopset dynamically, we start with a decremental algorithm of Roditty and Zwick [RZ04]. Their algorithm is similar to the hopset construction of Elkin and

Neiman [EN19b] in that it also defines clusters and bunches based on a sequence of sets $V = A_0 \supseteq A_1 \supseteq \dots \supseteq A_k = \emptyset$. The main difference is that it uses a different sequence of sampling probabilities, which impacts the running time and stretch.

The algorithm of Roditty and Zwick [RZ04] can maintain clusters up to a given depth d , in a graph subject to edge deletion in $O(dmn^{1/k})$ total time. This in turn allows us to efficiently maintain a d -restricted hopset, as long as d is not too large. However, in order to use the algorithm of Roditty and Zwick [RZ04] in our setting, we need to make several modifications.

The first modification is mentioned above: we need to use different sampling probabilities, which impacts the running time. Still, this only affects the analysis, and the algorithm mostly remains the same.

The second modification is more subtle. While the algorithm of Roditty and Zwick [RZ04] only works in the decremental setting, in our case we need to extend it to handle edge *insertions*. This is because we run it on a graph $G \cup \bigcup_{r=\log \beta}^{j-1} H_r$ (after applying scaling of Lemma 6). While edges of G can only be deleted, new edges may be added to some hopsets H_r .

We deal with this issue as follows. The algorithm of Roditty and Zwick [RZ04] decrementally maintains a collection of single-source shortest path trees (up to a bounded depth) using the Even-Shiloach algorithm (ES-tree) [SE81]. We modify the algorithm by replacing each ES-tree, by a *monotone* ES-tree proposed by [HKN14a, HKN16]. The monotone ES-tree, in addition to supporting edge deletions, also supports edge insertion operation in a limited way. Namely, whenever an edge (u, v) is inserted and the insertion of the edge causes a distance decrease in the tree, we do not update the currently maintained distance estimates. This change keep the running time roughly the same as the decremental only setting. However, we need to argue that this does not impact the overall hopset stretch. We can show this by combining the static hopset analysis, with the ideas used in [HKN14a] and the scaling technique. In our final algorithm, we need to run this restricted hopset algorithm on the sequence of scaled graphs, so that we can utilize the smaller scale hopsets in a hierarchical way to get our improved update time.

We note that while the use of monotone ES tree and the structure of clusters in our construction is similar to [HKN14a], our algorithm has several important differences. Other than using a different and more general base (static) hopset, we use a different approach to maintain the hopset efficiently by using path doubling and maintaining the bunches on the *scaled graphs*. Among other things, in [HKN14a] a different notion of approximate ball is used that is rather more lossy³ with respect to the hopbound/stretch tradeoffs.

2.3 Decremental Approximate Distances

We now use our algorithm for decrementally maintaining a hopset with hopbound β , to maintain $(1 + \epsilon)$ -approximate distance from s sources in near-optimal time. We use the scaling technique one more time on the hopset to compute distances from each source. This approach, also called h -SSSP, is widely used for bounding the running time of an Even-Shiloach tree for approximating path of at most h hops [Ber09, KL20]. This leads to total update time of $\tilde{O}(s\beta m)$, for s sources, when $m = n^{1+\Omega(1)}$.

Finally, we utilize our hopsets for maintaining a $(2k - 1)(1 + \epsilon)$ -approximate APSP queries in total update time that almost matches the best-known static running time. This algorithm is based on maintaining Thorup-Zwick distance oracle [TZ05] more efficiently. At a high-level, we maintain *both* a $(\beta, 1 + \epsilon)$ -hopset and Thorup-Zwick distance oracle simultaneously, and balance out the time required for these two algorithms. The hopset is used to make improve the time required for maintaining the distance oracle from $O(mn)$ time to $O(\beta mn^{1/k})$ time.

³This is also on reason we get an improvement in amortized single-source shortest path update time.

3 Decremental Hopset

In this section we provide our decremental hopset algorithms. Our goal is to implement the hopset algorithm described in Section 2.1 dynamically. In Section 3.1, we explain how a modification of a result by Roditty-Zwick [RZ04] will lead to an algorithm for computing a d -restricted hopset. The running time of this algorithm is $O(dmn^\rho)$ (where $\rho < 1$ is a constant), which is undesirable for large values of d . Hence in Section 3.2.1, and Section 3.2 we show how we can improve the running time to $\tilde{O}(mn^\rho)$ using scaling and path-doubling ideas.

3.1 Maintaining a restricted hopset

In this section our goal is to maintain a decremental *restricted* hopset. This is done by adaptation of a decremental algorithm by [RZ04] that maintains the Thorup-Zwick distance oracles [TZ05] with stretch $(2k - 1)$ for pairs of nodes within distance d in $\tilde{O}(dmn^{1/k})$ total time. The only difference is that we change the sampling probabilities based on the hopset algorithm described in Section 2.1, and that in addition to computing clusters we also construct the hopset (as outlined in Section 2.1 as well). In Section 3.1 we argue that the algorithm of [RZ04] can be extended to construct a $(d, \beta, 1 + \epsilon)$ -hopset. Later in Section 3.2 we improve the running time by combining path doubling and scaling ideas with our restricted hopset algorithm.

At a high-level, the idea is to run Even-Shiloach [SE81] trees for each node $u \in A_i \setminus A_{i+1}$ to compute $B(u)$. In order to bound the running time, we use the same modification as in the modified Dijkstra algorithm, which allows us to bound the number of shortest path explorations that visit each node. However there are few challenges in using these ideas. First, while in the static algorithm each node overlaps with at most $\tilde{O}(n^\rho)$ clusters, in dynamic settings this holds at any point in time but does not immediately hold for a sequence of updates, since nodes keep on changing clusters. Also, it is not enough to construct Even-Shiloach trees from all nodes $w \in A_i \setminus A_{i+1}$ to form clusters $C(w)$, since after a deletion a node may join a new cluster and hence there could be *insertions* in each tree. Roditty and Zwick [RZ04] provided an algorithm that handles these issues. By extending their techniques we can maintain the clusters and hence bunches and hopset edges. Next, we sketch the algorithm and analysis of [RZ04] and explain how it can be extended for maintaining a restricted hopset. More details of the algorithm can be found in Appendix B.

We sample sets $V = A_0 \supseteq A_1 \supseteq \dots \supseteq A_k = \emptyset$ initially. The sets remain unchanged during the updates. Next, we need to maintain values $d(v, A_i), 1 \leq i \leq k - 1$ for all nodes $v \in V$. This can be performed by computing a shortest path tree rooted at a dummy node s_i connected to all nodes in A_i . Let $\hat{d} = (1 + \epsilon)d$. We can use the Even-Shiloach [SE81] algorithm up to depth \hat{d} to maintain all these distances in $O(\hat{d}m)$ time. The pivots $p(v), \forall v \in V$ can also be maintained in this process.

Maintaining the clusters. Recall that for $z \in A_i \setminus A_{i+1}$ we have $v \in C(z)$ if and only if $d(z, v) < d(v, A_{i+1})$. After each deletion, for each node v and the cluster centers z we first check whether the distance $d(z, v)$ has increased. If $d(z, v) \geq d(v, A_{i+1})$, v will be removed from $C(z)$. The more subtle part is adding nodes to new clusters. For each $0 \leq i < k$, we define a set X_i consisted of all vertices whose distance to A_i is increased as a result of a deletion, but where this distance is still at most \hat{d} . The sets X_i can be computed while maintaining $d(v, A_i)$.

Note that a node v would join $C(w)$ only after an increase in $d(v, A_{i+1})$. Using this observation, after each deletion for every $v \in X_{i+1}, z \in B_i(u) \setminus B_i(v)$, and each edge $(u, v) \in E$ we check if $d(z, u) + w(u, v) < d(v, A_{i+1})$. If yes, then v joins $C(z)$, and v is pushed to a priority queue $Q(z)$. These nodes join clusters z , but there may be other nodes that also need to join $C(z)$ as a result of this change. Hence after this initial phase, for each $z \in A_i \setminus A_{i+1}$ where $Q(z) \neq \emptyset$, we run the

modified Dijkstra’s algorithm. Recall that in the modified Dijkstra’s algorithm when we explore neighbors of a node x , we only relax an edge (x, y) if $d(x, y) + w(x, y) < d(x, A_i)$. Then [RZ04] show that this process correctly maintains the clusters. We then repeat this process for all the $k + 1/\rho + 1$ iterations.

The update time analysis is more complicated, and is a consequence of the following lemma, which is a straightforward extension of a proof in [RZ04]. We include the full proof in Appendix B.

Lemma 8. *For every $v \in V$ and $0 \leq i \leq k - 1$, the expected total number of times the edges incident on v are scanned over all trees for each $w \in A_i$ (i.e. trees on $C(w)$) is $O(\hat{d}/q_i)$, where q_i is the sub-sampling probability.*

By combining the analysis of the modified Dijkstra algorithms of [TZ05], Theorem 7, and Lemma 8, we can show that a d -restricted hopset with the following guarantees can be constructed:

Theorem 9. *Fix $\epsilon > 0, k \geq 2$ and $\rho \leq 1$. Given a graph $G = (V, E, w)$ with integer and polynomial weights, subject to edge deletions we can maintain a $(d, \beta, 1 + \epsilon)$ -hopset, with $\beta = O\left(\left(\frac{1}{\epsilon} \cdot (k + 1/\rho)\right)^{k+1/\rho+1}\right)$ in $O(d(m + n^{1+\frac{1}{2k-1}})n^\rho)$ total time. The algorithm works correctly with high probability.*

3.2 Improved running time via. scaling and monotone ES tree

Recall that our algorithm maintains a sequence of edge sets $H_{\log \beta}, \dots, H_{\log W}$, where for each $\log \beta \leq j \leq \log W$, $H_{\log \beta} \cup \dots \cup H_j$ is a 2^j -restricted hopset of G .

Instead of computing each H_j separately, we use $G \cup_{r=\log \beta}^{j-1} H_r$ to construct H_j . We observe that at the cost of some small approximation errors, any path of length $\in [2^{j-1}, 2^j)$ in G can be approximated by a path of at most $2\beta + 1$ hops in $G \cup_{r=\log \beta}^{j-1} H_r$. In this section, we prove the following mainlemma and in Section 3.3 we will explain how this leads to our final hopset for all scales. Formally, we show the following.

Lemma 5. *Consider a graph $G = (V, E, w)$ subject to edge deletions. Assume that $\bar{H}_j := H_1, \dots, H_j$ is a $(2^j, \beta, (1 + \epsilon)^j)$ -hopset of G , which is updated dynamically, as the edges of G are deleted.*

Then, there is a data structure, which, given the sequence of changes to G and $\bar{H}_j := H_1 \cup \dots \cup H_j$, maintains a graph H_{j+1} , such that $\bar{H}_j \cup H_{j+1}$ is a $(2^{j+1}, \beta, (1 + \epsilon)^{j+1})$ -hopset of G .

The data structure can be maintained in $\tilde{O}\left((m + \Delta)n^\rho \cdot \frac{\beta}{\epsilon}\right)$ total time, where m is the initial size of G and Δ is the total number of edges inserted to \bar{H}_j over all updates, and $\beta = \left(\frac{1}{\epsilon \rho}\right)^{O(1/\rho)}$, and $\rho < 1$ is a constant.

There are two main challenges that we need to address for proving this lemma. First, we would like to make the running time independent of d . To that end, we are going to run our algorithm on a rescaled graph, which would allow us to only maintain distances up to depth $O(\beta/\epsilon)$. This relies on having the 2^j -restricted hopset \bar{H}_j , which allows us to maintain the hopset \bar{H}_{j+1} . Second, while G is undergoing deletions, H_j may be undergoing edge *insertions*. In Section 3.2.1 we explain how such insertions can be handled using the monotone ES tree algorithm (based on [HKN14a]). In Section 3.2.3 we use the properties of this algorithm to prove Lemma 5.

First we observe that we can add hopset edges for smaller scales and use the added edges in computing distances for larger scales. In particular, assuming that we have added the hopset edges up to distances 2^j , we compute hopset edges for the scale $(2^j, 2^{j+1}]$ by only exploring $(2\beta + 1)$ -hop bounded distances in $G \cup_{r=\log \beta}^{j-1} H_r$. We formalize this idea in the following lemma.

Lemma 10. *Given a graph $G = (V, E)$, $0 < \epsilon_1 < 1$, the set of $(\beta, 1 + \epsilon_1)$ -hopsets H_r , $\log \beta \leq r < j$ for each distance scale $(2^r, 2^{r+1}]$, provides a $(1 + \epsilon_1)$ -approximate distance for any pair $x, y \in V$, where $d(x, y) \leq 2^{j+1}$ using paths of length $(2\beta + 1)$. In other words, $\cup_{r=\log \beta}^{j-1} H_r$ is a $(2^j, \beta, 1 + \epsilon_1)$ -hopset AND a $(2^{j+1}, 2\beta + 1, 1 + \epsilon_1)$ -hopset.*

Proof. We can show this by an induction on j . Let π be the shortest path between x and y on G . Then π can be divided into two segments, where for each segment there is a $(1 + \epsilon_1)$ -stretch path using edges in $G \cup_{r=\log \beta}^{j-1} H_r$. Let $[x, z]$ and $[z', y]$ be the segments on π each of which has length at most 2^{j-1} . In other words, z is the furthest point from x on π that has distance at most 2^{j-1} , and z' is the next point on π . Then we have,

$$\begin{aligned} d_{G \cup_{r=1}^{j-1} H_r}^{(2\beta+1)}(x, y) &\leq [d_{G \cup_{r=1}^{j-1} H_r}^{(\beta)}(x, z) + w(z, z') + d_{G \cup_{r=1}^{j-1} H_r}^{(\beta)}(z', y)] \\ &\leq (1 + \epsilon_1)d_G(x, z) + w(z, z') + (1 + \epsilon_1)d_G(z', y) \\ &\leq (1 + \epsilon_1)d_G(x, y) \end{aligned}$$

□

This implies that it is enough to compute $(2\beta + 1)$ -hop limited distances in restricted hopsets for *each* scale. For using this idea in dynamic settings we have to deal with some technicalities. We should show that we can combine the rounding with the modification needed for handling insertions.

We first start by showing how we can maintain distances from a single-source. Then use this algorithm from all to maintain the bunches $B(u)$ for all $u \in V$, which gives us a restricted hopset for each distance scale.

3.2.1 Handling edge insertions

In this section, we explain the monotone ES tree algorithm, and the running time of maintaining a single SSSP in the same setting as in Lemma 5. In section 3.2.3, we will prove that even though we are using the monotone ES tree algorithm, the stretch argument for the hopset will still hold. We show how to handle edge insertions by using a variant of the monotone ES-tree algorithm [HKN14a] (and further used in the hopset construction of [HKN16]). This algorithm is given as Algorithm 1. The idea in a monotone ES tree is that if an insertion of an edge (u, v) causes the level of a node v to decrease, we will not decrease the level. In this case we say the edge (u, v) and the node v are *stretched*. More formally, a node v is stretched when $L(v) > \min_{(x,v) \in E} L(x) + w(x, v)$.

We observe multiple properties of the monotone ES tree algorithm as observed by [HKN14a, HKN16] that will be helpful in analyzing the stretch later:

- The level of a node never decreases.
- Only an inserted edge can be stretched.
- While an edge is stretched, its level remains the same. In other words, a stretched edge is not going to get stretched again unless it is deleted (or get a distance increase).

Also observe that we never underestimate the distances. This is clearly true for any edge weights obtained by the rounding in Lemma 6. It is also easy to see this is true for the stretched edges for the following reason: For any node v , the algorithm maintains the invariant that $L(v) \geq \min_{(x,v) \in E} L(x) + w(x, v)$. In other words, $L(v)$ is either an estimate based on rounding that is at least $d_G(s, v)$ or it is larger than such an estimate.

Algorithm 1: Maintaining a monotone ES tree up to depth D on G . Note that edge deletion can be achieved by setting the edge weight to ∞ .

```

1 Function INIT( $G, s, D$ )
2    $E := E(G) \cup \{e_v = (s, v) : v \in V(G) \setminus \{s\}, w(e_v) = D + 1\}$  /* This ensures that
   distances are maintained up to level  $D$  */
3   for  $v \in V$  do
4      $L(v) := 0$ 
5   for  $v \in V$  do
6     UPDATE( $v$ )

7 Function INSERTEDGE( $(a, b), c$ )
8    $E := E \cup \{(a, b)\}$ 
9    $w(a, b) := \hat{c}$ 
10  UPDATE( $b$ )

11 Function UPDATE( $v$ )
12   $upd := \min_{(x,v) \in E} L(x) + w(x, v)$ 
13  if  $v = s$  or  $L(v) \geq upd$  then
14    /* Node  $v$  is stretched. Ignore the change and update parent of  $v$ . */
15    return
16   $L(v) := upd$ 
17  for  $(v, y) \in E(G)$  do
18    UPDATE( $y$ )

```

Lemma 11. *We can maintain Algorithm 1 in $O((m + \Delta)D)$ overall update time on a graph with m edges, where Δ is the number of edge insertions.*

Proof sketch. The running time analysis of the algorithm follows based on an argument similar to the analysis of the classic ES tree algorithm [SE81, Kin99]. The total time for updating distances up to a depth D is $O((m + \Delta)D)$, roughly speaking, since the edges incident to each node v are scanned any time level of each node changes. Since distances can only increase there can be at most D times for nodes with depth at most D to the source. Furthermore, Δ is the number of added edges that also need to be scanned in each update. By summing over all edges incident to all nodes the claim follows. \square

3.2.2 Single-scale data structures

We start by defining a scaled graph using Lemma 6 as follows: $G^j := \text{SCALE}(G \cup_{r=\log \beta}^{j-1} H_r, 2^j, \epsilon', 2\beta + 1)$. We first describe the operations performed on this scaled graph. We then explain how we can put things together for all scales to get the desired guarantees.

The key insight for scaling $G \cup_{r=\log \beta}^{j-1} H_r, 2^j$ is that we can obtain H_j by computing an $O(\ell)$ -restricted hopset of G^j (using the algorithm of Lemma 5) and scaling back the weights of the hopset edges.

In addition to the graph G undergoing deletions, our decremental algorithm maintains for each $1 \leq j \leq \log W$:

- The set $\bar{H}_j = H_1 \cup \dots \cup H_j$, union of all hopset edges for distance scales up to $[2^j, 2^{j+1}]$.

- The scaled graphs $\bar{G}^j = G^1 \cup \dots \cup G^j$.
- Data structure obtained by constructing an $O(\beta/\epsilon)$ -restricted hopsets of Section 3.1 on \bar{G}^j . We denote this data structure by D_j .

The data structure D_j is maintained by running the monotone ES tree algorithm in Section 3.2.1 on \bar{G}^j for all $v \in V$, to maintain the bunches $B(v)$. The level each of these monotone ES tree data structures corresponds to the minimum distance computed over all the scaled graphs. We need to consider the union of all smaller scales since a pair of nodes u, v may belong to a smaller scale at time $t - 1$, and we need to ensure that such estimates are maintained properly in the corresponding monotone ES tree.

Once each data structure D_j is initialized with a graph, it can execute a single operation $\text{UPDATE}(E^-, E^+)$, which updates the maintained graph by removing the edges of E^- and adding edges E^+ , in addition to maintaining the monotone ES tree using Algorithm 1. In other words, Lemma 5 involves the operations performed by $\text{UPDATE}(E^-, E^+)$. The operation returns a pair (H^-, H^+) of edge sets, where H^- is the set of edges that are removed from the hopset and H^+ is the set of edges added to the hopset as a result of the update. Note that a change in the weight of a hopset edge is equivalent to removing the edge and adding it with a new weight.

For maintaining the hopset, we have to update distances on all scaled graphs after each deletion. While we add hopset edges throughout the algorithm, these edges will *not reduce* the distances between nodes in the original graph, since they correspond to an existing path, whose length can only increase. However for a given pair of nodes $u, v \in V$, $d_{G \cup H}^{(h)}(u, v)$ (the distance between u and v using only paths with h hops) can *decrease* when we add hopset edges, and this could in turn cause an *insertions* or distance reductions in the scaled graphs. Therefore we need to also take these insertions into account in the running time.

The algorithm for maintaining all these distances (approximately) is as follows: we run the algorithm of Section 3.1 for distances bounded by $d = \lceil \ell/\epsilon_0 \rceil$ starting on $j = \log \beta, \dots, \log W$ in increasing order of j to compute hopset edges H_j . After processing all the changes in scaled graph G^j , we add the inserted edges to G^{j+1} . Then we process the changes in G^{j+1} by running the algorithm of Section 3.1 and repeat until all distance scales of covered. Note that as discussed in Section 3.1, when the distances increase a node may join a new cluster which will lead to an insertion in H and in turn insertions in a sequence of graphs G^j . We use an argument similar to Lemma 8 on each scaled graph to get the overall update time. In a way we can see the added edges passed to each scale as a set of batch distance increases, between the corresponding endpoints. This mean we are not exactly in the setting of [RZ04] where only one deletion occurs at each time, but the exact same analysis as in Lemma 8 still holds.

Algorithm 2: Updating the hopset after deleting an edge e .

```

1 Given  $0 < \epsilon_2 < 1$ , set  $d = \frac{2\beta+1}{\epsilon_2}$ .
2  $(E^-, E^+) := (\{e\}, \emptyset)$ 
3 for  $j = \lceil \log \beta \rceil, \dots, \lceil \log W \rceil$  do
4    $(E^-, E^+) := D_j.\text{UPDATE}(E^-, E^+)$ 
   /* Update  $\bar{G}^j = G^1 \cup \dots \cup G^j$  by maintaining the data structure of Lemma 5
      using Algorithm 1. */
5   Update  $H_j$  by adding edges of  $E^+$  and removing edges of  $E^-$ 

```

We summarized the algorithm obtained by maintaining this data structure over all scales in Algorithm 2. In Line 4 of Algorithm 2 the steps of Lemma 5 are performed. This step also involves

computing a d -restricted-hopset on $G \cup \bar{H}_j$. By Theorem 9 and by properties of the monotone ES tree algorithm the running time follows.

Running time (proof of Lemma 5). We can now put all the steps discussed to maintain the data structure of Lemma 5. In particular, for obtaining a 2^{j+1} -restricted hopset, we maintain the data structure of Lemma 5 on \hat{G}^j for each cluster rooted at a node $z \in A_i \setminus A_{i+1}$ and by setting $\ell = 2\beta + 1$. By using Lemma 11 and Theorem 9 to compute d -restricted hopsets for $d = O(\beta/\epsilon)$. When weights are polynomial we get the running time of $\tilde{O}(\frac{\beta}{\epsilon}(m + \Delta)n^\rho)$, where Δ is the overall number of hopset edges added over all updates.

3.2.3 Hopset stretch

In this section, we prove the stretch we prove the stretch incurred for a single-scale by combining properties of the monotone ES-tree algorithm of Section 3.2.1 with the static hopset argument and the rounding framework. We will then show that by setting the appropriate parameters we can prove the stretch in Lemma 5.

Next, we use the path doubling observation in Lemma 10 and properties of monotone ES tree described in Section 3.2.1 to prove the stretch incurred in each scale. We denote the stretch of \bar{H}_j to be $(1 + \epsilon_j)$. We extended the static hopset argument to dynamic settings in the following lemma. For getting the final stretch and hopbound we can set parameters $\epsilon_2 = \epsilon'$ (error incurred by rounding), and $\delta = \frac{\epsilon}{8(k+1/\rho+1)}$ in the following lemma and get $1 + \epsilon_j = (1 + 3\epsilon')^j$.

Theorem 12. *Given a graph $G = (V, E)$, assume that we have maintained a $(2^j, \beta, (1 + \epsilon_j))$ -restricted hopset \bar{H}_j , and let H_{j+1} be the hopset obtained by running Algorithm 2 for any given $0 \leq \epsilon_2 < 1$ on $G \cup \bar{H}_j$. Fix $0 < \delta \leq \frac{1}{8(k+1/\rho+1)}$, and consider a pair $x, y \in V$ where $d_{t,G}(x, y) \in [2^j, 2^{j+1}]$. Then for $0 \leq i \leq k + 1/\rho + 1$, either of the following conditions holds:*

- $d_{G \cup \bar{H}_{j+1}}^{((3/\delta)^i)}(x, y) \leq (1 + 8\delta i)(1 + \epsilon_j)(1 + \epsilon_2)d_{t,G}(x, y)$ or,
- There exists $z \in A_{i+1}$ such that,

$$d_{G \cup \bar{H}_{j+1}}^{((3/\delta)^i)}(x, z) \leq 2(1 + \epsilon_j)(1 + \epsilon_2)d_{t,G}(x, y).$$

Proof. We use a double induction on i and time t . The main difference between this proof and the static argument (see Appendix A) is that whenever we use the second case in our inductive argument, this is when have added a hopset edge (z, x) , $z \in A_{i+1}$ with one the following properties:

- The edge inserted $(z, x) \in \bar{H}_{j+1}$ is stretched (when x is the source in the monotone ES tree). In this case the claim follows by the induction on time, since $L_t(z) = L_{t-1}(z)$.
- The edge $(z, x) \in \bar{H}_{j+1}$ is not stretched, in which case the argument is similar to the static case, and uses the induction on i .

Let $d_{t,j}(x, y) := d_{G \cup \bar{H}_j}^{((3/\delta)^i)}(x, y)$, in other words this is the hop-bounded distance after running monotone ES tree on G^j and scaling up the weights. At time $t = 0$ the claim follows from the static hopset argument. For any time t and the base case of $i = 0$, we have three cases. If $y \in B(x)$ then edge (x, y) is in the hopset, and the first condition of the lemma holds. Otherwise if $x \in A_1$, then $z = x$ trivially satisfies the second condition. Otherwise we have $x \in A_0/A_1$, and by setting

$z = p(x)$ we know that there is an edge $(x, z) \in \bar{H}_j$ such that $d_{t,j}(x, z) \leq (1 + \epsilon_2)d_{G \cup \bar{H}_j}(x, y)$ (by definition of $p(x)$ and after rounding). Hence the second condition holds.

By inductive hypothesis assume the claim holds for i . Consider the shortest path $\pi(x, y)$ between x and y . We divide this path into $1/\delta$ segments of length at most $\delta d_{t,G}(x, y)$ and denote the a -th segment by $[u_a, v_a]$, where u_a is the node closest to x (first node of distance at least $a\delta d_{t,G}(x, y)$) and v_a is the node furthest to x on this segment (of distance at most $(a + 1)\delta d_{t,G}(x, y)$).

We can then use the induction hypothesis on each segment. First consider the case where for all the segments the first condition holds for i , then there is a path of $(3/\delta)^{i+1}$ -hops consisted of the hopbounded path on each segment. We can show that this path satisfies the first condition for $i + 1$. In other words,

$$d_{t,G \cup \bar{H}_{j+1}}^{((3/\delta)^{i+1})}(x, y) \leq \sum_{a=1}^{1/\delta} d_{t,G \cup \bar{H}_{j+1}}^{((3/\delta)^i)}(u_a, v_a) + d_{t,G}^{(1)}(v_a, u_{a+1}) \leq (1 + 8\delta i)d_{t,G}(x, y)$$

Next, assume that there are at least two segments for which the first condition does not hold for i . Otherwise, if there is only one such segment a similar argument follows. Let $[u_l, v_l]$ be the first such segment (i.e. the segment closest to x , where u_l is the first and v_l is the last node on the segment, and let $[u_r, v_r]$ be the last such segment.

In the following argument we will consider multiple cases. The argument for the stretched edges in all these cases will be as follows: In each case we add a hopset edge (s, z) , there is a node $z \in A_{i+1}$ such that $z \in B(s)$. We use an induction on time t to argue that these balls are maintained using a monotone ES tree on $G \cup \bar{H}_j$ and they have the desired stretch for G . For our proof we only need to use the guarantee for the original graph. The weight assigned to each such edge is the distance based on the monotone ES tree rooted at s . In particular, in this case the weight assigned to this edge corresponds to $d_{t,j}(s, z) = \eta(2^j, \epsilon_2)L_t(z)$ on the shortest path tree rooted at s . When the edge is stretched, we have $L_t(z) = L_{t-1}(z)$. Since by induction on the monotone ES tree we have maintained $B(s)$ at time $t - 1$ the edge will have weight,

$$\begin{aligned} d_{t,j}(s, z) &= \eta(2^j, \epsilon_2)L_t(z) \leq \eta(2^j, \epsilon_2)L_{t-1}(z) \\ &\leq (1 + \epsilon_2)(1 + \epsilon_j)d_{t-1,G}(s, z) \leq (1 + \epsilon_2)(1 + \epsilon_j)d_{t,G}(s, z) \end{aligned}$$

Note that since distances are increasing over time, we know that if $d_{t-1,G}(x, y) \leq d_{t,G}(x, y) \leq 2^{j+1}$, and thus (x, y) belongs to $G^1 \cup \dots \cup G^j$, and we can use the rounding in Lemma 6 at time $t - 1$.

First by inductive hypothesis and since we are in the case that the second condition holds for segments $[u_l, z_l]$ and $[u_r, v_r]$, we have,

- $d_{G \cup \bar{H}_{j+1}}^{((3/\delta)^i)}(u_l, z_l) \leq 2(1 + \epsilon_2)(1 + \epsilon_j)d_{t,G}(u_l, v_l)$, and,
- $d_{t,G \cup \bar{H}_{j+1}}^{((3/\delta)^i)}(v_r, z_r) \leq 2(1 + \epsilon_2)(1 + \epsilon_j)d_{t,G}(u_r, v_r)$

Again, we consider two cases. First, in case $z_r \in B(z_l)$, we have added a single hopset edge $(z_r, z_l) \in \bar{H}_{j+1}$. By properties of the monotone ES tree algorithm rooted at z_r and rounding of Lemma 6, the weight of this edge is at most $(1 + \epsilon_2)(1 + \epsilon_j)d_{t,G}(z_r, z_l)$. As stated earlier, this follows from induction on time if this edge is stretched. If the edge (z_l, z_r) is not stretched we can use Lemma 6 and Lemma 10. In this case by definition for node not stretched we have,

$$\begin{aligned} d_{t,j}(z_l, z_r) &= \eta(2^j, \epsilon_2)L_t(z_r) \leq \eta(2^j, \epsilon_2)(L_t(z_l) + w_{G^j}(z_l, z_r)) \\ &= \eta(2^j, \epsilon_2)w_{G^j}(z_l, z_r) \leq (1 + \epsilon_2)d_{G \cup \bar{H}_j}^{(2\beta+1)}(z_l, z_r) \end{aligned}$$

Note that z_l , and $L(z_l) = 0$.

On the other hand, by triangle inequality, and above inequalities (based on induction hypothesis) we have,

$$d_{\bar{H}_{j+1}}^{(1)}(z_l, z_r) \leq (1 + \epsilon_2)(1 + \epsilon_j)d_G(z_l, z_r) \quad (1)$$

$$\leq (1 + \epsilon_2)(1 + \epsilon_j)[d_{G \cup \bar{H}_{j+1}}^{((3/\delta)^i)}(u_l, z_l) + d_G(u_l, v_r) + d_{G \cup \bar{H}_{j+1}}^{((3/\delta)^i)}(z_r, v_r)] \quad (2)$$

By applying the inductive hypothesis on segments before $[u_l, v_l]$, and after $[u_r, v_r]$, we have a path with at most $(3/\delta)^i$ for each of these segments, satisfying the first condition for the endpoints of the segment. Also, we have a $2(3/\delta)^i + 1$ -hop path going through u_l, z_l, z_r, v_r that satisfies the first condition for u_l, v_r .

Putting all of these together, we will show that there is a path of hopbound $(3/\delta)^{i+1}$ satisfying the first condition. In particular, we have (we drop the subscript t here),

$$d_{G \cup \bar{H}_{j+1}}^{(3/\delta)^{i+1}}(x, y) \leq \sum_{a=1}^{l-1} [d_{G \cup \bar{H}_{j+1}}^{((3/\delta)^i)}(u_a, v_a) + d_G^{(1)}(v_a, u_{a+1})] + d_{G \cup \bar{H}_{j+1}}^{((3/\delta)^i)}(u_l, z_l) \quad (3)$$

$$+ d_{\bar{H}_{j+1}}^{(1)}(z_l, z_r) + d_{G \cup \bar{H}_{j+1}}^{((3/\delta)^i)}(z_r, v_r) + d_G^{(1)}(v_r, u_{r+1}) \quad (4)$$

$$+ \sum_{a=r+1}^{1/\delta} [d_{G \cup \bar{H}_{j+1}}^{((3/\delta)^i)}(u_a, v_a) + d_G^{(1)}(v_a, u_{a+1})] \quad (5)$$

$$\leq (1 + 8\delta i)(1 + \epsilon_j)(1 + \epsilon_2)[d_G(x, u_l) + d_G(v_r, y)] + d_G(u_l, v_r) \quad (6)$$

$$+ (1 + \epsilon_2)(1 + \epsilon_j)[2d_G(u_l, z_l) + 2d_G(z_r, v_r)] \quad (7)$$

$$\leq (1 + \epsilon_2)(1 + \epsilon_j)[8\delta d_G(x, y) + (1 + 8\delta i)d_G(x, y)] \quad (8)$$

$$\leq (1 + 8\delta(i + 1))(1 + \epsilon_2)(1 + \epsilon_j)d_G(x, y) \quad (9)$$

In the first inequality we used the induction on i for each segment, and triangle inequality.

In the second inequality we are using the fact that nodes u_j, v_j for all j are on the shortest path between x and y in G , and we are replacing $d_{\bar{H}_{j+1}}^{(1)}(z_l, z_r)$ with inequality 2. In line 8 we used the fact that the length of each segment is at most $\delta \cdot d_G(x, y)$. Hence we have shown that the first condition in the lemma statement holds.

Finally, consider the case where $z_r \notin B(z_l)$. If $z_l \notin A_{i+2}$, we consider $z = p(z_l)$, where $z_l \in A_{i+2}$. We have added the edge (z_l, z) to the hopset. Assume that this edge is not stretched. By definition of $B(z_l)$, and since we are maintaining the balls on the *scaled graph* G^j , the weight assigned to this edge is at most $(1 + \epsilon_2)d_{G \cup \bar{H}_j}(z_l, z_r)$. If this edge is stretched, similar to the previous case we use the induction on time. We now claim that this choice of z satisfies the second lemma condition

using a similar reasoning as before.

$$d_{G \cup \bar{H}_{j+1}}^{(3/\delta)^{(i+1)}}(x, y) \leq \sum_{a=1}^{l-1} [d_{G \cup \bar{H}_{j+1}}^{((3/\delta)^i)}(u_a, v_a) + d_G^{(1)}(v_a, u_{a+1})] + d_{G \cup \bar{H}_{j+1}}^{((3/\delta)^i)}(u_l, z_l) + (1 + \epsilon_2)(1 + \epsilon_j) d_{\bar{H}_{j+1}}^{(1)}(z_l, z) \quad (10)$$

$$\leq (1 + 8\delta i)(1 + \epsilon_2)(1 + \epsilon_j) d_G(x, u_l) + d_{G \cup \bar{H}_{j+1}}^{((3/\delta)^i)}(u_l, z_l) + (1 + \epsilon_2)(1 + \epsilon_j) d_{\bar{H}_{j+1}}(z_l, z_r) \quad (11)$$

$$\leq (1 + 8\delta i)(1 + \epsilon_2)(1 + \epsilon_j) d_G(x, u_l) + d_{G \cup \bar{H}_{j+1}}^{((3/\delta)^i)}(u_l, z_l) \quad (12)$$

$$+ (1 + \epsilon_2)(1 + \epsilon_j) [2d_{G \cup \bar{H}_{j+1}}^{((3/\delta)^i)}(z_l, u_l) + d_G(u_l, v_r) + d_{G \cup \bar{H}_{j+1}}^{(3/\delta)^i}(v_r, z_r)] \quad (13)$$

$$\leq (1 + 8\delta i)(1 + \epsilon_2)(1 + \epsilon_j) d_{G \cup \bar{H}_{j+1}}^{((3/\delta)^i)}(x, v_r) + 6\delta(1 + \epsilon_j) d_G(x, y) \quad (14)$$

$$\leq 2(1 + \epsilon_2)(1 + \epsilon_j) d_G(x, y) \quad (15)$$

In the last inequality we used the fact that we set $\delta < \frac{1}{8(k+1/\rho+1)}$ and thus $8\delta i < 1$. The only remaining case is when $z_\ell \in A_{i+2}$, in which case a similar reasoning follows by setting $z = z_l$. \square

Since in the last phase of the algorithm the second condition cannot hold, we will get an overall hopbound of $(3/\delta)^{k+1/\rho+1}$. In the following lemma, we will show that by setting $\delta = O(\frac{\epsilon}{(k+1/\rho+1)})$ we get the desired stretch for Lemma 5. Next, we use Lemma 5 for all scales and by setting the appropriate error parameters we can prove our overall stretch and hopbound tradeoffs. We also prove the overall update time using the running time of the monotone ES tree algorithm to run the restricted hopset algorithm on the hopsets obtained for each scale.

Stretch and Hopbound. We will now use the stretch argument in Section 3.2.3 to get the hopbound and stretch over *all scales* by setting the appropriate parameters. As discussed, there are *two* error factors incurred in each scale. One is caused by the fact that we are using previously added hopset edges, which we denoted by $(1 + \epsilon_j)$ for scale j , and another is caused due to the rounding error, which we denote by $(1 + \epsilon_2)$. To get an overall stretch of $(1 + \epsilon)$, we will set $\epsilon' = \frac{\epsilon}{6 \log W}$ and $\epsilon_2 = \epsilon'$.

Corollary 13. *For each update t , for all $\log \beta \leq j \leq \log W$ and any pair $x, y \in V$, where $2^j \leq d_{t,G}(x, y) \leq 2^{j+1}$, we have $d_{t,G}(x, y) \leq d_{t, G \cup \bar{H}_j}(x, y) \leq (1 + 3\epsilon')^j \cdot d_{t,G}^{(\beta)}(x, y)$.*

Proof. We use an induction on j . The base case (any $j \leq \log \beta$) is satisfied by paths in G . First, by induction hypothesis, we have a $(2^j, \beta, (1 + 3\epsilon')^j)$ -hopset, and hence $1 + \epsilon_j = (1 + 3\epsilon')^j$.

We then use Theorem 12, for $\epsilon_2 = \epsilon'$, and $\delta = \frac{\epsilon'}{8(k+1/\rho+1)}$. For the final iteration $i = \frac{1}{k+1/\rho+1}$ since $A_{i+1} = \emptyset$, the second item can not hold. Hence the first item should hold, and since $8\delta i < \epsilon'$ we have,

$$d_{t, G \cup \bar{H}_j}^{(\beta)}(x, y) \leq (1 + 3\epsilon')^{j-1} (1 + \epsilon') (1 + \epsilon') d_{t,G}(x, y) \leq (1 + 3\epsilon')^j d_{t,G}(x, y).$$

Here $d_{t,j}(x, y)$ is the sum of weights in the monotone ES tree, which corresponds to the approximate β -limited distance of x and y on the scaled graph. \square

Proof of stretch and hopbound in Lemma 5. Now by simply setting $\epsilon' = \frac{\epsilon}{3}$ in Corollary 13 we get the desired stretch and hopbound.

3.3 Overall Hopset Analysis

We now use the stretch argument of Corollary 13 with the update time followed by Lemma 5 to get the following hopset guarantees.

Theorem 14. *The total update time in each scaled graph G^j , $1 \leq j \leq \log W$, over all deletions is $\tilde{O}((\ell/\epsilon')(n^{1+\nu} + m)n^\rho)$, and hence the total update time⁴ for maintaining $(\beta, 1 + \epsilon)$ -hopset with hopbound $\beta = O(\frac{\log n}{\epsilon} \cdot (k + 1/\rho))^{k+1/\rho+1}$ is $\tilde{O}(\frac{\beta}{\epsilon} \cdot mn^\rho)$.*

Proof. First we use Corollary 13 to prove the stretch and hopbound, by setting $j = \log W$. For the final scale we have $d_{t, \log W}(u, v) = (1 + 3\epsilon')^{\log W} d_G(u, v) \leq (1 + \epsilon) \log W$. The hopbound obtained is

$$O\left(\frac{1}{\epsilon'} \cdot (k + 1/\rho)\right)^{k+1/\rho+1} = O\left(\frac{\log n}{\epsilon} \cdot (k + 1/\rho)\right)^{k+1/\rho+1}.$$

The running time follows by Lemma 5 where $\Delta = O(n^{1+\nu})$, we get an overall running time of $\tilde{O}(mn^\rho \cdot \frac{\beta}{\epsilon})$ time. \square

Hence the total update $\tilde{O}(mn^\rho)$ and the hopbound β is polylogarithmic when ρ and k are constant.

4 Applications

In this section we explain two applications of our decremental hopsets to get improved bounds for $(1 + \epsilon)$ -approximate SSSP and MSSP and $(2k - 1)(1 + \epsilon)$ -APSP. For both of these problems we use a *hop-sensitive* extensions of the Even-Shiloach tree algorithm as described in [Ber09, KL20]. This algorithm can also be obtained by the scaling technique we used in Section 3.2.

Our algorithm for $(2k - 1)(1 + \epsilon)$ -APSP involves maintaining two data structures: A $(\beta, 1 + \epsilon)$ -hopset, and a Thorup-Zwick distance oracle [TZ05]. At a high-level the hopset will let us maintain the distance oracle much faster, at the expense of a $(1 + \epsilon)$ -factor loss in the stretch.

4.1 $(1 + \epsilon)$ -approximate SSSP and $(1 + \epsilon)$ -MSSP

Given a graph $G = (V, E)$ and a set S of size of sources, our goal is to maintain the distance from each source in $\tilde{O}(sm + mn^\rho)$, total update time (where ρ is a constant), and constant query time.

Once a (β, ϵ) -hopset is constructed, we can run Algorithm 1 on the union of scaled graphs $G^1 \cup G^2 \cup \dots \cup G^{\log W}$ to computed β -limited SSSP to get our results for SSSP and MSSP. Similar approaches for h -limited SSSP have also been used in previous work such as [Ber09, HKN14a, KL20].

Lemma 15 (*h -limited SSSP*). *Given a source s , and any $u \in V$, we can decrementally maintain a distance estimate $\hat{d}(s, u)$ such that $d_G^{(h)}(s, u) \leq \hat{d}(s, u) \leq (1 + \epsilon)d_G^{(h)}(s, u)$ in $O(mh \log W)$ total update time and $O(1)$ query time.*

⁴If weights are not polynomial the $\log n$ factor will be replace with $\log W$, and a factor of $\log^2 W$ will be added to the update time.

We cannot directly use this lemma since we are also maintaining a hopset that may also have insertions. But in the next theorems we argue that using the same techniques as we used for maintaining the hopset (that are similar to framework of [HKN16]), namely by combining monotone ES tree and scaling, we get our SSSP and MSSP results.

Theorem 16. *Given an undirected and weighted graph $G = (V, E)$, there is a decremental algorithm for maintaining $(1 + \epsilon)$ -approximate distances from a set S of sources in total update time of $\tilde{O}(\beta(|S|(m + n^{1+\frac{1}{2^k-1}}) + mn^\rho))$, where $\beta = O(\frac{\log W}{\epsilon} \cdot (k + 1/\rho)^{k+1/\rho+1})$, and with $O(1)$ query time.*

Proof. We maintain a $(\beta, \frac{\epsilon}{3})$ -hopset H based on Theorem 14.

Then we use a variant of the β -limited SSSP algorithm in Lemma 15 on $G \cup H$ from all the s sources.

To handle hopset edge insertion we again use the monotone ES tree algorithm of Section 3.2.1. In particular, after adding all the hopset edges at time t for all scales, we will run the monotone ES tree algorithm rooted at each source again on the union of all scaled graphs $G^1 \cup \dots \cup G^{\log W}$ (by setting $\epsilon_0 = \epsilon/3$) and let the level $L(v)$ of a node be $\min_j \eta(2^j, \frac{\epsilon}{3})L_j(s, v)$ where $L_j(s, v)$ is the level of v on G^j after running the monotone ES tree that is run up to depth β . By combining the stretch proved in Theorem 14 and the rounding in Lemma 6, we get an overall stretch of $(1 + \epsilon/3)^2 \leq (1 + \epsilon)$.

More specifically, we can show that by running the SSSP (using Algorithm 1) from each source s on \hat{G} similar structural properties used in Theorem 12 holds. Given a source $s \in S$ and a node v such that $d_{t,G}(s, v) \in [2^j, 2^{j+1}]$ we either have $v \in B_i(s)$ for some iteration $1 \leq i \leq 1/\rho + 1 + k$, or there are other nodes z_l, z_r (as defined in 12 on the shortest path between s and v such that there are hopset edges in $B(z_l)$ and $B(z_r)$ that preserve the distance. We described how each of these balls is (approximately) preserved using monotone ES tree. All the insertions or distance decreases are due to adding the hopset edges in each ball, which as argued in Section 3.2.3 will lead to overall stretch of $(1 + \epsilon)$ for $d_{t,G}(s, v)$.

The time required for maintaining the hopset is $\tilde{O}((m + n^{1+\nu})n^\rho)$ and by setting $n^\rho = s$ the time required for maintaining h -SSSP from all sources is $O(sm \cdot \beta) = \tilde{O}(sm)$, when $s = n^{\Omega(1)}$. \square

We next state two specific consequences. First implication is that when the number of sources is a polynomial, and the graph is not very sparse, we can get a near-optimal (up to polylogarithmic factors) algorithm for $(1 + \epsilon)$ -MSSP.

Corollary 17. *Given an undirected and weighted graph $G = (V, E)$, where $|E| = n^{1+\Omega(1)}$, there is a decremental algorithm for maintaining $(1 + \epsilon)$ -approximate distances from s sources, where $s = n^{\Omega(1)}$ in total update time of $\tilde{O}(sm)$, and with $O(1)$ query time.*

When the number of sources $s = n^{o(1)}$ (e.g. in case of SSSP), the best tradeoff can be obtain by setting $\rho = \frac{\log \log n}{\sqrt{\log n}}$. We will then have $\beta = 2^{\tilde{O}(\sqrt{\log n})}$ and also $n^\rho = 2^{\tilde{O}(\sqrt{\log n})}$. In this case we get improved bounds over the result of [HKN14a], which has a total update time of is $mn^{\tilde{O}(\log^{3/4} n)}$.

Corollary 18. *Given an undirected and weighted graph $G = (V, E)$, there is a decremental algorithm for maintaining $(1 + \epsilon)$ -approximate distances from s sources, when $0 < \epsilon < 1$ is a constant and $|E| = n \cdot 2^{\tilde{\Omega}(\sqrt{\log n})}$, with total update time of $\tilde{O}(sm \cdot 2^{\tilde{O}(\sqrt{\log n})})$, and with $O(1)$ query time. Hence, we can maintain $(1 + \epsilon)$ -approximate SSSP in $2^{\tilde{O}(\sqrt{\log n})}$ amortized time.*

4.2 APSP distance oracles

It is known that in static settings for any weighted graph $G = (V, E)$, we can construct a Thorup-Zwick [TZ05] distance oracle of size (w.h.p.) $\tilde{O}(n^{1+1/k})$, such that after the preprocessing time of

$\tilde{O}(mn^{1/k})$, we can query $(2k - 1)$ -approximate distances for any pair of nodes in $O(k)$ time. In this section we show that in decremental settings we can maintain these distance oracles in total update time of $\tilde{O}(mn^{1/k})$ (for graphs that are not too sparse), and we can query $(2k - 1)(1 + \epsilon)$ -approximate distances in $O(k)$ time. This can be done by maintaining a $(\beta, 1 + \epsilon)$ -hopset and a distance oracles for G at the same time, where β is polylogarithmic in n . Intuitively, the hopset will allow us to update distances faster on the distance oracles.

Distance oracle algorithm via a hopset. Assume that we are given a $(\beta, 1 + \epsilon)$ -hopset for G . The algorithm for constructing the Thorup-Zwick distance oracle is as follows: Similar to the algorithm in Section 2.1, we define sets $V = A_0 \supseteq A_1 \supseteq \dots \supseteq A_k = \emptyset$. But here each set A_{i+1} is obtained by sampling each element from A_i with probability $p_i = n^{-1/k^5}$. Same as before, for every node $u \in A_i \setminus A_{i+1}$, let $p_i(u) \in A_{i+1}$ be the closest node to set A_{i+1} . We the bunch of a node u is the set $B(u) = \cup_{i=1}^k B_i(u) = \{v \in A_i : d(u, v) < d(u, A_{i+1})\} \cup \{p(u)\}$, $C(v)$ called the cluster of v such that if $v \in B(u)$ then $u \in C(v)$. The distance oracle is consisted of bunches $B(v)$ for all $v \in V$, and the distances associated with them. Note that the information stored here are also different from the hopset algorithm described in Section 2.1, since there we only added edges for nodes $v \in A_i$ and their bunches. Thorup and Zwick [TZ05] show that this distance oracle has the following properties (in static settings):

Theorem 19 ([TZ05]). *There is a distance oracle of expected size $O(kn^{1+1/k})$, that can answer queries $(2k - 1)$ -approximate distance queries for a given weighted and undirected graph $G = (V, E)$ in $O(k)$ time for any $k \geq 2$. The preprocessing time in static settings is w.h.p. $\tilde{O}(mn^{1/k})$.*

As discussed in Section 3.1, Roditty and Zwick [RZ04] showed how to maintain this data structure in $O(mn)$ update time for *unweighted graphs*, but where the size is increased to $\tilde{O}(m + n^{1+1/k})$. For weighted graphs their updates time can be as large as $O(mn^{1+1/k})$. We will argue that by maintaining a $(\beta, 1 + \epsilon)$ -hopset along with the distance oracle we can improve the total update time to $\tilde{O}(\beta mn^{1/k})$. This combined with our hopset construction in Section 3.2 will lead to the desired bounds. More formally,

Theorem 20. *Given a weighted and undirected graph $G = (V, E)$ and a $(\beta, 1 + \epsilon)$ -hopset H for G , and a parameter $k \geq 2$, we can maintain a distance oracle of size $\tilde{O}(m + n^{1+1/k})$ and with stretch $(1 + \epsilon)(2k - 1)$ in $\tilde{O}(\frac{\beta}{\epsilon} \cdot mn^{1/k})$ total update time.*

Proof. We will again use the scaling idea described in Section 3.2. Similar to Theorem 16, we consider the graph $\hat{G} = G^1 \cup \dots \cup G^j$ that is the union of scaling of graphs $G \cup \bar{H}_j$, where $\epsilon_0 = \frac{\epsilon}{3}$ and \bar{H}_j is a $(2^j, \beta, \frac{\epsilon}{3})$ hopset. We then run the algorithm of Roditty-Zwick [RZ04] on \hat{G} up to depth $\lceil 3\beta/\epsilon \rceil$ for maintaining the clusters and the bunches. The algorithm is similar to the restricted hopset algorithm described in Section 2.1. The only differences are the sampling probabilities and the information stored. Therefore using the argument in Lemma 8 we can show that by running this algorithm on \hat{G} with depth $\lceil 3\beta/\epsilon \rceil$ we can maintain a bunch $B_i(u)$ for all nodes $u \in V$ in $\tilde{O}(\frac{\beta m}{\epsilon}) = \tilde{O}(\frac{\beta}{\epsilon} mn^{1/k})$ total update time. For handling insertions, similar to our previous algorithms we use monotone ES tree (for each bunch) on the union of scaled graphs, $\hat{G} = G^1 \cup \dots \cup G^{\log W}$ (by setting $\epsilon_0 = \epsilon/3$) and let the level $L(v)$ of a node be $\min_j \eta(2^j, \frac{\epsilon}{3}) L_j(s, v)$ where $L_j(s, v)$ is the level of v on G^j after running the monotone ES tree that is run up to depth β .

Again, when we combine the hopset stretch with the stretch with the rounding algorithm caused by rounding, we get an overall stretch of $(1 + \epsilon/3)^2 \leq 1 + 3\epsilon$. The overall stretch is thus $(2k - 1)(1 + \epsilon)$. \square

⁵This k should not be confused with the size parameter in the hopset algorithm of Section 2.1. Here we only use the fact that the hopset size can be bounded based on the graph density.

Theorem 21. *Given a weighted graph $G = (V, E)$ with polynomial weights, and parameter $k \geq 2$ and $0 < \epsilon < 1$, we can maintain a data structure with expected size $\tilde{O}(m + n^{1+1/k})$ and total update time of $\tilde{O}(mn^{1/k} \cdot (1/\epsilon)^{O(1)})$, that returns $(2k - 1)(1 + \epsilon)$ -stretch queries for any pair $u, v \in V$ with $O(k)$ query time.*

Proof. We construct and maintain a $(\beta, 1 + \frac{\epsilon}{3})$ -hopset using Theorem 14. If $m = n^{1+\Omega(1)}$ we can set $\rho = \frac{1}{k}$, and we set the hopset size parameter ν to a small constant⁶ such that $O(n^{1+\nu}) = O(m)$. If $m = n^{1+o(1)}$, we set $\rho = \frac{1}{k} - \nu$, where a $\nu < 1/k$ is a constant. In both cases time required for maintaining a hopset is $\tilde{O}(mn^{1/k} \cdot (1/\epsilon)^{O(1)})$. We get hopbound $\beta = O(\log n/\epsilon)^{\log(1/\nu)+1/k+1} = \text{polylog}(n)$. Hence we can also maintain the distance oracle in $\tilde{O}(mn^{1/k})$ total update time. The stretch will be $(2k - 1)(1 + \epsilon)$, and the query time remains the same as the static query time, which is $O(k)$. \square

References

- [Ber09] Aaron Bernstein. Fully dynamic $(2 + \epsilon)$ approximate all-pairs shortest paths with fast query and close to linear update time. In *2009 50th Annual IEEE Symposium on Foundations of Computer Science*, pages 693–702. IEEE, 2009.
- [BR11] Aaron Bernstein and Liam Roditty. Improved dynamic algorithms for maintaining approximate shortest paths under deletions. In *Proceedings of the twenty-second annual ACM-SIAM symposium on Discrete Algorithms*, pages 1355–1365. SIAM, 2011.
- [Che18] Shiri Chechik. Near-optimal approximate decremental all pairs shortest paths. In *2018 IEEE 59th Annual Symposium on Foundations of Computer Science (FOCS)*, pages 170–181. IEEE, 2018.
- [Coh00] Edith Cohen. Polylog-time and near-linear work approximation scheme for undirected shortest paths. *Journal of the ACM (JACM)*, 2000.
- [DN19] Michael Dinitz and Yasamin Nazari. Massively parallel approximate distance sketches. *OPODIS*, 2019.
- [EGN19] Michael Elkin, Yuval Gitlitz, and Ofer Neiman. Almost shortest paths and pram distance oracles in weighted graphs. *arXiv preprint arXiv:1907.11422*, 2019.
- [EN18] Michael Elkin and Ofer Neiman. Near-optimal distributed routing with low memory. In *Proceedings of the ACM Symposium on Principles of Distributed Computing*. ACM, 2018.
- [EN19a] Michael Elkin and Ofer Neiman. Hopsets with constant hopbound, and applications to approximate shortest paths. *SIAM Journal on Computing*, 2019.
- [EN19b] Michael Elkin and Ofer Neiman. Linear-size hopsets with small hopbound, and constant-hopbound hopsets in rnc. In *The 31st ACM Symposium on Parallelism in Algorithms and Architectures*, pages 333–341, 2019.

⁶The choice of size parameter impact the polylogarithmic factors. Hence one option is to choose the smallest constant such that the graph size is not smaller than the hopset size.

- [HKN14a] Monika Henzinger, Sebastian Krinninger, and Danupon Nanongkai. Decremental single-source shortest paths on undirected graphs in near-linear total update time. In *2014 IEEE 55th Annual Symposium on Foundations of Computer Science*, pages 146–155. IEEE, 2014.
- [HKN14b] Monika Henzinger, Sebastian Krinninger, and Danupon Nanongkai. A subquadratic-time algorithm for decremental single-source shortest paths. In Chandra Chekuri, editor, *Proceedings of the Twenty-Fifth Annual ACM-SIAM Symposium on Discrete Algorithms, SODA 2014, Portland, Oregon, USA, January 5-7, 2014*, pages 1053–1072. SIAM, 2014.
- [HKN16] Monika Henzinger, Sebastian Krinninger, and Danupon Nanongkai. Dynamic approximate all-pairs shortest paths: Breaking the $o(mn)$ barrier and derandomization. *SIAM Journal on Computing*, 45(3):947–1006, 2016.
- [HKN17] Monika Henzinger, Sebastian Krinninger, and Danupon Nanongkai. Sublinear-time maintenance of breadth-first spanning trees in partially dynamic networks. *ACM Trans. Algorithms*, 13(4):51:1–51:24, 2017.
- [HKNS15] Monika Henzinger, Sebastian Krinninger, Danupon Nanongkai, and Thatchaphol Saranurak. Unifying and strengthening hardness for dynamic problems via the online matrix-vector multiplication conjecture. In Rocco A. Servedio and Ronitt Rubinfeld, editors, *Proceedings of the Forty-Seventh Annual ACM on Symposium on Theory of Computing, STOC 2015, Portland, OR, USA, June 14-17, 2015*, pages 21–30. ACM, 2015.
- [HP19] Shang-En Huang and Seth Pettie. Thorup–zwick emulators are universally optimal hopsets. *Information Processing Letters*, 142:9–13, 2019.
- [Kin99] Valerie King. Fully dynamic algorithms for maintaining all-pairs shortest paths and transitive closure in digraphs. In *40th Annual Symposium on Foundations of Computer Science (Cat. No. 99CB37039)*, pages 81–89. IEEE, 1999.
- [KL20] Adam Karczmarz and Jakub Lacki. Simple label-correcting algorithms for partially dynamic approximate shortest paths in directed graphs. In *3rd Symposium on Simplicity in Algorithms, SOSA@SODA 2020*. SIAM, 2020.
- [KS97] Philip N Klein and Sairam Subramanian. A randomized parallel algorithm for single-source shortest paths. *Journal of Algorithms*, 1997.
- [MPVX15] Gary L Miller, Richard Peng, Adrian Vladu, and Shen Chen Xu. Improved parallel algorithms for spanners and hopsets. In *Proceedings of the Symposium on Parallelism in Algorithms and Architectures*. ACM, 2015.
- [Nan14] Danupon Nanongkai. Distributed approximation algorithms for weighted shortest paths. In *Proceedings of the ACM Symposium on Theory of computing*. ACM, 2014.
- [RZ04] Liam Roditty and Uri Zwick. Dynamic approximate all-pairs shortest paths in undirected graphs. In *45th Annual IEEE Symposium on Foundations of Computer Science*, pages 499–508. IEEE, 2004.
- [RZ12] Liam Roditty and Uri Zwick. Dynamic approximate all-pairs shortest paths in undirected graphs. *SIAM J. Comput.*, 41(3):670–683, 2012.

- [SE81] Yossi Shiloach and Shimon Even. An on-line edge-deletion problem. *Journal of the ACM (JACM)*, 28(1):1–4, 1981.
- [TZ05] Mikkel Thorup and Uri Zwick. Approximate distance oracles. *Journal of the ACM (JACM)*, 52(1):1–24, 2005.
- [TZ06] Mikkel Thorup and Uri Zwick. Spanners and emulators with sublinear distance errors. In *Proceedings of the seventeenth annual ACM-SIAM symposium on Discrete algorithm*, pages 802–809, 2006.

A Static Hopset Properties

In this section, we will briefly overview the (static) hopset algorithm of [EN19b] (which is similar to [HP19]). Given a weighted graph $G = (V, E)$, and a parameter k , we first construct a hopset of size $O(n^{1+\frac{1}{2^k-1}})$ and hopbound $O(k/\epsilon)^k$. We then modify the algorithm in order to get a better running time at the cost of a worse stretch. We define sets $V = A_0 \supseteq A_1 \supseteq \dots \supseteq A_k = \emptyset$. Let $\nu = \frac{1}{2^k-1}$. Each set A_{i+1} is obtained by sampling each element from A_i with probability $q_i = n^{-2^i \cdot \nu}$. Hence it can be shown that $E[|A_i|] = n^{1-2^{i-1}\nu}$.

For every vertex $u \in A_i \setminus A_{i+1}$, let $p(u) \in A_{i+1}$ be the closest node to set A_{i+1} . The bunch is set to $B(u) = \{v \in A_i : d(u, v) < d(u, A_{i+1})\} \cup \{p(u)\}$. Also, we define a set $C(v)$ called the cluster of v such that if $v \in B(u)$ then $u \in C(v)$. It can easily be shown that clusters are *connected* in a sense that if a node $v \in C(u)$ then any node z on the shortest path between v and u is also in $C(u)$. As we will see, this property is important for bounding the running time. The hopset is consisted of adding edges (u, v) where $v \in B(u)$, and setting the weight to be $d(u, v)$.

The algorithm described will lead to a $((k/\epsilon)^k, \epsilon)$ -hopset, but the running time can be as large $O(mn)$. In order to resolve this, [EN19b] proposed an algorithm using modified sampling probabilities of $q_i = \max(n^{-2^i \cdot \nu}, n^{-\rho})$. Using this approach, the number of iterations becomes $k+1/\rho+1$, but the hopbound is also increase to $O(\frac{k+1/\rho+1}{\epsilon})O(k+1/\rho+1)$. We briefly review some the properties of this hopset algorithm as discussed in [EN19b, HP19], and will then explain how [EN19b] modifies the algorithm to improve the running time.

One important component of this algorithm is the *modified Dijkstra's algorithm* that we will also utilize in our dynamic algorithms, and thus we briefly review it. This algorithm was presented by Thorup-Zwick [TZ05] and it allows us to construct the bunches and clusters for level i in $O((m+n \log n)/q_i)$ (expected) time. At a high-level this is done by making a modification to Dijkstra. In the original Dijkstra for each source $u \in A_i \setminus A_{i+1}$, at each iteration we consider an unvisited vertex v , and relax each incident edge (v, z) by setting $d(u, z) := \min\{d(u, z), d(u, v) + w(v, z)\}$. But in the modified algorithm this is done only if $d(u, v) + w(v, z) < d(z, A_{i+1})$. In other words each node z only "participates" in a shortest-path exploration from a source u only if $z \in B(u)$. Note that if $z \in B(u)$, all the nodes on the shortest path between u and z are considered. This will let us bound the running time by expected size of $B(u)$.

A.1 Properties

Size. For each $u \in A_i \setminus A_{i+1}$ we have $E[|B(u)|] \leq 1/q_i$. At a high-level, this can be shown by ordering vertices based on their distance to u , and noting that this size is the expected number of vertices visited in A_i that is included in A_{i+1} . This corresponds to a geometric random variable with parameter q_i and thus the expectation is $1/q_i = n^{2^i \nu}$. We can use this to show that for all i

the number of edges added is in expectation

$$\sum_{i=1}^{k-2} E[|A_i|]n^{2^i \cdot \nu} = kn^{1+\nu}.$$

Modified Dijkstra’s algorithm. Based on an algorithm in [TZ05] (and used in [EN19b]), the bunches for level i can be constructed in $O(m + n \log n)/q_i$. At a high-level this is done by making a modification to Dijkstra. In the original Dijkstra for each source $u \in A_i \setminus A_{i+1}$, at each iteration we consider an unvisited vertex v , and “relax” each incident edge (v, z) by setting $d(u, z) = \min\{d(u, z), d(u, v) + w(v, z)\}$. But in the modified algorithm this is done only if $d(u, v) + w(v, z) < d(z, A_{i+1})$. In other words each node z only “participates” in a shortest-path exploration from a source u only if $z \in B(u)$. Note that if $z \in B(u)$, all the nodes on the shortest path between u and z are considered. Since $|B(u)| \leq \frac{1}{q_i}$, this allows us to bound the running time by $O(mn^\rho)$.

A.2 Hopbound and Stretch.

We first analyze the hopbound and stretch of the original hopset algorithm. The extension to the more efficient variant will be straightforward. The following lemma was proved by [EN19b, HP19]. We give a proof sketch here. We use a similar idea in our dynamic hopset construction (in combination with monotone ES tree and scaling), and hence some of the missing details can be found in proof of Theorem 12.

Lemma 22. *Fix $0 < \delta \leq 1/8k$, and consider a pair $x, y \in V$. Then for $0 \leq i \leq k + 1$ we have either of the following conditions:*

- $d_{G \cup H}^{((3/\delta)^i)}(x, y) \leq (1 + 8\delta i)d_G(x, y)$ or,
- There exists $z \in A_{i+1}$ such that, $d_{G \cup H}^{((3/\delta)^i)}(x, z) \leq 2d_G(x, y)$.

Proof sketch. This can be shown by an induction on i . For the base case of $i = 0$, we have three cases. If $y \in B(x)$ then edge (x, y) is in the hopset, and the first condition of the lemma holds. Otherwise if $x \in A_1$, then $z = x$ trivially satisfies the second condition. Otherwise we have $x \in A_0/A_1$, and by setting $z = p(x)$ we know that there is an edge $(x, z) \in H$ such that $d(x, z) \leq d(x, y)$ by definition of $p(x)$, and hence the second condition holds.

Now assume the claim holds for i . Consider the shortest path $\pi(x, y)$ between x and y . We divide this path into $1/\delta$ segments of length roughly $\delta d_G(x, y)$ (up to rounding). Using triangle inequality on all segments we then use the induction hypothesis on each segment. If for all the segments the first condition holds for i , then there is a path of $(3/\delta)^{i+1}$ -hops consisted of the hopbounded path on each segment. We can show that this path satisfies the first condition for $i + 1$. Now, assume that there are at least two segments for which the first condition does not hold for i . Then let $[u_\ell, v_\ell]$ be the first such segment (i.e. closest to x) and let $[u_r, v_r]$ be the last such segment. Then by inductive hypothesis there are $z_\ell, z_r \in A_{i+1}$ such that:

- $d_{G \cup H}^{((3/\delta)^i)}(u_\ell, z_\ell) \leq 2d(u_\ell, v_\ell)$, and,
- $d_{G \cup H}^{((3/\delta)^i)}(v_r, z_r) \leq 2d(u_r, v_r)$

Again, we consider two cases. First, in case $z_r \in B(z_\ell)$, we have added a single hopset edge between z_r and z_ℓ with weight $d(z_r, z_\ell)$. By applying the inductive hypothesis on segments before $[u_\ell, v_\ell]$, and after $[u_r, v_r]$, we have a path with at most $(3/\delta)^i$ for each of these segments, satisfying the first condition for the endpoints of the segment. Also, we have a $2(3/\delta)^i + 1$ -hop path going through u_ℓ, z_ℓ, z_r, v_r that satisfies the first condition for u_ℓ, v_r . Putting all of these together, we can show that there is a path of hopbound $(3/\delta)^{i+1}$ satisfying the first condition. To get this we need to use the fact that the length of each segment is at most $\delta \cdot d(x, y)$. We have,

$$\begin{aligned}
d_{G \cup H}^{(3/\delta)^{i+1}}(x, y) &\leq \sum_{j=1}^{\ell-1} [d_{G \cup H}^{((3/\delta)^i)}(u_j, v_j) + d_G^{(1)}(v_j, u_{j+1})] + d_{G \cup H}^{((3/\delta)^i)}(u_\ell, z_\ell) \\
&\quad + d_H^{(1)}(z_\ell, z_r) + d_{G \cup H}^{((3/\delta)^i)}(u_r, v_r) + d_H^{(1)}(v_r, u_{r+1}) \\
&\quad + \sum_{j=r+1}^{(1/\delta)} [d_{G \cup H}^{((3/\delta)^i)}(u_j, v_j) + d_G^{(1)}(v_j, u_{j+1})] \\
&\leq 8\delta d_G(x, y) + (1 + 8\delta i)d_G(x, y) \\
&\leq (1 + 8\delta(i + 1))d_G(x, y)
\end{aligned}$$

Finally, consider the case where $z_r \notin B(z_\ell)$. If $z_\ell \notin A_{i+2}$, we consider $z = p(z_\ell)$. By definition we have added the edge (z_ℓ, z) to the hopset, we can show that the second condition holds. We use similar reasoning as before and also use the fact that we set $\delta < 1/8k$ to show that item 2 holds in this case. The only remaining case is when $z_\ell \in A_{i+2}$, in a similar but simpler reasoning follows by setting $z = z_\ell$. \square

We can now set $\delta = \Theta(k/\epsilon)$ in Lemma 22, and since $A_k = \emptyset$, for $i = k - 1$ only the first condition can hold. Therefore we get a hopbound of $\beta = \Theta(k/\epsilon)^k$.

Hopbound in the efficient variant. For more efficient construction, we considered a two phase algorithm. For the first phase we use similar reasoning as Lemma 22, but in the second phase the parameters change. The algorithm will require more *iterations* that will impact the overall hopbound. We require $k + 1/\rho + 1$ iterations overall. In the second phase we have $\delta' = (k + 1/\rho)/\epsilon$ and thus we have overall hopbound of $O(\frac{k+1/\rho}{\epsilon})^{k+1/\rho+1}$.

By putting everything we have the following guarantees for the static hopset:

Theorem 23 ([EN19b]). *There is an algorithm that given a weighted and undirected graph $G = (V, E)$, and $2 \leq k \leq \log \log n - 2$, $\frac{2}{2^k - 1} < \rho < 1$ computes a (β, ϵ) -hopset of size $O(n^{1 + \frac{1}{2^k - 1}})$, where $\beta = O((\frac{k+1/\rho}{\epsilon})^{k+1/\rho+1})$. It runs in $O(\frac{n^\rho}{\rho}(m + n \log n))$ expected time.*

B Details Omitted from Section 3.1

In this section, we explain the restricted hopset algorithm that is mainly based on algorithm of [RZ04] in more detail.

We sample sets $V = A_0 \supseteq A_1 \supseteq \dots \supseteq A_{i(\rho)} = \emptyset$, where $i(\rho) = k + 1/\rho + 1$ once and they remain the same during the updates. Next, we need to maintain values $d(v, A_i), 1 \leq i \leq k - 1$ for all nodes $v \in V$. This can be performed by computing a shortest path tree rooted at a dummy node s_i connected to all nodes in A_i . Let $\hat{d} = (1 + \epsilon)d$. We can use the Even-Schiloach [SE81] algorithm up to depth \hat{d} to compute all these distances in $O(\hat{d}m)$ time. The pivots $p(v), \forall v \in V$ can also be maintained in this process.

Maintaining the clusters. Recall that for $z \in A_i \setminus A_{i+1}$ we have $v \in C(z)$ if and only if $d(z, v) < d(v, A_{i+1})$. After each deletion, for each node v and the cluster centers z we first check whether the distance $d(z, v)$ has increased. If $d(z, v) \geq d(v, A_{i+1})$, v will be removed from $C(z)$. The more subtle part is adding nodes to new clusters. For each $0 \leq i < k$, we define a set X_i consisted of all vertices whose distance to A_i is increased as a result of a deletion, but where this distance is still at most \hat{d} . The sets X_i can be computed while maintaining $d(v, A_i)$.

Note that a node v would join $C(w)$ only after an increase in $d(v, A_{i+1})$. Using this observation, after each deletion for every $v \in X_{i+1}, z \in B_i(u) \setminus B_i(v)$, and each edge $(u, v) \in E$ we check if $d(z, u) + w(u, v) < d(v, A_{i+1})$. If yes, then v joins $C(z)$. We push v to a priority queue $Q(z)$ with key $d(z, u) + w(u, v)$. If v was already in the queue the key will be updated if this distance is smaller than the existing estimate. In this case we *mark* v . The marked nodes join clusters z , but there may be other nodes that also need to join $C(z)$ as a result of this change.

Hence after this initial phase, for each $z \in A_i \setminus A_{i+1}$ where $Q(z) \neq \emptyset$, we run the modified Dijkstra's algorithm. Recall that in the modified Dijkstra's algorithm when we explore neighbors of a node x , we only relax an edge (x, y) if $d(x, y) + w(x, y) < d(x, A_i)$. Then [RZ04] show that this process correctly maintains the clusters. We then repeat this process for all the $k + 1/\rho + 1$ iterations. We add a hopset edge between each $z \in A_i \setminus A_{i+1}$ and all nodes $v \in C(z)$ and set the weight of this edge to $w(v, z) = d_G(v, z)$.

We need to make one modification in the algorithm that is required for our hopset algorithm (in Section 3.2). Rather than running modified Dijkstra's for any node $z \in A_i \setminus A_{i+1}$, where $Q(z) \neq \emptyset$, we run it for all $A_i \setminus A_{i+1}$. The update time can still be bounded by $O(\hat{d}mn^\rho)$ using the same argument as in Lemma 8. The reason for this modification is that throughout our algorithm the roots of the shortest path trees we maintain change.

B.1 Proof of Lemma 8

Lemma 24. *For every $v \in V$ and $0 \leq i \leq k - 1$, the expected total number of times the edges incident on v are scanned over all trees for each $w \in A_i$ (i.e. trees on $C(w)$) is $O(\hat{d}/q_i)$, where q_i is the sub-sampling probability.*

Proof. Let $w \in A_i \setminus A_{i+1}$. The edges of a node $v \in V$ is scanned when v joins $C(w)$, and any time $d(v, w)$ is increased until v leaves $C(w)$. We start by analyzing the total cost of joining new clusters. Recall that v can join $C(w)$ only when $d(v, A_{i+1})$ increases, and in decremental settings this can happen at most \hat{d} times *per tree*. We argued that at any time, v joins at most $\tilde{O}(1/q_i)$ trees, and hence the total time for nodes joining new clusters is $\tilde{O}(\hat{d}m/q_i)$. Next, we consider the case when after the deletion the distance between v and the center increases. This will let us bound the number of times the edges incident on v are scanned for a tree rooted at some node in A_i . Let $d_t(w, v)$ denote the distance between v and w at time t (after t deletions), and let $C_t(w)$ denote the cluster rooted at w at time t . We bound the number of indices t for which $v \in C_t(w)$ and $d_t(w, v) < d_{t+1}(w, v)$. Let $w_{t,1}, w_{t,2}, \dots$ be the sequence of nodes in A_i sorted based on their distance from v at time t . Ties will be broken by ordering based on pairs $(d_t(v, w), d_{t+1}(v, w))$, i.e. nodes with the same distance from v at time t will be sorted based on their distance at time $t + 1$. This ensures that if $d_t(v, w_{t,j}) < d_{t+1}(v, w_{t,j})$, then $d_t(v, w_{t,j}) < d_{t+1}(v, w_{t+1,j})$. Same as before $\Pr[v \in C_t(w_{t,j})] \leq (1 - q_i)^{j-1}$, since $v \in C_t(w_{t,j})$ only if for all $j' < j$ we have $w_{t,j'} \in A_i \setminus A_{i+1}$. Let $I = \{(t, j) \mid d_t(v, w_{t,j}) < d_{t+1}(v, w_{t,j}) \leq \hat{d}\}$. Then since edges incident to v are scanned only if their distance increases, the expected number of times they are scanned over all trees rooted at centers in A_i is at most $\sum_{(t,j)} \Pr[v \in C_t(w_{t,j})]$. Also, by definition for a fixed j there can be at most \hat{d} pairs of form (t, j) . In other words, the distance to the j -th closest vertex can increase at most \hat{d} times,

and hence,

$$\sum_{(t,j)} \Pr[v \in C_t(w_{t,j})] \leq \hat{d} \sum_{j \geq 1} (1 - q_i)^{j-1} \leq \hat{d}/q_i.$$

□