

# Coordinate Methods for Matrix Games

Yair Carmon   Yujia Jin   Aaron Sidford   Kevin Tian  
`{yairc,yujiajin,sidford,kjtian}@stanford.edu`

## Abstract

We develop primal-dual coordinate methods for solving bilinear saddle-point problems of the form  $\min_{x \in \mathcal{X}} \max_{y \in \mathcal{Y}} y^\top A x$  which contain linear programming, classification, and regression as special cases. Our methods push existing fully stochastic sublinear methods and variance-reduced methods towards their limits in terms of per-iteration complexity and sample complexity. We obtain nearly-constant per-iteration complexity by designing efficient data structures leveraging Taylor approximations to the exponential and a binomial heap. We improve sample complexity via low-variance gradient estimators using dynamic sampling distributions that depend on both the iterates and the magnitude of the matrix entries.

Our runtime bounds improve upon those of existing primal-dual methods by a factor depending on *sparsity measures* of the  $m$  by  $n$  matrix  $A$ . For example, when rows and columns have constant  $\ell_1/\ell_2$  norm ratios, we offer improvements by a factor of  $m+n$  in the fully stochastic setting and  $\sqrt{m+n}$  in the variance-reduced setting. We apply our methods to computational geometry problems, i.e. minimum enclosing ball, maximum inscribed ball, and linear regression, and obtain improved complexity bounds. For linear regression with an elementwise nonnegative matrix, our guarantees improve on exact gradient methods by a factor of  $\sqrt{\text{nnz}(A)/(m+n)}$ .

# Contents

|          |   |           |
|----------|---|-----------|
| <b>1</b> | <b>Introduction</b>   | <b>1</b>  |
| 1.1      | Our results . . . . .   | 1         |
| 1.2      | Our approach . . . . .  | 4         |
| 1.3      | Related work . . . . .  | 11        |
| 1.4      | Paper organization . . . . .  | 12        |
| <b>2</b> | <b>Preliminaries</b>  | <b>13</b> |
| 2.1      | Local norm setups . . . . .   | 13        |
| 2.2      | The problem and optimality criterion . . . . .  | 14        |
| 2.3      | Matrix access models . . . . .  | 15        |
| 2.4      | Data structure interfaces . . . . .   | 15        |
| <b>3</b> | <b>Framework</b>  | <b>17</b> |
| 3.1      | Sublinear coordinate methods . . . . .  | 17        |
| 3.2      | Variance-reduced coordinate methods . . . . .   | 19        |
| <b>4</b> | <b>Matrix games</b>   | <b>22</b> |
| 4.1      | $\ell_1$ - $\ell_1$ sublinear coordinate method . . . . .                             | 22        |
| 4.2      | $\ell_1$ - $\ell_1$ variance-reduced coordinate method . . . . .                      | 24        |
| <b>5</b> | <b>Data structure implementation</b>  | <b>30</b> |
| 5.1      | <code>IterateMaintainer<sub>p</sub></code> . . . . .                                  | 30        |
| 5.2      | <code>ApproxExpMaintainer</code> . . . . .  | 33        |
| 5.3      | <code>ScaleMaintainer</code> . . . . .  | 38        |
| <b>6</b> | <b>Applications</b>   | <b>44</b> |
| 6.1      | Maximum inscribed ball . . . . .  | 45        |
| 6.2      | Minimum enclosing ball . . . . .  | 47        |
| 6.3      | Regression . . . . .  | 48        |
| <b>A</b> | <b>Deferred proofs from Section 2</b>   | <b>54</b> |
| <b>B</b> | <b>Deferred proofs from Section 3</b>   | <b>54</b> |
| <b>C</b> | <b>Deferred proofs for sublinear methods</b>  | <b>60</b> |
| <b>D</b> | <b>Deferred proofs for variance-reduced methods</b>                                   | <b>67</b> |
| <b>E</b> | <b>Additional results on variance-reduced methods</b>                                 | <b>76</b> |
| <b>F</b> | <b>Deferred proofs from Section 6</b>   | <b>80</b> |
| <b>G</b> | <b><code>IterateMaintainer<sub>2</sub></code>: numerical stability and variations</b> | <b>84</b> |

# 1 Introduction

Bilinear minimax problems of the form

$$\min_{x \in \mathcal{X}} \max_{y \in \mathcal{Y}} y^\top A x \text{ where } A \in \mathbb{R}^{m \times n}, \quad (1)$$

are fundamental to machine learning, economics and theoretical computer science [26, 46, 13]. We focus on three important settings characterized by different domain geometries. When  $\mathcal{X}$  and  $\mathcal{Y}$  are probability simplices—which we call the  $\ell_1$ - $\ell_1$  setting—the problem (1) corresponds to a zero-sum matrix game and also to a linear program in canonical feasibility form. The  $\ell_2$ - $\ell_1$  setting, where  $\mathcal{X}$  is a Euclidean ball and  $\mathcal{Y}$  is a simplex, is useful for linear classification (hard-margin support vector machines) as well as problems in computational geometry [10]. Further, the  $\ell_2$ - $\ell_2$  setting, where both  $\mathcal{X}$  and  $\mathcal{Y}$  are Euclidean balls (with general center), includes linear regression.

Many problems of practical interest are *sparse*, i.e., the number of nonzero elements in  $A$ , which we denote by  $\text{nnz}$ , satisfies  $\text{nnz} \ll mn$ . Examples include: linear programs with constraints involving few variables, linear classification with 1-hot-encoded features, and linear systems that arise from physical models with local interactions. The problem description size  $\text{nnz}$  plays a central role in several runtime analyses of algorithms for solving the problem (1).

However, sparsity is not an entirely satisfactory measure of instance complexity: it is not continuous in the elements of  $A$  and consequently it cannot accurately reflect the simplicity of “nearly sparse” instances with many small (but nonzero) elements. Measures of *numerical sparsity*, such as the  $\ell_1$  to  $\ell_2$  norm ratio, can fill this gap [17]. Indeed, many problems encountered in practice are numerically sparse. Examples include: linear programming constraints of the form  $x_1 \geq \frac{1}{n} \sum_i x_i$ , linear classification with neural network activations as features, and linear systems arising from physical models with interaction whose strength decays with distance.

Existing bilinear minimax solvers do not exploit the numerical sparsity of  $A$  and their runtime guarantees do not depend on it—the basic limitation of these methods is that they do not directly access the large matrix entries, and instead sample the full columns and rows in which they occur. To overcome this limitation, we propose methods that access  $A$  a single entry at a time, leverage numerical sparsity by accessing larger coordinates more frequently, and enjoy runtime guarantees that depend explicitly on numerical sparsity measures. For numerically sparse large-scale instances our runtimes are substantially better than the previous state-of-the-art. Moreover, our runtimes subsume the previous state-of-the-art dependence on  $\text{nnz}$  and  $\text{rcs}$ , the maximum number of nonzeros in any row or column.

In addition to proposing algorithms with improved runtimes, we develop two techniques that may be of broader interest. First, we design non-uniform sampling schemes that minimize regret bounds; we use a general framework that unifies the Euclidean and (local norms) simplex geometries, possibly facilitating future extension. Second, we build a data structure capable of efficiently maintaining and sampling from multiplicative weights iterations (i.e. entropic projection) *with a fixed dense component*. This data structure overcomes limitations of existing techniques for maintaining entropic projections and we believe it may prove effective in other settings where such projections appear.

## 1.1 Our results

Table 2 summarizes our runtime guarantees and puts them in the context of the best existing results. We consider methods that output (expected)  $\epsilon$ -accurate solutions of the saddle-point problem (1), namely a pair  $x, y$  satisfying

$$\mathbb{E} \left[ \max_{v \in \mathcal{Y}} v^\top A x - \min_{u \in \mathcal{X}} y^\top A u \right] \leq \epsilon.$$

The algorithms in Table 2 are all iterative solvers for the general problem  $\min_{x \in \mathcal{X}} \max_{y \in \mathcal{Y}} f(x, y)$ , specialized to  $f(x, y) = y^\top A x$ . Each algorithm presents a different tradeoff between per-iteration complexity and the required iteration count, corresponding to the matrix access modality: exact gradient methods compute matrix-vector products in each iteration, row-column stochastic gradient methods sample a row and a column in each iteration, and our proposed coordinate methods take this tradeoff to an extreme by sampling a single coordinate of the matrix per iteration.<sup>1</sup> In addition, variance reduction (VR) schemes combine both fast stochastic gradient computations and infrequent exact gradient computations, maintaining the amortized per-iteration cost of the stochastic scheme and reducing the total iteration count for sufficiently small  $\epsilon$ .

The runtimes in Table 2 depend on the numerical range of  $A$  through a matrix norm  $L$  that changes with both the problem geometry and the type of matrix access; we use  $L_{mv}$ ,  $L_{rc}$  and  $L_{co}$  to denote the constants corresponding to matrix-vector products, row-column queries and coordinated queries, respectively. Below, we describe these runtimes in detail. In the settings we study, our results are the first theoretical demonstration of runtime gains arising from sampling a single coordinate of  $A$  at a time, as opposed to entire rows and columns.

**Coordinate stochastic gradient methods.** We develop coordinate stochastic gradient estimators which allow per-iteration cost  $\tilde{O}(1)$  and iteration count  $\tilde{O}(n + m + (\frac{L_{co}}{\epsilon})^2)$ . We define  $L_{co}$  in Table 1; for each domain geometry, the quantity  $\frac{L_{co}}{L_{rc}}$  is a measure of the numerical sparsity of  $A$ , satisfying

$$1 \leq \frac{L_{co}^2}{L_{rc}^2} \leq \text{rcs}.$$

Every iteration of our method requires sampling an element in a row or a column with probability proportional to its entries. Assuming a matrix access model that allows such sampling in time  $\tilde{O}(1)$  (similarly to [5, 41, 15]), the total runtime of our method is  $\tilde{O}(n + m + (\frac{L_{co}}{\epsilon})^2)$ . In this case, for numerically sparse problems such that  $L_{co} = O(L_{rc})$ , the proposed coordinate methods outperform row-column sampling by a factor of  $m + n$ . Moreover, the bound  $L_{co}^2 \leq L_{rc}^2(m + n)$  implies that our runtime is never worse than that of row-column methods. When only coordinate access to the matrix  $A$  is initially available, we may implement the required sampling access via preprocessing in time  $O(\text{nnz})$ . This changes the runtime to  $\tilde{O}(\text{nnz} + (\frac{L_{co}}{\epsilon})^2)$ , so that the comparison above holds only when  $(\frac{L_{co}}{\epsilon})^2 = \tilde{\Omega}(\text{nnz})$ . In that regime, the variance reduction technique we describe below provides even stronger guarantees.

**Coordinate methods with variance reduction.** Using our recently proposed framework [8] we design a variance reduction algorithm with amortized per-iteration cost  $\tilde{O}(1)$ , required iteration count of  $\tilde{O}(\sqrt{\text{nnz}} \cdot \frac{L_{co}}{\epsilon})$  and total running time  $\tilde{O}(\text{nnz} + \sqrt{\text{nnz}} \cdot \frac{L_{co}}{\epsilon})$ . In the numerically sparse regime  $L_{co} = O(L_{rc})$ , our runtime improves on row-column VR by a factor of  $\sqrt{\text{nnz}/(m + n)}$ , and in general the bound  $L_{co} \leq L_{rc}\sqrt{m + n}$  guarantees it is never worse. Since variance reduction methods always require a single pass over the data to compute an exact gradient, this comparison holds regardless of the matrix access model. In the  $\ell_2$ - $\ell_2$  setting we note that for *elementwise*

---

<sup>1</sup> Interior point methods offer an alternative tradeoff between iteration cost and iteration count: the number of required iterations depends on  $1/\epsilon$  only logarithmically, but every iteration is costly, requiring a linear system solution which at present takes time  $\Omega(\min\{m, n\}^2)$ . In the  $\ell_1$ - $\ell_1$  geometry, the best known runtimes for interior point methods are  $\tilde{O}((\text{nnz} + \min\{m, n\}^2)\sqrt{\min\{m, n\}})$  [23],  $\tilde{O}(\max\{m, n\}^\omega)$  [12], and  $\tilde{O}(mn + \min\{m, n\}^3)$  [45]. In this paper we are mainly interested in the large-scale low-accuracy regime with  $L/\epsilon < \min(m, n)$  where the runtimes described in Table 2 are favorable (with the exception of [45] in certain cases). Our methods take only few passes over the data, which are not the case for many interior-point methods [23, 12]. Also, our methods do not rely on a general (ill-conditioned) linear system solver, which is a key ingredient in interior point methods.

|                     | $L_{mv}$ (matrix-vector) | $L_{rc}$ (row-column) | $L_{co}$ (coordinate)  |
|---------------------|--------------------------|-----------------------|--|
| $\ell_1$ - $\ell_1$ | $\max_{i,j}  A_{ij} $    | $\max_{i,j}  A_{ij} $ | $\max \left\{ \max_i \ A_{i:}\ _2, \max_j \ A_{:j}\ _2 \right\}$                   |
| $\ell_2$ - $\ell_1$ | $\max_i \ A_{i:}\ _2$    | $\max_i \ A_{i:}\ _2$ | $\max \left\{ \max_i \ A_{i:}\ _1, \ A\ _F \right\}^\dagger$                       |
| $\ell_2$ - $\ell_2$ | $\ A\ _{op}$             | $\ A\ _F$             | $\max \left\{ \sqrt{\sum_i \ A_{i:}\ _1^2}, \sqrt{\sum_j \ A_{:j}\ _1^2} \right\}$ |

Table 1: **Dependence on  $A$  for different methods in different geometries.** Comments:  $A_{i:}$  and  $A_{:j}$  denote the  $i$ th row and  $j$ th column of  $A$ , respectively. Numerically sparse instances satisfy  $L_{co} = O(L_{rc})$ .  $^\dagger$  In the  $\ell_2$ - $\ell_1$  setting we can also achieve, via alternative sampling schemes,  $L_{co} = L_{rc}\sqrt{rcs}$  and  $L_{co} = \max\{\max_i \|A_{i:}\|_1, \sqrt{\max_i \|A_{i:}\|_1 \max_j \|A_{:j}\|_1}\}$ .

| Method                             | Iteration cost          | Total runtime   |
|------------------------------------|-------------------------|---|
| Exact gradient [28, 31]            | $O(\text{nnz})$         | $\tilde{O}(\text{nnz} \cdot L_{mv} \cdot \epsilon^{-1})$                                      |
| Row-column [16, 10, 7]             | $O(n + m)$              | $\tilde{O}((m + n) \cdot L_{rc}^2 \cdot \epsilon^{-2})$                                       |
| Row-column VR [7, 8]               | $O(n + m)$              | $\tilde{O}(\text{nnz} + \sqrt{\text{nnz} \cdot (m + n)} \cdot L_{rc} \cdot \epsilon^{-1})$    |
| Sparse row-col (folklore)          | $\tilde{O}(\text{rcs})$ | $\tilde{O}(\text{rcs} \cdot L_{rc}^2 \cdot \epsilon^{-2})$                                    |
| Sparse row-col VR (Appendix E)     | $\tilde{O}(\text{rcs})$ | $\tilde{O}(\text{nnz} + \sqrt{\text{nnz} \cdot \text{rcs}} \cdot L_{rc} \cdot \epsilon^{-1})$ |
| <b>Coordinate (Section 3.1)</b>    | $\tilde{O}(1)$          | $\tilde{O}(\text{nnz} + L_{co}^2 \cdot \epsilon^{-2})$  |
| <b>Coordinate VR (Section 3.2)</b> | $\tilde{O}(1)$          | $\tilde{O}(\text{nnz} + \sqrt{\text{nnz}} \cdot L_{co} \cdot \epsilon^{-1})$                  |

Table 2: **Comparison of iterative methods for bilinear problems.** Comments:  $\text{nnz}$  denotes the number of nonzeros in  $A \in \mathbb{R}^{m \times n}$  and  $\text{rcs} \leq \max\{m, n\}$  denotes the maximum number of nonzeros in any row and column of  $A$ . The quantities  $L_{mv}$ ,  $L_{co}$  and  $L_{rc}$  depend on problem geometry (see Table 1).

| Task                                       | Method                 | Runtime   |
|--|------------------------|---|
| MaxIB                                      | Allen-Zhu et al. [2]   | $\tilde{O}(mn + \rho m \sqrt{n} \cdot \epsilon^{-1})$   |
|  | Our method (Theorem 3) | $\tilde{O}(\text{nnz} + \rho \sqrt{\text{nnz} \cdot \text{rcs}} \cdot \epsilon^{-1})^\dagger$   |
| MinEB<br>(when $m \geq n$ )                | Allen-Zhu et al. [2]   | $\tilde{O}(mn + m \sqrt{n} \cdot \epsilon^{-1/2})$  |
|  | Our method (Theorem 4) | $\tilde{O}(\text{nnz} + \sqrt{\text{nnz} \cdot \text{rcs}} \cdot \epsilon^{-1/2})^\dagger$  |
| Regression<br>( $A^\top A \succeq \mu I$ ) | AGD [30]               | $\tilde{O}(\text{nnz} \cdot \ A\ _{op} \frac{1}{\sqrt{\mu}})$   |
|  | Gupta and Sidford [17] | $\tilde{O}(\text{nnz} + \text{nnz}^{2/3} \cdot \left( \sum_{i \in [n]} \ A\ _F \cdot \ A_{i:}\ _1 \cdot \ A_{i:}\ _2 \right)^{1/3} \frac{1}{\sqrt{\mu}})$ |
|  | Our method (Theorem 5) | $\tilde{O}(\text{nnz} + \sqrt{\text{nnz}} \cdot \max \left\{ \sqrt{\sum_i \ A_{i:}\ _1^2}, \sqrt{\sum_j \ A_{:j}\ _1^2} \right\} \frac{1}{\sqrt{\mu}})$   |

Table 3: **Comparison of complexity for different applications.** Comments:  $\rho$  denotes the radii ratio of the minimum ball enclosing the rows of  $A$  and maximum ball inscribed in them.  $^\dagger$  For MaxIB and MinEB, we refer the reader to Section 6.2 for a more fine-grained runtime bound.

*non-negative* matrices,  $L_{\text{co}} = \max\{\|A\mathbf{1}\|_2, \|A^\top \mathbf{1}\|_2\} \leq L_{\text{mv}}\sqrt{m+n}$ , and consequently our method outperforms exact gradient methods by a factor of  $\sqrt{\text{nnz}/(m+n)}$ , even without any numerical or spectral sparsity in  $A$ . Notably, this is the same factor of improvement that row-column VR achieves over exact gradient methods in the  $\ell_1$ - $\ell_1$  and  $\ell_2$ - $\ell_1$  regimes.

**Optimality of the constant  $L_{\text{co}}$ .** For the  $\ell_1$ - $\ell_1$  and  $\ell_2$ - $\ell_2$  settings, we argue that the constant  $L_{\text{co}}$  in Table 1 is optimal in the restricted sense that no alternative sampling distribution for coordinate gradient estimation can have a better variance bound than  $L_{\text{co}}$  (a similar sense of optimality also holds for  $L_{\text{rc}}$  in each geometry). In the  $\ell_2$ - $\ell_1$  setting, a different sampling distribution produces an improved (and optimal) constant  $\max\{\max_i \|A_{i:}\|_1, \|A\|_{\text{op}}\}$ , where  $A_{i:}$  is the  $i$ th row of  $A$ , and  $|A|_{ij} = |A_{ij}|$  is the elementwise absolute value of  $A$ . However, it is unclear how to efficiently sample from this distribution.

**Row-column sparse instances.** Some problem instances admit a structured form of sparsity where every row and column has at most  $\text{rcs}$  nonzero elements. In all settings we have  $L_{\text{co}} \leq L_{\text{rc}}\sqrt{\text{rcs}}$  and so our coordinate methods naturally improve when  $\text{rcs}$  is small. Specifically, the sampling distributions and data structures we develop in this paper allow us to modify previous methods for row-column VR [8] to leverage row-column sparsity, reducing the amortized per-iteration cost from  $O(m+n)$  to  $\tilde{O}(\text{rcs})$ .

**Applications.** We illustrate the implications of our results for two problems in computational geometry, minimum enclosing ball (Min-EB) and maximum inscribed ball (Max-IB), as well as linear regression. For Min-EB and Max-IB in the non-degenerate case  $m \geq n$ , we apply our  $\ell_2$ - $\ell_1$  results to obtain algorithms whose runtime bounds coincide with the state-of-the-art [2] for dense problems, but can be significantly better for sparse or row-column sparse instances. For linear regression we focus on accelerated linearly converging algorithms, i.e., those that find  $x$  such that  $\|Ax - b\|_2 \leq \epsilon$  in time proportional to  $\mu^{-\frac{1}{2}} \log \frac{1}{\epsilon}$  where  $\mu$  is the smallest eigenvalue of  $A^\top A$ . Within this class and in a number of settings, our reduced variance coordinate method offers improvement over the state-of-the-art: for instances where  $\|A_{i:}\|_1 = O(\|A_{i:}\|_2)$  and  $\|A_{:j}\|_1 = O(\|A_{:j}\|_2)$  for all  $i, j$  it outperforms [17] by a factor of  $\text{nnz}^{1/6}$ , and for elementwise nonnegative instances it outperforms accelerated gradient descent by a factor of  $\sqrt{\text{nnz}/(m+n)}$ . See Table 3 for a detailed runtime comparison.

## 1.2 Our approach

We now provide a detailed overview of our algorithm design and analysis techniques, highlighting our main technical insights. We focus on the  $\ell_1$ - $\ell_1$  geometry, since it showcases all of our developments. Our technical contributions have two central themes:

1. **Sampling schemes design.** The key to obtaining efficient coordinate methods is carefully choosing the sampling distribution. Here, local norms analysis of stochastic mirror descent [39] on the one hand enables tight regret bounds, and on the other hand imposes an additional design constraint since the stochastic estimators must be bounded for the analysis to apply. We achieve estimators with improved variance bounds meeting this boundedness constraint by leveraging a “clipping” operation introduced by Clarkson et al. [10]. Specifically, in the simplex geometry, we truncate large coordinates of our estimators, and show that our method is robust to the resulting distortion.

2. **Data structure design.** Our goal is to perform iterations in  $\tilde{O}(1)$  time, but our mirror descent procedures call for updates that change  $m+n$  variables in each step. We resolve this tension via data structures that implicitly maintain the iterates. Variance reduction poses a considerable challenge here, because every reduced-variance stochastic gradient contains a dense component that changes all coordinates in a complicated way. In particular, existing data structures cannot efficiently compute the normalization factor necessary for projection to the simplex. We design a data structure that overcomes this hurdle via Taylor expansions, coordinate binning, and a binomial heap-like construction. The data structure computes approximate mirror projections, and we modify the standard mirror descent analysis to show it is stable under the particular structure of the resulting approximation errors.

At the intersection of these two themes is a novel sampling technique we call “sampling from the sum,” which addresses the same variance challenges as the “sampling from the difference” technique of [8], but is more amenable to efficient implementation with a data structure.

### 1.2.1 Coordinate stochastic gradient method

Our algorithm is an instance of stochastic mirror descent [29], which in the  $\ell_1$ - $\ell_1$  setting produces a sequence of iterates  $(x_1, y_1), (x_2, y_2), \dots$  according to

$$x_{t+1} = \Pi_{\Delta}(x_t \circ \exp\{-\eta \tilde{g}^x(x_t, y_t)\}) \quad \text{and} \quad y_{t+1} = \Pi_{\Delta}(y_t \circ \exp\{-\eta \tilde{g}^y(x_t, y_t)\}), \quad (2)$$

where  $\Pi_{\Delta}(v) = \frac{v}{\|v\|_1}$  is the projection onto the simplex (exp and log are applied to vectors elementwise, and elementwise multiplication is denoted by  $\circ$ ),  $\eta$  is a step size, and  $\tilde{g}^x, \tilde{g}^y$  are stochastic gradient estimators for  $f(x, y) = y^{\top} Ax$  satisfying

$$\mathbb{E} \tilde{g}^x(x, y) = \nabla_x f(x, y) = A^{\top} y \quad \text{and} \quad \mathbb{E} \tilde{g}^y(x, y) = -\nabla_y f(x, y) = -Ax.$$

We describe the computation and analysis of  $\tilde{g}^x$ ; the treatment of  $\tilde{g}^y$  is analogous. To compute  $\tilde{g}^x(x, y)$ , we sample  $i, j$  from a distribution  $p(x, y)$  on  $[m] \times [n]$  and let

$$\tilde{g}^x(x, y) = \frac{y_i A_{ij}}{p_{ij}(x, y)} e_j, \quad (3)$$

where  $p_{ij}(x, y)$  denotes the probability of drawing  $i, j$  from  $p(x, y)$  and  $e_j$  is the  $j$ th standard basis vector—a simple calculation shows that  $\mathbb{E} \tilde{g}^x = A^{\top} y$  for any  $p$ . We first design  $p(x, y)$  to guarantee an  $\tilde{O}((\frac{L_{\infty}}{\epsilon})^2)$  iteration complexity for finding an  $\epsilon$ -accurate solution, and then briefly touch on how to compute the resulting iterations in  $\tilde{O}(1)$  time.

**Local norms-informed distribution design.** The standard stochastic mirror descent analysis [29] shows that if  $\mathbb{E} \|\tilde{g}^x(x, y)\|_{\infty}^2 \leq L^2$  for all  $x, y$  (and similarly for  $\tilde{g}^y$ ), taking  $\eta = \frac{\epsilon}{L^2}$  and a choice of  $T = \tilde{O}((\frac{L}{\epsilon})^2)$  suffices to ensure that the iterate average  $\frac{1}{T} \sum_{t=1}^T (x_t, y_t)$  is an  $\epsilon$ -accurate solution in expectation. Unfortunately, this analysis demonstrably fails to yield sufficiently tight bounds for our coordinate estimator: there exist instances for which any distribution  $p$  produces  $L \geq nL_{rc}$ . We tighten the analysis using a *local norms* argument [cf. 39, Section 2.8], showing that  $\tilde{O}((\frac{L}{\epsilon})^2)$  iterations suffice whenever  $\|\eta \tilde{g}^x\|_{\infty} \leq 1$  with probability 1 and for all  $x, y$

$$\mathbb{E} \|\tilde{g}^x(x, y)\|_x^2 \leq L^2, \quad \text{where} \quad \|\gamma\|_x^2 = \sum_j x_j \gamma_j^2$$



is the local norm at  $x \in \mathcal{X}$ . We take

$$p_{ij} = y_i \frac{A_{ij}^2}{\|A_{i:}\|_2^2} \quad (4)$$

(recalling that  $x, y$  are both probability vectors). Substituting into (3) gives

$$\mathbb{E} \|\tilde{g}^x(x, y)\|_x^2 = \sum_{i,j} \frac{y_i^2 A_{ij}^2 x_j}{p_{ij}} = \sum_{i,j} y_i \|A_{i:}\|_2^2 x_j = \sum_i y_i \|A_{i:}\|_2^2 \leq \max_i \|A_{i:}\|_2^2 \leq L_{\text{co}}^2,$$

with  $L_{\text{co}} = \max\{\max_i \|A_{i:}\|_2, \max_j \|A_{:j}\|_2\}$  as in Table 1.

While this is the desired bound on  $\mathbb{E} \|\tilde{g}^x(x, y)\|_x^2$ , the requirement  $\|\eta \tilde{g}^x\|_\infty \leq 1$  does not hold when  $A$  has sufficiently small elements. We address this by clipping  $\tilde{g}$ : we replace  $\eta \tilde{g}^x$  with  $\text{clip}(\eta \tilde{g}^x)$ , where

$$[\text{clip}(v)]_i := \min\{|v_i|, 1\} \text{sign}(v_i),$$

the Euclidean projection to the unit box. The clipped gradient estimator clearly satisfies the desired bounds on infinity norm and local norm second moment, but is biased for the true gradient. Following the analysis of Clarkson et al. [10], we account for the bias by relating it to the second moment via

$$|\langle \gamma - \text{clip}(\gamma), x \rangle| \leq \|\gamma\|_x^2,$$

which allows to absorb the effect of the bias into existing terms in our error bounds. Putting together these pieces yields the desired bound on the iteration count.

**Efficient implementation.** Data structures for performing the update (2) and sampling from the resulting iterates in  $\tilde{O}(1)$  time are standard in the literature [e.g., 37]. We add to these the somewhat non-standard ability to also efficiently track the running sum of the iterates. To efficiently sample  $i, j \sim p$  according to (4) we first use the data structure to sample  $i \sim y$  in  $\tilde{O}(1)$  time and then draw  $j \in [n]$  with probability proportional to  $A_{ij}^2$  in time  $O(1)$ , via either  $O(\text{nnz})$  preprocessing or an appropriate assumption about the matrix access model. The “heavy lifting” of our data structure design is dedicated for supporting variance reduction, which we describe in the next section.

**Sampling distributions beyond  $\ell_1$ - $\ell_1$ .** Table 4 lists the sampling distributions we develop for the various problem geometries. Note that for the  $\ell_2$ - $\ell_1$  setting we give three different distributions for sampling the simplex block of the gradient (i.e.,  $\tilde{g}^y$ ); each distribution corresponds to a different parameter  $L_{\text{co}}$  (see comments following Table 1). The distribution  $q_{ij} \propto \sqrt{y_i} |A_{ij} x_j|$  yields a stronger bound  $L$  in the  $\ell_2$ - $\ell_1$  setting, but we do not know how to efficiently sample from it.

### 1.2.2 Coordinate variance reduction

To accelerate the stochastic coordinate method we apply our recently proposed variance reduction framework [8]. This framework operates in  $\frac{\alpha}{\epsilon}$  epochs, where  $\alpha$  is a design parameter that trades between full and stochastic gradient computations. Each epoch consists of three parts: (i) computing the exact gradient at a reference point  $(x_0, y_0)$ , (ii) performing  $T$  iterations of regularized stochastic mirror descent to produce the sequence  $(x_1, y_1), \dots, (x_T, y_T)$  and (iii) taking an extra-gradient step from the average of the iterates in (ii). Setting  $\kappa = 1/(1 + \eta\alpha/2)$ , the iterates  $x_t$  follow the recursion

$$x_{t+1} = \Pi_\Delta(x_t^\kappa \circ x_0^{1-\kappa} \circ \exp\{-\eta\kappa[g_0^x + \tilde{\delta}^x(x_t, y_t)]\}), \text{ where } \Pi_\Delta(v) = \frac{v}{\|v\|_1}, \quad (5)$$



and  $g_0^\times = A^\top y_0$  is the exact gradient at the reference point, and  $\tilde{\delta}^\times$  is a stochastic gradient *difference* estimator satisfying

$$\mathbb{E} \tilde{\delta}^\times(x, y) = \nabla_x f(x, y) - \nabla_x f(x_0, y_0) = A^\top (y - y_0).$$

The iteration for  $y_t$  is similar. In [8] we show that if  $\tilde{\delta}^\times$  satisfies

$$\mathbb{E} \|\tilde{\delta}^\times(x, y)\|_\infty^2 \leq L^2 \left( \|x - x_0\|_1^2 + \|y - y_0\|_1^2 \right) \quad \forall x, y \quad (6)$$

and a similar bound holds on  $\mathbb{E} \|\tilde{\delta}^y(x, y)\|_\infty^2$ , then  $T = O(\frac{L^2}{\alpha^2})$  iterations per epoch with step size  $\eta = \frac{\alpha}{L^2}$  suffice for the overall algorithm to return a point with expected error below  $\epsilon$ .

We would like to design a coordinate-based estimator  $\tilde{\delta}$  such that the bound (6) holds for  $L = L_{\text{co}}$  as in Table 1 and each iteration (5) takes  $\tilde{O}(1)$  time. Since every epoch also requires  $O(\text{nnz})$  time for matrix-vector product (exact gradient) computations, the overall runtime would be  $\tilde{O}((\text{nnz} + \frac{L_{\text{co}}^2}{\alpha^2}) \cdot \frac{\alpha}{\epsilon})$ . Choosing  $\alpha = L_{\text{co}}/\sqrt{\text{nnz}}$  then gives the desired runtime  $\tilde{O}(\text{nnz} + \sqrt{\text{nnz}} \cdot \frac{L_{\text{co}}}{\epsilon})$ .

**Distribution design (sampling from the difference).** We start with a straightforward adaptation of the general estimator form (3). To compute  $\tilde{\delta}^\times(x, y)$ , we sample  $i, j \sim p$ , where  $p$  may depend on  $x, x_0, y$  and  $y_0$ , and let

$$\tilde{\delta}^\times(x, y) = \frac{(y_i - [y_0]_i) A_{ij}}{p_{ij}} e_j, \quad (7)$$

where  $e_j$  is the  $j$ th standard basis vector. As in the previous section, we find that the requirement (6) is too stringent for coordinate-based estimators. Here too, we address this challenge with a local norms argument and clipping of the difference estimate. Using the “sampling from the difference” technique from [8], we arrive at

$$p_{ij} = \frac{|y_i - [y_0]_i|}{\|y - y_0\|_1} \cdot \frac{A_{ij}^2}{\|A_{i:}\|_2^2}. \quad (8)$$

This distribution satisfies the local norm relaxation of (6) with  $L^2 = L_{\text{co}}^2$ .

**Data structure design.** Efficiently computing (5) is significantly more challenging than its counterpart (2). To clarify the difficulty and describe our solution, we write

$$x_t = \Pi_\Delta(\hat{x}_t) = \hat{x}_t / \|\hat{x}_t\|_1$$

and break the recursion for the unnormalized iterates  $\hat{x}_t$  into two steps

$$\hat{x}'_t = \hat{x}_t^\kappa \circ \exp\{v\}, \text{ and} \quad (9)$$

$$\hat{x}_{t+1} = \hat{x}'_t \circ \exp\{s_t\}, \quad (10)$$

where  $v = (1 - \kappa) \log x_0 - \eta \kappa g_0^\times$  is a fixed dense vector, and  $s_t = -\eta \tilde{\delta}^\times(x_t, y_t)$  is a varying 1-sparse vector. The key task of the data structures is maintaining the normalization factor  $\|\hat{x}_t\|_1$  in near-constant time. Standard data structures do not suffice because they lack support for the dense step (9).

Our high-level strategy is to handle the two steps (9) and (10) separately. To handle the dense step (9), we propose the data structure **ScaleMaintainer** that efficiently approximates  $\|\hat{x}_t\|_1$  in the “homogeneous” case of no sparse updates (i.e.  $s_t = 0$  for all  $t$ ). We then add support for the sparse step (10) using a binomial heap-like construction involving  $O(\log n)$  instances of **ScaleMaintainer**.

**The ScaleMaintainer data structure.** When  $s_t = 0$  for all  $t$  the iterates  $\hat{x}_t$  admit closed forms

$$\hat{x}_{t+\tau} = \hat{x}_t^{\kappa^\tau} \circ \exp \left\{ v \sum_{t'=0}^{\tau-1} \kappa^{t'} \right\} = \hat{x}_t^{\kappa^\tau} \circ \exp \left\{ \frac{1 - \kappa^\tau}{1 - \kappa} v \right\} = \hat{x}_t \circ \exp \{ [1 - \kappa^\tau] \bar{v} \},$$

where  $\bar{v} = \frac{v}{1-\kappa} - \log x_t$ . Consequently, we design **ScaleMaintainer** to take as initialization  $\bar{n}$ -dimensional vectors  $\bar{x} \in \mathbb{R}_{\geq 0}^{\bar{n}}$ , and  $\bar{v} \in \mathbb{R}^{\bar{n}}$  and provide approximations of the normalization factor

$$Z_\tau(\bar{x}, \bar{v}) = \|\bar{x} \circ \exp\{(1 - \kappa^\tau)\bar{v}\}\|_1 \quad (11)$$

for arbitrary values of  $\tau \geq 1$ . We show how to implement each query of  $Z_\tau(\bar{x}, \bar{v})$  in amortized time  $\tilde{O}(1)$ . The data structure also supports initialization in time  $\tilde{O}(\bar{n})$  and deletions (i.e., setting elements of  $\bar{x}$  to zero) in amortized time  $\tilde{O}(1)$ .

To efficiently approximate the quantity  $Z_\tau(\bar{x}, \bar{v})$  we replace the exponential with its order  $p = O(\log n)$  Taylor series. That is, we would like to write

$$Z_\tau(\bar{x}, \bar{v}) = \sum_{i \in [\bar{n}]} [\bar{x}]_i e^{(1-\kappa^\tau)[\bar{v}]_i} \approx \sum_{i \in [\bar{n}]} [\bar{x}]_i \sum_{q=0}^p \frac{1}{q!} (1 - \kappa^\tau)^q [\bar{v}]_i^q = \sum_{q=0}^p \frac{(1 - \kappa^\tau)^q}{q!} \langle \bar{x}, \bar{v}^q \rangle.$$

The approximation  $\sum_{q=0}^p \frac{(1-\kappa^\tau)^q}{q!} \langle \bar{x}, \bar{v}^q \rangle$  is cheap to compute, since for every  $\tau$  it is a linear combination of the  $p = \tilde{O}(1)$  numbers  $\{\langle \bar{x}, \bar{v}^q \rangle\}_{q \in [p]}$  which we can compute once at initialization. However, the Taylor series approximation has low multiplicative error only when  $|(1 - \kappa^\tau)[\bar{v}]_i| = O(p)$ , which may fail to hold, as we may have  $\|\bar{v}\|_\infty = \text{poly}(n)$  in general. To handle this, suppose that for a fixed  $\tau$  we have an offset  $\mu \in \mathbb{R}$  and “active set”  $A \subseteq [\bar{n}]$  such that the following conditions hold for a threshold  $R = O(p)$ : (a) the Taylor approximation is valid in  $A$ , e.g. we have  $|(1 - \kappa^\tau)(\bar{v}_i - \mu)| \leq 2R$  for all  $i \in A$ , (b) entries outside  $A$  are small;  $(1 - \kappa^\tau)[\bar{v}_i - \mu] \leq -R$  for all  $i \notin A$ , and (c) at least one entry in the active set is large;  $(1 - \kappa^\tau)[\bar{v}_i - \mu] \geq 0$  for some  $i \in A$ . Under these conditions, the entries in  $A^c$  are negligibly small and we can truncate them, resulting in the approximation

$$e^{(1-\kappa^\tau)\mu} \left[ \sum_{q=0}^p \frac{(1 - \kappa^\tau)^q}{q!} \langle \bar{x}, (\bar{v} - \mu)^q \rangle_A + e^{-R} \langle \bar{x}, \mathbf{1} \rangle_{A^c} \right],$$

which we show approximates  $Z_\tau(\bar{x}, \bar{v})$  to within  $e^{O(R + \log n) - \Omega(p)}$  multiplicative error, where we used  $\langle a, b \rangle_S := \sum_{i \in S} a_i b_i$ ; here, we also require that  $\log \frac{\max_i \bar{x}_i}{\min_i \bar{x}_i} = O(R)$ , which we guarantee when choosing the initial  $\bar{x}$ .

The challenge then becomes efficiently mapping any  $\tau$  to  $\{\langle \bar{x}, (\bar{v} - \mu)^q \rangle_A\}_{q \in [p]}$  for suitable  $\mu$  and  $A$ . We address this by jointly bucketing  $\tau$  and  $\bar{v}$ . Specifically, we map  $\tau$  into a bucket index  $k = \lfloor \log_2 \frac{1-\kappa^\tau}{1-\kappa} \rfloor$ , pick  $\mu$  to be the largest integer multiple of  $R/((1-\kappa)2^k)$  such that  $\mu \leq \max_i \bar{v}_i$ , and set  $A = \{i \mid |(1-\kappa)2^k(\bar{v}_i - \mu)| \leq R\}$ . Since  $k \leq k_{\max} = \lfloor \log_2 \frac{1}{1-\kappa} \rfloor = O(\log n)$ , we argue that computing  $\langle \bar{x}, (\bar{v} - \mu)^q \rangle_A$  for every possible resulting  $\mu$  and  $A$  takes at most  $O(\bar{n} p \log \frac{1}{1-\kappa}) = \tilde{O}(\bar{n})$  time, which we can charge to initialization. We further show how to support deletions in  $\tilde{O}(1)$  time by carefully manipulating the computed quantities.

**Supporting sparse updates.** Building on **ScaleMaintainer**, we design the data structure **ApproxExpMaintainer** that (approximately) implements the entire mirror descent step (5) in time

$\tilde{O}(1)$ .<sup>2</sup> The data structure maintains vectors  $\bar{x} \in \Delta^n$  and  $\bar{v} \in \mathbb{R}^n$  and  $K = \lceil \log_2(n+1) \rceil$  instances of **ScaleMaintainer** denoted  $\{\text{ScaleMaintainer}_k\}_{k \in [K]}$ . The  $k$ th instance tracks a coordinate subset  $S_k \subseteq [n]$  such that  $\{S_k\}_{k \in [K]}$  partitions  $[n]$ , and has initial data  $[\bar{x}]_{S_k}$  and  $[\bar{v}]_{S_k}$ . We let  $\tau_k \geq 0$  denote the “time index” parameter of the  $k$ th instance. The data structure satisfies two invariants; first, the unnormalized iterate  $\hat{x}$  satisfies

$$[\hat{x}]_{S_k} = [\bar{x} \circ \exp\{(1 - \kappa^{\tau_k})\bar{v}\}]_{S_k}, \text{ for all } k \in [K]. \quad (12)$$

Second, the partition satisfies

$$|S_k| \leq 2^k - 1 \text{ for all } k \in [K], \quad (13)$$

where at initialization we let  $S_K = [n]$  and  $S_k = \emptyset$  for  $k < K$ ,  $\bar{x} = x_0$ ,  $\bar{v} = \frac{v}{1-\kappa} - \log x_0$  and  $\tau_K = 0$ .

The invariant (12) allows us to efficiently (in time  $\tilde{O}(K) = \tilde{O}(1)$ ) query coordinates of  $x_t = \hat{x}_t / \|\hat{x}_t\|_1$ , since **ScaleMaintainer** allows us to approximate  $\|\hat{x}_t\|_1 = \sum_{k \in [K]} Z_{\tau_k}([\bar{x}]_{S_k}, [\bar{v}]_{S_k})$  with  $Z$  as defined in (11). To implement the dense step (9), we simply increment  $\tau_k \leftarrow \tau_k + 1$  for every  $k$ . Let  $j$  be the nonzero coordinate of  $s_t$  in the sparse step (10), and let  $k \in [K]$  be such that  $j \in S_k$ . To implement (10), we delete coordinate  $j$  from **ScaleMaintainer** <sub>$k$</sub> , and create a singleton instance **ScaleMaintainer**<sub>0</sub> maintaining  $S_0 = \{j\}$  with initial data  $[\bar{x}]_{S_0} = e^{s_t} \hat{x}_j$ ,  $[\bar{v}]_{S_0} = v_j / (1 - \kappa) - \log(e^{s_t} \hat{x}_j)$  and  $\tau_0 = 0$ . Going from  $k = 1$  to  $k = K$ , we merge **ScaleMaintainer** <sub>$k-1$</sub>  into **ScaleMaintainer** <sub>$k$</sub>  until the invariant (13) holds again. For example, if before the sparse step we have  $|S_1| = 1$ ,  $|S_2| = 3$  and  $|S_3| = 2$ , we will perform 3 consecutive merges, so that afterwards we have  $|S_1| = |S_2| = 0$  and  $|S_3| = 7$ .

To merge two **ScaleMaintainer** <sub>$k-1$</sub>  into **ScaleMaintainer** <sub>$k$</sub> , we let  $S'_k = S_{k-1} \cup S_k$  and initialize a new **ScaleMaintainer** instance with  $[\bar{x}]_{S'_k} = [\hat{x}]_{S'_k}$ ,<sup>3</sup>  $[\bar{v}]_{S'_k} = [v]_{S'_k} / (1 - \kappa) - \log[\hat{x}]_{S'_k}$  and  $\tau_k = 0$ ; this takes  $\tilde{O}(|S'_k|) = \tilde{O}(2^k)$  time due to the invariant (13). Noting that a merge at level  $k$  can only happen once in every  $\Omega(2^k)$  updates, we conclude that the amortized cost of merges at each level is  $\tilde{O}(1)$ , and (since  $K = \tilde{O}(1)$ ), so is the cost of the sparse update.

**Back to distribution design (sampling from the sum).** Our data structure enables us to compute the iteration (5) and query coordinates of the iterates  $x_t$  and  $y_t$  in  $\tilde{O}(1)$  amortized time. However, we cannot compute  $\tilde{\delta}^x$  using the distribution (8) because we do not have an efficient way of sampling from  $|y_t - y_0|$ ; Taylor approximation techniques are not effective for approximating the absolute value because it is not smooth. To overcome this final barrier, we introduce a new design which we call “sampling from the sum,”

$$p_{ij}(x, y) = \left( \frac{1}{3}y_i + \frac{2}{3}[y_0]_i \right) \cdot \frac{A_{ij}^2}{\|A_{i:}\|_2^2}. \quad (14)$$

Sampling from the modified distribution is simple, as our data structure allows us to sample from  $y_t$ . Moreover, we show that the distribution (14) satisfies a relaxed version of (6) where the LHS is replaced by a local norm as before, and the RHS is replaced by  $L^2(V_{x_0}(x_t) + V_{y_0}(y_t))$ , where  $V_x(x')$  is the KL divergence between  $x$  and  $x'$ . In Table 5 we list the sampling distributions we design for variance reduction in the different domain geometries.

<sup>2</sup>The data structures **ApproxExpMaintainer** and **ScaleMaintainer** structure support two additional operations necessary for our algorithm: efficient approximate sampling from  $x_t$  and maintenance of a running sum of  $\hat{x}_\tau$ . Given the normalization constant approximation, the implementation of these operations is fairly straightforward, so we do not discuss them in the introduction.

<sup>3</sup>More precisely, for every  $j \in S'_k$  we set  $\bar{x}_j = \hat{x}_j + \varepsilon \max_{i \in S'_k} \hat{x}_i$ , where  $\varepsilon$  is a small padding constant that ensures the bounded multiplicative range necessary for correct operation of **ScaleMaintainer**.

| Setting                | $p_{ij}$   | $q_{ij}$   |
|------------------------|--|--|
| $\ell_1\text{-}\ell_1$ | $y_i \cdot \frac{A_{ij}^2}{\ A_{i:}\ _2^2}$  | $x_j \cdot \frac{A_{ij}^2}{\ A_{:j}\ _2^2}$  |
| $\ell_2\text{-}\ell_1$ | $y_i \cdot \frac{ A_{ij} }{\ A_{i:}\ _1}$  | $\frac{A_{ij}^2}{\ A\ _F^2}$   |
| $\ell_2\text{-}\ell_1$ | $y_i \cdot \frac{ A_{ij} }{\ A_{i:}\ _1}$  | $\propto x_j^2 \cdot \mathbf{1}_{A_{ij} \neq 0}$   |
| $\ell_2\text{-}\ell_1$ | $y_i \cdot \frac{ A_{ij} }{\ A_{i:}\ _1}$  | $\frac{A_{ij} \cdot x_j^2}{\sum_{k \in [n]} \ A_{:k}\ _1 \cdot x_k^2}$                       |
| $\ell_2\text{-}\ell_2$ | $\frac{\ A_{i:}\ _1^2}{\sum_{k \in [m]} \ A_{k:}\ _1^2} \cdot \frac{ A_{ij} }{\ A_{i:}\ _1}$ | $\frac{\ A_{:j}\ _1^2}{\sum_{k \in [n]} \ A_{:k}\ _1^2} \cdot \frac{ A_{ij} }{\ A_{:j}\ _1}$ |
| $\ell_2\text{-}\ell_2$ | $\frac{y_i^2}{\ y\ _2^2} \cdot \frac{ A_{ij} }{\ A_{i:}\ _1}$                                | $\frac{x_j^2}{\ x\ _2^2} \cdot \frac{ A_{ij} }{\ A_{:j}\ _1}$                                |

Table 4: **The distributions  $p, q$  used in our coordinate gradient estimator.** Comments: The estimator is of the form  $\tilde{g}(x, y) = (\frac{1}{p_{ij}} y_i A_{ij} \cdot e_j, -\frac{1}{q_{lk}} A_{lk} x_k \cdot e_l)$  where  $i, j \sim p$  and  $l, k \sim q$ .

| Setting                | $p_{ij}$   | $q_{ij}$   |
|------------------------|--|--|
| $\ell_1\text{-}\ell_1$ | $\frac{y_i + 2[y_0]_i}{3} \cdot \frac{A_{ij}^2}{\ A_{i:}\ _2^2}$                             | $\frac{x_j + 2[x_0]_j}{3} \cdot \frac{A_{ij}^2}{\ A_{:j}\ _2^2}$                             |
| $\ell_2\text{-}\ell_1$ | $\frac{y_i + 2[y_0]_i}{3} \cdot \frac{ A_{ij} }{\ A_{i:}\ _1}$                               | $\frac{A_{ij}^2}{\ A\ _F^2}$   |
| $\ell_2\text{-}\ell_1$ | $\frac{y_i + 2[y_0]_i}{3} \cdot \frac{ A_{ij} }{\ A_{i:}\ _1}$                               | $\propto [x - x_0]_j^2 \cdot \mathbf{1}_{A_{ij} \neq 0}$                                     |
| $\ell_2\text{-}\ell_1$ | $\frac{y_i + 2[y_0]_i}{3} \cdot \frac{ A_{ij} }{\ A_{i:}\ _1}$                               | $\frac{ A_{ij}  \cdot [x - x_0]_j^2}{\sum_{k \in [n]} \ A_{:k}\ _1 \cdot [x - x_0]_k^2}$     |
| $\ell_2\text{-}\ell_2$ | $\frac{\ A_{i:}\ _1^2}{\sum_{k \in [m]} \ A_{k:}\ _1^2} \cdot \frac{ A_{ij} }{\ A_{i:}\ _1}$ | $\frac{\ A_{:j}\ _1^2}{\sum_{k \in [n]} \ A_{:k}\ _1^2} \cdot \frac{ A_{ij} }{\ A_{:j}\ _1}$ |
| $\ell_2\text{-}\ell_2$ | $\frac{[y - y_0]_i^2}{\ y - y_0\ _2^2} \cdot \frac{ A_{ij} }{\ A_{i:}\ _1}$                  | $\frac{[x - x_0]_j^2}{\ x - x_0\ _2^2} \cdot \frac{ A_{ij} }{\ A_{:j}\ _1}$                  |

Table 5: **The distributions  $p, q$  used for our reduced variance coordinate gradient estimator.** Comments: The estimator is of the form  $\tilde{g}(x, y) = (A^\top y + \frac{1}{p_{ij}}(y_i - y_{0,i})A_{ij} \cdot e_j, -Ax - \frac{1}{q_{lk}}A_{lk}(x_k - x_{0,k}) \cdot e_l)$  where  $i, j \sim p$  and  $l, k \sim q$  and  $x_0, y_0$  is a reference point.

### 1.3 Related work

**Coordinate methods.** Updating a single coordinate at a time—or more broadly computing only a single coordinate of the gradient at every iteration—is a well-studied and successful technique in optimization [50]. Selecting coordinates at random is key to obtaining strong performance guarantees: Strohmer and Vershynin [42] show this for linear regression, Shalev-Shwartz and Tewari [36] show this for  $\ell_1$  regularized linear models, and Nesterov [32] shows this for general smooth minimization. Later works [22, 3, 33] propose accelerated coordinate methods. These works share two common themes: selecting the gradient coordinate from a non-uniform distribution (see also [34]), and augmenting the 1-sparse stochastic gradient with a dense momentum term. These techniques play important roles in our development as well.

To reap the full benefits of coordinate methods, iterations must be very cheap, ideally taking near-constant time. However, most coordinate methods require super-constant time, typically in the form of a vector-vector computation. Even works that consider coordinate methods in a primal-dual context [38, 2, 52, 27, 37] perform the coordinate updates only on the dual variable and require a vector-vector product (or more generally a component gradient computation) at every iteration.

A notable exception is the work of Wang [49, 48] which develops a primal-dual stochastic coordinate method for solving Markov decision processes, essentially viewing them as  $\ell_\infty$ - $\ell_1$  bilinear saddle-point problems. Using a tree-based  $\ell_1$  sampler data structure similar to the  $\ell_1$  sampler we use for simplex domains for the sublinear case, the method allows for  $\tilde{O}(1)$  iterations and a potentially sublinear runtime scaling as  $\epsilon^{-2}$ . Tan et al. [43] also consider bilinear saddle-point problems and variance reduction. Unlike our work, they assume a separable domain, use uniform sampling, and do not accelerate their variance reduction scheme with extra-gradient steps. The separable domain makes attaining constant iteration cost time much simpler, since there is no longer a normalization factor to track, but it also rules out applications to the simplex domain. While Tan et al. [43] report promising empirical results, their theoretical guarantees do not improve upon prior work.

Our work develops coordinate methods with  $\tilde{O}(1)$  iteration cost for new types of problems. Furthermore, it maintains the iteration efficiency even in the presence of dense components arising from the update, thus allowing for acceleration via an extra-gradient scheme.

**Data structures for optimization.** Performing iterations in time that is asymptotically smaller than the number of variables updated at every iteration forces us to carry out the updates implicitly using data structures; several prior works employ data structures for exactly the same reason. One of the most similar examples comes from Lee and Sidford [22], who design a data structure for an accelerated coordinate method in Euclidean geometry. In our terminology, their data structure allows performing each iteration in time  $O(\text{rcs})$  while implicitly updating variables of size  $O(n)$ . Duchi et al. [14] design a data structure based on balanced search trees that supports efficient Euclidean projection to the  $\ell_1$  ball of vector of the form  $u + s$  where  $u$  is in the  $\ell_1$  ball and  $s$  is sparse. They apply it in a stochastic gradient method for learning  $\ell_1$  regularized linear classifier with sparse features. Among the many applications of this data structure, Namkoong and Duchi [27] adapt it to efficiently compute Euclidean projections into the intersection of the simplex and a  $\chi^2$  ball for 1-sparse updates. Shalev-Shwartz and Wexler [37] and Wang [49, 48], among others, use binary tree data structures to perform multiplicative weights projection to the simplex and sampling from the iterates.

A recent work of Sidford and Tian [40] develops a data structure which is somewhat similar to our **ApproxExpMaintainer** data structure, for updates arising from a primal-dual method to efficiently solve  $\ell_\infty$  regression. Their data structure was also designed to handle updates to a simplex variable which summed a structured dense component and a sparse component. However, the data structure

design of that work specifically exploited the structure of the maximum flow problem in a number of ways, such as bounding the sizes of the update components and relating these bounds to how often the entire data structure should be restarted. Our data structure can handle a broader range of structured updates to simplex variables and has a much more flexible interface, which is crucial to the development of our variance-reduced methods as well as our applications.

Another notable use of data structures in optimization appears in second order methods, where a long line of work uses them to efficiently solve sequences of linear systems and approximately compute iterates [20, 4, 23, 12, 25, 44, 45]. Finally, several works on low rank optimization make use of sketches to efficiently represent their iterates and solutions [9, 51].

**Numerical sparsity.** Measures of numerical sparsity, such as the  $\ell_2/\ell_\infty$  or  $\ell_1/\ell_2$  ratios, are continuous and dimensionless relaxations of the  $\ell_0$  norm. The *stable rank* of a matrix  $A$  measures the numerical sparsity of its singular values (specifically, their squared  $\ell_2/\ell_\infty$  ratio) [11].

For linear regression, stochastic methods generally outperform exact gradient methods only when  $A$  has low stable rank, cf. discussion in [8, Section 4.3], i.e., numerically sparse singular values. In recent work, Gupta and Sidford [17] develop algorithms for linear regression and eigenvector problems for matrices with numerically sparse entries (as opposed to singular values). Our paper further broadens the scope of matrix problems for which we can benefit from numerical sparsity. Moreover, our results have implications for regression as well, improving on [17] in certain numerically sparse regimes.

In recent work by Babichev et al. [6], the authors develop primal-dual sublinear methods for  $\ell_1$ -regularized linear multi-class classification (bilinear games in  $\ell_1$ - $\ell_\infty$  geometry), and obtain complexity improvements depending on the numerical sparsity of the problem. Similarly to our work, careful design of the sampling distribution plays a central role in [6]. They also develop a data structure that allows iteration cost independent of the number of classes. However, unlike our work, Babichev et al. [6] rely on sampling entire rows and columns, have iteration costs linear in  $n + m$ , and do not utilize variance reduction. We believe that our techniques can yield improvements in their setting.

## 1.4 Paper organization

In Section 2, we set up our terminology, notation, the interfaces of our data structures, and the different matrix access models we consider. In Section 3 we develop our algorithmic framework: we present coordinate stochastic gradient methods in Section 3.1 and their reduced variance counterparts in Section 3.2. In Section 4 we apply both methods to solving  $\ell_1$ - $\ell_1$  matrix games; we show how to implement the method using our data structures and analyze the runtime. In Section 5, we discuss in detail the implementation and analysis of our data structures. Finally, in Section 6 we specialize our results to obtain algorithms for minimum enclosing ball and maximum inscribed ball problems as well as linear regression. Many proof details as well as our algorithms for other domain setups, i.e.  $\ell_2$ - $\ell_1$  and  $\ell_2$ - $\ell_2$  are deferred to the appendix.

## 2 Preliminaries

In Section 2.1, we abstract the properties of the different domains we handle into a general notion of a “local norm” setup under which we develop our results. In Section 2.2, we give the definition and optimality criterion of the bilinear saddle-point problem we study. In Section 2.3, we give the matrix access models used in the algorithms we design. In Section 2.4, we summarize the interfaces and complexity of the data structures we design, deferring their detailed implementations to Section 5.

### 2.1 Local norm setups

The analyses of our algorithms cater to the geometric of each specific domain. To express our results generically, for each pair of domains  $\mathcal{Z} = \mathcal{X} \times \mathcal{Y}$ , we define an associated “local norm setup”, which contains various data tailored for our analyses. While initially this notation may appear complicated or cumbersome, later it helps avoid redundancy in the paper. Further, it clarifies the structure necessary to generalize our methods to additional domain geometries.

**Definition 1.** A local norm setup is the quintuplet  $(\mathcal{Z}, \|\cdot\|, r, \Theta, \text{clip})$ , where

1.  $\mathcal{Z}$  is a compact and convex subset of  $\mathcal{Z}^* := \mathbb{R}^n \times \mathbb{R}^m$ .
2.  $\|\cdot\|$  is a local norm: for every  $z \in \mathcal{Z}$ , the function  $\|\cdot\|_z : \mathcal{Z}^* \rightarrow \mathbb{R}_{\geq 0}$  is a norm on  $\mathcal{Z}^*$ .
3.  $r : \mathcal{Z} \rightarrow \mathbb{R}$  is a convex distance generating function: its induced Bregman divergence

$$V_z(z') := r(z') - r(z) - \langle \nabla r(z), z' - z \rangle.$$

satisfies

$$\langle \gamma, z - z' \rangle - V_z(z') \leq \frac{1}{2} \|\gamma\|_*^2 := \frac{1}{2} \max_{s \in \mathcal{Z}} \|\gamma\|_s^2 \quad \text{for all } z, z' \in \mathcal{Z} \text{ and } \gamma \in \mathcal{Z}^*. \quad (15)$$

4.  $\Theta = \max_{z, z' \in \mathcal{Z}} \{r(z) - r(z')\}$  is the range of  $r$ . For  $z^* \in \arg \min_{z \in \mathcal{Z}} r(z)$  we have  $\Theta$  is an upper bound on the range of  $V_{z^*}(z) \leq \Theta$  for all  $z \in \mathcal{Z}$ .
5.  $\text{clip} : \mathcal{Z}^* \rightarrow \mathcal{Z}^*$  is a mapping that enforces a local version of (15):

$$|\langle \text{clip}(\gamma), z - z' \rangle| - V_z(z') \leq \|\gamma\|_z^2 \quad \text{for all } z, z' \in \mathcal{Z} \text{ and } \gamma \in \mathcal{Z}^*, \quad (16)$$

and satisfies the distortion guarantee

$$|\langle \gamma - \text{clip}(\gamma), z \rangle| \leq \|\gamma\|_z^2 \quad \text{for all } z \in \mathcal{Z} \text{ and } \gamma \in \mathcal{Z}^*. \quad (17)$$

Table 6 summarizes the three local norm setups we consider. Throughout the paper,

for a vector  $z \in \mathcal{X} \times \mathcal{Y}$ , we denote its  $\mathcal{X}$  and  $\mathcal{Y}$  blocks by  $z^x$  and  $z^y$ .

In addition, we write coordinate  $i$  of any vector  $v$  as  $[v]_i$ .

**Proposition 1.** The quintuplets  $(\mathcal{Z}, \|\cdot\|, r, \Theta, \text{clip})$  in Table 6 satisfy the local norm setup requirements in Definition 1.



|                       | $\ell_1\text{-}\ell_1$                          | $\ell_2\text{-}\ell_1$  | $\ell_2\text{-}\ell_2$  |
|-----------------------|---|---|-------------------------|
| $\mathcal{X}$         | $\Delta^n$                                      | $\mathbb{B}^n$  | $\mathbb{B}^n$          |
| $\mathcal{Y}$         | $\Delta^m$                                      | $\Delta^m$  | $\mathbb{B}^m$          |
| $\ \delta\ _z$        | $\sqrt{\sum_{k \in [n+m]} [z]_k [\delta]_k^2}$  | $\sqrt{\ \delta^x\ _2^2 + \sum_{i \in [m]} [z^y]_i [\delta^y]_i^2}$ | $\ \delta\ _2$          |
| $r$                   | $\sum_{k \in [n+m]} [z]_k \log[z]_k$            | $\frac{1}{2} \ z^x\ _2^2 + \sum_{i \in [m]} [z^y]_i \log[z^y]_i$    | $\frac{1}{2} \ z\ _2^2$ |
| $\Theta$              | $\log(mn)$                                      | $\frac{1}{2} + \log(m)$   | 1                       |
| $\text{clip}(\delta)$ | $\text{sign}(\delta) \circ \min\{1,  \delta \}$ | $(\delta^x, \text{sign}(\delta^y) \circ \min\{1,  \delta^y \})$     | $\delta$                |

Table 6: **Local norm setups.** Comments: In each case,  $\mathcal{Z} = \mathcal{X} \times \mathcal{Y}$ ,  $\Delta^n$  is the probability simplex  $\{x \mid x \in \mathbb{R}_{\geq 0}^n, \mathbf{1}_n^\top x = 1\}$ ,  $\mathbb{B}^n$  is the Euclidean ball  $\{x \in \mathbb{R}^n, \|x\|_2 \leq 1\}$ , the operations  $\text{sign}$ ,  $\min$ , and  $|\cdot|$  are performed entrywise on a vector, and  $\circ$  stands for the entrywise product between vectors.

While Proposition 1 is not new, for completeness and compatibility with our notation we prove it in Appendix A.

In each local norm setup, we slightly overload notation and use  $\|\cdot\|$  (without a subscript) to denote the dual norm of  $\|\cdot\|_*$ , i.e.,  $\|\eta\| := \max_{\delta: \|\delta\|_* \leq 1} \delta^\top \eta$ . In each domain geometry  $\|\cdot\|$  and  $\|\cdot\|_*$  are as follows:

$$\begin{aligned}
\|\eta\| &= \sqrt{\|\eta^x\|_1^2 + \|\eta^y\|_1^2} & \|\delta\|_* &= \sqrt{\|\delta^x\|_\infty^2 + \|\delta^y\|_\infty^2} & \text{for } \ell_1\text{-}\ell_1 \\
\|\eta\| &= \sqrt{\|\eta^x\|_2^2 + \|\eta^y\|_1^2} & \|\delta\|_* &= \sqrt{\|\delta^x\|_2^2 + \|\delta^y\|_\infty^2} & \text{for } \ell_2\text{-}\ell_1 \\
\|\eta\| &= \|\eta\|_2 & \|\delta\|_* &= \|\delta\|_2 & \text{for } \ell_2\text{-}\ell_2.
\end{aligned} \tag{18}$$

## 2.2 The problem and optimality criterion

Throughout, we consider the bilinear saddle point problem

$$\min_{x \in \mathcal{X}} \max_{y \in \mathcal{Y}} f(x, y), \text{ where } f(x, y) := y^\top A x + b^\top x - c^\top y, \text{ for } A \in \mathbb{R}^{m \times n}, b \in \mathbb{R}^n \text{ and } c \in \mathbb{R}^m. \tag{19}$$

We will always assume that every row and column of  $A$  has at least one nonzero entry (else removing said row or column does not affect the problem value), so that the number of nonzeros  $\text{nnz}$  is at least  $m + n - 1$ . To simplify the exposition of the  $\ell_1\text{-}\ell_1$  and  $\ell_2\text{-}\ell_1$  setups we will assume  $b = \mathbf{0}_n$  and  $c = \mathbf{0}_m$  as is standard in the literature. Adding linear terms to these setups is fairly straightforward and does not affect the complexity (up to logarithmic factors) of our designed algorithms using data structures designed in this paper (specifically **ApproxExpMaintainer** in Section 2.4); see Section 6 for an example. The gradient mapping associated with (19) for  $z = (z^x, z^y) \in \mathcal{Z} = \mathcal{X} \times \mathcal{Y}$  is

$$g(z) := (\nabla_x f(z), -\nabla_y f(z)) = (A^\top z^y + b, -A z^x + c). \tag{20}$$

The mapping  $g$  is continuous and monotone, where we call  $g$  monotone if and only if

$$\langle g(z') - g(z), z' - z \rangle \geq 0, \quad \forall z, z' \in \mathcal{Z}.$$

This holds due to the convexity-concavity (indeed, bilinearity) of function  $f$ . Our goal is to design randomized algorithms for finding an (expected)  $\epsilon$ -accurate saddle point  $z \in \mathcal{Z}$  such that, in expectation,

$$\mathbb{E} \text{Gap}(z) := \mathbb{E} \left[ \max_{y' \in \mathcal{Y}} f(z^x, y') - \min_{x' \in \mathcal{X}} f(x', z^y) \right] \leq \epsilon. \quad (21)$$

In order to do so, we aim to find a sequence  $z_1, z_2, \dots, z_K$  with (expected) low *average regret*, i.e., such that  $\mathbb{E} \max_{u \in \mathcal{Z}} \left\{ \frac{1}{K} \sum_{k=1}^K \langle g(z_k), z_k - u \rangle \right\} \leq \epsilon$ . Due to bilinearity of  $f$  we have

$$\mathbb{E} \text{Gap} \left( \frac{1}{K} \sum_{k=1}^K z_k \right) = \mathbb{E} \max_{u \in \mathcal{Z}} \left\{ \frac{1}{K} \sum_{k=1}^K \langle g(z_k), z_k - u \rangle \right\} \leq \epsilon.$$

Finally, we make the explicit assumption that whenever we are discussing an algorithm in this paper with a simplex domain (e.g. in  $\ell_1$ - $\ell_1$  or  $\ell_2$ - $\ell_1$  case), the quantity  $L_{\text{co}}/\epsilon$  is bounded by  $(m+n)^3$ , as otherwise we are in the high-accuracy regime where the runtimes of interior point methods or cutting-plane methods [24, 18] are favorable. Specifically for  $\ell_1$ - $\ell_1$  matrix games in this regime, interior-point methods [23, 12, 45] are always faster, see footnote in Section 1.1. We make this assumption for notational convenience when discussing logarithmic factors depending on multiple quantities, such as  $m$ ,  $n$ ,  $L_{\text{co}}$ , and  $\epsilon^{-1}$ .

## 2.3 Matrix access models

We design randomized algorithms which require accessing and sampling from the matrix  $A \in \mathbb{R}^{n \times m}$  in a variety of ways. Here, we list these operations, where we assume each takes constant time. Specific algorithms only require access to a subset of this list; we make a note of each algorithm's requirements when presenting it.

- A1. For  $i, j \in [m] \times [n]$ , return  $A_{ij}$ .
- A2. For  $i \in [m]$  and  $p \in \{1, 2\}$ , draw  $j \in [n]$  with probability  $|A_{ij}|^p / \|A_{i:}\|_p^p$ .
- A3. For  $j \in [n]$  and  $p \in \{0, 1, 2\}$ , draw  $i \in [m]$  with probability  $|A_{ij}|^p / \|A_{:j}\|_p^p$ .
- A4. For  $i \in [m]$  ( $j \in [n]$ ) and  $p \in \{1, 2\}$ , return  $\|A_{i:}\|_p$  ( $\|A_{:j}\|_p$ ).
- A5. For  $p \in \{1, 2\}$ , return  $\max_{i \in [m]} \|A_{i:}\|_p$ ,  $\max_{j \in [n]} \|A_{:j}\|_p$ ,  $\text{nnz}$ ,  $\text{rcs}$ , and  $\|A\|_F$ .

Given any representation of the matrix as a list of nonzero entries and their indices, we can always implement the access modes above (in the assumed constant time) with  $O(\text{nnz})$  time preprocessing; see e.g. Vose [47] for an implementation of the sampling (in a unit cost RAM model). Our variance-reduced algorithms have an additive  $O(\text{nnz})$  term appearing in their runtimes due to the need to compute at least one matrix-vector product to implement gradient estimators. Thus, their stated runtime bounds hold independently of matrix access assumptions.

## 2.4 Data structure interfaces

We rely on data structures to maintain and sample from the iterates of our algorithms. Below, we give a summary of the operations supported by our data structures and their runtime guarantees. We show how to implement these data structures in Section 5.

### 2.4.1 IterateMaintainer<sub>p</sub>

Given  $p \in \{1, 2\}$ , we design a data structure **IterateMaintainer<sub>p</sub>** which maintains an implicit representation of the current iterate  $x \in \mathbb{R}^n$  and a running sum  $s$  of all iterates. At initialization, this data structure takes as input the initial iterate  $x_0$  to be maintained and for  $p = 2$ , the data structure also takes as input a fixed vector  $v$ . It then supports the following operations.

| Category            | Function   | Runtime             |
|---------------------|--|---------------------|
| initialize          | <b>Init</b> ( $x_0, v$ ): $x \leftarrow x_0, s \leftarrow 0$   | $O(n)$              |
| update              | <b>Scale</b> ( $c$ ): $x \leftarrow cx$  | $O(1)$              |
|                     | <b>AddSparse</b> ( $j, c$ ): $[x]_j \leftarrow [x]_j + c$ (if $p = 1$ , we require $c \geq -[x]_j$ ) | $O(\log n)^\dagger$ |
|                     | <b>AddDense</b> ( $c$ ): $x \leftarrow x + cv$ (supported if $p = 2$ )                               | $O(1)$              |
|                     | <b>UpdateSum</b> ( $s$ ): $s \leftarrow s + x$   | $O(1)$              |
| query               | <b>Get</b> ( $j$ ): Return $[x]_j$   | $O(1)$              |
|                     | <b>GetSum</b> ( $j$ ): Return $[s]_j$  | $O(1)$              |
|                     | <b>GetNorm</b> ( $s$ ): Return $\ x\ _p$   | $O(1)$              |
| sample <sup>†</sup> | <b>Sample</b> ( $s$ ): Return $j$ with probability $[x]_j^p / \ x\ _p^p$                             | $O(\log n)$         |

<sup>†</sup> An alternative implementation does not support **Sample**, but performs **AddSparse** in time  $O(1)$ .

The implementation of **IterateMaintainer<sub>p</sub>** is given in Section 5.1. In Sections C.2 and D.3 we use variants of this data structure **WeightedIterateMaintainer<sub>2</sub>** and **CenteredIterateMaintainer<sub>2</sub>**, and defer the detailed discussions of their implementations to Appendix G.

### 2.4.2 ApproxExpMaintainer

To maintain multiplicative weights updates with a fixed dense component, we design a data structure **ApproxExpMaintainer** initialized with an arbitrary point  $x_0 \in \Delta^n$ , a direction  $v \in \mathbb{R}^n$ , a decay constant  $\kappa \in [0, 1]$  and an approximation error parameter  $\varepsilon$ . In order to specify the implementation of our data structure, we require the following definition.

**Definition 2** ( $\beta$ -padding). *For  $x, x' \in \Delta^n$ , we say  $x'$  is a  $\beta$ -padding of  $x$  if  $x' = \tilde{x} / \|\tilde{x}\|_1$ , for a point  $\tilde{x} \in \mathbb{R}_{\geq 0}^n$  with  $\tilde{x} \geq x$  entrywise and  $\|\tilde{x} - x\|_1 \leq \beta$ .*

Notions similar to  $\beta$ -padding appear in previous literature [e.g., 21]. A key technical property of  $\beta$ -padding is that they do not increase entropy significantly (see Lemma 5).

**ApproxExpMaintainer** maintains two vectors  $x, \hat{x} \in \Delta^n$  that, for an error tolerance parameter  $\varepsilon$ , satisfy the invariant

$$\hat{x} \text{ is a } \varepsilon\text{-padding of } x. \quad (22)$$

We now specify the interface, where  $\circ$  denotes elementwise product,  $[x^\kappa]_j = [x]_j^\kappa$  denotes elementwise power,  $\Pi_\Delta(z) = z / \|z\|_1$  normalizes  $z \in \mathbb{R}_{\geq 0}^n$  to lie in the simplex, and  $\|s\|_0$  denotes the number of nonzeros in vector  $s$ . To state our runtimes, we define

$$\omega := \max \left( \frac{1}{1 - \kappa}, \frac{n}{\lambda \varepsilon} \right).$$

For most of our applications of **ApproxExpMaintainer**,  $\omega$  is a polynomial in  $m$  and  $n$  (our iterate dimensions), so  $\log(\omega) = O(\log(mn))$  (with the exception of our maximum inscribed ball application,

| Category   | Function   | Runtime                             |
|------------|--|-------------------------------------|
| initialize | <b>Init</b> ( $x_0, v, \kappa, \varepsilon, \lambda$ ) : $\kappa \in [0, 1), \varepsilon > 0, \min_j [x_0]_j \geq \lambda$ | $O(n \log n \log^2 \omega)$         |
| update     | <b>MultSparse</b> ( $g$ ): $x \leftarrow \varepsilon$ -padding of $\Pi_\Delta(x \circ \exp(g))$                            | $O(\ g\ _0 \log^2 n \log^2 \omega)$ |
|            | <b>DenseStep</b> (): $x \leftarrow \Pi_\Delta(x^\kappa \circ \exp(v))$   | $O(\log n)$                         |
|            | <b>UpdateSum</b> (): $s \leftarrow s + \hat{x}$ (recall invariant (22))  | $O(\log n \log \omega)$             |
| query      | <b>Get</b> ( $j$ ): Return $[\hat{x}]_j$   | $O(\log n \log \omega)$             |
|            | <b>GetSum</b> ( $j$ ): Return $[s]_j$  | $O(\log^2 \omega)$                  |
| sample     | <b>Sample</b> (): Return $j$ with probability $[\hat{x}]_j$  | $O(\log n \log \omega)$             |

where our runtimes additionally depend polylogarithmically on the size of the hyperplane shifts  $b$ ; see Remark 2). We defer a more fine-grained runtime discussion to Section 5.3.

The role of **ApproxExpMaintainer** is in to efficiently implement the regularized and reduced-variance stochastic mirror descent steps of the form (5). To do this, we initialize the data structure with  $v = (1 - \kappa) \log x_0 - \eta \kappa g_0^\times$ . Then, the iteration (5) consists of calling **DenseStep**() followed by **MultSparse**( $-\eta \kappa \tilde{\delta}^\times$ ).

### 3 Framework

In this section, we develop our algorithmic frameworks. The resulting algorithms have either sub-linear or variance-reduced complexities. We develop our sublinear coordinate method framework in Section 3.1, and its variance-reduced counterpart in Section 3.2.

#### 3.1 Sublinear coordinate methods

In Section 3.1.1 we introduce the concept of a *local gradient estimator*, which allow stronger guarantees for stochastic mirror descent with clipping (Algorithm 1) via local norms analysis. Then, in Section 3.1.2 we state the form of the specific local gradient estimators we use in our coordinate methods, and motivate the values of  $L_{\text{co}}$  in Table 1.

##### 3.1.1 Convergence analysis

**Definition 3.** For local norm setup  $(\mathcal{Z}, \|\cdot\|, r, \Theta, \text{clip})$ , we call a stochastic gradient estimator  $\tilde{g} : \mathcal{Z} \rightarrow \mathcal{Z}^*$  an  $L$ -local estimator if it satisfies the following properties for all  $z \in \mathcal{Z}$ :

1. *Unbiasedness*:  $\mathbb{E}[\tilde{g}(z)] = g(z)$ .
2. *Second moment bound*: for all  $w \in \mathcal{Z}$ ,  $\mathbb{E}[\|\tilde{g}(z)\|_w^2] \leq L^2$ .

The following lemma shows that  $L$ -local estimators are unbiased for  $L$ -bounded operators.

**Lemma 1.** A gradient mapping that admits an  $L$ -local estimator satisfies  $\|g(z)\|_* \leq L$  for all  $z \in \mathcal{Z}$ .

*Proof.* For every  $z \in \mathcal{Z}$ , the function  $\|\cdot\|_z^2$  is convex. Thus by Jensen's inequality,

$$\|g(z)\|_z^2 = \|\mathbb{E} \tilde{g}(z)\|_z^2 \leq \mathbb{E} \|\tilde{g}(z)\|_z^2 \leq L^2.$$

Taking supremum over  $z \in \mathcal{Z}$  gives  $\|g(z)\|_*^2 \leq L^2$ . □

We note that the same result *does not* hold for  $\tilde{g}$  because maximum and expectation do not commute. That is,  $\mathbb{E} \|\tilde{g}\|_*^2$  is not bounded by  $L^2$ . This fact motivates our use of local norms analysis.

Below, we state Algorithm 1, stochastic mirror descent with clipping, and a guarantee on its rate of convergence using local gradient estimators. We defer the proof to Appendix B and note here that it uses the “ghost iterates” technique due to Nemirovski et al. [29] in order to rigorously bound the expected regret with respect to the best response to our iterates, rather than a pre-specified point. This technique is purely analytical and does not affect the algorithm. We also note that the second inequality in Proposition 2 holds with any convex-concave function  $f$ , similarly to [8, Corollary 1]; the first uses bilinearity of our problem structure.

---

**Algorithm 1:** Stochastic mirror descent

---

**Input:** Matrix  $A \in \mathbb{R}^{m \times n}$ ,  $L$ -local gradient estimator  $\tilde{g}$ , clipping function  $\text{clip}(\cdot)$

**Output:** A point with  $O(\frac{\Theta}{\eta T} + \eta L^2)$  expected duality gap

**Parameters:** Step-size  $\eta$ , number of iterations  $T$

- 1  $z_0 \leftarrow \arg \min_{z \in \mathcal{Z}} r(z)$
  - 2 **for**  $t = 1, \dots, T$  **do**
  - 3    $z_t \leftarrow \arg \min_{z \in \mathcal{Z}} \{ \langle \text{clip}(\eta \tilde{g}(z_{t-1})), z \rangle + V_{z_{t-1}}(z) \}$
  - 4 **return**  $\frac{1}{T+1} \sum_{t=0}^T z_t$
- 

**Proposition 2.** *Let  $(\mathcal{Z}, \|\cdot\|, r, \Theta, \text{clip})$  be a local norm setup, let  $L, \epsilon > 0$ , and let  $\tilde{g}$  be an  $L$ -local estimator. Then, for  $\eta \leq \frac{\epsilon}{9L^2}$  and  $T \geq \frac{6\Theta}{\eta\epsilon} \geq \frac{54L^2\Theta}{\epsilon^2}$ , Algorithm 1 outputs a point  $\bar{z}$  such that*

$$\mathbb{E} \text{Gap}(\bar{z}) \leq \mathbb{E} \left[ \sup_{u \in \mathcal{Z}} \frac{1}{T+1} \sum_{t=0}^T \langle g(z_t), z_t - u \rangle \right] \leq \epsilon.$$

### 3.1.2 Coordinate gradient estimators

We now state the general form which our local gradient estimators  $\tilde{g}$  take. At a point  $z \in \mathcal{Z}$ , for specified sampling distributions  $p(z), q(z)$ , sample  $i^x, j^x \sim p(z)$  and  $i^y, j^y \sim q(z)$ . Then, define

$$\tilde{g}(z) := \left( \frac{A_{i^x j^x} [z^y]_{i^x}}{p_{i^x j^x}(z)} e_{j^x}, \frac{-A_{i^y j^y} [z^x]_{j^y}}{q_{i^y j^y}(z)} e_{i^y} \right) + g(0) \quad \text{where } g(0) = (b, c). \quad (23)$$

It is clear that regardless of the distributions  $p(z), q(z)$ , for the gradient operator in (20),  $\tilde{g}(z)$  is an unbiased gradient estimator ( $\mathbb{E} [\tilde{g}(z)] = g(z)$ ) and  $\tilde{g}(z) - g(0)$  is 2-sparse.

**Optimal values of  $L_{\text{co}}$ .** In the remainder of this section we assume for simplicity the  $g(0) = 0$  (i.e. the objective  $f$  in (19) has not linear terms). Here we compute the optimal values of  $L$  for local gradient estimators (see Definition 3) of the form (23) for each of the local norm setups we consider. This motivates the values of  $L_{\text{co}}$  we derive in the following sections. First, in the  $\ell_1$ - $\ell_1$  case, the second moment of  $\|\tilde{g}^x(z)\|_{w^x}^2$  (the local norm of the  $\mathcal{X}$  block of  $\tilde{g}(z)$  at point  $w$ ) is

$$\mathbb{E} \left[ [w^x]_{j^x} \left( \frac{A_{i^x j^x} [z^y]_{i^x}}{p_{i^x j^x}(z)} \right)^2 \right] = \sum_{i \in [m], j \in [n]} \frac{A_{ij}^2 [z^y]_i^2 [w^x]_j}{p_{ij}(z)} \geq \left( \sum_{i \in [m], j \in [n]} |A_{ij}| [z^y]_i \sqrt{[w^x]_j} \right)^2.$$

Since  $z^y \in \Delta^m$  and  $\sqrt{w^x} \in \mathbb{B}^n$  with  $\|\sqrt{w^x}\|_2 = 1$ , the above lower bound is in the worst case  $\max_i \|A_{i:}\|_2^2$ . Similarly, the best possible bound on the  $\mathcal{Y}$  is  $\max_j \|A_{:j}\|_2^2$ . Therefore, in the  $\ell_1$ - $\ell_1$  setup, no local estimator has parameter  $L$  smaller than  $L_{\text{co}}$  in Table 1.

Next, in the  $\ell_2$ - $\ell_2$  case, the  $(\ell_2)$  second moment of the  $\mathcal{X}$  block is

$$\mathbb{E} \left[ \left( \frac{A_{i^x j^x} [z^y]_{i^x}}{p_{i^x j^x}(z)} \right)^2 \right] = \sum_{i \in [m], j \in [n]} \frac{A_{ij}^2 [z^y]_i^2}{p_{ij}(z)} \geq \left( \sum_{i \in [m], j \in [n]} |A_{ij}| [z^y]_i \right)^2 = \left( \sum_{i \in [m]} \|A_{i:}\|_1 [z^y]_i \right)^2.$$

In the worst case, this is at least  $(\sum_{i \in [m]} \|A_{i:}\|_1)^2$ ; similarly, the best second moment bound for the  $\mathcal{Y}$  block is  $(\sum_{j \in [n]} \|A_{:j}\|_1)^2$ , which means that  $L_{\text{co}}$  is similarly unimprovable in the  $\ell_2$ - $\ell_2$  setup.

Finally, in the  $\ell_2$ - $\ell_1$  case, where  $\mathcal{X} = \mathbb{B}^n$  and  $\mathcal{Y} = \Delta^m$ , we again have that the  $\ell_2$  second moment of the  $\mathcal{X}$  (ball) block is at least

$$\mathbb{E} \left[ \left( \frac{A_{i^x j^x} [z^y]_{i^x}}{p_{i^x j^x}(z)} \right)^2 \right] \geq \left( \sum_{i \in [m], j \in [n]} |A_{ij}| [z^y]_i \right)^2.$$

Here, since  $z^y \in \Delta^m$ , the worst-case lower bound of the variance is  $\max_i \|A_{i:}\|_1^2$ . Further, the local norm (at  $w$ ) second moment of the  $\mathcal{Y}$  (simplex) block is at least

$$\mathbb{E} \left[ [w^y]_{i^y} \left( \frac{A_{i^y j^y} [z^x]_{j^y}}{q_{i^y j^y}(z)} \right)^2 \right] \geq \left( \sum_{i \in [m], j \in [n]} |A_{ij}| [z^x]_j \sqrt{[w^y]_i} \right)^2.$$

Since  $z^x \in \mathbb{B}^n$  and  $\sqrt{w^y} \in \mathbb{B}^m$ , in the worst case this second moment can be as high as  $\|A\|_{\text{op}}$ , where we use  $|A|$  to denote the elementwise absolute value of  $A$ . This is better than the  $L_{\text{co}}$  in Table 1, suggesting there is room for improvement here. However, the sampling probabilities inducing this optimal variance bound are of the form

$$q_{ij}(z; w) \propto |A_{ij}| \sqrt{[w^y]_i} \cdot [z^x]_j,$$

and it unclear how to efficiently sample from this distribution. Improving our  $\ell_2$ - $\ell_1$  gradient estimator (or proving that no improvement is possible) remains an open problem.

## 3.2 Variance-reduced coordinate methods

In this section, we develop the algorithmic framework we use in our variance-reduced methods. We first define a type of “centered-local” gradient estimator, modifying the local gradient estimators of the previous section. We then give the general form of a variance-reduced method and analyze it in the context of our gradient estimators and the error incurred by our data structure maintenance.

### 3.2.1 General convergence result

**Definition 4.** For local norm setup  $(\mathcal{Z}, \|\cdot\|, r, \Theta, \text{clip})$ , and given a reference point  $w_0 = (w_0^x, w_0^y)$ , we call a stochastic gradient estimator  $\tilde{g}_{w_0} : \mathcal{Z} \rightarrow \mathcal{Z}^*$  an  $L$ -centered-local estimator if it satisfies the following properties:

1. *Unbiasedness:*  $\mathbb{E} [\tilde{g}_{w_0}(z)] = g(z)$ .
2. *Relative variance bound:* for all  $w \in \mathcal{Z}$ ,  $\mathbb{E} [\|\tilde{g}_{w_0}(z) - g(w_0)\|_w^2] \leq L^2 V_{w_0}(z)$ .

**Remark 1.** Similarly to Lemma 1, a gradient mapping that admits an  $L$ -centered-local estimator also satisfies  $\|g(z) - g(w_0)\|_*^2 \leq L^2 V_{w_0}(z)$ , by Jensen’s inequality.

Algorithm 2 below is an approximate variant of the variance reduction algorithm in our earlier work [8] which closely builds upon the “conceptual prox-method” of Nemirovski [28]. The algorithm repeatedly calls a stochastic oracle  $\mathcal{O} : \mathcal{Z} \rightarrow \mathcal{Z}$  to produce intermediate iterates, and then performs an extragradient (linearized) proximal step using the intermediate iterate. The main modification compared to [8] is Line 5, which accommodates slight perturbations to the extra-gradient step results. These perturbations arise due to input requirements of our data structures: we slightly pad coordinates in simplex blocks to ensure they are bounded away from zero.

---

**Algorithm 2:** OuterLoop( $\mathcal{O}$ ) (conceptual prox-method [28])

---

**Input:** Target approximation quality  $\varepsilon_{\text{outer}}$ ,  $(\alpha, \varepsilon_{\text{inner}})$ -relaxed proximal oracle  $\mathcal{O}(z)$  for gradient mapping  $g$  and some  $\varepsilon_{\text{inner}} < \varepsilon_{\text{outer}}$ , distance-generating  $r$

**Parameters:** Number of iterations  $K$ .

**Output:** Point  $\bar{z}_K$  with  $\mathbb{E} \text{Gap}(\bar{z}) \leq \frac{\alpha\Theta}{K} + \varepsilon_{\text{outer}}$

```

1  $z_0 \leftarrow \arg \min_{z \in \mathcal{Z}} r(z)$ 
2 for  $k = 1, \dots, K$  do
3    $z_{k-1/2} \leftarrow \mathcal{O}(z_{k-1})$      $\triangleright$  We implement  $\mathcal{O}(z_{k-1})$  by calling InnerLoop( $z_{k-1}, \tilde{g}_{z_{k-1}}, \alpha$ )
4    $z_k^* := \text{Prox}_{z_{k-1}}^\alpha(g(z_{k-1/2})) = \arg \min_{z \in \mathcal{Z}} \{ \langle g(z_{k-1/2}), z \rangle + \alpha V_{z_{k-1}}(z) \}$ 
5    $z_k \leftarrow$  any point satisfying  $V_{z_k}(u) - V_{z_k^*}(u) \leq \frac{\varepsilon_{\text{outer}} - \varepsilon_{\text{inner}}}{\alpha}$ , for all  $u \in \mathcal{Z}$ 
6 return  $\bar{z}_K = \frac{1}{K} \sum_{k=1}^K z_{k-1/2}$ 

```

---

The following definition summarizes the key property of the oracle  $\mathcal{O}$ .

**Definition 5** ([8, Definition 1]). *Let operator  $g$  be monotone and  $\alpha, \varepsilon_{\text{inner}} > 0$ . An  $(\alpha, \varepsilon_{\text{inner}})$ -relaxed proximal oracle for  $g$  is a (possibly randomized) map  $\mathcal{O} : \mathcal{Z} \rightarrow \mathcal{Z}$  such that  $z' = \mathcal{O}(z)$  satisfies*

$$\mathbb{E} \left[ \max_{u \in \mathcal{Z}} \{ \langle g(z'), z' - u \rangle - \alpha V_z(u) \} \right] \leq \varepsilon_{\text{inner}}.$$

The following proposition, a variant of [8, Proposition 1], shows that despite the error permitted tolerated in Line 5, the algorithm still converges with rate  $1/K$ . We defer its proof to Appendix B.

**Proposition 3.** *Let  $\mathcal{O}$  be an  $(\alpha, \varepsilon_{\text{inner}})$ -relaxed proximal oracle with respect to gradient mapping  $g$ , distance-generating function  $r$  with range at most  $\Theta$  and some  $\varepsilon_{\text{inner}} \leq \varepsilon_{\text{outer}}$ . Let  $z_{1/2}, z_{3/2}, \dots, z_{K-1/2}$  be iterates of Algorithm 2 and let  $\bar{z}_K$  be its output. Then*

$$\mathbb{E} \text{Gap}(\bar{z}_K) \leq \mathbb{E} \max_{u \in \mathcal{Z}} \frac{1}{K} \sum_{k=1}^K \langle g(z_{k-1/2}), z_{k-1/2} - u \rangle \leq \frac{\alpha\Theta}{K} + \varepsilon_{\text{outer}}.$$

Algorithm 3 is a variant of the variance-reduced inner loop of [8], adapted for local norms and inexact iterates (again, due to approximations made by the data structure). It tolerates error in three places:

1. Instead of estimating the gradient at the previous iterate  $w_{t-1}$ , we estimate it at a point  $\hat{w}_{t-1}$  such that  $w_{t-1} - \hat{w}_{t-1}$  has small norm and similar divergence from the reference point  $w_0$  (Line 2).
2. Instead of letting the next iterate be the exact mirror descent step  $w_t^*$ , we let be a point  $w_T$  that is close to  $w_t^*$  in norm and has similar divergences to from  $w_0$  and to any any point in  $\mathcal{Z}$  (Line 4).



3. The output  $\tilde{w}$  can be an approximation of the average of the iterates, as long as its difference to the true average has bounded norm (Line 5).

We quantify the effect of these approximations in Proposition 4, which gives a runtime guarantee for Algorithm 3 (where we recall the definition of  $\|\cdot\|$  as the dual norm of  $\|\cdot\|_*$ , see (18)). The proof is deferred to Appendix B.

---

**Algorithm 3: InnerLoop**( $w_0, \tilde{g}_{w_0}, \varphi$ )

---

**Input:** Initial  $w_0 \in \mathcal{Z}$ ,  $L$ -centered-local gradient estimator  $\tilde{g}_{w_0}$ , oracle quality  $\alpha > 0$

**Parameters:** Step size  $\eta$ , number of iterations  $T$ , approximation tolerance  $\varphi$

**Output:** Point  $\tilde{w}$  satisfying Definition 5

```

1 for  $t = 1, \dots, T$  do
2    $\hat{w}_{t-1} \approx w_{t-1}$  satisfying (a)  $V_{w_0}(\hat{w}_{t-1}) - V_{w_0}(w_{t-1}) \leq \frac{\varphi}{\alpha}$  and (b)  $\|\hat{w}_{t-1} - w_{t-1}\| \leq \frac{\varphi}{LD}$ 
3    $w_t^* \leftarrow \arg \min_{w \in \mathcal{Z}} \{ \langle w, \text{clip}(\eta \tilde{g}_{w_0}(\hat{w}_{t-1}) - \eta g(w_0)) + \eta g(w_0) \rangle + \frac{\alpha \eta}{2} V_{w_0}(w) + V_{w_{t-1}}(w) \}$ 
4    $w_t \approx w_t^*$  satisfying
      (a)  $\max_u [V_{w_t}(u) - V_{w_t^*}(u)] \leq \eta \varphi$ ,
      (b)  $V_{w_0}(w_t) - V_{w_0}(w_t^*) \leq \frac{\varphi}{\alpha}$ , and
      (c)  $\|w_t - w_t^*\| \leq \frac{\varphi}{2LD}$ 
5 return  $\tilde{w} \approx \frac{1}{T} \sum_{t=1}^T w_t$  satisfying  $\left\| \tilde{w} - \frac{1}{T} \sum_{t=1}^T w_t \right\| \leq \frac{\varphi}{LD}$ .
```

---

**Proposition 4.** Let  $(\mathcal{Z}, \|\cdot\|, r, \Theta, \text{clip})$  be any local norm setup. Let  $w_0 \in \mathcal{Z}$ ,  $\alpha \geq \varepsilon_{\text{inner}} > 0$ , and  $\tilde{g}_{w_0}$  be an  $L$ -centered-local estimator for some  $L \geq \alpha$ . Assume the domain is bounded by  $\max_{z \in \mathcal{Z}} \|z\| \leq D$ , that  $g$  is  $L$ -Lipschitz, i.e.  $\|g(z) - g(z')\|_* \leq L \|z - z'\|$ , that  $g$  is  $LD$ -bounded, i.e.  $\max_{z \in \mathcal{Z}} \|g(z)\|_* \leq LD$ , and that  $\hat{w}_0 = w_0$ . Then, for  $\eta = \frac{\alpha}{10L^2}$ ,  $T \geq \frac{6}{\eta\alpha} \geq \frac{60L^2}{\alpha^2}$ , and  $\varphi = \frac{\varepsilon_{\text{inner}}}{6}$ , Algorithm 3 outputs a point  $\hat{w} \in \mathcal{Z}$  such that

$$\mathbb{E} \max_{u \in \mathcal{Z}} [\langle g(\tilde{w}), \tilde{w} - u \rangle - \alpha V_{w_0}(u)] \leq \varepsilon_{\text{inner}}, \quad (24)$$

i.e. Algorithm 3 is an  $(\alpha, \varepsilon_{\text{inner}})$ -relaxed proximal oracle.

**Remark 2** (Assumption of boundedness on  $g$ ). The assumption that  $g$  is  $LD$ -bounded in the dual norm is immediate from other assumptions used in Proposition 4 in the case of the applications in Section 4, where we develop methods for solving  $\ell_1$ - $\ell_1$  matrix games and assume that  $g(0) = 0$ . In applications in Section 6, due to the existence of extra linear terms  $b, c \neq 0$ , all complexity bounds will have an additional dependence on  $\log(\|[b; c]\|_*)$  which we pay in the implementation of data structure **ApproxExpMaintainer** (i.e. the parameter  $L$  in the bound on  $g$  is larger if  $\|[b; c]\|_*$  is large). We hide this extra polylogarithmic factor in the  $\tilde{O}$  notation.

We also remark that (up to constants) the bounds on the range of  $\varepsilon_{\text{inner}} \leq \alpha \leq L$  in the statement of Proposition 4 correspond to the cases where the inner and outer loop consist of a single iteration.

### 3.2.2 Variance-reduced coordinate gradient estimators

We now state the general form which our centered-local estimators  $\tilde{g}_{w_0}$  take, given a reference point  $w_0 \in \mathcal{Z}$ . At a point  $z$ , for sampling distributions  $p(z; w_0), q(z; w_0)$  to be specified, sample  $i^x, j^x \sim p(z; w_0)$  and  $i^y, j^y \sim q(z; w_0)$ . Then, define

$$\tilde{g}_{w_0}(z) = \left( \frac{A_{i^x j^x}[z^y - w_0^y]_{i^x}}{p_{i^x j^x}(z; w_0)} e_{j^x}, \frac{-A_{i^y j^y}[z^x - w_0^x]_{j^y}}{q_{i^y j^y}(z; w_0)} e_{i^y} \right) + g(w_0). \quad (25)$$

It is clear that regardless of the distributions  $p(z; w_0), q(z; w_0)$ , this is an unbiased gradient estimator ( $\mathbb{E}[\tilde{g}_{w_0}(z)] = g(z)$ ). Furthermore,  $\tilde{g}_{w_0}(z) - g(w_0)$  is always 2-sparse.

## 4 Matrix games

In this section we instantiate the algorithmic framework of Section 3 in  $\ell_1$ - $\ell_1$  setup without linear terms, i.e.  $b = c = 0$  in the objective (19). This is the fundamental “matrix game” problem

$$\min_{x \in \Delta^m} \max_{y \in \Delta^n} y^\top A x.$$

We give two algorithms for approximately solving matrix games. In Section 4.1 we develop a stochastic coordinate method based on Algorithm 1 with potentially sublinear runtime  $\tilde{O}\left((L_{\text{co}}^{1,1}/\epsilon)^2\right)$ . In Section C we develop a coordinate variance-reduction based on Algorithm 2 with runtime  $\tilde{O}\left(\text{nnz} + \sqrt{\text{nnz}} \cdot L_{\text{co}}^{1,1}/\epsilon\right)$  that improves on the former runtime whenever it is  $\Omega(\text{nnz})$ . In both cases we have

$$L_{\text{co}}^{1,1} := \max \left\{ \max_i \|A_{i:}\|_2, \max_j \|A_{:j}\|_2 \right\} \quad (26)$$

as in Table 1.

Instantiations for the  $\ell_2$ - $\ell_1$  and  $\ell_2$ - $\ell_2$  setups follow similarly. We carry them out in Appendices C (for stochastic coordinate methods) and D (for variance reduction methods).

**Remark 3.** For simplicity in this section (and the remaining implementations in Appendices C, D), we will set  $g(0) = 0$  whenever the setup is not  $\ell_2$ - $\ell_2$ , as is standard in the literature. We defer a discussion of how to incorporate arbitrary linear terms in simplex domains to Section 6; up to additional logarithmic terms in the runtime, this extension is supported by **ApproxExpMaintainer**.

**Assumptions.** Throughout (for both Sections 4.1 and 4.2), we assume access to entry queries,  $\ell_2$  norms of rows and columns, and  $\ell_2$  sampling distributions for all rows and columns. We use the  $\ell_1$ - $\ell_1$  local norm setup (Table 6). We also define  $L_{\text{max}} := \|A\|_{\text{max}} = \max_{i \in [m], j \in [n]} |A_{ij}|$ .

### 4.1 $\ell_1$ - $\ell_1$ sublinear coordinate method

#### 4.1.1 Gradient estimator

For  $z \in \Delta^n \times \Delta^m$  and desired accuracy  $\epsilon > 0$ , we specify the sampling distributions  $p(z), q(z)$ :

$$p_{ij}(z) := [z^y]_i \frac{A_{ij}^2}{\|A_{i:}\|_2^2} \quad \text{and} \quad q_{ij}(z) := [z^x]_j \frac{A_{ij}^2}{\|A_{:j}\|_2^2}. \quad (27)$$

We first state and prove the local properties of this estimator.

**Lemma 2.** *In the  $\ell_1$ - $\ell_1$  setup, estimator (23) using the sampling distribution in (27) is a  $\sqrt{2}L_{\text{co}}^{1,1}$ -local estimator.*

*Proof.* Unbiasedness holds by definition. For arbitrary  $w^x$ , we have the variance bound:

$$\begin{aligned} \mathbb{E} \left[ \|\tilde{g}^x(z)\|_{w^x}^2 \right] &\leq \sum_{i \in [m], j \in [n]} p_{ij}(z) \cdot \left( [w^x]_j \cdot \left( \frac{A_{ij}[z^y]_i}{p_{ij}(z)} \right)^2 \right) = \sum_{i \in [m], j \in [n]} [w^x]_j \frac{A_{ij}^2 [z^y]_i^2}{p_{ij}(z)} \\ &\leq \sum_{i \in [m], j \in [n]} [w^x]_j [z^y]_i \|A_{i:}\|_2^2 \leq \max_{i \in [m]} \|A_{i:}\|_2^2 \leq (L_{1,1}^{\text{co}})^2. \end{aligned}$$

Similarly, we have

$$\mathbb{E} \left[ \|\tilde{g}^y(z)\|_{w^y}^2 \right] \leq (L_{1,1}^{\text{co}})^2.$$

The definition  $\|\tilde{g}(z)\|_w^2 = \|\tilde{g}^x(z)\|_{w^x}^2 + \|\tilde{g}^y(z)\|_{w^y}^2$  yields the claimed variance bound.  $\square$

#### 4.1.2 Implementation details

In this section, we discuss the details of how to leverage the `IterateMaintainer1` data structure to implement the iterations of our algorithm. The algorithm we analyze is Algorithm 1, using the local estimator defined in (23), and the distribution (27). We choose

$$\eta = \frac{\epsilon}{18 \left( L_{\text{co}}^{1,1} \right)^2} \text{ and } T = \left\lceil \frac{6\Theta}{\eta\epsilon} \right\rceil \geq \frac{108 \left( L_{\text{co}}^{1,1} \right)^2 \log(mn)}{\epsilon^2}.$$

Lemma 2 implies that our estimator satisfies the remaining requirements for Proposition 2, giving the duality gap guarantee in  $T$  iterations. In order to give a runtime bound, we claim that each iteration can be implemented in  $\log(mn)$  time, with  $O(m+n)$  additional runtime.

**Data structure initializations and invariants.** At the start of the algorithm, we spend  $O(m+n)$  time initializing data structures via  $\text{IM}_1^x.\text{Init}(\frac{1}{n}\mathbf{1}_n, \mathbf{0}_n)$  and  $\text{IM}_1^y.\text{Init}(\frac{1}{m}\mathbf{1}_m, \mathbf{0}_m)$ , where  $\text{IM}_1^x, \text{IM}_1^y$  are appropriate instantiations of `IterateMaintainer1` data structures. Throughout, we preserve the invariant that the points maintained by  $\text{IM}_1^x, \text{IM}_1^y$  correspond to the  $x$  and  $y$  blocks of the current iterate  $z_t$  at iteration  $t$  of the algorithm.

**Iterations.** For simplicity, we only discuss the runtime of updating the  $x$  block as the  $y$  block follows symmetrically. We divide each iteration into the following substeps, each of which we show runs in time  $O(\log mn)$ . We refer to the current iterate by  $z = (z^x, z^y)$ , and the next iterate by  $w = (w^x, w^y)$ .

*Sampling.* Recall that

$$p_{ij}(z) := [z^y]_i \frac{A_{ij}^2}{\|A_{i:}\|_2^2}.$$

We first sample coordinate  $i$  via  $\text{IM}_1^y.\text{Sample}()$  in  $O(\log m)$ . Next, we sample  $j \in [n]$  with probability proportional to  $A_{ij}^2$  using the data structure corresponding to  $A_{i:}$  in  $O(1)$  by assumption of the matrix access model.

*Computing the gradient estimator.* To compute  $c := \text{clip}(A_{ij}[z^y]_i/p_{ij})$ , it suffices to compute  $A_{ij}$ ,  $[z^y]_i$ , and  $p_{ij}$ . Using an entry oracle for  $A$  we obtain  $A_{ij}$ , and we get  $[z^y]_i$  by calling  $\text{IM}_1^y.\text{Get}(i)$ . Computing  $p_{ij}$  using the precomputed  $\|A_{i:}\|_2$  and the values of  $A_{ij}, [z^y]_i$  therefore takes  $O(1)$  time.

*Performing the update.* For the update corresponding to a proximal step, we have

$$w^x \leftarrow \Pi_{\mathcal{X}}(z^x \circ \exp(-\eta \tilde{g}^x(z))) = \frac{z^x \circ \exp(-\eta \tilde{g}^x(z))}{\|z^x \circ \exp(-\eta \tilde{g}^x(z))\|_1}.$$

We have computed  $\tilde{g}^x(z)$ , so to perform this update, we call

```

 $\xi \leftarrow \text{IM}_1^x.\text{Get}(j);$ 
 $\text{IM}_1^x.\text{AddSparse}(j, (\exp(-\eta c) - 1)\xi);$ 
 $\text{IM}_1^x.\text{Scale}(\text{IterateMaintainer}^x.\text{GetNorm}()^{-1});$ 
 $\text{IM}_1^x.\text{UpdateSum}().$ 

```

By assumption, each operation takes time  $O(\log n)$ , giving the desired iteration complexity. It is clear that at the end of performing these operations, the invariant that  $\text{IM}_1^x$  maintains the  $x$  block of the iterate is preserved.

**Averaging.** After  $T$  iterations, we compute the average point  $\bar{z}^x$ :

$$[\bar{z}^x]_j \leftarrow \frac{1}{T} \cdot \text{IM}_1^x.\text{GetSum}(j), \forall j \in [n].$$

By assumption, this takes  $O(n)$  time.

### 4.1.3 Algorithm guarantee

**Theorem 1.** *In the  $\ell_1$ - $\ell_1$  setup, the implementation in Section 4.1.2 has runtime*

$$O\left(\frac{\left(L_{\text{co}}^{1,1}\right)^2 \log^2(mn)}{\epsilon^2} + m + n\right),$$

and outputs a point  $\bar{z} \in \mathcal{Z}$  such that  $\mathbb{E} \text{Gap}(\bar{z}) \leq \epsilon..$

*Proof.* The runtime follows from the discussion in Section 4.1.2. The correctness follows from Proposition 2.  $\square$

**Remark 4.** Using our `IterateMaintainer1` data structure, the  $\ell_1$ - $\ell_1$  algorithm of Grigoriadis and Khachiyan [16] runs in time  $O(\text{rcs} \|A\|_{\max}^2 \log^2(mn)/\epsilon^2)$ , where  $\text{rcs}$  is the maximum number of nonzeros in any row or column. Our runtime universally improves upon it since  $(L_{1,1}^{\text{co}})^2 \leq \text{rcs} \|A\|_{\max}^2$ .

## 4.2 $\ell_1$ - $\ell_1$ variance-reduced coordinate method

### 4.2.1 Gradient estimator

Given reference point  $w_0 \in \Delta^n \times \Delta^m$ , for  $z \in \Delta^n \times \Delta^m$  and a parameter  $\alpha > 0$ , we specify the sampling distributions  $p(z; w_0), q(z; w_0)$ :

$$p_{ij}(z; w_0) := \frac{[z^y]_i + 2[w_0^y]_i}{3} \cdot \frac{A_{ij}^2}{\|A_{:,i}\|_2^2} \quad \text{and} \quad q_{ij}(z; w_0) := \frac{[z^x]_j + 2[w_0^x]_j}{3} \cdot \frac{A_{ij}^2}{\|A_{:,j}\|_2^2}. \quad (28)$$

We remark that this choice of sampling distribution, which we term “sampling from the sum” (of the current iterate and reference point), may be viewed as a computationally-efficient alternative to the distribution specified in [8], which was based on “sampling from the difference”. In particular, sampling from the difference is an operation which to the best of our knowledge is difficult to implement in sublinear time, so we believe that demonstrating that this alternative distribution suffices may be of independent interest. In order to show its correctness, we need the following claim, whose proof we defer to Appendix D.1.

**Lemma 3.** For  $y, y' \in \Delta^m$ , divergence  $V_y(y')$  generated by  $r(y) = \sum_{i \in [m]} [y]_i \log [y]_i - [y]_i$  satisfies

$$V_y(y') \geq \frac{1}{2} \|y' - y\|_{\frac{3}{2y+y'}}^2 = \frac{1}{2} \sum_{i \in [m]} \frac{([y]_i - [y']_i)^2}{\frac{2}{3}[y]_i + \frac{1}{3}[y']_i}.$$

We now show the local properties of this estimator.

**Lemma 4.** In the  $\ell_1$ - $\ell_1$  setup, estimator (25) using the sampling distribution in (28) is a  $\sqrt{2}L_{\text{co}}^{1,1}$ -centered-local estimator.

*Proof.* Unbiasedness holds by definition. For arbitrary  $w^x$ , we have the variance bound:

$$\begin{aligned} \mathbb{E} \left[ \|\tilde{g}_{w_0}^x(z) - g^x(w_0)\|_{w^x}^2 \right] &= \sum_{i \in [m], j \in [n]} p_{ij}(z; w_0) \cdot \left( [w^x]_j \cdot \left( \frac{A_{ij}([z^y]_i - [w_0^y]_i)}{p_{ij}(z; w_0)} \right)^2 \right) \\ &= \sum_{i \in [m], j \in [n]} [w^x]_j \frac{A_{ij}^2([z^y]_i - [w_0^y]_i)^2}{p_{ij}(z; w_0)} \\ &\leq \sum_{i \in [m], j \in [n]} [w^x]_j \frac{([z^y]_i - [w_0^y]_i)^2}{\frac{1}{3}[z^y]_i + \frac{2}{3}[w_0^y]_i} \|A_{i:}\|_2^2 \\ &\leq 2 \left( \max_i \|A_{i:}\|_2^2 \right) V_{w_0^y}(z^y), \end{aligned}$$

where in the last inequality we used Lemma 3. Similarly, we have for arbitrary  $w^y$ ,

$$\mathbb{E} \left[ \|\tilde{g}_{w_0}^y(z) - g^y(w_0)\|_{w^y}^2 \right] \leq 2 \left( \max_j \|A_{:j}\|_2^2 \right) V_{w_0^x}(z^x).$$

Combining these and using

$$\|\tilde{g}_{w_0}(z) - g(w_0)\|_w^2 := \|\tilde{g}_{w_0}^x(z) - g^x(w_0)\|_{w^x}^2 + \|\tilde{g}_{w_0}^y(z) - g^y(w_0)\|_{w^y}^2$$

yields the desired variance bound.  $\square$

## 4.2.2 Implementation details

In this section, we discuss the details of how to leverage the **ApproxExpMaintainer** data structure to implement the iterations of our algorithm. We first state one technical lemma on the effect of  $\beta$ -padding (Definition 2) on increasing entropy, used in conjunction with the requirements of Proposition 4 to bound the error tolerance required by our **ApproxExpMaintainer** data structure. The proof is deferred to Appendix D.1.

**Lemma 5.** Let  $x' \in \Delta^n$  be a  $\beta$ -padding of  $x \in \Delta^n$ . Then,

$$\sum_{j \in [n]} x'_j \log x'_j - \sum_{j \in [n]} x_j \log x_j \leq \frac{\beta n}{e} + \beta(1 + \beta).$$

This leads to the following divergence bounds which will be used in this section.

**Lemma 6.** Let  $x' \in \Delta^n$  be a  $\beta$ -padding of  $x \in \Delta^n$ . Then

$$V_{x'}(u) - V_x(u) \leq \beta, \forall u \in \mathcal{Z}$$

and if  $\|\log(x_0)\|_\infty \leq M$ , then

$$V_{x_0}(x') - V_{x_0}(x) \leq \beta \left( 2M + \frac{n}{e} + 1 + \beta \right)$$

*Proof.* Throughout this proof, let  $\tilde{x}$  be the point in Definition 2 such that  $\|\tilde{x} - x\|_1 \leq \beta$  and  $x' = \tilde{x} / \|\tilde{x}\|_1$ .

The first claim follows from expanding

$$V_{x'}(u) - V_x(u) = \sum_{j \in [n]} u_j \log \frac{x_j}{x'_j} = \sum_{j \in [n]} u_j \log \left( \frac{x_j}{\tilde{x}_j} \cdot \|\tilde{x}\|_1 \right) \leq \log(\|\tilde{x}\|_1) \leq \beta.$$

The first inequality used  $u \in \Delta^n$  and  $\tilde{x} \geq x$  entrywise, and the last inequality used  $\log(1 + \beta) \leq \beta$ .

For the second claim, we have by the triangle inequality

$$\|x - x'\|_1 \leq \|x - \tilde{x}\|_1 + \|\tilde{x} - x'\|_1 \leq \beta + (\|\tilde{x}\|_1 - 1) \|x'\|_1 \leq 2\beta.$$

The claim then follows from expanding

$$V_{x_0}(x') - V_{x_0}(x) = \sum_{j \in [n]} x'_j \log x'_j - \sum_{j \in [n]} x_j \log x_j + \langle \log x_0, x - x' \rangle,$$

and applying Lemma 5.  $\square$

The algorithm we analyze is Algorithm 2 with  $K = 3\alpha\Theta/\epsilon$ ,  $\varepsilon_{\text{outer}} = 2\epsilon/3$ ,  $\varepsilon_{\text{inner}} = \epsilon/3$  using Algorithm 3 as an  $(\alpha, \varepsilon_{\text{inner}})$ -relaxed proximal oracle. The specific modification we perform to define the iterates  $\{z_k\}$  of Algorithm 2 as modifications of the ideal iterates  $\{z_k^*\}$  uses the following definition.

**Definition 6.** For a simplex variable  $x' \in \Delta^n$ , we define  $\text{truncate}(x', \delta)$  to be the point  $x \in \Delta^n$  with  $x_j \propto \max(x'_j, \delta)$  for all  $j \in [n]$ . For a variable  $z$  on two blocks, we overload notation and define  $\text{truncate}(z, \delta)$  to be the result of applying  $\text{truncate}(\cdot, \delta)$  to each simplex block of  $z$ .

For our implementation, in each step of Algorithm 2, we will compute the point  $z_k^*$  exactly, and apply the operation  $z_k \leftarrow \text{truncate}(z_k^*, \delta)$ , for  $\delta = \frac{\varepsilon_{\text{outer}} - \varepsilon_{\text{inner}}}{\alpha(m+n)}$ . We now quantify the effect of truncation in terms of Bregman divergence to an arbitrary point.

**Lemma 7** (Effect of truncation). Let  $x' \in \Delta^n$ , and let  $x = \text{truncate}(x', \delta)$ . Then, for any  $u \in \Delta^n$ , and where divergences are with respect to entropy,

$$V_x(u) - V_{x'}(u) \leq \delta n.$$

*Proof.* Note that  $x$  is a  $\delta n$ -padding of  $x'$ , as it is the result of adding at most  $\delta$  to each coordinate and renormalizing to lie in the simplex. Consequently, the result follows from Lemma 6.  $\square$

Lemma 7 thus implies our iterates satisfy the requirements of Algorithm 2. Our implementation of Algorithm 3 will use approximation tolerance  $\varphi = \varepsilon_{\text{inner}}/6 = \epsilon/18$ , where we always set

$$L_{\text{co}}^{1,1} \geq \alpha \geq \varepsilon_{\text{inner}}. \quad (29)$$

This matches the requirements of Proposition 4. In the implementation of Algorithm 3, we use the centered-local gradient estimator defined in (25), using the sampling distribution (28). For each use of Algorithm 3, we choose

$$\eta = \frac{\alpha}{20 \left(L_{\text{co}}^{1,1}\right)^2} \text{ and } T = \left\lceil \frac{6}{\eta\alpha} \right\rceil \geq \frac{120 \left(L_{\text{co}}^{1,1}\right)^2}{\alpha^2}.$$

Our discussion will follow in four steps: first, we discuss the complexity of all executions in Algorithm 2 other than calls to the oracles. Next, we discuss the complexity of all initializations of **ApproxExpMaintainer** data structures. Then, we discuss the complexity of all other iterations of Algorithm 3. For simplicity, when discussing Algorithm 3, we will only discuss implementation of the  $x$ -block, and the  $y$ -block will follow symmetrically, while most runtimes are given considering both blocks. Lastly, we discuss complexity of computing the average iterate in the end of the inner loop. Altogether, the guarantees of Proposition 3 and Proposition 4 imply that if the guarantees required by the algorithm hold, the expected gap of the output is bounded by  $\epsilon$ .

**Outer loop extragradient steps.** Overall, we execute  $K = 3\alpha\Theta/\epsilon$  iterations of Algorithm 2, with  $\epsilon_{\text{outer}} = 2\epsilon/3$ ,  $\epsilon_{\text{inner}} = \epsilon/3$  to obtain the desired gap, where  $\Theta = \log(mn)$  in the  $\ell_1$ - $\ell_1$  setup. We spend  $O(\text{nnz})$  time executing each extragradient step in Algorithm 2 exactly to compute iterates  $z_k^*$ , where the dominant term in the runtime is computing each  $g(z_{k-1/2})$ , for  $k \in [K]$ . We can maintain the average point  $\bar{z}$  throughout the duration of the algorithm, in  $O(m+n)$  time per iteration. Finally, we spend an additional  $O(m+n)$  time per iteration applying **truncate** to each iterate  $z_k^*$ .

**Data structure initializations and invariants.** We consider the initialization of data structures for implementing an  $(\alpha, \epsilon_{\text{inner}} = \epsilon/3)$ -relaxed proximal oracle with error tolerance  $\varphi = \epsilon/18$ . First, note that the point  $w_0^x$  used in the initialization of every inner loop, by the guarantees of **truncate** operation, has no two coordinates with multiplicative ratio larger than  $\delta = \epsilon/(3\alpha(m+n)) \geq (m+n)^{-4}$ , by our choice  $\alpha \leq L_{\text{co}}^{1,1}$  (29) and our assumptions on  $L_{\text{co}}^{1,1}/\epsilon$  (cf. Section 2.2). Since clearly a simplex variable in  $\Delta^n$  has a coordinate at least  $1/n$ , the entries of  $w_0$  are lower bounded by  $\lambda = (m+n)^{-5}$ .

Next, we discuss the initial parameters given to  $\text{AEM}^x$ , an instance of **ApproxExpMaintainer** which will support necessary operations for maintaining the  $x$  variable (we will similarly initialize an instance  $\text{AEM}^y$ ). Specifically, the invariant that we maintain throughout the inner loop is that in iteration  $t$ , the “exact vector”  $x$  maintained by  $\text{AEM}^x$  corresponds to the  $x$  block of the current iterate  $w_t$ , and the “approximate vector”  $\hat{x}$  maintained corresponds to the  $x$  block of the approximate iterate  $\hat{w}_t$ , as defined in Algorithm 3.

We will now choose  $\tilde{\epsilon}$  so that if  $\text{AEM}^x$  is initialized with error tolerance  $\tilde{\epsilon}$ , all requirements of Proposition 4 (e.g. the bounds stipulated in Algorithm 3) are met. We first handle all divergence requirements. In a given iteration, denote the  $x$  blocks of  $w_t^*$ ,  $w_t$  and  $\hat{w}_t$  by  $x_t^*$ ,  $x_t$  and  $\hat{x}_t$  respectively, and recall  $\text{AEM}^x$  guarantees  $x_t$  is a  $\tilde{\epsilon}$ -padding of  $x_t^*$ , and  $\hat{x}_t$  is a  $\tilde{\epsilon}$ -padding of  $x_t^*$ . The former of these guarantees is true by the specification of **MultSparse** (which will be used in the implementation of the step, see “Performing the update” below), and the latter is true by the invariant on the points supported by  $\text{AEM}^x$ . Lines 2 and 4 of Algorithm 3 stipulate the divergence requirements, where



$$x_0 := w_0^x,$$

$$\max \{V_{x_0}(x_t) - V_{x_0}(x_t^*), V_{x_0}(\hat{x}_t) - V_{x_0}(x_t)\} \leq \frac{\varphi}{2\alpha} = \frac{\epsilon}{36\alpha} \quad (30)$$

and

$$\max_u [V_{x_t}(u) - V_{x_t^*}(u)] \leq \frac{\eta\varphi}{2} = \frac{\eta\epsilon}{36}. \quad (31)$$

Clearly, combining this guarantee with a similar guarantee on the  $y$  blocks yields the desired bound. Since we derived  $\|\log w_0\|_\infty \leq 5 \log(mn)$ , we claim that choosing

$$\tilde{\epsilon} \leq \frac{\epsilon}{36\alpha(m+n)}$$

suffices for the guarantees in (30). By the first part of Lemma 6, for all sufficiently large  $m+n$ ,

$$\max \{V_{x_0}(x_t) - V_{x_0}(x_t^*), V_{x_0}(\hat{x}_t) - V_{x_0}(x_t)\} \leq \tilde{\epsilon} \left(10 \log(mn) + \frac{n}{e} + 1 + \tilde{\epsilon}\right) \leq \frac{\epsilon}{36\alpha}.$$

Similarly for guarantees in (31), by the second part of Lemma 6 we know it suffices to choose

$$\tilde{\epsilon} \leq \frac{\epsilon^2}{720 \left(L_{\text{co}}^{1,1}\right)^2} \leq \frac{\epsilon\alpha}{720 \left(L_{\text{co}}^{1,1}\right)^2} = \frac{\eta\epsilon}{36}.$$

Here, we used the restriction  $\epsilon_{\text{inner}} \leq \alpha \leq L_{\text{co}}^{1,1}$ . Next, the norm requirements of Algorithm 3 (the guarantees in Lines 2, 4, and 5) imply we require

$$\tilde{\epsilon} \leq \frac{\epsilon}{18\sqrt{2}L_{\text{co}}^{1,1}},$$

where we used that  $g$  is  $\|A\|_{\max} \leq L_{\text{co}}^{1,1}$ -Lipschitz and the diameter of  $\mathcal{Z}$  is bounded by  $\sqrt{2}$ . Using our assumptions on the size of parameters in Section 2.2, it suffices to set the error tolerance

$$\tilde{\epsilon} = (m+n)^{-8}.$$

To give the remainder of specified parameters,  $\mathbf{AEM}^x$  is initialized via  $\mathbf{Init}(w_0^x, v, \kappa, \tilde{\epsilon})$  for

$$\kappa := \frac{1}{1 + \eta\alpha/2}, \quad v := (1 - \kappa) \log w_0^x - \eta\kappa g^x(w_0).$$

To motivate this form of updates, note that each iteration of Algorithm 3 requires us to compute

$$\arg \min \left\{ \langle c_t e_j + g^x(w_0), x \rangle + \frac{\alpha}{2} V_{w_0^x}(x) + \frac{1}{\eta} V_{w_t^x}(x) \right\}.$$

We can see that the solution to this update is given by

$$[w_{t+1}^*]^x \leftarrow \Pi_\Delta \left( [w_t^x]^\kappa \circ \exp((1 - \kappa) \log w_0^x - \eta\kappa g^x(w_0)) \circ \exp(-\eta\kappa c_t e_j) \right). \quad (32)$$

This form of update is precisely supported by our choice of  $\kappa$  and  $v$ , as well as the **DenseStep** and **MultSparse** operations. By the choice of parameters, we note that  $1 - \kappa \geq (m+n)^{-8}$ .

Finally, in order to support our sampling distributions and gradient computations, we compute and store the vectors  $w_0$  and  $g(w_0)$  in full using  $O(\text{nnz}(A))$  time at the beginning of the inner loop. In  $O(m+n)$  time, we also build two data structures which allow us to sample from entries of the given fixed vectors  $w_0^x$ , and  $w_0^y$ , in constant time respectively.

Following Section 2.4.2, we defined the parameter

$$\omega := \max \left( \frac{1}{1 - \kappa}, \frac{n}{\lambda \tilde{\epsilon}} \right) \leq (m+n)^{13}, \text{ so that } \log(\omega) = O(\log(mn)).$$

Altogether, these initializations take time  $O(\text{nnz} + (m+n) \log^3(mn))$ , following Section 2.4.2.

**Inner loop iterations.** We discuss how to make appropriate modifications to the  $x$ -block. For simplicity we denote our current iterate as  $z$ , and the next iterate as  $w$ . Also, we denote  $\hat{z}$  as the concatenation of implicit iterates that the two **ApproxExpMaintainer** copies maintain (see Section 2.4.2 for more details), which is  $\tilde{\varepsilon}$  close in  $\ell_1$  distance to  $z$ , the prior iterate, so that we can query or sample entries from  $\hat{z}$  using  $\mathbf{AEM}^x$  and  $\mathbf{AEM}^y$ . Each inner loop iteration consists of using a gradient estimator at  $\hat{z}$  satisfying  $\|\hat{z} - z\|_1 \leq \tilde{\varepsilon}$ , sampling indices for the computation of  $\tilde{g}_{w_0}(\hat{z})$ , computing the sparse part of  $\tilde{g}_{w_0}(\hat{z})$ , and performing the approximate update to the iterate. We show that we can run each substep using data structure  $\mathbf{AEM}^x$  in time  $O(\log^4(mn))$ , within the error tolerance of Proposition 4 due to the definition of  $\tilde{\varepsilon}$ . Combining with our discussion of the complexity of initialization, this implies that the total complexity of the inner loop, other than outputting the average iterate, is

$$O(T \log^4(mn) + \text{nnz} + (m+n) \log^3(mn)) = O\left(\frac{(L_{\text{co}}^{1,1})^2 \cdot \log^4(mn)}{\alpha^2} + \text{nnz} + (m+n) \log^3(mn)\right).$$

*Sampling.* Recall that the distribution we sample from is given by

$$p_{ij}(\hat{z}; w_0) := \frac{[\hat{z}^y]_i + 2[w_0^y]_i}{3} \cdot \frac{A_{ij}^2}{\|A_{i:}\|_2^2}.$$

First, with probability  $2/3$ , we sample a coordinate  $i$  from the precomputed data structure for sampling from  $w_0^y$  in constant time; otherwise, we sample  $i$  via  $\mathbf{AEM}^y.\text{Sample}()$ . Then, we sample an entry of  $A_{i:}$  proportional to its square via the precomputed data structure (cf. Section 2.3) in constant time. This takes in total  $O(\log mn)$  time.

*Computing the gradient estimator.* Proposition 4 requires us to compute the sparse component of the gradient estimator (25) at point  $\hat{z}$ . To do this for the  $x$  block, we first query  $[w_0^x]_j$  and  $[\hat{z}^y]_i \leftarrow \mathbf{AEM}^y.\text{Get}(i)$ , and then access the precomputed norm  $\|A_{i:}\|_2$  and entry  $A_{ij}$ . We then compute

$$c = \text{clip}\left(A_{ij} [\hat{z}^y - w_0^y]_i \cdot \frac{3}{[\hat{z}^y]_i + 2[w_0^y]_i} \cdot \frac{\|A_{i:}\|_2^2}{A_{ij}^2}\right).$$

By the guarantees of **ApproxExpMaintainer**, this takes total time bounded by  $O(\log(mn))$ .

*Performing the update.* To perform the update, by observing the form of steps in Algorithm 3 with our choice of entropy regularizer, the update form given by the regularized mirror-descent step is (as derived in the discussion of the initialization of  $\mathbf{AEM}^x$ , see (32))

$$[w^{*x} \leftarrow \Pi_{\Delta}((w^x)^\kappa \circ \exp((1 - \kappa) \log w_0^x - \eta \kappa g^x(w_0) - \eta \kappa c e_j)).$$

To implement this, recalling our choice of the vector  $v$  in the initialization of  $\mathbf{AEM}^x$ , it suffices to call

```

AEMx.DenseStep();
AEMx.MultSparse( $-\eta \kappa c e_j$ );
AEMx.UpdateSum().

```

By assumption, each operation takes time bounded by  $O(\log^4(mn))$ , where we note the vector used in the **MultSparse** operation is 1-sparse. The implementation of this update is correct up to a  $\tilde{\varepsilon}$ -padding, whose error we handled previously. By the discussion in the data structure initialization section, this preserves the invariant that the  $x$  block of the current iterate is maintained by  $\mathbf{AEM}^x$ .

**Average iterate computation.** At the end of each run of Algorithm 3, we compute and return the average iterate via calls  $\text{AEM}^\times.\text{GetSum}(j)$  for each  $j \in [n]$ , and scaling by  $1/T$ , and similarly query  $\text{AEM}^\mathcal{Y}$ . The overall complexity of this step is  $O((m+n)\log^2(mn))$ . The correctness guarantee, i.e. that the output approximates the average in  $\ell_1$  norm up to  $\varphi/LD$ , is given by the choice of  $\tilde{\varepsilon}$  and the guarantees of **ApproxExpMaintainer**, where in this case the domain size  $D$  is bounded by  $\sqrt{2}$ . This is never the dominant factor in the runtime, as it is dominated by the cost of initializations.

### 4.2.3 Algorithm guarantee

**Theorem 2.** *In the  $\ell_1$ - $\ell_1$  setup, let  $\text{nnz}' := \text{nnz} + (m+n)\log^3(mn)$ . The implementation in Section 4.2.2 with the optimal choice of  $\alpha = \max\left(\epsilon/3, L_{\text{co}}^{1,1} \log^2(mn) / \sqrt{\text{nnz}'}\right)$  has runtime*

$$O\left(\left(\text{nnz}' + \frac{\left(L_{\text{co}}^{1,1}\right)^2 \log^4(mn)}{\alpha^2}\right) \frac{\alpha \log(mn)}{\epsilon}\right) = O\left(\text{nnz}' + \frac{\sqrt{\text{nnz}'} L_{\text{co}}^{1,1} \log^3(mn)}{\epsilon}\right)$$

and outputs a point  $\bar{z} \in \mathcal{Z}$  such that

$$\mathbb{E} \text{Gap}(\bar{z}) \leq \epsilon.$$

*Proof.* The correctness of the algorithm is given by the discussion in Section 4.2.2 and the guarantees of Proposition 3 with  $K = 3\alpha\Theta/\epsilon$ ,  $\varepsilon_{\text{outer}} = 2\epsilon/3$ ,  $\varepsilon_{\text{inner}} = \epsilon/3$ , Proposition 4 with  $\varphi = \epsilon/15$ , and the data structure **ApproxExpMaintainer** with our choice of

$$\tilde{\varepsilon} := (m+n)^{-8},$$

to meet the approximation conditions in Line 2, 4 and 5 of Algorithm 3. The runtime bound is given by the discussion in Section 4.2.2, and the optimal choice of  $\alpha$  is clear.  $\square$

## 5 Data structure implementation

In this section, we give implementations of our data structures, fulfilling the interface and runtime guarantees of Section 2.4. In Section 5.1 we provide the implementation of **IterateMaintainer<sub>p</sub>** for  $p \in \{1, 2\}$  used for sublinear coordinate methods. In Section 5.2, we provide an implementation of **ApproxExpMaintainer** used in variance-reduced coordinate methods for simplex domains, provided we have an implementation of a simpler data structure, **ScaleMaintainer**, which we then provide in Section 5.3.

### 5.1 IterateMaintainer<sub>p</sub>

The **IterateMaintainer<sub>p</sub>**,  $p \in \{1, 2\}$  data structure is described in Section 2.4.1 and used for tracking the iterates in our fully stochastic methods and the Euclidean part of our the iterates in our variance-reduced methods. The data structure maintains an internal representation of  $x$ , the current iterate, and  $s$ , a running sum of all iterates. The main idea behind the efficient implementation of the data structure is to maintain  $x$  and  $s$  as a linear combination of sparsely-updated vectors. In particular, the data structure has the following state: scalars  $\xi_u, \xi_v, \sigma_u, \sigma_v, \iota, \nu$ ; vectors  $u, u', v$ , and the scalar  $\|v\|_2^2$ ; the vector  $v$  is only relevant for variance reduction and is therefore set 0 for the non-Euclidean case  $p = 1$ .

We maintain the following invariants on the data structure state at the end of every operation:

- $x = \xi_u u + \xi_v v$ , the internal representation of  $x$
- $s = u' + \sigma_u u + \sigma_v v$ , the internal representation of running sum  $s$
- $\iota = \langle x, v \rangle$ , the inner product of the iterate with fixed vector  $v$
- $\nu = \|x\|_p$ , the appropriate norm of the iterate

In addition, to support sampling, our data structure also maintains a binary tree  $\text{dist}_x$  of depth  $O(\log n)$ . Each leaf node is associated with a coordinate  $j \in [n]$ , and each internal node is associated with a subset of coordinates corresponding to leaves in its subtree. For the node corresponding to  $S \subseteq [n]$  (where  $S$  may be a singleton), we maintain the sums  $\sum_{j \in S} [u]_j^p$ ,  $\sum_{j \in S} [u]_j [v]_j$ , and  $\sum_{j \in S} [v]_j^p$ .

We now give the implementation of each operation supported by `IterateMaintainerd`, followed by proofs of correctness and of the runtime bounds when applicable.

### 5.1.1 Initialization

- `Init`( $x_0, v$ ). Runs in time  $O(n)$ .

If  $p = 1$  set  $v \leftarrow \mathbf{0}_n$ ; otherwise we compute and store  $\|v\|_2^2$ . Initialize the remaining data structure state as follows:  $(\xi_u, \xi_v, u) \leftarrow (1, 0, x_0)$ ,  $(\sigma_u, \sigma_v, u') \leftarrow (0, 0, \mathbf{0}_n)$ ,  $(\iota, \nu) \leftarrow (\langle x_0, v \rangle, \|x_0\|_p)$ . Initialize  $\text{dist}_x$ , storing the relevant sums in each internal node.

It is clear that  $x = \xi_u u + \xi_v v$ ,  $s = u' + \sigma_u u + \sigma_v v$ , and that the invariants of  $\iota, \nu$  hold. Each step takes  $O(n)$  time; for the first 4 steps this is immediate, and the final recursing upwards from the leaves spends constant time for each internal node, where there are  $O(n)$  nodes.

### 5.1.2 Updates

- `Scale`( $c$ ):  $x \leftarrow cx$ . Runs in time  $O(1)$ .

Multiply each of  $\xi_u, \xi_v, \nu, \iota$  by  $c$ .

- `AddSparse`( $j, c$ ):  $[x]_j \leftarrow [x]_j + c$ , with the guarantee  $c \geq -[x]_j$  if  $p = 1$ . Runs in time  $O(\log n)$ .

1.  $u \leftarrow u + \frac{c}{\xi_u} e_j$ .

2.  $u' \leftarrow u' - \frac{c\sigma_u}{\xi_u} e_j$ .

3. If  $p = 1$ ,  $\nu \leftarrow \nu + c$ . If  $p = 2$ ,  $\nu \leftarrow \sqrt{\nu^2 + 2c[\xi_u u + \xi_v v]_j + c^2}$ .

4.  $\iota \leftarrow \iota + c[v]_j$ .

5. For internal nodes of  $\text{dist}_x$  on the path from leaf  $j$  to the root, update  $\sum_{j \in S} [u]_j^p$ ,  $\sum_{j \in S} [u]_j [v]_j$  appropriately.

- `AddDense`( $c$ ):  $x \leftarrow x + cv$ . Runs in time  $O(1)$ . (Supported only for  $p = 2$ ).

Set  $\xi_v \leftarrow \xi_v + c$ ,  $\nu \leftarrow \sqrt{\nu^2 + 2c\iota + c^2 \|v\|_2^2}$ , and  $\iota \leftarrow \iota + c \|v\|_2^2$ .

- `UpdateSum`( $\cdot$ ):  $s \leftarrow s + x$ . Runs in time  $O(1)$ .

Set  $\sigma_u \leftarrow \sigma_u + \xi_u$  and  $\sigma_v \leftarrow \sigma_v + \xi_v$ .

Each of the runtime bounds clearly hold; we now demonstrate that the necessary invariants are preserved. Correctness of **Scale** and **UpdateSum** are clear. Regarding correctness of **AddSparse**, note that (ignoring the  $v$  terms when  $p = 1$ )

$$\begin{aligned}\xi_u \left( u + \frac{c}{\xi_u} e_j \right) + \xi_v v &= \xi_u u + \xi_v v + c e_j, \\ \left( u' - \frac{c \sigma_u}{\xi_u} e_j \right) + \sigma_u \left( u + \frac{c}{\xi_u} e_j \right) + \sigma_v v &= u' + \sigma_u u + \sigma_v v.\end{aligned}$$

When  $p = 1$ , the update to  $\nu$  is clearly correct. When  $p = 2$ , because only  $[x]_j$  changes,

$$\begin{aligned}[\xi_u u + \xi_v v + c e_j]_j^2 &= [\xi_u u + \xi_v v]_j^2 + 2c[\xi_u u + \xi_v v]_j + c^2, \\ ([\xi_u u + \xi_v v + c e_j]_j) \cdot [v]_j &= ([\xi_u u + \xi_v v]_j) \cdot [v]_j + c[v]_j.\end{aligned}$$

Thus, the updates to the norm and inner product are correct. Regarding correctness of **AddDense** when  $p = 2$ , we have

$$\begin{aligned}\xi_u u + (\xi_v + c)v &= \xi_u u + \xi_v v + cv, \\ \|x + cv\|_2^2 &= \nu^2 + 2c\iota + c^2 \|v\|_2^2, \\ \langle x + cv, v \rangle &= \iota + c \|v\|_2^2.\end{aligned}$$

Here, we use the invariants that  $\nu = \|x\|_2$  and  $\iota = \langle x, v \rangle$ .

### 5.1.3 Queries

- **Get**( $j$ ): Return  $[x]_j$ . Runs in time  $O(1)$ .  
Return  $\xi_u[u]_j + \xi_v[v]_j$ .
- **GetSum**( $j$ ): Return  $[s]_j$ . Runs in time  $O(1)$ .  
Return  $[u']_j + \sigma_u[u]_j + \sigma_v[v]_j$ .
- **Norm**( $\cdot$ ): Return  $\|x\|_p$ . Runs in time  $O(1)$ .  
Return  $\nu$ .

By our invariants, each of these operations is correct.

### 5.1.4 Sampling

The method **Sample** returns a coordinate  $j$  with probability proportional to  $[x]_j^p$  in time  $O(\log n)$ . To implement it, we recursively perform the following procedure, where the recursion depth is at most  $O(\log n)$ , starting at the root node and setting  $S = [n]$ :

1. Let  $S_1, S_2$  be the subsets of coordinates corresponding to the children of the current node.
2. Using scalars  $\xi_u, \xi_v$ , and the maintained  $\sum_{j \in S_i} [u]_j^p, \sum_{j \in S_i} [u]_j [v]_j, \sum_{j \in S_i} [v]_j^p$  when appropriate, compute  $\sum_{j \in S_i} [x]_j^p = \sum_{j \in S_i} [\xi_u u + \xi_v v]_j^p$  for  $i \in \{1, 2\}$ .
3. Sample a child  $i \in \{1, 2\}$  of the current node proportional to  $\sum_{j \in S_i} [x]_j^p$  by flipping an appropriately biased coin. Set  $S \leftarrow S_i$ .

It is clear that this procedure samples according to the correct probabilities. Furthermore, step 2 can be implemented in  $O(1)$  time using precomputed values, so the overall complexity is  $O(\log n)$ .

## 5.2 ApproxExpMaintainer

In this section, we give the implementation of **ApproxExpMaintainer** which supports dense update to simplex mirror descent iterates. For convenience, we restate its interface, where we recall the notation  $\|g\|_0$  for the number of nonzero entries in  $g$ , Definition 2 of an  $\varepsilon$ -padding, the invariant

$$\hat{x} \text{ is a } \varepsilon\text{-padding of } x, \quad (33)$$

and the notation

$$\omega := \max \left( \frac{1}{1 - \kappa}, \frac{n}{\lambda \epsilon} \right).$$

| Category   | Function   | Runtime                             |
|------------|--|-------------------------------------|
| initialize | <b>Init</b> ( $x_0, v, \kappa, \varepsilon, \lambda$ ) : $\kappa \in [0, 1], \varepsilon > 0, \min_j [x_0]_j \geq \lambda$ | $O(n \log n \log^2 \omega)$         |
| update     | <b>MultSparse</b> ( $g$ ): $x \leftarrow \varepsilon\text{-padding of } \Pi_\Delta(x \circ \exp(g))$                       | $O(\ g\ _0 \log^2 n \log^2 \omega)$ |
|            | <b>DenseStep</b> (): $x \leftarrow \Pi_\Delta(x^\kappa \circ \exp(v))$   | $O(\log n)$                         |
|            | <b>UpdateSum</b> (): $s \leftarrow s + \hat{x}$ (recall invariant (22))  | $O(\log n \log \omega)$             |
| query      | <b>Get</b> ( $j$ ): Return $[\hat{x}]_j$   | $O(\log n \log \omega)$             |
|            | <b>GetSum</b> ( $j$ ): Return $[s]_j$  | $O(\log^2 \omega)$                  |
| sample     | <b>Sample</b> (): Return $j$ with probability $[\hat{x}]_j$  | $O(\log n \log \omega)$             |

We build **ApproxExpMaintainer** out of a simpler data structure called **ScaleMaintainer**, which maintains the simplex projection of fixed vectors raised elementwise to arbitrary powers; this suffices to support consecutive **DenseStep** calls without **MultSparse** calls between them. To add support for **MultSparse**, we combine  $O(\log n)$  instances of **ScaleMaintainer** in a formation resembling a binomial heap: for every entry updated by **MultSparse** we delete it from the **ScaleMaintainer** instance currently holding it, put it in a new singleton **ScaleMaintainer** instance (after appropriate scaling due to **MultSparse**), and merge this singleton into existing instances. We now give a brief description of the **ScaleMaintainer** interface, and based on it, describe the implementation of **ApproxExpMaintainer**. We will provide the implementation of **ScaleMaintainer** in Section 5.3.

**ScaleMaintainer** is initialized with vectors  $\bar{x} \in \mathbb{R}_{\geq 0}^{n'}$  and  $\bar{\delta} \in \mathbb{R}^{n'}$  (with  $n' \leq n$ ) and supports efficient approximate queries on vectors of the form

$$x[\sigma] := \bar{x} \circ \exp(\sigma \bar{\delta}),$$

for any scalar  $\sigma \in [\sigma_{\min}, 1]$ . More specifically, the data structure allows efficient computation of  $\|x[\sigma]\|_1$  (to within small multiplicative error  $\varepsilon_{\text{scm}}$ ), as well as entry queries, sampling and running sum accumulation from a vector  $\hat{x}[\sigma]$  satisfying

$$\hat{x}[\sigma] \text{ is a } \varepsilon_{\text{scm}}\text{-padding of } \Pi_\Delta(\bar{x} \circ \exp(\sigma \bar{\delta})) = \frac{x[\sigma]}{\|x[\sigma]\|_1}. \quad (34)$$

We make the following assumptions on the input to the data structure:

$$\lambda_{\text{scm}} \leq [\bar{x}]_i \leq 1 \text{ for all } i \in [n'] \text{ and } \sigma \in (\sigma_{\min}, 1).$$

The upper bounds on  $\bar{x}$  and  $\sigma$  are arbitrary, and we may choose  $\lambda_{\text{scm}}$  and  $\sigma_{\min}$  to be very small since the data structure runtime depends on them only logarithmically. To summarize this dependence, we define

$$\omega_{\text{scm}} := \max \left\{ \frac{1}{\sigma_{\min}}, \frac{n}{\lambda_{\text{scm}} \varepsilon_{\text{scm}}} \right\}.$$

With these assumptions and notation, we define the formal interface of **ScaleMaintainer**.

| Category   | Function  | Runtime                                   |
|------------|---|---|
| initialize | <b>Init</b> ( $\bar{x}, \bar{\delta}, \sigma_{\min}, \varepsilon_{\text{scm}}, \lambda_{\text{scm}}$ )                    | $O(n' \log n \log^2 \omega_{\text{scm}})$ |
| update     | <b>Del</b> ( $j$ ): Remove coordinate $j$ from $\bar{x}, \bar{\delta}$  | $O(1)$                                    |
|            | <b>UpdateSum</b> ( $\gamma, \sigma$ ): $s \leftarrow s + \gamma \hat{x}[\sigma]$ , with $\hat{x}[\sigma]$ defined in (34) | $O(\log \omega_{\text{scm}})$             |
| query      | <b>Get</b> ( $j$ ): Return $[\hat{x}[\sigma]]_j$  | $O(\log \omega_{\text{scm}})$             |
|            | <b>GetSum</b> ( $j$ ): Return $[s]_j$ .   | $O(\log^2 \omega_{\text{scm}})$           |
|            | <b>GetNorm</b> ( $\sigma$ ): Return $1 \pm \varepsilon$ approx. of $\ \bar{x} \circ \exp(\sigma \bar{\delta})\ _1$        | $O(\log \omega_{\text{scm}})$             |
| sample     | <b>Sample</b> ( $\sigma$ ): Return $j$ with probability $[\hat{x}[\sigma]]_j$   | $O(\log n \log \omega_{\text{scm}})$      |

### 5.2.1 ApproxExpMaintainer state

Throughout this section, we denote  $K := \lceil \log n \rceil$ . **ApproxExpMaintainer** maintains a partition of  $[n]$  into  $K$  sets  $S_1 \dots, S_K$  (some of them possibly empty) that satisfy the invariant

$$|S_k| \leq 2^k \text{ for all } k \in [K]. \quad (35)$$

We refer to the index  $k$  as “rank” and associate with each rank  $k \in [K]$  the following data

1. Scalar  $\gamma_k \geq 0$  and nonnegative integer  $\tau_k$ .
2. Vectors  $\bar{x}_k, \bar{\delta}_k \in \mathbb{R}^{|S_k|}$  such that  $\lambda_{\text{scm}} \leq [\bar{x}_k]_i \leq 1$  for all  $i \in [|S_k|]$ , where  $\lambda_{\text{scm}} = \min(\varepsilon/n, \lambda)$ .
3. A **ScaleMaintainer** instance, denoted **ScaleMaintainer** $_k$ , initialized with  $\bar{x}_k, \bar{\delta}_k$  and  $\lambda_{\text{scm}}$  defined above,  $\sigma_{\min} = 1 - \kappa$  and  $\varepsilon_{\text{scm}} = \varepsilon/10$ , so that  $\log \omega_{\text{scm}} = O(\log \omega)$ .

**ApproxExpMaintainer** also maintains a vector  $u \in \mathbb{R}^n$  for auxiliary running sum storage.

Define the vector  $\delta \in \mathbb{R}^n$  by

$$[\delta]_{S_k} = \log \left( \gamma_k [\bar{x}_k \circ \exp((1 - \kappa^{\tau_k}) \bar{\delta}_k)] \right), \quad k \in \{1, \dots, K\}, \quad (36)$$

where  $[\delta]_{S_k}$  denotes the coordinates of  $\delta$  in  $S_k$ . Recall that  $x$  denotes the point in  $\Delta^n$  maintained throughout the operations of **ApproxExpMaintainer**; we maintain the key invariant that the point  $x$  is proportional to  $\exp(\delta)$ , i.e.,

$$x = \frac{\exp(\delta)}{\|\exp(\delta)\|_1}. \quad (37)$$

Specifically, we show in Section 5.2.3 that our implementation of **DenseStep** modifies  $\bar{x}, \bar{\delta}, \{\tau_k\}_{k=0}^K, \{\gamma_k\}_{k=0}^K$  so that the resulting effect on  $\delta$ , per definition (37), is

$$\delta \leftarrow \kappa \delta + v. \quad (38)$$

Similarly, our implementation of **MultSparse** modifies the state so that the resulting effect on  $\delta$  is

$$\frac{\exp(\delta)}{\|\exp(\delta)\|_1} \leftarrow \varepsilon\text{-padding of } \frac{\exp(\delta + v)}{\|\exp(\delta + v)\|_1}. \quad (39)$$

We remark that the role of  $\gamma_k$  is to scale  $\bar{x}_k$  so that it lies coordinatewise in the range  $[\lambda_{\text{scm}}, 1]$ , conforming to the **ScaleMaintainer** input requirement. This is also the reason we require the  $\varepsilon$ -padding operation in the definition of **MultSparse**.



### 5.2.2 $\varepsilon$ -padding point $\hat{x}$

We now concretely define the point  $\hat{x}$ , which is the  $\varepsilon$ -padding of  $x$  that `ApproxExpMaintainer` maintains. Let

$$\Gamma := \sum_{k=1}^K \gamma_k \text{ScaleMaintainer}_k.\text{GetNorm}(1 - \kappa^{\tau_k}), \quad (40)$$

be the approximation of  $\exp(\delta)$  derived from the `ScaleMaintainer` instances. For any  $j \in [n]$ , let  $k_j$  be such that  $j \in S_{k_j}$ , and let  $i_j$  be the index of  $j$  in  $S_{k_j}$ . The  $j$ th coordinate of  $\hat{x}$  is

$$[\hat{x}]_j := \frac{\gamma_{k_j} \text{ScaleMaintainer}_{k_j}.\text{GetNorm}(1 - \kappa^{\tau_{k_j}})}{\Gamma} \cdot \text{ScaleMaintainer}_{k_j}.\text{Get}(i_j, 1 - \kappa^{\tau_{k_j}}). \quad (41)$$

Since for each  $k$ ,  $\sum_{j \in S_k} \text{ScaleMaintainer}_k.\text{Get}(j, 1 - \kappa^{\tau_k}) = \text{ScaleMaintainer}_k.\text{GetNorm}(1 - \kappa^{\tau_k})$  we have that  $\hat{x} \in \Delta^n$ . We now prove that  $\hat{x}$  is a  $\varepsilon$ -padding of  $x$ . To do so, we prove the following lemma.

**Lemma 8.** *Let  $\varepsilon_{\text{scm}} \leq \frac{1}{10}$  and  $\{S_k\}_{k=1}^K$  be a partition of  $[n]$ . Suppose for each  $k \in [K]$ ,  $\hat{x}_k \in \Delta^{|S_k|}$  is an  $\varepsilon_{\text{scm}}$ -padding of  $x_k \in \Delta^{|S_k|}$ . Further, suppose we have positive scalars  $\{\nu_k\}_{k=1}^K$ ,  $\{\hat{\nu}_k\}_{k=1}^K$  satisfying*

$$(1 - \varepsilon_{\text{scm}})\nu_k \leq \hat{\nu}_k \leq (1 + \varepsilon_{\text{scm}})\nu_k, \text{ for all } 1 \leq k \leq K.$$

*Then, for  $N = \sum_{k=1}^K \nu_k$  and  $\hat{N} = \sum_{k=1}^K \hat{\nu}_k$ , we have that  $\hat{x} := \sum_{k=1}^K \frac{\hat{\nu}_k}{\hat{N}} \hat{x}_k$  is a  $10\varepsilon_{\text{scm}}$ -padding of  $x := \sum_{k=1}^K \frac{\nu_k}{N} x_k$ .*

*Proof.* For every  $k \in [K]$ , let  $\tilde{x}_k$  to be such that  $\tilde{x}_k \geq x_k$  elementwise,  $\hat{x}_k = \tilde{x}_k / \|\tilde{x}_k\|_1$ , and  $\|\tilde{x}_k - x_k\|_1 \leq \varepsilon_{\text{scm}}$ . Consider the point

$$\tilde{x} := \sum_{k=1}^K \frac{\tilde{\nu}_k}{\tilde{N}} \tilde{x}_k, \text{ where } \tilde{\nu}_k := \hat{\nu}_k \frac{\max_{k \in [K]} \|\tilde{x}_k\|_1}{\|\tilde{x}_k\|_1} \cdot \frac{1 + \varepsilon_{\text{scm}}}{1 - \varepsilon_{\text{scm}}},$$

so that  $\hat{x} = \tilde{x} / \|\tilde{x}\|_1$ . Since  $\tilde{x}_k \geq x_k$  elementwise,  $\hat{\nu}_k \geq (1 - \varepsilon_{\text{scm}})\nu_k$  and  $\hat{N} \leq (1 + \varepsilon_{\text{scm}})N$ , we have that  $\tilde{x} \geq x$  elementwise. Furthermore, we have  $\hat{\nu}_k \leq (1 + \varepsilon_{\text{scm}})\nu_k$  and  $\hat{N} \geq (1 - \varepsilon_{\text{scm}})N$ , and the properties  $\tilde{x}_k \geq x_k$  and  $\|\tilde{x}_k - x_k\|_1$  imply  $1 \leq \|\tilde{x}_k\|_1 \leq 1 + \varepsilon_{\text{scm}}$  as well as  $\frac{\max_{k \in [K]} \|\tilde{x}_k\|_1}{\|\tilde{x}_k\|_1} \leq 1 + \varepsilon_{\text{scm}}$ . Therefore

$$\|\tilde{x} - x\|_1 \leq \sum_{k=1}^K \frac{\nu_k}{N} \left\| \frac{(1 + \varepsilon_{\text{scm}})^3}{(1 - \varepsilon_{\text{scm}})^2} \tilde{x}_k - x_k \right\|_1 \leq \left( \frac{(1 + \varepsilon_{\text{scm}})^3}{(1 - \varepsilon_{\text{scm}})^2} - 1 \right) (1 + \varepsilon_{\text{scm}}) + \varepsilon_{\text{scm}} \leq 10\varepsilon_{\text{scm}},$$

where the final bound is verified numerically for  $\varepsilon_{\text{scm}} \leq 1/10$ .  $\square$

The `ScaleMaintainer` interface guarantees that calls to `ScaleMaintainer_k.GetNorm` return  $\|\bar{x}_k \circ \exp((1 - \kappa^{\tau_k})\bar{\delta}_k)\|_1$  to within a  $1 \pm \varepsilon_{\text{scm}}$  multiplicative factor, and moreover that `Get` returns entries from an  $\varepsilon_{\text{scm}}$ -padding of  $\Pi_{\Delta}(\bar{x}_k \circ \exp((1 - \kappa^{\tau_k})\bar{\delta}_k))$ . Thus, applying Lemma 8 with our definition of  $\hat{x}$  in (41) yields that  $\hat{x}$  is a  $10\varepsilon_{\text{scm}} = \varepsilon$ -padding of  $x$ .

### 5.2.3 ApproxExpMaintainer initialization and updates

We give the implementation and prove runtimes of `Init`, `MultSparse`, `DenseStep`, and `UpdateSum`.

**Init.** Upon initialization of **ApproxExpMaintainer**, we set  $\gamma_K = \max_{j \in [n]} [x_0]_j$  and  $\tau_k = 0$  for all  $k$ . We let  $S_K = [n]$  (so that  $S_k = \emptyset$  for all  $k < K$ ) and instantiate a single instance of **ScaleMaintainer** of rank  $K$  with parameters

$$\bar{x}_K = \frac{x_0}{\gamma_K}, \bar{\delta}_K = \frac{v}{1 - \kappa} - \log x_0, \varepsilon_{\text{scm}} = \frac{\varepsilon}{10}, \lambda_{\text{scm}} = \min\left(\frac{\varepsilon}{n}, \lambda\right).$$

It is clear that the invariant (37) holds at initialization, and that the coordinates of  $\bar{x}_K$  lie in the appropriate range, since we assume that  $x_0 \in [\lambda, 1]^n$ . We will use the same choices of  $\varepsilon_{\text{scm}}, \lambda_{\text{scm}}$  for every **ScaleMaintainer** instance. The overall complexity of this operation is  $O(n \log n \log^2 \omega)$ .

**MultSparse.** We state the implementation of **MultSparse**, prove that the resulting update is (39), and finally give its runtime analysis. We perform **MultSparse**( $g$ ) in sequence for each nonzero coordinate of  $g$ . Let  $j$  denote such nonzero coordinate and let  $k_j$  be such that  $j \in S_{k_j}$ ; the operation consists of the following steps.

1. Remove  $j$  from  $S_{k_j}$  and delete the corresponding coordinate from **ScaleMaintainer** $_{k_j}$  (via a call to **Del**).
2. Let  $S_0 = j$  and initialize **ScaleMaintainer** $_0$  with initial data  $\bar{x}$  and  $\bar{\delta}$  described below.
3. For  $k$  going from 1 to  $K$ , set  $S_k \leftarrow S_k \cup S_{k-1}$  and  $S_{k-1} = \emptyset$ , merging **ScaleMaintainer** $_k$  and **ScaleMaintainer** $_{k-1}$  as described below. If the new set  $S_k$  satisfies  $|S_k| \leq 2^k$ , break the loop; else, proceed to the next  $k$ .

We now state the initial data given to each **ScaleMaintainer** upon initialization in the steps above. Whenever a **ScaleMaintainer** $_k$  is created supporting  $S_k \subseteq [n]$ , we first compute  $\delta_i$  for each  $i \in S_k$  according to (37). When creating the singleton instance **ScaleMaintainer** $_0$  we perform the update

$$\delta_j \leftarrow \delta_j + g_j; \tag{42}$$

this implements multiplication of the  $j$ th coordinate by  $\exp(g_j)$ . To instantiate **ScaleMaintainer** $_k$ , we set  $\tau_k = 0$ ,  $\gamma_k \leftarrow \max_{i \in S_k} \exp([\delta]_i)$  and modify  $\delta$  according to

$$[\delta]_{S_k} \leftarrow \max\{[\delta]_{S_k}, \log(\lambda_{\text{scm}} \cdot \gamma_k)\}. \tag{43}$$

In other words, we raise very small entries of  $[\delta]_{S_k}$  to ensure that the ratio between any two entries of  $[\exp(\delta)]_{S_k}$  is in the range  $[\lambda_{\text{scm}}^{-1}, \lambda_{\text{scm}}]$ . We then give **ScaleMaintainer** $_k$  the initial data

$$\bar{x}_k = \frac{1}{\gamma_k} [\exp(\delta)]_{S_k}, \bar{\delta}_k = \left[ \frac{v}{1 - \kappa} - \delta \right]_{S_k}. \tag{44}$$

It is clear that entries of  $\bar{x}_k$  are in the range  $[\lambda_{\text{scm}}, 1]$ , and invariant (37) holds at initialization, as  $\tau_k = 0$ . Therefore, the operation (42) implements  $x \leftarrow \Pi_{\Delta}(x \circ \exp(g))$  exactly; it remains to show that the operation (43) amounts to an  $\varepsilon$ -padding of  $\exp(\delta)/\|\exp(\delta)\|_1$ . We do so by invoking the following lemma, substituting the values of  $\delta$  before (42) for  $\delta^-$  and  $\delta^+$  respectively, and  $\lambda_{\text{scm}} \leq \varepsilon/n$  for  $\rho$ .

**Lemma 9.** *Let  $\delta^-, \delta^+ \in \mathbb{R}^n$  satisfy*

$$[\delta^+]_i = \max\left\{[\delta^-]_i, \max_j [\delta^-]_j + \log \rho\right\} \text{ for all } j \in [n] \text{ and } \rho \leq 1.$$

*Then,  $\exp(\delta^+)/\|\exp(\delta^+)\|_1$  is a  $\rho n$ -padding of  $\exp(\delta^-)/\|\exp(\delta^-)\|_1$ .*

*Proof.* Let  $x = \exp(\delta^-) / \|\exp(\delta^-)\|_1$ ,  $x' = \exp(\delta^+) / \|\exp(\delta^+)\|_1$ , and  $\tilde{x} = \exp(\delta^+) / \|\exp(\delta^-)\|_1$ . Clearly  $x' = \tilde{x} / \|\tilde{x}\|_1$  and  $\tilde{x} \geq x$  element-wise. Moreover, letting  $M = \max_j \exp([\delta^-]_j)$ , we have

$$\|\tilde{x} - x\|_1 = \frac{\|\exp(\delta^+) - \exp(\delta^-)\|_1}{\|\exp(\delta^-)\|_1} \leq \frac{\rho M |\{i \mid [\delta^+]_i \neq [\delta^-]_i\}|}{\|\exp(\delta^-)\|_1} \leq \frac{\rho M \cdot n}{\|\exp(\delta^-)\|_1} \leq \rho n,$$

establishing the  $\rho n$ -padding property.  $\square$

Finally, we discuss runtime. Recall that the cost of initializing a **ScaleMaintainer** with  $|S|$  elements is  $O(|S| \log n \log^2 \omega)$ . So, step 1 of our implementation of **MultSparse**, i.e., calling **Del** once and initializing a rank-1 **ScaleMaintainer** per nonzero element, costs  $O(\|g\|_0 \log n \log^2 \omega)$ . We now discuss costs of merging in step 2. We show these merges cost an amortized  $O(\log^2 n \log^2 \omega)$  per nonzero coordinate of  $g$ , leading to the claimed bound. Specifically, we show the cost of  $T$  deletions and initializations due to nonzero entries of **MultSparse** arguments is  $O(T \log^2 n \log^2 \omega)$ . Consider the number of times a rank- $k$  set can be created through merges: we claim it is upper bounded by  $O(T/2^k)$ . It follows that the overall complexity of step 2 is

$$O\left(\sum_{k=0}^K 2^k \frac{T}{2^k} \log n \log^2 \omega\right) = O(T \log^2 n \log^2 \omega).$$

The claimed bound on the number of rank- $k$  merges holds because at least  $2^{k-1}$  deletions (and hence that many **MultSparse** calls) must occur between consecutive rank- $k$  merges. To see this, for each  $k$ , maintain a potential  $\Phi_k$  for the sum of cardinalities of all rank  $\ell$  sets for  $\ell < k$ . Each deletion increases  $\Phi_k$  by at most 1. For an insertion merge to create a rank- $k$  set,  $\Phi_k$  must have been at least  $2^{k-1} + 2$ ; after the merge, it is 0, as in its creation, all rank- $\ell$  sets for  $\ell < k$  must have been merged. So, there must have been at least  $2^{k-1}$  deletions in between merges.

**DenseStep.** To implement **DenseStep** we simply increment  $\tau_k \leftarrow \tau_k + 1$  for all  $k$ ; clearly, this takes time  $O(\log n)$ . We now show that (37) is maintained, i.e., that the resulting update to the variable  $\delta$  under **DenseStep** is (38). Recall that **ScaleMaintainer** $_k$  is initialized according (44). Clearly, (37) holds at initialization for the set  $S_k$ , as  $1 - \kappa^0 = 0$ . We now show that it continues to hold after any number of **DenseStep** calls. Let  $\delta_0$  be the value of  $[\delta]_{S_k}$  when **ScaleMaintainer** $_k$  is initialized, and let  $\delta_\tau$  be the value of  $[\delta]_{S_k}$  after  $\tau$  calls to **DenseStep**, each performing the update  $x \leftarrow \Pi_\Delta(x^\kappa \circ \exp(v))$ . This is consistent with the update  $\delta_{\tau+1} = \kappa \delta_\tau + [v]_{S_k}$ , which requires

$$\delta_\tau = \kappa^\tau \delta_0 + \sum_{\tau'=0}^{\tau-1} \kappa^{\tau'} [v]_{S_k} = \kappa^\tau \delta_0 + \frac{1 - \kappa^\tau}{1 - \kappa} [v]_{S_k} = \log(\gamma_k \bar{x}_k) + (1 - \kappa^\tau) \bar{\delta}_k,$$

where in the final transition we substituted  $\delta_0 = \log(\gamma_k \bar{x}_k)$  and  $[v]_{S_k} = (1 - \kappa)[\bar{\delta}_k + \delta_0]$  according to (44). We see that the required form of  $\delta_\tau$  is identical to its definition (36) and consequently that (37) holds.

**UpdateSum.** We maintain the running sum  $s$  via the invariant

$$[s]_{S_k} = [u]_{S_k} + \text{ScaleMaintainer}_k.\text{GetSum}(), \quad \forall k \in [K], \quad (45)$$

which we preserve in two separate procedures. First, whenever **UpdateSum**() is called, we compute the quantity  $\Gamma$  defined in (40), and for each  $k \in [K]$  call

$$\text{ScaleMaintainer}_k.\text{UpdateSum}\left(\frac{\gamma_k \text{ScaleMaintainer}_k.\text{GetNorm}(1 - \kappa^{\tau_k})}{\Gamma}\right).$$

It is straightforward to see that this indeed preserves the invariant (45) for our definition of  $\hat{x}$  in (41), and takes time  $O(\log n \log \omega)$ . Next, whenever a coordinate is deleted from a **ScaleMaintainer** <sub>$k$</sub>  instance, or an entire **ScaleMaintainer** <sub>$k$</sub>  instance is deleted due to a merge operation, we update

$$u_j \leftarrow u_j + \text{ScaleMaintainer}_k.\text{GetSum}(j)$$

for every deleted coordinate  $j$ , or  $j$  involved in the merge, respectively. We charge the cost of this operations to that of new **ScaleMaintainer** instance, which we accounted for in the analysis of **MultSparse**.

### 5.2.4 Queries

**Get( $j$ )**. Recalling our definition of  $\hat{x}$  (41), we compute  $\Gamma$  in time  $O(\log n \log \omega)$  by obtaining **GetNorm** $(1 - \kappa^{\tau_k})$  for each  $k$ , and then call **Get** $(j, 1 - \kappa^{\tau_k})$  in time  $O(\log \omega)$  for the relevant  $k$ .

**GetSum( $j$ )**. Recalling our definition of  $s$  (45), we implement **GetSum** $(j)$  in  $O(\log \omega)$  time via a single call to **GetSum** on the relevant **ScaleMaintainer** instance, and querying a coordinate of  $u$ .

**Sample**. Recalling (41), we first compute  $\Gamma$ , as well as all  $\gamma_k \text{ScaleMaintainer}_k.\text{GetNorm}(1 - \kappa^{\tau_k})$ , in  $O(\log n \log \omega)$  time. We then sample an instance **ScaleMaintainer** <sub>$k$</sub> , for  $0 \leq k \leq K$ , proportional to the value  $\gamma_k \text{ScaleMaintainer}_k.\text{GetNorm}(1 - \kappa^{\tau_k})$ , in  $O(\log n)$  time. Finally, for the sampled instance, we call **ScaleMaintainer** <sub>$k$</sub> .**Sample** $(1 - \kappa^{\tau_k})$  to output a coordinate in  $O(\log n \log \omega)$  time. By the definition of  $\hat{x}$  used by **ApproxExpMaintainer**, as well as the definitions used by each **ScaleMaintainer** <sub>$k$</sub>  instance, it is clear this preserves the correct sampling probabilities.

## 5.3 ScaleMaintainer

Finally, we provide a self-contained treatment of **ScaleMaintainer**, the main building block in the implementation of **ApproxExpMaintainer** described above.

### 5.3.1 Interface

For ease of reference we restate the interface of **ScaleMaintainer**, where for the sake of brevity we drop the subscript scm from  $\varepsilon$  and  $\lambda$ , and use  $n$  rather than  $n'$  to denote the input dimension. Recall that for the vectors  $\bar{x}$  and  $\bar{\delta}$  given at initialization, the data structure keeps track of vectors of the form

$$\hat{x}[\sigma] := \text{a } \varepsilon\text{-padding of } \Pi_{\Delta}(\bar{x} \circ \exp(\sigma \bar{\delta})), \quad (46)$$

where  $\sigma$  is any scalar in the range  $\{0\} \cup [\sigma_{\min}, 1]$ .

The implementation of the data structure relies on three internal parameters: polynomial approximation order  $p \in \mathbb{N}$ , truncation threshold  $R \geq 0$ , and  $\sigma$  discretization level  $K \in \mathbb{N}$ . To satisfy the accuracy requirements we set these as

$$R = \Theta(1) \log \frac{1}{\varepsilon \lambda}, \quad p = \Theta(1) \log \frac{1}{\varepsilon \lambda}, \quad \text{and} \quad K = \left\lceil \log \frac{1}{\sigma_{\min}} \right\rceil;$$

we give the runtime analysis in terms of these parameters.

### 5.3.2 Overview

We now outline our design of **ScaleMaintainer**, where the main challenge is supporting efficient **GetNorm** operations under no assumptions on the numerical range of the input  $\bar{\delta}$ .

| Category   | Function   | Runtime         |
|------------|--|-----------------|
| initialize | <b>Init</b> ( $\bar{x}, \bar{\delta}, \sigma_{\min}, \varepsilon, \lambda$ ): require $\bar{x} \in [\lambda, 1]^n$ | $O(npK \log n)$ |
| update     | <b>Del</b> ( $j$ ): Remove coordinate $j$ from $\bar{x}, \bar{\delta}$   | $O(1)$          |
|            | <b>UpdateSum</b> ( $\gamma, \sigma$ ): $s \leftarrow s + \gamma \hat{x}[\sigma]$                                   | $O(p)$          |
| query      | <b>Get</b> ( $j, \sigma$ ): Return $[\hat{x}[\sigma]]_j$   | $O(p)$          |
|            | <b>GetSum</b> ( $j$ ): Return $[s]_j$ .  | $O(pK)$         |
|            | <b>GetNorm</b> ( $\sigma$ ): Return $1 \pm \varepsilon$ approx. of $\ \bar{x} \circ \exp(\sigma \bar{\delta})\ _1$ | $O(p)$          |
| sample     | <b>Sample</b> ( $\sigma$ ): Return $j$ with probability $[\hat{x}[\sigma]]_j$                                      | $O(p \log n)$   |

**Exponential approximation via Taylor expansion.** Our main strategy is to replace the exponential in the definition of  $\hat{x}[\sigma]$  with its Taylor expansion of order  $p = O(\log \frac{n}{\varepsilon \lambda})$ , giving the following approximation to the **GetNorm**( $\sigma$ )

$$\|\bar{x} \circ \exp(\sigma \bar{\delta})\|_1 \approx \left\langle \bar{x}, \sum_{q=0}^p \frac{1}{q!} (\sigma \bar{\delta})^q \right\rangle = \sum_{q=0}^p \frac{\sigma^q}{q!} \langle \bar{x}, \bar{\delta}^q \rangle,$$

where  $q$ th powers are applied to  $\bar{\delta}$  elementwise. By pre-computing all the inner products  $\{\langle \bar{x}, \bar{\delta}^q \rangle\}_{q=0}^p$  at initialization, we may evaluate this Taylor approximation of **GetNorm** in time  $O(p)$ . The validity of the approximation relies on the following well-known fact.

**Fact 1** (Theorem 4.1 in [35]). *Let  $\varepsilon', R \geq 0$ . A Taylor series  $f_p(t) = \sum_{q=0}^p \frac{t^q}{q!}$  of degree  $p = O(R + \log \frac{1}{\varepsilon'})$  satisfies*

$$|\exp(t) - f_p(t)| \leq \exp(t) \varepsilon' \text{ for all } t \in [-R, 0].$$

**Truncating small coordinates and  $\sigma$  discretization.** For Fact 1 to directly imply the desired approximation guarantee for **GetNorm**, the entries of  $\sigma \bar{\delta}$  must all lie in  $[-R, 0]$  for some  $R = \tilde{O}(1)$ . However, this will not hold in general, as our data structure must support any value of  $\bar{\delta}$ . For a fixed value of  $\sigma$ , we can work instead with a shifted and truncated version of  $\bar{\delta}$ , i.e.,

$$\tilde{\delta}[\sigma, \mu] := \max\{\bar{\delta} - \mu, -R/\sigma\},$$

where the offset  $\mu$  is roughly the maximum element of  $\bar{\delta}$ . Fact 1 allows us to approximate the exponential of  $\sigma \tilde{\delta}[\sigma, \mu]$ , and for  $R = \Theta(\log(\frac{n}{\varepsilon \lambda}))$  we argue that the truncation of the smallest entries of  $\delta$  results in small multiplicative error. Unfortunately, the dependence of  $\tilde{\delta}[\sigma, \mu]$  on  $\sigma$  would defeat the purpose of efficient computation, because it is impossible to precompute  $\{\langle \bar{x}, \tilde{\delta}[\sigma, \mu]^q \rangle\}_{q=0}^p$  for every  $\sigma \in [\sigma_{\min}, 1]$ . To address this, we argue that truncation of the form  $\tilde{\delta}[\hat{\sigma}, \mu]$  is accurate enough for any  $\sigma \in [\hat{\sigma}/2, \hat{\sigma}]$ . Therefore, it suffices to discretize  $[\sigma_{\min}, 1]$  into  $K = \lceil \log \frac{1}{\sigma_{\min}} \rceil$  levels

$$\hat{\sigma}_k := 2^{k-1} \sigma_{\min}$$

and precompute  $\langle \bar{x}, \tilde{\delta}[\hat{\sigma}_k, \mu]^q \rangle$  for every  $k \in [K]$  in  $q \leq p$ . This allows us to compute **GetNorm**( $\sigma$ ) in  $O(p) = \tilde{O}(1)$  time, with  $O(npK) = \tilde{O}(n)$  preprocessing time.

**Supporting deletion via lazy offset selection.** Had the dataset not supported deletions, we could have simply set  $\mu$  to be the largest entry of  $\bar{\delta}$  (independent of  $k$ ). However, with deletions the largest entry of  $\bar{\delta}$  could change, potentially invalidating the truncation. To address this, we maintain a different threshold  $\mu_k$  for every  $k \in [K]$ , and argue that the approximation remains valid if the invariant

$$\bar{\delta}_{\max} \leq \mu_k \leq \bar{\delta}_{\max} + \frac{R}{2\hat{\sigma}_k} \text{ for every } k \in [K] \quad (47)$$

holds, where  $\bar{\delta}_{\max} := \max_j \bar{\delta}_j$ . Writing

$$\tilde{\delta}[k] := \tilde{\delta}[\hat{\sigma}_k, \mu_k] = \max \left\{ \bar{\delta} - \mu_k, -\frac{R}{\hat{\sigma}_k} \right\} \text{ for every } k \in [K], \quad (48)$$

the data structure only needs to maintain  $\mu_k$  and  $\langle \bar{x}, \tilde{\delta}[k]^q \rangle$  for every  $k \in [K]$  in  $q \leq p$ .

When deleting coordinate  $j$ , for every  $k$  we test whether the invariant (47) remains valid.<sup>4</sup> If it does, we keep  $\mu_k$  the same and implement deletion (for this value of  $k$ ) in time  $O(p) = \tilde{O}(1)$  by subtracting  $[\bar{x}]_j [\tilde{\delta}[k]]_j^q$  from  $\langle \bar{x}, \tilde{\delta}[k]^q \rangle$  for every  $q \leq p$ . If the invariant is no longer valid, we reset  $\mu_k$  to the new value of  $\bar{\delta}_{\max}$  and recompute  $\langle \bar{x}, \tilde{\delta}[k]^q \rangle$  for every  $q \leq p$ . Note that the re-computation time is proportional to the number of un-truncated coordinates in the newly defined  $\tilde{\delta}[k]$ . The key observation here is that every re-computation decreases  $\mu_k$  by at least  $R/(2\hat{\sigma}_k)$  and so no element of  $\bar{\delta}$  can remain un-truncated for more than two re-computation. Therefore, the cost of recomputing inner products due to deletions, for the entire lifetime of the data structure, is at most  $O(npK) = \tilde{O}(n)$ , which we charge to the cost of initialization.

**Explicit expression for  $\hat{x}[\sigma]$ .** Following the preceding discussion, for any  $\sigma \geq \sigma_{\min}$  we set

$$k^* = \left\lceil \log_2 \frac{\sigma}{\sigma_{\min}} \right\rceil, \text{ so that } \sigma \in \left[ \frac{\hat{\sigma}_{k^*}}{2}, \hat{\sigma}_{k^*} \right],$$

and define

$$Z[\sigma] := e^{\sigma \mu_{k^*}} \sum_{q=0}^p \frac{\sigma^q}{q!} \langle \bar{x}, \tilde{\delta}[k^*]^q \rangle \approx \|\bar{x} \circ \exp(\sigma \bar{\delta})\|_1 \quad (49)$$

$$\hat{x}[\sigma] := \frac{e^{\sigma \mu_{k^*}}}{Z[\sigma]} \sum_{q=0}^p \frac{\sigma^q}{q!} \bar{x} \circ \tilde{\delta}[k^*]^q \approx \Pi_{\Delta}(\bar{x} \circ \exp(\sigma \bar{\delta})), \quad (50)$$

with  $\tilde{\delta}$  as defined in (48).

### 5.3.3 Correctness

We now prove that the approximation guarantees of **ScaleMaintainer** hold.

**Proposition 5.** *There exist  $R = O(1) \cdot \log \frac{n}{\varepsilon \lambda}$  and  $p = O(1) \cdot \log \frac{n}{\varepsilon \lambda}$  such that for all  $\sigma \in [\sigma_{\min}, 1]$ , if the invariant (47) holds we have that  $Z[\sigma]$  is an  $\varepsilon$  multiplicative approximation of  $\|\bar{x} \circ \exp(\sigma \bar{\delta})\|_1$  and  $\hat{x}[\sigma]$  is a  $\varepsilon$ -padding of  $\Pi_{\Delta}(\bar{x} \circ \exp(\sigma \bar{\delta}))$ , with  $Z[\sigma]$  and  $\hat{x}[\sigma]$  defined in Eq.s (49) and (50) respectively.*

<sup>4</sup> We can query the maximum entry of  $\bar{\delta}$  under deletions in  $O(1)$  time via a standard data structure, e.g. a doubly-linked list of the sorted entries of  $\bar{\delta}$ .

*Proof.* To simplify notation, we write  $\mu = \mu_{k^\star}$  and  $\hat{\sigma} = \hat{\sigma}_{k^\star}$ . We begin by noting that the inequalities (47) and  $\sigma \leq \hat{\sigma}$  imply that  $\sigma \tilde{\delta}_i[k^\star] \in [-R, 0]$  for every  $i \in [n]$  and we may therefore apply Fact 1 to obtain

$$\sum_{q=0}^p \frac{\sigma^q}{q!} \bar{x}_j \tilde{\delta}_i[k^\star]^q \geq (1 - \varepsilon') \bar{x}_i \exp(\sigma \tilde{\delta}_i[k]) \geq (1 - \varepsilon') e^{-\sigma \mu} \bar{x}_i \exp(\sigma \bar{\delta}_i[k]) \quad (51)$$

for every  $i \in [n]$ . Therefore, we have

$$Z[\sigma] \geq (1 - \varepsilon') \|\bar{x} \circ \exp(\sigma \bar{\delta})\|_1. \quad (52)$$

Similarly, we have

$$\sum_{q=0}^p \frac{\sigma^q}{q!} \bar{x}_j \tilde{\delta}_i[k^\star]^q \leq (1 + \varepsilon') \bar{x}_i \exp(\sigma \tilde{\delta}_i[k]) \leq (1 + \varepsilon') e^{-\sigma \mu} \bar{x}_i (\exp(\sigma \bar{\delta}_i[k]) + \exp(-\sigma R/\hat{\sigma}))$$

Note that the condition (47) also implies that  $\tilde{\delta}_j[k^\star] \geq -R/(2\hat{\sigma})$  for some  $j \in [n]$  (namely the maximal element of  $\bar{\delta}$ ). Using also  $\bar{x}_j \geq \lambda$ , we have

$$e^{\sigma \mu} \exp(-\sigma R/\hat{\sigma}) \leq \exp(-\sigma R/(2\hat{\sigma})) \frac{\bar{x}_j}{\lambda} \exp(\sigma \bar{\delta}_j).$$

Taking  $R \geq 2 \log \frac{2n}{\lambda \varepsilon'}$  and recalling that  $\sigma \geq \hat{\sigma}/2$ , we have  $\exp(-\sigma R/(2\hat{\sigma})) \leq \lambda \varepsilon'/(2n)$  and consequently

$$e^{\sigma \mu} \exp(-\sigma R/\hat{\sigma}) \leq \varepsilon' \bar{x}_j \exp(\sigma \bar{\delta}_j) \leq \frac{\varepsilon'}{n} \|\bar{x} \circ \exp(\sigma \bar{\delta})\|_1.$$

Substituting back and using  $\bar{x}_i \leq 1$  and  $\varepsilon' < 1$  gives

$$e^{\sigma \mu} \sum_{q=0}^p \frac{\sigma^q}{q!} \bar{x}_j \tilde{\delta}_i[k^\star]^q \leq (1 + \varepsilon') \bar{x}_i \exp(\sigma \bar{\delta}_i) + \frac{\varepsilon'}{n} \|\bar{x} \circ \exp(\sigma \bar{\delta})\|_1. \quad (53)$$

Summing over  $i \in [n]$ , we obtain

$$Z[\sigma] \leq (1 + 2\varepsilon') \|\bar{x} \circ \exp(\sigma \bar{\delta})\|_1 \quad (54)$$

Therefore,  $Z[\sigma]$  is a  $2\varepsilon'$ -multiplicative approximation of  $\|\bar{x} \circ \exp(\sigma \bar{\delta})\|_1$ .

It remains to show that  $\hat{x}[\sigma]$  is a  $\varepsilon$ -padding of  $x[\sigma] := \Pi_\Delta(\bar{x} \circ \exp(\sigma \bar{\delta}))$ . First, if we define  $\tilde{x} = \frac{1+2\varepsilon'}{1-\varepsilon'} \hat{x}[\sigma]$  then the bounds (51) and (54) imply that  $\tilde{x} \geq x[\sigma]$  elementwise. Also, the bounds (52) and (53) imply that

$$\hat{x}_i[\sigma] - x_i[\sigma] \leq \frac{(1 + \varepsilon')x_i[\sigma] + \varepsilon'/n}{1 - \varepsilon'}$$

for every  $i \in [n]$ . Therefore, for  $\varepsilon' < 1/10$ ,

$$\|\tilde{x} - x[\sigma]\|_1 \leq \left( \frac{1 + 2\varepsilon'}{1 - \varepsilon'} \right)^2 - 1 \leq 10\varepsilon',$$

so that  $\hat{x}[\sigma]$  is a  $10\varepsilon'$  padding of  $x[\sigma]$ . Taking  $\varepsilon' = \varepsilon/10$  concludes the proof.  $\square$

### 5.3.4 Implementation: data structure state and initialization

Besides storing  $\bar{x}$  and  $\bar{\delta}$ , the data structure maintains the following fields.

1. An offset  $\mu_k \in \mathbb{R}$  for every  $k \leq K = \left\lceil \log \frac{1}{\sigma_{\min}} \right\rceil$ , initialized as  $\mu_k = \max_j [\bar{\delta}]_j$  for all  $k$ .
2. A balanced binary tree with  $n$  leaves. For node  $v$  in the tree,  $k \in [K]$  and  $q \in \{0, \dots, p\}$ , we store

$$A_v[k, q] := \left\langle \bar{x}, \tilde{\delta}[k]^q \right\rangle_{S_v},$$

where  $\tilde{\delta}[k] = \max\{\bar{\delta} - \mu_k, -R/\hat{\sigma}_k\}$  as before, the set  $S_v$  contains the leaves in the subtree rooted in  $v$ , and  $\langle a, b \rangle_S := \sum_{i \in S} a_i b_i$ . When referring to the root of the tree we omit the subscript, i.e., we write

$$A[k, q] := \left\langle \bar{x}, \tilde{\delta}[k]^q \right\rangle.$$

3. A vector  $u \in \mathbb{R}^n$  and coefficients  $c_{k,q} \in \mathbb{R}$  for every  $k \in [K]$  and  $q \in \{0, \dots, p\}$ , for maintaining the running sum. We initialize them all to be 0. The running sum obeys the following invariant:

$$s = u + \sum_{k=1}^K \sum_{q=0}^p \frac{c_{k,q}}{q!} \bar{x} \circ \tilde{\delta}[k]^q. \quad (55)$$

4. A doubly linked list of the sorted entries of  $\bar{\delta}$ , with a pointer to the maximal element of  $\bar{\delta}$  as well as pointers to the largest element smaller than  $\mu_k - R/\hat{\sigma}_k$  for every  $k \in [K]$ .

Initializing the data structure for maintaining the maximum element takes time  $O(n \log n)$  due to the need to sort  $\bar{\delta}$ . With it, initializing  $\mu_k$  is trivial and so is the initialization of  $u$  and  $c_{q,k}$ . Initializing the data stored in the binary tree takes time  $O(npK)$ , since for every value  $k$  and  $q$  and internal node  $v$  with children  $v', v''$  we can recursively compute  $A_v[k, q]$  as  $A_{v'}[k, q] + A_{v''}[k, q]$ . We will also charge some additional deletion costs to the initialization runtime, resulting in the overall complexity  $O(npK \log n)$ .

### 5.3.5 Implementation: queries and sampling

**GetNorm( $\sigma$ ).** We compute  $k^* = \left\lceil \log_2 \frac{\sigma}{\sigma_{\min}} \right\rceil$  and return  $Z[\sigma] = e^{\sigma k^*} \sum_{q=0}^p \frac{\sigma^q}{q!} A[k^*, q]$ . Clearly, this takes  $O(p)$  time and Proposition 5 provides the claimed approximation guarantee.

**Get( $j, \sigma$ ).** We compute  $Z[\sigma]$  and  $k^*$  as described above and return  $\frac{e^{\sigma \mu_{k^*}}}{Z[\sigma]} \sum_{q=0}^p \frac{\sigma^q}{q!} \bar{x}_j \tilde{\delta}_j[k^*]^q$  in accordance with the form (50) of  $\hat{x}[\sigma]$ . Again, this takes  $O(p)$  time and Proposition 5 provides the claimed approximation guarantee.

**GetSum( $j$ ).** Recalling the invariant (55), we return  $u_j + \sum_{k=1}^K \sum_{q=0}^p \frac{c_{k,q}}{q!} \bar{x}_j \tilde{\delta}_j[k]^q$  in time  $O(pK)$ .

**Sample( $\sigma$ ).** We perform a random walk from the root of our binary tree data structure to a leaf. At each internal node  $v$  with children  $v'$  and  $v''$ , we select node  $v'$  with probability

$$\frac{\langle \mathbf{1}, \hat{x}[\sigma] \rangle_{S_{v'}}}{\langle \mathbf{1}, \hat{x}[\sigma] \rangle_{S_v}} = \frac{\sum_{q=0}^p \frac{\sigma^q}{q!} A_{v'}[k^*, q]}{\sum_{q=0}^p \frac{\sigma^q}{q!} A_v[k^*, q]},$$



and otherwise select  $v''$ , where  $k^* = \left\lceil \log_2 \frac{\sigma}{\sigma_{\min}} \right\rceil$ . We return the index associated with the leaf in which we end the walk; the probability of returning index  $j$  is exactly  $[\hat{x}[\sigma]]_j$ . Each step in the walk takes time  $O(p)$  and there are  $O(\log n)$  steps, so the total time is  $O(p \log n)$ .

### 5.3.6 Implementation: updates

**UpdateSum**( $\sigma$ ). Recalling the invariant (55) and the form (50) of  $\hat{x}[\sigma]$ , we compute  $k^*$  and  $Z[\sigma]$  as in the **GetNorm** implementation, and update update

$$c_{k^*,q} \leftarrow c_{k^*,q} + \frac{e^{\sigma \mu_{k^*}} \sigma^q}{Z[\sigma]}$$

for every  $q \in \{0, \dots, p\}$ . This takes time  $O(p)$ .

**Del**( $j$ ). We set  $[\bar{\delta}_j] \leftarrow -\infty$ , remove the element corresponding to index  $j$  from the doubly linked list, and perform the following operations for each  $k \in [K]$  separately. First, we check if the new maximum element of  $\bar{\delta}$  is a least  $\mu_k - R/(2\hat{\sigma}_k)$ . If it is, we leave  $\mu_k$  unchanged and we simply update

$$A_v[k, q] \leftarrow A_v[k, q] - \bar{x}_j \bar{\delta}_j[k]^q$$

for every  $q \leq p$  and node  $v$  on the path from the root to the leaf corresponding to index  $j$ . Since the length of the path is  $O(\log n)$ , this update takes time  $O(p \log n)$ .

Otherwise, the new maximum element is less than  $\mu_k - R/(2\hat{\sigma}_k)$ , and we must change  $\mu_k$  in order to maintain the invariant (47). Let  $\mu_k^{\text{new}}$  be the new maximum element of  $\bar{\delta}$ , and let

$$U_k = \left\{ i \mid [\bar{\delta}]_i \geq \mu_k^{\text{new}} + \frac{R}{\hat{\sigma}_k} \right\}$$

be the new set of un-truncated indices. (We find the elements in this set when we update the pointer to the first element smaller than  $\mu_k - R/\hat{\sigma}_k$ ). We recompute  $A_v[k, q] = \left\langle \bar{x}, \bar{\delta}[k]^q \right\rangle_{S_v}$  for every  $q \leq p$  and every node  $v$  with a child in  $U_k$ . Performing the computation recursively from leaf to root, this take at most  $O(|U_k|p \log n)$  time. To maintain the invariant (55) as the definition of  $\bar{\delta}[k]$  changes, we update

$$u_j \leftarrow u_j + \sum_{q=0}^p \frac{c_{k,q}}{q!} \bar{x}_j ([\bar{\delta}_j - \mu_k^{\text{new}}]^q - [\max\{\bar{\delta}_j - \mu_k, -R/\hat{\sigma}_k\}]^q) \quad \text{for every } j \in U_k;$$

this update takes  $O(|U_k|p)$  time. Finally, we update  $\mu_k \leftarrow \mu_k^{\text{new}}$ .

Summing over  $k \in [K]$ , deletion operations of the first kind (with  $\mu_k$  unchanged) take at most  $O(Kp \log n)$  time per call to **Del**. Operations of the second kind (with  $\mu_k$  decreased) take time  $O(Np \log n)$  throughout the data structure lifetime, where  $N = \sum_{t \geq 1} \sum_{k=1}^K |U_k^{(t)}|$  and for each  $k \in [K]$  we write  $U_k^{(1)}, U_k^{(2)}, \dots$  to denote the different sets  $U_k$  generated by all calls to **Del**. For each  $k$ , if  $\mu_k$  is decreased at all then it must decrease by at least  $R/(2\hat{\sigma}_k)$ . Therefore, by definition of  $U_k$ , an index  $j$  can belong to  $U_k^{(t)}$  for at most 2 values of  $t$ . Consequently, we have  $N = O(nK)$ . Therefore, deletion operations of the second kind contribute at most  $O(nKp \log n)$  to the total runtime, which we charge to initialization.

## 6 Applications

In this section, we leverage the techniques of this paper to obtain improved runtimes for solving certain structured optimization problems.

In Sections 6.1 and 6.2, we use a variant of our variance-reduced coordinate method in the  $\ell_2$ - $\ell_1$  setup to obtain algorithms for solving the maximum inscribed ball (Max-IB) and minimum enclosing ball (Min-EB) problems. Our algorithms improve upon the runtimes of those in Allen-Zhu et al. [2] by a factor depending on the sparsity of the matrix. This improvement stems from a preprocessing step in [2] where the input is randomly rotated to improve a norm dependence of the algorithm. Our methods avoid this preprocessing and obtain runtimes dependent on the both the sparsity and numerical sparsity of the data, providing universal improvements in the sparse regime, in the non-degenerate case where the span of the points is full-rank.

In Section 6.3, we use the results of our variance-reduced algorithm in the  $\ell_2$ - $\ell_2$  setup (cf. Section D.2) to obtain improved regression algorithms for a variety of data matrices, including when the matrix is numerically sparse or entrywise nonnegative.

Our methods in this section rely on an extension of the outer loop of this paper (Algorithm 2) for *strongly monotone minimax problems*, developed in our previous work [8]. Specifically, for a separable regularizer  $r(x, y) = r^x(x) + r^y(y)$  on a joint space for any of our setups, consider the following composite bilinear minimax problem:

$$\min_{x \in \mathcal{X}} \max_{y \in \mathcal{Y}} f(x, y) := y^\top A x + \mu^x \phi(x) - \mu^y \psi(y), \text{ where } \phi = V_{x'}^x, \psi = V_{y'}^y. \quad (56)$$

We call such problem a  $(\mu^x, \mu^y)$ -strongly monotone problem; this is a special case of a generalization of the notion of strong convexity, in the case of convex minimization. For general strongly-monotone problems, Carmon et al. [8] provided a variant of Algorithm 2 with the following guarantee.

**Proposition 6** (Proposition 5, Carmon et al. [8]). *For problem (56), denote  $\mu := \sqrt{\mu^x \mu^y}$  and  $\rho := \sqrt{\mu^x / \mu^y}$ . Let  $\mathcal{O}$  be an  $(\alpha, \varepsilon)$ -relaxed proximal oracle for operator  $g(x, y) := (\nabla_x f(x, y), -\nabla_y f(x, y))$ , let  $\Theta$  be the range of  $r$ , and let  $\|(\nabla_x f(z), -\nabla_y f(z'))\|_* \leq G$ , for all  $z, z' \in \mathcal{Z}$ . Let  $z_K$  be the output of  $K$  iterations of `OuterLoopStronglyMonotone`, Algorithm 7 of Carmon et al. [8]. Then*

$$\mathbb{E} \text{Gap}(z_K) \leq \sqrt{2}G \sqrt{\left( \left( \frac{\alpha}{\mu + \alpha} \right)^K \left( \rho + \frac{1}{\rho} \right) \Theta + \frac{\varepsilon}{\mu} \right)}.$$

Each iteration  $k \in [K]$  consists of one call to  $\mathcal{O}$ , producing a point  $z_{k-1/2}$ , and one step of the form

$$z_k \leftarrow \left\{ \langle g(z_{k-1/2}), z \rangle + \alpha \hat{V}_{z_{k-1}}(z) + \mu \hat{V}_{z_{k-1/2}}(z) \right\}, \quad (57)$$

where  $\hat{V} := \rho V^x + \rho^{-1} V^y$ . In particular, by setting

$$\varepsilon = \frac{\mu \epsilon^2}{4G^2},$$

using  $K = \tilde{\mathcal{O}}(\alpha/\mu)$  iterations, we have the guarantee  $\mathbb{E} \text{Gap}(z_K) \leq \epsilon$ .

The  $(\alpha, \varepsilon)$ -relaxed proximal oracle works similarly as in Algorithm 3 except for the additional composite terms. For completeness we include the algorithm with its theoretical guarantees and implementation in Section E.2 (see Algorithm 4, Proposition 1 and Section E.2.2).

In all of our applications discussed in this section, the cost of each step (57) is  $O(\text{nnz})$ , stemming from the computation of  $g(x, y)$ . The resulting algorithms therefore have runtime

$$\tilde{O}\left((\text{nnz} + (\text{cost of implementing } \mathcal{O})) \cdot \frac{\alpha}{\mu}\right).$$

## 6.1 Maximum inscribed ball

In the maximum inscribed ball (Max-IB) problem, we are given a polyhedron  $P \subset \mathbb{R}^n$  defined by  $m$  halfspaces  $\{H_i\}_{i \in [m]}$ , each characterized by a linear constraint  $H_i = \{x \in \mathbb{R}^n : \langle a_i, x \rangle + b_i \geq 0\}$ , i.e.  $P = \cap_{i \in [m]} H_i$ . The goal is to (approximately) find a point  $x^* \in P$  that maximizes the smallest distance to any of the bounding hyperplanes  $H_i$ , i.e.

$$x_* \in \arg \max_{x \in P} \min_{i \in [m]} \frac{\langle a_i, x \rangle + b_i}{\|a_i\|_2}.$$

More formally, if the optimal radius of the maximum inscribed ball is  $r^*$ , the goal is to find an  $\epsilon$ -accurate solution, i.e. a point in  $P$  which has minimum distance to all bounding hyperplanes at least  $(1 - \epsilon)r^*$ .

Given halfspace information  $A, b$  where  $A_{i:} = a_i$  for all  $i \in [m]$ , the polytope is defined by  $P = \{x \mid Ax + b \geq 0\}$ . We use the following notation in this section:  $B := \|b\|_\infty$ ,  $r^*$  is the value of the maximum inscribed ball problem,  $R$  is the radius of the minimum enclosing ball, which is defined as the Euclidean ball containing  $P$  with smallest radius possible,  $x^*$  is the center of the maximum inscribed ball, and  $\rho$  is an upper bound on the aspect ratio  $R/r^*$ . As in Allen-Zhu et al. [2], we will make the following assumptions:

1. The polytope is bounded, and thus  $m \geq n$ . This is without loss of generality since when the polytope is unbounded, the aspect ratio  $\rho = \infty$ , and our runtime result holds trivially.
2.  $\|A_{i:}\|_2^2 = 1$  for all  $i \in [m]$ , so  $\|A\|_{2 \rightarrow \infty} = 1$ , by properly scaling  $A$  (one can consider the trivial case when for some  $i$ ,  $a_i = 0$  separately).
3. The origin is inside polytope  $P$ , i.e.  $O \in P$ , by properly shifting  $P$ .

We also define the following constant (see Appendix D.3) in this section with respect to the rescaled matrix  $A$ ,

$$L_{\text{co}}^{2,1} := \min \left\{ L_{\text{co}}^{2,1,(1)}, L_{\text{co}}^{2,1,(2)}, L_{\text{co}}^{2,1,(3)} \right\} \leq \sqrt{\text{rcs}} \cdot L_{\text{rc}}^{2,1} \leq \sqrt{\text{rcs}},$$

given the definitions of  $L_{\text{co}}^{2,1,(1)}, L_{\text{co}}^{2,1,(2)}, L_{\text{co}}^{2,1,(3)}$  as in (94), (95), and (96), and the second assumption above (namely, that  $L_{\text{rc}}^{2,1} = \max_{i \in [m]} \|A_{i:}\|_2 = 1$ ).

Allen-Zhu et al. [2] show that solving Max-IB is equivalent to the following minimax problem:

$$r^* := \max_{x \in \mathbb{R}^n} \min_{y \in \Delta_m} f(x, y) := y^\top Ax + y^\top b, \quad (58)$$

and moreover, to solve the problem to  $\epsilon$ -multiplicative accuracy, it suffices to find  $x_\epsilon^*$  that solves the minimax problem to  $\epsilon$ -multiplicative accuracy in terms of the one-sided gap of the  $x$  block, i.e.

$$\min_{y \in \Delta_m} f(x_\epsilon^*, y) \geq (1 - \epsilon) f(x^*, y^*),$$

where  $(x^*, y^*)$  is the optimal saddle point of problem (58). We first state several bounds on the parameters of the problem from Allen-Zhu et al. [2].

**Fact 2** (Geometric properties of Max-IB). *We have  $\|x^*\|_2 \leq 2R$ , and*

$$r^* = \max_{x \in \mathbb{R}^n} \min_{y \in \Delta_m} f(x, y) := y^\top A x + y^\top b \leq B \leq 2R.$$

These facts imply that we can instead consider the constrained minimax problem (where we overload our definition of  $f$  for the rest of the section):

$$r^* := \max_{x \in \mathbb{B}^n} \min_{y \in \Delta_m} f(x, y) = y^\top \tilde{A} x + y^\top b, \quad \text{where } \tilde{A} = 2R \cdot A. \quad (59)$$

We first use a “warm start” procedure to find a constant multiplicative estimate of  $r^*$ , which uses the strongly monotone algorithm `OuterLoopStronglyMonotone` of Carmon et al. [8] together with Algorithm 4 of Section E.2 as a relaxed proximal oracle on the  $(\mu, \mu)$ -strongly monotone problem

$$\max_{x \in \mathbb{B}^n} \min_{y \in \Delta_m} f_\mu(x, y) := y^\top \tilde{A} x + y^\top b + \mu \sum_{i \in [m]} [y]_i \log[y]_i - \frac{\mu}{2} \|x\|_2^2,$$

and a line search over parameter  $\mu$ . The following lemma is an immediate consequence of Proposition 6 and Corollary 1, whose proof we defer to Appendix F.1.

**Lemma 10.** *We can spend  $\tilde{O}(\text{nnz} + \rho\sqrt{\text{nnz}} \cdot L_{\text{co}}^{2,1})$  time preprocessing to obtain a 8-multiplicative approximation  $\hat{r}$  of  $r^*$ , i.e.*

$$\frac{\hat{r}}{8} \leq r^* \leq \hat{r}.$$

Finally, we use our variance-reduced coordinate algorithm, namely Algorithm 4 as a relaxed proximal oracle in `OuterLoopStronglyMonotone` together with Proposition 6 once more to solve (59) to the desired accuracy. The implementation in Section E.2.2 and complexity results in Section D.3 yield the runtime. This implementation crucially uses our development of the `ApproxExpMaintainer` data structure in order to obtain a runtime depending directly on `rcs` rather than dimensions of the matrix, as well as independence on  $B$ . For completeness, a proof can be found in Appendix F.1.

**Theorem 3.** *The algorithm of Section D.3 can be used to find an  $\epsilon$ -accurate solution  $x_\epsilon^*$  to Max-IB satisfying  $\min_{y \in \Delta_m} f(x_\epsilon^*, y) \geq (1 - \epsilon)r^*$  with high probability in time <sup>5</sup>*

$$\tilde{O}\left(\text{nnz} + \frac{\rho\sqrt{\text{nnz}} \cdot L_{\text{co}}^{2,1}}{\epsilon}\right) = \tilde{O}\left(\text{nnz} + \frac{\rho\sqrt{\text{nnz}} \cdot \text{rcs}}{\epsilon}\right).$$

**Remark 5.** Because we assumed  $m \geq n$ , in the case  $A$  is dense, up to logarithmic terms our runtime improves upon the runtime of  $\tilde{O}(\rho m\sqrt{n}/\epsilon)$  in Allen-Zhu et al. [2] by a factor of at least

$$\sqrt{\frac{mn}{\text{nnz}} \cdot \frac{m}{\text{rcs}}}$$

generically. This is an improvement when  $A$  is sparse or column-sparse, i.e.  $\text{nnz} \ll mn$ , or  $\text{rcs} \ll m$ . Such a saving is larger when  $A$  has numerical sparsity so that e.g.  $(L_{\text{co}}^{2,1})^2 \leq \max_{i \in [m]} \|A_{i:}\|_1^2 + (\max_{i \in [m]} \|A_{i:}\|_1) (\max_{j \in [n]} \|A_{:j}\|_1) < \text{rcs} \cdot \max_{i \in [m]} \|A_{i:}\|_2^2$ .

<sup>5</sup>Here  $\tilde{O}$  is hiding an additional factor of  $\text{polylog}(\|b\|_\infty)$  due to the additional cost in the runtime of `ApproxExpMaintainer`, caused by the linear term  $b$  (see Remark 2).

## 6.2 Minimum enclosing ball

In the minimum enclosing ball (Min-EB) problem, we are given a set of data points  $\{a_1, \dots, a_m\}$  with  $a_1 = 0, \max_{i \in [m]} \|a_i\| = 1$ .<sup>6</sup> The goal is to find the minimum radius  $R^*$  such that there exists a point  $x$  with distance at most  $R^*$  to all points. Following the presentation of Allen-Zhu et al. [2], we consider Min-EB in an equivalent form. Define the vector  $b$  to have  $b_i = \frac{1}{2} \|a_i\|_2^2$  entrywise. Then, Min-EB is equivalent to the minimax problem

$$R^* := \min_{x \in \mathbb{R}^n} \max_{y \in \Delta^m} \frac{1}{2} \sum_i y_i \|x - a_i\|_2^2 = \min_{x \in \mathbb{R}^n} \max_{y \in \Delta^m} f(x, y), \text{ where } f(x, y) := y^\top A x + y^\top b + \frac{1}{2} \|x\|_2^2. \quad (60)$$

By assumption,  $\|A\|_{2 \rightarrow \infty} = 1$ . We let  $(x^*, y^*)$  be the optimal solution to the saddle point problem. We first state several bounds on the quantities of the problem. These bounds were derived in Allen-Zhu et al. [2] and obtained by examining the geometric properties of the problem.

**Fact 3.** *The following bounds hold:  $\|x^*\|_2 \leq 1$ , and  $R^* \geq 1/8$ .*

To achieve a multiplicative approximation, since  $R^* \geq 1/8$  by Fact 3, it suffices to obtain a pair  $(x_\epsilon^*, y_\epsilon^*)$  achieving  $\max_y f(x_\epsilon^*, y) - \min_x f(x, y_\epsilon^*) \leq \epsilon/8$ . In light of minimax optimality, Lemma 11 (proved in Section F.2) shows that it suffices to consider, for  $\epsilon' = \Theta(\epsilon/\log m)$ , solving the following  $(1, \epsilon')$ -strongly monotone problem to sufficient accuracy:

$$\min_{x \in \mathbb{R}^n} \max_{y \in \Delta^m} f_{\epsilon'}(x, y) := y^\top A x + y^\top b - \epsilon' \sum_{i \in [m]} [y]_i \log[y]_i + \frac{1}{2} \|x\|_2^2. \quad (61)$$

**Lemma 11.** *Setting  $\epsilon' = \epsilon/(32 \log m)$ , an  $\epsilon/16$ -accurate solution to (61) is an  $\epsilon/8$ -accurate solution to the original problem (60).*

As an immediate result of the above lemma, the runtime in Section D.3 and the correctness proofs of Proposition 6 and Corollary 1, we obtain the following guarantee.

**Theorem 4.** *The strongly monotone algorithm `OuterLoopStronglyMonotone` of Carmon et al. [8], using Algorithm 4 of Section E.2 and the estimator of Section D.3 as a relaxed proximal oracle, finds an  $\epsilon$ -accurate solution  $x_\epsilon^*$  to Min-EB satisfying  $R^* \leq \max_y f(x_\epsilon^*, y) \leq (1 + \epsilon)R^*$  with high probability in time*

$$\tilde{O} \left( \text{nnz} + \frac{\sqrt{\text{nnz}} \cdot L_{\text{co}}^{2,1}}{\sqrt{\epsilon}} \right) = \tilde{O} \left( \text{nnz} + \frac{\sqrt{\text{nnz} \cdot \text{rcs}}}{\sqrt{\epsilon}} \right).$$

**Remark 6.** When  $m \geq n$ ,<sup>7</sup> up to logarithmic terms our runtime improves the  $\tilde{O}(m\sqrt{n}/\sqrt{\epsilon})$  runtime of Allen-Zhu et al. [2] by a factor of

$$\sqrt{\frac{mn}{\text{nnz}} \cdot \frac{m}{\text{rcs}}}$$

generically. This is an improvement when  $A$  is sparse or column-sparse, i.e.  $\text{nnz} \ll mn$ , or  $\text{rcs} \ll m$ . As in Section 6.1, the improvement is larger when  $A$  is numerically sparse, i.e. when  $(L_{\text{co}}^{2,1})^2 \leq \max_{i \in [m]} \|A_{i:}\|_1^2 + (\max_{i \in [m]} \|A_{i:}\|_1) (\max_{j \in [n]} \|A_{:,j}\|_1) < \text{rcs} \cdot \max_{i \in [m]} \|A_i\|_2^2$ .

<sup>6</sup>This can be assumed without loss of generality by shifting and rescaling as in Allen-Zhu et al. [2] and considering the trivial case when all  $a_i, i \in [m]$  are equal.

<sup>7</sup>When  $m < n$ , the runtime of the algorithm in Allen-Zhu et al. [2] still holds and is sometimes faster than ours.

### 6.3 Regression

We consider the standard  $\ell_2$  linear regression problem in a data matrix  $A \in \mathbb{R}^{m \times n}$  and vector  $b \in \mathbb{R}^m$ , i.e.  $\min_{x \in \mathbb{R}^n} \|Ax - b\|_2$ . In particular, we consider the equivalent primal-dual form,

$$\min_{x \in \mathbb{R}^n} \max_{y \in \mathbb{B}^m} f(x, y) := y^\top (Ax - b). \quad (62)$$

Throughout, we assume the smallest eigenvalue of  $A^\top A$  is  $\mu > 0$  and denote an optimal solution to (62) by  $z^* = (x^*, y^*)$  (where  $x^*$  is the unique solution to the regression problem). Our strategy is to consider a sequence of modified problems, parameterized by  $\beta > 0$ ,  $x' \in \mathbb{R}^n$ :

$$\min_{x \in \mathbb{R}^n} \max_{y \in \mathbb{B}^m} f_{x'}^\beta(x, y) := y^\top (Ax - b) + \frac{\beta}{2} \|x - x'\|_2^2 - \frac{\beta}{2} \|y\|_2^2. \quad (63)$$

We denote the optimal solution to (63) by  $z_{(\beta, x')}^* = (x_{(\beta, x')}^*, y_{(\beta, x')}^*)$ ; when clear from context, for simplicity we drop  $\beta$  and write  $z_{x'}^* = (x_{x'}^*, y_{x'}^*)$  (as  $\beta = \sqrt{\mu}$  throughout our algorithm). Lemma 12 (proved in Section F.3) states a known relation between the optimal solutions for (62) and (63).

**Lemma 12.** *Letting  $(x^*, y^*)$  be the optimal solution for (62) and  $(x_{x'}^*, y_{y'}^*)$  be the optimal solution for (63), the following relation holds:*

$$\|x_{x'}^* - x^*\|_2 \leq \frac{1}{1 + \frac{\mu}{\beta^2}} \|x' - x^*\|_2.$$

We give a full implementation of the regression algorithm in Algorithm 5 (see Section F.3), and state its correctness and runtime in Theorem 5. The algorithm repeatedly solves problems of the form (63) in phases, each time using Lemma 12 to ensure progress towards  $x^*$ . Observing that each subproblem is  $(\beta, \beta)$ -strongly monotone, each phase is conducted via `OuterLoopStronglyMonotone`, an algorithm of Carmon et al. [8], using the  $\ell_2$ - $\ell_2$  algorithms of Section D.2 as a proximal oracle. Due to the existence of composite terms, our inner loop steps are slightly different than in Section D.2; we give a more formal algorithm for the relaxed proximal oracle and its implementation in Algorithm 4 and Appendix E.2. We remark that by a logarithmic number of restarts per phase, a standard argument boosts Theorem 5 to a high-probability claim.

**Theorem 5.** *Given data matrix  $A \in \mathbb{R}^{m \times n}$ , vector  $b \in \mathbb{R}^m$ , and desired accuracy  $\epsilon \in (0, 1)$ , assuming  $A^\top A \succeq \mu I$  for  $\mu > 0$ , Algorithm 5 outputs an expected  $\epsilon$ -accurate solution  $\tilde{x}$ , i.e.*

$$\mathbb{E} [\|\tilde{x} - x^*\|_2] \leq \epsilon,$$

and runs in time

$$\tilde{O} \left( \text{nnz} + \sqrt{\text{nnz}} \cdot \frac{\max \left\{ \sqrt{\sum_i \|A_{i:}\|_1^2}, \sqrt{\sum_j \|A_{:j}\|_1^2} \right\}}{\sqrt{\mu}} \right).$$

We give two settings where the runtime of Algorithm 5 improves upon the state of the art.

**Entrywise nonnegative  $A$ .** In the particular setting when all entries of  $A$  are nonnegative,<sup>8</sup> by Proposition 7 our complexity as stated in Theorem 5 improves by a factor of  $\sqrt{\text{nnz}/(m+n)}$  the runtime of accelerated gradient descent [30], which is the previous state-of-the-art in certain regimes with runtime  $O(\text{nnz} \cdot \|A\|_{\text{op}}/\sqrt{\mu})$ . This speedup is most beneficial when  $A$  is dense.

<sup>8</sup>More generally, this holds for arbitrary  $A \in \mathbb{R}^{m \times n}$  satisfying  $\|A\|_{\text{op}} \leq \|A\|_{\text{op}}$ .

**Numerically sparse  $A$ .** For numerically sparse  $A$  with  $\|A_{i:}\|_1/\|A_{i:}\|_2 = O(1)$ ,  $\|A_{:j}\|_1/\|A_{:j}\|_2 = O(1)$  for all  $i \in [m]$ ,  $j \in [n]$ , we can choose  $\alpha = \sqrt{\mu}$  in Algorithm 5 and obtain the runtime

$$O\left(\text{nnz} + \frac{\max\{\sum_i \|A_{i:}\|_1^2, \sum_j \|A_{:j}\|_1^2\}}{\mu}\right) = O\left(\text{nnz} + \frac{\|A\|_F^2}{\mu}\right)$$

using the argument in Theorem 5. Under a (similar, but weaker) numerically sparse condition  $\|A_{i:}\|_1/\|A_{i:}\|_2 = O(1)$ , the prior state-of-the-art stochastic algorithm [19] obtains a runtime of  $O(\text{nnz} + \text{rcs} \cdot \|A\|_F^2/\mu)$ , and the recent state-of-the-art result in the numerically sparse regime [17] improves this to  $O(\text{nnz} + (\|A\|_F^2/\mu)^{1.5})$  when  $\text{rcs} = \Omega(\|A\|_F/\sqrt{\mu})$ . Improving universally over both, our method gives  $O(\text{nnz} + \|A\|_F^2/\mu)$  in this setting.

## Acknowledgements

This research was supported in part by Stanford Graduate Fellowships, NSF CAREER Award CCF-1844855, NSF Graduate Fellowship DGE-1656518 and a PayPal research gift. We thank the anonymous reviewers who helped improve the completeness and readability of this paper by providing many helpful comments.

## References

- [1] Z. Allen-Zhu, Y. T. Lee, and L. Orecchia. Using optimization to obtain a width-independent, parallel, simpler, and faster positive sdp solver. In *Proceedings of the twenty-seventh annual ACM-SIAM symposium on Discrete algorithms*, pages 1824–1831. Society for Industrial and Applied Mathematics, 2016.
- [2] Z. Allen-Zhu, Z. Liao, and Y. Yuan. Optimization algorithms for faster computational geometry. In *43rd International Colloquium on Automata, Languages, and Programming*, pages 53:1–53:6, 2016.
- [3] Z. Allen-Zhu, Z. Qu, P. Richtárik, and Y. Yuan. Even faster accelerated coordinate descent using non-uniform sampling. In *International Conference on Machine Learning*, pages 1110–1119, 2016.
- [4] E. Andersen, C. Roos, T. Terlaky, T. Trafalis, and J. Warners. The use of low-rank updates in interior-point methods. *Numerical Linear Algebra and Optimization*, pages 1–12, 1996.
- [5] M. G. Azar, R. Munos, and H. J. Kappen. Minimax pac bounds on the sample complexity of reinforcement learning with a generative model. *Machine learning*, 91(3):325–349, 2013.
- [6] D. Babichev, D. Ostrovskii, and F. Bach. Efficient primal-dual algorithms for large-scale multiclass classification. *arXiv preprint arXiv:1902.03755*, 2019.
- [7] P. Balamurugan and F. R. Bach. Stochastic variance reduction methods for saddle-point problems. In *Advances in Neural Information Processing Systems*, 2016.
- [8] Y. Carmon, Y. Jin, A. Sidford, and K. Tian. Variance reduction for matrix games. In *Advances in Neural Information Processing Systems*, 2019.
- [9] K. L. Clarkson and D. P. Woodruff. Low rank approximation and regression in input sparsity time. In *Proceedings of the 45th annual ACM symposium on Symposium on theory of computing*, pages 81–90. ACM, 2013.
- [10] K. L. Clarkson, E. Hazan, and D. P. Woodruff. Sublinear optimization for machine learning. In *51th Annual IEEE Symposium on Foundations of Computer Science*, pages 449–457, 2010.
- [11] M. B. Cohen, J. Nelson, and D. P. Woodruff. Optimal approximate matrix product in terms of stable rank. In *43rd International Colloquium on Automata, Languages, and Programming (ICALP 2016)*. Schloss Dagstuhl-Leibniz-Zentrum fuer Informatik, 2016.
- [12] M. B. Cohen, Y. T. Lee, and Z. Song. Solving linear programs in the current matrix multiplication time. *arXiv preprint arXiv:1810.07896*, 2018.
- [13] G. B. Dantzig. *Linear Programming and Extensions*. Princeton University Press, Princeton, NJ, 1953.
- [14] J. Duchi, S. Shalev-Shwartz, Y. Singer, and T. Chandra. Efficient projections onto the  $\ell_1$ -ball for learning in high dimensions. In *Proceedings of the 25th international conference on Machine learning*, pages 272–279. ACM, 2008.
- [15] A. Gilyén, S. Lloyd, and E. Tang. Quantum-inspired low-rank stochastic regression with logarithmic dependence on the dimension. *arXiv preprint arXiv:1811.04909*, 2018.
- [16] M. D. Grigoriadis and L. G. Khachiyan. A sublinear-time randomized approximation algorithm for matrix games. *Operation Research Letters*, 18(2):53–58, 1995.



- [17] N. Gupta and A. Sidford. Exploiting numerical sparsity for efficient learning: faster eigenvector computation and regression. In *Advances in Neural Information Processing Systems*, pages 5269–5278, 2018.
- [18] H. Jiang, Y. T. Lee, Z. Song, and S. C.-w. Wong. An improved cutting plane method for convex optimization, convex-concave games, and its applications. In *Proceedings of the 52nd Annual ACM SIGACT Symposium on Theory of Computing*, pages 944–953, 2020.
- [19] R. Johnson and T. Zhang. Accelerating stochastic gradient descent using predictive variance reduction. In *Advances in Neural Information Processing Systems*, 2013.
- [20] N. Karmarkar. A new polynomial-time algorithm for linear programming. In *Proceedings of the sixteenth annual ACM symposium on Theory of computing*, pages 302–311. ACM, 1984.
- [21] I. Koutis, G. L. Miller, and R. Peng. Approaching optimality for solving SDD linear systems. In *51th Annual IEEE Symposium on Foundations of Computer Science, FOCS 2010, October 23-26, 2010, Las Vegas, Nevada, USA*, pages 235–244, 2010.
- [22] Y. T. Lee and A. Sidford. Efficient accelerated coordinate descent methods and faster algorithms for solving linear systems. In *2013 IEEE 54th Annual Symposium on Foundations of Computer Science*, 2013.
- [23] Y. T. Lee and A. Sidford. Efficient inverse maintenance and faster algorithms for linear programming. In *IEEE 56th Annual Symposium on Foundations of Computer Science*, pages 230–249, 2015.
- [24] Y. T. Lee, A. Sidford, and S. C.-w. Wong. A faster cutting plane method and its implications for combinatorial and convex optimization. In *2015 IEEE 56th Annual Symposium on Foundations of Computer Science*, pages 1049–1065. IEEE, 2015.
- [25] Y. T. Lee, Z. Song, and Q. Zhang. Solving empirical risk minimization in the current matrix multiplication time. In *Conference on Learning Theory, COLT 2019, 25-28 June 2019, Phoenix, AZ, USA*, pages 2140–2157, 2019.
- [26] M. Minsky and S. Papert. *Perceptrons—an introduction to computational geometry*. MIT Press, 1987.
- [27] H. Namkoong and J. C. Duchi. Stochastic gradient methods for distributionally robust optimization with f-divergences. In *Advances in Neural Information Processing Systems*, pages 2208–2216, 2016.
- [28] A. Nemirovski. Prox-method with rate of convergence  $O(1/t)$  for variational inequalities with lipschitz continuous monotone operators and smooth convex-concave saddle point problems. *SIAM Journal on Optimization*, 15(1):229–251, 2004.
- [29] A. Nemirovski, A. Juditsky, G. Lan, and A. Shapiro. Robust stochastic approximation approach to stochastic programming. *SIAM Journal on optimization*, 19(4):1574–1609, 2009.
- [30] Y. Nesterov. A method for solving a convex programming problem with convergence rate  $o(1/k^2)$ . *Doklady AN SSSR*, 269:543–547, 1983.
- [31] Y. Nesterov. Dual extrapolation and its applications to solving variational inequalities and related problems. *Mathematical Programming*, 109(2-3):319–344, 2007.
- [32] Y. Nesterov. Efficiency of coordinate descent methods on huge-scale optimization problems. *SIAM Journal on Optimization*, 22(2):341–362, 2012.

- [33] Y. Nesterov and S. U. Stich. Efficiency of the accelerated coordinate descent method on structured optimization problems. *SIAM Journal on Optimization*, 27(1):110–123, 2017.
- [34] P. Richtárik and M. Takáč. On optimal probabilities in stochastic coordinate descent methods. *Optimization Letters*, 10(6):1233–1243, 2016.
- [35] S. Sachdeva and N. K. Vishnoi. Faster algorithms via approximation theory. *Foundations and Trends in Theoretical Computer Science*, 9(2):125–210, 2014.
- [36] S. Shalev-Shwartz and A. Tewari. Stochastic methods for  $\ell_1$ -regularized loss minimization. *Journal of Machine Learning Research*, 12:1865–1892, 2011.
- [37] S. Shalev-Shwartz and Y. Wexler. Minimizing the maximal loss: How and why. In *ICML*, pages 793–801, 2016.
- [38] S. Shalev-Shwartz and T. Zhang. Stochastic dual coordinate ascent methods for regularized loss minimization. *Journal of Machine Learning Research*, 14:567–599, 2013.
- [39] S. Shalev-Shwartz et al. Online learning and online convex optimization. *Foundations and Trends in Machine Learning*, 4(2):107–194, 2012.
- [40] A. Sidford and K. Tian. Coordinate methods for accelerating  $\ell_\infty$  regression and faster approximate maximum flow. In *59th IEEE Annual Symposium on Foundations of Computer Science, FOCS 2018, Paris, France, October 7-9, 2018*, pages 922–933, 2018.
- [41] A. Sidford, M. Wang, X. Wu, and Y. Ye. Variance reduced value iteration and faster algorithms for solving markov decision processes. In *Proceedings of the Twenty-Ninth Annual ACM-SIAM Symposium on Discrete Algorithms*, pages 770–787. Society for Industrial and Applied Mathematics, 2018.
- [42] T. Strohmer and R. Vershynin. A randomized Kaczmarz algorithm with exponential convergence. *Journal of Fourier Analysis and Applications*, 15(2):262, 2009.
- [43] C. Tan, T. Zhang, S. Ma, and J. Liu. Stochastic primal-dual method for empirical risk minimization with  $o(1)$  per-iteration complexity. In *Advances in Neural Information Processing Systems*, 2018.
- [44] J. van den Brand. A deterministic linear program solver in current matrix multiplication time. *arXiv preprint arXiv:1910.11957*, 2019.
- [45] J. van den Brand, Y. T. Lee, A. Sidford, and Z. Song. Solving tall dense linear programs in nearly linear time. In *Proceedings of the 52nd Annual ACM SIGACT Symposium on Theory of Computing*, 2020. To appear.
- [46] J. Von Neumann and O. Morgenstern. *Theory of games and economic behavior (commemorative edition)*. Princeton university press, 1944.
- [47] M. D. Vose. A linear algorithm for generating random numbers with a given distribution. *IEEE Transactions on software engineering*, 17(9):972–975, 1991.
- [48] M. Wang. Primal-dual  $\pi$  learning: Sample complexity and sublinear run time for ergodic Markov decision problems. *arXiv preprint arXiv:1710.06100*, 2017.
- [49] M. Wang. Randomized linear programming solves the discounted Markov decision problem in nearly-linear (sometimes sublinear) running time. *arXiv preprint arXiv:1704.01869*, 2017.
- [50] S. J. Wright. Coordinate descent algorithms. *Mathematical Programming*, 151(1):3–34, 2015.

- [51] A. Yurtsever, M. Udell, J. A. Tropp, and V. Cevher. Sketchy decisions: Convex low-rank matrix optimization with optimal storage. In *International Conference on Artificial Intelligence and Statistics (AISTATS)*, pages 1188–1196, 2017.
- [52] Y. Zhang and L. Xiao. Stochastic primal-dual coordinate method for regularized empirical risk minimization. *The Journal of Machine Learning Research*, 18(1):2939–2980, 2017.

# Appendix

## A Deferred proofs from Section 2

*Proof of Proposition 1.* It is clear that our choices of  $\mathcal{X}, \mathcal{Y}$  are compact and convex, and that the local norms we defined are indeed norms (in all cases, they are quadratic norms). Validity of our choices of  $\Theta$  follow from the well-known facts that for  $x \in \Delta^n$ , the entropy function  $\sum_{j \in [n]} x_j \log x_j$  is convex with range  $\log n$ , and that for  $x \in \mathbb{B}^n$ ,  $\frac{1}{2} \|x\|_2^2$  is convex with range  $\frac{1}{2}$ .

In the Euclidean case we have that  $V_x(x') = \frac{1}{2} \|x - x'\|_2^2$  and (15) follows from the Cauchy-Schwarz and Young inequalities:

$$\langle \gamma, x' - x \rangle \leq \frac{1}{2} \|\gamma\|_2^2 + \frac{1}{2} \|x - x'\|_2^2.$$

Similarly, for the simplex we have that entropy is 1-strongly-convex with respect to  $\|\cdot\|_1$  and therefore  $V_y(y') \geq \frac{1}{2} \|y - y'\|_1^2$ , and we obtain (15) from the Hölder and Young inequalities,

$$\langle \gamma, y' - y \rangle \leq \frac{1}{2} \|\gamma\|_\infty^2 + \frac{1}{2} \|y - y'\|_1^2,$$

where we note that  $\|\gamma\|_\infty = \|\gamma\|_*$  in this case.

Finally,  $\text{clip}(\cdot)$  is not the identity only when the corresponding domain is the simplex, in which case entropy satisfies the local norms bound [cf. 8, Lemma 13],

$$\langle \gamma, y - y' \rangle - V_y(y') \leq \sum_{i \in [m]} \gamma_i^2 y_i \quad \text{for all } y, y' \in \Delta^m \text{ and } \gamma \in \mathbb{R}^m \text{ such that } \|\gamma\|_\infty \leq 1.$$

Noting that  $\|\text{clip}(\gamma)\|_\infty \leq 1$  and that  $\|\text{clip}(\gamma)\|_y \leq \|\gamma\|_y$  for all  $y \in \Delta^m$ , we have the desired local bound (16). Finally, for every coordinate  $i \in [m]$  we have

$$|\gamma_i - [\text{clip}(\gamma)]_i| = |\gamma_i| - 1 \cdot \mathbb{I}_{\{\gamma_i > 1\}} \leq |\gamma_i| \cdot \mathbb{I}_{\{\gamma_i > 1\}} \leq |\gamma_i|^2.$$

Consequently,  $|\langle \gamma - \text{clip}(\gamma), z \rangle| \leq \sum_{i \in [m]} \gamma_i^2 z_i$ , giving the distortion bound (17).  $\square$

## B Deferred proofs from Section 3

### B.1 Proof of Proposition 2

In this section, we provide a convergence result for mirror descent under local norms. We require the following well-known regret bound for mirror descent.

**Lemma 13** ([8, Lemma 12]). *Let  $Q : \mathcal{Z} \rightarrow \mathbb{R}$  be convex, let  $T \in \mathbb{N}$ ,  $z_0 \in \mathcal{Z}$  and  $\gamma_0, \gamma_1, \dots, \gamma_T \in \mathcal{Z}^*$ . The sequence  $z_1, \dots, z_T$  defined by*

$$z_t = \arg \min_{z \in \mathcal{Z}} \{ \langle \gamma_{t-1}, z \rangle + Q(z) + V_{z_{t-1}}(z) \}$$

*satisfies for all  $u \in \mathcal{Z}$  (denoting  $z_{T+1} := u$ ),*

$$\sum_{t=0}^T \langle \gamma_t, z_t - u \rangle + \sum_{t=1}^T \langle \nabla Q(z_t), z_t - u \rangle \leq V_{z_0}(u) + \sum_{t=0}^T \{ \langle \gamma_t, z_t - z_{t+1} \rangle - V_{z_t}(z_{t+1}) \}. \quad (64)$$

The proposition follows from this regret bound, the properties of the local norm setup, and the “ghost iterate” argument due to [29].

**Proposition 2.** *Let  $(\mathcal{Z}, \|\cdot\|, r, \Theta, \text{clip})$  be a local norm setup, let  $L, \epsilon > 0$ , and let  $\tilde{g}$  be an  $L$ -local estimator. Then, for  $\eta \leq \frac{\epsilon}{9L^2}$  and  $T \geq \frac{6\Theta}{\eta\epsilon} \geq \frac{54L^2\Theta}{\epsilon^2}$ , Algorithm 1 outputs a point  $\bar{z}$  such that*

$$\mathbb{E} \text{Gap}(\bar{z}) \leq \mathbb{E} \left[ \sup_{u \in \mathcal{Z}} \frac{1}{T+1} \sum_{t=0}^T \langle g(z_t), z_t - u \rangle \right] \leq \epsilon.$$

*Proof.* Defining

$$\tilde{\Delta}_t := g(z_t) - \frac{1}{\eta} \text{clip}(\eta \tilde{g}(z_t))$$

and the ghost iterates

$$s_t = \arg \min_{s \in \mathcal{Z}} \left\{ \left\langle \frac{1}{2} \eta \tilde{\Delta}_{t-1}, s \right\rangle + V_{s_{t-1}}(s) \right\} \quad \text{with } s_0 = w_0,$$

we rearrange the regret as

$$\eta \sum_{t=0}^T \langle g(z_t), z_t - u \rangle \leq \sum_{t=0}^T \langle \text{clip}(\eta \tilde{g}(z_t)), z_t - u \rangle + \sum_{t=0}^T \langle \eta \tilde{\Delta}_t, s_t - u \rangle + \sum_{t=0}^T \langle \eta \tilde{\Delta}_t, z_t - s_t \rangle, \quad (65)$$

and bound each term in turn.

We first apply Lemma 13 with  $Q = 0$  and  $\gamma_t = \text{clip}(\eta \tilde{g}(z_t))$ , using (16) to conclude that

$$\sum_{t=0}^T \langle \text{clip}(\eta \tilde{g}(z_t)), z_t - u \rangle \leq V_{z_0}(u) + \eta^2 \sum_{t=0}^T \|\tilde{g}(z_t)\|_{z_t}^2, \quad \text{for all } u \in \mathcal{Z}. \quad (66)$$

Next, we apply Lemma 13 again, this time with  $\gamma_t = \frac{1}{2} \eta \tilde{\Delta}_t$ , to obtain the regret bound

$$\begin{aligned} \sum_{t=0}^T \langle \eta \tilde{\Delta}_t, s_t - u \rangle &\leq 2V_{z_0}(u) + \sum_{t=0}^T \left\{ \langle \eta \tilde{\Delta}_t, s_t - s_{t+1} \rangle - 2V_{s_t}(s_{t+1}) \right\} \\ &\leq 2V_{z_0}(u) + \eta^2 \sum_{t=0}^T \left\{ \|\tilde{g}(z_t)\|_{s_t}^2 + \frac{1}{2} \|g(z_t)\|_*^2 \right\}, \end{aligned} \quad (67)$$

for all  $u \in \mathcal{Z}$ , where we used

$$\begin{aligned} \langle \eta \tilde{\Delta}_t, s_t - s_{t+1} \rangle - 2V_{s_t}(s_{t+1}) &\leq \langle \eta g(z_t), s_t - s_{t+1} \rangle - V_{s_t}(s_{t+1}) \\ &\quad + |\langle \text{clip}(\eta \tilde{g}(z_t)), s_t - s_{t+1} \rangle| - V_{s_t}(s_{t+1}), \end{aligned}$$

and then appealed to the bounds (15) and (16) in the definition of the local norm setup. Now, substituting (66) and (67) into (65), maximizing over  $u$ , and taking an expectation, we obtain

$$\begin{aligned} \mathbb{E} \sup_{u \in \mathcal{Z}} \sum_{t=0}^T \langle \eta g(z_t), z_t - u \rangle &\leq 3\Theta + \eta^2 \mathbb{E} \sum_{t=0}^T \left\{ \|\tilde{g}(z_t)\|_{z_t}^2 + \|\tilde{g}(z_t)\|_{s_t}^2 + \frac{1}{2} \|g(z_t)\|_*^2 \right\} \\ &\quad + \mathbb{E} \sum_{t=0}^T \langle \eta \tilde{\Delta}_t, z_t - s_t \rangle. \end{aligned} \quad (68)$$

To bound the last term we use the fact that  $g(z_t) = \mathbb{E} [\tilde{g}(z_t) \mid z_t, s_t]$  (which follows from the first part of Definition 3). We then write

$$\left| \mathbb{E} \left\langle \eta \tilde{\Delta}_t, z_t - s_t \right\rangle \right| \leq \mathbb{E} |\langle \eta \tilde{g}(z_t) - \text{clip}(\eta \tilde{g}(z_t)), z_t - s_t \rangle| \leq \eta^2 \|\tilde{g}(z_t)\|_{z_t}^2 + \eta^2 \|\tilde{g}(z_t)\|_{s_t}^2, \quad (69)$$

where the first inequality is by Jensen's inequality, and the last is due to the property (17) of the local norm setup. Substituting (69) into (68), we obtain

$$\mathbb{E} \sup_{u \in \mathcal{Z}} \sum_{t=0}^T \langle \eta g(z_t), z_t - u \rangle \leq 3\Theta + \eta^2 \mathbb{E} \sum_{t=0}^T \left\{ 2 \|\tilde{g}(z_t)\|_{z_t}^2 + 2 \|\tilde{g}(z_t)\|_{s_t}^2 + \frac{1}{2} \|g(z_t)\|_*^2 \right\}.$$

Finally, using the second moment bound of local gradient estimator (Definition 3) and its consequence Lemma 1, we may bound each of the expected squared norm terms by  $L^2$ . Dividing through by  $\eta(T+1)$  gives

$$\mathbb{E} \sup_{u \in \mathcal{Z}} \left[ \frac{1}{T+1} \sum_{t=0}^T \langle g(z_t), z_t - u \rangle \right] \leq \frac{3\Theta}{\eta(T+1)} + \frac{9\eta L^2}{2}.$$

Our choices  $\eta = \frac{\epsilon}{9L^2}$  and  $T \geq \frac{6\Theta}{\eta\epsilon}$  imply that the right hand side is at most  $\epsilon$ , as required.  $\square$

## B.2 Proof of Proposition 3

**Proposition 3.** *Let  $\mathcal{O}$  be an  $(\alpha, \varepsilon_{\text{inner}})$ -relaxed proximal oracle with respect to gradient mapping  $g$ , distance-generating function  $r$  with range at most  $\Theta$  and some  $\varepsilon_{\text{inner}} \leq \varepsilon_{\text{outer}}$ . Let  $z_{1/2}, z_{3/2}, \dots, z_{K-1/2}$  be iterates of Algorithm 2 and let  $\bar{z}_K$  be its output. Then*

$$\mathbb{E} \text{Gap}(\bar{z}_K) \leq \mathbb{E} \max_{u \in \mathcal{Z}} \frac{1}{K} \sum_{k=1}^K \langle g(z_{k-1/2}), z_{k-1/2} - u \rangle \leq \frac{\alpha\Theta}{K} + \varepsilon_{\text{outer}}.$$

*Proof.* For some iteration  $k$ , we have by the optimality conditions on  $z_k^*$  that

$$\langle g(z_{k-1/2}), z_k^* - u \rangle \leq \alpha \left( V_{z_{k-1}}(u) - V_{z_k^*}(u) - V_{z_{k-1}}(z_k^*) \right) \quad \forall u \in \mathcal{Z}.$$

Summing over  $k$ , writing  $\langle g(z_{k-1/2}), z_k^* - u \rangle = \langle g(z_{k-1/2}), z_{k-1/2} - u \rangle - \langle g(z_{k-1/2}), z_{k-1/2} - z_k^* \rangle$ , and rearranging yields

$$\begin{aligned} \sum_{k=1}^K \langle g(z_{k-1/2}), z_{k-1/2} - u \rangle &\leq \alpha V_{z_0}(u) + \sum_{k=1}^K \alpha \left( V_{z_k}(u) - V_{z_k^*}(u) \right) \\ &\quad + \sum_{k=1}^K \left( \langle g(z_{k-1/2}), z_{k-1/2} - z_k^* \rangle - \alpha V_{z_{k-1}}(z_k^*) \right), \end{aligned} \quad (70)$$

for all  $u \in \mathcal{Z}$ . Since  $z_0$  minimizes  $r$ , the first term is bounded by  $V_{z_0}(u) \leq r(u) - r(z_0) \leq \Theta$ . The second term is bounded by the definition of  $z_k$  in Algorithm 2:

$$\sum_{k=1}^K \alpha \left( V_{z_k}(u) - V_{z_k^*}(u) \right) \leq K(\varepsilon_{\text{outer}} - \varepsilon_{\text{inner}}).$$

Thus, maximizing (70) over  $u$  and then taking an expectation yields

$$\begin{aligned} \mathbb{E} \max_{u \in \mathcal{Z}} \sum_{k=1}^K \langle g(z_{k-1/2}), z_{k-1/2} - u \rangle &\leq \alpha \Theta + K(\varepsilon_{\text{outer}} - \varepsilon_{\text{inner}}) \\ &+ \sum_{k=1}^K \mathbb{E} [\langle g(z_{k-1/2}), z_{k-1/2} - z_k^* \rangle - \alpha V_{z_{k-1}}(z_k^*)]. \end{aligned}$$

Finally, by Definition 5,  $\mathbb{E} [\langle g(z_{k-1/2}), z_{k-1/2} - z_k^* \rangle - \alpha V_{z_{k-1}}(z_k^*)] \leq \varepsilon_{\text{inner}}$  for every  $k$ , and the result follows by dividing by  $K$ .  $\square$

### B.3 Proof of Proposition 4

We provide a convergence result for the variance-reduced stochastic mirror descent scheme in Algorithm 3. We first state the following helper bound which is an application of Lemma 15. It is immediate from the variance bound of local-centered estimators (Property 2 of Definition 4) and the fact that all local norms (whether the domains are balls or simplices) are quadratic.

**Lemma 14.** *For any  $w \in \mathcal{Z}$ ,  $(L, \epsilon)$ -centered-local estimator  $\tilde{g}_{w_0}$  satisfies*

$$\mathbb{E} \|\tilde{g}_{w_0}(z) - g(z)\|_w^2 \leq L^2 V_{w_0}(z).$$

**Lemma 15.** *Let  $\|\cdot\|_D$  be a quadratic norm in a diagonal matrix, e.g. for some  $D = \text{diag}(d)$  and  $d \geq 0$  entrywise, let  $\|x\|_D^2 = \sum d_i x_i^2$ . Then, if  $X$  is a random vector, we have*

$$\mathbb{E} \|X - \mathbb{E}[X]\|_D^2 \leq \mathbb{E} \|X\|_D^2.$$

*Proof.* This follows from the definition of variance:

$$\mathbb{E} \|X - \mathbb{E}[X]\|_D^2 = \mathbb{E} \|X\|_D^2 - \|\mathbb{E}[X]\|_D^2 \leq \mathbb{E} \|X\|_D^2.$$

$\square$

**Proposition 4.** *Let  $(\mathcal{Z}, \|\cdot\|, r, \Theta, \text{clip})$  be any local norm setup. Let  $w_0 \in \mathcal{Z}$ ,  $\alpha \geq \varepsilon_{\text{inner}} > 0$ , and  $\tilde{g}_{w_0}$  be an  $L$ -centered-local estimator for some  $L \geq \alpha$ . Assume the domain is bounded by  $\max_{z \in \mathcal{Z}} \|z\| \leq D$ , that  $g$  is  $L$ -Lipschitz, i.e.  $\|g(z) - g(z')\|_* \leq L \|z - z'\|$ , that  $g$  is  $LD$ -bounded, i.e.  $\max_{z \in \mathcal{Z}} \|g(z)\|_* \leq LD$ , and that  $\hat{w}_0 = w_0$ . Then, for  $\eta = \frac{\alpha}{10L^2}$ ,  $T \geq \frac{6}{\eta\alpha} \geq \frac{60L^2}{\alpha^2}$ , and  $\varphi = \frac{\varepsilon_{\text{inner}}}{6}$ , Algorithm 3 outputs a point  $\hat{w} \in \mathcal{Z}$  such that*

$$\mathbb{E} \max_{u \in \mathcal{Z}} [\langle g(\tilde{w}), \tilde{w} - u \rangle - \alpha V_{w_0}(u)] \leq \varepsilon_{\text{inner}}, \quad (24)$$

i.e. Algorithm 3 is an  $(\alpha, \varepsilon_{\text{inner}})$ -relaxed proximal oracle.

*Proof.* For any  $u \in \mathcal{Z}$ , and defining  $\tilde{\Delta}_t := \tilde{g}(\hat{w}_t) - g(w_0)$  and  $\Delta_t := g(\hat{w}_t) - g(w_0)$ , we have

$$\begin{aligned} \sum_{t \in [T]} \langle \eta g(w_t), w_t - u \rangle &= \sum_{t \in [T]} \langle \text{clip}(\eta \tilde{\Delta}_t) + \eta g(w_0), w_t - u \rangle + \sum_{t \in [T]} \langle \eta \Delta_t - \text{clip}(\eta \tilde{\Delta}_t), w_t - u \rangle \\ &+ \sum_{t \in [T]} \langle \eta g(w_t) - \eta g(\hat{w}_t), w_t - u \rangle. \end{aligned} \quad (71)$$

We proceed to bound the three terms on the right hand side of (71) in turn. For the first term, recall the guarantees for the “ideal” iterates of Algorithm 3,

$$w_t^* = \arg \min_{w \in \mathcal{Z}} \left\{ \left\langle \text{clip}(\eta \tilde{\Delta}_t) + \eta g(w_0), w \right\rangle + \frac{\alpha\eta}{2} V_{w_0}(w) + V_{w_{t-1}}(w) \right\}.$$

By using the optimality conditions of these iterates, defining  $Q(z) := \langle \eta g(w_0), z \rangle + \frac{\alpha\eta}{2} V_{w_0}(z)$ ,  $\gamma_t := \text{clip}(\eta \tilde{\Delta}_t)$ , and defining for notational convenience  $w_{T+1}^* := u$ ,

$$\begin{aligned} \sum_{t \in [T]} \langle \gamma_{t-1} + \nabla Q(w_t^*), w_t^* - u \rangle &\leq \sum_{t \in [T]} \langle -\nabla V_{w_{t-1}}(w_t^*), w_t^* - u \rangle \\ &= \sum_{t \in [T]} (V_{w_{t-1}}(u) - V_{w_t^*}(u) - V_{w_{t-1}}(w_t^*)) \\ &= V_{w_0}(u) + \sum_{t \in [T]} (V_{w_t}(u) - V_{w_t^*}(u)) - \sum_{t=0}^T V_{w_t}(w_{t+1}^*). \end{aligned} \quad (72)$$

We thus have the chain of inequalities, recalling  $\gamma_0 = 0$ ,

$$\begin{aligned} &\sum_{t \in [T]} \left\langle \text{clip}(\eta \tilde{\Delta}_t) + \eta g(w_0), w_t - u \right\rangle + \frac{\alpha\eta}{2} \sum_{t \in [T]} \langle \nabla V_{w_0}(w_t^*), w_t^* - u \rangle \\ &= \sum_{t=0}^T \langle \gamma_t, w_t - u \rangle + \sum_{t \in [T]} \langle \nabla Q(w_t^*), w_t^* - u \rangle + \sum_{t \in [T]} \langle \eta g(w_0), w_t - w_t^* \rangle \\ &\stackrel{(i)}{\leq} V_{w_0}(u) + \sum_{t \in [T]} (V_{w_t}(u) - V_{w_t^*}(u)) + \sum_{t=0}^T (\langle \gamma_t, w_t - w_{t+1}^* \rangle - V_{w_t}(w_{t+1}^*)) + \sum_{t \in [T]} \langle \eta g(w_0), w_t - w_t^* \rangle \\ &\stackrel{(ii)}{\leq} V_{w_0}(u) + 2\eta\varphi T + \sum_{t=0}^T \left( \langle \text{clip}(\eta \tilde{\Delta}_t), w_t - w_{t+1}^* \rangle - V_{w_t}(w_{t+1}^*) \right) \stackrel{(iii)}{\leq} V_{w_0}(u) + 2\eta\varphi T + \sum_{t=0}^T \eta^2 \left\| \tilde{\Delta}_t \right\|_{w_t}^2. \end{aligned} \quad (73)$$

Here, (i) was by rearranging (72) via the equality

$$\sum_{t \in [T]} \langle \gamma_{t-1}, w_t^* - u \rangle = \sum_{t=0}^T \langle \gamma_t, w_t - u \rangle - \sum_{t=0}^T \langle \gamma_t, w_t - w_{t+1}^* \rangle,$$

(ii) was by the conditions  $\max_u [V_{w_t}(u) - V_{w_t^*}(u)] \leq \eta\varphi$  and  $\|w_t - w_t^*\| \leq \frac{\varphi}{LD}$  satisfied by the iterates, and (iii) was by the property of clipping (15), as defined in the problem setup. Now by rearranging and using the three-point property of Bregman divergence (i.e.  $\langle -\nabla V_{w'}(w), w - u \rangle = V_{w'}(u) - V_w(u) - V_{w'}(w)$ ), it holds that

$$\begin{aligned} \sum_{t \in [T]} \left\langle \text{clip}(\eta \tilde{\Delta}_t) + \eta g(w_0), w_t - u \right\rangle &\leq V_{w_0}(u) + 2\eta\varphi T + \eta^2 \sum_{t=0}^T \left\| \tilde{\Delta}_t \right\|_{w_t}^2 + \frac{\alpha\eta}{2} \sum_{t \in [T]} (V_{w_0}(u) - V_{w_0}(w_t^*)) \\ &\leq V_{w_0}(u) + 3\eta\varphi T + \eta^2 \sum_{t=0}^T \left\| \tilde{\Delta}_t \right\|_{w_t}^2 + \frac{\alpha\eta}{2} \sum_{t \in [T]} (V_{w_0}(u) - V_{w_0}(\hat{w}_t)), \end{aligned} \quad (74)$$



where the second inequality follows from the condition  $V_{w_0}(\hat{w}_t) - V_{w_0}(w_t^*) \leq \frac{2\varphi}{\alpha}$  satisfied by iterates of Algorithm 3. To bound the second term of (71), we define the ghost iterate sequence  $\{s_t\}$  by

$$s_t = \arg \min_{s \in \mathcal{Z}} \left\{ \frac{1}{2} \langle \eta \Delta_{t-1} - \text{clip}(\eta \tilde{\Delta}_{t-1}), s \rangle + V_{s_{t-1}}(s) \right\} \quad \text{with } s_0 = w_0.$$

Applying Lemma 13 with  $Q = 0$  and  $\gamma_t = \frac{1}{2}(\eta \Delta_t - \text{clip}(\eta \tilde{\Delta}_t))$ , and observing that again  $\gamma_0 = 0$ ,

$$\begin{aligned} & \sum_{t \in [T]} \langle \eta \Delta_t - \text{clip}(\eta \tilde{\Delta}_t), s_t - u \rangle \\ & \leq 2V_{w_0}(u) + \sum_{t=0}^T \left\{ \langle \eta \Delta_t - \text{clip}(\eta \tilde{\Delta}_t), s_t - s_{t+1} \rangle - 2V_{s_t}(s_{t+1}) \right\} \\ & \leq 2V_{w_0}(u) + \eta^2 \sum_{t=0}^T \left( \|\Delta_t\|_*^2 + \|\tilde{\Delta}_t\|_{s_t}^2 \right). \end{aligned}$$

Here, we used properties (15) and (16). Consequently,

$$\begin{aligned} & \sum_{t \in [T]} \langle \eta \Delta_t - \text{clip}(\eta \tilde{\Delta}_t), w_t - u \rangle \\ & = \sum_{t \in [T]} \langle \eta \Delta_t - \text{clip}(\eta \tilde{\Delta}_t), w_t - s_t \rangle + \sum_{t \in [T]} \langle \eta \Delta_t - \text{clip}(\eta \tilde{\Delta}_t), s_t - u \rangle \\ & \leq 2V_{w_0}(u) + \eta^2 \sum_{t=0}^T \left( \|\Delta_t\|_*^2 + \|\tilde{\Delta}_t\|_{s_t}^2 \right) + \sum_{t \in [T]} \langle \eta \Delta_t - \text{clip}(\eta \tilde{\Delta}_t), w_t - s_t \rangle. \end{aligned} \tag{75}$$

To bound the third term of (71), we use the condition  $\|w_t - \hat{w}_t\| \leq \frac{\varphi}{LD}$  which implies

$$\sum_{t \in [T]} \langle \eta g(w_t) - \eta g(\hat{w}_t), w_t - u \rangle \leq \sum_{t \in [T]} \|\eta g(w_t) - \eta g(\hat{w}_t)\|_* \|w_t - u\| \leq 2\eta\varphi T. \tag{76}$$

Combining our three bounds (74), (75), and (76) in the context of (71), using  $\hat{w}_0 = w_0$  and  $\tilde{g}(w_0) = g(w_0)$ , and finally dividing through by  $\eta T$ , we obtain

$$\begin{aligned} & \frac{1}{T} \sum_{t \in [T]} \langle g(w_t), w_t - u \rangle - \left( \frac{3}{\eta T} + \frac{\alpha}{2} \right) V_{w_0}(u) \\ & \leq 5\varphi + \frac{1}{T} \sum_{t \in [T]} \left( \eta \|\tilde{\Delta}_t\|_{w_t}^2 + \eta \|\tilde{\Delta}_t\|_{s_t}^2 + \eta \|\Delta_t\|_*^2 + \left\langle \Delta_t - \frac{1}{\eta} \text{clip}(\eta \tilde{\Delta}_t), w_t - s_t \right\rangle - \frac{\alpha}{2} V_{w_0}(\hat{w}_t) \right). \end{aligned} \tag{77}$$

Since  $T \geq \frac{6}{\alpha\eta}$ , taking a supremum over  $u \in \mathcal{Z}$  in (77) and then an expectation yields

$$\begin{aligned} & \mathbb{E} \sup_{u \in \mathcal{Z}} \left[ \frac{1}{T} \sum_{t \in [T]} \langle g(w_t), w_t - u \rangle - \alpha V_{w_0}(u) \right] \leq 5\varphi \\ & + \frac{1}{T} \mathbb{E} \left[ \sum_{t \in [T]} \eta \|\tilde{\Delta}_t\|_{w_t}^2 + \eta \|\tilde{\Delta}_t\|_{s_t}^2 + \eta \|\Delta_t\|_*^2 + \left\langle \Delta_t - \frac{1}{\eta} \text{clip}(\eta \tilde{\Delta}_t), w_t - s_t \right\rangle - \frac{\alpha}{2} V_{w_0}(\hat{w}_t) \right]. \end{aligned} \tag{78}$$

We will show the second line of (78) is nonpositive. To do so, observe for each  $t \in [T]$ , by the property (17) of  $\text{clip}(\cdot)$ , since conditional on  $w_t, s_t, \tilde{\Delta}_t$  is unbiased for deterministic  $\Delta_t$ ,

$$\left| \mathbb{E} \left\langle \Delta_t - \frac{1}{\eta} \text{clip}(\eta \tilde{\Delta}_t), w_t - s_t \right\rangle \right| = \left| \mathbb{E} \left\langle \tilde{\Delta}_t - \frac{1}{\eta} \text{clip}(\eta \tilde{\Delta}_t), w_t - s_t \right\rangle \right| \leq \eta \left\| \tilde{\Delta}_t \right\|_{w_t}^2 + \eta \left\| \tilde{\Delta}_t \right\|_{s_t}^2. \quad (79)$$

Finally, by using property 2 of the centered-local estimator  $\tilde{\Delta}_t$ , as well as Remark 1, we have for each  $t \in [T]$ ,

$$\mathbb{E} \left[ \eta \left\| \tilde{\Delta}_t \right\|_{w_t}^2 \right] \leq \eta L^2 V_{w_0}(\hat{w}_t), \quad \mathbb{E} \left[ \eta \left\| \tilde{\Delta}_t \right\|_{s_t}^2 \right] \leq \eta L^2 V_{w_0}(\hat{w}_t), \quad \text{and} \quad \eta \left\| \Delta_t \right\|_*^2 \leq \eta L^2 V_{w_0}(\hat{w}_t). \quad (80)$$

Using bounds (79) and (80) in (78), as well as  $\eta \leq \frac{\alpha}{10L^2}$ ,

$$\mathbb{E} \sup_{u \in \mathcal{Z}} \left[ \frac{1}{T} \sum_{t \in [T]} \langle g(w_t), w_t - u \rangle - \alpha V_{w_0}(u) \right] \leq 5\varphi. \quad (81)$$

For the final claim, denote the true average iterate by  $\bar{w} := \frac{1}{T} \sum_{t \in [T]} w_t$ . We have  $\forall u \in \mathcal{Z}$ ,

$$\begin{aligned} \langle g(\tilde{w}), \tilde{w} - u \rangle &\stackrel{(i)}{=} -\langle g(\tilde{w}), u \rangle = \langle g(\bar{w}) - g(\tilde{w}), u \rangle + \langle g(\bar{w}), \bar{w} - u \rangle \\ &\stackrel{(ii)}{\leq} \varphi + \langle g(\bar{w}), \bar{w} - u \rangle \\ &= \frac{1}{T} \sum_{t \in [T]} \langle g(w_t), w_t - u \rangle + \varphi. \end{aligned}$$

Here, (i) used the fact that linearity of  $g$  gives  $\langle g(z), z \rangle = 0, \forall z \in \mathcal{Z}$ , and (ii) used Hölder's inequality  $\langle g(\bar{w}) - g(\tilde{w}), u \rangle \leq \|g(\bar{w}) - g(\tilde{w})\|_* \|u\| \leq 2LD \|\tilde{w} - \bar{w}\| \leq \varphi$  following from the approximation guarantee  $\|\tilde{w} - \bar{w}\| \leq \frac{\varphi}{2LD}$ . Combining with (81) yields the conclusion, as  $6\varphi = \varepsilon_{\text{inner}}$ .  $\square$

## C Deferred proofs for sublinear methods

### C.1 $\ell_2$ - $\ell_2$ sublinear coordinate method

**Assumptions.** The algorithm in this section will assume access to entry queries,  $\ell_1$  norms of rows and columns, and  $\ell_1$  sampling distributions for rows and columns. Further, it assumes the ability to sample a row or column proportional to its squared  $\ell_1$  norm; given access to all  $\ell_1$  norms, the algorithm may spend  $O(m+n)$  constructing these sampling oracles in  $O(m+n)$  time, which does not affect its asymptotic runtime. We use the  $\ell_2$ - $\ell_2$  local norm setup (Table 6). We define

$$L_{\text{co}}^{2,2} := \sqrt{\sum_{i \in [m]} \|A_{i:}\|_1^2 + \sum_{j \in [n]} \|A_{:j}\|_1^2}. \quad (82)$$

#### C.1.1 Gradient estimator

For  $z \in \mathbb{B}^n \times \mathbb{B}^m$ , we specify two distinct choices of sampling distributions  $p(z), q(z)$  which obtain the optimal Lipschitz constant. The first one is an oblivious distribution:

$$p_{ij}(z) := \frac{\|A_{i:}\|_1^2}{\sum_{k \in [m]} \|A_{k:}\|_1^2} \cdot \frac{|A_{ij}|}{\|A_{i:}\|_1} \quad \text{and} \quad q_{ij}(z) := \frac{\|A_{:j}\|_1^2}{\sum_{k \in [n]} \|A_{:k}\|_1^2} \cdot \frac{|A_{ij}|}{\|A_{:j}\|_1}. \quad (83)$$

The second one is a dynamic distribution:

$$p_{ij}(z) := \frac{[z^y]_i^2}{\|z^y\|_2^2} \cdot \frac{|A_{ij}|}{\|A_{i:}\|_1} \quad \text{and} \quad q_{ij}(z) := \frac{[z^x]_j^2}{\|z^x\|_2^2} \cdot \frac{|A_{ij}|}{\|A_{:j}\|_1}. \quad (84)$$

We now state the local properties of each estimator.

**Lemma 16.** *In the  $\ell_2$ - $\ell_2$  setup, estimator (23) using the sampling distribution in (83) or (84) is an  $L_{\text{co}}^{2,2}$ -local estimator.*

*Proof.* For convenience, we restate the distributions here: they are respectively

$$p_{ij}(z) := \frac{\|A_{i:}\|_1^2}{\sum_{k \in [m]} \|A_{k:}\|_1^2} \cdot \frac{|A_{ij}|}{\|A_{i:}\|_1} \quad \text{and} \quad q_{ij}(z) := \frac{\|A_{:j}\|_1^2}{\sum_{k \in [n]} \|A_{:k}\|_1^2} \cdot \frac{|A_{ij}|}{\|A_{:j}\|_1}$$

and

$$p_{ij}(z) := \frac{[z^y]_i^2}{\|z^y\|_2^2} \cdot \frac{|A_{ij}|}{\|A_{i:}\|_1} \quad \text{and} \quad q_{ij}(z) := \frac{[z^x]_j^2}{\|z^x\|_2^2} \cdot \frac{|A_{ij}|}{\|A_{:j}\|_1}.$$

Unbiasedness holds by definition. We first show the variance bound on the  $x$  block for distribution (83):

$$\begin{aligned} \mathbb{E} \left[ \|\tilde{g}^x(z)\|_2^2 \right] &= \sum_{i \in [m], j \in [n]} p_{ij}(z) \cdot \left( \frac{A_{ij}[z^y]_i}{p_{ij}(z)} \right)^2 = \sum_{i \in [m], j \in [n]} \frac{A_{ij}^2 [z^y]_i^2}{p_{ij}(z)} \\ &= \sum_{i \in [m], j \in [n]} \frac{|A_{ij}|}{\|A_{i:}\|_1} [z^y]_i^2 \cdot \left( \sum_{i \in [m]} \|A_{i:}\|_1^2 \right) = \sum_{i \in [m]} \|A_{i:}\|_1^2. \end{aligned}$$

Similarly, we have

$$\mathbb{E} \left[ \|\tilde{g}^y(z)\|_2^2 \right] \leq \sum_{j \in [n]} \|A_{:j}\|_1^2.$$

Now, we show the variance bound on the  $x$  block for distribution (84):

$$\begin{aligned} \mathbb{E} \left[ \|\tilde{g}^x(z)\|_2^2 \right] &= \sum_{i \in [m], j \in [n]} p_{ij}(z) \cdot \left( \frac{A_{ij}[z^y]_i}{p_{ij}(z)} \right)^2 = \sum_{i \in [m], j \in [n]} \frac{A_{ij}^2 [z^y]_i^2}{p_{ij}(z)} \\ &= \sum_{i \in [m], j \in [n]} |A_{ij}| \|A_{i:}\|_1 \|z^y\|_2^2 \leq \sum_{i \in [m]} \|A_{i:}\|_1^2, \end{aligned}$$

and a similar bound holds on the  $y$  block.  $\square$

We remark that using the oblivious distribution (83) saves a logarithmic factor in the runtime compared to the dynamic distribution, so for the implementation of all of our  $\ell_2$ - $\ell_2$  algorithms we will use the oblivious distribution.

### C.1.2 Implementation details

In this section, we discuss the details of how to leverage the `IterateMaintainer2` data structure to implement the iterations of our algorithm. The algorithm we analyze is Algorithm 1, using the local estimator defined in (23), and the distribution (83). We choose

$$\eta = \frac{\epsilon}{9 \left(L_{\text{co}}^{2,2}\right)^2} \text{ and } T = \left\lceil \frac{6\Theta}{\eta\epsilon} \right\rceil \geq \frac{54 \left(L_{\text{co}}^{2,2}\right)^2}{\epsilon^2}.$$

Lemma 16 implies that our estimator satisfies the remaining requirements for Proposition 2, giving the duality gap guarantee in  $T$  iterations. In order to give a runtime bound, we claim that each iteration can be implemented in constant time, with  $O(m+n)$  additional runtime.

**Data structure initializations and invariants.** At the start of the algorithm, we spend  $O(m+n)$  time initializing data structures via  $\text{IM}_2^x.\text{Init}(\mathbf{0}_n, b)$ ,  $\text{IM}_2^y.\text{Init}(\mathbf{0}_m, c)$ , where  $\text{IM}_2^x, \text{IM}_2^y$  are instantiations of `IterateMaintainer2` data structures. Throughout, we preserve the invariant that the points maintained by  $\text{IM}_2^x, \text{IM}_2^y$  correspond to the  $x$  and  $y$  blocks of the current iterate  $z_t$  at iteration  $t$  of the algorithm. We note that we instantiate data structures which do not support `Sample()`.

**Iterations.** For simplicity, we only discuss the runtime of updating the  $x$  block as the  $y$  block follows symmetrically. We divide each iteration into the following substeps, each of which we show run in constant time. We refer to the current iterate by  $z = (z^x, z^y)$ , and the next iterate by  $w = (w^x, w^y)$ .

*Sampling.* Because the distribution is oblivious, sampling both  $i$  and  $j \mid i$  using precomputed data structures takes constant time.

*Computing the gradient estimator.* To compute  $c := A_{ij}[z^y]_i/p_{ij}$ , it suffices to compute  $A_{ij}, [z^y]_i$ , and  $p_{ij}$ . Using an entry oracle for  $A$  obtains  $A_{ij}$  in constant time, and calling  $\text{IM}_2^y.\text{Get}(i)$  takes constant time. Computing  $p_{ij}$  using the precomputed row norms and the values of  $A_{ij}, [z^y]_i$  takes constant time.

*Performing the update.* For the update corresponding to a proximal step, we have

$$w^x \leftarrow \Pi_{\mathcal{X}}(z^x - \eta \tilde{g}^x(z)) = \frac{z^x - \eta \tilde{g}^x(z)}{\max\{\|z^x - \eta \tilde{g}^x(z)\|_2, 1\}}.$$

We have computed  $\tilde{g}^x(z)$ , so to perform this update, we call

```

IM2x.AddSparse( $j, -\eta c$ );
IM2x.AddDense( $-\eta$ );
IM2x.Scale( $\max\{\text{IM}_2^x.\text{GetNorm}(), 1\}^{-1}$ );
IM2x.UpdateSum().

```

By assumption, each operation takes constant time because we do not support `Sample` in our instances of  $\text{IM}_2$ , giving the desired iteration complexity. It is clear that at the end of performing these operations, the invariant that  $\text{IM}_2^x$  maintains the  $x$  block of the iterate is preserved.

**Averaging.** After  $T$  iterations, we compute the average point  $\bar{z}^x$ :

$$[\bar{z}^x]_j \leftarrow \frac{1}{T} \cdot \text{IM}_2^x.\text{GetSum}(j), \forall j \in [n].$$

By assumption, this takes  $O(n)$  time.

### C.1.3 Algorithm guarantee

**Theorem 6.** *In the  $\ell_2$ - $\ell_2$  setup, the implementation in Section C.1.2 has runtime*

$$O\left(\frac{\left(L_{\text{co}}^{2,2}\right)^2}{\epsilon^2} + m + n\right)$$

and outputs a point  $\bar{z} \in \mathcal{Z}$  such that

$$\mathbb{E} \text{Gap}(\bar{z}) \leq \epsilon.$$

*Proof.* The runtime bound follows from the discussion in Section C.1.2. The correctness follows from Proposition 2.  $\square$

**Remark 7.** Using our `IterateMaintainer2` data structure, the  $\ell_2$ - $\ell_2$  algorithm of Balamurugan and Bach [7] runs in time  $O(\text{rcs}\|A\|_F^2/\epsilon^2)$ . Our runtime universally improves upon it since

$$\sum_{i \in [m]} \|A_{i:}\|_1^2 + \sum_{j \in [n]} \|A_{:j}\|_1^2 \leq 2\text{rcs} \|A\|_F^2.$$

## C.2 $\ell_2$ - $\ell_1$ sublinear coordinate method

**Assumptions** The algorithm in this section will assume access to every oracle listed in Section 2.3. However, for a specific matrix  $A$ , only one of three sampling distributions will be used in the algorithm; we describe the specific oracle requirements of each distribution following their definition. We use the  $\ell_2$ - $\ell_1$  local norm setup (Table 6). Throughout this section, we will assume that the linear term in (23) is  $g(0) = 0$  uniformly.

Finally, in this section we assume access to a weighted variant of `IterateMaintainer2`, which takes a nonnegative weight vector  $w$  as a static parameter. `WeightedIterateMaintainer2` supports two modified operations compared to the data structure `IterateMaintainer2`: its `GetNorm()` operation returns  $\sqrt{\sum_j [w]_j [x]_j^2}$ , and its `Sample()` returns coordinate  $j$  with probability proportional to  $[w]_j [x]_j^2$  (cf. Section 2.4.1). We give the implementation of this extension in Appendix G.

### C.2.1 Gradient estimator

For  $z \in \mathbb{B}^n \times \Delta^m$  and desired accuracy  $\epsilon > 0$ , we specify three distinct choices of sampling distributions  $p(z), q(z)$ . Each of our distributions induces an estimator with different properties.

The first one is

$$p_{ij}(z) := \frac{|A_{ij}|}{\|A_{i:}\|_1} \cdot [z^y]_i \quad \text{and} \quad q_{ij}(z) := \frac{A_{ij}^2}{\|A\|_F^2}. \quad (85)$$

The second one is

$$p_{ij}(z) := \frac{|A_{ij}|}{\|A_{i:}\|_1} \cdot [z^y]_i \quad \text{and} \quad q_{ij}(z) := \frac{[z^x]_j^2 \cdot \mathbf{1}_{\{A_{ij} \neq 0\}}}{\sum_{l \in [n]} \text{cs}_l \cdot [z^x]_l^2}. \quad (86)$$

Here, we let  $\text{cs}_j \leq \text{rcs}$  denote the number of nonzero elements in column  $A_{:j}$ . The third one is

$$p_{ij}(z) := \frac{|A_{ij}|}{\|A_{i:}\|_1} \cdot [z^y]_i \quad \text{and} \quad q_{ij}(z) := \frac{|A_{ij}| \cdot [z^x]_j^2}{\sum_{l \in [n]} \|A_{:l}\|_1 \cdot [z^x]_l^2}. \quad (87)$$

For  $L_{\text{co}}^{2,1,(1)}$ ,  $L_{\text{co}}^{2,1,(2)}$ , and  $L_{\text{co}}^{2,1,(3)}$  to be defined, the estimators induced by these distributions are local estimators whose guarantees depend on these constants respectively. Furthermore, these Lipschitz constants are in general incomparable and depend on specific properties of the matrix. Therefore, we may choose our definition of  $L_{\text{co}}^{2,1}$  to be the minimum of these constants, by choosing an appropriate estimator. We now state the local properties of each estimator.

**Lemma 17.** *In the  $\ell_2$ - $\ell_1$  setup, estimator (23) using the sampling distributions in (85), (86), or (87) is respectively a  $L_{\text{co}}^{2,1,(k)}$ -local estimator, for  $k \in \{1, 2, 3\}$ , and*

$$\begin{aligned} L_{\text{co}}^{2,1,(1)} &:= \sqrt{\max_{i \in [m]} \|A_{i:}\|_1^2 + \|A\|_{\text{F}}^2}, \\ L_{\text{co}}^{2,1,(2)} &:= \sqrt{2\text{rcs} \max_{i \in [m]} \|A_{i:}\|_2^2}, \\ L_{\text{co}}^{2,1,(3)} &:= \sqrt{\max_{i \in [m]} \|A_{i:}\|_1^2 + \left(\max_{i \in [m]} \|A_{i:}\|_1\right) \left(\max_{j \in [n]} \|A_{:j}\|_1\right)}. \end{aligned}$$

*Proof.* First, we give the proof for the sampling distribution (85). Unbiasedness holds by definition. For the  $x$  block, we have the variance bound:

$$\begin{aligned} \mathbb{E} \left[ \|\tilde{g}^x(z)\|_2^2 \right] &= \sum_{i \in [m], j \in [n]} p_{ij}(z) \cdot \left( \frac{A_{ij}[z^y]_i}{p_{ij}(z)} \right)^2 = \sum_{i \in [m], j \in [n]} |A_{ij}| \|A_{i:}\|_1 [z^y]_i \\ &= \sum_{i \in [m]} \|A_{i:}\|_1^2 [z^y]_i \leq \max_{i \in [m]} \|A_{i:}\|_1^2. \end{aligned}$$

For arbitrary  $w^y$ , we have the variance bound on the  $y$  block:

$$\begin{aligned} \mathbb{E} \left[ \|\tilde{g}^y(z)\|_{w^y}^2 \right] &= \sum_{i \in [m], j \in [n]} q_{ij}(z) \cdot \left( [w^y]_i \cdot \left( \frac{A_{ij}[z^x]_j}{q_{ij}(z)} \right)^2 \right) = \sum_{i \in [m], j \in [n]} [w^y]_i \frac{A_{ij}^2 [z^x]_j^2}{q_{ij}(z)} \\ &= \sum_{i \in [m], j \in [n]} [w^y]_i [z^x]_j^2 \|A\|_{\text{F}}^2 \leq \|A\|_{\text{F}}^2. \end{aligned}$$

Next, we give the proof for the sampling distribution (86). Unbiasedness holds by definition. By Cauchy-Schwarz and our earlier proof, we have the variance bound for the  $x$  block:

$$\mathbb{E} \left[ \|\tilde{g}^x(z)\|_2^2 \right] \leq \max_{i \in [m]} \|A_{i:}\|_1^2 \leq \text{rcs} \max_{i \in [m]} \|A_{i:}\|_2^2.$$

For arbitrary  $w^y$ , we have the variance bound on the  $y$  block, where  $S_i := \{j \mid \mathbf{1}_{A_{ij} \neq 0} = 1\}$ :

$$\begin{aligned} \mathbb{E} \left[ \|\tilde{g}^y(z)\|_{w^y}^2 \right] &= \sum_{i \in [m], j \in S_i} q_{ij}(z) \cdot \left( [w^y]_i \cdot \left( \frac{A_{ij}[z^x]_j}{q_{ij}(z)} \right)^2 \right) = \sum_{i \in [m], j \in S_i} [w^y]_i \frac{A_{ij}^2 [z^x]_j^2}{q_{ij}(z)} \\ &\leq \sum_{i \in [m], j \in S_i} [w^y]_i A_{ij}^2 \text{rcs} \leq \text{rcs} \max_{k \in [m]} \|A_{k:}\|_2^2. \end{aligned}$$

Finally, we give the proof for the sampling distribution (87). Unbiasedness and the variance bound for the  $x$  block again hold. For arbitrary  $w^y$ , we have the variance bound on the  $y$  block:

$$\begin{aligned}\mathbb{E} \left[ \|\tilde{g}^y(z)\|_{w^y}^2 \right] &= \sum_{i \in [m], j \in [n]} q_{ij}(z) \cdot \left( [w^y]_i \cdot \left( \frac{A_{ij}[z^x]_j}{q_{ij}(z)} \right)^2 \right) = \sum_{i \in [m], j \in [n]} [w^y]_i \frac{A_{ij}^2 [z^x]_j^2}{q_{ij}(z)} \\ &\leq \left( \sum_{i \in [m], j \in [n]} [w^y]_i |A_{ij}| \right) \left( \sum_{l \in [n]} \|A_{:l}\|_1 [z^x]_l^2 \right) \\ &\leq \left( \max_{k \in [m]} \|A_{k:}\|_1 \right) \left( \max_{l \in [n]} \|A_{:l}\|_1 \right).\end{aligned}$$

□

By using the definitions of  $L_{\text{co}}^{2,1,(1)}$ ,  $L_{\text{co}}^{2,1,(2)}$ , and  $L_{\text{co}}^{2,1,(3)}$ , we define the constant

$$L_{\text{co}}^{2,1} := \sqrt{\max_{i \in [m]} \|A_{i:}\|_1^2 + \min \left( \|A\|_F^2, \text{rcs} \max_{i \in [m]} \|A_{i:}\|_2^2, \left( \max_{i \in [m]} \|A_{i:}\|_1 \right) \left( \max_{j \in [n]} \|A_{:j}\|_1 \right) \right)}. \quad (88)$$

In particular, by choosing whichever of the distributions (85), (86), or (87) yields the minimal Lipschitz constant, we may always ensure we have a  $L_{\text{co}}^{2,1}$ -local estimator. We now discuss the specific precomputed quantities each estimator requires, among those listed in Section 2.3. All distributions require access to entry queries,  $\ell_1$  norms of rows, and  $\ell_1$  sampling distributions for rows.

- Using the sampling distribution (85) requires additional access to  $\ell_2$  sampling distributions for rows and columns and the Frobenius norm of  $A$ .
- Using the sampling distribution (86) requires additional access to uniform sampling nonzero entries of columns.
- Using the sampling distribution (87) requires additional access to  $\ell_1$  norms of columns and  $\ell_1$  sampling distributions for columns.

### C.2.2 Implementation details

In this section, we discuss the details of how to leverage the appropriate `IterateMaintainer1` and `IterateMaintainer2` data structures to implement the iterations of our algorithm. The algorithm we analyze is Algorithm 1, using the local estimator defined in (23), and the best choice of distribution among (85), (86), (87). We choose

$$\eta = \frac{\epsilon}{9 \left( L_{\text{co}}^{2,1} \right)^2} \text{ and } T = \left\lceil \frac{6\Theta}{\eta\epsilon} \right\rceil \geq \frac{54 \left( L_{\text{co}}^{2,1} \right)^2 \log(2m)}{\epsilon^2}.$$

Lemma 17 implies that our estimator satisfies the remaining requirements for Proposition 2, giving the duality gap guarantee in  $T$  iterations. In order to give a runtime bound, we claim that each iteration can be implemented in  $O(\log mn)$  time, with  $O(m+n)$  additional runtime. For simplicity, because most of the algorithm implementation details are exactly same as the discussion of Section 4.1.2 for the simplex block  $y \in \mathcal{Y}$ , and exactly the same as the discussion of Section C.1.2 for

the ball block  $x \in \mathcal{X}$ , we discuss the differences here, namely the implementations of sampling and gradient computation.

We assume that we have initialized  $\text{IM}_1^Y$ , an instantiation of `IterateMaintainer`<sub>1</sub>, and  $\text{IM}_2^X$ , an instantiation of `IterateMaintainer`<sub>2</sub>. When the choice of distribution is (86), we also assume access to  $\text{WIM}_2^X$ , an instantiation of `WeightedIterateMaintainer`<sub>2</sub> initialized with the weight vector of nonzero counts of columns of the matrix; similarly, for distribution (87) we instantiate a `WeightedIterateMaintainer`<sub>2</sub> with the weight vector of  $\ell_1$  norms of each column.

*Sampling.* Recall that

$$p_{ij}(z) := \frac{|A_{ij}|}{\|A_{i:}\|_1} \cdot [z^Y]_i.$$

We first sample coordinate  $i$  via  $\text{IM}_1^Y.\text{Sample}()$  in  $O(\log m)$ , and then sample  $j$  using the data structure corresponding to  $A_{i:}$  in  $O(1)$ . Next, to sample from the distribution

$$q_{ij}(z) := \frac{A_{ij}^2}{\|A\|_F^2}$$

required by (85), we can sample a coordinate of the matrix proportional to its square in constant time using our matrix access. To sample from the distribution

$$q_{ij}(z) := \frac{[z^X]_j^2 \cdot \mathbf{1}_{\{A_{ij} \neq 0\}}}{\sum_{l \in [n]} \text{cs}_l \cdot [z^X]_l^2}$$

required by (86), we first sample coordinate  $j$  via  $\text{WIM}_2^X.\text{Sample}()$  in  $O(\log n)$ , and then uniformly sample a coordinate  $i$  amongst the entries of  $A_{:j}$  for which the indicator labels as nonzero. Finally, to sample from the distribution

$$q_{ij}(z) := \frac{|A_{ij}| \cdot [z^X]_j^2}{\sum_{l \in [n]} \|A_{:l}\|_1 \cdot [z^X]_l^2}$$

required by (87), we sample coordinate  $j$  via  $\text{WIM}_2^X.\text{Sample}()$ , and then sample a coordinate  $i$  proportional to its absolute value using a column sampling oracle.

*Computing the gradient estimator.* By the proofs of Theorem 1 and Theorem 6, it suffices to compute  $p_{i^X j^X}, q_{i^Y j^Y}$  in constant time. Calling  $\text{IM}_2^X.\text{Get}(j)$ ,  $\text{IM}_1^Y.\text{Get}(i)$ ,  $\text{IM}_2^X.\text{GetNorm}()$ , and  $\text{WIM}_2^X.\text{GetNorm}()$  when appropriate, and using access to precomputation allows us to obtain all relevant quantities for the computations in  $O(1)$ .

### C.2.3 Algorithm guarantee

**Theorem 7.** *In the  $\ell_2$ - $\ell_1$  setup, the implementation in Section C.2.2 has runtime*

$$O\left(\frac{\left(L_{\text{co}}^{2,1}\right)^2 \log m \log(mn)}{\epsilon^2} + m + n\right)$$

and outputs a point  $\bar{z} \in \mathcal{Z}$  such that

$$\mathbb{E} \text{Gap}(\bar{z}) \leq \epsilon.$$



*Proof.* The runtime bound follows from the discussion in Section C.2.2. The correctness follows from Proposition 2.  $\square$

**Remark 8.** Using our `IterateMaintainer1` and `IterateMaintainer2` data structures, the  $\ell_2$ - $\ell_1$  algorithm of Clarkson et al. [10] runs in time  $O(\text{rcs} \max_{i \in [m]} \|A_i\|_2^2 \log^2(mn)/\epsilon^2)$ . By noting the definition of  $L_{\text{co}}^{2,1,(2)}$ , our runtime universally improves upon it since  $\left(L_{\text{co}}^{2,1}\right)^2 \leq 2\text{rcs} \max_{i \in [m]} \|A_i\|_2^2$ .

## D Deferred proofs for variance-reduced methods

### D.1 Helper proofs

**Lemma 3.** For  $y, y' \in \Delta^m$ , divergence  $V_y(y')$  generated by  $r(y) = \sum_{i \in [m]} [y]_i \log[y]_i - [y]_i$  satisfies

$$V_y(y') \geq \frac{1}{2} \|y' - y\|_{\frac{3}{2y+y'}}^2 = \frac{1}{2} \sum_{i \in [m]} \frac{([y]_i - [y']_i)^2}{\frac{2}{3}[y]_i + \frac{1}{3}[y']_i}.$$

*Proof.* Let  $\gamma \in \mathbb{R}^m$ . Note that for every  $\tau \in [0, 1]$  (with elementwise multiplication, division and square root),  $\langle \gamma, y - y' \rangle = \left\langle \gamma \sqrt{(1-\tau)y + \tau y'}, \frac{y - y'}{\sqrt{(1-\tau)y + \tau y'}} \right\rangle$ . Therefore, using  $2\langle u, w \rangle \leq \|u\|_2^2 + \|w\|_2^2$ , we have for every  $\tau \in [0, 1]$ ,

$$2\langle \gamma, y - y' \rangle \leq \sum_{i \in [m]} ((1-\tau)[y]_i + \tau[y']_i) [\gamma]_i^2 + \sum_{i \in [m]} \frac{([y]_i - [y']_i)^2}{(1-\tau)[y]_i + \tau[y']_i}.$$

Applying the double integral  $\int_0^1 dt \int_0^t d\tau$  to both sides of the inequality, and using  $\int_0^1 dt \int_0^t 1 \cdot d\tau = \frac{1}{2}$  and  $\int_0^1 dt \int_0^t \tau \cdot d\tau = \frac{1}{6}$  gives

$$\langle \gamma, y - y' \rangle \leq \sum_{i \in [m]} \left( \frac{1}{3}[y]_i + \frac{1}{6}[y']_i \right) [\gamma]_i^2 + \int_0^1 dt \int_0^t \sum_{i \in [m]} \frac{([y]_i - [y']_i)^2}{(1-\tau)[y]_i + \tau[y']_i} d\tau.$$

Identifying the double integral with the expression

$$V_y(y') = \sum_{i \in [m]} \left( y'_i \log \frac{y'_i}{y_i} + y_i - y'_i \right) = \int_0^1 dt \int_0^t \sum_{i \in [m]} \frac{(y_i - y'_i)^2}{(1-\tau)y_i + \tau y'_i} d\tau. \quad (89)$$

for the divergence induced by entropy, the result follows by choosing  $[\gamma]_i = \frac{[y]_i - [y']_i}{\frac{2}{3}[y]_i + \frac{1}{3}[y']_i}$ .  $\square$

**Lemma 5.** Let  $x' \in \Delta^n$  be a  $\beta$ -padding of  $x \in \Delta^n$ . Then,

$$\sum_{j \in [n]} x'_j \log x'_j - \sum_{j \in [n]} x_j \log x_j \leq \frac{\beta n}{e} + \beta(1 + \beta).$$

*Proof.* Letting  $\tilde{x}$  be the point inducing  $x'$  in Definition 2, we have

$$\begin{aligned} \sum_{j \in [n]} x'_j \log x'_j - \sum_{j \in [n]} x_j \log x_j &= \left( \sum_{j \in [n]} x'_j \log x'_j - \sum_{j \in [n]} \tilde{x}_j \log \tilde{x}_j \right) \\ &\quad + \left( \sum_{j \in [n]} \tilde{x}_j \log \tilde{x}_j - \sum_{j \in [n]} x_j \log x_j \right). \end{aligned}$$

We bound these two terms separately. For the first term, let  $\|\tilde{x}\|_1 = 1 + b$ , for some  $b \leq \beta$ ; we see that entrywise,  $(1 + b)x'_j = \tilde{x}_j$ . For each  $j \in [n]$ ,

$$\begin{aligned} x'_j \log x'_j - \tilde{x}_j \log \tilde{x}_j &= x'_j \log x'_j - (1 + b)x'_j \log((1 + b)x'_j) \\ &= bx'_j \log \frac{1}{x'_j} - (1 + b)x'_j \log(1 + b) \\ &\leq bx'_j \log \frac{1}{x'_j} \leq \frac{\beta}{e}. \end{aligned}$$

The first inequality was due to nonnegativity of  $(1 + b) \log(1 + b)$  and  $x'_j$ , and the second was due to the maximum value of the scalar function  $z \log \frac{1}{z}$  over the nonnegative reals being  $1/e$ . Summing over all coordinates yields that the first term is bounded by  $\beta n/e$ .

For the second term, we have by integration that entrywise

$$\begin{aligned} \tilde{x}_j \log \tilde{x}_j - x_j \log x_j &= \int_{\alpha=0}^1 (1 + \log(x_j + \alpha(\tilde{x}_j - x_j)))(\tilde{x}_j - x_j) d\alpha \\ &\leq \int_{\alpha=0}^1 (1 + \log(\tilde{x}_j))(\tilde{x}_j - x_j) d\alpha \\ &\leq \int_{\alpha=0}^1 \tilde{x}_j(\tilde{x}_j - x_j) d\alpha \leq (1 + \beta)|\tilde{x}_j - x_j|. \end{aligned}$$

The first inequality is by  $\tilde{x}_j \geq x_j$  for all  $j \in [n]$  and  $\log(x)$  is monotone in  $x > 0$ ; the second is by  $\log(x) \leq x - 1$  for all  $x > 0$ ; the third again uses  $\tilde{x}_j \geq x_j$  and that  $\tilde{x}_j \leq \|\tilde{x}\|_1 \leq 1 + \beta$ , and the second condition in Definition 2. Finally, combining yields the desired

$$\sum_{j \in [n]} x'_j \log x'_j - \sum_{j \in [n]} x_j \log x_j \leq \frac{\beta n}{e} + \beta(1 + \beta).$$

□

## D.2 $\ell_2$ - $\ell_2$ variance-reduced coordinate method

**Assumptions.** As in Section C.1, the algorithm in this section will assume access to entry queries,  $\ell_1$  norms of rows and columns, and  $\ell_1$  sampling distributions for rows and columns, and the ability to sample a row or column proportional to its squared  $\ell_1$  norm. We use the  $\ell_2$ - $\ell_2$  local norm setup (cf. Table 6). Again, we define

$$L_{\text{co}}^{2,2} := \sqrt{\sum_{i \in [m]} \|A_{i:}\|_1^2 + \sum_{j \in [n]} \|A_{:j}\|_1^2}.$$

### D.2.1 Gradient estimator

Given reference point  $w_0 \in \mathbb{B}^n \times \mathbb{B}^m$ , for  $z \in \mathbb{B}^n \times \mathbb{B}^m$ , we specify two distinct sampling distributions  $p(z; w_0), q(z; w_0)$  which obtain the optimal Lipschitz constant. The first one is an oblivious distribution:

$$p_{ij}(z; w_0) := \frac{\|A_{i:}\|_1^2}{\sum_{k \in [m]} \|A_{k:}\|_1^2} \cdot \frac{|A_{ij}|}{\|A_{i:}\|_1} \quad \text{and} \quad q_{ij}(z; w_0) := \frac{\|A_{:j}\|_1^2}{\sum_{k \in [n]} \|A_{:k}\|_1^2} \cdot \frac{|A_{ij}|}{\|A_{:j}\|_1}. \quad (90)$$

The second one is a dynamic distribution:

$$p_{ij}(z; w_0) := \frac{[w_0^y - z^y]_i^2}{\|w_0^y - z^y\|_2^2} \cdot \frac{|A_{ij}|}{\|A_{i:}\|_1} \quad \text{and} \quad q_{ij}(z; w_0) := \frac{[w_0^x - z^x]_j^2}{\|w_0^x - z^x\|_2^2} \cdot \frac{|A_{ij}|}{\|A_{:j}\|_1}. \quad (91)$$

We now state the local properties of each estimator.

**Lemma 18.** *In the  $\ell_2$ - $\ell_2$  setup, estimator (25) using the sampling distribution in (90) or (91) is a  $\sqrt{2}L_{\text{co}}^{2,2}$ -centered-local estimator.*

*Proof.* Unbiasedness holds by definition in both cases. We first show the variance bound on the  $x$  block for distribution (90):

$$\begin{aligned} \mathbb{E} \left[ \|\tilde{g}_{w_0}^x(z) - g^x(w_0)\|_2^2 \right] &= \sum_{i \in [m], j \in [n]} p_{ij}(z; w_0) \cdot \left( \frac{A_{ij}[z^y - w_0^y]_i}{p_{ij}(z; w_0)} \right)^2 = \sum_{i \in [m], j \in [n]} \frac{A_{ij}^2 [z^y - w_0^y]_i^2}{p_{ij}(z; w_0)} \\ &= \sum_{i \in [m], j \in [n]} \frac{|A_{ij}|}{\|A_{i:}\|_1} [z^y - w_0^y]_i^2 \cdot \left( \sum_{k \in [m]} \|A_{k:}\|_1^2 \right) \\ &= \left( \sum_{i \in [m]} \|A_{i:}\|_1^2 \right) \|z^y - w_0^y\|_2^2. \end{aligned}$$

Similarly, we have

$$\mathbb{E} \left[ \|\tilde{g}_{w_0}^y(z) - g^y(w_0)\|_2^2 \right] \leq \left( \sum_{j \in [n]} \|A_{:j}\|_1^2 \right) \|z^x - w_0^x\|_2^2.$$

Combining these and using  $\|z^x - w_0^x\|_2^2 + \|z^y - w_0^y\|_2^2 = 2V_{w_0}(z)$  yields the desired variance bound. Now, we show the variance bound on the  $x$  block for distribution (91):

$$\begin{aligned} \mathbb{E} \left[ \|\tilde{g}_{w_0}^x(z) - g^x(w_0)\|_2^2 \right] &= \sum_{i \in [m], j \in [n]} p_{ij}(z; w_0) \cdot \left( \frac{A_{ij}[z^y - w_0^y]_i}{p_{ij}(z; w_0)} \right)^2 = \sum_{i \in [m], j \in [n]} \frac{A_{ij}^2 [z^y - w_0^y]_i^2}{p_{ij}(z; w_0)} \\ &= \sum_{i \in [m], j \in [n]} |A_{ij}| \|A_{i:}\|_1 \|z^y - w_0^y\|_2^2 \\ &= \left( \sum_{i \in [m]} \|A_{i:}\|_1^2 \right) \|z^y - w_0^y\|_2^2. \end{aligned}$$

and a similar bound holds on the  $y$  block.  $\square$

Again, for algorithmic considerations (i.e. an additional logarithmic factor in the complexity of sampling from (91)), we will only discuss using the oblivious distribution (90) in our algorithm.

### D.2.2 Implementation details

In this section, we discuss the details of how to leverage the `IterateMaintainer2` data structure to implement the iterations of our algorithm. The algorithm we analyze is Algorithm 2 with  $K = \alpha\Theta/\epsilon$ ,

using Algorithm 3 as an  $(\alpha, 0)$ -relaxed proximal oracle. In the implementation of Algorithm 3, we use the centered-local gradient estimator defined in (90). For each use of Algorithm 3, we choose

$$\eta = \frac{\alpha}{20 \left( L_{\text{co}}^{2,2} \right)^2} \text{ and } T = \left\lceil \frac{6}{\eta \alpha} \right\rceil \geq \frac{120 \left( L_{\text{co}}^{2,2} \right)^2}{\alpha^2}. \quad (92)$$

Our discussion will follow in three steps: first, we discuss the complexity of all executions in Algorithm 2 other than the calls to the oracles, as well as the initialization procedure for each inner loop. Next, we discuss the complexity of each iteration of Algorithm 3. Finally, we discuss the complexity of computing the average iterate in each run of Algorithm 3. For simplicity, when discussing Algorithm 3, we will only discuss implementation of the  $x$ -block, and the  $y$ -block will follow symmetrically. Altogether, the guarantees of Proposition 3 and Proposition 4 imply that if the guarantees required by the algorithm hold, the expected gap of the output is bounded by  $\epsilon$ .

**Outer loop extragradient steps and inner loop data structures.** Overall, we execute  $K = \alpha \Theta / \epsilon$  iterations of Algorithm 2, and let  $\varepsilon_{\text{outer}} = \varepsilon_{\text{inner}} = 0$  to obtain the desired gap, where  $\Theta = 1$  in the  $\ell_2$ - $\ell_2$  setup. We spend  $O(\text{nnz})$  time executing each extragradient step in Algorithm 2 exactly, where the dominant term in the runtime is the computation of each  $g(z_{k-1/2})$ , for  $k \in [K]$ . Also, we can maintain the average point  $\bar{z}$  throughout the duration of the algorithm, in  $O(m + n)$  time per iteration. At the beginning of each inner loop, we initialize a data structure  $\text{IM}_2^\times$  which does not support sampling, an instance of `IterateMaintainer2`, with  $\text{IM}_2^\times.\text{Init}(w_0^\times, v)$ , for

$$v = (1 - \kappa)w_0^\times - \eta \kappa g^\times(w_0),$$

where  $\kappa := \frac{1}{1 + \eta \alpha / 2}$ . The inner loop will preserve the invariant that the point maintained by  $\text{IM}_2^\times$  is the  $x$  block of the current inner loop iterate  $w_t$  in each iteration  $t$ . To motivate this initialization, we recall the form of the updates,

$$w_{t+1}^\times \leftarrow \Pi_{\mathcal{X}} \left( \kappa \left( w_t^\times + \left( \frac{1}{\kappa} - 1 \right) w_0^\times - \eta \tilde{g}_{w_0}^\times(w_t) \right) \right), \quad (93)$$

where  $\Pi_{\mathcal{X}}(w) = \frac{w}{\max\{1, \|w\|_2\}}$ , and the fixed dense part of  $\tilde{g}_{w_0}^\times(w_t)$  is  $g^\times(w_0)$ . Therefore, in the following discussion we will be able to maintain this difference via a scaling by  $\kappa$ , an appropriate addition of the scaled dense vector, and a sparse update.

Finally, we also store the vector  $w_0$  in full, supporting entry queries.

**Inner loop iterations.** Each inner loop iteration consists of sampling indices for the computation of  $\tilde{g}_{w_0}$ , computing the sparse part of  $\tilde{g}_{w_0}$ , and performing the update to the iterate. We show that we can run each substep in constant time. Then, this implies that the total complexity of the inner loop, other than initializing the data structures and outputting the average iterate, is

$$O(T) = O \left( \frac{\left( L_{\text{co}}^{2,2} \right)^2}{\alpha^2} \right).$$

We discuss how to make appropriate modifications to the  $x$ -block. For simplicity we denote our current iterate as  $z$ , and the next iterate as  $w$ . Recall that the distribution is given by

$$p_{ij}(z; w_0) := \frac{\|A_{i:}\|_1^2}{\sum_{k \in [m]} \|A_{k:}\|_1^2} \cdot \frac{|A_{ij}|}{\|A_{i:}\|_1}.$$

*Sampling.* By using precomputed distributions, we can sample  $i \propto \|A_{i:}\|_1^2$  and then  $j \mid i \propto |A_{ij}|$  in constant time.

*Computing the gradient estimator.* Computing the sparse component of the gradient estimator 25 requires computing  $A_{ij}$ ,  $[z^y - w_0^y]_i$ , and  $p_{ij}(z; w_0)$ . Using appropriate use of precomputed access to entries and row norms (it is clear we may pay  $O(m + n)$  at the beginning of the algorithm to store the sum  $\sum_{k \in [m]} \|A_{k:}\|_1^2$ ), entry  $[w_0^y]_i$ , and  $\text{IM}_2^x.\text{Get}(i)$  allows us to perform the required computation of the sparse component

$$c := [\tilde{g}_{w_0}^x(z) - g(w_0)]_j$$

in constant time, by assumption.

*Performing the update.* In order to perform the update, we recall the form of the update given by (93). Thus, it suffices to call

```

IM2x.Scale( $\kappa$ );
IM2x.AddDense(1);
IM2x.AddSparse( $j, -\kappa\eta c$ );
IM2x.Scale( $\max\{\text{IM}_2^x.\text{GetNorm}(), 1\}^{-1}$ );
IM2x.UpdateSum();

```

By assumption, each operation takes constant time. By the discussion in the data structure initialization section, it is clear that we preserve the invariant that the point maintained by  $\text{IM}_2^x$  is the  $x$  block of the current iterate.

**Average iterate computation.** At the end of each run of Algorithm 3, we spend  $O(n)$  time computing and returning the average iterate via appropriate calls to  $\text{IM}_2^x.\text{GetSum}(j)$  for each  $j \in [n]$ , and scaling by  $1/T$ . This operation is asymptotically dominated by the  $O(\text{nnz}(A))$  cost of the extragradient step.

### D.2.3 Algorithm guarantee

**Theorem 8.** *In the  $\ell_2$ - $\ell_2$  setup, the implementation in Section D.2.2 with the optimal choice of  $\alpha = \max\{\epsilon, L_{\text{co}}^{2,2} \sqrt{1/\text{nnz}}\}$  has runtime*

$$O\left(\left(\text{nnz} + \frac{(L_{\text{co}}^{2,2})^2}{\alpha^2}\right) \frac{\alpha}{\epsilon}\right) = O\left(\text{nnz} + \frac{\sqrt{\text{nnz}} L_{\text{co}}^{2,2}}{\epsilon}\right)$$

and outputs a point  $\bar{z} \in \mathcal{Z}$  such that

$$\mathbb{E} \text{Gap}(\bar{z}) \leq \epsilon.$$

*Proof.* The correctness of the algorithm is given by the discussion in Section D.2.2 and the guarantees of Proposition 3 and Proposition 4. The runtime bound is given by the discussion in Section D.2.2, and the optimal choice of  $\alpha$  is clear.  $\square$

To better understand the strengths of our runtime guarantee, Proposition 7 shows that Theorem 8 implies a universal improvement for  $\ell_2$ - $\ell_2$  games compared to accelerated gradient descent for matrices  $A$  with nonnegative entries (or more generally, for  $A$  with  $\|A\|_{\text{op}} = O(\|A\|_{\text{op}})$ ).

**Proposition 7.** For any  $A \in \mathbb{R}^{m \times n}$ , we have

$$L_{\text{co}}^{2,2} := \max \left\{ \sqrt{\sum_i \|A_{i:}\|_1^2}, \sqrt{\sum_j \|A_{:j}\|_1^2} \right\} \leq \sqrt{m+n} \cdot \|A\|_{\text{op}}.$$

*Proof.* Denote  $\mathbf{1}_k$  as the all 1 vector in  $\mathbb{R}^k$ . We have the following sequence of inequalities:

$$\sqrt{\sum_{i \in [m]} \|A_{i:}\|_1^2} = \| |A|^\top \mathbf{1}_m \|_2 = \max_{x \in \mathbb{B}^n} \mathbf{1}_m^\top |A| x \leq \|\mathbf{1}_m\|_2 \max_{x \in \mathbb{B}^n} \| |A| x \|_2 \leq \sqrt{m} \| |A| \|_{\text{op}}.$$

Similarly, bounding  $\max_{y \in \mathbb{B}^n} y^\top |A| \mathbf{1}_n$  implies  $\sqrt{\sum_{j \in [n]} \|A_{:j}\|_1^2} \leq \sqrt{n} \| |A| \|_{\text{op}}$ . Taking a maximum and using  $\max\{\sqrt{m}, \sqrt{n}\} \leq \sqrt{m+n}$  implies the result.  $\square$

**Remark 9.** For matrix  $A \in \mathbb{R}^{m \times n}$ , combining the guarantees of Theorem 8 with the bound from Proposition 7 implies a runtime bounded by

$$O \left( \text{nnz} + \frac{\sqrt{\text{nnz} \cdot (m+n)} \| |A| \|_{\text{op}}}{\epsilon} \right).$$

Whenever  $\|A\|_{\text{op}} \geq \| |A| \|_{\text{op}}$ , this is an improvement by a factor of  $\sqrt{\text{nnz}/(m+n)}$  compared to the accelerated full-gradient method (c.f. Table 2), which obtains a runtime of  $O(\text{nnz} \cdot \|A\|_{\text{op}}/\epsilon)$ . This applies without any sparsity or numerical sparsity assumptions, and is the same speedup factor as we obtained for  $\ell_1$ - $\ell_1$  and  $\ell_2$ - $\ell_1$  games using a variance reduction framework with row and column based gradient estimators in Carmon et al. [8]. The  $\ell_2$ - $\ell_2$  variance reduction algorithms of Carmon et al. [8] and Balamurugan and Bach [7] do not offer such improvements, and our improvement stems from our coordinate-based gradient estimators and our data structure design.

### D.3 $\ell_2$ - $\ell_1$ variance-reduced coordinate method

**Assumptions.** The algorithm in this section will assume access to entry queries,  $\ell_1$  norms of rows,  $\ell_2$  sampling distributions for rows and columns, and the Frobenius norm of  $A$ . We use the  $\ell_2$ - $\ell_1$  local norm setup (cf. Table 6). Again, we define

$$L_{\text{co}}^{2,1,(1)} := \sqrt{\max_{i \in [m]} \|A_{i:}\|_1^2 + \|A\|_{\text{F}}^2}, \quad (94)$$

$$L_{\text{co}}^{2,1,(2)} := \sqrt{2\text{rcs} \max_{i \in [m]} \|A_{i:}\|_2^2}, \quad (95)$$

$$L_{\text{co}}^{2,1,(3)} := \sqrt{\max_{i \in [m]} \|A_{i:}\|_1^2 + \left( \max_{i \in [m]} \|A_{i:}\|_1 \right) \left( \max_{j \in [n]} \|A_{:j}\|_1 \right)}. \quad (96)$$

Finally, in this section we assume access to a centered variant of `WeightedIterateMaintainer2`, which takes a point  $x_0$  as a static parameter, where  $x_0$  is in the space as the iterates  $x$  maintained. `CenteredIterateMaintainer2` supports two additional operations compared to the data structure `WeightedIterateMaintainer2`: `Sample()` returns coordinate  $j$  with probability proportional to  $[w]_j [x - x_0]_j^2$  (cf. Section 2.4.1) in  $O(\log n)$  time, and we may query  $\|x - x_0\|_w^2$  in constant time, where  $w$  is a specified weight vector. We give the implementation of this extension in Appendix G.

### D.3.1 Gradient estimator

Given reference point  $w_0 \in \mathbb{B}^n \times \Delta^m$ , for  $z \in \mathbb{B}^n \times \Delta^m$  and a parameter  $\alpha > 0$ , as in Section C.2, we specify three distinct choices of sampling distributions  $p(z; w_0), q(z; w_0)$ .

The first one is

$$p_{ij}(z; w_0) := \frac{[z^y]_i + 2[w_0^y]_i}{3} \cdot \frac{|A_{ij}|}{\|A_{i:}\|_1} \quad \text{and} \quad q_{ij}(z; w_0) := \frac{A_{ij}^2}{\|A\|_F^2}. \quad (97)$$

The second one is

$$p_{ij}(z; w_0) := \frac{[z^y]_i + 2[w_0^y]_i}{3} \cdot \frac{|A_{ij}|}{\|A_{i:}\|_1} \quad \text{and} \quad q_{ij}(z) := \frac{[z^x - w_0^x]_j^2 \cdot \mathbf{1}_{\{A_{ij} \neq 0\}}}{\sum_{l \in [n]} \text{cs}_l \cdot [z^x - w_0^x]_l^2}. \quad (98)$$

As in Section C.2,  $\text{cs}_j$  is the number of nonzeros of  $A_{:j}$ . The third one is

$$p_{ij}(z; w_0) := \frac{[z^y]_i + 2[w_0^y]_i}{3} \cdot \frac{|A_{ij}|}{\|A_{i:}\|_1} \quad \text{and} \quad q_{ij}(z) := \frac{|A_{ij}| \cdot [z^x - w_0^x]_j^2}{\sum_{l \in [n]} \|A_{:l}\|_1 \cdot [z^x - w_0^x]_l^2}. \quad (99)$$

We now state the local properties of each estimator.

**Lemma 19.** *In the  $\ell_2$ - $\ell_1$  setup, estimator (25) using the sampling distributions in (97), (98), or (99) is respectively a  $\sqrt{2}L_{\text{co}}^{2,1,(k)}$ -centered-local estimator, for  $k \in \{1, 2, 3\}$ .*

*Proof.* First, we give the proof for the sampling distribution (97). Unbiasedness holds by definition. For the  $x$  block, we have the variance bound:

$$\begin{aligned} \mathbb{E} \left[ \|\tilde{g}_{w_0}^x(z) - g^x(w_0)\|_2^2 \right] &= \sum_{i \in [m], j \in [n]} p_{ij}(z; w_0) \left( \frac{A_{ij}[z^y - w_0^y]_i}{p_{ij}(z; w_0)} \right)^2 = \sum_{i \in [m], j \in [n]} \frac{A_{ij}^2 [z^y - w_0^y]_i^2}{p_{ij}(z; w_0)} \\ &\leq 2 \max_{i \in [m]} \|A_{i:}\|_1^2 V_{w_0^y}(z^y), \end{aligned}$$

where in the last inequality we used Lemma 3.

For arbitrary  $w^y$ , we have the variance bound on the  $y$  block:

$$\begin{aligned} \mathbb{E} \left[ \|\tilde{g}_{w_0}^y(z) - g^y(w_0)\|_{w^y}^2 \right] &= \sum_{i \in [m], j \in [n]} [w^y]_i \frac{A_{ij}^2 [z^x - w_0^x]_j^2}{q_{ij}(z; w_0)} \\ &= \sum_{i \in [m], j \in [n]} [w^y]_i [z^x - w_0^x]_j^2 \|A\|_F^2 \leq 2 \|A\|_F^2 V_{w_0^x}(z^x). \end{aligned}$$

Combining these and using

$$\|\tilde{g}_{w_0}(z) - g(w_0)\|_w^2 := \|\tilde{g}_{w_0}(z)^x - g(w_0)^x\|_2^2 + \|\tilde{g}_{w_0}(z)^y - g(w_0)^y\|_{w^y}^2$$

yields the desired variance bound. For the remaining two distributions, the same argument demonstrates unbiasedness and the variance bound for the  $x$  block. For sampling distribution (98) and arbitrary  $w^y$ , we have the variance bound on the  $y$  block:

$$\begin{aligned} \mathbb{E} \left[ \|\tilde{g}_{w_0}^y(z) - g^y(w_0)\|_{w^y}^2 \right] &= \sum_{i \in [m], j \in [n]} [w^y]_i \frac{A_{ij}^2 [z^x - w_0^x]_j^2}{q_{ij}(z; w_0)} \\ &\leq \left( \sum_{i \in [m], j \in [n]} [w^y]_i A_{ij}^2 \right) \left( \text{rcs} \sum_{j \in [n]} [z^x - w_0^x]_j^2 \right) \\ &\leq 2 \text{rcs} \max_{i \in [m]} \|A_{i:}\|_2^2 V_{w_0^x}(z^x). \end{aligned}$$

Finally, for sampling distribution (99), we have the variance bound on the  $y$  block:

$$\begin{aligned}\mathbb{E} \left[ \|\tilde{g}_{w_0}^y(z) - g^y(w_0)\|_{w^y}^2 \right] &= \sum_{i \in [m], j \in [n]} [w^y]_i \frac{A_{ij}^2 [z^x - w_0^x]_j^2}{q_{ij}(z; w_0)} \\ &\leq \left( \sum_{i \in [m], j \in [n]} [w^y]_i |A_{ij}| \right) \left( \sum_{l \in [n]} \|A_{:l}\|_1 \cdot [z^x - w_0^x]_l^2 \right) \\ &\leq 2 \left( \max_{i \in [m]} \|A_{i:}\|_1 \right) \left( \max_{j \in [n]} \|A_{:j}\|_1 \right) V_{w_0^x}(z^x).\end{aligned}$$

□

Finally, as in Section C.2, we define the constant

$$L_{\text{co}}^{2,1} := \sqrt{\max_{i \in [m]} \|A_{i:}\|_1^2 + \min \left( \|A\|_{\text{F}}^2, \text{rcs} \max_{i \in [m]} \|A_{i:}\|_2^2, \left( \max_{i \in [m]} \|A_{i:}\|_1 \right) \left( \max_{j \in [n]} \|A_{:j}\|_1 \right) \right)},$$

and note that Lemma 19 implies that we can obtain a  $\sqrt{2}L_{\text{co}}^{2,1}$ -centered-local estimator by appropriately choosing a sampling distribution depending on the minimizing parameter.

### D.3.2 Implementation details

The algorithm we analyze is Algorithm 2 with  $K = 3\alpha\Theta/\epsilon$ ,  $\epsilon_{\text{outer}} = 2\epsilon/3$  using Algorithm 3 as an  $(\alpha, \epsilon_{\text{inner}} = \epsilon/3)$ -relaxed proximal oracle with  $\varphi = \epsilon/18$ . In the implementation of Algorithm 2, we again apply the `truncate`( $\cdot, \delta$ ) operation to each iterate  $z_k^*$ , where the `truncate` operation only affects the  $y$  block; choosing  $\delta = \frac{\epsilon_{\text{outer}} - \epsilon_{\text{inner}}}{\alpha m}$  suffices for its guarantees (see Section 4.2.2 for the relevant discussion). In the implementation of Algorithm 3, we use the centered-local gradient estimator defined in (25), using the sampling distribution amongst (97), (98), or (99) which attains the variance bound  $L_{\text{co}}^{2,1}$ . For each use of Algorithm 3, we choose

$$\eta = \frac{\alpha}{20 \left( L_{\text{co}}^{2,1} \right)^2} \text{ and } T = \left\lceil \frac{6}{\eta \alpha} \right\rceil = \frac{120 \left( L_{\text{co}}^{2,1} \right)^2}{\alpha^2}.$$

For simplicity, because most of the algorithm implementation details are exactly the same as the discussion of Section 4.2.2 for the simplex block  $y \in \mathcal{Y}$ , and exactly the same as the discussion of Section D.2.2 for the ball block  $x \in \mathcal{X}$ , we discuss the differences here.

**Outer loop extragradient steps.** We execute  $3\alpha \log(2m)/\epsilon$  iterations of Algorithm 2 to obtain the desired gap. We spend  $O(\text{nnz})$  time executing each extragradient step exactly, and then  $O(m+n)$  time applying the `truncate` operation and maintaining the average point  $\bar{z}$ . When we initialize the inner loop, we also create a data structure supporting sampling from  $w_0^y$  in constant time.

**Data structure initializations and invariants.** On the simplex block, we follow the strategy outlined in Section 4.2.2. We initialize our simplex maintenance data structure  $\mathbf{AEM}^y(w_0^y, v, \kappa, \tilde{\epsilon})$  with parameters

$$\kappa := \frac{1}{1 + \eta \alpha / 2}, \quad v := (1 - \kappa) \log w_0^y - \eta \kappa g^y(w_0), \quad \tilde{\epsilon} := (m + n)^{-8}.$$



We will again maintain the invariant that the data structures maintain “exact” and “approximate” points corresponding to the iterates of our algorithm. The correctness of this setting with respect to the requirements of Proposition 4, i.e. the approximation conditions in Line 2, 4 and 5 in Algorithm 3, follows from the discussion of Section 4.2.2; we note that the condition  $\min_j [w_0^x]_j \geq (m+n)^{-5} = \lambda$  again holds, and that  $1 - \kappa \geq (m+n)^{-8}$ . Thus, for the parameter  $\omega$  used in the interface of `ApproxExpMaintainer`, we have

$$\log(\omega) = \log \left( \max \left( \frac{1}{1 - \kappa}, \frac{m}{\lambda \tilde{\varepsilon}} \right) \right) = O(\log(mn)).$$

On the ball block, we follow the strategy outlined in Section D.2.2, but instead of using an `IterateMaintainer2` on the  $x$ -block, we use `CIM2x`, an instance of `CenteredIterateMaintainer2` data structure initialized with the point  $w_0^x$ , supporting the required sampling operation. For the sampling distribution (98), we use the weight vector of column nonzero counts, and for (99) we use the weight vector of column  $\ell_1$  norms. Overall, the complexity of the initializations on both blocks is bounded by  $O(n + m \log^2(m) \log^2(mn))$ .

**Inner loop iterations.** We discuss how to sample from each of the distributions (97), (98), and (99) in  $O(\log(m) \log(mn))$ . Combining with the discussions of implementing the inner loop in Sections 4.2.2 and D.2.2, the total complexity of the inner loop, other than outputting the average iterate, is

$$\begin{aligned} & O(T \log^2(m) \log^2(mn) + \text{nnz} + m \log(m) \log^2(mn)) \\ &= O \left( \frac{\left( L_{\text{co}}^{2,1,(1)} \right)^2 \log^2(m) \log^2(mn)}{\alpha^2} + \text{nnz} + m \log(m) \log^2(mn) \right). \end{aligned}$$

As in the variance-reduced  $\ell_1$ - $\ell_1$  setting, the dominant term in the runtime is the complexity of calling `AEMy.AddSparse` in each iteration. Recall that the distribution  $p$  in every case is given by

$$p_{ij}(z; w_0) := \frac{[z^y]_i + 2[w_0^y]_i}{3} \cdot \frac{|A_{ij}|}{\|A_{i:}\|_1}$$

With probability  $2/3$  we sample a coordinate  $i$  from the precomputed data structure for sampling from  $w_0^y$ , and otherwise we sample  $i$  via `AEMy.Sample()`. Then, we sample an entry  $j$  proportional to its magnitude from the  $\ell_1$  sampling oracle for  $A_{i:}$  in constant time. The runtime is dominated by  $O(\log(m) \log(mn))$ .

To sample from the distribution  $q$  in (97), we follow the outline in Section D.3. Similarly, for sampling from distributions (98) and (99), we follow the outline in Section D.3 but replace all calls to an `IterateMaintainer` instance with a call to `CIM2x` initialized with an appropriate weight vector. In all cases, the runtime is  $O(\log m)$  which does not dominate the iteration complexity.

Finally, it is clear from discussions in previous sections that the iterate maintenance invariants of our data structures are preserved by the updates used in this implementation.

### D.3.3 Algorithm guarantee

**Theorem 9.** *In the  $\ell_2$ - $\ell_1$  setup, let  $\text{nnz}' := \text{nnz} + m \log(m) \log^2(mn)$ . The implementation in Section D.3.2 with the optimal choice of  $\alpha = \max\left(\epsilon/3, L_{\text{co}}^{2,1} \log(m) \log(mn) / \sqrt{\text{nnz}'}\right)$  has runtime*

$$O\left(\left(\text{nnz}' + \frac{\left(L_{\text{co}}^{2,1}\right)^2 \log^2(m) \log^2(mn)}{\alpha^2}\right) \frac{\alpha \log(m)}{\epsilon}\right) = O\left(\text{nnz}' + \frac{\sqrt{\text{nnz}'} L_{\text{co}}^{2,1} \log(mn) \log^2(m)}{\epsilon}\right)$$

and outputs a point  $\bar{z} \in \mathcal{Z}$  such that

$$\mathbb{E} [\text{Gap}(z)] \leq \epsilon.$$

*Proof.* The correctness of the algorithm is given by the discussion in Section D.3.2 and the guarantees of Proposition 3 with  $K = 3\alpha\Theta/\epsilon$ ,  $\varepsilon_{\text{outer}} = 2\epsilon/3$ ,  $\varepsilon_{\text{inner}} = \epsilon/3$ , Proposition 4 with  $\varphi = \epsilon/18$  and data structure `ApproxExpMaintainer` with our choice of

$$\tilde{\varepsilon} := (m + n)^{-8}$$

to meet the approximation conditions in Line 2, 4 and 5 in Algorithm 3. The runtime bound is given by the discussion in Section D.3.2, and the optimal choice of  $\alpha$  is clear.  $\square$

## E Additional results on variance-reduced methods

### E.1 Row-column sparsity variance-reduced methods

By instantiating relaxed proximal oracles with row-column based gradient estimators developed in [8], implemented with the data structures we develop in Section 5, we obtain the improved complexities as stated in Table 2. Namely, up to logarithmic factors, we generically replace a dependence on  $O(m + n)$  with  $O(\text{rcs})$ , where  $\text{rcs}$  is defined as the maximum number of nonzero entries for any row or column. In this section, we give implementation details.

The estimators  $\tilde{g}_{w_0}$  of [8], parameterized by reference point  $w_0$ , sample a full column or row of the matrix (rather than a coordinate). To compute  $\tilde{g}_{w_0}(z)$  we sample  $i \sim p(z)$  and  $j \sim q(z)$  independently according to a specified distribution depending on the setup, and use the estimator

$$\tilde{g}_{w_0}(z) := \left( A^\top w_0^y + A_{i:} \frac{[z^y]_i - [w_0^y]_i}{p_i(w)}, -Aw_0^x - A_{:j} \frac{[z^x]_j - [w_0^x]_j}{q_j(w)} \right), \quad (100)$$

The key difference between this estimator with that of Section 3.2.2 is that its difference with  $g(w_0)$  is  $O(\text{rcs})$ -sparse rather than  $O(1)$ -sparse, requiring `MultSparse` steps with  $O(\text{rcs})$ -sparse vectors. In all other respects, the implementation details are exactly the same as those in Section 4.2 and Appendix D, so we omit them for brevity. We now state our sampling distributions used with the estimator form (100), and the corresponding centered local variance bounds.

In the  $\ell_1$ - $\ell_1$  setup, we use the sampling distribution (from reference point  $w_0 \in \Delta^m \times \Delta^n$ )

$$p_i(z) := \frac{[z^y]_i + 2[w_0^y]_i}{3} \quad \text{and} \quad q_j(z) := \frac{[z^x]_j + 2[w_0^x]_j}{3}. \quad (101)$$

**Lemma 20.** *In the  $\ell_1$ - $\ell_1$  setup, gradient estimator (100) using the sampling distribution in (101) is a  $\sqrt{2} \|A\|_{\max}$ -centered-local estimator.*

*Proof.* Unbiasedness holds by definition. For the variance bound, it suffices to show that

$$\mathbb{E} \|\tilde{g}_{w_0}(z) - g(w_0)\|_\infty^2 \leq 2 \|A\|_{\max}^2 V_{w_0^\times}(z^\times);$$

clearly this implies the weaker relative variance bound statement (along with an analogous bound on the  $y$  block). To this end, we have

$$\mathbb{E} \|\tilde{g}_{w_0}(z) - g(w_0)\|_\infty^2 \leq \sum_{i \in [m]} \frac{\|A_{i:}\|_\infty^2 [z^y - w_0^y]_i^2}{p_i(z)} \leq 2 \|A\|_{\max}^2 V_{w_0^\times}(z^\times),$$

where the last inequality used Lemma 3.  $\square$

In the  $\ell_2$ - $\ell_2$  setup, we use the oblivious sampling distribution

$$p_i = \frac{\|A_{i:}\|_2^2}{\|A\|_F^2} \quad \text{and} \quad q_j = \frac{\|A_{:j}\|_2^2}{\|A\|_F^2}. \quad (102)$$

We proved that gradient estimator (100) using the sampling distribution in (102) admits a  $\|A\|_F$ -centered estimator in [8], which is an equivalent definition to Definition 4 in the  $\ell_2$ - $\ell_2$  setup. In the  $\ell_2$ - $\ell_1$  setup, we use the sampling distribution (from reference point  $w_0 \in \mathbb{B}^n \times \Delta^m$ )

$$p_i(z) = \frac{[z^y]_i + 2[w_0^y]_i}{3} \quad \text{and} \quad q_j(z) = \frac{([z^\times]_j - [w_0^\times]_j)^2}{\|z^\times - w_0^\times\|_2^2}. \quad (103)$$

**Lemma 21.** *In the  $\ell_2$ - $\ell_1$  setup, gradient estimator (100) using the sampling distribution in (103) is a  $\sqrt{2}L$ -centered-local estimator with  $L = \max_{i \in [m]} \|A_{i:}\|_2 = \|A\|_{2 \rightarrow \infty}$ .*

*Proof.* Unbiasedness holds by definition. For the variance bound, we first note

$$\begin{aligned} \mathbb{E} \left[ \|\tilde{g}_{w_0}^\times(z) - g^\times(w_0)\|_2^2 \right] &\leq \sum_{i \in [m]} \|A_{i:}\|_2^2 \frac{([z^y]_i - [w_0^y]_i)^2}{\frac{1}{3}[z^y]_i + \frac{2}{3}[w_0^y]_i} \leq \max_{i \in [m]} \|A_{i:}\|_2^2 \left( \sum_{i \in [m]} \frac{([z^y]_i - [w_0^y]_i)^2}{\frac{1}{3}[z^y]_i + \frac{2}{3}[w_0^y]_i} \right) \\ &\leq 2 \max_{i \in [m]} \|A_{i:}\|_2^2 V_{w_0^y}(z^y), \end{aligned}$$

where for the last inequality we use Lemma 3. On the other block, we have

$$\max_{i \in [m]} \mathbb{E} [\tilde{g}_{w_0}^y(w) - g^y(w_0)]_i^2 \leq \max_{i \in [m]} \sum_{j \in [n]} \frac{A_{ij}^2 [w^\times - w_0^\times]_j^2}{q_j(w)} = 2 \max_{i \in [m]} \|A_{i:}\|_2^2 V_{w_0^\times}(w^\times).$$

Summing these two bounds concludes the proof.  $\square$

## E.2 Extensions with composite terms

In this section, we give a brief discussion of how to change Proposition 4 and implementations of the procedures in Sections 3.1 and 3.2 to handle modified regularization in the context of Proposition 6, and composite regularization terms in the objective in the methods of Section 6. Specifically we consider a composite optimization problem of the form:

$$\min_{x \in \mathcal{X}} \max_{y \in \mathcal{Y}} y^\top A x + \mu^\times \phi(x) - \mu^y \psi(y) \quad \text{where } \phi = V_{x'}^\times \text{ and } \psi = V_{y'}^y.$$

For simplicity of notation we define  $\Upsilon(x, y) := \mu^\times \phi(x) + \mu^y \psi(y)$ . We remark that  $x' = 0$  recovers the case of  $\phi = r^\times$  when  $\mathcal{X} = \mathbb{B}^n$ , and  $x' = \frac{1}{n} \mathbf{1}$  recovers the case of  $\phi = r^\times$  when  $\mathcal{X} = \Delta^n$  (similarly setting  $y'$  allows us to recover this for the  $y$  block).

### E.2.1 Changes to inner loop

In this section, we first discuss the necessary changes to Algorithm 3 and Proposition 4. For simplicity of notation, we denote  $\rho := \sqrt{\mu^x/\mu^y}$ ,  $\hat{V}^x := \rho V^x$ ,  $\hat{V}^y := \frac{1}{\rho} V^y$ ,  $\hat{V} := \hat{V}^x + \hat{V}^y$ .

---

#### Algorithm 4: InnerLoop( $w_0, \tilde{g}_{w_0}, \varphi$ )

---

**Input:** Initial  $w_0 \in \mathcal{Z}$ ,  $(L, \alpha)$ -centered-local gradient estimator  $\tilde{g}_{w_0}$ , oracle quality  $\alpha > 0$

**Parameters:** Step size  $\eta$ , number of iterations  $T$ , approximation tolerance  $\varphi$

**Output:** Point  $\tilde{w}$  satisfying Definition 5

```

1 for  $t = 1, \dots, T$  do
2    $\hat{w}_{t-1} \approx w_{t-1}$  satisfying  $\hat{V}_{w_0}(\hat{w}_{t-1}) - \hat{V}_{w_0}(w_{t-1}) \leq \frac{\varphi}{\alpha}$  and  $\|\hat{w}_{t-1} - w_{t-1}\| \leq \frac{\varphi}{LD}$ 
3    $w_t^* \leftarrow \arg \min \left\{ \langle \text{clip}(\eta \tilde{g}_{w_0}(\hat{w}_{t-1}) - \eta g(w_0)), w \rangle + \eta \Upsilon(w) + \frac{\eta \alpha}{2} \hat{V}_{w_0}(w) + \hat{V}_{w_{t-1}}(w) \right\}$ 
4    $w_t \approx w_t^*$  satisfying  $\max_u [\hat{V}_{w_t}(u) - \hat{V}_{w_t^*}(u)] \leq \frac{\varphi}{1 + \sqrt{\mu^x \mu^y}}$ ,  $\hat{V}_{w_0}(w_t) - \hat{V}_{w_0}(w_t^*) \leq \frac{\varphi}{\alpha}$ , and
       $\hat{V}_{z'}(w_t) - \hat{V}_{z'}(w_t^*) \leq \frac{\varphi}{\sqrt{\mu^x \mu^y}}$ 
5 return  $\tilde{w} \approx \frac{1}{T} \sum_{t=1}^T w_t$  satisfying  $\|\tilde{w} - \frac{1}{T} \sum_{t=1}^T w_t\| \leq \frac{\varphi}{LD}$ ,  $\max_u [\hat{V}_{\tilde{w}}(u) - \hat{V}_{\tilde{w}}(u)] \leq \frac{\varphi}{\sqrt{\mu^x \mu^y}}$ ,
       $\hat{V}_{w'}(\tilde{w}) - \hat{V}_{w'}(\bar{w}) \leq \frac{\varphi}{\sqrt{\mu^x \mu^y}}$ , and  $\|w_t - w_t^*\| \leq \frac{\varphi}{2LD}$ 

```

---

**Corollary 1.** Let  $(\mathcal{Z}, \|\cdot\|, r, \Theta, \text{clip})$  be any local norm setup. Let  $w_0 \in \mathcal{Z}$ ,  $\varepsilon_{\text{inner}} > 0$ , and  $\tilde{g}_{w_0}$  be an  $L$ -centered-local estimator for some  $L \geq \alpha \geq \varepsilon_{\text{inner}}$ . Assume the problem has bounded domain size  $\max_{z \in \mathcal{Z}} \|z\| \leq D$ ,  $g$  is  $L$ -Lipschitz, i.e.  $\|g(z) - g(z')\|_* \leq L \|z - z'\|$ , that  $g$  is  $LD$ -bounded, i.e.  $\max_{z \in \mathcal{Z}} \|g(z)\|_* \leq LD$ , and  $\hat{w}_0 = w_0$ . Then, for  $\eta = \frac{\alpha}{10L^2}$ ,  $T \geq \frac{8}{\eta\alpha} \geq \frac{60L^2}{\alpha^2}$ ,  $\varphi = \frac{\varepsilon_{\text{inner}}}{10}$ , Algorithm 4 outputs a point  $\hat{w} \in \mathcal{Z}$  such that

$$\mathbb{E} \max_{u \in \mathcal{Z}} [\langle g(\tilde{w}) + \nabla \Upsilon(\tilde{w}), \tilde{w} - u \rangle - \alpha V_{w_0}(u)] \leq \varepsilon_{\text{inner}}, \quad (104)$$

i.e. Algorithm 4 is an  $(\alpha, \varepsilon_{\text{inner}})$ -relaxed proximal oracle.

*Proof sketch.* Note that the only change is in the definition of the regularized mirror descent step with extra composite terms

$$w_t^* \leftarrow \arg \min \left\{ \langle \text{clip}(\eta \tilde{g}_{w_0}(\hat{w}_{t-1}) - \eta g(w_0)), w \rangle + \eta \Upsilon(w) + \frac{\eta \alpha}{2} \hat{V}_{w_0}(w) + \hat{V}_{w_{t-1}}(w) \right\}.$$

Denote  $\nabla \Upsilon(w) = (\mu^x \nabla \phi(w^x), \mu^y \nabla \psi(w^y))$ , so that for the final regret bound there are two additional error terms. The first term comes from the error in regularized mirror descent steps via (denoting  $z' = (x', y')$ )

$$\begin{aligned} & \frac{1}{T} \sum_{t \in [T]} [-\langle \nabla \Upsilon(w_t^*), w_t^* - u \rangle + \langle \nabla \Upsilon(w_t), w_t - u \rangle] \\ & \leq \frac{\sqrt{\mu^x \mu^y}}{T} \sum_{t \in [T]} \left( \hat{V}_{z'}(w_t) - \hat{V}_{z'}(w_t^*) + \hat{V}_{w_t}(u) - \hat{V}_{w_t^*}(u) \right) \leq 2\varphi \end{aligned}$$

following the approximation guarantee in Line 4. The other term comes from averaging error. Denote the true average iterate by  $\bar{w} := \frac{1}{T} \sum_{t \in [T]} w_t$ . We have  $\forall u \in \mathcal{Z}$ ,

$$\begin{aligned} \langle g(\tilde{w}), \tilde{w} - u \rangle - \frac{1}{T} \sum_{t \in [T]} \langle g(w_t), w_t - u \rangle &= -\langle g(\tilde{w}), u \rangle - \langle g(\bar{w}), \bar{w} - u \rangle \\ &= \langle g(\bar{w}) - g(\tilde{w}), u \rangle \leq \varphi, \end{aligned}$$

and also

$$\begin{aligned}
\langle \nabla \Upsilon(\tilde{w}), \tilde{w} - u \rangle &= \langle \nabla \Upsilon(\tilde{w}) - \nabla \Upsilon(\bar{w}), \tilde{w} - u \rangle + \langle \nabla \Upsilon(\bar{w}), \tilde{w} - \bar{w} \rangle + \langle \nabla \Upsilon(\bar{w}), \bar{w} - u \rangle \\
&\stackrel{(i)}{=} \sqrt{\mu^x \mu^y} \left( -\hat{V}_{\bar{w}}(u) + \hat{V}_{\bar{w}}(u) + \hat{V}_{\bar{w}}(\tilde{w}) \right) + \langle \nabla \Upsilon(\bar{w}), \tilde{w} - \bar{w} \rangle + \langle \nabla \Upsilon(\bar{w}), \bar{w} - u \rangle \\
&\stackrel{(ii)}{=} \sqrt{\mu^x \mu^y} \left( -\hat{V}_{\bar{w}}(u) + \hat{V}_{\bar{w}}(u) + \hat{V}_{w'}(\tilde{w}) - \hat{V}_{w'}(\bar{w}) \right) + \langle \nabla \Upsilon(\bar{w}), \bar{w} - u \rangle, \\
&\stackrel{(iii)}{\leq} 2\varphi + \langle \nabla \Upsilon(\bar{w}), \bar{w} - u \rangle \\
&\stackrel{(iv)}{\leq} 2\varphi + \frac{1}{T} \sum_{t \in [T]} \langle \nabla \Upsilon(w_t), w_t - u \rangle.
\end{aligned}$$

where we use (i) the three-point property of Bregman divergence, (ii) the fact that  $\hat{V}_{\bar{w}}(\tilde{w}) + \langle \nabla \Upsilon(\bar{w}), \tilde{w} - \bar{w} \rangle = \hat{V}_{w'}(\tilde{w}) - \hat{V}_{w'}(\bar{w})$  again by the three-point property, (iii) the approximation guarantee of Line 5, and (iv) the fact that  $\langle \nabla \Upsilon(w), w - u \rangle$  is convex in  $w$  for our choices of  $\Upsilon$ . Hence incorporating the above extra error terms into the regret bound yields the conclusion, as  $10\varphi = \varepsilon_{\text{inner}}$  by our choice of  $\varphi$ .  $\square$

## E.2.2 Changes to implementation

Broadly speaking, all of these modifications can easily be handled via appropriate changes to the initial data given to our data structures `CenteredIterateMaintainer2` and `ApproxExpMaintainer`. We discuss general formulations of iterations with these modifications in both simplices and Euclidean balls, and provide appropriate modifications to the initial data given to our data structures. Finally, it is simple to check that all relevant parameters are still bounded by a polynomial in the dimensions of variables, so no additional cost due to the data structure is incurred. For simplicity here we only consider for the  $x$ -block when  $\phi^x(x) = \mu r(x)$  and remark that the case when  $\phi^x(x) = \mu V_{x'}(x)$  for some  $x'$  follows similarly.

**$\ell_1$  domains.** For this section, define a domain  $\mathcal{X} = \Delta^n$ , let  $r(x) = \sum_{j \in [n]} x_j \log x_j$  be entropy, and let  $\mu, \alpha, \eta, \rho$  be nonnegative scalar parameters. Consider a sequence of iterates of the form

$$x_{t+1} \leftarrow \arg \min_{x \in \mathcal{X}} \langle \tilde{g}_{x_0}(x_t), x \rangle + \mu r(x) + \frac{\alpha \rho}{2} V_{x_0}(x) + \frac{\rho}{\eta} V_{x_t}(x).$$

This update sequence, for the form of gradient estimator

$$\tilde{g}_{x_0}(x) = g(x_0) + b + g'(x),$$

where  $g'(x)$  is a vector with suitable sparsity assumptions depending on the point  $x$ , and  $b$  is some fixed vector, generalizes all of the settings described above used in our various relaxed proximal oracle implementations. Optimality conditions imply that the update may be rewritten as

$$x_{t+1} \leftarrow \Pi_{\Delta} \left( \exp \left( \frac{\frac{\rho}{\eta} \log x_t + \frac{\alpha \rho}{2} \log x_0 - g(x_0) - b - g'(x_t)}{\mu + \frac{\alpha \rho}{2} + \frac{\rho}{\eta}} \right) \right).$$

Thus, initializing an `ApproxExpMaintainer` instance with

$$\kappa = \frac{1}{\frac{\mu \eta}{\rho} + \frac{\alpha \eta}{2} + 1}, \quad v = \frac{\frac{\alpha \rho}{2} \log x_0 - g(x_0) - b}{\mu + \frac{\alpha \rho}{2} + \frac{\rho}{\eta}}$$

enables `DenseStep` to propagate the necessary changes to the iterate; we propagate changes due to  $g'(x_t)$  via `AddSparse` and the appropriate sparsity assumptions.

$\ell_2$  **domains.** For this section, define a domain  $\mathcal{X} = \mathbb{B}^n$ , let  $r(x) = \frac{1}{2} \|x\|_2^2$  be entropy, and let  $\mu, \alpha, \eta, \rho$  be nonnegative scalar parameters. Consider a sequence of iterates of the form

$$x_{t+1} \leftarrow \arg \min_{x \in \mathcal{X}} \langle \tilde{g}_{x_0}(x_t), x \rangle + \mu r(x) + \frac{\alpha \rho}{2} V_{x_0}(x) + \frac{\rho}{\eta} V_{x_t}(x).$$

This update sequence, for the form of gradient estimator

$$\tilde{g}_{x_0}(x) = g(x_0) + b + g'(x),$$

where  $g'(x)$  is a vector with suitable sparsity assumptions depending on the point  $x$ , and  $b$  is some fixed vector, generalizes all of the settings described above used in our various relaxed proximal oracle implementations. Optimality conditions imply that the update may be rewritten as

$$x_{t+1} \leftarrow \Pi_{\mathbb{B}^n} \left( \frac{\frac{\rho}{\eta} x_t + \frac{\alpha \rho}{2} x_0 - g(x_0) - b - g'(x_t)}{\mu + \frac{\alpha \rho}{2} + \frac{\rho}{\eta}} \right).$$

Thus, initializing an `CenteredIterateMaintainer` instance with

$$v = \frac{\frac{\alpha \rho}{2} x_0 - g(x_0) - b}{\mu + \frac{\alpha \rho}{2} + \frac{\rho}{\eta}}$$

enables `AddDense`, `Scale`, and `GetNorm` to propagate the necessary changes to the iterate; we propagate changes due to  $g'(x_t)$  via `AddSparse` and the appropriate sparsity assumptions.

## F Deferred proofs from Section 6

### F.1 Proofs from Section 6.1

*Proof of Lemma 10.* We consider the following  $(\mu, \mu)$ -strongly monotone problem, for various levels of  $\mu$ :

$$\max_{x \in \mathbb{B}^n} \min_{y \in \Delta_m} f_\mu(x, y) := y^\top \tilde{A}x + y^\top b + \mu \sum_{i \in [m]} [y]_i \log[y]_i - \frac{\mu}{2} \|x\|_2^2.$$

We claim we can implement an  $(\alpha, \varepsilon)$ -relaxed proximal oracle for this problem in time

$$\tilde{O} \left( \frac{\left( L_{\text{co}}^{2,1} \right)^2}{\alpha^2} \right).$$

The oracle is a composite implementation of Algorithm 3 as in Algorithm 4, using the estimator of Appendix D.3. By an application of Proposition 6, the overall complexity of solving this problem is (by choosing the optimal  $\alpha$ , and overloading the constant  $L_{\text{co}}^{2,1}$  to be with respect to  $\tilde{A}$ ):

$$\tilde{O} \left( \left( \text{nnz} + \frac{\left( L_{\text{co}}^{2,1} \right)^2}{\alpha^2} \right) \frac{\alpha}{\mu} \right) = \tilde{O} \left( \text{nnz} + \frac{\sqrt{\text{nnz}} \cdot L_{\text{co}}^{2,1}}{\mu} \right).$$

By conducting a line search over the parameter  $\mu$  via repeatedly halving, the total cost of solving each of these problems is dominated by the last setting, wherein  $\mu = \Theta(r^*/\log m)$ , and  $R/\mu = \tilde{O}(\rho)$ ; here, we recall that we rescaled  $\tilde{A}$  so that  $L_{\text{co}}^{2,1} = O(R)$ . We defer details of the line search procedure to Lemma C.3 of Allen-Zhu et al. [1].  $\square$

*Proof of Theorem 3.* We solve the problem (58) to duality gap  $\epsilon\hat{r}/8 \leq \epsilon r^*$ , using the algorithm of Appendix D.3 for  $\ell_2$ - $\ell_1$  games. The complexity of this algorithm is (choosing  $\alpha$  optimally)

$$\tilde{O} \left( \left( \text{nnz}(\tilde{A}) + \frac{(L_{\text{co}}^{2,1})^2}{\alpha^2} \right) \cdot \frac{\alpha}{\epsilon\hat{r}} \right) = \tilde{O} \left( \text{nnz} + \frac{\rho\sqrt{\text{nnz}} \cdot L_{\text{co}}^{2,1}}{\epsilon} \right),$$

as claimed. Here, we used that  $\tilde{A}$  is a rescaling of  $A$  by  $2R$ , and  $\hat{r}$  is a constant multiplicative approximation of  $r$ . The approximate solution  $(x_{\epsilon'}, y_{\epsilon}^*)$  obtains the requisite duality gap in expectation; Markov's inequality implies that with logarithmic overhead in the runtime, we can obtain a pair of points satisfying with high probability

$$\max_x f(x, y_{\epsilon'}^*) - \min_y f(x_{\epsilon'}, y) = \max_x f(x, y_{\epsilon'}^*) - f(x^*, y^*) + f(x^*, y^*) - \min_y f(x_{\epsilon'}, y) \leq \epsilon'.$$

Because  $y^*$  is the best response to  $x^*$ , we have  $f(x^*, y_{\epsilon'}^*) \geq f(x^*, y^*)$ , which implies

$$\max_x f(x, y_{\epsilon'}^*) - f(x^*, y^*) = \max_x f(x, y_{\epsilon'}^*) - f(x^*, y_{\epsilon'}^*) + f(x^*, y_{\epsilon'}^*) - f(x^*, y^*) \geq 0.$$

Combining yields  $f(x^*, y^*) - \min_y f(x_{\epsilon'}, y) \leq \epsilon' \leq \epsilon r^*$ , so since  $f(x^*, y^*) = r^*$ , rearranging implies  $\min_y f(x_{\epsilon'}, y) \geq r^* - \epsilon' \geq (1 - \epsilon)r^*$ . Thus,  $x_{\epsilon'}$  is an  $\epsilon$ -approximate solution for Max-IB.  $\square$

## F.2 Proofs from Section 6.2

*Proof of Lemma 11.* If  $(x', y')$  is an approximately optimal solution with duality gap  $\epsilon/16$  for (61), by definition

$$\max_{y \in \Delta^m} f_{\epsilon'}(x', y) - \min_{x \in \mathbb{R}^n} f_{\epsilon'}(x, y') \leq \frac{\epsilon}{16}.$$

Therefore, the following sequence of inequalities hold:

$$\begin{aligned} \max_{y \in \Delta^m} f(x', y) - \min_{x \in \mathbb{R}^n} f(x, y') &= \left( \max_{y \in \Delta^m} f(x', y) - \max_{y \in \Delta^m} f_{\epsilon'}(x', y) \right) \\ &+ \left( \max_{y \in \Delta^m} f_{\epsilon'}(x', y) - \min_{x \in \mathbb{R}^n} f_{\epsilon'}(x, y') \right) + \left( \min_{x \in \mathbb{R}^n} f_{\epsilon'}(x, y') - \min_{x \in \mathbb{R}^n} f(x, y') \right) \\ &\stackrel{(i)}{\leq} \left( \max_{y \in \Delta^m} f(x', y) - \max_{y \in \Delta^m} f_{\epsilon'}(x', y) \right) + \frac{\epsilon}{16} + \left( \min_{x \in \mathbb{R}^n} f_{\epsilon'}(x, y') - \min_{x \in \mathbb{R}^n} f(x, y') \right) \\ &\stackrel{(ii)}{\leq} \frac{\epsilon}{32} + \frac{\epsilon}{16} + \frac{\epsilon}{32} = \frac{\epsilon}{8}. \end{aligned}$$

In (i), we used the fact that the pair  $(x', y')$  has good duality gap with respect to  $f_{\epsilon'}$ , and in (ii) we used that for the first summand,  $f_{\epsilon'}(x', \cdot)$  approximates  $f(x', \cdot)$  to an additive  $\epsilon/32$ , and for the third summand,  $-\epsilon' \sum_{i \in [m]} [y']_i \log[y']_i$  is bounded by  $\epsilon/32$ , and all other terms cancel.  $\square$

## F.3 Proofs from Section 6.3

*Proof of Lemma 12.* At optimality for (62), it holds that

$$\begin{cases} y_{x'}^* = \frac{1}{\beta}(Ax_{x'}^* - b) \\ x_{x'}^* = x' - \frac{1}{\beta}A^\top y_{x'}^* \end{cases}.$$

By substituting  $y_{x'}^*$  and rearranging terms we get

$$\left(I + \frac{1}{\beta^2} A^\top A\right) (x_{x'}^* - x^*) = x' - x^*,$$

which in turn gives

$$\|x_{x'}^* - x^*\|_2 = \left\| \left(I + \frac{1}{\beta^2} A^\top A\right)^{-1} (x' - x^*) \right\|_2 \leq \frac{1}{1 + \mu/\beta^2} \|x' - x^*\|_2.$$

For the last inequality we use the fact that

$$\left\| I + \frac{1}{\beta^2} A^\top A \right\|_2^{-1} = \lambda_{\min} \left( I + \frac{1}{\beta^2} A^\top A \right)^{-1} = \frac{1}{1 + \mu/\beta^2},$$

by the definition of  $\mu$  and since  $I$  and  $A^\top A$  commute.  $\square$

**Theorem 5.** Given data matrix  $A \in \mathbb{R}^{m \times n}$ , vector  $b \in \mathbb{R}^m$ , and desired accuracy  $\epsilon \in (0, 1)$ , assuming  $A^\top A \succeq \mu I$  for  $\mu > 0$ , Algorithm 5 outputs an expected  $\epsilon$ -accurate solution  $\tilde{x}$ , i.e.

$$\mathbb{E} [\|\tilde{x} - x^*\|_2] \leq \epsilon,$$

and runs in time

$$\tilde{O} \left( \text{nnz} + \sqrt{\text{nnz}} \cdot \frac{\max \left\{ \sqrt{\sum_i \|A_{i:}\|_1^2}, \sqrt{\sum_j \|A_{:j}\|_1^2} \right\}}{\sqrt{\mu}} \right).$$

*Proof.* We first prove correctness. We bound the progress from  $x^{(h)}$  to  $x^{(h+1)}$ , for some  $h \in [H]$ , by

$$\frac{1}{2} \|x^{(h+1)} - x^*\|_2^2 \leq \|x^{(h+1)} - x_{x^{(h)}}^*\|_2^2 + \|x_{x^{(h)}}^* - x^*\|_2^2 \leq 2V_{z^{(h+1)}}(z_{x^{(h)}}^*) + \|x_{x^{(h)}}^* - x^*\|_2^2. \quad (105)$$

The first inequality used  $\|a + b\|_2^2 \leq 2\|a\|_2^2 + 2\|b\|_2^2$ , and the second used the definition of the divergence in the  $\ell_2$ - $\ell_2$  setup. Next, choosing a sufficiently large value of  $K = \tilde{O}(\beta/\mu)$ , we use Proposition 6 to obtain a point  $z^{(h+1)}$  satisfying

$$V_{z^{(h+1)}}(z_{x^{(h)}}^*) \leq \frac{\epsilon^2}{80} V_{z^{(h)}}(z_{x^{(h)}}^*) \leq \frac{\epsilon^2}{40} V_{z^{(h)}}(z^*) + \frac{\epsilon^2}{40} V_{z^*}(z_{x^{(h)}}^*). \quad (106)$$

Further, using Lemma 12 with  $x' = x^{(h)}$ ,  $\beta = \sqrt{\mu}$  yields

$$\|x_{x^{(h)}}^* - x^*\|_2 \leq \frac{1}{2} \|x^{(h)} - x^*\|_2. \quad (107)$$

Plugging these two bounds into (105), and using the form of the divergence in the  $\ell_2$ - $\ell_2$  setup,

$$\begin{aligned} \frac{1}{2} \|x^{(h+1)} - x^*\|_2^2 &\stackrel{(106)}{\leq} \frac{\epsilon^2}{20} V_{z^{(h)}}(z^*) + \frac{\epsilon^2}{20} V_{z^*}(z_{x^{(h)}}^*) + \|x_{x^{(h)}}^* - x^*\|_2^2 \\ &\stackrel{(107)}{\leq} \frac{1}{2} \left( \frac{\epsilon^2}{20} + \frac{\epsilon^2}{20} + \frac{1}{2} \right) \|x^{(h)} - x^*\|_2^2 + \frac{\epsilon^2}{40} \left( \|y^{(h)} - y^*\|_2^2 + \|y_{x^{(h)}}^* - y^*\|_2^2 \right) \\ &\leq \frac{3}{4} \cdot \frac{1}{2} \|x^{(h)} - x^*\|_2^2 + \frac{\epsilon^2}{5}. \end{aligned} \quad (108)$$



---

**Algorithm 5:** Coordinate variance reduced method for linear regression

---

**Input:** Matrix  $A \in \mathbb{R}^{m \times n}$  with  $i$ th row  $A_{i:}$  and  $j$ th column  $A_{:j}$ , vector  $b \in \mathbb{R}^m$ , accuracy  $\epsilon$

**Output:** A point  $\tilde{x}$  with  $\|\tilde{x} - x^*\|_2 \leq \epsilon$

```
1  $L \leftarrow \max \left\{ \sqrt{\sum_i \|A_{i:}\|_1^2}, \sqrt{\sum_j \|A_{:j}\|_1^2} \right\}, \alpha \leftarrow L/\sqrt{nnz}, \beta = \sqrt{\mu}, \eta \leftarrow \frac{\alpha}{4L^2}$ 
2  $T \leftarrow \left\lceil \frac{4}{\eta\alpha} \right\rceil, K \leftarrow \tilde{O}(\alpha/\beta), H = \tilde{O}(1), z^{(0)} = (x^{(0)}, y^{(0)}) \leftarrow (\mathbf{0}_n, \mathbf{0}_m), (z_0^x, z_0^y) \leftarrow (\mathbf{0}_n, \mathbf{0}_m)$ 
3 for  $h = 1, 2, \dots, H$  do
4   for  $k = 1, \dots, K$  do
5      $\triangleright$  Relaxed oracle query:
6      $(x_0, y_0) \leftarrow (z_{k-1}^x, z_{k-1}^y), (g_0^x, g_0^y) \leftarrow (A^\top y_0 + \beta(x_0 - x^{(h-1)}), -Ax_0 + \beta y_0)$ 
7     for  $t = 1, \dots, T$  do
8        $\triangleright$  Gradient estimation:
9       Sample  $i \sim p$  where  $p_i = \frac{([y_{t-1}]_i - [y_0]_i)^2}{\|y_{t-1} - y_0\|_2^2}$ 
10      Sample  $j \sim q$  where  $q_j = \frac{([x_{t-1}]_j - [x_0]_j)^2}{\|x_{t-1} - x_0\|_2^2}$ 
11      Set  $\tilde{g}_{t-1} = g_0 + \left( A_{i:} \frac{[y_{t-1}]_i - [y_0]_i}{p_i}, -A_{:j} \frac{[x_{t-1}]_j - [x_0]_j}{q_j} \right)$ 
12       $\triangleright$  Mirror descent step:
13       $x_t \leftarrow \frac{1}{1 + \eta\alpha/2} \left( x_{t-1} + \frac{\eta\alpha}{2} x_0 - \eta \tilde{g}_{t-1}^x \right)$ 
14       $y_t \leftarrow \Pi_Y \left( \frac{1}{1 + \eta\alpha/2} \left( y_{t-1} + \frac{\eta\alpha}{2} y_0 - \eta \tilde{g}_{t-1}^y \right) \right) \quad \triangleright \Pi_Y(v) = \frac{v}{\max\{1, \|v\|_2\}}$ 
15       $z_{k-1/2} \leftarrow \frac{1}{T} \sum_{t=1}^T (x_t, y_t)$ 
16       $\triangleright$  Extragradient step:
17       $z_k^x \leftarrow \frac{\alpha}{\alpha + 2\beta} z_{k-1}^x + \frac{2\beta}{\alpha + 2\beta} z_{k-1/2}^x - \frac{1}{\alpha + 2\beta} \left( A^\top z_{k-1/2}^y + \beta(z_{k-1/2}^x - x^{(h-1)}) \right)$ 
18       $z_k^y \leftarrow \Pi_Y \left( \frac{\alpha}{\alpha + 2\beta} z_{k-1}^y + \frac{2\beta}{\alpha + 2\beta} z_{k-1/2}^y + \frac{1}{\alpha + 2\beta} \left( Az_{k-1/2}^x - \beta z_{k-1/2}^y \right) \right)$ 
19       $\triangleright$  Reshifting the oracle:
20       $z^{(h)} = (x^{(h)}, y^{(h)}) \leftarrow z_K = (z_K^x, z_K^y)$ 
21 return  $\tilde{x} \leftarrow x^{(H)}$ 
```

---

In the last inequality we use the conditions that  $\epsilon \in (0, 1)$  and  $\mathcal{Y} = \mathbb{B}^m$ . Recursively applying this bound for  $h \in [H]$ , and for a sufficiently large value of  $H = \tilde{O}(1)$ , we have the desired

$$\|x^{(H)} - x^*\|_2^2 \leq \left(\frac{3}{4}\right)^H \|x^{(0)} - x^*\|_2^2 + \frac{4\epsilon^2}{5} \leq \epsilon^2.$$

To bound the runtime, recall the inner loop runs for  $T = O((L_{\text{co}}^{2,2})^2/\alpha^2)$  iterations, each costing constant time, and the outer loop runs for  $K = \tilde{O}(\alpha/\beta)$  iterations, each costing  $O(T + \text{nnz})$ . Finally, since  $H = \tilde{O}(1)$ , the overall complexity of the algorithm is

$$\tilde{O}\left(\left(\text{nnz} + \frac{(L_{\text{co}}^{2,2})^2}{\alpha^2}\right) \frac{\alpha}{\beta}\right).$$

Choosing  $\alpha = \max\{L_{\text{co}}^{2,2}/\sqrt{\text{nnz}}, \beta\}$  optimally and substituting

$$\beta = \sqrt{\mu}, \quad L_{\text{co}}^{2,2} = \max\left\{\sqrt{\sum_i \|A_{i:}\|_1^2}, \sqrt{\sum_j \|A_{:j}\|_1^2}\right\},$$

we have the desired runtime bound on Algorithm 5.  $\square$

## G IterateMaintainer<sub>2</sub>: numerical stability and variations

### G.1 Numerical stability of IterateMaintainer<sub>1</sub>.

We discuss the implementation of a numerically stable version of IterateMaintainer<sub>1</sub>, and the complexity of its operations, for use in our sublinear algorithms in Section 4.1 and Section C.2. We discuss this implementation for a simplex block, e.g. a simplex variable of dimension  $n$ , as for an  $\ell_2$  geometry numerical stability is clear. The main modifications we make are as follow.

- We reinitialize the data structure whenever the field  $\nu$  grows larger than some fixed polynomial in  $n$ , or if  $n/2$  iterations have passed.
- We track the coordinates modified between restarts.
- Every time we reinitialize, we maintain the invariant that the multiplicative range of coordinates of  $x$  is bounded by a polynomial in  $n$ , i.e.  $\max_j x_j / \min_j x_j$  is bounded by some fixed polynomial in  $n$ . We will implement this via an explicit truncation, and argue that such an operation gives negligible additive error compared to the accuracy of the algorithm.
- We implicitly track the set of truncated coordinates at each data structure restart. We do so by explicitly tracking the set of non-truncated coordinates whenever a truncation operation happens (see the discussion below), in constant amortized time.

We now discuss the complexity and implementation of these restarts. First, note that  $\nu$  can never decrease by more than a multiplicative polynomial in  $n$  between restarts, because of nonnegativity of the exponential, the fact that the original range at the time of the last restart is multiplicatively bounded, and we restart every time half the coordinates have been touched. Thus, the only source of numerical instability comes from when  $\nu$  grows by more than a multiplicative polynomial in  $n$ . Suppose this happens in  $\tau$  iterations after the restart. Then,

- If  $\tau < n/2$ , we claim we can implement the restart in  $O(\tau)$ , so the amortized cost per iteration is  $O(1)$ . To see this, for every coordinate touched in these  $\tau$  iterations, we either keep or explicitly truncate if the coordinate is too small. For every coordinate not touched in these  $\tau$  iterations, the relative contribution is at most inverse polynomial in  $n$ ; we truncate all such coordinates. Then, we compute the normalization constant according to all non-truncated coordinates, such that the value of all truncated coordinates is set to a fixed inverse polynomial in  $n$ . We can implement this by implicitly keeping track of the set of truncated coordinates as well as their contribution to the normalization factor, and explicitly setting their value in the data structure when they are updated by **AddSparse**. Overall, this does not affect the value of the problem by more than a small multiple of  $\epsilon$ , by our assumptions on  $L_{rc}/\epsilon$ . To see that we can track the non-truncated coordinates explicitly, we note that it is a subset of the at most  $\tau$  coordinates that were touched, so this can be done in constant amortized time.
- If  $\tau = n/2$ , we claim we can implement the restart in  $O(n)$ , so the amortized cost per iteration is  $O(1)$ . This is clear: we can do so by explicitly recomputing all coordinates, and truncating any coordinates which have become too small.

We describe how the data structure implements this through its maintained fields: for non-truncated coordinates, we do not do anything other than change the scaling factor  $\nu$ , and for truncated coordinates, we reset the values of  $u, u'$  in that coordinate appropriately once they have been sparsely updated. Overall, this does not affect the amortized runtime of our algorithm.

## G.2 WeightedIterateMaintainer<sub>2</sub>

In this section, we give implementation details for a weighted generalization of **IterateMaintainer<sub>2</sub>**, which we will call **WeightedIterateMaintainer<sub>2</sub>**. It is used in Section C.2, when using the sampling distribution (87). At initialization, **WeightedIterateMaintainer<sub>2</sub>** is passed an additional parameter  $w \in \mathbb{R}_{\geq 0}^n$ , a nonnegative weight vector. We let

$$\langle u, v \rangle_w := \sum_{j \in [n]} [w]_j [u]_j [v]_j, \|v\|_w := \sqrt{\langle v, v \rangle_w}.$$

**WeightedIterateMaintainer<sub>2</sub>** supports all the same operations as **IterateMaintainer<sub>2</sub>**, with two differences:

- For the current iterate  $x$ , **WeightedIterateMaintainer<sub>2</sub>**.Norm() returns weighted norm  $\|x\|_w$ .
- For the current iterate  $x$ , **WeightedIterateMaintainer<sub>2</sub>**.Sample() returns a coordinate  $j$  with probability proportional to  $[w]_j [x]_j^2$ .

Similarly to **IterateMaintainer<sub>2</sub>**, **WeightedIterateMaintainer<sub>2</sub>** maintains the following fields.

- Scalars  $\xi_u, \xi_v, \sigma_u, \sigma_v, \iota, \nu$
- Vectors  $u, u', v, w$
- Precomputed value  $\|v\|_w^2$ .

We maintain the following invariants on the data structure fields at the end of every operation:

- $x = \xi_u u + \xi_v v$ , the internal representation of  $x$

- $s = v + \sigma_u u + \sigma_v v$ , the internal representation of running sum  $s$
- $\iota = \langle x, v \rangle_w$ , the weighted inner product of the iterate with fixed vector  $v$
- $\nu = \|x\|_w$ , the weighted norm of the iterate

To support sampling, our data structure also maintains a binary tree  $\text{dist}_x$  of depth  $O(\log n)$ . For the node corresponding to  $S \subseteq [n]$  (where  $S$  may be a singleton), we maintain

- $\sum_{j \in S} [w]_j [u]_j^2$ ,  $\sum_{j \in S} [w]_j [u]_j [v]_j$ ,  $\sum_{j \in S} [w]_j [v]_j^2$

We now give the implementation of the necessary operations for **WeightedIterateMaintainer<sub>2</sub>**, giving additional proofs of correctness when applicable.

### Initialization.

- **Init**( $x_0, v, w$ ). Runs in time  $O(n)$ .
  1.  $(\xi_u, \xi_v, u) \leftarrow (1, 0, x_0)$ .
  2.  $(\sigma_u, \sigma_v, u') \leftarrow (0, 0, \mathbf{0}_n)$ .
  3.  $(\iota, \nu) \leftarrow (\langle x_0, v \rangle_w, \|x_0\|_w)$ .
  4. Compute and store  $\|v\|_w^2$ .
  5. Initialize  $\text{dist}_x$ , storing the relevant sums in each internal node.

**Updates.** **Scale**( $c$ ) and **UpdateSum**() follow identically to the analysis of **IterateMaintainer<sub>2</sub>**.

- **AddSparse**( $j, c$ ):  $[x]_j \leftarrow [x]_j + c$ . Runs in time  $O(\log n)$ .
  1.  $u \leftarrow u + \frac{c}{\xi_u} e_j$ .
  2.  $u' \leftarrow u' - \frac{c \sigma_u}{\xi_u} e_j$ .
  3.  $\nu \leftarrow \sqrt{\nu^2 + 2c[w]_j [\xi_u u + \xi_v v]_j + c^2 [w]_j}$ .
  4.  $\iota \leftarrow \iota + c[w]_j [v]_j$ .
  5. For internal nodes of  $\text{dist}_x$  on the path from leaf  $j$  to the root, update  $\sum_{j \in S} [w]_j [u]_j^2$ ,  $\sum_{j \in S} [w]_j [u]_j [v]_j$  appropriately.
- **AddDense**( $c$ ):  $x \leftarrow x + cv$ . Runs in time  $O(1)$ .
  1.  $\xi_v \leftarrow \xi_v + c$ .
  2.  $\nu \leftarrow \sqrt{\nu^2 + 2c\iota + c^2 \|v\|_w^2}$ .
  3.  $\iota \leftarrow \iota + c \|v\|_w^2$ .

We demonstrate that the necessary invariants on  $\iota, \nu$  are preserved. Regarding correctness of **AddSparse**, the updates to  $u$  and  $u'$  are identical to in the analysis of **IterateMaintainer<sub>2</sub>**. Next, because only  $[x]_j$  changes, the updates to  $\nu, \iota$  are correct respectively by

$$\begin{aligned} [w]_j \cdot [\xi_u u + \xi_v v + c]_j^2 &= [w]_j \cdot ([\xi_u u + \xi_v v]_j^2 + 2c[\xi_u u + \xi_v v]_j + c^2), \\ [w]_j \cdot ([\xi_u u + \xi_v v + c]_j) \cdot [v]_j &= [w]_j \cdot ([\xi_u u + \xi_v v]_j \cdot [v]_j + c[v]_j). \end{aligned}$$

Regarding correctness of **AddDense**,

$$\begin{aligned} \|x + cv\|_w^2 &= \nu^2 + 2c\iota + c^2 \|v\|_w^2, \\ \langle x + cv, v \rangle_w &= \iota + c \|v\|_w^2. \end{aligned}$$

Here, we used that the invariants  $\nu = \|x\|_w$  and  $\iota = \langle x, v \rangle_w$  held.

**Queries.** `Get(j)` and `GetSum(j)` follow identically to the analysis of `IterateMaintainer2`.

- `Norm()`: Return  $\|x\|_w$ . Runs in time  $O(1)$ .

1. Return  $\nu$ .

**Sampling.** To support `Sample`, we must produce a coordinate  $j$  with probability proportional to  $[w]_j[x]_j^2$ . To do so, we recursively perform the following procedure, where the recursion depth is at most  $O(\log n)$ , starting at the root node and setting  $S = [n]$ : the proof of correctness is identical to the proof in the analysis of `IterateMaintainer2.Sample()`.

1. Let  $S_1, S_2$  be the subsets of coordinates corresponding to the children of the current node.
2. Using scalars  $\xi_u, \xi_v$ , and the maintained  $\sum_{j \in S_i} [w]_j[u]_j^2$ ,  $\sum_{j \in S_i} [w]_j[u]_j[v]_j$ ,  $\sum_{j \in S_i} [w]_j[v]_j^2$ , compute  $\sum_{j \in S_i} [w]_j[x]_j^2 = \sum_{j \in S_i} [w]_j[\xi_u u + \xi_v v]_j^2$  for  $i \in \{1, 2\}$ .
3. Sample a child  $i \in \{1, 2\}$  of the current node proportional to  $\sum_{j \in S_i} [w]_j[x]_j^2$  by flipping an appropriately biased coin. Set  $S \leftarrow S_i$ .

### G.3 CenteredIterateMaintainer<sub>2</sub>

In this section, we give implementation details for a generalization of `WeightedIterateMaintainer2`, which we call `CenteredIterateMaintainer2`. It is used in Section D.3, when using the sampling distributions (98) and (99). At initialization, `CenteredIterateMaintainer2` is passed an additional parameter  $x_0 \in \mathbb{R}^n$ , a reference point. `CenteredIterateMaintainer2` supports all the same operations as `WeightedIterateMaintainer2`, with two differences:

- For the current iterate  $x$ , `CenteredIterateMaintainer2.Sample()` returns a coordinate  $j$  with probability proportional to  $[w]_j[x - x_0]_j^2$ .
- `CenteredIterateMaintainer2` supports querying  $\|x - x_0\|_w^2$  in constant time.

Because all the other operations, fields, and invariants supported and maintained by the data structure are exactly the same as `IterateMaintainer2`, we only discuss the changes made to the binary tree  $\text{dist}_x$  in this section for brevity. In particular, to support sampling, our data structure also maintains a binary tree  $\text{dist}_x$  of depth  $O(\log n)$ . For the node corresponding to  $S \subseteq [n]$  (where  $S$  may be a singleton), we maintain

- $\sum_{j \in S} [w]_j[u]_j^2$ ,  $\sum_{j \in S} [w]_j[u]_j[v]_j$ ,  $\sum_{j \in S} [w]_j[v]_j^2$
- $\sum_{j \in S} [w]_j[x_0]_j^2$ ,  $\sum_{j \in S} [w]_j[u]_j[x_0]_j$ ,  $\sum_{j \in S} [w]_j[v]_j[x_0]_j$

At initialization, `CenteredIterateMaintainer2` creates this data structure and stores the relevant sums in each internal node. Upon modifications to  $u$  due to updates of the form `AddSparse(j, c)`, `CenteredIterateMaintainer2` propagates the changes along internal nodes of  $\text{dist}_x$  on the path from leaf  $j$  to the root. Thus, using these maintained values and the stored values  $\xi_u, \xi_v$ , it is clear that for any appropriate subset  $S$ , we are able to compute the quantity

$$\sum_{j \in S} [w]_j[\xi_u + \xi_v v - x_0]_j^2 = \sum_{j \in S} [w]_j (\xi_u^2 [u]_j^2 + \xi_v^2 [v]_j^2 + 2\xi_u \xi_v [u]_j [v]_j + [x_0]_j^2 + 2\xi_u [u]_j [x_0]_j + 2\xi_v [v]_j [x_0]_j)$$

in constant time, admitting the sampling oracle in time  $O(\log n)$  by propagating down the tree maintained by  $\text{dist}_x$ . This proves the desired sampling complexity. Finally, by appropriately querying the stored values in the root node, we can return  $\|x - x_0\|_w^2$  in constant time.