

Efficient Constant-Factor Approximate Enumeration of Minimal Subsets for Monotone Properties with Weight Constraints

Yasuaki Kobayashi  

Kyoto University, Kyoto, Japan

Kazuhiro Kurita  

National Institute of Informatics, Tokyo, Japan

Kunihiro Wasa  

Toyohashi University of Technology, Aichi, Japan

Abstract

A property Π on a finite set U is *monotone* if for every $X \subseteq U$ satisfying Π , every superset $Y \subseteq U$ of X also satisfies Π . Many combinatorial properties can be seen as monotone properties. The problem of finding a minimum subset of U satisfying Π is a central problem in combinatorial optimization. Although many approximate/exact algorithms have been developed to solve this kind of problem on numerous properties, a solution obtained by these algorithms is often unsuitable for real-world applications due to the difficulty of building accurate mathematical models on real-world problems. A promising approach to overcome this difficulty is to *enumerate* multiple small solutions rather than to *find* a single small solution. To this end, given a weight function $w : U \rightarrow \mathbb{N}$ and an integer k , we devise algorithms that *approximately* enumerate all minimal subsets of U with weight at most k satisfying Π for various monotone properties Π , where “approximate enumeration” means that algorithms output all minimal subsets satisfying Π whose weight at most k and may output some minimal subsets satisfying Π whose weight exceeds k but is at most ck for some constant $c \geq 1$. These algorithms allow us to efficiently enumerate minimal vertex covers, minimal dominating sets in bounded degree graphs, minimal feedback vertex sets, minimal hitting sets in bounded rank hypergraphs, etc., of weight at most k with constant approximation factors.

2012 ACM Subject Classification Mathematics of computing \rightarrow Discrete mathematics

Keywords and phrases Approximate enumeration, Output-sensitive, Monotone property, Supergraph technique

Digital Object Identifier 10.4230/LIPIcs...

1 Introduction

Let U be a finite set. A property Π on U is *monotone* if for every $X \subseteq U$ satisfying Π , every superset $Y \subseteq U$ of X also satisfies Π . Many basic combinatorial properties, such as being a spanning subgraph of a graph, the linear dependency of columns of a matrix, and being a transversal of a hypergraph, can be seen as a monotone property on suitable sets U . Thus, many combinatorial optimization problems can be formulated as a minimization problem with a monotone property over a finite set U . Due to the nature of combinatorial problems, numerous minimization problems with monotone properties, such as the minimum vertex cover problem and the minimum dominating set problem, are proven to be intractable. Hence, the concept of approximation algorithms is one of the most popular approaches to this difficulty, which aims to find a “good” solution with a provable guarantee on its weight. However, in many real-world applications, such a “good” solution may be inadequate, even if one can find a best one, due to ambiguous “true” objectives and/or informal unwritten constraints. To tackle these issues, enumerating multiple good solutions would be a promising approach. In this context, there are several attempts to enumerate multiple good solutions



© Yasuaki Kobayashi, Kazuhiro Kurita, and Kunihiro Wasa;
licensed under Creative Commons License CC-BY 4.0

Leibniz International Proceedings in Informatics

LIPICs Schloss Dagstuhl – Leibniz-Zentrum für Informatik, Dagstuhl Publishing, Germany

rather than to compute a single best solution, which have received considerable attention in the last decades.

One of the best known attempts to achieve this goal is *K-best enumeration* [23, 29, 40, 43]. An algorithm is called a *K-best enumeration algorithm* if it generates K distinct solutions and there is no solution (strictly) better than those generated by the algorithm. Obviously, the optimization counterpart corresponds to the case $K = 1$. Many K -best enumeration algorithms have been developed in the literature: E.g., spanning trees [29], s - t paths [30, 40], s - t cuts [52], and (weighted) perfect matchings [43] (See also [23], for more information). Among others, enumerating multiple solutions with some specific order has attracted special interests in the field of database research, which they call *ranked enumeration* [20, 46, 51]. When we wish to enumerate K solutions in the non-decreasing order of their quality, this is equivalent to K -best enumeration.

A common obstacle to applying these approaches to enumerate multiple (best) solutions with a monotone property Π is that the underlying minimization problem has to be tractable since we need to find an optimal solution efficiently in the first place. As in Table 1, however, many problems of finding a minimum subset satisfying Π , which we focus on in this paper, are NP-hard. One of possible solutions to avoid this obstacle is due to [3, 24, 36]. They relaxed the rigorous definition of the output order in ranked enumeration by considering an *approximation order*. More precisely, an enumeration algorithm outputs solutions in θ -approximation order for some $\theta \geq 1$ if, for every two solutions output by the algorithm, the cost of the former solution is not worse than θ times the cost of the latter solution. This notion was first introduced by Fagin et al. [24] and enables us to find an initial solution by polynomial-time approximation algorithms. In particular, Ajami and Cohen [3] devised an algorithm for enumerating (weighted) set covers in H_d -approximation order in polynomial delay, where d is the largest size of a hyperedge and H_d is the sum of the first d numbers in the harmonic series. However, the technique used in [3] may produce *non-minimal* solutions. These non-minimal solutions can be considered redundant in the sense that for a smallest solution X , there are exponentially many “approximate” solutions containing X , which can be easily obtained from X . This redundancy highly affects the overall performance of enumeration algorithms. They extended their algorithm so that it enumerates only minimal solutions in approximation order. However, the running time of this extension is no longer proven to be upper bounded by a polynomial in the number of minimal solutions. Our goal here is to develop enumeration algorithms such that the outputs satisfy the approximation quality requirement and the running time is upper bounded by the number of solutions.

1.1 Summary of our results

In this paper, given a monotone property Π on a finite set U , a weight function $w : U \rightarrow \mathbb{N}$, and a positive integer k , our aim is to design algorithms that enumerate all the *inclusion-wise minimal* subsets S of U satisfying Π whose weight $w(S)$ is at most k . Here, we define $w(S) = \sum_{e \in S} w(e)$. We measure the running time of these algorithms in an output-sensitive way (See [32, 49], for more information). However, because our primary focus of this paper is monotone properties whose minimization versions are NP-hard, there seems to be no hope of developing even a polynomial-delay or incremental-polynomial time algorithm for enumerating subsets satisfying those properties with weight at most k . Therefore, this paper introduces yet another concept to enumerate multiple good solutions.

Suppose that we are given a function $f : 2^U \rightarrow \mathbb{N}$ and a positive integer k . Let \mathcal{R} be the collection of all feasible solutions in 2^U and $\mathcal{S} = \{S \in \mathcal{R} : f(S) \leq k\}$. An enumeration algorithm \mathcal{A} *approximately enumerates* \mathcal{S} if it enumerates solutions \mathcal{R}' with $\mathcal{S} \subseteq \mathcal{R}' \subseteq \mathcal{R}$.

without duplication. In other words, we allow enumeration algorithms to output some feasible solutions in $\mathcal{R} \setminus \mathcal{S}$ but forbid to output non-feasible solutions in $2^U \setminus \mathcal{R}$. The running time of an approximate enumeration algorithm \mathcal{A} is measured by both of the input size and the cardinality of \mathcal{R}' . Moreover, to evaluate the quality of solutions enumerated by \mathcal{A} , we define the *approximation factor* of \mathcal{A} as the ratio $\max_{S \in \mathcal{R}'} \frac{f(S)}{k}$. Given this, we call \mathcal{A} is an *α -approximate enumeration algorithm* when the approximation factor of \mathcal{A} is at most α .

In this paper, we develop two frameworks for designing efficient approximate enumeration algorithms for enumerating minimal subsets satisfying Π for several monotone properties Π with constant approximation factors as shown in Theorems 4 and 5. The description of these frameworks is general, and hence we can derive approximate enumeration algorithms for many monotone properties in a unified way. We summarize some problems to which we can apply our frameworks and known approximation and enumeration (without weight constraints) results in Table 1. We would like to emphasize that our enumeration algorithms never output a non-minimal feasible solution even if its weight is at most k , and works efficiently even if k is large in contrast to parameterized enumeration algorithms [18, 25].

We mainly focus on linear weight functions, that is, the weight of a solution is defined to be the sum of weights of elements in it. However, our frameworks allow us to enumerate approximate solutions on more general weight functions. For instance, we obtain a polynomial-delay 3-approximate enumeration algorithm for minimal vertex covers with monotone submodular cost.

As further algorithmic contributions, we give polynomial-delay approximate enumeration algorithms with constant approximation factors for two specific properties, EDGE DOMINATING SET and STEINER SUBGRAPH¹. For these properties, our framework for obtaining a polynomial delay running time bound cannot be applied directly. To obtain polynomial delay bounds with constant approximation factors, we present problem-specific techniques, which would be of independent interest.

1.2 Technical overview of our framework

Although the concept of our approximate enumeration would be new, the approach to this is rather well known. We employ the *supergraph technique*, which is frequently used in designing enumeration algorithms in the literature [13, 15, 16, 35, 48]. In this technique, we consider a directed graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ whose node set \mathcal{V} corresponds to the set of solutions. The key to designing an enumeration algorithm with the supergraph technique is to ensure that, by appropriately defining the arc set \mathcal{E} , \mathcal{G} is strongly connected: If \mathcal{G} is strongly connected, one can enumerate all the nodes of \mathcal{G} by traversing its arcs from an arbitrary node. In order to define “arcs” from a solution, Cohen, Kimelfeld, and Sagiv [15] invented a general technique to ensure the strong connectivity of \mathcal{G} for enumerating maximal induced subgraphs with hereditary properties or connected hereditary properties. In their technique, they consider a subproblem of an enumeration problem, called an *input-restricted problem*, and if one can efficiently solve this subproblem, they show that the entire enumeration problem can be solved efficiently as well. In particular, if the input-restricted problem for a monotone property Π can be solved in time polynomial in the input size, then we say that Π has a *CKS property*. Note that as they used this term for hereditary properties on graphs, we slightly abuse this notion for our purpose. Very recently, Cao [13] comprehensively discussed the

¹ In our setting, every minimal Steiner subgraph is a (minimal) Steiner tree and hence our approximate enumeration algorithm enumerates (minimal) Steiner trees only.

■ **Table 1** Summary of approximation factors of known polynomial-time approximation algorithms for finding a *minimum weight* Π -set, known results for enumerating *minimal* Π -sets, and our results. The approximation factors marked by * are for unweighted graphs, and these marked by † are obtained by reducing to the minimum weight d -hitting set problem. “DelP” and “IncP” stand for “polynomial delay” and “incremental polynomial time”, respectively.

| | Property Π | approx. | enum. | Our results | |
|---------|--|----------------------------|---------------|------------------------|------|
| Sect. 4 | VERTEX COVER | 2 | DelP [50] | 3 | DelP |
| | BOUNDED DEGREE- d DELETION | $2 + \ln d$ [44] | DelP [13, 15] | $3 + \ln d$ | DelP |
| | CLUSTER DELETION | 2 [4] | DelP [13, 15] | 3 | DelP |
| | SPLIT DELETION | $2 + \varepsilon$ [22, 41] | DelP [13, 15] | $3 + \varepsilon$ | DelP |
| | PSEUDO SPLIT DELETION | 4^\dagger | DelP [13, 15] | 5 | DelP |
| | THRESHOLD DELETION | 4^\dagger | DelP [13, 15] | 5 | DelP |
| Thm. 14 | STAR FOREST EDGE DELETION | 3^\dagger | DelP | 4 | DelP |
| Thm. 17 | DOMINATING SET IN DEGREE- Δ GRAPHS | $O(\log \Delta)$ [14] | DelP [33] | $O(\log \Delta)$ | DelP |
| Cor. 10 | STAR FOREST VERTEX DELETION | 4^\dagger | IncP [13] | 6 | IncP |
| | FEEDBACK VERTEX SET | 2 [8] | DelP [48] | 4 | IncP |
| | CATERPILLAR DELETION | 7^* [45] | IncP | 9^* | IncP |
| | PLANAR- \mathcal{F} DELETION | $O(1)^*$ [26] | IncP | $O(1)^*$ | IncP |
| | TREewidth- η DELETION | $O(1)^*$ [26] | IncP | $O(1)^*$ | IncP |
| Cor. 11 | BLOCK DELETION | 4^* [1] | IncP | 6^* | IncP |
| | BICLUSTER DELETION | 4^\dagger | IncP [15] | 6 | IncP |
| | COGRAPH DELETION | 4^\dagger | DelP [11] | 6 | IncP |
| | TRIVIAALLY PERFECT DELETION | 4^\dagger | DelP [13] | 6 | IncP |
| Thm. 12 | d -HITTING SET | d [7] | IncP [10] | $\frac{(d+4)(d-1)}{2}$ | IncP |
| Thm. 21 | EDGE DOMINATING SET | 2 [28] | DelP [34] | 5 | DelP |
| Thm. 25 | STEINER SUBGRAPH | 1.39 [12] | DelP [37] | 2.39 | DelP |

applicability of this technique.

To apply this technique to our problem setting, we need to define a supergraph whose node set contains all minimal solutions of weight at most k . However, there are two obstacles to this: (1) we need to find a “seed solution” of weight at most k , which is essentially difficult to obtain, and (2) we need to ensure the strong connectivity of the supergraph defined on the set of minimal solutions of weight at most k . Fortunately, in our approximation setting, we do overcome these obstacles: (1) we can use known polynomial-time approximation algorithms for finding a “seed solution”, and (2) for every two “small” minimal solutions, there is a path between these solutions whose “internal solutions” are all small in the supergraph defined by the weight constrained version of input-restricted problems. Given this, it suffices to show that input-restricted problems with weight constraints can be solved efficiently.

More precisely, given a minimal subset X of U satisfying Π and $x \in X$, the input-restricted problem requires to enumerate all minimal subsets R of U with $w(R) \leq k$ such that $(X \setminus \{x\}) \cup R$ satisfies Π . Without the weight constraint on R , it is the original version of the input-restricted problem defined by Cohen et al. [15]. However, CKS properties are rather restrictive. It is easy to observe that many monotone properties are not CKS properties. In particular, the number of solutions of input-restricted problems can be exponential in the input size. For such a property, Cohen et al. [15] showed that if the

solutions of the input-restricted problem can be enumerated in incremental polynomial time, the entire enumeration algorithm also runs in incremental polynomial time as well. We develop approximate enumeration algorithms along this line. To solve weight-constrained input-restricted problems, we can intensively exploit problem-specific structures. For instance, to solve the weight constrained input-restricted problem for minimal feedback vertex sets, it suffices to show that, given a vertex-weighted graph G , a minimal feedback vertex set X of G , and $x \in X$, there is an incremental-polynomial time algorithm for enumerating minimal feedback vertex sets R with $x \notin R$ and $w(R) \leq k$ in the graph G' obtained from G by deleting $(X \setminus \{x\})$. The key observation here is that G' has treewidth at most two and hence we can easily enumerate such sets by dynamic programming over tree decompositions.

For EDGE DOMINATING SET and STEINER SUBGRAPH, we exploit a new supergraph technique that ensures the reachability from a “seed solution” to every small solution by defining elaborated neighborhood relation in \mathcal{G} , which is inspired by polynomial-delay enumeration algorithms for minimal induced trivially perfect graphs [13] and minimal induced Steiner subgraphs in claw-free graphs [38].

2 Running time of enumeration algorithms

We say that an enumeration algorithm runs in *polynomial delay* if the followings are upper bounded by a polynomial in the input size $|U|$: (1) the maximum time interval between any two consecutive outputs, (2) the preprocessing time, and (3) the postprocessing time. An enumeration algorithm runs in *incremental polynomial time* if the i^{th} solution can be obtained in time $(i + |U|)^{O(1)}$. In other words, given a set $\mathcal{O} \subseteq 2^U$ of solutions generated so far, the algorithm runs in time $(|\mathcal{O}| + |U|)^{O(1)}$ to find a new solution not contained in \mathcal{O} or decide that every solution has already been contained in \mathcal{O} . If the total running time of an enumeration algorithm is upper bounded by a polynomial in both the input size and the number of outputs, we say that the algorithm runs in *output-polynomial time* or *polynomial total time*.

3 Preliminaries

Let $G = (V, E)$ be a graph without self-loops and multiple edges. The vertex set and edge set of G are denoted by $V(G)$ and $E(G)$, respectively. For a vertex $v \in V$, the neighborhood or the set of neighbors of v is denoted by $N_G(v)$. The set of incident edges of v is denoted by $\Gamma_G(v)$. We denote by $d_G(v)$ the degree of v in G , that is, $d_G(v) = |N_G(v)|$. The maximum degree of a vertex in G is denoted by Δ_G , and we call it the maximum degree of G . If the graph G is clear from the context, we omit the subscript G in these notations. For $X \subseteq V$, we denote by $G[X]$ the subgraph of G induced by X . A graph $H = (U, F)$ is a subgraph of G if $U \subseteq V$ and $F \subseteq E$. Moreover, H is an induced subgraph of G if $U \subseteq V$ and $F = \{\{u, v\} \in E \mid u, v \in U\}$. For $F \subseteq E$, we denote by $G - F$ the graph obtained from G by deleting the edges in F , that is, $G - F = (V, E \setminus F)$.

Let U be a finite set and let Π be a monotone property over U . Let $w : U \rightarrow \mathbb{N}$ be a weight function. For $X \subseteq U$, we define $w(X)$ as $\sum_{x \in X} w(x)$. We call $w(X)$ the *weight of* X . A set $X \subseteq U$ is called a Π -set if it satisfies Π . We say that $X \subseteq U$ is a (Π, w, k) -set if it is a Π -set and $w(X)$ is at most k . When w is the unit weight function, we simply call it (Π, k) -set. A subset X is a *minimal* (Π, w, k) -set (resp. *minimal* (Π, k) -set) if any proper subset X' of X is not a (Π, w, k) -set (resp (Π, k) -set). Now, we define our problem as follows:

MINIMAL (Π, w, k) -SETS ENUMERATION PROBLEM

Input: A finite set U with monotone property Π , a weight function $w : U \rightarrow \mathbb{N}$, and a positive integer k
Output: All minimal (Π, w, k) -sets of U

If we allow k to be arbitrarily large, then MINIMAL (Π, w, k) -SETS ENUMERATION PROBLEM is equivalent to a usual enumeration problem for minimal subsets satisfying Π . However, we note that the problem is particularly difficult in general as mentioned in the previous section. To cope with this difficulty, we allow us to use a “seed set”, which is an arbitrary minimal (Π, w, ck) -set for some constant $c > 1$, as input. Since finding a minimum vertex cover can be approximated in factor two, we can find such a “seed set” in polynomial time for enumerating minimal Π_{vc} -sets. Given such a “seed set”, we devise a polynomial-delay algorithm for enumerating minimal Π -sets containing all the minimal (Π, w, k) -sets and some minimal Π -sets enumerated by the algorithm may have weight exceeding k . Recall that the approximation factor α of the algorithm is defined by $\alpha = \frac{k}{\tilde{k}}$, where \tilde{k} is the maximum weight of a solution output by the algorithm. Formally, our goal is to solve the MINIMAL (Π, w, k) -SETS ENUMERATION PROBLEM approximately.

4 General frameworks for approximate enumeration

Our frameworks are based on the supergraph technique. In this technique, we consider a directed graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ whose node set \mathcal{V} corresponds to the collection of minimal Π -sets. The key to designing an enumeration algorithm with the supergraph technique is to ensure that, by appropriately defining the arc set \mathcal{E} , \mathcal{G} is strongly connected. To ensure the strong connectivity of \mathcal{G} , we define a “measure” between two Π -sets. This idea has been used for enumeration of maximal induced subgraphs with hereditary properties² [13, 15, 16, 48] and enumeration of minimal subsets for specific properties [9, 35]. In [15], Cohen et al. studied enumeration problems for *maximal* induced subgraphs with hereditary properties or connected hereditary properties. The crucial observation is as follows: For any pair H, H' of maximal induced subgraphs satisfying some hereditary property Π , if we can define a neighborhood of H such that the neighborhood contains H'' with $|V(H) \cap V(H')| < |V(H'') \cap V(H')|$, then \mathcal{G} becomes strongly connected since H has a neighbor H'' that is “closer” than H to H' , which implies there is a directed path from H to H' in \mathcal{G} via the neighborhood relation.

We apply the essentially same idea to MINIMAL (Π, w, k) -SETS ENUMERATION PROBLEM. For a minimal Π -set $S \subseteq U$, we develop an enumeration algorithm for enumerating minimal Π -sets $S_1, S_2, \dots, S_t \subseteq U$ such that for every minimal Π -set S' , there is S_i with $|S \cup S'| > |S_i \cup S'|$. The key difference from [15] is that we use the cardinality of the union with S' as a “measure” rather than that of the intersection, which is also important for approximation guarantees. The following lemma is an easy observation.

► **Lemma 1.** *Let S and S' be minimal Π -sets. Then, $S = S'$ if and only if $|S| = |S \cup S'|$.*

Proof. The only if part is trivial. Since $|S| = |S \cup S'|$, we have $S' \subseteq S$. The minimality of S implies that $S = S'$. ◀

To design a c -approximation enumeration algorithm for MINIMAL (Π, w, k) -SETS ENUMERATION PROBLEM, our strategy is to construct a subgraph \mathcal{G}' of \mathcal{G} such that

² The property Π is *hereditary* if, for any graph satisfying Π , every induced subgraph also satisfies Π .

- \mathcal{G}' contains all the minimal (Π, w, k) -sets and
- from an arbitrary minimal (Π, w, ck) -set S , there is a directed path to every minimal (Π, w, ck) -set in \mathcal{G}' ,

where c is a value depending on the property Π and a known polynomial-time approximation algorithm for finding seed solution S . To this end, we solve slightly generalized version of the input-restricted problem, which is defined as follows.

INPUT-RESTRICTED MINIMAL (Π, w, k) -SETS PROBLEM $((\Pi, w, k)$ -IRP)

Input: A finite U with monotone property Π , a weight function $w : U \rightarrow \mathbb{N}$, a positive integer k , a minimal Π -set $X \subseteq U$, and an element $x \in X$.

Output: All minimal subsets $R \subseteq U \setminus \{x\}$ with $w(R) \leq k$ such that $(X \setminus \{x\}) \cup R$ is a Π -set.

The solutions of (Π, w, k) -IRP is denoted by $\mathcal{S}(U, \Pi, w, k, X, x)$. Since (Π, w, k) -IRP is also an enumeration problem of a monotone property with an weight constraint, we can apply approximate enumeration algorithms to it. Let \mathcal{A} be an enumeration algorithm for (Π, w, k) -IRP with approximation factor d . The collection of sets output by \mathcal{A} is denoted by $\mathcal{S}_{\mathcal{A}}(U, \Pi, w, k, X, x)$, that is, $\mathcal{S}_{\mathcal{A}}(U, \Pi, w, k, X, x)$ contains all inclusion-wise minimal $R \subseteq U$ with $w(R) \leq k$ such that $(X \setminus \{x\}) \cup R$ is a Π -set and may contain some inclusion-wise minimal $R \subseteq U$ with $k < w(R) \leq dk$ such that $(X \setminus \{x\}) \cup R$ is a Π -set. Note that for $R \in \mathcal{S}_{\mathcal{A}}(U, \Pi, w, k, X, x)$, $(X \setminus \{x\}) \cup R$ may not be a minimal Π -set. If no confusion arises, we simply write \mathcal{S} (resp. $\mathcal{S}_{\mathcal{A}}$) to denote $\mathcal{S}(U, \Pi, w, k, X, x)$ (resp. $\mathcal{S}_{\mathcal{A}}(U, \Pi, w, k, X, x)$).

A function $\mu(\tilde{X})$ computes a minimal Π -set from a Π -set \tilde{X} by greedily removing an element e from \tilde{X} as long as $\tilde{X} \setminus \{e\}$ is a Π -set. Note the resultant set of $\mu(\tilde{X})$ is a subset of \tilde{X} and if the membership of Π can be checked in polynomial time, it is computed in polynomial time as well. The following lemmas show basic properties of $\mathcal{S}_{\mathcal{A}}$ and $\mu(\cdot)$.

► **Lemma 2.** *Let $X \subseteq U$ be a minimal Π -set and let $x \in X$. For distinct $R, R' \in \mathcal{S}_{\mathcal{A}}$, $\mu((X \setminus \{x\}) \cup R) \neq \mu((X \setminus \{x\}) \cup R')$.*

Proof. It is sufficient to prove that $R \subseteq \mu((X \setminus \{x\}) \cup R)$ for $R \in \mathcal{S}_{\mathcal{A}}$. Suppose for contradiction that $R \cap \mu((X \setminus \{x\}) \cup R) = T$ for some $T \subset R$. By the monotonicity of Π , $(X \setminus \{x\}) \cup T$ is a Π -set, contradicting to the minimality of R . ◀

► **Lemma 3.** *Let $X \subseteq U$ be a minimal Π -set and let $x \in X$. Then, for every minimal (Π, w, k) -set $Y \subseteq U \setminus \{x\}$ excluding x , there is $R \in \mathcal{S}_{\mathcal{A}}$ such that $\mu((X \setminus \{x\}) \cup R) \cup Y \subset X \cup Y$.*

Proof. By the monotonicity of Π , $(X \setminus \{x\}) \cup Y$ is a Π -set. Then, there is an inclusion-wise minimal set $R \subseteq Y$ such that $(X \setminus \{x\}) \cup R$ is a Π -set and $w(R) \leq w(Y) \leq k$, which implies that $R \in \mathcal{S}_{\mathcal{A}}$. Since $R \subseteq Y$ and $x \notin R$, we have

$$X \cup Y \supset (X \setminus \{x\} \cup R) \cup Y \supseteq \mu((X \setminus \{x\}) \cup R) \cup Y,$$

completing the proof of the lemma. ◀

We define an arc from a minimal Π -set X to a minimal Π -set Z if $Z = \mu((X \setminus \{x\}) \cup R)$ for some $x \in X$ and $R \in \mathcal{S}_{\mathcal{A}}$. By Lemmas 2 and 3, we can conclude that \mathcal{G} has a directed path from every minimal Π -set X to every minimal (Π, w, k) -set Y . Moreover, every internal node Z on the path is a minimal $(\Pi, w, w(X \cup Y))$ -set since $Z \cup Y \subset X \cup Y$. Now, we are ready to describe our algorithm based on the supergraph technique shown in Algorithm 1.

► **Theorem 4.** *Let U be a finite set, let Π be a monotone property over U , let w be a weight function, and let k be a positive integer. Suppose that the membership of Π can be decided*

■ **Algorithm 1** $(c + d + 1)$ -approximate enumeration for MINIMAL (Π, w, k) -SETS ENUMERATION PROBLEM.

Input: A minimal Π -set S of U with $w(S) \leq ck$ for some $c \geq 1$

```

1 Output  $S$  and add  $S$  to  $\mathcal{Q}$  and  $\mathcal{O}$ ;
2 while  $\mathcal{Q}$  is not empty do
3   Let  $X$  be a minimal  $\Pi$ -set in  $\mathcal{Q}$  and delete it from  $\mathcal{Q}$ ;
4   foreach  $x \in X$  do
5     Compute  $\mathcal{S}_{\mathcal{A}}(U, \Pi, w, k, X, x)$  by a  $d$ -approximate enumeration algorithm  $\mathcal{A}$ ;
6     foreach  $R \in \mathcal{S}_{\mathcal{A}}(U, \Pi, w, k, X, x)$  do
7        $Z \leftarrow \mu((X \setminus \{x\}) \cup R)$ ;
8       if  $Z \notin \mathcal{O}$  then
9         Output  $Z$  and add  $Z$  to  $\mathcal{O}$ ;
10        if  $w(Z) < w(S) + k$  then
11          Add  $Z$  to  $\mathcal{Q}$ ;
```

in polynomial time and there is an output-polynomial time enumeration algorithm \mathcal{A} for (Π, w, k) -IRP with approximation factor d . Then, given a minimal Π -set of weight at most ck , Algorithm 1 solves MINIMAL (Π, w, k) -SETS ENUMERATION PROBLEM with approximation factor $c + d + 1$ in output polynomial time. Moreover, it is improved to incremental polynomial time if \mathcal{A} runs in incremental polynomial time.

Proof. We first show that Algorithm 1 outputs all the minimal (Π, w, k) -sets of U . Let S be a minimal (Π, w, ck) -set, which is given as input. Let \mathcal{O} be the collection of minimal Π -sets generated by Algorithm 1. Suppose for contradiction that there is a minimal (Π, w, k) -set Y that is not contained in \mathcal{O} . We choose a minimal Π -set X and a minimal (Π, w, k) -set Y in such a way that $|X \cup Y|$ is minimized over all minimal Π -sets $X \in \mathcal{O}$ and minimal (Π, w, k) -sets $Y \notin \mathcal{O}$. We can choose such X as $S \in \mathcal{O}$. Let $x \in X \setminus Y$. By Lemma 3, $\mathcal{S}_{\mathcal{A}}$ contains $R \subseteq U$ such that $(X \setminus \{x\}) \cup R$ is a Π -set and $\mu((X \setminus \{x\}) \cup R) \cup Y \subset X \cup Y$. This implies that $|X \cup Y| > |\mu((X \setminus \{x\}) \cup R) \cup Y|$, which contradicts to the choices of X and Y . Since the approximation factor of \mathcal{A} is d and every minimal Π -set X computed in \mathcal{Q} has weight at most $(c + 1)k$, every minimal Π -set Z generated by Algorithm 1 has weight at most

$$w(Z) = w(\mu((X \setminus \{x\}) \cup R)) \leq w(X) + w(R) \leq (c + d + 1)k. \quad (1)$$

Hence, the approximation factor of Algorithm 1 is $c + d + 1$.

As for the time complexity, suppose first that $\mathcal{S}_{\mathcal{A}}$ can be computed in output polynomial time, namely $O((|U| + |\mathcal{S}_{\mathcal{A}}|)^t)$ for some constant t for each minimal Π -set X and $x \in X$. By Lemma 2, for $R \in \mathcal{S}_{\mathcal{A}}$, $\mu((X \setminus \{x\}) \cup R)$ is distinct from $\mu((X \setminus \{x\}) \cup R')$ for any $R' \in \mathcal{S}_{\mathcal{A}}$ with $R' \neq R$. Thus, we have $|\mathcal{S}_{\mathcal{A}}| \leq |\mathcal{O}|$. Therefore, the total running time is upper bounded by

$$\sum_{X \in \mathcal{O}} \sum_{x \in X} O((|U| + |\mathcal{S}_{\mathcal{A}}|)^t) = O((|U| + |\mathcal{O}|)^{t+1}),$$

which is polynomial in $|U| + |\mathcal{O}|$.

Suppose next that \mathcal{A} runs in incremental polynomial time. Let $\mathcal{O}' \subseteq \mathcal{O}$ be a set of minimal Π -sets that have already been generated by the entire algorithm at some point in the execution. Now, consider the running time of the loop at line 4. Since \mathcal{Q} contains sets in \mathcal{O}' , the loop repeats at most $|\mathcal{O}'|$ times without outputting a minimal Π -set Z at line 9. Moreover, for each

■ **Algorithm 2** A polynomial-delay $(c+1)$ -approximate enumeration algorithm for MINIMAL (Π, w, k) -SETS ENUMERATION PROBLEM, where Π is a CKS property.

Input: A minimal Π -set S of U with $w(S) \leq ck$ for some $c \geq 1$

```

1 Output  $S$  and add  $S$  to  $\mathcal{Q}$  and  $\mathcal{O}$ ;
2 while  $\mathcal{Q}$  is not empty do
3   Let  $X$  be a minimal  $\Pi$ -set in  $\mathcal{Q}$ ;
4   Delete  $X$  from  $\mathcal{Q}$ , add  $X$  to  $\mathcal{O}$ , and output  $X$ ;
5   foreach  $x \in X$  do
6     Compute  $\mathcal{S}(U, \Pi, w, k, X, x)$ ;
7     foreach  $R \in \mathcal{S}(U, \Pi, w, k, X, x)$  do
8        $Z \leftarrow \mu((X \setminus \{x\}) \cup R)$ ;
9       if  $Z \notin \mathcal{O}$  then
10        if  $w(Z) < w(S) + k$  then
11          Add  $Z$  to  $\mathcal{Q}$ ;
```

$X \in \mathcal{O}'$ and $x \in X$, either $\mu((X \cup \{x\}) \cup R) \notin \mathcal{O}'$ for some $R \in \mathcal{S}_A$ or $\mu((X \setminus \{x\}) \cup R) \in \mathcal{O}'$ for all $R \in \mathcal{S}_A$. By Lemma 2, for each $R \in \mathcal{S}_A$, $\mu((X \setminus \{x\}) \cup R)$ is a unique solution among \mathcal{S}_A . This implies that we can either find a solution $\mu((X \setminus \{x\}) \cup R) \notin \mathcal{O}'$ or conclude that no $R \in \mathcal{S}_A$ with $\mu((X \setminus \{x\}) \cup R) \notin \mathcal{O}'$ exists in time $O(\sum_{1 \leq i \leq |\mathcal{O}'|} (i \cdot |U|)^t) = O(|U|^t |\mathcal{O}'|^{t+1})$, where t is a constant depending on the running time of \mathcal{A} . Therefore, the delay of the running time after generating \mathcal{O}' is upper bounded by

$$\sum_{X \in \mathcal{O}'} \sum_{x \in X} O(|U|^t \cdot |\mathcal{O}'|^{t+1}) = O(|U|^{t+1} \cdot |\mathcal{O}'|^{t+2}),$$

which yields an incremental polynomial time bound. \blacktriangleleft

As applications of Theorem 4, we give incremental-polynomial time approximate enumeration algorithms for many properties, such as FEEDBACK VERTEX SET, TREewidth- η DELETION, TRIVIAALLY PERFECT DELETION, and d -HITTING SET.

When we can solve (Π, w, k) -IRP in $|U|^{O(1)}$ time, we can simultaneously improve the running time and approximation factors of MINIMAL (Π, w, k) -SETS ENUMERATION PROBLEM.

► **Theorem 5.** *Suppose that \mathcal{S} can be enumerated in $|U|^{O(1)}$ total time. Then, one can solve MINIMAL (Π, w, k) -SETS ENUMERATION PROBLEM with approximation factor $c+1$ in polynomial delay.*

Proof. It is not hard to see that Algorithm 2 outputs all minimal (Π, w, k) -sets by the same argument as in Theorem 4. Since all steps inside while loop at line 2 can be done in polynomial time, the delay is upper bounded by a polynomial in $|U|$. Moreover, since we add only $(\Pi, w, (c+1)k)$ -sets to \mathcal{Q} , approximation factor of the algorithm is $c+1$. \blacktriangleleft

To apply Theorems 4 and 5 to a specific monotone property Π , we need to develop a polynomial-time algorithm for solving (Π, w, k) -IRP. Cohen, Kimelfeld, and Sagiv [15] and Cao [13] showed that there are several properties on graphs can be solved the problem exactly in polynomial time. In what follows, we say that Π is a *CKS property* [13] if the problem can be computed in time polynomial in $|U|$ for any k, X , and x . Cohen et al. and Cao showed that the following graph properties are CKS properties.

► **Proposition 6** ([13, 15]). *Let $G = (V, E)$ be a graph. Let \mathcal{C} be one of the following classes of graphs; complete graphs, graphs with no edges, cluster graphs, complete bipartite*

graphs, complete p -partite graphs for any positive integer p , complete split graphs, split graphs, pseudo-split graphs, threshold graphs, and graphs of maximum degree d for fixed d . Suppose that Π is the property of being a vertex subset $S \subseteq V$ such that $G[V \setminus S]$ is in \mathcal{C} . Then, Π is a CKS property.

Moreover, the problem of computing a minimum vertex set whose removal leaves a subgraph in a graph class listed in Proposition 6 can be approximated with a constant factor in polynomial time. Therefore, our approximate enumeration framework can be applied to those properties Π and enumerate minimal (Π, w, k) -sets with constant approximation factors in polynomial delay.

Our frameworks can be used for more general weight functions. A function $f : 2^U \rightarrow \mathbb{N}$ is *monotone* if $f(X) \leq f(Y)$ for $X \subseteq Y \subseteq U$ and is *subadditive* if $f(X) + f(Y) \geq f(X \cup Y)$ for $X, Y \subseteq U$. One of the famous examples of subadditive functions is a submodular function. A function is *submodular* if $f(X) + f(Y) \geq f(X \cup Y) + f(X \cap Y)$ for $X, Y \subseteq U$. To bound the approximation factor of our enumeration algorithms for a monotone subadditive function f , we can replace function w with f in inequality (1):

$$f(Z) = f(\mu((X \setminus \{x\}) \cup R)) \leq f(X \cup R) \leq f(X) + f(R) \leq (c + d + 1)k,$$

where the first and second inequalities are obtained from the monotonicity and subadditivity of f , respectively. This gives a polynomial-delay 3-approximate enumeration for minimal vertex covers with monotone submodular cost by combining Theorem 5 with a polynomial-time 2-approximation algorithm for the minimum vertex cover problem with submodular cost function due to [31].

5 Applications of our framework

In this section, we give some concrete examples for efficient approximation enumeration algorithms.

5.1 Approximate Enumeration for Vertex Deletion Problems with Width Parameters

In this subsection, we particularly work on *vertex deletion properties on graphs*. Let $G = (V, E)$ be a graph. We say that a monotone property Π over V is a *vertex deletion property* if for every minimal Π -set X of V and $R \subseteq X$, $X \setminus R$ is a minimal Π -set of $G[V \setminus R]$. Many properties can be formulated as vertex deletion properties. In particular, for a (possibly infinite) family of graphs \mathcal{F} , the property of being a vertex set whose removal breaks all induced subgraphs isomorphic to any graph in \mathcal{F} is a vertex deletion property.

To solve hard problems on graphs, *width parameters*, such as *treewidth* and *cliquewidth*, have become ubiquitous tools, and Courcelle's theorem [17] is a cornerstone result to develop efficient algorithms on graphs when these parameters are small. If the treewidth (resp. cliquewidth) of a graph is upper bounded by a constant, the problem of finding a minimum weight vertex or edge set satisfying a property expressible by a formula in MSO_2 (resp. MSO_1) can be solved in linear time [5, 17]. There are numerous properties that are expressible in MSO_1 and MSO_2 . We refer to [19, 39] for the detailed definitions of these width parameters and a brief introduction to Courcelle's theorem.

For our purpose, we use the following lemmas.

► **Lemma 7.** *Let $G = (V, E)$ be a graph with constant treewidth and let Π be a monotone property on V . Suppose that Π can be expressed by a formula in MSO_2 . Then, for $x \in V$, one can enumerate all the minimal (Π, w, k) -sets excluding x in polynomial delay.*

Proof. Let $X \subseteq V$. Let $\phi(X)$ be a predicate that is true if and only if X is a Π -set, which is expressed by a formula in MSO_2 . As Π is monotone, the minimality of X can be expressed as:

$$\phi_m(X) := \phi(X) \wedge \forall v \in V. (v \in X \implies \neg \phi(X \setminus \{v\})).$$

Let $I \subseteq V$ and let $O \subseteq V \setminus I$. Then, the property that there is a minimal Π -set X excluding x such that $I \subseteq X$ and $O \cap X = \emptyset$ is expressible with the following formula:

$$\phi_m(x, I, O) := \exists X \subseteq V. (\phi_m(X) \wedge \forall v \in V. ((v \in I \implies v \in X) \wedge (v \in (O \cup \{x\}) \implies v \notin X))).$$

Now, we can enumerate all the minimal (Π, w, k) -sets of excluding x in polynomial delay by the K -best enumeration technique [40].

- We first compute a minimum weight (Π, w, k) -set S excluding x by the optimization version of Courcelle's theorem with MSO_2 formula $\phi_m(x, \emptyset, \emptyset)$. If $w(S) > k$, we do nothing. Otherwise, we add a tuple $(S, \emptyset, \emptyset)$ to a queue.
 - Remove a tuple (S', I, O) from the queue that minimizes $w(S')$ among those in the queue. Output S' and do the following. We repeat this and the subsequent step unless the queue is empty.
 - Let v_1, v_2, \dots, v_t be the vertices in $S' \setminus I$. For each $1 \leq i \leq t$, we compute a minimal (Π, w, k) -set S'' including $I \cup \{v_1, \dots, v_{i-1}\}$ and excluding $O \cup \{v_i\}$ with MSO_2 formula $(x, I \cup \{v_1, \dots, v_{i-1}\}, O \cup \{v_i\})$ that minimizes $w(S'')$. If $w(S'') \leq k$, add S'' to the queue.
- An essential difference from [40] is that, in the K -best enumeration, the algorithm terminates immediately after generating K solutions. Thus, the correctness of this algorithm directly follows from [40]. ◀

We also give an enumeration algorithm on bounded cliquewidth graphs. The proof is analogous to the previous one and hence omitted here.

► **Lemma 8.** *Let $G = (V, E)$ be a graph with constant cliquewidth and let Π be a monotone property over V . Suppose that Π can be expressed by a formula in MSO_1 . Then, for $x \in V$, one can enumerate all the minimal (Π, w, k) -sets excluding x in polynomial delay.*

Now, we show the main result of this subsection.

► **Theorem 9.** *Let $G = (V, E)$ be a graph and let Π be a monotone vertex deletion property over V that is expressible by a formula in MSO_2 (resp. MSO_1). Suppose that for every Π -set X , the graph obtained from G by deleting X has constant treewidth (resp. constant cliquewidth). Given a Π -set S of weight at most ck for some $c > 0$, one can enumerate all the minimal (Π, w, k) -sets with approximation factor $c + 2$ in incremental polynomial time.*

Proof. Let $X \subseteq V$ be a minimal Π -set. Suppose that for every Π -set X , the treewidth (resp. cliquewidth) of $G[V \setminus X]$ is at most a constant. Since adding a vertex increases its treewidth by at most one (resp. cliquewidth to at most twice plus one [42]), $G[V \setminus (X \setminus \{x\})]$ also has a constant treewidth (resp. cliquewidth). For $x \in X$ and $R \subseteq V \setminus (X \setminus \{x\})$, let $\phi(R, x)$ be the predicate that is true if and only if R is a minimal Π -set of $G[V \setminus (X \setminus \{x\})]$ excluding x , which is expressed by a formula in MSO_2 (resp. MSO_1). By Lemmas 7 and 8, there is an algorithm \mathcal{A} that compute $\mathcal{S}_{\mathcal{A}}(V, \Pi, w, k, X, x)$ exactly in polynomial delay, and hence by Theorem 4, we can enumerate all the minimal (Π, w, k) -sets in incremental polynomial time with approximation factor $c + 2$. ◀

Let \mathcal{F} be a finite set of graphs that contains at least one planar graph. It is known that every graph that does not contain a fixed planar graph H as a minor has a constant treewidth [47]. The property $\Pi_{\mathcal{F}}$ of being a vertex set that hits all the minors of graphs in \mathcal{F} can be expressed in a MSO_2 formula. Moreover, there is an $O(1)$ -approximate algorithm for finding a smallest *cardinality* $\Pi_{\mathcal{F}}$ -set [26] if \mathcal{F} contains at least one planar graph. Note that for weighted graphs, the best known approximation factor for this problem is polylogarithmic [2]. These facts yield the following corollary.

► **Corollary 10.** *Let $G = (V, E)$ be a graph. Let \mathcal{F} be a set of graphs that contains at least one planar graph and let $\Pi_{\mathcal{F}}$ be the vertex deletion property corresponding to every set S whose removal from G leaves a graph does not contain any graph in \mathcal{F} as a minor. Then, one can enumerate all the minimal (Π, k) -sets with a constant approximation factor in incremental polynomial time.*

By Corollary 10, we have incremental polynomial-time approximate enumeration algorithms for minimal feedback vertex sets, minimal caterpillar forest vertex deletion sets, minimal star forest vertex deletion sets, minimal outerplanar vertex deletion sets, and minimal treewidth- η vertex deletion sets for fixed integer η . We note that the approximation algorithm due to [26] is randomized and the expected approximation factor is upper bounded by a constant. Also note that, for specific problems, such as the minimum feedback vertex set problem, the minimum caterpillar forest vertex set problem (also known as the pathwidth-one vertex set deletion problem), and the minimum star forest vertex deletion set problem, they admit deterministic constant factor approximation algorithms [8, 21, 45]³.

As for dense graph classes, some graph classes have constant cliquewidth: Block graphs, cographs, bipartite chain graphs, and trivially perfect graphs are of bounded cliquewidth. Since the classes of cographs, bipartite chain graphs, and trivially perfect graphs can be respectively characterized by finite sets of forbidden induced subgraphs, there are $O(1)$ -approximation algorithms for finding a minimum weight set $S \subseteq V$ such that $G[V \setminus S]$ is a cograph, a bipartite chain graph or a trivially perfect graph. Although no characterization by a finite set of forbidden induced subgraphs for block graphs is known, there is a constant factor approximation algorithm for the minimum block graph vertex deletion problem on unweighted graphs [1]. Moreover, the property of being a block graphs is expressible in MSO_1 by using the fact that a graph is a block graph if and only if every biconnected component induces a clique. Therefore, as another consequence of Theorem 9, we have the following corollary.

► **Corollary 11.** *Let $G = (V, E)$ be a graph. Let \mathcal{C} be one of the following classes of graphs; cographs, bipartite chain graphs, and trivially perfect graphs. Let Π be the property of being a set of vertices whose removal leaves a graph in \mathcal{C} . Then, one can enumerate all the minimal (Π, w, k) -sets with constant approximation factors in incremental polynomial time. For block graphs, one can enumerate all the minimal (Π, k) -sets with approximation factor 6 in incremental polynomial time.*

Since the property of being a set of vertices whose removal leaves a distance hereditary graph is monotone and every distance hereditary graph has cliquewidth at most five, we can apply our framework to this property. However, there is no known polynomial-time

³ In [45], they did not explicitly mention the approximability of the minimum caterpillar forest vertex deletion set problem, while we can easily obtain a deterministic 7-approximation algorithm from their argument.

constant factor approximation algorithm for finding a minimum vertex set of this property. The current best approximation factor is polylogarithmic in the input size due to Agrawal et al. [2].

5.2 d -Hitting Set

Let $\mathcal{H} = (V, \mathcal{E})$ be a hypergraph. A *hitting set* of \mathcal{H} is a subset S of V such that $S \cap e \neq \emptyset$ for every $e \in \mathcal{E}$. The existence of an output-polynomial time enumeration algorithm for minimal hitting sets is a long-standing open problem in this field and the best known algorithm runs in quasi-polynomial time in the size of input and output [27]. There are several studies for developing efficient enumeration algorithms for special hypergraphs. In particular, if every hyperedge contains at most d vertices for some fixed constant $d \geq 2$, there is an incremental polynomial time enumeration algorithm [10]. We say that such a hypergraph has *rank* at most d and call a hitting set of rank- d hypergraphs a *d -hitting set*.

We show that minimal d -hitting sets of hypergraphs with weight at most k can be enumerated in incremental-polynomial time with approximation factor $\frac{(d+4)(d-1)}{2}$. It is known that the problem of computing a minimum weight d -hitting set of \mathcal{H} has a polynomial-time d -approximation algorithm. We use this algorithm to compute a seed set.

► **Theorem 12.** *Let $\mathcal{H} = (V, \mathcal{E})$ be a hypergraph with rank at most d . Then, there is an incremental-polynomial $\frac{(d+4)(d-1)}{2}$ -approximate enumeration algorithm for enumerating minimal d -hitting sets of \mathcal{H} .*

Proof. Let k be a positive integer. We show, by induction on d , that there is an approximate enumeration algorithm for minimal d -hitting sets of \mathcal{H} of weight at most k . If $d = 2$, then the problem is equivalent to the vertex cover case, and hence, by Proposition 6, we have a 3-approximate polynomial delay enumeration algorithm.

Now, we assume that we can enumerate in incremental-polynomial time all the minimal $(d-1)$ -hitting sets of weight at most k with the approximation factor $\frac{(d+3)(d-2)}{2}$ for every hypergraph having rank at most $d-1$. We consider an enumeration algorithm for minimal d -hitting sets of \mathcal{H} . Let Π_{HS} be the property of being a hitting set of a hypergraph \mathcal{H} . Observe that, for a minimal hitting set $X \subseteq V$ of \mathcal{H} and $x \in X$, INPUT-RESTRICTED MINIMAL (Π_{HS}, w, k) -SETS PROBLEM for \mathcal{H} can be seen as the problem of enumerating minimal $(d-1)$ -hitting sets in a hypergraph \mathcal{H}' obtained from \mathcal{H} by deleting all the hyperedges intersecting with $X \setminus \{x\}$ and removing x from each remaining hyperedge. By the induction hypothesis, we can enumerate minimal $(d-1)$ -hitting sets of \mathcal{H}' with approximation factor $\frac{(d+3)(d-2)}{2}$ in incremental-polynomial time. Since there is a polynomial-time d -approximation algorithm for the minimum d -hitting set problem, by Theorem 4, we can enumerate all the minimal d -hitting sets of \mathcal{H} in incremental-polynomial time with approximation factor $d + \frac{(d+3)(d-2)}{2} + 1 = \frac{(d+4)(d-1)}{2}$. ◀

5.3 Star Forest Edge Deletion

A graph is called a *star forest* if each component is a star graph. A *star graph* is a graph isomorphic to $K_{1,t}$, a complete bipartite graph of $t+1$ vertices. The *center* of a star is a vertex of degree greater than one. Note that we regard an isolated vertex or a complete graph of two vertices as a star. A vertex v is called a *leaf* if degree of v is equal to one. Let $G = (V, E)$ be a graph. A vertex set $S \subseteq V$ (resp. an edge set $F \subseteq E$) is called a *star forest vertex deletion set* (resp. *star forest edge deletion set*) of G if $G[V \setminus S]$ (resp. $G - F$) is a star forest. Let Π_{SFVD} and Π_{SFED} be the properties of being a star forest vertex and edge deletion

XX:14 Constant-Factor Approx. Enumeration with Weight Constraints

set of G , respectively. It is easy to see that both properties are monotone over V and E , respectively.

► **Lemma 13.** Π_{SFED} is a CKS property.

Proof. Let $G = (V, E)$ be a graph, $X \subseteq E$ be a minimal star forest edge deletion set of G , and $e = \{u, v\} \in X$. Let \mathcal{S} be a collection of a set of edges R such that $(X \setminus \{e\}) \cup R$ is star forest edge deletion. Since X is a minimal star forest deletion, $G - (X \setminus \{e\})$ contains exactly one component C that is not a star. Hence, R only contains edges in C .

We consider two cases: (1) exactly one of $d_C(u)$ or $d_C(v)$ is more than one, or (2) both $d_C(u)$ and $d_C(v)$ are more than one. In Case (1), we may assume $d_C(u) > 1$. Since C is not a star and $C - \{e\}$ is a star, C contains w with $d_C(w) > 1$ that is adjacent to u in C . This implies that u is a leaf in $G - X$. There are two minimal star forest edge deletion sets R of C without containing e : $\{\{u, w\}\}$ and $\Gamma_C(w) \setminus \{\{u, w\}\}$. Suppose that both $d_C(u)$ and $d_C(v)$ are more than one, namely Case (2). As R does not contain e , at least one of u and v , say u , is a leaf in $C - R$. Thus, R contains all edges but e incident to u . If v is also a leaf in $C - R$ (i.e., e is a component in $C - R$), then R contains all edges but e incident to v as above. Otherwise, v is the center vertex of degree at least two in the star component C' of $C - R$. Then, every neighbor w of v in C' must be a leaf. Therefore, R contains all edges incident to $w \in N_C(v)$ except one edge $\{v, w\}$. By guessing whether u and v are leaves or centers in $C - R$, we can uniquely determine minimal star forest edge deletion set R of C .

In all cases, there are only a constant number of possibility of minimal star forest edge deletion set R of C . Hence, \mathcal{S} contains a constant number of sets, which can be computed in polynomial time. ◀

Since there is a polynomial-time 3-approximation algorithm for finding a minimum star forest edge deletion set [21], by Theorem 5, we have the following theorem.

► **Theorem 14.** *There is an approximate enumeration algorithm for minimal star forest edge deletion sets with approximation factor 4 that runs in polynomial delay.*

Contrary to this, we cannot directly apply our framework to the vertex counterpart. We should remark that this does not imply there is no polynomial-delay enumeration algorithm with constant approximation factor.

► **Proposition 15.** Π_{SFVD} is not a CKS property.

Proof. From a star graph $K_{1,2n}$ with leaves $\{v_1, v_2, \dots, v_{2n}\}$ for some integer n and the center r , we construct a graph $G = (V, E)$ by adding an edge between v_{2i-1} and v_{2i} for each $1 \leq i \leq n$. Let $X = \{r\}$. Then, X is a minimal star forest vertex deletion set of G . It is easy to verify that there are exponentially many minimal star forest vertex deletion sets Y of $G[V]$ that exclude r since for each $1 \leq i \leq n$, Y contains either v_{2i-1} or v_{2i} , which implies that 2^n possible combinations of Y . ◀

5.4 Dominating Set in Bounded Degree Graphs

Let $G = (V, E)$ be a graph. We say that $D \subseteq V$ is a *dominating set* of G if every vertex in V is either contained in D or adjacent to a vertex in D . Let Π_{Dom} be the property of being a dominating set of G . Although it is not hard to see that Π_{Dom} is not a CKS property, we can prove that it does have a CKS property when the maximum degree of G is upper bounded by a constant.

► **Lemma 16.** Π_{Dom} is a CKS property, provided every vertex of G has degree at most some fixed constant Δ .

Proof. Let X be a minimal dominating set of G . Since the degree of every vertex of G is at most Δ , there are a constant number of non-dominated vertices $U \subseteq N(x)$ by $X \setminus \{x\}$. Moreover, since such a vertex in U can be dominated by its neighbor, there are a constant number of possibilities of minimal vertex addition. Therefore, \mathcal{S} can be computed in polynomial time. ◀

It is well known that the minimum dominating set problem admits a polynomial-time $O(\log \Delta)$ -approximation algorithm on graphs of maximum degree Δ [14]. This yields the following approximate enumeration.

► **Theorem 17.** *There is an approximate enumeration algorithm for minimal dominating sets on bounded degree graphs with approximation factor $O(\log \Delta)$ runs in polynomial delay, where Δ is the maximum degree of input graphs.*

6 Approximate enumeration beyond our frameworks

In this section, as another algorithmic contribution, we propose polynomial-delay constant factor approximate enumeration algorithms for minimal edge dominating sets and minimal Steiner subgraphs, which seem to be difficult to apply the previous frameworks directly.


6.1 Minimal edge dominating sets

Let $G = (V, E)$ be a graph. Let $n = |V|$ and $m = |E|$. A set $D \subseteq E$ of edges is an *edge dominating set* of G if every edge e in E either belongs to D or has an edge $f \in D$ that shares a common end vertex. Let $w : E \rightarrow \mathbb{N}$ be a weight function. In the latter case, we say that e is *dominated by* D or D *dominates* e . Let $X \subseteq E$ be an edge dominating set of G . When an edge $e \in E$ is dominated by X , but is not dominated by $X \setminus \{x\}$ for some $x \in X$, e is called the *private edge of* x . Moreover, we say that x has the private edge e . Note that x may have itself as the private edge. It is known that X is a minimal edge dominating set of G if and only if any edge in X has at least one private edge. Let Π_{EDS} be the property of being an edge dominating set of a graph $G = (V, E)$.

Kanté et al. developed a polynomial-delay and polynomial-space enumeration algorithm for minimal edge dominating sets [34]. Their algorithm is based on the reverse search technique [6]. It would be highly nontrivial to extend their algorithm to our problem setting. Moreover, unfortunately, Π_{EDS} is not CKS property. Figure 1 depicts such an example of G and X . This implies that we cannot directly apply the framework in Section 4.

In this subsection, we show that it is still possible to approximately enumerate all minimal edge dominating sets in polynomial delay with a constant approximation factor. To make our idea clear, we first describe an algorithm for enumerating all minimal edge dominating sets of G without weight constraints and postpone proving an approximation guarantee to the last of this subsection.

The algorithm is also based on the supergraph technique. Thus, we need to build a directed graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$, where \mathcal{V} is the set of minimal edge dominating sets of G and \mathcal{E} is the set of arcs based on two types of neighborhood. The precise definition of neighbors will be given later. Intuitively speaking, to construct a directed path from X to Y , we repeatedly exchange edges in $X \setminus Y$ with edges outside X . Let $x = \{u, v\} \in X \setminus Y$. Note that Y contains at least one edge e incident to u or v as otherwise x is not dominated by Y . If Y contains



■ **Figure 1** Example of an intractable case of the input-restricted problem. Thick lines indicate edges in X . There are at least 2^i minimal sets Y such that $(X \setminus \{x\}) \cup Y$ is an edge dominating set of G since we can take independently z_{2j-1} or z_{2j} for each $1 \leq j \leq i$. Note that $(X \setminus \{x\}) \cup Y$ needs not be minimal.

two edges $e \in \Gamma(u)$ and $f \in \Gamma(v)$, then the type-I neighbor of X with respect to (x, e, f) is “closer” than X to Y . On the other hand, if Y does not contain any edges in $\Gamma(v)$, we cannot find a type-I neighbor which is “closer” to Y . Then we dare to choose a “detour” by taking a type-II neighbor of X that covers $\Gamma(v)$ from the “outside” of $\Gamma(v)$. From this type-II neighbor, we can construct a directed path to Y by tracing a type-I neighbor of each minimal edge dominating set on the path.

To complete the description of \mathcal{G} , we define two types of neighbors of a minimal edge dominating set X defined as follows:


- For any edge $x = \{u, v\}$ in X , let e and f be edges such that $e \in \Gamma(u) \setminus \{x\}$ and $f \in \Gamma(v) \setminus \{x\}$. Note that e or f might belong to X . We say that $Z_1 = \mu((X \setminus \{x\}) \cup \{e, f\})$ is the *type-I neighbor of X with respect to (x, e, f)* . When either $\Gamma(u) \setminus \{x\}$ or $\Gamma(v) \setminus \{x\}$ is empty, say $\Gamma(v) = \{x\}$, then we define $Z_1 = \mu((X \setminus \{x\}) \cup \{e\})$, and we also call it the type-I neighbor of X with respect to (x, e) .
- For any edge $x = \{u, v\}$ in X , let $e \neq x$ be an edge that shares an end vertex, say u , with x . Define $W_{u,x,e}(X)$ as an arbitrary minimal set of edges such that $(X \setminus \{x\}) \cup (W_{u,x,e}(X) \cup \{e\})$ is an edge dominating set of G with $W_{u,x,e}(X) \cap \Gamma(v) = \emptyset$. Note that $W_{u,x,e}(X)$ may not be appropriately defined since $\Gamma(v)$ may contain an edge that cannot be dominated by any edge in $E \setminus \Gamma(v)$. If $W_{u,x,e}(X)$ is well-defined, we say that $Z_2 = \mu((X \setminus \{x\}) \cup (W_{u,x,e}(X) \cup \{e\}))$ is the *type-II neighbor of X with respect to (u, x, e)* .

Note that $W_{u,x,e}(X)$ is a minimal set of edges that excludes x and dominates edges of $\Gamma(v) \setminus \{x\}$ not dominated by $(X \setminus \{x\}) \cup \{e\}$. Thus, every edge in $W_{u,x,e}(X)$ has the private edge in $\Gamma(v)$. This also implies $W_{u,x,e}(X)$ contains at most $|\Gamma(v)| \leq \Delta$ edges. This observation is useful to analyze the delay of the algorithm in Theorem 20. We can easily see a type-I and type-II neighbor of X are always minimal edge dominating sets of G .

We first show that \mathcal{G} is strongly connected. Let X and Y be two distinct minimal edge dominating sets of G . We wish to prove that there is a neighbor Z of X such that $|Z \cup Y| < |X \cup Y|$, that is, Z is “closer” to Y than X in \mathcal{G} . However, X may not have such a neighbor. To prove the strong connectivity of \mathcal{G} , we show that if $X \neq Y$, then there always exists a desirable set Z with $|Z \cup Y| < |X \cup Y|$ such that \mathcal{G} has a directed path from X to Z .

► **Lemma 18.** *Let X and Y be distinct two minimal edge dominating sets of G and let $x = \{u, v\}$ be an edge in $X \setminus Y$. Without loss of generality, Y contains an edge e incident to u . If (a) Y contains an edge in $\Gamma(v)$ or (b) X contains an edge in $\Gamma(v) \setminus \{x\}$, then X has a type-I neighbor Z satisfying $|Z \cup Y| < |X \cup Y|$.*

Proof. If (a) holds, that is, Y contains an edge f in $\Gamma(v)$, then the type-I neighbor Z of X with respect to (x, e, f) satisfies $|Z \cup Y| \leq |(X \setminus \{x\}) \cup \{e, f\} \cup Y| < |X \cup Y|$.



■ **Figure 2** A running example of Lemma 19. We define $Z_0 = (X \setminus \{x\}) \cup \{\{w_3, w'_3\}, \{w_2, w_4\}, e\}$, where $W_{u,x,e}(X) = \{\{w_3, w'_3\}, \{w_2, w_4\}\}$ and $Z_0^* = \mu(Z_0)$. Edges $W_{u,x,e}(X)$ dominate undominated edges of $\Gamma(v)$ by $X \setminus \{x\}$. $Z_1^* = \mu(Z_0^* \cup \{\{w_2, w'_2\}, \{w_4, w'_4\}\} \setminus \{\{w_2, w_4\}\})$ is the type-I neighbor with respect to $(\{w_2, w_4\}, \{w_2, w'_2\}, \{w_4, w'_4\})$. Then, we have $|Z_1^* \cup Y| = 12 < 14 = |X \cup Y|$.

In what follows, we suppose that (a) does not hold but (b) holds. If $\Gamma(v)$ contains exactly one edge x , then the type-I neighbor Z of X with respect to (x, e) satisfies $|Z \cup Y| \leq |(X \setminus \{x\}) \cup \{e\} \cup Y| < |X \cup Y|$. Thus, in what follows, we assume that $\Gamma(v)$ contains more than one edges. Note that $|\Gamma(u)|$ is also more than one since $\Gamma(u)$ has at least two edges e and x .

Suppose that X contains edges in $\Gamma(v) \setminus \{x\}$. As Y has no edges incident to v and $x \notin Y$, Y contains at least one edge e incident to u . By the assumption that X has an edge f in $\Gamma(v) \setminus \{x\}$, x has no private edges incident to v at X , which implies that every private edge of x at X is incident to u . Hence, $Z' = (X \setminus \{x\}) \cup \{e, f\}$ is an edge dominating set of G . Moreover, $|X \cup Y| > |Z' \cup Y| \geq |\mu(Z') \cup Y|$ as $x \notin Y$ and $e \in Y$. Since $Z = \mu(Z')$ is the type-I neighbor of X with respect to (x, e, f) . ◀

We assume the condition of Lemma 18 does not hold, that is, $Y \cap \Gamma(v) = \emptyset$ and $X \cap \Gamma(v) = \{x\}$. By this assumption, Y contains at least one edge $e \in \Gamma(u)$ with $e \neq x$. Moreover, we assume that $\Gamma(v) \setminus \{x\}$ contains at least one edge as otherwise the type-I neighbor $Z = \mu((X \setminus \{x\}) \cup \{e\})$ of X satisfies $|Z \cup Y| < |X \cup Y|$ and hence we are done. From these assumptions, at Y , it follows that the edges in $\Gamma(v) \setminus \{x\}$ are dominated by edges not incident to v . Recall that $W_{u,x,e}(X)$ is defined to be an arbitrary minimal set of edges such that $(X \setminus \{x\}) \cup (W_{u,x,e}(X) \cup \{e\})$ is an edge dominating set with $W_{u,x,e}(X) \cap \Gamma(v) = \emptyset$. Such a set $W_{u,x,e}(X)$ is well-defined since Y contains edges not in $\Gamma(v)$ that dominates those in $\Gamma(v) \setminus \{x\}$. This observation yields the following lemma.

► **Lemma 19.** *Let X and Y be distinct minimal edge dominating sets of G . Let $x \in X \setminus Y$ with $x = \{u, v\}$. Suppose that $Y \cap \Gamma(v) = \emptyset$, $X \cap \Gamma(v) = \{x\}$, and Y contains an edge $e \neq x$ incident to u . Then, X has a type-II neighbor Z_0^* such that there is a directed path from Z_0^* to a minimal edge dominating set Z with $|Z \cup Y| < |X \cup Y|$.*

Proof. Let e_1, e_2, \dots, e_t be the edges in $W_{u,x,e}(X) \setminus Y$ in an arbitrary order, where $t = |W_{u,x,e}(X) \setminus Y|$, and let $Z_0^* = \mu((X \setminus \{x\}) \cup (W_{u,x,e}(X) \cup \{e\}))$ be the type-II neighbor of X . For each $1 \leq i \leq t$, we define Z_i^* as follows. If $e_i \notin Z_{i-1}^*$, we define $Z_i^* = Z_{i-1}^*$. A concrete example of Z_i^* can be found in Figure 2.

Suppose otherwise that $e_i \in Z_{i-1}^*$. Let $w_i \in N(v)$ that is one of the end vertices of e_i . Since Y has no edges incident to v and $e_i \notin Y$, there is an edge $f_i \in Y$ with $f_i \neq e_i$ that dominates edge $\{v, w_i\}$. Let $w'_i \neq w_i$ be the other end vertex of e_i (i.e., $e_i = \{w_i, w'_i\}$). If both w_i and w'_i are contained in $N(v)$, then Y has an edge $h_i \in \Gamma(w'_i) \setminus \Gamma(v)$ as otherwise edge $\{v, w'_i\}$ is not dominated by Y , contradicting to the fact that Y is an edge dominating set of G . We define Z_i^* as the type-I neighbor of Z_{i-1}^* with respect to (e_i, f_i, h_i) . Suppose next that w'_i is not contained in $N(v)$. By the minimality of $W_{u,x,e}(X)$, X has no edges incident to w_i . This implies that X contains an edge $h_i \in \Gamma(w'_i)$ dominating e_i . We then define Z_i^* as the type-I neighbor of Z_{i-1}^* with respect to (e_i, f_i, h_i) if $h_i \neq x$, and otherwise, define Z_i^* as the type-I neighbor of Z_{i-1}^* with respect to (e_i, f_i, e) . Note that if $h_i = x$, then one of the end vertices of e_i is u , and then Z_i^* is a legal type-I neighbor of Z_{i-1}^* . Finally, we have Z_t^* and denote it by Z . Since $f_i \in Y$, $h_i \in X \cup Y$, $e_i \notin X \cup Y$ for every $1 \leq i \leq t$, and $e \in Y$, we have $Z \subseteq X \cup Y$. Moreover, as $x \notin Z$, we have $|X \cup Y| > |Z \cup Y|$. ◀

Finally, we analyze the delay of the algorithm. Note that every minimal edge dominating sets has $O(n\Delta^2)$ neighbors. Moreover, computing type-I and type-II neighbors can be done in $O(n\Delta)$ time. The detail of this analysis can be found in the proof of the next theorem.

► **Theorem 20.** *One can enumerate all minimal edge dominating sets in a graph with $O(n^2\Delta^3)$ delay.*

Proof. Each minimal edge dominating set of G has $O(n\Delta^2)$ neighbors and computing each neighbor can be done in $O(n\Delta)$ time, assuming that the operation $\mu(\cdot)$ is done in time $O(n\Delta)$. Thus, we consider the time complexity to compute $\mu(\tilde{X})$. Let \tilde{X} be an edge dominating set of G . Since Π_{eds} is monotone property, we can compute $\mu(\tilde{X})$ as the following procedure:

1. Let $(e_1, \dots, e_{|\tilde{X}|})$ be the edges in \tilde{X} .
2. For each $1 \leq i \leq |\tilde{X}|$, if $\tilde{X} \setminus \{e_i\}$ is an edge dominating set of G , then we update \tilde{X} to $\tilde{X} \setminus \{e_i\}$.

To check the condition that $\tilde{X} \setminus \{e_i\}$ is an edge dominating set of G , it suffices to check whether $|\Gamma(u) \cup \Gamma(v) \cap (\tilde{X} \setminus \{e_i\})| \geq 1$ for any $\{u, v\} \in E$. This can be done in $O(\Delta)$ time for each Step 2 of the above procedure by simply keeping track of the value $|\Gamma(u) \cup \Gamma(v) \cap \tilde{X}|$ for each $\{u, v\} \in E$ and updating it in $O(\Delta)$ time when removing e_i from \tilde{X} . Hence, we can compute $\mu(\tilde{X})$ in $O(|\tilde{X}| \Delta)$ time. Finally, we consider the cardinality of \tilde{X} that appears in our algorithm. In our algorithm, we use function $\mu(\cdot)$ when computing type-I or type-II neighbors of a minimal edge dominating set X . By the definition of neighbors, \tilde{X} is either of the form $(X \setminus \{x\}) \cup \{e, f\}$ or of the form $(X \setminus \{x\}) \cup (W_{u,x,e}(X) \cup \{e\})$. For the former case, we have $|\tilde{X}| \leq |X| + 2$ and for the latter case, we have $|\tilde{X}| \leq |X| + |W_{u,x,e}(X)|$. Since $|W_{u,x,e}(X)|$ is at most Δ , which is observed at the definition of type-II neighbors, we have $|\tilde{X}| \leq |X| + \Delta$. Moreover, every minimal edge dominating set X is a star forest. To see this, it suffices to show that any minimal edge dominating set contains neither a cycle C_3 of three vertices nor a path P_4 of four vertices as a subgraph. If X contains a C_3 , then $X \setminus \{e\}$ is also an edge dominating set for any $e \in E(C_3)$. If X contains a $P_4 = (e_1, e_2, e_3)$, then $X \setminus \{e_2\}$ is also an edge dominating set, contradicting to the minimality of X . Thus, X is a star forest and hence $|X| \leq n - 1$. ◀

Since the best known delay of enumerating minimal edge dominating set is $O(n^6)$ due to [34], our result even improves the delay of minimal edge dominating set enumeration. Note that the algorithm in [34] runs in polynomial space, whereas ours runs in exponential space.

In order to extend the above enumeration algorithm to an approximate one for weight-constrained minimal edge dominating sets, we slightly modify the algorithm. According to the

definition of the type-II neighbor, we can arbitrarily choose a minimal edge set $W_{u,x,e}(X)$ such that $(X \setminus \{x\}) \cup (W_{u,x,e}(X) \cup \{e\})$ is an edge dominating set of G with $W_{u,x,e}(X) \cap \Gamma(v) = \emptyset$. However, for our approximate enumeration, $W_{u,x,e}(X)$ must have small weight. We observe that for every minimal edge dominating set Y of G with $Y \cap \Gamma(v) = \emptyset$, there is an edge set X^* such that $(X \setminus \{x\}) \cup (X^* \cup \{e\})$ is an edge dominating set of G , $X^* \cap \Gamma(v) = \emptyset$, and $w(X^*) \leq w(Y)$. This follows from the fact that $(X \setminus \{x\}) \cup (Y \cup \{e\})$ is indeed an edge dominating set of G and $Y \cap \Gamma(v) = \emptyset$.

To compute a small weight edge set X^* such that $(X \setminus \{x\}) \cup (X^* \cup \{e\})$ is an edge dominating set of G and $X^* \cap \Gamma(v) = \emptyset$, we use a polynomial-time approximation algorithm \mathcal{A} for the minimum weight edge dominating set problem. Consider an edge-weighted graph $H = \bigcup_{u' \in U'} \Gamma(u')$, where U' is set of vertices that has incident edges that are not dominated by $(X \setminus \{x\}) \cup \{e\}$. For each edge $e \in \Gamma(v) \cap E(H)$, we set $w'(e) := \infty$ and for each edge $e \in E(H) \setminus \Gamma(v)$, we set $w'(e) := w(e)$. It is not difficult to prove that $Y \cap E(H)$ is an edge dominating set of H . We apply \mathcal{A} to (H, w') and have an edge set X' such that $(X \setminus \{x\}) \cup (X' \cup \{e\})$ is an edge dominating set of G and $X' \cap \Gamma(v) = \emptyset$. Moreover, we have $w(X^*) \leq w(X') \leq c \cdot w(Y)$, where c is the approximation factor of \mathcal{A} .

The above lemma implies that every minimal edge dominating set on a suitable path on \mathcal{G} from X to Y does not have weight more than $w(X) + (c + 1)w(Y)$. Note that we can compute $W_{u,x,e}(X)$ in polynomial time with approximation factor $c = 2$ by a known approximation algorithm [28]. Hence, the main theorem of this subsection is established.

► **Theorem 21.** *There is a polynomial-delay 5-approximate enumeration algorithm for enumerating minimal edge dominating sets using polynomial time preprocessing.*

Proof. Let X be an arbitrary minimal edge dominating set of G with weight at most ck . We can find X in time polynomial by [28] with $c = 2$. For every minimal edge dominating set Y of weight at most k distinct from X , there is a type-I neighbor Z with $|Z \cup Y| < |X \cup Y|$ or a type-II neighbor Z_0^* such that there is a directed path $\mathcal{P} = (Z_0^*, Z_1^*, \dots, Z_t^* = Z)$ from Z_0^* to Z in \mathcal{G} with $|Z \cup Y| < |X \cup Y|$. Recall that, in the construction of Z_i^* , $Z_i^* = \mu((Z_{i-1}^* \setminus \{e_i\}) \cup \{f, h\})$ for some $e_i \in Z_{i-1}^* \setminus (X \cup Y)$ and $f, h \in X \cup Y$. It follows that $w(Z_i^* \cup X \cup Y) \leq w(Z_{i-1}^* \cup X \cup Y)$ for every $1 \leq i \leq t$. Thus, for every $0 \leq i \leq t$,

$$\begin{aligned} w(Z_i^* \cup Y) &\leq w(Z_0^* \cup X \cup Y) \\ &\leq w((X \setminus \{x\}) \cup (W_{u,x,e}(X) \cup \{e\}) \cup X \cup Y) \\ &\leq w(X \cup Y) + 2 \cdot w(Y). \end{aligned}$$

Since we compute $W_{u,x,e}(X)$ by a polynomial-time 2-approximation algorithm of [28], we have $W_{u,x,e}(X) \leq 2 \cdot w(Y)$. Thus, every “internal” minimal edge dominating set Z_i^* satisfies $w(Z_i^* \cup Y) \leq w(X \cup Y) + 2 \cdot w(Y) \leq 5k$. Therefore, we can eventually find such a minimal edge dominating set Z by traversing type-I or type-II neighbors of weight at most $5k$. By applying the same argument from Z to Y , every “internal” minimal edge dominating set Z' , we have $w(Z' \cup Y) \leq w(Z \cup Y) + 2 \cdot w(Y) < w(X \cup Y) + 2 \cdot w(Y) \leq 5k$. Therefore, by generating a type-I or a type-II neighbors of weight at most $5k$, we can, in polynomial delay, enumerate all the minimal edge dominating sets of G of weight at most k with approximation factor 5. ◀

6.2 Minimal Steiner subgraphs

Let $G = (V, E)$ be a graph and let $W \subseteq V$ be a set of terminals. In this subsection, we assume that $|W| \geq 2$. A subgraph H of G is a *Steiner subgraph* of (G, W) if there is a

path between every pair of vertices of W in H . It is easy to see that the property of being a Steiner subgraph of (G, W) is a monotone property over E . Moreover, every minimal Steiner subgraph forms a tree, called a *Steiner tree*. There are polynomial-delay enumeration algorithms for minimal Steiner trees [37, 38]. These algorithms are based on branching and it seems not to be easy to extend these algorithms to an approximate enumeration algorithm. Therefore, the goal of this subsection is to enumerate all the minimal Steiner trees of (G, W) in polynomial delay with an approximation guarantee.

Let Π_{ST} be the property of being a minimal Steiner subgraph of (G, W) and $w : E \rightarrow \mathbb{N}$ be a weight function. In this subsection, we may not distinguish between a subgraph and the set of edges in it. Unfortunately, the property Π_{ST} is not a CKS property. To see this, we consider a graph with two adjacent terminals s and t . Let x be the edge between s and t . Then, $X = \{x\}$ is a minimal Steiner tree of this graph and every other minimal Steiner trees is an s - t path avoiding x between s and t in the graph and hence there are exponentially many such paths in general. Thus, Π_{ST} is not a CKS property. However, we can solve (Π_{ST}, w, k) -IRP in polynomial delay since $\mathcal{S}(E, \Pi, w, k, X, x)$ contains all paths weight at most k between the two components of $X \setminus \{x\}$, which can be enumerated in polynomial delay by the k -best enumeration algorithm for s - t paths [40]. Moreover, since the minimum Steiner tree problem is polynomial-time approximable with factor 1.39 [12], by plugging these into Theorem 4, we obtain an incremental-polynomial time 3.39-approximate enumeration algorithm for minimal Steiner subgraphs. In this subsection, we further improve this result by giving a polynomial-delay 2.39-approximate enumeration algorithm for minimal Steiner subgraphs.

The technique we used here is also the supergraph technique. To this end, we define the neighbors of a minimal Steiner tree $X \subseteq E$ of (G, W) in the supergraph \mathcal{G} as follows. We extend function $\mu(\cdot)$ in such a way that for a vertex set $W' \subseteq V$ and a Steiner subgraph X of (G, W') , $\mu(X, W')$ is a minimal Steiner tree of (G, W') that is a subgraph of X . Let x be an edge in X . Since X is a tree, there are exactly two components C_1 and C_2 of $X \setminus \{x\}$. Recall that C_1 and C_2 are also considered as sets of edges. Let $e = \{u, v\}$ be an edge incident to a vertex in C_1 with $V(C_1) \cap \{u, v\} = \{u\}$ and $e \neq x$. Let $C'_1 = \mu(C_1 \cup \{e\}, W_1 \cup \{v\})$ and $C'_2 = \mu(C_2, W_2)$, where $W_i := W \cap V(C_i)$. Since $C_1 \cup \{e\}$ and C_2 are respectively Steiner subgraphs of $(G, W_1 \cup \{v\})$ and (G, W_2) , C'_1 and C'_2 are well-defined. Let $P_{x,e}$ be an arbitrary shortest v - w path in $G[V \setminus V(C'_1)]$, where w is a vertex in C'_2 . Let us note that $P_{x,e}$ might be a single vertex v when $v = w$. Observe that $C'_1 \cup C'_2 \cup P_{x,e}$ is a Steiner subgraph of (G, W) . This follows from the fact that $P_{x,e}$ connects two components $V(C'_1)$ and $V(C'_2)$. Then, $Z = \mu(C'_1 \cup C'_2 \cup P_{x,e})$ is defined to be a neighbor of X (with respect to (x, e)). The neighbor of X is defined to be the union of all neighbors with respect to possible pairs $x \in X$ and $e \in E \setminus \{x\}$. The number of neighbors of each minimal Steiner tree X is $O(nm)$, and we can enumerate all neighbors of X in polynomial time.

If \mathcal{G} is strongly connected, then we can enumerate all minimal Steiner trees in polynomial delay. We begin with proving that \mathcal{G} is strongly connected. Before proving the strong connectivity of \mathcal{G} , we observe the following auxiliary lemma, which are easy to verify.

► **Lemma 22.** *Let X and Y be a pair of minimal Steiner trees of (G, W) , $x \in X$, and C_1 and C_2 be the two components of $X \setminus \{x\}$. Then, Y has a path P that connects C_1 and C_2 .*

Proof. Since X is a minimal Steiner tree of (G, W) , C_1 and C_2 have terminals w_1 and w_2 , respectively. As Y is also a Steiner subgraph of (G, W) , Y has a w_1 - w_2 path P . Thus, P contains a subpath between vertices in C_1 and in C_2 . ◀

The idea to proving the strong connectivity is as follows. By Lemma 22, there is a

path P between C_1 and C_2 . If the shortest path $P_{x,e}$ is equal to P , then we are done: we can find a neighbor $Z \subseteq (X \setminus \{e\}) \cup P$ of X , which implies $|Z \cup Y| < |X \cup Y|$. Otherwise, by appropriately selecting edges for a neighbor Z' of Z , Z' contains “more edges” of P than Z in some sense. By repeating this, we can eventually find a neighbor Z^* satisfying $Z^* \subseteq (X \setminus \{e\}) \cup P$, proving that $|Z^* \cup P| \leq |Z^* \cup Y| < |X \cup Y|$. The key to the strong connectivity of \mathcal{G} is the following lemma.

► **Lemma 23.** *Let X and Y be a pair of minimal Steiner trees of (G, W) . Then, \mathcal{G} has a directed path from X to a minimal Steiner tree Z that satisfies $|Z \cup Y| < |X \cup Y|$.*

Proof. Let x_1 be an edge in $X \setminus Y$ and let C_1 and C_2 be the components of $X \setminus \{x_1\}$. By Lemma 22, there is a path P in Y between vertices in C_1 and in C_2 . Then, $(X \setminus \{x_1\}) \cup P$ is a Steiner subgraph of (G, W) . In the following, we show that there is a path from X to a minimal Steiner tree $Z \subseteq E$ of (G, W) in \mathcal{G} with $Z \subseteq (X \setminus \{x_1\}) \cup P$, implying that

$$|Z \cup Y| \leq |(X \setminus \{x_1\}) \cup P \cup Y| < |X \cup Y|.$$

Let e_1, \dots, e_t be the sequence of edges of P appearing in this order such that e_1 and e_t are incident to a vertex in C_1 and a vertex in C_2 , respectively. For each $1 \leq i \leq t$, we let $e_i = \{v_i, v_{i+1}\}$. As $e_i \in Y$, we have $x_1 \neq e_i$ for $1 \leq i \leq t$. We consider the neighbor X_1 of X with respect to (x_1, e_1) . Let $C'_1 = \mu(C_1 \cup \{e\}, W_1 \cup \{v\})$ and $C'_2 = \mu(C_2, W_2)$, where $W_i = W \cap V(C_i)$. If $X_1 \subseteq (X \setminus \{x_1\}) \cup P$, we are done. Assume otherwise. Let P_{x_1, e_1} be the shortest path used in defining X_1 . By the assumption, we have $P_{x_1, e_1} \neq P$. Since P_{x_1, e_1} contains e_1 , P and P_{x_1, e_1} have common edge e_1 . Let e_{i_1} be the edge in P such that for every $1 \leq i \leq i_1$, $e_i \in P_{x_1, e_1}$ and $e_{i_1} \notin P_{x_1, e_1}$. By the definition of P_{x_1, e_1} , we have $i_1 > 1$. Let $x_2 \neq e_{i_1-1}$ be the edge of P_{x_1, e_1} that shares end vertex v_{i_1} with e_{i_1} . Then, observe that the neighbor X_2 of X_1 with respect to (x_2, e_{i_1}) has all edges e_1, \dots, e_{i_1} . This follows from the fact that we define $P_{x_2, e_{i_1}}$ as a shortest path between the two components of $C''_1 = \mu((X_1 \setminus \{x_2\}) \cup \{e_{i_1}\}, W_1 \cup \{v_{i_1+1}\})$ and $C''_2 = \mu(X_1 \setminus \{x_2\}, W_2)$ and v_{i_1+1} is considered as a terminal, which implies that e_1, \dots, e_{i_1} are all bridges in C''_1 and thus these edges are contained in X_2 . Moreover, we claim that $X_2 \setminus C_1 \cup C_2 \cup \{e_1, \dots, e_{i_1}\} \cup P_{x_2, e_{i_1}}$. This follows from the following facts: $C''_1 \subseteq C_1 \cup \{e_1, \dots, e_{i_1}\}$; $C''_2 \subseteq C_2$.

By repeatedly applying this argument, we can eventually find a minimal Steiner tree Z that contains all edges in P and hence we have $Z \subseteq C_1 \cup C_2 \cup \{e_1, \dots, e_t\} \subseteq (X \setminus \{x_1\}) \cup P$. ◀

Thus, we can enumerate all minimal Steiner trees in polynomial delay. Next, we prove that we can approximately enumerate all minimal Steiner trees with the approximation factor $c + 1$. Suppose that we have a polynomial-time c -approximation algorithm for finding a minimum weight Steiner tree. Let X be a minimal Steiner tree of (G, W) whose weight is at most ck . By Lemma 23, \mathcal{G} has a directed path from X to every minimal Steiner tree Y with weight at most k . To show that we can approximately enumerate all solutions, we prove that every internal node on the directed path has weight at most $(c + 1)k$.

► **Lemma 24.** *Let X and Y be a pair of minimal Steiner tree of (G, W) with weight at most ck and k , respectively. Then, \mathcal{G} has a directed path from X to Y on which any minimal Steiner tree has weight at most $(c + 1)k$.*

Proof. Let Z be a minimal Steiner tree of (G, W) defined in Lemma 23. Then, \mathcal{G} has a directed path from X to Z . In the proof of Lemma 23, we have shown that $X_j \subseteq C_1 \cup C_2 \cup \{e_1, \dots, e_{i_j-1}\} \cup P_{x_j, e_{i_j}}$ for every minimal Steiner tree X_j on the path from X to

Z . Since $P_{x_j, e_{i_j}}$ is chosen as a shortest path, its weight is at most $w(\{e_{i_j-1}, \dots, e_t\})$. Thus, we have

$$\begin{aligned} w(X_j) &\leq w(C_1 \cup C_2 \cup \{e_1, \dots, e_{i_j-1}\} \cup P_{x_j, e_{i_j}}) \\ &< w(X \cup P) \\ &\leq w(X \cup Y) \\ &\leq (c+1)k. \end{aligned}$$

By applying Lemma 23 again for Z and Y , every solution Z' from Z to Y , we also have

$$w(Z') \leq w(Z \cup Y) < w(X \cup Y) \leq (c+1)k,$$

as $Z \subseteq X \cup Y$, completing the proof of lemma. \blacktriangleleft

Note that there can be a directed path from X to Y in \mathcal{G} that has an internal node corresponding to a minimal Steiner tree with weight more than $(c+1)k$. In our enumeration algorithm, we simply ignore such solutions and, by Lemmas 23 and 24, the “trimmed” supergraph still has a directed path from any solution with weight at most ck to any solution with weight at most k . Therefore, we obtain the following theorem.

► **Theorem 25.** *There is a polynomial-delay 2.39-approximate enumeration algorithm for enumerating minimal Steiner trees using polynomial time preprocessing*

References

- 1 Akanksha Agrawal, Sudeshna Kolay, Daniel Lokshtanov, and Saket Saurabh. A Faster FPT Algorithm and a Smaller Kernel for Block Graph Vertex Deletion. In *Proc. of LATIN 2016*, volume 9644 of *LNCS*, pages 1–13. Springer Berlin Heidelberg, 2016.
- 2 Akanksha Agrawal, Daniel Lokshtanov, Pranabendu Misra, Saket Saurabh, and Meirav Zehavi. Polylogarithmic Approximation Algorithms for Weighted- \mathcal{F} -Deletion Problems. In *Proc. of APPROX/RANDOM 2018*, volume 116 of *LIPICs*, pages 1:1–1:15, 2018.
- 3 Zahi Ajami and Sara Cohen. Enumerating Minimal Weight Set Covers. In *Proc. of ICDE 2019*, pages 518–529, 2019.
- 4 Manuel Aprile, Matthew Drescher, Samuel Fiorini, and Tony Huynh. A tight approximation algorithm for the cluster vertex deletion problem. *CoRR*, abs/2007.08057, 2020.
- 5 Stefan Arnborg, Jens Lagergren, and Detlef Seese. Easy problems for tree-decomposable graphs. *J. Algorithm*, 12(2):308–340, 1991.
- 6 David Avis and Komei Fukuda. Reverse search for enumeration. *Discrete Applied Mathematics*, 65(1):21–46, 1996.
- 7 Reuven Bar-Yehuda and Shimon Even. A linear-time approximation algorithm for the weighted vertex cover problem. *J. Algorithms*, 2(2):198–203, 1981.
- 8 Ann Becker and Dan Geiger. Optimization of Pearl’s method of conditioning and greedy-like approximation algorithms for the vertex feedback set problem. *Artificial Intelligence*, 83(1):167–188, 1996.
- 9 Endre Boros, Khaled M. Elbassioni, Vladimir Gurvich, and Leonid Khachiyan. Enumerating Minimal Dcuts and Strongly Connected Subgraphs and Related Geometric Problems. In *Proc. of IPCO*, volume 3064 of *LNCS*, pages 152–162, 2004.
- 10 Endre Boros, Khaled M. Elbassioni, Vladimir Gurvich, and Leonid Khachiyan. Generating Maximal Independent Sets for Hypergraphs with Bounded Edge-Intersections. In *Proc. of LATIN 2004*, volume 2976 of *LNCS*, pages 488–498, 2004.
- 11 Caroline Brosse, Aurélie Lagoutte, Vincent Limouzy, Arnaud Mary, and Lucas Pastor. Efficient enumeration of maximal split subgraphs and sub-cographs and related classes, 2020.

- 12 Jarosław Byrka, Fabrizio Grandoni, Thomas Rothvoss, and Laura Sanità. Steiner Tree Approximation via Iterative Randomized Rounding. *J. ACM*, 60(1), 2013.
- 13 Yixin Cao. Enumerating Maximal Induced Subgraphs. *CoRR*, abs/2004.09885, 2020.
- 14 V. Chvatal. A Greedy Heuristic for the Set-Covering Problem. *Math. Oper. Res.*, 4(3):233–235, 1979.
- 15 Sara Cohen, Benny Kimelfeld, and Yehoshua Sagiv. Generating all maximal induced subgraphs for hereditary and connected-hereditary graph properties. *J. Comput. Syst. Sci.*, 74(7):1147–1159, 2008.
- 16 Alessio Conte and Takeaki Uno. New polynomial delay bounds for maximal subgraph enumeration by proximity search. In *Proc. of STOC 2019*, pages 1179–1190, 2019.
- 17 Bruno Courcelle. The monadic second-order logic of graphs. I. Recognizable sets of finite graphs. *Inform. Comput.*, 85(1):12–75, 1990.
- 18 Nadia Creignou, Arne Meier, Julian-Steffen Müller, Johannes Schmidt, and Heribert Vollmer. Paradigms for Parameterized Enumeration. *Theor. Comp. Sys.*, 60(4):737–758, 2017.
- 19 Marek Cygan, Fedor V. Fomin, Lukasz Kowalik, Daniel Lokshtanov, Daniel Marx, Marcin Pilipczuk, Michal Pilipczuk, and Saket Saurabh. *Parameterized Algorithms*. Springer Publishing Company, Incorporated, 1st edition, 2015.
- 20 Shaleen Deep and Paraschos Koutris. Ranked Enumeration of Conjunctive Query Results. *CoRR*, abs/1902.02698, 2019.
- 21 Erik D. Demaine, Timothy D. Goodrich, Kyle Kloster, Brian Lavalley, Quanquan C. Liu, Blair D. Sullivan, Ali Vakilian, and Andrew van der Poel. Structural Rounding: Approximation Algorithms for Graphs Near an Algorithmically Tractable Class. In *Proc. of ESA 2019*, volume 144 of *LIPICs*, pages 37:1–37:15, 2019.
- 22 Matthew Drescher, Samuel Fiorini, and Tony Huynh. A simple $(2+\epsilon)$ -approximation algorithm for split vertex deletion. *CoRR*, abs/2009.11056, 2020.
- 23 David Eppstein. k -Best Enumeration. In *Encyclopedia of Algorithms*, pages 1003–1006. Springer, New York, NY, 2016.
- 24 Ronald Fagin, Amnon Lotem, and Moni Naor. Optimal aggregation algorithms for middleware. *J. Comput. Syst. Sci.*, 66(4):614–656, 2003.
- 25 Henning Fernau. On Parameterized Enumeration. In *Proc. of COCOON 2002*, volume 2387 of *LNCS*, pages 564–573, 2002.
- 26 Fedor V. Fomin, Daniel Lokshtanov, Neeldhara Misra, and Saket Saurabh. Planar F -Deletion: Approximation, Kernelization and Optimal FPT Algorithms. In *Proc. of FOCS 2012*, page 470–479, 2012.
- 27 Michael L. Fredman and Leonid Khachiyan. On the Complexity of Dualization of Monotone Disjunctive Normal Forms. *J. Algorithms*, 21(3):618–628, 1996.
- 28 Toshihiro Fujito. Approximating Bounded Degree Deletion via Matroid Matching. In *Proc. of CIAC 2017*, pages 234–246, Cham, 2017. Springer International Publishing.
- 29 Harold N. Gabow. Two Algorithms for Generating Weighted Spanning Trees in Order. *SIAM J. Comput.*, 6(1):139–150, 1977.
- 30 Walter Hoffman and Richard Pavley. A Method for the Solution of the N th Best Path Problem. *J. ACM*, 6(4):506–514, 1959.
- 31 Satoru Iwata and Kiyohito Nagano. Submodular function minimization under covering constraints. In *50th Annual IEEE Symposium on Foundations of Computer Science, FOCS 2009, October 25-27, 2009, Atlanta, Georgia, USA*, pages 671–680. IEEE Computer Society, 2009.
- 32 David S. Johnson, Mihalis Yannakakis, and Christos H. Papadimitriou. On generating all maximal independent sets. *Inform. Process. Lett.*, 27(3):119 – 123, 1988.
- 33 Mamadou Moustapha Kanté, Vincent Limouzy, Arnaud Mary, and Lhouari Nourine. Enumeration of Minimal Dominating Sets and Variants. In *Proc. of FCT 2011*, volume 6914 of *LNCS*, pages 298–309, 2011.

- 34 Mamadou Moustapha Kanté, Vincent Limouzy, Arnaud Mary, Lhouari Nourine, and Takeaki Uno. Polynomial Delay Algorithm for Listing Minimal Edge Dominating Sets in Graphs. In *Proc. of WADS 2015*, pages 446–457, 2015.
- 35 Leonid Khachiyan, Endre Boros, Konrad Borys, Khaled M. Elbassioni, Vladimir Gurvich, and Kazuhisa Makino. Generating Cut Conjunctions in Graphs and Related Problems. *Algorithmica*, 51(3):239–263, 2008.
- 36 Benny Kimelfeld and Yehoshua Sagiv. Finding and approximating top-k answers in keyword proximity search. In *Proc. of PODS 2006*, pages 173–182, 2006.
- 37 Benny Kimelfeld and Yehoshua Sagiv. Efficiently enumerating results of keyword search over data graphs. *Inf. Syst.*, 33(4-5):335–359, 2008.
- 38 Yasuaki Kobayashi, Kazuhiro Kurita, and Kunihiro Wasa. Polynomial delay enumeration for minimal steiner problems, 2020.
- 39 Stephan Kreutzer. *Algorithmic meta-theorems*, page 177–270. London Mathematical Society Lecture Note Series. Cambridge University Press, 2011.
- 40 Eugene L. Lawler. A Procedure for Computing the K Best Solutions to Discrete Optimization Problems and Its Application to the Shortest Path Problem. *Manage. Sci.*, 18(7):401–405, 1972.
- 41 Daniel Lokshtanov, Pranabendu Misra, Fahad Panolan, Geevarghese Philip, and Saket Saurabh. A $(2 + \epsilon)$ -factor approximation algorithm for split vertex deletion. In Artur Czumaj, Anuj Dawar, and Emanuela Merelli, editors, *47th International Colloquium on Automata, Languages, and Programming, ICALP 2020, July 8-11, 2020, Saarbrücken, Germany (Virtual Conference)*, volume 168 of *LIPIcs*, pages 80:1–80:16. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2020.
- 42 V. Lozin and D. Rautenbach. On the Band-, Tree-, and Clique-Width of Graphs with Bounded Vertex Degree. *SIAM J. Discrete Math.*, 18(1):195–206, 2004.
- 43 Katta G. Murty. Letter to the Editor—An Algorithm for Ranking all the Assignments in Order of Increasing Cost. *Oper. Res.*, 16(3):682–687, 1968.
- 44 Michael Okun and Amnon Barak. A new approach for approximating node deletion problems. *Inform. Process. Lett.*, 88(5):231 – 236, 2003.
- 45 Geevarghese Philip, Venkatesh Raman, and Yngve Villanger. A Quartic Kernel for Pathwidth-One Vertex Deletion. In *WG 2010*, volume 6410 of *LNCS*, pages 196–207, 2010.
- 46 Noam Ravid, Dori Medini, and Benny Kimelfeld. Ranked Enumeration of Minimal Triangulations. In *Proc. of PODS 2019*, pages 74–88, 2019.
- 47 Neil Robertson and P.D Seymour. Graph minors. V. Excluding a planar graph. *J. Comb. Theory B*, 41(1):92 – 114, 1986.
- 48 Benno Schwikowski and Ewald Speckenmeyer. On enumerating all minimal solutions of feedback problems. *Discret. Appl. Math.*, 117(1-3):253–265, 2002.
- 49 Yann Strozecki. Enumeration Complexity. *Bull. EATCS*, 129, 2019.
- 50 Shuji Tsukiyama, Mikio Ide, Hiromu Ariyoshi, and Isao Shirakawa. A New Algorithm for Generating All the Maximal Independent Sets. *SIAM J. Comput.*, 6(3):505–517, 1977.
- 51 Nikolaos Tziavelis, Wolfgang Gatterbauer, and Mirek Riedewald. Optimal Join Algorithms Meet Top-k. In *Proc. of SIGMOD 2020*, pages 2659–2665, 2020.
- 52 Vijay V. Vazirani and Mihalis Yannakakis. Suboptimal Cuts: Their Enumeration, Weight and Number (Extended Abstract). In *Proc. of ICALP 1992*, volume 623 of *LNCS*, page 366–377, 1992.