

CryptoCredit: Securely Training Fair Models

Leo de Castro
MIT CSAIL
Cambridge, Massachusetts
ldc@mit.edu

Jiahao Chen
J.P.Morgan AI Research
New York, New York
jiahao.chen@jpmorgan.com

Antigoni Polychroniadou
J.P.Morgan AI Research
New York, New York
antigoni.poly@jpmorgan.com

ABSTRACT

When developing models for regulated decision making, sensitive features like age, race and gender cannot be used and must be obscured from model developers to prevent bias. However, the remaining features still need to be tested for correlation with sensitive features, which can only be done with the knowledge of those features. We resolve this dilemma using a fully homomorphic encryption scheme, allowing model developers to train linear regression and logistic regression models and test them for possible bias without ever revealing the sensitive features in the clear. We demonstrate how it can be applied to leave-one-out regression testing, and show using the adult income data set that our method is practical to run.

CCS CONCEPTS

• **Applied computing** → **Economics**; • **Theory of computation** → **Cryptographic protocols**; • **Computing methodologies** → **Supervised learning by regression**.

KEYWORDS

fully homomorphic encryption, logistic regression, Wald test

ACM Reference Format:

Leo de Castro, Jiahao Chen, and Antigoni Polychroniadou. 2020. CryptoCredit: Securely Training Fair Models. In *ACM International Conference on AI in Finance (ICAIF '20)*, October 15–16, 2020, New York, NY, USA. ACM, New York, NY, USA, 9 pages. <https://doi.org/10.1145/3383455.3422567>

1 INTRODUCTION

Major institutions are incorporating machine learning systems to drive decisions more efficiently and accurately in tasks such as loan approval, prediction of defaults and fraud detection. While machine learning algorithms progress rapidly and transform the industry, they introduce the following challenge:

How can we ensure that machine learning algorithms do not inadvertently perpetuate bias that is inherent in the training data?

In a well-known example of historical bias appearing in a machine learning model, in 2016 a model to predict future criminal recidivism turned out to be biased against African-Americans [2, 16].

More and more financial institutions have developed teams of machine learning experts to develop models of creditworthiness. These models are trained on historical credit data, which raises concerns that these models could perpetuate historical biases against marginalized groups [4, 15, 22]. To address this concern, some consumer financial institutions have also developed compliance teams that are responsible for ensuring that the methods to determine credit do not violate federal anti-discrimination laws.

One of the basic distinctions between the compliance team and the machine learning team is that the compliance team is able to see all fields in the customer database, including those corresponding to classes protected by anti-discrimination law (i.e. age, race, sex, etc.) [9], while the machine learning team is only able to see a subset of the data fields. The compliance team determines which features the machine learning team is allowed to see and, subsequently, use to train their models.

Obviously, the fields directly corresponding to the protected classes are not allowed to be viewed by the machine learning team. However, biases in the data could allow a model to implicitly learn these protected fields. This is represented by previously unprotected fields having strong correlation with the protected field. A classic example of this phenomenon is race and zip code, known as redlining [12, 19]. Even if a machine learning model does not directly use the race field during training, if the zip code field is also used during training, then the model could implicitly learn the race field since, in many areas, race and zip codes are highly correlated. This would be a reason that the compliance team would remove the zip code field from the fields available to the machine learning team.

However, discovering these correlations is often difficult, since the bulk of the machine learning expertise is concentrated in the machine learning teams, who are not allowed to see the protected fields. The machine learning team could potentially assess whether or not there is unconscious bias in the training data by building models to predict the prohibitive features from the rest of the features. This state of affairs introduces another challenge:

How can we ensure that privacy of prohibitive features is preserved when the model is trained?

To solve this seemingly paradoxical problem, we use cryptography. Modern cryptography employs a rigorous mathematical approach to compute on encrypted data. A cryptographic tool, called Fully Homomorphic Encryption (FHE) solves the problem of secure computation between two parties, Alice and Bob. More specifically, Alice has an input x and Bob has a function f . Alice wishes to outsource the computation of $f(x)$ to Bob without revealing x . FHE allows Alice to encrypt her input x into a ciphertext ct_x that

Permission to make digital or hard copies of part or all of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for third-party components of this work must be honored. For all other uses, contact the owner/author(s).
ICAIF '20, October 15–16, 2020, New York, NY, USA
© 2020 Copyright held by the owner/author(s).
ACM ISBN 978-1-4503-7584-9/20/10.
<https://doi.org/10.1145/3383455.3422567>

can be safely sent to Bob. Bob can then homomorphically evaluate the function f on the ciphertext ct_x to produce a new ciphertext $\text{ct}_{f(x)}$ that encrypts $f(x)$. This resulting ciphertext $\text{ct}_{f(x)}$ is returned to Alice, who decrypts to obtain $f(x)$.

1.1 Our Contributions

We frame the problem of securely developing a fair ML model as a secure computation outsourcing problem. More specifically, the compliance team has training data X that must be kept private. At the same time, the compliance team has limited computing resources and needs to outsource the training of the ML model to the machine learning team. This problem can be solved with FHE, since the compliance team can encrypt the training data set X and send only the ciphertext to the machine learning team. The machine learning team then trains their model over the encrypted data set, then returns the model to the compliance team.

Not all aspects of the training data set are hidden from the machine learning team. The feature labels (or *schema*) are revealed to the machine learning team, and, in addition, the feature labels are indicated as either protected or unprotected. Only the unprotected features are used in training the ML models, but the protected features are very useful in evaluating fairness tests on these ML models.

In Section 3, we introduce one of the simplest methods for fairness testing in regression models, which are commonly used in econometrics and other financial applications [3, 31]. The basic idea is leave-one-out regression, in which we train two regression models using the same feature set X , but including also S in only one of the models. The idea is then to test whether or not the coefficients in these two models show statistically significant differences. We present the classical approach to hypothesis testing using Wald tests to test the equality of regression coefficients [37]. In Section 4, we show how to use our privacy preserving techniques to perform these LOO regression by training on the encrypted features. In Section 5, we apply our analysis of leave-one-out regression and Wald’s test to the UCI Adult data set [17, 25], a well-studied data set of extracted census data with many fields similar to a loan application. When training in a privacy preserving manner a linear model on this data set, we found that our test revealed biases in the training data that were learned by the model. Specifically, we found the linear model learned the correlation between the “Age” feature and the “Marital Status” feature, with the “Never Married” feature and the “Widowed” feature having the strongest correlation. This aligns nicely with intuition.

In addition, we found that certain models were better than others at detecting biases in the training data. Specifically, while the linear regression model was able to detect strong biases in the training data, the logistic regression model did not seem to learn this correlation, despite having essentially the same accuracy as the linear model.

1.2 Related Work

Fairness in artificial intelligence. In recent years, concerns over fairness in automated decision-making systems has received well-deserved attention [29, 39], particularly in predictive policing [2, 6, 11, 16, 28] and credit decisioning [1, 10, 15]. Fairness is enshrined in

regulatory requirements for some applications, notably in credit [9, 15] and hiring decisions [13, 19, 26, 32]. Several authors have criticized the use of automated decision making without regard to fairness or interpretability needs in other applications [14, 35, 36, 40]. However, most of the work focuses on binary outcome variables, and less so on continuous outcomes which result from regression studies. Nevertheless, the work of Kleinberg et al. [24], Pleiss et al. [30] on calibration notions of fairness deserve special attention, as being applicable specifically to regression models with continuous outcomes.

As described in the introduction, our work is based on a direct analysis of the coefficients of regression models, as is common in econometric analysis with a history going back at least to Conway and Roberts [13]. A similar (but not identical) treatment of linear regression models is given in Pope and Sydnor [31]. Similar ideas also appear in the leave one covariate out (LOCO) method of Lei et al. [27] for explaining variable-level importance.

2 BACKGROUND

2.1 Notation & Terminology

DEFINITION 2.1 (DATA SCHEMA). For a data set $\mathcal{D}$, denote the schema for $\mathcal{D}$ as $\mathcal{S}_{\mathcal{D}}$. The schema of the dataset consists of the labels of the features of the dataset.

DEFINITION 2.2 (DATA SET SELECT OPERATION). Let $\mathcal{D}$ be a data set with schema $\mathcal{S}_{\mathcal{D}}$, and let $\mathcal{S}_{\mathcal{T}} \subseteq \mathcal{S}_{\mathcal{D}}$ denote a subset of the features in $\mathcal{S}_{\mathcal{D}}$. The Select operation takes in a subset of features $\mathcal{S}_{\mathcal{T}}$ along with a data set $\mathcal{D}$ and produces a new dataset $\mathcal{T}$ with the same entries as in $\mathcal{D}$ except with only the features in $\mathcal{S}_{\mathcal{T}}$.

$$\mathcal{T} \leftarrow \text{Select}(\mathcal{S}_{\mathcal{T}}, \mathcal{D})$$

For a subset T of a set S , denote the compliment of T in S by T^c , where $T^c \cap T = \emptyset$ and $T^c \cup T = S$. We also denote $T^c = S \setminus T$.

2.2 Leave-One-Out Regression

In this section, we describe leave-one-out (LOO) regression, which is fundamental tool for the statistical tests we perform on machine learning models in this work. The goal of LOO regression is to determine how a given feature f in a data set $\mathcal{D}$ is related to the other features in the data set. The high-level idea is to train a model $\mathcal{M}$ on the data set $\mathcal{D}$, then train a second model $\mathcal{M}'$ on the data set $\mathcal{D} \setminus \{f\}$, then measure how the coefficients of the model $\mathcal{M}'$ differ from the original model $\mathcal{M}$. If the weights corresponding to another feature f' change significantly, then we conclude that f' and f are correlated.

2.3 Cryptographic Notions

In this section, we give high level definitions for the cryptographic primitives that we will use in the protocols below. All of these primitives will be used in a black-box manner.

A fully homomorphic encryption scheme allows us to perform arbitrary computations on encrypted data without decrypting it. Although the notion was introduced back in [33], the first implementation is due to a much later breakthrough of [20], and has now been followed with much exciting activity [7, 8, 38]. In a nutshell, the data owner can encrypt a message m using a private key to produce some ciphertext c , which can be sent to some external party.

The external party can then compute any function f on the ciphertext, which will result in a new ciphertext c' that corresponds to $f(m)$. The data owner can then decrypt c' to obtain $f(m)$.

FHE solves the problem of secure computation between two parties, a compliance team Comp and a machine learning team ML : Comp encrypts their input and sends it to ML, who can homomorphically evaluate the function on Comp's encrypted input and its own input, sending only the resulting ciphertext back to Comp, who can decrypt.

We formalize the algorithms that comprise a fully homomorphic encryption scheme.

DEFINITION 2.3 (FULLY HOMOMORPHIC ENCRYPTION). *A fully homomorphic encryption scheme*

$\text{FHE} = (\text{KeyGen}, \text{Encrypt}, \text{Eval}, \text{Decrypt})$

is a set of probabilistic polynomial-time algorithms defined as follows:

- $\text{KeyGen}(1^\lambda) \rightarrow (\text{sk}, \text{pk}, \text{evk})$
Given the security parameter λ , outputs a key pair consisting of a public encryption key pk , a secret decryption key sk , and an evaluation key evk .
- $\text{Encrypt}(\text{pk}, m) \rightarrow \text{ct}$
Given a message $m \in \mathcal{M}$ and an encryption key pk , outputs a ciphertext ct .
- $\text{Eval}(\text{evk}, f, \text{ct}_1, \text{ct}_2, \dots, \text{ct}_n) \rightarrow \text{ct}'$
Given the evaluation key, a description of a function $f: \mathcal{M}^n \rightarrow \mathcal{M}$, and n ciphertexts encrypting messages $m_1, \dots, m_n$, outputs the result ciphertext ct' encrypting $m' = f(m_1, \dots, m_n)$.
- $\text{Decrypt}(\text{sk}, \text{ct}) = m$
Given the secret decryption key and a ciphertext ct encrypting m , outputs m .

We now briefly provide intuition for the security definition of an FHE scheme. Note that our only concern is security for the compliance team, and we will not consider any security notion for the machine learning team¹. The standard and most basic security definition of an encryption scheme is known as *semantic security* [21].

DEFINITION 2.4 (SEMANTIC SECURITY [21]). *An FHE scheme satisfies semantic security if no probabilistic polynomial time adversary $\mathcal{A}$ can succeed in the following task with probability greater than $1/2 + \text{negl}(\lambda)$, where $\text{negl}(\lambda)$ is a function that shrinks faster than $1/\text{poly}(\lambda)$ for every polynomial poly .*

$\mathcal{A}$ takes as input pk and evk and produces two messages $m_1, m_2 \in \mathcal{M}$. $\mathcal{A}$ then takes in the encryptions of m_1 and m_2 , denoted ct_1 and ct_2 , in a random order. $\mathcal{A}$ must then decide which ciphertext is an encryption of m_1 and which ciphertext is an encryption of m_2 .

Intuitively, Definition 2.4 says that the encryptions of two messages should be indistinguishable, even for adversarially chosen messages. As encryption schemes, all known FHE schemes satisfy this security definition.

¹This is often referred to as *circuit privacy* or *function privacy* in the FHE literature.

3 LEAVE-ONE-OUT REGRESSION AND WALD'S TEST

In this section, we present a series of tests that we will perform on trained models to approach a model that is independent of a set of protected features. The setting is formally similar to that of covariate adjustment [34], and is also similar, but not identical to, the treatment of Pope and Sydnor [31]. Let $S = (S_1, S_2, \dots, S_{n_s})$ be set of sensitive features, $X = (X_1, X_2, \dots, X_{n_x})$ be the set of ordinary features, and Y be the target variable (with prediction $\hat{Y}$).

The idea is to create two linear regression models

$$\mathcal{M} : Y = X\beta + S\gamma + \epsilon_{\mathcal{M}}, \text{ and} \quad (1)$$

$$\mathcal{M}' : Y = X\zeta + \epsilon_{\mathcal{M}'}, \quad (2)$$

where $\beta \in \mathbb{R}^{n_x}$, $\gamma \in \mathbb{R}^{n_s}$, and $\zeta \in \mathbb{R}^{n_x}$ are the vectors of regression coefficients and $\epsilon_{\mathcal{M}}, \epsilon_{\mathcal{M}'}$ are the corresponding noise terms.

Alternatively, we may also consider a similar pair of logistic regression models

$$\mathcal{M} : \log \frac{Y}{1-Y} = X\beta + S\gamma + \epsilon_{\mathcal{M}}, \text{ and} \quad (3)$$

$$\mathcal{M}' : \log \frac{Y}{1-Y} = X\zeta + \epsilon_{\mathcal{M}'}, \quad (4)$$

with similarly defined symbols. To abuse notation, we distinguish linear regression from logistic regression modeling by discussion context, keeping the same notation for consistency of discussion. Nevertheless, β_i will always refer to the regression coefficient for the i th feature, regardless of regression model, and similarly for γ_i and ζ_i .

We can now use the generalized Wald's test to test constraints on the regression parameters [37]. Let N be number of data points, n_X be the number of ordinary features, which is the number of columns of X , n_S be the number of sensitive features, which is the number of columns of S , D be a diagonal matrix with the first $n_X + n_S$ entries equal to $1/(N - n_X - n_S)$ and the next n_X entries equal to $N - n_X$, whose i th diagonal entry counts the degrees of freedom used to estimate the i th coefficient, and $\theta = (\beta \ \gamma \ \zeta)^T \in \mathbb{R}^{2n_X+n_S}$ be the vector of all coefficients belonging to both models. Furthermore, let $\hat{\theta} = (\hat{\beta} \ \hat{\gamma} \ \hat{\zeta})^T \in \mathbb{R}^{2n_X+n_S}$ be the estimators for the parameters, and $\mathbb{E}(\cdot)$ denote the expectation value. To test hypotheses of the form $H\theta = c$, where H is a matrix of size $k \times (2n_X + n_S)$, construct the test statistic

$$W = (H\hat{\theta} - c)^T (HD^{1/2}\hat{\Sigma}D^{1/2}H^T)^{-1} (H\hat{\theta} - c) \sim \chi_k^2, \quad (5)$$

where $\hat{\theta}$ are the estimates for the parameters, and $\hat{\Sigma} = \mathbb{E}((\hat{\theta} - \mathbb{E}\hat{\theta})(\hat{\theta} - \mathbb{E}\hat{\theta})^T)$ is the estimated covariance matrix for the parameters.

This general form of Wald's test allows us to test multiple equalities simultaneously. The multiple equality testing can be useful for testing hypotheses like $\beta = \zeta$, testing equalities of all the coefficients simultaneously, $\gamma = 0$ for testing for the null effect of S , or more fine-grained tests where multiple dummy variables encoding the same categorical variable can be tested. Nevertheless, in this paper, we focus exclusively on hypothesis involving one

equality test for simplicity, while being illustrative of the general case. More specifically, we test pairwise equality hypotheses of the form $\beta_i = \zeta_i$, each to be tested against their corresponding alternative hypothesis $\beta_i \neq \zeta_i$. Let H_i be the $1 \times (2n_X + n_S)$ matrix with the $(1, i)$ th entry equal to +1 and $(1, n_X + n_S + i)$ th entry equal to -1, and all other entries being 0. The corresponding Wald statistic is then

$$W = \frac{(\hat{\beta}_i - \hat{\zeta}_i)^2}{\frac{\hat{\Sigma}_{\beta_i \beta_i}}{N - n_X - n_S} - \frac{\hat{\Sigma}_{\beta_i \zeta_i} + \hat{\Sigma}_{\zeta_i \beta_i}}{\sqrt{((N - n_X - n_S)(N - n_X))}} + \frac{\hat{\Sigma}_{\zeta_i \zeta_i}}{N - n_X}} \quad (6)$$

$$\approx \frac{(\hat{\beta}_i - \hat{\zeta}_i)^2}{\text{se}(\hat{\beta}_i)^2 + \text{se}(\hat{\zeta}_i)^2} \sim \chi_1^2,$$

where we approximate $\hat{\Sigma}_{\beta_i \zeta_i} = \mathbb{E}((\hat{\beta}_i - \mathbb{E}\hat{\beta}_i)(\hat{\zeta}_i - \mathbb{E}\hat{\zeta}_i)) \approx 0$, and note that $\text{se}(\hat{\beta}_i) = \sqrt{\Sigma_{\beta_i \beta_i} / (N - n_X - n_S)}$ and $\text{se}(\hat{\zeta}_i) = \sqrt{\Sigma_{\zeta_i \zeta_i} / (N - n_X)}$ are exactly the definitions of the standard errors for the respective coefficients.

From (6), we have Algorithm 1, which allows us to determine the coefficients in a model that are correlated with a protected feature.

Algorithm 1 Univariate Wald Test, denoted WaldTest

Input: Two models $\mathcal{M}$ and $\mathcal{M}'$, and significance level $0 < \alpha < 1$.

- 1: The models $\mathcal{M}$ and $\mathcal{M}'$ must satisfy the constraint that the training data $\mathcal{D}$ for $\mathcal{M}$ and training data $\mathcal{D}'$ for model $\mathcal{M}'$ satisfy the relation that $\mathcal{S}_{\mathcal{D}'} = \mathcal{S}_{\mathcal{D}} \cup \{p\}$, where p is the protected feature.
 - 2: Compute the critical value W^* from the χ_1^2 -distribution. For the standard $\alpha = 0.05$, $W^* = 3.9$.
 - 3: $\tilde{S} \leftarrow \emptyset$
 - 4: **for** each feature $i \in \mathcal{S}_{\mathcal{D}}$ **do**
 - 5: Estimate the coefficients $\hat{\beta}_i$ and $\hat{\zeta}_i$ for the i th feature in models $\mathcal{M}$ and $\mathcal{M}'$ respectively.
 - 6: Compute the standard errors $\text{se}(\hat{\beta}_i)$ and $\text{se}(\hat{\zeta}_i)$ of the coefficients $\hat{\beta}_i$ and $\hat{\zeta}_i$.
 - 7: Compute the Wald statistic, $W_i = \frac{(\hat{\beta}_i - \hat{\zeta}_i)^2}{\text{se}(\hat{\beta}_i)^2 + \text{se}(\hat{\zeta}_i)^2}$, of (6), testing the null hypothesis $\beta_i = \zeta_i$ against its alternative $\beta_i \neq \zeta_i$.
 - 8: **if** $W_i > W^*$ **then**
 - 9: $\tilde{S} \leftarrow \tilde{S} \cup \{i\}$
 - 10: **end if**
 - 11: **end for**
- Output:** $\tilde{S}$
-

4 A SECURE FAIRNESS SYSTEM

In this section, we present the design of our secure machine learning fairness protocol. The protocol is run between two parties: the machine learning party ML and the compliance party Comp. Comp begins with a dataset $\mathcal{D} = \mathcal{P} \cup \mathcal{U}$, where each entry in $\mathcal{D}$ consists of a set of sensitive features $\mathcal{P}$ and a set of unsensitive

features $\mathcal{U}$. We call features that are *a priori* prohibited from use “sensitive features”, and features that are *a priori* permitted to use “unsensitive features”. After the fairness tests are performed, we will have features in the unsensitive set that are correlated with the features in the sensitive set. None of these features may be used in the training data of the final model, and we call these features “protected features”. All features that are not protected are “unprotected features”.

The sets $\mathcal{P}$ and $\mathcal{U}$ are denoted by schema $\mathcal{S}_{\mathcal{P}}$ and $\mathcal{S}_{\mathcal{U}}$. At a high level, the goal of this protocol is to produce a model $\mathcal{M}$ that is independent of all features in $\mathcal{P}$. The approach is to identify features in $\mathcal{U}$ that encode features in $\mathcal{P}$. The protocol proceeds in a series of rounds, and at the end of each round the set $\mathcal{U}$ is updated to exclude features correlated with features $\mathcal{P}$. When $\mathcal{U}$ is not updated at the end of the round, the model trained on the features in the most recent $\mathcal{U}$ is accepted as a fair model.

The high level security goal of the protocol is to hide the values of the protected features from the machine learning team. By hiding these values, we can argue that these values could not have implicitly influenced their decision to include or exclude unprotected features.

4.1 A Single Round of the Fairness Protocol

A single round of the protocol is given in Algorithms 2 and 3. The full protocol, presented in Algorithms 4 and 5 in Section 4.2, primarily consists of running Algorithms 2 and 3 repeatedly until the resulting model passes the Wald test.

Beginning with Algorithm 2, the inputs to a single round for the compliance team is a data set $\mathcal{D}$, a schema of sensitive features $\mathcal{S}_{\mathcal{P}}$, a schema of unprotected features $\mathcal{S}_{\mathcal{U}}$ and an FHE key pair pk and sk . The schema of sensitive and unprotected features must partition the data set $\mathcal{D}$. In other words, the two schema must satisfy $\emptyset = \mathcal{S}_{\mathcal{P}} \cap \mathcal{S}_{\mathcal{U}}$ and $\mathcal{S}_{\mathcal{D}} = \mathcal{S}_{\mathcal{P}} \cup \mathcal{S}_{\mathcal{U}}$, where $\mathcal{S}_{\mathcal{D}}$ is the schema for the whole data set. In each round of the protocol, the compliance team sends the encrypted dataset to the machine learning team along with the partition of sensitive and unprotected features, represented by $\mathcal{S}_{\mathcal{P}}$ and $\mathcal{S}_{\mathcal{U}}$. The machine learning team then trains a model on the unprotected features using a fully homomorphic encryption scheme. The result of this training is an encrypted model that the machine learning team returns to the compliance team. Since the compliance team has the FHE secret key sk , they can decrypt the encrypted model to obtain the model weights in the clear.

In addition to the model $\mathcal{M}$ trained on the unprotected features, the compliance team also receives a series of models $\mathcal{M}'_i$ for each sensitive feature $p_i \in \mathcal{S}_{\mathcal{P}}$. The model $\mathcal{M}'_i$ is trained on the dataset $\tilde{\mathcal{U}}_i = \text{Select}(\mathcal{S}_{\mathcal{U}} \cup \{p_i\}, \mathcal{D})$, which is all unprotected features plus the single sensitive feature p_i . For each of these models $\mathcal{M}'_i$, the compliance team performs the univariate Wald test as described in Algorithm 1. If there are features in $\mathcal{S}_{\mathcal{U}}$ that are correlated with the sensitive feature p_i and the model $\mathcal{M}$ has learned this correlation, the Wald test will detect this by examining the difference in the weights $\mathcal{M}$ from the weights of $\mathcal{M}'_i$. The output of this test will be the set of features $\tilde{S}_i \subseteq \mathcal{S}_{\mathcal{U}}$ that are correlated with p_i . The features in $\tilde{S}_i$ are now considered protected, and in subsequent

rounds these features will be excluded from the set of unprotected features.

In Algorithm 3, we have the machine learning team's view of a single round of the fairness protocol. The bulk of this algorithm is spent running the learning algorithm `Learn` on the various encrypted data sets. The round for ML begins by receiving the encrypted data set $\text{ct}_{\mathcal{D}}$ from the compliance team. ML also receives a partition of the data set into sensitive and unprotected features, which are denoted by $\mathcal{S}_{\mathcal{P}}$ and $\mathcal{S}_{\mathcal{U}}$. ML begins by performing a homomorphic `Select` operation in the encrypted data set $\text{ct}_{\mathcal{D}}$ to obtain an encryption of the data set with only the unprotected features, which we denote $\text{ct}_{\mathcal{U}}$. Next, ML homomorphically evaluates their learning algorithm of choice using $\text{ct}_{\mathcal{U}}$ as input to produce an encryption of the resulting model, which we denote $\text{ct}_{\mathcal{M}}$.

In order to produce the inputs for the univariate Wald fairness test, ML must also train models for each of the sensitive features. For each feature $p_i \in \mathcal{S}_{\mathcal{P}}$, ML produces a new set of training data $\tilde{\mathcal{U}}_i = \text{Select}(\mathcal{S}_{\mathcal{U}} \cup \{p_i\}, \mathcal{D})$. This operation must be performed homomorphically over the encrypted data set $\text{ct}_{\mathcal{D}}$ to obtain $\text{ct}_{\tilde{\mathcal{U}}_i}$, an encryption of $\tilde{\mathcal{U}}_i$. Using this encrypted training data, ML again runs the learning algorithm to obtain an encryption of the model $\mathcal{M}_{p_i}$. The encryptions of these models $\text{ct}_{\mathcal{M}_{p_i}}$ along with the encryption of the real model $\text{ct}_{\mathcal{M}}$ are returned to the compliance team. The compliance team then performs fairness tests, and the results of the fairness tests are represented in the inputs to the next round.

Algorithm 2 Single Round of Fairness Protocol for Comp, denoted `CompOneRound`

Input: Data set $\mathcal{D}$
 Schema of sensitive features $\mathcal{S}_{\mathcal{P}}$
 Scheme of unprotected features $\mathcal{S}_{\mathcal{U}}$
 FHE public key pk
 FHE secret key sk .

- 1: Encrypt the dataset $\text{ct}_{\mathcal{D}} \leftarrow \text{Encrypt}(\text{pk}, \mathcal{D})$.
- 2: Send the encrypted dataset $\text{ct}_{\mathcal{D}}$ along with the two schemas $\mathcal{S}_{\mathcal{P}}$ and $\mathcal{S}_{\mathcal{U}}$ to ML.
- 3: Receive encrypted model $\text{ct}_{\mathcal{M}}$ trained on $\mathcal{S}_{\mathcal{U}}$ from ML.
- 4: $\mathcal{M} \leftarrow \text{FHE.Decrypt}(\text{sk}, \text{ct}_{\mathcal{M}})$
- 5: $\tilde{\mathcal{S}} \leftarrow \emptyset$
- 6: **for** $p_i \in \mathcal{S}_{\mathcal{P}}$ **do**
- 7: Receive encrypted model $\text{ct}_{\mathcal{M}'_i}$ from ML.
- 8: $\mathcal{M}_{p_i} \leftarrow \text{FHE.Decrypt}(\text{sk}, \text{ct}_{\mathcal{M}'_i})$
- 9: $\tilde{\mathcal{S}}_i \leftarrow \text{WaldTest}(\mathcal{M}, \mathcal{M}'_i)$
- 10: $\tilde{\mathcal{S}} \leftarrow \tilde{\mathcal{S}}_i \cup \tilde{\mathcal{S}}$
- 11: **end for**

Output: $\mathcal{M}, \tilde{\mathcal{S}}$

4.2 Full Fairness Protocol

Building off of the algorithms in Section 4.1, we can define our full fairness protocol in Algorithms 4 and 5. These algorithms follow naturally from the discussion in Section 4.1, as they are essentially

Algorithm 3 Single Round of the Fairness Protocol for ML, denoted `MLOneRound`

Input: FHE evaluation key evk
 Learning algorithm `Learn`.

- 1: Receive the encrypted dataset $\text{ct}_{\mathcal{D}}$.
- 2: Receive the schema for the sensitive and unprotected features $\mathcal{S}_{\mathcal{P}}$ and $\mathcal{S}_{\mathcal{U}}$.
- 3: Select the features for the training data $\mathcal{S}_{\mathcal{T}} \subseteq \mathcal{S}_{\mathcal{U}}$.
- 4: $\text{ct}_{\mathcal{U}} \leftarrow \text{Eval}(\text{evk}, \text{Select}(\mathcal{S}_{\mathcal{U}}, \cdot), \text{ct}_{\mathcal{D}})$.
- 5: $\text{ct}_{\mathcal{M}} \leftarrow \text{Eval}(\text{evk}, \text{Learn}(\cdot), \text{ct}_{\mathcal{U}})$
- 6: Send $\text{ct}_{\mathcal{M}}$ to Comp.
- 7: **for** $p_i \in \mathcal{S}_{\mathcal{P}}$ **do**
- 8: $\mathcal{S}_{\tilde{\mathcal{U}}_i} \leftarrow \mathcal{S}_{\mathcal{U}} \cup \{p_i\}$
- 9: $\text{ct}_{\tilde{\mathcal{U}}_i} \leftarrow \text{Eval}(\text{evk}, \text{Select}(\mathcal{S}_{\tilde{\mathcal{U}}_i}, \cdot), \text{ct}_{\mathcal{D}})$
- 10: $\text{ct}_{\mathcal{M}_{p_i}} \leftarrow \text{Eval}(\text{Learn}(\cdot), \text{ct}_{\tilde{\mathcal{U}}_i})$
- 11: Send $\text{ct}_{\mathcal{M}_{p_i}}$ to Comp.
- 12: **end for**

just running the single round algorithms until the machine learning team produces a model that is sufficiently independent of the sensitive features.

At the end of each round, the compliance team obtains a candidate model and a set of protected features $\tilde{\mathcal{S}}$ in the candidate model's training data that are correlated with the sensitive features. In the next round, the compliance team removes the features in $\tilde{\mathcal{S}}$ from the unprotected features $\mathcal{S}_{\mathcal{U}}$, then uses this updated $\mathcal{S}_{\mathcal{U}}$ in the input for the next round. If $\tilde{\mathcal{S}} = \emptyset$, then the candidate model is accepted as a fair model.

Algorithm 4 Full Fairness Protocol for Comp

Input: Data set $\mathcal{D}$
 Schema of protected features $\mathcal{S}_{\mathcal{P}}$
 Security parameter λ .

- 1: $(\text{sk}, \text{pk}, \text{evk}) \leftarrow \text{FHE.KeyGen}(1^\lambda)$
- 2: Send evk to ML.
- 3: **while** `True` **do**
- 4: Let $\mathcal{S}_{\mathcal{U}} = \mathcal{S}_{\mathcal{P}}^c$
- 5: $\mathcal{M}, \tilde{\mathcal{S}} \leftarrow \text{CompOneRound}(\mathcal{D}, \mathcal{S}_{\mathcal{P}}, \mathcal{S}_{\mathcal{U}}, \text{pk}, \text{sk})$
- 6: **if** $\tilde{\mathcal{S}}$ equals $\emptyset$ **then**
- 7: Send Terminate signal to ML.
- 8: **Return:** $\mathcal{M}$
- 9: **end if**
- 10: Send Continue signal to ML.
- 11: $\mathcal{S}_{\mathcal{U}} = \mathcal{S}_{\mathcal{U}} \setminus \tilde{\mathcal{S}}$
- 12: **end while**

We can see that Algorithm 4 always terminates, since $\tilde{\mathcal{S}} \subseteq \mathcal{S}_{\mathcal{U}}$, so $\mathcal{S}_{\mathcal{U}}$ must shrink with each iteration of the while loop. If $\mathcal{S}_{\mathcal{U}}$ does not shrink, then it must be that $\tilde{\mathcal{S}} = \emptyset$, so the while loop terminates. Similarly, we have that Algorithm 5 terminates exactly when Algorithm 4 terminates. Since we have already argued that Algorithm 4 terminates, we have that Algorithm 5 terminates as well.

Algorithm 5 Full Fairness Protocol for ML

Input: Learning algorithm Learn.

```

1: Receive FHE evaluation key evk from Comp.
2: while True do
3:   Run MLOneRound (evk, Learn)
4:   Receive Signal from Comp.
5:   if Signal equals Terminate then
6:     Return
7:   end if
8: end while

```

4.3 Security

We now briefly and informally argue the security of the fairness protocol defined by Algorithms 4 and 5. Recall that our goal is to hide the values of the protected features from the machine learning team. Since we do not know which features will be in the protected set at the start of the protocol, we have the protocol hide all features from the machine learning team.

The remainder of the security argument follows directly from the semantic security of the FHE scheme, since the only information sent to the machine learning team related to the values of the data are FHE ciphertexts, which hide the encrypted values.

5 CASE STUDY: UCI ADULT DATASET

In this section, we implement the system described in Section 4 to train a linear model on the adult income dataset, a popular data set which is available at the machine learning dataset repository of the University of California at Irvine [17, 25]. The UCI Adult data set contains 14 attributes extracted from 1994 census data, of which 3 are federally protected classes: age, sex and race. For simplicity, we consider age only in our study. For the remaining 11 features, we use a standard dummy variable transformation of the categorical variables, also known as one-hot encoding, encoding a categorical variable with m levels into $m - 1$ binary variables, dropping one of the dummy variables to avoid collinearity issues in the subsequent regression. This transformation of the categorical variables yielded a total of $n_X = 87$ features, being a mix of numeric and binary variables. Dropping all rows with missing entries yields a final data set of 30,162 rows in the training subset and 15,060 rows in the testing subset, which we use in our analysis. The target feature is a binary variable indicating if the person corresponding to the entry has an income of at least \$50,000 per year. Denote this set of $n_X = 87$ features by $\mathcal{U}$ and the age protected class as $\mathcal{P}$, represented by a single positive integer. We begin our experiments with $\mathcal{U} = \text{Adult}$ and $\mathcal{P} = \{\text{Age}\}$.

5.1 Linear Regression Model

We began by training two models using the linear regression learning algorithm. The first model $\mathcal{M}$ was trained on $\mathcal{U}$ and achieves an accuracy of 83%². The second model $\mathcal{M}'$ was trained on the dataset $\mathcal{U} \cup \{\text{Age}\}$ and also achieved an accuracy of 83%. The train-test split of the data entries were identical for both models.

²The trivial accuracy for the UCI Adult data set is 75.4%, which is the proportion of persons in the data set making less than \$50,000 dollars per year.

	Original Coefficient	Coefficient with Age	W	p
Never Married	-0.0775	-0.0063	12.041	0.0005
Widowed	0.0895	0.009	4.445	0.0350

Table 1: Features with the largest difference in standard errors between the OLS model without Age and the OLS model with Age. These were the only features that changed more than two standard errors.

We then compute the WaldTest on inputs $\mathcal{M}$ and $\mathcal{M}'$ to obtain the set of features that the model $\mathcal{M}$ correlates with Age, and calculate the corresponding p -values to test at the usual $\alpha = 0.05$ level of significance. We found two features that changed significantly out of the $n_X = 87$ coefficients, and these results are shown in full in Table 2, with the significant features summarized in Table 1. These features are the Never-married and Widowed categories of marital status. The significance of the Never-married category persists even after applying the very conservative Bonferroni correction for multiple hypothesis testing [18], at the $\alpha/n_X = 0.0006$ level.

To account for this correlation in the marital status feature, we reduce the marital status feature from seven categories to a single binary category of {Unmarried, Married} in the next round. We repeat this experiment with the unprotected features updated to reflect this change to the marital status. Both of the resulting models remained around 83% accuracy and none of the features between the two models changed significantly. We can then conclude that this final model trained on the unprotected Adult data set with the updated marital status feature is independent of the protected Age feature.

5.2 Logistic Regression Model

While biases may be present in the Adult data set, not all models will learn this bias equally. To illustrate this, we performed the leave-one-out regression experiment with $\mathcal{U} = \text{Adult}$ and $\mathcal{P} = \{\text{Age}\}$ using a logistic regression learning model. Once again, the two models achieved 83% accuracy, but, unlike the linear regression model, the weights in the logistic regression model did not change significantly when the Age feature was added. Based on this test, we can conclude that this logistic regression model has not detected the biases in the Adult data set that the linear regression model was able to learn. It is an interesting question for future work to consider how different models learn biases. The full results of this experiment are shown in Table 3.

5.3 Encrypted Implementation

The protocol in Section 4 is agnostic to the underlying homomorphic encryption scheme as well as the method in which the learning algorithm is implemented using the chosen homomorphic encryption scheme. Implementations of logistic regression using homomorphic encryption abound [5, 23]. We implemented secure logistic regression training on the Adult data set using the HELR library from [23] on a standard machine³. While the full running time for training a single logistic regression model was about 45

³We used an AWS instance with a 3.0 GHz CPU with 8 cores and 32 GB of RAM.

minutes, only about three minutes of computation was actually spent progressing the logistic regression function. The remainder of the computation time was spent on the bootstrapping operation. This operation does not advance the underlying computation; rather, it is a technical operation necessary to maintain the correctness of the result when the function circuit is sufficiently deep. However, our goal in this setting is not to hide the learning algorithm from the compliance team, only to minimize the amount of machine learning expertise on the compliance side. This allows us to employ much more efficient *interactive* bootstrapping routine that can be run by the compliance team. By introducing interaction, we can effectively eliminate almost all of the computation time spent on the bootstrapping operation. It is an interesting direction for future work to optimize this fairness outsourcing protocol.

Disclaimer. This paper was prepared for informational purposes by the Artificial Intelligence Research group of JPMorgan Chase & Co and its affiliates (“JP Morgan”), and is not a product of the Research Department of JP Morgan. JP Morgan makes no representation and warranty whatsoever and disclaims all liability, for the completeness, accuracy or reliability of the information contained herein. This document is not intended as investment research or investment advice, or a recommendation, offer or solicitation for the purchase or sale of any security, financial instrument, financial product or service, or to be used in any way for evaluating the merits of participating in any transaction, and shall not constitute a solicitation under any jurisdiction or to any person, if such solicitation under such jurisdiction or to such person would be unlawful.

REFERENCES

- [1] Grace M Abuhamad. 2019. *The Fallacy of Equating “Blindness” with Fairness : Ensuring Trust in Machine Learning Applications to Consumer Credit*. MS. MIT.
- [2] Julia Angwin, Jeff Larson, Surya Mattu, and Lauren Kirchner. 2016. Machine bias. ProPublica.
- [3] Arthur P. Baines and Marsha J. Courchane. 2014. Fair Lending: Implications for the Indirect Auto Finance Market. Charles River Associates.
- [4] Solon Barocas and Andrew Selbst. 2016. Big Data’s Disparate Impact. *California Law Rev.* 104, 1 (2016), 671–729.
- [5] Flavio Bergamaschi, Shai Halevi, Tzipora T. Halevi, and Hamish Hunt. 2019. Homomorphic Training of 30,000 Logistic Regression Models. In *Applied Cryptography and Network Security*, Robert H. Deng, Valérie Gauthier-Umaña, Martín Ochoa, and Moti Yung (Eds.). Springer International Publishing, Cham, 592–611.
- [6] Richard Berk, Hoda Heidari, Shahin Jabbari, Michael Kearns, and Aaron Roth. 2018. Fairness in Criminal Justice Risk Assessments: The State of the Art. *Sociological Methods & Research* (2018), in press.
- [7] Zvika Brakerski, Craig Gentry, and Vinod Vaikuntanathan. 2014. (Leveled) Fully Homomorphic Encryption without Bootstrapping. *ACM Trans. Comput. Theory* 6, 3, Article 13 (July 2014), 36 pages.
- [8] Zvika Brakerski and Vinod Vaikuntanathan. 2011. Efficient Fully Homomorphic Encryption from (Standard) LWE. In *IEEE 52nd Annual Symposium on Foundations of Computer Science, FOCS, Rafail Ostrovsky (Ed.)*. IEEE Computer Society, Palm Springs, CA, 97–106.
- [9] Jiahao Chen. 2018. Fair lending needs explainable models for responsible recommendation. In *FATREC’18 Proceedings of the Second Workshop on Responsible Recommendation*. Vancouver, British Columbia, Canada, 4. arXiv:1809.04684
- [10] Jiahao Chen, Nathan Kallus, Xiaojie Mao, Geoffry Svacha, and Madeleine Udell. 2019. Fairness Under Unawareness: Assessing Disparity When Protected Class Is Unobserved. In *Proceedings of the Conference on Fairness, Accountability, and Transparency (FAT* ’19)*. Association for Computing Machinery, New York, NY, 339–348.
- [11] Alexandra Chouldechova. 2017. Fair Prediction with Disparate Impact: A Study of Bias in Recidivism Prediction Instruments. *Big Data* 5, 2 (2017), 153–163.
- [12] Ethan Cohen-Cole. 2011. Credit card redlining. *Rev. Econ. Stat.* 93, 2 (2011), 700–713.
- [13] Delores A. Conway and Harry V. Roberts. 1983. Reverse Regression, Fairness, and Employment Discrimination. *Journal of Business & Economic Statistics* 1, 1 (1983), 75–85.
- [14] Sam Corbett-Davies, Emma Pierson, Avi Feller, Sharad Goel, and Aziz Huq. 2017. Algorithmic Decision Making and the Cost of Fairness. In *Proceedings of the 23rd*

Feature	$\hat{\beta}_i$	$se(\hat{\beta}_i)$	$\hat{\zeta}_i$	$se(\hat{\zeta}_i)$	W_i	p
Local-gov	-0.2172	0.0280	-0.2132	0.0280	0.0102	0.9195
Private	-0.1558	0.0240	-0.1354	0.0240	0.3613	0.5478
Self-emp-inc	0.0344	0.0320	0.0234	0.0320	0.0591	0.8080
Self-emp-not-inc	-0.2514	0.0280	-0.2591	0.0280	0.0378	0.8458
State-gov	-0.2611	0.0310	-0.2469	0.0300	0.1084	0.7420
Without-pay	-0.4112	0.1900	-0.4560	0.1890	0.0279	0.8672
11th	0.1069	0.0470	0.1826	0.0470	1.2971	0.2547
12th	0.2195	0.0770	0.3491	0.0770	1.4164	0.2340
1st-4th	-0.2989	0.1320	-0.5680	0.1330	2.0623	0.1510
5th-6th	-0.2225	0.1000	-0.4277	0.1000	2.1054	0.1468
7th-8th	-0.2517	0.0680	-0.4027	0.0680	2.4655	0.1164
9th	-0.1275	0.0490	-0.1974	0.0490	1.0175	0.3131
Assoc-acdm	0.5862	0.1850	0.9424	0.1860	1.8436	0.1745
Assoc-voc	0.5150	0.1560	0.8106	0.1560	1.7953	0.1803
Bachelors	0.8746	0.2140	1.2797	0.2150	1.7834	0.1817
Doctorate	1.5701	0.3050	2.1082	0.3060	1.5512	0.2130
HS-grad	0.2703	0.0960	0.4459	0.0970	1.6556	0.1982
Masters	1.1515	0.2440	1.5947	0.2450	1.6429	0.1999
Preschool	-0.2939	0.1790	-0.6219	0.1800	1.6695	0.1963
Prof-school	1.4820	0.2750	1.9854	0.2760	1.6694	0.1963
Some-college	0.4193	0.1260	0.6595	0.1260	1.8171	0.1777
education	-0.0646	0.0300	-0.1214	0.0300	1.7924	0.1806
Married-AF-spouse	0.3060	0.1610	0.3992	0.1610	0.1676	0.6823
Married-civ-spouse	0.1936	0.0520	0.2313	0.0510	0.2679	0.6047
Married-spouse-absent	0.0558	0.0390	0.0687	0.0390	0.0547	0.8151
Never-married	-0.0775	0.0140	-0.0063	0.0150	12.0414	0.0005**
Separated	0.0117	0.0260	0.0289	0.0250	0.2274	0.6335
Widowed	0.0895	0.0270	0.0090	0.0270	4.4446	0.0350
Armed-Forces	-0.2248	0.2360	-0.1841	0.2350	0.0149	0.9027
Craft-repair	-0.0058	0.0170	0.0022	0.0170	0.1107	0.7393
Exec-managerial	0.2934	0.0170	0.2877	0.0170	0.0562	0.8126
Farming-fishing	-0.1858	0.0270	-0.1886	0.0270	0.0054	0.9415
Handlers-cleaners	-0.0847	0.0230	-0.0673	0.0230	0.2862	0.5927
Machine-op-inspct	-0.0845	0.0200	-0.0771	0.0200	0.0685	0.7936
Other-service	-0.0476	0.0170	-0.0399	0.0170	0.1026	0.7488
Priv-house-serv	0.0175	0.0610	-0.0027	0.0610	0.0548	0.8149
Prof-specialty	0.1426	0.0180	0.1457	0.0180	0.0148	0.9031
Protective-serv	0.1785	0.0310	0.1871	0.0310	0.0385	0.8445
Sales	0.1013	0.0170	0.1052	0.0170	0.0263	0.8711
Tech-support	0.1557	0.0260	0.1616	0.0260	0.0257	0.8725
Transport-moving	-0.0492	0.0220	-0.0491	0.0220	0.0000	0.9974
Not-in-Family	-0.4286	0.0510	-0.3988	0.0510	0.1707	0.6795
Other-relative	-0.3836	0.0500	-0.3381	0.0500	0.4141	0.5199
Own-child	-0.4229	0.0510	-0.3453	0.0510	1.1576	0.2820
Unmarried	-0.4503	0.0530	-0.4094	0.0520	0.3034	0.5817
Wife	0.1134	0.0200	0.1354	0.0200	0.6050	0.4367
hours-per-week	0.0061	0.0000	0.0065	0.0000	N/A	N/A
Canada	-0.2482	0.1800	-0.2576	0.1790	0.0014	0.9705
China	-0.5128	0.1870	-0.5120	0.1860	0.0000	0.9976
Columbia	-0.5449	0.1910	-0.5484	0.1900	0.0002	0.9896
Cuba	-0.3161	0.1820	-0.3392	0.1810	0.0081	0.9283
Dominican-Republic	-0.4350	0.1870	-0.4316	0.1860	0.0002	0.9897
Ecuador	-0.4091	0.2140	-0.3985	0.2140	0.0012	0.9721
El-Salvador	-0.3361	0.1810	-0.3129	0.1800	0.0083	0.9276
England	-0.2557	0.1830	-0.2604	0.1820	0.0003	0.9855
France	-0.2318	0.2150	-0.2215	0.2140	0.0012	0.9729
Germany	-0.2554	0.1780	-0.2500	0.1770	0.0005	0.9828
Greece	-0.4793	0.2120	-0.5059	0.2110	0.0079	0.9291
Guatemala	-0.2932	0.1890	-0.2505	0.1880	0.0257	0.8727
Haiti	-0.3744	0.1990	-0.3811	0.1980	0.0006	0.9810
Holand-Netherlands	-0.3151	0.1720	-0.3421	0.1720	0.0007	0.9789
Honduras	-0.3570	0.2630	-0.3290	0.2620	0.0057	0.9399
Hong	-0.4256	0.2320	-0.3862	0.2310	0.0145	0.9042
Hungary	-0.3617	0.2570	-0.4017	0.2560	0.0122	0.9122
India	-0.4434	0.1810	-0.4250	0.1800	0.0052	0.9425
Iran	-0.3170	0.1990	-0.3010	0.1980	0.0032	0.9545
Ireland	-0.2232	0.2200	-0.2232	0.2190	0.0000	1.0000
Italy	-0.1962	0.1870	-0.2148	0.1860	0.0050	0.9438
Jamaica	-0.3773	0.1840	-0.3750	0.1830	0.0001	0.9929
Japan	-0.2389	0.1900	-0.2299	0.1890	0.0011	0.9732
Laos	-0.5419	0.2380	-0.5245	0.2370	0.0027	0.9587
Mexico	-0.4344	0.1690	-0.3908	0.1680	0.0335	0.8548
Nicaragua	-0.4587	0.2060	-0.4318	0.2060	0.0085	0.9264
Outlying-US(Guam-USVI-etc)	-0.6610	0.2510	-0.6685	0.2500	0.0004	0.9831
Peru	-0.4478	0.2100	-0.4518	0.2090	0.0002	0.9892
Philippines	-0.2712	0.1740	-0.2809	0.1730	0.0016	0.9685
Poland	-0.4190	0.1910	-0.4309	0.1900	0.0020	0.9648
Portugal	-0.4434	0.2060	-0.4196	0.2050	0.0067	0.9347
Puerto-Rico	-0.3881	0.1790	-0.3922	0.1790	0.0003	0.9871
Scotland	-0.5051	0.2700	-0.5046	0.2690	0.0000	0.9990
South	-0.5824	0.1860	-0.5774	0.1850	0.0004	0.9848
Taiwan	-0.4902	0.1990	-0.4603	0.1980	0.0113	0.9152
Thailand	-0.5519	0.2380	-0.5231	0.2380	0.0073	0.9318
Trinidad&Tobago	-0.4410	0.2350	-0.4572	0.2340	0.0024	0.9610
United-States	-0.3001	0.1660	-0.2983	0.1660	0.0001	0.9939
Vietnam	-0.4805	0.1880	-0.4686	0.1870	0.0020	0.9642
Yugoslavia	-0.2402	0.2420	-0.2316	0.2410	0.0006	0.9799

Table 2: Estimated coefficients β and ζ in the respective linear regression models $\mathcal{M}$ (1) and $\mathcal{M}'$ (2), along with their standard errors (se), Wald statistic (6), and its p -value as determined from the χ^2_1 -distribution. Bold p -values are significant at the $\alpha = 0.05$ level; values marked ** are significant at the Bonferroni-corrected $\alpha/n_X = 0.0006$ level. Only the Never-married and Widowed categories of marital status show statistically significant differences between β_i and ζ_i .

Feature	$\hat{\beta}_i$	$se(\hat{\beta}_i)$	$\hat{\zeta}_i$	$se(\hat{\zeta}_i)$	W_i	p
Local-gov	-1.2222	0.1050	-1.1829	0.1040	0.0707	0.7903
Private	-0.9785	0.0870	-1.0847	0.0860	0.7537	0.3853
Self-emp-inc	-0.4591	0.1150	-0.3583	0.1150	0.3841	0.5354
Self-emp-not-inc	-1.2819	0.1020	-1.2774	0.1010	0.0010	0.9750
State-gov	-1.4024	0.1170	-1.3379	0.1150	0.1546	0.6942
Without-pay	-0.0642	0.7550	-0.0580	0.7460	0.0000	0.9953
11th	-1.2592	0.2220	-1.2487	0.2200	0.0011	0.9732
12th	-0.5439	0.3330	-0.5270	0.3300	0.0013	0.9712
1st-4th	-0.4908	0.5470	-0.4476	0.5340	0.0032	0.9549
5th-6th	-0.8337	0.4300	-0.7778	0.4180	0.0087	0.9257
7th-8th	-1.4437	0.2880	-1.3697	0.2800	0.0339	0.8538
9th	-1.0654	0.2330	-1.0179	0.2260	0.0214	0.8837
Assoc-acdm	-0.4001	0.7100	-0.4239	0.7070	0.0006	0.9810
Assoc-voc	-0.3023	0.5970	-0.3400	0.5950	0.0020	0.9643
Bachelors	0.4935	0.8170	0.4311	0.8140	0.0029	0.9569
Doctorate	1.1556	1.1600	1.1284	1.1540	0.0003	0.9867
HS-grad	-0.6676	0.3730	-0.6800	0.3720	0.0006	0.9812
Masters	0.7324	0.9300	0.7498	0.9260	0.0002	0.9894
Preschool	-0.1453	0.8130	-0.1316	0.7860	0.0001	0.9903
Prof-school	1.4555	1.0470	1.4311	1.0420	0.0003	0.9868
Some-college	-0.2981	0.4830	-0.2713	0.4820	0.0015	0.9687
education	0.0066	0.1130	-0.0096	0.1130	0.0103	0.9193
Married-AF-spouse	0.0945	0.5810	0.0921	0.5870	0.0000	0.9977
Married-civ-spouse	0.3700	0.2530	0.3461	0.2530	0.0045	0.9467
Married-spouse-absent	-0.3959	0.2140	-0.3817	0.2060	0.0023	0.9619
Never-married	-1.0609	0.0760	-1.0122	0.0760	0.2053	0.6505
Separated	-0.5968	0.1560	-0.6017	0.1520	0.0005	0.9821
Widowed	-0.3541	0.1510	-0.3160	0.1380	0.0347	0.8522
Armed-Forces	-0.0209	0.9310	-0.0198	0.9240	0.0000	0.9993
Craft-repair	-0.1118	0.0720	-0.0743	0.0710	0.1375	0.7107
Exec-managerial	0.5813	0.0600	0.5542	0.0680	0.0783	0.7797
Farming-fishing	-1.1937	0.1310	-1.1836	0.1280	0.0030	0.9560
Handlers-cleaners	-1.2222	0.1400	-1.2311	0.1410	0.0020	0.9643
Machine-op-inspct	-0.8202	0.0970	-0.8737	0.0980	0.1505	0.6980
Other-service	-1.6790	0.1250	-1.7034	0.1240	0.0192	0.8898
Priv-house-serv	-0.2535	0.4060	-0.2343	0.3790	0.0012	0.9724
Prof-specialty	0.3759	0.0730	0.4542	0.0720	0.5832	0.4451
Protective-serv	0.3820	0.1170	0.3813	0.1160	0.0000	0.9966
Sales	0.1872	0.0730	0.2486	0.0730	0.3537	0.5520
Tech-support	0.6317	0.1010	0.6531	0.1000	0.0227	0.8803
Transport-moving	-0.3347	0.0910	-0.3523	0.0900	0.0189	0.8906
Not-in-family	-1.2453	0.2510	-1.1301	0.2520	0.1049	0.7460
Other-relative	-1.1723	0.2280	-1.1185	0.2280	0.0278	0.8675
Own-child	-2.1693	0.2570	-2.1192	0.2600	0.0188	0.8910
Unmarried	-1.9072	0.2630	-1.8586	0.2630	0.0171	0.8960
Wife	0.2722	0.0680	0.2379	0.0680	0.1272	0.7213
hours-per-week	0.0185	0.0020	0.0161	0.0020	0.7200	0.3961
Canada	-0.0900	0.6610	-0.0756	0.6500	0.0002	0.9876
China	-0.2274	0.6900	-0.2141	0.6800	0.0002	0.9890
Columbia	-0.2045	0.7590	-0.1919	0.7440	0.0001	0.9905
Cuba	-0.1338	0.6770	-0.1165	0.6640	0.0003	0.9854
Dominican-Republic	-0.2096	0.7630	-0.1968	0.7450	0.0001	0.9904
Ecuador	-0.0701	0.8420	-0.0668	0.8290	0.0000	0.9978
El-Salvador	-0.2189	0.7160	-0.2056	0.7020	0.0002	0.9894
England	-0.0582	0.6750	-0.0466	0.6630	0.0002	0.9902
France	0.0032	0.7930	0.0058	0.7760	0.0000	0.9981
Germany	-0.1087	0.6510	-0.0935	0.6400	0.0003	0.9867
Greece	-0.0989	0.7740	-0.0899	0.7660	0.0001	0.9934
Guatemala	-0.1373	0.7910	-0.1294	0.7740	0.0001	0.9943
Haiti	-0.0921	0.8310	-0.0854	0.8150	0.0000	0.9954
Holand-Netherlands	-0.0009	0.6030	-0.0009	0.5980	0.0000	1.0000
Honduras	-0.0231	1.4540	-0.0219	1.3780	0.0000	0.9995
Hong	-0.0479	0.8700	-0.0453	0.8550	0.0000	0.9983
Hungary	-0.0299	0.9050	-0.0255	0.8830	0.0000	0.9972
India	-0.2407	0.6610	-0.2250	0.6520	0.0003	0.9865
Iran	-0.0548	0.7270	-0.0501	0.7150	0.0000	0.9963
Ireland	-0.0119	0.8840	-0.0105	0.8740	0.0000	0.9991
Italy	-0.0552	0.6850	-0.0428	0.6720	0.0002	0.9897
Jamaica	-0.1542	0.7110	-0.1436	0.7000	0.0001	0.9915
Japan	-0.0446	0.7110	-0.0400	0.6980	0.0000	0.9963
Laos	-0.0587	0.9130	-0.0554	0.9130	0.0000	0.9980
Mexico	-1.4682	0.6420	-1.4426	0.6300	0.0008	0.9773
Nicaragua	-0.0993	0.8450	-0.0945	0.8340	0.0000	0.9968
Outlying-US(Guam-USVI-etc)	-0.0629	1.0150	-0.0588	0.9810	0.0000	0.9977
Peru	-0.0791	0.8690	-0.0749	0.8550	0.0000	0.9973
Philippines	-0.1455	0.6420	-0.1240	0.6310	0.0006	0.9809
Poland	-0.1274	0.7090	-0.1169	0.6990	0.0001	0.9916
Portugal	-0.1234	0.7840	-0.1158	0.7680	0.0000	0.9945
Puerto-Rico	-0.2873	0.6860	-0.2685	0.6730	0.0004	0.9844
Scotland	-0.0291	1.0110	-0.0269	1.0010	0.0000	0.9988
South	-0.2352	0.7020	-0.2205	0.6920	0.0002	0.9881
Taiwan	-0.0826	0.7430	-0.0769	0.7350	0.0000	0.9956
Thailand	-0.0486	0.9420	-0.0460	0.9180	0.0000	0.9984
Trinidad&Tobago	-0.0595	0.8860	-0.0542	0.8680	0.0000	0.9966
United-States	-0.2211	0.6070	-0.2960	0.5970	0.0077	0.9299
Vietnam	-0.1795	0.7370	-0.1692	0.7250	0.0001	0.9921
Yugoslavia	-0.0097	0.9010	-0.0086	0.8890	0.0000	0.9993

Table 3: Estimated coefficients $\hat{\beta}$ and $\hat{\zeta}$ in the respective logistic regression models $\mathcal{M}(3)$ and $\mathcal{M}'(4)$, with other notation as defined in Table 2. None of the features are found to show statistically significant differences between the coefficients β_i and ζ_i .

- ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD '17). Association for Computing Machinery, New York, NY, 797–806.
- [15] Marsha Courchane, David Nebhut, and David Nickerson. 2000. Lessons Learned: Statistical Techniques and Fair Lending. *Journal of Housing Research* 11, 2 (2000), 277–295.
- [16] Julia Dressel and Hany Farid. 2018. The accuracy, fairness, and limits of predicting recidivism. *Science Advances* 4, 1, Article eao5580 (2018), 5 pages.
- [17] Dheeru Dua and Casey Graff. 2017. UCI Machine Learning Repository. <http://archive.ics.uci.edu/ml>
- [18] Olive Jean Dunn. 1961. Multiple Comparisons among Means. *J. Amer. Stat. Assoc.* 56, 293 (1961), 52–64.
- [19] Michael Feldman, Sorelle A. Friedler, John Moeller, Carlos Scheidegger, and Suresh Venkatasubramanian. 2015. Certifying and Removing Disparate Impact. In *Proceedings of the 21th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD '15)*, Longbing Cao, Chengqi Zhang, Thorsten Joachims, Geoff Webb, Dragos D Margineantu, and Graham Williams (Eds.). ACM, Sydney, NSW, Australia, 259–268.
- [20] Craig Gentry. 2009. Fully Homomorphic Encryption Using Ideal Lattices. In *Proceedings of the Forty-First Annual ACM Symposium on Theory of Computing (STOC '09)*. Association for Computing Machinery, New York, NY, USA, 169–178.
- [21] Shafi Goldwasser and Silvio Micali. 1982. Probabilistic Encryption & How to Play Mental Poker Keeping Secret All Partial Information. In *Proceedings of the Fourteenth Annual ACM Symposium on Theory of Computing (STOC '82)*. Association for Computing Machinery, New York, NY, USA, 365–377.
- [22] Mikella Hurley and Julius Adebayo. 2016. Credit Scoring in the Era of Big Data. *Yale Journal of Law & Technology* 148 (2016), 148–216.
- [23] Miran Kim, Yongsoo Song, Shuang Wang, Yuhou Xia, and Xiaoqian Jiang. 2017. Secure Logistic Regression Based on Homomorphic Encryption: Design and Evaluation. *JMIR Medical Informatics* 6 (08 2017).
- [24] Jon Kleinberg, Sendhil Mullainathan, and Manish Raghavan. 2017. Inherent Trade-Offs in the Fair Determination of Risk Scores. In *Proceedings of the 8th Innovations in Theoretical Computer Science Conference (Leibniz International Proceedings in Informatics (LIPIcs))*, Christos H. Papadimitriou (Ed.), Vol. 67. Schloss Dagstuhl–Leibniz-Zentrum fuer Informatik, Dagstuhl, Germany, Article 43, 23 pages.
- [25] Ron Kohavi. 1996. Scaling up the Accuracy of Naive-Bayes Classifiers: A Decision-Tree Hybrid. In *Proceedings of the Second International Conference on Knowledge Discovery and Data Mining (KDD '96)*, Evangelos Simoudis, Jiawei Han, and Usama Fayyad (Eds.). AAAI Press, Palo Alto, California, 202–207.
- [26] Anja Lambrecht and Catherine Tucker. 2019. Algorithmic bias? An empirical study of apparent gender-based discrimination in the display of stem career ads. *Management Science* 65, 7 (2019), 2966–2981.
- [27] Jing Lei, Max G'Sell, Alessandro Rinaldo, Ryan J. Tibshirani, and Larry Wasserman. 2018. Distribution-Free Predictive Inference for Regression. *J. Amer. Stat. Assoc.* 113, 523 (2018), 1094–1111.
- [28] Ninareh Mehrabi, Fred Morstatter, Nripsuta Saxena, Kristina Lerman, and Aram Galstyan. 2019. A Survey on Bias and Fairness in Machine Learning. (2019), 31. arXiv:1908.09635
- [29] Cecilia Munoz, Megan Smith, and D. J. Patil. 2016. *Big Data: A Report on Algorithmic Systems, Opportunity, and Civil Rights*. Technical Report. Executive Office of the President of USA.
- [30] Geoff Pleiss, Manish Raghavan, Felix Wu, Jon Kleinberg, and Kilian Q Weinberger. 2017. On fairness and calibration. In *Advances in Neural Information Processing Systems 30*, I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (Eds.). Curran Associates, Red Hook, NY, 5680–5689.
- [31] Devin G. Pope and Justin R. Sydnor. 2011. Implementing anti-discrimination policies in statistical profiling models. *American Economic Journal: Economic Policy* 3, 3 (2011), 206–231.
- [32] Manish Raghavan, Solon Barocas, Jon Kleinberg, and Karen Levy. 2019. Mitigating Bias in Algorithmic Employment Screening: Evaluating Claims and Practices. (2019), 24. arXiv:1906.09208
- [33] R L Rivest, L Adleman, and M L Dertouzos. 1978. *On Data Banks and Privacy Homomorphisms*. Academic Press, Orlando, FL, 169–179.
- [34] Laurence D. Robinson and Nicholas P. Jewell. 1991. Some Surprising Results about Covariate Adjustment in Logistic Regression Models. *International Statistical Review* 59, 2 (Aug. 1991), 227–240.
- [35] Cynthia Rudin. 2019. Stop explaining black box machine learning models for high stakes decisions and use interpretable models instead. *Nature Machine Intelligence* 1, 5 (2019), 206–215.
- [36] Andrew D. Selbst, Danah Boyd, Sorelle A. Friedler, Suresh Venkatasubramanian, and Janet Vertesi. 2019. Fairness and Abstraction in Sociotechnical Systems. In *Proceedings of the Conference on Fairness, Accountability, and Transparency (FAT* '19)*. Association for Computing Machinery, New York, NY, USA, 59–68.
- [37] Robert J. Serfling. 1980. *Approximation Theorems of Mathematical Statistics*. Wiley-Interscience, New York, Chapter 4, 138–170.

- [38] Marten van Dijk, Craig Gentry, Shai Halevi, and Vinod Vaikuntanathan. 2010. Fully Homomorphic Encryption over the Integers. In *Advances in Cryptology – EUROCRYPT 2010*, Henri Gilbert (Ed.). Springer Berlin Heidelberg, Berlin, Heidelberg, 24–43.
- [39] Meredith Whittaker, Meryl Alper, Cynthia L. Bennett, and Emily Rogers. 2019. *Disability, Bias, and AI*. Technical Report. AI Now Institute at NYU, New York.
- [40] Tal Zarsky. 2016. The Trouble with Algorithmic Decisions: An Analytic Road Map to Examine Efficiency and Fairness in Automated and Opaque Decision Making. *Science Technology and Human Values* 41, 1 (2016), 118–132.