An improved spectral clustering method for community detection under the degree-corrected stochastic blockmodel

Huan Qing^{*} and Jingli Wang[†]

Abstract

For community detection problem, spectral clustering is a widely used method for detecting clusters in networks. In this paper, we propose an improved spectral clustering (ISC) approach under the degree corrected stochastic block model (DCSBM). ISC is designed based on the k-means clustering algorithm on the weighted leading K + 1 eigenvectors of a regularized Laplacian matrix where the weights are their corresponding eigenvalues. Theoretical analysis of ISC shows that under mild conditions the ISC yields stable consistent community detection. Numerical results show that ISC outperforms classical spectral clustering methods for community detection on both simulated and eight empirical networks. Especially, ISC provides a significant improvement on two weak signal networks Simmons and Caltech, with error rates of 121/1137 and 96/590, respectively.

keyword: Community detection; spectral clustering; weak signal networks; degree-corrected stochastic blockmodel; regularized Laplacian matrix

^{*}Department of Mathematics, China University of Mining and Technology, China.

[†]Corresponding author. Email: jlwang@nankai.edu.cn. School of Statistics & Data Science, Nankai University, China

1. Introduction

Detecting communities in networks plays a key role in understanding the structure of networks in various areas, including but not limited to computer science, social science, physics, and statistics (McPherson et al. (2001); Duch and Arenas (2005); Fortunato (2010); Papadopoulos et al. (2012)). The community detection problem appeals to an ascending number of attention recently (Newman (2006); Karrer and Newman (2011); Bickel and Chen (2009); Jin (2015)). To solve the community detection problem, substantial approaches, such as Snijders and Nowicki (1997); Nowicki and Snijders (2001); Daudin et al. (2008); Bickel and Chen (2009); Rohe et al. (2011); Amini et al. (2013), are designed based on the standard framework, the stochastic block model (SBM) (Holland et al. (1983)), since it is mathematically simple and relatively easy to analyze (Bickel and Chen (2009)). However, the assumptions of SBM are too restrictive to implement in real networks. It is assumed that the distribution of degrees within the community is Poisson, that is, the nodes within each community have the same expected degrees. Unfortunately, in many natural networks, the degrees follow approximately a power-law distribution (Kolaczyk (2009); Goldenberg et al. (2010); Jin (2015)). The corrected-degree stochastic block model (DCSBM) (Karrer and Newman (2011)) is developed based on the power-law distribution which allows the degree of nodes varies among different communities. For the community detection problem, a number of methods have been developed based on DCSBM, including some model-based methods and spectral methods. Model-based methods include profile likelihood maximization and modularity maximization as Karrer and Newman (2011) and Chen et al. (2018). While spectral methods are constructed based on the application of the leading eigenvectors of the adjacency matrix or its variants (see Qin and Rohe (2013); Jin (2015); Zhang et al. (2020); Jing et al. (2021)). Compared with spectral methods, model-based methods are pretty time-consuming (Qin and Rohe (2013); Jin (2015); Zhang et al. (2020)).

A weak signal network can be defined by a network whose adjacency matrix's (or its variants) (K + 1)-th eigenvalue is close to the K-th one in magnitude assuming there are K clusters in the given network (Jin et al. (2018)). However, classical spectral clustering methods such as spectral clustering on ratios-of-eigenvectors (SCORE) (Jin (2015)), regularized spectral clustering (RSC) (Qin and Rohe (2013)) and overlapping continuous community assignment model (OCCAM) (Zhang et al. (2020)) fail to detect two typical weak signal networks Simmons and Caltech (Jin et al. (2018)). As shown in Table 1, we find that it is challenging to detect weak signal networks for the recently published symmetrized Laplacian inverse matrix method (SLIM for short) Jing et al. (2021). Though the convexified modularity maximization (CMM) method (Chen et al. (2018)) and the latent space model based (LSCD) method (Ma and Ma (2017)) have better performances than SCORE, RSC and OCCAM as shown in the Table 2 of Jin et al. (2018), these two approaches are time consuming as shown in the Table 4 of Jin et al. (2018). However, even though Jin et al. (2018) proposed a method called SCORE+ which can be applied to deal with weak signal networks by considering one more eigenvector for clustering, we find that it is challenging and hard to build theoretical framework for it.

In this paper, we aim to seek for a spectral clustering algorithm that has strong statistical performance guarantees under DCSBM, and provides competitive empirical performance when detecting both strong signal networks and weak signal networks. We construct a novel Improved Spectral Clustering (ISC) approach under the classical model DCSBM. ISC is designed based on a regularized Laplacian matrix L_{δ} defined in Section 3 and using the production of the leading (K+1) eigenvectors with unit-norm and the leading (K+1) eigenvalues for clustering. Some theoretical results are established to ensure a stable performance of the proposed method. As we show in numerical studies, our approach ISC has satisfactory performances in simulated networks and empirical examples, especially, for two real-world weak signal networks Simmons and Caltech (introduced in Section 2). In all, our approach is comparable to or improves upon the published stateof-the-art methods in the literature.

The details of motivation are described in section 2. In Section 3, we propose the ISC approach after introducing the classical DCSBM model. Section 4 presents the theoretical framework of ISC where we show that the ISC yields stable consistent community detection under mild conditions. Section 5 investigates the performance of the ISC via comparing with five spectral clustering methods on both numerical networks and eight empirical datasets. Section 6 concludes.

2. Motivation

Before introducing our algorithm, we briefly describe two empirical networks Simmons and Caltech which inspire us to design our algorithm.

	ISC	SCORE	OCCAM	RSC	SLIM
Simmons	121/1137	268/1137	268/1137	244/1137	275/1137
Caltech	96/590	180/590	192/590	170/590	150/590

The Simmons network induced by nodes with graduation year between 2006 and 2009 has a largest connected component with 1137 nodes. Traud et al. (2011) found that there exists community structure in the Simmons network based on the observation that there is a strong correlation with the graduation year such that students enrolled by the college in the same year are more likely to be friends (i.e., node in Simmons network denotes student, and edge denotes the friendship). Naturally, the Simmons network contains four communities such that students in the same year are in the same community, which is applied as the ground truth to test the performances of community detection approaches.

The Caltech network contains a largest component with 590 nodes and Traud et al. (2011) found that the community structure in the Caltech network is highly correlated with the eight dorms that a student is from such that students in the same dorm are more likely to be friends (i.e., node in Caltech network denotes student, and edge denotes the friendship). Therefore, the Caltech network contains eight communities such that students in the same dorm are in the same community, which is applied as the ground truth in this paper.

Simmons (as well as Caltech) is regarded as a weak signal network since the leading (K+1)-th eigenvalue of the adjacency matrix or its variants are close to the leading K-th eigenvalue assuming it has K clusters. Jin et al. (2018) found that the leading (K+1)-th eigenvector of the adjacency matrix or its variants may also contain information about nodes labels for weak signal networks. The intuition behind our method is that published spectral methods such as SCORE (Jin (2015)), RSC (Qin and Rohe (2013)) and OCCAM (Zhang et al. (2020)) fail to detect Simmons and Caltech as shown in Jin et al. (2018). The error rates (defined in 57) of our ISC and other four spectral methods SCORE, OCCAM, RSC, and SLIM on the two weak signal networks are recorded by Table 1, from which we can find that SCORE, OCCAM, RSC, and SLIM perform poor with high error rates while our ISC has satisfactory performances on the two datasets Simmons and Caltech.

3. Problem setup and the ISC algorithm

In this section, we set up the community detection problem under DCSBM, and then introduce our algorithm ISC.

The following notations will be used throughout the paper: $\|\cdot\|_F$ for a matrix denotes the Frobenius norm. $\|\cdot\|$ for a matrix denotes the spectral norm. $\|\cdot\|$ for a vector denotes the l_2 -norm. For convenience, when we say "leading eigenvectors" or "leading eigenvalues", we are comparing the *magnitudes* of the eigenvalues. For any matrix or vector x, x' denotes the transpose of x.

Consider an undirected, no-loops, and unweighted connected network \mathcal{N} with n nodes. Let A be an adjacency matrix of network \mathcal{N} such that $A_{ij} = 1$ if there is an edge between node i and j, $A_{ij} = 0$ otherwise, for $i, j = 1, \ldots, n$ (A is symmetric with diagonal entries being zeros). We assume that there exist K perceivable non-overlapping clusters

$$V^{(1)}, V^{(2)}, \dots, V^{(K)},$$
(31)

and each node belongs to exactly only one cluster, and K is assumed to be known in this paper. Let ℓ be an $n \times 1$ vector such that $\ell(i)$ takes values from $\{1, 2, \ldots, K\}$ and $\ell(i)$ is the cluster label for node $i, i = 1, \cdots, n$. ℓ is unknown and our goal is to estimate ℓ with given (A, K).

3.1 The degree-corrected stochastic block model

In this paper, we consider the degree-corrected stochastic block model (DCSBM) (Karrer and Newman (2011)) which is a generalization of the classic stochastic block model (SBM) (Holland et al. (1983)). Under DCSBM, a set of tuning parameters are used to control the node degrees. θ is the $n \times 1$ degree vector and $\theta_i > 0$ is the *i*-th element of θ . Let *P* be a $K \times K$ matrix such that

$$P$$
 is symmetric, nonsingular, nonnegative and irreducible. (32)

Generally, the elements of P denote the probability of generating an edge between distinct nodes, therefore the entries of P are always assumed to be in the interval [0, 1]. In this paper, we call P as the mixing matrix for convenience. Then under DCSBM, the probability of an edge between node i and node j is

$$Pr(A_{ij} = 1) = \theta_i \theta_j P_{g_i g_j},\tag{33}$$

where $\theta_i \theta_j P_{g_i g_j} \in [0, 1]$ and g_i denotes the cluster that node *i* belongs to. Note that if $g_i = g_j$ for any two distinct nodes *i*, *j* such that $\theta_i = \theta_j$, the DCSBM model degenerates to SBM. Then the degree heterogeneity matrix $\Theta \in \mathcal{R}^{n \times n}$ and the $n \times K$ membership matrix $Z \in \mathcal{R}^{n \times K}$ can be presented as:

$$\Theta = \operatorname{diag}(\theta_1, \theta_2, \dots, \theta_n), \ Z_{ik} = \mathbb{1}_{\{g_i = k\}} \text{ for } 1 \le i \le n, 1 \le k \le K.$$
(34)

Definition 1. Model (31)-(34) constitute the so-called degree-corrected stochastic block model (DCSBM), and denote it by $DCSBM(n, P, \Theta, Z)$ for convenience.

3.2 The algorithm: ISC

Under $DCSBM(n, P, \Theta, Z)$, the details of ISC method proceed as follows:

ISC. Input: A, K, and a ridge regularizer $\delta > 0$. Output: community labels for all nodes.

Step 1: Obtain the graph Laplacian with ridge regularization by

$$L_{\delta} = (D + \delta dI)^{-1/2} A (D + \delta dI)^{-1/2},$$

where $d = \frac{d_{\max} + d_{\min}}{2}$, $d_{\max} = \max_{1 \le i \le n} d_i$, $d_{\min} = \min_{1 \le i \le n} d_i$ (where d_i is the degree of node *i*, i.e., $d_i = \sum_{j=1}^n A_{ij}$ for $1 \le i \le n$), and *I* is the $n \times n$ identity matrix. Note that the ratio of the largest diagonal entry of $D + \delta dI$ and the smallest one is in $\left[\frac{d_{\min}}{d_{\max}}, \frac{d_{\max}}{d_{\min}}\right]$. Conventional choices for δ are 0.05 and 0.10.

Step 2: Compute the leading K+1 eigenvalues and eigenvectors with unit norm of L_{δ} , and then calculate the weighted eigenvectors matrix:

$$\hat{X} = [\hat{\eta}_1, \hat{\eta}_2, \dots, \hat{\eta}_K, \hat{\eta}_{K+1}] \cdot \operatorname{diag}(\hat{\lambda}_1, \hat{\lambda}_2, \dots, \hat{\lambda}_K, \hat{\lambda}_{K+1}),$$

where $\hat{\lambda}_i$ is the *i*-th leading eigenvalue of L_{δ} , and $\hat{\eta}_i$ is the respective eigenvector with unit-norm, for $i = 1, \dots, K + 1$.

Step 3: Normalizing each row of \hat{X} to have unit length, and denote by \hat{X}^* ,

$$\hat{X}_{ij}^* = \hat{X}_{ij} / (\sum_{j=1}^{K+1} \hat{X}_{ij}^2)^{1/2}, i = 1, \dots, n, j = 1, \dots, K+1.$$

Step 4: For clustering, apply k-means method to \hat{X}^* with assumption that there are K clusters.

Compared with tradition spectral clustering methods such as SCORE, RSC and OCCAM, our ISC is quite different from them. The differences can be stated in the following four aspects: (a) ISC applies a graph Laplacian with ridge regularization L_{δ} instead of the graph Laplacian L_{τ} in RSC. (b) ISC uses eigenvalues to re-weight the columns of \hat{X} , i.e., the \hat{X} in ISC is computed as the production of eigenvectors and eigenvalues, instead of simply using the eigenvectors as in SCORE and RSC. Meanwhile, we apply leading eigenvalues with power 1 instead of power 0.5 in OCCAM, which ensures that our ISC can detect dis-associative networks while OCCAM can not. (c) ISC always selects the leading (K+1) eigenvectors and eigenvalues for clustering while other spectral clustering approaches only apply the leading K eigenvectors for clustering, such as SCORE and RSC. This main characteristic enables the ISC to deal with weak signal networks. (d) RSC takes the average degree as default regularizer τ , and SCORE is sensitive to the choice of threshold, while our ISC is insensitive to the choice of δ as long as it is slightly larger than zero (see Section 5 for details). All these four aspects are significant in supporting the performances of our ISC. The numerical comparison of these methods is demonstrated in Section 5.

4. Theoretical Results

4.1 Population analysis of the ISC

This section presents the population analysis of ISC method to show that it returns perfect clusters in the ideal case.

Under $DCSBM(n, P, \Theta, Z)$, denote the expectation matrix of the adjacency matrix A as $\Omega = \mathbb{E}[A]$ such that $\Omega_{ij} = Pr(A_{ij} = 1) = \theta_i \theta_j P_{g_i g_j}$. Following Jin (2015), Karrer and Newman (2011) and Qin and Rohe (2013), matrix Ω can be expressed as

$$\Omega = \Theta Z P Z' \Theta.$$

Then the population Laplacian can be written as

$$\mathscr{L} = \mathscr{D}^{-1/2} \Omega \mathscr{D}^{-1/2},$$

where \mathscr{D} is a diagonal matrix which contains the expected node degrees, $\mathscr{D}_{ii} = \sum_{j}^{n} \Omega_{ij}$. And the regularized Laplacian \mathscr{L}_{δ} in $\mathcal{R}^{n \times n}$ can be presented as

$$\mathscr{L}_{\delta} = \mathscr{D}_{\delta}^{-1/2} \Omega \mathscr{D}_{\delta}^{-1/2},$$

where $\mathscr{D}_{\delta} = \mathscr{D} + \delta dI$, δ and d are tuning parameters.

We find that the regularized Laplacian matrix has an explicit form which is a product of some matrices. For convenience, we introduce some notations. Let Q be a $K \times n$ matrix with $Q = PZ'\Theta$, and let D_P be a $K \times K$ diagonal matrix with $D_P(i,i) = \sum_{j=1}^n Q_{ij}, i = 1, 2, ..., K$. Define θ^{δ} as an $n \times 1$ vector whose *i*-th entry θ_i^{δ} is $\theta_i \frac{\mathscr{D}_{ii}}{\mathscr{D}_{ii} + \delta d}$. And let Θ_{δ} be a diagonal matrix whose *ii*'th entry is θ_i^{δ} for $1 \leq i \leq n$. Define a $K \times K$ symmetric matrix \tilde{P} as $\tilde{P} = D_P^{-1/2} P D_P^{-1/2}$. Based on these notations, Lemma 1 gives the explicit form for \mathscr{L}_{δ} .

Lemma 1. (Explicit form for \mathscr{L}_{δ}) Under $DCSBM(n, P, \Theta, Z)$, \mathscr{L}_{δ} can be written as

$$\mathscr{L}_{\delta} = \mathscr{D}_{\delta}^{-1/2} \Omega \mathscr{D}_{\delta}^{-1/2} = \Theta_{\delta}^{1/2} Z \tilde{P} Z' \Theta_{\delta}^{1/2}.$$

Note that Lemma 1 is equivalent to the Lemma 3.2 in Qin and Rohe (2013), so we omit the proof of it here.

To express the eigenvectors of \mathscr{L}_{δ} , we rewrite \mathscr{L}_{δ} in the following form:

$$\mathscr{L}_{\delta} = \|\tilde{\theta}\|^2 \tilde{\Gamma} \tilde{D} \tilde{P} \tilde{D} \tilde{\Gamma}',$$

where $\tilde{\theta} = (\tilde{\theta}_1, \ldots, \tilde{\theta}_n)' = (\sqrt{\theta_1^{\delta}}, \ldots, \sqrt{\theta_n^{\delta}})'$, $\tilde{\theta}^{(k)}$ is an $n \times 1$ vector with elements $\tilde{\theta}_i^{(k)} = \tilde{\theta}_i \mathbb{1}_{(g_i=k)}$ for $1 \leq i \leq n, 1 \leq k \leq K$, \tilde{D} is a $K \times K$ diagonal matrix of the *overall degree intensities* such that $\tilde{D}(k,k) = \|\tilde{\theta}^{(k)}\|/\|\tilde{\theta}\|$, and $\tilde{\Gamma}$ is an $n \times K$ matrix such that

$$\tilde{\Gamma} = \begin{bmatrix} \frac{\tilde{\theta}^{(1)}}{\|\tilde{\theta}^{(1)}\|} & \frac{\tilde{\theta}^{(2)}}{\|\tilde{\theta}^{(2)}\|} & \dots & \frac{\tilde{\theta}^{(K)}}{\|\tilde{\theta}^{(K)}\|} \end{bmatrix}.$$

Note that $\tilde{\Gamma}'\tilde{\Gamma} = I$, where I is the $K \times K$ identity matrix.

By the definition (32) of P and basic knowledge of algebra, we know that the rank of \mathscr{L}_{δ} is K when there are K clusters, therefore \mathscr{L}_{δ} has K nonzero eigenvalues. Lemma 2 gives the expressions of the leading Keigenvectors of \mathscr{L}_{δ} .

Lemma 2. Under $DCSBM(n, P, \Theta, Z)$, suppose all eigenvalues of $\tilde{D}\tilde{P}\tilde{D}$ are simple. Let $\lambda_1/\|\tilde{\theta}\|^2, \lambda_2/\|\tilde{\theta}\|^2, \ldots, \lambda_K/\|\tilde{\theta}\|^2$ be such eigenvalues, arranged in the descending order of the magnitudes, and let a_1, a_2, \ldots, a_K

be the associated (unit-norm) eigenvectors. Then the K nonzero eigenvalues of \mathscr{L}_{δ} are $\lambda_1, \lambda_2, \ldots, \lambda_K$, and the associated (unit-norm) eigenvectors are

$$\eta_k = \sum_{i=1}^{K} [a_k(i) / \|\tilde{\theta}^{(i)}\|] \cdot \tilde{\theta}^{(i)}, k = 1, 2, \dots, K$$

Based on the regularized Laplacian \mathscr{L}_{δ} and its eigenvalues and eigenvectors, we can write down the Ideal ISC algorithm as follows:

Ideal ISC. Input: Ω . Output: ℓ .

Step 1: Obtain \mathscr{L}_{δ} .

Step 2: Obtain $X = [\eta_1, \eta_2, \ldots, \eta_K, \eta_{K+1}] \cdot \operatorname{diag}(\lambda_1, \lambda_2, \ldots, \lambda_K, \lambda_{K+1}).$ Since \mathscr{L}_{δ} only has K nonzero eigenvalues (i.e., $\lambda_i \neq 0$ for $1 \leq i \leq K$ and $\lambda_{K+1} = 0$), we have $X = [\lambda_1 \eta_1, \lambda_2 \eta_2, \ldots, \lambda_K \eta_K, \lambda_{K+1} \eta_{K+1}] = [\lambda_1 \eta_1, \lambda_2 \eta_2, \ldots, \lambda_K \eta_K, 0].$

Step 3: Obtain X^* , the row-normalized version of X.

Step 4: Apply k-means to X^* , assuming there are K clusters.

Note that the Ideal ISC algorithm is obtained by applying Ω to replace the input the adjacency matrix A in the ISC algorithm, that's why we call it as the Ideal ISC algorithm. Lemma 3 confirms that the Ideal ISC algorithm can return the perfect clustering under $DCSBM(n, P, \Theta, Z)$.

Lemma 3. Under $DCSBM(n, P, \Theta, Z)$, X has K distinct rows, and for any two distinct nodes $i, j, if g_i = g_j$, the j-th row of X equals the i-th row of it.

Applying K-means to X leads to the true community labels of each node. The above population analysis for ISC method presents a direct understanding of why the ISC algorithm works and guarantees that ISC method returns perfect clustering results under the ideal case.

4.2 Characterization of the matrix X^*

We wish to bound $\|\hat{X}^* - X^*\|_F$. To do so, first we need to find the bound of $\|\hat{X} - X\|_F$ based on the bound of the difference between eigenvalues of L_{δ} and \mathscr{L}_{δ} . Then, we give Lemma 4 to bound the difference between eigenvalues of L_{δ} and \mathscr{L}_{δ} .

Lemma 4. Under $DCSBM(n, P, \Theta, Z)$, if $d\delta + \min_i \mathscr{D}_{ii} > 3\log(4n/\epsilon)$, with probability at least $1 - \epsilon$,

$$\max_{1 \le k \le K} |\hat{\lambda}_k - \lambda_k| \le 4\sqrt{\frac{3\log(4n/\epsilon)}{d\delta + \min_i \mathscr{D}_{ii}}} \text{ and } \sum_{i=1}^K |\hat{\lambda}_i - \lambda_i|^2 \le \frac{48K\log(4n/\epsilon)}{d\delta + \min_i \mathscr{D}_{ii}}.$$

Let \hat{X}_i, X_i denote the *i*-th row of \hat{X} and X, respectively. Next, we apply results of Lemma 4 to obtain the bound for $\|\hat{X}^* - X^*\|_F$, which is given in the following lemma.

Lemma 5. Under $DCSBM(n, P, \Theta, Z)$, define $m = \min_i \{\min\{\|\hat{X}_i\|, \|X_i\|\}\}$ as the length of the shortest row in \hat{X} and X. Then, for any $\epsilon > 0$ and sufficiently large n, assume that

(a)
$$\left(\frac{\log(4n/\epsilon)}{d\delta + \min_i \mathscr{D}_{ii}}\right)^{1/2} \le \frac{\lambda_K}{8\sqrt{3}}, \quad (b) \quad d\delta + \min_i \mathscr{D}_{ii} > 3\log(4n/\epsilon),$$

with probability at least $1 - \epsilon$, the following hold

$$\begin{aligned} \|\hat{X} - X\|_F &\leq \left(\frac{48K\log(4n/\epsilon)}{d\delta + \min_i \mathscr{D}_{ii}} + \hat{\lambda}_{K+1}\right)^{1/2} + \frac{32K}{\lambda_K} \left(\frac{3\log(4N/\epsilon)}{d\delta + \min_i \mathscr{D}_{ii}}\right)^{1/2}, \\ \|\hat{X}^* - X^*\|_F &\leq \frac{1}{m} \left(\frac{48K\log(4n/\epsilon)}{d\delta + \min_i \mathscr{D}_{ii}} + \hat{\lambda}_{K+1}\right)^{1/2} + \frac{32K}{m\lambda_K} \left(\frac{3\log(4N/\epsilon)}{d\delta + \min_i \mathscr{D}_{ii}}\right)^{1/2}. \end{aligned}$$

4.3 Bound of Hamming error rate of ISC

This section bounds the Hamming error rate (Jin (2015)) of ISC under DCSBM to show that ISC yields stable consistent community detection.

The Hamming error rate of ISC is defined as:

$$\operatorname{Hamm}_{n}(\hat{\ell}, \ell) = \min_{\pi \in S_{K}} H_{p}(\hat{\ell}, \pi(\ell))/n,$$

where $S_K = \{\pi : \pi \text{ is a permutation of the set } \{1, 2, \dots, K\}\}^{-1}, \pi(\ell) \text{ is the } n \times 1 \text{ vector such that } \pi(\ell)(i) = \pi(\ell(i)) \text{ for } 1 \leq i \leq n, \text{ and } H_p(\ell, \ell) \text{ is the expected number of mismatched labels defined as below}$

$$H_p(\hat{\ell}, \ell) = \sum_{i=1}^n P(\hat{\ell}(i) \neq \ell(i)).$$

The following theorem is the main theoretical result of ISC, which bounds the Hamming error of ISC algorithm under mild conditions and shows that the ISC method yields stable consistent community detection if we assume that the adjacency matrix A are generated from the DCSBM model.

¹Due to the fact that the clustering errors should not depend on how we tag each of the K communities, that's why we need to consider permutation to measure the clustering errors of ISC here.

Theorem 1. Set $err_n = 4\left[\frac{1}{m}\sqrt{\frac{48K\log(4n/\epsilon)}{d\delta+\min_i\mathscr{D}_{ii}}} + \hat{\lambda}_{K+1}^2 + \frac{32K}{m\lambda_K}\sqrt{\frac{3\log(4N/\epsilon)}{d\delta+\min_i\mathscr{D}_{ii}}}\right]^2$, under $DCSBM(n, P, \Theta, Z)$ and the same assumptions as in Lemma 5 hold, suppose as $n \to \infty$, we have

$$err_n/\min\{n_1, n_2, \ldots, n_K\} \to 0,$$

where n_k is the size of the k-th community for $1 \le k \le K$. For the estimated label vector $\hat{\ell}$ by ISC, with probability at least $1 - \epsilon$, we have

$$\operatorname{Hamm}_{n}(\hat{\ell}, \ell) \leq err_{n}/n.$$

Note that by the assumption (a) in Theorem 5, we can zoom $\operatorname{Hamm}_n(\hat{\ell}, \ell)$ as

$$\operatorname{Hamm}_{n}(\hat{\ell}, \ell) \leq \frac{(\sqrt{K\lambda_{K}^{2} + 4\hat{\lambda}_{K+1}^{2}} + 8K)^{2}}{nm^{2}}, \tag{45}$$

which tells us that 1) with the increasing of n, while keeping other parameters fixed, the Hamming error rates of ISC decreases to zero; 2) a larger K suggests a larger error bound, which means that it becomes harder to detect communities for ISC when K increases; 3) for weak signal networks, since $\hat{\lambda}_{K+1}$ is close to $\hat{\lambda}_K$ in magnitude, and we also know that λ_K is close to $\hat{\lambda}_K$ by Lemma 4, we can conclude that $\hat{\lambda}_{K+1}$ is close to λ_K in some sense, therefore, for weak signal networks, we can even roughly simplify the bound of Hamm_n($\hat{\ell}, \ell$) by

$$\operatorname{Hamm}_{n}(\hat{\ell}, \ell) \leq \frac{(|\hat{\lambda}_{K+1}|\sqrt{K+4}+8K)^{2}}{nm^{2}}.$$
 (46)

As for strong signal networks, $\hat{\lambda}_K$ is much larger than $\hat{\lambda}_{K+1}$ in magnitude, by Lemma 4, $4\hat{\lambda}_{K+1}^2$ is also smaller than $K\lambda_K^2$ for $K \ge 2$, hence the bound of the Hamming error rate for strong signal networks mainly depends on the K-th leading eigenvalue.

Combining (45) and (46), we can find that our ISC can detect both strong signal networks and weak signal networks. The main reason is that its theoretical bound of clustering error depends on the leading K-th eigenvalue of L_{δ} for strong signal networks and the bound relies on the leading (K + 1)-th eigenvalue of L_{δ} when dealing with weak signal networks.

5. Numerical Results

We compare ISC with a few recent methods: SCORE, OCCAM, RSC, SCORE+ and SLIM via synthetic data and eight real-world networks. Unless specified, we set the regularizer $\delta = 0.1$ for ISC in this section. For each procedure, the clustering error rate is measured by

$$\min_{\{\pi: \text{permutation over } \{1,2,\dots,K\}\}} \frac{1}{n} \sum_{i=1}^{n} 1\{\pi(\hat{\ell}(i)) \neq \ell(i)\}.$$
 (57)

where $\ell(i)$ and $\hat{\ell}(i)$ are the true and estimated labels of node *i*.

5.1 Synthetic data experiment

In this subsection, we use two simulated experiments to investigate the performances of these approaches.

Experiment 1. We investigate performances of these approaches under SBM when K = 2 and 3 by increasing n. Set $n \in \{40, 80, 120, \ldots, 400\}$. For each fixed n, we record the mean of the error rates of 50 repetitions. Meanwhile, to check that whether we generate weak signal networks during simulation, we also (including Experiment 2) record the mean of the quantity $1 - \left|\frac{\lambda_{K+1}}{\lambda_{K}}\right|$ where λ_k (k = K, K+1) denotes the k-th leading eigenvalue of A and L_{δ} .

Experiment 1(a). Let K = 2 in this sub-experiment. Generate ℓ by setting each node belonging to one of the clusters with equal probability (i.e., $\ell(i) - 1 \stackrel{\text{i.i.d.}}{\sim} \text{Bernoulli}(1/2)$). Set the mixing matrix $P_{1(a)}$ as

$$P_{1(a)} = \begin{bmatrix} 0.9 & 0.5\\ 0.5 & 0.9 \end{bmatrix}$$

Generate θ as $\theta(i) = 0.2$ for $g_i = 1$, $\theta(i) = 0.6$ for $g_i = 2$.

Experiment 1(b). Let K = 3 in this sub-experiment. ℓ is generated same as in Experiment 1(a). Set the mixing matrix $P_{1(b)}$ as

$$P_{1(b)} = \begin{bmatrix} 0.9 & 0.5 & 0.5 \\ 0.5 & 0.9 & 0.5 \\ 0.5 & 0.5 & 0.9 \end{bmatrix}.$$

Generate θ as $\theta(i) = 0.2$ for $g_i = 1$, $\theta(i) = 0.6$ for $g_i = 2$, and $\theta(i) = 0.8$ for $g_i = 3$.

The numerical results of Experiment 1 are shown in Figure 1 from which we can find that 1) ISC outperforms the other five procedures obviously in Experiment 1(a) and 1(b). 2) error rates of ISC and SCORE+ decrease as n increases, while the other four approaches perform unsatisfactory even when n increases in Experiment 1(a). This phenomenon occurs because even the sample size n is increasing to 400, it is still too small for SCORE, OCCAM, RSC and SLIM. Furthermore, by Figure 2, we can find that the quantity $1 - \left|\frac{\lambda_{K+1}}{\lambda_{K}}\right|$ is almost always smaller than 0.1 when the eigenvalue λ is from the adjacency matrix A and $1 - \left|\frac{\lambda_{K+1}}{\lambda_{K}}\right|$ is always smaller than 0.1 when λ is from the regularized Laplacian L_{δ} in this experiment, which indicate that λ_{K} and λ_{K+1} are close enough. By the definition of weak signal networks, the networks generated in this experiment are weak signal networks². In all, ISC outperforms other methods when the network is weak signal.



Figure 1: Numerical results of Experiment 1. Left panel: Experiment 1(a). Right panel: Experiment 1(b). y-axis: error rates.

 $^{^{2}}$ As far as we know, there are two real-world weak signal networks Simmons and Caltech (Jin et al. (2018)), which suggests that generating weak signal networks numerically is significant since it can help us to test whether our newly designed methods can deal with weak signal networks, not only depending on the performances of the two real-world weak signal networks Simmons and Caltech.



Figure 2: Numerical results of Experiment 1. Left panel: Experiment 1(a). Right panel: Experiment 1(b). y-axis: $1 - \left|\frac{\lambda_{K+1}}{\lambda_K}\right|$. The black circle line denotes that the two eigenvalues are from A in the quantity $1 - \left|\frac{\lambda_{K+1}}{\lambda_K}\right|$, while the black diamond line denotes that the two eigenvalues are from L_{δ} (we use the same labels in Experiment 2).

Experiment 2. In this experiment, we study how decreasing the difference of θ between different communities, the ratios of the size between different communities, and the ratios of diagonal and off-diagonal entries of the mixing matrix impact the performance of our ISC approach when n = 400 and K = 2.

Experiment 2(a). We study the influence of decreasing the difference of θ between different communities under SBM in this sub-experiment. Set a_0 in $\{0.05, 0.1, 0.15, \ldots, 0.45, 0.5\}$. We generate ℓ by setting each node belonging to one of the clusters with equal probability. And set the mixing matrix $P_{2(a)}$ as

$$P_{2(a)} = \begin{bmatrix} 0.9 & 0.5\\ 0.5 & 0.9 \end{bmatrix}$$

Generate θ as $\theta(i) = 1 - a_0$ if $g_i = 1$, $\theta(i) = a_0$ for $g_i = 2$. Note that for each a_0 , $\theta(i)$ is a fixed number for all nodes in the same community and hence this is a SBM case. For each a_0 (as well as b_0 and c_0 in the following experiments), we record the mean of clustering error rates of 50 sampled networks.

Experiment 2(b). We study how the proportion between the diagonals and off-diagonals of P affects the performance of these methods under SBM in this sub-experiment. Set the proportion b_0 in $\{1/20, 2/20, 3/20, \ldots, 10/20\}$. We generate ℓ by setting each node belonging to one of the clusters with equal probability. Set θ as $\theta(i) = 0.2$ if $g_i = 1$ and $\theta(i) = 0.6$ otherwise. The mixing matrix $P_{2(b)}$ is set as below:

$$P_{2(b)} = \begin{bmatrix} 0.5 & b_0 \\ b_0 & 0.5 \end{bmatrix}.$$

Experiment 2(c). All parameters are same as Experiment 2(b), except that we set $g_i = 1$ for $1 \le i \le 100$, $g_i = 2$ for $101 \le i \le n$, and $\theta_i = 0.5 + 0.5(i/n)^2$ for $1 \le i \le n$ (i.e., Experiment 2(c) is the DCSBM case).

Experiment 2(d). We study how the proportion between the size of clusters influences the performance of these methods under SBM in this subexperiment. We set the proportion c_0 in $\{1, 2, \ldots, 9\}$. Set $n_1 = \operatorname{round}(\frac{n}{c_0+1})$ as the number of nodes in cluster 1 where $\operatorname{round}(x)$ denotes the nearest integer for any real number x. Note that c_0 is the ratio ³ of the sizes of cluster 2 and cluster 1. We generate ℓ such that for $i = 1, \ldots, n_1, g_i = 1$; for $i = (n_1 + 1), \ldots, n, g_i = 2$. And the mixing matrix $P_{2(d)}$ is as follows:

$$P_{2(d)} = \begin{bmatrix} 0.9 & 0.5\\ 0.5 & 0.9 \end{bmatrix}.$$

Let θ be $\theta(i) = 0.4$ if $g_i = 1$ and $\theta(i) = 0.6$ otherwise.

Experiment 2(e). All parameters are same as Experiment 2(d), except that $\theta_i = 0.5 + 0.5(i/n)^2$ for $1 \le i \le n$ (i.e., Experiment 2(e) is the DCSBM case).

Experiment 2(f). All parameters are same as Experiment 2(d), except that $\theta_i = 0.5 + 0.5i/n$ for $1 \le i \le n$.

The numerical results of Experiment 2 are demonstrated in Figure 3, from which we can find that 1) ISC always have better performances than the other five approaches in this experiment. 2) numerical results of Experiment 2(d), 2(e), and 2(f) tells us that though it becomes challenging for all the six approaches to have satisfactory detection performances for a fixed size network when the size of one of the cluster decreases, our approach ISC always outperforms other five approaches. Recall that when the quantity $1 - \left|\frac{\lambda_{K+1}}{\lambda_K}\right|$ is larger than 0.1, the network is a strong signal network. Figure 4 shows that we generate both strong and weak signal networks in this experiment. When the network is weak signal, our ISC always performs satisfactory shown by Figure 3. Especially, in the last three panels of Figure 3, our ISC performs much better than other methods when the networks are strong signal. Therefore, generally speaking, numerical results of Experiment 2 concludes that our ISC almost always outperforms the other five

³Number of nodes in cluster 2 is $n - \text{round}(\frac{n}{c_0+1}) \approx n - \frac{n}{c_0+1} = c_0 \frac{n}{c_0+1}$, therefore number of nodes in cluster 2 is around c_0 times of that in cluster 1.



Figure 3: Numerical results of Experiment 2. Top three panels (from left to right): Experiment 2(a), Experiment 2(b), and Experiment 2(c). Bottom three panels (from left to right): Experiment 2(d), Experiment 2(e), and Experiment 2(f). y-axis: error rates.

procedures whether the simulated network is strong signal or weak signal.

Combining the numerical results of the above two experiments, we can draw a conclusion that our ISC has significant advantages over the three classical spectral clustering procedures SCORE, OCCAM and RSC, especially when dealing with weak signal networks. Numerical results also show that our ISC outperforms the recent spectral clustering approach SLIM. Though SCORE+ in Jin et al. (2018) is designed based on applying one more eigenvector for clustering when dealing with weak signal networks, our ISC outperforms SCORE+ in Experiment 1 and Experiment 2. This statement is also supported by the results of the next sub-section where we deal with eight real-world networks (two of them Simmons and Caltech are typical weak signal networks). Meanwhile, by observing the quantity $1 - \left|\frac{\lambda_{K+1}}{\lambda_K}\right|$ where the two eigenvalues are from A or L_{δ} in the above two experiments, we find that the networks we generated are weak signal networks numerically. The generation of weak signal networks is important since it can help us as well as readers to test the designed algorithms whether they



Figure 4: Numerical results of Experiment 2. Top three panels (from left to right): Experiment 2(a), Experiment 2(b), and Experiment 2(c). Bottom three panels (from left to right): Experiment 2(d), Experiment 2(e), and Experiment 2(f). y-axis: $1 - \left|\frac{\lambda_{K+1}}{\lambda_{K}}\right|$.

can detect information of nodes labels for weak signal networks.

5.2 Application to real-world datasets

In this paper, eight real-world network datasets are analyzed to test the performances of our ISC. The eight datasets are used in Jin et al. (2018) and can be downloaded directly from http://zke.fas.harvard.edu/software.html. Table 2 presents some basic information about the eight datasets. These eight datasets are networks with known labels for all nodes where the true label information is surveyed by researchers. From Table 2, we can see that d_{\min} and d_{\max} are always quite different for any one of the eight realworld datasets, which suggests a DCSBM case. The true labels of the eight real-world datasets are originally suggested by the authors/creators, and we take them as the "ground truth". Note that just as Jin et al. (2018), there is pre-processing of the eight datasets because some nodes may have mixed memberships. For the Polbooks data, the books labeled as "neutral"

Dataset	Source	n	K	d_{\min}	d_{\max}
Karate	Zachary (1977)	34	2	1	17
Dolphins	Lusseau (2003, 2007); Lusseau et al. (2003)	62	2	1	12
Football	Girvan and Newman (2002)	110	11	7	13
Polbooks	Jin et al. (2018)	92	2	1	24
UKfaculty	Nepusz et al. (2008)	79	3	2	39
Polblogs	Adamic and Glance (2005)	1222	2	1	351
Simmons	Traud et al. (2011)	1137	4	1	293
Caltech	Traud et al. (2011)	590	8	1	179

Table 2: Eight real-world data sets with known label information analyzed in this paper.

Table 3: The quantity $1 - \left|\frac{\lambda_{K+1}}{\lambda_K}\right|$ for the eight real-world datasets, where λ_k are the k-th leading eigenvalues from A or L_{δ} .

$1 - \left \frac{\lambda_{K+1}}{\lambda_K}\right $	Karate	Dolphins	Football	Polbooks	UKfaculty	Polblogs	Simmons	Caltech
A	0.0984	0.1863	0.0213	0.5034	0.2996	0.5101	0.0804	0.0777
L_{δ}	0.1610	0.2116	0.1469	0.2720	0.3666	0.4570	0.0540	0.0241

are removed. For the football network, the five "independent" teams are deleted. For the UK faculty data, the smallest group with only 2 nodes is removed. Therefore, after such pre-processing, the assumption that the given network consists of K "non-overlapping" communities is reasonable and satisfied by the eight real-world networks. Readers who are interested in the background information of the eight real-world networks can refer to Jin et al. (2018) or the source papers listed in Table 2 for more details.

Table 3 presents the quantity of $1 - \left|\frac{\lambda_{K+1}}{\lambda_{K}}\right|$ for the eight real-world datasets. It needs to mention that when $1 - \left|\frac{\lambda_{K+1}}{\lambda_{K}}\right| < 0.1$, the (K + 1)-th eigenvalue is quite close to the K-th one. From Table 3 we can find that the quantities for A of Karate, Football, Simmons and Caltech are smaller than 0.1. While the quantities for L_{δ} are larger than 0.1 for Karate and Football but smaller than 0.1 for Simmons and Caltech. As discussed in Jin et al. (2018), we know Karate and Football are usually taken as strong signal networks, while Simmons and Caltech are weak signal networks. Therefore, the quantity of L_{δ} could be more effective to distinguish weak and strong signal networks.

Next we study the performances of these methods (note that we also compare our ISC with the convexied modularity maximization (CMM) method by Chen et al. (2018)) on the eight real-world networks. First,

Methods	Karate	Dolphins	Football	Polbooks	UKfaculty	Polblogs	Simmons	Caltech
SCORE	0/34	0/62	5/110	1/92	1/79	58/1222	268/1137	180/590
SCORE_{K+1}	0/34	0/62	5/110	24/92	35/79	281/1222	187/1137	150/590
OCCAM	0/34	1/62	4/110	3/92	5/79	60/1222	268/1137	192/590
RSC	0/34	1/62	5/110	3/92	0/79	64/1222	244/1137	170/590
RSC_{K+1}	0/34	15/62	4/110	3/92	2/79	79/1222	134/1137	100/590
SCORE+	1/34	2/62	6/110	2/92	2/79	51/1222	127/1137	98/590
SLIM	1/34	0/62	6/110	2/92	1/79	51/1222	275/1137	150/590
$\operatorname{SLIM}_{K+1}$	1/34	0/62	6/110	2/92	2/79	53/1222	268/1137	157/590
CMM	0/34	1/62	7/110	1/92	7/79	62/1222	137/1137	106/590
ISC	0/34	1/62	3/110	3/92	1/79	64/1222	121/1137	96/590

Table 4: Error rates on the eight empirical data sets.

we'd note that in the procedure of SCORE, RSC and SLIM, there is one common step which computes the leading K eigenvectors of A or its variants. For fair comparison, we set SCORE_{K+1} , RSC_{K+1} and SLIM_{K+1} as three new algorithms such that SCORE_{K+1} is SCORE method but using the leading K + 1 eigenvectors, RSC_{K+1} is RSC by applying the leading K + 1 eigenvectors, and SLIM_{K+1} is SLIM by applying the leading K + 1eigenvectors (i.e., ISC, SCORE_{K+1} , RSC_{K+1} , and SLIM_{K+1} all apply K+1eigenvectors for clustering).

Table 4 summaries the error rates on the eight real-world networks. For Karate, Dolphins, Football, Polboks, UKfaculty, and Polblogs, ISC has similar performances as SCORE, OCCAM, RSC and CMM, while SCORE+ and SLIM perform best with the error rate 51/1222 for Polblogs. However, for the Football network, ISC has the smallest number of errors while CMM has the largest. Though $SCORE_{K+1}$, RSC_{K+1} and $SLIM_{K+1}$ also apply the leading K + 1 eigenvectors for clustering, these three approaches fail to detect some of the eight real-world datasets with pretty high error rates. For instance, $SCORE_{K+1}$ fails to detect Polbooks, Ukfaculty and Polblogs, meanwhile RSC_{K+1} fails to detect Dolphins. When dealing with Simmons and Caltech, ISC has excellent performances on these two datasets and significantly outperforms all other approaches with 121/1137 error rate for Simmons and 96/590 for Caltech. $SLIM_{K+1}$ perform similar as SLIM and both two procedures fail to detect Simmons and Caltech with high error rates. Deserved to be mentioned, $SCORE_{K+1}$ and RSC_{K+1} perform better than the original SCORE and RSC for Simmons and Caltech, respectively. This phenomenon occurs because the leading K + 1 eigenvalue of A or its variants for Simmons (Caltech) is close to the leading K eigenvalue as shown in the Table 3, and hence the leading K+1 eigenvector also contains label information.

Then we study the different choice of the tuning parameters δ . In Table 5, set $\delta \in \{0, 0.025, 0.05, \dots, 0.175, 0.20\}$, and fix other parameters and record the corresponding number of errors for the eight real-world networks. The results of Table 5 tells us that ISC successfully detect these networks except that it fails to detect Simmons when δ is 0 or 0.025. Since when δ is set as 0, L_{δ} is the Laplacian matrix L. Therefore, according to the results of Table 5, we suggest that δ should be larger than 0. Next, we further study the choice of δ by taking values in $\{0.005, 0.01, 0.015, \ldots, 1\}$ (there are 200 choices of δ) and $\delta \in \{1, 2, \dots, 200\}$ (there are 200 choices of δ). The number of errors for the eight real-world networks with a variety of δ are plotted in the Figure 5. From Figure 5 we can see that ISC always successfully detect information of nodes labels for the eight real-world networks even when δ is set as large as hundreds or as small as 0.005. The results of Table 5 and Figure 5 suggest that ISC is insensitive to different choices of δ as long as $\delta > 0$, and we can even set δ as large as hundreds. Actually, this phenomenon is supported by Theorem 1, which tell us that when fixing parameters n, P, Θ, Z under DCSBM and increasing δ , two assumptions (a) and (b) in Lemma 5 still hold, which suggests the feasibility of our ISC.

Finally, we study the value $d = \frac{d_{\max} + d_{\min}}{2}$. Note that the value δd in our regularized Laplacian matrix L_{δ} $(L_{\delta} = (D + \delta dI)^{-1/2}A(D + \delta dI)^{-1/2})$, actually, is the regularizer τ in the regularized Laplacian matrix L_{τ} $(L_{\tau} = (D + \tau I)^{-1/2}A(D + \tau I)^{-1/2})$ which is defined in the RSC approach and the default choice of τ is set as the average degree. Then, one question arises naturally, whether we can apply other values such as d_{\max}, d_{\min} or \bar{d} (the average degree) to replace d in our ISC method? The answer is YES. We replace d by d_{\max}, d_{\min} and \bar{d} in our algorithm, and demonstrate the numerical results in Table 6 with notation $\mathrm{ISC}_{d_{\max}}$, $\mathrm{ISC}_{d_{\min}}$ and $\mathrm{ISC}_{\bar{d}}$, respectively. From Table 6, we can find that 1) $\mathrm{ISC}_{d_{\min}}$ fails to detect Simmons and Caltech with number of errors as large as 305 and 154, respectively; 2) $\mathrm{ISC}_{\bar{d}}$ fails to detect Simmons with number of errors as large as 200; 3) $\mathrm{ISC}_{d_{\max}}$ performs better than $\mathrm{ISC}_{d_{\min}}$ and $\mathrm{ISC}_{\bar{d}}$, and ISC outperforms $\mathrm{ISC}_{d_{\max}}$ for all datasets. As shown by the numerical results in Table 6, ISC almost always performs better than $\mathrm{ISC}_{d_{\max}}$, $\mathrm{ISC}_{d_{\min}}$ and $\mathrm{ISC}_{\bar{d}}$, which suggests us the default choice of d is $d = \frac{d_{\max} + d_{\min}}{2}$ in this paper.

Remark 1. According to the numerical results with several d in Table 6, we find that ISC is sensitive to the choice of d since $ISC_{d_{\min}}$ fails to detect Simmons and Caltech, $ISC_{\bar{d}}$ fails to detect Simmons. Luckily, though ISC

δ	Karate	Dolphins	Football	Polbooks	UKfculty	Polblogs	Simmons	Caltech
0	1	1	3	3	2	60	307	122
0.025	1	1	3	3	2	61	200	96
0.05	0	1	3	3	2	63	122	98
0.075	0	1	6	3	1	63	121	96
0.10	0	1	3	3	1	64	121	96
0.125	0	0	3	3	1	64	121	96
0.15	0	0	3	3	1	65	121	97
0.175	0	0	3	3	1	66	121	96
0.20	0	0	5	3	1	67	123	98

Table 5: Community detection errors of ISC on the eight empirical data sets for different δ .

Table 6: Error rates on the eight empirical datasets.

Methods	Karate	Dolphins	Football	Polbooks	UKfaculty	Polblogs	Simmons	Caltech
ISC	0/34	1/62	3/110	3/92	1/79	64/1222	121/1137	96/590
$ISC_{d_{max}}$	0/34	0/62	3/110	3/92	1/79	67/1222	123/1137	98/590
$\mathrm{ISC}_{d_{\min}}$	1/34	1/62	6/110	3/92	2/79	60/1222	305/1137	154/590
$\mathrm{ISC}_{\bar{d}}$	0/34	1/62	3/110	3/92	2/79	60/1222	200/1137	96/590

is sensitive to the choice of d, when d is set as $d = \frac{d_{\max} + d_{\min}}{2}$, ISC always has satisfactory performances according to all the numerical results in this paper. We argue that whether there exists an optimal d (instead of simply setting it as $\frac{d_{\max} + d_{\min}}{2}$ based on the numerical results) based on rigorous theoretical analysis, and we leave it as future work.

6. Discussion

In this paper, we introduced a community detection method named ISC based on the production of the leading eigenvalues and eigenvectors of the regularized graph Laplacian in networks. Under DCSBM, we established theoretical proprieties for the proposed method. From the simulation and empirical results we can find that the ISC method demonstrably outperforms classical spectral clustering methods (such as SCORE, RSC, OCCAM and SCORE+) and the newly-published community detection method SLIM, especially for weak signal networks. The most important step in our proposed method is that we always apply K + 1 eigenvectors for clustering. Thus we implemented this idea on other competitors, SCORE, RSC and SLIM, which are denoted as SCORE_{K+1} , RSC_{K+1} and SLIM_{K+1}



Figure 5: Community detection errors of ISC on the eight empirical data sets for different δ . The first eight panels: $\delta \in \{0.005, 0.01, 0.015..., 1\}$; the last eight panels: $\delta \in \{1, 2, ..., 200\}$. y-axis: number errors.

in numerical studies. Meanwhile, as demonstrated in the numerical results of eight real-world networks, SCORE_{K+1} and SLIM_{K+1} fail to detect some real-world networks, such as Dolphins, Football, UKfaculty and Polblogs while SLIM_{K+1} performs poor on the two weak signal networks Simmons and Caltech. As for OCCAM, it can not consider K + 1 eigenvectors for clustering. By Zhang et al. (2020), we know that OCCAM is designed originally for overlapping community detection problems, therefore it's meaningful to extend OCCAM for weak signal networks, and we leave it as future work. Meanwhile, since both SLIM_{K+1} and SLIM have unsatisfactory performances on Simmons and Caltech, we may conclude that it is challenging to extend the spectral clustering approaches based on the symmetric Laplacian inverse matrix (SLIM) Jing et al. (2021) to function satisfactory on weak signal networks, and we leave it as future work. Overall, our method ISC is appealing and indispensible in the area of community detection, especially when dealing with weak signal networks.

There are several open problems which drive us to some interesting and meaningful extensions of our ISC method. For example, it remains unclear about how to build the theoretic framework for the generation of weak signal networks, such as directed, weighted, dynamic and mixed membership networks, etc. Therefore, extending ISC to the above weak signal networks is significant. It also remains unclear that whether there exist optimal δ and d for ISC. Meanwhile, constructing newly variants of the adjacency matrix A may help us to design spectral method with even better performances than ISC for weak signal networks. Recall that we always assume that the number of communities K is known in advance for a given network and aim to detect nodes labels. However, in practice, the true number of clusters is usually unknown, and when we turn to weak signal networks, because the (K + 1)-th eigenvalue is close to the K-th one of A or its variants, traditional methods (Chen and Lei (2018); Hu et al. (2019); Le and Levina (2015)) aiming at estimating the number of clusters may fail to find the true number of clusters of weak signal networks. So it is crucial and meaningful for researchers to construct methods to estimate the number of clusters for both strong signal and weak signal networks. Based on the special form of the OCCAM algorithm, we know that it can not apply (K+1) eigenvectors for clustering to deal with weak signal networks, therefore it's meaningful to extend OCCAM to solve weak signal networks' community detection problem. Furthermore, more than the mixed membership community detection, the question that dealing with dynamic weak signal networks may possibly occur in the multiple networks community detection problem as in Arroyo and Levina (2020). Finally, since both $SLIM_{K+1}$ and SLIM fail to detect Simmons and Caltech, it is meaningful to design spectral clustering algorithms based on the symmetrized Laplacian inverse matrix Jing et al. (2021) for both strong signal and weak signal networks. We leave studies of these problems to our future work.

References

Adamic, L. A. and N. Glance (2005). The political blogosphere and the 2004 U.S. election: divided they blog. In *Proceedings of the 3rd international* workshop on Link discovery, pp. 36–43.

- Amini, A. A., A. Chen, P. J. Bickel, and E. Levina (2013). Pseudo-likelihood methods for community detection in large sparse networks. Annals of Statistics 41(4), 2097–2122.
- Arroyo, J. and E. Levina (2020). Simultaneous prediction and community detection for networks with application to neuroimaging. *arXiv preprint* arXiv:2002.01645.
- Bickel, P. J. and A. Chen (2009). A nonparametric view of network models and Newman–Girvan and other modularities. Proceedings of the National Academy of Sciences of the United States of America 106(50), 21068– 21073.
- Chen, K. and J. Lei (2018). Network cross-validation for determining the number of communities in network data. *Journal of the American Statistical Association* 113(521), 241–251.
- Chen, Y., X. Li, and J. Xu (2018). Convexified modularity maximization for degree-corrected stochastic block models. Annals of Statistics 46(4), 1573-1602.
- Daudin, J. J., F. Picard, and S. Robin (2008). A mixture model for random graphs. *Statistics and Computing* 18(2), 173–183.
- Duch, J. and A. Arenas (2005). Community detection in complex networks using extremal optimization. *Physical Review E* 72(2), 027104.
- Fortunato, S. (2010). Community detection in graphs. *Physics Reports* 486(3), 75–174.
- Girvan, M. and M. E. J. Newman (2002). Community structure in social and biological networks. *Proceedings of the National Academy of Sciences* of the United States of America 99(12), 7821–7826.
- Goldenberg, A., A. X. Zheng, S. E. Fienberg, and E. M. Airoldi (2010). A survey of statistical network models. *Foundations and Trends® in Machine Learning archive* 2(2), 129–233.
- Holland, P. W., K. B. Laskey, and S. Leinhardt (1983). Stochastic blockmodels: First steps. Social Networks 5(2), 109–137.

- Hu, J., H. Qin, T. Yan, and Y. Zhao (2019). Corrected Bayesian information criterion for stochastic block models. *Journal of the American Statistical* Association, 1–13.
- Jin, J. (2015). Fast community detection by SCORE. Annals of Statistics 43(1), 57–89.
- Jin, J., Z. T. Ke, and S. Luo (2018). SCORE+ for network community detection. arXiv preprint arXiv:1811.05927.
- Jing, B., T. Li, N. Ying, and X. Yu (2021). Community Detection in Sparse Networks Using the Symmetrized Laplacian Inverse Matrix (SLIM). Statistica Sinica.
- Karrer, B. and M. E. J. Newman (2011). Stochastic blockmodels and community structure in networks. *Physical Review E* 83(1), 16107.
- Kolaczyk, E. D. (2009). Statistical analysis of network data: methods and models.
- Le, C. M. and E. Levina (2015). Estimating the number of communities in networks by spectral methods. *arXiv preprint arXiv:1507.00827*.
- Lusseau, D. (2003). The emergent properties of a dolphin social network. Proceedings of The Royal Society B: Biological Sciences 270, 186–188.
- Lusseau, D. (2007). Evidence for social role in a dolphin social network. Evolutionary Ecology 21(3), 357–366.
- Lusseau, D., K. Schneider, O. J. Boisseau, P. Haase, E. Slooten, and S. M. Dawson (2003). The bottlenose dolphin community of Doubtful Sound features a large proportion of long-lasting associations. *Behavioral Ecology and Sociobiology* 54(4), 396–405.
- Ma, Z. and Z. Ma (2017). Exploration of large networks with covariates via fast and universal latent space model fitting. *arXiv preprint arXiv:1705.02372*.
- McPherson, M., L. Smith-Lovin, and J. M. Cook (2001). Birds of a feather: homophily in social networks. *Review of Sociology* 27(1), 415–444.

- Nepusz, T., A. Petróczi, L. Négyessy, and F. Bazsó (2008). Fuzzy communities and the concept of bridgeness in complex networks. *Physical Review E* 77(1), 16107–16107.
- Newman, M. (2006). Modularity and community structure in networks. Bulletin of the American Physical Society.
- Nowicki, K. and T. A. B. Snijders (2001). Estimation and prediction for stochastic blockstructures. Journal of the American Statistical Association 96 (455), 1077–1087.
- Papadopoulos, S., Y. Kompatsiaris, A. Vakali, and P. Spyridonos (2012). Community detection in social media. *Data Mining and Knowledge Dis*covery 24(3), 515–554.
- Qin, T. and K. Rohe (2013). Regularized spectral clustering under the degree-corrected stochastic blockmodel. In Advances in Neural Information Processing Systems 26, pp. 3120–3128.
- Rohe, K., S. Chatterjee, and B. Yu (2011). Spectral clustering and the highdimensional stochastic blockmodel. Annals of Statistics 39(4), 1878– 1915.
- Snijders, T. A. B. and K. Nowicki (1997). Estimation and prediction for stochastic blockmodels for graphs with latent block structur. *Journal of Classification* 14(1), 75–100.
- Traud, A. L., E. D. Kelsic, P. J. Mucha, and M. A. Porter (2011). Comparing community structure to characteristics in online collegiate social network. *Siam Review* 53(3), 526–543.
- Zachary, W. W. (1977). An information flow model for conflict and fission in small groups. Journal of Anthropological Research 33(4), 452–473.
- Zhang, Y., E. Levina, and J. Zhu (2020). Detecting overlapping communities in networks using spectral methods. SIAM Journal on Mathematics of Data Science 2(2), 265–283.