

A Rely-Guarantee Specification of Mixed-Criticality Scheduling

Cliff B Jones¹ and Alan Burns²

¹ School of Computing, Newcastle University, UK

² Department of Computer Science, University of York, UK

Abstract. The application considered is mixed-criticality scheduling. The core formal approaches used are Rely-Guarantee conditions and the Timeband framework; these are applied to give a layered description of job scheduling which includes resilience to jobs overrunning their expected execution time. A novel formal modelling idea is proposed to handle the relationship between actual time and its approximation in hardware clocks.

Dedication

One of the authors could have provided many anecdotes about his long association with Tom Maibaum. We thought however that a technical contribution would be more appropriate for someone who has made so many contributions to the subject. It is a pleasure to dedicate this paper to Tom — in the full expectation that he will not agree with all of the content! (We must also explain that the poetic extract is there for scientific reasons and has nothing to do with advancing ages.)

The Moving Finger writes; and, having writ,
Moves on: nor all thy Piety nor Wit
Shall lure it back to cancel half a Line,
Nor all thy Tears wash out a Word of it.

Rubaiyat of Omar Khayyam
(Translated by Edward FitzGerald)

1 Introduction

The objective of the research described in this paper is to develop a framework based on time bands and rely-guarantee conditions for formally specifying and reasoning about properties of mixed-criticality scheduling (MCS); the key correctness issues revolve around timing. The background ideas are summarised in Section 3 after the application area is outlined in Section 2.

The following paragraphs relate this objective to the wider topic of Cyber Physical Systems (CPS).

Correctness in safety-critical CPS can be considered from two perspectives: (i) (pre-run-time) verification, and (ii) survivability. Pre-run-time *verification* of a safety-critical system is the process of ensuring, prior to deployment, that the run-time behaviour of the system will be consistent with expectations. Verification assumptions are made regarding the kinds of circumstances that will be encountered by the system during run-time and guarantees are used to specify the required runtime behaviour of the system (provided that the assumptions hold).

In contrast, **survivability** addresses expectations of system behaviour in the event that the assumptions fail to hold in full (in which case a fault or error is said to have occurred during run-time). Survivability may further be considered to comprise two notions: robustness and resilience [BDBB18]. Informally, the robustness of a system is a measure of the severity and number of faults it can tolerate without compromising the quality of service it offers while resilience refers to the degree of fault for which it can provide degraded yet acceptable quality of service.

Section 2 outlines the application area while Section 3 briefly sketches published ideas on the timeband framework and rely-guarantee thinking together with the application of both of these formalisms to the specification of cyber physical systems. Section 4 tackles the thorny issue of the passage of time (see the quotation at the head of this paper): coming up with a satisfactory way to relate real physical time to values manipulated by programs held up writing this paper for some . . . time! These ideas are brought together in Section 5 to write layered descriptions of MCS covering both optimistic and resilient modes. The customary summary and statement of future work are given in Section 6.

2 Mixed-criticality scheduling

The implementation of any real-time system requires a run-time scheduler that will follow the rules that define the required behaviour of the scheduling approach that has been chosen to deliver the temporal properties of the application. A human scheduling specialist will choose the basic approach, for example a fixed priority scheme with priorities assigned via the deadline monotonic algorithm, or the Earliest Deadline First protocol. Appropriate scheduling analysis will then be applied to a specification of the application to determine whether all deadlines can be met at run-time by the chosen scheduling approach.

Typical characteristics of an application are the number of jobs or tasks involved, the worst-case execution times of these entries, their deadlines and possible constraints on their arrival patterns. The dynamic run-time scheduler will rely on the validity of these parameters and will guarantee to manage the order of execution in accordance with the rules of the chosen scheduling protocol.

An increasingly important trend in the design of real-time systems is the integration of components with different levels of criticality on a common hard-

ware platform. Criticality is a designation of the level of assurance against failure needed for a system component. A mixed-criticality system is one that has two or more distinct levels (for example safety critical, mission critical and low-critical). Perhaps up to five levels may be identified (see, for example, the IEC 61508, DO-178B and DO-178C, DO-254 and ISO 26262 standards). Typical names for the levels are ASILs (Automotive Safety and Integrity Levels), DALs (Design Assurance Levels or Development Assurance Levels) and SILs (Safety Integrity Levels).

A key aspect of MCS is that system parameters, such as the worst-case execution time (WCET) of a job, become dependent on the criticality level of the job. So the same code will have a higher WCET if it is defined to be safety-critical (as a higher level of assurance is required) than it would if it is just considered to be mission critical or indeed non-critical. Criticality also has a role when the system becomes overloaded; the jobs of the lower level of criticality may have to be abandoned to protect the integrity of the safety-critical (high integrity) jobs.

A mixed criticality (MC-) scheduler is one that manages a set of mixed criticality jobs (or tasks, but jobs only in this paper) so that all deadlines are met if all jobs execute for no more than a lower bound on their execution time. In addition, the MC-scheduler must ensure that all high criticality jobs meet their deadlines if any job executes for more than its lower bound (but less than a conservative upper bound defined for each job).

It must be emphasised that the internal details of MC-scheduler, and the theory used to define the associated schedulability analysis (for example the EDF-VD or AMC protocols) are not the emphasis in this paper — there is plenty of prior research on that [BD17]. Nor is there an explanation of how previously-proposed MC-scheduling algorithms can be shown to satisfy particular sets of rely-guarantee (R/G) specifications — that is (important) future work. This paper only seeks to provide a clear and intuitive specification of the formalism. The history of formal methods (such as Hoare Logic) prompts the belief that there is a good likelihood that methods can be developed for showing that specific MC-scheduling algorithms satisfy (or fail to so do) particular R/G specifications.

3 Background approaches


This section describes previously published ideas on which the developments in this paper are based.

3.1 Rely-guarantee reasoning for concurrency

Pre and post conditions are used to document the intended behaviour of sequential programs. Such specifications can be said to document the “Why” rather than the “How” of a component. Furthermore, developments of Tony Hoare’s “axiomatic approach” [Hoa69,Hoa71] provide ways of evolving verified implementations in a top-down style. (Even if the development is not actually undertaken in this way, such a structure provides understandable documentation.)

Key to layering such a description is a property that is often referred to as “compositionality”: the specification of a component describes all that need be achieved by its implementation; such specifications insulate a component from considerations about its environment and facilitate the verification of one design step before proceeding to further stages of development.

Finding compositional development methods for concurrent software proved challenging with many initial methods (e.g. [AM71,Ash75,Owi75,OG76]) needing to reason jointly about the combination of one thread with its sibling threads and/or environment. This negates the ability to achieve top-down design. The Rely-Guarantee approach [Jon81,Jon83a,Jon83b] offers compositional specifications for a class of shared-variable concurrent programs. Just as pre conditions record assumptions about the context in which a component can be deployed, a rely condition indicates what interference a component must tolerate. Thus pre and rely conditions are information to the developer and warnings to anyone who wishes to deploy the specified component. A similar comparison can be made between the two conditions that record properties that the developed code must satisfy: post conditions describe the relation required of starting and finishing states³ whereas guarantee conditions indicate an upper bound on the impact that steps of the component can have on its environment. A picture of these components of a specification is given in Figure 1.



pre/rely are assumptions the developer can make

guar/post are commitments that the code must achieve

Fig. 1. Picturing the parts of a Rely-Guarantee specification

In [Hoa69], Hoare offered proof rules that justify development to the main sequential programming constructs. It is not surprising that the proof rules which justify steps of development employing parallelism are more complicated: they essentially need to show the compatibility of the rely and guarantee conditions.⁴ The current paper does not go into these details because description rather than proof is the objective here.

One observation that does carry over from development methods for sequential programs to many applications of the Rely-Guarantee approach is the importance of data abstraction and reification [Jon07]. Although predicates over

³ Pre and post conditions are as in [Hoa69] except that in VDM [Jon80] post conditions are relations over initial and final states.

⁴ A significant reworking [HJC14,JHC15,HJ18] presents the original rely-guarantee ideas in a more algebraic style.

states provide an element of procedural abstraction, specifications of significant systems can only be made brief and perspicuous by using abstract data types that match the problem. Subsequent development steps must show that representations of the abstractions preserve the properties of the specification. Development and justification of more concrete representations is variously referred to as “refinement” or “reification”.

3.2 Time bands

The motivation for the timeband framework comes from a number of observations about complex time-sensitive systems. Of relevance to this paper are the following:

- systems can be best understood by distinguishing different granularities (of time), i.e. there are different abstract views of the dynamics of the system
- it is useful to view certain actions (events) as atomic and “instantaneous” in one time band, while allowing them to have internal state and behaviour that takes time at a more detailed level of description
- the durations of certain actions are important, but the measuring of time must not be made artificially precise and must allow for tolerance (non-determinacy) in the temporal domain.

Key references include [BHJ20,BH10,WWB12,WOBW10,BBT07,BB06].

The central notion in the framework is that of a time band that is defined by its *granularity*, G , (e.g. 1 millisecond) and its *precision*, ρ , (e.g. 5 microseconds). Granularity defines the unit of time of the band; precision bounds the maximum duration of an event that is deemed to be instantaneous in its band.

Whilst it is the case that system descriptions can be given on a single time axis, inevitably, this has to be a fine granularity and it becomes difficult to “see the wood for the trees.” It is much clearer if the behaviour of a system is given in terms of a finite set of ordered *bands*. System activities are described in some band B if they engage in significant events at the time scale represented by B , i.e. they have dynamics that give rise to changes that are observable or meaningful in the granularity of band B .

A complete system specification must address all dynamic behaviours. At the lowest level, circuits (e.g. gates) have propagation delays measured in nanoseconds or even picoseconds; at intermediate levels, tasks/threads have rates and deadlines that are usually expressed in tens of milliseconds; at yet-higher levels, missions can change every hour; and maintenance may need to be undertaken every month.

Understanding the behaviour of circuits allows the worst-case execution time of tasks to be predicted. At a higher band this allows deadlines to be checked and the schedulability of whole missions to be verified.

In this paper, behaviour of the application jobs and the scheduler is placed in a band that reflects the deadlines of the jobs; this might be a band with a granularity of one millisecond, or a finer granularity if that is required. The

precision in this band will be sufficiently short so that the duration of certain actions, for example a context switch, can be ignored.

Precision is employed, in Section 4.1, to constrain the difference between external ‘real’ time and any interval interpretation of time as delivered by a hardware clock.

3.3 Specifying resilient CPS

As indicated in Section 3.1, the Rely-Guarantee approach was originally conceived for developments where a specified system was to be decomposed into concurrent processes. The general idea has however been shown to be applicable to contexts where a component is being specified which will execute in an environment that evolves in parallel with the specified component. Examples include [HJJ03,JHJ07] but these suffered from the fact that time was treated on a single (i.e. the finest) band.

In [BHJ20], the timeband approach was used to make the rely and guarantee conditions more intelligible. This indicated that combining the timeband and rely-guarantee approaches can be used to specify CPS. A particular issue with CPS is that they need to be resilient in the sense that they are likely to have layers of required behaviour:

- optimistic (or optimal) behaviour is required when everything is performing in accord with the strongest rely conditions — the control system is required to meet its strongest guarantee condition;
- when some rely conditions are not satisfied, something in the environment is not behaving in an optimal way (this can be caused by a timing problem) — a weaker rely condition can describe a less desirable environment assumption under which the control system can only achieve a weaker guarantee condition;
- such layering of rely and guarantee conditions can be repeated over as many levels as required.

Such nested conditions (combined with time bands) are illustrated in [BHJ20, §4]. Another idea that appears to be useful in specifying CPS is the setting of “may/must” levels (again often linked to time): [BHJ20, §4.3] contains an example where a short period of aberrant behaviour can be flagged but the control system is required to report a longer period of misbehaviour. This pattern of specification appears to be useful quite frequently.

4 Handling time

Specifying the sort of scheduling problem described in Section 2 presents additional challenges not faced in, for example, [BHJ20]:

- internal machine clocks must be linked to the passage of actual time
- state variables are needed that record the amount of time used by a job.

What follows is a novel approach to these two problems linking the passage of time with the values recorded in computer clocks. The simple scheduling task considered in the body of the paper concerns a finite number of “one shot” jobs; extensions to address tasks are mentioned in Section 6.2.

4.1 *ClockValue* vs. *Time*

The first step is to distinguish an abstract notion of *Time* from what clocks record in a computer (a clock will contain a *ClockValue*). Consider a collection of *States* indexed by the abstract notion of *Time*:

$$\Sigma = \textit{Time} \rightarrow \textit{State}$$

This is a function; *Time* should be “dense” like the real numbers (so Σ cannot be modelled as a list) — but fortunately it transpires that little need be said about *Time* because specifications of operations (e.g. the scheduler and the jobs that it controls) are written with respect to the t component of *State*:

$$\begin{aligned} \textit{State} :: t & : \textit{ClockValue} \\ & \dots \end{aligned}$$

For a given $\sigma : \Sigma$ at time α (because the identifier t is used for a component of *State* above, $\alpha \in \textit{Time}$ is used here), its *ClockValue* ($\sigma(\alpha).t$) can differ from α ; that is an issue for a fine time band and time bands need to be chosen such that the allowable difference is within the precision of the coarser band so that it can essentially be assumed that the *ClockValue* in the machine is always sufficiently close to *Time*.⁵

Assume that the precision of the band is ρ , equality $=_\rho$ is with respect to that precision. Then the relationship between t and α is defined by the following predicate:

$$P_t(\sigma) \stackrel{\text{def}}{=} \forall \alpha \in \textit{Time} \cdot \sigma(\alpha).t =_\rho \alpha$$

4.2 Recording execution time

A *State* contains an indexed collection of *Jobs* in its *curr* field (and *exec* which is a subset⁶ of the domain of that mapping indicating the jobs that are scheduled for execution).

$$\begin{aligned} \textit{State} :: t & : \textit{ClockValue} \\ & \textit{curr} : I \xrightarrow{m} \textit{Job} \\ & \textit{exec} : I\text{-set} \end{aligned}$$

Among other fields (see below) a *Job* has a record of how long it has been executing:

$$\begin{aligned} \textit{Job} :: e & : \textit{Duration} \\ & \dots \end{aligned}$$

⁵ At the finer time band, issues such as clock drift could also be formalised. In a distributed system, there would be a local *State* for each processor and their clocks could also differ within the appropriate precision.

⁶ The *exec* field is a set to cover multi-processors.

Neither the scheduler nor any job can change t or e which are instead linked to the autonomous (i.e. not under the control of software) progress of time: the key properties are that, if $i \in \text{exec}$ over a period of time from α_1 to α_2 , then the e field for the indexed *State* must advance as much as the difference in the *Time*⁷ i.e. $e_2 - e_1$ must be equal, within the precision of the time band, to $\alpha_2 - \alpha_1$; furthermore, when $i \notin \text{exec}$ the e field of that *Job* remains unchanged.

Thus the link between *Time* and e is defined by a predicate over Σ :

$$\begin{aligned}
 P_e(\sigma) &\stackrel{\text{def}}{=} \\
 &\forall \alpha_1, \alpha_2 \in \text{Time}, i \in \text{Index} \cdot \\
 &((\forall \alpha \mid \alpha_1 \leq \alpha \leq \alpha_2 \cdot i \in \sigma(\alpha).\text{exec}) \Rightarrow \\
 &\quad \sigma(\alpha_2).\text{curr}(i).e - \sigma(\alpha_1).\text{curr}(i).e =_{\rho} \alpha_2 - \alpha_1) \wedge \\
 &((\forall \alpha \mid \alpha_1 \leq \alpha \leq \alpha_2 \cdot i \notin \sigma(\alpha).\text{exec}) \Rightarrow \\
 &\quad \sigma(\alpha_2).\text{curr}(i).e = \sigma(\alpha_1).\text{curr}(i).e)
 \end{aligned}$$

Although *Time* is dense and progresses outside the influence of the software (*Scheduler* or *Jobs*), it is precisely that software that brings about discrete changes to *State*. Essentially, real time is about the Σ function whereas programs actually bring about discrete changes in *States* (except, of course, neither *Scheduler* nor *Jobs* can write to t or e whose values are constrained by P_t/P_e above).

Although the focus in Section 5 is on specifications for the scheduler and the jobs to which it is allocating time, the progress of *Time* is really a third concurrent process. What could be thought of as a guarantee condition of this enigmatic process (the conjunction of P_e and P_t) can be used as an assumption in any reasoning about the more tangible components (*Scheduler* and *Jobs*).

5 Job-Based Scheduling

As outlined in Section 2, scheduling work can be divided into two parts. A human scheduler considers the likely arrival pattern –and estimates of the *worst case execution time*– of jobs and chooses a scheduling algorithm for the run-time scheduling software (which comprises the second part). The aim of the software component is to ensure that jobs complete execution by their respective deadlines. The rely conditions of the combined scheduling activities would detail the inputs to the static part of scheduling. In this section, the focus is on specifying the run-time scheduling software using rely and guarantee conditions.

In safety-critical situations, resilience is crucial and minor deviation from the estimated run times must not be allowed to cause highly-critical (hi-crit) jobs to miss their deadlines. The categorisation of jobs as hi/lo-crit is part of the human, off-line, process.⁸ Here, nested rely and guarantee conditions are used to specify an optimistic mode in which all jobs can meet their deadlines and

⁷ The difference between two values of type *Time* is a *Duration* as is the difference between two values of type *Duration*.

⁸ In reality, there could be many levels of criticality but the approach can be illustrated with just two.

a fault-tolerant mode in which only hi-crit jobs are guaranteed to meet their deadlines.

In real scheduling there is likely to be a *task level* above jobs but this is not addressed in the current paper.

5.1 Starting and ending *Jobs*

The run-time Scheduler manages the execution of *Jobs* (indexed by $i \in I$ — the set I is an arbitrary index set). As indicated in Section 4.2, *curr* contains information about those jobs that have started and not yet finished.

The information stored for each job is as follows:

```

Job :: e : Duration
       d : Time
       C : Duration
       X : Duration

```

As mentioned in Section 4.1, the time (e) that a job has been executing cannot be changed directly by the scheduler and is updated in accordance with P_e . The deadline by which a job should complete (d) is set when a job starts (see *START* below) — it is shown to be of type *Time* because deadlines relate to the external world but P_t ensures that software can use t : *ClockValue* as an acceptable surrogate. The C field contains the expected maximum execution time of the job but the X field distinguishes between lo-crit (where $X = 0$) and hi-crit jobs where the latter have a non-zero *Duration* that can be allocated if necessary.

The arrival of jobs is not controlled by the scheduler; the *START* operation is specified as follows:

```

START (D: Duration, C: Duration, X: Duration) i: I
ext rd t      : ClockValue
wr curr : I  $\xrightarrow{m}$  Job
post  $i \notin \text{dom } curr \wedge$ 
       $curr' = curr \cup \{i \mapsto mk\text{-Job}(0, D + t, C, X)\}$ 

```

The execution time (e) at the start of a job is set to zero; the D argument is the relative deadline — adding the clock time gives the absolute deadline (d); and C is an estimate of WCET.

Notice that starting a Job does not make it execute — that is the role of the *Scheduler*. Thus, jobs start and are added to *curr*; the scheduler moves their index to *exec*.

Ending a job just removes it from *curr*.

```

END (i: I)
ext wr curr : I  $\xrightarrow{m}$  Job
post  $curr' = \{i\} \triangleleft curr$ 

```

5.2 Dynamic scheduler

The *exec* field of a *State* records the indexes of *Jobs* that are actively executing (thus *exec* contains a subset of the domain of *curr*); the scheduler moves job indexes into and out of *exec*. In fact, that is all it can do⁹ and that makes its way of achieving its specification rather indirect.

These specifications are anyway expressed at two levels: an optimistic mode in which all jobs can be scheduled successfully and a resilient mode in which lo-crit jobs can be abandoned if necessary to meet the deadlines of hi-crit jobs.

Optimistic mode The overall scheduling objective is to make sure that jobs can finish by their respective deadlines; if all jobs were of equal criticality, this could be expressed by requiring that the following optimistic invariant is maintained:

$$\begin{aligned} \text{inv-State}_O : \text{State} &\rightarrow \mathbb{B} \\ \text{inv-State}_O(\text{mk-State}(t, \text{curr},)) &\triangleq \\ \forall \text{mk-Job}(e, d, C,) \in \mathbf{rng} \text{curr} \cdot C - e &\leq d - t \end{aligned}$$

This states that all jobs currently in the system must have room to finish by their deadline time (d). A corollary of this is that each job would terminate no later than its deadline. (It is shown below that a more conservative invariant must be preserved to achieve resilience.)

Preserving inv-State_O can be viewed as the key obligation of the scheduler but the only way in which the *SCHEDULER* can achieve this is by allocating time to *Jobs* in *curr* which entails moving their index into *exec* (P_e then governs the increase in their e field).

Anyone familiar with the literature on the Rely-Guarantee approach might wonder if such invariants should be couched as guarantee conditions of the form:

$$\text{inv-State}(st) \Rightarrow \text{inv-State}(st')$$

The reason for preferring the invariant is that *Time* is advancing even if the scheduler is inactive. A guarantee condition puts constraints on what happens over steps of the relevant process; maintaining the invariant imposes a stronger requirement that the scheduler does something often enough.

To realise the maintenance of this invariant, the rely condition of the scheduler must cover:

- reliance on all *Jobs* respecting their C
- for each job, the values of its C and d are unchanging (see second conjunct of the rely condition and remember that jobs can arrive in –and leave from– *curr*)
- furthermore the value of e for each job is increasing (in line with t/α).

⁹ In some resilient modes, the scheduler can re-allocate “budgets” and/or terminate jobs.

```

SCHEDULERO
ext rd t : ClockValue
rd curr :  $I \xrightarrow{m} Job$ 
wr exec : I-set
rely  $(\forall mk\text{-}Job(e', , C, ) \in \mathbf{rng} \textit{curr}' \cdot e' \leq C) \wedge$ 
 $\forall i \in (\mathbf{dom} \textit{curr} \cap \mathbf{dom} \textit{curr}')$ 
 $\textit{curr}'(i).d = \textit{curr}(i).d \wedge$ 
 $\textit{curr}'(i).C = \textit{curr}(i).C \wedge$ 
 $\textit{curr}'(i).e \geq \textit{curr}(i).e$ 

```

Correspondingly, the specification of each job is defined as follows:

```

JOB(i)
ext rd t : ClockValue
rd e : Duration
rd d : ClockValue
rd C : Duration
rely  $t' \geq t \wedge$ 
 $C' = C \wedge d' = d \wedge e' \geq e \wedge$ 
 $C - e' \leq d - t'$ 
guar  $e' \leq C$ 

```

Although the guarantee conditions of jobs imply the rely condition of the scheduler, it cannot be implemented unless the developer can also assume that P_e is satisfied. Notice that the value C has two roles: each job relies on its environment behaving according to whatever model or measuring process was used to derive C , but the job also has a contract with the scheduler not to execute for more than C . The scheduler is assumed to have used some form of analysis to verify (offline usually) that if all jobs respect their guarantee conditions then it will indeed provide the necessary capacity to each job. Hence the job can rely upon receiving C before its deadline.

It should again be noted that this specification of the Scheduler's behaviour does not include the actual details of the scheduling algorithm or dispatching policy — it is just a specification of what the Scheduler must achieve (its obligations). For a specific set of jobs it may not be possible to derive a valid scheduler that can meet this specification.

Resilient mode In resilient mode, the scheduler only guarantees that hi-crit jobs get serviced and lo-crit jobs ($X = 0$) might be terminated or fail to complete by their deadlines.¹⁰ The specification does not require such terminations, it simply specifies a lower bound on the scheduler.

To see that $inv\text{-}State_O$ is not strong enough as an invariant to handle mixed criticality, consider the following example which shows that there is an issue

¹⁰ A third possibility is that some lo-crit jobs do complete by their deadlines. It is just that the scheduler is not required to achieve this.

when resilience to overrunning hi-crit jobs is included. Suppose there was a hi-crit job (a) with: $e_a = 10$, $d_a = 56$, $C_a = 15$ and $X_a = 3$. There might also be some other lo-crit jobs so $curr$ would contain:

$$\left\{ \begin{array}{l} a \mapsto mk\text{-}Job(10, 56, 15, 3), \\ b \mapsto \dots \end{array} \right\}$$

If this situation existed at $t = 52$, there would be insufficient time to complete the hi-crit job (a) by its deadline. (Presumably some other job with an earlier deadline would have been using the resource.) A scheduler could abandon execution of any lo-crit jobs such as b and employ the extra allowance stored for a — in the example there is an extra allowance of 3 units of time to be allocated to a but it is too late to meet the deadline (56) so this does not help. Therefore the situation must not be allowed to arise at $t = 52$ — it is clear that the scheduler has not kept enough “fat” to be able to complete a by its deadline. The conservative invariant below requires that all of the extra allocations can be accommodated.

As indicated at the beginning of Section 5.2, the optimistic invariant preserves enough resource to be able to complete all jobs whether hi or lo-crit. In contrast, $inv\text{-}State_R$ enshrines a cautious approach of making sure that hi-crit jobs can meet their deadlines even if they all use their extra time allocation:

$$\begin{aligned} inv\text{-}State_R : State &\rightarrow \mathbb{B} \\ inv\text{-}State_R(mk\text{-}State(t, curr,)) &\triangleq \\ \forall mk\text{-}Job(e, d, C, X) \in \mathbf{rng} \, curr \cdot X > 0 &\Rightarrow C + X - e \leq d - t \end{aligned}$$

In resilient mode ($SCHEDULER_R$), the weaker rely condition concerns only hi-crit jobs and accepts that their execution might need the extra (X) execution time. So the invariant only requires that the scheduler concerns itself with hi-crit jobs.¹¹

Notice that this represents what the scheduler must do — it is at liberty to attempt to schedule more jobs than required including some that are marked ($X = 0$) as lo-crit.

The specifications are:

$$\begin{aligned} &SCHEDULER_R \\ \mathbf{ext} \, \mathbf{rd} \, t &: ClockValue \\ \mathbf{rd} \, curr &: I \xrightarrow{m} Job \\ \mathbf{wr} \, exec &: I\text{-set} \\ \mathbf{rely} \, (\forall mk\text{-}Job(e', \cdot, C, X) \in \mathbf{rng} \, curr' \cdot X > 0 &\Rightarrow e' \leq C + X) \wedge \\ &\forall i \in (\mathbf{dom} \, curr \cap \mathbf{dom} \, curr') \cdot \\ &\quad curr'(i).d = curr(i).d \wedge \\ &\quad curr'(i).C = curr(i).C \wedge \\ &\quad curr'(i).e \geq curr(i).e \end{aligned}$$

¹¹ Many schedulers live more dangerously and hold only a global reserve (“fat”) or work with $3/4$ of X — this would require a different specification.

In resilient mode each hi-crit job promises to stay within its extended execution time; lo-crit jobs make no promises.

```

JOB(i)
  ext rd t : ClockValue
  rd e : Duration
  rd d : ClockValue
  rd C : Duration
  rd X : Duration
  rely  $t' \geq t \wedge$ 
     $C' = C \wedge d' = d \wedge e' \geq e \wedge X' = X \wedge$ 
     $C + X - e' \leq d - t'$ 
  guar  $X > 0 \Rightarrow e' \leq C + X$ 

```

It is important to realise that the design of the scheduler must create code that satisfies both $SCHEDULER_O$ and $SCHEDULER_R$: all jobs will meet their deadlines providing none are greedy and hi-crit jobs will get the extra resources to meet their deadlines — if necessary at the expense of lo-crit jobs being abandoned.

6 Conclusions

The formal methods basis for this paper is the timebands framework and the rely-guarantee approach. These ideas have previously been shown to be applicable to the specification of Cyber Physical Systems (CPS). Time bands have been used to avoid the confusion that arises when coarse-grained concepts are discussed at a fine granularity. Rely-guarantee conditions both help separate documentation of components and –when nested– help distinguish resilient modes of operation from the ideal behaviour of a system.

The targeted application of this paper is Mixed Criticality Scheduling; tackling MCS has required an important extension to the previously used notations.

6.1 Summary

The objective in writing this paper was to take existing ideas on the timeband framework and rely-guarantee approaches and to extend them so that they can be useful in specifying MCS. To achieve this, a novel approach to viewing time as a separate index has been proposed: assumptions about the relationship between actual *Time* and what happens inside a computer are recorded essentially as guarantee conditions on the unstoppable progress of “the moving finger”.

With MCS, the trigger that indicates that ideal behaviour cannot be achieved is related to time: if hi-crit jobs need more resource than their optimistic estimates, a scheduler has to take action such as abandoning lo-crit jobs. Layered rely-guarantee conditions cope well with describing such nested modes.

The important task of relating the passage of *Time* in the real world with what is going on inside the computer has been handled by having a model in

which there is a function from *Time* to machine states; this function cannot be affected by programs but programs do bring about discrete changes in the machine states. Crucially, the relationship between the *Time* index and values in the machine states is defined by a predicate that can be thought of as a guarantee condition. Appropriate definition of the precision of the time band concerns issues such as clock accuracy and drift.

6.2 Further work

Of course, much work remains to be done. This introductory paper is restricted to scheduling jobs. Sketches for describing the “task level” using the same formal ideas exist and show that they appear to suffice. This material will be the subject of a companion paper that will also say more on the transition between modes.

There is extensive published work on MC scheduling and implementation, but little on their formal specification. The Rely-Guarantee (R/G) approach has proved to be a useful formalism for specifying non-real-time safety-critical systems and the main contribution here is to extend R/G to (i) time and (ii) multiple criticalities. Such a formalism will prove to be essential since the notion of mixed criticality has subtle semantics: concepts such as correctness, resilience and robustness are rarely straightforward or intuitive for such systems.

It is important to remember that the material in the body of this paper concerns only specifications. These specifications set a necessary condition on implementations but they are at liberty to achieve more. A typical scheduler will ensure that jobs with the earliest deadline are executed first (EDF); more useful schedulers might abandon lo-crit jobs in stages if so doing provides enough resource for the hi-crit jobs. The usefulness of the specifications in the body of this paper has to be judged by seeing how easy it is to show that such implementations satisfy the specifications proposed here.

An ambitious extension that has not yet been worked on would be to specify probability distributions on assumptions about timing and on the commitment to timely job completion.

Acknowledgements

This paper relates to one aspect of research that is on going with Sanjoy Baruah and Iain Bate. The authors also acknowledge useful suggestions made by Ian Hayes on an earlier draft of this paper.

This research has been supported in part by EPSRC (UK) grants, STRATA and MCCps and Leverhulme grant RPG-2019-020.

References

- AM71. E. A. Ashcroft and Z. Manna. Formalization of properties of parallel programs. In B. Meltzer and D. Michie, editors, *Machine Intelligence*, 6, pages 17–41. Edinburgh University Press, 1971.

- Ash75. Edward A Ashcroft. Proving assertions about parallel programs. *Journal of Computer and System Sciences*, 10(1):110–135, 1975.
- BB06. A. Burns and G.D. Baxter. Time bands in systems structure. In *Structure for Dependability*, pages 74–90. Springer, 2006.
- BBT07. G. Baxter, A. Burns, and K. Tan. Evaluating timebands as a tool for structuring the design of socio-technical systems. In P. Bust, editor, *Contemporary Ergonomics 2007*, pages 55–60. Taylor & Francis, 2007.
- BD17. A. Burns and R.I. Davis. A survey of research into mixed criticality systems. *ACM Computer Surveys*, 50(6):1–37, 2017.
- BDBB18. A. Burns, R. Davis, S. K. Baruah, and I. Bate. Robust mixed-criticality systems. *IEEE Transactions on Computers*, 67(10):1478–1491, 2018.
- BH10. Alan Burns and Ian J. Hayes. A timeband framework for modelling real-time systems. *Real-Time Systems*, 45(1–2):106–142, 6 2010.
- BHJ20. Alan Burns, Ian J. Hayes, and Cliff B. Jones. Deriving specifications of control programs for cyber physical systems. *The Computer Journal*, 63(5):774–790, 2020.
- HJ18. I. J. Hayes and C. B. Jones. A guide to rely/guarantee thinking. In Jonathan Bowen, Zhiming Liu, and Zili Zhan, editors, *Engineering Trustworthy Software Systems – Third International School, SETSS 2017*, volume 11174 of *Lecture Notes in Computer Science*, pages 1–38. Springer-Verlag, 2018.
- HJC14. Ian J. Hayes, Cliff B. Jones, and Robert J. Colvin. Laws and semantics for rely-guarantee refinement. Technical Report CS-TR-1425, Newcastle University, 7 2014.
- HJJ03. Ian Hayes, Michael Jackson, and Cliff Jones. Determining the specification of a control system from that of its environment. In Keijiro Araki, Stefani Gnesi, and Dino Mandrioli, editors, *FME 2003: Formal Methods*, volume 2805 of *Lecture Notes in Computer Science*, pages 154–169. Springer Verlag, 2003.
- Hoae69. C. A. R. Hoare. An axiomatic basis for computer programming. *Communications of the ACM*, 12(10):576–580, 1969.
- Hoae71. C. A. R. Hoare. Proof of a program: FIND. *Communications of the ACM*, 14(1):39–45, January 1971.
- JHC15. Cliff B. Jones, Ian J. Hayes, and Robert J. Colvin. Balancing expressiveness in formal approaches to concurrency. *Formal Aspects of Computing*, 27(3):465–497, 2015.
- JHJ07. Cliff B. Jones, Ian J. Hayes, and Michael A. Jackson. Deriving specifications for systems that are connected to the physical world. In Cliff B. Jones, Zhiming Liu, and Jim Woodcock, editors, *Formal Methods and Hybrid Real-Time Systems: Essays in Honour of Dines Bjørner and Zhou Chaochen on the Occasion of Their 70th Birthdays*, volume 4700 of *Lecture Notes in Computer Science*, pages 364–390. Springer Verlag, 2007.
- Jon80. C. B. Jones. *Software Development: A Rigorous Approach*. Prentice Hall International, Englewood Cliffs, N.J., USA, 1980.
- Jon81. C. B. Jones. *Development Methods for Computer Programs including a Notion of Interference*. PhD thesis, Oxford University, 6 1981. Printed as: Programming Research Group, Technical Monograph 25.
- Jon83a. C. B. Jones. Specification and design of (parallel) programs. In *Proceedings of IFIP’83*, pages 321–332. North-Holland, 1983.

- Jon83b. C. B. Jones. Tentative steps toward a development method for interfering programs. *Transactions on Programming Languages and System*, 5(4):596–619, 1983.
- Jon07. C. B. Jones. Splitting atoms safely. *Theoretical Computer Science*, 375(1–3):109–119, 2007.
- OG76. S. S. Owicki and D. Gries. An axiomatic proof technique for parallel programs I. *Acta Informatica*, 6:319–340, 1976.
- Owi75. S. S. Owicki. *Axiomatic Proof Techniques for Parallel Programs*. PhD thesis, Department of Computer Science, Cornell University, 1975. Published as technical report 75-251.
- WOBW10. J. Woodcock, M. Oliveira, A. Burns, and K. Wei. Modelling and implementing complex systems with timebands. In *Proc. IEEE Conference on Secure System Integration and Reliability Improvement (SSIRI)*, pages 1–13, 2010.
- WWB12. K. Wei, J. Woodcock, and A. Burns. Modelling temporal behaviour in complex systems with timebands. In M. Hinchey and L. Coyle, editors, *Conquering Complexity*, pages 277–307. Springer, 2012.