

GottBERT: a pure German Language Model

Raphael Scheible¹, Fabian Thomczyk¹, Patric Tippmann¹, Victor Jaravine¹ and Martin Boeker¹

{raphael.scheible,thomczyk,tippmann,victor.zharavin,martin.boeker}
@imbi.uni-freiburg.de

¹ Institute of Medical Biometry and Statistics, Medical Center, Faculty of Medicine, University of Freiburg

Abstract

Lately, pre-trained language models advanced the field of natural language processing (NLP). The introduction of Bidirectional Encoders for Transformers (BERT) and its optimized version RoBERTa have had significant impact and increased the relevance of pre-trained models. First, research in this field mainly started on English data followed by models trained with multilingual text corpora. However, current research shows that multilingual models are inferior to monolingual models. Currently, no German single language RoBERTa model is yet published, which we introduce in this work (GottBERT). The German portion of the OSCAR data set was used as text corpus. In an evaluation we compare its performance on the two Named Entity Recognition (NER) tasks Conll 2003 and GermEval 2014 as well as on the text classification tasks GermEval 2018 (fine and coarse) and GNAD with existing German single language BERT models and two multilingual ones. GottBERT was pre-trained related to the original RoBERTa model using fairseq. All downstream tasks were trained using hyperparameter presets taken from the benchmark of German BERT. The experiments were setup utilizing FARM. Performance was measured by the F_1 score. GottBERT was successfully pre-trained on a 256 core TPU pod using the RoBERTa BASE architecture. Even without extensive hyperparameter optimization, in all NER and one text classification task, GottBERT already outperformed all other tested German and multilingual models. In order to support the German NLP field, we publish GottBERT under the AGPLv3 license.

1 Introduction

The computation of contextual pre-trained word representation is the current trend of neural networks in natural language processing (NLP).

This trend has a long history, starting with non-contextualized word representations of which the most prominent are word2vec (Goldberg and Levy, 2014), GloVe (Pennington et al., 2014) and fastText (Joulin et al., 2016, 2017; Bojanowski et al., 2017; Mikolov et al., 2018), evolving to deep contextualized models such as ELMo (Alsentzer et al., 2019) and flair (Akbik et al., 2019). Most recently, the field of NLP experienced remarkable progress, by the use of Transformer (Vaswani et al., 2017) based approaches. Especially Bidirectional Encoder Representations from Transformers (BERT) (Devlin et al., 2019) impacted the field which subsequently was robustly optimized to RoBERTa (Liu et al., 2019). These Transformer based approaches use large scale pre-trained language models. For application, such models are fine tuned by a supervised training on the specific downstream task leading to performance improvements in many tasks. On the other hand, the computation of the language model is performed unsupervised. Large text blobs are required for training and strong hardware such as hundreds of GPUs (Martin et al., 2020) or TPUs (You et al., 2020). Initially, most of the research took place in English followed by multilingual approaches (Conneau et al., 2019). Although, multilingual approaches were trained on large texts of many languages, they were outperformed by single language models (de Vries et al., 2019; Martin et al., 2020; Le et al., 2020; Delobelle et al., 2020). Single language models trained with the Open Super-large Crawled ALMANaCH coRpus (OSCAR) (Ortiz Suárez et al., 2020) showed good performance due to the size and variance of the OSCAR (Martin et al., 2020; Delobelle et al., 2020). Following this ongoing trend, we pre-train the first German RoBERTa single language model with the German portion of the OSCAR - the German OSCAR text trained BERT (GottBERT). In an evaluation we compare its performance on the two named

entity recognition tasks Conll 2003 and GermEval 2014, as well as on the two text classification tasks GermEval 2018 and GNAD with existing German single language BERT models and two multilingual ones.

2 Related Work

Most recently Transformer based models widely impacted the field of NLP. From neural translation (Ott et al., 2018; Ng et al., 2019) to generative language models as GPT2 (Radford et al., 2019), remarkable performance gains were achieved. With BERT, an approach facilitating pre-trained transformer based models was introduced. Fine-tuned on downstream tasks, BERT based approaches improved the performance of several NLP tasks (Devlin et al., 2019; Liu et al., 2019). BERT models though, were first released as single language models in English based on 16GB of raw text and as the multilingual model mBERT based on Wikipedia dumps in about 100 languages (Devlin, 2018). These models were followed by single language models for several languages: Bertje (de Vries et al., 2019) for Dutch, FinBERT (Virtanen et al., 2019) for Finish, German BERT¹ and a German BERT from the MDZ Digital Library team at the Bavarian State Library to which we refer as dbmz BERT in this paper². German BERT was trained using 12GB of raw text data basing on German Wikipedia (6GB), the OpenLegalData dump (2.4GB) and news articles (3.6GB). dbmz BERT used as source data a German Wikipedia dump, EU Bookshop corpus, Open Subtitles, CommonCrawl, ParaCrawl and News Crawl which sums up to a dataset of 16GB. With the release of RoBERTa a new standard for raw text size was set as it was trained on 160GB of raw English text. Further, RoBERTa enhances the original BERT approach by removing segment embeddings, next sentence prediction and improved hyperparameters. Additionally, instead of using wordpiece (Schuster and Nakajima, 2012) tokenization, RoBERTa utilizes GPT2’s byte pair encoding (BPE) (Radford et al., 2019) with the benefit that language-specific tokenizers are not required. Other than mBERT, the multilingual XLM-RoBERTa (Conneau et al., 2019) was trained on 2.5TB of filtered CommonCrawl data. CamemBERT is a French RoBERTa

model that was trained on the OSCAR and uses sentencepiece (Kudo and Richardson, 2018) BPE. Further, they pre-trained a model with 4GB of the French OSCAR portion and another model with 4GB of the French Wikipedia. The comparison of these models using downstream tasks shows that high text variance leads to better results. UmBERTo³ is an Italian RoBERTa model, similarly designed as CamemBERT. RobBERT, the Dutch single language RoBERTa, was trained on 39GB of the Dutch portion of the OSCAR and outperformed Bertje. A more recent version of RobBERT showed the performance gains of language specific BPE compared to the English based GPT2 BPE in downstream tasks. Most recently FlauBERT (Le et al., 2020) for French was released trained on 71GB data. They cleaned a 270GB corpus of mixed sources by filtering out meaningless content and Unicode-normalization. Data was pre-tokenized by Moses (Koehn et al., 2007) and encoded by fastBPE⁴ which is an implementation of Sennrich et al. (2016). Following the approach of utilizing the OSCAR, we computed the German OSCAR text trained BERT (GottBERT). However, the drawback of BERT approaches is the computational power requirement. Multiple GPUs or TPUs were used for pre-training. All listed RoBERTa based models were computed on GPUs whereas GottBERT is the first published RoBERTa model pre-trained on TPUs.

3 GottBERT

GottBERT bases on the robustly optimized BERT architecture RoBERTa, which was pre-trained with the German portion of the OSCAR using the fairseq framework (Ott et al., 2019).

Training Data

The GottBERT model is trained on the German portion of the OSCAR, a recently published large multilingual text corpus extracted from Common Crawl. The German data portion of the OSCAR measures 145GB of text containing approximately 21.5 billion words in approximately 459 million documents (one document per line).

Pre-processing

Originally, RoBERTa uses GPT2 (Radford et al., 2019) byte pair encoding to segment the input into

¹<https://deepset.ai/german-bert>

²<https://github.com/dbmdz/berts#german-bert>

³<https://github.com/musixmatchresearch/umberto>

⁴<https://github.com/glample/fastBPE>

subword units. Therefore, no pre-tokenization is required and thus no language-specific tokenizer as e.g. `moses` (Koehn et al., 2007) must be used. Its original vocabulary was computed on English data. For GottBERT we computed a vocabulary of 52k subword tokens based on 40 GB randomly sampled documents of the German OSCAR portion. Compared to the original GPT2 tokenizer, which was trained on English data, this leads to a 40% smaller size of the binary data which are fed into fairseq (Ott et al., 2019). Furthermore, according to Delobelle et al. (2020), it leads to a performance increase.

Pre-training

Using fairseq, we pre-trained GottBERT on a 256 core TPU pod using the RoBERTa BASE architecture. We trained the model in 100k update steps using a batch size of 8k. A 10k iteration warmup of the learning rate to a peak of 0.0004 was applied, from which the learning rate polynomially decayed to zero.

Downstream Tasks

Based on the pre-trained BERT models, several downstream tasks were trained. The Framework for Adapting Representation Models (FARM)⁵ already comes with pre-configured experiments for German language. Originally, these experiments were setup to benchmark German BERT. We adopted this set of hyperparameters without additional grid search optimization. FARM is based on Hugging Face’s Transformer library (Wolf et al., 2019). As we trained GottBERT with fairseq, we converted GottBERT into the Hugging Face format.

Named Entity Recognition We evaluated GottBERT on two NER tasks. One was the German part of CoNLL 2003 shared task (Tjong Kim Sang and De Meulder, 2003). It contains three main entity classes and one for other miscellaneous entities. As measurement we used the *harmonic mean of precision and recall* F_1 . The second NER task was GermEval 2014 (Benikova et al., 2014). It extends the CoNLL 2003 shared task by fine-grained labels and embedded markables. Fine-grained labels allow the indication of NER subtypes common in German, namely derivations and parts: e.g. “Mann” → “männlich” and “Mann” → “mannhaft”. In order to recognize nested NEs embedded markables are required. Specifically, this was realized

by annotating main classes as well as two levels of subclasses. Performance was measured by the use of an adapted F_1 evaluation metric Benikova et al. (2014), which considers the equality of labels and spans (text passages) and additionally levels in the class hierarchy.

Text Classification GermEval task 2018 (Risch et al., 2018) is a text classification task that contains two subtasks of different granularity: the coarse-grained binary classification of German tweets and fine-grained classification of the same tweets into four different classes. Based on the One Million Posts Corpus (Schabus et al., 2017) which is intended to test performance on German language, the 10k German News Articles Dataset (10kGNAD) topic classification⁶ was created. The dataset contains approximately 10k news articles of an Austrian newspaper which are to be classified into 9 categories. As both classification datasets do not provide a pre-defined validation set, we used 90% of the original training set for training and 10% for validation. Data was split randomly. For evaluation we computed the mean of the F_1 -scores of each class/category.

4 Results

In order to evaluate the performance, each downstream task ran 10 times using different seeds. As measure, the F_1 scores of the experiments based on the test set was used. The score is the best of 10 runs of the respective experiment of each trained model. The best score selection is based on validation set. We compared GottBERT’s performance with four other models listed in Table 1.

Named Entity Recognition For the two tested NER tasks, CoNLL 2003 and GermEval 2014, GottBERT outperformed all others models followed by dbmz BERT (see Table 2). Obviously, the amount and characteristic of data of the German portion of the OSCAR is beneficial. The third place goes to XLM RoBERTa. Interestingly, mBERT outperforms German BERT, although mBERT’s amount of German data can be assumed to be smaller compared to German BERT. Notably, mBERT performs an exponentially smoothed weighting of the data in order to balance the variance in data size of all the different languages. Consequently, even if we knew the data size of the German portion of mBERT, a direct comparison would not be possible.

⁵<https://github.com/deepset-ai/FARM>

⁶<https://tblock.github.io/10kGNAD>

Model	Type	#Languages	Data Size	Data Source
GottBERT	RoBERTa	1	145GB	OSCAR
dbmz BERT	BERT	1	16GB	Wikipedia, EU Bookshop corpus ⁷ , Open Subtitles, Common-,Para-,NewsCrawl
mBERT _{cased}	BERT	104	unknown	Wikipedia
German BERT	BERT	1	12GB	news articles, Open Legal Data ⁸ , Wikipedia
XLNet RoBERTa	RoBERTa	100	2.5TB (66.6GB German)	CommonCrawl, Wikipedia

Table 1: This table shows the models, we used in our experiments. Additional information about the pre-training and architecture is listed. Unfortunately, for mBERT we did not find any estimate about the data size.

Model	CoNLL 2003	GermEval 2014
GottBERT	83.57	86.84
dbmz BERT	<u>82.30</u>	<u>85.82</u>
mBERT _{cased}	81.20	85.39
German BERT	81.18	85.03
XLNet RoBERTa	81.36	85.41

Table 2: F_1 scores of NER experiments based on the test set. Best score out of 10 runs (selection based on validation set).

Text Classification Table 2 shows the F_1 scores of the classification tasks. In GermEval 2018 coarse and 10kGNAD, dbmz BERT outperforms the other models followed by German BERT. GottBERT only performs best in GermEval 2018 fine. In 10kGNAD even XLNet RoBERTa outperforms GottBERT. In general, the two RoBERTa based models seem not to develop their full potential, which might be due to sub-optimal hyperparameters.

5 Conclusion

In this work we present the German single language RoBERTa based model GottBERT which was computed on 145GB plain text. GottBERT is the first German single language RoBERTa based model. Even without extensive hyperparameter optimization, in three out of five downstream tasks, GottBERT already outperformed all other tested models. As the authors of German BERT released the parameters within the FARM framework, we assume the parameters for the downstream tasks are probably not optimal for RoBERTa based models. Consequently, further extensive hyperparameter optimization of the downstream tasks might lead to better results for GottBERT. Dodge et al. (2020) give insights into hyperparameter optimization, its

complexity and effects in relation to BERT. Further, they present a solution to lower costs. Due to the required effort, we currently leave this open as future work and release GottBERT in hugging-face and fairseq format to the community under the AGPLv3 license.

Acknowledgments

This work was supported by the German Ministry for Education and Research (BMBF FKZ 01ZZ1801B) and supported with Cloud TPUs from Google’s TensorFlow Research Cloud (TFRC). We would like to thank Ian Graham for constructive criticism of the manuscript and Louis Martin for the helping email contact. A special thanks goes to Myle Ott, who implemented the TPU feature in fairseq and intensively supported us to get our computation run. Finally, we would like to recognizeably thank the people behind the scenes who essentially made this work possible: Frank Werner, Georg Koch, Friedlinde Bühler and Jochen Knaus of our internal IT team, Philipp Munz and Christian Wiedemann of Wabion GmbH and last but not least Nora Limbourg the Google Cloud Customer Engineer assigned to us.

Model	GermEval 2018 coarse	GermEval 2018 fine	10kGNAD
GottBERT	76.39	51.25	89.20
dbmz BERT	77.32	<u>50.97</u>	90.86
mBERT _{cased}	72.87	44.78	88.72
German BERT	<u>77.23</u>	49.28	<u>90.66</u>
XLM RoBERTa	75.15	45.63	89.30

Table 3: F_1 scores of text classification experiments based on the test set. Best score out of 10 runs (selection based on validation set).

References

- Alan Akbik, Tanja Bergmann, Duncan Blythe, Kashif Rasul, Stefan Schweter, and Roland Vollgraf. 2019. [FLAIR: An Easy-to-Use Framework for State-of-the-Art NLP](#). In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics (Demonstrations)*, pages 54–59, Minneapolis, Minnesota. Association for Computational Linguistics.
- Emily Alsentzer, John R. Murphy, Willie Boag, Wei-Hung Weng, Di Jin, Tristan Naumann, and Matthew B. A. McDermott. 2019. [Publicly Available Clinical BERT Embeddings](#). *arXiv:1904.03323 [cs]*. ArXiv: 1904.03323.
- Darina Benikova, Chris Biemann, Max Kisselew, and Sebastian Padó. 2014. GermEval 2014 Named Entity Recognition Shared Task: Companion Paper. *Proceedings of the KONVENS GermEval Shared Task on Named Entity Recognition*, pages 104–112.
- Piotr Bojanowski, Edouard Grave, Armand Joulin, and Tomas Mikolov. 2017. Enriching Word Vectors with Subword Information. *Transactions of the Association for Computational Linguistics*, 5:135–146.
- Alexis Conneau, Kartikay Khandelwal, Naman Goyal, Vishrav Chaudhary, Guillaume Wenzek, Francisco Guzmán, Edouard Grave, Myle Ott, Luke Zettlemoyer, and Veselin Stoyanov. 2019. [Unsupervised cross-lingual representation learning at scale](#). *CoRR*, abs/1911.02116.
- Pieter Delobelle, Thomas Winters, and Bettina Berendt. 2020. [RobBERT: a Dutch RoBERTa-based Language Model](#). *arXiv:2001.06286 [cs]*. ArXiv: 2001.06286.
- Jacob Devlin. 2018. [Multilingual BERT Readme Document](#).
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. [BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding](#). In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.
- Jesse Dodge, Gabriel Ilharco, Roy Schwartz, Ali Farhadi, Hannaneh Hajishirzi, and Noah Smith. 2020. [Fine-Tuning Pretrained Language Models: Weight Initializations, Data Orders, and Early Stopping](#). *arXiv:2002.06305 [cs]*. ArXiv: 2002.06305.
- Yoav Goldberg and Omer Levy. 2014. [word2vec Explained: deriving Mikolov et al.’s negative-sampling word-embedding method](#). *arXiv:1402.3722 [cs, stat]*. ArXiv: 1402.3722.
- Armand Joulin, Edouard Grave, Piotr Bojanowski, Matthijs Douze, H  rve J  gou, and Tomas Mikolov. 2016. FastText.zip: Compressing text classification models. *arXiv preprint arXiv:1612.03651*.
- Armand Joulin, Edouard Grave, Piotr Bojanowski, and Tomas Mikolov. 2017. Bag of Tricks for Efficient Text Classification. In *Proceedings of the 15th Conference of the European Chapter of the Association for Computational Linguistics: Volume 2, Short Papers*, pages 427–431. Association for Computational Linguistics.
- Philipp Koehn, Hieu Hoang, Alexandra Birch, Chris Callison-Burch, Marcello Federico, Nicola Bertoldi, Brooke Cowan, Wade Shen, Christine Moran, Richard Zens, Chris Dyer, Ond  rej Bojar, Alexandra Constantin, and Evan Herbst. 2007. [Moses: Open Source Toolkit for Statistical Machine Translation](#). In *Proceedings of the 45th Annual Meeting of the Association for Computational Linguistics Companion Volume Proceedings of the Demo and Poster Sessions*, pages 177–180, Prague, Czech Republic. Association for Computational Linguistics.
- Taku Kudo and John Richardson. 2018. [SentencePiece: A simple and language independent subword tokenizer and detokenizer for Neural Text Processing](#). In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 66–71, Brussels, Belgium. Association for Computational Linguistics.
- Hang Le, Lo  c Vial, Jibril Frej, Vincent Segonne, Maximin Coavoux, Benjamin Lecouteux, Alexandre Al-lauzen, Beno  t Crabb  , Laurent Besacier, and Didier Schwab. 2020. [FlauBERT: Unsupervised Language Model Pre-training for French](#). *arXiv:1912.05372 [cs]*. ArXiv: 1912.05372.
- Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis,

- Luke Zettlemoyer, and Veselin Stoyanov. 2019. [RoBERTa: A Robustly Optimized BERT Pretraining Approach](#). *arXiv:1907.11692 [cs]*. ArXiv: 1907.11692.
- Louis Martin, Benjamin Muller, Pedro Javier Ortiz Suárez, Yoann Dupont, Laurent Romary, Éric de la Clergerie, Djamé Seddah, and Benoît Sagot. 2020. [CamemBERT: a Tasty French Language Model](#). In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 7203–7219, Online. Association for Computational Linguistics.
- Tomas Mikolov, Edouard Grave, Piotr Bojanowski, Christian Puhersch, and Armand Joulin. 2018. [Advances in Pre-Training Distributed Word Representations](#). In *Proceedings of the Eleventh International Conference on Language Resources and Evaluation (LREC 2018)*, Miyazaki, Japan. European Language Resources Association (ELRA).
- Nathan Ng, Kyra Yee, Alexei Baevski, Myle Ott, Michael Auli, and Sergey Edunov. 2019. [Facebook FAIR’s WMT19 News Translation Task Submission](#). In *Proceedings of the Fourth Conference on Machine Translation (Volume 2: Shared Task Papers, Day 1)*, pages 314–319, Florence, Italy. Association for Computational Linguistics.
- Pedro Javier Ortiz Suárez, Laurent Romary, and Benoît Sagot. 2020. [A Monolingual Approach to Contextualized Word Embeddings for Mid-Resource Languages](#). In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 1703–1714, Online. Association for Computational Linguistics.
- Myle Ott, Sergey Edunov, Alexei Baevski, Angela Fan, Sam Gross, Nathan Ng, David Grangier, and Michael Auli. 2019. [fairseq: A Fast, Extensible Toolkit for Sequence Modeling](#). *arXiv:1904.01038 [cs]*. ArXiv: 1904.01038.
- Myle Ott, Sergey Edunov, David Grangier, and Michael Auli. 2018. [Scaling Neural Machine Translation](#). *arXiv:1806.00187 [cs]*. ArXiv: 1806.00187.
- Jeffrey Pennington, Richard Socher, and Christopher Manning. 2014. [GloVe: Global Vectors for Word Representation](#). In *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 1532–1543, Doha, Qatar. Association for Computational Linguistics.
- Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. 2019. Language models are unsupervised multitask learners. *OpenAI Blog*, 1(8):9.
- Julian Risch, Eva Krebs, Alexander Löser, Alexander Riese, and Ralf Krestel. 2018. Fine-Grained Classification of Offensive Language. In *Proceedings of GermEval 2018 (co-located with KONVENS)*, pages 38–44.
- Dietmar Schabus, Marcin Skowron, and Martin Trapp. 2017. [One Million Posts: A Data Set of German Online Discussions](#). In *Proceedings of the 40th International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR)*, pages 1241–1244, Tokyo, Japan.
- Mike Schuster and Kaisuke Nakajima. 2012. [Japanese and Korean voice search](#). In *2012 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 5149–5152. ISSN: 2379-190X.
- Rico Sennrich, Barry Haddow, and Alexandra Birch. 2016. [Neural Machine Translation of Rare Words with Subword Units](#). *arXiv:1508.07909 [cs]*. ArXiv: 1508.07909.
- Erik F. Tjong Kim Sang and Fien De Meulder. 2003. [Introduction to the CoNLL-2003 Shared Task: Language-Independent Named Entity Recognition](#). In *Proceedings of the Seventh Conference on Natural Language Learning at HLT-NAACL 2003 - Volume 4, CONLL ’03*, pages 142–147, USA. Association for Computational Linguistics. Event-place: Edmonton, Canada.
- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. 2017. [Attention is All you Need](#). In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems 30*, pages 5998–6008. Curran Associates, Inc.
- Antti Virtanen, Jenna Kanerva, Rami Ilo, Jouni Luoma, Juhani Luotolahti, Tapio Salakoski, Filip Ginter, and Sampo Pyysalo. 2019. [Multilingual is not enough: BERT for Finnish](#). *arXiv:1912.07076 [cs]*. ArXiv: 1912.07076.
- Wietse de Vries, Andreas van Cranenburgh, Arianna Bisazza, Tommaso Caselli, Gertjan van Noord, and Malvina Nissim. 2019. [BERTje: A Dutch BERT Model](#). *arXiv:1912.09582 [cs]*. ArXiv: 1912.09582.
- Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, and Jamie Brew. 2019. [Huggingface’s transformers: State-of-the-art natural language processing](#). *CoRR*, abs/1910.03771.
- Yang You, Jing Li, Sashank Reddi, Jonathan Hseu, Sanjiv Kumar, Srinadh Bhojanapalli, Xiaodan Song, James Demmel, Kurt Keutzer, and Cho-Jui Hsieh. 2020. [Large Batch Optimization for Deep Learning: Training BERT in 76 minutes](#). *arXiv:1904.00962 [cs, stat]*. ArXiv: 1904.00962 version: 5.