

Open Korean Corpora: A Practical Report

Won Ik Cho

Seoul National University
Seoul, Korea

tsatsuki@snu.ac.kr

Sangwhan Moon

Tokyo Institute of Technology
Tokyo, Japan

sangwhan@iki.fi

Youngsook Song

Kyung Hee University
Seoul, Korea

youngsoksong@khu.ac.kr

Abstract

Korean is often referred to as a low-resource language in the research community. While this claim is partially true, it is also because the availability of resources is inadequately advertised and curated. This work curates and reviews a list of Korean corpora, first describing institution-level resource development, then further iterate through a list of current open datasets for different types of tasks. We then propose a direction on how open-source dataset construction and releases should be done for less-resourced languages to promote research.

1 Introduction

The Korean language is less explored in terms of corpus and computational linguistics, but its prevalence is often underrated. It regards about 80 million language users and is recently adopted in multilingual research as it is bound to CJK (Chinese, Japanese, and Korean), also handling a distinguished writing system.

However, compared to the industrial need, the interest in Korean natural language processing (NLP) has not been developed much in international viewpoints, which recurrently hinders the related publication and further academic extension. Besides, in the recent NLP, where the benchmark practice is a trend, such systems lack at this point, deterring abroad and even native researchers who start Korean NLP from finding directions. Park et al. (2016) has shown a decent survey, but it seems that the techniques are mainly on the NLP pipeline. Also, albeit some curations on Korean NLP¹ and datasets², we considered that little more organization is required, and better if internationally available. Our attempts are expected to mitigate the

challenges that the researchers who handle Korean from a multi- or cross-lingual viewpoint may face.

In this paper, we scrutinize the struggles of government, institutes, industry, and individuals to construct public Korean NLP resources. First, we state how the institutional organizations have tackled the issue by making up the accessible resources, and point out the limitation thereof regarding international availability and license, to finally introduce and curate the fully public datasets along with the proposed criteria. Through this, we want to find out the current state of Korean corpora across the NLP tasks and whether they are freely or conditionally available. Our survey is to be curated and updated in the public repository³.

2 Accessible Resources

With the increase in popularity of machine learning-driven methods in NLP, constructing a novel dataset and releasing it to the public can be considered the cornerstone of advancing research of a given language. While we believe many useful datasets exist behind industry walls, this is not particularly useful for advancing open research. Fortunately, there are organizations that construct and distribute cleaned, pre-processed datasets which are occasionally accompanied by a task and the annotation. In the context of Korean, there are numerous efforts in this field driven by government-affiliated organizations.

2.1 Datasets from public institutions

National Institute of Korean Language (NIKL) is an institution that establishes the norm

¹<https://github.com/datanada/Awesome-Korean-NLP>

²<https://littlefoxdiary.tistory.com/42>

³<https://github.com/ko-nlp/Open-korean-corpora>

This is May 2023 version (second edition) of the manuscript. You can find the first version in an online archive (Cho et al., 2020b).

for Korean linguistics⁴. However, at the same time, it usually undergoes the massive dataset construction from the view of computational linguistics, to apt to the new wave of language artificial intelligence (AI). Widely known ones include Korean word dictionaries⁵ and Sejong Corpus (Kim, 2006)⁶. The dictionary contains fundamental and new lexicons that make up Korean (along with the content), and the Sejong Corpus is a large-scale labeled NLP pipeline corpus for the tasks such as constituency and dependency parsing, mainly provided in *.xlm*-like format. Besides, recently, labeled corpora of about 300 million word size is released⁷, covering inter-sentence tasks such as similarity and entailment. The corpora (of about 37 datasets as of May 2023) are continuously being updated regarding typos and inappropriate contents, upon user report and academic feedback.

Electronics and Telecommunications Research Institute (ETRI) has been collecting, refining, and tagging language processing and speech learning data over a long period of time⁸. Aside from NIKL, which mainly focuses on classical NLP pipelines, ETRI has also built a database for semantic analysis and question answering (QA), which are the outcome of a project Exo-brain⁹. The project includes syntax-semantic ones such as part of speech (POS) tagging and semantic role labeling (SRL), simultaneously providing construction guidelines for the corpora.

AI HUB is a platform organized by National Information Society Agency (NIA) in which a large-scale dataset are integrated¹⁰. The datasets are built for various tasks at the government level, to promote the development of the AI industry. Provided resources are labeled or parallel corpora in real-life domains. Here, the domains are law, patent, common sense, open dialog, machine reading comprehension, and machine translation. Also, about

1,000 hours of speech corpus is provided to be used in spoken language modeling¹¹. Recently, some new datasets have been distributed on wellness and emotional dialog, so that many people can have trials for social good and public AI. Also, open dictionary NIADic¹² is freely available, provided by K-ICT Big Data Center. As of May 2023, there are 97 Korean language datasets being provided, and are continuously being managed by the institution.

2.2 Accessibility

The above datasets guarantee high quality, along with well-defined guidelines and the well-educated workers. However, their usage is often unfortunately confined to domestic researchers for procedural issues. Researchers abroad can indeed access the data, but they may face difficulty filling out and submitting the particular application form, instead of the barrier-free downloading system. Also, in most cases, modification and redistribution are restricted, making them uncompetitive in view of quality enhancement (Han et al., 2017).

Here, we want to introduce datasets that can be utilized as an alternative to the limitedly accessible Korean NLP resources. Instead of scrutinizing all available corpora, we are going to curate them under specific criteria.

3 Open Datasets

All the datasets to be introduced from now on are fully open access. This means that the dataset is downloadable with a single click or cloning, or at least one can acquire the dataset with simple signing. We set three checklists for the status of the corpus, namely *documentation*, *usage*, and *redistribution*. The first one is on how fine-grained the corpus description is.

- Does the corpus have any documentation on the usage? (**doc**)
- Does the corpus have a related article?¹³ (**paper**)
- Does the corpus have a internationally available publication? (**int'l**)

⁴<https://www.korean.go.kr/>

⁵The search portal is provided in <https://stdict.korean.go.kr/main/main.do> while the full word and content list are available at <https://github.com/korean-word-game/db>

⁶Though the original link is outdated, one can refer to the following URL to download and preprocess the corpus <https://github.com/coolengineer/sejong-corpus>

⁷<https://corpus.korean.go.kr/>

⁸<https://www.etri.re.kr/intro.html>

⁹<http://exobrain.kr/pages/ko/result/outputs.jsp>

¹⁰<http://www.aihub.or.kr/>

¹¹<https://www.aihub.or.kr/aidata/105>

¹²https://kbig.kr/portal/kbig/knowledge/files/bigdata_report.page?bltnNo=10000000016451

¹³Article is here more a complete form of document than *doc* above, and some domestic publications are included here since they are not internationally available.

Next, we check whether the dataset is both academically and commercially available, academic use only, or unknown (**all, academic, unknown**). For the last one, we also investigate if redistribution is available with or without modification, if neither, or unknown (**rd, rd/mod-x, none, unknown**)¹⁴. These attributes are noted along with each corpus title.

Primarily, we want to introduce the recent trials on constructing Korean NLP benchmarks in current pretrained language models (PLMs) era, and then look around the specific areas of Korean NLP.

3.1 Benchmark studies

Due to emerging PLM studies in Korean and their public release (Yang, 2021), the need of fair evaluation has grown for a few years. This led to the construction of benchmark dataset that follows GLUE, General Language Understanding Evaluation benchmark (Wang et al., 2018), and such need had called for the participation of companies and institutions to create new benchmarks that aim to evaluate PLMs’ capabilities of Korean understanding.

KLUE [int'l, all, rd]
Park et al. (2021) is first non-government-driven Korean language understanding evaluation benchmark created by researchers from multiple organizations (institutes and companies). KLUE consists of eight newly constructed datasets, namely topic classification (KLUE-TC or YNAT, 63K sentences), semantic textual similarity (KLUE-STs, 12K sentence pairs), natural language inference (KLUE-NLI, 31K sentence pairs), named entity recognition (KLUE-NER, 31K sentences), relation extraction (KLUE-RE, 48K sentences), dependency parsing (KLUE-DP, 15K sentences), machine reading comprehension (KLUE-MRC, 29K questions), and dialogue state tracking (KLUE-DST or WoS, 10K dialogues). KLUE aims at NLU benchmark that can evaluate the performance of PLMs not biased to the task specification, text domain or style, or tokenization methodology etc., and is widely used in Korean NLP community as a useful source of training and evaluation¹⁵.

KoBEST [int'l, all, rd]
Jang et al. (2022) is a new Korean benchmark

dataset designed for more challenging language understanding tasks. It comprises five newly constructed datasets: BoolQ (6K paragraph-sentence pairs), COPA (5K sentence triplets), KB-WiC (6K sentence pairs), KB-HellaSwag (3K paragraph and four pairs of sentences), and SentiNeg (4K sentence pairs). KoBEST aims to evaluate a model’s ability to reason based on more complex knowledge beyond textual form, such as the passage of time, meaning of text, and causality¹⁶.

3.2 Parsing and tagging

As a part of the classical NLP pipeline, we aggregate studies on POS tagging, tree tagging and dependency parsing, named entity recognition (NER) and SRL.

KAIST Morpho-Syntactically Annotated Corpus [paper, academic, none]
Lee et al. (1999) applies morphological analysis to freely available KAIST raw corpus¹⁷. The scale is about 70M words and the domain includes novel, non-literature, article, etc.

OpenKorPOS [int'l, all, rd]
Moon et al. (2022) is a semi-automatically constructed corpus for Korean part-of-speech tagging, built with multiple open-source Korean POS analyzers on Wikipedia dataset¹⁸. The corpus contains about 55M words (eojeols) and inherits the license of Wikipedia.

KAIST Korean Tree-Tagging Corpus [int'l, academic, none]
Choi et al. (1994)¹⁹ bases on independently collected 30K sentences that are annotated according to the tree tagging scheme for Korean.

UD Korean KAIST [int'l, academic, none]
Chun et al. (2018) applies universal dependency (UD) parsing (McDonald et al., 2013) to the Korean Tree-Tagging Corpus (Choi et al., 1994)²⁰.

PKT-UD [int'l, academic, none]
Chun et al. (2018); Oh et al. (2020)²¹ applies UD

¹⁴Though there are various license criteria such as MIT or CC, we did not note them here so as to intuitively display how people should utilize the dataset.

¹⁵<https://klue-benchmark.com/>

¹⁶https://huggingface.co/datasets/skt/kobest_v1

¹⁷http://semanticweb.kaist.ac.kr/home/index.php/KAIST_Corpus

¹⁸<https://github.com/openkorpos>

¹⁹<http://semanticweb.kaist.ac.kr/home/index.php/Corpus4>

²⁰<https://github.com/emorynlp/ud-korean>

²¹Also available at UD-Korean repository, but currently previous version. PKT v2020 data will be uploaded.

parsing to the Penn Korean Treebank (Han et al., 2001)²².

KMOU NER [paper, academic, rd]
is an NER dataset built by Korean Marine and Ocean University²³. The named entities are tagged for about 24K utterances according to name, time, and number. The data source are Exo-brain (by ETRI) and their own data combined, while the re-distribution is available only for the latter.

AIR×NAVER NER/SRL

[doc, academic, none]
adopted NER²⁴ and SRL²⁵ data constructed by Changwon National University for the purpose of a public competition²⁶, and is annotated according to CoNLL format (Tjong Kim Sang and De Meulder, 2003). Corpus size is about 90K and 35K each.

KoNEC & KoNNEC [paper, all, rd]
KoNEC (Cheong et al., 2022) is an NER dataset²⁷ that annotates 150 types of named entities on the raw corpus of the KLUE-NER data, and KoNNEC²⁸ is annotated using a nested entity annotation approach on the KoNEC data.

3.3 Entailment, sentence similarity, and paraphrase

Here we aggregate corpora for logical inference and checking similarity, as well as style transfer datasets as a part of paraphrase datasets.

Question Pair [doc, all, rd]
consists of about 10,000 open domain sentence pairs²⁹, with the binary labels that are hand-annotated on whether the sentences are paraphrase or irrelevant.

KorNLI/KorSTS [int'l, all, rd]
Ham et al. (2020) is a natural language inference (NLI) and sentence textual similarity (STS) dataset for Korean³⁰. For KorNLI, the train set was con-

²²<https://catalog.ldc.upenn.edu/LDC2006T09> LDC materials are not curated here.

²³<https://github.com/kmounlp/NER>

²⁴http://air.changwon.ac.kr/?page_id=10

²⁵http://air.changwon.ac.kr/?page_id=14

²⁶<https://github.com/naver/nlp-challenge>

²⁷<https://github.com/korean-named-entity/konec>

²⁸<https://github.com/korean-named-entity/konne>

²⁹https://github.com/songys/Question_pair

³⁰<https://github.com/kakaobrain/KorNLUDatasets>

structed by machine translating SNLI (Bowman et al., 2015) and MNLI (Williams et al., 2018), and the valid and test set were constructed by human translation of XNLI (Conneau et al., 2018). Just as in the original dataset, the pairs are labelled with entailment, contradiction, or neutral. About 940K examples are provided for training, and 2,490 and 5,010 respectively for dev and test. For KorSTS, the scoring was done from 0 to 5 to elaborate rather than the binary label that determines paraphrase. Following the scheme of NLI, 5,749 training data were machine translated using the STS-B dataset (Cer et al., 2017) as a source, while 1,500 dev set and 1,379 test set pairs are human translated.

ParaKQC [int'l, all, rd]
Cho et al. (2020a)³¹ originally consists of 10,000 questions and commands, and each instance is labeled with 4 topics (mail, smart agent, scheduling, and weather) and 4 speech acts (*wh*-question, alternative question, prohibition, and requirement). The sentence set can be extended to about 540K sentence pairs that determine sentence similarity and paraphrase.

StyleKQC [int'l, all, rd]
Cho et al. (2022b) is Korean style transfer and paraphrase dataset that deals with formal and informal Korean questions and commands³². It builds upon the construction scheme of ParaKQC and contains 30K sentences, namely 15K for formal and informal style each, built upon 3,000 source phrases and covers six domains regarding smart agents.

Korean Smile Style Dataset

[doc, academic, rd]
Kim (2022b) is colloquial style transfer dataset that contains sentences in 17 styles, built upon a total of about 2,500 dialogs³³. Styles include formal and informal, robot-like, chat-style, etc., which are casually classified by the dataset builder.

3.4 Intention understanding, sentiment analysis, and offensive language detection

Beyond corpora that cover sentence pairs, here we introduce some corpora that suit single sentence classification task, that mainly deal with intention or sentiment.

³¹<https://github.com/warnikchow/paraKQC>

³²<https://github.com/cynthia/stylekqc>

³³https://github.com/smilegate-ai/korean_smile_style_dataset

3i4K [int'l, all, rd]
Cho and Kim (2022) aims an utterance-level speech act classification of the Korean language³⁴. The volume reaches 61K, hand-labeled with 7 classes, namely fragment, statement, question, command, rhetorical question/command, and intonation-dependent utterances.

NSMC [doc, all, rd]
is a review sentiment corpus³⁵ of size 200K, which consists of Naver movie comments automatically labeled according to the methodology of **Maas et al. (2011)**. It adopts pos/neg binary labels, and it has been widely used as a benchmark for pretrained language models.

Kocasm [doc, all, rd]
Kim and Cho (2019)³⁶ is a Korean sarcasm dataset constructed following the collection scheme of **Ghosh and Veale (2016)**. It contains about 9K Korean tweets crawled online according to some sarcasm-related hashtags and were binary classified manually by authors.

BEEP! [int'l, all, rd]
Moon et al. (2020) is a hand-labeled, crowd-sourced dataset of about 9.4K Naver entertainment news comments with hate speech and social bias³⁷. Bias and hate attribute consists of 3 labels, namely gender/others/none and hate/offensive/none, respectively.

APEACH [int'l, all, rd]
Yang et al. (2022) is a balanced evaluation set containing a total of 4K Korean sentences that are either hate speech or non-hate speech³⁸. All sentences in the dataset were generated by human participants under the instruction of task managers (authors) and the moderator (of the crowdsourcing platform), given one of ten topics (racism, sexual harassment, gender stereotypes, etc.) per sentence as a condition.

Korean Unsmile Dataset

[docu, academic, rd/mod-x]
Kim (2022a) is an offensive language corpus that contains 19K utterances, namely 10K hate speech, 4K offensive language, and 5K clean expressions.

³⁴<https://github.com/warnikchow/3i4k>

³⁵<https://github.com/e9t/nsmc>

³⁶<https://github.com/SpellOnYou/korean-sarcasm>

³⁷<https://github.com/kocohub/korean-hate-speech>

³⁸<https://github.com/jason9693/APEACH>

All instances are classified into hate speech, offensive language (comments and profanity terms), and clean expressions, while hate speech can be further annotated with seven multi-label topics.

HateScore [int'l, academic, rd]
Kang et al. (2022) is a multilabel hate speech detection corpus that shares the similar construction scheme with Unsmile³⁹. It contains 35K instances that consist of 24K online comments, 2.2K neutral sentences from Wikipedia, 1.7K sentences generated human-in-the-loop, and 7.1K rule-generated sentences.

KOLD [int'l, all, rd]
Jeong et al. (2022) is Korean offensive language detection corpus that is constructed upon 40K Korean comments from NAVER news and YouTube⁴⁰. Comments are annotated hierarchically with the type (offensive and not-offensive) and the target (untargeted, individual, or group) of offensive language, which also contains the corresponding text spans. The target group and its attribute are also annotated.

K-MHaS [int'l, all, rd]
Lee et al. (2022a) is a multi-labeled Korean hate speech dataset built upon 109K utterances from Korean online news comments, tagged in (a) binary manner and (b) 8 fine-grained hate speech classes including politics, origin, physical, age, gender, religion, race, and profanity⁴¹.

KODOLI [int'l, all, rd]
Park et al. (2023) is a recently published Korean dataset for offensive language identification of size about 38K sentences⁴². It consists of various texts collected and sampled from online communities and news articles, and the texts are tagged in offensive, likely-offensive and none labels. It also contains two auxiliary annotations regarding abusive language and sentiment.

DKTC [doc, academic, rd]
Cho et al. (2022a) is Korean dataset of threatening conversations, which consists of 4K conversations regarding threatening, chantage, bullying, and other harassment (1K each) for train, and 500 test

³⁹<https://github.com/sgunderscore/hatescore-korean-hate-speech>

⁴⁰<https://github.com/boychaboy/KOLD>

⁴¹<https://github.com/adlnlp/K-MHaS>

⁴²<https://github.com/cardy20/KODOLI>

dataset containing conversations without threatening⁴³.

3.5 QA and dialogue

In this section, we list up QA and dialogue datasets which include question passages or conversations those have significantly longer text compared to sentence-level instances.

KorQuAD 1.0, 2.0

[int'l, all, rd/mod-x]
provides human-generated QA corpus and leaderboard for Korean⁴⁴. KorQuAD 1.0 (Lim et al., 2019) benchmarks SQuAD 1.0 (Rajpurkar et al., 2016) and consists of total 70K questions. KorQuAD 2.0 of size 100K aims at machine reading comprehension for structured HTML natural questions, which was created referring to the scheme of Google Natural Questions (Kwiatkowski et al., 2019)⁴⁵.

HuLiC [doc, academic, rd]
consists of human-human conversations of 40K turns and human-machine conversations of 75K turns, where humans talk about movies and human-machine talk about open topics⁴⁶. Workers' demographics and other evaluation attributes such as sensibleness, specificity, human-likeness (evaluated turn-wisely), and preference (evaluated every 20 turns).

OPELA [int'l, academic, rd]
Lee et al. (2022b) is a Korean persona dialogue dataset consisting of about 600 conversations, which are created by human participants, namely eleven persona actors (accompanying character profiles) and about 500 user actors⁴⁷. Conversations were made on a chatting app provided by the crowdsourcing platform, where moderators and task managers could monitor the conversation process and moderate the probable issues. Dialogues are additionally annotated with six psychology-related attributes, and 1/3 of the created data was published online for public usage.

CareCall [int'l, academic, rd]
Bae et al. (2022) corpus is a Korean "Role specified" Open-domain dialogue in caring senior cit-

izens domain⁴⁸. The dataset is created by using LLMs, along with human support. 10K filtered dialogues are bot-generated via one-shot dialogue generation and human filtering, and each consists of a list of utterances, where each line is tagged with the role (system or user), text, out-of-bounds (boolean whether checks if the utterance of the system violates role specifications).

3.6 Summarization, Translation, and Transliteration

Summarization, translation, and transliteration datasets are separately grouped to specify their usual usage of sequence-to-sequence architectures.

Sci-news-sum-kr [doc, academic, rd]
contains about 50 Korean news summarizations generated by two Korean natives⁴⁹. Since the size is not large, it is recommended to be used as a dev set.

sae4K [int'l, all, rd]
Cho et al. (2020c) contains the directive sentence summarization of the sentence level⁵⁰. It includes about 50K pairs of utterance and natural language query pair for questions and commands, where the data is partly based on 3i4K (Cho and Kim, 2022) and some are human-generate in concurrence with Cho et al. (2020a).

Korean Parallel Corpora

[int'l, academic, rd/mod-x]
Park et al. (2016) contains about 100K en-ko sentence pairs for machine translation (MT). The data mainly bases on news articles, and now also provides the data on North Korean⁵¹.

KAIST Translation Evaluation Set

[doc, academic, none]
is an evaluation set of size about 3,000 for en-ko MT⁵², augmented with index, original sentence, translation, related articles, and text source.

KAIST Chinese-Korean Multilingual Corpus

[doc, academic, none]

⁴³<https://github.com/tunib-ai/DKTC>

⁴⁴<https://korquad.github.io/>

⁴⁵<https://ai.google.com/research/NaturalQuestions/>

⁴⁶<https://github.com/smilegate-ai/HuLiC>

⁴⁷<https://github.com/smilegate-ai/OPELA>

⁴⁸<https://github.com/naver-ai/carecall-corpus>

⁴⁹<https://github.com/theeluwin/sci-news-sum-kr-50>

⁵⁰<https://github.com/warnikchow/sae4k>

⁵¹<https://github.com/jungyeul/korean-parallel-corpora>

⁵²<http://semanticweb.kaist.ac.kr/home/index.php/Evaluateset2>

contains 60K short sentence pairs for zh-ko MT⁵³.

Transliteration Dataset [doc, all, rd]
is not an official data repository⁵⁴, but en-ko transliteration is collected from public dictionaries such as NIKL or Wiktionary⁵⁵. A total of about 35K en (word) - ko (pronunciation) pairs are included.

KAIST Transliteration Evaluation Set [doc, academic, none]
is a word-pronunciation pair for phonotactics in en-ko⁵⁶, and consists of 7,186 words excerpted from the loanword dictionary⁵⁷.

3.7 Korean in multilingual corpora

We also investigate Korean examples in multilingual corpora, where the type of the dataset may belong to one of the types discussed above.

Multilingual G2P Conversion [int'l, all, rd]

Gorman et al. (2020) is a shared task of SIGMORPHON 2020⁵⁸, which aims to transform grapheme sequence into a phoneme sequence. The dataset was created with WikiPron⁵⁹ (Lee et al., 2020), and has been built for 10 languages including Korean (3,600 pairs for train, and 450 for dev/test each).

PAWS-X [int'l, all, rd]
Yang et al. (2019) is a dataset that consists of 23,659 human translated PAWS evaluation pairs (Zhang et al., 2019) and about 300K machine-translated ones, for 6 languages including Korean⁶⁰. Among them, Korean occupies about 5K train pairs, and 1,965 and 1,972 for dev/test each.

TyDi-QA [int'l, all, rd]
Clark et al. (2020) pursues typological diversity in QA, and provides a total of 200,000 question-answer pairs for 11 linguistically diverse languages,

⁵³<http://semanticweb.kaist.ac.kr/home/index.php/Corpus9>

⁵⁴<https://github.com/muik/transliteration>

⁵⁵https://en.wiktionary.org/wiki/Wiktionary:Main_Page

⁵⁶<http://semanticweb.kaist.ac.kr/home/index.php/Evaluateset3>

⁵⁷<http://www-lib.tufts.ac.jp/opac/xo/openurl/search?rft.issn=0000200626>

⁵⁸<https://sigmorphon.github.io/sharedtasks/2020/task1/>

⁵⁹<https://github.com/CUNY-CL/wikipron>

⁶⁰<https://github.com/google-research-datasets/paws/tree/master/pawsx>

including Korean⁶¹. Among them, Korean occupies about 11K train pairs, and 1,698/1,722 for dev/test each.

XPersona [int'l, all, rd]
Lin et al. (2020) is a dataset for evaluating personalized chatbots⁶². It provides the dataset of Zhang et al. (2018) translated to 7 languages, including Korean, where Korean displays 299 dialogues with 4,684 utterances.

MultiCoNER [int'l, all, rd]
Malmasi et al. (2022) is a large multilingual dataset contains 36 NE classes, representing real-world challenges for NER⁶³.

Multilingual Tweet Intimacy Analysis

[int'l, unk, unk]
Pei et al. (2022) is a multilingual tweet intimacy dataset (MINT) suggested as a task of SemEval 2023⁶⁴. Tweets of six languages labeled in score 1-5 are used in both training and test (each 2K instances), and also tweets of four languages including Korean are used only for zero-shot evaluation (each 500 instances).

IWSLT 2023 [int'l, all, rd]
holds a formality track that accommodates research in formality translation, where the released dataset consists of 1,000 pairs for en-ko and en-vi each, and 600 zero-shot examples each for en-pt and en-ru⁶⁵. Each pair includes a source English sentence and an informal/formal version of the sentence in the target language.

3.8 Speech corpora

Though most of the datasets discussed in this paper are in text format, we also incorporate speech corpora which can be usefully utilized in speech recognition, speech synthesis, or spoken language processing. Speech datasets are usually massive, that a downloading via a single click is not necessarily guaranteed. Thus, we listed some of them as open even if they require some application form.

KSS [doc, academic, rd]
Park (2018) is a book corpus read by a female voice

⁶¹<https://github.com/google-research-datasets/tydiqa>

⁶²<https://github.com/HLTCHKUST/Xpersona>

⁶³<https://registry.opendata.aws/multiconer/>

⁶⁴<https://sites.google.com/umich.edu/semEval-2023-tweet-intimacy/home>

⁶⁵<https://iwslt.org/2023/formality>

actress. 12K speech utterances and transcriptions are provided⁶⁶.

Zeroth [doc, all, rd]
is an automatic speech recognition (ASR) dataset that contains approximately 50 hours of well-refined training data⁶⁷. The speech corpus is provided free upon request and can be utilized for both research and commercial purposes.

ClovaCall [int'l, academic, none]
[Ha et al. \(2020\)](#) is an ASR dataset that consists of approximately 80 hours of telephone speech⁶⁸. The corpus is provided upon request, for only research purposes.

Pansori-TED×KR [int'l, academic, rd/mod-x]
[Choi and Lee \(2018\)](#) is an ASR dataset obtained by extracting the voices of Korean speakers from Pansori (Korean traditional song in colloquial style) and TED videos, with the transcription augmented⁶⁹. The total reaches 3 hours, but it incorporates unique phonations that are not viable in other datasets.

ProSem [int'l, all, rd]
[Cho et al. \(2019\)](#) is a spoken language understanding corpus for syntactic ambiguity resolution in Korean, classifying spoken utterances into 7 speech acts⁷⁰. For about 7,100 utterances recorded by two speakers, namely a male and a female, the ground truth text and label are annotated along with the English translation.

kosp2e [int'l, academic, rd]
[Cho et al. \(2021\)](#) is a Korean speech to English text translation dataset that consists of 30K utterances and their Korean script/English translation⁷¹. The dataset is based on four publicly available corpora, and the license follows each source corpus. It covers various text domains such as news, textbook, AI agent and diary, and all translations were manually performed.

JIT/JSS [int'l, all, rd]
[Park et al. \(2020\)](#) are datasets containing audio

files recorded by a native Jeju speaker, along with transcript files⁷².

3.9 Other topics

Here, we accommodate other Korean datasets that are substantial in their quantity, quality, and documentation, but were not discussed in the previous sections.

KoCHET [int'l, academic, unk]
[Kim et al. \(2022\)](#) is a Korean cultural heritage corpus for Entity-related Tasks, covering the area of named entity recognition, relation extraction (RE), and entity typing (ET), consisting of 112K NER, 38K RE, and 113K ET examples⁷³. The construction of the dataset was advised by cultural heritage experts of Korea, and the modified redistribution is allowed for worldwide researchers.

KommonGen [int'l, all, rd]
[Seo et al. \(2021\)](#) is a Korean-generated dataset that translates MS-COCO data captions into Korean and uses them for generalized common sense inference⁷⁴. Though only partly available, the team expanded the research to be internationally available ([Seo et al., 2022](#)) and published the official train set (43K instances) and test set (2K instances) online. The full dataset is available in AI HUB, a government-driven dataset hub for Korean AI, but the access is restricted only to Korean citizens⁷⁵.

LBox Open [int'l, academic, rd]
[Hwang et al. \(2022\)](#) is a multi-task benchmark for Korean legal language understanding and judgment prediction, where the precedent corpus consists of 150K cases of Korean legal precedent (80K from law open data and 70K from the creator's own database)⁷⁶. Tasks include case name classification (100 classes, 10K pairs), statute classification (46 classes, 2,760 pairs), fine/imprisonment range prediction (10K examples), summarization, etc.

K2NLG [doc, academic, rd]
is a dataset for the task of generating summaries from knowledge sets (or knowledge graphs). The

⁶⁶<https://www.kaggle.com/bryanpark/korean-single-speaker-speech-dataset>

⁶⁷<https://github.com/goodatlas/zeroth>

⁶⁸<https://github.com/clovaai/ClovaCall>

⁶⁹<https://github.com/yc9701/pansori-tedxkr-corpus>

⁷⁰<https://github.com/warnikchow/prosem>

⁷¹<https://github.com/warnikchow/kosp2e>

⁷²<https://github.com/kakaobrain/jejueo>

⁷³<https://github.com/Gyeongmin47/>

[KoCHET-A-Korean-Cultural-Heritage-corpus-for-Entity-r](#)

⁷⁴<https://github.com/nlpai-lab/>

[KommonGen](#)

⁷⁵<https://aihub.or.kr/aihubdata/data/view.do?currMenu=120&topMenu=100&aihubDataSe=extrldata&dataSetSn=459>

⁷⁶<https://github.com/lbox-kr/lbox-open>

object types and relationships of the target knowledge in the model follow the KBox ontology⁷⁷.

Korean Ambiguity Dataset

[int'l, all, rd]

Bareun (2023) is a word sense disambiguation task constructed by Bareun NLP in collaboration with Seoul National University Korean linguistics department, which contains 35K sentences and about 8,200 surface forms of Korean⁷⁸. It aims at building a comprehensive and objective benchmark on the morpheme-level decomposition of Korean sentences.

Korean GEC dataset

[int'l, academic, rd]

Yoon et al. (2022) is a secondary-processed dataset for correcting grammatical errors in Korean, derived from the Korean language learner corpus. The Korean GEC dataset can only be used under the same license as the original data⁷⁹.

4 Summary

In total, we surveyed 62 corpora, namely 40 Korean text corpora, 14 multilingual corpora, and 8 speech corpora. They are composed of 2 benchmark studies, 10 datasets on parsing and tagging, 6 datasets on entailment, sentence similarity, and paraphrase, 11 datasets on intention understanding, sentiment analysis, and offensive language detection, 5 datasets on QA and dialogue, 7 datasets on summarization, translation, and transliteration, 7 datasets on Korean in multilingual corpora, 8 datasets on speech (pre-)processing, and 6 Korean datasets on other underclassified topics⁸⁰. We highlight the advent of Korean-specific benchmark datasets and the increasing number of datasets concerning offensive language, which highly concerns the prevalence of large LMs and PLM studies regarding evaluation and risk prevention. We deem that this trend is not temporary, but the future trend is currently obscure due to the decreased need of task-specific corpora. We will update the full specification table of datasets in our github repository⁸¹.

⁷⁷<https://github.com/machinereading/K2NLG-Dataset>

⁷⁸<https://github.com/bareun-nlp/korean-ambiguity-data>

⁷⁹https://github.com/soyoung97/standard_korean_gec

⁸⁰Note that these statistics do not incorporate the datasets provided by NIKL, ETRI, and AI HUB.

⁸¹<https://github.com/ko-nlp/Open-korean-corpora#view-at-a-glance>

Documentation Ensuring that a curated list of resources is up-to-date is a challenge. In this regard, we aim to make our work open and canonical, as an online repository of curated resources for Korean. For the research community to have unconstrained access to all current open resources, while endorsing community contributions, the following criteria are crucial:

- The canonical, current version of this paper will be regularly published as a revision, e.g., on arxiv.org, based on a community-open version of this paper.
- The resources will also have a corresponding registry, following the same metadata protocol for usability in different types of research, as we used in this protocol.
- Each new contribution to the resource list will have a corresponding entry in the acknowledgments section.

We will make the registry machine parseable, so that other curated sites such as nlpprogress.com, can utilize the registry to automate updates. The project will be maintained as an open-source project, under a permissive license. A living document is a new territory for the field of academia, but we strongly believe that given the rapid progress of NLP research, this is an experiment worth attempting; and hope that a successful effort can inspire other languages to follow the same approach. Our approach is to be described in the public repository, guaranteeing the accessibility for domestic and abroad researchers. Also, a large portion of the data are expected to be more easily accessible via Koco⁸² and Korpora⁸³, the recently constructed dataset wrappers for Korean NLP.

Limitation Given recent developments in building Korean PLMs, the need for (commercially) available Korean raw texts has become significant in both industry and open source domains. Though a large portion of government or institution-driven corpora suffices such need, and also Korean web texts have been managed within multilingual web crawl corpora disclosed in venues such as LREC, we have not covered those raw texts in this paper since both types of corpora (namely annotated ones and those for PLM pretraining) differs a lot in terms of the cleanliness/format of the data and the objective of construction. For sure, one may

⁸²<https://github.com/inmoonlight/koco>

⁸³<https://github.com/ko-nlp/Korpora>

utilize the annotated corpora in their pretraining of PLMs and vice versa – that is, annotate a part of massive raw text for some specific tasks, but we deemed that the survey on raw texts can be handled more thoroughly within reports of open source (or industry-driven) Korean PLM building projects such as Polyglot (Ko et al., 2022), and will possibly redirect the readers to that region for a better opportunity of knowledge.

Another limitation of our study is that, while recent development of large language models such as ChatGPT⁸⁴ has brought a wave of change in data annotation and construction schemes, our study is still focused on datasets that are built in conventional ways – manual or semi-automatic. We believe that human-generated or human-annotated datasets are still a valuable reference for machine annotation, prompting, or future studies of human behaviors or thoughts, especially in Korean NLP, where the model-centric researches are actively ongoing but computational analysis of language data is still less highlighted.

5 Conclusion

In this paper, we investigated the Korean NLP datasets constructed and released as public resources. Our curation suggests a variety of open corpora that are freely available. This information will not only be helpful for the Korean researchers who want to start NLP, but also for the abroad ones who are interested in Korean NLP. Nonetheless, we think that Korean open corpora are still less disclosed or not yet sufficient. It is notable that the Korean government is currently supplying substantial funds to build a database. To guide this well, appropriate management and documentation should be guaranteed, so that the construction is meaningful and the outcome is internationally available.

Acknowledgments

The authors are grateful for all the contributors of the open Korean corpora. Special thanks goes to Seungyoung Lim, Jiyeon Ham, Jiyeon Han, Hyunjoong Kim and Jihyung Moon for checking and proofreading. We also appreciate team Ko-NLP for accommodating the public repository of our project.

References

- Sanghwan Bae, Donghyun Kwak, Sungdong Kim, Donghoon Ham, Soyoung Kang, Sang-Woo Lee, and Woomyoung Park. 2022. [Building a role specified open-domain dialogue system leveraging large-scale language models](#). In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 2128–2150, Seattle, United States. Association for Computational Linguistics.
- Team Bareun. 2023. [Korean morpheme disambiguation evaluation dataset](https://github.com/bareun-nlp/korean-ambiguity-data). <https://github.com/bareun-nlp/korean-ambiguity-data>.
- Samuel R. Bowman, Gabor Angeli, Christopher Potts, and Christopher D. Manning. 2015. [A large annotated corpus for learning natural language inference](#). pages 632–642.
- Daniel Cer, Mona Diab, Eneko Agirre, Iñigo Lopez-Gazpio, and Lucia Specia. 2017. [SemEval-2017 task 1: Semantic textual similarity multilingual and crosslingual focused evaluation](#). pages 1–14.
- Yunam Cheong, Youngsook Song, and Hyun-Jo You. 2022. [konne: A korean nested named entity corpus](#). In *Proceedings of the World Convention of the Korean Language*. The Society of Korean Linguistics.
- Soyoung Cho, Sangchun Ha, Myeonghyeon Ryu, Bitna Keum, and Kyubyong Park. 2022a. [DKTC, dataset of korean threatening conversations](https://github.com/tunib-ai/DKTC). <https://github.com/tunib-ai/DKTC>.
- Won Ik Cho, Jeonghwa Cho, Jeemin Kang, and Nam Soo Kim. 2019. [Prosody-semantics interface in Seoul Korean: Corpus for a disambiguation of wh-intervention](#). In *Proceedings of the 19th International Congress of the Phonetic Sciences (ICPhS 2019)*, pages 3902–3906.
- Won Ik Cho, Jong In Kim, Young Ki Moon, and Nam Soo Kim. 2020a. [Discourse component to sentence \(DC2S\): An efficient human-aided construction of paraphrase and sentence similarity dataset](#). In *Proceedings of The 12th Language Resources and Evaluation Conference*, pages 6819–6826.
- Won Ik Cho and Nam Soo Kim. 2022. [Text implicates prosodic ambiguity: A corpus for intention identification of the korean spoken language](#). *ACM Trans. Asian Low-Resour. Lang. Inf. Process.*, 22(1).
- Won Ik Cho, Seok Min Kim, Hyunchang Cho, and Nam Soo Kim. 2021. [kosp2e: Korean Speech to English Translation Corpus](#). In *Proc. Interspeech 2021*, pages 3705–3709.
- Won Ik Cho, Sangwhan Moon, Jongin Kim, Seokmin Kim, and Nam Soo Kim. 2022b. [StyleKQC: A style-variant paraphrase corpus for Korean questions and commands](#). In *Proceedings of the Thirteenth Language Resources and Evaluation Conference*, pages

⁸⁴<https://openai.com/blog/chatgpt>

- 7122–7128, Marseille, France. European Language Resources Association.
- Won Ik Cho, Sangwhan Moon, and Youngsook Song. 2020b. [Open Korean corpora: A practical report](#). In *Proceedings of Second Workshop for NLP Open Source Software (NLP-OSS)*, pages 85–93, Online. Association for Computational Linguistics.
- Won Ik Cho, Youngki Moon, Sangwhan Moon, Seok Min Kim, and Nam Soo Kim. 2020c. [Machines getting with the program: Understanding intent arguments of non-canonical directives](#). In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pages 329–339, Online. Association for Computational Linguistics.
- Key-Sun Choi, Young S Han, Young G Han, and Oh W Kwon. 1994. KAIST tree bank project for Korean: Present and future development. In *Proceedings of the International Workshop on Sharable Natural Language Resources*, pages 7–14. Citeseer.
- Yoon Choi and Bowon Lee. 2018. Pansori: ASR corpus generation from open online video contents. *arXiv preprint arXiv:1812.09798*.
- Jayeol Chun, Na-Rae Han, Jena D Hwang, and Jinho D Choi. 2018. Building universal dependency treebanks in Korean. In *Proceedings of the Eleventh International Conference on Language Resources and Evaluation (LREC 2018)*.
- Jonathan H. Clark, Eunsol Choi, Michael Collins, Dan Garrette, Tom Kwiatkowski, Vitaly Nikolaev, and Jennimaria Palomaki. 2020. [TyDi QA: A benchmark for information-seeking question answering in typologically diverse languages](#). *Transactions of the Association for Computational Linguistics*, 8:454–470.
- Alexis Conneau, Ruty Rinott, Guillaume Lample, Adina Williams, Samuel Bowman, Holger Schwenk, and Veselin Stoyanov. 2018. [XNLI: Evaluating cross-lingual sentence representations](#). pages 2475–2485.
- Aniruddha Ghosh and Tony Veale. 2016. [Fracking sarcasm using neural network](#). In *Proceedings of the 7th Workshop on Computational Approaches to Subjectivity, Sentiment and Social Media Analysis*, pages 161–169, San Diego, California. Association for Computational Linguistics.
- Kyle Gorman, Lucas FE Ashby, Aaron Goyzueta, Arya D McCarthy, Shijie Wu, and Daniel You. 2020. The SIGMORPHON 2020 shared task on multilingual grapheme-to-phoneme conversion. In *Proceedings of the 17th SIGMORPHON Workshop on Computational Research in Phonetics, Phonology, and Morphology*, pages 40–50.
- Jung-Woo Ha, Kihyun Nam, Jin Gu Kang, Sang-Woo Lee, Sohee Yang, Hyunhoon Jung, Eunmi Kim, Hyeji Kim, Soojin Kim, Hyun Ah Kim, et al. 2020. ClovaCall: Korean goal-oriented dialog speech corpus for automatic speech recognition of contact centers. *arXiv preprint arXiv:2004.09367*.
- Jiyeon Ham, Yo Joong Choe, Kyubyong Park, Ilji Choi, and Hyungjoon Soh. 2020. KorNLI and KorSTS: New benchmark datasets for Korean natural language understanding. *arXiv preprint arXiv:2004.03289*.
- Chung-hye Han, Na-Rae Han, Eon-Suk Ko, Martha Palmer, and Heejong Yi. 2001. Penn Korean Treebank: Development and evaluation. In *Proceedings of the 16th Pacific Asia Conference on Language, Information and Computation*, pages 69–78.
- Gyeong-Eun Han, Seul-Ye Baek, and Jae-Soo Lim. 2017. Open sourced and collaborative method to fix errors of Sejong morphologically annotated corpora. In *Annual Conference on Human and Language Technology*, pages 228–232. Human and Language Technology.
- Wonseok Hwang, Dongjun Lee, Kyoungyeon Cho, Hanuhl Lee, and Minjoon Seo. 2022. A multi-task benchmark for korean legal language understanding and judgement prediction. *arXiv preprint arXiv:2206.05224*.
- Myeongjun Jang, Dohyung Kim, Deuk Sin Kwon, and Eric Davis. 2022. Kobest: Korean balanced evaluation of significant tasks. In *Proceedings of the 29th International Conference on Computational Linguistics*, pages 3697–3708.
- Younghoon Jeong, Juhyun Oh, Jongwon Lee, Jaimeen Ahn, Jihyung Moon, Sungjoon Park, and Alice Oh. 2022. [KOLD: Korean offensive language dataset](#). In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 10818–10833, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.
- TaeYoung Kang, Eunrang Kwon, Junbum Lee, Youngeun Nam, Junmo Song, and JeongKyu Suh. 2022. Korean online hate speech dataset for multilabel classification: How can social science aid developing better hate speech dataset? *arXiv preprint arXiv:2204.03262*.
- Gyeongmin Kim, Jinsung Kim, Junyoung Son, and Heuseok Lim. 2022. [KoCHET: A Korean cultural heritage corpus for entity-related tasks](#). In *Proceedings of the 29th International Conference on Computational Linguistics*, pages 3496–3505, Gyeongju, Republic of Korea. International Committee on Computational Linguistics.
- Hansaem Kim. 2006. Korean national corpus in the 21st century Sejong project. In *Proceedings of the 13th NIJL International Symposium*, pages 49–54. National Institute for Japanese Language Tokyo.
- Jiwon Kim and Won Ik Cho. 2019. Kocasm: Korean automatic sarcasm detection. <https://github.com/SpellOnYou/korean-sarcasm>.

- Seonghyun Kim. 2022a. Korean unsmile dataset: Human-annotated multi-label korean hate speech dataset. https://github.com/smilegate-ai/korean_unsmile_dataset.
- Seonghyun Kim. 2022b. Smilestyle: Parallel style-variant corpus for korean multi-turn chat text dataset. https://github.com/smilegate-ai/korean_smile_style_dataset.
- Hyunwoong Ko, Kichang Yang, Minho Ryu, Taekyoon Choi, Seungmu Yang, jiwung Hyun, and Sungho Park. 2022. Polyglot-Ko: Open-Source Korean Autoregressive Language Model.
- Tom Kwiatkowski, Jennimaria Palomaki, Olivia Redfield, Michael Collins, Ankur Parikh, Chris Alberti, Danielle Epstein, Illia Polosukhin, Jacob Devlin, Kenton Lee, et al. 2019. Natural questions: a benchmark for question answering research. *Transactions of the Association for Computational Linguistics*, 7:453–466.
- Jackson L. Lee, Lucas F.E. Ashby, M. Elizabeth Garza, Yeonju Lee-Sikka, Sean Miller, Alan Wong, Arya D. McCarthy, and Kyle Gorman. 2020. Massively multilingual pronunciation modeling with WikiPron. In *Proceedings of the 12th Language Resources and Evaluation Conference*, pages 4223–4228, Marseille, France. European Language Resources Association.
- Jean Lee, Taejun Lim, Heejun Lee, Bogeun Jo, Yangsok Kim, Heegeun Yoon, and Soyeon Caren Han. 2022a. K-MHaS: A multi-label hate speech detection dataset in Korean online news comment. In *Proceedings of the 29th International Conference on Computational Linguistics*, pages 3530–3538, Gyeongju, Republic of Korea. International Committee on Computational Linguistics.
- Woon-Jae Lee, Sun-Bae Kim, Gil-Yeon Kim, and Key-Sun Choi. 1999. Implementation of modularized morphological analyzer. In *Proceedings of the Annual Conference on Human and Language Technology*, pages 123–136.
- Yoon Kyung Lee, Won Ik Cho, Seoyeon Bae, Hyunwoo Choi, Jisang Park, Nam Soo Kim, and Sowon Hahn. 2022b. "feels like i've known you forever": empathy and self-awareness in human open-domain dialogs.
- Seungyoung Lim, Myungji Kim, and Jooyoul Lee. 2019. KorQuAD 1.0: Korean QA dataset for machine reading comprehension. *arXiv preprint arXiv:1909.07005*.
- Zhaojiang Lin, Zihan Liu, Genta Indra Winata, Samuel Cahyawijaya, Andrea Madotto, Yejin Bang, Etsuko Ishii, and Pascale Fung. 2020. XPersona: Evaluating multilingual personalized chatbot. *arXiv preprint arXiv:2003.07568*.
- Andrew L. Maas, Raymond E. Daly, Peter T. Pham, Dan Huang, Andrew Y. Ng, and Christopher Potts. 2011. Learning word vectors for sentiment analysis. In *Proceedings of the 49th Annual Meeting of the Association for Computational Linguistics: Human Language Technologies*, pages 142–150, Portland, Oregon, USA. Association for Computational Linguistics.
- Shervin Malmasi, Anjie Fang, Besnik Fetahu, Sudipta Kar, and Oleg Rokhlenko. 2022. MultiCoNER: A large-scale multilingual dataset for complex named entity recognition. In *Proceedings of the 29th International Conference on Computational Linguistics*, pages 3798–3809, Gyeongju, Republic of Korea. International Committee on Computational Linguistics.
- Ryan McDonald, Joakim Nivre, Yvonne Quirnbach-Brundage, Yoav Goldberg, Dipanjan Das, Kuzman Ganchev, Keith Hall, Slav Petrov, Hao Zhang, Oscar Täckström, et al. 2013. Universal dependency annotation for multilingual parsing. In *Proceedings of the 51st Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 92–97.
- Jihyung Moon, Won Ik Cho, and Junbum Lee. 2020. BEEP! Korean corpus of online news comments for toxic speech detection. pages 25–31.
- Sangwhan Moon, Won Ik Cho, Hye Joo Han, Naoaki Okazaki, and Nam Soo Kim. 2022. OpenKorPOS: Democratizing Korean tokenization with voting-based open corpus annotation. In *Proceedings of the Thirteenth Language Resources and Evaluation Conference*, pages 4975–4983, Marseille, France. European Language Resources Association.
- Tae Hwan Oh, Ji Yoon Han, Hyonsu Choe, Seokwon Park, Han He, Jinho D. Choi, Na-Rae Han, Jena D. Hwang, and Hansaem Kim. 2020. Analysis of the Penn Korean Universal Dependency treebank (PKT-UD): Manual revision to build robust parsing model in Korean. pages 122–131.
- Jungyeul Park, Jeon-Pyo Hong, and Jeong-Won Cha. 2016. Korean language resources for everyone. In *Proceedings of the 30th Pacific Asia conference on language, information and computation: Oral Papers*, pages 49–58.
- Kyubyong Park. 2018. KSS dataset: Korean single speaker speech dataset.
- Kyubyong Park, Yo Joong Choe, and Jiyeon Ham. 2020. Jejueo datasets for machine translation and speech synthesis. In *Proceedings of the 12th International Conference on Language Resources and Evaluation (LREC 2020)*.
- San-hee Park, Kang-min Kim, O-joun Lee, Youjin Kang, Jaewon Lee, Su-min Lee, and Sangkeun Lee. 2023. "why do I feel offended?" - Korean dataset for offensive language identification. In *Findings*

- of the Association for Computational Linguistics: *EACL 2023*, pages 1112–1123, Dubrovnik, Croatia. Association for Computational Linguistics.
- Sungjoon Park, Jihyung Moon, Sungdong Kim, Won Ik Cho, Jiyeon Han, Jangwon Park, Chisung Song, Junseong Kim, Yongsook Song, Taehwan Oh, et al. 2021. Klue: Korean language understanding evaluation. *arXiv preprint arXiv:2105.09680*.
- Jiaxin Pei, Vítor Silva, Maarten Bos, Yozon Liu, Leonardo Neves, David Jurgens, and Francesco Barbieri. 2022. Semeval 2023 task 9: Multilingual tweet intimacy analysis. *arXiv preprint arXiv:2210.01108*.
- Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. 2016. SQuAD: 100,000+ questions for machine comprehension of text. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pages 2383–2392.
- Jaehyung Seo, Seounghoon Lee, Chanjun Park, Yoonna Jang, Hyeonseok Moon, Sugyeong Eo, Seonmin Koo, and Heuiseok Lim. 2022. A dog is passing over the jet? a text-generation dataset for Korean commonsense reasoning and evaluation. In *Findings of the Association for Computational Linguistics: NAACL 2022*, pages 2233–2249, Seattle, United States. Association for Computational Linguistics.
- Jaehyung Seo, Chanjun Park, Hyeonseok Moon, Sugyeong Eo, Myunghoon Kang, Seounghoon Lee, and Heuiseok Lim. 2021. Kommongen: A dataset for korean generative commonsense reasoning evaluation. In *Proceedings of the 33th Annual Conference on Human & Cognitive Language Technology*.
- Erik F Tjong Kim Sang and Fien De Meulder. 2003. Introduction to the CoNLL-2003 shared task: language-independent named entity recognition. In *Proceedings of the seventh conference on Natural language learning at HLT-NAACL 2003-Volume 4*, pages 142–147.
- Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel R Bowman. 2018. Glue: A multi-task benchmark and analysis platform for natural language understanding. *arXiv preprint arXiv:1804.07461*.
- Adina Williams, Nikita Nangia, and Samuel Bowman. 2018. A broad-coverage challenge corpus for sentence understanding through inference. pages 1112–1122.
- Kichang Yang. 2021. Transformer-based korean pre-trained language models: A survey on three years of progress. *arXiv preprint arXiv:2112.03014*.
- Kichang Yang, Wonjun Jang, and Won Ik Cho. 2022. APEACH: Attacking pejorative expressions with analysis on crowd-generated hate speech evaluation datasets. In *Findings of the Association for Computational Linguistics: EMNLP 2022*, pages 7076–7086, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.
- Yinfei Yang, Yuan Zhang, Chris Tar, and Jason Baldridge. 2019. PAWS-X: A cross-lingual adversarial dataset for paraphrase identification. pages 3687–3692.
- Soyoung Yoon, Sungjoon Park, Gyuwan Kim, Junhee Cho, Kihyo Park, Gyu Tae Kim, Minjoon Seo, and Alice Oh. 2022. Towards standardizing korean grammatical error correction: Datasets and annotation. *arXiv preprint arXiv:2210.14389*.
- Saizheng Zhang, Emily Dinan, Jack Urbanek, Arthur Szlam, Douwe Kiela, and Jason Weston. 2018. Personalizing dialogue agents: I have a dog, do you have pets too? *arXiv preprint arXiv:1801.07243*.
- Yuan Zhang, Jason Baldridge, and Luheng He. 2019. PAWS: Paraphrase adversaries from word scrambling. pages 1298–1308.