

On Unimodality of Independence Polynomials of Trees

Ron Yosef

Department of Computer Science
HIT - Holon Institute of Technology
Holon, Golomb 52, [Israel](#)
rony@my.hit.ac.il
ron-yosef.com

Matan Mizrachi

Department of Computer Science
HIT - Holon Institute of Technology
Holon, Golomb 52, [Israel](#)
matanmi@my.hit.ac.il

Or Kadrawi

Department of Computer Science
Ariel University
Ariel 4070000, [Israel](#)
orka@ariel.ac.il

December 30, 2020

Abstract

An independent set in a graph is a set of pairwise non-adjacent vertices. The independence number $\alpha(G)$ is the size of a maximum independent set in the graph G . The independence polynomial of a graph is the generating function for the sequence of numbers of independent sets of each size. In other words, the k -th coefficient of the independence polynomial equals the number of independent sets comprised of k vertices. For instance, the degree of the independence polynomial of the graph G is equal to $\alpha(G)$. In 1987, Alavi, Malde, Schwenk, and Erdős conjectured that the independence polynomial of a tree is unimodal. In what follows, we provide support to this assertion considering trees with up to 20 vertices. Moreover, we show that the corresponding independence polynomials are log-concave and, consequently, unimodal. The algorithm computing the independence polynomial of a given tree makes use of a database of non-isomorphic unlabeled trees to prevent repeated computations.

Keywords— independent set, independence polynomial, tree, log-concave sequence, unimodal sequence.

1 Introduction

The question of whether the independence polynomial of trees is unimodal is an open question. Although this is a question that has yet to be answered, it has long been conjectured that independence polynomials of trees are unimodal [15][11].

When discussing the *independence polynomial* of graphs, Alavi et al. [15] generally showed that the independence sequence of a graph G could be not unimodal. For example, the graph $K_{25} + 4K_2$ has an independence sequence of $\{1, 33, 24, 32, 16\}$, hence, its independence polynomial of $1 + 33x + 24x^2 + 32x^3 + 16x^4$ is not unimodal.

Our proof is mainly based on three algorithms. First, an algorithm that builds a unique identifier for a given tree. Second, an algorithm that computes the independence polynomial of a given tree. Third, the main algorithm, that manages the iteration and insertion of the trees.

We created a database that contains all of the unlabeled and non-isomorphic trees with up to 20 vertices. We saved the following details about each tree in our database: a sorted array of degrees, number of vertices, independence polynomial, a unique identifier (the primary key of database) and a Boolean flag representing whether the independence polynomial is unimodal. We used these details to prove our claim and to analyze the research results.

According to Cayley's formula [3], the amount of labeled trees with n vertices is n^{n-2} . Therefore, the number of labeled trees with up to 20 vertices equals to $\sum_{k=1}^{20} k^{k-2}$. However, in our case, as will be mentioned later in the article, we would like to examine only non-isomorphic unlabeled trees; hence, Cayley's formula is not useful for our objectives. The number of all the non-isomorphic unlabeled trees with up to 20 vertices is 1,346,025 [13]. After inserting all of the non-isomorphic unlabeled trees with up to 20 vertices, we showed that all trees with up to 20 vertices have a unimodal independence polynomial by running a simple SQL query. The query counted the number of trees whose unimodal flag is False. The count returned the result 0, meaning that all of the database trees have a unimodal independence polynomial. Also, we ran an SQL query that validated whether all the trees in our database have a log-concave independence polynomial.

2 Related Work

Logarithmically concave and unimodal sequences take place in many areas of mathematics, such as algebra and combinatorics (see [1] and [4]). As a well-known example, the sequence of binomial coefficients is unimodal. As been said at the beginning of the introduction, the conjecture that the independence polynomial of trees is unimodal was never proved.

However, for other different types of graphs, it was proved that their independence polynomial is unimodal.

Y. O. Hamidoune showed that the independence polynomial of every graph $G = (V, E)$, where G is claw-free, is log-concave [5]. One can easily see that the independence polynomial of a line graph, path graph, cycle graph, barbell graph, and more classes of claw-free graphs is unimodal. Moreover, Yi Wang and Bao-Xuan Zhu showed that the independence polynomial of each vertebrated graph

is log-concave, and, hence, unimodal [14]. In [10][8], V. E. Levit, E. Mandrescu proved the unimodality of independence polynomials for some well-covered trees, including centipedes and well-covered spiders.

Unlike the methods used to prove the above results, in this paper we provide a direct proof by using the brute-force method. We split our statement into a finite number of cases (1,346,025 in total [13]) and checked each case.

3 Preliminaries

This section provides basic definitions regarding the model explored throughout this paper and an introduction to the methods utilized to prove our statement.

3.1 Independence Polynomial

An *independent set* of a graph is a set of pairwise non-adjacent vertices. The independence number $\alpha(G)$ is the size of a maximum independent set in the graph $G = (V, E)$, where G is a finite, connected, undirected, loop-less graph, with vertex set V and edges set E . Following Gutman and Harary (1983) [7], the *independence polynomial* of G is defined to be:

$$I(G; x) = \sum_{n=0}^{\alpha(G)} s_n x^n = s_0 + s_1 x + s_2 x^2 + \dots + s_{\alpha(G)} x^{\alpha(G)} \quad (1)$$

where s_k denotes the number of independent sets of cardinality k in graph G , for $k \in [0, \alpha(G)] \cap \mathbb{N}$. Note that $s_0 = 1$ [10]. Readers can refer to a survey on *independence polynomials* in [11]. A finite sequence $s_k_{k=0}^{\alpha(G)} \subseteq \mathbb{N}$ is said to be:

- unimodal $\iff \exists n \in \{0, 1, \dots, \alpha(G)\}$ such that: $s_0 \leq s_1 \leq s_2 \leq \dots \leq s_n \geq s_{n+1} \geq s_{n+2} \geq \dots \geq s_{\alpha(G)}$
- log-concave $\iff \forall n \in \{1, \dots, \alpha(G) - 1\}$ $(s_n)^2 \geq s_{n-1} s_{n+1}$

If $G = (V, E)$ is a tree and $|V| \subseteq \{1, 2, \dots, 20\}$, the independence polynomial sequence of coefficients $(s_k)_{k=0}^{\alpha(G)}$ is a log-concave (therefore, an unimodal) sequence (see, for instance, [11]).

Readers can refer to [9] for reviewing log-concave independence polynomial concerning some graph products.

Throughout the entire paper, $T = (V, E)$ is an undirected, finite tree, with indexed vertex set $V = V(T)$ and edges set $E = E(T)$.

The operation that will be applied in order to delete any arbitrary set of vertices $V' \subseteq V$ and their edges, is denoted by $T - V' = T' = (V'', E')$, when $V'' = \{v \in V : v \notin V'\}$ and $E' = \{e = (u, v) \in E : v, u \notin V'\}$.

In order to prove the main result of the paper, we use the two following properties of the *independence polynomials*:

$$\begin{aligned} I(G; x) &= I(G - v; x) + x \cdot I(G - N[v]; x) : v \in V(G) \\ \forall v \in V(G), N[v] &= \{u \in V(G) : (u, v) \in E(G)\} \cup \{v\} \end{aligned} \quad (2)$$

where $N[v]$ is the neighborhood of the vertex v including v itself, and

$$\begin{aligned} G - v &= (V(G) \setminus \{v\}, E(G) \setminus e(v)) : e(v) = \{(u, v) \in E(G)\} \\ G - N[v] &= (V(G) \setminus N[v], E(G) \setminus e(N[v])) : \\ e(N[v]) &= \{(u, v) \in E(G)\} \cup \{(u, k) \in E(G - v) \cap (u, v) \in E(G)\} \end{aligned}$$

$$I(G_1 \cup G_2; x) = I(G_1; x) \cdot I(G_2; x) \quad [11][6] \quad (3)$$

An isomorphism of graphs $G_1 = (V_1, E_1) \cong G_2 = (V_2, E_2)$ is a bijection $\phi : V_1 \rightarrow V_2$ such that $\forall u, v \in V_1, (u, v) \in E_1 \iff (\phi(u), \phi(v)) \in E_2$

4 Algorithms

4.1 Unique-ID-Constructor

In order to store all of the non-isomorphic unlabeled trees in our database without any duplication, we constructed a unique identifier for each unlabeled tree. The unique identifier enables us to fetch an unlabeled tree from the database with much ease.

The unique identifier of each unlabeled tree is a unique primary key in our database. The algorithm based on the tree canonization explained and proved in [2]. Specifically, one can say that our algorithm implements methods mentioned in [2].

Table 1: Variables used in Algorithm 1 (Unique-ID-Constructor).

Variable	Definition
dist	A method that returns the distance between two input vertices that is defined by the number of edges in the shortest path connecting them.
D	An array consisting of the distances between each of the tree's vertices and the tree's root.
h	The maximum value of D.
IdArr	An array consisting of the unique ID of each sub-tree of the given tree and the unique ID of the given tree itself.
newID	A temporary array, consists of the IDs of the given vertex's neighbors, that are also farther away from the root, than the given vertex.
ϵ	An empty word.
concatenateAll	A list method that concatenates each of the input list's strings to each other ordered from left to right.
sortBinary	A list method that sorts its elements by their binary values in descending order.

Algorithm 1: Constructed a unique identifier for unlabeled tree

Input: Tree $T = (V, E, r)$
Output: T 's unique identifier
 1 $D \leftarrow \{dist(r, u), \forall u \in V\};$
 2 $h \leftarrow max\{d \in D\};$
 3 $IdArr \leftarrow \{(\epsilon, \epsilon, \dots, \epsilon) : |IdArr| = |V|\};$
 4 **for** $i \leftarrow h$ **to** 0 **do**
 5 **foreach** $v \in V$ **and** $dist(v, r) = i$ **do**
 6 **if** $i = h$ **then**
 7 $IdArr[v.index] \leftarrow '10';$
 8 **else**
 9 $newID = \{$
 10 **foreach** $u \in N(v)$ **do**
 11 $\quad \mathbf{if} \ dist(u, r) = i + 1 \ \mathbf{then}$
 12 $\quad \quad newID \leftarrow newID \cup \{IdArr[u.index]\}$
 13 $newID \leftarrow newID.sortBinary();$
 14 $IdArr[v.index] \leftarrow concatenateAll(newID);$
 15 $IdArr[v.index] \leftarrow concatenateAll(\{'1', IdArr[v.index], '0'\});$
 16 **return** $IdArr[r.index];$

The algorithm constructs an array of all the distances from the root to each vertex, and stores the maximum distance in h (line 1-2). It then initializes $IdArr$ with empty words, an array with the length of $|V|$ (line 3). Afterward, it iterates from the maximum distance (from the tree's root to another vertex) h to 0 (line 4). For each vertex v that its distance equals to i , the algorithm is doing one of two things, depending on i 's value (line 6). If i equals to h , the algorithm inserts '10' into $IdArr$ at the vertex's index (representing a leaf vertex) (lines 6-7). Otherwise, the algorithm iterates over each of v 's neighbors, denoted by u , and checks whether the distance between u and r equals to $i + 1$ (line 10-11). If so, the algorithm adds the the binary value of u 's ID to $newID$ array (line 12). At the end of this process, $newID$ array is being sorted descendingly by binary values (line 13). Now, the ID of v is the product of concatenation, from left to right, of each element in $newID$ as a string, and then the algorithm adds '1' to the beginning of v 's ID and 0 to its end (line 15-16). Once the process is done with $i = 0$, the algorithm returns the root's unique identifier (line 16).

Figure 1 constitutes an example for the algorithm, with $|V| = 4$.




Figure 1: Tree with 4 vertices

While vertex '2' is obvious to be the tree's root, and the longest distance from the root is 1 to any vertex in the tree, we want to compute the tree's unique ID. Every single vertex without considering the root itself is the root's neighbor. Thus, at the end of the very first iteration of the main loop in the algorithm, IdArr will become ['10', '10', ϵ , '10']. At the second iteration, IdArr becomes ['10', '10', '11010100', '10'], as a result of chaining '10' to itself three times, concatenating the output with the existing ϵ at the root's index in IdArr, then finalizing the process with adding '1' and '0' to both ends respectively. Meaning, '1101010' is the tree's unique ID.

4.2 Tree-Independence-Polynomial-Compute

In this subsection, we will use predefined functions designed to deal with database fetching. We can fetch independence polynomials of trees that have already been computed. Furthermore, as already been said, we can check for every input if an isomorphic tree to it exists in the database.

Table 2: Variables used in Tree-Independence-Polynomial-Compute.

Variable	Definition
DB	The database which consists of the computed trees' independence polynomials and their unique IDs.
fetchPolynomial	A database method that returns the matching independence polynomial for the input unique ID (returns NULL if the unique ID doesn't exist in the database).
exists	Holds the output of the fetchPolynomial method.
T'	An array that consists of every tree component in the output forest from $T - r$
T''	An array that consists of every tree component in the output forest from $T - N[r]$
P_1	The product of all trees', in T' , independence polynomials.
P_2	The product of all trees', in T'' , independence polynomials.

Algorithm 2: Tree-Independence-Polynomial-Compute

Input: $T = (V, E, r, uid)$
Output: $I(T; x)$, the tree's independence polynomial.

```

1  $exists \leftarrow DB.fetchPolynomial(uid);$ 
2 if  $exists \neq NULL$  then
3   | return  $exists$ ;
4 else
5   | if  $|V| = 0$  then
6     | return 1;
7   | if  $|V| = 1$  then
8     | return  $1 + x$ ;
9   |  $T' \leftarrow T - r : T' = \{T'_1 \cup T'_2 \cup \dots \cup T'_n : \forall 1 \leq i \leq n, T'_i = Tree\};$ 
10  |  $T'' \leftarrow T - N[r] : T'' = \{T''_1 \cup T''_2 \cup \dots \cup T''_m : \forall 1 \leq i \leq m, T''_i = Tree\};$ 
11  $P_1 \leftarrow 1;$ 
12  $P_2 \leftarrow 1;$ 
13 for  $1 \leq i \leq n$  do
14   |  $P_1 = P_1 \cdot TreeIndependencePolynomialCompute(T'_i);$ 
15 for  $1 \leq i \leq m$  do
16   |  $P_2 = P_2 \cdot TreeIndependencePolynomialCompute(T''_i);$ 
17 return  $I(T; x) = P_1 + x \cdot P_2;$ 

```

The algorithm receives a tree. If the tree exists in the database, then the algorithm does not compute its independence polynomial. Instead, it fetches the polynomial from the database and returns the output (lines 1-3). Otherwise, the algorithm computes the tree's independence polynomial (lines 4-16). We have decided not to keep the two trees, which have one vertex or no vertices at all, so the algorithm returns the independence polynomial of those kinds of trees without any real-time computations. If the size of V equals 0, the algorithm return 1, and if the size of V equals 1, the algorithm returns $1 + x$ (lines 5-8). In each of other cases, the algorithm removes r and $N[r]$, separately, from $T = (V, E)$, and constructs two arrays, consisting of the tree components of the resulted forests $T - r$ and $T - N[r]$, T' and T'' , respectively (lines 9-10). At this point, the algorithm calls itself recursively with each of the trees in T' and computing the output product, then does the same for the trees in T'' . The products being stored in P_1 and P_2 respectively (lines 13-16). The algorithm ends with returning the independence polynomial of $T = (V, E)$ as $P_1 + x \cdot P_2$ (line 17).

Figure 2 constitutes an example for the algorithm, with $|V| = 7$.




Figure 2: $T = (V, E)$

The algorithm receives Figure 2, and then it constructs T' as an array of two P_3 graphs (Figure 3), and construct T'' as an array of two P_2 graphs (Figure 3).




Figure 3: $T - r$




Figure 4: $T - N[r]$

it then computes the product of all the trees in T' and T'' as P_1 and P_2 . This computation happens instantly has P_2 graph and P_3 graph already exists in the database. Afterwords, the algorithm returns $P_1 + x \cdot P_2$ as the independence polynomial of Figure 2.

4.3 Main-Algorithm

We built an algorithm to insert all the non-isomorphic unlabeled trees with up to 20 vertices. The algorithm iterates from 2 to $k \leq 20$, where k stands for the number of vertices in a tree. The first unlabeled tree been inserted into the database was $T(V, E) : |V| = 1$, as its independence polynomial $I(T; x) = 1 + x$, which is unimodal, and its unique ID is '10'. This tree is inserted manually into the database since we are using dynamic programming in the algorithm.

In each iteration, it fetches all of the non-isomorphic unlabeled trees with $k - 1$ vertices from the database, and for each fetched unlabeled tree, it generates $k - 1$ trees with k vertices. Each generated tree results from adding a new leaf node to a different node of the tree.

Then, the Unique-ID-Constructor algorithm (4.1) is being used for each generated tree to enable us to check out the existence of any isomorphic tree, to the iterated one, in the database. In case there is no isomorphic tree in the database, the Tree-Independence-Polynomial-Compute algorithm (4.2) is being used to compute the iterated tree's independence polynomial $I(T; x)$.

At this point, $I(T; x)$ is being checked for unimodality and whether it is log-concave polynomial. We store all of these in the database and continue to the next tree. To efficiently insert all the non-isomorphic unlabeled trees with up to 20 vertices into the database, we used a mechanism to split the iterations on the trees between several instances of the following algorithm. We ran the algorithm non-stop on 20 Docker containers on a remote server for a week.

Table 3: Variables used in Algorithm 3 (Main-Algorithm).

Variable	Definition
DB	The database which consists of the computed trees' independence polynomials and their unique ID's.
fetchAllTrees	A database method that returns an array of the matching trees (re-constructed with unique IDs) for the input number of vertices.
isAllTreesInserted	A database method that compares the number [13] of inserted trees with the received vertex number to the expected number of trees with that vertex number.
Trees	Holds the output of the fetchAllTrees method.
T	A tree from the Trees array.
AllTPossible	An array consists of trees, which are made by connecting a new vertex to each of T 's vertices, one at a time.
T'	A tree from AllTPossible array.
isTreeExists	A database method that checks if a tree exists in the database.
P	Holds the output of Tree-Independence-Polynomial-Compute (algorithm 2), which is the input tree's independence polynomial.
isUni	A polynomial method that returns <i>True</i> if the input polynomial is unimodal, and <i>False</i> otherwise.
insert	A database method that inserts to the database the new given data.

Algorithm 3: Insert all the non-isomorphic unlabeled trees with up to 20 vertices

Input: Array L , which consists of the number of non-isomorphic unlabeled trees with up to 20 vertices.

Output: None

```

1 for  $2 \leq i \leq 20$  do
2    $l \leftarrow L[i]$ ;
3   if  $|DB.fetchAllTrees(|V| = i)| = l$  then
4     continue;
5   else
6      $Trees \leftarrow DB.fetchAllTrees(|V| = i - 1)$ ;
7     foreach  $T \in Trees$  do
8        $AllTPossible \leftarrow \{T \cup \{u\}_k, \forall 1 \leq k \leq i - 1 \mid T \cup \{u\}_k$  means
          connecting a vertex to the Tree via the vertex indexed with
          integer  $k\}$ ;
9       foreach  $T' \in AllTPossible$  do
10        if  $DB.isTreeExists(T'.uid)$  then
11          continue;
12        else
13           $P \leftarrow Tree\text{-Independence-Polynomial-Compute}(T')$ ;
14           $uni \leftarrow isUni(P)$ ;
15           $DB.insert(T'.uid, T'.degreeArr, |V(T')|, P, uni)$ ;
16        if  $DB.isAllTreesInserted(|V| = i, l)$  then
17          break;
```

The algorithm receives an array consisting of the number of non-isomorphic unlabeled trees with $2 \leq |V| \leq 20$. The algorithm iterates from $i = 2$ to 20. If all possible non-isomorphic unlabeled trees with i vertices are already in the database, the algorithm continues (lines 3-4). Otherwise, the algorithm fetches all of the trees with $i - 1$ vertices (line 6). It iterates over each tree and creates an array of all the possible trees with i vertices by connecting a new vertex to each existing vertex in the given tree. For each new tree, the algorithm computes its independence polynomial if it does not already exist in the database. After iterating over each new tree, the algorithm checks whether all of the possible non-isomorphic unlabeled trees with i vertices are already in the database before continuing to the next tree with $i - 1$ vertices (lines 16-17).

Figure 5 constitutes an example for the main algorithm, where $|V| = 3$.




Figure 5: $T = (V, E) : |V| = 3$

In order to insert all the non-isomorphic unlabeled trees with four vertices, the algorithm fetches all the non-isomorphic unlabeled trees with three vertices from the database (Figure 5). Then, it iterates on each of the non-isomorphic unlabeled trees with three vertices. On each tree, the algorithm constructs an array of 3 trees with four vertices by adding a new node to each of the tree's exiting nodes, one at a time (Figures 6,7,8).




Figure 6: Figure 5 with a new node connected to node number 1




Figure 7: Figure 6 with a new node connected to node number 2




Figure 8: Figure 6 with a new node connected to node number 3

The algorithm then iterates on each tree. Starting with Figure 6, the algorithm checks if the tree exists in the database. The tree does not exist in the database; therefore, the algorithm computes its independence polynomial and checks if it is unimodal before inserting it with additional data into the database. The same process also happens in Figure 7 and Figure 8. However, in Figure 8, the algorithm continues the iteration because the tree already exists in the database, since (Figure 7 is isomorphic to Figure 8).

5 Algorithms proof

5.1 Tree-Independence-Polynomial-Compute

This algorithm's main requirement is to have in the database it uses all of the trees with $V - 1$ vertices to compute the independence polynomial of a given tree with V Vertices. Thus, we assume that every $T' = (V', E', r', uid')$: $|V'| < |V|$ exists in the database.

When the algorithm receives $T = (V, E, r, uid)$, it first tries to fetch its independence polynomial from the database. If it exists, the algorithm returns the fetched polynomial. Otherwise, the algorithm computes T 's independence polynomial as mentioned in (2).

$$T' = T - r = \{T_1 \cup T_2 \cup \dots \cup T_n : 1 \leq n < |V|\}$$

$$I(T' : x) = I(T - r : x)$$

$$I(T' - r : x) = I(T_1 \cup T_2 \cup \dots \cup T_n)$$

$$I(T'_1 \cup T'_2 \cup \dots \cup T'_n) = I(T_1) \cdot I(T_2) \cdot \dots \cdot I(T_n) = P_1 \quad (\text{according to (3)})$$

$$\forall T_i \in \{T_1 \cup T_2 \cup \dots \cup T_n\}, \quad |V(T_i)| < |V(T)| \implies T_i \in DB \implies$$

$$I(T_i : x) = DB.fetchPolynomial(T_i.uid)$$

$$T'' = T - N[r] = \{T_1 \cup T_2 \cup \dots \cup T_n : 1 \leq n \leq |V| - |N[v]|\}$$

$$I(T'' : x) = I(T - N[r] : x)$$

$$I(T'' : x) = I(T_1 \cup T_2 \cup \dots \cup T_n)$$

$$I(T_1 \cup T_2 \cup \dots \cup T_n) = I(T_1) \cdot I(T_2) \cdot \dots \cdot I(T_n) = P_2 \quad (\text{according to 3})$$

$$\forall T_i \in \{T_1 \cup T_2 \cup \dots \cup T_n\}, \quad |V_{T_i}| < |V_T| \implies T_i \in DB \implies$$

$$I(T_i : x) = DB.fetchPolynomial(T_i.uid)$$

Then it returns $P_1 + x \cdot P_2$ as $I(T : x)$ as mentioned in 2;

5.2 Main-Algorithm

Lemma 5.1 Every tree with $n + 1$ vertices, where $n \geq 2$ can be constructed by adding a new leaf node to an existing node of a tree with n vertices.

Proof. Suppose a tree $T_i(V_i, E_i)$, where $|V_i| = n + 1, n \geq 2$ can not be constructed by adding a new leaf node to a tree, $T_j(V_j, E_j)$ where $|V_j| = n$. Then, removing a leaf node from T_i will not result a tree, T_j . This contradicts the fact that T_j is a connected acyclic graph with $|E_j| = |V_j| - 1$.

Corollary 5.2 A collection of all the trees with $n + 1$ vertices can be constructed, where $n \geq 2$, by adding a new leaf node to each existing node of a tree, one at a time, for all the trees with $n \geq 1$ vertices (*Lemma 5.1*).

Theorem 5.3 For every input array $L = \{s_0, s_1, s_2, s_3, \dots, s_n : s_i = \text{the number of non isomorphic trees with } i \text{ vertices}\}$, *Main-Algorithm(L)* computes the independence polynomial of each tree $T = (V, E, uid) : 2 \leq |V| \leq n$ and store the results in the DB.

Proof. For the sake of this proof, we will use strong induction.

base case: $n = 2$:

The main loop in the algorithm will be iterated once. $l = L_2 = 1$. Assuming that the DB is currently holding nothing but the data of $T = (V, E, uid) : |V| = 1$, that has been manually inserted. The first condition in the loop will not be matched, and as a result, the algorithm fetches the only graph existing in the DB, which is, as said, $T = (V, E, uid) : |V| = 1$. Then, the *AllTPossible* array is assigned as the one only possible "extended" tree for a tree with one vertex, that is, the tree with two vertices, and due to the nonexistence of the tree in the DB, the algorithm computes its independence polynomial and insert its findings to the DB. Thus, the statement is true for $n = 2$.

Inductive step: Suppose the statement is true for $n = 3, 4, \dots, k$. If $n = k + 1$, then, once again, the algorithm skips the first condition that proposed to make the algorithm continue working from the point it last stopped at; for example, in cases of a connection failure with the DB. Afterward, the algorithm fetches every non isomorphic tree $T = (V, E, uid) : |V| = k$ (we suppose all of them exist in the DB) and "extending" each of them to trees with $k + 1$ vertices by adding a new leaf node to each existing node of each tree (as Lemma 5.1). The independence polynomial of each extended tree that does not exist in the database is computed before inserting it into the database. After going through each of the trees with k vertices, the algorithm will succeed in computing the independence polynomial of every non isomorphic tree with $k + 1$ vertices (Corollary 5.2) and insert the relevant information of each tree into the DB.

6 Experimental Results

6.1 Experimental Setup

We have implemented our algorithms with Typescript and used NodeJS servers to execute our algorithms.

We have used PostgreSQL database and a Linux Ubuntu server serving as a docker server for our working environment.

In order to efficiently insert all of the non-isomorphic unlabeled trees with up to 20 vertices into the database, we used a mechanism to split the iterations on the trees between several instances of the algorithm. We have split the workload equally, ensuring that each algorithm instance will iterate on different trees from the database. We ran our algorithm 24/7 on 20 containers on our server for a week. Both the database's and the server's specifications are listed in Table 4.

Table 4: The database's and the server's specifications.

	Database	Server
CPU	8 CPU Core	1 CPU Core
RAM	16GB RAM	2GB RAM
DISK SPACE	240GB SSD	50GB SSD

Running 20 instances of our algorithm working parallel caused the database CPU to reach its limit, thus because our algorithm is frequently fetching data from the database to prevent calculation of trees that already exist in the database. Because of that, we have used the indexing feature of PostgreSQL DB to boost our database performance twice as much.

6.2 The Unimodality of The Independence Polynomial

As said above, by running a simple SQL query, we showed that all the trees with up to 20 vertices have a unimodal independence polynomial. The query counted the number of non-isomorphic unlabeled trees whose unimodal flag is False. The count returned the result 0, meaning that all of the trees with up to 20 vertices have a unimodal independence polynomial. Furthermore, we ran an SQL query that validated that all trees with up to 20 vertices have a log-concave independence polynomial.

6.3 Analysis of The Independent Sets

By applying a simple SQL query on our database, we were able to count, for every cardinality k , the number of times it satisfies the following

$$\forall T \in DB.Trees, k = ArgMax\{|S| : S = \{s_0, s_1, \dots, s_{\alpha(T)}\} \text{ and } I(T; x) = \sum_{i=0}^{\alpha(T)} s_i x^i$$

With up to 1,346,025 trees in total [13], we also found that $0 \leq k \leq 11$. Note that we considered the lower cardinal as the maximum, in case of two or more maximums.

Table 5: The number of trees satisfies the equation above, for each cardinality k .

k	Number of trees with most independent sets of cardinality k
0	2
1	0
2	3
3	23
4	239
5	3234
6	58442
7	851104
8	420209
9	12700
10	68
11	0

6.4 Different cases and examples

We have encountered several cases that are worth mentioning.

6.4.1 Identical Independence Polynomials

Theorem 7.1 Two trees can have the same *Independence Polynomial* if they have the same number of vertices.

Proof. let $T_1 = (V_1, E_1)$, $T_2 = (V_2, E_2)$ be an arbitrary trees, and

$$I_i(T_i : x) = \sum_{n=0}^{\alpha(T_i)} S_{i_n} x^n : i = 1, 2 \quad (1)$$

where S_{1_1} and S_{2_1} denote the number of independent sets of cardinality 1 in trees T_1 and T_2 respectively. For every graph $G = (V, E) : |V| = n$, there are $|V|$ independent sets of cardinality 1, which means $S_{1_1} = |V_1|$ and $S_{2_1} = |V_2|$ ([12]) $\Rightarrow I_1(T_1 : x) = I_2(T_2 : x) \Leftrightarrow |V_1| = |V_2|$. ■

Also, two trees can have the same independence polynomial, and have or not have the same sorted array of degrees.




Figure 9: Two non-isomorphic unlabeled trees with the same Independence Polynomial, and the same sorted array of degrees.

In Figure 9, both trees have the independence polynomial of $1 + 9x + 28x^2 + 37x^3 + 21x^4 + 4x^5$, and a sorted array of degrees equals to $\{3, 3, 2, 2, 2, 1, 1, 1, 1\}$.




Figure 10: Two non-isomorphic unlabeled trees with the same Independence Polynomial, and different sorted arrays of degrees.

Figure 10, Both of the trees have an independence polynomial of $1 + 8x + 21x^2 + 23x^3 + 11x^4 + 2x^5$. The left tree possesses a sorted array of degrees of $\{3, 3, 3, 1, 1, 1, 1, 1\}$, and the right tree possesses a sorted array of degrees of $\{4, 2, 2, 2, 1, 1, 1, 1\}$.

There are three independence polynomials which are most common among the trees with up to 20 vertices, and each of them can be found 25 times among all the non-isomorphic unlabeled trees with 20 vertices.

$$\begin{aligned}
 &1 + 20x + 171x^2 + 825x^3 + 2499x^4 + 5006x^5 + 6802x^6 + 6319x^7 + \\
 &\quad 3984x^8 + 1662x^9 + 435x^{10} + 64x^{11} + 4x^{12} \\
 &1 + 20x + 171x^2 + 827x^3 + 2521x^4 + 5106x^5 + 7052x^6 + 6702x^7 + \\
 &\quad 4360x^8 + 1900x^9 + 529x^{10} + 85x^{11} + 6x^{12} \\
 &1 + 20x + 171x^2 + 827x^3 + 2523x^4 + 5125x^5 + 7127x^6 + 6863x^7 + \\
 &\quad 4566x^8 + 2061x^9 + 604x^{10} + 104x^{11} + 8x^{12}
 \end{aligned}$$

6.4.2 Independence Polynomial with acceding/descending coefficients sequence

Except for P_0 and P_1 , with the polynomials of 1 and $1 + x$ respectively, we did not find any trees with acceding nor descending independence polynomial coefficients sequence.

6.4.3 Fibonacci sequence of coefficients

We found four trees of all the non-isomorphic trees with up to 20 vertices, whose independence polynomials have coefficients that are Fibonacci numbers.




Figure 11: Trees with Fibonacci numbers as independence sequence

The trees in the above figure have independence Polynomials (from left to right) as follows:

$$\begin{aligned}
 &1 + 8x + 21x^2 + 21x^3 + 8x^4 + x^5 \\
 &\quad 1 + 3x + x^2 \\
 &\quad 1 + 2x \\
 &\quad 1 + x
 \end{aligned}$$

6.4.4 Symmetrical Independence Polynomial

We found that 60 trees of all the non-isomorphic trees with up to 20 vertices have an independence Polynomial coefficients sequence that is symmetrical.




Figure 12: Several trees with symmetric independence polynomial coefficients sequence

The independence polynomials of the trees in the above figure (from left to right) are as follows:

$$\begin{aligned}
 &1 + 9x + 28x^2 + 40x^3 + 28x^4 + 9x^5 + x^6 \\
 &1 + 8x + 21x^2 + 21x^3 + 8x^4 + x^5 \\
 &1 + 6x + 10x^2 + 6x^3 + x^4
 \end{aligned}$$

7 Conclusion and Future Work

In this paper, we showed that all of the trees consists with up to 20 vertices, have a unimodal and log-concave independence polynomial.

We are considering improving our algorithm so that it will be able to run directly on all of the non-isomorphic unlabeled trees without any duplication. The algorithm will be programmed to generate unique IDs in a sequence that will enable us to efficiently iterating over all of the trees with n vertices. Such a sequence will not include two ids representing the same unlabeled tree.

References

- [1] E. A. Bender and E. R. Canfield. Log-concavity and related properties of the cycle index polynomials. *Journal of Combinatorial Theory, Series A*, 74:57–70, 1996.
- [2] Samuel R. Buss. Alogtime algorithms for tree isomorphism, comparison, and canonization. *Kurt Gödel Colloquium on Computational Logic and Proof Theory*, 5:18–33, 1997.
- [3] A Cayley. A theorem on trees. *The Quarterly Journal of Mathematics*, 23:376–378, 1889.
- [4] W. M. B. Dukes. On a unimodality conjecture in matroid theory. *Discrete Mathematics and Theoretical Computer Science*, 5:181–190, 2002.

- [5] Yahya Ould Hamidoune. On the numbers of independent k -sets in a claw free graph. *Journal Of Combinatorial Theory, Series B*, 50:241–244, 1990.
- [6] Cornelis Hoede and Xueliang Li. Clique polynomials and independent set polynomials of graphs. *Discrete Mathematics*, 125:219–228, 1994.
- [7] F. Harary I. Gutman. Generalizations of the matching polynomial. *Utilitas Mathematica*, 24:97–106, 1983.
- [8] V. E. Levit and E. Mandrescu. On well-covered trees with unimodal independence polynomials. *Congressus Numerantium*, 159:193–202, 2002.
- [9] V. E. Levit and E. Mandrescu. Graph products with log-concave independence polynomials. *WSEAS Transactions on Mathematics*, 3:487–493, 2004.
- [10] Vadim E. Levit and Eugen Mandrescu. On unimodality of independence polynomials of some well-covered trees. *Discrete Mathematics and Theoretical Computer Science*, 4:237–256, 2003.
- [11] Vadim E. Levit and Eugen Mandrescu. The independence polynomial of a graph - a survey. *International Conference on Algebraic Informatics, Aristotle University of Thessaloniki*, 1:231–252, 2005.
- [12] T.S. Michael and William N. Traves. Independence sequences of well-covered graphs: non-unimodality and the roller-coaster conjecture. *Graphs and Combinatorics*, 19:403–411, 2003.
- [13] N. J. A. Sloane. Number of trees with n unlabeled nodes. Available at <http://oeis.org/A000055>.
- [14] Y. Wang and B. X. Zhu. On the unimodality of independence polynomials of some graphs. *European Journal of Combinatorics*, 32:10–20, 2011.
- [15] P. Malde Y. Alavi, P. Erdős and A. Schwenk. The vertex independence sequence of a graph is not constrained. *Congressus Numerantium*, 58:15–23, 1987.