# Triangle Centrality

Paul Burkhardt \*

April 30, 2021

#### Abstract

Triangle centrality is introduced for finding important vertices in a graph based on the concentration of triangles surrounding each vertex. An important vertex in triangle centrality is at the center of many triangles, and therefore it may be in many triangles or none at all.

Given a simple, undirected graph G = (V, E), with n = |V| vertices and m = |E| edges, where N(v) is the neighborhood set of v,  $N_{\triangle}(v)$  is the set of neighbors that are in triangles with v, and  $N_{\triangle}^{+}(v)$  is the closed set that includes v, then the triangle centrality for v, where  $\triangle(v)$  and  $\triangle(G)$  denote the respective triangle counts of v and G, is given by

$$TC(v) = \frac{\frac{1}{3} \sum_{u \in N_{\triangle}^{+}(v)} \triangle(u) + \sum_{w \in \{N(v) \setminus N_{\triangle}(v)\}} \triangle(w)}{\triangle(G)}.$$

It follows that the vector of triangle centralities for all vertices is

$$\mathbf{C} = \frac{\left(3A - 2\check{T} + I\right)T\mathbf{1}}{\mathbf{1}^{\top}T\mathbf{1}},$$

where A is adjacency matrix of G, I is the identity matrix,  $\mathbf{1}$  is the vectors of all ones, and the elementwise product  $A^2 \circ A$  gives T, and  $\check{T}$  is the binarized analog of T.

We give optimal algorithms that compute triangle centrality in  $O(m^{3/2})$  time and O(m+n) space. Using fast matrix multiplication it takes  $n^{\omega+o(1)}$  time where  $\omega$  is the matrix product exponent.

On a Concurrent Read Exclusive Write (CREW) Parallel Random Access Memory (PRAM) machine, we give a near work-optimal algorithm that takes  $O(\log n)$  time using  $O(m\sqrt{m})$  CREW PRAM processors. In MapReduce, we show it takes four rounds using  $O(m\sqrt{m})$  communication bits, and is therefore optimal.

We also give a deterministic algorithm to find the triangle neighborhood and triangle count of each vertex in  $O(m\sqrt{m})$  time and O(m+n) space. It can be also easily be computed in  $O(m\bar{\delta}(G))$  expected time, where  $\bar{\delta}(G)$  is the average graph degeneracy and is related to the arboricity. We leave it as an open problem to deterministically compute triangle neighbors in  $O(m\bar{\delta}(G))$  time and O(m+n) space.

Our empirical results demonstrate that triangle centrality uniquely identified central vertices thirty-percent of the time in comparison to five other well-known centrality measures, while being asymptotically faster to compute on sparse graphs than all but the most trivial of these other measures.

Keywords: graph, triangle, centrality, algorithm, parallel, pram, mapreduce

## 1 Introduction

Given a network of entities, namely a graph G = (V, E) with a set of n = |V| vertices connected by a set of m = |E| edges, we wish to know the most important vertices in the graph. This clearly has many applications in web search, network routing, or simply identifying influential individuals in society and media. We introduce a new graph centrality that models influence by the concentration of triangles around a vertex. Here, a triangle is a fully-connected graph of three vertices, and is both a 3-clique and a 3-cycle.

The fundamental concept of a central or important vertex in a graph is not well-defined. There is no precise, singular mathematical definition of importance or influence in a graph. Hence the notion of centrality can take different meanings, which has led to many graph centrality measures. See [7,9,27,59,65] for a more comprehensive survey. We also stress that the centrality measures we'll discuss rely on the topology of a

<sup>\*</sup>Research Directorate, National Security Agency, Fort Meade, MD 20755. Email: pburkha@nsa.gov

graph and therefore importance derived from the structural property of the network may not align with importance denoted by actual roles and functions of the real-world entities represented in the graph. The degree of success with centrality measures therefore relies on how closely the structural network aligns with the semantic or functional network.

Triangles in graphs indicate cohesiveness, meaning increased interconnections among vertices. If an individual has two friends and these two friends are also friends, then the trio is more cohesive. A concentration of triangles indicates increased network density, thereby allowing information and influence to spread more rapidly because there are more connected pathways. Given a social network in which every pair of vertices are connected, thus the graph is a clique, then any individual can give information to any other in a single step. This represents maximum cohesion and the graph would have the maximum number of triangles possible, e.g. it would have  $\binom{n}{3}$  triangles for a clique of n vertices. The role of triangles in cohesive networks was formally developed by Friggeri et al. in 2011 [36], but cohesive networks based on triangles was explored earlier with the introduction of the k-truss by Cohen in 2005 [24], later published in 2009 [25]. The k-truss is a maximal subgraph in which each edge is incident to k triangles. See [18] for a more complete analysis of graph trusses. The importance of triangles was recognized earlier in 1998 when Watts and Strogatz [70] found that triangles were integral to the property of real-world networks, and introduced the clustering coefficient as a measure of how likely a pair of neighbors of a vertex may themselves be directly connected. More precisely, the clustering coefficient is the ratio of the triangle count of a vertex to its maximum possible triangle count. Triangles are also a key component of clusters in social networks [57,60,61].

Our new triangle centrality [16] is based on the sum of triangle counts for a vertex and its neighbors, normalized over the total triangle count in the graph. We also treat triangle neighbors of a vertex distinctly from other neighbors of that vertex. For a vertex v to be important in our measure, it requires the support of two adjacent vertices  $\{u, w\}$  that must either be in a triangle with v or in a triangle with a neighbor of v. A significant implication of this is that v can be important without being in many triangles or perhaps not in any triangles. We posit that if v has neighbors u involved in many triangles, and hence are themselves important, then these u affirm that vertex v is also important. This central vertex v binds together vertices that have strong evidence of importance, without itself being in any triangles. Importance in our measure is then based on "quality" and not "quantity" of direct contacts. This is also a feature in other centrality measures. In the words of Borgatti and Everett when describing eigenvector centrality, a central actor is one who "knows everybody who is anybody" as opposed to "knows everybody" [9]. But in our measure, a vertex without triangles does not contribute to the importance of its neighbors, no matter if it has a high centrality rank. This asymmetry to the contribution of centrality is unlike other measures like eigenvector centrality in which every vertex imparts a proportion of its rank to its neighbors. Such asymmetric influence can be seen in real-world settings. For example, a leader with many followers is a central figure because the leader has followers. But being follower does not make the follower important.

We believe the stronger hypothesis required by our triangle centrality also makes it more robust to noise and adversarial gaming. This is because it requires the cooperation from a pair of connected vertices to contribute to the rank. In contrast, an adversary or cheater could inflate the rank in measures that depend heavily on direct neighbors by spamming or creating many spurious links.

We will give a precise, mathematical definition for our triangle centrality, but the reader should note that it is based on our specific notion of importance. An important vertex by our measure is therefore important by definition, but this may not align with the real-world meaning. We will justify the definition and demonstrate its efficacy with empirical results. Clearly, our centrality is of no use in triangle-free graphs, such as bipartite graphs and trees.

The runtime for computing triangle centrality is bounded by counting triangles. Any vertex v with d(v) neighbors cannot be in more than  $\binom{d(v)}{2}$  triangles, and overall there cannot be more than  $\binom{n}{3} = O(n^3)$  triangles in G. Thus it follows from  $m \leq n^2$  that there are  $\binom{\sqrt{m}}{3} = O(m\sqrt{m})$  triangles. Therefore an algorithm that counts or lists all triangles in  $O(m^{3/2})$  time is optimal, and there are many such methods that are well-known [5,15,22,23,52,63,66]. A tighter upper-bound for counting triangles is  $O(m\bar{\delta}(G))$  time, where  $\bar{\delta}(G)$  is a new parameter called the average degeneracy of a graph introduced in [18].

We will give algorithms for computing triangle centrality in  $O(m\sqrt{m})$  time and O(m+n) space. Hence our algorithms are asymptotically equivalent to triangle counting and are therefore optimal. Moreover, our algorithms complete in a constant number of steps. In contrast, iterative methods like those based on

eigenvector centrality are slower and can take many steps before converging. We also give parallel algorithms for Concurrent Read Exclusive Write (CREW) Parallel Random Access Machine (PRAM) and MapReduce models. Our CREW algorithm is nearly work-optimal, taking  $O(\log n)$  time and  $O(m\sqrt{m})$  processors. Our MapReduce algorithm takes O(1) rounds and communicates  $O(m\sqrt{m})$  bits, and is therefore optimal.

Of independent interest, we introduce an algorithm for computing the triangle neighborhood for each vertex. Although this is trivial using hash tables, it is surpisingly difficult to achieve in linear space and deterministic optimal time. A randomized algorithm can compute the triangle neighbors in  $O(m\bar{\delta}(G)) \leq O(m\sqrt{m})$  expected time. In contrast, our triangle neighbor algorithm simultaneously computes the triangle counts and triangle neighbors in  $O(m\sqrt{m})$  deterministic time and O(m+n) space using simple arrays. We leave it as an open problem to solve in  $O(m\bar{\delta}(G))$  deterministic time.

We summarize our contribution in Section 3 and set the motivation in Section 4. We define triangle centrality, compare it to standard centrality measures, and introduce basic observations in Sections 5, 6, 7. Optimal algorithms are given in Sections 8 and 9. In Section 10 we describe a practical algorithm for listing the triangle neighborhood in optimal time and linear space without relying on hash tables. Finally we compare our triangle centrality to common centrality measures in Section 11 and demonstrate runtime performance in Section 12.

## 2 Notation

All following descriptions are for simple, undirected graphs denoted by G = (V, E) with n = |V| vertices and m = |E| edges. The vertices in G are labeled [n] = 1, 2, 3...n. A complete graph of n vertices is an n-clique and is denoted by  $K_n$ . The neighborhood of a vertex v is  $N(v) = \{u|(u,v) \in E\}$ , then the number of neighbors of a vertex is its degree d(v) = |N(v)|. A path is a consecutive sequence of adjacent edges in E. The distance  $d_G(u,v)$  is the shortest-path length between vertices v and v. The diameter v is the maximum distance in v. In this paper all discussions assume that v is a connected graph, meaning a path exists between every pair of vertices. Throughout, directed edges are given in ordered-pair notation, v in the diameter v and ends with v is the v-directed edges are denoted by v is the v-directed edges are denoted by v-directed edges edges are denoted by v-directed edges edges

The local triangle count will be denoted by  $\triangle(v)$  for a vertex v and  $\triangle(G)$  for the total (global) triangle count of G. We denote the subset of neighbors in triangles with v by  $N_{\triangle}(v) = \{u \in N(v) | N(u) \cap N(v) \neq \emptyset\}$ , and if v is included then the closed triangle neighborhood of v is  $N_{\triangle}^+(v) = \{v\} \cup N_{\triangle}(v)$ . We will refer to  $N_{\triangle}^+(v)$  as the triangle core of v.

Let  $\pi: V \to 1, \ldots, n$  be an ordering on vertices in G such  $\pi(u) < \pi(v)$  if d(u) < d(v) or in the case of a tie then u < v. We will say that vertex u is a higher-ordered or higher-ranked vertex than v if  $\pi(u) > \pi(v)$ . We denote  $N_{\pi}(v) = \{u \in N(v) | \pi(u) > \pi(v)\}$  as the abbreviated adjacency set of v containing only the higher-ordered neighbors. Then  $|N_{\pi}(v)| = O(\sqrt{m})$  because a vertex v cannot have more than  $\sqrt{m}$  neighbors with higher degree, otherwise it leads to the impossible result of more than O(m) edges in G.

Let  $A \in \{0,1\}^{n \times n}$  be the symmetric adjacency matrix for G. We use the lowercase notation of a matrix for its entries, hence the  $(ij)^{th}$  entry of A is written a(i,j). Then a(i,j) = 1 indicates an  $\{i,j\}$  edge, otherwise a(i,j) = 0. For any matrix X we denote the  $j^{th}$  column vector of X by  $\mathbf{X_j}$  and the corresponding row vector by  $\mathbf{X_j}^{\top}$ , where superscript  $\top$  represents the transpose. The  $\ell_1$  norm for a column vector is given by  $\|\mathbf{X_j}\|_1 = \sum_i |x(i,j)|$ . We use  $\mathrm{tr}(X) = \sum x(i,i)$  for the trace of a square matrix, X. The support of a vector  $\mathbf{x}$ , denoted by  $\mathrm{supp}(\mathbf{x})$ , refers to the set of indices corresponding to nonzero entries in  $\mathbf{x}$ , thus  $\mathrm{supp}(\mathbf{x}) = \{i | x(i) \neq 0\}$ . Let  $\circ$  denote the Hadamard product operator for elementwise matrix multiplication. The vector  $\mathbf{1}$  is a vector of all ones, and I is the identity matrix. We use  $\check{X}$  to denote the binary (boolean) form of a matrix or vector; nonzeros take the value of 1. The graph triangle matrix  $T = A^2 \circ A$  holds the triangle counts between a vertex and its neighbors.

Throughout this paper we will use the following abbreviations defined in Table 1.

Table 1: Centrality glossary

ТС	Triangle Centrality
BC	Betweenness Centrality
CC	Closeness Centrality
DC	Degree Centrality
$\mathrm{EV}$	Eigenvector Centrality
PR	PageRank Centrality

## 3 Contribution

We introduce triangle centrality for identifying important vertices in a graph based on the sum of triangle counts for a vertex and its neighbors, adjusted for triangle neighbors, over the total triangle count in the graph. Specifically we give the following definition.

**Definition 1.** The triangle centrality TC(v) of a vertex v is given by the equation,

$$TC(v) = \frac{\frac{1}{3} \sum_{u \in N_{\triangle}^{+}(v)} \triangle(u) + \sum_{w \in \{N(v) \setminus N_{\triangle}(v)\}} \triangle(w)}{\triangle(G)}.$$
 (1)

The values for triangle centrality are bounded in the interval [0, 1] to indicate the proportion of triangles centered at a vertex. We derive an algebraic formulation for triangle centrality leading to the next definition.

**Definition 2.** The algebraic triangle centrality C for all vertices is given by the equation,

$$\mathbf{C} = \frac{\left(3A - 2\check{T} + I\right)T\mathbf{1}}{\mathbf{1}^{\top}T\mathbf{1}}.$$
 (2)

Since triangle centrality depends only upon triangle counts, and there are  $O(m^{3/2})$  possible triangles in G, we show that triangle centrality can be optimally computed by our Algorithm 1. Hence our main algorithmic result is the following.

**Theorem 1.** Triangle centrality can be computed in  $O(m\sqrt{m})$  time and O(m+n) space for all vertices in a simple, undirected graph G = (V, E).

Triangle centrality treats triangle counts from triangle neighbors independently from non-triangle neighbors. But finding the triangle neighborhood of a vertex in deterministic, worst-case optimal time and linear space without relying on perfect hashing is surprisingly difficult. We are able to solve this using simple arrays making it a practical alternative to perfect hashing. Our TRIANGLENEIGHBOR algorithm lists triangle neighbors and counts triangles in deterministic, optimal time and linear space. We believe that identifying triangle neighbors may have applications in clustering and community detection and therefore our TRIANGLENEIGHBOR algorithm may be of independent interest. Our next result follows.

**Theorem 2.** Algorithm TRIANGLENEIGHBOR counts triangles and finds triangle neighbors in  $O(m\sqrt{m})$  time and O(m+n) space for all vertices in a simple, undirected graph G=(V,E).

Our main algorithm given in Algorithm 2 employs this new triangle neighborhood algorithm to compute the triangle centrality using simple arrays instead of perfect hashing, and achieves the desired asymptotic bounds asserted by our next theorem.

**Theorem 3.** Algorithm 2 computes the triangle centrality in  $O(m\sqrt{m})$  time and O(m+n) space for all vertices in a simple, undirected graph G = (V, E).

Our Algorithm 3 is a linear algebraic algorithm that achieves the following result.

**Theorem 4.** There is a linear algebraic algorithm that computes the triangle centrality in  $O(m\sqrt{m})$  time and O(m+n) space for all vertices given a sparse matrix A for a simple, undirected graph G=(V,E).

We can also use fast matrix multiplication to calculate triangle centrality in  $n^{\omega+o(1)}$  time, or similar bounds in terms of m using the result of Yuster and Zwick [75].

**Theorem 5.** Triangle centrality can be computed in  $n^{\omega+o(1)}$  time using fast matrix multiplication, where  $\omega$  is the matrix multiplication exponent, for all vertices in a simple, undirected graph G = (V, E).

Next we give parallel algorithms to compute the triangle centrality on a CREW PRAM and in MapReduce. The MapReduce algorithm is optimal and the CREW PRAM is optimal up to a logarithmic factor, yielding the following results.

**Theorem 6.** Triangle centrality can be computed on a CREW PRAM in  $O(\log n)$  time using  $O(m\sqrt{m})$  processors for all vertices in a simple, undirected graph G = (V, E).

**Theorem 7.** Triangle centrality can be computed using MapReduce in four rounds and  $O(m\sqrt{m})$  communication bits for all vertices in a simple, undirected graph G = (V, E).

The advantages of triangle centrality include the following.

- 1. It does not iteratively update values and finishes in a constant number of steps.
- 2. It can identify an important vertex through indirect evidence, e.g. not a member of triangles but neighbors have many triangles.
- 3. It uses a stronger hypothesis by relying on the contribution from a connected pair of vertices rather than a single vertex, thus making it less susceptible to tampering or counter-measures.
- 4. It is relatively fast compute with runtime that is asymptotically equivalent to triangle counting.

### 4 Motivation

In social network analysis, triangles have been found to indicate network cohesion and clustering [36,57,60]. A pair of vertices that share a common neighbor implies a minimal degree of mutual association. But if that same pair are themselves connected, then there is much stronger cohesion between all vertices in that triangle.

Consider an email spammer that sends an email to many random individuals. Most any pair of the email recipients likely have no other association aside from having received an email from the spammer. This should not imply that the spammer is important, especially with respect to each of the recipients. Now consider a social network where there are many friends with mutual contacts, hence triangles. An email from an individual to all of their direct contacts has more relevance than an email from the spammer because most any pair of the friend recipients have some existing relationship, suggesting that the email recipients are not just randomly selected.

We claim that a vertex is important if many neighbors of that vertex are cohesive with their own neighbors, thus further strengthening the influence. Hence a vertex can be important because its neighbors are in many triangles, without that vertex itself having any triangles. This does not exclude a central vertex from being in triangles, in fact we say a vertex is quite important if it is a member of many triangles. Thus our measure finds important vertices that have both direct and indirect evidence of importance.

We believe that this method for centrality can identify important vertices in networks that have strong social network properties and organizational hierarchies where both direct and indirect connectivity need to be accounted. This also indicates that longer range interactions play a role in identifying an important vertex. Suppose the top vertex in an organizational hierarchy has no triangles, but if a direct contact is in many triangles then that contact is in effect conferring the support of it triangle members to that top vertex. Thus the top vertex is receiving support from vertices that are two steps away. We claim that importance is due to the concentration of triangles around a vertex but that vertex itself need not be involved in many triangles. This localization of support is not modeled by other centrality measures.

For an explicit example, consider a hierarchical organization such as a corporation in which the Chief Executive Office (CEO) has a very small number of direct subordinates. But these subordinates, e.g. other officers in the company, have mutual associates such as office managers, administrators, staff, etc. that assist

them in carrying out the CEO's objectives. Thus the top of the organization may have very few contacts, but the subordinate contacts are likely connected because they must share similar information or orders handed down by the top. In turn, these subordinates may have many mutual associates that are also members of triangles. Thus the top vertex in the hierarchy could have few or no triangles, but if there are many triangles concentrated around its direct contacts and their contacts, it suggests that top vertex is important in the network.

Another consideration is if two connected vertices share a mutual contact, then that mutual contact receives stronger support than from two vertices that are not connected. In a real-world scenario, this could mean that the original pair of connected vertices have conferred and agreed upon the selection of the mutual vertex as a contact. This differs starkly from other centrality measures where the contribution or "vote" for a vertex comes from neighbors regardless of the connection between neighbors. Thus the email spammer described earlier can appear as an important vertex in these measures.

Our new approach measures the concentration of triangles in the subgraph of diameter four of each vertex in order to successfully identify these highly important vertices. To illustrate our premise, we argue that vertex "a" in each of the graphs in Figure 1 is the most triangle-centric vertex, and henceforth the most important vertex. We will compare the ranking of vertex "a" in our discussion of other centrality measures at the end of Section 6, and later in Section 11 we will analyze triangle centrality results with these other measures on twenty realistic graphs.




Figure 1: Vertex "a" in each graph is the most central vertex.

## 5 Derivation

We use triangle counts for importance because it is indicative of dense subgraphs and therefore stronger cohesion among vertices. If the graph is a clique, then it has the maximum number of triangles. In a social network context, triangles present more pathways for the spread of information or influence.

Our notion of centrality is then based on the triangle counts from a vertex and each of its neighbors, but that vertex itself need not be involved in many triangles. The contribution of triangle counts for the centrality of a vertex comes from its subgraph within a diameter of four. Hence we claim that a vertex is important if it is in many triangles, or if its neighbors are in many triangles. This leads us to separate the neighbors of a vertex into those that are in triangles with that vertex and those that are not. Recall  $N_{\triangle}^+(v)$  is the triangle core of v, meaning the subset of triangle neighbors of v and v itself. Our precise definition of triangle centrality is given next.

**Definition 1.** The triangle centrality TC(v) of a vertex v is given by the equation,

$$TC(v) = \frac{\frac{1}{3} \sum_{u \in N_{\triangle}^{+}(v)} \triangle(u) + \sum_{w \in \{N(v) \setminus N_{\triangle}(v)\}} \triangle(w)}{\triangle(G)}.$$
 (1)

In our definition, the centrality values are rational numbers bounded in the range [0,1] to indicate the proportion of triangles centered at a vertex. This is accomplished by first multiplying the triangle core  $N_{\triangle}^+(v)$  by a  $\frac{1}{3}$  factor to prevent overcounting triangles because the same triangle is counted by each of its three vertices. Then we normalize the entire value by the total triangle count in G. Therefore if the graph is a clique, then each vertex is equally central.

An example calculation of Equation 1 is given in Figure 2. Overall there are three triangles in Figure 2, two from  $N_{\triangle}^+(v)$  and one from a neighbor of v that is not in  $N_{\triangle}^+(v)$ . Without the  $\frac{1}{3}$  factor the triangles in  $N_{\triangle}^+(v)$  would be overcounted, once from each vertex of a triangle. We argue that v is at the center of the concentration of triangles in Figure 2, and therefore its triangle centrality value is exactly one.




Figure 2: Example calculation of triangle centrality.

## 5.1 Algebraic derivation

The triangle centrality given in Equation 1 can also be formulated in linear algebra using the adjacency matrix A and the graph triangle matrix. This author introduced the graph triangle matrix in [15] and defined it as  $T = A^2 \circ A$ . Thus T encodes the triangle neighbors of each vertex, just as A encodes all neighbors. It follows that the triangle counts can be obtained from T.

**Theorem** (Thm. 1 [15]). Given G and the Hadamard product  $(A^2 \circ A)$ , then  $\triangle(v) = \frac{1}{2} \sum_v (A^2 \circ A)_v$  and  $\triangle(G) = \frac{1}{6} \sum_{ij} (A^2 \circ A)_{ij}$ .

Since A is symmetric, then  $T = T^{\top}$ . The matrix  $T = A^2 \circ A$  cannot have more nonzeros than A due to the Hadamard operation, and the value of a nonzero t(i,j) indicates the count of triangles incident to the  $\{i,j\}$  edge. Hence,

$$\triangle(v) = \frac{1}{2} \|\mathbf{T}_{\mathbf{v}}\|_1 = \mathbf{T}_{\mathbf{v}}^{\top} \mathbf{1}$$
$$\triangle(G) = \frac{1}{6} \mathbf{1}^{\top} T \mathbf{1}.$$

The indices corresponding to nonzeros in each  $\mathbf{T}_{\mathbf{v}}$  column vector represents the triangle neighbors of v, so then  $N_{\triangle}(v) = \text{supp}(\mathbf{T}_{\mathbf{v}})$ . Appropriate substitution using T in Equation 1 leads to

$$TC(v) = \frac{\sum_{u \in \{v\} \cup \text{supp}(\mathbf{T_v})} \|\mathbf{T_u}\|_1 + 3\sum_{w \in \text{supp}(\mathbf{A_v} - \mathbf{T_v})} \|\mathbf{T_w}\|_1}{\mathbf{1}^\top T \mathbf{1}}.$$

Now recall that a matrix-vector multiplication produces a linear combination of the matrix column vectors corresponding to indices of nonzero entries in the vector, each respectively scaled by the nonzero value. Then summing the triangle counts for all triangle neighbors of v, hence  $\sum_{u \in N_{\triangle}(v)} \|\mathbf{T}_{\mathbf{u}}\|_1$ , can be achieved by the  $(T\check{\mathbf{T}}_{\mathbf{v}})^{\mathsf{T}}\mathbf{1}$  product. The core triangle sum  $\sum_{u \in \{v\} \cup \text{supp}(\mathbf{T}_{\mathbf{v}})} \|\mathbf{T}_{\mathbf{u}}\|_1$ , which includes the triangle count for v, can be obtained by  $(T\check{\mathbf{T}}_{\mathbf{v}} + \mathbf{T}_{\mathbf{v}})^{\mathsf{T}}\mathbf{1}$ . Similarly, to get the sum of triangle counts from non-triangle neighbors we

use  $(T(\mathbf{A_v} - \mathbf{\check{T}_v}))^{\top} \mathbf{1}$ . The next steps demonstrate how to transform the triangle centrality into matrix-vector products.

$$TC(v) = \frac{\sum_{u \in \{v\} \cup \text{supp}(\mathbf{T_v})} \|\mathbf{T_u}\|_1 + 3\sum_{w \in \text{supp}(\mathbf{A_v} - \mathbf{T_v})} \|\mathbf{T_w}\|_1}{\mathbf{1}^\top T \mathbf{1}}$$

$$= \frac{(T\check{\mathbf{T}_v} + \mathbf{T_v})^\top \mathbf{1} + 3(T(\mathbf{A_v} - \check{\mathbf{T}_v}))^\top \mathbf{1}}{\mathbf{1}^\top T \mathbf{1}}$$

$$= \frac{\left(3T\mathbf{A_v} - 2T\check{\mathbf{T}_v} + \mathbf{T_v}\right)^\top \mathbf{1}}{\mathbf{1}^\top T \mathbf{1}}$$

$$= \frac{\left(3\mathbf{A_v} - 2\check{\mathbf{T}_v} + \mathbf{I_v}\right)^\top T \mathbf{1}}{\mathbf{1}^\top T \mathbf{1}}.$$

This subsequently leads to the linear algebraic formulation for triangle centrality in matrix notion as defined in Definition 2.

**Definition 2.** The algebraic triangle centrality **C** for all vertices is given by the equation,

$$\mathbf{C} = \frac{\left(3A - 2\check{T} + I\right)T\mathbf{1}}{\mathbf{1}^{\top}T\mathbf{1}}.$$
 (2)

Given T, the linear algebraic triangle centrality can be computed with just two matrix-vector multiplications, two matrix additions, and a single inner product.

## 6 Related work

There are many different graph centrality measures, but we will limit our discussion to closeness [4], degree [62, 67], eigenvector [6], betweenness [34], and PageRank [11] because these are well-known and are available in many graph libraries including the Matlab graph toolkit. We remark that there is no "best" centrality measure. Each has a specific design purpose and are selected for use based on the context. Here, we briefly describe and compare these common centrality measures to triangle centrality in an effort to show that for some contexts, triangle centrality may be more appropriate. Moreover, triangle centrality is asymptotically faster than these other measures with the exception of degree centrality. A summary of the worst-case runtime (work) for these centralities is given Table 2. We refer the reader to [7,9,27,59,65] for more detail on these common centrality measures. Later in Section 11 we'll give a more exhaustive comparison of these centralities on real-world graphs.

Table 2: Runtime asymptotic upper-bounds

Centrality	Work
Degree	O(m)
Triangle	$O(m^{1.5})$
Betweenness	O(mn)
Closeness	O(mn)
PageRank	$O(n^3)$
Eigenvector	$O(n^3)$

Closeness centrality was defined by Bavelas in 1950 [4], making one of the earliest measures for identifying central actors in a network. In closeness centrality a central vertex is closest to all others. The closeness centrality of a vertex v is the inverse of the average distance from v to all other vertices. Hence it is defined by,

$$CC(v) = \frac{n-1}{\sum_{u \in V} d_G(v, u)}.$$

Some texts refer to the reciprocal of this equation for closeness centrality [35] where larger values indicate farness as opposed to closeness. In matrix notation the closeness centrality for all vertices is,

$$\mathbf{C}_{cc} = (n-1) \frac{1}{A^n \mathbf{1}}.$$

The closeness centrality relies on distances and is therefore useful in gauging longer-range interactions. But a vertex with high degree such as a star-like subgraph can exert more influence in this centrality measure. Closeness centrality also requires finding all-pairs shortest paths and hence takes O(mn) time, which is slower than computing triangle centrality.

Degree centrality was proposed in 1954 by Shaw [67] and refined later in 1974 by Nieminen [62]. This centrality measures importance based on the degree of a vertex and therefore important vertices are those with high degree. The degree centrality of a vertex v is then DC(v) = d(v). Using the adjacency matrix A, the degree centrality DC(v) is given by,

$$DC(v) = \sum_{u \in V} a(v, u) = \|\mathbf{A_v}\|_1 = \mathbf{A_v}^{\top} \mathbf{1}.$$

It then follows that all DC(v) values is computed by,

$$\mathbf{C}_{dc} = A\mathbf{1}$$
.

This measure is very simple because it depends only on the degrees, and thus is also easy to compute. But the simplicity also means that it may not accurately model importance in a complex network. An email spammer could rank highly in degree centrality. In contrast, a low-degree vertex can be important in triangle centrality because its triangle count can be far higher than its degree. The maximum number of triangles for a vertex is quadratic in its degree, given by  $\binom{d(v)}{2}$ . This is compounded if the neighbors of a low-degree vertex also have close to their maximum triangle count. Such a vertex would be considered unimportant in degree centrality, which may be misleading in some contexts as we have argued. For example, vertex "a" in Figure 1b is ranked last in degree centrality. Then in Figure 1a all vertices are equally ranked because of uniform degree and therefore no distinction is made among them. Yet clearly the structure of the network in Figure 1a is not uniform and it can be argued a distinction can be made between the vertices. But degree centrality is fast to compute, taking only O(m) time whereas triangle centrality takes  $O(m^{3/2})$  time.

Eigenvector centrality was formalized by Bonacich in 1972 [6]. It measures the number and quality of connections associated with a vertex based on the largest eigenvalue of the adjacency matrix. Important vertices under this measure are those with many connections, especially if the connections are to other important vertices. Eloquently put by Borgatti and Everett, a central actor is therefore one who "knows everybody who is anybody" [9]. The eigenvector centrality of a vertex v is given by the  $v^{th}$  component of the eigenvector corresponding to the largest eigenvalue in A. Specifically, the relative eigenvector centrality EV(v) for a vertex v where  $\lambda$  is the largest eigenvalue of A is then,

$$EV(v) = \frac{1}{\lambda} \sum_{u \in V} a(v, u) EV(u).$$

Given a vector  $\mathbf{C}_{ev}$  to hold all EV(v), then it follows from the familiar  $A\mathbf{x} = \lambda \mathbf{x}$  form of eigenvalue equations that the eigenvector centrality in matrix notation for all vertices is,

$$\mathbf{C}_{ev} = \frac{1}{\lambda} A \mathbf{C}_{ev}.$$

The advantage of this measure is it gives more weight to connections from important vertices than those that are not important. It can be seen as the weighted sum of connections from any distance in the graph, and hence it takes in account the entire network topology. The central vertex "a" in Figure 1a is ranked the highest by eigenvector centrality. But the disadvantage of eigenvector centrality is it is influenced by degree. Low-degree vertices that act as bridges connecting dense subgraphs would be ranked poorly by eigenvector

centrality, such as vertex "a" in Figure 1b, but clearly such vertices are important because their removal would disconnect the subgraphs. The vertex "a" in Figure 1b is ranked last in eigenvector centrality. It is also relatively expensive to compute eigenvectors, especially for very large graphs, making eigenvector centrality less scalable than our triangle centrality. Eigenvector centrality can be computed in  $O(n^3)$  time using the power iteration method [38]. On sparse graphs, our triangle centrality is faster, taking  $O(m^{3/2})$  time.

Betweenness centrality, first introduced in 1977 by Freeman [34], is similar to closeness centrality in both ranking and runtime. It measures importance by the number of shortest-paths a vertex intersects. An important vertex in this measure has a large fraction of shortest-paths that intersect it over all possible shortest-paths. This implies that an important or central vertex in a graph under this measure is one whose removal will disrupt the flow of information to many other vertices. Let  $\sigma_{ij}$  be the number of shortest paths from i to j, and  $\sigma_{ij}(v)$  be the number of these shortest paths that intersect v. Then the betweenness centrality BC(v) for a vertex v is,

$$BC(v) = \sum_{i \neq v \neq j} \frac{\sigma_{ij}(v)}{\sigma_{ij}}.$$

Betweenness centrality directly accounts for longer range interactions, explicitly relying on the number of paths through a vertex. Like triangle centrality, it identifies vertex "a" in Figure 1a and Figure 1b as being the most important. But this model of importance relies heavily on distances and does not capture local subnetwork characteristics. A vertex with many leaf nodes can rank higher in betweenness centrality than a vertex whose neighbors are interconnected because the shortest-paths between the leaf nodes must go through their common neighbor. But it can be argued that the vertex whose neighbors are interconnected is more important. For example, betweenness centrality ranks the vertex with the most leaf nodes in Figures 1c, 1d as the most important, rather than vertex "a". It is also more expensive to compute betweenness centrality than triangle centrality because it requires finding all-pairs shortest-paths, taking O(mn) time [10].

PageRank centrality was published in 1998 by Brin and Page as the underlying technology for the Google search engine [11]. The PageRank centrality is a variant of eigenvector centrality and therefore has similar advantages and disadvantages. Importance is due to the quantity and quality of links, just as in eigenvector centrality. But PageRank also allows some randomness through a damping factor. Applied to web search, PageRank centrality treats the World Wide Web as a graph where web pages are vertices and hyperlinks are edges. An important web page in PageRank has many hyperlinks, and especially so if the hyperlinks are from other important web pages. The PageRank centrality PR(v) of a vertex v and damping factor d is,

$$PR(v) = \frac{1-d}{n} + d\sum_{u \in N(u)} \frac{PR(u)}{d(u)}.$$

Let the vector  $\mathbf{C}_{pr}$  hold all PR(v) values, then the algebraic form is,

$$\mathbf{C}_{pr} = d\mathcal{M}\mathbf{C}_{pr} + \frac{1-d}{n}\mathbf{1},$$

where  $\mathcal{M} = (K^{-1}A)^{\top}$  and K is a diagonal matrix in which the entries are the vertex degrees.

It is possible that a vertex with many low-quality connections may still be considered high-ranking in PageRank by nature of having high degree, making it susceptible to spurious results or gaming. PageRank does not identify vertex "a" as the most central vertex in any of the examples in Figure 1. Computing the PageRank takes the same time as eigenvector centrality and hence is slower than computing triangle centrality.

A comparison of the relative ranking of vertex "a" in each of the graphs in Figure 1 by the aforementioned centrality measures is given in Table 3. We used the graph toolkit in Matlab to compute rankings from these aforementioned centrality measures. Only triangle centrality ranks "a" first in all Figure 1 graphs. It is followed by closeness centrality which ranks "a" first in all but Figure 1d. The PageRank centrality does not rank "a" first in any of the graphs. The graphs in Figure 1 are idealistic but give some insight on the role of triangles and degree in measuring importance. It is clear that degree plays a much less significant role for triangle centrality than it does for the other measures. We consider this is an advantage for triangle centrality because it it harder to inflate rankings. In section 11 we'll compare these measures on more realistic graphs.

Table 3: Rank-order comparison for vertex "a" in Figures 1a-1d

	ТС	ВС	CC	DC	EV	PR
Figure 1a	1	1	1	1	1	7
Figure 1b	1	1	1	25	25	25
Figure 1c	1	2	1	2	2	$^2$
Figure 1d	1	2	2	2	1	2

## 7 Observations

By weighting the triangle contribution from triangle neighbors we can obtain convenient expressions for special cases. In some cases it leads to the surprising result that the triangle centrality for a vertex is not explicitly dependent on the number of triangles. These can be useful to quickly test and validate implementations of triangle centrality.

**Observation 1.** The triangle centrality for every vertex is 1 if G is a clique.

*Proof.* Since G is a clique then every neighbor of a vertex v is a triangle neighbor; also d(v) = n - 1 for each vertex and  $\triangle(G)$  equates to  $\binom{n}{3}$ . By Equation 1 this leads to,

$$TC(v) = \frac{\frac{1}{3} \sum_{u \in N_{\Delta}^{+}(v)} \triangle(u)}{\triangle(G)} = \frac{\frac{1}{3} \sum_{v \in V} {\binom{d(v)}{2}}}{\binom{n}{3}}$$
$$= \frac{\frac{n}{3} {\binom{n-1}{2}}}{\binom{n}{3}} = \frac{\binom{n}{3}}{\binom{n}{3}} = 1.$$

**Observation 2.** The triangle centrality for a vertex is  $\frac{3}{k}$  if it is not in triangles and its neighbors are in copies of  $K_k$  containing all triangles in G, where  $k \geq 3$ .

*Proof.* Since all triangles are in copies of  $K_k$  adjacent to v then  $\triangle(G) = d(v) \binom{k}{3}$ , and the sum of triangle counts for the neighbors of v is  $d(v) \binom{k-1}{2}$ . Therefore the triangle centrality for a vertex v whose neighbors are each in a  $K_k$  and v itself has no triangles is  $\frac{3}{k}$  as follows from Equation 1.

$$TC(v) = \frac{\sum_{u \in N(v)} \triangle(u)}{\triangle(G)} = \frac{\binom{k-1}{2}}{\binom{k}{3}} = \frac{3}{k}.$$

**Observation 3.** The triangle centrality for a vertex is  $\frac{1}{p}$  if it is in one of  $p \ge 1$  disjoint copies of  $K_k$  containing all triangles in G, where  $k \ge 3$ .

*Proof.* Since all triangles are in the p disjoint copies of  $K_k$  then  $\triangle(G) = p\binom{k}{3}$ , and any vertex v in a  $K_k$  has  $\triangle(v) = \binom{k-1}{2}$  triangles. By Equation 1 the triangle centrality is then,

$$TC(v) = \frac{\frac{1}{3} \sum_{u \in N_{\triangle}^{+}(v)} \triangle(u)}{\triangle(G)} = \frac{\frac{k}{3} {k-1 \choose 2}}{\triangle(G)}$$
$$= \frac{{k \choose 3}}{\triangle(G)} = \frac{{k \choose 3}}{p{k \choose 3}} = \frac{1}{p}.$$

**Observation 4.** The triangle centrality for a vertex can be one of the following if G is a chain of  $p \geq 3$  copies of  $K_k$ , each connected by a single vertex, where  $k \geq 3$ :

- i)  $\frac{(2k+2)}{pk}$  if joining two internal  $K_k$ 's
- ii)  $\frac{(2k+1)}{pk}$  if joining the head or tail  $K_k$
- iii)  $\frac{(k+2)}{pk}$  does not join  $K_k$ 's and is not in head or tail  $K_k$
- iv)  $\frac{(k+1)}{pk}$  does not join  $K_k$ 's and is in head or tail  $K_k$

*Proof.* We begin with some preliminary facts. Any vertex v in a  $K_k$  that does not join another  $K_k$  has degree d(v) = k-1 and  $\triangle(v) = \binom{k-1}{2}$  triangles. Any vertex v that joins two  $K_k$ 's has degree d(v) = 2(k-1) and  $\triangle(v) = 2\binom{k-1}{2}$ . Since all triangles are in the  $K_k$ 's then  $\triangle(G) = p\binom{k}{3}$ . We will use the next relation to prove each of the cases.

$$\frac{1}{3\triangle(G)}\binom{k-1}{2} = \frac{\binom{k-1}{2}}{3p\binom{k}{3}} = \frac{1}{pk}.$$

In case i) a vertex v joins two internal  $K_k$ 's and since G is a chain of at least four  $K_k$ 's, then two neighbors also join  $K_k$  and these will have the same number of triangles as v. There are d(v) - 2 = 2(k-2) remaining neighbors. The triangle centrality for v is,

$$TC(v) = \frac{1}{3\triangle(G)} {k-1 \choose 2} (2+4+2(k-2))$$
  
=  $\frac{(2k+2)}{vk}$ .

In case ii) a vertex v joins a head or tail  $K_k$  to the chain. It has one neighbor that also joins  $K_k$ 's and d(v) - 1 = 2k - 3 remaining neighbors. The triangle centrality for v is,

$$TC(v) = \frac{1}{3\triangle(G)} {k-1 \choose 2} \left(2+2+2k-3\right)$$
$$= \frac{(2k+1)}{pk}.$$

In case iii) a vertex v does not join any  $K_k$  and is not in the head or tail  $K_k$ . Two of its neighbors join  $K_k$ 's so there are d(v) - 2 = k - 3 remaining neighbors. The triangle centrality for v is,

$$TC(v) = \frac{1}{3\triangle(G)} {k-1 \choose 2} \left(1+4+k-3\right)$$
$$= \frac{(k+2)}{pk}.$$

In case iv) a vertex v does not join any  $K_k$  but is in the head or tail  $K_k$ . One neighbor joins  $K_k$ 's. The triangle centrality for v is,

$$TC(v) = \frac{1}{3\triangle(G)} {k-1 \choose 2} \left(1+2+k-2\right)$$
$$= \frac{(k+1)}{pk}.$$

The next observation follows immediately from Observation 4.

**Observation 5.** The triangle centrality for a vertex is  $\frac{(2k+2)}{pk}$  if it joins copies of  $K_k$ , otherwise it is  $\frac{(k+2)}{pk}$ , where G is a ring of  $p \geq 3$  copies of  $K_k$ , each connected by a single vertex, where  $k \geq 3$ .

Let us consider the example in Figure 1b to further demonstrate the intuition behind Definition 1. There are four 6-cliques connected to vertex "a". The local triangle count for "a" is zero so it cannot contribute to the centrality of its neighbors, and thus every vertex in the 6-cliques must have the same triangle centrality value. Each 6-clique contains  $\binom{6}{3} = 20$  triangles leading to  $\triangle(G) = 80$ .

Although each clique vertex in Figure 1b is locally central within its clique, there are four such cliques so the overall importance of any one of the clique vertices should be one-fourth that of a vertex that centered all triangles. This aligns with Observation 3 where each clique vertex has a triangle centrality of  $\frac{1}{4} = 0.25$ .

Now observe that each 6-clique vertex has a local triangle count of  $\binom{5}{2} = 10$ , which is one-eighth of the triangle count. Although vertex "a" is not in any triangles, its four neighbors account for one-half of the total number of triangles. Thus we say that vertex "a" is the center of half the triangles in the graph. It follows from Observation 2 that "a" has triangle centrality  $\frac{3}{6} = 0.5$ .

There are some cases where the rank of triangle vertices and their non-triangle neighbors are the same. Imagine the simple case where the graph has one triangle and each vertex of that triangle also has neighbors not in the triangle. Then we make the following observation.

**Observation 6.** The triangle centrality is 1 for a triangle vertex and its neighbors if the neighbors are not in other triangles.

The proof of Observation 6 is obvious. In this case the triangle centrality does not discriminate between triangle vertices and their neighbors, which may be counter-intuitive. Although it can be argued that the triangle vertices are more important, our goal was to also give importance to vertices that may not be in triangles. The side effect of this is elucidated by Observation 6.

## 8 Algorithm

The first task in computing triangle centrality is to get the triangle count of every vertex in the graph. This task can be achieved by any efficient triangle counting algorithm in  $O(m^{3/2})$  time. See [63] for a brief discussion on efficiently finding triangles. The second task is summing the triangle counts from neighbors of a vertex, with separate sums for triangle and non-triangle neighbors. This requires first identifying the specific triangle neighbors of each vertex. Then for every vertex, we need to calculate the core triangle sum,  $\sum_{u \in N_{\triangle}^+(v)} \Delta(u)$ , and the non-core triangle sum,  $\sum_{w \in \{N(v) \setminus N_{\triangle}(v)\}} \Delta(w)$ . Given these sums and  $\Delta(G)$ , the triangle centrality follows. This procedure leads to our elementary algorithm in Figure 3. We will refer to the elementary steps in Figure 3 throughout the remaining algorithm descriptions and results.

- 1. For each vertex  $v \in V$ , compute the local triangle count,  $\Delta(v)$ , and update  $\Delta(G)$
- 2. For each vertex  $v \in V$ , find and store v's triangle neighbors
- 3. For each vertex  $v \in V$  do
  - i. Calculate the core triangle sum,  $x = \sum_{u \in N_{\wedge}^{+}(v)} \triangle(u)$
  - ii. Sum all neighbor triangle counts,  $s = \sum_{u \in N(v)} \triangle(u)$
  - iii. Get non-core triangle sum,  $\sum_{w \in \{N(v) \backslash N_{\triangle}(v)\}} \triangle(w) = s x + \triangle(v)$
  - iv. Compute the triangle centrality  $TC(v) = \frac{\frac{1}{3} \sum_{u \in N_{\triangle}^+(v)} \triangle(u) + \sum_{w \in \{N(v) \setminus N_{\triangle}(v)\}} \triangle(w)}{\triangle(G)}$

Figure 3: Triangle Centrality elementary algorithm.

Since a triangle is symmetric, it can be reported by the lowest-degree vertex in the triangle. Hence with degree-ordering, all triangles can be counted and listed in optimal time. This has been well-known since 1985 when Chiba and Nishizeki [21] showed that computing the set intersection using the smaller of the two neighborhood sets will lead to  $\sum_{(v,u)\in E} \min(d(v),d(u)) \leq 2ma(G) = O(m\sqrt{m})$  time, where a(G) is the arboricity of G. Recall the arboricity is the minimum number of disjoint forests whose union covers E. In 2005, Shank and Wagner [66] demonstrated that finding all unique, adjacent pairs of neighbors from the lowest-degree vertex also leads to optimal time. There are numerous triangle counting and listing algorithms that are variations of either adjacency-intersection or neighbor-pairing. Refer to [52,63] for a review.

Recall that  $\pi$ -ordering denotes degree-ordering from lowest- to highest-degree, where ties are broken by smallest vertex label. We use abbreviated adjacency sets,  $N_{\pi}(v)$ , to achieve optimal runtime. These adjacency sets are degree-ordered, meaning that  $N_{\pi}(v)$  holds the neighbors u of v that satisfy  $\pi(v) < \pi(u)$ . The remaining neighbors may be placed at the end of  $N_{\pi}(v)$  or left out completely.

Our basic algorithm for triangle centrality is given in Algorithm 1. The first iteration over V computes both the triangle counts and the triangle neighborhood using a hash-based algorithm given in Listing 3, which is described in Section 10.1.

### Algorithm 1

```
Require: T, an array of lists for holding the triangle neighbors of each v \in V
Require: N_{\pi}(v), abbreviated adjacency sets for each v \in V
 1: for v \in V do
        for u \in N_{\pi}(v) do
 2:
            set t := 0
 3:
 4:
            for w \in N(v) do
                if \{u,w\} \in E and \pi(v) < \pi(u) < \pi(w) then
 5:
                    increment \triangle(v), \triangle(u), \triangle(w), \triangle(G)
                                                                                                 ▷ triangle counts, Step 1
 6:
                    if t is 0 then
 7:
                        set t := 1
 8:
 9:
                        add u to T(v) and add v to T(u)
                                                                                              ▶ triangle neighbors, Step 2
10: for v \in V do
                                                                                                                    ⊳ Step 3
        set x := \triangle(v) and s := 0
11:
        for u \in T(v) do
12:
            set x := x + \triangle(u)
                                                                                             ⊳ core triangle sum, Step 3.i
13:
        for u \in N(v) do
14:
            set s := s + \triangle(u)
                                                                                       ⊳ neighbor triangle sum, Step 3.ii
15:
        set y := s - x + \triangle(v)
                                                                                      ⊳ non-core triangle sum, Step 3.iii
16:
        output TC(v) = (\frac{1}{3}x + y)/\triangle(G)
                                                                                                   ⊳ Equation 1, Step 3.iv
17:
```

Claim 1. The abbreviated adjacency sets  $N_{\pi}(v)$  for each  $v \in V$  can be built in O(m) time and space.

Proof. Suppose each N(v) is stored in a simple array. Set a pointer p to the beginning of the array for an N(v). Now iterate over the array and upon any  $u \in N(v)$  such that  $\pi(v) < \pi(u)$ , exchange that u with the neighbor at the position pointed to by p, then move p to the next space. At the end, all higher-ordered neighbors are at the front of the array for N(v), and p points to the last such neighbor, thereby delineating higher- from lower-ordered neighbors. Reordering N(v) in this manner takes d(v) time, so for all vertices it takes  $\sum_{v \in V} d(v) = O(m)$  time. It requires O(m) space to store all N(v) as arrays. Therefore the claim holds.

**Theorem 1.** Triangle centrality can be computed in  $O(m\sqrt{m})$  time and O(m+n) space for all vertices in a simple, undirected graph G=(V,E).

*Proof.* Algorithm 1 achieves this using abbreviated adjacency sets,  $N_{\pi}(v)$ , which can be built in O(m) time as established by Claim 1.

The first iteration over all vertices in V counts triangles and stores a list of unique triangle neighbors for each vertex. It accomplishes this by detecting all  $u, w \in N_{\pi}(v)$  unique neighbor pairs of v that make a

 $\{u,w\}$  edge and are therefore in a  $\{v,u,w\}$  triangle. Given perfect hashing, testing for an edge in E takes O(1) time. There are  $|N_{\pi}(v)| \cdot |N(v)|$  neighbor pairs for each vertex and since  $|N_{\pi}(v)| = O(\sqrt{m})$  this leads to  $O(\sqrt{m}d(v))$  neighbor pairs. All other operations take O(1) time. Thus overall the first iteration over V takes  $\sqrt{m} \sum_{v \in V} d(v) \leq O(m\sqrt{m})$  time for all vertices.

The second iteration over V takes O(m) time as follows. A vertex v cannot have more than d(v) triangle neighbors, hence the size of T(v) is at most d(v). Then iterating over triangle neighbors to get the core triangle sum,  $\sum_{u \in N_{\triangle}^+(v)} \triangle(u)$ , and then over all neighbors to get the sum,  $\sum_{u \in N(v)} \triangle(u)$ , takes  $2\sum_{v \in V} d(v) = O(m)$  time. All other operations take O(1) time.

In total, calculating the triangle centrality takes  $O(m\sqrt{m}+m)=O(m\sqrt{m})$  time.

The space complexity depends upon the storage for triangle counts, triangle neighbors, hash table on edges, and all  $N_{\pi}(v)$ . An array of size n holds triangle counts. The array T holds the triangle neighbor lists for every vertex, and since a vertex v has at most d(v) triangle neighbors, then T takes  $\sum_{v \in V} d(v) = 2m$  space. A hash table on edges takes O(m) space. The  $N_{\pi}(v)$  can be either a subset in N(v) or stored separately, where the latter will take an extra O(m) space. In total the algorithm takes O(m+n) space.

Altogether, it takes  $O(m\sqrt{m})$  time and O(m+n) space as claimed.

Algorithm 1 is very simple but it requires perfect hashing, and an astute reader will notice that each triangle is detected three times. This makes Algorithm 1 less appealing for practical settings and motivates our main algorithm, which we describe next.

### 8.1 Main algorithm

Finding the triangle neighbors in Step 2 of Figure 3, needed to compute the core triangle sum  $\sum_{u \in N_{\Delta}^+(v)} \Delta(u)$ , in worst-case optimal time and linear space is surprisingly difficult without relying on perfect hashing. In practical settings, perfect hashing may be unwieldy because it requires rebuilding hash tables each time the graph changes. Building a perfect hash table requires randomization and therefore takes non-determinisic time [33]. An optimal method for getting triangle neighbors of each vertex is further complicated by the use of degree-ordering because only the lowest degree vertex in a triangle has knowledge of the triangle. Therefore the higher degree vertices in a triangle require the lowest-degree triangle neighbor to provide it the necessary information. Our TRIANGLENEIGHBOR algorithm (Procedure 1, Section 10) solves the problem of finding triangle neighbors for each vertex using simple arrays in  $O(m\sqrt{m})$  deterministic time and O(m+n) space, while also computing all triangle counts. Moreover it processes each triangle at most once.

This may have independent applications so we describe TRIANGLENEIGHBOR in Section 10 for the interested reader. Here, we apply it in our main algorithm for triangle centrality given in Algorithm 2, which computes triangle centrality without hashing or processing each triangle more than once, and is still simple to implement and keeps within the desired bounds. We assert the complexity of TRIANGLENEIGHBOR in Theorem 2, leaving the analysis and proof for Section 10.

**Theorem 2.** Algorithm TRIANGLENEIGHBOR counts triangles and finds triangle neighbors in  $O(m\sqrt{m})$  time and O(m+n) space for all vertices in a simple, undirected graph G=(V,E).

### Algorithm 2

**Require:** X, array for the core triangle sum of each  $v \in V$ , initialized to zero **Require:**  $L_v$ , array of size  $|N_{\pi}(v)|$  for each  $v \in V$  with each entry initialized to 0  $\triangleright \triangle(v), \triangle(G), \text{ Steps } 1, 2$ 1: Call TriangleNeighbor 2: for  $v \in V$  do ⊳ Step 3 3: for  $u \in N_{\pi}(v)$  do set i to the index of  $u \in N_{\pi}(v)$ 4: 5: if  $L_v(i)$  is 1 then set  $X(v) := X(v) + \triangle(u)$  and  $X(u) := X(u) + \triangle(v)$ ⊳ core triangle sum, Step 3.i 6: 7: for  $v \in V$  do set  $x := X(v) + \triangle(v)$  and s := 08: for  $u \in N(v)$  do 9: set  $s := s + \triangle(u)$ ⊳ neighbor triangle sum, Step 3.ii 10: set  $y := s - x + \triangle(v)$ ⊳ non-core triangle sum, Step 3.iii 11: output  $TC(v) = (\frac{1}{3}x + y)/\triangle(G)$ 12: ▶ Equation 1, Step 3.iv

**Theorem 3.** Algorithm 2 computes the triangle centrality in  $O(m\sqrt{m})$  time and O(m+n) space for all vertices in a simple, undirected graph G = (V, E).

*Proof.* The triangle counts and triangle neighbors (Steps 1, 2) are computed by the TRIANGLENEIGHBOR algorithm in Procedure 1. It follows from Theorem 2 that TRIANGLENEIGHBOR takes  $O(m\sqrt{m})$  time.

The first iteration over all vertices  $v \in V$  after calling TRIANGLENEIGHBOR takes O(m) time as follows. Since  $|N_{\pi}(v)| \leq \sqrt{m} \leq d(v)$  for each vertex v, then overall it takes  $\sum_{v \in V} d(v) = 2m$  time to iterate over all higher-ordered neighbors of each vertex. All other operations take O(1) time. Thus it takes O(m) time to compute the triangle core sum (Step 3.i). Then summing the triangle counts from each neighbor  $u \in N(v)$  (Step 3.ii) takes  $\sum_{v \in V} d(v) = 2m$  for every vertex. All other operations take O(1) time. In total it takes O(m) time to calculate the sums and the triangle centrality.

Each  $L_v$  takes  $|N_{\pi}(v)| \leq d(v)$  space, then overall these takes O(m) space. It takes O(n) space to hold triangle counts and the triangle core sum for every vertex.

```
Therefore it takes O(m\sqrt{m}) and O(m+n) space as claimed.
```

Next we describe a linear algebraic algorithm for triangle centrality. For sparse graphs, this algebraic algorithm matches the bounds of the combinatorial algorithms introduced earlier. But the algebraic algorithm may have practical benefits because it can leverage highly optimized matrix libraries. In recent years there has been interest in applying decades of experience with matrix computation in the design of linear algebraic graph algorithms [3,12,13,17,46,73,74], culminating into the GraphBLAS specification and implementations that can already compute the graph triangle matrix [14,28–30,72].

### 8.2 Algebraic algorithm

Given the graph triangle matrix T, the linear algebraic triangle centrality defined in Definition 2 is simple to compute, requiring just two matrix-vector products, two matrix additions, and an inner-product. Our Algorithm 3 computes it in optimal time and linear space for sparse graphs if T can be constructed in  $O(m\sqrt{m})$  time and O(m+n) space.

#### Algorithm 3

```
Require: A, adjacency matrix in sparse matrix representation
```

**Require:**  $T = A^2 \circ A$ , graph triangle matrix in sparse matrix representation

```
1: Create binary matrix \tilde{T}

2: set X := 3A - 2\tilde{T} + I

3: set \mathbf{y} := T\mathbf{1}

4: set k := \mathbf{1}^{\top}\mathbf{y}

5: output \mathbf{C} := \frac{1}{k}X\mathbf{y}
```

 $\triangleright$  Equation 2

**Claim 2.** A sparse matrix representing  $T = A^2 \circ A$  can be built in  $O(m\sqrt{m})$  time and O(m+n) space.

Proof. First, count triangles and for each unique (u,v) triangle edge, update the list of triangle neighbors for u with v and vice versa. This can be accomplished in  $O(m\sqrt{m})$  time using TRIANGLENEIGHBOR or any of the triangle neighborhood algorithms in Section 10.1. At the end of counting, iterate over the triangle neighbor lists and output weighted edges  $(v,u,\Delta(u))$ . Since each v has at most d(v) triangle neighbors, then writing the edges takes  $\sum_{v\in V} d(v) = O(m)$  time. Finally, build a sparse matrix T on these weighted edges, which takes O(m) time. This T is equivalent to the graph triangle matrix produced by  $A^2 \circ A$ . Storing the triangle counts to complete the triangle neighbor edge list takes O(n) space. All triangle neighbors and hence nonzeros in T take O(m) space. Thus in total, T can be built in  $O(m\sqrt{m})$  time and O(m+n) space.

**Theorem 4.** There is a linear algebraic algorithm that computes the triangle centrality in  $O(m\sqrt{m})$  time and O(m+n) space for all vertices given a sparse matrix A for a simple, undirected graph G=(V,E).

*Proof.* Algorithm 3 achieves this by computing Equation 2 using sparse matrix representation for both the adjacency matrix A and graph triangle matrix T. Thus all operations on these matrices are over nonzeros only.

It was established by Claim 2 that the matrix T can be built in  $O(m\sqrt{m})$  time and O(m+n) space. Now recall that both A and T have O(m) nonzero values. Then setting all nonzero values to unity in T to construct  $\check{T}$  takes O(m) time. Scalar operations and matrix additions on these matrices take O(m) time. Therefore it takes O(m) time to produce 3A and  $2\check{T}$ , and subsequently the matrix addition  $3A - 2\check{T} + I$  also takes O(m) time.

A sparse matrix-vector multiplication takes O(m) time. There are two matrix-vector multiplications in the algorithm. The first produces the  $T\mathbf{1}$  vector and the second is the product of the  $3A-2\check{T}+I$  matrix with this  $T\mathbf{1}$  vector. The inner product between  $\mathbf{1}^{\top}$  and the  $T\mathbf{1}$  vector takes O(n) time. Therefore all algebraic multiplications take O(m+n) total time.

Since T holds only triangle neighbors then T and T take O(m) space. The effective addition of triangle neighbors to non-triangle neighbors resulting from the 3A-2T+I matrix addition leads to the same amount of space as required by A. Thus these matrices combined take O(m) space. All other space is for holding the vector  $T\mathbf{1}$ , which takes O(n) space.

Altogether with the construction of T and  $\check{T}$ , the algorithm completes in  $O(m\sqrt{m})$  time and O(m+n) space.

Using fast matrix multiplication we can calculate triangle centrality in  $n^{\omega+o(1)}$  time, or similar bounds in terms of m using the result of Yuster and Zwick [75].

**Theorem 5.** Triangle centrality can be computed in  $n^{\omega+o(1)}$  time using fast matrix multiplication, where  $\omega$  is the matrix multiplication exponent, for all vertices in a simple, undirected graph G = (V, E).

The proof follows as an immediate consequence of fast matrix products in computing Equation 2. The best-known fast matrix multiplication result gives  $\omega = 2.37286$  [2].

# 9 Parallel Algorithm

### 9.1 PRAM Algorithm

We will describe Parallel Random Access (PRAM) algorithms for triangle centrality in this section. In a PRAM [32] each processor can access any global memory location in unit time. Processors can read from global memory, perform a computation, and write a result to global memory in a single clock cycle. All processors execute these instructions at the same time. A read or write to a memory location is restricted to one processor at a time in an Exclusive Read Exclusive Write (EREW) PRAM. Writes to a memory location are restricted to a one processor at a time in a Concurrent Read Exclusive Write (CREW) PRAM. A Concurrent Read Concurrent Write (CRCW) PRAM permits concurrent read and write to a memory location by any number of processors, but values concurrently written by multiple processors to the same memory location are handled by a resolution protocol.

It follows directly from matrix multiplication that the algebraic triangle centrality (Definition 2) can be computed on a CREW PRAM in  $O(\log n)$  time using  $O(n^3)$  processors. The work is bounded by the matrix multiplication of  $A^2$  needed to get the graph triangle matrix T, and it is well-known that multiplying two  $n \times n$  matrices takes  $O(\log n)$  time using  $O(n^3)$  CREW processors [43]. We can show that triangle centrality can be computed with the same runtime but using  $O(m\sqrt{m})$  CREW processors, and is therefore work-optimal up to a logarithmic factor.<sup>1</sup> This is achieved by Algorithm 4, in which statements contained within a **for all** construct are performed concurrently and all statements are executed in top-down order.

### Algorithm 4

```
Require: Array P_v of size 2d(v) for each v \in V initialized to zero
Require: Array X_v of size d(v) for each v \in V initialized to zero
Require: Arrays T_v, S_v of size d(v) for each v \in V initialized to zero
Require: Processor p for each \{u, w\} pair in N_{\pi}(v) assigned to cell p in P_w, P_u, P_v, X_w, X_u, X_v.
 1: for all \{u, w\} \in N_{\pi}(v), \forall v \in V \text{ do}
         if \{u, w\} \in E and \pi(v) < \pi(u) < \pi(w) then
 2:
             write v, u to P_w[p], and v, w to P_u[p], and u, w to P_v[p]
 3:
             set X_w[p] := 1, X_u[p] := 1, X_v[p] := 1
 4:
 5: for all v \in V do
 6:
         parallel sum over X_v and set sum to \triangle(v)
    for all v \in V do
         parallel sum over all \triangle(v) and set sum to \triangle(G)
                                                                                                                          ⊳ Step 1
         parallel sort and scan over P_v and write to T_v
                                                                                \triangleright Step 2, T_v stores triangle neighbors of v
 9:
    for all u \in T_v, \forall v \in V do
10:
         set T_v[u] := \triangle(u)
                                                                       \triangleright replace each triangle neighbor u of v with \triangle(u)
11:
    for all (u, v) \in E do
12:
         set S_v[u] := \triangle(u)
13:
    for all v \in V do
14:
                                                                                                          \triangleright Step 3.i, sans \triangle(v)
         parallel sum over T_v and set sum to x
15:
         parallel sum over S_v and set sum to s
16:
                                                                                                                       ⊳ Step 3.ii
17:
    for all v \in V do
        set x := x + \triangle(v)
18:
        set y := s - x + \triangle(v)
output TC(v) = (\frac{1}{3}x + y)/\triangle(G)
19:
                                                                                          ⊳ non-core triangle sum, Step 3.iii
                                                                                                        ▶ Equation 1, Step 3.iv
20:
```

**Theorem 6.** Triangle centrality can be computed on a CREW PRAM in  $O(\log n)$  time using  $O(m\sqrt{m})$  processors for all vertices in a simple, undirected graph G = (V, E).

Proof. Observe there are  $O(m\sqrt{m})$  processors for the first step. Each of these processors concurrently reads its assigned u, w pair from  $N_{\pi}(v)$  and if  $\{u, w\} \in E$  and  $\pi(v) < \pi(u) < \pi(w)$  then a unique triangle is found. Subsequently, each unique triangle can only be found by a unique processor p. Each p exclusively writes the three unique triangle vertex pairs to its designated cell in the arrays  $P_w, P_u, P_v$ . That same processor also exclusively writes 1 to it designated cell in the arrays  $X_w, X_u, X_v$ . This first step takes O(1) time using  $O(m\sqrt{m})$  processors.

The remaining steps in the algorithm utilizes parallel sum and scan primitives which are known to take  $O(\log n)$  time on a CREW [43].

Then the triangle counts are computed by parallel sum over each  $X_v$ . Since  $X_v$  is O(d(v)) in size then it takes O(m) processors and  $O(\log n)$  time to compute and store the counts. A second parallel sum to get  $\Delta(G)$  takes the same time and number of processors. Finally, getting the unique triangle neighbors of each vertex requires a parallel sort and scan over each  $P_v$ . Parallel sorting can be accomplished in  $O(\log n)$  time [26] and scanning to remove duplicates takes the same time. Thus altogether using O(m) processors the triangle neighbors are written to each  $T_v$  in  $O(\log n)$  time using O(m) processors.

<sup>&</sup>lt;sup>1</sup>Work for parallel processing is  $T(n) \times p$  for runtime T(n) using p processors. It is optimal if it equals the sequential runtime.

Then each triangle neighbor u in  $T_v$  is replaced with  $\Delta(u)$ . Given a processor for each of the d(v) cells in  $T_v$ , then for all  $v \in V$  it takes O(m) processors to exclusively overwrite the entries in O(1) time. Similarly, given a processor for each  $(u, v) \in E$  edge that writes to the corresponding  $S_v[u]$  cell, the  $\Delta(u)$  for all d(v) neighbors of u of v are exclusively written in each  $S_v$ . This takes O(1) time and  $\sum_v d(v) = O(m)$  processors.

Next, the sum of triangle counts for neighbors are obtained by parallel sum over the arrays  $T_v, S_v$ , taking  $O(\log n)$  time and O(m) processors. Finally the triangle centrality for each  $v \in V$  is computed in parallel, taking O(1) time and O(n) processors.

Therefore in total, the triangle centrality can be computed in  $O(\log n)$  time using  $O(m\sqrt{m})$  CREW processors.

## 9.2 MapReduce Algorithm

The MapReduce model [39, 45, 64] is used to design distributed computing algorithms where efficiency is parameterized by the number of rounds and communication bits. The model appeared some years after the programming paradigm was popularized by Google [31]. It has been successfully employed in practice for massive-scale algorithms [15, 19, 20, 41, 44, 48, 68, 69]. Algorithms in MapReduce use map and reduce functions, executed in sequence. The input is a set of  $\langle key, value \rangle$  pairs that are "mapped" by instances of the map function into a multiset of  $\langle key, value \rangle$  pairs. The map output pairs are "reduced" and also output as a multiset of  $\langle key, value \rangle$  pairs by instances of the reduce function where a single reduce instance gets all values associated with a key. A round of computation is a single sequence of map and reduce executions where there can be many instances of map and reduce functions. Each map or reduce function can complete in polynomial time for input n. Each map or reduce instance is limited to  $O(n^{1-\epsilon})$  memory for a constant  $\epsilon > 0$ , and an algorithm is allowed  $O(n^{2-2\epsilon})$  total memory. The number of machines/processors is bounded to  $O(n^{1-\epsilon})$ , but each machine can run more than one instance of a map or reduce function.

We give a straightforward, 4-round MapReduce algorithm for triangle centrality in Algorithm 5. The basic procedure is to list all triangle edges, then separately combine the endpoints of these edges with the original edge endpoints, and finally accumulate the endpoint counts for each vertex to get the triangle counts and compute the triangle centrality. We will show that it takes O(1)-rounds and communicates  $O(m\sqrt{m})$  bits. Our approach does not require storing any previous state between rounds and is simple to implement. The MapReduce rounds are described next. The input is presumed to be degree-annotated edges in the form of  $\langle (v, d(v)), (u, d(u)) \rangle$  key-value pairs.

In the first round the map function returns only the degree-ordered edges. This ensures that the subsequent reduce function communicates  $O(\sqrt{m}d(v))$  unique neighbor pairs for each vertex. Thus the reduce function in this round gets  $\langle v, \{u|u \in N(v)\}\rangle$  and returns  $\langle uw, v\rangle$  for all  $u, w \in N(v)$  pairs where u < w. In addition a  $\langle uv, 0\rangle$  pair is returned where u < v and 0 signifies that u, v are endpoints of an edge. The goal is to identify in the next round if a pair of neighbors from v are also adjacent, and therefore form a triangle with v. The emitted keys are sorted ordered pairs so that (u, v) and (v, u) will be collected together in the next round. Overall this round communicates  $O(m\sqrt{m})$  bits.

The map function in the second round is the identity function. The reduce function returns triangle neighbor pairs from each triangle obtained in  $\langle uw, \{0, \{v\}\} \rangle$  where the value set contains a 0, which denotes that u, w are triangle endpoints. The reduce function returns all possible pairs for a  $\{u, w, v\}$  triangle as key-values but annotated with 1 so these can be distinguished as triangle neighbors in the next round. Thus for each v in the value set, the reduce function returns the pairs,

$$\langle v, (u, 1) \rangle, \langle u, (v, 1) \rangle, \langle v, (w, 1) \rangle, \langle w, (v, 1) \rangle, \langle u, (w, 1) \rangle, \langle w, (u, 1) \rangle.$$

The third round reads the original edge input in addition to the output from the second round to complete the neighborhood set of each vertex. The rounds up to this point discarded the adjacency information and kept only triangle neighbors. The map function therefore maps  $\langle (v, d(v)), (u, d(u)) \rangle$  to  $\langle v, (u, 0) \rangle$ . Any  $\langle v, (u, 1) \rangle$  pair from the second round is mapped to itself (identity). The reduce function gets the local triangle count  $\Delta(v)$  for the key v by counting the number of (u, 1) values. It should be noted that there can be a multiplicity of a specific (u, 1) value because (u, v) can be in many triangles. Moreover, the second round returned v, u and v, w from the same  $\{v, u, w\}$  triangle and so that triangle will be double-counted in this round. Hence the count of all (u, 1) values equates to  $2\Delta(v)$  and must be halved for the output. At this point the triangle count for each v is known, but in order to compute the triangle centrality the triangle

counts for each neighbor u of v is needed and moreover these counts must be separated between triangle and non-triangle neighbors. Therefore the reduce function will return each neighbor u, annotated if it is a triangle neighbor or not, with the triangle count of v so in the next round each vertex will be able to sum the triangle counts of its neighbors accordingly. Recall that only triangle neighbors from the previous round will have the number 1 annotation, and edges from the original graph have number 0. These numbers are used to distinguish if a neighbor u of v is a triangle neighbor or not. Thus if u appears in the values with only 0 then it is not a triangle neighbor. The reduce function identifies the triangle and non-triangle neighbors and then for each unique  $u \in N(v)$  from the values it returns  $\langle u, (\triangle(v), \$) \rangle$  where

$$\$ = \begin{cases} 1 & \text{if u is a triangle neighbor,} \\ 0 & \text{otherwise.} \end{cases}$$

Also, the key v is returned with its triangle count since it is needed to complete the triangle core sum on the closed triangle neighborhood,  $N_{\wedge}^{+}(v)$ .

The fourth and final round calculates the triangle centrality for every vertex. The map function is the identity. The reduce function takes  $\langle v, \{(\triangle(u),\$)\}\rangle$  and sums all  $\triangle(u)$  in the values separately for triangle neighbors (\$=1) and non-triangle neighbors (\$=0). Then the triangle centrality is calculated for each  $v \in V$  and returned. We remark that the  $\triangle(G)$  can be accumulated at the end of third round and provided to each map and reduction function in the final round, but we leave out the details for brevity.

#### Algorithm 5

#### Round 1

▷ return edge and neighbor pairs

MAP:

$$\langle (v, d(v)), (u, d(u)) \rangle \longrightarrow \langle v, u \rangle$$
 (if  $\pi(v) < \pi(u)$ )

REDUCE:

$$\langle v, N(v) \rangle \longrightarrow \begin{cases} \langle uv, 0 \rangle & u < v \\ \{\langle uw, v \rangle\} & u, w \in N(v), u < w \end{cases}$$

#### Round 2

> return oriented triangle edges

 $Map \mapsto Identity$ 

REDUCE:

$$\langle uw, \{0, \{v\}\} \rangle \longrightarrow \{\langle v, (u, 1) \rangle, \langle u, (v, 1) \rangle, \langle v, (w, 1) \rangle, \langle w, (v, 1) \rangle, \langle u, (w, 1) \rangle, \langle w, (u, 1) \rangle\}_{\forall v}$$

#### Round 3

 $\triangleright$  add E again and compute triangle counts

MAP:

$$\langle v, (u, 1) \rangle \longrightarrow \langle v, (u, 1) \rangle$$
$$\langle (v, d(v)), (u, d(u)) \rangle \longrightarrow \langle v, (u, 0) \rangle$$

REDUCE:

$$\langle v, (\{(u,0)|u \in N(v)\}, (u,1), \ldots)\rangle \longrightarrow \begin{cases} \{\langle u, (\triangle(v), \$)\rangle\}_{\forall u \in N(v)} \\ \langle v, (\triangle(v), 1)\rangle \end{cases}$$

where  $\triangle(v) = \frac{1}{2} \sum_{i=1}^{n} (u, 1)$ , and \$ = 1 if u is a triangle neighbor and 0 otherwise.

#### Round 4

▷ calculate triangle centrality

 $Map \mapsto Identity$ REDUCE:

$$\langle v, \{(\triangle(u), \$)\}\rangle \longrightarrow \left\{\left\langle v, \frac{\frac{1}{3}x + y}{\triangle(G)}\right\rangle\right\}$$
  $(x = \sum_{u}(\triangle(u), 1), y = \sum_{u}(\triangle(u), 0))$ 

**Theorem 7.** Triangle centrality can be computed using MapReduce in four rounds and  $O(m\sqrt{m})$  communication bits for all vertices in a simple, undirected graph G = (V, E).

*Proof.* We will show that Algorithm 5 achieves this claim. The accounting for the number of communication bits is as follows.

The first round makes unique pairwise combinations of neighbor vertices for each vertex. Only degreeordered edges (v, u), where  $\pi(v) < \pi(u)$ , are used to create neighbor pairs, leaving half the edges. Then each vertex v has  $O(\sqrt{m})$  neighbors, all with higher degree, otherwise it would lead to a contradiction of  $\sum_{u \in N(v)} d(u) > O(m)$ . This leads to  $\sum_{v \in V} {d(v) \choose 2} \le \sum_{v \in V} d(v)^2 \le \sqrt{m} \sum_{v \in V} d(v) \le O(m\sqrt{m})$  unique neighbor pairs. Each degree-ordered edge is also returned with the number 0, where there are m instead of 2m edges. Thus in total there are  $m + m\sqrt{m} = O(m\sqrt{m})$  bits communicated by this round.

The second round takes all  $O(m\sqrt{m})$  key-value pairs from the first round but ignores those key-value pairs that do not have the number 0 in the values. This leaves only key-value pairs that correspond to triangle edges. The reduce step then returns the three edges of each triangle as directed pairs. This leads to a total of six triangle neighbor pairs for every triangle. Since there are  $O(m\sqrt{m})$  triangles then overall this round communicates  $O(m\sqrt{m})$  bits.

The third round combines all 2m edges with the triangle neighbor pairs from the second round to complete the neighborhood of each vertex. The triangle counts for triangle and non-triangle neighbors are computed in the reduce step. Then for each vertex v the unique neighbors  $u \in N(v)$  are returned with  $\triangle(v)$  and respectively the number 1 or 0 if u is a triangle neighbor or not. Also v is returned with  $(\triangle(v), 1)$  to complete the triangle core  $N_{\triangle}^+(v)$  of v. Altogether this amounts to  $2m + \sum_{v \in V} d(v) + 1 \le n + 4m \le O(n+m)$  bits communicated in this round.

The fourth and final round sums the counts from triangle neighbors and non-triangle neighbors separately, then computes the triangle centrality. This round returns each vertex with its triangle centrality and therefore communicates O(n) bits.

Altogether each round communicates  $O(m\sqrt{m})$  bits and there are four rounds. Therefore the algorithm takes four MapReduce rounds and communicates  $O(m\sqrt{m})$  bits as claimed.

## 10 Triangle Neighborhood

In many triangle applications, such as computing the clustering coefficient [70] or transitivity ratio [40,61], only the triangle count of a vertex is needed. But in triangle centrality the triangle counts must be partitioned between triangle and non-triangle neighbors. Identifying triangle neighbors is therefore integral to triangle centrality. But this may have other applications. Statistics based on the triangle neighborhood of a vertex could be used for clustering and community detection.

It isn't difficult to identify the triangle neighbors of a vertex. But a triangle neighbor pair  $\{u,v\}$  may be in many different triangles, so the primary challenge to uniquely identifying triangle neighbors is avoiding duplicates. Naïvely listing triangle neighbors for each vertex and sorting will remove duplicates, but takes  $O(m\sqrt{m})$  overall space because that many triangles could be enumerated.

Finding the triangle neighborhood of each vertex in optimal expected time and linear space is easily achievable using perfect hashing [33], as we show in the following section (10.1). But it is burdensome to rely on hash tables which must be re-built on subsequent changes to the graph. Moreover, building a perfect hash table requires randomization. Hash tables in parallel computations are also less appealing because updates and lookups must be synchronized to avoid race conditions.

Finding the triangle neighborhood of each vertex in deterministic, optimal time and linear space without hash tables is not obvious, yet this has received little attention. We solve the problem using simple arrays, and simultaneously obtain the triangle counts for free. Thus we give a simple, deterministic algorithm to count triangles and list the triangle neighbors of every vertex in  $O(m\sqrt{m})$  time and O(m+n) space. Our approach is simple, easily implemented, and amenable to parallel computation. We begin with a basic review of hash-based methods for getting triangle counts and triangle neighbors.

## 10.1 Hash-based Triangle neighborhood

The triangle neighbors of every vertex can be uniquely identified in linear space and optimal expected time using perfect hashing. This is achievable with a simple modification of well-known triangle counting algorithms. Recall that a triangle in G is both a 3-cycle and a 3-clique. An edge is a triangle edge if the endpoints share a common neighbor. Thus all triangles can be identified by computing the set intersection between the neighborhoods of the endpoints of every edge. Equivalently, triangles can be found from every vertex by checking if the unique pairs of neighbors are adjacent. Directly computing triangles using either approach is inefficient and will take O(mn) time. Let us consider basic triangle counting with a folklore algorithm for neighbor-pairing in Listing 1.

## Listing 1 Neighbor-Pair Triangle Counting

```
Require: Abbreviated adjacency sets N_{\pi}(v) for each v \in V for v \in V do

for u \in N_{\pi}(v) do

for w > u \in N_{\pi}(v) do

if \{u, w\} \in E then

increment \Delta(v), \Delta(u), \Delta(w), \Delta(G)
```

The algorithm in Listing 1 requires constant-time access to verify any edge. This is possible in linear space given perfect hashing over edges. Since  $|N_{\pi}(v)| = O(\sqrt{m}) = O(d(v))$ , then there is  $O(\sqrt{m}d(v))$  work for each vertex leading to  $\sqrt{m} \sum_{v \in V} d(v) = O(m\sqrt{m})$  expected time overall. The time is in expectation because while lookups to the table takes constant worst-case time, building the perfect hash table requires randomization. It is possible for v, u to be in many triangles and hence must not be redundantly added to their respective triangle neighbor lists. We address this by pairing the endpoints of each triangle edge just once. Thus for a triangle edge (v, u) the vertex v gets u in its neighbor list, and vice versa, and then all other triangles incident to that edge are skipped. Therefore each vertex of a triangle uniquely gets the other vertices after all three edges of the triangle have been processed. This method only requires a simple modification of Listing 1, as shown in Listing 2.

#### Listing 2 Simple Hash-based Neighbor-Pair Triangle Neighborhood

```
Require: Abbreviated adjacency sets N_{\pi}(v) for each v \in V for v \in V do

for u \in N_{\pi}(v) do

for w \in N(v) do

if \{u, w\} \in E then

add u to v's triangle neighbor list

add v to u's triangle neighbor list

continue to next u \in N_{\pi}(v)
```

The algorithm in Listing 2 exchanges the endpoints of each triangle edge when updating the lists, and since the edges are adjacent then each vertex in the triangle will get the other triangle vertices. Observe that N(v) is used in the inner-most loop resulting in detecting the same triangle three times, once for each edge of the triangle. But the asymptotic complexity is the same as the basic triangle counting algorithm because the work is still bounded by  $O(\sqrt{m}d(v))$  for each vertex. The triangle counts can also be simultaneously computed and keep within the desired asymptotic bounds by allowing every triangle edge to be processed as shown in Listing 3.

#### Listing 3 Hash-based Neighbor-Pair Triangle Neighborhood

```
Require: Abbreviated adjacency sets N_{\pi}(v) for each v \in V for v \in V do

for u \in N_{\pi}(v) do

set t := 0

for w \in N(v) do

if \{u, w\} \in E and \pi(v) < \pi(u) < \pi(w) then

increment \Delta(v), \Delta(u), \Delta(w), \Delta(G)

if t is 0 then

set t := 1

add u to v's triangle neighbor list

add v to u's triangle neighbor list
```

Next we'll review simple, intersection-based triangle counting algorithm that uses sorted, abbreviated adjacency sets,  $N_{\pi}(v)$ . This algorithm is given in Listing 4.

#### Listing 4 Adjacency-Intersection Triangle Counting

```
Require: Sorted, abbreviated adjacency sets N_{\pi}(v) for each v \in V for v \in V do

for u \in N_{\pi}(v) do

for w \in N_{\pi}(v) \cap N_{\pi}(u) do

increment \Delta(v), \Delta(u), \Delta(w), \Delta(G)
```

Since the  $N_{\pi}(v)$  are sorted and  $O(\sqrt{m})$  in size, then the set intersections in Listing 4 take  $O(m\sqrt{m})$  time over all vertices. Subsequently, we can efficiently count all triangles. The set intersections in Listing 4 can alternatively be accomplished by using hash tables so common neighbors  $w \in N_{\pi}(v) \cap N_{\pi}(u)$  are found by testing if the elments in the smaller set are contained in the larger set. Using this, the asymptotic upper-bound can be tightened using the average degeneracy of the graph, which was introduced in [18]. The average degeneracy is defined as,

$$\bar{\delta}(G) = \frac{1}{m} \sum_{\{v,u\} \in E} \min(d(v), d(u)).$$

The tighter bound on runtime for Listing 4 is then,

$$\sum_{\{v,u\}\in E} \min(d(v),d(u)) \le m\bar{\delta}(G) = O(m\bar{\delta}(G)).$$

The arboricity a(G) is  $2\bar{\delta}(G)$  and since  $a(G) \leq \sqrt{m}$  then  $O(m\bar{\delta}(G)) \leq O(m\sqrt{m})$ .

We modify Listing 4 with perfect hash tables to directly find and list the triangle neighbors. This derived method is given in Listing 5.

## Listing 5 Hash-based Adjacency-Intersection Triangle Neighborhood

**Require:** Perfect hash tables  $H_v$  for each  $v \in V$ 

**Require:** abbreviated adjacency sets  $N_{\pi}(v)$  for each  $v \in V$ , stored in perfect hash tables

for  $v \in V$  do

for  $u \in N_{\pi}(v)$  do

for  $w \in N_{\pi}(v) \cap N_{\pi}(u)$  do

insert v into  $H_u$  and  $H_w$ 

insert u into  $H_w$  and  $H_v$ 

insert w into  $H_u$  and  $H_v$ 

Claim 3. Listing the triangle neighbors of each vertex in G takes  $O(m\bar{\delta}(G))$  expected time and O(m+n) space.

Proof. The algorithm in Listing 5 achieves the stated claim as follows. Each set intersection,  $N_{\pi}(v) \cap N_{\pi}(u)$ , takes  $\min(d(v), d(u))$  time because common neighbors are found by checking if elements of the smaller set are contained in the larger set. Since these are perfect hash tables, each check takes O(1) time, but building the hash tables take expected linear time. Then for all edges the set intersections take  $\sum_{\{v,u\}\in E} \min(d(v),d(u)) = m\bar{\delta}(G) \leq ma(G) \leq 2m\sqrt{m} = O(m\sqrt{m})$  time.

Since a vertex cannot have more than d(v) triangle neighbors then each  $H_v$  has size d(v), hence taking O(m) space in total. Then listing out the triangle neighbors from all  $H_v$  would take  $\sum_{v \in V} d(v) = O(m)$  time. Therefore the claim holds.

#### 10.2 Hash-free Algorithm

In Section 8 we introduced our TRIANGLENEIGHBOR algorithm listed in Procedure 1. It is a practical and deterministic algorithm for counting triangles and listing triangle neighbors in optimal time and linear space using only simple arrays. In this section we describe TRIANGLENEIGHBOR in detail and analyze its complexity asserted by Theorem 2.

#### Procedure 1 Triangle Neighbor

```
Require: L_v, array of size |N_{\pi}(v)| for each v \in V with each entry initialized to 0
Require: N_{\pi}(v), sorted abbreviated adjacency for each v \in V
 1: for v \in V do
 2:
         for u \in N_{\pi}(v) do
 3:
             \operatorname{set} t := 0
             set i to the index of u \in N_{\pi}(v)
 4:
             for w \in N_{\pi}(v) \cap N_{\pi}(u) do
 5:
                 set t := 1
 6:
 7:
                 set l to index of w \in N_{\pi}(v) and r to index of w \in N_{\pi}(u)
                                                                                                  ▶ indices from set intersection
                 set L_v(l) := 1 and L_u(r) := 1
 8:
                 increment \triangle(v), \triangle(u), \triangle(w), \triangle(G)
 9:
             if t \neq 0 then
10:
                 set L_v(i) := 1
11:
```

First observe that degree-ordering prevents directed cycles. It should also be clear that any given triangle has a single degree-ordering. Thus each  $\{v,u,w\}$  triangle can be represented by the directed subgraph in Figure 4 corresponding to the ordering  $\pi(v) < \pi(u) < \pi(w)$ . The v,u,w labels have no specific meaning and are only convenient placeholders for the actual vertex labels. Let us call v,u,w respectively the low, middle, and high vertices.



Figure 4: Degree-ordered triangle pattern

It is evident that the highest-ordered vertex can be discovered from the two other vertices in the triangle. This gives us some insight on how to solve the problem. To keep within the desired asymptotic bounds and avoid hash tables, we compute the set intersection over the abbreviated adjacency sets,  $N_{\pi}(v)$ . Then any  $\{v, u, w\}$  triangle represented in Figure 4 can only be reported by computing  $N_{\pi}(v) \cap N_{\pi}(u)$  because v is not in  $N_{\pi}(u)$  or  $N_{\pi}(w)$ . Therefore only the  $\{v, u\}$  edge can facilitate the  $N_{\pi}(v) \cap N_{\pi}(u)$  set intersection. Meaning the set intersections will only involve the abbreviated adjacencies of the low and middle vertices in each triangle, and only the high vertex can be returned by the set intersections. We can use this to our advantage. For the remaining discussion we will assume without loss of generality the triangle ordering in Figure 4.

In computing  $N_{\pi}(v) \cap N_{\pi}(u)$  we know that  $\{v, u\}, \{u, w\}, \{v, w\}$  are all triangle neighbor pairs, but these can be found in many other triangles. We manage duplication of triangle neighbors by computing the set intersection,  $N_{\pi}(v) \cap N_{\pi}(u)$ , from only the (v,u) edge orientation and marking off triangle neighbors. This will return the high vertex w once and therefore each triangle is detected at most one time. Consequently we can also uniquely count triangles. From (v, u) the pairs  $\{v, w\}, \{u, w\}$  are obtained. Meaning we use the "low-middle" edge to make the {low, high} and {middle, high} pairings. Thus the highest-ordered vertex w in the  $\{v, u, w\}$  triangle is paired with the triangle's two lower-ordered vertices. The lower-ordered vertices v, u each respectively mark w to avoid duplicate pairings because w can be with either v or u in other triangles. This leaves the  $\{v,u\}$  pairing, which is managed as follows. On detection of any w from  $N_{\pi}(v) \cap N_{\pi}(u)$ , we mark that u is a triangle neighbor of v. Here u is higher-order than v in the triangle but not the highest-ordered, since the set intersection is acquired from the "low-middle" edge. But there can be another triangle containing (v, u) where u is the high vertex. Hence u will be returned by the set intersection between  $N_{\pi}(v)$  and the abbreviated adjacency of the middle vertex. Without mitigation this will result in duplicate pairing of v and u. But we are already marking the highest-ordered vertex w returned by each set intersection, thus u will be marked when processing another triangle containing (v, u). Only the fact that a neighbor was marked a triangle neighbor matters, not the count of marking that same neighbor. Since all set intersections are over the abbreviated sets, the runtime will remain optimal. Then the handling of marking triangle neighbors to avoid duplication requires only simple arrays. We describe this in detail next.

For every  $v \in V$  an array  $L_v$  of size  $|N_{\pi}(v)|$  is used to mark the position of each  $u \in N_{\pi}(v)$  that is a triangle neighbor of v, as determined by the set intersections. Thus the higher-ordered triangle neighbors of v have the same position in  $L_v$  as in  $N_{\pi}(v)$ . The set intersection  $N_{\pi}(v) \cap N_{\pi}(u)$  is computed as a linear scan over  $N_{\pi}(v)$  and  $N_{\pi}(u)$ , with two pointers to track the positions in  $N_{\pi}(v)$ ,  $N_{\pi}(u)$ . Then any triangle neighbor w found by the set intersection must respectively correspond to positions in  $L_v$  and  $L_u$ . For example, suppose w is found from  $N_{\pi}(v) \cap N_{\pi}(u)$  where w is the fifth neighbor in  $N_{\pi}(v)$  and it is the eighth neighbor in  $N_{\pi}(u)$ . Then positions five and eight in  $L_v$  and  $L_u$  respectively are set to 1 to mark that w is a triangle neighbor of v and u. At the end of computing  $N_{\pi}(v) \cap N_{\pi}(u)$ , if any common neighbor w was found then the position of  $u \in N_{\pi}(v)$  is set to 1 in  $L_v$ .

It is important to note that Procedure 1 does not output the triangle neighbors explicitly, leaving it to subsequent applications. The triangle neighborhoods are contained in the  $L_v$  arrays so any application can process the information as needed. Observe that only the low vertex v in a  $\{v, u, w\}$  triangle like in Figure 4 has marked both u, w as triangle neighbors, whereas u has marked only w, and w has not marked either v or u. But this is sufficient information to identify all triangle neighbors of each vertex. For each v, simply scan over all  $u \in N_{\pi}(v)$  and if the corresponding position for u in  $L_v$  is 1 then add u to the triangle neighbor list of v and also add v to the triangle neighbor list of u. This effectively ensures that the endpoints of each triangle edge are paired, and thus accomplishes the goal of optimally finding all triangle neighbors of each vertex in linear space without hash tables, while also computing all triangle counts.

In summary, our TRIANGLENEIGHBOR algorithm iterates over degree-ordered edges and finds triangle neighbors using degree-ordered set intersections. An array for each vertex is used to mark triangle neighbors identified from set intersection computations. Each  $N_{\pi}(v)$  is a subset of N(v), then N(v) can be a concatenation of  $N_{\pi}(v)$  and the remaining neighbors, given some marker for delineation. The primary work performed by the algorithm is in computing the set intersections, which takes  $O(m\sqrt{m})$  time. Moreover, the set intersection is computed exactly once for each  $\{v, u, w\}$  triangle, and thus the triangle is processed only once for both triangle neighborhood identification and triangle counting. A final pass over each  $N_{\pi}(v)$  to process the triangle neighbors of every v takes only O(m) time. Because each triangle is processed at most once and only simple arrays are used, it is appealing for practical settings. An alternative algorithm that reduces synchronization in parallel settings at the cost of computing the set intersection twice for each triangle is given in Appendix A. Next we prove the complexity asserted by Theorem 2, restated here.

**Theorem 2.** Given a simple, undirected graph G = (V, E), TRIANGLENEIGHBOR counts triangles and lists triangle neighbors in  $O(m\sqrt{m})$  time and O(m+n) space for all vertices in G.

Proof of Theorem 2. The TRIANGLENEIGHBOR algorithm first requires abbreviated adjacency sets,  $N_{\pi}(v)$ , which can be built in O(m) time as established by Claim 1. The work is bounded by sorting the  $N_{\pi}(v)$ , initializing and updating each  $L_v$ , and computing the set intersection  $N_{\pi}(v) \cap N_{\pi}(u)$ . The total time is then as follows.

The  $N_{\pi}(v)$  are at most d(v) in size, then sorting each takes  $d(v) \log d(v)$  time. Thus for all vertices, it takes  $\log n \sum_{v \in V} d(v) = O(m \log n)$  time.

Since each  $L_v$  is at most  $|N_{\pi}(v)| \leq d(v)$  in size, then for all vertices it takes  $\sum_{v \in V} d(v) = O(m)$  time in total to initialize and make updates.

Each  $N_{\pi}(v)$  is sorted and  $O(\sqrt{m})$  in size. Thus computing  $N_{\pi}(v) \cap N_{\pi}(u)$  for each (v, u) edge takes  $O(m\sqrt{m})$  time.

It takes a total of O(m) space for all  $L_v$  since each vertex cannot have more than d(v) triangle neighbors. The  $N_{\pi}(v)$  is stored as the first subset in N(v), hence the  $N_{\pi}(v)$  do not require extraneous space. It takes O(n) space to hold triangle counts and O(m) space to store the triangle neighbors of every vertex.

In total, the algorithm takes  $O(m\sqrt{m})$  time and O(m+n) space.

The correctness of TRIANGLENEIGHBOR is immediate because the endpoints of each triangle edge are oppositely updated and since triangle edges are adjacent, then each triangle vertex will get the other two vertices. The triangle counts follow naturally and are essentially free in the computation.

## 11 Comparison

This section compares triangle centrality to the five other centrality measures discussed in this paper using more realistic graphs than those in Figure 1. Table 4 lists the twenty real-world graphs used in the comparisons. We used Matlab to compute betweenness, closeness, degree, eigenvector, and PageRank centralities. Prior to computing the centrality measures we ensured the graphs were symmetrized, weights and loops were removed, and vertices were labeled from 1..n without gaps, hence obtaining simple, undirected and unweighted graphs. There was a plurality of agreement between triangle centrality and the other measures in many of these graphs, thus giving support to efficacy of triangle centrality. An analysis of the results will follow but first we illustrate four of the smaller networks to aid in visual comparisons of the centralities. If names of nodes in these four networks were known, we assigned numeric vertex labels corresponding to the lexicographic ordering on names. In these next figures, the highest-ranked vertices are indicated by the centrality measures that ranked them.

No.		n (vertices)	m (edges)	$\triangle(G)$ (triangles)	Ref.
1	Borgatti 2006 Figure 3	19	32	13	[8]
2	Zachary's Karate club	34	78	45	[76]
3	Lusseau's Dolphin network	62	159	95	[56]
4	Kreb's 9/11 Hijackers network	62	153	133	[51]
5	Knuth's Les Miserables network	77	254	467	[47]
6	Kreb's US Political Books network	105	441	560	[49]
7	Newman's David Copperfield word adjacencies	112	425	284	[58]
8	Girvan-Newman Division IA College Football network	115	613	810	[37]
9	Watts-Strogatz C. elegans neural network	297	2148	3241	[70]
10	Adamic-Glance 2004 US Election Political Blogosphere	1224	16,715	101,042	[1]
11	Newman's Netscience Co-Authorship network	1461	2742	3764	[58]
12	Watts-Strogatz Western States Power Grid	4941	6594	651	[70]
13	SNAP ca-HepTh	9875	25,973	28,339	[53]
14	SNAP ca-AstroPh	18,771	198,050	1,351,441	[53]
15	SNAP email-Enron	36,692	183,831	727,044	[53]
16	Newman's Condensed Matter Physics network	39,577	175,692	378,063	[57]
17	SNAP web-Stanford	281,903	1,992,636	11,329,473	[53]
18	SNAP com-DBLP	317,080	1,049,866	2,224,385	[53]
19	SNAP com-Amazon	334,863	925,872	667,129	[53]
20	SNAP roadNet-PA	1,088,092	1,541,898	67,150	[53]

Table 4: Test Graphs

Figure 5 depicts a network that appeared in Borgatti's 2006 article [8, Fig. 3]. This network is interesting because 4 of the 19 vertices, more than 20%, are considered central according to the centrality measures described in this paper. There appear to be two clusters that can be disconnected if the vertex ranked highest by betweenness or closeness is removed. But there is a majority agreement among the centrality measures on the vertex ranked highest by triangle centrality.




Figure 5: Borgatti 2006 [8, Fig. 3]

Figure 6 depicts a similar illustration of Zachary's karate club social network [76] that appears in [71, Fig.

2]. This is a well-studied network and serves as a benchmark for clustering and community detection [37]. The network was constructed by Zachary [76] after observing 34 members in a karate club from 1970 to 1972. Following a dispute between the instructor (vertex 1) and administrator (vertex 34), the karate club network split into two respective communities [37]. The instructor and administrator were ranked highest by all the centrality measures except for triangle centrality. The triangle centrality is alone in ranking vertex 14 as the most central. Vertex degree plays a significant role in this network. The instructor and administrator have the two highest degrees in the graph, respectively 16 and 17. In contrast, vertex 14 has degree 5. We remind the reader that the rankings rely on the topology of the graph. While the functional roles of the karate club's two main adversaries imply their influence, it may be that vertex 14 is more important from a structural standpoint. In addition to vertex 14 being central with respect to triangles, it also connects the two communities and appears in the overlap between them [54,71,77].




Figure 6: Zachary's Karate Club

Figure 7 depicts Lusseau's social network of 62 bottlenose dolphins living off Doubtful Sound in New Zealand between 1994 and 2001 [56]. This is another benchmark network for clustering. According to Lusseau and Newman [55], the disappearance of one dolphin, named SN100 (vertex 37), split the network into two communities, but when SN100 reappeared the communities rejoined. Then it comes as no surprise that SN100 is considered the most central by the betweenness and closeness centralities. But it is the dolphin named Grin (vertex 15) that is ranked highest by the remaining centralities including triangle centrality. Grin also has the highest degree in the graph.




Figure 7: Lusseau's Dolphin Network

Figure 8 depicts Kreb's network of the 9/11 hijackers and their accomplices [50,51]. This network of 62 vertices includes the 19 hijackers and 43 co-conspirators. The functional leader of the hijackers was Mohamed Atta (vertex 38) and it's evident from the network that he played an important structural role.

Mohamed Atta has the highest degree and second-highest triangle count, respectively 22 and 42. Marwan Al-Shehhi (vertex 35) has the second-highest degree and highest triangle count, respectively 18 and 47. The largest clique size in the graph is six, and one such clique contains both Mohamed Atta and Marwan Al-Shehhi, but Marwan Al-Shehhi is also a member of an overlapping 6-clique (vertices 2, 20, 35, 55, 58, 59). These two highly ranked vertices gain the same triangle contribution from 14 common neighbors, but Mohamed Atta is at the center of more triangles.

All centrality measures in this study ranked Mohamed Atta the highest. This is an example showing that triangle centrality aligns with the consensus on a central node. We also note that Marwan Al-Shehhi is ranked the second-highest by triangle centrality, which also agrees with closeness, degree, and eigenvector centralities. Thus there is a majority agreement with triangle centrality on the top two vertices in this network.




Figure 8: Kreb's 9/11 Hijackers Network

To aid in evaluating mutual agreement between a centrality measure and competing measures, we devise a special  $m \times n$  dot matrix, where the m rows are networks and the n columns are competing centrality measures. Given a dot matrix K for centrality measure k, we place a dot in the k(i,j) entry if there is agreement on the most central vertex in graph i between centrality measures k and j. The  $\mathbf{K_j}$  column with the most dots indicates that centrality j agrees the most with centrality k and thus is the most similar to k. Then the relative agreement between k and all j centrality measures is simply the sum of dots divided by the total possible. Finally, if the same row across all mutual-rank matrices is completely filled, then all centrality measures ranked the same vertex as the most central. Conversely, an empty row indicates that each centrality measure ranked a different central vertex from all others, suggesting there was no agreement on centrality.

Figure 9a depicts a  $20 \times 5$  dot matrix for each of the six centrality measures in this study, where the rows are the test graphs in Table 4 and the columns are competitor measures. For convenience the percent agreement and similarity (column sums) are included in Figures 9b and 9c, respectively. The dot matrix for triangle centrality has 34 dot entries, meaning out of 20 graphs and 5 competing measures, it agrees with 34% of the choices made for the most central vertex by the other measures. But there are 6 empty rows, which indicates that the central vertex was uniquely identified by triangle centrality in 6 out of the 20 (30%) graphs (Table 4: Nos. 2,8,10,11,18,19). Conversely, there are 14 non-empty rows so triangle centrality had agreement with at least one other centrality measure in 14 out of 20 graphs (70%). We see that eigenvector centrality is the most similar to triangle centrality, selecting the same central vertex in 14 of the graphs (70%). This happens to coincide with number of graphs in which triangle centrality had agreement on centrality, but reader should note it is not generally true. Now observe that closeness centrality has 9 empty rows, the

most among the measures, and only 31% agreement overall. This suggests that closeness centrality has the least agreement with the other measures, followed by betweenness centrality. It is also evident from these dot matrices that degree centrality is the most mutually associated measure, indicating the ubiquitous role that degree plays in structural importance. We can also see from these matrices that the centrality measures all agreed on the central vertex in three graphs (Table 4: Nos. 4,7,17), meaning there was no ambiguity on the central vertex.




Figure 9: (a) Dot matrices  $(20 \times 5)$  for each centrality measure; rows are the graphs numbered 1-20 from Table 4 and columns are given by the respective row in the Column Fields matrix. (b) Percent agreement in ranking. (c) Similarity matrix based on column sums.

In our comparative analysis of centrality we used each centrality measure to answer only the most basic question: "who the most important?". The answer to this question is relative to the centrality measure and hence the top-ranked vertex by a centrality measure is, by virtue of definition, the most important. But the notion of "most" central under even just a single centrality measure is not well-defined because there can be ties for the top rank, and the ranks can be real numbers and hence the separation between the top and next rank may be arbitrarily close. However, nominating the most important node in a network, after handling ties and numeric precision, is a convenient point of analysis. Next we will determine similarity between the centrality measures by using the Jaccard index [42] on the top k rankings, where k is a constant.

The Jaccard index is given by

$$J(i,j) = \frac{|S_i \cap S_j|}{|S_i \cup S_j|} = \frac{|S_i \cap S_j|}{|S_i| + |S_j| - |S_i \cap S_j|},$$

where  $S_i, S_j$  are two sets. Hence, J(i,j) = J(j,i) is a rational number in the interval [0,1] and denotes the fraction of overlap between the sets, where values of 0 and 1 respectively indicate disjoint and equivalent sets. Therefore we interpret two sets to be similar if the Jaccard index is close to 1. The difference 1 - J(i,j) suggests a distance between sets  $S_i, S_j$  and can be used as a similarity metric.

We compare the Jaccard index for top ten (k=10) rankings across all the measures. Since  $|S_i| = |S_j|$  for all pairs then the range of J(i,j) values follows  $\frac{c}{20-c}$ , where c=0..10. Therefore the possible Jaccard index values are  $0, \frac{1}{19}, \frac{2}{18}, \frac{3}{17}, \ldots, 1$ . These are unique so given the real values it isn't difficult to determine the rational form. Also note since the sets are fixed size, then as the numerator increases the denominator

decreases by the same amount. Therefore it is easy to see that a larger set intersection corresponds to a larger Jaccard index.


Table 5 tabulates each of the six centrality measures with their closest, by Jaccard index, centrality competitor for each of the graphs in Table 4 using the top k = 10 rankings. For each centrality measure i we denote  $C_j$  as the closest centrality measure j to i. This is independent of the ordering within the top ten rankings unless there are ties. In the case of a tie, we look at the first node in i's top ten list and choose the j that ranks that same node higher than the other tied measures, moving down i's list on ties or misses. Empty entries in Table 5 indicate J(i,j) = 0 for each pair of centrality measures. The interested reader can find the full table of all-pairs Jaccard similarity in Appendix B.

Table 5: Most similar centrality pairs for graphs in Table 4. (Jaccard index J(i, j) over top k = 10 rankings)

		TC	$_{ m BC}$		CC $DC$				EV	PR		
Graph No.	$C_{j}$	J(i,j)	$C_j$	J(i,j)	$C_j$	J(i,j)	$C_j$	J(i,j)	$C_j$	J(i,j)	$C_j$	J(i,j)
1	EV	.82	CC	.67	ВС	.67	EV	.67	TC	.82	DC	.67
2	$^{\rm CC}$	.67	$^{\rm CC}$	.82	$_{\mathrm{BC}}$	.82	EV	.82	DC	.82	DC	1.0
3	EV	.54	$^{\rm CC}$	.43	$_{\mathrm{BC}}$	.43	$_{\mathrm{PR}}$	.67	DC	.54	DC	.67
4	EV	.54	$_{\mathrm{PR}}$	.67	DC	1.0	$^{\rm CC}$	1.0	TC	.54	$_{\mathrm{BC}}$	.67
5	EV	1.0	$_{\mathrm{PR}}$	.67	DC	.54	$_{\mathrm{PR}}$	.54	TC	1.0	$_{\mathrm{BC}}$	.67
6	DC	.67	$^{\rm CC}$	.54	$_{\mathrm{BC}}$	.54	$_{\mathrm{PR}}$	.82	TC	.54	DC	.82
7	EV	.54	$_{\mathrm{PR}}$	.82	DC	.82	$^{\rm CC}$	.82	DC	.67	$_{\mathrm{BC}}$	.82
8	DC	.25	$^{\rm CC}$	.33	$_{\mathrm{BC}}$	.33	$_{\mathrm{PR}}$	.67	DC	.33	DC	.67
9	EV	1.0	DC	.54	DC	.54	$_{\mathrm{PR}}$	1.0	TC	1.0	DC	1.0
10	EV	.82	$_{\mathrm{PR}}$	.82	DC	.82	$_{\mathrm{PR}}$	1.0	TC	.82	DC	1.0
11	DC	.25	$^{\rm CC}$	.54	$_{\mathrm{BC}}$	.54	$_{\mathrm{PR}}$	.33	DC	.18	$_{\mathrm{BC}}$	.33
12	EV	.82	$^{\rm CC}$	.25	$_{\mathrm{BC}}$	.25	$_{\mathrm{PR}}$	.54	TC	.82	DC	.54
13	EV	.67	$_{\mathrm{PR}}$	.43	$_{\mathrm{BC}}$	.33	$_{\mathrm{PR}}$	.54	TC	.67	DC	.54
14	EV	.67	$_{\mathrm{PR}}$	.33	DC	.54	TC	.67	TC	.67	$^{\rm CC}$	.54
15	EV	.82	$_{\mathrm{PR}}$	.67	TC	.67	$_{\mathrm{PR}}$	.67	TC	.82	DC	.67
16	EV	1.0	$_{\mathrm{PR}}$	.43	DC	.43	$^{\rm CC}$	.43	TC	1.0	$_{\mathrm{BC}}$	.43
17	EV	.33	$_{\mathrm{PR}}$	.33	$_{\mathrm{BC}}$	.18	EV	.82	DC	.82	$_{\mathrm{BC}}$	.33
18	EV	.82	$_{\mathrm{PR}}$	.43	$_{\mathrm{BC}}$	.25	$_{\mathrm{BC}}$	.25	TC	.82	$_{\mathrm{BC}}$	.43
19	DC	.33	DC	.25	$_{\mathrm{BC}}$	.18	$_{\mathrm{PR}}$	.54	TC	.11	DC	.54
20	EV	.05					$_{\mathrm{PR}}$	.05	TC	.05	DC	.05

A visual summary of Table 5 is displayed in Figure 10a using dot matrices for the most similar  $C_j$  to each centrality measure. The counts of  $C_j$  for each centrality measure i in Table 5 are given in Figure 10b. The most frequent  $C_j$  for i can be interpreted as the most similar centrality measure to i over the twenty graphs from Table 4. Observe for each centrality measure in Figure 10b that the most similar centrality to it coincides with the most similar in Figure 9c. This suggests that the top-ranked vertex was a reasonable proxy in comparing measures. The results in Figure 10b demonstrate that similarity is not always symmetric, thus a j can be the most similar to i but i may not be the most similar to j. This is evident between betweenness and closeness centralities.

It is also interesting that the number of j centralities that are most similar to an i centrality is three or less, with the exception of degree centrality. Moreover, it is clear in Figure 10 that each centrality has a competitor measure that is predominantly more similar to it than the others. From this data we again surmise that eigenvector and triangle centrality are similar. The degree of similarity is indicated by the count given in Figure 10b, which has an upper-bound of 20 since that is the number of graphs used in our comparisons. Our results show that closeness is most similar to betweenness, betweenness is most similar to PageRank, PageRank is most similar to degree, and degree is most similar to PageRank. These results also supports our earlier observation that degree centrality is often similar to the other measures.



(a) Summary of similarity from Table 5.

	TC	BC	CC	DC	EV	PR
TC	0	0	1	4	15	0
$_{\mathrm{BC}}$	0	0	7	2	0	10
CC	1	11	0	7	0	0
DC	1	1	3	0	3	12
EV	14	0	0	6	0	0
PR	0	7	1	12	0	0

(b) Frequency counts from Table 5.

Figure 10: (a) Jaccard-based dot matrices  $(20 \times 5)$  for each centrality measure; rows are the graphs numbered 1-20 from Table 4 and columns are given by the respective row in the Column Fields matrix. (b) Counts of closest Jaccard similarities from Table 5.

Overall, we conclude that triangle centrality finds the central vertex in many of the same graphs as other measures, and it aligns with the consensus when there is no ambiguity. Yet, it uniquely identified central vertices in 30% of the graphs, suggesting that it centered on characteristics that are missed by other measures. This makes it a valuable and complementary tool for graph centrality analysis. Moreover, it is asymptotically faster to compute on sparse graphs than the other measures with the exception of degree centrality.

## 12 Performance

Next we give performance results for computing triangle centrality on larger graphs from the Stanford Network Analysis Project (SNAP) [53]. Because the asymptotic runtime bound for triangle centrality differs from the other centrality measures we've discussed, it would be meaningless to compare empirical wallclock times. Therefore we give benchmarks only for triangle centrality.

We implement our main algorithm given in Algorithm 2 in C++ and Posix threads. The benchmarks were run on a single workstation with 256 GB of RAM and 28 Intel Xeon E5-2680 cores. Table 6 tabulates the runtime results.

Table 6: Runtime

	n (vertices)	m (edges)	$\triangle(G)$ (triangles)	wallclock (seconds)
com-Youtube	1,134,890	2,987,624	3,056,386	0.231
as-Skitter	1,696,415	11,095,298	28,769,868	0.589
com-LiveJournal	3,997,962	34,681,189	177,820,130	1.51
com-Orkut	3,072,441	117,185,083	627,584,181	4.87
com-Friendster	$65,\!608,\!366$	1,806,067,135	$4,\!173,\!724,\!142$	68.4

## Acknowledgments

The author thanks David G. Harris for helpful comments.

## References

- [1] L. A. Adamic and N. Glance. The political blogosphere and the 2004 U.S. election: Divided they blog. In *Proceedings of the 3rd International Workshop on Link Discovery*, LinkKDD'05, pages 36–43, 2005.
- [2] J. Alman and V. V. Williams. A refined laser method and faster matrix multiplication. In *Proceedings* of the 2021 ACM-SIAM Symposium on Discrete Algorithms, SODA'21, pages 522–539, 2021.
- [3] A. Azad and A. Buluç. A work-efficient parallel sparse matrix-sparse vector multiplication algorithm. In 2017 IEEE International Parallel and Distributed Processing Symposium, IPDPS'17, pages 688–697, May 2017.
- [4] A. Bavelas. Communication patterns in task oriented groups. *Journal of the Acoustical Society of America*, 22:271–282, 1950.
- [5] A. Björklund, R. Pagh, and V. V. Williams. Listing triangles. In *Proceedings of International Colloquium on Automata, Languages, and Programming*, pages 223–234, 2014.
- [6] P. Bonacich. Factoring and weighting approaches to status scores and clique identification. *Journal of Mathematical Sociology*, 2:113–120, 1972.
- [7] S. P. Borgatti. Centrality and network flow. Social Networks, 27(1):55-71, 2005.
- [8] S. P. Borgatti. Identifying sets of key players in a social network. *Computational and Mathematical Organization Theory*, 12:21–34, 2006.
- [9] S. P. Borgatti and M. G. Everett. A graph-theoretic perspective on centrality. Social Networks, 28(4):466-484, 2006.
- [10] U. Brandes. A faster algorithm for betweenness centrality. Journal of Mathematical Sociology, 25(2):163–177, 2001.
- [11] S. Brin and L. Page. The anatomy of a large-scale hypertextual web search engine. *Computer Networks and ISDN Systems*, 30:1–7, 1998.
- [12] H. M. Bücker and C. Sohr. Reformulating a breadth-first search algorithm on an undirected graph in the language of linear algebra. In 2014 International Conference on Mathematics and Computers in Sciences and in Industry, pages 33–35, 2014.
- [13] A. Buluç and K. Madduri. Parallel breadth-first search on distributed memory systems. In Proceedings of 2011 International Conference for High Performance Computing, Networking, Storage and Analysis, SC'11, pages 65:1–65:12, 2011.
- [14] A. Buluç, T. Mattson, S. McMillan, J. Moreira, and C. Yang. Design of the GraphBLAS API for C. In Parallel and Distributed Processing Symposium Workshops, GABB17. IEEE International, 2017.
- [15] P. Burkhardt. Graphing trillions of triangles. Information Visualization, 16(3):157–166, 2016.
- [16] P. Burkhardt. Internal NSA conference, 2017.
- [17] P. Burkhardt. Optimal algebraic breadth-first search for sparse graphs. ACM Transactions on Knowledge Discovery from Data, 15(5), 2021.
- [18] P. Burkhardt, V. Faber, and D. G. Harris. Bounds and algorithms for graph trusses. *Journal of Graph Algorithms and Applications*, 24(3):191–214, 2020.

- [19] P. Burkhardt and C. A. Waring. A cloud-based approach to big graphs. In *Proceedings of the 19th Annual IEEE High Performance Extreme Computing conference*, HPEC'15, pages 1–8, 2015.
- [20] G. Chennupati, R. Vangara, E. Skau, H. Djidjev, and B. Alexandrov. Distributed non-negative matrix factorization with determination of the number of latent features. *Journal of Supercomuting*, 76:7458– 7488, 2020.
- [21] N. Chiba and T. Nishizeki. Arboricity and subgraph listing algorithms. SIAM Journal on Computing, 14(1):210–223, 1985.
- [22] S. Chu and J. Cheng. Triangle listing in massive networks and its applications. In *Proceedings of the* 17th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, pages 672–680, 2011.
- [23] S. Chu and J. Cheng. Triangle listing in massive networks. ACM Transitions on Knowledge Discovery from Data, 6(4):17:1–17:32, 2012.
- [24] J. Cohen, 2005. Unpublished technical report.
- [25] J. Cohen. Graph twiddling in a MapReduce world. Computing in Science and Engineering, 11(4):29–41, 2009.
- [26] R. Cole. Parallel merge sort. SIAM Journal on Computing, 17(4):770–785, 1988.
- [27] K. Das, S. Samanta, and M. Pal. Study on centrality measures in social networks: a survey. *Social Network Analysis and Mining*, 8(13), 2018.
- [28] T. A. Davis. Graph algorithms via SuiteSparse: GraphBLAS: triangle counting and k-truss. In *Proceedings of the 2018 IEEE High Performance Extreme Computing Conference*, HPEC'18, pages 1–6, 2018.
- [29] T. A. Davis. Algorithm 1000: SuiteSparse:GraphBLAS: graph algorithms in the language of sparse linear algebra. ACM Transactions on Mathematical Software, 45(4):1–25, 2019.
- [30] T. A. Davis. SuiteSparse:GraphBLAS. http:faculty.cse.tamu.edu/davis/GraphBLAS.html, 2019.
- [31] J. Dean and S. Ghemawat. MapReduce: simplified data processing on large clusters. In *Proceedings* of the 6th conference on symposium on operating systems design and implementation, OSDI '04, pages 137–150, 2004.
- [32] S. Fortune and J. Wyllie. Parallelism in random access machines. In *Proceedings of the ACM Symposium on Theory of Computing*, STOC'78, pages 114–118, 1978.
- [33] M. L. Fredman, J. Komlós, and E. Szemerédi. Storing a sparse table with o(1) worst case access time. Journal of the ACM, 31(3):538-544, 1984.
- [34] L. C. Freeman. A set of measures of centrality based on betweenness. Sociometry, 40(1):35-41, 1977.
- [35] L. C. Freeman. Centrality in social networks: Conceptual clarification. Social Networks, 1:215–239, 1979.
- [36] A. Friggeri, G. Chelius, and E. Fleury. Triangles to capture social cohesion. In 2011 IEEE Third International Conference on Social Computing, pages 258–265, 2011.
- [37] M. Girvan and M. E. Newman. Community structure in social and biological networks. *Proceedings of the National Academy of Sciences*, 99(12):7821–7826, 2002.
- [38] G. H. Golub and C. F. V. Loan. *Matrix Computations*. The Johns Hopkins University Press, fourth edition, 2013.

- [39] M. T. Goodrich, N. Sitchinava, and Q. Zhang. Sorting, searching, and simulation in the MapReduce framework. In *Proceedings of International Symposium on Algorithms and Computation*, ISAAC'11, pages 374–383, 2011.
- [40] F. Harary and H. J. Kommel. Matrix measures for transitivity and balance. *Journal of Mathematical Sociology*, 6:199–210, 1979.
- [41] N. J. Harvey, C. Liaw, and P. Liu. Greedy and local ratio algorithms in the mapreduce model. In *Proceedings of the 30th on symposium on parallelism in algorithms and architectures*, SPAA'18, pages 43–52, 2018.
- [42] P. Jaccard. Distribution de la flore alpine dans le bassin des Dranses et dans quelques région voisines. Bulletin de la Société Vaudoise des Sciences Naturelles, 37:241–272, 1901.
- [43] J. JaJa. An Introduction to Parallel Algorithms. Addison Wesley, 1992.
- [44] U. Kang, B. Meeder, and C. Faloutsos. Spectral analysis for billion-scale graphs: Discoveries and Implementation. In *Proceedings of the 15th Pacific-Asia conference on advances in knowledge discovery and data mining*, PAKDD'11, pages 13–25, 2011.
- [45] H. Karloff, S. Suri, and S. Vassilvitskii. A model of computation for MapReduce. In *Proceedings of the* 21st annual ACM-SIAM symposium on discrete algorithms, SODA '10, pages 938–948, 2010.
- [46] J. Kepner and J. Gilbert. *Graph Algorithms in the Language of Linear Algebra*. Society for Industrial and Applied Mathematics, 2011.
- [47] D. E. Knuth. The Stanford GraphBase: A platform for combinatorial computing. Addison-Wesley, 1993.
- [48] T. G. Kolda, A. Pinar, T. Plantenga, C. Sheshadhri, and C. Task. Counting triangles in massive graphs with mapreduce. SIAM Journal on Scientific Computing, 36(5):S48–S77, 2014.
- [49] V. E. Krebs. Books about us politics. http://www.orgnet.com/.
- [50] V. E. Krebs. Mapping networks of terrorist cells. Connections, 24(3):43–52, 2002.
- [51] V. E. Krebs. Uncloaking terrorist networks. https://firstmonday.org/ojs/index.php/fm/article/view/941/863, April 2002.
- [52] M. Latapy. Main-memory triangle computations for very large (sparse (power-law)) graphs. *Theoretical Computer Science*, 407:458–473, 2008.
- [53] J. Leskovec and A. Krevl. SNAP Datasets: Stanford large network dataset collection. http://snap.stanford.edu/data, June 2014.
- [54] H. V. Lierde, T. W. Chow, and G. Chen. Scalable spectral clustering for overlapping community detection in large-scale networks. *IEEE Transactions on Knowledge and Data Engineering*, 32(4):754– 767, 2019.
- [55] D. Lusseau and M. E. Newman. Identifying the role that animals play in their social networks. Proceedings of the Royal Society of London. B, Biological Sciences, 271:S477–S481, 2004.
- [56] D. Lusseau, K. Schneider, O. J. Boisseau, P. Haase, E. Slooten, and S. M. Dawson. The bottlenose dolphin community of Doubtful Sound features a large proportion of long-lasting associations. *Behavioral Ecology and Sociobiology*, 54:396–405, 2003.
- [57] M. E. Newman. The structure of scientific collaboration networks. *Proceedings of the National Academy of Sciences*, 98(2):404–409, 2001.
- [58] M. E. Newman. Finding community structure in networks using the eigenvectors of matrices. *Physical Review E*, 74(3):036104, 2006.

- [59] M. E. Newman. Networks: An Introduction. Oxford University Press, 2010.
- [60] M. E. Newman and J. Park. Why social networks are different from other types of networks. *Physical Review E*, 68(3):036122, 2003.
- [61] M. E. Newman, D. J. Watts, and S. H. Strogatz. Random graph models of social networks. *Proceedings of the National Academy of Sciences*, 99:2566–2572, 2002.
- [62] J. Nieminen. On centrality in a graph. Scandinavian Journal of Psychology, 15:322–336, 1974.
- [63] M. Ortmann and U. Brandes. Triangle listing algorithms: back from the diversion. In *Proceedings of the Meeting on Algorithm Engineering and Experiments*, pages 1–8, 2014.
- [64] A. Pietracaprina, G. Pucci, M. Riondato, F. Silvestri, and E. Upfal. Space-round tradeoffs for MapReduce computations. In *Proceedings of the 2012 ACM international conference on supercomputing*, SC '12, pages 235–244, 2012.
- [65] F. A. Rodrigues. A Mathematical Modeling Approach from Nonlinear Dynamics to Complex Systems, volume 22 of Nonlinear Systems and Complexity, chapter Network Centrality: An Introduction, pages 177–196. Springer, 2018.
- [66] T. Schank and D. Wagner. Finding, counting and listing all triangles in large graphs, an experimental study. In Workshop on Experimental and Efficient Algorithms, WEA, pages 606–609, 2005.
- [67] M. Shaw. Group structure and the behavior of individuals in small groups. Journal of Psychology, 38:139–149, 1954.
- [68] C. E. Tsourakakis, U. Kang, G. L. Miller, and C. Faloutsos. DOULION: Counting triangles in massive graphs with a coin. In *Proceedings of the 15th ACM SIGKDD international conference on knowledge* discovery and data mining, KDD'09, pages 837–846, 2009.
- [69] R. Vernica, M. J. Carey, and C. Li. Efficient parallel set-similarity joins using mapreduce. In Proceedings of the 2010 ACM SIGMOD international conference on management of data, SIGMOD'10, pages 495– 506, 2010.
- [70] D. J. Watts and S. H. Strogatz. Collective dynamics of 'small-world' networks. *Nature*, 393(6684):440–442, 1998.
- [71] J. J. Whang, I. S. Dhillon, and D. F. Gleich. Non-exhaustive, overlapping k-means. In Proceedings of the 2015 SIAM International Conference on Data Mining, pages 936–944, 2015.
- [72] C. Yang, A. Buluç, and J. D. Owens. Implementing push-pull efficiently in GraphBLAS. In *Proceedings* of the International Conference on Parallel Processing, ICPP 2018, pages 89:1–89:11, 2018.
- [73] C. Yang, A. Buluç, and J. D. Owens. Graphblast: A high-performance linear algebra-based graph framework on the gpu. arXiv 1908.01407, 2019.
- [74] C. Yang, Y. Wang, and J. D. Owens. Fast sparse matrix and sparse vector multiplication algorithm on the GPU. In Proceedings of the 2015 IEEE International Parallel and Distributed Processing Symposium Workshop, IPDPSW'15, pages 841–847, 2015.
- [75] R. Yuster and U. Zwick. Fast sparse matrix multiplication. ACM Transactions on Algorithms, 1(1):2–13, 2005.
- [76] W. W. Zachary. An information flow model for conflict and fission in small groups. *Journal of Anthro*pological Research, 33:452–473, 1977.
- [77] M. Zarei, D. Izadi, and K. A. Samani. Detecting overlapping community structure of networks based on vertex-vertex correlations. *Journal of Statistical Mechanics: Theory and Experiment*, 2009(11):P11013, 2009.

## A Alternative Hash-free Triangle neighborhood

Sections 8.1 and 10.2 introduced TRIANGLENEIGHBOR (Procedure 1) as an efficient hash-free triangle neighborhood algorithm. Here we give Procedure 2 that is a modified version of Procedure 1 that is asymptotically equivalent but requires less synchronization across processors at the cost of computing the set intersection twice for each triangle. This may be of interest in some settings where synchronization is a bottleneck.

#### Procedure 2 Alternative Triangle Neighbor

```
Require: T, an array of lists for holding the triangle neighbors of each v \in V
Require: N(v) with sorted N_{\pi}(v) as a subset for each v \in V
 1: for v ∈ V do
         create array L of size |N_{\pi}(v)| with each entry initialized to 0
 2:
 3:
         for u \in N(v) do
             \operatorname{set} t := 0
 4:
             set p to the index of u \in N_{\pi}(v), or null if not a member
 5:
             for w \in N_{\pi}(v) \cap N_{\pi}(u) do
 6:
                 set t := 1
 7:
 8:
                 set i to index of w \in N_{\pi}(v)
                                                                                               > position from set intersection
 9:
                 increment \triangle(v), \triangle(u), \triangle(w), \triangle(G) each by \frac{1}{2}
                 if L[i] \neq 0 then
10:
                     set L[i] := 1
11:
                      add w to T(v) and add v to T[w]
12:
             if t \neq 0, p \neq \text{null}, L[p] \neq 0 then
13:
                 set L[p] := 1
14:
                 add u to T(v) and add v to T[u]
15:
         \operatorname{discard} L
16:
```

In computing  $N_{\pi}(v) \cap N_{\pi}(u)$  we know that  $\{v, u\}, \{u, w\}, \{v, w\}$  are all triangle neighbor pairs, but these can be found in many other triangles. We manage duplication of triangle neighbors by computing the set intersection,  $N_{\pi}(v) \cap N_{\pi}(u)$ , from both  $\{v, u\}$  edge orientations and marking off triangle neighbors. This will return the high vertex w twice. From (v, u) the pairs  $\{v, u\}, \{v, w\}$  are obtained, and (u, v) begets only  $\{u, w\}$ . Meaning we use the "low-middle" edge to make the {low, middle} and {low, high} pairings, and the "middle-low" edge produces the {middle, high} pairing. Thus the highest-ordered vertex w in the  $\{v, u, w\}$ triangle is paired with the triangle's two lower-ordered vertices simply by pairing w with the starting  $\{v,u\}$ edge endpoint that initiated the  $N_{\pi}(v) \cap N_{\pi}(u)$  intersection. Moreover, the lower-ordered vertices v, u each respectively mark w to avoid duplicate pairings because w can be with either v or u in other triangles. This leaves the  $\{v,u\}$  pairing, which is managed as follows. The  $\{v,u\}$  pair is only made from the (v,u) edge; recall that  $\pi(v) < \pi(u)$ . This is necessary to ensure pairing v and u but it does not prevent duplication. Here u is higher-order than v in the triangle but not the highest-ordered, thus u is the middle vertex whereas v is the low vertex. But there can be another triangle containing (v, u) where u is the high vertex. Hence u will be returned by the set intersection between  $N_{\pi}(v)$  and the abbreviated adjacency of the middle vertex. Without mitigation this will result in duplicate pairing of v and u. But we are already marking the highest-ordered vertex w returned by each set intersection, thus w will be marked when processing the triangle containing (v,u) where u is the high vertex. It then only requires that we mark u from the (v,u) edge where u is the middle vertex to avoid duplication.

Procedure 2 identifies the  $\{v,u\}$ ,  $\{u,w\}$ ,  $\{v,w\}$  pairs from both  $\{u,v\}$  counter-oriented edges and therefore computes  $N_{\pi}(v) \cap N_{\pi}(u)$  twice. But, independently treating the two calculations of  $N_{\pi}(v) \cap N_{\pi}(u)$  from the starting endpoint of the  $\{v,u\}$  edge facilitates managing duplicate triangle neighbors without communicating information between v and u. Thus marking triangle neighbors requires local arrays  $L_v$  that can only be updated from v while iterating over its neighborhood to compute the set intersections. This is in contrast to Procedure 1 where the  $L_v$  are stored globally and can be updated while processing neighbors u of v. In this approach only the low and middle vertices can be used to pair the triangle neighbors and subsequently the high vertex is independently managed within the respective  $L_v$  and  $L_u$  arrays without cross-referencing.

Moreover, the low-to-middle triangle neighbor pairing is only possible from the "low-middle" edge so the low vertex can also manage duplication within its independent processing step.

# **B** All-Pairs Jaccard Similarity

Table 7: All-Pairs Jaccard similarity of top k = 10 rankings over graphs in Table 4.

	Graph No.																			
J(i,j)	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
J(TC,BC)	5 15	<u>8</u> 12	$\frac{1}{19}$	5 15	$\frac{4}{16}$	5 15	5 15	0	$\frac{6}{14}$	5 15	0	0	0	$\frac{3}{17}$	$\frac{2}{18}$	$\frac{2}{18}$	2 18	0	1 19	0
J(TC,CC)	$\frac{5}{15}$	$\frac{8}{12}$	$\frac{3}{17}$	$\frac{6}{14}$	$\frac{5}{15}$	$\frac{2}{18}$	$\frac{5}{15}$	$\frac{2}{18}$	$\frac{6}{14}$	$\frac{5}{15}$	0	0	0	$\frac{7}{13}$	$\frac{8}{12}$	$\frac{5}{15}$	$\frac{2}{18}$	0	$\frac{2}{18}$	0
J(TC,DC)	$\frac{7}{13}$	$\frac{7}{13}$	$\frac{5}{15}$	$\frac{6}{14}$	$\frac{7}{13}$	$\frac{8}{12}$	$\frac{6}{14}$	$\frac{4}{16}$	$\frac{9}{11}$	5 15	$\frac{4}{16}$	$\frac{1}{19}$	0	$\frac{8}{12}$	$\frac{4}{16}$	$\frac{4}{16}$	$\frac{5}{15}$	$\frac{1}{19}$	$\frac{5}{15}$	$\frac{1}{19}$
$_{ m J(TC,EV)}$	9	$\frac{8}{12}$	$\frac{7}{13}$	$\frac{7}{13}$	1	$\frac{7}{13}$	$\frac{7}{13}$	$\frac{3}{17}$	1	$\frac{9}{11}$	0	$\frac{9}{11}$	$\frac{8}{12}$	$\frac{8}{12}$	$\frac{9}{11}$	1	$\frac{5}{15}$	$\frac{9}{11}$	$\frac{2}{18}$	$\frac{1}{19}$
J(TC,PR)	$\frac{6}{14}$	$\frac{7}{13}$	$\frac{5}{15}$	$\frac{5}{15}$	$\frac{4}{16}$	$\frac{8}{12}$	$\frac{5}{15}$	$\frac{2}{18}$	$\frac{9}{11}$	$\frac{5}{15}$	0	0	0	$\frac{5}{15}$	$\frac{2}{18}$	$\frac{2}{18}$	$\frac{2}{18}$	0	$\frac{3}{17}$	0
$_{\rm J(BC,CC)}$	$\frac{8}{12}$	$\frac{9}{11}$	$\frac{6}{14}$	$\frac{8}{12}$	$\frac{6}{14}$	$\frac{7}{13}$	$\frac{7}{13}$	$\frac{5}{15}$	$\frac{6}{14}$	$\frac{9}{11}$	$\frac{7}{13}$	$\frac{4}{16}$	$\frac{5}{15}$	$\frac{4}{16}$	$\frac{3}{17}$	$\frac{5}{15}$	$\frac{3}{17}$	$\frac{4}{16}$	$\frac{3}{17}$	0
J(BC,DC)	$\frac{8}{12}$	$\frac{8}{12}$	$\frac{6}{14}$	$\frac{8}{12}$	$\frac{7}{13}$	5 15	$\frac{7}{13}$	$\frac{1}{19}$	$\frac{7}{13}$	9	$\frac{2}{18}$	0	5 15	5 15	$\frac{7}{13}$	$\frac{3}{17}$	$\frac{3}{17}$	$\frac{4}{16}$	$\frac{4}{16}$	0
$_{ m J(BC,EV)}$	$\frac{6}{14}$	$\frac{8}{12}$	$\frac{3}{17}$	$\frac{5}{15}$	$\frac{4}{16}$	$\frac{3}{17}$	5 15	0	$\frac{6}{14}$	5 15	$\frac{1}{19}$	0	0	$\frac{1}{19}$	$\frac{3}{17}$	$\frac{2}{18}$	$\frac{2}{18}$	0	0	0
J(BC,PR)	$\frac{8}{12}$	$\frac{8}{12}$	5 15	$\frac{8}{12}$	$\frac{8}{12}$	$\frac{5}{15}$	$\frac{9}{11}$	$\frac{2}{18}$	$\frac{7}{13}$	$\frac{9}{11}$	$\frac{5}{15}$	0	$\frac{6}{14}$	5 15	$\frac{8}{12}$	$\frac{6}{14}$	5 15	$\frac{6}{14}$	$\frac{3}{17}$	0
$_{\rm J(CC,DC)}$	$\frac{7}{13}$	9	5 15	1	$\frac{7}{13}$	$\frac{2}{18}$	$\frac{9}{11}$	$\frac{3}{17}$	$\frac{7}{13}$	$\frac{9}{11}$	$\frac{2}{18}$	0	$\frac{4}{16}$	$\frac{7}{13}$	$\frac{4}{16}$	$\frac{6}{14}$	$\frac{2}{18}$	$\frac{2}{18}$	$\frac{3}{17}$	0
$_{ m J(CC,EV)}$	$\frac{6}{14}$	9	$\frac{4}{16}$	$\frac{7}{13}$	$\frac{5}{15}$	$\frac{3}{17}$	$\frac{7}{13}$	$\frac{2}{18}$	$\frac{6}{14}$	5 15	$\frac{1}{19}$	0	0	$\frac{6}{14}$	$\frac{8}{12}$	$\frac{5}{15}$	$\frac{2}{18}$	0	0	0
J(CC,PR)	$\frac{8}{12}$	9	$\frac{4}{16}$	$\frac{8}{12}$	$\frac{7}{13}$	$\frac{2}{18}$	$\frac{8}{12}$	$\frac{4}{16}$	$\frac{7}{13}$	9	$\frac{4}{16}$	0	$\frac{3}{17}$	$\frac{7}{13}$	$\frac{2}{18}$	$\frac{3}{17}$	$\frac{2}{18}$	$\frac{1}{19}$	$\frac{2}{18}$	0
J(DC,EV)	$\frac{8}{12}$	$\frac{9}{11}$	$\frac{7}{13}$	$\frac{7}{13}$	$\frac{7}{13}$	5 15	$\frac{8}{12}$	$\frac{5}{15}$	9	$\frac{5}{15}$	$\frac{3}{17}$	$\frac{1}{19}$	0	$\frac{6}{14}$	5 15	$\frac{4}{16}$	9	$\frac{1}{19}$	$\frac{1}{19}$	$\frac{1}{19}$
J(DC,PR)	$\frac{8}{12}$	1	$\frac{8}{12}$	$\frac{8}{12}$	$\frac{7}{13}$	9	$\frac{8}{12}$	$\frac{8}{12}$	1	1	5 15	$\frac{7}{13}$	$\frac{7}{13}$	$\frac{7}{13}$	$\frac{8}{12}$	$\frac{2}{18}$	$\frac{3}{17}$	$\frac{4}{16}$	$\frac{7}{13}$	$\frac{1}{19}$
J(EV,PR)	7	9 11	6 14	5 15	$\frac{4}{16}$	5 15	6 14	$\frac{3}{17}$	9 11	$\frac{5}{15}$	$\frac{3}{17}$	0	0	$\frac{4}{16}$	3 17	2 18	2 18	0	0	0