

# Signature-Based Abduction with Fresh Individuals and Complex Concepts for Description Logics (Extended Version)

Patrick Koopmann

Institute for Theoretical Computer Science, Technische Universität Dresden

patrick.koopmann@tu-dresden.de

## Abstract

Given a knowledge base and an observation as a set of facts, ABox abduction aims at computing a *hypothesis* that, when added to the knowledge base, is sufficient to entail the observation. In signature-based ABox abduction, the hypothesis is further required to use only names from a given set. This form of abduction has applications such as diagnosis, KB repair, or explaining missing entailments. It is possible that hypotheses for a given observation only exist if we admit the use of fresh individuals and/or complex concepts built from the given signature, something most approaches so far do not support or only support with restrictions. In this paper, we investigate the computational complexity of this form of abduction—allowing either fresh individuals, complex concepts, or both—for various description logics, and give size bounds on the hypotheses if they exist.

## 1 Introduction

Description logics (DLs) are a powerful formalism to describe knowledge bases (KBs) containing both general domain knowledge from a DL ontology and a set of facts (the ABox). Using a DL reasoner, we can then infer information that is implicit in the data, and can be logically deduced based on the ontology [Baader *et al.*, 2017]. Sometimes it is useful to not only reason about what logically follows from a DL KB, but to reason also about what does *not* follow. In abduction, we are given a KB as background knowledge, in combination with a set of facts (the observation) that cannot be deduced from the background knowledge. We are then looking for the missing piece in the background knowledge (the hypothesis) that is needed to make the observation logically entailed [Elsenbroich *et al.*, 2006]. This form of reasoning has many applications: 1) it can be used to *explain* why something cannot be deduced [Calvanese *et al.*, 2013], 2) it can be used for *diagnosis* tasks, giving the hypothesis as possible explanation for an unexpected observation [Obeid *et al.*, 2019], and 3) it can be used in *KB repair* to give hints on how to fix missing entailments [Wei-Kleiner *et al.*, 2014].

As a simplified application example from the geology domain, assume we have observed that in an area near a canal,

holes appeared in the street as a result of subsidence due to an unstable ground. A possible explanation could involve the presence of a formation of so-called *evaporite* below the street, which dissolves when in contact with water [Fidelibus *et al.*, 2011]. Our background knowledge consists of a geology ontology together with data about the area. Among others, it contains the following abbreviated axioms:

1.  $\text{EvaFor} \sqcap \exists \text{bord} . (\text{Wat} \sqcap \neg \exists \text{lin} . \text{WatPro}) \sqsubseteq \exists \text{aff} . \text{Dis}$
2.  $\text{EvaFor} \sqcap \exists \text{aff} . \text{Dis} \sqsubseteq \forall \text{abov} . \text{Unst}$
3.  $(\text{Wat} \sqcup \text{Str}) \sqcap \text{EvaFo} \sqsubseteq \perp$       4.  $\text{Wat}(\text{can})$       5.  $\text{Str}(\text{str})$

which state that 1. an **Evaporite Formation** which **borders** to a **Waterway** without **Water-Proof lining** will be **affected** by **Dissolution**; 2. All ground **above** an evaporite formation affected by dissolution is **Unstable**; 3. waterways and **Streets** are not evaporite formations; 4. *can* is a waterway; 5. *str* is a street. Our observation would be that the street is unstable:  $\text{Unst}(a_1)$ , and a hypothesis based on our background knowledge would be

$$\mathcal{H} = \{ \text{EvaFor}(e), \text{abov}(e, \text{str}), \text{bord}(e, \text{can}), \forall \text{lin} . \perp(\text{can}) \}$$

stating that there is an evaporite formation  $e$  below the street that borders with the canal, and that the canal has no lining. A team of geologists can then verify the hypothesis by analysing the canal and the ground below the street. We highlight two aspects of this hypothesis: 1) it refers to a previously unknown individual, the evaporite formation, and 2) it uses a complex (composed) DL concept ( $\forall \text{lin} . \perp$ ). We are interested in hypotheses like this for *signature based abduction*, where we are additionally given a signature  $\Sigma$  of *abducibles*—a vocabulary of names to be used within the hypothesis [Koopmann *et al.*, 2020]. The aim of  $\Sigma$  is to restrict to hypotheses that have explanatory character. In the present example, we would exclude *aff* and *Dis* from  $\Sigma$ , as the dissolution alone would be a too shallow explanation, and *Wat*, because we already know the waterways in the area. Furthermore, we are looking at *ABox abduction*, in which observations and hypotheses are ABoxes, in contrast to TBox abduction [Du *et al.*, 2017; Wei-Kleiner *et al.*, 2014], KB abduction [Koopmann *et al.*, 2020; Elsenbroich *et al.*, 2006] or concept abduction [Bienvenu, 2008].

While there are practical approaches to ABox abduction without signature-restriction [Klarman *et al.*, 2011; Halland and Britz, 2012; Pukancová and Homola, 2017],

works on signature-based ABox abduction often restrict hypotheses to flat ABoxes with a given set of individuals [Ceylan *et al.*, 2020; Du *et al.*, 2012]—which essentially means that statements in a hypothesis can be picked from a finite set—or they restrict to *rewritable* DLs which have limited expressivity [Du *et al.*, 2014; Calvanese *et al.*, 2013]. As with DLs, we usually have the open-world semantics, in which not all individuals are known, and DLs offer much more expressivity, it is a natural next step to look also at abduction allowing for fresh individuals and complex concepts in the result. This changes the nature of the abduction problem drastically as there is now an unbounded set of axioms that may occur in a hypothesis. Problems such as “Does axiom  $\alpha$  belong to some/every/an optimal solution?” [Calvanese *et al.*, 2013; Ceylan *et al.*, 2020] become less helpful while new questions become interesting, such as whether we can give bounds on the number of individuals in a hypothesis, or on the overall size of the hypothesis.

Without understanding the theoretical properties yet, practical methods for signature-based abduction that admit expressive DL concepts in the hypothesis are presented in [Koopmann *et al.*, 2020; Del-Pinto and Schmidt, 2019]. The authors there consider hypotheses that we would call *complete* in the sense that they cover all hypotheses at the same time. To make this possible, solutions are represented in a very expressive DL using non-classical operators such as fixpoints and axiom disjunction. In this setting, ABox abduction can be reduced to uniform interpolation, which however may produce solutions that are triple exponentially large [Zhao and Schmidt, 2017; Lutz and Wolter, 2011]. A natural question is whether this blow-up is really necessary, or whether we can obtain smaller or simpler hypotheses if we drop the requirement of completeness and look for hypotheses in a classical DL that is sufficient to entail the observation.

Unfortunately, our results indicate that this is not the case: if we only allow for fresh individuals but not for complex concepts, hypotheses may require exponentially many assertions for DLs between  $\mathcal{EL}_\perp$  and  $\mathcal{ALCC}$ , while for  $\mathcal{ALCCF}$  there does not even exist a general bound. If in addition, we allow for complex concepts, we are able to explain more observations, but the explanations may become *triple exponentially large* in comparison to the input. Motivated by this, we also consider a variant of the abduction problem in which we are additionally given a bound on the size of the hypothesis. To summarize, our contributions are the following.

1. we investigate signature-based ABox abduction for DLs ranging from  $\mathcal{EL}$  to  $\mathcal{ALCCQI}$  where hypotheses may use *fresh individuals, complex concepts* or *both*,
2. we give tight bounds on the size of hypotheses if they exist,
3. we analyse the computational complexity of deciding whether a hypothesis exists, and
4. we analyse the complexity of deciding whether a hypothesis of bounded size exists.

Proof details are provided in the appendix.

## 2 Description Logics and ABox Abduction

We recall the DLs relevant to this paper [Baader *et al.*, 2017] and provide the formal definition of the abduction problem we consider in this paper.

Let  $N_C$ ,  $N_R$  and  $N_I$  be three pair-wise disjoint sets of respectively *concept*, *role* and *individual names*. A *role*  $R$  is either a role name  $r$  or an *inverse role*  $r^-$ , where  $r \in N_R$ .  $\mathcal{EL}$  *concepts* are built according to the following syntax rule, where  $A \in N_C$  and  $R \in N_R$ :

$$C ::= \top \mid A \mid C \sqcap C \mid \exists R.C$$

More expressive DLs allow for the following additional concepts, where  $n \in \mathbb{N}$ , and in brackets, we give the name of the corresponding DL:

$$\perp \ (\mathcal{EL}_\perp) \quad \neg C \ (\mathcal{ALC}) \quad \leq 1R. \top \ (\mathcal{ALCF}) \quad \leq nR.C \ (\mathcal{ALCQ})$$

In each case, all previous constructs are allowed in the DL as well. Using the letter  $\mathcal{I}$  in the DL name we express that in the above,  $R$  may also be an inverse role. For example,  $(\geq nr^-.C)$  is an  $\mathcal{ALCQI}$  concept but not an  $\mathcal{ALCQ}$ -concept, and  $\exists r.\perp$  is an  $\mathcal{EL}_\perp$  concept. Additional operators are introduced as abbreviations:  $C \sqcup D = \neg(\neg C \sqcap \neg D)$  and  $\forall R.C = \neg \exists R.\neg C$ .

A *KB* is a set of *axioms*, that is, *concept inclusions* (CIs)  $C \sqsubseteq D$ , *concept assertions*  $C(a)$  and *role assertions*  $r(a, b)$ , where  $C, D$  are concepts,  $a, b \in N_I$  and  $r \in N_R$ . If a KB contains only concept and role assertions, it is called *ABox*, and if every concept assertion is of the form  $A(a)$ , where  $A \in N_C$ , *flat ABox*. Given a concept/axiom/KB/ABox  $E$ , we denote by  $\text{sub}(E)$  the set of (sub-)concepts occurring in  $E$ , by  $\text{sig}(E)$  the set of concept and role names occurring in  $E$ , and by  $\text{ind}(E)$  the set of individual names in  $E$ . By  $\text{size}(E)$ , we denote the number of symbols required to write  $E$  down, where operators, as well as concept, role and individual names count as one, numbers are encoded in binary and the introduced abbreviations can be used.

The semantics of DLs is defined based on *interpretations*, which are tuples  $\mathcal{I} = \langle \Delta^\mathcal{I}, \cdot^\mathcal{I} \rangle$  of a set  $\Delta^\mathcal{I}$  of *domain elements* and an *interpretation function*  $\cdot^\mathcal{I}$  which maps every  $a \in N_I$  to some  $a^\mathcal{I} \in \Delta^\mathcal{I}$ , every  $A \in N_C$  to some  $A^\mathcal{I} \subseteq \Delta^\mathcal{I}$ , every  $r \in N_R$  to some  $r^\mathcal{I} \subseteq \Delta^\mathcal{I} \times \Delta^\mathcal{I}$ , satisfies  $(r^-)^\mathcal{I} = (r^\mathcal{I})^-$ , and is extended to concepts as follows, where  $\#S$  denotes the cardinality of the set  $S$ :

$$\begin{aligned} \perp^\mathcal{I} &= \emptyset & (C \sqcap D)^\mathcal{I} &= C^\mathcal{I} \cap D^\mathcal{I} & (\neg C)^\mathcal{I} &= \Delta^\mathcal{I} \setminus C^\mathcal{I} \\ (\exists R.C)^\mathcal{I} &= \{d \in \Delta^\mathcal{I} \mid \langle d, e \rangle \in R^\mathcal{I}, e \in C^\mathcal{I}\} \\ (\leq nR.C)^\mathcal{I} &= \{d \in \Delta^\mathcal{I} \mid \#\{\langle d, e \rangle \in R^\mathcal{I} \mid e \in C^\mathcal{I}\} \leq n\} \end{aligned}$$

$\mathcal{I}$  satisfies an axiom  $\alpha$ , in symbols  $\mathcal{I} \models \alpha$ , if  $\alpha = C \sqsubseteq D$  and  $C^\mathcal{I} \subseteq D^\mathcal{I}$ ;  $\alpha = C(a)$  and  $a^\mathcal{I} \in C^\mathcal{I}$ ; or  $\alpha = r(a, b)$  and  $\langle a^\mathcal{I}, b^\mathcal{I} \rangle \in r^\mathcal{I}$ . If  $\mathcal{I}$  satisfies all axioms in a KB  $\mathcal{K}$ , we write  $\mathcal{I} \models \mathcal{K}$  and call  $\mathcal{I}$  a *model* of  $\mathcal{K}$ . A KB entails an axiom/KB  $E$ , in symbols  $\mathcal{K} \models E$ , if  $\mathcal{I} \models E$  for every model  $\mathcal{I}$  of  $\mathcal{K}$ . If  $\mathcal{K}$  has no model, it is *inconsistent* and we write  $\mathcal{K} \models \perp$ .

We can now define the main reasoning problem we are concerned with in this paper. We consider *signature-based ABox abduction problems*, which for convenience, we just call abduction problems from here on.

**Definition 1.** Let  $\mathcal{L}$  be a DL. An  $\mathcal{L}$  abduction problem is given by a triple  $\mathfrak{A} = \langle \mathcal{K}, \Phi, \Sigma \rangle$ , with an  $\mathcal{L}$  KB  $\mathcal{K}$  of background knowledge, an  $\mathcal{L}$  ABox  $\Phi$  as observation, and a signature  $\Sigma \subseteq \mathbb{N}_C \cup \mathbb{N}_R$  of abducibles; and asks whether there exists a hypothesis for  $\mathfrak{A}$ , i.e. an  $\mathcal{L}$  ABox  $\mathcal{H}$  satisfying

**A1**  $\mathcal{K} \cup \mathcal{H} \not\models \perp$ , **A2**  $\mathcal{K} \cup \mathcal{H} \models \Phi$ , and **A3**  $\text{sig}(\mathcal{H}) \subseteq \Sigma$ .

If we require  $\mathcal{H}$  additionally to be flat, we speak of a flat abduction problem.

Condition **A1** is required to avoid trivial solutions, since everything follows from a basic inconsistency. Condition **A2** ensures the hypothesis is indeed effective, and Condition **A3** is what makes this a *signature-based* abduction problem.

In addition, different minimality criteria can be put on the hypothesis, such as *size-*, *subset-*, *semantic minimality* [Calvanese et al., 2013], or *completeness* [Koopmann et al., 2020]. In this paper, we consider size minimality, for which the corresponding decision problem is the following.

**Definition 2.** A size-restricted (flat)  $\mathcal{L}$  abduction problem is a tuple  $\mathfrak{A} = \langle \mathcal{K}, \Phi, \Sigma, n \rangle$ , where  $\mathfrak{A}' = \langle \mathcal{K}, \Phi, \Sigma \rangle$  is a (flat)  $\mathcal{L}$  abduction problem and  $n$  is a number encoded in binary. A hypothesis for  $\mathfrak{A}$  is an  $\mathcal{L}$ -ABox  $\mathcal{H}$  which is a hypothesis for  $\mathfrak{A}'$  and additionally satisfies  $\text{size}(\mathcal{H}) \leq n$ .

### 3 Flat ABox Abduction

We first consider flat ABox abduction: the size of hypotheses, and the complexity of deciding their existence. This problem is similar to that of *query emptiness* [Baader et al., 2016] which asks whether for a given set  $\mathcal{T}$  of CIs, Boolean query  $q$  and signature  $\Sigma$ , there exists a flat ABox  $\mathcal{A}$  with  $\text{sig}(\mathcal{A}) \subseteq \Sigma$ , s.t.  $\mathcal{T} \cup \mathcal{A}$  entails that query. Query emptiness for *instance queries* is essentially the special case of flat ABox abduction where the observation is of the form  $A(a)$  and the background knowledge contains only CIs. This immediately gives us lower bounds for the decision problem of flat ABox abduction. The other results in this section do not follow, but can be shown similarly as in [Baader et al., 2016]. Similar to query emptiness, flat ABox abduction only becomes interesting if the DL is powerful enough to create inconsistencies. Otherwise, we can construct a trivial hypothesis candidate as

$$\mathcal{H} = \{A(a) \mid A \in (\Sigma \cap \mathbb{N}_C), a \in \text{ind}(\mathcal{K} \cup \Phi)\} \cup \{r(a, b) \mid r \in (\Sigma \cap \mathbb{N}_R), a, b \in \text{ind}(\mathcal{K} \cup \Phi)\}.$$

Clearly,  $\mathcal{H}$  satisfies **A1** and **A3**. If it does not satisfy **A2**, then neither would any other ABox. Consequently, if there is a solution to the abduction problem, then  $\mathcal{H}$  must be such a solution. This means that for  $\mathcal{EL}$ , flat ABox abduction can always be performed in polynomial time. On the other hand, already for  $\mathcal{EL}_\perp$ , solutions may require exponentially many fresh individual names.

**Theorem 1.** *There exists a family  $\langle \mathcal{K}_n, \Phi, \Sigma \rangle_{n>0}$  of flat  $\mathcal{EL}_\perp$  abduction problems s.t. every hypothesis is of size exponential in the size of  $\mathcal{K}_n$ .*

*Proof.* We set  $\Phi = A(a)$  and  $\Sigma = \{B, r\}$ , and let  $\mathcal{K}_n$  use concept names  $X_1, \overline{X}_1, \dots, X_n, \overline{X}_n$  to encode an exponential counter.  $\mathcal{K}_n$  uses this to ensure that an  $r$ -chain of distinct

$2^n$  elements from  $a$  to an instance of  $B$  entails  $A(a)$ .

$$\begin{aligned} B &\sqsubseteq \overline{X}_1 \sqcap \dots \sqcap \overline{X}_n \\ \exists r. (\overline{X}_i \sqcap X_{i-1} \sqcap \dots \sqcap X_1) &\sqsubseteq X_i \quad \text{for } i \in \llbracket 1, n \rrbracket \\ \exists r. (X_i \sqcap X_{i-1} \sqcap \dots \sqcap X_1) &\sqsubseteq \overline{X}_i \quad \text{for } i \in \llbracket 1, n \rrbracket \\ \exists r. (\overline{X}_i \sqcap \overline{X}_j) &\sqsubseteq \overline{X}_i \quad \text{for } i, j \in \llbracket 1, n \rrbracket, j < i \\ \exists r. (X_i \sqcap \overline{X}_j) &\sqsubseteq X_i \quad \text{for } i, j \in \llbracket 1, n \rrbracket, j < i \\ X_i \sqcap \overline{X}_i &\sqsubseteq \perp \quad \text{for } i \in \llbracket 1, n \rrbracket \\ X_1 \sqcap \dots \sqcap X_n &\sqsubseteq A \end{aligned}$$

The only way to produce this chain of  $2^n$  elements is using  $2^n - 1$  role assertions, which establishes our lower bound.  $\square$

This bound remains tight if we add expressivity up to  $\mathcal{ALCT}$ , while we lose any bound on the size once we additionally allow concepts of the form  $\leq 1r$ .  $\top$ .

**Theorem 2.** *If there exists a hypothesis for a flat  $\mathcal{L}$  abduction problem  $\mathfrak{A}$ , then there exists one of size*

1. polynomial in the size of  $\mathfrak{A}$  if  $\mathcal{L} = \mathcal{EL}$ ,
2. exponential in the size of  $\mathfrak{A}$  if  $\mathcal{L} = \mathcal{ALCT}$ , and
3. if  $\mathcal{L} = \mathcal{ALCF}$ , no general upper bound based on  $\mathfrak{A}$  can be given.

*Proof sketch.* We already established the bound for  $\mathcal{L} = \mathcal{EL}$ . For  $\mathcal{ALCT}$ , we assume there exists some hypothesis  $\mathcal{H}_0$ , based on which we build one of bounded size. For this, we pick any model  $\mathcal{I}$  of  $\mathcal{H}_0 \cup \mathcal{K}$ , which allows us to identify individual names  $a \in \text{ind}(\mathcal{H}_0)$  using at most exponentially many types  $\text{tp}(a) = \text{tp}(a^\mathcal{I})_{\mathcal{I}}$ , where

$$\text{tp}(d)_{\mathcal{I}} = \{C \in \text{sub}(\mathcal{K} \cup \Phi) \mid d \in C^\mathcal{I}\}.$$

We associate to every type  $\text{tp}(a)$  an individual name  $b_{\text{tp}(a)}$ , and define  $h : \text{ind}(\mathcal{H}_0) \rightarrow \mathbb{N}_I$  by  $h(a) = a$  if  $a \in \text{ind}(\mathcal{K} \cup \Phi)$  and  $h(a) = b_{\text{tp}(a)}$  otherwise. The hypothesis  $\mathcal{H}$  is then:

$$\{A(h(a)) \mid A(a) \in \mathcal{H}_0\} \cup \{r(h(a), h(b)) \mid r(a, b) \in \mathcal{H}_0\}.$$

Based on  $\mathcal{I}$  and  $h$ , one can construct a model for  $\mathcal{K} \cup \mathcal{H}$ , so that  $\mathcal{H}$  satisfies **A1**. Because  $\mathcal{H}_0$  satisfies **A3**, by construction, so does  $\mathcal{H}$ . Finally, using the fact that  $h$  is a homomorphism from  $\mathcal{K} \cup \mathcal{H}_0$  into  $\mathcal{K} \cup \mathcal{H}$  s.t. for every  $a \in \text{ind}(\mathcal{K} \cup \Phi)$   $h(a) = a$ , we can show that  $\mathcal{K} \cup \mathcal{H} \models \Phi$ , and thus **A2**.

For  $\mathcal{L} = \mathcal{ALCF}$ , we note that if there was a bound on the size of hypotheses, we could decide the instance query emptiness problem for  $\mathcal{ALCF}$  by iterating over all candidates, contradicting that this problem is undecidable for  $\mathcal{ALCF}$  [Baader et al., 2016].  $\square$

The proof of Theorem 2 indicates how types can be used to perform abduction, which is used in the following theorem.

**Theorem 3.** *Flat  $\mathcal{L}$  ABox abduction is*

- P-complete for  $\mathcal{L} = \mathcal{EL}$ ,
- EXPTIME-complete for  $\mathcal{L} = \mathcal{EL}_\perp$ ,
- CONEXPTIME-complete for  $\mathcal{L} = \mathcal{ALCT}$ ,
- undecidable for  $\mathcal{L} = \mathcal{ALCF}$ .

*Proof sketch.* For  $\mathcal{EL}$ , we already described a method to compute and verify hypotheses in P. For the other DLs, we use type elimination to compute in exponential time the set  $T_{\mathcal{K} \cup \Phi}$  of types  $t \subseteq \text{sub}(\mathcal{K} \cup \Phi)$  that can occur in models of  $\mathcal{K}$ . For a type  $t$  and a set  $T$  of types, we denote by  $S_T^r(t) \subseteq T$  the types an  $r$ -successor of a  $t$ -individual can have. We iterate over all assignments  $s : \text{ind}(\mathcal{K} \cup \Phi) \rightarrow T_{\mathcal{K} \cup \Phi}$  for which we set

$$\mathcal{H}_s = \{A(a) \mid a \in I, A \in s(a) \cap \Sigma\} \\ \cup \{r(a, b) \mid a, b \in I, r \in \Sigma, s(b) \in S_{T_{\mathcal{K} \cup \Phi}}^r(s(a))\},$$

where  $I$  contains an additional individual name for every type and  $s$  is extended to  $I$ . If there exists a hypothesis, then the hypothesis constructed in the proof for Theorem 2 is contained in some such  $\mathcal{H}_s$  s.t.  $\mathcal{K} \cup \mathcal{H}_s \not\models \perp$ , so that we can directly check **A1–A3** from Def. 2 on the generated  $\mathcal{H}_s$ . **A1** can be verified syntactically using the types. For  $\mathcal{EL}_\perp$ , **A2** is verified in time polynomial in the size of  $\mathcal{H}_s$  and thus in EXP-TIME. For  $\mathcal{ALCI}$ , we guess a model of  $\mathcal{K} \cup \mathcal{H}_s$  that does not entail  $\Phi$  by assigning a type to every individual and possibly adding a new element per type. If this fails,  $\mathcal{K} \cup \mathcal{H}_s \models \Phi$ .  $\square$

## 4 Abduction with Complex Concepts

As illustrated in the introduction, abduction may only be successful if we also admit complex concepts in the hypothesis. Determining such hypotheses turns out to be more challenging than for flat hypotheses, and we cannot find a correspondence to a known problem as for flat abduction. Indeed, one might assume such a relation to uniform interpolation: given a KB  $\mathcal{K}$  and a signature  $\Sigma$ , the uniform interpolant of  $\mathcal{K}$  for  $\Sigma$  is a  $\Sigma$  ontology that captures all entailments of  $\mathcal{K}$  within  $\Sigma$  [Koopmann and Schmidt, 2015]. By negating the observation, this can be used to perform *complete* abduction [Koopmann *et al.*, 2020; Del-Pinto and Schmidt, 2019], that is, to compute a hypothesis that would be entailed by any other hypothesis. However, if we are interested just in computing any hypothesis rather than a complete one, this correspondence falls short, as uniform interpolants have stronger requirements than hypotheses, and the reasons for non-existence are different: namely, capturing *all* entailments of  $\mathcal{K}$  in  $\Sigma$  in the uniform interpolant, using only names from  $\Sigma$ , may require infinitely many axioms in case of cyclic axioms. In contrast, for abduction, non-existence is always due to Condition **A1**.

We consider abduction for  $\mathcal{ALC}$ ,  $\mathcal{EL}$ , and  $\mathcal{EL}_\perp$ , starting with the latter. In  $\mathcal{EL}$  and  $\mathcal{EL}_\perp$ , complex concepts do not bring much benefit compared to fresh individuals: an  $\mathcal{EL}_\perp$  concept can only state the existence of role successors, which we can also do in flat ABoxes. In fact, for  $\mathcal{EL}_\perp$ , if we allow complex concepts *instead* of fresh individuals, hypotheses even get more complex.

**Theorem 4.** *There exists a family of  $\mathcal{EL}_\perp$  abduction problems for which every hypothesis without fresh individuals is at least of double exponential size. If there exists such a hypothesis, there always exists one of at most double exponential size, whose existence can be decided in exponential time.*

*Proof sketch.* The family of abduction problems is obtained similarly as in the proof for Theorem 1, only that we now use

two roles  $r$  and  $s$ . To get the corresponding upper bound, we first flatten an existing hypothesis  $\mathcal{H}_0$  and again simplify the ABox based on the types in some model, however this time making sure the resulting flat ABox can be translated back into a complex one without fresh individuals.

The same care has to be taken when we modify the method used for Theorem 3. Specifically, we have to make sure that the hypothesis  $\mathcal{H}_s$  that we generate for a given mapping  $s : \text{ind}(\mathcal{K} \cup \Phi) \rightarrow T_{\mathcal{K} \cup \Phi}$  does not contain cycles between fresh individuals, so that it can be translated into a hypothesis without fresh individuals. Our fresh individuals are now of the form  $b_{a,t,i}$ , where  $a \in \text{ind}(\mathcal{K} \cup \Phi)$ ,  $t \in T = T_{\mathcal{K} \cup \Phi}$ , and  $i \in \llbracket 1, 2^{|T|} \rrbracket$ . Set  $b_{a,s(a),0} = a$ .  $\mathcal{H}_s$  is then defined as:

$$\mathcal{H}_s = \{A(b_{a,t,k}) \mid a \in \text{ind}(\mathcal{A}), t \in T, k \in \llbracket 0, 2^{|T|} \rrbracket, \\ A \in (T \cap \Sigma)\} \\ \cup \{r(b_{a,t_1,k}, b_{a,t_2,k+1}) \mid a \in \text{ind}(\mathcal{K} \cup \Phi), t_1 \in T, r \in \Sigma, \\ t_2 \in S_T^r(t_1), k \in \llbracket 0, 2^{|T|} - 1 \rrbracket\} \\ \cup \{r(a, b) \mid s(b) \in S_T^r(s(a))\} \quad \square$$

The hardness result requires again  $\perp$ : for  $\mathcal{EL}$ , we can always use a flat solution as in the last section. In contrast, with more expressivity, the problem becomes even harder, even if we do admit fresh individuals. The reason is that for concepts of the form  $\forall r.C$ , fresh individuals cannot come to the rescue anymore, and disjunctions may become necessary. The following theorem is shown by a modification of a construction in [Ghilardi *et al.*, 2006].

**Theorem 5.** *There is a family of  $\mathcal{ALC}$  abduction problems for which the smallest (non-flat) ABox hypotheses are triple exponential in size.*

We can show that this bound is tight.

**Theorem 6.** *Let  $\mathcal{A}$  be an  $\mathcal{ALC}$  abduction problem. Then, there exists a hypothesis for  $\mathcal{A}$  iff there exists a hypothesis of triple exponential size.*

To show this theorem, we use a technique similar as for Theorem 2: we take an arbitrary hypothesis, and transform it into one of triple exponential size. However, this time, a construction based on a single model is not sufficient, and we have to take into account an appropriate abstraction of *several* models of  $\mathcal{K} \cup \mathcal{H}_0$ . We thus proceed as follows:

1. we abstract the KB  $\mathcal{K} \cup \mathcal{H}_0$  into a model abstraction,
2. we reduce the size of this abstraction,
3. based on which we construct a hypothesis  $\mathcal{H}$  of triple exponential size.

In the model abstraction, elements are represented as nodes  $v \in V$  that are labeled with a set  $\lambda(v)$  of types with the intuitive meaning “this element may have one of the types in  $\lambda(v)$ ”. Role relations are represented using tuples  $\langle v_1, t, r, v_2 \rangle$  which are read as: if the node  $v_1$  has type  $t$ , then it has an  $r$ -successor corresponding to  $v_2$ . Roughly, from a model abstraction, we can obtain a model using the following inductive procedure: 1) start with the nodes that represent individuals, 2) assign to each node a type from its label set, 3) if for those types, the node requires successor nodes, add those

and continue in 2). To allow for unbounded paths in models for finite acyclic model abstractions, we further have “open” nodes whose role successors are only restricted by the TBox.

**Definition 3.** An interpretation abstraction for  $\langle \mathcal{K}, \Phi, \Sigma \rangle$  is a tuple  $\mathcal{J} = \langle V, \lambda, s, \mathfrak{R}, F \rangle$ , where

- $V$  is a set of nodes,
- $\lambda : V \rightarrow 2^{T_{\mathcal{K} \cup \Phi}}$  maps each node to a set of types,
- partial function  $s : \mathbb{N}_1 \dashrightarrow V$  assigns individuals to nodes
- $\mathfrak{R} \subseteq (V \times T_{\mathcal{K} \cup \Phi} \times (\Sigma \cap \mathbb{N}_R) \times V)$  is the role assignment,
- and  $F \subseteq V$  is the set of open nodes.

$\mathcal{J}$  abstracts an interpretation  $\mathcal{I}$  if there is a subset  $\Delta' \subseteq \Delta^{\mathcal{I}}$  and a function  $h : \Delta' \rightarrow V$  s.t. for every  $d \in \Delta'$  and  $r \in (\Sigma \cap \mathbb{N}_R)$ :

**I1** for all  $a \in \mathbb{N}_1$ , if  $s(a)$  is defined, then  $s(a) = h(a^{\mathcal{I}})$

**I2**  $\text{tp}(d)_{\mathcal{I}} \in \lambda(h(d))$ ,

**I3** if  $h(d) \notin F$ , then for every  $e \in \Delta^{\mathcal{I}}$ ,  $\langle d, e \rangle \in r^{\mathcal{I}}$  iff  $e \in \Delta'$  and  $\langle h(d), \text{tp}(d)_{\mathcal{I}}, r, h(e) \rangle \in \mathfrak{R}$ .

We need some additional requirements to make sure an interpretation abstraction can be represented as an  $\mathcal{ALC}$  ABox  $\mathcal{H}$  s.t.  $\text{sig}(\mathcal{H}) \subseteq \Sigma$ . We call a node  $v \in V$  for which there exists  $a \in \mathbb{N}_1$  with  $s(a) = v$  internal node, and otherwise outgoing node. If  $v = s(a)$  for  $a \in \text{ind}(\mathcal{K} \cup \Phi)$ , we call  $v$  named node. A path in  $\langle V, \lambda, s, \mathfrak{R}, F \rangle$  is a sequence

$$\pi = v_0, t_0, r_0, v_1, t_1, r_1, \dots, t_{n-1}, r_{n-1}, v_n$$

s.t. for each  $i \in \llbracket 0, n-1 \rrbracket$ ,  $\langle v_i, t_i, r_i, t_{i+1} \rangle \in \mathfrak{R}$ .  $\pi$  is cyclic if it contains a node twice, and its length is its number of nodes.

**Definition 4.**  $\mathcal{J} = \langle V, \lambda, s, \mathfrak{R}, F \rangle$  is called  $\mathcal{ALC}$ -conform if

**D1** there is no cyclic path between outgoing nodes,

**D2** for every internal node  $v$ , if  $\langle v, t, r, v' \rangle \in \mathfrak{R}$ , then  $\langle v, t', r, v' \rangle \in \mathfrak{R}$  for every  $t' \in \lambda(v')$ , and

**D3** for every  $\langle v_1, t, r, v_2 \rangle \in \mathfrak{R}$ , where  $v_2$  is internal, there exists  $\langle v_1, t, r, v'_2 \rangle \in \mathfrak{R}$  s.t.  $v'_2$  is outgoing.

We say that  $\mathcal{J}$  is  $\Sigma$ -complete if

**D4** for every  $v \in V$ , and  $t_1 \in \lambda(v)$ ,  $\lambda(v)$  contains every type  $t_2 \in T_{\mathcal{K} \cup \Phi}$  s.t.  $\lambda(t_1) \cap \Sigma = \lambda(t_2) \cap \Sigma$ , and

**D5** for every  $\langle v_1, t, r, v_2 \rangle \in \mathfrak{R}$  and  $t' \in T_{\mathcal{K} \cup \Phi}$  s.t.  $t \cap \Sigma = t' \cap \Sigma$ , also  $\langle v_1, t', r, v_2 \rangle \in \mathfrak{R}$ .

**D1** ensures that we can represent the outgoing paths from a node  $s(a)$  in a single assertion  $C(a)$ . **D2** expresses that the relations between internal nodes is independent of the type, which allows to represent them using role assertions. **D3** is needed to capture allowed paths using universal role restrictions. **D4** and **D5** ensure that  $\mathcal{J}$  can be captured using only names in  $\Sigma$ .

From here on, we fix an abduction problem  $\mathfrak{A} = \langle \mathcal{K}, \Phi, \Sigma \rangle$ . We say that  $\mathcal{J}$  explains  $\Phi$  iff some model of  $\mathcal{K}$  is abstracted by  $\mathcal{J}$  and every model of  $\mathcal{K}$  that is abstracted by  $\mathcal{J}$  entails  $\Phi$ . If  $\mathcal{J}$  is  $\mathcal{ALC}$ -conform,  $\Sigma$ -complete, and explains  $\Phi$ , we call it a hypothesis abstraction.

**Lemma 1.** Every hypothesis  $\mathcal{H}$  for  $\mathfrak{A}$  can be translated into a hypothesis abstraction.

Now that we can translate hypotheses into an alternative representation, the next step is to decrease their size while making sure they still explain the observation. For this, we can now use similar techniques as in Theorems 2 and 4, where we now identify nodes  $v \in V$  based on their label  $\lambda(v)$  instead of on a single type.

**Lemma 2.** Let  $\mathcal{J}$  be a hypothesis abstraction. Then,  $\mathcal{J}$  can be transformed into a hypothesis abstraction  $\mathcal{J}' = \langle V', \lambda', \mathfrak{R}', F' \rangle$  where, for  $\ell = |T_{\mathcal{K} \cup \Phi}| \cdot 2^{|T_{\mathcal{K} \cup \Phi}|}$ , i)  $V'$  contains at most  $\ell$  internal nodes, ii) every  $v \in V'$  has at most  $\ell$  successors in  $\mathfrak{R}'$ , and iii) every path of outgoing nodes contains at most  $\ell$  nodes.

The final ingredient to establish Theorem 6 is the following lemma.

**Lemma 3.** For every  $\mathcal{ALC}$ -conform,  $\Sigma$ -complete interpretation abstraction  $\mathcal{J} = \langle V, \lambda, s, \mathfrak{R}, F \rangle$ , there exists an ABox  $\mathcal{H}$  s.t. i) the models of  $\mathcal{K} \cup \mathcal{H}$  are exactly the models of  $\mathcal{K}$  accepted by  $\mathcal{J}$ , ii)  $|\text{ind}(\mathcal{H})| \leq |V|$ , and iii) for every  $a \in \text{ind}(\mathcal{H})$ ,  $\mathcal{H}$  contains one assertion  $C(a)$ , with  $\text{size}(C)$  exponentially bounded by the path lengths between outgoing nodes in  $\mathcal{J}$ .

Unfortunately, interpretation abstractions cannot be as easily constructed by a deterministic procedure as we did for Theorems 3 and 4, as there can be non-trivial interactions between connected internal nodes, and we only have a double exponential upper bound on their number. To decide  $\mathcal{ALC}$  abduction, we can however guess an interpretation abstraction within the bounds of Lemma 2, and then guess assignments of types to nodes to obtain its models. We thus obtain the following theorem.

**Theorem 7.**  $\mathcal{ALC}$  ABox abduction is in  $\text{N2EXPTIME}^{\text{NP}}$ .

## 5 Size-Restricted Abduction

Because hypotheses can become very large, a natural requirement is to compute hypotheses of minimal or bounded size. We here obtain the following complexities.

**Theorem 8.** Size restricted  $\mathcal{L}$  ABox abduction is

- NP-complete for  $\mathcal{L} = \mathcal{EL}$ ,
- NEXPTIME-complete for  $\mathcal{L} = \mathcal{EL}_{\perp}$ ,
- NEXPTIME<sup>NP</sup>-complete for the flat variant and  $\mathcal{L} \in \{\mathcal{ALC}, \mathcal{ALCT}\}$ , and
- in 2EXPTIME for  $\mathcal{L} = \mathcal{ALCQL}$ .

The upper bounds are based on guess-and-check algorithms. For  $\mathcal{EL}$ , we exploit the fact that, by Theorem 2, we can always find a solution of polynomial size. For  $\mathcal{EL}_{\perp}$ , we note that the size of the hypothesis is exponentially bounded by the number of bits used for the size bound  $k$ . The NEXPTIME<sup>NP</sup>-upper bound can be obtained by a refinement of the procedure used in the proof for Theorem 3. For the double exponential upper bound, we iterate over the double exponentially many possible KBs within the size and signature bounds—independent on whether we are interested in flat or complex solutions—and then check for entailment in time exponential in the size of the current solution. The lower bounds are provided by the following lemmas.

**Lemma 4.** *Size-restricted  $\mathcal{EL}$  abduction is NP-hard.*

*Proof sketch.* We reduce the NP-complete problem CNF-SAT to deciding whether a given signature-based problem has a hypothesis of size at most  $k$ . Let  $\phi = c_1 \wedge \dots \wedge c_n$  be a CNF formula over propositional variables  $p_1, \dots, p_m$ .  $\mathcal{K}$  contains the following axioms:

$$\begin{aligned} \text{True} \sqsubseteq P \quad \text{False} \sqsubseteq P \quad \exists r. \text{True} \sqsubseteq C \quad \exists s. \text{False} \sqsubseteq C \\ r(c_i, p_j) \text{ for every } i \in \llbracket 1, n \rrbracket, j \in \llbracket 1, m \rrbracket, \text{ if } p_j \in c_j \\ s(c_i, p_j) \text{ for every } i \in \llbracket 1, n \rrbracket, j \in \llbracket 1, m \rrbracket, \text{ if } \neg p_j \in c_j \end{aligned}$$

$\Phi$  contains  $P(p_i)$  for every  $i \in \llbracket 1, m \rrbracket$  and  $C(c_i)$  for every  $i \in \llbracket 1, n \rrbracket$ . Finally,  $\Sigma = \{\text{True}, \text{False}\}$ .  $\langle \mathcal{K}, \Phi, \Sigma \rangle$  has a hypothesis of size at most  $2m$  iff  $\phi$  is satisfiable.  $\square$

**Lemma 5.** *Size restricted  $\mathcal{EL}_\perp$  abduction is NEXPTIME-hard.*

*Proof sketch.* The hardness follows from a reduction of the NEXPTIME-complete *exponential tiling problem*, which is given by a tuple  $\langle T, T_I, t_e, V, H, n \rangle$  of a set  $T$  of tile types, a sequence  $T_I \in T^*$  of initial tiles, a final tile  $t_e$ , vertical and horizontal tiling conditions  $V, H \subseteq T \times T$ , and a number  $n$  in unary encoding. A solution to this problem is then a *tiling*, as a function  $f : \llbracket 1, 2^n \rrbracket \times \llbracket 1, 2^n \rrbracket \rightarrow T$  assigning tiles to coordinates, s.t. the first tiles are as in  $T_I$ ,  $f(2^n, 2^n) = t_e$ , and that obeys the vertical and horizontal tiling conditions [van Emde Boas, 1997].

In the reduction, concept names Start and End respectively mark the initial and the final tile. We implement two binary counters  $X$  and  $Y$  as for Theorem 1 which are decremented over the roles  $x$  and  $y$ , and encode the coordinates of the tiles. Each tile type  $t \in T$  is represented by a concept name  $A_t$ . We enforce the horizontal tiling conditions using CIs

$$\exists x. A_t \sqcap A_{t'} \sqsubseteq \perp \quad \text{for each } \langle t, t' \rangle \in (T \times T) \setminus H$$

and correspondingly for the vertical conditions. The (hidden) concept name  $B \notin \Sigma$  is used to ensure that the hypothesis contains at least one individual per coordinate. This name is initialised by the individual satisfying Start, and then propagated in  $x$  and  $y$  direction, provided that a tiling type is associated. The observation to be explained is  $\text{End}(a)$ , where End occurs in the following CI:

$$\prod_{i=1}^n X_i \sqcap \prod_{i=1}^n Y_i \sqcap B \sqcap A_{t_e} \sqsubseteq \text{End}$$

and the abducibles are

$$\Sigma = \{\text{Start}, x, y\} \cup \{A_t \mid t \in T\}.$$

Without the size restriction, a valid hypothesis corresponds to a binary tree with tile types associated to each node, and tiling conditions ensured along the  $x$ - and  $y$ -successors. To make sure it forms a  $2^n \times 2^n$  grid, we choose the size  $k$  appropriately in a way that every coordinate can be used at most once. Valid hypotheses of size  $k$  then correspond to solutions to the tiling problem.  $\square$

To present the proof idea for the NEXPTIME<sup>NP</sup>-hardness result more concisely, we introduce a new tiling problem.

**Definition 5.** A NEXPTIME<sup>NP</sup>-tiling problem is given by a tuple  $\langle T, T_I, t_e, H_1, V_1, H_2, V_2, n \rangle$ , where  $\langle T, T_I, t_e, H_1, V_1, n \rangle$  is an exponential tiling problem,  $H_2, V_2 \subseteq T \times T$  are additional tiling conditions, and for which we want to decide the existence of a valid tiling  $f : \llbracket 1, 2^n \rrbracket \times \llbracket 1, 2^n \rrbracket \rightarrow T$  for the tiling problem  $\langle T, T_I, t_e, V_1, H_1, n \rangle$ , s.t. for no  $i \in \llbracket 1, 2^n \rrbracket$ , there exists a valid tiling for the tiling problem  $\langle T, f(i), t_e, V_2, H_2, n \rangle$ , where  $f(i)$  denotes the  $i$ th row of the tiling  $f$ .

In other words, we have to find a tiling using conditions  $H_1$  and  $V_1$ , while avoiding any rows that can be first row of any tiling for conditions  $H_2$  and  $V_2$ .

**Lemma 6.** *The NEXPTIME<sup>NP</sup>-tiling problem is NEXPTIME<sup>NP</sup>-hard.*

**Lemma 7.** *Size-restricted  $\mathcal{ALC}$  abduction is NEXPTIME<sup>NP</sup>-hard.*

*Proof sketch.* We modify the construction for Lemma 5 to encode the NEXPTIME<sup>NP</sup>-tiling problem. We now use 3 roles  $x, y, z$  and corresponding binary counters so that, together with the size restriction, each hypothesis will have the shape of a cube. The bottom side of this cube has to correspond to a tiling for  $\langle T, T_I, t_e, V_1, H_1, n \rangle$ , which can be achieved using similar axioms as for Lemma 5. For nodes outside of the bottom side of the cube, we require the use a different set of concept names for the tile types, which are of the form  $A_t^*$ , and for which we have the axiom  $T^* \sqsubseteq \bigsqcup_{t \in T} A_t^*$ . We use

$$\Sigma = \{\text{Start}, x, y, z, T^*\} \cup \{A_t \mid t \in T\},$$

and again require every coordinate to be assigned some tile type. For the coordinates outside the bottom side, we have to use the concept name  $T^*$  to assign tile types, which leaves the precise selection of the tile type to the different models of the hypothesis. We detect tiling errors in the different  $x \times z$ -squares with the following axioms

$$\exists x. A_t^* \sqcap A_{t'} \sqsubseteq B_3 \quad \text{for } \langle t, t' \rangle \in (T \times T) \setminus H_2$$

and correspondingly for  $V_2$ . This information is propagated along the succeeding coordinates so that the observation  $\text{End}(a)$  is only entailed if every model of the hypothesis encodes a tiling error on each of the  $x \times z$  squares.  $\square$

## 6 Outlook

We believe that our results for complex abduction in  $\mathcal{ALC}$  can be extended to  $\mathcal{ALCI}$ , and that the bound for size restricted  $\mathcal{ALCQI}$  abduction in is tight. A question is whether we can improve the NEXPTIME<sup>NP</sup>-bound for the most general variant of our abduction problem. Apart from that, we want to investigate our setting for observations formulated as conjunctive queries, which would allow us to explain negative query answers [Calvanese *et al.*, 2013]. Another interesting question is what happens if we allow fresh individual names for abduction with ontologies formulated using existential rules. For the  $\mathcal{EL}_\perp$ -variant, we are currently working on a practical method for computing size-minimal flat hypotheses.

## Acknowledgements

Patrick Koopmann is supported by DFG grant 389793660 of TRR 248 (see <https://www.perspicuous-computing.science/>).

## References

- [Baader *et al.*, 2016] Franz Baader, Meghyn Bienvenu, Carsten Lutz, and Frank Wolter. Query and predicate emptiness in ontology-based data access. *J. Artif. Intell. Res.*, 56:1–59, 2016.
- [Baader *et al.*, 2017] Franz Baader, Ian Horrocks, Carsten Lutz, and Ulrike Sattler. *An Introduction to Description Logic*. Cambridge University Press, 2017.
- [Bienvenu, 2008] Meghyn Bienvenu. Complexity of abduction in the  $\mathcal{EL}$  family of lightweight description logics. In *Proceedings of KR 2008*, pages 220–230. AAAI Press, 2008.
- [Calvanese *et al.*, 2013] Diego Calvanese, Magdalena Ortiz, Mantas Simkus, and Giorgio Stefanoni. Reasoning about explanations for negative query answers in DL-Lite. *J. Artif. Intell. Res.*, 48:635–669, 2013.
- [Ceylan *et al.*, 2020] İsmail İlkan Ceylan, Thomas Lukasiewicz, Enrico Malizia, Cristian Molinaro, and Andrius Vaicenavicius. Explanations for negative query answers under existential rules. In Diego Calvanese, Esra Erdem, and Michael Thielscher, editors, *Proceedings of KR 2020*, pages 223–232. AAAI Press, 2020.
- [Del-Pinto and Schmidt, 2019] Warren Del-Pinto and Renate A. Schmidt. ABox abduction via forgetting in  $\mathcal{ALC}$ . In *The Thirty-Third AAAI Conference on Artificial Intelligence, AAAI 2019*, pages 2768–2775. AAAI Press, 2019.
- [Du *et al.*, 2012] Jianfeng Du, Guilin Qi, Yi-Dong Shen, and Jeff Z. Pan. Towards practical ABox abduction in large description logic ontologies. *Int. J. Semantic Web Inf. Syst.*, 8(2):1–33, 2012.
- [Du *et al.*, 2014] Jianfeng Du, Kewen Wang, and Yi-Dong Shen. A tractable approach to ABox abduction over description logic ontologies. In Carla E. Brodley and Peter Stone, editors, *Proceedings of the Twenty-Eighth AAAI Conference on Artificial Intelligence*, pages 1034–1040. AAAI Press, 2014.
- [Du *et al.*, 2017] Jianfeng Du, Hai Wan, and Huaguan Ma. Practical TBox abduction based on justification patterns. In *Proceedings of the Thirty-First AAAI Conference on Artificial Intelligence*, pages 1100–1106, 2017.
- [Elsenbroich *et al.*, 2006] Corinna Elsenbroich, Oliver Kutz, and Ulrike Sattler. A case for abductive reasoning over ontologies. In *Proceedings of the OWLED’06 Workshop on OWL: Experiences and Directions*, 2006.
- [Fidelibus *et al.*, 2011] M Dolores Fidelibus, Francisco Gutiérrez, and Giuseppe Spilotro. Human-induced hydrogeological changes and sinkholes in the coastal gypsum karst of Lesina Marina area (Foggia Province, Italy). *Engineering Geology*, 118(1-2):1–19, 2011.
- [Ghilardi *et al.*, 2006] Silvio Ghilardi, Carsten Lutz, and Frank Wolter. Did I damage my ontology? A case for conservative extensions in description logics. In Patrick Doherty, John Mylopoulos, and Christopher A. Welty, editors, *Tenth International Conference on Principles of Knowledge Representation and Reasoning (KR 2006)*, pages 187–197. AAAI Press, 2006.
- [Halland and Britz, 2012] Ken Halland and Katarina Britz. ABox abduction in  $\mathcal{ALC}$  using a DL tableau. In *2012 South African Institute of Computer Scientists and Information Technologists Conference, SAICSIT ’12*, pages 51–58, 2012.
- [Klarman *et al.*, 2011] Szymon Klarman, Ulle Endriss, and Stefan Schlobach. ABox abduction in the description logic  $\mathcal{ALC}$ . *Journal of Automated Reasoning*, 46(1):43–80, 2011.
- [Koopmann and Schmidt, 2015] Patrick Koopmann and Renate A. Schmidt. Uniform interpolation and forgetting for  $\mathcal{ALC}$  ontologies with ABoxes. In *Proceedings of AAAI 2015*, pages 175–181. AAAI Press, 2015.
- [Koopmann *et al.*, 2020] Patrick Koopmann, Warren Del-Pinto, Sophie Tournet, and Renate A. Schmidt. Signature-based abduction for expressive description logics. In Diego Calvanese, Esra Erdem, and Michael Thielscher, editors, *Proceedings of the 17th International Conference on Principles of Knowledge Representation and Reasoning, KR 2020*, pages 592–602. AAAI Press, 2020.
- [Lutz and Wolter, 2011] Carsten Lutz and Frank Wolter. Foundations for uniform interpolation and forgetting in expressive description logics. In *Proceedings of IJCAI 2011*, pages 989–995. IJCAI/AAAI, 2011.
- [Obeid *et al.*, 2019] Mariam Obeid, Zeinab Obeid, Asma Moubaidin, and Nadim Obeid. Using description logic and Abox abduction to capture medical diagnosis. In Franz Wotawa, Gerhard Friedrich, Ingo Pill, Roxane Koitz-Hristov, and Moonis Ali, editors, *Advances and Trends in Artificial Intelligence. From Theory to Practice*, pages 376–388, Cham, 2019. Springer International Publishing.
- [Pukancová and Homola, 2017] Júlia Pukancová and Martin Homola. Tableau-based ABox abduction for the  $\mathcal{ALCHO}$  description logic. In *Proceedings of the 30th International Workshop on Description Logics*, 2017.
- [van Emde Boas, 1997] Peter van Emde Boas. The convenience of tilings. *Lecture Notes in Pure and Applied Mathematics*, pages 331–363, 1997.
- [Wei-Kleiner *et al.*, 2014] Fang Wei-Kleiner, Zlatan Dragisic, and Patrick Lambrix. Abduction framework for repairing incomplete  $\mathcal{EL}$  ontologies: Complexity results and algorithms. In *Proceedings of the Twenty-Eighth AAAI Conference on Artificial Intelligence*, pages 1120–1127. AAAI Press, 2014.
- [Zhao and Schmidt, 2017] Yizheng Zhao and Renate A. Schmidt. Role forgetting for  $\mathcal{ALCOQH}(\nabla)$ -ontologies using an Ackermann-based approach. In Carles Sierra, editor, *Proceedings of the Twenty-Sixth International Joint Conference on Artificial Intelligence, IJCAI 2017*, pages 1354–1361. ijcai.org, 2017.

# Proof Details

## A Flat ABox Hypotheses

**Theorem 2.** *If there exists a hypothesis for a flat  $\mathcal{L}$  abduction problem  $\mathfrak{A}$ , then there exists one of size*

1. polynomial in the size of  $\mathfrak{A}$  if  $\mathcal{L} = \mathcal{EL}$ ,
2. exponential in the size of  $\mathfrak{A}$  if  $\mathcal{L} = \mathcal{ALCC}\mathcal{I}$ , and
3. if  $\mathcal{L} = \mathcal{ALCC}\mathcal{F}$ , no general upper bound based on  $\mathfrak{A}$  can be given.

*Proof.* Let  $\mathcal{H}_0$  be a hypothesis for  $\langle \mathcal{K}, \Phi, \Sigma \rangle$ . We first complete the argument in the main text for  $\mathcal{L} = \mathcal{ALCC}\mathcal{I}$ , and then for  $\mathcal{L} = \mathcal{EL}$ .

For  $\mathcal{L} = \mathcal{ALCC}\mathcal{I}$ , we construct  $\mathcal{H}$  and  $h$  as in the main text based on an arbitrary hypothesis  $\mathcal{H}_0$  and an arbitrary model  $\mathcal{I}$  of  $\mathcal{K} \cup \mathcal{H}_0$ . Note that there can be at most exponentially many distinct types occurring in  $\mathcal{I}$  (one for each subset of  $\text{sub}(\mathcal{K} \cup \Phi)$ ). Consequently,  $\mathcal{H}$  contains at most exponentially many individual names, and, because it is flat, at most exponentially many assertions. It remains to show that  $\mathcal{H}$  satisfies **A1** and **A2**.

For **A2**, we need to show that  $\mathcal{K} \cup \mathcal{H} \not\models \perp$ . For this, we construct the interpretation  $\mathcal{J}$  based on the types occurring in  $\mathcal{I}$ . The domain of  $\mathcal{J}$  contains an element for every individual in  $\mathcal{K} \cup \Phi$  and additionally types occurring in  $\mathcal{I}$ . We first define a superset of the domain:

$$\Delta = \text{ind}(\mathcal{K} \cup \Phi) \cup \{\text{tp}(d)_{\mathcal{I}} \mid d \in \Delta^{\mathcal{I}}\}$$

We define a function  $g : \Delta^{\mathcal{I}} \rightarrow \Delta$  by setting:

$$g(d) = \begin{cases} a & \text{if } d = a^{\mathcal{I}} \text{ and } a \in \text{ind}(\mathcal{K} \cup \Phi) \\ \text{tp}(d)_{\mathcal{I}} & \text{otherwise} \end{cases}$$

The interpretation  $\mathcal{J}$  is now defined as follows for all  $a \in \mathbf{N}_{\mathbf{I}}$ ,  $A \in \mathbf{N}_{\mathbf{C}}$  and  $r \in \mathbf{N}_{\mathbf{R}}$ :

- $\Delta^{\mathcal{J}} = \{g(d) \mid d \in \Delta^{\mathcal{I}}\}$
- $a^{\mathcal{J}} = \begin{cases} a & \text{if } a \in \text{ind}(\mathcal{K} \cup \Phi) \\ t & \text{if } a \in \text{ind}(\mathcal{H}) \setminus \text{ind}(\mathcal{K} \cup \Phi) \\ & \text{and } a = b_t \text{ for } t \in T_{\mathcal{K} \cup \Phi} \\ \text{arbitrary} & \text{otherwise} \end{cases}$
- $A^{\mathcal{J}} = \{g(d) \mid d \in A^{\mathcal{I}}\}$ ,
- $r^{\mathcal{J}} = \{\langle g(d), g(e) \rangle \mid \langle d, e \rangle \in r^{\mathcal{I}}\}$

It can be shown by structural induction that for every concept  $C \in \text{sub}(\mathcal{K} \cup \Phi)$  and  $d \in \Delta^{\mathcal{I}}$ ,  $d \in C^{\mathcal{I}}$  iff  $g(d) \in C^{\mathcal{J}}$ , which implies that  $\mathcal{J}$  is a model of  $\mathcal{K}$ . Note however that this would not work for  $\mathcal{L} = \mathcal{ALCC}\mathcal{F}$ , since the transformation can change the number of role-successors.

We can also show that  $\mathcal{J} \models \mathcal{H}$ . First observe that for every  $a \in \text{ind}(\mathcal{K} \cup \mathcal{H}_0)$  and  $b \in \text{ind}(\mathcal{K} \cup \mathcal{H})$ ,  $h(a) = b$  iff  $g(a^{\mathcal{I}}) = b^{\mathcal{J}}$ : if  $a \in \text{ind}(\mathcal{K} \cup \Phi)$ , we have by definition  $h(a) = a$ ,  $g(a^{\mathcal{I}}) = a$  and  $a = a^{\mathcal{I}}$ . Otherwise, we have  $h(a) = b_{\text{tp}(a^{\mathcal{I}})_{\mathcal{I}}}$ ,  $g(a^{\mathcal{I}}) = \text{tp}(a^{\mathcal{I}})_{\mathcal{I}}$  and  $b_{\text{tp}(a^{\mathcal{I}})_{\mathcal{I}}}^{\mathcal{J}} = \text{tp}(a^{\mathcal{I}})_{\mathcal{I}}$ . In both cases, we have  $h(a) = b$  iff  $g(a^{\mathcal{I}}) = b^{\mathcal{J}}$ .

Assume  $A(b) \in \mathcal{H}$ . Then  $b = h(a)$  for some  $a \in \text{ind}(\mathcal{K} \cup \mathcal{H}_0)$  and  $A(a) \in \mathcal{H}_0$ . We have  $g(a^{\mathcal{I}}) = b^{\mathcal{J}}$  by the above observation, and we have already pointed out that this implies for every  $C \in \text{sub}(\mathcal{K} \cup \Phi)$  that  $a^{\mathcal{I}} \in C^{\mathcal{I}}$  iff  $b^{\mathcal{J}} \in C^{\mathcal{J}}$ . Since  $\mathcal{I} \models \mathcal{H}_0$ , we have  $a^{\mathcal{I}} \in A^{\mathcal{I}}$ , and thus  $b^{\mathcal{J}} \in A^{\mathcal{J}}$ , so that  $\mathcal{J} \models A(b)$ .

Assume  $r(b_1, b_2) \in \mathcal{H}$ . Then, there exists  $r(a_1, a_2) \in \mathcal{H}_0$  s.t.  $h(a_1) = b_1$  and  $h(a_2) = b_2$ . Again we can conclude that  $g(a_1^{\mathcal{I}}) = b_1^{\mathcal{J}}$ ,  $g(a_2^{\mathcal{I}}) = b_2^{\mathcal{J}}$  and  $\langle a_1^{\mathcal{I}}, a_2^{\mathcal{I}} \rangle \in r^{\mathcal{I}}$ , which by definition of  $r^{\mathcal{J}}$  implies that  $\langle b_1^{\mathcal{J}}, b_2^{\mathcal{J}} \rangle \in r^{\mathcal{J}}$ , so that  $\mathcal{J} \models r(b_1, b_2)$ .

We have shown that  $\mathcal{J} \models \mathcal{K} \cup \mathcal{H}$ , and thus that  $\mathcal{K} \cup \mathcal{H}$  is satisfiable, that is, that  $\mathcal{H}$  satisfies **A1**.

It remains to show **A2**, that is,  $\mathcal{K} \cup \mathcal{H} \models \Phi$ . Assume  $\mathcal{K} \cup \mathcal{H} \not\models \Phi$ , that is, there exists some assertion  $\alpha \in \Phi$  s.t.  $\mathcal{K} \cup \mathcal{H} \not\models \alpha$ . If  $\alpha$  is of the form  $r(a, b)$ , then this axiom must explicitly occur in either  $\mathcal{K}$  or  $\mathcal{H}_0$ , since  $\mathcal{ALCC}\mathcal{I}$  is not expressive enough to enforce such entailments in a different way). If  $r(a, b) \in \mathcal{K}$ , trivially  $\mathcal{K} \cup \mathcal{H} \models r(a, b)$ . If  $r(a, b) \in \mathcal{H}_0$ , by construction also  $r(a, b) \in \mathcal{H}$ .

Assume  $\alpha$  is of the form  $C(a)$ , and there exists a model  $\mathcal{J}$  of  $\mathcal{K} \cup \mathcal{H}$  s.t.  $\mathcal{J} \not\models C(a)$ . Using the homomorphism  $h : \text{ind}(\mathcal{H}_0) \mapsto \text{ind}(\mathcal{H})$ , we can transform  $\mathcal{J}$  into a model  $\mathcal{J}'$  of  $\mathcal{K} \cup \mathcal{H}_0$  s.t.  $\mathcal{J}' \not\models C(a)$ . Specifically, we define  $\mathcal{J}'$  by

- $\Delta^{\mathcal{J}'} = \Delta^{\mathcal{J}} \cup \{a^{\mathcal{J}'} \mid a \in \text{ind}(\mathcal{H}_0)\}$ ,
- $A^{\mathcal{J}'} = A^{\mathcal{J}} \cup \{a^{\mathcal{J}'} \mid a \in \text{ind}(\mathcal{H}_0), h(a)^{\mathcal{J}} \in A\}$  for all  $A \in \mathbf{N}_{\mathbf{C}}$ , and
- $r^{\mathcal{J}'} = r^{\mathcal{J}} \cup \{\langle a^{\mathcal{J}'}, b^{\mathcal{J}'} \rangle \mid a, b \in \text{ind}(\mathcal{H}_0), \langle h(a)^{\mathcal{J}}, h(b)^{\mathcal{J}} \rangle \in r^{\mathcal{J}}\}$  for all  $r \in \mathbf{N}_{\mathbf{R}}$ .

$\mathcal{J}'$  can be seen as the result of duplicating some elements from  $\mathcal{J}$  based on  $h$ , while keeping their concept names and role successors. Thus, it is easy to see that the transformation is type-preserving, that is, for every  $a \in \text{ind}(\mathcal{H})$  and  $b \in \text{ind}(\mathcal{H}_0)$  s.t.  $h(b) = a$ , we have  $\text{tp}(a^{\mathcal{J}})_{\mathcal{J}} = \text{tp}(b^{\mathcal{J}'})_{\mathcal{J}'}$ . As a consequence,  $\mathcal{J}' \models \mathcal{K}$  and  $\mathcal{J}' \not\models C(a)$ . Furthermore, by construction,  $\mathcal{J}' \models \mathcal{H}_0$ . We obtain that  $\mathcal{K} \cup \mathcal{H}_0 \not\models \Phi$ , and thus contradicting that  $\mathcal{H}_0$  was a hypothesis for  $\Phi$  to begin with. Consequently, there cannot be such a model  $\mathcal{J}$  of  $\mathcal{K} \cup \mathcal{H}$ , and we must have  $\mathcal{K} \cup \mathcal{H} \models \Phi$ .

We have shown that  $\mathcal{H}$  satisfies Conditions **A1**–**A2**, and thus that it is an exponentially sized hypothesis for  $\langle \mathcal{K}, \Phi, \Sigma \rangle$ .

Now assume  $\mathcal{L} = \mathcal{EL}$ . We then construct a polynomially sized hypothesis by

$$\mathcal{H} = \{A(a) \mid A \in \Sigma \cap \mathbf{N}_{\mathbf{C}}, a \in \text{ind}(\mathcal{K} \cup \Phi)\} \cup \{r(a, b) \mid r \in \Sigma \cap \mathbf{N}_{\mathbf{R}}, a, b \in \text{ind}(\mathcal{K} \cup \Phi)\}$$

Again we can define a homomorphism  $h$  from  $\mathcal{H}_0$  onto  $\mathcal{H}$ : this time, we map every individual name not in  $\text{ind}(\mathcal{K} \cup \Phi)$  to some randomly selected individual name. We have  $\text{sig}(\mathcal{H}) \subseteq \Sigma$  by construction, and  $\mathcal{K} \cup \mathcal{H} \not\models \perp$  since every  $\mathcal{EL}$  KB is consistent.  $\mathcal{K} \cup \mathcal{H} \models \Phi$  can be shown as for  $\mathcal{L} = \mathcal{ALCC}\mathcal{I}$  using the homomorphism  $h$ . It follows that  $\mathcal{H}$  is a polynomially sized hypothesis for  $\langle \mathcal{K}, \Phi, \Sigma \rangle$ .

Finally, for  $\mathcal{L} = \mathcal{ALCC}\mathcal{F}$ , the existence of any upper bound would allow us to decide existence of abductive solutions by a simple guess-and-check algorithm. In particular, this would



allow to decide the IQ-query emptiness problem which asks, given a TBox  $\mathcal{T}$ , a signature  $\Sigma$  and a concept  $C$ , whether there exist any flat ABoxes in  $\Sigma$  that entail  $C(a)$  for some individual name  $a \in \mathbb{N}_I$ . As shown in [Baader *et al.*, 2016], this problem is undecidable for  $\mathcal{ALCF}$  TBoxes, however, it can be easily reduced to flat  $\mathcal{ALCF}$  abduction.  $\square$

**Theorem 3.** *Flat  $\mathcal{L}$  ABox abduction is*

- P-complete for  $\mathcal{L} = \mathcal{EL}$ ,
- EXPTIME-complete for  $\mathcal{L} = \mathcal{EL}_\perp$ ,
- CONEXPTIME-complete for  $\mathcal{L} = \mathcal{ALCI}$ ,
- undecidable for  $\mathcal{L} = \mathcal{ALCF}$ .

*Proof.* We only need to consider the upper bounds for the cases  $\mathcal{L} = \mathcal{EL}_\perp$  and  $\mathcal{L} = \mathcal{ALCI}$ .

We first describe how to compute a maximal set  $T_{\mathcal{K} \cup \Phi}$  of types for  $\mathcal{K} \cup \Phi$  using type elimination. This construction is fairly standard and only included here for self-containment. For a role  $R$ , we set  $\text{InV}(r) = r^-$  and  $\text{InV}(r^-) = r$ .

We start with the set  $T_0 = \{t \mid t \subseteq \text{sub}(\mathcal{K}) \cup \text{sub}(\Phi)\}$  from which we construct a sequence  $T_0, T_1, \dots, T_n$  of such sets. For a given such set  $T_i$ , a type  $t \subseteq \text{sub}(\mathcal{K} \cup \Phi)$  and a role  $R$ , we denote by  $S_{T_i}^R(t)$  the set of all types  $t' \in T_i$  s.t. for every  $\exists R.C \in (\text{sub}(\mathcal{K} \cup \Phi) \setminus t)$ ,  $C \not\subseteq t'$ , and for every  $\exists \text{InV}(R).C \in (\text{sub}(\mathcal{K} \cup \Phi) \setminus t')$ ,  $C \not\subseteq t$ .  $S_{T_i}^R(t)$  contains the  $R$ -successor candidates of  $t$  within  $T_i$ , that is, types from  $T_i$  that an  $R$ -successor of an instance of  $t$  could have. For each  $i \in \llbracket 1, n \rrbracket$ ,  $T_i$  is obtained from  $T_{i-1}$  by removing an element  $t$  that fails to satisfy any of the following conditions:

1.  $\perp \not\subseteq t$ ,
2. for every  $C \sqcap D \in \text{sub}(\mathcal{K} \cup \Phi)$ ,  $C \sqcap D \in t$  iff  $\{C, D\} \subseteq t$ ,
3. for every  $\neg C \in \text{sub}(\mathcal{K} \cup \Phi)$ ,  $C \in t$  iff  $\neg C \not\subseteq t$ ,
4. if  $C \in t$  and  $C \sqsubseteq D \in \mathcal{K}$ , then  $D \in t$ , and
5. if  $\exists R.C \in t$ , then there exists  $t' \in S_{T_{i-1}}^R(t)$  s.t.  $C \in t'$ .

We set  $T_{\mathcal{K} \cup \Phi} = T_n$ . Since  $T_0$  contains exponentially many elements,  $T_{\mathcal{K} \cup \Phi}$  is obtained after at most exponentially many steps, each taking polynomial time.

We define a *selector function* to be any function  $s : \text{ind}(\mathcal{K} \cup \Phi) \rightarrow T_{\mathcal{K} \cup \Phi}$ . We note that there are at most exponentially many such selector functions, specifically,

$$|T|^{|\text{ind}(\mathcal{K} \cup \Phi)|} \leq \left(2^{|\text{sub}(\mathcal{K} \cup \Phi)|}\right)^{|\text{ind}(\mathcal{K} \cup \Phi)|} \\ \leq 2^{\text{size}(\mathcal{K} \cup \Phi)^2}$$

We call such a selector function *compatible with  $\mathcal{K}$*  if for every  $A(a) \in \mathcal{K}$ ,  $A \in s(a)$ , and for every  $r(a, b) \in \mathcal{K}$ ,  $s(b) \in S_{T_{\mathcal{K} \cup \Phi}}^r(s(a))$ .

For every selector function  $s$  compatible with  $\mathcal{K}$ , we build a hypothesis candidate  $\mathcal{H}_s$  as follows. To every type  $t \in T_{\mathcal{K} \cup \Phi}$ , we assign an fresh individual name  $b_t$ . The set

$$I = \text{ind}(\mathcal{K} \cup \Phi) \cup \{b_t \mid t \in T_{\mathcal{K} \cup \Phi}\}$$

contains the individual names in our hypothesis, to which we extend  $s$  by setting  $s(b_t) = t$ .  $\mathcal{H}_s$  is then defined as

$$\mathcal{H}_s = \{A(a) \mid a \in I, A \in s(a) \cap \Sigma\} \\ \cup \{r(a, b) \mid a, b \in I, r \in \Sigma, s(b) \in S_{T_{\mathcal{K} \cup \Phi}}^r(s(a))\}$$

**Claim 1.** *If  $s$  is a selector function compatible with  $\mathcal{K}$ , then  $\mathcal{K} \cup \mathcal{H}_s \not\models \perp$ .*

*Proof of claim.* We construct a model  $\mathcal{I}$  for  $\mathcal{K} \cup \mathcal{H}_s$  based on  $T_{\mathcal{K} \cup \Phi}$  and  $s$ :

- $\Delta^{\mathcal{I}} = I$ ,
- for all  $a \in I$ :  $a^{\mathcal{I}} = a$
- $A^{\mathcal{I}} = \{a \in I \mid A \in s(a) \cap \mathbb{N}_C\}$ ,
- $r^{\mathcal{I}} = \{(a, b) \in I \times I \mid s(b) \in S_{T_{\mathcal{K} \cup \Phi}}^r(s(a))\}$

It is now standard to show by induction on the structure of concepts that for every  $a \in \mathbb{N}_I$  and  $C \in s(a)$ ,  $a \in C^{\mathcal{I}}$ . From the construction of the type set  $T_{\mathcal{K} \cup \Phi}$  it then follows that  $\mathcal{I}$  satisfies all GCIs in  $\mathcal{K}$ . Since  $s$  is compatible with  $\mathcal{K}$ , it follows that  $\mathcal{I}$  also satisfies all assertions in  $\mathcal{K}$ . Finally, by construction  $\mathcal{I} \models \mathcal{H}_s$ .  $\blacksquare$

**Claim 2.** *If there exists a flat hypothesis for  $\langle \mathcal{K}, \Phi, \Sigma \rangle$ , then there exists a selector function  $s$  s.t.  $\mathcal{H}_s$  is such a hypothesis.*

*Proof of claim.* Assume there exists a flat hypothesis  $\mathcal{H}_0$  for  $\langle \mathcal{K}, \Phi, \Sigma \rangle$ . Since for every selector function  $s$  compatible to  $\mathcal{K}$ ,  $\mathcal{H}_s$  satisfies **A1** by Claim 1 and **A3** by construction, we only need to show that there exist some such  $s$  s.t.  $\mathcal{H}_s$  satisfies **A2**. We use the construction from the proof for Theorem 2 to obtain, based on  $\mathcal{H}_0$ , an assignment of types  $\text{tp}(a)$  to every  $a \in \text{ind}(\mathcal{K} \cup \Phi)$ , as well as the exponentially bounded hypothesis  $\mathcal{H}$ . Define  $s$  s.t.  $s(a) = \text{tp}(a^{\mathcal{I}})$  for every  $a \in \text{ind}(\mathcal{K} \cup \Phi)$ .  $s$  is compatible with  $\mathcal{K}$ , and  $\mathcal{H} \subseteq \mathcal{H}_s$ . Consequently,  $\mathcal{K} \cup \mathcal{H}_s \models \Phi$  and  $\mathcal{H}_s$  satisfies **A1–A2**.  $\blacksquare$

Claim 2 allows to obtain an EXPTIME-decision procedure for the case where  $\mathcal{L} = \mathcal{EL}_\perp$ : specifically, we first compute  $T_{\mathcal{K} \cup \Phi}$  in exponential time, and then iterate over the exponentially many possible selector functions  $s$  and check whether  $\mathcal{H}_s$  satisfies **A1** and **A2**. Since entailment checking in  $\mathcal{EL}_\perp$  can be decided in polynomial time and each  $\mathcal{H}_s$  is exponentially large, the entire procedure runs in deterministic exponential time.

For  $\mathcal{L} = \mathcal{ALCI}$ , entailment checking is EXPTIME-hard, so that this procedure would only yield in 2EXPTIME-upper bound. To obtain a CONEXPTIME upper bound, we devise a non-deterministic procedure to determine whether there is *no* flat hypothesis for  $\langle \mathcal{K}, \Phi, \Sigma \rangle$ . For this, by Claim 1 and 2, we need to show that for every selector function  $s$ , there exists some model  $\mathcal{I}$  of  $\mathcal{K} \cup \mathcal{H}_s$  s.t.  $\mathcal{I} \not\models \Phi$ . For this, we first check whether for some  $r(a, b) \in \Phi$ ,  $r(a, b) \notin \mathcal{H}_s \cup \mathcal{K}$ . If this test fails, we guess a function  $s_e : \text{ind}(\mathcal{H}_s) \rightarrow T_{\mathcal{K} \cup \Phi}$  and check whether

- s1**  $s_e$  is compatible with  $\mathcal{K} \cup \mathcal{H}_s$  in the sense above, and
- s2** for some  $C(a) \in \Phi$ ,  $C \not\subseteq s_e(a)$ .

If for every selector  $s$  function, one of these checks is successful, we accept, and otherwise we reject. Since this non-deterministic procedure requires exponentially many steps units, we obtain the required CONEXPTIME upper bound, provided that the algorithm is correct.

**Claim 3.**  $\mathcal{K} \cup \mathcal{H}_s \models \Phi$  iff for every  $r(a, b) \in \Phi$ ,  $r(a, b) \in \mathcal{H}_s$ , and no function  $s_e : \text{ind}(\mathcal{H}_s) \rightarrow T_{\mathcal{K} \cup \Phi}$  satisfies Conditions **s1** and **s2**.

*Proof of claim.* Assume  $\mathcal{K} \cup \mathcal{H}_s \not\models \Phi$  and for every  $r(a, b) \in \Phi$ ,  $r(a, b) \in \mathcal{H}_s$ . There then exists a model  $\mathcal{I}$  of  $\mathcal{K} \cup \mathcal{H}_s$  s.t.  $\mathcal{I} \not\models \Phi$ . Define  $s_e$  by setting  $s_e(a) = \text{tp}(a^{\mathcal{I}})_{\mathcal{I}}$ , and we obtain from the fact that  $\mathcal{I}$  is a model of  $\mathcal{K} \cup \mathcal{H}_s$  that  $s_e$  satisfies Condition **s1**, and from the fact that  $\mathcal{I} \not\models \Phi$ , that there is some  $C(a) \in \Phi$  s.t.  $a^{\mathcal{I}} \notin C^{\mathcal{I}}$ , which implies  $C \notin s_e(a)$  and thus Condition **s2**.

For the other direction, first observe that if  $r(a, b) \notin \mathcal{H}_s \cup \mathcal{K}$  for some  $r(a, b) \in \Phi$ , we can always find a model  $\mathcal{I}$  of  $\mathcal{K} \cup \mathcal{H}_s$  s.t.  $\mathcal{I} \not\models \Phi$ . Assume for every  $r(a, b) \in \Phi$ , we have also  $r(a, b) \in \mathcal{H}_s \cup \mathcal{K}$ , and there exists a function  $s_e : \text{ind}(\mathcal{H}_s) \rightarrow T_{\mathcal{K} \cup \Phi}$  that satisfies both Condition **s1** and **s2**. We define

$$s_e^* : \text{ind}(\mathcal{H}_s) \cup T_{\mathcal{K} \cup \Phi} \rightarrow T_{\mathcal{K} \cup \Phi}$$

by setting  $s_e^*(a) = s_e(a)$  if  $a \in \text{ind}(\mathcal{H}_s)$  and  $s_e^*(t) = t$  if  $t \in T_{\mathcal{K} \cup \Phi}$ . We define an interpretation  $\mathcal{I}$  as follows:

- $\Delta^{\mathcal{I}} = \{a^{\mathcal{I}} \mid a \in \text{ind}(\mathcal{H}_s)\} \cup T_{\mathcal{K} \cup \Phi}$ ,
- for every  $A \in \mathbf{N}_C$ ,  $A^{\mathcal{I}} = \{d \in \Delta^{\mathcal{I}} \mid A \in s_e^*(d)\}$
- for every  $r \in \mathbf{N}_R$ ,  $r^{\mathcal{I}} = \{\langle d, e \rangle \in \Delta^{\mathcal{I}} \times \Delta^{\mathcal{I}} \mid s_e^*(e) \in S_{T_{\mathcal{K} \cup \Phi}}^r(s_e^*(d))\}$

One easily verifies that for every  $d \in \Delta^{\mathcal{I}}$ ,  $\text{tp}(d)_{\mathcal{I}} = s_e^*(t)$ . This implies that  $\mathcal{I}$  satisfies every GCI in  $\mathcal{K}$ , and by Condition **s2** that  $\mathcal{I} \not\models C(a)$  for some  $C(a) \in \Phi$ . Using Condition **s1**, one also verifies that  $\mathcal{I}$  is a model of every assertion in  $\mathcal{K} \cup \mathcal{H}_s$ . ■

We obtain that our non-deterministic procedure is correct, and correspondingly that for  $\mathcal{L} = \mathcal{ALCC}$ , existence of flat hypotheses is in CONEXPTIME. □

## B Complex ABox Hypotheses for $\mathcal{EL}_{\perp}$

We show Theorem 4 using three separate lemma for the lower bound of the size, the upper bound of the size, as well as for the decision procedure.

**Lemma 8.** *There exists a family of  $\mathcal{EL}_{\perp}$  TBoxes  $(\mathcal{T}_n)_{n \geq 1}$  s.t. each  $\mathcal{T}_n$  is of size polynomial in  $n$  and every hypothesis for  $\langle \mathcal{T}_n, A(a), \{B, r, s\} \rangle$  that uses only  $a$  as individual name is of double exponential size.*

*Proof.*  $\mathcal{T}_n$  can be seen in Figure 1 and works as described in the main text. □

**Lemma 9.** *Let  $\langle \mathcal{K}, \Phi, \Sigma \rangle$  be a signature based abduction problem s.t.  $\mathcal{K}$  and  $\Phi$  are formulated in  $\mathcal{EL}_{\perp}$ . Then, there exists a solution to the abduction problem without fresh individual names iff there exists such a solution of double exponentially bounded size.*

*Proof.* Let  $\mathcal{H}_0$  be a hypothesis for  $\langle \mathcal{K}, \Phi, \Sigma \rangle$ . We first create a flattened version of  $\mathcal{H}_0$ , where we use a mapping  $\text{root} : \mathbf{N}_I \rightarrow \mathbf{N}_I$  to keep track of a “root individual” for each individual added. Initially, we set  $\text{root}(a) := a$  for every  $a \in \text{ind}(\mathcal{H}_0)$ . We then exhaustively apply the following rules:

$$1. (C \sqcap D)(a) \implies C(a), D(a)$$

$$2. (\exists r.C)(a_1) \implies r(a_1, a_2), C(a_2), \text{ where } a_2 = b_{\text{root}(a_1), C} \text{ is fresh}$$

Denote the resulting ABox by  $\mathcal{H}_1$  and note that  $\mathcal{H}_1$  is a flat hypothesis for  $\langle \mathcal{K}, \Phi, \Sigma \rangle$ . Moreover,  $\mathcal{H}_1$  is *forest-like* in the sense that the fresh role-descendants of any fixed individual name  $a$  from  $\mathcal{H}_0$  form a tree. Specifically, for every fresh individual name  $b_{a,C}$  there exists exactly one role assertion of the form  $r(a', b_{a,C})$ .

Similar to the proof for Theorem 2, we take a random model  $\mathcal{I}$  of  $\mathcal{K} \cup \mathcal{H}_1$ , which allows us to assign a type  $\text{tp}(a^{\mathcal{I}})_{\mathcal{I}}$  to every individual in  $\mathcal{H}_1$ .

We use this type to reduce the path length from any individual from  $\mathcal{H}_0$  to an individual in  $\mathcal{H}_1$  by removing repeated types on each path. To keep track of our changes, we use a mapping  $h$  which is initialised with  $h(a) = a$  for every  $a \in \text{ind}(\mathcal{H}_1)$  and updated during the construction. We then repeat the following steps exhaustively:

1. If for two individual names  $a, b$ ,  $\text{root}(a) = \text{root}(b)$ ,  $\text{tp}(a^{\mathcal{I}})_{\mathcal{I}} = \text{tp}(b^{\mathcal{I}})_{\mathcal{I}}$  and there is a non-empty path from  $a$  to  $b$ , then replace the role assertion of the form  $r(a', a)$  by  $r(a', b)$ , and remove all role assertions involving  $a$ . Set  $h(a) := b$ .
2. If for any two role assertions of the form  $r(a, b), r(a, c)$ , we have  $\text{root}(b) = \text{root}(c)$  and  $\text{tp}(b^{\mathcal{I}})_{\mathcal{I}} = \text{tp}(c^{\mathcal{I}})_{\mathcal{I}}$ , then remove all role assertions involving  $c$ . Set  $h(c) := b$ .

Denote the resulting ABox by  $\mathcal{H}_2$ . Different to the construction for Theorem 2,  $h$  is not a homomorphism. We note that the operation preserves the forest shape, and moreover makes sure that every path from an individual name  $a \in \text{ind}(\mathcal{H}_0)$  to an individual name  $b_{a,C}$  is exponentially bounded, and for every individual name  $a$ , there are at most exponentially many role assertions of the form  $r(a, b)$ . As a result, for every individual name  $a \in \text{ind}(\mathcal{H}_0)$ , there are  $(2^n)^{2^n}$  individual names  $b$  with  $\text{root}(a) = b$ . We can thus build a double exponentially bounded hypothesis candidate by “rolling up” the ABox again, or exhaustively applying the following operation:

- If  $a$  has no role successor and  $\text{root}(a) \neq a$ , replace the role assertion  $r(b, a)$  by

$$\exists r. \bigwedge \{C \mid C(a) \text{ occurs in the current ABox}\}.$$

Denote the resulting hypothesis by  $\mathcal{H}$ . We show that it satisfies Conditions **A1**–**A2**. For this, it suffices to show that  $\mathcal{H}_2$  satisfies those conditions. Note that we already observed that  $\mathcal{H}_1$  is a flat hypothesis for  $\langle \mathcal{K}, \Phi, \Sigma \rangle$ .

Condition **A3** that  $\text{sig}(\mathcal{H}_2) \subseteq \Sigma$  is satisfied by construction since we do not introduce any new names. For **A1**, we need to find a model  $\mathcal{J}$  of  $\mathcal{K} \cup \mathcal{H}_2$ , which we do based our model  $\mathcal{I}$  of  $\mathcal{K} \cup \mathcal{H}_1$ .  $\mathcal{J}$  is constructed as follows:

- $\Delta^{\mathcal{J}} = \Delta^{\mathcal{I}}$ ,
- $a^{\mathcal{J}} = a^{\mathcal{I}}$  for all  $a \in \mathbf{N}_I$ ,
- $A^{\mathcal{J}} = A^{\mathcal{I}}$  for all  $A \in \mathbf{N}_C$ ,
- $r^{\mathcal{J}} = \{\langle a^{\mathcal{J}}, h(b)^{\mathcal{J}} \rangle \mid \langle a^{\mathcal{I}}, b^{\mathcal{I}} \rangle \in r^{\mathcal{I}}\} \cup \{\langle d, e \rangle \mid e \neq a^{\mathcal{I}} \text{ for all } a \in \text{ind}(\mathcal{H}_0)\}$ .

$$\begin{aligned}
& B \sqsubseteq \overline{X}_1 \sqcap \dots \sqcap \overline{X}_n & (1) \\
& \exists r. (\overline{X}_i \sqcap X_{i-1} \sqcap \dots \sqcap X_1) \sqcap \exists s. (\overline{X}_i \sqcap X_{i-1} \sqcap \dots \sqcap X_1) \sqsubseteq X_i & \text{for } i \in \llbracket 1, n \rrbracket & (2) \\
& \exists r. (X_i \sqcap X_{i-1} \sqcap \dots \sqcap X_1) \sqcap \exists s. (X_i \sqcap X_{i-1} \sqcap \dots \sqcap X_1) \sqsubseteq \overline{X}_i & \text{for } i \in \llbracket 1, n \rrbracket & (3) \\
& \exists r. (\overline{X}_i \sqcap \overline{X}_j) \sqcap \exists s. (\overline{X}_i \sqcap \overline{X}_j) \sqsubseteq \overline{X}_i & \text{for } i, j \in \llbracket 1, n \rrbracket, j < i & (4) \\
& \exists r. (X_i \sqcap \overline{X}_j) \sqcap \exists s. (X_i \sqcap \overline{X}_j) \sqsubseteq X_i & \text{for } i, j \in \llbracket 1, n \rrbracket, j < i & (5) \\
& X_i \sqcap \overline{X}_i \sqsubseteq \perp & \text{for } i \in \llbracket 1, n \rrbracket & (6) \\
& X_1 \sqcap \dots \sqcap X_n \sqsubseteq A & (7)
\end{aligned}$$

Figure 1: Background KB in  $\mathcal{EL}_\perp$  enforcing a double exponentially large hypothesis if fresh individual names are not admitted.

It can be shown by induction on the structure of concepts that for every concept  $C \in \text{sub}(\mathcal{K} \cup \Phi)$  and  $d \in \Delta^{\mathcal{I}}$ ,  $d \in C^{\mathcal{I}}$  iff  $d \in C^{\mathcal{J}}$ , which implies  $\text{tp}(d)_{\mathcal{I}} = \text{tp}(e)_{\mathcal{J}}$  and that  $\mathcal{J}$  is a model of  $\mathcal{K} \cup \mathcal{H}_2$ .

For Condition **A2**, assume there is a model  $\mathcal{I}_2$  of  $\mathcal{K} \cup \mathcal{H}_2$  s.t.  $\mathcal{I}_2 \not\models \Phi$ . Based on  $\mathcal{I}_2$ , we construct a model  $\mathcal{I}_1$  of  $\mathcal{K} \cup \mathcal{H}_1$ . Define  $m : \Delta^{\mathcal{I}_2} \cup \text{ind}(\mathcal{K} \cup \mathcal{H}_1) \rightarrow \Delta^{\mathcal{I}_2}$  by

$$m(d) = \begin{cases} d & \text{if } d \in \Delta^{\mathcal{I}_2} \\ h(d)^{\mathcal{I}_2} & \text{if } d \in \text{ind}(\mathcal{K} \cup \mathcal{H}_1). \end{cases}$$

Using  $m$ , we define  $\mathcal{I}_1$  as follows

- $\Delta^{\mathcal{I}_1} = \Delta^{\mathcal{I}_2} \cup \text{ind}(\mathcal{K} \cup \mathcal{H}_1)$ ,
- $a^{\mathcal{I}_1} = a$  for all  $a \in \text{ind}(\mathcal{K} \cup \mathcal{H}_1)$ ,
- $A^{\mathcal{I}_1} = \{d \in \Delta^{\mathcal{I}_1} \mid m(d) \in A^{\mathcal{I}_2}\}$  for all  $A \in \mathbf{N}_C$ , and
- $r^{\mathcal{I}_1} = \{\langle d, e \rangle \mid \langle m(d), m(e) \rangle \in r^{\mathcal{I}_2}\}$  for all  $r \in \mathbf{N}_R$ .

Again it is straightforward to prove that the construction is type preserving, a model of  $\mathcal{K} \cup \mathcal{H}_1$ , and  $\mathcal{I}_1 \not\models \Phi$  for the same reason as for  $\mathcal{I}_1$ . It follows that there cannot be a model  $\mathcal{I}_2$  of  $\mathcal{K} \cup \mathcal{H}_2$  s.t.  $\mathcal{I}_2 \not\models \Phi$ , and thus that  $\mathcal{K} \cup \mathcal{H}_2$  satisfies Condition **A2**.  $\square$

**Lemma 10.** *It can be decided in exponential time whether a given  $\mathcal{EL}_\perp$  abduction problem has a solution without fresh individuals.*

*Proof.* We use a similar procedure as in Theorem 3 using the in exponential time computed set  $T_{\mathcal{K} \cup \Phi}$  of types for  $\mathcal{K} \cup \Phi$  and the guessed selector function  $s : \text{ind}(\mathcal{K} \cup \Phi) \rightarrow T_{\mathcal{K} \cup \Phi}$ . However, this time, the hypothesis is constructed differently by making sure that we do not introduce cycles between introduced individuals, so that the flat ABox can always be “rolled up” into a complex ABox without fresh individual names. To be able to do this, our introduced individuals are of the form  $b_{a,t,i}$ , where  $a \in \text{ind}(\mathcal{K} \cup \Phi)$ ,  $t \in T_{\mathcal{K} \cup \Phi}$ , and  $i \in \llbracket 1, 2^{|T_{\mathcal{K} \cup \Phi}|} \rrbracket$ . Note that still, there are only exponentially many individuals of this form. For convenience, we set  $b_{a,s(a),0} = a$ .

The ABox  $\mathcal{H}_s$  is then defined as follows, where  $T = T_{\mathcal{K} \cup \Phi}$ :

$$\begin{aligned}
\mathcal{H}_s = \{ & A(b_{a,t,k}) \mid a \in \text{ind}(\mathcal{K} \cup \Phi), t \in T, k \in \llbracket 0, 2^{|T|} \rrbracket, \\
& A \in (t \cap \Sigma) \} \\
& \cup \{ r(b_{a,t_1,k}, b_{a,t_2,k+1}) \mid a \in \text{ind}(\mathcal{K} \cup \Phi), t_1 \in T, \\
& \quad r \in \Sigma, t_2 \in S_T^r(t_1), k \in \llbracket 0, 2^{|T|} - 1 \rrbracket \} \\
& \cup \{ r(a, b) \mid s(b) \in S_T^r(s(a)) \}.
\end{aligned}$$

Since  $\mathcal{H}_s$  is of exponential size, we can verify  $\mathcal{K} \cup \mathcal{H}_s \models \Phi$  in exponential time, which means that, since we have to consider exponentially many selector functions, the entire procedure runs in exponential time. One can show similarly as for Theorem 3 that for every selector function  $s$  that is compatible with  $\mathcal{K}$ ,  $\mathcal{H}_s$  satisfies **A1** and **A3**. It remains to show that for every hypothesis  $\mathcal{H}_0$  without fresh individuals of the current abduction problem, there is a corresponding compatible selector function  $s$  s.t.  $\mathcal{H}_s$  satisfies also **A2**, that is,  $\mathcal{K} \cup \mathcal{H}_s \models \Phi$ . For this, we first transform  $\mathcal{H}_0$  as in Lemma 9 into a flat, forest-like hypothesis  $\mathcal{H}_2$ . Recall that this construction assigns every individual  $a$  a type  $\text{tp}(a^{\mathcal{I}})_{\mathcal{I}}$  based on an arbitrary interpretation  $\mathcal{I}$ , and is such that, on every path from a named individual to a fresh individual, no type is repeated. Choose  $s$  s.t.  $s(a) = \text{tp}(a^{\mathcal{I}})_{\mathcal{I}}$ . Using that  $s$  is constructed from a model of  $\mathcal{K}$ , one can show that  $s$  is compatible with  $\mathcal{K}$ . We show that also  $\mathcal{K} \cup \mathcal{H}_2 \models \Phi$  iff  $\mathcal{K} \cup \mathcal{H}_s \models \Phi$ . For this, we define a mapping  $m : \text{ind}(\mathcal{H}_2) \rightarrow \text{ind}(\mathcal{H}_s)$  inductively as follows:

- for every  $a \in \text{ind}(\mathcal{K} \cup \Phi)$ ,  $m(a) = a = b_{a,s(a),0}$ ,
- for every  $r(a, b) \in \mathcal{H}_2$  s.t.  $b \notin \text{ind}(\mathcal{K} \cup \Phi)$  and  $m(a) = b_{a,t,i}$ , set  $m(b) = b_{a,t',i+1}$ , where  $t' = \text{tp}(b^{\mathcal{I}})_{\mathcal{I}}$ .

The induction terminates because  $\mathcal{H}_2$  has the “forest-shape”, that is, for every individual name  $a \in \text{ind}(\mathcal{K} \cup \Phi)$ , the fresh ancestors of  $a$  form a tree. By checking the definition of  $\mathcal{H}_s$ , one can see that for every  $A(a) \in \mathcal{H}_2$ , we have  $A(m(a)) \in \mathcal{H}_s$ , and for every  $r(a, b) \in \mathcal{H}_2$ , we have  $r(m(a), m(b)) \in \mathcal{H}_2$ .  $m$  is thus a homomorphism from  $\mathcal{H}_2$  into  $\mathcal{H}_s$ , which can be used as in the proof for Theorem 2 to show that  $\mathcal{H}_2 \models \Phi$  implies that also  $\mathcal{H}_s \models \Phi$ .  $\square$

$$\top \sqsubseteq \exists r. \top \sqcap \exists s. \top \quad (8)$$

$$\forall (r \cup s). (B \sqcup B') \sqsubseteq B' \quad (9)$$

$$B \sqsubseteq \text{Init} \sqcap \neg \text{Bit} \quad (10)$$

$$\forall (r \cup s). (\text{Init} \sqcap \bigsqcup_{i=1}^n \overline{X}_i) \sqsubseteq \text{Init} \sqcap \neg \text{Bit} \quad (11)$$

$$\prod_{i=1}^n \overline{X}_i \sqsubseteq \text{Flip} \quad (12)$$

$$\forall (r \cup s). (\text{Flip} \sqcap \text{Bit}) \sqsubseteq \text{Flip} \quad (13)$$

$$\bigsqcup_{i=1}^n X_i \sqcap \exists (r \cup s). (\neg \text{Flip} \sqcup \neg \text{Bit}) \sqsubseteq \neg \text{Flip} \quad (14)$$

$$\prod_{i=0}^n X_i \sqcap \text{Flip} \sqcap B' \sqsubseteq \text{Error} \sqcup \text{Goal} \quad (15)$$

$$\text{Error} \sqsubseteq \neg \text{Init} \sqcap \exists (r \cup s). (\text{Error} \sqcup E_0) \quad (16)$$

$$E_0 \sqsubseteq \prod_{i=1}^n \overline{Y}_i \sqcap E \sqcap (\text{NBit} \leftrightarrow \text{Bit}) \quad (17)$$

$$E \sqcap \text{NBit} \sqsubseteq \exists (r \cup s). (E \sqcap \text{NBit}) \quad (18)$$

$$E \sqcap \neg \text{NBit} \sqsubseteq \exists (r \cup s). (E \sqcap \neg \text{NBit}) \quad (19)$$

$$\prod_{i=1}^n Y_i \sqcap E \sqsubseteq \exists r. E_f \sqcup \exists s. E_f \quad (20)$$

$$E_f \sqcap \text{Flip} \sqsubseteq (\text{Bit} \leftrightarrow \text{NBit}) \quad (21)$$

$$E_f \sqcap \neg \text{Flip} \sqsubseteq (\text{Bit} \leftrightarrow \neg \text{NBit}) \quad (22)$$

Figure 2: Part of the background knowledge base requiring a double exponentially large hypothesis.

## C Complex ABox Abduction for $\mathcal{ALC}$

**Theorem 5.** *There is a family of  $\mathcal{ALC}$  abduction problems for which the smallest (non-flat) ABox hypotheses are triple exponential in size.*

*Proof.* The idea is, similar as for the bound in Theorem 4, to enforce the hypothesis to represent a binary tree with the concept name  $B$  on its leafs. However, this time, instead of using an  $n$ -bit counter as in Theorem 1, we use a trick from [Ghilardi *et al.*, 2006] to implement a  $2^n$ -bit counter. Here, a single counter value is encoded by a chain of  $2^n$  elements satisfying either  $\text{Bit}$  or  $\neg \text{Bit}$ , depending on whether the corresponding bit has the value 1 or 0. The counting then produces a chain of  $2^{2^n} \cdot 2^n$  elements, where each consecutive  $2^n$  elements represent the next number in the sequence.

The hypothesis for our problem will be of the form  $C(a)$ , where  $C$  only uses universal restriction, conjunction, and negation on concept names, to express that every path of  $r$ - and  $s$ -successors must lead to an instance of  $B$ , and reading each path backwards from the  $B$ -instance to  $a$ , it must encode contain a sequence of  $2^{2^n}$  increasing counter values. The signature is  $\Sigma = \{r, s, \text{Bit}, B\}$  and the observation is  $\text{Goal}(a)$ . To disallow solutions such as  $(\forall r. \perp \sqcap \forall s. \perp)(a)$ , we add  $\top \sqsubseteq \exists r. \top \sqcap \exists s. \top$  to  $\mathcal{K}$ . A concept  $B'$  is used to mark elements from which every path of  $s$ - and  $r$ -successors leads to an instance of  $B$ . The concept name  $\text{Bit}$  is used for our counter. To identify bit positions in the current counter value, we use an  $n$ -bit-counter as for Theorem 1 which is initialised at instances of  $B$ .

The construction is similar to that given in [Ghilardi *et al.*, 2006] to give a triple exponential lower bound for witness concepts of conservative extensions in  $\mathcal{ALC}$ , but slightly adapted to be applicable to the abduction problem, as well as improved in its representation. The background knowledge base  $\mathcal{K}$  contains the axioms in Figure 2, together with Axioms (1)–(6) from Figure 1 as they are, as well as Axioms (2)–(6) from Figure 1 with  $X_i/\overline{X}_i$  replaced by  $Y_i/\overline{Y}_i$ . In Figure 2, we use the construct  $\forall (r \cup s). C$  as an abbreviation for  $\forall r. C \sqcap \forall s. C$ ,  $\exists (r \cup s). C$  as abbreviation for  $\exists r. C \sqcup \exists s. C$ , and  $C \leftrightarrow D$  as abbreviation for  $(C \sqcap D) \sqcup (\neg C \sqcap \neg D)$ .

The set of abducibles is  $\Sigma = \{s, r, \text{Bit}, B\}$ , and our observation is  $\Phi = \{\text{Goal}(a)\}$ . We explain the axioms in  $\mathcal{K}$  one after the other.

- The axioms taken from Figure 1 implement binary counters—one using concept names  $X_0, \dots, X_n$  to represent positive bit values, and one using concept names  $Y_0, \dots, Y_n$  to represent positive bit values. We call those two single exponential counters  $X$ -counter and  $Y$ -counter respectively. The  $X$ -counter is initialised at instances of  $B$ , while we do not state yet where the  $Y$ -counter is initialised. The  $X$ -counter is used to keep track of the current bit position in the double exponential counter.
- (8) ensures that no hypothesis can limit the length of  $r$  or  $s$ -paths in an interpretation, and is needed to avoid the use of concepts  $\forall r. \perp$  and  $\forall s. \perp$  in hypotheses.

- (9) uses the concept  $B'$  to mark elements from which every path along  $r$ - and  $s$ -edges leads to an instance of  $B$ .
- (10)–(11) make sure that any element from which there are only paths of less than  $2^n$  elements to an instance of  $B$  satisfies  $\text{InIt}$  and  $\neg\text{Bit}$ . Those first paths of length  $2^n$  represent the initial value of 0 of the double exponential counter.
- (12)–(14) use the concept name  $\text{Flip}$  to mark elements which correspond to a bit that should flip for the next double exponential counter value .
- (15) now gives the conditions for the observation to be entailed. With the previous axioms, it should be clear that  $\prod_{i=0}^n X_i \sqcap \text{Flip}$  is satisfied by instances from which every element on every path of length  $2^n$  satisfies  $\text{Bit}$ , or, if we are on the last bit of the double exponential counter with the current value of  $2^{2^n} - 1$ . Axiom (15) states now: if we are in such a situation, and we additionally satisfy  $B'$ , which is, every path of  $r$ - and  $s$ -successors leads eventually to an instance of  $B$ , then we satisfy either  $\text{Error}$  or  $\text{Goal}$ . Consequently, the hypothesis has to make sure that  $\text{Error}$  is not satisfied in order to entail the observation. Intuitively,  $\text{Error}$  can only be satisfied if the double exponential counter made an error on one of the paths leading to a  $B$ -instance. Consequently, to avoid  $\text{Error}$  from being satisfied, all paths to the next  $B$ -instance have to use the double exponential counter correctly, that is, encode all numbers from 0 to  $2^{2^n} - 1$  in decreasing order.
- (16)–(22) now implement this error-detection mechanism via the concept  $\text{Error}$ . Specifically, if we have an instance of  $E_0$  before we reached the initial value of the double exponential counter (marked using the concept name  $\text{InIt}$ ).  $E_0$  marks the first bit where we observe the error: it initialises the  $Y$ -counter (which uses the concept names  $Y_i/\bar{Y}_i$ ), and stores the current bit value using in the concept name  $\text{NBit}$ . The value of  $\text{NBit}$  is now transported, together with the concept name  $E$ , along some path of  $r$ - and  $s$ -successors of length  $2^n$  until the  $Y$ -counter reaches its maximum value. We have then reached the corresponding bit position in the previous value of the double exponential counter at which the error is supposed to happen, which we mark with the concept  $E_f$ . Now we compare the stored bit-value in  $\text{NBit}$  with the current  $\text{Bit}$ -value and verify that a counting error has indeed happened.

For a hypothesis to entail  $\text{Goal}(a)$ , it has to be of the form  $C(a)$ , where  $C$  expresses that every path along  $r$ - and  $s$ -successors eventually leads to an instance of  $B$ , and that, when following those paths down from these  $B$ -instances to  $a$ , they encode the sequence of all consecutive  $2^n$ -bit values via the concept  $\text{Bit}$ . This can only be done by a concept of triple exponential size. Specifically, let  $\pi$  be a string of 0s and 1 that is the result of concatenating all  $2^n$ -bit numbers, starting from the lowest value, and ending with the largest, and let  $\pi[i]$  denote to the  $i$ th bit on that sequence. Note that  $\pi$  has length  $\ell = 2^{2^n} \cdot 2^n$ . Define  $\text{Bit}[i]$  by  $\text{Bit}[i] = \text{Bit if}$

$\pi[i] = 1$  and  $\text{Bit}[i] = \neg\text{Bit}$  if  $\pi[i] = 0$ . A hypothesis for  $\text{Goal}(a)$  would be the concept  $C(a)$  recursively defined as follows:

- $C_0 = B \sqcap \text{Bit}[0]$
- for  $i \in \llbracket 1, \ell - 1 \rrbracket$ ,  $C_i = \text{Bit}[i] \sqcap \forall(r \cup s).C_{i-1}$
- $C = C_\ell$ .

This finishes the proof.  $\square$

**Lemma 1.** *Every hypothesis  $\mathcal{H}$  for  $\mathfrak{A}$  can be translated into a hypothesis abstraction.*

*Proof.* Let  $\mathbf{I}$  be the set of all models of  $\mathcal{K} \cup \mathcal{H}$ . We first construct an interpretation abstraction  $\mathfrak{I}_1$  based on  $\mathbf{I}$ , which is then modified to become  $\Sigma$ -complete.  $\mathfrak{I}_1 = \langle V, \lambda_1, s, \mathfrak{R}_1, F \rangle$  is constructed together with a function  $I$  that assigns to every  $v \in V$  a set  $I(v)$  of pairs  $\langle \mathcal{I}, d \rangle$  of an interpretation  $\mathcal{I} \in \mathbf{I}$  and a domain element  $d \in \Delta^{\mathcal{I}}$ .

For every individual name  $a \in \text{ind}(\mathcal{K} \cup \mathcal{H})$ , we add a node  $v_a$  with  $s(a) = v_a$  and  $\lambda_1(v_a) = \{\text{tp}(a^{\mathcal{I}})_{\mathcal{I}} \mid \mathcal{I} \in \mathbf{I}\}$ . We set  $I(v) = \{\langle \mathcal{I}, a^{\mathcal{I}} \rangle \mid \mathcal{I} \in \mathfrak{I}_1\}$ , and to capture the role assertions, for every  $r(a, b) \in \mathcal{K} \cup \mathcal{A}$  and  $\mathcal{I} \in \mathbf{I}$ , we add the role assignment  $\langle v_a, \text{tp}(a^{\mathcal{I}})_{\mathcal{I}}, r, v_b \rangle$  to  $\mathfrak{R}_1$ .

We add further outgoing nodes based on the following inductive construction. For two connected nodes  $v_1, v_2$  we denote their *distance* as the number of nodes occurring in the shortest path connecting them. Let  $n$  be the maximal nesting depth in  $\mathcal{A}$ , by which we mean nesting of existential or universal role restrictions. For every node  $v$  whose distance to the next named node is less than  $n$ , every type  $t \in \lambda_1(v)$ , and every  $\exists r.C \in t$ , we add a node  $v'$  unique to  $\langle v, t, \exists r.C \rangle$  and set

$$I(v') = \{ \langle \mathcal{I}, d \rangle \mid \langle \mathcal{I}, d_1 \rangle \in I(v), \text{tp}(d_1)_{\mathcal{I}} = t, \\ \langle d_1, d \rangle \in r^{\mathcal{I}}, d \in C^{\mathcal{I}} \}$$

$$\lambda_1(v') = \{ \text{tp}(d)_{\mathcal{I}} \mid \langle \mathcal{I}, d \rangle \in I(v') \}$$

$$\langle v, t, r, v' \rangle \in \mathfrak{R}_1.$$

Every outgoing node  $v$  whose distance to the next named individual is  $n$  is added to  $F$ .

The construction directly ensures that  $\mathfrak{I}_1$  satisfies Conditions **D1** and **D2**. It is also not hard to understand that  $\mathfrak{I}_1$  abstracts at least one interpretation from  $\mathbf{I}$ , and thus a model of  $\mathcal{K}$ . We can show that it also explains  $\Phi$ , that is, that every model of  $\mathcal{K}$  that is abstracted by  $\mathfrak{I}_1$  is also a model of  $\Phi$ . Specifically, let  $\mathcal{I}$  be such a model of  $\mathcal{K}$ , and  $h : \Delta' \rightarrow V$  be the mapping that witnesses this. Since  $\mathcal{K} \cup \mathcal{H} \models \Phi$ , for every  $C(a) \in \Phi$ , we must have  $a^{\mathcal{I}} \in C^{\mathcal{I}}$  for all  $\mathcal{I} \in \mathbf{I}$ , and thus  $C \in t$  for every  $t \in \lambda_1(s(a))$ . By Condition **I1** and **I2**, it follows that  $\mathcal{I} \models C(a)$  for every  $C(a) \in \Phi$ . Now assume  $r(a, b) \in \Phi$ . We then must have  $r(a, b) \in \mathcal{K} \cup \mathcal{H}$ . If  $r(a, b) \in \mathcal{K}$ ,  $\mathcal{I} \models r(a, b)$  follows from the fact that  $\mathcal{I}$  is a model of  $\mathcal{K}$ . Otherwise,  $r(a, b) \in \mathcal{H}$ , and our construction explicitly added  $\langle v_a, t, r, v_b \rangle$  to  $\mathfrak{R}_1$  for every  $t \in \lambda_1(v_a)$ , so that by Conditions **I1** and **I3**, also  $\mathcal{I} \models r(a, b)$ . It follows that  $\mathcal{I} \models \Phi$ , and thus that  $\mathfrak{I}_1$  explains  $\mathcal{I}$ .

It remains to ensure  $\Sigma$ -completeness. For this, we modify  $\mathfrak{I}_1$  into an interpretation abstraction  $\mathfrak{J}$  that is  $\Sigma$ -complete, while still abstracting the same models of  $\mathcal{K}$ . This way,

we make sure that  $\mathcal{J}$  also explains  $\Phi$ . Specifically,  $\mathcal{J} = \langle V, \lambda, s, \mathfrak{R}, F \rangle$  is obtained from  $\mathcal{J}_1 = \langle V, \lambda_1, s, \mathfrak{R}_1, F \rangle$  by setting:

- for every  $v \in V$ ,  $\lambda(v) = \{t \in T_{\mathcal{K} \cup \Phi} \mid t' \in \lambda_1(v), t \cap \Sigma = t' \cap \Sigma\}$ ,
- $\mathfrak{R} = \mathfrak{R}_1 \cup \{\langle v_1, t, r, v_2 \rangle \mid \langle v_1, t', r, v_2 \rangle \in \mathfrak{R}_1, t \in T_{\mathcal{K} \cup \Phi}, t \cap \Sigma = t' \cap \Sigma\}$

Since we only added types, every model abstracted by  $\mathcal{J}_1$  is also abstracted by  $\mathcal{J}$ . We show that also every model of  $\mathcal{K}$  that is abstracted by  $\mathcal{J}$  is abstracted by  $\mathcal{J}_1$ . Assume  $\mathcal{I}$  is a model of  $\mathcal{K}$  that is abstracted by  $\mathcal{J}$  via  $h : \Delta' \rightarrow V$ . We show that  $\mathcal{I}$  then is a model of  $\mathcal{H}$ , and thus  $\mathcal{I} \in \mathbf{I}$ , from which it follows from our construction that for every  $d \in \Delta'$ ,  $\text{tp}(d)_{\mathcal{I}} \in \lambda_1(h(d))$ , and thus that  $\mathcal{I}$  is also abstracted by  $\mathcal{J}_1$ . For  $r(a, b) \in \mathcal{H}$ , by Conditions **I1** and **I3**, we must have  $\langle a^{\mathcal{I}}, b^{\mathcal{I}} \rangle \in r^{\mathcal{I}}$ , and thus  $\mathcal{I} \models r(a, b)$ . Consider  $C(a) \in \mathcal{H}$ .

By construction, for every  $d \in \Delta'$ , there exists some type  $t' \in \lambda_1(h(d))$  s.t.  $t' \cap \Sigma = \text{tp}(d)_{\mathcal{I}} \cap \Sigma$ . Define  $f : \Delta' \rightarrow T_{\mathcal{K} \cup \Phi}$  by setting  $f(d) = t'$  for some such type. Inspection of the construction of  $\mathcal{J}_1$  shows that there is an interpretation  $\mathcal{I}_1 \in \mathbf{I}$  that implements exactly those types, that is, for every  $d \in \Delta'$ , there exists some  $d^{\mathcal{I}_1} \in \Delta^{\mathcal{I}_1}$  s.t.  $\langle \mathcal{I}, d^{\mathcal{I}_1} \rangle \in I(h(d))$  and  $\text{tp}(d^{\mathcal{I}_1})_{\mathcal{I}_1} = f(d)$ . Essentially, the tuples  $\langle d, d^{\mathcal{I}_1} \rangle$  are the basis of a  $\Sigma$ -bisimulation as in [Lutz and Wolter, 2011] between  $\mathcal{I}$  and  $\mathcal{I}_1$ , from which it follows that for every  $C \in \text{sub}(\mathcal{H})$  and  $a \in \text{ind}(\mathcal{H})$ ,  $a^{\mathcal{I}} \in C^{\mathcal{I}}$  iff  $a^{\mathcal{I}_1} \in C^{\mathcal{I}_1}$ . We show this property directly without introducing the notion of bisimulation first.

For a node  $v \in V$ , denote by  $\text{dist}(v)$  the distance to the next internal node (or 0 if  $v$  is internal). and for a concept  $C$ , by  $\text{nd}(C)$  the nesting depth of role restrictions of  $C$ . We extend  $\text{dist}$  to  $\Delta'$  by setting  $\text{dist}(d) = \text{dist}(h(d))$ . Recall that  $n$  is the maximal nesting depth of any concept in  $\mathcal{H}$ , and that our instruction insures that for any outgoing node,  $\text{dist}(v) \leq n$ . Consequently, every path of outgoing nodes has at most length  $n - \text{dist}(v)$ . We show by structural induction that for every  $C \in \text{sub}(\mathcal{H})$  and  $d \in \Delta'$ , s.t.  $(n - \text{dist}(d)) \leq \text{nd}(C)$ ,  $d \in C^{\mathcal{I}}$  iff  $d^{\mathcal{I}_1} \in C^{\mathcal{I}_1}$ . We distinguish the cases based on the syntactical shape of  $C$ .

- For  $C = \top$ , the claim follows trivially.
- For  $C = A \in \mathbf{Nc}$ , we note that by construction,  $\text{tp}(d)_{\mathcal{I}} \cap \Sigma = \text{tp}(d^{\mathcal{I}_1})_{\mathcal{I}_1} \cap \Sigma$ , which implies that  $d \in A^{\mathcal{I}}$  iff  $d^{\mathcal{I}_1} \in A^{\mathcal{I}_1}$ .
- For  $C = \neg D$ , by inductive hypothesis,  $d \in D^{\mathcal{I}}$  iff  $d^{\mathcal{I}_1} \in D^{\mathcal{I}_1}$ , so that also  $d \in (\neg D)^{\mathcal{I}}$  iff  $d^{\mathcal{I}_1} \in (\neg D)^{\mathcal{I}_1}$ .
- Let  $C = C_1 \sqcap C_2$ . We have  $d \in (C_1 \sqcap C_2)^{\mathcal{I}}$  iff  $d \in C_1^{\mathcal{I}}$  and  $d \in C_2^{\mathcal{I}}$ . By inductive hypothesis, this holds iff  $d^{\mathcal{I}_1} \in C_1^{\mathcal{I}_1}$  and  $d^{\mathcal{I}_1} \in C_2^{\mathcal{I}_1}$ , which holds iff  $d^{\mathcal{I}_1} \in (C_1 \sqcap C_2)^{\mathcal{I}_1}$ .
- Finally, let  $C = \exists r.D$ . If  $d \in C^{\mathcal{I}}$ , there must be  $\langle d, e \rangle \in r^{\mathcal{I}}$ , which by **I3** means that  $\langle h(d), \text{tp}(d)_{\mathcal{I}}, r, h(e) \rangle \in \mathfrak{R}$ . By construction, we have  $\langle h(d), f(d), r, h(e) \rangle \in \mathfrak{R}_1$ , which means by construction of  $\mathcal{J}$  that we have  $\langle d^{\mathcal{I}_1}, e^{\mathcal{I}_1} \rangle \in r^{\mathcal{I}_1}$ . Note that  $\text{dist}(e) = \text{dist}(d) + 1$ , and  $\text{nd}(D) = \text{nd}(C) - 1$ , so that we can apply the

inductive hypothesis. We obtain  $e^{\mathcal{I}_1} \in D^{\mathcal{I}_1}$ , and thus  $d^{\mathcal{I}_1} \in (\exists r.D)^{\mathcal{I}_1}$ .

Now assume  $d^{\mathcal{I}_1} \in C^{\mathcal{I}_1}$ . By construction, we then must have  $\langle h(d), \text{tp}(d^{\mathcal{I}_1})_{\mathcal{I}_1}, r, v' \rangle \in \mathfrak{R}_1$  s.t.  $e \in C^{\mathcal{I}_1}$  for all  $\langle \mathcal{I}_1, e \rangle \in I(v')$ , and by construction, we have  $\langle h(d), \text{tp}(d)_{\mathcal{I}}, r, v' \rangle \in \mathfrak{R}$ . By **I3**, there must then be  $e \in \Delta'$  s.t.  $h(e) = v'$ . Since thus  $\langle \mathcal{I}_1, e^{\mathcal{I}_1} \rangle \in I(v')$ , we obtain that  $e^{\mathcal{I}_1} \in D^{\mathcal{I}_1}$ , which by inductive hypothesis means that  $e^{\mathcal{I}} \in D^{\mathcal{I}}$ . It follows that  $d \in C^{\mathcal{I}}$ .

It follows now in particular that for any  $a \in \text{ind}(\mathcal{H} \cup \mathcal{K})$  and  $C \in \mathcal{H}$ ,  $a^{\mathcal{I}_1} \in C^{\mathcal{I}_1}$  iff  $a^{\mathcal{I}} \in C^{\mathcal{I}}$ . Since  $\mathcal{I}_1 \in \mathbf{I}$ , we have  $\mathcal{I}_1 \models \mathcal{H}$ , and thus for all  $C(a) \in \mathcal{H}$ ,  $\mathcal{I}_1 \models C(a)$ . As a consequence, we obtain  $\mathcal{I} \models C(a)$ , and thus  $\mathcal{I} \in \mathcal{J}$  and  $\mathcal{I}$  is abstracted also by  $\mathcal{J}_1$ .  $\square$

**Lemma 2.** *Let  $\mathcal{J}$  be a hypothesis abstraction. Then,  $\mathcal{J}$  can be transformed into a hypothesis abstraction  $\mathcal{J}' = \langle V', \lambda', \mathfrak{R}', F' \rangle$  where, for  $\ell = |T_{\mathcal{K} \cup \Phi}| \cdot 2^{|T_{\mathcal{K} \cup \Phi}|}$ , i)  $V'$  contains at most  $\ell$  internal nodes, ii) every  $v \in V'$  has at most  $\ell$  successors in  $\mathfrak{R}'$ , and iii) every path of outgoing nodes contains at most  $\ell$  nodes.*

*Proof.* To show that  $\mathcal{J}$  can be reduced into an interpretation abstraction of the required size, we use the facts that

- n1** nodes that have no connection to a named node can be removed,
- n2** we can identify internal nodes with the same label,
- n3** if there are two role assignments  $\langle v_1, t, r, v_2 \rangle, \langle v_1, t, r, v_2' \rangle \in \mathfrak{R}$  and  $\lambda(v_2) = \lambda(v_2')$ , then the latter can be removed, and
- n4** the length of any path from or to a named node that does not contain another named node can be restricted to  $\ell$ .

Point **n1** does not require further explanation, while the others need more of an argument.

For **n2**, assume  $v_1, v_2 \in V$  are two internal nodes s.t.  $\lambda(v_1) = \lambda(v_2)$ . Define a mapping  $m : V \rightarrow (V \setminus \{v_2\})$  by setting  $m(v) = v$  for  $v \neq v_2$  and  $m(v_2) = v_1$ . We construct a new interpretation abstraction  $\mathcal{J}_1 = \langle V_1, \lambda_1, s, \mathfrak{R}_1, F_1 \rangle$  by setting

- $V_1 = V \setminus \{v_2\}$ ,
- $\lambda_1(v) = \lambda(v)$  for all  $v \in V_1$ ,
- $\mathfrak{R}_1 = \{\langle m(v), t, r, m(v') \rangle \mid \langle v, t, r, v' \rangle \in \mathfrak{R}\}$ , and
- $F_1 = F \cap V_1$ .

One easily verifies that  $\mathcal{J}_1$  satisfies Conditions **D1–D5**, and thus is  $\mathcal{ALC}$ -conform and  $\Sigma$ -complete. To show that it explains  $\Phi$ , we need to show that  $\mathcal{J}_1$  abstracts at least one model of  $\mathcal{K}$ , and every model of  $\mathcal{K}$  abstracted by  $\mathcal{J}_1$  entails  $\mathcal{H}$ . Let  $\mathcal{I}$  be a model of  $\mathcal{K}$  abstracted by  $\mathcal{J}$  via  $h : \Delta' \rightarrow V$ . Let  $a_{v_1}$  be such that  $s(a_{v_1}) = v_1$ , and  $a_{v_2}$  be such that  $s(a_{v_2}) = v_2$ . We construct a new interpretation  $\mathcal{I}_1$  which has as domain  $\Delta^{\mathcal{I}_1} = \{d \in \Delta^{\mathcal{I}} \mid h(d) \neq v_2\}$ . Define a mapping  $m : \Delta^{\mathcal{I}} \rightarrow \Delta^{\mathcal{I}_1}$  by setting  $m(d) = d$  if  $d \notin \Delta'$  or  $h(d) \neq v_2$ , and  $m(d) = a_{v_1}^{\mathcal{I}}$  otherwise. Construct  $\mathcal{I}_1$  as

- $A^{\mathcal{I}_1} = A^{\mathcal{I}} \cap \Delta^{\mathcal{I}_1}$  for all  $A \in \mathbf{Nc}$ , and
- $r^{\mathcal{I}_1} = \{\langle m(d), m(e) \rangle \mid \langle d, e \rangle \in r^{\mathcal{I}}\}$  for all  $r \in \mathbf{Nr}$ .

The transformation is type-preserving, and since  $\mathcal{I} \models \mathcal{K}$ , so does  $\mathcal{I}_1$ . We can obtain a function  $h' : (\Delta' \cap \Delta^{\mathcal{I}_1}) \rightarrow V'$  witnessing abstraction by  $\mathcal{J}_1$  by setting  $h'(d) = h(m(d))$ , for which Conditions **I1–I3** are easily verified. Consequently,  $\mathcal{J}_1$  abstracts a model of  $\mathcal{K}$ . Now let  $\mathcal{I}$  be a model of  $\mathcal{K}$  abstracted by  $\mathcal{J}_1$ . By duplicating the individual  $d$  s.t.  $h(d) = v_1$  to an individual  $d'$  with  $h(d') = v_2$ , we can in a similar fashion construct a  $\mathcal{I}_1$  that is abstracted by  $\mathcal{J}$ , and that entails  $\mathcal{K} \cup \Phi$  iff so does  $\mathcal{I}$ .

It follows that every model of  $\mathcal{K}$  abstracted by  $\mathcal{J}_1$  entails  $\mathcal{H}$ , so that  $\mathcal{J}_1$  explains  $\Phi$ . **n3** can be shown in the same way.

For Point **n4**, we only consider the case of a path from an named node. The other case is similar. Assume there is such a path

$$v_1, t_1, r_1, v_2, t_2, r_2, \dots, r_{n-1}, t_{n-1}, v_n$$

where  $n > \ell$ . We show that  $\mathcal{J}$  can then be modified in a way that preserves all properties required by the Lemma so that this path becomes shorter. We ignore the types for now, and consider  $\pi = v_1, r_1, \dots, r_{n-1}, v_n$ . We say that an interpretation  $\mathcal{I}$  abstracted by  $\mathcal{J}$  via  $h$  implements  $\pi$  iff there exists  $d_i \in \Delta'$  with  $h(d_i) = v_i$  for all  $i \in \llbracket 1, n \rrbracket$  s.t.  $\langle d_i, d_{i+1} \rangle \in r_i$  for all  $i \in \llbracket 1, n-1 \rrbracket$ . If there is no interpretation  $\mathcal{I}$  that implements  $\pi$ , let  $i$  be the largest element in  $\llbracket 1, n \rrbracket$  s.t. the path  $v_1, r_1, \dots, r_{i-1}, v_i$  is implemented. Clearly, we can then remove all role assignments  $\langle v_i, t, r, v_{i+1} \rangle$ , since they do not affect the interpretations abstracted by  $\mathcal{J}$ . Otherwise, assume the interpretation  $\mathcal{I}$  implements  $\pi$ , and  $h$  is the function by which  $\mathcal{I}$  is abstracted by  $\mathcal{J}$ . For  $i \in \llbracket 1, n \rrbracket$ , let  $d_i \in \Delta'$  be s.t.  $h(d_i) = v_i$ . Because of **I3** in Definition 3, for every  $i \in \llbracket 1, n-1 \rrbracket$  there exists  $\langle v_i, \text{tp}(d_i)_{\mathcal{I}}, r_i, v_{i+1} \rangle \in \mathfrak{R}$ , so that we can assume that  $t_i = \text{tp}(d_i)_{\mathcal{I}}$ . Because there are at most  $\ell$  pairs  $\langle t, T \rangle$  of a type  $a$  of types, by the pigeon hole principle, there must be  $i, j \in \llbracket 1, n \rrbracket$  s.t.  $i < j$ ,  $\lambda(v_i) = \lambda(v_j)$  and  $t_i = t_j$ . We modify  $\mathfrak{R}$  so that it “skips” the elements between  $v_i$  and  $v_j$ , by replacing  $\langle v_{i-1}, t_{i-1}, r_{i-1}, v_i \rangle$  with  $\langle v_{i-1}, t_{i-1}, r_{i-1}, v_j \rangle$ .

Denote by  $\mathcal{J}_1 = \langle V_1, \lambda_1, s, \mathfrak{R}_1 \rangle$  the result of applying this operation.  $\mathcal{J}_1$  is  $\mathcal{ALC}$ -conform and  $\Sigma$ -complete if so is  $\mathcal{J}$ . We show that furthermore,  $\mathcal{J}_1$  still explains  $\Phi$ , that is, that for every model  $\mathcal{I}_1$  of  $\mathcal{K}$  is abstracted by  $\mathcal{J}$ , we have  $\mathcal{I}_1 \models \Phi$ . Let  $\mathcal{I}_1$  be a model of  $\mathcal{K}$  that is abstracted by  $\mathcal{J}_1$  via the mapping  $h_1 : \Delta' \rightarrow V_1$ . If  $\mathcal{I}_1$  does not use the new role assignment  $\langle v_{i-1}, t_{i-1}, r_{i-1}, v_j \rangle$ , then it is also abstracted by  $\mathcal{J}$ . Otherwise, there are  $d'_{i-1}, d'_j \in \Delta'$  s.t.  $h_1(d'_{i-1}) = v_{i-1}$ ,  $h_1(d'_j) = v_j$  and  $\langle d'_{i-1}, d'_j \rangle \in r_{i-1}$ . Based on  $\mathcal{I}_1$  and the model  $\mathcal{I}$  used before, we construct a model  $\mathcal{I}_2$  that is abstracted by  $\mathcal{J}$  s.t.  $\mathcal{I}_2 \models \mathcal{K}$  and  $\mathcal{I}_2 \not\models \Phi$ .

Intuitively, we adapt  $\mathcal{I}_1$  by putting the path connecting  $d_i$  and  $d_j$  in  $\mathcal{I}$  between  $d_{i-1}$  and  $d_i$ . Specifically, we define  $\mathcal{I}_2$

as follows:

$$\begin{aligned} \Delta^{\mathcal{I}_2} &= \Delta^{\mathcal{I}_1} \cup \Delta^{\mathcal{I}} \setminus \{d'_j\}, \\ A^{\mathcal{I}_2} &= A^{\mathcal{I}_1} \cup A^{\mathcal{I}} \text{ for every } A \in \text{Nc}, \\ r^{\mathcal{I}_2} &= \{ \langle d_1, d_2 \rangle \in r^{\mathcal{I}_1} \mid d_1 \neq d'_j \text{ or } d_2 \neq d'_j \} \\ &\quad \cup r^{\mathcal{I}} \\ &\quad \cup \{ \langle d_1, d_i \rangle \mid \langle d_1, d'_j \rangle \in \mathcal{I}_1 \} \\ &\quad \cup \{ \langle d_j, d_2 \rangle \mid \langle d'_j, d_2 \rangle \in \mathcal{I}_2 \} \text{ for every } r \in \text{Nr}, \\ a^{\mathcal{I}_2} &= a^{\mathcal{I}_1} \text{ for every } a \in \text{Nl}. \end{aligned}$$

Because  $\text{tp}(d_j)_{\mathcal{I}} = \text{tp}(d'_j)_{\mathcal{I}_1}$ , the construction is type-preserving, which implies  $\mathcal{I}_2 \models \mathcal{K}$ , but also  $\mathcal{I}_2 \not\models \Phi$ . Furthermore,  $\mathcal{I}_2$  is abstracted by  $\mathcal{J}$ .  $\square$

**Lemma 3.** *For every  $\mathcal{ALC}$ -conform,  $\Sigma$ -complete interpretation abstraction  $\mathcal{J} = \langle V, \lambda, s, \mathfrak{R}, F \rangle$ , there exists an ABox  $\mathcal{H}$  s.t. i) the models of  $\mathcal{K} \cup \mathcal{H}$  are exactly the models of  $\mathcal{K}$  accepted by  $\mathcal{J}$ , ii)  $|\text{ind}(\mathcal{H})| \leq |V|$ , and iii) for every  $a \in \text{ind}(\mathcal{H})$ ,  $\mathcal{H}$  contains one assertion  $C(a)$ , with  $\text{size}(C)$  exponentially bounded by the path lengths between outgoing nodes in  $\mathcal{J}$ .*

*Proof.* For every internal node  $v \in V$ , let  $a_v$  be the individual s.t.  $s(a_v) = v$ . We assign to every node  $v \in V$  and  $i \geq 0$  a depth-bounded concept  $C_v^{(i)}$ , and to every  $v \in V$  a concept  $C_v$ .  $C_v^{(0)}$  is defined by

$$C_v^{(0)} = \bigsqcup_{t \in \lambda(v)} \left( \prod_{A \in t \cap \Sigma \cap \text{Nc}} A \sqcap \prod_{A \in (\Sigma \cap \text{Nc}) \setminus t} \neg A \right)$$

For  $i > 0$ , if  $v \in F$ ,  $C_v^{(i)} = C_v^{(0)}$ , and otherwise

$$C_v^{(i)} = \bigsqcup_{t \in \lambda(v)} \left( \prod_{A \in t \cap \Sigma \cap \text{Nc}} A \sqcap \prod_{A \in (\Sigma \cap \text{Nc}) \setminus t} \neg A \right) \quad (23)$$

$$\sqcap \prod \{ \exists r. C_{v'} \mid \langle v, t, r, v' \rangle \in \mathfrak{R}, v' \text{ is outgoing} \} \quad (24)$$

$$\sqcap \prod_{r \in \text{Nr} \cap \Sigma} \forall r. \left( \bigsqcup \{ C_{v'}^{(i-1)} \mid \langle v, t, r, v' \rangle \in \mathfrak{R} \} \right) \quad (25)$$

We then set  $C_v = C_v^{(n)}$ , where  $n$  is the maximal path length of any path of outgoing edges. As the outgoing nodes cannot form a cycle due **D1**, the induction on the existential role restrictions always terminates. The depth-bound is used to ensure that the induction also terminates for the universal restrictions. These universal restrictions are used to restrict the possible successors in accordance with **I3**, without conflicting with the internal nodes which may form cycles.

$\mathcal{H}$  contains the concept assertion  $C_v(a_v)$  for every internal node  $v$ , and the role assertion  $r(a_v, a_{v'})$  for every  $\langle v, t, r, v' \rangle \in \mathfrak{R}$  for which  $v$  and  $v'$  are internal. One can verify that  $\mathcal{H}$  satisfies the size restrictions given in the lemma.

It remains to show that every model of  $\mathcal{K}$  abstracted by  $\mathcal{J}$  is a model of  $\mathcal{H}$ , and that every model of  $\mathcal{K} \cup \mathcal{H}$  is abstracted by  $\mathcal{J}$ .

Assume  $\mathcal{I}$  is abstracted by  $\mathcal{J}$  via  $h : \Delta' \rightarrow V$ . We show by induction on the nesting depth that for every node  $v$ ,  $h(v) \in C_v^{\mathcal{I}}$ : For  $v \in F$ , by **I2**, we have  $\text{tp}(h(v))_{\mathcal{I}} \in \lambda(v)$ , and thus

$$h(v) \in \left( \prod_{A \in t \cap \Sigma \cap N_c} A \sqcap \prod_{A \in (\Sigma \cap N_c) \setminus t} \neg A \right)^{\mathcal{I}}.$$

For the induction step, assume that for every role successor  $v'$  of  $v$  we have  $h(v') \in C_{v'}^{\mathcal{I}}$ . It then follows directly from the definition that then  $h(v) \in C_v^{\mathcal{I}}$ . Consequently,  $\mathcal{I} \models C(a_v)$  for every  $C(a_v) \in \mathcal{H}$ . Let  $r(a_v, a_{v'}) \in \mathcal{H}$ . By Condition **D2**, because  $v$  and  $v'$  are internal, we have  $\langle v, t, r, v' \rangle \in \mathfrak{R}$  for every type  $t \in \lambda(v)$ . It follows by **I3** that  $\langle h(v), h(v') \rangle \in r^{\mathcal{I}}$ , and thus  $\mathcal{I} \models r(a_v, a_{v'})$ . We have shown that  $\mathcal{I} \models \mathcal{H}$ .

Now assume  $\mathcal{I} \models \mathcal{H}$ . We recursively build a function  $h : \Delta' \rightarrow V$  that satisfies conditions **I1–I3**, and thus witnesses that  $\mathcal{I}$  is abstracted by  $\mathcal{J}$ . For each internal node  $v$ , we have a named individual  $a_v$  and we set  $h(v) = a_v^{\mathcal{I}}$ . Outgoing nodes are assigned inductively based on the definition of  $C_v$ . If  $h(d) = v$  and  $d \in C_v^{\mathcal{I}}$ , there is a disjunct  $C_{v,t}$  of  $C_v$  s.t.  $d \in C_{v,t}^{\mathcal{I}}$ . If  $C_{v,t}^{\mathcal{I}}$  has as conjunct  $\exists r.C_{v'}$ , then there must be  $\langle d, d' \rangle \in r^{\mathcal{I}}$  s.t.  $d' \in C_{v'}^{\mathcal{I}}$ , and we set  $h(d') = v'$ . As a result, we obtain a mapping  $h : \Delta' \rightarrow V$  for some  $\Delta' \subseteq \Delta^{\mathcal{I}}$  s.t.  $h(d) \in C_{h(d)}^{\mathcal{I}}$ . We show that this implies  $\text{tp}(d)_{\mathcal{I}} \in \lambda(h(d))$ . Because  $d \in C_{h(d)}^{\mathcal{I}}$ , there exists  $t \in \lambda(h(d))$  s.t.

$$d \in \left( \prod_{A \in t \cap \Sigma \cap N_c} A \sqcap \prod_{A \in (\Sigma \cap N_c) \setminus t} \neg A \right)^{\mathcal{I}},$$

which means that  $\text{tp}(d)_{\mathcal{I}} \cap \Sigma = t \cap \Sigma$ . By **D4**, we then have  $\text{tp}(d)_{\mathcal{I}} \in \lambda(h(d))$ . We obtain that  $h$  satisfies **I2**. **I1** is satisfied by construction and **I3** is a consequence of the fact that  $\text{tp}(d)_{\mathcal{I}} \in \lambda(h(d))$  for every  $d \in \Delta'$ . We have shown that  $\mathcal{I}$  is abstracted by  $\mathcal{J}$ .  $\square$

**Theorem 7.** *ALC ABox abduction is in  $\text{N2EXPTIME}^{\text{NP}}$ .*

*Proof.* We guess an *ALC*-conform,  $\Sigma$ -complete interpretation abstraction  $\mathcal{J}$  within the size bounds of Lemma 2. Because we can reuse outgoing nodes with the same label, it suffices to guess one such interpretation abstraction that is of at most double exponential size, similar as we did for Lemma 10. We then verify it abstracts some model of  $\mathcal{K}$  by guessing for each node  $v$  a type  $t \in \lambda(v)$  and checking whether those types can be implemented by a model of  $\mathcal{K}$ . This check is possible in polynomial time by just considering a node, its assigned type, and its successors. Finally, we verify that it explains the observation by making another such guess to verify whether there exists a model of  $\mathcal{K}$  s.t.  $\mathcal{K} \models \Phi$ .  $\square$

## D Size-Restricted Abduction

Regarding the upper bounds, only the argument for flat solutions in *ALCI* requires some additional argument.

**Lemma 11.** *Existence of hypotheses for size restricted *ALCI* abduction problems can be decided in  $\text{NEXPTIME}^{\text{NP}}$ .*

*Proof.* Let  $\mathfrak{A} = \langle \mathcal{K}, \Phi, \Sigma, k \rangle$  be the size-restricted abduction problem. We modify the *CONEXPTIME*-procedure in the proof for Theorem 3 as follows: after we computed in deterministic exponential time the set  $T_{\mathcal{K} \cup \Phi}$  of types, we guess a flat ABox  $\mathcal{H}$  of size at most  $k$  s.t. for every  $r(a, b) \in \Phi$ ,  $r(a, b) \in \mathcal{H}$ . Since  $k$  is encoded in binary,  $\mathcal{H}$  may be up to exponential in size. To decide whether  $\mathcal{H}$  is a hypothesis, we use the NP-oracle to decide whether for every selector function  $s_e : \text{ind}(\mathcal{H}) \rightarrow T_{\mathcal{K} \cup \Phi}$ , either  $s_e$  is not compatible with  $\mathcal{K} \cup \mathcal{H}$ , or for some  $C(a) \in \Phi$ ,  $C \notin s_e(a)$ . This can be easily verified by a non-deterministic, polynomially time bounded oracle which takes as input the pairs  $\langle T_{\mathcal{K} \cup \Phi}, \mathcal{H} \rangle$ , guesses the function  $s_e$ , and accepts if  $s_e$  is compatible with  $\mathcal{K} \cup \mathcal{H}$  and for some  $C(a) \in \Phi$ ,  $C \notin s_e(a)$ .  $\square$

**Lemma 4.** *Size-restricted  $\mathcal{EL}$  abduction is NP-hard.*

*Proof.* Let  $\phi$ ,  $\mathcal{K}$ ,  $\Phi$  and  $\Sigma$  be as in the proof sketch of the main text. We need to show that  $\langle \mathcal{K}, \Phi, \Sigma \rangle$  has a hypothesis of size at most  $2m$  iff  $\phi$  is satisfiable. If  $\phi$  is satisfiable by a truth assignment  $as : \{p_1, \dots, p_m\} \rightarrow \{0, 1\}$ , we can build a hypothesis of size  $2m$  by setting

$$\mathcal{H} = \{\text{True}(p_i) \mid a(p_i) = 1\} \cup \{\text{False}(p_i) \mid as(p_i) = 0\}.$$

Now assume  $\langle \mathcal{K}, \Phi, \Sigma \rangle$  has a hypothesis  $\mathcal{H}$  of size at most  $2m$ . For every variable  $p_i$ , the only way to entail  $P(p_i)$  using only names from  $\Sigma$  is to add either  $\text{True}(p_i)$  or  $\text{False}(p_i)$  to the hypothesis. Each such assertion adds 2 to the size of  $\mathcal{H}$ , and as  $\mathcal{H}$  is not allowed to have a size greater than  $2m$ , it must thus contain exactly one such axiom for each variable. The satisfying truth assignment  $as : \{p_1, \dots, p_m\} \rightarrow \{0, 1\}$  is then obtained by setting  $as(p_i) = 0$  if  $\text{False}(p_i) \in \mathcal{H}$  and  $as(p_i) = 1$  if  $\text{True}(p_i) \in \mathcal{H}$ . Since  $\mathcal{K} \cup \mathcal{H} \models C(c_i)$  for every clause  $c_i$ , we can see that  $as$  makes every clause in  $\phi$  true, and is thus a satisfying assignment.  $\square$

**Lemma 5.** *Size restricted  $\mathcal{EL}_{\perp}$  abduction is  $\text{NEXPTIME}$ -hard.*

*Proof.* We first give a more formal definition of the exponential tiling problem. The problem is given by a tuple  $\langle T, T_I, t_e, V, H, n \rangle$  of a set  $T$  of tile types, a sequence  $T_I = t_1 \dots t_m \in T^*$  of initial tiles, a final tile  $t_e$ , vertical and horizontal tiling conditions  $V, H \subseteq T \times T$ , and a number  $n$  in binary encoding. We call a mapping

$$f : \llbracket 1, 2^n \rrbracket \times \llbracket 1, 2^n \rrbracket \rightarrow T$$

a *tiling*, which is *valid* iff  $f(2^n, 2^n) = t_e$ , for all  $i \in \llbracket 1, m \rrbracket$ ,  $f(i, 1) = t_i$ , and for all  $i \in \llbracket 1, 2^n - 1 \rrbracket$  and  $j \in \llbracket 1, 2^n \rrbracket$ ,

$$\langle f(i, j), f(i+1, j) \rangle \in H$$

and

$$\langle f(j, i), f(j, i+1) \rangle \in V.$$

Based on  $T$ ,  $H$ ,  $V$  and  $n$ , we construct an  $\mathcal{EL}_{\perp}$  KB  $\mathcal{K}$ , an ABox  $\Phi$ , and a signature  $\Sigma$  s.t.  $\langle \mathcal{K}, \Phi, \Sigma \rangle$  has an ABox hypothesis of size at most

$$k = 2 \cdot (2^{2n} - m) + 3 \cdot 2 \cdot (2^{2n} - 2^n) + 2$$

iff the tiling problem has a solution.



We define the signature as

$$\Sigma = \{\text{Start}, x, y\} \cup \{A_t \mid t \in T\},$$

where the concept name *Start* will mark the first tile, the role names *x* and *y* will denote the horizontal and vertical neighbourhood in the tiling, and each tile type  $t \in T$  has a corresponding concept name  $A_t$ . The observation is  $\Phi = \{\text{End}(a)\}$ .

$\mathcal{K}$  uses additional concept names  $C_1, \overline{C}_1, \dots, C_n, \overline{C}_n$  for  $C \in \{X, Y\}$  to encode a binary counter for both coordinates, and a special concept name  $B$  that will ensure that every tile is represented in the hypothesis. Together with a tile, the concept name *Start* initialises the counter:

$$\text{Start} \sqcap A_t \sqsubseteq \overline{X}_1 \sqcap \dots \sqcap \overline{X}_n \sqcap \overline{Y}_1 \sqcap \dots \sqcap \overline{Y}_n \quad \text{for every } t \in T.$$

To entail the observation, both counters must reach  $2^n$  on an individual name marked with  $B$  and some tile type:

$$X_1 \sqcap \dots \sqcap X_n \sqcap Y_1 \sqcap \dots \sqcap Y_n \sqcap B \sqcap A_e \sqsubseteq \text{End}$$

Every domain element represents at most one counter value:

$$C_i \sqcap \overline{C}_i \sqsubseteq \perp \quad \text{for every } i \in \llbracket 1, n \rrbracket, C \in \{X, Y\}.$$

The counter values are incremented along the *x* and *y*-predecessors using the following axioms for  $\langle C, c \rangle \in \{\langle X, x \rangle, \langle Y, y \rangle\}$ :

$$\begin{aligned} \exists c. (\overline{C}_i \sqcap C_{i-1} \sqcap \dots \sqcap C_1) &\sqsubseteq C_i && \text{for } i \in \llbracket 1, n \rrbracket \\ \exists c. (C_i \sqcap C_{i-1} \sqcap \dots \sqcap C_1) &\sqsubseteq \overline{C}_i && \text{for } i \in \llbracket 1, n \rrbracket \\ \exists c. (\overline{C}_i \sqcap \overline{C}_j) &\sqsubseteq \overline{C}_i && \text{for } i, j \in \llbracket 1, n \rrbracket, j < i \\ \exists c. (C_i \sqcap \overline{C}_j) &\sqsubseteq Z_i && \text{for } i, j \in \llbracket 1, n \rrbracket, j < i. \end{aligned}$$

The vertical and horizontal tiling conditions are ensured using the following axioms:

$$\begin{aligned} \exists x. A_t \sqcap A_{t'} &\sqsubseteq \perp \text{ for every } \langle t, t' \rangle \in (T \times T) \setminus H \\ \exists y. A_t \sqcap A_{t'} &\sqsubseteq \perp \text{ for every } \langle t, t' \rangle \in (T \times T) \setminus V \end{aligned}$$

The initial tilings from  $T_I$  are specified as follows

$$\begin{aligned} \text{Start} &\sqsubseteq I_1 \\ I_i &\sqsubseteq \forall x. I_{i+1} && \text{for } i \in \llbracket 1, m-1 \rrbracket \\ I_i &\sqsubseteq A_{t_i} && \text{for } i \in \llbracket 1, m \rrbracket \end{aligned}$$

Finally, the special concept name  $B$  is used to ensure that every hypothesis contains an individual name for every tile. This name is initialised by the individual satisfying *Start*, and then propagated in *x* and *y* direction, provided that both the *x* and the *y* successor satisfy it, or one of the counter values is 0 (in which case we do not require a successor in the corresponding direction)

$$\begin{aligned} \text{Start} &\sqsubseteq B \\ \overline{X}_1 \sqcap \dots \sqcap \overline{X}_n \sqcap \exists y. (A_t \sqcap B) &\sqsubseteq B && \text{for every } t \in T \\ \overline{Y}_1 \sqcap \dots \sqcap \overline{Y}_n \sqcap \exists x. (A_t \sqcap B) &\sqsubseteq B && \text{for every } t \in T \\ \exists x. (A_t \sqcap B) \sqcap \exists y. (A_{t'} \sqcap B) &\sqsubseteq B && \text{for every } t, t' \in T \end{aligned}$$

This completes the construction.

First, assume the tiling problem has a solution  $f$ . Based on  $f$ , we construct a hypothesis for  $\langle \mathcal{K}, \Phi, \Sigma \rangle$  of size  $k$ . We use  $2^{2^n}$  individual names  $a_{i,j}$  assigned with coordinates  $i, j \in \llbracket 1, 2^n \rrbracket$ , where for convenience, we let  $a_{2^n, 2^n} = a$ . The hypothesis is then:

$$\begin{aligned} \mathcal{H} = &(\{A_t(a_{i,j}) \mid f(i,j) = t\} \setminus \{A_{t_i}(a_{i,1}) \mid 1 \in \llbracket 1, m \rrbracket\}) \\ &\cup \{x(a_{i+1,j}, a_{i,j}) \mid i \in \llbracket 1, 2^n - 1 \rrbracket, j \in \llbracket 1, 2^n \rrbracket\} \\ &\cup \{y(a_{i,j+1}, a_{i,j}) \mid i \in \llbracket 1, 2^n \rrbracket, j \in \llbracket 1, 2^n - 1 \rrbracket\} \\ &\cup \{\text{Start}(a_{1,1})\} \end{aligned}$$

It is standard to verify that  $\text{size}(\mathcal{H}) = k$ ,  $\mathcal{K} \cup \mathcal{H} \models B(a_{i,j})$  for every  $i, j \in \llbracket 1, 2^n \rrbracket$ , as well as  $\mathcal{K} \cup \mathcal{H} \models \Phi$ .

Now assume  $\langle \mathcal{K}, \Phi, \Sigma \rangle$  has a hypothesis  $\mathcal{H}$  of size  $k$ . Since  $\mathcal{K} \cup \mathcal{H} \models \Phi$ ,  $\mathcal{H}$  has to ensure the following:

1.  $\mathcal{K} \cup \mathcal{H} \models (C_1 \sqcap \dots \sqcap C_n)(a)$  for both  $C \in \{X, Y\}$ . Since *Start* is the only name in  $\Sigma$  that can trigger the assignment of any counter value, there must be some assertion  $\text{Start}(a_0) \in \mathcal{H}$ , as well as a path of length  $2^{n+1}$  along *x* and *y*-successors connecting  $a$  to  $a_0$ .
2.  $\mathcal{K} \cup \mathcal{H} \models B(a)$ . While the assertions mentioned so far ensure  $\mathcal{K} \cup \mathcal{H} \models B(a_0)$ , any element on the path connecting  $a$  to  $a_0$  must entail  $B$  as well. This means that either 1) their *X*-counter corresponds to 0 and they have a *y*-successor satisfying  $B$  and  $A_t$  for some  $t \in T$ , 2) their *Y*-counter corresponds to 0 and they have an *x*-successor satisfying  $B$  and  $A_t$  for some  $t \in T$ , or 3) they have both an *x*-successor and a *y*-successor satisfying  $B$  and some tile.

These conditions, together with the fact that every individual can have only one counter value assigned, require that for every coordinate  $\langle x, y \rangle \in \llbracket 1, 2^n \rrbracket \times \llbracket 1, 2^n \rrbracket$  there must exist at least one individual satisfying the corresponding counter values, for which  $\mathcal{H}$  explicitly states the tile type and its *x* and *y*-successor.

Except for the  $m$  initial tiles, we thus need one concept assertion per tile type, plus the assertion  $\text{Start}(a_{1,1})$ . Therefore, we need at least  $2^{2^n} - m + 1$  concept assertions (for the tile types) and  $2 \cdot (2^{2^n} - 2^n)$  role assertions (for the neighbourhood). Each concept assertion has at least size 2, and every role assertion has size 3, which means that

$$\text{size}(\mathcal{H}) \geq 2 \cdot (2^{2^n} - m) + 3 \cdot 2 \cdot (2^{2^n} - 2^n) - 2 = k.$$

Since also  $\text{size}(\mathcal{H}) \leq k$ , we obtain that  $\text{size}(\mathcal{H}) = k$ , and that  $\mathcal{H}$  is the smallest ABox that satisfies all these conditions. We obtain that every coordinate  $\langle i, j \rangle \in \llbracket 1, 2^n \rrbracket \times \llbracket 1, 2^n \rrbracket$  is represented by exactly one individual name which has a tile type assigned in  $\mathcal{H}$ . As  $\mathcal{K}$  furthermore enforces that the tiling conditions are met, we obtain that  $\mathcal{H}$  can be used to construct a solution to the tiling problem.  $\square$

**Lemma 6.** *The NEXPTIME<sup>NP</sup>-tiling problem is NEXPTIME<sup>NP</sup>-hard.*

*Proof.* We show that the NEXPTIME<sup>NP</sup> tiling problem is NEXPTIME<sup>NP</sup> hard by a reduction from the word acceptance problem for non-deterministic exponentially time bounded Turing machines with access to an NP-oracle.

For convenience, we assume the Turing machine  $\mathfrak{T}$  to have a slightly different behaviour than usual: while there is a special state  $q_?$  to trigger oracle queries, we do not use dedicated states for the query outcome. Instead, when in query state  $q_?$ , the machine immediately fails if the oracle  $\mathfrak{T}_o$  would accept the word, and otherwise goes into another state as specified by the transition relation. This is without loss of generality, as we can simulate regular oracle calls as follows: 1) guess the outcome of the oracle call, 2) if the guess is yes, verify this by performing the computation in  $\mathfrak{T}$ , 3) if the guess is no, verify this using the oracle  $\mathfrak{T}_o$ .

Let

$$\mathfrak{T}_o = \langle Q_o, \Sigma_o, \Gamma_o, \beta, q_{o0}, F_o, \Delta_o \rangle$$

be the non-deterministic Turing machine to be used by the oracle, where

- $Q_o$  are the states,
- $\Sigma_o$  is the input alphabet
- $\Gamma_o$  with  $\Sigma_o \subseteq \Gamma_o$  is the tape alphabet
- $\beta \in (\Gamma_o \setminus \Sigma_o)$  is the blank symbol,
- $q_{o0} \in Q_o$  is the initial state,
- $F_o$  contain the accepting states, and
- $\Delta_o \subseteq Q_o \times \Gamma_o \times Q_o \times \Gamma_o \times \{-1, +1\}$  is the transition function, where a tuple  $\langle q_1, a_1, q_2, a_2, D \rangle$  states that, when the machine is in state  $q_1$  and reads an  $a_1$  at the current tape position, then it moves to state  $q_2$ , writes  $a_2$  at the current tape position, and moves the tape head according to the value of  $D$ .

The non-deterministic oracle Turing machine using this oracle is defined as

$$\mathfrak{T} = \langle Q, \Sigma, \Gamma, \beta, \Gamma_o, q_0, F, \Delta, q_? \rangle$$

where

- $Q$  are the states,
- $\Sigma$  is the input alphabet,
- $\Gamma$  with  $\Sigma \subseteq \Gamma$  is the tape alphabet,
- $\beta \in (\Gamma \setminus \Sigma)$  is again the blank symbol
- $\Gamma_o$  is the oracle input tape alphabet,
- $q_0$  is the initial state,
- $F \subseteq Q$  is the set of accepting states,
- $\Delta \subseteq ((Q \times \Gamma \times \Gamma_o) \times (Q \times \Gamma \times \{-1, 0, +1\}) \times \Gamma_o \times \{-1, 0, +1\})$  is the transition relation, (which works on two tapes, the standard tape and the oracle tape), and
- $q_? \in (Q \setminus F)$  is the query state to query the oracle.

We further assume  $\mathfrak{T}_o$  to be polynomially bounded, that is, there exists a polynomial  $p_1$  s.t. for input words  $w$ , each run on  $\mathfrak{T}_o$  uses at most  $p_1(|w|)$  steps, and  $\mathfrak{T}$  to be exponentially bounded, that is, there exists a polynomial  $p_2$  s.t. for input words  $w$ , every run of  $\mathfrak{T}$  requires at most  $2^{p_2(|w|)}$  steps. Note that as a result, we can bound both the tape and the length of runs on both Turing machines by  $2^{p(|w|)}$  for some polynomial  $p$ .

Given  $\mathfrak{T}$ ,  $\mathfrak{T}_o$  and the input word  $w = a_1, \dots, a_n$ , we construct a  $\text{NEXPTIME}^{\text{NP}}$ -tiling problem. Without loss of generality, we assume  $n > 2$ . Our set  $T$  of tile types contains the special tiling type  $t_e$  that also serves as final tile, and all other tile types are pairs  $t = \langle t_1, t_2 \rangle$ , where

$$t_1 \in Q \times \Gamma \times \{l, h, r, -, 0\},$$

and

$$t_2 \in Q_o \times \Gamma_o \times \{l, h, r, -, 0\}.$$

The two components of the tile type are used to define the different tape contents, the first component being the tape of  $\mathfrak{T}$ , and the second the tape of  $\mathfrak{T}_o$ . For a tile type  $t = \langle t_1, t_2 \rangle$ ,  $t_1 = \langle q, a, D \rangle$  denotes that  $\mathfrak{T}$  is in state  $q$ , the current tape cell stores  $a$ , and  $D$  refers to the relative position to the tape head: *left*, *here*, *right*, or *elsewhere* (-). The value of  $D = 0$  is furthermore used to mark the first configuration.

The initial tiles are then

$$T_I = \langle t_1^{(1)}, t_2^{(1)} \rangle, \dots, \langle t_1^{(n+1)}, t_2^{(n+1)} \rangle$$

where the first components are defined by

- $t_1^{(1)} = \langle q_0, a_1, h \rangle$ ,
- $t_1^{(2)} = \langle q_0, a_2, l \rangle$ ,
- $t_1^{(i)} = \langle q_0, a_i, 0 \rangle$  for  $i \in \llbracket 3, n \rrbracket$ , and
- $t_1^{(n+1)} = \langle q_0, \beta, 0 \rangle$ ,

and the second components are defined by

- $t_2^{(1)} = \langle q_{o0}, \beta, h \rangle$ ,
- $t_2^{(2)} = \langle q_{o0}, \beta, l \rangle$ , and
- $t_2^{(i)} = \langle q_{o0}, \beta, 0 \rangle$  for  $i \in \llbracket 3, n+1 \rrbracket$ .

The horizontal tiling condition  $H_1$  contains all tuples  $\langle \langle t_1, t_2 \rangle, \langle t'_1, t'_2 \rangle \rangle$ , s.t. for  $i \in \{1, 2\}$ ,  $t_i = \langle q, a, D \rangle$  and  $t'_i = \langle q', a', D' \rangle$ :

- $q = q'$ ,
- if  $D = 0$  and  $a = \beta$ , then  $D' = D$  and  $a' = \beta$ ,
- if  $D = l$ , then  $D' = h$ ,
- if  $D = h$ , then  $D' = r$ ,
- if  $D = r$ , then  $D' \in \{0, -\}$ , and
- if  $D = -$ , then  $D' \in \{0, -, l\}$ .

This makes sure that in the first row of the tiling, all tiles following the initial tiles represent the situation where both tapes have a blank symbol, and that in every row, the state associated to a tile must be the same.

The vertical tiling condition  $V_1$  encodes the transitions from one configuration to another.  $V_1$  contains all tuples  $\langle \langle t_1, t_2 \rangle, \langle t'_1, t'_2 \rangle \rangle \in V_1$ , where for  $i \in \{1, 2\}$ ,  $t_i = \langle q, a, D \rangle$  and  $t'_i = \langle q', a', D' \rangle$ , we have

- $D' \neq 0$ ,
- if  $D \neq h$ , then  $a = a'$ ,
- for  $i = 2$ ,  $q = q' = q_{o0}$ ,
- for  $i = 1$ ,  $\mathfrak{T}$  has a transition from  $q$  to  $q'$

- if  $D = h$ , then the transition from  $q$  to  $q'$  reads  $a$  and writes  $a'$  (on the normal tape if  $i = 1$ , and the oracle tape if  $i = 2$ ),
- if  $D = l$ , then  $D' = h$  if the transition moves the head on the corresponding tape to the left, and otherwise  $D' = -$ ,
- if  $D = r$ , then  $D' = h$  if the transition moves to the right, and otherwise  $D' = -$ , and
- if  $D = h$ , then  $D' = r$  if the transition moves to the left, and  $D' = l$  if the transition moves to the right.

In addition,  $V_1$  contains  $\langle\langle t_1, t_2 \rangle, t_e\rangle$  for every  $t_1$  with associated state  $q_f \in F$ , to make sure the final tile is reached once the Turing machine enters a final state.

Intuitively, the tiling problem  $\langle H_1, V_1, T_I, t_e, p(n) \rangle$  encodes the behavior of  $\mathfrak{T}$  without the oracle. More formally: if we consider the variant of  $\mathfrak{T}$  where  $q_?$  acts just like a normal state, this Turing machine accepts  $w$  iff the tiling problem has a solution.

To now take into account the oracle, it remains to specify the tiling conditions for  $H_2$  and  $V_2$ , which are similar to those for  $H_1$  and  $V_1$ . Note that we want the rows of the first tiling *not* to be initial rows of a tiling for  $\langle H_2, V_2, f(i), t_e, p(n) \rangle$ , unless the encoded state is  $q_?$  and they encode the initial configuration of an accepting run for  $\mathfrak{T}_o$ . Since  $\mathfrak{T}_o$  has only one tape,  $H_2$  and  $V_2$  now only consider the state of the first component of the tile type, which has to be  $q_?$ , and otherwise only consider the second component. Regarding the second component, they are defined just like  $H_1$  and  $V_1$  except that now, they consider transitions in  $\mathfrak{T}_o$ , and modify the state in the second component and not in the first.  $\square$

**Lemma 7.** *Size-restricted  $\mathcal{ALC}$  abduction is  $\text{NEXPTIME}^{\text{NP}}$ -hard.*

*Proof.* The background KB  $\mathcal{K}$  can be seen in Figure 3, and works like it is described in the main text. The signature of abducibles is

$$\Sigma = \{\text{Start}, x, y, T^*\} \cup \{A_t \mid t \in T\}$$

and the observation to be explained is  $\text{End}(a)$ . We describe the different parts of the knowledge base. In the following, we denote by “base tiling” the tiling on the bottom of the generated cube, which is going to be the solution of the tiling problem  $\langle T, T_I, t_e, V_1, H_1, n \rangle$ , while we call the other tilings  $x \times z$ -tilings.

- (26) puts the first tile and initialises all 3 counters.
- (27) gives the conditions for the observation to be entailed: all counters must reach their maximum value, and additionally the concepts  $B_2$  and  $B_4$  must be satisfied. Intuitively,  $B_2$  signals that every coordinate always has a tile associated, and  $B_4$  that for none of the rows in the base tiling, a tiling compatible to  $H_2$  and  $V_2$  can be found.
- (28)–(30) make sure the initial tiles in  $T_I = \{t_1, \dots, t_m\}$  are placed.
- (31)–(35) implement the binary counters for the three coordinates.

- (39)–(39) specify the behaviour of the “hidden tiles” that should not be explicit in the hypothesis, to allow for different tilings to be tested in the models of the hypothesis: the abducible  $T^*$  states the existence of a hidden tile, only one hidden tile can be used at the same time, and hidden tiles can only be used outside of the ground plane of the cube.
- (40)–(43) ensure that every coordinate is assigned a (hidden or explicit) tile type. Specifically,  $B_1$  is entailed at coordinates for which every preceding coordinate has a tile type associated,  $B_2$  is entailed if additionally, the current coordinate has a tile type associated, and for  $c \in \{x, y, z\}$ ,  $B_c$  states the  $c$ -coordinate has either value 0, or the next lower  $c$ -neighbour satisfies  $B_2$ . Consequently, we require either  $\text{Start}$  or  $B_x \sqcap B_y \sqcap B_z$  to entail  $B_1$ .
- (44) and (45) are as in the proof for Lemma 5, and make sure that the base tiling does not break the tiling conditions  $H_1$  and  $V_1$ .
- (46) and (47) test for the tiling conditions on the hidden tilings, and mark errors using the concept name  $B_3$ , which is then propagated towards all  $x$ - and  $y$ -predecessors through (48).
- Finally, (49) makes sure that the concept name  $B_4$ —required for the observation—is propagated along the  $y$ -axis to check whether all tiling attempts on the different  $H_2$ - $V_2$ -tilings fail.

Similar as for Lemma 5, we can find a bound  $k$  that ensures that for every coordinate at most one individual is used, so that hypotheses consists of assertions forming a cube, where the bottom side corresponds to a valid tiling, while the remaining coordinates have the concept name  $T^*$  assigned. The observation  $\text{End}(a)$  can only be entailed by such a cube if the  $\text{NEXPTIME}^{\text{NP}}$ -tiling problem has a solution.  $\square$

$$\text{Start} \sqcap A_t \sqsubseteq \prod_{i=1}^n (\overline{X}_i \sqcap \overline{Y}_i \sqcap \overline{Z}_i) \quad \text{for every } t \in T \quad (26)$$

$$\prod_{i=1}^n (X_i \sqcap Y_i \sqcap Z_i) \sqcap B_2 \sqcap B_4 \sqsubseteq \text{End} \quad \text{for every } t \in T \quad (27)$$

$$\text{Start} \sqsubseteq I_1 \quad (28)$$

$$I_i \sqsubseteq \forall x. I_{i+1} \quad \text{for } i \in \llbracket 1, m-1 \rrbracket \quad (29)$$

$$I_i \sqsubseteq A_{t_i} \quad \text{for } i \in \llbracket 1, m \rrbracket \quad (30)$$

$$C_i \sqcap \overline{C}_i \sqsubseteq \perp \quad \text{for every } i \in \llbracket 1, n \rrbracket, C \in \{X, Y, Z\} \quad (31)$$

$$\exists c. (\overline{C}_i \sqcap C_{i-1} \sqcap \dots \sqcap C_1) \sqsubseteq C_i \quad \text{for } i \in \llbracket 1, n \rrbracket, \langle C, c \rangle \in \{\langle X, x \rangle, \langle Y, y \rangle, \langle Z, z \rangle\} \quad (32)$$

$$\exists c. (C_i \sqcap C_{i-1} \sqcap \dots \sqcap C_1) \sqsubseteq \overline{C}_i \quad \text{for } i \in \llbracket 1, n \rrbracket, \langle C, c \rangle \in \{\langle X, x \rangle, \langle Y, y \rangle, \langle Z, z \rangle\} \quad (33)$$

$$\exists c. (\overline{C}_i \sqcap \overline{C}_j) \sqsubseteq \overline{C}_i \quad \text{for } i, j \in \llbracket 1, n \rrbracket, j < i, \langle C, c \rangle \in \{\langle X, x \rangle, \langle Y, y \rangle, \langle Z, z \rangle\} \quad (34)$$

$$\exists c. (C_i \sqcap \overline{C}_j) \sqsubseteq C_i \quad \text{for } i, j \in \llbracket 1, n \rrbracket, j < i, \langle C, c \rangle \in \{\langle X, x \rangle, \langle Y, y \rangle, \langle Z, z \rangle\} \quad (35)$$

$$T^* \sqsubseteq \bigsqcup_{t \in T} A_t^* \quad (36)$$

$$A_t^* \sqcap A_{t'}^* \sqsubseteq \perp \quad \text{for every } t, t' \in T \text{ s.t. } t \neq t' \quad (37)$$

$$\prod_{i=1}^n \overline{Z}_i \sqcap \bigsqcup_{t \in T} A_t^* \sqsubseteq \perp \quad (38)$$

$$\bigsqcup_{i=1}^n Z_i \sqcap \bigsqcup_{t \in T} A_t \sqsubseteq \perp \quad (39)$$

$$\text{Start} \sqsubseteq B_1 \quad (40)$$

$$B_1 \sqcap (A_t \sqcup A_t^*) \sqsubseteq B_2 \quad \text{for every } t \in T \quad (41)$$

$$(\prod_{i=1}^n \overline{C}_i) \sqcup \exists c. B_2 \sqsubseteq B_c \quad \text{for every } \langle C, c \rangle \in \{\langle X, x \rangle, \langle Y, y \rangle, \langle Z, z \rangle\} \quad (42)$$

$$B_x \sqcap B_y \sqcap B_z \sqsubseteq B_1 \quad (43)$$

$$\exists x. A_t \sqcap A_{t'} \sqsubseteq \perp \quad \text{for every } \langle t, t' \rangle \in (T \times T) \setminus H_1 \quad (44)$$

$$\exists y. A_t \sqcap A_{t'} \sqsubseteq \perp \quad \text{for every } \langle t, t' \rangle \in (T \times T) \setminus V_1 \quad (45)$$

$$(\exists x. A_t \sqcap A_{t'}) \sqcup (\exists x. A_t^* \sqcap A_{t'}^*) \sqsubseteq B_3 \quad \text{for every } \langle t, t' \rangle \in (T \times T) \setminus H_2 \quad (46)$$

$$\exists z. A_t^* \sqcap A_{t'}^* \sqsubseteq B_3 \quad \text{for every } \langle t, t' \rangle \in (T \times T) \setminus V_1 \quad (47)$$

$$\exists x. B_3 \sqcup \exists z. B_3 \sqsubseteq B_3 \quad (48)$$

$$\prod_{i=1}^n (X_i \sqcap Z_i) \sqcap (B_3 \sqcup \neg A_{t_e}) \sqsubseteq B_4 \quad (49)$$

Figure 3: Background knowledge for the reduction from the NEXPTIME<sup>NP</sup>-tiling problem.