

# FINDING TRIANGLES OR INDEPENDENT SETS

Adrian Dumitrescu\*

January 7, 2022

## Abstract

(I) We revisit the algorithmic problem of finding all triangles in a graph  $G = (V, E)$  with  $n$  vertices and  $m$  edges. According to a result of Chiba and Nishizeki (1985), this task can be achieved by a combinatorial algorithm running in  $O(m^{3/2})$  time. All earlier running time analyses for this algorithm are based on considering graph parameters such as arboricity or degeneracy and rely on classic results due to Nash-Williams from the 1960s. We derive these worst-case bounds from first principles and with very simple proofs. We then provide a combinatorial algorithm for finding all triangles in a graph and show that is amenable to the same running time analysis. We also show that the running time of such an algorithm cannot be improved in the worst-case and for the entire range of parameters  $m$  and  $n$ . Our arguments are extended to the problem of finding all small complete subgraphs of a given fixed size.

(II) Given a graph  $G = (V, E)$  with  $n$  vertices and  $m$  edges, we present a randomized algorithm that computes a  $(1 \pm \varepsilon)$ -approximation of the number of triangles in  $G$  and finds a witness with high probability in  $O(n^{\omega(1-\delta)})$  or  $O\left((mn^{-2\delta})^{\frac{2\omega}{\omega+1}}\right)$  expected time, provided  $G$  has a suitable superlinear number of edges and triangles (where  $\omega < 2.376$  is the exponent of matrix multiplication, and  $\varepsilon \leq 0.5$ ,  $\delta \leq 0.25$  are positive constants). This limits the range of a conjecture of Pătraşcu (2010) regarding the triangle detection problem.

(III) We present an algorithm which given a graph  $G = (V, E)$  performs one of the following tasks in  $O(m + n)$  (i.e., linear) time: (i) compute a  $\Omega(1/\sqrt{n})$ -approximation of a maximum independent set in  $G$  (a well-known NP-hard problem), or (ii) find a triangle in  $G$ . The run-time is faster than that for any previous method for each of these tasks. For dense graphs, i.e., graphs with  $\Theta(n^2)$  edges, the first task can be replaced by: “Compute a constant-factor approximation of a maximum independent set in  $G$ .” A series of trade-off results is also available.

**Keywords:** triangle, complete subgraph, detection problem, enumeration algorithm, approximation algorithm.

## 1 Introduction

The problem of deciding whether a given graph  $G = (V, E)$  contains a complete subgraph on  $k$  vertices is among the most natural and easily stated algorithmic graph problems. If the subgraph size  $k$  is part of the input, then the problem is clearly NP-complete as it includes in particular the CLIQUE problem. Similarly, the problem of deciding whether a given graph  $G = (V, E)$  contains a simple cycle of length  $k$  belongs to the same class of easily stated algorithmic graph problems. The similarity continues for if the cycle length  $k$  is part of the input to the latter problem, then this problem also becomes NP-complete as it includes in particular the HAMILTONIAN CYCLE problem.

---

\*AlgoResearch (algoResearch.org). Email ad.dumitrescu@gmail.com

Let  $|V| = n, |E| = m$ . For every fixed  $k$ , determining whether a given graph  $G = (V, E)$  contains a simple cycle of length  $k$  can be done in either  $O(mn)$  expected time [34] or  $O(n^\omega \log n)$  [2], where  $\omega < 2.376$  is the exponent of matrix multiplication [10]. On the other hand, for every fixed  $k$ , determining whether a given graph  $G = (V, E)$  contains a complete subgraph on  $k$  vertices can be accomplished by a brute-force algorithm running in  $O(n^k)$  time. For  $k = 3$ , deciding whether a graph contains a triangle and finding one if it does (or counting all triangles in a graph) can be done in  $O(n^\omega)$  time by the algorithm of Itai and Rodeh [23]: the algorithm compares  $M$  and  $M^2$ , where  $M$  is the graph adjacency matrix. Alternatively, this task can be done in  $O(m^{2\omega/(\omega+1)}) = O(m^{1.41})$  time by the algorithm of Alon, Yuster, and Zwick [3]. Itai and Rodeh [23] and also Papadimitriou and Yannakakis [39] as well as Chiba and Nishizeki [9] showed that triangles in planar graphs can be found in  $O(n)$  time. For  $k = 4$ , deciding whether a graph contains a  $K_4$  and finding one if it does (or counting all  $K_4$ 's in a graph) can be done in  $O(n^{\omega+1})$  time by the algorithm of Alon, Yuster, and Zwick [3], and in  $O(m^{(\omega+1)/2}) = O(m^{1.69})$  time by the algorithm of Kloks, Kratsch, and Müller [26].

In contrast to the problem of detecting the existence of subgraphs of a certain kind, the analogous problem of listing *all* such subgraphs has usually higher complexity, as expected. For example, finding all triangles in a given graph (each triangle appears in the output list) can be accomplished in  $O(m^{3/2})$  time and with  $O(n^2)$  space by an extended version of the algorithm of Itai and Rodeh [23]. Bar-Yehuda and Even [5] improved the space complexity of the algorithm from  $O(n^2)$  to  $O(n)$  by avoiding the use of the adjacency matrix. Chiba and Nishizeki [9] further refined the time complexity in terms of graph arboricity (the minimum number of edge-disjoint spanning forests into which its edges can be partitioned); their algorithm lists all triangles in a graph in  $O(m\alpha)$  time, where  $\alpha$  is the arboricity. Since there are graphs  $G$  with  $\alpha(G) = \Theta(m^{1/2})$ , this does not improve the worst-case dependence on  $m$  (which, in fact, cannot be improved). More general, for every fixed  $\ell \geq 3$ , Chiba and Nishizeki gave an algorithm for listing all copies of  $K_\ell$  in  $O(\alpha^{\ell-2} \cdot m)$  time.

We distinguish several variants of the general problem of finding triangles in a given undirected graph  $G = (V, E)$ :

1. the triangle *detection* (or *finding*) problem is that of finding a triangle in  $G$  or reporting that none exists;
2. the triangle *counting* problem is that of determining the total number of triangles in  $G$ ;
3. the triangle *listing* problem is that of listing (reporting) all triangles in  $G$ , with each triangle appearing in the output list.

Other variants (not studied here) are worth mentioning. For instance, the *edge triangle counting* problem is that of computing for every edge  $e \in E$  the number of triangles in  $G$  which contain  $e$  [12].

Obviously any algorithm for listing all triangles can be easily transformed into one for triangle detection or into one for listing a specified number of triangles (by stopping after the required number of triangles have been output). Unless specified otherwise: (i) all algorithms discussed are assumed to be deterministic; (ii) all graphs mentioned are undirected; (iii) all logarithms are in base 2.

It should be noted that the asymptotically fastest algorithms for matrix multiplication, specifically those running in, say,  $O(n^{2.5})$  time—and many are also used in this paper—have mainly a theoretical importance and are otherwise largely impractical [31, Ch. 10.2.4].

**Our results.** The following are shown for the problem of finding small subgraphs of a given size.

- (i) For every  $n, m \geq 3$ , there exists a graph  $G$  of order  $n$  with  $m$  edges that contains  $\Theta(m^{3/2})$  triangles (Lemma 2 in Section 3). This extends previous results of this kind to the entire range

of parameters  $m$  and  $n$ . As such, the dependency on  $m$  in the running time  $O(m^{3/2})$  of the algorithm of Chiba and Nishizeki (or that of the extended algorithm of Itai and Rodeh) is asymptotically tight.

- (ii) We provide a combinatorial algorithm for listing all triangles in a graph and show that is amenable to the same running time analysis, and thus runs in time  $O(m\alpha) = O(m^{3/2})$  time, where  $\alpha$  is the graph arboricity (Algorithm HYBRID in Subsection 2.1).
- (iii) For every  $n$  and  $b \leq n/2$  there exists a graph  $G$  of order  $n$  with  $m$  edges and arboricity  $\alpha \leq b$  that has  $\Omega(m\alpha)$  triangles. More generally, for every  $n$ ,  $b \leq n/2$  and a fixed  $\ell$ , there exists a graph  $G$  of order  $n$  with  $m$  edges and  $\alpha(G) \leq b$  that has  $\Omega(\alpha^{\ell-2} \cdot m)$  copies of  $K_\ell$  (Lemmas 3 and 4 in Section 3). As such, the dependency on  $m$  and  $\alpha$  in the running time  $O(m\alpha)$  of the algorithm of Chiba and Nishizeki for listing all triangles, and  $O(\alpha^{\ell-2} \cdot m)$  respectively for listing all copies of  $K_\ell$ , is asymptotically tight.
- (iv) Let  $0 < \varepsilon \leq 0.5$  and  $0 < \delta \leq 0.25$  be positive constants. Given a graph  $G = (V, E)$  with  $n$  vertices,  $m = \Omega(n^{1+3.82\delta})$  edges, and  $t = \Omega(m^{1+\delta})$  triangles, there is a randomized algorithm that computes an estimate in the interval  $[(1 - \varepsilon)t, (1 + \varepsilon)t]$  of the number of triangles in  $G$  and finds a witness with high probability in  $O(n^{\omega(1-\delta)})$  or  $O\left((mn^{-2\delta})^{\frac{2\omega}{\omega+1}}\right)$  expected time (Theorem 3 in Section 1). This implies that the validity of a lower bound for triangle detection inquired by Pătraşcu [40]—if it were to hold—is restricted to a certain range of the graph parameters  $m$  and  $t$ ; in particular,  $m$  and  $t$  cannot be too large.
- (v) Given a graph  $G = (V, E)$  with  $n$  vertices and  $m$  edges, an independent set of size  $\lceil 2m/n \rceil$  or a triangle can be found in  $O(m + n)$  time (Theorem 4 in Section 5). As a corollary: Given a graph  $G = (V, E)$ , one of the following tasks can be performed in  $O(m + n)$  time: (i) compute a  $\Omega(1/\sqrt{n})$ -approximation of a maximum independent set in  $G$ , or (ii) find a triangle in  $G$ .

**Preliminaries and notation.** Let  $G = (V, E)$  be an undirected graph. The *neighborhood* of a vertex  $v \in V$  is the set  $N(v) = \{w : (v, w) \in E\}$  of all adjacent vertices, and its cardinality  $\deg(v) = |N(v)|$  is called the *degree* of  $v$  in  $G$ .

A *clique* in a graph  $G = (V, E)$  is a subset  $C \subset V$  of vertices, each pair of which is connected by an edge in  $E$ . The CLIQUE problem is to find a clique of maximum size in  $G$ . An *independent set* of a graph  $G = (V, E)$  is a subset  $I \subset V$  of vertices such that no two of them are adjacent in  $G$ . The INDEPENDENT-SET problem is to find a maximum-size independent set in  $G$ .

Let  $E[X]$  and  $\text{Var}[X]$  denote the *expectation* and respectively, the *variance*, of a random variable  $X$ . If  $X$  and  $Y$  are random variables,  $\text{Cov}(X, Y) = E[XY] - E[X] \cdot E[Y]$  is their *covariance*. If  $E$  is an event in a probability space,  $\text{Prob}(E)$  denotes its probability. Chebyshev’s inequality (see for instance [33, p. 49]) is the following: For any  $a > 0$ ,

$$\text{Prob}(|X - E[X]| \geq a) \leq \frac{\text{Var}[X]}{a^2}. \tag{1}$$

The  $\tilde{O}$  notation used to describe the asymptotic complexity of algorithms hides polylogarithmic factors or more generally factors of the form  $n^{o(1)}$ , i.e.,  $\tilde{O}(\text{poly}(n)) = O(n^{o(1)}\text{poly}(n))$ .

**3Sum.** The 3SUM problem is to decide, given a set  $A \subset \mathbb{R}$  of size  $n$ , whether there exist  $a, b, c \in A$  such that  $a + b + c = 0$ . It was originally conjectured that 3SUM requires  $\Omega(n^2)$  time on the Real RAM [4, 19]. Grønlund and Pettie [19] gave the first algorithms for 3SUM running in subquadratic time and thereby disproved this conjecture. Specifically, they gave a deterministic algorithm that runs in  $O(n^2(\log \log n / \log n)^{2/3})$  time, and a randomized algorithm that runs in

$O(n^2(\log \log n)^2/\log n)$  expected time with high probability. Gold and Sharir [18] provided a slightly faster deterministic algorithm running in  $O(n^2 \log \log n/\log n)$  time. The revised conjecture is that 3SUM requires  $\Omega(n^{2-o(1)})$  time on the Real RAM [19]. Obtaining a specified time bound for a problem is said to be “3SUM-hard” if doing so would violate the revised conjecture above.

The 3SUM problem and its variants are quite relevant in the field of algorithm complexity. Although the 3SUM problem itself does not seem to have practical applications, it has enjoyed wide interest due to numerous problems that can be reduced from it. Thus, lower bounds on 3SUM imply lower bounds on several problems in computational geometry, dynamic graph algorithms, triangle listing, and others; see [16, 19] for an enumeration of such problems.

**Graph parameters.** For a graph  $G$ , its *arboricity*  $\alpha(G)$  is the minimum number of edge-disjoint spanning forests into which  $G$  can be decomposed [9]. For instance, it is known and easy to show that  $\alpha(K_n) = \lceil n/2 \rceil$ . A characterization of arboricity is provided by the following classic result [36, 37, 46]; see also [11, p. 60].

**Theorem 1.** (Nash-Williams 1964; Tutte 1961) *A multigraph  $G = (V, E)$  can be partitioned into at most  $k$  forests if and only if every set  $U \subseteq V$  induces at most  $k(|U| - 1)$  edges.*

The *degeneracy*  $d(G)$  of an undirected graph  $G$  is the smallest number  $d$  for which there exists an *acyclic orientation* of  $G$  in which all the out-degrees are at most  $d$ . The degeneracy of a graph is linearly related to its arboricity, i.e.,  $\alpha(G) = \Theta(d(G))$ ; more precisely  $\alpha(G) \leq d(G) \leq 2\alpha(G) - 1$ ; see [3, 14, 30, 49].

Recall that testing whether a graph contains a triangle can be done in  $O(m^{2\omega/(\omega+1)}) = O(m^{1.41})$  time by the algorithm of Alon, Yuster, and Zwick [3]. One can speculate [40] that if  $\omega = 2$  then this task can be accomplished in  $O(m^{4/3})$  time. Exploiting the connection with 3SUM, Pătraşcu obtained the following conditional lower bound (recall the meaning of “3SUM-hard”):

**Theorem 2.** [40] *In a graph with  $m$  edges, reporting  $m$  triangles in  $O(m^{4/3-\varepsilon})$  time is 3SUM-hard.*

Pătraşcu also remarked that it would be very interesting to extend the lower bound of Theorem 2 to the computationally easier case of triangle detection. From the other direction and attempting to test the limits of this question, we prove the following algorithmic result which includes triangle detection but relies on the input graph having a super-linear number of edges and triangles (the precise conditions are specified in the theorem).

**Theorem 3.** *Let  $0 < \varepsilon \leq 0.5$  and  $0 < \delta \leq 0.25$  be positive constants. Given a graph  $G = (V, E)$  with  $n$  vertices,  $m = \Omega(n^{1+3.82\delta})$  edges, and  $t = \Omega(m^{1+\delta})$  triangles, there is a randomized algorithm that finds the following with high probability:*

- (i) *an estimate in the interval  $[(1 - \varepsilon)t, (1 + \varepsilon)t]$  of the number of triangles in  $G$ .*
- (ii) *a triangle in  $G$ .*

*The expected running time of the algorithm for items (i) and (ii) is*

$$O\left(n^{\omega(1-\delta)}\right) \text{ or } O\left(\left(mn^{-2\delta}\right)^{\frac{2\omega}{\omega+1}}\right).$$

*For item (i) an additional factor of  $\varepsilon^{-2}$  is incurred.*

It is worth noting that the running time of our algorithm beats the one of the algorithm of Alon et al. for the class of graphs described in Theorem 3 for every  $\delta$ . Indeed, we have

$$mn^{-2\delta} = o(m), \text{ thus } \left(mn^{-2\delta}\right)^{\frac{2\omega}{\omega+1}} = o\left(m^{\frac{2\omega}{\omega+1}}\right).$$

Moreover, the running time of our algorithm beats the one in the conjecture even with the *current* fastest matrix multiplication algorithm for certain values of  $\delta$ . Indeed, for  $\delta \geq 0.054$  we have  $(mn^{-2\delta})^{1.41} = o(m^{4/3})$ .

## 2 Triangle finding algorithms

A summary of previous work in the area of triangle finding and enumeration appears in Section A of the appendix. We next present a new algorithm for listing all triangles. While its general idea is not new, the specific hybrid data structure use appears to not have been previously considered.

### 2.1 A hybrid algorithm for listing all triangles

We start by noting that using both an adjacency list representation and an adjacency matrix representation of the graph allows one to obtain a very time-efficient neighborhood merge (intersection) procedure. We give a short outline and include our algorithm below. Let  $V = \{1, 2, \dots, n\}$  and let  $M$  be the adjacency matrix of  $G$ . A triangle  $ijk$  with  $i < j < k$  is reported when edge  $ij$  is processed, and so each triangle is reported exactly once.

The following hybrid algorithm employs an edge-based approach for listing all triangles in  $G$ . For each edge  $ij$ , the algorithm scans the adjacency list of the endpoint of lower degree (among  $i$  and  $j$ ) and for each neighbor it checks for the needed entry in the adjacency matrix  $M$  corresponding to the third triangle edge.

HYBRID( $G$ )

**Input:** an undirected graph  $G = (V, E)$   
**1** **foreach** edge  $ij \in E, (i < j)$  **do**  
**2**     **if**  $\deg(i) \leq \deg(j)$  **then**  $x \leftarrow i, y \leftarrow j$   
**3**     **else**  $x \leftarrow j, y \leftarrow i$   
**4**     **foreach**  $k \in ADJ(x)$  **do**  
**5**         **if**  $j < k$  and  $M(y, k) = 1$  **then** report triangle  $ijk$   
**6**     **end**  
**7** **end**

There are at most  $\min(\deg(i), \deg(j))$  triangles based on edge  $ij$  and overall at most

$$\sum_{uv \in E, u < v} \min(\deg(u), \deg(v))$$

triangles in  $G$ . The runtime of the algorithm is proportional to this quantity; the space used is quadratic. A short and elegant decomposition argument by Chiba and Nishizeki [9, Lemma 2] shows that

$$\sum_{uv \in E, u < v} \min(\deg(u), \deg(v)) \leq 2m\alpha, \tag{2}$$

where  $\alpha$  is the arboricity of  $G$ . Consequently, our algorithm runs in time  $O(m\alpha)$ .

Whereas the space used is quadratic, the hybrid algorithm appears to win by running time and simplicity. In particular, no additional data structures nor hashing are used, no sorting (by degree or otherwise) and no doubly linked lists are needed, etc. It should be noted for instance that similar algorithms studied in [43, 44] that use hashing in order to run in linear space are 6 to 8 times slower than their “unoptimized” counterparts on most graphs in their study with about  $0.5 \times 10^6$  vertices. On a graph with about  $5 \times 10^6$  vertices, “the two algorithms *edge-iterator-hashed* and *forward-hashed*, which use hashed data structures for every node, perform badly” the authors write [44, p. 8].

## 2.2 The analysis

We derive a new analysis of the algorithm of Chiba and Nishizeki [9]. The analysis also applies to our hybrid algorithm. They proved that for any graph  $G$ , its arboricity is bounded from above as follows:  $\alpha(G) \leq \lceil (2m + n)^{1/2}/2 \rceil$ , which implies that  $\alpha(G) = O(m^{1/2})$  for a connected graph  $G$ . The proof relies on a classic result of Nash-Williams [36, 37] who showed that

$$\alpha(G) = \max_{H \subset G} \lceil q/(p-1) \rceil, \quad (3)$$

where  $H$  runs over all nontrivial subgraphs of  $G$ ,  $p$  is the number of vertices and  $q$  is the number of edges of  $H$ .

Chiba and Nishizeki [9] gave a combinatorial algorithm running in  $O(m\alpha(G))$  time for listing all triangles in an arbitrary graph  $G$  with  $n$  vertices and  $m$  edges. By the upper bound on  $\alpha(G)$  mentioned above, their algorithm runs in  $O(m^{3/2})$  time on any graph. If  $G$  is planar,  $\alpha(G) \leq 3$  (see [20, p. 124]), so the algorithm runs in  $O(m)$  (i.e., linear) time on planar graphs.

Define the following function on edges of  $G$ . For  $uv = e \in E$ , let

$$f(e) = \min(\deg(u), \deg(v)) \text{ and } F(G) = \sum_{uv \in E, u < v} f(e). \quad (4)$$

Our next goal here is to bypass the Nash-Williams arboricity bound and derive the inequality  $F(G) = O(m^{3/2})$  from first principles and thereby obtain  $O(m^{3/2})$  as an upper bound on the worst-case running time of our algorithm for listing all triangles in a graph. (Recall that  $F(G) \leq 2m\alpha$  by (2).)

**Lemma 1.** *Let  $G$  be a graph on  $n$  vertices with  $m$  edges. Then*

$$F(G) = O(m^{3/2}).$$

*Proof.* (folklore) There are two types of edges  $uv$ :

1.  $\min(\deg(u), \deg(v)) \leq 2\sqrt{m}$
2.  $\min(\deg(u), \deg(v)) > 2\sqrt{m}$

Since there are at most  $m$  edges of type 1 and each contributes at most  $2\sqrt{m}$  to the sum in  $F(G)$ , the total contribution from edges of this type is at most  $2m^{3/2}$ .

Each edge of type 2 connects two nodes of degree  $> 2\sqrt{m}$ , and there are at most  $2m/(2\sqrt{m}) = \sqrt{m}$  such nodes. The degree of each of them thus contributes at most  $\sqrt{m}$  times and the sum of all degrees of such nodes is at most  $2m$ . It follows that the total contribution from edges of type 2 to the sum in  $F(G)$  is at most  $2m^{3/2}$ .

Overall, we have  $F(G) \leq 4m^{3/2}$ . □

**Remarks.** Lemma 1 immediately gives the same upper bound,  $4m^{3/2}$  on the number of triangles in a graph. It is in fact known [42] that this number is at most  $(2^{1/2}/3)m^{3/2}$  (and this bound is sharp). More generally, for every fixed  $\ell \geq 3$ , the number of copies of  $K_\ell$  is at most  $O(\alpha^{\ell-2} \cdot m)$ ; as it follows from [9].

### 3 Constructions

**Lemma 2.** *For every  $n \geq 3$  and  $3 \leq m \leq \binom{n}{2}$ , there exists a graph  $G$  of order  $n$  with  $m$  edges that contains  $\Theta(m^{3/2})$  triangles.*

*Proof.* Let  $x = \sqrt{2m}$ ; we may assume that  $x$  is an integer. Since  $m \leq \binom{n}{2}$ , we have  $x \leq n - 1$ . Let  $G = (V, E)$  where  $V = V_1 \cup V_2$ ,  $|V_1| = x$ , and  $|V_2| = n - x$ ; Set  $V_1$  makes a complete subgraph and set  $V_2$  is an independent set in  $G$ . A number of  $m - \binom{x}{2} \leq |V_1| \cdot |V_2|$  edges are added arbitrarily to connect vertices in  $V_1$  to vertices in  $V_2$ , whence  $G$  has  $m$  edges. (The inequality  $m - \binom{x}{2} \leq x(n - x)$  needed for verifying the validity of the construction reduces to  $x \leq n - \frac{1}{2}$ , which is satisfied by the choice of  $x$ .) Let  $T$  be the set of triangles in  $G$ . We have

$$|T| \geq \binom{x}{3} = \Theta(m^{3/2}),$$

as required. □

**Lemma 3.** *For every  $n$  and  $b \leq n/2$ , there exists a graph  $G$  of order  $n$  with  $\alpha \leq b$  that has  $\Theta(m\alpha)$  triangles, where  $m$  is the number of edges in  $G$  and  $\alpha$  is the arboricity of  $G$ .*

*Proof.* We may assume that  $b$  is even and  $b/2 \mid n$ , thus  $n = (2k + 1)b/2$ . Let  $G = (V, E)$  where  $V = V_1 \cup V_2$ , and  $|V_1| = kb$ ,  $|V_2| = b/2$ . Set  $V_1$  consists of  $k$  complete subgraphs of order  $b$  whereas  $V_2$  is an independent set of size  $b/2$  in  $G$ . All edges in  $V_1 \times V_2$  are present in  $G$ . See Fig. 1.




Figure 1: Illustration of the graph  $G$  for  $k = 3$ ,  $b = 4$ .

Let  $T$  be the set of triangles in  $G$ . We have

$$m = |E| = k \binom{b}{2} + k \frac{b^2}{2} = \Theta(kb^2),$$

$$|T| = k \binom{b}{3} + k \binom{b}{2} \frac{b}{2} = \Omega(kb^3) = \Omega(bm).$$

Note that the arboricity of  $G$  is bounded from above by  $b$ . Indeed,  $\alpha \leq \frac{b}{2} + \frac{b}{2} = b$ , since  $\alpha(K_b) = b/2$  and the edges in  $V_1 \times V_2$  can be partitioned into  $b/2$  stars centered at the vertices in  $V_2$ . □

Lemma 3 generalizes to complete subgraphs of any fixed size.

**Lemma 4.** *Let  $\ell \in \mathbb{N}$  be fixed. For every  $n$  and  $b \leq n/2$ , there exists a graph  $G$  of order  $n$  with  $\alpha \leq b$  that has  $\Omega(\alpha^{\ell-2} \cdot m)$  copies of  $K_\ell$ , where  $m$  is the number of edges in  $G$  and  $\alpha$  is the arboricity of  $G$ .*

*Proof.* We use the same construction from the proof of Lemma 3. Let  $K$  be the set of complete subgraphs of order  $\ell$ . We have

$$m = |E| = k \binom{b}{2} + k \frac{b^2}{2} = \Theta(k b^2),$$

$$|K| = k \binom{b}{\ell} + k \binom{b}{\ell-1} \frac{b}{2} = \Omega(k b^\ell) = \Omega(b^{\ell-2} m),$$

as required. □

## 4 Approximate counting and triangle detection

In this section we outline a randomized algorithm for approximately counting the triangles in  $G$  and thereby prove Theorem 3. The algorithm provides an estimate that is in the interval  $[(1-\varepsilon)t, (1+\varepsilon)t]$ , where  $t$  is the number of triangles in  $G$  and  $\varepsilon > 0$  is a given constant. In particular the algorithm can provide a constant factor-approximation. The algorithm is very simple and natural, however, it does not appear to have been considered and analyzed previously. The algorithm calls for an exact count in the graph induced by a small sample of vertices, as given by the algorithm of Itai and Rodeh [23] or by the algorithm of Alon, Yuster, and Zwick [3]. Recall that these algorithms run in  $O(n^\omega) = O(n^{2.376})$  time and  $O(m^{2\omega/(\omega+1)}) = O(m^{1.41})$  time, respectively, on input graphs with  $n$  vertices and  $m$  edges. We refer to any of these algorithms as EXACT-COUNT( $G$ ).

APPROX-COUNT( $G$ )

**Input:** an undirected graph  $G = (V, E)$  and  $0 < \delta \leq 0.25$

**Output:** a  $(1 \pm \varepsilon)$ -approximation of the number of triangles in  $G$

- 1 Extract a random vertex sample  $U \subset V$  by retaining each vertex with probability  $p = n^{-\delta}$
- 2 Let  $Z$  be the number of triangles in the induced graph  $G[U]$  obtained by the algorithm EXACT-COUNT
- 3 **return**  $Zn^{3\delta}$  and halt

**Analysis (sketch).** An analysis of a similar nature (using Chebyshev's inequality and the second moment method for studying the threshold behavior in random graphs) can be found in [33, Ch. 6.5]. Let  $t$  denote the number of triangles in  $G$ . Let  $X = |U|$  (the size of  $U$ ). Let  $Y$  and  $Z$  be the random variables denoting the number of edges and triangles that survive in  $G[U]$ .

By the linearity of expectation, we have

$$\mathbb{E}[X] = np = n^{1-\delta}, \tag{5}$$

$$\mathbb{E}[Y] = mp^2 = mn^{-2\delta}, \tag{6}$$

$$\mathbb{E}[Z] = tp^3 = tn^{-3\delta}. \tag{7}$$

The third equality yields  $\mathbb{E}[Zn^{3\delta}] = n^{3\delta} \cdot \mathbb{E}[Z] = t$ , as intended ( $t$  is the desired output).

The expectations  $\mathbb{E}[X]$ ,  $\mathbb{E}[Y]$  and  $\mathbb{E}[Z]$  are used for determining the expected running times  $\mathbb{E}[X^\omega]$  and  $\mathbb{E}\left[Y^{\frac{2\omega}{\omega+1}}\right]$  and the approximation factor. Deviation inequalities are used throughout the proof. Due to space constraints the detailed analysis of algorithm APPROX-COUNT appears in Appendix B.



## 5 Triangles or independent sets

Recall the INDEPENDENT-SET problem mentioned in the introduction. As the dual of CLIQUE, the problem is known to be NP-complete [24]. Any clique  $C$  in  $G$  is an independent set of the same size in  $\overline{G}$ , the *complement* of  $G$  and vice versa. As such, any approximation algorithm for one of these problems can be converted to an approximation algorithm with the same approximation ratio for the other problem by simply running it on the complement graph [47, Ch. 10.2]. The CLIQUE problem is also hard to approximate. First, there is no constant approximation algorithm for CLIQUE unless  $P=NP$  [47, p. 421]. Further, according to an old result of Håstad [21], for every positive constant  $\varepsilon > 0$ , it is NP-hard to approximate CLIQUE to within  $n^{1/2-\varepsilon}$ . This result was strengthened by Zuckerman [50] who proved that it is NP-hard to approximate CLIQUE to within  $n^{1-\varepsilon}$ . The same results hold for INDEPENDENT-SET. The best approximation algorithm known achieves an approximation ratio of  $O(n/\log^2 n)$  [7]; see also [35]. The current best exact algorithm runs in exponential time [48].

According to a celebrated theorem of Turán [45], every graph of order  $n$  and average degree  $\delta$  contains an independent set of size at least  $n/(\delta+1)$ . As such, sparse graphs have large independent sets. A constructive proof of Turán’s Theorem given by Erdős yields a linear-time greedy algorithm—included below—for finding an independent set of this size; see for instance [22, p. 118]. Note that if  $G$  is dense, i.e., it has  $\Theta(n^2)$  edges, then  $\delta = \Omega(n)$ , the independent set size guaranteed by the  $n/(\delta+1)$  bound is only  $O(1)$  and computing a constant-factor approximation is ruled out unless  $P=NP$ .

INDEPENDENT-SET( $G$ )

**Input:** an undirected graph  $G = (V, E)$

- 1 Set  $I \leftarrow \emptyset$
- 2 If  $G$  is empty then stop; otherwise choose a vertex  $v$  of minimum degree in the current graph
- 3 Add  $v$  to  $I$ , delete  $v$  and all its neighbors (along with all edges incident to at least one of these vertices) from  $G$  and go to Step 2

Shifting now to the triangle detection problem, it is obviously solvable in polynomial time by a brute force algorithm running in  $O(n^3)$  time (or by any of the faster algorithms discussed previously). The currently fastest algorithm, due to Alon, Yuster, and Zwick [3], finds a triangle in a given graph—if one exists—in  $O(n^\omega)$  time or in  $O(m^{2\omega/(\omega+1)}) = O(m^{1.41})$  time.

However, due to its importance as a natural and easily stated algorithmic graph problem, the triangle detection problem along with its many variants (listing all triangles, or listing only a prescribed number of them, or counting the triangles) has received lots of attention starting in the 1980s and more recently in the perspective of developing lower bounds for dynamic problems. A plethora of recent results have focused on understanding the relation between TRIANGLE DETECTION and TRIANGLE LISTING and especially on separating the one-time cost (in terms of  $m$  and  $\alpha(G)$  for example) from the per-triangle cost (in terms of the number of triangles  $t$ ) [12, 29].

A specific relevant question was posed by Kopelowitz et al. [29]: Is the  $m\alpha(G)$  time necessary for reasons other than worst case output considerations? The authors partially answered this question affirmatively [29, Theorem 1.9].

Oddly enough, if one allows the algorithm the freedom to decide whether to find a large independent set *or* a triangle, then there exists a very simple and fast deterministic algorithm. The results are summarized in Theorem 4 and Corollary 1.

**Theorem 4.** *Given a graph  $G = (V, E)$  with  $n$  vertices and  $m$  edges, an independent set of size  $\lfloor 2m/n \rfloor$  or a triangle can be found in  $O(m+n)$  time.*

It is worth noting that the size of the independent set found by the algorithm in Theorem 4 grows inversely proportionally with the size of the independent set found by the greedy algorithm. In particular,

- If  $m = \Theta(n^2)$ , an independent set of size  $\Omega(n)$  or a triangle can be found in  $O(m+n)$  time. If an independent set is returned, it is notably a constant-factor approximation; indeed,  $\text{OPT} \leq n$ . In contrast, the greedy algorithm is guaranteed only a set of size  $O(1)$ !
- If  $m = \Theta(dn)$ , an independent set of size  $\Omega(d)$  or a triangle can be found in  $O(m+n)$  time. In contrast, the greedy algorithm finds a set of size  $\Omega(n/d)$ .

*Proof.* (of Theorem 4). Let  $v$  be a vertex of maximum degree in  $G$  and let  $\Gamma(v)$  be its neighborhood. Since the average degree in  $G$  is  $2m/n$ , we have  $|\Gamma(v)| \geq \lceil 2m/n \rceil$ . Arbitrarily retain a subset  $U \subset \Gamma(v)$  of this size:  $|U| = \lceil 2m/n \rceil$ . If  $U$  is an independent set we are done; in the other case we are also done since a triangle incident to  $v$  has been found: if, say,  $x, y \in U$  and  $xy \in E$ , then  $\langle v, x, y \rangle$  is a triangle in  $G$ . Assuming that the adjacency matrix of  $G$  is used, the independent set test takes

$$O(|U|^2 + m + n) = O(m^2/n^2 + m + n) = O(m + n) \quad (8)$$

time, as required.  $\square$

**Corollary 1.** *Given a graph  $G = (V, E)$ , one of the following tasks can be performed in  $O(m+n)$  time: (i) compute a  $\Omega(1/\sqrt{n})$ -approximation of a maximum independent set in  $G$ , or (ii) find a triangle in  $G$ .*

*Proof.* Let  $G$  be a graph of order  $n$ . Since a largest independent set has size at most  $n$ , finding an independent set of size  $\Omega(\sqrt{n})$  achieves the first objective. If the average degree is at most  $\sqrt{n}$  the greedy algorithm  $\text{INDEPENDENT-SET}(G)$  yields an independent set of size about  $\sqrt{n}$  thereby achieving the first objective. If the average degree is at least  $\sqrt{n}$ , let  $v$  be a vertex of maximum degree. Arbitrarily retain a subset  $U \subset \Gamma(v)$  of this size:  $|U| = \lceil \sqrt{n} \rceil$ . If  $U$  is an independent set the first objective has been achieved. In the other case a triangle incident to  $v$  has been found and the second objective has been achieved.  $\square$

**Remarks.**  $\text{INDEPENDENT-SET}$  remains NP-complete for triangle-free graphs [41]; see also [24, p. 194–195]. The argument in the proof of Theorem 4 is reminiscent of arguments used in coloring triangle-free graphs. Let  $G$  be a triangle-free graph of order  $n$ . By repeatedly removing independent sets of size about  $\sqrt{n}$  yields an efficient algorithm for coloring  $G$  with  $O(\sqrt{n})$  colors. Consequently,  $\chi(G) = O(\sqrt{n})$ . A slightly larger independent set is implied from results of Ajtai, Komlós and Szemerédi [1], who showed that if  $G$  is a triangle-free graph of order  $n$ , then  $G$  contains an independent set of size  $\Omega(\sqrt{n \log n})$ . Consequently,  $\chi(G) = O(\sqrt{n/\log n})$ . Apart from the constant factor, this bound is the best possible (by a celebrated result of Kim [25]). See also [17] for a perspective on these results.

## 6 Concluding remarks

Kolountzakis et al. [27] gave a randomized algorithm that computes a  $(1 \pm \varepsilon)$ -approximation of the number of triangles in a graph in  $O\left(m + \frac{m^{3/2} \Delta \log n}{t \varepsilon^2}\right)$  expected time, where  $\Delta < n$  is the maximum number of triangles in which any single edge is contained. Recently, Eden et al. [13] gave a randomized algorithm that computes a  $(1 \pm \varepsilon)$ -approximation of the number of triangles in

a graph in  $O\left(\frac{n}{t^{1/3}} + \frac{m^{3/2}}{t}\right) \cdot \text{poly}(\log n, 1/\varepsilon)$  expected time. It would be interesting to know if these algorithms can be adapted for finding a triangle in the graph and what are the corresponding running times vis-à-vis Pătraşcu’s question regarding triangle detection mentioned in the introduction.

**Acknowledgment.** The author thanks an anonymous reviewer for communicating the short folklore proof of Lemma 1 which now replaces a previous lengthier argument.

## References

- [1] M. Ajtai, J. Komlós, and E. Szemerédi, A note on Ramsey numbers, *Journal of Combinatorial Theory Ser. A* **29** (1980), 354–360.
- [2] N. Alon, R. Yuster, and U. Zwick, Color-coding, *Journal of the ACM* **42** (1995), 844–856.
- [3] N. Alon, R. Yuster, and U. Zwick, Finding and counting given length cycles, *Algorithmica* **17(3)** (1997), 209–223.
- [4] I. Baran, E. D. Demaine, and M. Pătraşcu, Subquadratic algorithms for 3SUM, *Algorithmica* **50(4)** (2008), 584–596.
- [5] R. Bar-Yehuda and S. Even, On approximating a vertex cover for planar graphs, *Proc. 14th Annual ACM Symposium on Theory of Computing (STOC)*, San Francisco, 1982, pp. 303–309.
- [6] A. Björklund, R. Pagh, V. V. Williams, and U. Zwick, Listing triangles, *Proc. 41st International Colloquium on Automata, Languages, and Programming (ICALP)*, Copenhagen, 2014, Springer, vol. 8572 of LNCS, pp. 223–234.
- [7] R. B. Boppana and M. M. Halldórsson, Approximating maximum independent sets by excluding subgraphs, *BIT Comput. Sci. Sect.* **32(2)** (1992), 180–196.
- [8] D. de Caen, An upper bound on the sum of squares of degrees in a graph, *Discrete Mathematics* **185(1-3)** (1998), 245–248.
- [9] N. Chiba and T. Nishizeki, Arboricity and subgraph listing algorithms, *SIAM Journal on Computing* **14(1)** (1985), 210–223.
- [10] D. Coppersmith and S. Winograd, Matrix multiplication via arithmetic progressions, *J. Symb. Comput.* **9(3)** (1990), 251–280.
- [11] R. Diestel, *Graph Theory*, Springer, New York, 1997.
- [12] L. Duraj, K. Kleiner, A. Polak, and V. V. Williams, Equivalences between triangle and range query problems, *Proc. 2020 ACM-SIAM Symposium on Discrete Algorithms (SODA)*, Salt Lake City, UT, SIAM 2020, pp. 30–47; [arXiv:1908.11819](https://arxiv.org/abs/1908.11819).
- [13] T. Eden, A. Levi, D. Ron, and C. Seshadhri, Approximately counting triangles in sublinear time, *SIAM J. Comput.* **46(5)** (2017), 1603–1646.
- [14] D. Eppstein, Arboricity and bipartite subgraph listing algorithms, *Inf. Process. Lett.* **51(4)** (1994), 207–211.
- [15] D. Eppstein, M. T. Goodrich, M. Mitzenmacher, and M. R. Torres, 2-3 cuckoo filters for faster triangle listing and set intersection, *Proc. 36th ACM SIGMOD-SIGACT-SIGAI Symposium on Principles of Database Systems, PODS*, Chicago, IL, 2017, pp. 247–260.

- [16] A. Gajentaan and M. H. Overmars, On a class of  $O(n^2)$  problems in computational geometry, *Comput. Geom.* **45(4)** (2012), 140–152.
- [17] J. Gimbel and C. Thomassen, Coloring triangle-free graphs with fixed size, *Discrete Mathematics* **219(1-3)** (2000), 275–277.
- [18] O. Gold and M. Sharir, Improved bounds for 3SUM,  $k$ -SUM, and linear degeneracy, *Proc. 25th Annual European Symposium on Algorithms, ESA 2017*, LIPIcs, volume 87, pp. 42:1–42:13. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, <https://doi.org/10.4230/LIPIcs.ESA.2017.42>.
- [19] A. Grønlund and S. Pettie, Threesomes, degenerates, and love triangles, *Journal of ACM* **65(4)** (2018), 22:1–22:25.
- [20] F. Harary, *Graph Theory*, revised, Addison–Wesley, Reading, Massachusetts, 1972.
- [21] J. Håstad, Clique is hard to approximate within  $n^{1-\epsilon}$ , *Acta Mathematica* **182** (1999), 105–142.
- [22] D. Hochbaum, Approximating covering and packing problems: set cover, vertex cover, independent set, and related problems, in *Approximation Algorithms for NP-Hard Problems* (D. S. Hochbaum, editor), 1997, PWS Publishing Co., pp. 94–143.
- [23] A. Itai and M. Rodeh, Finding a minimum circuit in a graph, *SIAM Journal on Computing* **7(4)** (1978), 413–423.
- [24] Michael R. Garey and David S. Johnson, *Computers and Intractability: A Guide to the Theory of NP-Completeness*, W.H. Freeman and Co., New York, 1979.
- [25] J. H. Kim, The Ramsey number  $R(3, t)$  has order of magnitude  $t^2/\log t$ , *Random Structures and Algorithms* **7** (1995), 173–207.
- [26] T. Kloks, D. Kratsch, and H. Müller, Finding and counting small induced subgraphs efficiently, *Information Processing Letters* **74(3-4)** (2000), 115–121.
- [27] M. Kolountzakis, G. Miller, R. Peng, and C. Tsourakakis, Efficient triangle counting in large graphs via degree-based vertex partitioning, *Internet Mathematics* **8(1-2)** (2012), 161–185.
- [28] T. Kopelowitz, S. Pettie, and E. Porat, Dynamic set intersection, *Proc. 14th International Symposium on Algorithms and Data Structures, WADS 2015*, Victoria, BC, Canada, 2015, Springer, vol. 9214 of LNCS, pp. 470–481.
- [29] T. Kopelowitz, S. Pettie, and E. Porat, Higher lower bounds from the 3SUM conjecture, *Proc. 27th Annual ACM-SIAM Symposium on Discrete Algorithms, SODA 2016*, Arlington, VA, 2016, pp. 1272–1287.
- [30] D. R. Lick and A. T. White,  $k$ -degenerate graphs, *Canadian Journal of Mathematics* **22(5)** (1970), 1082–1096.
- [31] U. Manber, *Introduction to Algorithms - A Creative Approach*, Addison-Wesley, Reading, Massachusetts, 1989.
- [32] J. Matoušek, *Thirty-three Miniatures*, American Mathematical Society, 2010.
- [33] M. Mitzenmacher and E. Upfal, *Probability and Computing: Randomized Algorithms and Probabilistic Analysis*, 2nd edition, Cambridge University Press, 2017.

- [34] B. Monien, How to find long paths efficiently, *Annals of Discrete Mathematics* **25** (1985), 239–254.
- [35] R. Motwani, J. Naor, and P. Raghavan, Randomized approximation algorithms in combinatorial optimization, in *Approximation Algorithms for NP-Hard Problems* (D. S. Hochbaum, editor), 1997, PWS Publishing Co., pp. 447–481.
- [36] C. St. J. A. Nash-Williams, Edge-disjoint spanning trees of finite graphs, *Journal of the London Mathematical Society* **36** (1961), 445–450.
- [37] C. St. J. A. Nash-Williams, Decomposition of finite graphs into forests, *Journal of the London Mathematical Society* **1(1)** (1964), 12–12.
- [38] M. Ortmann and U. Brandes, Triangle listing algorithms: back from the diversion, *Proc. 16th Workshop on Algorithm Engineering and Experiments, ALENEX 2014*, Portland, Oregon, 2014, pp. 1–8.
- [39] C. H. Papadimitriou and M. Yannakakis, The clique problem for planar graphs, *Information Processing Letters* **13(4/5)** (1981), 131–133.
- [40] M. Pătraşcu, Towards polynomial lower bounds for dynamic problems, *Proceedings 42nd ACM Symposium on Theory of Computing, (STOC)*, Cambridge, Massachusetts, 2010, pp. 603–610.
- [41] S. Poljak, A note on stable sets and colorings of graphs, *Commentationes Mathematicae Universitatis Carolinae* **15(2)** (1974), 307–309.
- [42] I. Rivin, Counting cycles and finite dimensional  $L^p$  norms, *Advances in Applied Mathematics* **29(4)** (2002), 647–662.
- [43] T. Schank, *Algorithmic Aspects of Triangle-Based Networks Analysis*, PhD thesis, Universität Fridericiana zu Karlsruhe (TH), 2007.
- [44] T. Schank and D. Wagner, Finding, counting and listing all triangles in large graphs, an experimental study, 35 pages. A short version in *Proc. 4th International Workshop on Experimental and Efficient Algorithms, (WEA)*, Santorini Island, Greece, Springer, vol. 3503 of LNCS, 2005, pp. 606–609.
- [45] P. Turán, On an external problem in graph theory, *Mat. Fiz. Lapok* **48** (1941), 436–452.
- [46] W. Tutte, On the problem of decomposing a graph into  $n$  connected factors, *Journal of the London Mathematical Society* **36** (1961), 221–230.
- [47] D. P. Williamson and D. B. Shmoys, *The Design of Approximation Algorithms*, Cambridge University Press, 2011.
- [48] G. J. Woeginger, Open problems around exact algorithms, *Discret. Appl. Math.* **156(3)** (2008), 397–405.
- [49] X. Zhou and T. Nishizeki, Edge-coloring and  $f$ -coloring for various classes of graphs, *J. Graph Algorithms Appl.* **3(1)** (1999), 1–18.
- [50] D. Zuckerman, Linear degree extractors and the inapproximability of Max Clique and Chromatic Number, *Theory of Computing* **3(1)** (2007), 103–128.

## A Previous algorithms for triangle counting and enumeration

### A.1 Early algorithms

**The algorithms of Itai and Rodeh (1978).** The authors presented three methods for finding triangles. Initially intended for triangle detection (i.e., finding a triangle in the graph if there is one), the first algorithm [23] runs in  $O(m^{3/2})$  time. The algorithm can be extended to list all triangles within the same  $O(m^{3/2})$  overall time and works as follows:

ITAI-RODEH( $G$ )

**Input:** an undirected graph  $G = (V, E)$

- 1 Find a spanning tree for each connected component of  $G$
- 2 List all triangles containing at least one tree edge
- 3 Delete the tree edges from  $G$  and go to Step 1

The second is a randomized algorithm that checks whether there is an edge contained in a triangle. It runs in  $O(mn)$  worst-case time and  $O(n^{5/3})$  expected time. The third algorithm relies on Boolean matrix multiplication and runs in  $O(n^\omega)$  time. (Boolean matrix multiplication can be reduced to standard matrix multiplication; see [31, Ch. 10.2.4] for details.) See [32, Ch. 10] for a short exposition of this elegant method.

**The algorithm of Chiba and Nishizeki (1985).** The algorithm of Chiba and Nishizeki [9] uses a vertex-iterator approach for listing all triangles in  $G$ . It relies on the observation that each triangle containing a vertex  $v$  corresponds to an edge joining two neighbors of  $v$ . The authors propose to represent the graph with doubly-linked adjacency lists and mutual references between the two stubs of an edge to ensure that each deletion takes constant time. Here we include a more compact version as described by Ortmann and Brandes [38], who also developed an improved version that avoids double linkage and vertex deletion altogether.

CHIBA-NISHIZEKI( $G$ )

**Input:** an undirected graph  $G = (V, E)$

- 1 Sort vertices such that  $\deg(v_1) \geq \deg(v_2) \geq \dots \geq \deg(v_n)$
- 2 **for**  $u = v_1, v_2, \dots, v_{n-2}$  **do**
- 3     **foreach** vertex  $v \in N(u)$  **do** mark  $v$
- 4     **foreach** vertex  $v \in N(u)$  **do**
- 5         **foreach** vertex  $w \in N(v)$  **do**
- 6             **if**  $w$  is marked **then** output triangle  $uvw$
- 7         **end**
- 8         unmark  $v$
- 9     **end**
- 10     $G \leftarrow G - u$
- 11 **end**

Chiba and Nishizeki [9] showed that their algorithm runs in  $O(m\alpha)$  time and also that  $\alpha = O(\sqrt{m})$ ; consequently, the running time is  $O(m^{3/2})$ , which is tight in the worst case. Since their algorithm lists all triangles in time  $O(m^{3/2})$ , the following combinatorial bound is implied.

**Corollary 2.** ([23, 9]) *For any graph  $G$  of order  $n$  with  $m$  edges and arboricity  $\alpha$ ,  $G$  contains  $O(m\alpha) = O(m^{3/2})$  triangles.*

It is very likely that the  $O(m^{3/2})$  upper bound on the number of triangles in a graph is much older than these references indicate. In any case, other proofs are worth mentioning [13, 27], including algebraic ones [42]. We provide yet another one in Subsection 2.1.

Ortmann and Brandes [38] gave a survey of other approaches, including edge-iterators. Algorithms in this category iterate over all edges and intersect the neighborhoods of the endpoints of each edge. We refer the interested reader to the references therein. A straightforward neighborhood merge requires  $O(\deg(u) + \deg(v))$  time per edge  $uv$ ; however, this is not good enough to list all triangles in  $O(m^{3/2})$  time. Two variants developed by Shanks [43] use  $O(m)$  extra space to represent neighborhoods in hash sets and obtain the intersection in  $O(\min(\deg(u), \deg(v)))$  time; and this suffices for listing all triangles in  $O(m^{3/2})$  time.

**The algorithm of Alon, Yuster and Zwick (1997).** The authors showed that deciding whether a graph contains a triangle and finding one if it does (or counting all triangles in a graph) can be done in  $O(m^{2\omega/(\omega+1)}) = O(m^{1.41})$  time [3]. The idea is to find separately triangles for which at least one vertex has low degree (for an appropriately set threshold) and triangles whose all three vertices have high degree. Triangles of the latter type are handled using matrix multiplication in a smaller subgraph. The edge triangle counting problem mentioned in Section 1 can be also solved within the same time by the above algorithm.

## A.2 Recent algorithms

Recently Björklund et al. [6] have obtained output-sensitive algorithms for finding (and listing) all triangles in a graph. Their algorithms are tailored for dense and sparse graphs. The corresponding running times are

$$\tilde{O}(n^\omega + n^{3(\omega-1)/(5-\omega)}t^{2(3-\omega)/(5-\omega)}) \text{ and } \tilde{O}(m^{3(\omega-1)/(5-\omega)}t^{(3-\omega)/(5-\omega)}), \quad (9)$$

respectively. For  $t \sim m^{3/2}$  the latter bound becomes  $\tilde{O}(m^{3/2})$  and is therefore larger than the  $O(m^{3/2})$  bound by a  $n^{o(1)}$  factor. As such, the worst-case running time of  $O(m^{3/2})$  of the algorithms in Section 2 is still the best for general graphs in terms of  $m$ . If a graph contains  $T$  triangles and it is required to only list  $t$  of them, Björklund et al. [6] gave an algorithm running in time

$$\tilde{O}\left(n^\omega + \left(\left(\frac{t}{T}\right)^{1/3} n\right)^{3(\omega-1)/(5-\omega)} t^{2(3-\omega)/(5-\omega)}\right). \quad (10)$$

As such, the time taken by their algorithm for triangle detection ( $t = 1$ ) does not beat  $O(n^\omega)$ .

Several recent approaches provide asymptotic improvements by taking advantage of the bit-level parallelism offered by the word-RAM model. Although they do not appear to be very practical, these methods asymptotically improve on the  $O(m\alpha + k)$  running time of the earlier algorithms (in particular that in [9]) as follows.

Kopelowitz et al [28] introduced a dynamic set intersection data structure and used it to list the triangles in a graph  $G$  in  $O(m(\alpha \log^2 w/w + \log w) + k)$  expected time in the word-RAM (a.k.a. practical RAM) model. Here  $w$  is the number of bits in a machine word.

Given a connected graph  $G$  with arboricity  $\alpha$  and  $k$  triangles, Eppstein et al. [15] used 2-3 cuckoo filters and hash tables to list all triangles in  $O(\alpha m \log w/w + k)$  expected time in the word-RAM model.

## B Analysis of Algorithm Approx-Count

We first estimate the running time. Let  $\mu_X = \mathbb{E}[X] = n^{1-\delta}$ . By Chernoff bounds on the sum of Bernoulli trials [33, Thm. 4.4] and taking (5) into account, we have

$$\text{Prob}(X \geq 6\mu_X) = \text{Prob}(X \geq 6n^{1-\delta}) \leq 2^{-6n^{1-\delta}} \leq 2^{-n^{3/4}}. \quad (11)$$

This yields

$$\begin{aligned} \mathbb{E}[X^\omega] &\leq \text{Prob}(X \leq 6\mu_X) \cdot (6\mu_X)^\omega + \text{Prob}(X \geq 6\mu_X) \cdot n^\omega \\ &\leq \left(6n^{1-\delta}\right)^\omega + 2^{-n^{3/4}} n^\omega = O\left(n^{\omega(1-\delta)}\right). \end{aligned}$$

For  $i = 1, \dots, m$ , define the indicator random variables  $Y_i$  by

$$Y_i = \begin{cases} 1 & \text{if edge } i \text{ appears in } G[U] \\ 0 & \text{else.} \end{cases}$$

We have  $\mathbb{E}[Y_i] = p^2$ . Then  $Y = \sum_{i=1}^m Y_i$ . Note that the variables  $Y_i$  are (in general) not independent. The variance of  $Y$  is given by

$$\text{Var}[Y] = \text{Var}\left[\sum_{i=1}^m Y_i\right] = \sum_{i=1}^m \text{Var}[Y_i] + 2 \sum_{i < j} \text{Cov}(Y_i, Y_j). \quad (12)$$

We have

$$\text{Var}[Y_i] = \mathbb{E}[Y_i] - (\mathbb{E}[Y_i])^2 \leq \mathbb{E}[Y_i] = p^2,$$

and

$$\begin{aligned} \text{Cov}(Y_i, Y_j) &= \mathbb{E}[Y_i Y_j] - \mathbb{E}[Y_i] \mathbb{E}[Y_j] \\ &= \begin{cases} 0 & \text{if the two edges have no vertex in common,} \\ p^3 - p^4 & \text{if the two edges have a vertex in common.} \end{cases} \end{aligned}$$

The number of pairs of edges having a common vertex is (see for instance [8]):  $\sum_{v \in V} \binom{\deg(v)}{2} \leq mn$ . This implies

$$\sum_{i < j} \text{Cov}(Y_i, Y_j) \leq mmp^3, \text{ thus } \text{Var}[Y] \leq mp^2 + 2mnp^3.$$

Let  $\mu_Y = \mathbb{E}[Y] = mn^{-2\delta}$ . Taking (6) into account and applying Chebyshev's inequality (1) to  $Y$  yields

$$\text{Prob}(|Y - \mu_Y| \geq \mu_Y) \leq \frac{\text{Var}[Y]}{\mu_Y^2} \leq \frac{mp^2 + 2mnp^3}{m^2 p^4} = \frac{1 + 2np}{mp^2} = O\left(\frac{n^{1+\delta}}{m}\right).$$

Consequently we obtain

$$\begin{aligned} \mathbb{E}\left[Y^{\frac{2\omega}{\omega+1}}\right] &\leq \text{Prob}(Y \leq 2\mu_Y) \cdot (2\mu_Y)^{\frac{2\omega}{\omega+1}} + \text{Prob}(Y \geq 2\mu_Y) \cdot m^{\frac{2\omega}{\omega+1}} \\ &= O\left(\left(mn^{-2\delta}\right)^{\frac{2\omega}{\omega+1}} + \frac{n^{1+\delta}}{m} \cdot m^{\frac{2\omega}{\omega+1}}\right) = O\left(\left(mn^{-2\delta}\right)^{\frac{2\omega}{\omega+1}}\right), \end{aligned}$$



where in the last step we have used the inequality

$$n^{1+(1+\frac{4\omega}{\omega+1})\delta} \leq n^{1+3.82\delta} = O(m).$$

It follows that the expected running time is

$$O\left(n^{\omega(1-\delta)}\right) \text{ or } O\left(\left(mn^{-2\delta}\right)^{\frac{2\omega}{\omega+1}}\right).$$

We next analyze the approximation factor. Arbitrarily label the triangles in  $G$  by  $1, 2, \dots, t$ . For  $i = 1, \dots, t$ , define the indicator random variables  $Z_i$  by

$$Z_i = \begin{cases} 1 & \text{if triangle } i \text{ appears in } G[U] \\ 0 & \text{else.} \end{cases}$$

We have  $E[Z_i] = p^3$ . Then  $Z = \sum_{i=1}^t Z_i$ . Note that the variables  $Z_i$  are (in general) not independent. The variance of  $Z$  is given by

$$\text{Var}[Z] = \text{Var}\left[\sum_{i=1}^t Z_i\right] = \sum_{i=1}^t \text{Var}[Z_i] + 2 \sum_{i<j} \text{Cov}(Z_i, Z_j). \quad (13)$$

We have

$$\text{Var}[Z_i] = E[Z_i] - (E[Z_i])^2 \leq E[Z_i] = p^3,$$

and

$$\begin{aligned} \text{Cov}(Z_i, Z_j) &= E[Z_i Z_j] - E[Z_i]E[Z_j] \\ &= \begin{cases} 0 & \text{if the two triangles have no vertex in common,} \\ p^5 - p^6 & \text{if the two triangles have a single vertex in common,} \\ p^4 - p^6 & \text{if the two triangles have two vertices in common.} \end{cases} \end{aligned}$$

The number of pairs of triangles having one or two vertices in common are at most  $3tm$  and  $3tn$ , respectively. By substituting these expressions into (13) we obtain an upper bound on the variance of  $Z$ :

$$\text{Var}[Z] \leq tp^3 + 6tmp^5 + 6tnp^4. \quad (14)$$

We assumed that  $t = \Omega(m^{1+\delta})$ . Applying Chebyshev's inequality (1) to  $Z$  yields that the approximate count returned by the algorithm is outside of the interval  $[(1-\varepsilon)t, (1+\varepsilon)t]$  with vanishing probability (as  $n \rightarrow \infty$ ). Indeed, for a fixed  $\varepsilon > 0$  we have

$$\begin{aligned} \text{Prob}\left(\left|Zn^{3\delta} - t\right| \geq \varepsilon t\right) &\leq \frac{\text{Var}[Zn^{3\delta}]}{\varepsilon^2(E[Zn^{3\delta}])^2} = \frac{\text{Var}[Z]}{\varepsilon^2(E[Z])^2} \\ &\leq \frac{(tp^3 + 6tmp^5 + 6tnp^4)}{\varepsilon^2 t^2 p^6} \leq \frac{24}{\varepsilon^2 t} \left(n^{3\delta} + mn^\delta + n^{1+2\delta}\right) \\ &= O\left(\frac{mn^\delta + n^{1+2\delta}}{\varepsilon^2 t}\right) = O\left(n^{-3.82\delta^2}\right). \end{aligned}$$

Finally, by the second moment method, we have

$$\text{Prob}(Z = 0) \leq \frac{\text{Var}[Z]}{(E[Z])^2} = O\left(n^{-3.82\delta^2}\right). \quad (15)$$

If a nonzero count is returned by the algorithm,  $G[U]$  contains  $Z > 0$  triangles, hence one of these triangles can be also identified within the same time (as mentioned in Section 1). This concludes the proof of Theorem 3.  $\square$