

A pragmatic approach for designing transparent WDM optical networks with multi-objectives

Dao Thanh Hai, Le Anh Ngoc

Received: date / Accepted: date

Abstract The era of Artificial Intelligence and Internet of Things are underway, pushing the proliferation of bandwidth-intensive services such as virtual realities, big data exchanges and autonomous vehicles. In this context, optical transport networks based on WDM technologies forming the core part of Internet infrastructure carrying multi-Tb/s has to be re-considered from both designing, planning, operation and management perspectives so as to support exponential traffic growth in a greater efficiency. Thanks to the convergence of significant advances in optical transmission technologies, and photonic switching, transparent (all-optical) architecture has come into practice, paving the way for eliminating the over-utilization of costly optical-electrical-optical (O-E-O) interfaces and hence, yielding remarkable savings of cost and energy consumption compared to opaque architecture. Traditional designs for transparent optical networks based on single-objective optimization model aiming at optimizing solely a single performance metric appears to be insufficient to capture the nuances of practical designs while conventional multi-objective approach tends to reach (non-) optimal solutions. Different from existing works, we present a new framework for multi-objective WDM network designs capturing several goals on one hand and on the other hand, achieving optimal solutions. Moreover, our proposal exploits the characteristics of each constituent objectives to lay the foundation for setting up weight coefficient so that the order of optimization

is guaranteed. Equally important, our proposal is pragmatic in the sense that the complexity of the optimization model remains the same as the single-objective model while the quality of solution has been greatly improved. We have extensively tested realistic optical core networks topologies, that is, COST239 and NSFNET, with various network traffic conditions and it turns out that our design brings about a saving of wavelength link usage up to roughly 28% in the most favorable cases while 14% is expected for the least favorable cases.

Keywords routing and wavelength assignment · integer linear programming · dedicated protection · optical networks · fiber optics communication

1 Introduction

The era of Artificial Intelligence and Internet of Things have started to penetrate into the daily lives in an unprecedented way. On one hand, more and more devices have been connected to Internet, paving the way for digitization and then datafication of (almost) everything. On the other hand, the proliferation of bandwidth-demanding services driven by big data analysis, cloud computing and generally digital future have been accelerating in a rapid manner. A case in point for illustration is how data-intensive the operation of a self-driving car is. It is estimated that such an autonomous car generates a huge amounts of data, roughly 5Tb per hour and it is equivalent of a supercomputer in terms of generating and transmitting a mind-boggling amount of data. Such two driving forces have been push-pulling the scale of challenge posed by global consumption of data and the explosive growth of Internet traffic. As recently announced in Cisco Annual Internet Report, the number of devices connected to IP networks will be as more as

F. Author
Post and Telecommunication Institute of Technology
E-mail: haidt102@gmail.com

S. Author
Electric Power University
E-mail: anhngoclevn@gmail.com

three times than the global population by 2023, representing a growth of 10% CAGR. As a consequence of such growth, Internet traffic will be increasing three-fold accordingly, reaching a CAGR of 25% and it means that Global Internet traffic in 2020 will be equivalent to 95x the volume of the entire Global Internet in 2005 [1].

Fiber-optic networks exploiting wavelength division multiplexing (WDM) technologies have long been constituting the core part of Internet infrastructure, supporting the exchange of Internet traffic from a point to any point in the planet thanks to the immense transmission capacity in the order of Tb/s and beyond [2]. The exponential growth of Internet traffic guided by the rise and growing penetration of bandwidth-intensive services such as virtual realities and AI-enabled applications indeed are posing critical challenges for optical transport networks and hence necessitating for a reconsideration from both designing, planning and management perspectives to achieve greater capital and operational efficiency. From the architectural standpoint, core optical networks have been evolving from the opaque mode to translucent and eventually fully transparent operation. Traditionally, the opaque nodes had been widely implemented for core networks since transmission technologies had been limited to short distances and photonic switching technologies had not been exploited. In this kind of networks, the optical signal are terminated and regenerated at every node by making use of the optical-electrical-optical (O-E-O) conversion. While operating so brings advantage of eliminating cascading physical impairments and allowing multi-vendor interoperability, its critical downside of over-utilizing costly O-E-O conversion makes it less scalable as the traffic increases. In an attempt to reduce the proliferation of expensive O-E-O usage, translucent networks have been exploited to replace the fully opaque architecture. In this hybrid operation mode, the optical signal remains in optical domain as far as possible before its regeneration (i.e., the regeneration could be either in optical domain or via O-E-O interface). Alternatively, the regeneration could also be employed to ease the wavelength continuity constraints. Noticed that the signal can be regenerated several times in the network before it reaches the destination and hence, could be used different wavelengths at each segment. Thanks to the enormous advancements in optical components, transmission technologies and photonic switching, the vision of all-optical core networks have been experimentally and practically realized, bringing in significant savings of cost, footprint, and power by eliminating unnecessary O-E-O regeneration. Indeed, fully transparent optical core networks nowadays have been widely deployed by

network operators and efficient designing of such transparent networks therefore has been of ever-growing importance as the spectrum resources has to be optimized while maintaining the efficiency of operations. Different from the opaque and translucent networks, operating transparent networks require carefully designed algorithms so that the full benefits of technology could be attained and in this perspective, the essential problem to be solved impacting to all phases of network operations from planning, designing to management is the routing and wavelength assignment (RWA) issue. Basically, RWA involves the finding of a route and assign certain wavelength for a demand so as to optimize a number of performance metrics such as spectrum efficiency, cost or power consumption while meeting technological constraints typically including wavelength continuity and wavelength uniqueness [3, 4]

Being a critical issue for the operation of transparent WDM networks, RWA has been extensively addressed in the literature [5–7]. Generally, RWA problem could be formulated in the form of a combinatorial optimization model which could be solved then by either exact approaches to obtain the optimal solutions or heuristic approaches to acquire acceptable and/or near-optimal outcomes [7]. On one hand, exact approaches based on solving the mixed integer linear programming formulation has the merit of optimality (i.e., higher quality solutions) which could be translated to greater capital expenditure and operation expenditure efficiency. However, the key drawback of such approaches lies in the NP-hard nature of RWA problems and thus, for large-scale networks and/or for certain traffic instances, the solution may be difficult to reach in a practical time frame. On the other hand, effective heuristic algorithms has been sought as an alternative technique aiming at approximated solutions in a rapid manner [8]. Meta-heuristics extends the quality of general heuristic algorithms by adding specific features of each RWA variants into the algorithms and thus, tailoring the solution to the problem to achieve better performance [9, 10]. In essence, heuristic-based approaches trade solution qualities for running time in contrast to the exact ones. RWA problems could have different variants depending on the context and the goal of the studies. In the context of survivable network designs, the authors in [11, 12] developed efficient routing strategy to be tolerant to fault issues. Further to the protection scenarios, network coding has been added as a new layer of design and this results in a different variant of RWA, called routing, wavelength and network coding assignment (RWNCA) [13–16]. Doing so helps to boost the spectral efficiency of optical core networks by reduc-

ing the redundant capacity demanded by protection requirement and the respective mathematical formulation for network design has been introduced in [17,18]. With respect to energy efficiency, RWA has been re-purposed to make it energy-aware [19,20]. In the paradigm of elastic transmission technologies, RWA problems are transformed into routing and spectrum assignment and the works in [21–24] proposed new algorithms for solving such related RWA problem in elastic optical networks. A significant part of existing works on RWA have nevertheless been focusing on optimizing a single metric and such conventional metric can be either the number of wavelength—for the un-bounded scenario to support a given set of traffic demands or alternatively, the throughput in the case of capacity-constrained scenario and hence, the target is to support as many traffic as possible.

Planning a network indeed involves a number of metrics, sometimes, conflicting ones and/or with different priorities. Therefore, a multi-objective optimization framework has to be developed to capture the real need of network planning process. In addressing this issue, existing works in the literature have been developed into two directions. The first one is rather straightforward by combining several objectives into a single integrated one with weight coefficients. While this direction appears to be intuitive, existing works in the literature have remained obscured in providing insights on the impact of weight coefficients to the significance of constituents. Besides, the selection of weight coefficients have been largely based on the so-called rule of thumb and hence, difficult to justify. As an alternative approach, the second direction focuses on the application of general multi-objective framework based on meta-heuristic models including swarm intelligence, aiming at obtaining approximate multi-objective solutions (i.e., approximated Pareto front) [8–10]. Such approach has nevertheless the essential drawback of missing the particularities of the problem under consideration, in addition to the inherent shortcoming of non-optimal solutions.

In mitigating the downsides of existing approaches for multi-objective RWA design in the literature, this paper goes extra miles with a new integer linear programming model which is capable of optimizing two and more objectives in a strict order. Specifically, the traditional wavelength count metric is optimized as the first priority while wavelength link usage—being correlated to operational expense—would be a secondary goal. Such two constituent objectives are combined appropriately into an integrated objective and in guaranteeing

the order of optimization, we propose a framework for analyzing and then determining the weight coefficients so that the strict hierarchy between constituent goals are ensured. To this end, the remaining of the paper is organized as follows. In Sect. 2, we present an illustrative example highlighting the key difference of single-objective approach and our multi-objective proposal. Next, in Sect. 3, the new optimization model capturing both wavelength count and wavelength link usage is introduced. We also introduce an extensive analysis of the impact of weight coefficient to the order and priority of constituent objectives. In verifying the efficacy of our proposal, Sect. 4 is dedicated to comprehensive numerical simulations on realistic topologies, COST239 and NSFNET, in different traffic conditions and protection requirements. Finally, Sect. 5 concludes the paper.

2 Multi-objective transparent WDM network design


Assuming that there are two traffic requests, from node A to node D and from node E to node D. One such optimal provisioning—Design A—for those requests in terms of *wavelength link* is shown in Fig. It is straightforward to verify that the shortest route has been chosen to serve both requests and this design consumes three wavelength links which is an optimal outcome from a conventional single-objective design. On the other hand, such design makes use of two distinctive wavelengths as the routing of connection A-D and E-D share a common link E-D and therefore their wavelengths must be different, that is, λ_1 and λ_2 as in Fig. 1a

Consider an alternative single-objective design with respect to *wavelength count*—Design B, one such optimal design is shown in Fig. 1b. It is shown that only one wavelength is needed to accommodate both requests and this is the optimal result obtained from solving the optimization model of such design. However, with respect to *wavelength link* usage, Design B incurs five wavelength links which is roughly 70% higher than the Design A presented in Fig. 1a


In improving the Design B in Fig. 1b, one can refer to the Design C shown in Fig. 1c. This Design is a bi-objective model aiming at optimizing the wavelength count first and then the wavelength link usage. It is observed that for Design C, only one wavelength is needed while the wavelength link usage is also minimized, that is, *four* units compared to the (non-optimized) *five* as shown in Design B. Design C therefore on one hand achieves optimal wavelength count as Design B and on the other hand, minimize the wavelength link usage as

the secondary objective. The comparison of three Designs is summarized in Tab. 1


The problem emerged from above analysis is that traditional single-objective designs aim at optimizing a single performance metric and hence possibly incur certain penalties with respect to other objectives. Specifically, it is of particular interest to have a Design that is capable of minimizing multi-objectives in a strict order, that is, the first objective is minimized and then the second objective is optimized among a pool of optimal solutions with respect to the first objective. The same reasoning is applied for general cases of more than two objectives. We aim to propose a general framework for obtaining such pragmatic Designs in this paper.



(a) An optimal single objective design with respect to wavelength link



(b) An optimal single objective design with respect to wavelength count



(c) An optimal bi-objective design with respect to both wavelength count and wavelength link in an ordered fashion

Fig. 1: An illustrative comparison of different Designs

Table 1: Performance Comparison of Designs

Design	Performance Metric	
	Wavelength Count	Wavelength Link Usage
Design 1	2	3
Design 2	1	4
Design 3	1	3

3 Joint Wavelength Count and Wavelength Link Usage Optimization

From the mathematical perspectives, optical networks design and planning problems belong to the broad class of optimization models. In particular, the planning process of a transport network focuses on how each traffic demand is provisioned so as to minimize/maximize the network performance (e.g., spectrum efficiency). Accommodating a traffic demand then involves the selection of links over which the demand is routed, the backup route for that demand—if protection service is provided—in cases of link failures on the working route, the assignment of wavelength for both working and protection signals. When it comes to the design and planning aspects for optical core networks, the timescales for consideration is long-term as the traffic is assumed to be relatively static and this task has to be performed before the network deployment process. In this context, there is generally a large set of demands to be handled simultaneously and the goal is to find optimal strategy to do so.

In this part, we present an efficient optimization model for accommodating traffic demands arisen in the long-term planning of optical core networks. Inputs to the formulation are set of nodes and links composing the physical optical network, set of traffic requests and the task is to determine routing for each demand including the working and protection route, the wavelength for both working and protection signals so as to minimize the network resources measured by the number of used wavelength and the wavelength link usage. The fully transparent network architecture is adopted and thus, the wavelength continuity constraint has to be enforced. The network design is formulated in the form of a mixed integer linear programming model composing of an integrated objective function, that is, wavelength count and wavelength link consumption. We present a framework for analyzing and determining the weight coefficients so that the order of optimization goals are ensured.

Given Information:

- $G(V, E)$: Physical fiber-networks topology composing of $|V|$ nodes and $|E|$ fiber links. The starting node and ending node of a link $e \in E$ are denoted as $s(e)$ and $r(e)$, respectively
- D : Set of all traffic requests. The source node and receiving node of a demand $d \in D$ are denoted as $s(d)$ and $r(d)$ respectively; It is assumed that all demands request *one wavelength capacity*
- C : Set of all wavelength channels on each fiber link. The fiber link capacity measured by number of wavelength channels is therefore $|C|$
- α_1, α_2 : Real numbers representing weight coefficients to specify the relative significance of constituent objective
- q_d : Binary constant specifying the protection service for demand d , $q_d = 1$ for dedicated protection of demand d while $q_d = 0$ implies no protection requirement

Variables:

- $x_d^{e,c} \in \{0, 1\}$: equals to 1 if link e and wavelength channel c is used for working path of demand d , 0 otherwise.
- $y_d^{e,c} \in \{0, 1\}$: equals to 1 if link e and wavelength channel c is used for protection path of demand d , 0 otherwise.
- $\theta_d^c \in \{0, 1\}$: equals to 1 if the wavelength channel c is used to carry demand d , 0 otherwise.
- $\gamma_{e,c} \in \{0, 1\}$: equals to 1 if the wavelength channel c is used on link e , 0 otherwise
- $\delta_c \in \{0, 1\}$: equals to 1 if the wavelength channel c is used in any fiber link of the network, 0 otherwise

Objective: *Minimize the following integrated objective function*

$$\alpha_1 \times \sum_{c \in C} \delta_c + \alpha_2 \times \sum_{c \in C} \sum_{e \in E} \gamma_{e,c} \quad (1)$$

Subject to the following constraints:

$$\sum_{c \in C} \theta_d^c = 1 \quad \forall d \in D \quad (2)$$

$$\sum_{e \in E: v \equiv s(e)} x_d^{e,c} - \sum_{e \in E: v \equiv r(e)} x_d^{e,c} = \begin{cases} \theta_d^c & \text{if } v \equiv s(d) \\ -\theta_d^c & \text{if } v \equiv r(d) \\ 0 & \text{otherwise} \end{cases} \quad \forall v \in V, \forall d \in D, \forall c \in C \quad (3)$$

$$\sum_{e \in E: v \equiv s(e)} y_d^{e,c} - \sum_{e \in E: v \equiv r(e)} y_d^{e,c} = \begin{cases} \theta_d^c & \text{if } v \equiv s(d) \\ -\theta_d^c & \text{if } v \equiv r(d) \\ 0 & \text{otherwise} \end{cases} \quad \forall v \in V, \forall d \in D : q_d = 1, \forall c \in C \quad (4)$$

$$\sum_{d \in D} x_d^{e,c} + \sum_{d \in D} y_d^{e,c} = \gamma_{e,c} \quad \forall e \in E, \forall c \in C \quad (5)$$

$$\sum_{c \in C} \gamma_{e,c} \leq |C| \delta_c \quad \forall e \in E \quad (6)$$

The integrated objective function in Eq. 1 consists of two constituents being weighted by coefficients α_1 and α_2 respectively. The first objective δ_c is a conventional performance indicator, that is, the number of wavelength channels needed to support traffic demands while the second objective $\gamma_{e,c}$ measures the used wavelength link which directly corresponds to the operational expenses of network when it is in-operation. Eq. 2 is a constraint to ensure that all demands must be provisioned by having a proper wavelength channel. Eq. 3 and Eq. 4 are flow conservation constraints for working and protection flow respectively. Constraint expressed by Eq. 5 enforces the uniqueness of each wavelength channel, that is, each wavelength channel is used by at most one lightpath—either working or protection. The final constraint in Eq. 6 defines the use of a wavelength channel in a network, that is, a wavelength channel is counted as used when it is assigned for a lightpath in any link of the network.

3.1 Determining Weight Coefficients

As can be seen in Eq. 1, weight coefficients α_1 and α_2 determine the relative significance of constituent objectives and it would be our interest to find a suitable range of α_1 and α_2 so as the first objective—minimizing the wavelength channel count—is performed with a strict priority and then the second objective—wavelength link usage—is optimized.

In order to provide such hierarchy of optimization, we exploit the specific characteristic of each constituent objective. In fact, it is known that the first objective is lower-bounded and upper-bounded as $0 \leq \sum_{c \in C} \delta_c \leq |C|$. Similarly, the second objective also has a lower bound and upper-bound as $0 \leq \sum_{c \in C} \sum_{e \in E} \gamma_{e,c} \leq$

$|C||E|$. Next the minimum step of variation for each objective is also known, that is, *one*. Let us consider the case that $\alpha_1 > |E||C| \times \alpha_2$.

We assume that there is a minimum increase from the first objective, that is, from δ_c to $\delta_c + 1$ and there is an arbitrary change Δ in the second objective. The net impact on the integrated objective function is therefore $N = \alpha_1 \times (\delta_c + 1 - \delta_c) + \alpha_2 \times \Delta$. Conditioned on $-|E||C| \leq \Delta \leq |E||C|$ and $\alpha_1 > |E||C| \times \alpha_2$, it is easy to verify that N is always greater than zero. This observation reveals the fact that variation of the integrated objective function is in the same direction with the first constituent objective despite arbitrary deviation of the second objective. More specifically, under the case that $\alpha_1 > |E||C| \times \alpha_2$, there is a strict order of optimization, that is, the first objective is optimized first and then the second objective is taken into consideration.

4 Numerical Evaluations

This section is dedicated to provide a comprehensive evaluation of our design proposal in realistic network topologies, COST239 and NSFNET, in various traffic conditions. The key characteristic of these networks are reported in Tab. 2. In order to evaluate the efficacy of the integrated objective design, it is benchmarked with the traditional single-objective design that is widely used in the literature. In particular, four Designs are under comparison. The first and second Design are the conventional single-objective RWA in the case of no protection and dedicated protection respectively (i.e., `rwa_wc` and `rwa_wc_p`). The third and fourth design are the (multi-) bi-objective RWA (i.e., `rwa_intwc` and `rwa_intwc_p`) aiming at minimizing the wavelength count first and wavelength link usage as a secondary goal. Description of these four Designs together with their objective functions are shown in Tab. 3. To represent different traffic conditions, we consider three traffic loads, that is, low, medium and high whose difference is the number of traffic demands. The high load is characterized by the fact that all the node pairs in the network have traffic requests while for the low and medium ones, $\approx 30\%$ and $\approx 70\%$ of all node pairs have traffic respectively. For each type of traffic load, 10 instances of traffic matrices are generated for simulations. In solving the optimization model based on mixed integer linear programming of four designs, we use CPLEX solver version 12.7 with academic license. All the results are optimally obtained and in most demanding cases, the running time is less than 1 hour.

Table 4 presents a comprehensive simulation results comparing the traditional single-objective Designs and our proposal of multi-objective Designs in two scenarios, that is, with dedicated protection and without protection. The performance metric for comparison are wavelength count and wavelength link usage. Note that the results are averaged over 10 traffic instances.

On a first observation, it is noted that the integrated objective Designs achieve the same quality of solution compared to the traditional single-objective Designs with respect to wavelength count metric and this is ensured consistently over different load conditions and for both two networks (i.e., between `rwa_pc` and `rwa_intwc` on wavelength count, between `rwa_wc_p` and `rwa_intwc_p` on wavelength count). This is the experimental confirmation from our theoretical analysis in Sect. 3. Note that such same quality of solution could be achieved only by proper set-up of the weight coefficients and we have demonstrated a framework for doing so.

As can be seen in Tab. 4, adding protection requirement in provisioning traffic requests have caused redundant capacity including extra spectrum capacity and/or hardware equipments. Interestingly, such impact is different depending on traffic load conditions. For COST239 network, in the low-load condition, an increase of 85% wavelength count has to be incurred while in medium and high-load, the impact is more severe, being 130% and 171% respectively. For NSFNET network which is sparser than COST239 network, the cost of having protection is very high and it is relatively consistent over three different traffic loads. Specifically, with respect to wavelength count, adding protection demands an increase of more than 200% wavelengths.

Next, the important observation involves how the proposal of integrated objective Designs is more efficient than the traditional single objective approach. This can be verified by focusing on the comparison of wavelength link usage. As has been clearly shown from results in Tab. 4, the integrated objective approach consistently outperforms in all traffic load conditions and for both cases of protection or without protection. Specifically, at low-load, the integrated Designs (i.e., `rwa_intwc` and `rwa_intwc_p`) yield 14% and 20% savings of wavelength link for COST239 and NSFNET networks respectively. For the case of protection, that saving is more significant, being 19% for COST239 and 28% for NSFNET network. The highest saving is recorded at medium-load condition as our proposal is 20% to 22% more efficient than its counterpart for both cases of protection or without protection and for both COST239

and NSFNET network.




Fig. 2: Network topologies for evaluation

Table 2: Topology Characteristic

Parameters	Network Topology	
	COST239	NSFNET
Nodes	11	14
Links	26x2	21x2
Average degree of nodes	3	3.4
Min node degree	2	3
Max node degree	4	5

5 Conclusions

This paper set out to investigate a different approach for solving the multi-objective RWA problem arisen in the designing and planning of transparent WDM optical networks. Inspired by the observation that, in practice, in addition to the key design metric, other performance metrics should also be included for consideration and hence, being optimized in the optimization model with different priorities. In doing so, we have presented a new framework for combining multiple objectives into a single integrated objective function with appropriate weight coefficients. The priority of each constituent objective is determined by its weights and we have provided a comprehensive analysis on the impact of weight coefficients to their priorities. Extensive numerical simulations have been carried out on realistic network topologies including COST239 and NSFNET, with various traffic conditions and protection requirements and it has been highlighted that our proposal

could yield a saving of up to 28% wavelength link usage in most favorable cases while in the worst cases, the saving has remained roughly 14%. The contribution of this paper—the network design formulation—could therefore provide insights for network operators in re-designing their networks to achieve greater capital and operational efficiency.

In extending this work, one promising direction would be to translate our proposal to more practical performance indicators including cost and energy consumption—which of course depending on the technological and network settings, in addition to including more than two objectives in the integrated objective function. Further research might also explore the multi-objective designs in the context of advanced technological and architectural frameworks including photonic network coding and/or space division multiplexing-elastic optical networks.

Conflict of interest

The authors declare that they have no conflict of interest.

References

1. Cisco: The zettabyte era : Trends and analysis (2017). URL <http://www.cisco.com/c/en/us/solutions/collateral/service-provider/>
2. Winzer, P.J., Neilson, D.T., Chraplyvy, A.R.: Fiber-optic transmission and networking: the previous 20 and the next 20 years. *Opt. Express* **26**(18), 24,190–24,239 (2018). DOI 10.1364/OE.26.024190. URL <http://www.opticsexpress.org/abstract.cfm?URI=oe-26-18-24190>
3. Saleh, A., Simmons, J.M.: All-optical networking: Evolution, benefits, challenges, and future vision. *Proceedings of the IEEE* **100**(5), 1105–1117 (2012). DOI 10.1109/JPROC.2011.2182589
4. Saleh, A., Simmons, J.M.: Technology and architecture to enable the explosive growth of the internet. *Communications Magazine, IEEE* **49**(1), 126–132 (2011). DOI 10.1109/MCOM.2011.5681026
5. Zang, H., Jue, J.P.: A review of routing and wavelength assignment approaches for wavelength-routed optical wdm networks. *Optical Networks Magazine* **1**, 47–60 (2000)
6. Zang, H., Ou, C., Mukherjee, B.: Path-protection routing and wavelength assignment (rwa) in wdm mesh networks under duct-layer constraints. *Networking, IEEE/ACM Transactions on* **11**(2), 248–258 (2003). DOI 10.1109/TNET.2003.810313
7. Solving routing and wavelength assignment problem with maximum edge-disjoint paths
8. Tian, X., Yang, J., Ding, H., Yang, Y.: Multi-objective routing and wavelength assignment based priority algorithm in wdm networks. In: 2012 Fourth International Symposium on Information

Table 3: Description of Four Designs for Benchmarking

Design Name	Objective Function	Description
rwa_wc	$\sum_{c \in C} \delta_c$	Wavelength count is a sole objective for minimization There is no protection in provisioning a demand
rwa_wc_p	$\sum_{c \in C} \delta_c$	Wavelength count is a sole objective for minimization There is a dedicated protection in provisioning a demand
rwa_intwc	$\sum_{c \in C} \delta_c + \frac{1}{1+ C E } \sum_{c \in C} \sum_{e \in E} \gamma_{e,c}$	Minimize wavelength count first and then wavelength link usage There is no protection in provisioning a demand
rwa_intwc_p	$\sum_{c \in C} \delta_c + \frac{1}{1+ C E } \sum_{c \in C} \sum_{e \in E} \gamma_{e,c}$	Minimize wavelength count first and then wavelength link usage There is dedicated protection in provisioning a demand

Table 4: Performance Comparison of Four Designs on COST239 and NSFNET topology

Network Topology	Traffic Condition	Design Name	Performance Metrics	
			Wavelength Count	Wavelength Link Usage
COST239	Low-load	rwa_wc	1.4	33.2
		rwa_wc_p	2.6	85.3
		rwa_intwc	1.4	28.7
		rwa_intwc_p	2.6	69.1
	Medium-load	rwa_wc	2.0	73.5
		rwa_wc_p	4.6	169.3
		rwa_intwc	2.0	57.4
		rwa_intwc_p	4.6	136.1
	High-load	rwa_wc	2.8	109.3
		rwa_wc_p	7.6	278.3
		rwa_intwc	2.8	87.7
		rwa_intwc_p	7.6	218.0
NSFNET	Low-load	rwa_wc	3.4	83.7
		rwa_wc_p	10.5	246.5
		rwa_intwc	3.4	67.0
		rwa_intwc_p	10.5	178.7
	Medium-load	rwa_wc	5.6	160.9
		rwa_wc_p	19.6	461.8
		rwa_intwc	5.6	132.4
		rwa_intwc_p	19.6	377.9
	High-load	rwa_wc	7.3	230.0
		rwa_wc_p	24.7	676.4
		rwa_intwc	7.3	198.6
		rwa_intwc_p	24.7	586.3

- Science and Engineering (ISISE 2012), pp. 87–92. IEEE Computer Society, Los Alamitos, CA, USA (2012). DOI 10.1109/ISISE.2012.28. URL <https://doi.ieeecomputersociety.org/10.1109/ISISE.2012.28>
9. Leesutthipornchai, P., Charnsripinyo, C., Wattanapongsakorn, N.: Solving multi-objective routing and wavelength assignment in wdm network using hybrid evolutionary computation approach. *Computer Communications* **33**(18), 2246–2259 (2010). DOI <https://doi.org/10.1016/j.comcom.2010.07.029>
 10. Rubio-Largo, A., Vega-Rodriguez, M.A., Gomez-Pulido, J.A., Sanchez-Perez, J.M.: Solving the routing and wavelength assignment problem in wdm networks by using a multiobjective variable neighborhood search algorithm. In: E. Corchado, P. Novais, C. Analide, J. Sedano (eds.) *Soft Computing Models in Industrial and Environmental Applications*, 5th International Workshop (SOCO 2010), pp. 47–54. Springer Berlin Heidelberg, Berlin, Heidelberg (2010)
 11. Walkowiak, K., Klinkowski, M., Rabiega, B., Gościński, R.: Routing and spectrum allocation algorithms for elastic optical networks with dedicated path protection. *Optical Switching and Networking* **13**, 63–75 (2014). DOI <https://doi.org/10.1016/j.osn.2014.02.002>
 12. Bhatt, U.R., Tokekar, S.: Survivable routing and wavelength assignment strategy for multiclass wdm optical networks. In: 2011 International Conference on Computational Intelligence and Communication Networks, pp. 711–715 (2011). DOI 10.1109/CICN.2011.155
 13. Hai, D.T.: Leveraging the survivable all-optical wdm network design with network coding assignment. *IEEE Communications Letters* **21**(10), 2190–2193 (2017). DOI 10.1109/LCOMM.2017.2720661
 14. Hai, D.T.: On solving the 1+1 routing, wavelength and network coding assignment problem with a bi-objective integer linear programming model. *Telecommunication Systems* **71**(2), 155–165 (2019). DOI 10.1007/s11235-018-0474-9. URL <https://doi.org/10.1007/s11235-018-0474-9>
 15. Dao, T.H.: On optimal designs of transparent wdm networks with 1+1 protection leveraged by all-optical XOR network coding schemes. *Optical Fiber Technology* **40**, 93 – 100 (2018). DOI <https://doi.org/10.1016/j.yofte.2017.11.009>

16. Hai, D.T.: On routing, spectrum and network coding assignment problem for transparent flex-grid optical networks with dedicated protection. *Computer Communications* **147**, 198 – 208 (2019). DOI <https://doi.org/10.1016/j.comcom.2019.08.005>
17. Hai, D.T.: An optimal design framework for 1+1 routing and network coding assignment problem in wdm optical networks. *IEEE Access* **5**, 22,291–22,298 (2017). DOI [10.1109/ACCESS.2017.2761809](https://doi.org/10.1109/ACCESS.2017.2761809)
18. Hai, D.T.: Re-designing dedicated protection in transparent wdm optical networks with xor network coding. In: 2018 Advances in Wireless and Optical Communications (RTUWO), pp. 118–123 (2018). DOI [10.1109/RTUWO.2018.8587873](https://doi.org/10.1109/RTUWO.2018.8587873)
19. Coiro, A., Listanti, M., Matera, F.: Energy-efficient routing and wavelength assignment in translucent optical networks. *IEEE/OSA Journal of Optical Communications and Networking* **6**(10), 843–857 (2014). DOI [10.1364/JOCN.6.000843](https://doi.org/10.1364/JOCN.6.000843)
20. Coiro, A., Listanti, M., Valenti, A., Matera, F.: Power-aware routing and wavelength assignment in multi-fiber optical networks. *J. Opt. Commun. Netw.* **3**(11), 816–829 (2011). DOI [10.1364/JOCN.3.000816](https://doi.org/10.1364/JOCN.3.000816). URL <http://jocn.osa.org/abstract.cfm?URI=jocn-3-11-816>
21. Hai, D.T., Morvan, M., Gravey, P.: Combining heuristic and exact approaches for solving the routing and spectrum assignment problem. *IET Optoelectronics* **12**(2), 65–72 (2018). DOI [10.1049/iet-opt.2017.0013](https://doi.org/10.1049/iet-opt.2017.0013)
22. Dao, H., Morvan, M., Gravey, P.: An efficient network-side path protection scheme in ofdm-based elastic optical networks. *International Journal of Communication Systems* **31**(1), e3410. DOI [10.1002/dac.3410](https://doi.org/10.1002/dac.3410). URL <https://onlinelibrary.wiley.com/doi/abs/10.1002/dac.3410>. E3410 dac.3410
23. Dao Thanh, H., Morvan, M., Gravey, P.: On the usage of flexible transponder in survivable transparent flex-grid optical network. In: 2014 9th International Symposium on Communication Systems, Networks Digital Sign (CSNDSP), pp. 1123–1127 (2014). DOI [10.1109/CSNDSP.2014.6923998](https://doi.org/10.1109/CSNDSP.2014.6923998)
24. Hai, D., Morvan, M., Gravey, P.: On the routing and spectrum assignment with multiple objectives. In: Advanced Photonics for Communications, p. JT3A.12. Optical Society of America (2014). URL <http://www.osapublishing.org/abstract.cfm?URI=PS-2014-JT3A.12>