

# Towards an Online Empathetic Chatbot with Emotion Causes

Yanran Li\*, Ke Li\*

Hongke Ning, xiaoqiang Xia, Yalong Guo, Chen Wei, Jianwei Cui, Bin Wang

Xiaomi AI Lab

liyanran,like16,ninghongke,xiaoxiaoqiang,guoyalong,weichen,cuijianwei,wangbin11@xiaomi.com

## ABSTRACT

Existing emotion-aware conversational models usually focus on controlling the response contents to align with a specific emotion class, whereas empathy is the ability to understand and concern the feelings and experience of others. Hence, it is critical to learn the causes that evoke the users' emotion for empathetic responding, a.k.a. emotion causes. To gather emotion causes in online environments, we leverage counseling strategies and develop an empathetic chatbot to utilize the causal emotion information. On a real-world online dataset, we verify the effectiveness of the proposed approach by comparing our chatbot with several SOTA methods using automatic metrics, expert-based human judgements as well as user-based online evaluation.

## CCS CONCEPTS

• Computing methodologies → Discourse, dialogue and pragmatics; Natural language generation.

## KEYWORDS

Empathetic Chatbots, Response Generation, Dialogue Systems

### ACM Reference Format:

Yanran Li\*, Ke Li and Hongke Ning, xiaoqiang Xia, Yalong Guo, Chen Wei, Jianwei Cui, Bin Wang. 2021. Towards an Online Empathetic Chatbot with Emotion Causes. In *Proceedings of the 44th International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR '21)*, July 11–15, 2021, Virtual Event, Canada. ACM, New York, NY, USA, 5 pages. <https://doi.org/10.1145/3404835.3463042>

## 1 INTRODUCTION

Since empathy plays a vital role for amicable social conversation and trustful social bonding [6], it is critical to endow social chatbots with the ability of empathy. However, existing approaches tend to produce responses that are rarely empathetic, as indicated by previous studies [26]. Specifically, the majority of existing emotion-aware conversational models focus on controlling the response contents to align with a specific emotion class [13, 16, 28, 35], whereas empathy is the ability to understand and concern the feelings and experience of others [9].

\*Both authors contributed equally to this research.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from [permissions@acm.org](mailto:permissions@acm.org).  
SIGIR '21, July 11–15, 2021, Virtual Event, Canada.

© 2021 Copyright held by the owner/author(s). Publication rights licensed to ACM.  
ACM ISBN 978-1-4503-8037-9/21/07...\$15.00  
<https://doi.org/10.1145/3404835.3463042>

Table 1: Two Conversation Examples.

Turn	Utterance	Strategy & Cause
U1	I'm upset.	None
S1	Everything will be OK.	None
U1	I'm upset.	None
S1	Sorry to hear that. What happened?	effective questioning
U2	We <b>broke up</b> .	emotion cause
S2	Oh dear, it must be hurt. Did you argue for something?	active listening

To facilitate empathetic responding, we argue that it is also necessary for the chatbots to learn the causes behind user's emotion, a.k.a., emotion causes, in addition to the emotion class. Although emotion cause has been regarded as an important information for emotion classification in conversation [12, 22, 23] and news text [11, 33], its benefit for empathetic response generation is yet to be explored. Especially for online chatbots, it is non-trivial to exploit the causal emotion information. Usually, open-domain chatbots are trained over "pseudo" conversations from social media platforms, where people are more reserved to share negative emotions as compared to private channels like messaging apps and chatbots [2, 10]. Though it is plausible to train empathetic chatbots using the crowd-sourced EMPATHETICDIALOGUES dataset [26], the conversation behavior on it is still distinguished from what we observed from online real logs. To be specific, we sample 8,000 conversations in EMPATHETICDIALOGUES dataset and another 8,000 real online conversations from XiaoAI, one of the largest Chinese social chatbots,<sup>1</sup> and manually label the emotion causes in the conversations. We find that while 89% of conversations begin with the speaker expressing their emotion causes in EMPATHETICDIALOGUES dataset, there are only 7% of online logs containing user emotion causes. In other words, online users tend not initiatively to self-disclose their emotion causes, and might not reveal the reasons if the chatbot did not explicitly ask. As a result, the chatbots trained over these datasets often simply produce general responses that are not empathetic, and exhibit detached to users, as shown in the upper example in Table 1. This critically harms user experience and weakens the user-chatbot stickness.

To remedy these issues, we get inspired from Psychological studies [14, 20] and develop EMMA, an online Empathetic chatbot based on the user emotion causes. When a user starts a conversation, our approach firstly detects user emotion class and recognizes the emotion causes. If no emotion cause is detected, our chatbot EMMA directs users to self-disclose more based on effective questioning and active listening, the two counseling strategies that are often

<sup>1</sup>According to Xiaomi's second-quarter report, there are 78.4 million monthly active users of XiaoAI. <https://www.statista.com/statistics/967715/worldwide-xiaomi-ai-assistant-users/>

used by psychologists to encourage further engagement and gather detailed information during the counseling conversations [3, 5]. Finally, EMMA produces empathetic responses based on the conversation history, detected emotion class as well as the emotion causes. In brief, we highlight our contributions as follows: (1) We identify the significance of emotion cause for empathetic response generation; (2) We develop an online empathetic chatbot EMMA by leveraging causal emotion information obtained through counseling strategies; (3) We curate a large-scale empathetic conversation dataset from real-world online logs, and manually annotate the emotion causes on them; (4) We empirically demonstrate the effectiveness of our approach using automatic metrics, expert-based human judgements as well as user-based online evaluation. The dataset and codes will be released soon.

## 2 DATASET: X-EMAC

We construct a novel empathetic conversation dataset with causal emotion information to examine the benefit of emotion causes for empathetic response generation, especially in online environments. **Emotion Cause.** Following previous work [22, 23], we define emotion cause as the continuous text span in an utterance that can be used to detect or infer the speaker’s emotion.


To begin with, we randomly sample a large set of user queries from XiaoAi online logs, and ask human experts to annotate the queries with four common emotion classes: sad, anger, joy and others. These annotated queries are used to train an emotion classifier.

**Counseling Strategies.** To encourage online users to self-disclose more information, we hire psychologists to manually write a set of diverse templates using the counseling strategies of active listening and effective questioning [3, 5]. The templates are designed specific to each emotion class and in average, there are 53 templates per class. Then, we deploy the templates online as the corresponding responses to those user queries that are classified into certain emotion classes (sad, anger, joy), and collect the next turn of real-time user responses to the templates. According to these three turns of conversations (online user-online template-online user), human experts are required to annotate the span of emotion causes in each utterance, and write empathetic responses with high-quality. We also filter dirty and sensitive conversations carefully. The statistics of the resulted XiaoAI Empathetic Conversation (X-EMAC) dataset are summarized in below.

**Table 2: Statistics of Dataset X-EMAC.**

Total Number of Conversations	16,873
Total Number of Templates	157
Total Types of Emotion Causes	29
Average Utterances per Conversation	4
Average Words per Utterance	8.9

Based on the user experiences, the emotion causes in the annotated spans are manually categorized into 29 common and coarse-grained types like missing someone, broken up, etc. Notably, we find that 62% of users will respond to our counseling-based templates,



**Figure 1: Emma: An Empathetic Chatbot.**

indicating the effectiveness of the proposed strategies in encouraging user engagement during online empathetic conversations, which will also be demonstrated in our experiments.

## 3 MODEL: EMMA

Formally, our task is to learn a response generation model via maximum likelihood estimation and generate a response  $Y = \{y_1, \dots, y_T\}$  according to the user query  $X = \{x_1, \dots, x_N\}$  and history conversations  $H$ , where  $N$  and  $T$  are the corresponding token numbers. To make the generated responses more empathetic, we also leverage emotional information like emotion label  $L$  and emotion causes  $C$ . We will detail the methods of emotion classification and emotional cause extraction in the experiment parts. Overall, the conditional probability of generating a response  $Y$  can be formulated as:

$$P_Y = \prod_{i=1}^T P(y_i | y_{0:t-1}, X, H, L, C) \quad (1)$$

Since pre-trained language models (PLMs) have demonstrated their great potentials in dialogue response generation [1, 8, 30, 32, 34], we focus on the following sub-questions: (1) Whether PLMs equipped with causal emotion information are able to generate empathetic responses; (2) Whether PLMs are able to capture counseling strategies in leading empathetic conversations.

To answer these sub-questions, we develop an **Empathetic** chatbot based on the user **emotion causes**, namely EMMA. Based on GPT [24], EMMA also consists of multiple blocks of multi-head self-attention mechanism [29]. Specifically, we concatenate the embeddings of user query and emotional information into one, long text sequence. Following common practice [30], we also include speaker embedding indicating speaker information and two special symbols [CLS] and [SEP] to separate the sequences.

As depicted in Figure 1, when there is no history dialogue, the concatenated input to EMMA contains the query embeddings, emotional label as well as emotion cause embeddings. Intuitively, EMMA

will produce responses with active listening and effective questioning strategies when the [hasCause] indicator is observed as [None]. As the conversation goes, EMMA considers the history conversation information, and the input becomes [CLS][speaker1]q1[speaker2]r1[speaker1]q2[sep]label[SEP]hasCause[SEP]Cause[SEP]. Due to space limit, we do not illustrate the history information in Figure 1.

## 4 EXPERIMENTS

To evaluate our approach EMMA for building online empathetic chatbot, we conduct several sets of experiments<sup>2</sup> on the proposed dataset X-EMAC to examine: (1) the benefits of emotion cause; (2) the effectiveness of counseling strategies; and discuss (3) the difficulties and insights we learn.

### 4.1 Experimental Setups

**Compared Models.** We compare with the following approaches: (1) BERT-RETRIEVE, an 12-layer BERT [7] trained over a LCCC-large dataset,<sup>3</sup> which consists of 12 million multi-round short-text conversations from social media; (2) UNILM-GENERATION, the SOTA PLM for both natural language understanding and generation tasks with its official implementation;<sup>4</sup> (3) CDIAL-GPT, the SOTA Chinese PLM for short-text conversation generation task with its official implementation;<sup>5</sup> (4) Our EMMA and its variant EMMA-Cause, where emotion cause information is removed from the input sequences.

**Implementation Details.** We divide the dataset into train/dev/test sets randomly with the ratio of 8:1:1, where dev set is used to tune the model parameters, and the test set is used to compare the model performances. For word segmentation, we use Jieba,<sup>6</sup> and the vocabulary is constrained to 1,998 words. The dimension of word embedding is set to 768, the number of the warmup epoch is set to 1, and the maximum learning rate is 5e-3. We implement the models based on the huggingface library,<sup>7</sup> and test them on NVIDIA Telsa V100. For fair comparison, all the compared models are using 12 layers with 12 attention heads, and optimized using AdamW optimizer [19]. Based on the empirical results, the number of gradient accumulation is set to 64.

**Evaluation Metrics.** We adopt three kinds of assessments: (1) The **word-level automatic metrics** including Perplexity (PPL) and distinct n-grams [15], which indicate the fluency and informativeness of the generated responses respectively; (2) The **3-scale expert-based human judgements** in terms of empathy and relevance [26]. We randomly sample 250 conversations and the responses from each compared model. Then, we hire 3 professional experts from a third-party annotation company to evaluate the response quality with scale of {0,1,2}. For example, empathy measures the extent of understanding exhibited by the chatbots to the users’ feelings; (3) A **user-based online evaluation** net sale value (NSV), which suggests the users preferences on chatbot’s replies. In online chatbots and social platforms like Reddit, users can click the icons of thumb up and down, indicating they like or dislike a response. By summing up the total numbers of “like”

**Table 3: Experimental Results on Using Emotion Cause.**

Model	PPL	Dist-1	Empathy	Relev.	NSV
BERT-RET	-	<b>0.291</b>	0.97	1.69	-3.1%
UNILM-GEN	58.54	0.138	1.03	1.68	4.3%
CDIAL-GPT	62.33	0.083	1.03	1.42	-
EMMA	<b>19.66</b>	0.039	<b>1.43</b>	<b>1.75</b>	<b>28.5%</b>
-Cause	20.79	0.031	1.24	1.59	16.9%

**Table 4: Human A/B Test Results.**

Model	Win	Loss	Tie
EMMA v.s. BERT-RET	56%	6%	37%
EMMA v.s. UNILM-GEN	51%	15%	34%
EMMA v.s. CDIAL-GPT	62%	6%	32%
EMMA v.s. EMMA-CAUSE	35%	12%	53%

and “dislike” a chatbot (method) receives, we are able to calculate that  $NSV = (\#upvotes - \#downvotes) / (\#upvotes + \#downvotes)$ . The higher the NSV is, the better the conversational model is preferred.

### 4.2 Results and Analysis

**The Benefit of Emotion Causes.** As shown in Table 3, the retrieval-based BERT model in the first row performs the worst. Even though it yields decent distinct-n scores and satisfactory relevance score, its responses are rated as the least empathetic by human experts and are disliked most by the online users. Considering that BERT-RETRIEVE is trained on 12 million of conversations collected from internet, its disappointing performance validates that it is unsafe to directly train online open-domain chatbot using social media data, which may contain a lot of less empathetic responses that will harm user experience.

The performances of UNILM-GEN and CDIAL-GPT in the second and third rows are similar but defective. They are SOTA response generation models and are expected to capture implicit knowledge like conversation patterns [17]. However, as implied by the expert-based judgements, the responses generated by them are of low empathy and moderate relevance. Between them, UNILM-GEN is slightly better than CDIAL-GPT. We conjecture that it is because UNILM-GEN together models the bi-directional context, while CDIAL-GPT only follows a left-to-right manner to predict a text sequence [8]. Nevertheless, the online user feedback on UNILM-GEN still suggests a room for improvement.

When examining the performances of EMMA and its variant (the last two rows), we can see that the proposed approach outperforms the other PLMs especially on empathy and NSV scores. The improvements are largely brought by emotional information utilization, which demonstrates the significance of emotional information in empathetic response generation. The performance gap between EMMA and EMMA-CAUSE further indicates the benefit of emotion cause, which has been neglected before. While emotion class label is integrated into both EMMA and its variant EMMA-CAUSE, only EMMA has the ability of capturing fine-grained user experience and

<sup>2</sup>We will release the dataset and the codes for future research.

<sup>3</sup><https://github.com/thu-coai/CDial-GPT>

<sup>4</sup><https://github.com/microsoft/unilm>

<sup>5</sup><https://github.com/thu-coai/CDial-GPT>

<sup>6</sup><https://github.com/fxsjy/jieba>

<sup>7</sup><https://github.com/huggingface/transformers>

**Table 5: Experimental Results on Counseling Strategies (CS).**

Model	Dist-1	Dist-2	Empathy	Relevance
BERT-RETRIEVE	<b>0.294</b>	<b>0.596</b>	0.95	1.60
BERT-RETRIEVE+CT.	0.106	0.254	1.06	1.77
UNILM-GEN	0.140	0.402	1.02	1.58
UNILM-GEN+CT.	0.036	0.103	<b>1.17</b>	1.69

**Table 6: Case Studies. Due to space limit, we omit the original Chinese text.**

Context/Model	Query/Responses
<i>q1:</i>	<i>I am unhappy.</i>
<i>r1-CS:</i>	<i>Don't worry, I'm always here for listening.</i>
<i>q2:</i>	<i>My father beat me.</i>
BERT-RET.	I'm also unhappy this year.
BERT-RET.+CT.	What happened?
UNILM-GEN	Just leave it.
UNILM-GEN+CT.	He beat you because you did not listen to him.
CDIAL-GPT	My father and mother also beat me.
EMMA	Sounds terrible! Could you tell more about why and when it happened?

responding with proper communication strategies, the ability of empathy [9].

We also carry out an expert-based human A/B test to verify the comparison results. We compare the best model EMMA with each other PLM in a pair-wise manner. For fair comparison, the expert annotators do not know which model the response is from. As shown in Table 4, it is obvious that our empathetic chatbot EMMA are more favored by the professionals, which is consistent with online user preferences.

**The Effectiveness of Counseling Strategies.** The experimental results shown above also imply that PLM models like GPT are able to learn counseling strategies on the X-EMAC dataset. Typically, we leverage the strategies of effective questioning and active listening, which enable the chatbot to sound more attentive and encourage the users to describe more about their situations [20]. It is thus possible to apply these strategies for acquiring more detailed information in the second-round of user queries than their initial ones.

To this end, we conduct another set of experiments to investigate the strategy effectiveness. We take BERT-RETRIEVE and UNILM-GENERATION as exemplars, and compare their responses to two different set of queries. The first set of queries are the users' beginning queries as they start the conversations, and the other set are the second-round queries as the users replying to the templates with counseling strategies (CS). The comparison results are summarized in Table 5, where we can see clear improvements over empathy and relevance when both model are fed with more specific queries acquired through counseling strategies.

When examining the distinct-n scores in Table 1 and Table 5, it is also worth noting that the distinct-n scores seem often contradict to expert-based and user-based judgements, which has also been found in previous studies [27, 31]. After manually checking the

**Table 7: Results on Emotion Classification (ECf.) and Emotion Cause Extraction (ECE).**

Task	Precision	Recall	Exact_Match	Fuzzy_Match
ECf.	0.924	0.862	-	-
ECE	-	-	0.746	0.903
<b>ECf. + ECE</b>	<b>0.930</b>	<b>0.863</b>	<b>0.750</b>	<b>0.910</b>

examples of generated responses from the compared models, we conclude that the responses with too many distinct n-grams often include content that are not sympathetic to users experiences. This somehow results in a decrease of response diversity. For better understanding, we show some examples of generated responses from the compared models in Table 6.

### 4.3 Discussions

**The Mutual Benefits of Joint Learning.** There exist auxiliary approaches for the tasks of emotion classification (ECf.) and emotion cause extraction (ECE) [23]. In this work, we cast ECf. as a multi-classification task, and ECE as a reading comprehension task [25]. Since these two tasks are standard and dominated with PLM models, we adopt BERT to perform both ECf. and ECE.

Following common practice, we report the precision and recall for ECf., whereas Exact\_Match and Fuzzy\_Match scores for ECE in Table 7. Because we only have 4 emotion classes annotated in X-EMAC dataset, it is fair that BERT-based model yields acceptable precision and recall scores. Clearly, the scores on emotion cause extraction task (ECE) are lower than those on emotion classification (ECf.). It is reasonable because ECE is a more difficult task than ECf. As discussed in [22], emotion causes can be context-depended or context-independent, and sometimes they are latent and unmentioned in the text. Inspired by previous work [4, 33], we add up the losses from the two tasks and joint learning the model parameters. Despite the fact that both tasks are inherited with some difficulties, these two tasks are mutually indicative for each other. By combining the two worlds, we are able to further improve the understanding of the conversation and increase the precision and accuracy of the tasks.

**Error Analysis.** It is also promising to jointly learn the emotional understanding model and response generation model for better holistic performance. Currently, we do not regulate the generated responses and the model is still possible to bypass the causal emotion information during the generation. Intuitively, we can perceive the empathy level of the generated responses and formulate it as an additional loss to be optimized together. Such loss is beneficial to check whether the user emotion is well understood, and is also helpful for generation model to improve itself. In this way, we are able to build up the empathetic chatbots in a holistic fashion.

**Future Work.** The focus of this work is to explore the benefit of emotion cause in empathetic response generation using a simple but effective approach. Towards building building online empathetic chatbots, there are other important research problems such as how to mimicking user's emotion more naturally [21] and how to integrating commonsense knowledge more selectively [18]. In the future, we plan to improve the understanding of user emotion

by integrating commonsense reasoning, and investigate response rewriting to make the counseling templates more natural.

## 5 ETHICS DECLARATION

The dataset was sourced with license and consent from XiaoAI chatbot, and this work was approved by XiaoAI team. All personally identifiable information in our dataset was removed. Towards preventing unsafe expressions, all of our responses and strategies are proof-read and double-checked by XiaoAI team and mental health professionals before online deployment.

## REFERENCES

- [1] Siqi Bao, H. He, Fan Wang, and Hua Wu. 2020. PLATO: Pre-trained Dialogue Generation Model with Discrete Latent Variable. In *ACL*.
- [2] Natalya N. Bazarova, Y. Choi, Victoria Schwanda Sosik, Dan Cosley, and J. Whitlock. 2015. Social Sharing of Emotions on Facebook: Channel Differences, Satisfaction, and Replies. *Proceedings of the 18th ACM Conference on Computer Supported Cooperative Work & Social Computing* (2015).
- [3] T. Bickmore and D. Schulman. 2007. Practical approaches to comforting users with relational agents. In *CHI Extended Abstracts*.
- [4] Ying Chen, Wenjun Hou, Xiyao Cheng, and S. Li. 2018. Joint Learning for Emotion Classification and Emotion Cause Detection. In *EMNLP*.
- [5] Lucette B. Comer and Tanya Drollinger. 2013. Active Empathetic Listening and Selling Success: A Conceptual Framework. *Journal of Personal Selling and Sales Management* 19 (2013), 15–29.
- [6] J. Decety. 2010. The Neurodevelopment of Empathy in Humans. *Developmental Neuroscience* 32 (2010), 257 – 267.
- [7] J. Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. In *NAACL-HLT*.
- [8] Li Dong, Nan Yang, Wenhui Wang, Furu Wei, Xiaodong Liu, Yu Wang, Jianfeng Gao, M. Zhou, and H. Hon. 2019. Unified Language Model Pre-training for Natural Language Understanding and Generation. *ArXiv abs/1905.03197* (2019).
- [9] Nancy Eisenberg and Natalie D. Eggum. 2009. Empathic responding: Sympathy and personal distress.
- [10] E. Goffman. 1981. Forms of talk.
- [11] Lin Gui, Ruifeng Xu, Qin Lu, Dongyin Wu, and Y. Zhou. 2016. Emotion Cause Extraction, A Challenging Task with Corpus Construction. In *SMP*.
- [12] Lin Gui, L. Yuan, Ruifeng Xu, B. Liu, Qin Lu, and Y. Zhou. 2014. Emotion Cause Detection with Linguistic Construction in Chinese Weibo Text. In *NLPCC*.
- [13] Chenyang Huang, Osmar R Zaiane, A. Trabelsi, and Nouha Dziri. 2018. Automatic Dialogue Generation with Expressed Emotions. In *NAACL-HLT*.
- [14] L. Karp. 2015. Can empathy be taught? Reflections from a medical student active-listening workshop. *Rhode Island medical journal* 98 6 (2015).
- [15] J. Li, Michel Galley, Chris Brockett, Jianfeng Gao, and W. Dolan. 2016. A Diversity-Promoting Objective Function for Neural Conversation Models. *ArXiv abs/1510.03055* (2016).
- [16] Jingyuan Li and X. Sun. 2018. A Syntactically Constrained Bidirectional-Asynchronous Approach for Emotional Conversation Generation. In *EMNLP*.
- [17] Piji Li. 2020. An Empirical Investigation of Pre-Trained Transformer Language Models for Open-Domain Dialogue Generation. *ArXiv abs/2003.04195* (2020).
- [18] Qintong Li, Piji Li, Zhumin Chen, and Z. Ren. 2020. Towards Empathetic Dialogue Generation over Multi-type Knowledge. *arXiv: Computation and Language* (2020).
- [19] I. Loshchilov and F. Hutter. 2017. Fixing Weight Decay Regularization in Adam. *ArXiv abs/1711.05101* (2017).
- [20] Nurul Lubis, S. Sakti, Koichiro Yoshino, and S. Nakamura. 2019. Dialogue Model and Response Generation for Emotion Improvement Elicitation.
- [21] Navonil Majumder, Pengfei Hong, S. Peng, Jiankun Lu, Deepanway Ghosal, Alexander Gelbukh, R. Mihalcea, and Soujanya Poria. 2020. MIME: MIMicking Emotions for Empathetic Response Generation. *ArXiv abs/2010.01454* (2020).
- [22] Soujanya Poria, Navonil Majumder, Devamanyu Hazarika, Deepanway Ghosal, Rishabh Bhardwaj, Samson Yu Bai Jian, Romila Ghosh, Niyati Chhaya, Alexander Gelbukh, and R. Mihalcea. 2020. Recognizing Emotion Cause in Conversations. *ArXiv abs/2012.11820* (2020).
- [23] Soujanya Poria, Navonil Majumder, R. Mihalcea, and E. Hovy. 2019. Emotion Recognition in Conversation: Research Challenges, Datasets, and Recent Advances. *IEEE Access* 7 (2019), 100943–100953.
- [24] A. Radford and Karthik Narasimhan. 2018. Improving Language Understanding by Generative Pre-Training.
- [25] Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. 2016. SQuAD: 100, 000+ Questions for Machine Comprehension of Text. In *EMNLP*.
- [26] Hannah Rashkin, Eric Michael Smith, Margaret Li, and Y-Lan Boureau. 2019. Towards Empathetic Open-domain Conversation Models: A New Benchmark and Dataset. In *ACL*.
- [27] Ashish Sharma, I. W. Lin, Adam S. Miner, David C. Atkins, and Tim Althoff. 2021. Towards Facilitating Empathic Conversations in Online Mental Health Support: A Reinforcement Learning Approach. *ArXiv abs/2101.07714* (2021).
- [28] Lei Shen and Yang Feng. 2020. CDL: Curriculum Dual Learning for Emotion-Controllable Response Generation. In *ACL*.
- [29] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, L. Kaiser, and Illia Polosukhin. 2017. Attention is All you Need. *ArXiv abs/1706.03762* (2017).
- [30] Yida Wang, Pei Ke, Yinhe Zheng, Kaili Huang, Yong Jiang, Xiaoyan Zhu, and Minlie Huang. 2020. A Large-Scale Chinese Short-Text Conversation Dataset. In *NLPCC*. <https://arxiv.org/abs/2008.03946>
- [31] Anuradha Welivita and Pearl Pu. 2020. A Taxonomy of Empathetic Response Intents in Human Social Conversations. In *Proceedings of the 28th International Conference on Computational Linguistics*. International Committee on Computational Linguistics, Barcelona, Spain (Online), 4886–4899. <https://doi.org/10.18653/v1/2020.coling-main.429>
- [32] Thomas Wolf, Victor Sanh, Julien Chaumond, and Clement Delangue. 2019. TransferTransfo: A Transfer Learning Approach for Neural Network Based Conversational Agents. *ArXiv abs/1901.08149* (2019).
- [33] Rui Xia and Zixiang Ding. 2019. Emotion-Cause Pair Extraction: A New Task to Emotion Analysis in Texts. In *ACL*.
- [34] Yizhe Zhang, S. Sun, Michel Galley, Yen-Chun Chen, Chris Brockett, Xiang Gao, Jianfeng Gao, Jingjing Liu, and W. Dolan. 2020. DialoGPT: Large-Scale Generative Pre-training for Conversational Response Generation. In *ACL*.
- [35] Hao Zhou, Minlie Huang, T. Zhang, Xiaoyan Zhu, and Bing Liu. 2018. Emotional Chatting Machine: Emotional Conversation Generation with Internal and External Memory. In *AAAI*.