CONCURRENT MATCHING LOGIC

SHANGBEI WANG

Nanjing University of Aeronautics and Astronautics, Nanjing, China *e-mail address*: wangshangbei123@nuaa.edu.cn

ABSTRACT. Matching logic cannot handle concurrency. We introduce concurrent matching logic (CML) to reason about fault-free partial correctness of shared-memory concurrent programs. We also present a soundness proof for concurrent matching logic (CML) in terms of operational semantics. Under certain assumptions, the assertion of CSL can be transformed into the assertion of CML. Hence, CSL can be seen as an instance of CML.

INTRODUCTION

It is inevitable that the concurrent execution of shared-memory programs produce races in which one process changes a piece of state that is simultaneously being used by another process. There are a number of approaches to guarantee both race-freedom and correctness when reasoning about shared-memory concurrent programs. Based on "spatial separation", Hoare[Hoa72] introduced formal proof rules for shared-memory concurrent programs. Expanding Hoare's work, Owicki and Gries[OG76a][OG76b] introduced a syntax-directed logic for shared-memory concurrent programs. The critical variables and resources are key in Owicki and Gries's logic. The critical variables are identifiers which can by concurrently read and written by processes. Each occurrence of a critical variable must be inside a critical region protected by a resource name. As a result, processes are mutually exclusive access to critical variables and free of races. However, Brookes Bro07 pointed out that this approach works well for pointer-free shared-memory concurrent programs, but fails when pointer aliases are included in concurrent programs. Concurrent Separation Logic (CSL) was proposed by O'Hearn[O'h07] using separation logic[Rey02], together with an adaptation of the Owicki-Gries's methodology, to reason about partial correctness of concurrent pointer-programs. The innovation of CSL is to insert the separating conjunction into rules dealing with resource invariants and parallel composition. But Reynolds has shown that O'Hearn's rules are unsound without restrictions on resource

Key words and phrases: Concurrency; Matching logic; Soundness; Race condition.

invariants[OYR09]. Brookes[Bro07] used action traces to provide a denotational semantics that can detect race. Then, the inference rules of O'Hearn were redefined in a more semantically way, and the sound of the proof rules was proved. Ian Wehrman and Josh Berdine found a counter example, suggesting that the sound of this method was based on the implicit assumption that no other program modified it. In order to avoid this problem, Brookes developed a fully compositional concurrent separation logic by adding "rely set" to the assertions of CSL[Bro11].

Dijkstra[Dij68] stated that one of the basic principles of concurrent program is that processes should be loosely connected. Processes should be considered completely independent of each other except when they are explicitly interacting with each other. The principle reflected in the above approaches is the idea of "resource separation". At any time, the state can be divided into two separate portions, one for the process and the other satisfying the relevant resource invariant, for the available resource. When a process acquires a resource, it has ownership of the separate portion of state associated with the resource; When releasing a resource, it must ensure that resource invariant continues to hold and return ownership of the corresponding separate portion of state. The idea of "resource separation" fit particularly well with the viewpoint of separation logic. Therefore, O'Hearn inserted the separating conjunction in appropriate places in the rules studied by Owicki and Gries, and then the very popular concurrent separation logic (CSL) came into being.

Matching logic[Ros17b][RES10] introduced by Grigore Roşu has inherent support for heap separation without the need to extend the logic with separating conjunction. In other words, matching logic inherently supports the viewpoint of "resource separation". In addition, Grigore Roşu showed that separation logic is an instance of matching logic both syntactically and semantically[Ros17b]. Therefore, it is natural to think that matching logic can be used for proving certain correction properties of concurrent programs. Unfortunately, matching logic does not typically handle concurrency. Inspired by the concurrent separation logic (CSL), we introduce Concurrent Matching Logic (CML) for reasoning about fault-free partial correctness of shared-memory concurrent programs in this paper. First, we give an operational semantics model for concurrency, using K semantics framework

[RŞ10][Ros17a], which include race-detection. Our operational semantics , based on "actions", is transition traces semantics, describes the interleaving behavior of processes and without interference unless synchronized. Second, in order to be able to handle concurrency, we not only extend Grigore Roşu's matching logic inference rules, allowing resource declarations and concurrent compositions, but also adjust the pattern of the matching logic. Like CSL, the assertion requires a "rely set" A, which represents a set of variables that are not changed by "environment moves". CSL uses separation logic formulas to describe the state before and after process execution. Instead of logic formulas, matching logic uses patterns. The separation logic formula is abstract, and CSL can gracefully handle "environment moves" simply by relying on the "rely set". However, pattern involves "low-level" operational aspects, such as how to express the state. In addition to a "rely set" A, we need a "key set" B to handle "environment moves". "Key set" B is also a collection of

variables that is used when a concrete configuration γ matches CML pattern. Finally, we give the notion of validity and prove CML is sound to our operational semantics model for concurrency. We also analyze the relationship between the CML and the CSL, and point out that under certain assumptions, the assertions of CSL can be transformed into the assertions of CML. That is to say any property provable using CSL is also provable using CML.

1. Preliminaries

K Semantics Framework. K is an executable semantic framework. The operational semantics of a program language L is defined as a rewrite logic theory $(\Sigma_L, \mathcal{E}_L, \mathcal{R}_L)$ [MOM96] by K. Let L^o be the algebraic specification $(\Sigma_L, \mathcal{E}_L^o)$ where $\mathcal{E}_L^o \subseteq \mathcal{E}_L$ and \mathcal{T}^o be the initial L^o algebra. Term $\langle s_c \rangle_s \langle h_c \rangle_h \langle N_c \rangle_r$ in \mathcal{T}^o is called state and $\langle k_c \rangle_k \langle s_c \rangle_s \langle h_c \rangle_h \langle N_c \rangle_r$ is called concrete configuration which is to add a sequence of commands to the state.

Let v_1, v_2, \ldots, v_n are integer values and l_1, l_2, \ldots, l_n are addresses which are also integer values. A state $\langle s_c \rangle_s \langle h_c \rangle_h \langle N_c \rangle_r$ consists of a store $\langle s_c \rangle_s$, a heap $\langle h_c \rangle_h$ and a set of resource names $\langle N_c \rangle_r$. The store $\langle s_c \rangle_s$ has the form of $\langle i_1 \mapsto v_1, i_2 \mapsto v_2, \ldots, i_n \mapsto v_n \rangle_s$ mapping identifiers to integers. Let's define $\operatorname{dom}(s_c) = \{i | (i \mapsto v) \in s_c\}$. The heap $\langle h_c \rangle_h$ maps addresses to integers and $\operatorname{dom}(h_c) = \{l | (l \mapsto v) \in h_c\}$. We use the notation $[s_c | i \mapsto v]$ to indicate that the store is consistent with all identifiers of s_c except i, which is mapped to v; and the similar notation $[h_c | l \mapsto v']$. The notation $h_c \setminus l$ denotes the removal of address lfrom the domain of h_c and $\operatorname{dom}(h_c \setminus l) = \operatorname{dom}(h_c) - \{l\}$. The "initial" state has the form of $\langle s_c \rangle_s \langle h_c \rangle_h \langle \{\} \rangle_r$ because resources are initially available.

The rules in K are divided into structural rules and semantic rules. For example

$$e_1 + e_2 \rightleftharpoons e_1 \frown \Box + e_2$$

The symbol \rightleftharpoons represent two structural rules, one from left to right and the other from right to left. The first rule says that in the expression $e_1 + e_2$, e_1 can be evaluated first, and e_2 is reserved for later evaluation. Since the above rules are bidirectional, when the first and second rules are used iteratively, they complete the evaluation of e_1 and e_2 . Then, semantic rule tells how to process.

Separation Logic Formula. A separation logic formula[Rey02][O'H19] is given by the following grammar.

$$p ::= b \mid \mathbf{emp} \mid e \mapsto e' \mid p_1 * p_2 \mid p_1 \land p_2 \mid p_1 \lor p_2 \mid \neg p$$

Let $\langle s_1 \rangle_s \langle h_1 \rangle_h \langle N_1 \rangle_r$, $\langle s_2 \rangle_s \langle h_2 \rangle_h \langle N_2 \rangle_r$ are states. If $\operatorname{dom}(h_1) \cap \operatorname{dom}(h_2) = \emptyset$, h_1 and h_2 are called disjoint, written $h_1 \perp h_2$. we also write $h_1 \cdot h_2 = h_1 \cup h_2$.

The satisfaction relation $\langle s_c \rangle_s \langle h_c \rangle_h \langle N_c \rangle_r \models p$ is defined as follows:

Lemma 1.1. Let p is a separation logic formula, e is a expression, i is an identifier that occurs freely in formula p, p[e/i] means to replace i in p with e, then

$$<\!\!s_c\!\!>_s<\!\!h_c\!\!>_h<\!\!N_c\!\!>_r\models p[e/i]\Leftrightarrow<\!\![s_c|i\mapsto s_c(e)]\!\!>_s<\!\!h_c\!\!>_h<\!\!N_c\!\!>_r\models p$$

Proof. by induction on the structure of p.

A separation logic formula p is precise[Bro07] if, for all states $\langle s_c \rangle_s \langle h_c \rangle_h \langle N_c \rangle_r$, there is at most one sub-heap $h_{c1} \subseteq h_c$ such that $\langle s_c \rangle_s \langle h_{c1} \rangle_h \langle N_c \rangle_r \models p$.

Resource. As in Owicki-Gries[OG76b], each resource name r has a set X containing the protected identifiers and a resource invariant R[Hoa72]. A resource context Γ has the form

$$r_1(X_1): R_1, \cdots, r_n(X_n): R_n$$

where r_1, \dots, r_n are different resource names, R_1, \dots, R_n are separation logic formulas and $r(X) : R \in \Gamma$ imply r protects $x \in X$.

Let $\mathbf{owned}(\Gamma) = X_1 \cup X_2 \cup \cdots \cup X_n$, $\mathbf{inv}(\Gamma) = R_1 * R_2 * \cdots * R_n$, and $\mathbf{dom}(\Gamma) = \{r_1, r_2, \cdots, r_n\}$. For each *i*, if R_i is precise and $\mathbf{free}(R_i) \subseteq X_i$, we say Γ is well-formed.

Matching Logic Pattern. In G. Roşu's matching logic, program variables are syntactic constants. In other words, one cannot quantify over program variables. Let Var is an infinite set of logical variables. The pattern of matching logic has the form $\exists X((o = c) \land p)$ where "o" is a placeholder; $X \subset Var$ is a set of bound variables; c is a pattern structure; $FOL_{=}$ formula p is a constraint. Valuation (γ, τ) has a concrete configuration γ and a map τ : $Var \rightarrow Int$. $(\gamma, \tau) \models \exists X((o = c) \land p)$ iff there exists θ_{τ} : $Var \rightarrow Int$ with $\theta_{\tau} \upharpoonright_{Var/X} = \tau \upharpoonright_{Var/X}$ such that $\gamma = \theta_{\tau}(c)$ and $\theta_{\tau} \models p$.

Matching logic works well on the sequential processes [CR19][CLR21][RS12][RS11], but not on the shared-memory concurrent processes. The reasons are as follows:

- Matching logic cannot handle concurrency. There are critical variables which can by concurrently read and written by processes. Matching logic has no rules to guarantee that processes are mutually exclusive access to the critical variables and freedom from races;
- Program variables are syntactic constants in matching logic. The syntax-directed method such as "rely set" representing a set of program identifiers assumed to be left unmodified by the "environment moves" cannot be used in matching logic;
- CSL uses separation logic formula to describe the state before and after process execution. Instead of separation logic formula, matching logic uses pattern. Separation logic formula is relatively abstract and CSL can deal with "environment moves" gracefully. However, pattern involves "low-level" operational aspects, such as how to express the state. "Environment moves" is a disaster for matching logic.

2. Syntax

Syntax. The program language L is the same as in the Concurrent separation logic[Bro07]. Suppose r, i, e, b, E, c are meta-variables, and r represents resource names, i represents identifiers, e represents integer expressions, b represents boolean expressions, E represents list expressions, c represents commands. The resource name acts like a binary semaphore. It is also an integer variable, but the value is limited to either 0, which means the resource is in used, or 1, which means the resource is available. The expression is pure, that is, the value of the expression is heap-independent. The syntax of command is defined as follows:

$$c ::=$$
skip $| i := e | i := [e] | [e_1] := e_2 | i :=$ **cons** $E |$ **dispose** $e | k_1; k_2$

| if b then k_1 else $k_2 |$ while b do k | resource r in k | with r when b do k | $k_1 || k_2$

with r when b do k is a conditional critical region of resource r. Before a process enters the conditional critical section of resource r, it must wait until resource r is available, then obtain resource r and estimate the value of b: if b is true, the process executes k and releases resource r when k completes; if b is false, the process releases resources r and waits for a retry. A resource can only be held by one process at a time. **resource** r **in** k introduces a local resource name r, whose scope is k, it means that the resource r is assumed initially available in k and the actions involving r are executed without interference.

Actions. An action is an atomic unit used to measure the execution of a program. Let λ is a meta-variable ranging over actions and λ has the following form

 $\lambda ::= \delta \mid i = v \mid i := v \mid [l] = v \mid [l] := v \mid \mathbf{alloc}(l, E) \mid \mathbf{disp} \mid l \mid \mathbf{try} \mid r \mid \mathbf{acq} \mid r \mid \mathbf{rel} \mid r \mid \mathbf{abort}$

where v ranges over integers, l over addresses which are also integers, E over list of integers. Every action has a natural and intuitive explanation. For example, **try** r means that the resource named r failed to be obtained.

Let $\mathbf{free}(\lambda)$ is the set of identifiers that occur freely in λ , $\mathbf{mod}(\lambda)$ is the set of identifiers that can be modified in λ , $\mathbf{writes}(\lambda)$ is the set of identifiers or heap cells that can be

modified in λ , reads (λ) is the set of identifiers or heap cells whose values are read by λ , and res (λ) is the set of resource names that occur freely in λ .

$$\mathbf{mod}(\lambda) = \begin{cases} \{i\}, & \lambda \equiv i := v \\ \emptyset, & otherwise \end{cases}$$
$$\mathbf{writes}(\lambda) = \begin{cases} \{i\}, & \lambda \equiv i := v \\ \{l\}, & \lambda \equiv [l] := v \\ \{l, l+1, \cdots, l+n\}, & \lambda \equiv \mathbf{alloc}(l, E) \\ \{l\}, & \lambda \equiv \mathbf{dispose} \ l \\ \emptyset, & otherwise \end{cases}$$
$$\mathbf{reads}(\lambda) = \begin{cases} \{i\}, & \lambda \equiv i = v \\ \{l\}, & \lambda \equiv [l] = v \\ \emptyset, & otherwise \end{cases}$$
$$\mathbf{free}(\lambda) = \mathbf{reads}(\lambda) \cup \mathbf{writes}(\lambda)$$
$$\mathbf{mod}(\lambda) \subseteq \mathbf{writes}(\lambda)$$

Concurrent Matching Logic

Concurrent Matching Logic Pattern. A first major distinction between concurrent matching logic (CML) and G. Roşu's matching logic is that program variables are logical variables. Instead of assuming p is an arbitrary $FOL_{=}$ formula, we require p to be separation logic formula and to be precise.

Let **Var** is a set of logical variables, i_1, i_2, \ldots, i_n are identifiers, v_1, v_2, \ldots, v_n are integer values, l_1, l_2, \ldots, l_n are addresses and $x_1, x_2, \ldots, x_n \in$ **Var**. Intuitively, at any stage of program execution, the state can be divided into three portions, one portion owned by the program, one portion owned by the environment, and the rest portion belonging to currently available resources. The pattern of CML is used to describe the state before and after the program is executed. Therefore, the definition of CML pattern is as follows.

Definition 2.1. Concurrent matching logic(CML) pattern has the form

$$\exists X((o = \langle k \rangle_k \langle s \rangle_s \langle h_1, h_2, H \rangle_h \langle N_1, N_2 \rangle_r) \land p)$$

where $X \in \mathbf{Var}$ is the set of bound variables; k is a sequence of commands; s has the form of $i_1 \mapsto x_1, \ldots, i_n \mapsto x_n$; h_1, h_2, H are mappings from addresses to integers; N_1, N_2 are sets of resources; p is the separation logic formula.

Note that h_1, h_2, H, N_1, N_2 do not contain the variables in **Var**. In CML pattern, h_1, N_1 represents part of the heap and part of the resource owned by the process, h_2, N_2 is owned by the environment, and H represents the remaining heap and satisfies the resource invariants of the currently available resources. However, how do we divide store into corresponding portions? This is impossible because store can be shared between concurrent processes.

Therefore, we introduce the "key set" B, which is a set of identifiers owned by the process. More importantly, identifiers in "key set" B cannot be changed by "environment moves".

Definition 2.2. A concrete configuration $\gamma = \langle k \rangle_k \langle s_c \rangle_s \langle h_{1c}, h_{2c}, H_c \rangle_h \langle N_{1c}, N_{2c} \rangle_r$ matches CML pattern $\exists X((o = \langle k \rangle_k \langle s \rangle_s \langle h_1, h_2, H \rangle_h \langle N_1, N_2 \rangle_r) \land p)$ on "key set" B, iff there is some $\tau : Var \to Int$ such that $(\gamma, \tau) \models_B \exists X((o = \langle k \rangle_k \langle s \rangle_s \langle h_1, h_2, H \rangle_h \langle N_1, N_2 \rangle_r) \land p)$ which is equivalent that

- there exists some θ_{τ} : $Var \to Int$ with $\theta_{\tau} \upharpoonright_{Var/X} = \tau \upharpoonright_{Var/X};$
- $s_c \upharpoonright_B = \theta_\tau(s) \upharpoonright_B;$
- $h_{1c} = h_1$ and $N_{1c} = N_1;$
- $\langle s_c \rangle_s \langle h_{1c} \rangle_h \langle \{\} \rangle_r \models p.$

Definition 2.3. Concurrent matching logic(CML) assertion has the form $\Gamma \vdash_{A,B} \exists X((o = \langle k \rangle_k \langle s \rangle_s \langle h_1, h_2, H \rangle_h \langle N_1, N_2 \rangle_r) \land p) \Downarrow \exists X'((o = \langle \cdot \rangle_k \langle s' \rangle_s \langle h_1', h_2', H' \rangle_h \langle N_1', N_2' \rangle_r) \land q)$ where A is rely set; B is key set; p, q and the resource invariants in Γ , do not mention resource names. We say that an assertion is well-formed if Γ is well-formed resource context, $\mathbf{free}(p) \cup \mathbf{free}(q) \subseteq A$, $\mathbf{free}(k) \subseteq \mathbf{owned}(\Gamma) \cup A$, and $B \subseteq \mathbf{dom}(s)$.

The following inference rules will restrict which identifiers k can write and read. k can only read and write the identifier protected by resource r inside a critical region of r. For the sake of convenience in writing, $\langle k \rangle_k \langle s \rangle_s \langle h_1, h_2, H \rangle_h \langle N_1, N_2 \rangle_r \wedge p$ is abbreviated as $\langle k \rangle_k LS \wedge p$ where $LS = \langle s \rangle_s \langle h_1, h_2, H \rangle_h \langle N_1, N_2 \rangle_r$. We also use the following notation convention:

Inference rules.

• SKIP

$$\Gamma \vdash_{A,B} \exists X(o = <\mathbf{skip}>_k LS \land p) \Downarrow \exists X(o = <\cdot>_k LS \land p)$$

if $\mathbf{free}(p) \subseteq A$ • ASSIGNMENT

 $\frac{\Gamma \vdash_{A,B} \exists X(o = <\rho_e >_k LS \land p[e/i]) \Downarrow \exists X(o = <v >_k LS \land p[e/i])}{\Gamma \vdash_{A,B} \exists X(o = <i := e >_k LS \land p[e/i]) \Downarrow \exists X(o = <\cdot >_k LS[s \mid i \mapsto v] \land p)}$ if $i \notin \mathbf{owned}(\Gamma)$ and $\mathbf{free}(e) \subseteq A$

• SEQUENCE

$$\Gamma \vdash_{A_1,B} \exists X_1(o = \langle k_1 \rangle_k LS_1 \land p_1) \Downarrow \exists X_2(o = \langle \cdot \rangle_k LS_2 \land p_2)$$

$$\Gamma \vdash_{A_2,B} \exists X_2(o = \langle k_2 \rangle_k LS_2 \land p_2) \Downarrow \exists X_3(o = \langle \cdot \rangle_k LS_3 \land p_3)$$

$$\overline{\Gamma \vdash_{A_1 \cup A_2,B} \exists X_1(o = \langle k_1; k_2 \rangle_k LS_1 \land p_1) \Downarrow \exists X_3(o = \langle \cdot \rangle_k LS_3 \land p_3)}$$

where $LS_1 = \langle s \rangle_s \langle h_1, h_2, H \rangle_h \langle N_1, N_2 \rangle_r$, $LS_2 = \langle s' \rangle_s \langle h'_1, h_2, H' \rangle_h \langle N'_1, N_2 \rangle_r$, $LS_3 = \langle s'' \rangle_s \langle h''_1, h_2, H'' \rangle_h \langle N''_1, N_2 \rangle_r$

• CONDITIONAL

$$\Gamma \vdash_{A,B} \exists X_1(o = \langle k_1 \rangle_k LS_1 \land p \land b) \Downarrow \exists X_2(o = \langle \cdot \rangle_k LS_2 \land q)$$

$$\Gamma \vdash_{A,B} \exists X_1(o = \langle k_2 \rangle_k LS_1 \land p \land \neg b) \Downarrow \exists X_2(o = \langle \cdot \rangle_k LS_2 \land q)$$

$$\overline{\Gamma \vdash_{A,B} \exists X_1(o = \langle \mathbf{if} \ b \ \mathbf{then} \ k_1 \ \mathbf{else} \ k_2 \rangle_k LS_1 \land p) \Downarrow \exists X_2(o = \langle \cdot \rangle_k LS_2 \land q) }$$

$$\text{where } LS_1 = \langle s \rangle_s \langle h_1, h_2, H \rangle_h \langle N_1, N_2 \rangle_r, \ LS_2 = \langle s' \rangle_s \langle h'_1, h_2, H' \rangle_h \langle N'_1, N_2 \rangle_r$$

$$\bullet \text{ LOOP}$$

$$\frac{\Gamma \vdash_{A,B} \exists X (o = \langle k \rangle_k LS \land p \land b) \Downarrow \exists X (o = \langle \cdot \rangle_k LS \land p)}{\Gamma \vdash_{A,B} \exists X (o = \langle \cdot \rangle_k LS \land p) \Downarrow \exists X (o = \langle \cdot \rangle_k LS \land p \land \neg b)}$$

• PARALLEL

$$\Gamma \vdash_{A_1,B_1} \exists X_1(o = \langle k_1 \rangle_k LS_1 \land p_1) \Downarrow \exists X_2(o = \langle \cdot \rangle_k LS'_1 \land q_1)$$

$$\Gamma \vdash_{A_2,B_2} \exists X_1(o = \langle k_2 \rangle_k LS_2 \land p_2) \Downarrow \exists X_2(o = \langle \cdot \rangle_k LS'_2 \land q_2)$$

 $\overline{\Gamma \vdash_{A_1 \cup A_2, B_1 \cup B_2} \exists X_1(o = \langle k_1 \parallel k_2 \rangle_k LS \land (p_1 * p_2))} \Downarrow \exists X_2(o = \langle \cdot \rangle_k LS_f \land (q_1 * q_2))$ where $LS = \langle s \rangle_s \langle h_1 \cdot h_2, h_3, H \rangle_h \langle N_1 \cup N_2, N_3 \rangle_r , LS_1 = \langle s \rangle_s \langle h_1, h_2 \cdot h_3, H \rangle_h \langle h_1 \rangle_r \rangle_r \langle h_1 \wedge h_2 \wedge h_2 \wedge h_1 \wedge h_2 \wedge h_2 \wedge h_2 \wedge h_1 \wedge h_2 \wedge h$

 $N_{1}, N_{2} \cup N_{3} >_{r}, LS'_{1} = \langle s' \rangle_{s} \langle h'_{1}, h'_{2} \cdot h'_{3}, H' \rangle_{h} \langle N'_{1}, N'_{2} \cup N'_{3} \rangle_{r}, LS_{2} = \langle s \rangle_{s} \langle h_{2}, h_{1} \cdot h_{3}, H \rangle_{h} \langle N_{2}, N_{1} \cup N_{3} \rangle_{r}, LS'_{2} = \langle s' \rangle_{s} \langle h'_{2}, h'_{1} \cdot h'_{3}, H' \rangle_{h} \langle N'_{2}, N'_{1} \cup N'_{3} \rangle_{r}, LS_{f} = \langle s' \rangle_{s} \langle h'_{1} \cdot h'_{2}, h'_{3}, H' \rangle_{h} \langle N'_{1} \cup N'_{2}, N'_{3} \rangle_{r} \text{ and } \mathbf{mod}(k_{1}) \cap A_{2} = \mathbf{mod}(k_{1}) \cap B_{2} = \mathbf{mod}(k_{2}) \cap A_{1} = \mathbf{mod}(k_{2}) \cap B_{1} = \emptyset \text{ and } N_{1} \cap N_{2} = \emptyset$

• ENVIRONMENT MOVES

$$\frac{\Gamma \vdash_{A_2,B_2} \exists X(o = \langle k_2 \rangle_k LS_2 \land p_2) \Downarrow \exists X'(o = \langle \cdot \rangle_k LS'_2 \land q_2)}{\Gamma \vdash_{A_1,B_1} \exists X'(o = \langle k_1 \rangle_k LS_1 \land p_1) \Downarrow \exists X'(o = \langle k_1 \rangle_k LS'_1 \land p_1)}$$

where $LS_1 = \langle s \rangle_s \langle h_1, h_2, H \rangle_h \langle N_1, N_2 \rangle_r$, $LS'_1 = \langle s' \rangle_s \langle h_1, h'_2, H' \rangle_h \langle N_1, N'_2 \rangle_r$, $LS_2 = \langle s \rangle_s \langle h_2, h_1, H \rangle_h \langle N_2, N_1 \rangle_r$, $LS'_2 = \langle s' \rangle_s \langle h'_2, h_1, H' \rangle_h \langle N'_2, N_1 \rangle_r$ and writes $(k_2) \cap A_1 =$ writes $(k_2) \cap B_1 = \emptyset$

• REGION

 $\begin{array}{l} \Gamma \vdash_{A \cup Y,B} \exists X(o = <k >_k LS_1 \land ((p \land b) \ast R)) \Downarrow \exists X'(o = < \cdot >_k LS_2 \land (q \ast R)) \\ \hline \Gamma, r(Y) : R \vdash_{A,B} \exists X(o = < \mathbf{with} \ r \ \mathbf{when} \ b \ \mathbf{do} \ k >_k LS_1 \land p) \Downarrow \exists X'(o = < \cdot >_k LS_2 \land q) \\ \text{where } LS_1 = <s >_s < h_1, h_2, H >_h < N_1, N_2 >_r, \ LS_2 = <s' >_s < h'_1, h'_2, H' >_h < N'_1, N'_2 >_r \\ \bullet \ \text{RESOURCE} \end{array}$

$$\frac{\Gamma, r(Y) : R \vdash_{A,B} \exists X(o = <\!\!k\!\!>_k LS'_1 \land p) \Downarrow \exists X'(o = <\!\!\cdot\!\!>_k LS'_2 \land q)}{\Gamma \vdash_{A \cup Y,B} \exists X(o = <\!\!\mathbf{resource} \ r \ \mathbf{in} \ k\!\!>_k LS_1 \land (p \ast R)) \Downarrow \exists X'(o = <\!\!\cdot\!\!>_k LS_2 \land (q \ast R))}$$

where $LS_1 = \langle s \rangle_s \langle h_1 \cdot h, h_2, H \rangle_h \langle N_1, N_2 \rangle_r$, $LS_2 = \langle s' \rangle_s \langle h'_1 \cdot h', h'_2, H' \rangle_h \langle N'_1, N'_2 \rangle_r$, $LS'_1 = \langle s \rangle_s \langle h_1, h_2, H \cdot h \rangle_h \langle N_1, N_2 \rangle_r$, $LS'_2 = \langle s' \rangle_s \langle h'_1, h'_2, H' \cdot h' \rangle_h \langle N'_1, N'_2 \rangle_r$.

• LOOKUP

$$\begin{split} & \Gamma \vdash_{A,B} \exists X(o = <\rho_e >_k LS \land p) \Downarrow \exists X(o = <l >_k LS \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <[l] = v >_k LS \land p) \Downarrow \exists X(o = <v >_k LS \land p) \\ & \overline{\Gamma \vdash_{A,B} \exists X(o = <i := [e] >_k LS \land p[v/i]) \Downarrow \exists X(o = <\cdot >_k LS[s \mid i \mapsto v] \land p)} \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] >_k LS \land p[v/i]) \Downarrow \exists X(o = <\cdot >_k LS[s \mid i \mapsto v] \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] >_k LS \land p[v/i]) \Downarrow \exists X(o = <\cdot >_k LS[s \mid i \mapsto v] \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] >_k LS \land p[v/i]) \Downarrow \exists X(o = <\cdot >_k LS[s \mid i \mapsto v] \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] >_k LS \land p[v/i]) \Downarrow \exists X(o = <\cdot >_k LS \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] >_k LS \land p[v/i]) \Downarrow \exists X(o = <\cdot >_k LS \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] >_k LS \land p[v/i]) \Downarrow \exists X(o = <\cdot >_k LS \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] >_k LS \land p[v/i]) \Downarrow \exists X(o = <\cdot >_k LS \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] >_k LS \land p[v/i]) \Downarrow \exists X(o = <\cdot >_k LS \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] >_k LS \land p[v/i]) \Downarrow \exists X(o = <\cdot >_k LS \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] \land p \land p \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] \land p \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] \land p \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] \land p \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] \land p \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] \land p \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] \land p \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] \land p \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] \land p \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] \land p \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] \land p \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] \land p \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] \land p \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] \land p \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] \land p \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] \land p \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] \land p \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] \land p \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] \land p \land p \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] \land p \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] \land p \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] \land p \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] \land p \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] \land p \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] \land p \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] \land p \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <i := [e] \land p \land p) \\ & \Gamma \vdash_{A$$

- if $i \notin \mathbf{owned}(\Gamma)$ and $\mathbf{free}(e) \subseteq A$
- UPDATE

$$\begin{split} & \Gamma \vdash_{A,B} \exists X(o = <\rho_e >_k LS \land p) \Downarrow \exists X(o = _k LS \land p) \\ & \Gamma \vdash_{A,B} \exists X(o = <\rho_{e'} >_k LS \land p) \Downarrow \exists X(o = _k LS \land p) \\ & \overline{\Gamma \vdash_{A,B} \exists X(o = <[e] := e' >_k LS \land p) \Downarrow \exists X(o = <\cdot >_k LS[h_1 \mid l \mapsto v] \land p)} \end{split}$$

• ALLOCATION

 $\overline{\Gamma \vdash_{A,B} \exists X(o = <\mathbf{alloc}(l, [v_0, \cdots, v_n]) >_k LS \land p) \Downarrow \exists X(o = <l >_k LS[h_1 \mid l \mapsto v_0, \cdots, l + n \mapsto v_n] \land p)}$ • DISPOSAL

$$\frac{\Gamma \vdash_{A,B} \exists X(o = <\rho_e >_k LS \land p) \Downarrow \exists X(o = _k LS \land p)}{\Gamma \vdash_{A,B} \exists X(o = <\mathbf{dispose} \ e >_k LS \land p) \Downarrow \exists X(o = <\cdot >_k LS \land p)}$$

• FRAME

$$\frac{\Gamma \vdash_{A,B} \exists X(o = \langle k \rangle_k \ LS_1 \land p) \Downarrow \exists X'(o = \langle \cdot \rangle_k \ LS_2 \land q)}{\Gamma \vdash_{A \cup \mathbf{free}(R),B} \exists X(o = \langle k \rangle_k \ LS_1 \land (p \ast R)) \Downarrow \exists X'(o = \langle \cdot \rangle_k \ LS_2 \land (q \ast R))}$$

where $LS_1 = \langle s \rangle_s \langle h_1, h_2, H \rangle_h \langle N_1, N_2 \rangle_r$, $LS_2 = \langle s' \rangle_s \langle h'_1, h'_2, H' \rangle_h \langle N'_1, N'_2 \rangle_r$ and

- $\mathbf{mod}(c) \cap \mathbf{free}(R) = \emptyset$
- CONSEQUENCE

$$\frac{\Gamma \vdash_{A,B} \exists X(o = _k LS_1 \land p) \Downarrow \exists X'(o = <\cdot >_k LS_2 \land q)}{\Gamma \vdash_{A',B} \exists X(o = _k LS_1 \land p') \Downarrow \exists X'(o = <\cdot >_k LS_2 \land q')}$$

where $LS_1 = \langle s \rangle_s \langle h_1, h_2, H \rangle_h \langle N_1, N_2 \rangle_r$, $LS_2 = \langle s' \rangle_s \langle h'_1, h'_2, H' \rangle_h \langle N'_1, N'_2 \rangle_r$ and $A \subseteq A', \exists X(o = \langle k \rangle_k LS_1 \land p') \Rightarrow \exists X(o = \langle k \rangle_k LS_1 \land p), \exists X'(o = \langle \cdot \rangle_k LS_2 \land q) \Rightarrow \exists X'(o = \langle \cdot \rangle_k LS_2 \land q')$

• AUXILIARY

$$\frac{\Gamma \vdash_{A \cup Y, B \cup Y} \exists X(o = _k LS_1 \land p) \Downarrow \exists X'(o = <\cdot >_k LS_2 \land q)}{\Gamma \vdash_{A,B} \exists X(o = _k LS_1[s \setminus Y] \land p) \Downarrow \exists X'(o = <\cdot >_k LS_2[s \setminus Y] \land q)}$$

where $LS_1 = \langle s \rangle_s \langle h_1, h_2, H \rangle_h \langle N_1, N_2 \rangle_r$, $LS_2 = \langle s' \rangle_s \langle h'_1, h'_2, H' \rangle_h \langle N'_1, N'_2 \rangle_r$ if Y is a auxiliary for $k, Y \cap (\mathbf{free}(p) \cup \mathbf{free}(q)) = \emptyset, Y \cap \mathbf{owned}(\Gamma) = \emptyset$

Examples. We now discuss some example programs and assertions, to illustrate the way the inference rules work.

(1) The rely set

The assertions

(a) $r(\{a,x\}): x = a \land emp \vdash_{\{a,t\},\{x,t\}} \exists \{t_v, x_v, a_v\} (o = < with r when true do t := x >_k < x \mapsto x_v, t \mapsto t_v, a \mapsto a_v >_s < \cdot >_h < \cdot >_r \land emp) \Downarrow \exists \{t_v, x_v, a_v\} (o = < \cdot >_k < x \mapsto x_v, t \mapsto x_v, a \mapsto a_v >_s < \cdot >_h < \cdot >_r \land t = a \land emp)$

(b) $r(\{a,x\}): x = a \land emp \vdash_{\{a,t\},\{x,t\}} \exists \{t_v, x_v, a_v\}(o = < with r when true do x := t>_k < x \mapsto x_v, t \mapsto x_v, a \mapsto a_v>_s < \cdot>_h < \cdot>_r \land t = a \land emp) \Downarrow \exists \{t_v, x_v, a_v\}(o = < \cdot>_k < x \mapsto x_v, t \mapsto x_v, a \mapsto a_v>_s < \cdot>_h < \cdot>_r \land emp)$

are valid and well-formed. Each is also provable from ASSIGNMENT, CONSEQUENCE and REGION.

Let c_1 be with r when true do t := x; with r when true do x := t. The assertion (c) $r(\{a,x\}) : x = a \land \operatorname{emp} \vdash_{\{a,t\},\{x,t\}} \exists \{t_v, x_v, a_v\} (o = \langle c_1 \rangle_k \langle x \mapsto x_v, t \mapsto t_v, a \mapsto a_v \rangle_s \langle \cdot \rangle_h \langle \cdot \rangle_r \land \operatorname{emp}) \Downarrow \exists \{t_v, x_v, a_v\} (o = \langle \cdot \rangle_k \langle x \mapsto x_v, t \mapsto x_v, a \mapsto a_v \rangle_s \langle \cdot \rangle_h \langle \cdot \rangle_r \land \operatorname{emp})$

is valid, well-formed, and provable from (a) and (b) using SEQUENCE. Let c_1 be as above and let c_2 be with r when true do (x := x + 1; a := a + 1). The assertion

(d) $r(\{a,x\}): x = a \land emp \vdash_{A,\{x,t,a\}} \exists \{t_v, x_v, a_v\} (o = \langle c_1 \parallel c_2 \rangle_k \langle x \mapsto x_v, t \mapsto t_v, a \mapsto a_v \rangle_s \langle \cdot \rangle_h \langle \cdot \rangle_r \land emp) \Downarrow \exists \{t'_v, x'_v, a'_v\} (o = \langle \cdot \rangle_k \langle x \mapsto x'_v, t \mapsto t'_v, a \mapsto a'_v \rangle_s \langle \cdot \rangle_h \langle \cdot \rangle_r \land emp)$

is not valid because of executing $c_1 \parallel c_2$ without interference does not necessarily preserve equality of x and a. Moreover, the assertion (d) is not provable. Suppose

$$\begin{split} r(\{a,x\}) &: x = a \land \mathbf{emp} \vdash_{A_1,B_1} \exists \{t_v, x_v, a_v\} (o = <c_1 >_k < x \mapsto x_v, t \mapsto t_v, a \mapsto a_v >_s < \\ &:>_h < \cdot >_r \land \mathbf{emp}) \Downarrow \exists \{t'_v, x'_v, a'_v\} (o = <\cdot >_k < x \mapsto x'_v, t \mapsto t'_v, a \mapsto a'_v >_s < \cdot >_h < \cdot >_r \land \mathbf{emp}) \\ r(\{a,x\}) &: x = a \land \mathbf{emp} \vdash_{A_2,B_2} \exists \{t_v, x_v, a_v\} (o = <c_2 >_k < x \mapsto x_v, t \mapsto t_v, a \mapsto a_v >_s < \\ &:>_h < \cdot >_r \land \mathbf{emp}) \Downarrow \exists \{t'_v, x'_v, a'_v\} (o = <\cdot >_k < x \mapsto x'_v, t \mapsto t'_v, a \mapsto a'_v >_s < \cdot >_h < \cdot >_r \land \mathbf{emp}) \\ A_1 \text{ would have to contain } x \text{ or } a, \text{ but } c_2 \text{ modifies both of these variables, so the side condition on the PARALLEL rule would fail. This examples is the counterexample found by Ian Wehrman and Josh Berdine showing that, without the rely set, the assertion (d) is is provable in the original concurrent separation logic but not valid. \end{split}$$

(2) Auxiliary variable

 $r(\{x, a, b\}) : x = a + b \land \mathbf{emp} \vdash_{\{a\}, \{a\}} \exists \{x_v, a_v, b_v\} (o = <\mathbf{with} \ r \ \mathbf{when} \ true \ \mathbf{do} \ x := x + 1; a := a + 1 >_k < x \mapsto x_v, a \mapsto a_v, b \mapsto b_v >_s <\cdot >_h <\cdot >_r \ \land a = 0 \land \mathbf{emp}) \Downarrow \exists \{x_v, a_v, b_v\} (o = <\cdot >_k < x \mapsto x_v + 2, a \mapsto a_v + 1, b \mapsto b_v + 1 >_s <\cdot >_h <\cdot >_r \land a = 1 \land \mathbf{emp})$ is valid, and provable from REGION and ENVIRONMENT MOVE, because

 $\vdash_{\{x,a,b\},\{a\}} \exists \{x_v, a_v, b_v\} (o = <x := x+1; a := a+1>_k < x \mapsto x_v, a \mapsto a_v, b \mapsto b_v >_s <\cdot>_h < \cdot>_r \land (x = a + b \land \mathbf{emp}) \ast (a = 0 \land \mathbf{emp})) \Downarrow \exists \{x_v, a_v, b_v\} (o = <\cdot>_k < x \mapsto x_v + 1, a \mapsto a_v + 1, b \mapsto b_v >_s <\cdot>_h <\cdot>_r \land (x = a + b \land \mathbf{emp}) \ast (a = 1 \land \mathbf{emp}))$ is provable from ASSIGNMENT, SEQUENCE and CONSEQUENCE.

Similarly we can prove

 $r(\{x,a,b\}): x = a + b \land \operatorname{emp} \vdash_{\{b\},\{b\}} \exists \{x_v, a_v, b_v\} (o = < \operatorname{with} r \text{ when } true \text{ do } x :=$

 $\begin{aligned} x + 1; b &:= b + 1 >_k < x \mapsto x_v, a \mapsto a_v, b \mapsto b_v >_s < \cdot >_h < \cdot >_r \land b = 0 \land \mathbf{emp}) \Downarrow \\ \exists \{x_v, a_v, b_v\} (o = <\cdot >_k < x \mapsto x_v + 2, a \mapsto a_v + 1, b \mapsto b_v + 1 >_s <\cdot >_h <\cdot >_r \land b = 1 \land \mathbf{emp}) \\ \text{Using PARALLEL and CONSEQUENCE we can then derive} \\ r(\{x, a, b\}) : x = a + b \land \mathbf{emp} \vdash_{\{a, b\}, \{a, b\}} \exists \{x_v, a_v, b_v\} (o = <(\mathbf{with } r \mathbf{ when } true \mathbf{ do } x := x + 1; a := a + 1) \parallel (\mathbf{with } r \mathbf{ when } true \mathbf{ do } x := x + 1; b := b + 1) >_k < x \mapsto x_v, a \mapsto a_v, b \mapsto b_v >_s <\cdot >_h <\cdot >_r \land a = 0 \land b = 0 \land \mathbf{emp}) \Downarrow \exists \{x_v, a_v, b_v\} (o = <\cdot >_k < x \mapsto x_v + 2, a \mapsto a_v + 1, b \mapsto b_v + 1 >_s <\cdot >_h <\cdot >_r \land a = 1 \land b = 1 \land \mathbf{emp}) \\ \text{which is also valid. Using RESOURCE and CONSEQUENCE we then obtain} \\ \vdash_{\{x,a,b\},\{a,b\}} \exists \{x_v, a_v, b_v\} (o = <\mathbf{resource } r \mathbf{ in } ((\mathbf{with } r \mathbf{ when } true \mathbf{ do } x := x + 1; a := a + 1) \parallel (\mathbf{with } r \mathbf{ when } true \mathbf{ do } x := x + 1; b := b + 1)) >_k < x \mapsto x_v, a \mapsto a_v, b \mapsto b_v >_s <\cdot a_v + 1; a := a + 1) \parallel (\mathbf{with } r \mathbf{ when } true \mathbf{ do } x := x + 1; b := b + 1) >_k < x \mapsto x_v, a \mapsto a_v, b \mapsto b_v >_s <\cdot a_v + 1; a := a + 1) \parallel (\mathbf{with } r \mathbf{ when } true \mathbf{ do } x := x + 1; b := b + 1) >_k < x \mapsto x_v, a \mapsto a_v, b \mapsto b_v >_s <\cdot a_v + 1; a := a + 1) \parallel (\mathbf{with } r \mathbf{ when } true \mathbf{ do } x := x + 1; b := b + 1) >_k < x \mapsto x_v, a \mapsto a_v, b \mapsto b_v >_s <\cdot a_v + 1; a := a + 1) \parallel (\mathbf{with } r \mathbf{ when } true \mathbf{ do } x := x + 1; b := b + 1) >_k < x \mapsto x_v, a \mapsto a_v, b \mapsto b_v >_s <\cdot a_v < a_v + 1; a := a + 1) \parallel (\mathbf{with } r \mathbf{ when } true \mathbf{ do } x := x + 1; b := b + 1) >_k < x \mapsto x_v, a \mapsto a_v, b \mapsto b_v >_s <\cdot a_v < a_v >_s < a_v >_s <a + 1 > a_v < a_v >_s <a + 1 > a_v < a_v >_s <a + 1 > a_v < a_v <a + 1 > a_v < a_v >_s <a + 1 > a_v <a + 1 > a_v <\mathbf{ do } x <\mathbf{ do } <\mathbf{ do } <\mathbf{ do } x <\mathbf{ do } <a + 1 > a_v <a + 1 > a_v <a + 1 > a_v <a + 1 >$

 $a+1) \parallel (\textbf{with } r \textbf{ when } true \textbf{ do } x := x+1; b := b+1)) >_k < x \mapsto x_v, a \mapsto a_v, b \mapsto b_v >_s < \cdot >_h < \cdot >_r \land x = a + b \land a = 0 \land b = 0 \land \textbf{ emp}) \Downarrow \exists \{x_v, a_v, b_v\} (o = < \cdot >_k < x \mapsto x_v + 2, a \mapsto a_v + 1, b \mapsto b_v + 1 >_s < \cdot >_h < \cdot >_r \land x = a + b \land a = 1 \land b = 1 \land \textbf{ emp})$

By ASSIGNMENT, SEQUENCE and CONSEQUENCE we then have $\vdash_{\{x,a,b\},\{a,b\}} \exists \{x_v, a_v, b_v\} (o = <a := 0 ; b := 0; \text{ resource } r \text{ in } ((\text{with } r \text{ when } true \text{ do} x := x + 1; a := a + 1) \parallel (\text{with } r \text{ when } true \text{ do} x := x + 1; b := b + 1)) >_k < x \mapsto x_v, a \mapsto a_v, b \mapsto b_v >_s <\cdot >_h <\cdot >_r \land x = 0 \land \text{emp}) \Downarrow \exists \{x_v, a_v, b_v\} (o = <\cdot >_k < x \mapsto x_v + 2, a \mapsto a_v + 1, b \mapsto b_v + 1 >_s <\cdot >_h <\cdot >_r \land x = 2 \land \text{emp})$

Finally, since a, b is an auxiliary variable set for this program, and $\{a, b\} \cap \{x\} = \emptyset$ and $\{a, b\} \cap \emptyset = \emptyset$, we can use the AUXILIARY rule to obtain

 $\vdash_{\{x\},\{\}} \exists \{x_v, a_v, b_v\} (o = < \text{resource } r \text{ in } ((\text{with } r \text{ when } true \text{ do } x := x + 1) \parallel (\text{with } r \text{ when } true \text{ do } x := x + 1)) >_k < x \mapsto x_v >_s < \cdot >_h < \cdot >_r \land x = 0 \land \text{emp}) \Downarrow \exists \{x_v, a_v, b_v\} (o = < \cdot >_k < x \mapsto x_v + 2 >_s < \cdot >_h < \cdot >_r \land x = 2 \land \text{emp})$

3. Semantic

Local state. From the perspective of the interaction between a process and its environment, A state $\langle s \rangle_s \langle h \rangle_h \langle N \rangle_r$ can be expressed as $\langle s \rangle_s \langle h_1, h_2, H \rangle_h \langle N_1, N_2 \rangle_r$, where h_1, N_1 represents part of the heap and part of the resource owned by the process, h_2, N_2 is owned by the environment, and H represents the remaining heap and satisfies the resource invariants of the currently available resources. Obviously, $h = h_1 \cdot h_2 \cdot H$ and $N = N_1 \cup N_2$. For a well-formed resource context Γ and a set of resource names N, let $\Gamma \upharpoonright N = \{r(X) : R \in \Gamma | r \in N\}$ and $\Gamma \setminus N = \{r(X) : R \in \Gamma | r \notin N\}$.

Definition 3.1. We say $\langle s \rangle_s \langle h_1, h_2, H \rangle_h \langle N_1, N_2 \rangle_r$ is a local state for Γ if:

- $h_1 \perp h_2$, $h_1 \perp H$ and $h_2 \perp H$;
- $N_1 \cap N_2 = \emptyset$, s(r) = 0 for $r \in N_1 \cup N_2$, s(r) = 1 otherwise;
- $<\!\!s\!\!>_s<\!\!H\!\!>_h<\!\!N_1, N_2\!\!>_r\models \mathbf{inv}(\Gamma \setminus (N_1 \cup N_2))$

Let Σ_{Γ} be the set of local states for Γ .

Semantic rules for Actions. Let $\langle s \rangle_s \langle h_1, h_2, H \rangle_h \langle N_1, N_2 \rangle_r \in \Sigma_{\Gamma}$, A is rely set, B is key set, the semantic rules for actions are as follows:

- $<\!\delta\!\!>_k<\!\!s\!\!>_s<\!\!h_1,h_2,H\!\!>_h<\!\!N_1,N_2\!\!>_r \xrightarrow{\Gamma,A,B}<\!\!\cdot\!\!>_k<\!\!s\!\!>_s<\!\!h_1,h_2,H\!\!>_h<\!\!N_1,N_2\!\!>_r$
- $\langle i = v \rangle_k \langle s \rangle_s \langle h_1, h_2, H \rangle_h \langle N_1, N_2 \rangle_r \xrightarrow{\Gamma, A, B} \langle v \rangle_k \langle s \rangle_s \langle h_1, h_2, H \rangle_h \langle N_1, N_2 \rangle_r$ if s(i) = v and $i \in \mathbf{owend}(\Gamma \upharpoonright N_1) \cup A$
- $\langle i = v \rangle_k \langle s \rangle_s \langle h_1, h_2, H \rangle_h \langle N_1, N_2 \rangle_r \xrightarrow{\Gamma, A, B} \text{abort} \quad \text{if } i \notin \text{owend}(\Gamma \upharpoonright N_1) \cup A$
- $< [l] = v >_k < s >_s < h_1, h_2, H >_h < N_1, N_2 >_r \xrightarrow{\Gamma, A, B} < v >_k < s >_s < h_1, h_2, H >_h < N_1, N_2 >_r$ if $h_1(l) = v$

•
$$<[l] = v >_k < s >_s < h_1, h_2, H >_h < N_1, N_2 >_r \xrightarrow{\Gamma, A, B}$$
 abort if $l \notin \mathbf{dom}(h_1)$

• $\langle i := v \rangle_k \langle s \rangle_s \langle h_1, h_2, H \rangle_h \langle N_1, N_2 \rangle_r \xrightarrow{\Gamma, A, B} \langle \cdot \rangle_k \langle [s \mid i \mapsto v] \rangle_s \langle h_1, h_2, H \rangle_h \langle N_1, N_2 \rangle_r$ if $i \notin \mathbf{owned}(\Gamma \setminus N_1)$

•
$$\langle i := v \rangle_k \langle s \rangle_s \langle h_1, h_2, H \rangle_h \langle N_1, N_2 \rangle_r \xrightarrow{} abort \text{ if } i \in owned(\Gamma \setminus N_1)$$

- $<[l] := v >_k < s >_s < h_1, h_2, H >_h < N_1, N_2 >_r \xrightarrow{\Gamma,A,B} < \cdot >_k < s >_s < [h_1 | l \mapsto v], h_2, H >_h < N_1, N_2 >_r \xrightarrow{\Gamma,A,B} < \cdot >_k < s >_s < [h_1 | l \mapsto v], h_2, H >_h < N_1, N_2 >_r \xrightarrow{\Gamma,A,B} < \cdot >_k < s >_s < [h_1 | l \mapsto v], h_2, H >_h < N_1, N_2 >_r \xrightarrow{\Gamma,A,B} < \cdot >_k < s >_s < [h_1 | l \mapsto v], h_2, H >_h < N_1, N_2 >_r \xrightarrow{\Gamma,A,B} < \cdot >_k < s >_s < [h_1 | l \mapsto v], h_2, H >_h < N_1, N_2 >_r \xrightarrow{\Gamma,A,B} < \cdot >_k < s >_s < [h_1 | l \mapsto v], h_2, H >_h < N_1, N_2 >_r \xrightarrow{\Gamma,A,B} < \cdot >_k < s >_s < [h_1 | l \mapsto v], h_2, H >_h < N_1, N_2 >_r \xrightarrow{\Gamma,A,B} < \cdot >_k < s >_s < [h_1 | l \mapsto v], h_2, H >_h < N_1, N_2 >_r \xrightarrow{\Gamma,A,B} < \cdot >_k < s >_s < [h_1 | l \mapsto v], h_2, H >_h < N_1, N_2 >_r \xrightarrow{\Gamma,A,B} < \cdot >_k < s >_s < [h_1 | l \mapsto v], h_2, H >_h < N_1, N_2 >_r \xrightarrow{\Gamma,A,B} < \cdot >_k < s >_s < [h_1 | l \mapsto v], h_2, H >_h < N_1, N_2 >_r \xrightarrow{\Gamma,A,B} < \cdot >_k < s >_s < [h_1 | l \mapsto v], h_2, H >_h < N_1, N_2 >_r \xrightarrow{\Gamma,A,B} < \cdot >_k < s >_s < [h_1 | l \mapsto v], h_2, H >_h < N_1, N_2 >_r \xrightarrow{\Gamma,A,B} < \cdot >_k < s >_s < [h_1 | l \mapsto v], h_2, H >_h < N_1, h_2 >_r \xrightarrow{\Gamma,A,B} < \cdot >_k < s >_s < [h_1 | l \mapsto v], h_2, H >_h < N_1, h_2 >_r \xrightarrow{\Gamma,A,B} < \cdot >_k < s >_s < [h_1 | l \mapsto v], h_2, H >_h < N_1, h_2 >_r \xrightarrow{\Gamma,A,B} < \cdot >_k < s >_s < [h_1 | l \mapsto v], h_2 >_r < \dots >_k < s >_s < [h_1 | l \mapsto v], h_2 >_r < \dots >_k < \dots <_k < \dots >_k < \dots >_k$
- $<[l] := v >_k < s >_s < h_1, h_2, H >_h < N_1, N_2 >_r \xrightarrow{\Gamma, A, B} \text{ abort } \text{ if } l \notin \text{dom}(h_1)$
- <**alloc** $(l, [v_0, \cdots, v_n]) >_k < s >_s < h_1, h_2, H >_h < N_1, N_2 >_r \xrightarrow{\Gamma, A, B} < l >_k < s >_s < h'_1, h_2, H >_h < N_1, N_2 >_r$ if $\{l, l+1, \cdots, l+n\} \cap$ **dom** $(h_1 \cdot h_2 \cdot H) = \emptyset$ and $h'_1 = [h_1 \mid l \mapsto v_0, \cdots, l+n \mapsto v_n]$
- $N_1, N_2 >_r \text{ if } \{l, l+1, \cdots, l+n\} \cap \mathbf{dom}(h_1 \cdot h_2 \cdot H) = \emptyset \text{ and } h'_1 = [h_1 \mid l \mapsto v_0, \cdots, l+n \mapsto v_n]$ $\bullet < \mathbf{dispose} \mid l >_k < s >_s < h_1, h_2, H >_h < N_1, N_2 >_r \xrightarrow[\Gamma, A, B]{} < \cdot >_k < s >_s < h_1 \setminus l, h_2, H >_h < N_1, N_2 >_r \text{ if } l \in \mathbf{dom}(h_1)$
- <dispose $l>_k<$ $s>_s<$ $h_1, h_2, H>_h<$ $N_1, N_2>_r \xrightarrow{\Gamma, A, B}$ abort if $l \notin$ dom (h_1)
- <try $r>_k<$ $s>_s<$ $h_1, h_2, H>_h<$ $N_1, N_2>_r \xrightarrow{\Gamma, A, B}<$ $\cdot>_k<$ $s>_s<$ $h_1, h_2, H>_h<$ $N_1, N_2>_r$ if $r \in N_1 \cup N_2$
- $\langle \operatorname{acq} r \rangle_k \langle s \rangle_s \langle h_1, h_2, H \rangle_h \langle N_1, N_2 \rangle_r \xrightarrow{\Gamma, A, B} \langle \cdot \rangle_k \langle [s \mid r \mapsto 0] \rangle_s \langle h_1 \cdot h_r, h_2, H h_r \rangle_h \langle N_1 \cup \{r\}, N_2 \rangle_r$ if $r \notin N_1 \cup N_2$, $h_r \subseteq H$ and $\langle s \rangle_s \langle h_r \rangle_h \langle \{\} \rangle_r \models \operatorname{inv}(\Gamma \upharpoonright r)$
- $\langle \operatorname{rel} r \rangle_k \langle s \rangle_s \langle h_1, h_2, H \rangle_h \langle N_1, N_2 \rangle_r \xrightarrow{\Gamma, A, B} \operatorname{abort} \quad \text{if } \forall h_r \subseteq h_1 \quad \langle s \rangle_s \langle h_r \rangle_h \langle h_r$

The semantics rules describe the process's execution of action λ and its impact on the ownership of heap and resources. The execution of λ is legal only if the ownership rule is respected and the separation attribute is maintained. If the execution of λ violates the rules, an **abort** result occurs. By swapping the roles of process and environment, we gain environment moves $\rightsquigarrow_{\Gamma,A,B}$, which respects Γ and does not modify identifiers in A and B.

Definition 3.2.

 $<\lambda>_k<s>_s<h_1, h_2, H>_h< N_1, N_2>_r \rightsquigarrow_{\Gamma,A,B}<\lambda>_k<s'>_s<h_1, h'_2, H'>_h< N_1, N'_2>_r$ iff there is an action μ such that $writes(\mu) \cap A = \emptyset$ and $writes(\mu) \cap B = \emptyset$ and

$$<\!\!\mu\!\!>_k<\!\!s\!\!>_s<\!\!h_2,h_1,H\!\!>_h<\!\!N_2,N_1\!\!>_r\!\!\xrightarrow[\Gamma,A',B']\!<\!\!\cdot\!\!>_k<\!\!s'\!\!>_s<\!\!h_2',h_1,H'\!\!>_h<\!\!N_2',N_1\!\!>_r$$

We then define

$$<\!\!\lambda\!\!>_k<\!\!s\!\!>_s<\!\!h_1,h_2,H\!\!>_h<\!\!N_1,N_2\!\!>_r\xrightarrow[\Gamma,A,B]{}<\!\!\cdot\!\!>_k<\!\!s'\!\!>_s<\!\!h_1',h_2',H'\!\!>_h<\!\!N_1',N_2'\!\!>_r$$

iff

$$<\!\!\lambda\!\!>_k<\!\!s\!\!>_s<\!\!h_1,h_2,H\!\!>_h<\!\!N_1,N_2\!\!>_r\!\!\rightsquigarrow^*_{\Gamma,A',B'}<\!\!\lambda\!\!>_k<\!\!s''\!\!>_s<\!\!h_1,h_2'',H''\!\!>_h<\!\!N_1,N_2'\!\!>_r\!\!\xrightarrow{}_{\Gamma,A,B'}$$

$$<\!\!\cdot\!\!>_k<\!\!s''\!\!>_s<\!\!h_1',h_2'',H'''\!\!>_h<\!\!N_1',N_2''\!\!>_r\!\!\rightsquigarrow^*_{\Gamma,A'',B''}<\!\!\cdot\!\!>_k<\!\!s'\!\!>_s<\!\!h_1',h_2',H'\!\!>_h<\!\!N_1',N_2'\!\!>_r$$

Trace. We call a non-empty finite or infinite sequence of actions as a trace. ϵ stands for empty trace. Let *i* is an identifier, *l* is an address, *r* is a resource name, λ is an action, α, β are traces, and T, T_1, T_2 are sets of traces. $\alpha \setminus r$ means to replace all the resource actions on *r* in α with δ . $\alpha\beta$ represents the trace obtained by connecting α and β . If α is infinite, then $\alpha\beta$ is also infinite. T_1T_2 is a set of traces connected by the trace in T_1 and the trace in T_2 . $T^0 = \{\delta\}$ and $T^{n+1} = T^nT$. The semantic rules extended to the trace are as follows.

•
$$<\lambda \alpha >_k < s >_s < h_1, h_2, H >_h < N_1, N_2 >_r \xrightarrow{\Gamma, A, B} <\alpha >_k < s' >_s < h'_1, h_2, H' >_h < N'_1, N_2 >_r$$

if $<\lambda >_k < s >_s < h_1, h_2, H >_h < N_1, N_2 >_r \xrightarrow{\Gamma, A, B} <\cdot >_k < s' >_s < h'_1, h_2, H' >_h < N'_1, N_2 >_r$

•
$$<\lambda \alpha >_k < s >_s < h_1, h_2, H >_h < N_1, N_2 >_r \xrightarrow{\Gamma, A, B} <\alpha >_k < s' >_s < h'_1, h'_2, H' >_h < N'_1, N'_2 >_r$$

if $<\lambda >_k < s >_s < h_1, h_2, H >_h < N_1, N_2 >_r \xrightarrow{\Gamma, A, B} <\cdot >_k < s' >_s < h'_1, h'_2, H' >_h < N'_1, N'_2 >_r$

 $T_{[i:1]}$ is the subset of T. If $\alpha \in T_{[i:1]},$ then

$$<\!\!\alpha\!\!>_k<\!\![s\mid i\mapsto 1]\!\!>_s<\!\!h_1,h_2,H\!\!>_h<\!\!N_1,N_2\!\!>_r\!\!\xrightarrow[\Gamma,A,B]{}^*<\!\!\cdot\!\!>_k<\!\!s'\!\!>_s<\!\!h_1',h_2,H'\!\!>_h<\!\!N_1',N_2\!\!>_r$$

Semantics of expressions and commands. Let $e = i_1 + i_2$, iteratively using structure rules and semantics rules, we get

 $i_1 + i_2 = (i_1 = v_1 \frown \Box + i_2) \rightharpoonup (v_1 + i_2) \rightharpoonup (i_2 = v_2 \frown v_1 + \Box) \rightharpoonup (v_1 + v_2) \rightarrow (v_1 + I_{nt} v_2)$ If we do not express the structural rules explicitly, $i_1 + i_2$ can be simplified to

$$i_1 + i_2 = (i_1 = v_1)(i_2 = v_2) \frown (v_1 +_{Int} v_2)$$

where $(i_1 = v_1)(i_2 = v_2)$ is a trace, $(v_1 +_{Int} v_2)$ is an integer value and \uparrow a delimiter to split the trace and the integer value. In fact, K uses strictness attribute in order to avoid writing obvious structural rules. Then, the semantic of expression $e_1 + e_2$ is expressed as a trace paired with an integer value. Since the expression is pure, the only action involved

in such a trace is read action (i = v).

Let v, v_1, v_2, \ldots, v_n are integer values, $\alpha, \alpha_1, \alpha_2, \alpha_3, \rho, \rho_1, \rho_2$ are traces, l is address, λ, μ are actions, e, e_1, e_2, \ldots, e_n are integer expressions, b is boolean expression, i is identifier, $E = [e_1, e_2, \ldots, e_n]$ is list expression, $V = [v_1, v_2, \ldots, v_n]$ is list integer value and []] is the semantic function which is given by structural induction as follows.

$$\llbracket 6 \rrbracket = \delta \curvearrowright 6$$

$$\llbracket i \rrbracket = i = v \curvearrowright v$$

$$\llbracket e_1 + e_2 \rrbracket = \rho_1 \rho_2 \curvearrowright (v_1 +_{Int} v_2) \quad where \llbracket e_1 \rrbracket = \rho_1 \curvearrowright v_1 \text{ and } \llbracket e_2 \rrbracket = \rho_2 \curvearrowright v_2$$

$$\llbracket (e_1, e_2, \dots, e_i, \dots, e_n) \rrbracket = \rho_1 \dots \rho_i \dots \rho_n \curvearrowright [v_1, v_2, \dots, v_i, \dots, v_n] \quad where \llbracket e_i \rrbracket = \rho_i \curvearrowright v_i$$

Similarly,

$$\llbracket true \rrbracket = \delta \curvearrowright true$$
$$\llbracket false \rrbracket = \delta \curvearrowright false$$
$$\llbracket b \rrbracket_{true} = \rho_1 \curvearrowright true$$
$$\llbracket b \rrbracket_{false} = \rho_2 \curvearrowright false$$

The command is relatively complicated and can be expressed as a set of traces, which can be either finite or infinite.

$$\begin{bmatrix} \mathbf{skip} \end{bmatrix} = \{\delta\} \\ \begin{bmatrix} i := e \end{bmatrix} = \{\rho(i := v) \mid \llbracket e \rrbracket = \rho \land v\} \\ \llbracket i := [e] \rrbracket = \{\rho([l] = v)(i := v) \mid \llbracket e \rrbracket = \rho \land l\} \\ \llbracket [e_1] := e_2 \rrbracket = \{\rho_1 \rho_2([l] := v) \mid \llbracket e_1 \rrbracket = \rho_1 \land l \text{ and } \llbracket e_2 \rrbracket = \rho_2 \land v\} \\ \llbracket i := \mathbf{cons } E \rrbracket = \{\rho(\mathbf{alloc}(l, V))(i := l) \mid \rho \land V\} \\ \llbracket \mathbf{dispose } e \rrbracket = \{\rho(\mathbf{dispose } l) \mid \rho \land l\} \\ \llbracket k_1; k_2 \rrbracket = \llbracket k_1 \rrbracket \llbracket k_2 \rrbracket \\ \llbracket \mathbf{if } b \mathbf{ then } k_1 \mathbf{ else } k_2 \rrbracket = \llbracket b \rrbracket_{true} \llbracket k_1 \rrbracket \cup \llbracket b \rrbracket_{false} \llbracket k_2 \rrbracket \\ \llbracket \mathbf{while } b \mathbf{ do } k \rrbracket = \llbracket \mathbf{if } b \mathbf{ then } (k; \mathbf{while } b \mathbf{ do } k) \mathbf{ else skip} \rrbracket \\ \llbracket \mathbf{resource } r \mathbf{ in } k \rrbracket = \{\alpha \backslash r \mid \alpha \in \llbracket k \rrbracket_{[r:1]}\} \\ \llbracket \mathbf{with } r \mathbf{ when } b \mathbf{ do } k \rrbracket = wait^* enter \cup wait^{\omega} \\ where wait = \{\mathbf{try } r\} \cup \{(\mathbf{acq } r)\rho(\mathbf{rel } r) \mid \rho \in \llbracket b \rrbracket_{false}\} \\ and enter = \{(\mathbf{acq } r)\rho\alpha(\mathbf{rel } r) \mid \llbracket b \rrbracket_{true} and \alpha \in \llbracket k \rrbracket \} \\ \llbracket k_1 \Vert k_2 \rrbracket = \cup \{\alpha_1 \{A_1, B_1\} \Vert \{A_2, B_2\} \alpha_2 \mid \alpha_1 \in \llbracket k_1 \rrbracket and \alpha_2 \in \llbracket k_2 \rrbracket \\ and \mathbf{writes}(\alpha_1) \cap A_2 = \emptyset and \mathbf{writes}(\alpha_2) \cap B_1 = \emptyset \} \end{cases}$$

where

$$\lambda \alpha_{1\{A_1,B_1\}} \|_{\{A_2,B_2\}} \mu \alpha_2 = \{\lambda \alpha_3 \mid \alpha_3 \in \alpha_{1\{A_1,B_1\}} \|_{\{A_2,B_2\}} \mu \alpha_2\}$$

$$\cup \{\mu \alpha_3 \mid \alpha_3 \in \lambda \alpha_{1\{A_1, B_1\}} \|_{\{A_2, B_2\}} \alpha_2 \}$$
$$\cup \{ \mathbf{abort} \mid \mathbf{writes}(\lambda) \cap \mathbf{free}(\mu) \neq \emptyset \text{ or } \mathbf{writes}(\mu) \cap \mathbf{free}(\lambda) \neq \emptyset \}$$

Validity.

Definition 3.3. The well-formed assertion $\Gamma \vdash_{A,B} \exists X((o = \langle k \rangle_k \langle s \rangle_s \langle h_1, h_2, H \rangle_h \langle N_1, N_2 \rangle_r) \land p) \Downarrow \exists X'((o = \langle \cdot \rangle_k \langle s' \rangle_s \langle h'_1, h'_2, H' \rangle_h \langle N'_1, N'_2 \rangle_r) \land q)$ is valid iff $\langle s_c \rangle_s \langle h_{1c}, h_{2c}, H_c \rangle_h \langle N_{1c}, N_{2c} \rangle_r \in \Sigma_{\Gamma}$ with **owned**(Γ) $\cup A \subseteq$ **dom**(s_c), if there exits a map $\tau : Var \to Int$ such that $(\langle k \rangle_k \langle s_c \rangle_s \langle h_{1c}, h_{2c}, H_c \rangle_h \langle N_{1c}, N_{2c} \rangle_r, \tau) \models_B \exists X((o = \langle k \rangle_k \langle s_c \rangle_s \langle h_{1c}, h_{2c}, H_c \rangle_h \langle N_{1c}, N_{2c} \rangle_r, \tau) \models_B \exists X((o = \langle k \rangle_k \langle s_c \rangle_s \langle h_{1c}, h_{2c}, H_c \rangle_h \langle N_{1c}, N_{2c} \rangle_r, \tau) \models_B \exists X((o = \langle k \rangle_k \langle s_c \rangle_s \langle h_{1c}, h_{2c}, H_c \rangle_h \langle N_{1c}, N_{2c} \rangle_r, \tau) \models_B \exists X((o = \langle k \rangle_k \langle s_c \rangle_s \langle h_{1c}, h_{2c}, H_c \rangle_h \langle N_{1c}, N_{2c} \rangle_r, \tau) \models_B \exists X((o = \langle k \rangle_k \langle s_c \rangle_s \langle h_{1c}, h_{2c}, H_c \rangle_h \langle N_{1c}, H_c \rangle_h \langle N_{1c},$

- $\neg (\langle \alpha \rangle_k \langle s_c \rangle_s \langle h_{1c}, h_{2c}, H_c \rangle_h \langle N_{1c}, N_{2c} \rangle_r \xrightarrow{} \\ \xrightarrow{} \\ \Gamma, A, B \\ \end{array}^* abort)$
- if $<\alpha>_k< s_c>_s< h_{1c}, h_{2c}, H_c>_h< N_{1c}, N_{2c}>_r \xrightarrow{} (\Gamma, A, B)^* < \cdot>_k< s'_c>_s< h'_{1c}, h'_{2c}, H'_c>_h< N'_{1c}, N'_{2c}>_r, then (<\cdot>_k< s'_c>_s< h'_{1c}, h'_{2c}, H'_c>_h< N'_{1c}, N'_{2c}>_r, \tau) \models_B \exists X'((o =<\cdot>_k< s'_s< h'_1, h'_2, H'_2>_r) \land q)$

4. Soundness

The proof of soundness of the inference rules is a rule-by-rule case analysis. We start with some important properties of the semantics.

Lemma 4.1. Let $h \perp h_3$, $h_1 \perp h_2$, $h = h_1 \cdot h_2$, $N \cap N_3 = \emptyset$, $N = N_1 \cup N_2$, $N_1 \cap N_2 = \emptyset$, λ is an action.

- $\begin{array}{ll} (1) \ I\!f < \lambda >_k < s >_s < h, h_3, H >_h < N, N_3 >_r \xrightarrow[\Gamma,A_1 \cup A_2,B_1 \cup B_2]{}^* \ \textbf{abort}, \ then \ < \lambda >_k < s >_s < h_1, h_3 \cdot h_2, H >_h < N_1, N_3 \cup N_2 >_r \xrightarrow[\Gamma,A_1,B_1]{}^* \ \textbf{abort} \end{array}$
- $(2) If <\lambda >_{k}< s>_{s}< h, h_{3}, H>_{h}< N, N_{3}>_{r} \xrightarrow{\Gamma,A_{1}\cup A_{2},B_{1}\cup B_{2}} *<\cdot>_{k}< s'>_{s}< h', h'_{3}, H'>_{h}< N', N'_{3}>_{r}, then <\lambda >_{k}< s>_{s}< h_{1}, h_{3} \cdot h_{2}, H>_{h}< N_{1}, N_{3} \cup N_{2}>_{r} \xrightarrow{\Gamma,A_{1}\cup A_{2},B_{1}\cup B_{2}} * abort or there are h'_{1}, N'_{1} such that h' = h'_{1} \cdot h_{2} and N'_{1} \cap N_{2} = \emptyset and N' = N'_{1} \cup N_{2} and <\lambda >_{k}< s>_{s}< h_{1}, h_{3} \cdot h_{2}, H>_{h}< N_{1}, N_{3} \cup N_{2}>_{r} \xrightarrow{\Gamma,A_{1},B_{1}} * abort or there A_{1}, h'_{3} \cdot h_{2}, H>_{h}< N_{1}, N_{3} \cup N_{2}>_{r} \xrightarrow{\Gamma,A_{1},B_{1}} * <\cdot>_{k}< s'>_{s}< h'_{1}, h'_{3} \cdot h_{2}, H'>_{h}< N'_{1}, N'_{3} \cup N_{2}>_{r}.$

The proof is shown in Appendix A (Lemma 4.1).

Lemma 4.2. $h \perp h_3$, $h_1 \perp h_2$, $h = h_1 \cdot h_2$, $N \cap N_3 = \emptyset$, $N = N_1 \cup N_2$, $N_1 \cap N_2 = \emptyset$, α is an *trace*.

(1) If $\langle \alpha \rangle_k \langle s \rangle_s \langle h, h_3, H \rangle_h \langle N, N_3 \rangle_r \xrightarrow{\Gamma, A_1 \cup A_2, B_1 \cup B_2}^* \text{ abort}$, then $\langle \alpha \rangle_k \langle s \rangle_s \langle h_1, h_3 \cdot h_2, H \rangle_h \langle N_1, N_3 \cup N_2 \rangle_r \xrightarrow{\Gamma, A_1, B_1}^* \text{ abort}$

 $\begin{array}{ll} (2) \ If < \alpha >_k < s >_s < h, h_3, H >_h < N, N_3 >_r \xrightarrow{} & (\Gamma, A_1 \cup A_2, B_1 \cup B_2) \\ N', N'_3 >_r, \ then \ < \alpha >_k < s >_s < h_1, h_3 \cdot h_2, H >_h < N_1, N_3 \cup N_2 >_r \xrightarrow{} & \text{abort } or \ there \\ are \ h'_1, \ N'_1 \ such \ that \ h' = h'_1 \cdot h_2 \ and \ N'_1 \cap N_2 = \emptyset \ and \ N' = N'_1 \cup N_2 \ and \ < \alpha >_k < s >_s < h_1, h_3 \cdot h_2, H >_h < N_1, N_3 \cup N_2 >_r \xrightarrow{} & (N'_1 \cup N_2) \\ (N'_1, N'_1 \ such \ that \ h' = h'_1 \cdot h_2 \ and \ N'_1 \cap N_2 = \emptyset \ and \ N' = N'_1 \cup N_2 \ and \ < \alpha >_k < s >_s < h_1, h_3 \cdot h_2, H >_h < N_1, N_3 \cup N_2 >_r \xrightarrow{} & (N'_1, N'_3 \cup N_2 >_r \\ (T, A_1, B_1) \end{array}$

Lemma 4.2 is a generalization of Lemma 4.1, the proof of Lemma 4.2 is an obvious induction proof.

Theorem 4.3. Let $\operatorname{mod}(\alpha_1) \cap A_2 = \operatorname{mod}(\alpha_2) \cap A_1 = \emptyset$, $\operatorname{free}(\alpha_1) \subseteq \operatorname{owned}(\Gamma) \cup A_1$, $\operatorname{free}(\alpha_2) \subseteq \operatorname{owned}(\Gamma) \cup A_2$, $N_1 \cap N_2 = \emptyset$, $N = N_1 \cup N_2$, $N \cap N_3 = \emptyset$, $h = h_1 \cdot h_2$, $h \perp h_3$, and $\alpha \in \alpha_{1\{A_1,B_1\}} \|_{\{A_2,B_2\}} \alpha_2$

- (1) If $\langle \alpha \rangle_k \langle s \rangle_s \langle h, h_3, H \rangle_h \langle N, N_3 \rangle_r \xrightarrow{\Gamma, A_1 \cup A_2, B_1 \cup B_2}^* \text{ abort, then } \langle \alpha_1 \rangle_k \langle s \rangle_s \langle h_1, h_3 \cdot h_2, H \rangle_h \langle N_1, N_3 \cup N_2 \rangle_r \xrightarrow{\Gamma, A_1, B_1}^* \text{ abort } or \langle \alpha_2 \rangle_k \langle s \rangle_s \langle h_2, h_3 \cdot h_1, H \rangle_h \langle N_2, N_3 \cup N_1 \rangle_r \xrightarrow{\Gamma, A_2, B_2}^* \text{ abort}$
- $(2) If < \alpha >_{k} < s >_{s} < h, h_{3}, H >_{h} < N, N_{3} >_{r} \xrightarrow{} (\Gamma, A_{1} \cup A_{2}, B_{1} \cup B_{2})}^{*} < \cdot >_{k} < s' >_{s} < h', h'_{3}, H' >_{h} < N', N'_{3} >_{r}, then < \alpha_{1} >_{k} < s >_{s} < h_{1}, h_{3} \cdot h_{2}, H >_{h} < N_{1}, N_{3} \cup N_{2} >_{r} \xrightarrow{} (\Gamma, A_{1}, B_{1})^{*} \text{ abort}, \\ < \alpha_{2} >_{k} < s >_{s} < h_{2}, h_{3} \cdot h_{1}, H >_{h} < N_{2}, N_{3} \cup N_{1} >_{r} \xrightarrow{} (\Gamma, A_{2}, B_{2})^{*} \text{ abort or there are } h'_{1}, h'_{2}, \\ N'_{1}, N'_{2} such that N'_{1} \cap N'_{2} = \emptyset, N' = N'_{1} \cup N'_{2}, h' = h'_{1} \cdot h'_{2} and < \alpha_{1} >_{k} < s >_{s} < h_{1}, h_{3} \cdot h_{2}, H >_{h} < N_{1}, N_{3} \cup N_{2} >_{r} \xrightarrow{} (\Gamma, A_{1}, B_{1})^{*} < \cdot >_{k} < s' >_{s} < h'_{1}, h'_{3} \cdot h'_{2}, H' >_{h} < N'_{1}, N'_{3} \cup N'_{2} >_{r}, \\ < \alpha_{2} >_{k} < s >_{s} < h_{2}, h_{3} \cdot h_{1}, H >_{h} < N_{2}, N_{3} \cup N_{1} >_{r} \xrightarrow{} (\Gamma, A_{2}, B_{2})^{*} < \cdot >_{k} < s' >_{s} < h'_{2}, h'_{3} \cdot h'_{1}, H' >_{h} < N'_{2}, N'_{3} \cup N'_{1} >_{r}$

The proof is shown in Appendix A (Theorem 4.3).

- **Theorem 4.4.** (1) If $\langle s \rangle_s \langle h_1 \cdot h, h_2, H \rangle_h \langle N_1, N_2 \rangle_r \in \Sigma_{\Gamma}$ and $\langle s \rangle_s \langle h \rangle_h \langle \{\} \rangle_r \models R$ and free $(R) \subseteq X$ and $r \notin \operatorname{dom}(\Gamma)$, then $\langle [s \mid r \mapsto 1] \rangle_s \langle h_1, h_2, H \cdot h \rangle_h \langle N_1, N_2 \rangle_r \in \Sigma_{\Gamma, r(X):R}$;
- (2) If $r \notin \operatorname{dom}(\Gamma)$ and $\beta \in \llbracket k \rrbracket_{r:1}$ and $\langle \beta \backslash r \rangle_k \langle s \rangle_s \langle h_1 \cdot h, h_2, H \rangle_h \langle N_1, N_2 \rangle_r \xrightarrow[\Gamma, A, B]{}^*$ **abort**, then $\langle \beta \rangle_k \langle [s \mid r \mapsto 1] \rangle_s \langle h_1, h_2, H \cdot h \rangle_h \langle N_1, N_2 \rangle_r \xrightarrow[(\Gamma, r(X):R), A, B]{}^*$ **abort**;
- (3) If $r \notin \operatorname{dom}(\Gamma)$ and $\beta \in \llbracket k \rrbracket_{r:1}$ and $\langle \beta \backslash r \rangle_k \langle s \rangle_s \langle h_1 \cdot h, h_2, H \rangle_h \langle N_1, N_2 \rangle_r \xrightarrow{\Gamma, A, B}^* \langle \cdot \rangle_k \langle s' \rangle_s \langle h'_1 \cdot h', h'_2, H' \rangle_h \langle N'_1, N'_2 \rangle_r$, then either $\langle \beta \rangle_k \langle [s \mid r \mapsto 1] \rangle_s \langle h_1, h_2, H \cdot h \rangle_h \langle N_1, N_2 \rangle_r \xrightarrow{\Gamma, A, B}^*$ abort or $\langle \beta \rangle_k \langle [s \mid r \mapsto 1] \rangle_s \langle h_1, h_2, H \cdot h \rangle_h \langle N_1, N_2 \rangle_r \xrightarrow{\Gamma, T(X):R), A, B}^* \langle \cdot \rangle_k \langle [s' \mid r \mapsto 1] \rangle_s \langle h'_1, h'_2, H' \cdot h' \rangle_h \langle N'_1, N'_2 \rangle_r$.

The Theorem 4.4 is very intuitive, we omit the proof.

Theorem 4.5. (Soundness)

Every provable assertion $\Gamma \vdash_{A,B} \exists X((o = \langle k \rangle_k \langle s \rangle_s \langle h_1, h_2, H \rangle_h \langle N_1, N_2 \rangle_r) \land p) \Downarrow \exists X'((o = \langle \cdot \rangle_k \langle s' \rangle_s \langle h'_1, h'_2, H' \rangle_h \langle N'_1, N'_2 \rangle_r) \land q) \text{ is valid.}$

Proof. The proof is by induction on the length of the derivation, that every provable assertion is valid. For some of the rules this is fairly easy, we omit the proof. We only provide proof details for PARALLEL and RESOURCE.

• PARALLEL; Let $LS = \langle s \rangle_s \langle h_1 \cdot h_2, h_3, H \rangle_h \langle N_1 \cup N_2, N_3 \rangle_r$ and $LS_1 = \langle s \rangle_s \langle h_1, h_2 \cdot h_3, H \rangle_h \langle N_1, N_2 \cup N_3 \rangle_r$ and $LS'_1 = \langle s' \rangle_s \langle h'_1, h'_2 \cdot h'_3, H' \rangle_h \langle N'_1, N'_2 \cup N'_3 \rangle_r$ and $LS_2 = \langle s \rangle_s \langle h_2, h_1 \cdot h_3, H \rangle_h \langle N_2, N_1 \cup N_3 \rangle_r$ and $LS'_2 = \langle s' \rangle_s \langle h'_2, h'_1 \cdot h'_3, H' \rangle_h \langle N'_2, N'_1 \cup N'_3 \rangle_r$ and $LS'_1 = \langle s' \rangle_s \langle h'_1, h'_2, h'_3, H' \rangle_h \langle N'_2, N'_1 \cup N'_3 \rangle_r$ and $LS'_1 = \langle s' \rangle_s \langle h'_1, h'_2, h'_3, H' \rangle_h \langle N'_2, N'_3 \rangle_r$.

Suppose $\Gamma \vdash_{A_1,B_1} \exists X_1(o = \langle k_1 \rangle_k LS_1 \land p_1) \Downarrow \exists X_2(o = \langle \cdot \rangle_k LS'_1 \land q_1)$ and $\Gamma \vdash_{A_2,B_2} \exists X_1(o = \langle k_2 \rangle_k LS_2 \land p_2) \Downarrow \exists X_2(o = \langle \cdot \rangle_k LS'_2 \land q_2)$ are well-formed and valid, and $\operatorname{\mathbf{mod}}(k_1) \cap A_2 = \operatorname{\mathbf{mod}}(k_1) \cap B_2 = \operatorname{\mathbf{mod}}(k_2) \cap A_1 = \operatorname{\mathbf{mod}}(k_2) \cap B_1 = \emptyset$ and $N_1 \cap N_2 = \emptyset$. We next show that $\Gamma \vdash_{A_1 \cup A_2, B_1 \cup B_2} \exists X_1(o = \langle k_1 \parallel k_2 \rangle_k LS \land (p_1 * p_2)) \Downarrow \exists X_2(o = \langle \cdot \rangle_k LS'_1 \land (q_1 * q_2))$ is valid.

Let $\tau: Var \to Int$ and $\langle s_c \rangle_s \langle h_c, h_{3c}, H_c \rangle_h \langle N_c, N_{3c} \rangle_r \in \Sigma_{\Gamma}$ and $\langle k_1 \parallel k_2 \rangle_k \langle s_c \rangle_s \langle h_c, h_{3c}, H_c \rangle_h \langle N_c, N_{3c} \rangle_r, \tau \rangle \models_{B_1 \cup B_2} \exists X_1(o = \langle k_1 \parallel k_2 \rangle_k LS \land (p_1 * p_2))$, then we have

- (1) there exists some θ_{τ} : $Var \to Int$ with $\theta_{\tau} \upharpoonright_{Var/X_1} = \tau \upharpoonright_{Var/X_1};$
- (2) $s_c \upharpoonright_{B_1 \cup B_2} = \theta_\tau(s) \upharpoonright_{B_1 \cup B_2};$
- (3) $h_c = h_1 \cdot h_2$ and $N_c = N_1 \cup N_2$;
- $(4) < s_c >_s < h_c >_h < \{\} >_r \models p_1 * p_2.$

Let $h_{1c}\perp h_{2c}$ and $h_c = h_{1c} \cdot h_{2c}$ and $\langle s_c \rangle_s \langle h_{1c} \rangle_h \langle \{\} \rangle_r \models p_1$ and $\langle s_c \rangle_s \langle h_{2c} \rangle_h \langle \{\} \rangle_r \models p_2$ and $N_{1c} = N_1$ and $N_{2c} = N_2$ and $N = N_1 \cup N_2$. Since $\alpha_1 \in \llbracket k_1 \rrbracket$ and $\alpha_2 \in \llbracket k_2 \rrbracket$ and $\mathbf{mod}(k_1) \cap A_2 = \mathbf{mod}(k_2) \cap A_1 = \emptyset$, then $\mathbf{mod}(\alpha_1) \cap A_2 = \mathbf{mod}(\alpha_2) \cap A_1 = \emptyset$. Let $\alpha \in \alpha_{1\{A_1,B_1\}} \parallel_{\{A_2,B_2\}} \alpha_2$,

- (1) if $\langle \alpha \rangle_k \langle s_c \rangle_s \langle h_c, h_{3c}, H_c \rangle_h \langle N_c, N_{3c} \rangle_r \xrightarrow{\Gamma,A_1 \cup A_2, B_1 \cup B_2}^*$ **abort**, then by Theorem 4.3, either $\langle \alpha_1 \rangle_k \langle s_c \rangle_s \langle h_{1c}, h_{3c} \cdot h_{2c}, H_c \rangle_h \langle N_{1c}, N_{3c} \cup N_{2c} \rangle_r \xrightarrow{\Gamma,A_1,B_1}^*$ **abort** or $\langle \alpha_2 \rangle_k \langle s_c \rangle_s \langle h_{2c}, h_{3c} \cdot h_{1c}, H_c \rangle_h \langle N_{2c}, N_{3c} \cup N_{1c} \rangle_r \xrightarrow{\Gamma,A_2,B_2}^*$ **abort**. Neither case is possible because they contradict the validity of the hypothesis $\Gamma \vdash_{A_1,B_1} \exists X_1 (o = \langle k_1 \rangle_k LS_1 \wedge p_1) \Downarrow \exists X_2 (o = \langle \cdot \rangle_k LS'_1 \wedge q_1)$ and $\Gamma \vdash_{A_2,B_2} \exists X_1 (o = \langle k_2 \rangle_k LS_2 \wedge p_2) \Downarrow \exists X_2 (o = \langle \cdot \rangle_k LS'_2 \wedge q_2).$
- $(2) \text{ if } \langle \alpha \rangle_k \langle s_c \rangle_s \langle h_c, h_{3c}, H_c \rangle_h \langle N_c, N_{3c} \rangle_r \xrightarrow{\Gamma, A_1 \cup A_2, B_1 \cup B_2} * \langle \cdot \rangle_k \langle s'_c \rangle_s \langle h'_c, h'_{3c}, H'_c \rangle_h \langle N'_c, N'_{3c} \rangle_r, \text{ then by Theorem 4.3, there are } h'_{1c}, h'_{2c}, N'_{1c}, N'_{2c} \text{ such that } N'_{1c} \cap N'_{2c} = \emptyset, N' = N'_{1c} \cup N'_{2c}, h' = h'_{1c} \cdot h'_{2c} \text{ and } \langle \alpha_1 \rangle_k \langle s_c \rangle_s \langle h_{1c}, h_{3c} \cdot h_{2c}, H_c \rangle_h \langle N_{1c}, N_{3c} \cup N_{1c}, N_{3c} \cup N_{1c}, N_{3c} \cup N_{1c}, N_{3c} \cup N_{2c} \rangle_r \text{ and } \langle \alpha_2 \rangle_k \langle s' \rangle_s \langle h'_{1c}, h'_{3c} \cdot h'_{2c}, h'_{3c} \cup h'_{2c} \rangle_r \text{ and } \langle \alpha_2 \rangle_k \langle s' \rangle_s \langle h'_{2c}, h'_{3c} \cdot h_{1c}, H_c \rangle_h \langle N_{2c}, N_{3c} \cup N_{1c} \rangle_r \xrightarrow{\Gamma, A_2, B_2} * \langle \cdot \rangle_k \langle s' \rangle_s \langle h'_{2c}, h'_{3c} \cdot h'_{1c}, H'_c \rangle_h \langle N'_{2c}, N'_{3c} \cup N'_{1c} \rangle_r$

By the induction hypothesis for $\Gamma \vdash_{A_1,B_1} \exists X_1(o = \langle k_1 \rangle_k LS_1 \land p_1) \Downarrow \exists X_2(o = \langle \cdot \rangle_k LS'_1 \land q_1)$, we have $(\langle \cdot \rangle_k \langle s'_c \rangle_s \langle h'_{1c}, h'_{3c} \cdot h'_{2c}, H'_c \rangle_h \langle N'_{1c}, N'_{3c} \cup N'_{2c} \rangle_r, \tau) \models_{B_1} \exists X_2(o = \langle \cdot \rangle_k LS'_1 \land q_1).$

By the induction hypothesis for $\Gamma \vdash_{A_2,B_2} \exists X_1(o = \langle k_2 \rangle_k \ LS_2 \land p_2) \Downarrow \exists X_2(o = \langle \cdot \rangle_k \ LS'_2 \land q_2)$, we have $(\langle \cdot \rangle_k \langle s'_c \rangle_s \langle h'_{2c}, h'_{3c} \cdot h'_{1c}, H'_c \rangle_h \langle N'_{2c}, N'_{3c} \cup N'_{1c} \rangle_r, \tau) \models_{B_2}$

 $\exists X_2(o = <\cdot>_k LS'_2 \land q_2).$ Hence, $(<\cdot>_k < s'_c >_s < h'_c, h'_{3c}, H'_c >_h < N'_c, N'_{3c} >_r, \tau) \models_{B_1, B_2} \exists X_2(o = <\cdot>_k LS_f \land (q_1 * q_2)).$

• RESOURCE; Let $LS_1 = \langle s \rangle_s \langle h_1 \cdot h, h_2, H \rangle_h \langle N_1, N_2 \rangle_r$, $LS_2 = \langle s' \rangle_s \langle h'_1 \cdot h', h'_2, H' \rangle_h \langle N'_1, N'_2 \rangle_r$, $LS'_1 = \langle s \rangle_s \langle h_1, h_2, H \cdot h \rangle_h \langle N_1, N_2 \rangle_r$, $LS'_2 = \langle s' \rangle_s \langle h'_1, h'_2, H' \cdot h' \rangle_h \langle N'_1, N'_2 \rangle_r$. Suppose $\Gamma, r(Y) : R \vdash_{A,B} \exists X(o = \langle k \rangle_k LS'_1 \wedge p) \Downarrow \exists X'(o = \langle \cdot \rangle_k LS'_2 \wedge q)$ is well-formed and valid.

Let τ : $Var \to Int$ and $\langle s_c \rangle_s \langle h_{1c} \cdot h_c, h_{2c}, H_c \rangle_h \langle N_{1c}, N_{2c} \rangle_r \in \Sigma_{\Gamma}$ and $\langle s_c \rangle_s \langle h_{1c} \rangle_h \langle \{\} \rangle_r \models p$ and $\langle s_c \rangle_s \langle h_c \rangle_h \langle \{\} \rangle_r \models R$, then ($\langle \text{resource } r \text{ in } k \rangle_k \langle s_c \rangle_s \langle h_{1c} \cdot h_c, h_{2c}, H_c \rangle_h \langle N_{1c}, N_{2c} \rangle_r, \tau$) $\models_B \exists X(o = \langle \text{resource } r \text{ in } k \rangle_k LS_1 \land (p * R))$. Let $\alpha \in \llbracket k \rrbracket_{[r:1]}$.

(1) If $\langle \alpha \rangle_k \langle s_c \rangle_s \langle h_{1c}, h_{2c}, H_c \rangle_h \langle N_{1c}, N_{2c} \rangle_r \xrightarrow[\Gamma,A\cup Y,B]{}^*$ **abort**, then, by Theorem 4.4, $\langle \alpha \rangle_k \langle [s_c \mid r \mapsto 1] \rangle_s \langle h_{1c}, h_{2c}, H_c \cdot h_c \rangle_h \langle N_{1c}, N_{2c} \rangle_r \xrightarrow[(\Gamma,r(Y):R),A,B]{}^*$ **abort**. However, this is possible because they contradict the validity of the hypothesis

However, this is possible because they contradict the validity of the hypothesis $\Gamma, r(Y) : R \vdash_{A,B} \exists X(o = \langle k \rangle_k LS'_1 \land p) \Downarrow \exists X'(o = \langle \cdot \rangle_k LS'_2 \land q).$

(2) If
$$\langle \alpha | r \rangle_k \langle s_c \rangle_s \langle h_{1c} \cdot h_c, h_{2c}, H_c \rangle_h \langle N_{1c}, N_{2c} \rangle_r \xrightarrow{}{}_{\Gamma,A \cup Y,B} \langle \cdot \rangle_k \langle s'_c \rangle_s \langle h'_{1c} \cdot h'_c, h'_{2c}, H'_c \rangle_h \langle N'_{1c}, N'_{2c} \rangle_r$$
, then by Theorem 4.4,

a), either
$$\langle \alpha \rangle_k < [s_c \mid r \mapsto 1] \rangle_s < h_{1c}, h_{2c}, H_c \cdot h_c \rangle_h < N_{1c}, N_{2c} \rangle_r \xrightarrow[(\Gamma, r(Y):R), A, B]{}^*$$
 abort
This is possible as above

This is possible as above.
b), or
$$\langle \alpha \rangle_k \langle [s_c \mid r \mapsto 1] \rangle_s \langle h_{1c}, h_{2c}, H_c \cdot h_c \rangle_h \langle N_{1c}, N_{2c} \rangle_r$$

 $[s'_c \mid r \mapsto 1] \rangle_s \langle h'_{1c}, h'_{2c}, H'_c \cdot h'_c \rangle_h \langle N'_{1c}, N'_{2c} \rangle_r$.
By the induction hypothesis for $\Gamma, r(Y) : R \vdash_{A,B} \exists X(o = \langle k \rangle_k LS'_1 \land p) \Downarrow \exists X'(o = \langle \cdot \rangle_k LS'_2 \land q)$, we have $(\langle \cdot \rangle_k \langle [s'_c \mid r \mapsto 1] \rangle_s \langle h'_{1c}, h'_{2c}, H'_c \cdot h'_c \rangle_h \langle N'_{1c}, N'_{2c} \rangle_r, \tau) \models_B \exists X'(o = \langle \cdot \rangle_k LS'_2 \land q)$.
Hence, $(\langle \cdot \rangle_k \langle s'_c \rangle_s \langle h'_{1c} \cdot h'_c, h'_{2c}, H'_c \rangle_h \langle N'_{1c}, N'_{2c} \rangle_r, \tau) \models_B \exists X'(o = \langle \cdot \rangle_k LS_2 \land (q * R))$.

5. Relation to CSL

Before we discuss the relationship between CML and CSL, let's take a closer look at the assertions of CML. The assertion of CML has the form of $\Gamma \vdash_{A,B} \exists X((o = \langle k \rangle_k \langle s \rangle_s \langle h_1, h_2, H \rangle_h \langle N_1, N_2 \rangle_r) \land p) \Downarrow \exists X'((o = \langle \cdot \rangle_k \langle s' \rangle_s \langle h_1', h_2', H' \rangle_h \langle N_1', N_2' \rangle_r) \land q)$. Let's consider a special case where $A = \emptyset$ and $B = \operatorname{dom}(s)$ and $h_1 = h_2 = H = h_1' = h_2' = H' = \operatorname{emp}$ and $N_1 = N_2 = N_1' = N_2' = \emptyset$ and $\Gamma = \emptyset$ and p, q do not contain separating conjunction, but is only a first-order logical formula. In this case, CML simplifies to matching logic.

The assertion of CSL has the form of $\Gamma \vdash_A \{p\}k\{q\}$. Note that the CML pattern provides

more information specifications than CSL. We fix a finite set of program identifiers Z which is large enough. We assume that Z_v, Z'_v are two sets of variables called "semantic clone" of Z. Let s_z, s'_z map each program identifier z in Z to its corresponding "semantic clone" variable. **S2M** is a mapping taking CSL's assertion to CML's assertion.

$$\begin{aligned} \mathbf{S2M}(\Gamma \vdash_A \{p\}k\{q\}) &\equiv \Gamma \vdash_{A,\{\}} \exists Z \cup Z_v((o = _k < s_z >_s < -, -, ->_h < -, ->_r) \land p) \\ & \Downarrow \exists Z \cup Z'_v((o = <\cdot >_k < s'_z >_s < -, -, ->_h < -, ->_r) \land q) \end{aligned}$$

where "-" is a special notation, which we call "free-match" notation, that is, these positions are free from match when a concrete configuration γ matches CML pattern. For example, let $\langle s \rangle_s \langle h_1, h_2, H \rangle_h \langle N_1, N_2 \rangle_r \in \Sigma_{\Gamma}$ and $\tau : Var \to Int$, then

$$(<\!\!k\!\!>_k<\!\!s\!\!>_s<\!\!h_1,h_2,H\!\!>_h<\!\!N_1,\!N_2\!\!>_r,\tau)\models_{\{\}}\exists Z\cup Z_v((o=\!<\!\!k\!\!>_k<\!\!s_z\!\!>_s<\!\!-,-,-\!\!>_h<\!\!-,-\!\!>_r)\wedge p)$$
 iff

- there exists some θ_{τ} : $Var \to Int$ with $\theta_{\tau} \upharpoonright_{Var/\{Z \cup Z_v\}} = \tau \upharpoonright_{Var/\{Z \cup Z_v\}};$
- $s = \theta_{\tau}(s);$
- $<\!\!s\!\!>_s<\!\!h_1\!\!>_h<\!\!\{\}\!\!>_r\models p.$

Theorem 5.1. If the assertion $\Gamma \vdash_A \{p\}k\{q\}$ is valid in CSL, then the assertion $\mathbf{S2M}(\Gamma \vdash_A \{p\}k\{q\})$ $\{p\}k\{q\}$) is valid in CML.

Proof. Our semantic model is also applicable to CSL. Let $\langle s_c \rangle_s \langle h_{1c}, h_{2c}, H_c \rangle_h \langle N_{1c}, N_{2c} \rangle_r \in$ Σ_{Γ} with **owned**(Γ) $\cup A \subseteq$ **dom**(s_c) and $\langle s_c \rangle_s \langle h_{1c}, h_{2c}, H_c \rangle_h \langle N_{1c}, N_{2c} \rangle_r \models p$. If $\Gamma \vdash_A \{p\}k\{q\}$ is valid, then for all traces $\alpha \in [\![k]\!]$,

• $\neg (\langle \alpha \rangle_k \langle s_c \rangle_s \langle h_{1c}, h_{2c}, H_c \rangle_h \langle N_{1c}, N_{2c} \rangle_r \xrightarrow{} * \mathbf{abort});$

• If $<\alpha>_k< s_c>_s< h_{1c}, h_{2c}, H_c>_h< N_{1c}, N_{2c}>_r \xrightarrow{\Gamma,A,\{\}}^* <\cdot>_k< s_c'>_s< h_{1c}', h_{2c}', H_c'>_h<$ $N'_{1c}, N'_{2c} >_r$, then $<\!\!s'_c\!\!>_s<\!\!h'_{1c}, h'_{2c}, H'_c\!\!>_h<\!\!N'_{1c}, N'_{2c}\!\!>_r\models q$.

 $\mathbf{S2M}(\Gamma \vdash_A \{p\}k\{q\}) \equiv \Gamma \vdash_{A,\{\}} \exists Z \cup Z_v((o = \langle k \rangle_k \langle s_z \rangle_s \langle -, -, -\rangle_h \langle -, -\rangle_r) \land p) \Downarrow$ $\exists Z \cup Z'_v((o = \langle \cdot \rangle_k \langle s'_z \rangle_s \langle -, -, -\rangle_h \langle -, -\rangle_r) \land q).$ It's easy to find a τ : $Var \to Int$ such that $(\langle k \rangle_k \langle s_c \rangle_s \langle h_{1c}, h_{2c}, H_c \rangle_h \langle N_{1c}, N_{2c} \rangle_r, \tau) \models_{\{\}}$ $\exists Z \cup Z_v((o = \langle k \rangle_k \langle s_z \rangle_s \langle -, -, -\rangle_h \langle -, -\rangle_r) \land p). \text{ Since } \langle \alpha \rangle_k \langle s_c \rangle_s \langle h_{1c}, h_{2c}, H_c \rangle_h \langle$ $N'_{1c}, N'_{2c} >_r \models q, \text{ then } (<\!\!\cdot\!\!>_k<\!\!s'_c\!\!>_s<\!\!h'_{1c}, h'_{2c}, H'_c\!\!>_h<\!\!N'_{1c}, N'_{2c}\!\!>_r, \tau) \models_{\{\}} \exists Z \cup Z'_v((o =<\!\!\cdot\!\!>_k<\!\!s'_v) \models_{\{\}} =<\!\!s'_v =<\!$ $s'_{z} >_{s} < -, -, ->_{h} < -, ->_{r}) \land q$. Hence, the assertion $\mathbf{S2M}(\Gamma \vdash_A \{p\}k\{q\})$ is valid in CML.

Compared with CSL, CML has the following characteristics:

• The CML pattern provides more information specifications than CSL; CSL uses separation logic formula to describe the state before and after process execution. Instead of separation logic formula, CML uses pattern. Separation logic formula is relatively abstract. However, pattern involves "low-level" operational aspects, such as how to express the state. In CML pattern, h_1, N_1 represents part of the heap and part of the resource owned by the process, h_2, N_2 is owned by the environment, H represents the remaining

heap and satisfies the resource invariants of the currently available resources, and the "key set" B represents the store portion owned by the process.

• S2M is a mapping taking CSL's assertion to CML's assertion. S2M($\Gamma \vdash_A \{p\}k\{q\}$) is a special form of CML assertion where key set B is empty. Hence, CSL can be seen as an instance of CML.

6. Conclusions

Matching logic works well on the sequential processes, but not on the shared-memory concurrent processes. Nevertheless, the matching logic inherently supports the viewpoint of "resource separation". Inspired by the concurrent separation logic (CSL), we introduce Concurrent Matching Logic (CML). However, CML's pattern involves "low-level" operational aspects, such as how to express the state. In addition to a "rely set" A, we also need a "key set" B. We give the notion of validity and prove CML is sound to our operational semantics model for concurrency. We also analyze the relationship between the CML and the CSL, and point out that under certain assumptions, CSL can be seen as an instance of CML. There are many extensions for CSL, such as: permissions[Boy03][BCOP05], locksin-the-heap[GBC⁺07][HAN08]. We hope to use CML to handle these extensions, which is also our follow-up work.

References

- [BCOP05] Richard Bornat, Cristiano Calcagno, Peter O'Hearn, and Matthew Parkinson. Permission accounting in separation logic. In Proceedings of the 32nd ACM SIGPLAN-SIGACT symposium on Principles of programming languages, pages 259–270, 2005.
- [Boy03] John Boyland. Checking interference with fractional permissions. In International Static Analysis Symposium, pages 55–72. Springer, 2003.
- [Bro07] Stephen Brookes. A semantics for concurrent separation logic. *Theoretical Computer Science*, 375(1-3):227–270, 2007.
- [Bro11] Stephen Brookes. A revisionist history of concurrent separation logic. Electronic Notes in Theoretical Computer Science, 276:5–28, 2011.
- [CLR21] Xiaohong Chen, Dorel Lucanu, and Grigore Roşu. Matching logic explained. Journal of Logical and Algebraic Methods in Programming, 120:100638, 2021.
- [CR19] Xiaohong Chen and Grigore Roşu. Matching μ-logic. In 2019 34th Annual ACM/IEEE Symposium on Logic in Computer Science (LICS), pages 1–13. IEEE, 2019.
- [Dij68] Edsger W Dijkstra. Cooperating sequential processes. In The origin of concurrent programming, pages 65–138. Springer, 1968.
- [GBC⁺07] Alexey Gotsman, Josh Berdine, Byron Cook, Noam Rinetzky, and Mooly Sagiv. Local reasoning for storable locks and threads. In Asian Symposium on Programming Languages And Systems, pages 19–37. Springer, 2007.
- [HAN08] Aquinas Hobor, Andrew W Appel, and Francesco Zappa Nardelli. Oracle semantics for concurrent separation logic. In European Symposium on Programming, pages 353–367. Springer, 2008.
- [Hoa72] Charles Antony Richard Hoare. Towards a theory of parallel programming. In *The origin of* concurrent programming, pages 231–244. Springer, 1972.

- [MOM96] Narciso Martí-Oliet and José Meseguer. Rewriting logic as a logical and semantic framework. Electronic Notes in Theoretical Computer Science, 4:190–225, 1996.
- [OG76a] Susan Owicki and David Gries. An axiomatic proof technique for parallel programs i. Acta informatica, 6(4):319–340, 1976.
- [OG76b] Susan Owicki and David Gries. Verifying properties of parallel programs: An axiomatic approach. Communications of the ACM, 19(5):279–285, 1976.
- [O'h07] Peter W O'hearn. Resources, concurrency, and local reasoning. *Theoretical computer science*, 375(1-3):271–307, 2007.
- [O'H19] Peter O'Hearn. Separation logic. Communications of the ACM, 62(2):86–95, 2019.
- [OYR09] Peter W O'Hearn, Hongseok Yang, and John C Reynolds. Separation and information hiding. ACM Transactions on Programming Languages and Systems (TOPLAS), 31(3):1–50, 2009.
- [RES10] Grigore Roşu, Chucky Ellison, and Wolfram Schulte. Matching logic: An alternative to hoare/floyd logic. In International Conference on Algebraic Methodology and Software Technology, pages 142–162. Springer, 2010.
- [Rey02] John C Reynolds. Separation logic: A logic for shared mutable data structures. In Proceedings 17th Annual IEEE Symposium on Logic in Computer Science, pages 55–74. IEEE, 2002.
- [Ros17a] Grigore Rosu. K: A semantic framework for programming languages and formal analysis tools. Dependable Software Systems Engineering, 50:186, 2017.
- [Ros17b] Grigore Rosu. Matching logic. arXiv preprint arXiv:1705.06312, 2017.
- [RŞ10] Grigore Roşu and Traian Florin Şerbănută. An overview of the k semantic framework. The Journal of Logic and Algebraic Programming, 79(6):397–434, 2010.
- [RS11] Grigore Rosu and Andrei Stefanescu. Matching logic: a new program verification approach (nier track). In 2011 33rd International Conference on Software Engineering (ICSE), pages 868–871. IEEE, 2011.
- [RŞ12] Grigore Roşu and Andrei Ştefănescu. From hoare logic to matching logic reachability. In *Inter*national Symposium on Formal Methods, pages 387–402. Springer, 2012.

APPENDIX A.

Proof. (Lemma 4.1) Case analysis for each form of action. Most cases are straightforward. Here are the cases for acq r and rel r.

• For $\lambda = \mathbf{acq} \ r; \ r \notin N \cup N_3$, Obviously, $\langle \mathbf{acq} \ r \rangle_k \langle s \rangle_s \langle h, h_3, H \rangle_h \langle N, N_3 \rangle_r \xrightarrow[\Gamma,A_1,B_1]{}^*$ **abort** is vacuous. If $\langle \mathbf{acq} \ r \rangle_k \langle s \rangle_s \langle h, h_3, H \rangle_h \langle N, N_3 \rangle_r \xrightarrow[\Gamma,A_1\cup A_2,B_1\cup B_2]{}^* \langle \cdot \rangle_k \langle s' \rangle_s \langle h_3, H \rangle_h \langle h_3$

 $h', h'_3, H' >_h < N', N'_3 >_r$, then:

- (1) there are actions $\mu_1, \mu_2, \ldots, \mu_n$ such that for $1 \le i \le n$, $\operatorname{writes}(\mu_i) \cap (A_1 \cup A_2) = \emptyset$ and $\operatorname{writes}(\mu_i) \cap (B_1 \cup B_2) = \emptyset$ and $\langle \operatorname{acq} r \rangle_k \langle s \rangle_s \langle h, h_3, H \rangle_h \langle N, N_3 \rangle_r \rightsquigarrow^*_{\Gamma, A', B'} \langle \operatorname{acq} r \rangle_k \langle s'' \rangle_s \langle h, h_3'', H'' \rangle_h \langle N, N_3'' \rangle_r;$
- acq $r >_k < s'' >_s < h, h''_3, H'' >_h < N, N''_3 >_r;$ (2) there is h_r such that $h_r \subseteq H''$ and $< s'' >_s < h_r >_h < \{\} >_r \models \operatorname{inv}(\Gamma \upharpoonright r)$ and <acq $r >_k < s'' >_s < h, h''_3, H'' >_h < N, N''_3 >_r \xrightarrow{\Gamma, A_1 \cup A_2, B_1 \cup B_2} < \cdot >_k < [s'' \upharpoonright r \mapsto 0] >_s < h \cdot h_r, h''_3, H'' - h_r >_h < N \cup \{r\}, N''_3 >_r;$
- (3) there are $\nu_1, \nu_2, ..., \nu_m$ such that for $1 \le j \le m$, $\operatorname{writes}(\nu_j) \cap (A_1 \cup A_2) = \emptyset$ and $\operatorname{writes}(\nu_j) \cap (B_1 \cup B_2) = \emptyset$ and $<\cdot >_k < [s'' \mid r \mapsto 0] >_s < h \cdot h_r, h''_3, H'' - h_r >_h < N \cup \{r\}, N''_3 >_r \sim^*_{\Gamma,A',B'} <\cdot >_k <s' >_s <h \cdot h_r, h'_3, H' >_h < N \cup \{r\}, N''_3 >_r.$

Since $h_2 \perp h_3$ and (1), then

$$<\!\!\operatorname{acq} r\!\!>_k<\!\!s\!\!>_s<\!\!h_1, h_2 \cdot h_3, H\!\!>_h<\!\!N_1, N_3 \cup N_2\!\!>_r \rightsquigarrow^*_{\Gamma,A',B'} \\<\!\!\operatorname{acq} r\!\!>_k<\!\!s''\!\!>_s<\!\!h_1, h_2 \cdot h''_3, H''\!\!>_h<\!\!N_1, N''_3 \cup N_2\!\!>_r$$

By (2)

$$< \mathbf{acq} \ r >_k < s'' >_s < h_1, h_2 \cdot h_3'', H'' >_h < N_1, N_3'' \cup N_2 >_r \xrightarrow{\Gamma, A_1, B_1} < < \cdot >_k < [s'' \mid r \mapsto 0] >_s < h_1 \cdot h_r, h_2 \cdot h_3'', H'' - h_r >_h < N_1 \cup \{r\}, N_3'' \cup N_2 >_r$$

$$<:>_k<[s'' \mid r \mapsto 0]>_s< h_1 \cdot h_r, h_2 \cdot h''_3, H'' - h_r>_h< N_1 \cup \{r\}, N''_3 \cup N_2>_r \rightsquigarrow^*_{\Gamma,A',B'}$$
$$<:>_k<\!s'\!>_s<\!h_1 \cdot h_r, h_2 \cdot h'_3, H'\!>_h<\!N_1 \cup \{r\}, N'_3 \cup N_2\!>_r$$

Hence, $<\!\!\mathbf{acq}\ r\!\!>_k<\!\!s\!\!>_s<\!\!h_1, h_2\cdot h_3, H\!\!>_h<\!\!N_1, N_3\cup N_2\!\!>_r \xrightarrow{}_{\Gamma,A_1,B_1}<\!\!\cdot\!\!>_k<\!\!s'\!\!>_s<\!\!h_1\cdot h_r, h_2\cdot$

- For $\lambda = \operatorname{rel} r$; $r \in N$. If $\langle \operatorname{rel} r \rangle_k \langle s \rangle_s \langle h, h_3, H \rangle_h \langle N, N_3 \rangle_r \xrightarrow{\Gamma, A_1 \cup A_2, B_1 \cup B_2}^*$ abort, then there are actions $\mu_1, \mu_2, \ldots, \mu_n$ such that for $1 \leq i \leq n, 0 \leq n$, writes $(\mu_i) \cap$ $(A_1 \cup A_2) = \emptyset$ and $writes(\mu_i) \cap (B_1 \cup B_2) = \emptyset$ and $\langle rel \ r >_k < s >_s < h, h_3, H >_h < h_1$ $N, N_3 >_r \rightsquigarrow^*_{\Gamma, A', B'} < \mathbf{rel} \ r >_k < s'' >_s < h, h''_3, H'' >_h < N, N''_3 >_r \text{ and } \forall h_r \subseteq h, < s'' >_s < h_r >_h < h''_3 >_h < N, N''_3 >_r$ $\{\}>_r\models \neg \mathbf{inv}(\Gamma \upharpoonright r). \text{ Since } h = h_1 \cdot h_2, \text{ then } \forall h_r \subseteq h_1, \langle s'' \rangle_s \langle h_r \rangle_h \langle \{\}>_r\models \neg \mathbf{inv}(\Gamma \upharpoonright r)$ and hence that $\langle \operatorname{rel} r \rangle_k \langle s \rangle_s \langle h_1, h_3 \cdot h_2, H \rangle_h \langle N_1, N_3 \cap N_2 \rangle_r \xrightarrow{} h_1 h_2 h_3 \circ h_2$ abort.

$$If < \mathbf{rel} \ r >_k < s >_s < h, h_3, H >_h < N, N_3 >_r \xrightarrow[\Gamma, A_1 \cup A_2, B_1 \cup B_2]{} < \cdot >_k < s' >_s < h', h'_3, H' >_h < N'_1 >_h < h'_2 >_h < h'_2$$

- $N', N'_3 >_r$, then
- (1) there are actions $\mu_1, \mu_2, \ldots, \mu_n$ such that for $1 \le i \le n$, writes $(\mu_i) \cap (A_1 \cup A_2) = \emptyset$ and writes $(\mu_i) \cap (B_1 \cup B_2) = \emptyset$ and $\langle \operatorname{rel} r \rangle_k \langle s \rangle_s \langle h, h_3, H \rangle_h \langle N, N_3 \rangle_r \rightsquigarrow_{\Gamma, A', B'}^* \langle h, h_3, H \rangle_h \langle N, N_3 \rangle_r \wedge_{\Gamma, A', B'}^* \langle h, h_3, H \rangle_h \langle N, h_3, H \rangle_h \langle h, h_3, H \rangle_h \langle h$ $\mathbf{rel} \; r\!\!>_k<\!\!s''\!\!>_s<\!\!h, h''_3, H''\!\!>_h<\!\!N, N''_3\!\!>_r;$
- (2) there is h_r such that $h_r \subseteq h$ and $\langle s'' \rangle_s \langle h_r \rangle_h \langle \{\} \rangle_r \models \operatorname{inv}(\Gamma \upharpoonright r)$ and $\langle \operatorname{rel} r \rangle_k \langle s'' \rangle_s \langle h, h''_3, H'' \rangle_h \langle N, N''_3 \rangle_r \xrightarrow{\Gamma, A_1 \cup A_2, B_1 \cup B_2} \langle \cdot \rangle_k \langle [s'' \upharpoonright r \mapsto 1] \rangle_s \langle h h_r, h''_3, H'' \rangle_r$ $h_r >_h < N - \{r\}, N_3'' >_r;$
- (3) there are $\nu_1, \nu_2, \ldots, \nu_m$ such that for $1 \leq j \leq m$, writes $(\nu_j) \cap (A_1 \cup A_2) = \emptyset$ and $writes(\nu_j) \cap (B_1 \cup B_2) = \emptyset \text{ and } \langle \cdot \rangle_k \langle [s'' \mid r \mapsto 1] \rangle_s \langle h - h_r, h''_3, H'' \cdot h_r \rangle_h \langle h_r$ $N - \{r\}, N_3'' >_r \rightsquigarrow_{\Gamma,A',B'}^* <:>_k <\!\!s'\!\!>_s <\!\!h - h_r, h_3', H' \!\!>_h <\!\!N - \{r\}, N_3' \!\!>_r.$

Since $h_2 \perp h_3$ and (1), then

$$\begin{aligned} <\!\!\mathbf{rel} \; r\!\!>_k <\!\!s\!\!>_s <\!\!h_1, h_2 \cdot h_3, H\!\!>_h <\!\!N_1, N_3 \cup N_2 \!\!>_r \rightsquigarrow^*_{\Gamma, A', B'} \\ <\!\!\mathbf{rel} \; r\!\!>_k <\!\!s''\!\!>_s <\!\!h_1, h_2 \cdot h''_3, H''\!\!>_h <\!\!N_1, N''_3 \cup N_2 \!\!>_r \end{aligned}$$

If $h_r \not\subseteq h_1$, then $\langle \operatorname{rel} r \rangle_k \langle s'' \rangle_s \langle h_1, h_2 \cdot h_3'', H'' \rangle_h \langle N_1, N_3'' \cup N_2 \rangle_r \xrightarrow{\Gamma, A_1, B_1} \operatorname{abort}$ and hence that $\langle \operatorname{rel} r \rangle_k \langle s \rangle_s \langle h_1, h_3 \cdot h_2, H \rangle_h \langle N_1, N_3 \cap N_2 \rangle_r \xrightarrow[\Gamma, A_1, B_1]{}^* abort.$

Otherwise, $h_r \subseteq h_1$, by (2), $<\mathbf{rel} \ r>_k < s''>_s < h_1, h_2 \cdot h''_3, H''>_h < N_1, N''_3 \cup N_2 >_r \xrightarrow{\Gamma, A_1, B_1}$ $<\cdot>_k < [s'' | r \mapsto 1]>_s < h_1 - h_r, h_2 \cdot h''_3, H'' \cdot h_r>_h < N_1 - \{r\}, N''_3 \cup N_2 >_r$ By (3) $<\cdot>_k < [s'' | r \mapsto 1]>_s < h_1 - h_r, h_2 \cdot h''_3, H'' \cdot h_r>_h < N_1 - \{r\}, N''_3 \cup N_2 >_r \rightsquigarrow^*_{\Gamma, A', B'}$ $<\cdot>_k < s'>_s < h_1 - h_r, h_2 \cdot h'_3, H'>_h < N_1 - \{r\}, N''_3 \cup N_2 >_r$ Hence, $<\mathbf{rel} \ r>_k < s>_s < h_1, h_2 \cdot h_3, H>_h < N_1, N_3 \cup N_2 >_r \xrightarrow{\overline{\Gamma, A_1 \cup A_2, B_1 \cup B_2}} < \cdot>_k < s'>_s < h_1 - h_r, h_2 \cdot h'_3, H'>_h < N_1 - \{r\}, N''_3 \cup N_2 >_r$

Proof. (Theorem 4.3) By induction on the lengths of α_1 and α_2 .

- when one of the traces is empty.
 - Without loss of generality, assume that $\alpha_2 = \epsilon$, then $\alpha = \alpha_1$
 - (1) If $\langle \alpha \rangle_k \langle s \rangle_s \langle h, h_3, H \rangle_h \langle N, N_3 \rangle_r \xrightarrow{\Gamma, A_1 \cup A_2, B_1 \cup B_2}^*$ **abort**, then $\langle \alpha_1 \rangle_k \langle s \rangle_s \langle h_1, h_3 \cdot h_2, H \rangle_h \langle N_1, N_3 \cup N_2 \rangle_r \xrightarrow{\Gamma, A_1, B_1}^*$ **abort** by Lemma 4.2.
 - (2) If $\langle \alpha \rangle_k \langle s \rangle_s \langle h, h_3, H \rangle_h \langle N, N_3 \rangle_r \xrightarrow{\Gamma, A_1 \cup A_2, B_1 \cup B_2} * \langle \cdot \rangle_k \langle s' \rangle_s \langle h', h'_3, H' \rangle_h \langle N', N'_3 \rangle_r$, by Lemma 4.2, there are $h'_1, h'_2 = h_2, N'_1, N'_2 = N_2$ such that $N'_1 \cap N'_2 = \emptyset$, $N' = N'_1 \cup N'_2, h' = h'_1 \cdot h'_2$ and $\langle \alpha_1 \rangle_k \langle s \rangle_s \langle h_1, h_3 \cdot h_2, H \rangle_h \langle N_1, N_3 \cup N_2 \rangle_r \xrightarrow{\Gamma, A_1, B_1} * \langle \cdot \rangle_k \langle s' \rangle_s \langle h'_1, h'_3 \cdot h'_2, H' \rangle_h \langle N'_1, N'_3 \cup N'_2 \rangle_r$.

The result follows.

• $\alpha_1 = \lambda_1 \alpha'_1, \ \alpha_2 = \lambda_2 \alpha'_2, \ \text{and} \ \alpha \in \alpha_{1\{A_1\}} \|_{\{A_2\}} \alpha_2.$ If $\langle \alpha \rangle_k \langle s \rangle_s \langle h, h_3, H \rangle_h \langle N, N_3 \rangle_r \xrightarrow[\Gamma,A_1 \cup A_2,B_1 \cup B_2]{}^*$ **abort**, then $\operatorname{writes}(\lambda_1) \cap \operatorname{free}(\lambda_2) \neq \emptyset$ or $(\operatorname{writes}(\lambda_2) \cap \operatorname{free}(\lambda_1) \neq \emptyset$. Since $\operatorname{writes}(\alpha_1) \cap A_2 = \emptyset$ and $\operatorname{writes}(\alpha_2) \cap A_1 = \emptyset$ and $N_1 \cap N_2 = \emptyset$ and $h_1 \perp h_2$, it follows that either $\langle \lambda_1 \rangle_k \langle s \rangle_s \langle h_1, h_3 \cdot h_2, H \rangle_h \langle N_1, N_3 \cup N_2 \rangle_r \xrightarrow[\Gamma,A_1,B_1]{}^*$ abort or $\langle \lambda_2 \rangle_k \langle s \rangle_s \langle h_2, h_3 \cdot h_1, H \rangle_h \langle N_2, N_3 \cup N_1 \rangle_r \xrightarrow[\Gamma,A_2,B_2]{}^*$ abort.

The result then follows.

Otherwise, without loss of generality, assume that: $\alpha = \lambda \alpha_3$ and $\alpha_3 \in \alpha'_1 \{A_1\} \|_{\{A_2\}} \mu \alpha'_2$. (1) If $\langle \alpha \rangle_k \langle s \rangle_s \langle h, h_3, H \rangle_h \langle N, N_3 \rangle_r \xrightarrow{\Gamma, A_1 \cup A_2, B_1 \cup B_2}^*$ abort, then either $\langle \lambda \rangle_k \langle s \rangle_s \langle h, h_3, H \rangle_h \langle N, N_3 \rangle_r \xrightarrow{\Gamma, A_1 \cup A_2, B_1 \cup B_2}^*$ abort or there is a local state $\langle s'' \rangle_s \langle h'', h''_3, H'' \rangle_h \langle N'', N''_3 \rangle_r$ such that $\langle \lambda \rangle_k \langle s \rangle_s \langle h, h_3, H \rangle_h \langle N, N_3 \rangle_r \xrightarrow{\Gamma, A_1 \cup A_2, B_1 \cup B_2}^*$ $\langle \cdot \rangle_k \langle s'' \rangle_s \langle h'', h''_3, H'' \rangle_h \langle N'', N''_3 \rangle_r$ and $\langle \alpha_3 \rangle_k \langle s'' \rangle_s \langle h'', h''_3, H'' \rangle_h \langle N'', N''_3 \rangle_r$ $\xrightarrow{\Gamma, A_1 \cup A_2, B_1 \cup B_2}^*$ abort. In the first subgraph by Lemma 4.1, we get $\langle \lambda \rangle_s \langle s \rangle \langle h \rangle_s \langle h \rangle_s h \rangle_s \langle h$

In the first subcase, by Lemma 4.1, we get $\langle \lambda \rangle_k \langle s \rangle_s \langle h_1, h_3 \cdot h_2, H \rangle_h \langle N_1, N_3 \cup N_2 \rangle_r \xrightarrow[\Gamma,A_1,B_1]{}^*$ **abort**. So $\langle \alpha_1 \rangle_k \langle s \rangle_s \langle h_1, h_3 \cdot h_2, H \rangle_h \langle N_1, N_3 \cup N_2 \rangle_r \xrightarrow[\Gamma,A_1,B_1]{}^*$ **abort**

In the second subcase, by Lemma 4.1, either $\langle \lambda \rangle_k \langle s \rangle_s \langle h_1, h_3 \cdot h_2, H \rangle_h \langle N_1, N_3 \cup N_2 \rangle_r \xrightarrow[\Gamma, A_1, B_1]{}^*$ abort and hence $<\alpha_1>_k<s>_s<h_1,h_3\cdot h_2,H>_h<N_1,N_3\cup N_2>_r\xrightarrow{}*$ abort; or there are h_1'', N_1'' such that $h'' = h_1'' \cdot h_2$ and $N_1'' \cap N_2 = \emptyset$ and $N'' = N_1'' \cup N_2$ and $\langle \lambda \rangle_k \langle s \rangle_s \langle h_1, h_3 \cdot h_2, H \rangle_h \langle N_1, N_3 \cup N_2 \rangle_r \xrightarrow{} (\Gamma, A_1, B_1)^* \langle \cdot \rangle_k \langle s'' \rangle_s \langle h_1'', h_3'' \cdot h_2, H'' \rangle_h \langle h_3 \cdot h_3 \cdot h_3 \cdot h_3 \cdot h_3 \cdot h_3 \rangle_h \langle h_3 \cdot h_3 \cdot h_3 \cdot h_3 \cdot h_3 \cdot h_3 \cdot h_3 \rangle_h \langle h_3 \cdot h_3 \cdot h_3 \cdot h_3 \cdot h_3 \cdot h_3 \rangle_h \langle h_3 \cdot h_3 \cdot h_3 \cdot h_3 \cdot h_3 \cdot h_3 \rangle_h \langle h_3 \cdot h_3 \cdot h_3 \cdot h_3 \cdot h_3 \cdot h_3 \rangle_h \langle h_3 \cdot h_3 \cdot h_3 \cdot h_3 \cdot h_3 \cdot h_3 \cdot h_3 \rangle_h \langle h_3 \cdot h_3 \cdot$ $N_1'', N_3'' \cup N_2 >_r.$ By the induction hypothesis for α_3 , we have either $\langle \alpha'_1 \rangle_k \langle s'' \rangle_s \langle h''_1, h''_3 \cdot h_2, H'' \rangle_h \langle N''_1, N''_3 \cup N_2 \rangle_r \xrightarrow[\Gamma, A_1, B_1]{}^*$ abort and hence $\langle \alpha_1 \rangle_k \langle s \rangle_s \langle h_1, h_3 \cdot h_2, H \rangle_h \langle N_1, N_3 \cup N_2 \rangle_r \xrightarrow[\Gamma, A_1, B_1]{}^* \text{ abort.}$ or $\langle \alpha_2 \rangle_k \langle s'' \rangle_s \langle h_2, h''_3 \cdot h''_1, H'' \rangle_h \langle N_2, N''_3 \cup N'' \rangle_r \xrightarrow[\Gamma, A_2, B_2]{}^* \text{ abort.}$ Since $writes(\alpha_1) \cap A_2 = \emptyset$ and $writes(\alpha_1) \cap B_2 = \emptyset$, by environment move, we get < $\alpha_2 \!\!>_k <\!\!s \!\!>_s <\!\!h_2, h_3 \cdot h_1, H \!\!>_h <\!\!N_2, N_3 \cup N \!\!>_r \rightsquigarrow_{\Gamma,A_2,B_2} <\!\!\alpha_2 \!\!>_k <\!\!s''\!\!>_s <\!\!h_2, h''_3 \cdot h''_1, H''\!\!>_h <\!\!m_2 <\!\!m_2$ $N_2, N_3'' \cup N'' >_r$ and hence $<\alpha_2>_k< s>_s< h_2, h_3 \cdot h_1, H>_h< N_2, N_3 \cup N>_r \xrightarrow{}{}_{\Gamma \to 0} + \delta_2$ abort. The result then follows. $(2) \ \text{If } <\!\alpha\!>_k <\!s\!>_s <\!h,h_3,H\!>_h <\!N,N_3\!>_r \xrightarrow[\Gamma,A_1\cup A_2,B_1\cup B_2]{}^* <\!\cdot\!>_k <\!s'\!>_s <\!h',h'_3,H'\!>_h <\!$ $N', N'_{3} >_{r}, \text{ then there is a local state } < s'' >_{s} < h'', h''_{3}, H'' >_{h} < N'', N''_{3} >_{r} \text{ such that } < \lambda >_{k} < s >_{s} < h, h_{3}, H >_{h} < N, N_{3} >_{r} \xrightarrow{}_{\Gamma,A_{1} \cup A_{2},B_{1} \cup B_{2}} * < \cdot >_{k} < s'' >_{s} < h'', h''_{3}, H'' >_{h} < N''_{h} >_{h}$ $N'', N_3'' >_r \text{ and } <\alpha_3 >_k < s'' >_s < h'', h_3'', H'' >_h < N'', N_3'' >_r \xrightarrow[\Gamma, A_1 \cup A_2, B_1 \cup B_2]{}^* < \cdot >_k < s' >_s < s' >$ $h', h'_3, H' >_h < N', N'_3 >_r.$ Use Lemma 4.1 for the first step. If $\langle \lambda \rangle_k \langle s \rangle_s \langle h_1, h_3 \cdot h_2, H \rangle_h \langle N_1, N_3 \cup N_2 \rangle_r \xrightarrow[\Gamma, A_1, B_1]{}^*$ abort, we get $\langle \alpha_1 \rangle_k \langle n_1 \rangle_h \langle n_2 \rangle_h \langle n_3 \rangle_h \langle n_4 \rangle_h \langle n_4$ $s >_s < h_1, h_3 \cdot h_2, H >_h < N_1, N_3 \cup N_2 >_r \xrightarrow{\Gamma, A_1, B_1}^*$ abort as above. otherwise, there are h_1'' , N_1'' such that $h'' = h_1'' \cdot h_2$ and $N_1'' \cap N_2 = \emptyset$ and $N'' = N_1'' \cup N_2$ and $\langle \lambda \rangle_k \langle s \rangle_s \langle h_1, h_3 \cdot h_2, H \rangle_h \langle N_1, N_3 \cup N_2 \rangle_r \xrightarrow{} * \langle \cdot \rangle_k \langle s'' \rangle_s \langle h_1, h_3 \cdot h_2, H \rangle_h \langle h_1, h_3 \cup N_2 \rangle_r \xrightarrow{} * \langle \cdot \rangle_k \langle s'' \rangle_s \langle h_1, h_3 \cdot h_2, H \rangle_h \langle h_1, h_3 \cup N_2 \rangle_r \xrightarrow{} * \langle \cdot \rangle_k \langle s'' \rangle_s \langle h_1, h_3 \cdot h_2, H \rangle_h \langle h_1, h_2 \cap h_1 \rangle_s \langle h_1, h_2 \cap h_1 \rangle_s \langle h_1, h_2 \cap h_2 \cap h_1 \rangle_s \langle h_1, h_2 \cap h_1 \rangle_s \langle h_1, h_2 \cap h_1 \rangle_s \langle h_1, h_2 \cap h_2 \cap h_1 \rangle_s \langle h_1, h_2 \cap h_1 \rangle_s \langle h_1, h_2 \cap h_1 \rangle_s \langle h_1, h_2 \cap h_1 \rangle_s \langle h_1, h_2 \cap h_2 \cap h_2 \cap h_1 \rangle_s \langle h_1, h_2 \cap h_2 \cap h_2 \cap h_1 \rangle_s \langle h_1, h_2 \cap h_2 \cap h_2 \cap h_1 \rangle_s \langle h_1, h_2 \cap h_2$ $h_1'', h_3'' \cdot h_2, H'' >_h < N_1'', N_3'' \cup N_2 >_r.$ The induction hypothesis for α_3 implies that a), either $\langle \alpha'_1 \rangle_k \langle s'' \rangle_s \langle h''_1, h''_3 \cdot h_2, H'' \rangle_h \langle N''_1, N''_3 \cup N_2 \rangle_r \xrightarrow[\Gamma,A_1,B_1]{}^*$ **abort**, so that $<\!\!\alpha_1\!\!>_k<\!\!s\!\!>_s<\!\!h_1,h_3\cdot h_2,H\!\!>_h<\!\!N_1,N_3\cup N_2\!\!>_r\xrightarrow[\Gamma,A_1,B_1]{}^*$ abort. b), or $<\alpha_2>_k< s''>_s< h_2, h''_3\cdot h''_1, H''>_h< N_2, N''_3\cup N''_1>_r \xrightarrow{} * abort.$ we get $<\alpha_2>_k<s>_s<h_2, h_3\cdot h_1, H>_h<N_2, N_3\cup N_1>_r\xrightarrow[\Gamma, A_2, B_2]{}^*$ abort as above. c), or there are h'_1, h'_2, N'_1, N'_2 such that $N'_1 \cap N'_2 = \emptyset$, $N' = N'_1 \cup N'_2, h' = h'_1 \cdot h'_2$ and $< \alpha'_1 >_k < s'' >_s < h''_1, h''_3 \cdot h_2, H'' >_h < N''_1, N''_3 \cup N_2 >_r \xrightarrow{} r < \cdot >_k < s' >_s <$ $h'_1, h'_3 \cdot h'_2, H' >_h < N'_1, N'_3 \cup N'_2 >_r \text{ and } <\alpha_2 >_k < s'' >_s < h_2, h''_3 \cdot h''_1, H'' >_h < N_2, N''_3 \cup$

$$\begin{split} N_1'' >_r &\xrightarrow{} \\ \overrightarrow{\Gamma, A_2, B_2}^* < \cdot >_k < s' >_s < h_2', h_3' \cdot h_1', H' >_h < N_2', N_3' \cup N_1' >_r. \\ &\text{Hence, } < \alpha_1 >_k < s >_s < h_1, h_3 \cdot h_2, H >_h < N_1, N_3 \cup N_2 >_r \xrightarrow{} \\ \overrightarrow{\Gamma, A_1, B_1}^* < \cdot >_k < s' >_s < h_1', h_3' \cdot h_2', H' >_h < N_1', N_3' \cup N_2' >_r. \\ &\text{Since writes}(\alpha_1) \cap A_2 = \emptyset \text{ and writes}(\alpha_1) \cap B_2 = \emptyset, \text{ by environment move, we get} \\ < \alpha_2 >_k < s >_s < h_2, h_3 \cdot h_1, H >_h < N_2, N_3 \cup N_1 >_r \xrightarrow{} \\ \overrightarrow{\Gamma, A_2, B_2}^* < \cdot >_k < s' >_s < h_2', h_3' \cdot h_1', H' >_h < N_2' < N_3 \cup N_1 >_r \\ &N_2', N_3' \cup N_1' >_r. \end{split}$$

That completes the proof.

This work is licensed under the Creative Commons Attribution License. To view a copy of this license, visit https://creativecommons.org/licenses/by/4.0/ or send a letter to Creative Commons, 171 Second St, Suite 300, San Francisco, CA 94105, USA, or Eisenacher Strasse 2, 10777 Berlin, Germany