

# Polynomial stability of piezoelectric beams with magnetic effect and tip body

Yanning An, Wenjun Liu\* and Aowen Kong

School of Mathematics and Statistics, Nanjing University of Information Science and Technology, Nanjing 210044, China

## Abstract

In this paper, we consider a dissipative system of one-dimensional piezoelectric beam with magnetic effect and a tip load at the free end of the beam, which is modeled as a special form of double boundary dissipation. Our main aim is to study the well-posedness and asymptotic behavior of this system. By introducing two functions defined on the right boundary, we first transform the original problem into a new abstract form, so as to show the well-posedness of the system by using Lumer-Philips theorem. We then divide the original system into a conservative system and an auxiliary system, and show that the auxiliary problem generates a compact operator. With the help of Weyl's theorem, we obtain that the system is not exponentially stable. Moreover, we prove the polynomial stability of the system by using a result of Borichev and Tomilov (Math. Ann. **347** (2010), 455–478).

**2010 Mathematics Subject Classification:** 35B40, 95C20, 93D20.

**Keywords:** polynomial stability, semigroup method, lack of exponential stability.

## 1 Introduction

Piezoelectric materials are materials that can exchange mechanical energy, electrical energy and nuclear energy in motion. Their structures are generally composed of beams or slabs. Due to the advantages like small size, high power density, fast response time, large mechanical force and high resolution, they have more and more application prospects in many fields, such as the latest cutting-edge applications: cardiac pacemaker [8], course changing bullet, structural health monitoring [7], nano locator [15], ultrasonic imaging device, ultrasonic welding and cleaning device, energy collection [11]. The piezoelectric effect usually is shown as two types. One is to generate charge in the interior by applying mechanical force, which is called direct piezoelectric effect [19, 27]. Another is from the external electric field through its internal mechanical stress, which is called reverse piezoelectric effect. Due to the asymmetry of crystals, the above two effects have the same origin [14]. In the piezoelectric beam, which constitutes the electronic device, the mechanical disturbance responds in the form of electricity. When piezoelectric materials are integrated into components of electronic circuits, the mechanical effects on structures are also very important when they are interfered by electrical, magnetic or electromagnetic properties. There

---

\*Corresponding author. Email address: wjliu@nuist.edu.cn (W. J. Liu).

are three main ways to drive piezoelectric materials in such electronic devices: to supply voltage, current or charge to the electrodes. Therefore, it is very important to describe the interaction of these three effects (mechanical, electrical and magnetic) for understanding the stability conditions of these systems ([3,9,40]). The equation of piezoelectric beam with magnetic effect is based on the description of electromagnetic coupling by Maxwell equation and the mechanical behavior of beam by Mindlin-Timoshenko theory ([3,9]).

Let us refer to several previous works on the stability results for the piezoelectric models. In [29,30], Morris and Özer considered the effects of three effects (mechanical, electrical and magnetic) for the first time. They studied the dissipative systems

$$\begin{aligned}\rho v_{tt} - \alpha v_{xx} + \gamma \beta p_{xx} &= 0, & (x, t) \in (0, L) \times (0, T), \\ \mu p_{tt} - \beta p_{xx} + \gamma \beta v_{xx} &= 0, & (x, t) \in (0, L) \times (0, T),\end{aligned}\tag{1.1}$$

with boundary conditions

$$\begin{aligned}v(0, t) &= \alpha v_x(L, t) - \gamma \beta p_x(L, t) = 0, & t \in (0, T), \\ p(0, t) &= \beta p_x(L, t) - \gamma \beta v_x(L, t) + V(t) = 0, & t \in (0, T),\end{aligned}\tag{1.2}$$

where  $v(x, t)$  and  $p(x, t)$  represent respectively the displacement of the upper and lower plates, and  $\rho, \mu, \alpha, \beta, \gamma$  denote respectively the mass density per unit volume, the magnetic permeability, the elastic stiffness, the beam coefficient of impermeability and the piezoelectric coefficient. The relationship between  $\alpha, \beta$  and  $\gamma$  is given as  $\alpha = \alpha_1 + \gamma^2 \beta$ , where  $\alpha_1 > 0$  represents the elastic stiffness of the model derived from the electrostatic and quasi-static methods of Euler Bernoulli small displacement (see example [30]). And  $V(t) = \frac{p_t(L, t)}{h}$  is the prescribed voltage on the beam electrodes. The authors showed that system (1.1)-(1.2) with only one boundary control was not exponentially stable.

In [34], Ramos et al. studied a one-dimensional system of piezoelectric beams with magnetic effect, the system is shown as

$$\begin{aligned}\rho v_{tt} - \alpha v_{xx} + \gamma \beta p_{xx} &= 0, & (x, t) \in (0, L) \times (0, T), \\ \mu p_{tt} - \beta p_{xx} + \gamma \beta v_{xx} &= 0, & (x, t) \in (0, L) \times (0, T),\end{aligned}\tag{1.3}$$

with boundary conditions

$$\begin{aligned}v(0, t) &= \alpha v_x(L, t) - \gamma \beta p_x(L, t) + \frac{\xi_1}{h} v_t(L, t) = 0, & t \in (0, T), \\ p(0, t) &= \beta p_x(L, t) - \gamma \beta v_x(L, t) + \frac{\xi_2}{h} p_t(L, t) = 0, & t \in (0, T),\end{aligned}\tag{1.4}$$

where  $\xi_i, i = 1, 2$  are positive constant feedback gains. By using multiplier method, the authors proved that the system is exponentially stable, and obtained that the exponential stability is equivalent to the exact observability at the boundary.

Yang and Wang [39] studied the piezoelectric layer actuated by a voltage source without

magnetic effects. They modeled the system

$$\begin{cases} u_{tt} - \alpha_u u_{xx} - G_u z = 0, & (x, t) \in (0, L) \times (0, T), \\ v_{tt} - \alpha_v v_{xx} + G_v z = 0, & (x, t) \in (0, L) \times (0, T), \\ y_{tt} - I y_{xxtt} + y_{xxxx} - G_1 z_x = 0, & (x, t) \in (0, L) \times (0, T), \\ \phi = \frac{1}{h}(-\varphi + \psi + H\omega_x), & (x, t) \in (0, L) \times (0, T), \end{cases} \quad (1.5)$$

with the boundary conditions

$$\begin{cases} u(0, t) = v(0, t) = y(0, t) = y_x(0, t) = 0, & t \in (0, T), \\ u_x(L, t) = l_1 u_t(L, t), & t \in (0, T), \\ v_x(L, t) = -l_2 v_t(L, t), & t \in (0, T), \\ y_{xx}(L, t) = -l_3 y_{xt}(L, t), & t \in (0, T), \\ I y_{xtt}(L, t) - y_{xxx}(L, t) + G_1 z(1, t) = 0, & t \in (0, T), \end{cases} \quad (1.6)$$

where  $u(x, t)$  and  $v(x, t)$  are the longitudinal displacements of the bottom layer and the top layer, respectively, and  $y(x, t)$  is the transverse displacement of each floor (the transverse displacement of the three floors is regarded as equal). By using the method of Riesz basis, the authors obtained the exponential stability of system (1.5)-(1.6).

Recently, some researchers have studied Timoshenko system with tip body and hybrid system with tip load damped, see [31, 35, 37]. In industry, many piezoelectric beam devices are in the form of a boundary with a tip body, such as the electrostatic energy harvester mentioned in reference [12, 36]. The tip body has mass, so its appearance will bring tip inertia, which will affect the stability of the system. Therefore, it is necessary to study the piezoelectric beam system with tip load.

In this paper, we shall study the polynomial stability of a piezoelectric beam system with magnetic effect and tip body. Considering a piezoelectric beam with a tip load, the beam is clamped at  $x = 0$ , and the tip is fixed at  $x = L$ . The center of mass of the tip is the connection point between the tip body and the piezoelectric beam plate. We assume that the beam interacts with the tip body, and the force of the vibrating beam moves to the end load according to Newton's law. By using the feedback boundary force control to the displacement velocity at  $x = L$ , dissipation is introduced into the piezoelectric system. Then the coupling model is given by

$$\begin{cases} \rho V_{tt} - \alpha V_{xx} + \gamma \beta P_{xx} = 0, & (x, t) \in (0, L) \times (0, T), \\ \mu P_{tt} - \beta P_{xx} + \gamma \beta V_{xx} = 0, & (x, t) \in (0, L) \times (0, T), \end{cases} \quad (1.7)$$

with the double boundary conditions

$$\begin{aligned} V(0, t) &= P(0, t) = 0, & t \in (0, T), \\ \alpha V_x(L, t) - \gamma \beta P_x(L, t) + \xi_1 V_t(L, t) + m_1 V_{tt}(L, t) &= 0, & t \in (0, T), \\ \beta P_x(L, t) - \gamma \beta V_x(L, t) + \xi_2 P_t(L, t) + m_2 P_{tt}(L, t) &= 0, & t \in (0, T), \end{aligned} \quad (1.8)$$

and the initial conditions

$$(V(x, 0), V_t(x, 0), P(x, 0), P_t(x, 0)) = (V_0(x), V_1(x), P_0(x), P_1(x)), x \in (0, L). \quad (1.9)$$

where  $V(x, t), P(x, t)$  represent respectively the longitudinal displacements of the upper and lower plates,  $\xi_1, \xi_2$  are positive constant feedback gains, and  $m_1, m_2$  are mass of tip load. Equations (1.8)<sub>2</sub> and (1.8)<sub>3</sub> are obtained by the force balance at the end  $x = L$ . The third term in the boundary conditions at the end  $x = L$  represents the influence of the magnetic effect, and the first two terms represent shear force.

In this paper, we study the stability of a piezoelectric beam with a tip on both plates. After getting the well-posedness of the system by using the classical Lumer-Philips theorem, we will start to analyze the stability of the system. By dealing with the resolvent equation of system (1.7)-(1.9), we obtain an observable inequality. Then, combined with Borichev and Tomilov theorem [5], we will prove that the system is polynomial stable. The difficulty of stability analysis lies in how to obtain that the system is lack of uniform stability. Because the system has only two equations, and the partial derivatives in the  $x$  direction of the equations are second order. So it is difficult to construct a suitable function sequence and use the usual Gearhart-Herbst-Prüss-Huang theorem as in [23, 24] to prove that the system is not exponentially stable. To overcome this difficulty, we divide the original system into a conservative system and an auxiliary system, and show that the auxiliary problem generates a compact operator. By using the Wely's theorem [38], we get that the growth bound of the original system is 0, that is, the system is not uniformly exponential stable. Since uniform stability and uniform exponential stability are equivalent in strongly continuous semigroups, we show that the system is not uniformly stable. Some typical problems can be found in references [1, 2, 4, 6, 16–18, 20, 22–24, 24–26, 28, 32, 33].

The structure of this paper is as follows. In the next section, we will give the well-posedness of system (1.7)-(1.9). In Section 3, we will show the lack of uniform stability. Finally, we will get the polynomial stability of the system in Section 4.

## 2 Well-posedness

In this section, we give a well-posedness result for problem (1.7)-(1.9) by using a semigroup approach.

To define the semigroup associated with (1.7)-(1.9), we introduce two new functions which are defined by

$$u(t) = V_t(L, t) \quad \text{and} \quad \eta(t) = P_t(L, t), \quad t > 0, \quad (2.1)$$

respectively, with

$$u(0) = V_1(L) = u_0 \quad \text{and} \quad \eta(0) = P_1(L) = \eta_0. \quad (2.2)$$

By using the definition of  $u, \eta$ , we can change system (1.7)-(1.9) to

$$\rho V_{tt} - \alpha V_{xx} + \gamma \beta P_{xx} = 0, \quad (x, t) \in (0, L) \times (0, T), \quad (2.3)$$

$$\mu P_{tt} - \beta P_{xx} + \gamma \beta V_{xx} = 0, \quad (x, t) \in (0, L) \times (0, T), \quad (2.4)$$

with the boundary conditions

$$V(0, t) = \alpha V_x(L, t) - \gamma \beta P_x(L, t) + \xi_1 u(t) + m_1 u_t(t) = 0, \quad t \in (0, +\infty), \quad (2.5)$$

$$P(0, t) = \beta P_x(L, t) - \gamma \beta V_x(L, t) + \xi_2 \eta(t) + m_2 \eta_t(t) = 0, \quad t \in (0, +\infty), \quad (2.6)$$

and the initial conditions

$$(V(x, 0), V_t(x, 0), P(x, 0), P_t(x, 0), u(0), \eta(0)) = (V_0, V_1, P_0, P_1, u_0, \eta_0) \quad x \in (0, L). \quad (2.7)$$

The energy of system (2.3)-(2.7) is given by

$$E(t) = \frac{1}{2} \int_0^L \left[ \rho |V_t|^2 + \alpha_1 |V_x|^2 + \mu |P_t|^2 + \beta |\gamma V_x - P_x|^2 \right] dx + \frac{m_1}{2} |u|^2 + \frac{m_2}{2} |\eta|^2. \quad (2.8)$$

Multiplying (2.3), (2.4) by  $V_t$  and  $P_t$  respectively, and using the boundary conditions (2.5)-(2.6), we get

$$\frac{d}{dt} E(t) = -\xi_1 |V_t(L, t)|^2 - \xi_2 |P_t(L, t)|^2. \quad (2.9)$$

Let us define the space  $\mathcal{H}$  as

$$\mathcal{H} := H_*^1(0, L) \times L^2(0, L) \times H_*^1(0, L) \times L^2(0, L) \times \mathbb{C} \times \mathbb{C},$$

for  $H_*^1(0, L) = \{f \in H^1(0, L) : f(0) = 0\}$ , equipped with the inner product

$$\begin{aligned} \langle U_1, U_2 \rangle_{\mathcal{H}} &= \int_0^L \left[ \rho \Phi_1 \overline{\Phi_2} + \mu \Theta_1 \overline{\Theta_2} + \alpha_1 V_{1,x} \overline{V_{2,x}} + \beta (\gamma V_{1,x} - P_{1,x}) \overline{(\gamma V_{2,x} - P_{2,x})} \right] dx \\ &\quad + m_1 u_1 \overline{u_2} + m_2 \eta_1 \overline{\eta_2}, \end{aligned}$$

where  $U_i = (V_i, \Phi_i, P_i, \Theta_i, u_i, \eta_i) \in H, i = 1, 2$ . Set the vector function  $U = (V, V_t, P, P_t, u, \eta)^T$ , then system (2.3)-(2.7) can be written as

$$\begin{cases} U_t = \mathcal{A}U \\ U(0) = U_0 \end{cases} \quad (2.10)$$

where  $U_0 = (V_0, V_1, P_0, P_1, u_0, \eta_0)^T$  and  $\mathcal{A} : \mathcal{D}(\mathcal{A}) \subset \mathcal{H} \rightarrow \mathcal{H}$  is given by

$$\mathcal{A} = \begin{bmatrix} 0 & \text{I} & 0 & 0 & 0 & 0 \\ \frac{\alpha}{\rho} \partial_{xx} & 0 & -\frac{\gamma \beta}{\rho} \partial_{xx} & 0 & 0 & 0 \\ 0 & 0 & 0 & \text{I} & 0 & 0 \\ -\frac{\gamma \beta}{\mu} \partial_{xx} & 0 & \frac{\beta}{\mu} \partial_{xx} & 0 & 0 & 0 \\ -\frac{\alpha}{m_1} \varsigma & 0 & \frac{\gamma \beta}{m_1} \varsigma & 0 & -\frac{\xi_1}{m_1} \text{I} & 0 \\ \frac{\gamma \beta}{m_2} \varsigma & 0 & -\frac{\beta}{m_2} \varsigma & 0 & 0 & -\frac{\xi_2}{m_2} \text{I} \end{bmatrix},$$

with  $\varsigma \circ \varphi = \varphi_x(L)$ . The domain of the operator  $\mathcal{A}$  is given by

$$\mathcal{D}(\mathcal{A}) := \{U \in \mathcal{H}; \Phi, \Theta \in H_*^1(0, L), V, P \in H^2(0, L), \Phi(L) = u, \Theta(L) = \eta\},$$

with  $U = (V, \Phi, P, \Theta, u, \eta)$ .

We now show that operator  $\mathcal{A}$  generates a  $C_0$ -semigroup  $\{\mathcal{S}_{\mathcal{A}}(t)\}_{t \geq 0}$  of contractions in the space  $\mathcal{H}$ . For this purpose, we need the following two lemmas.

**Lemma 2.1** *The operator  $\mathcal{A}$  is dissipative and satisfies that for any  $U \in \mathcal{D}(\mathcal{A})$ ,*

$$\operatorname{Re}\langle \mathcal{A}U, U \rangle_H = -\xi_1|u|^2 - \xi_2|\eta|^2 \leq 0. \quad (2.11)$$

**Proof.** For any  $U \in \mathcal{D}(\mathcal{A})$ , relation (2.11) can be easily verified by using the inner product in  $\mathcal{H}$  and integration by parts.  $\square$

**Lemma 2.2** *The operator  $\mathcal{A}$  is bijective and  $0 \in \varrho(\mathcal{A})$ , where  $\varrho(\mathcal{A})$  is the resolvent set of  $\mathcal{A}$ .*

**Proof.** We need to prove that for any  $F = (f_1, f_2, f_3, f_4, f_5, f_6) \in \mathcal{H}$ , there exists a  $U = (V, \Phi, P, \Theta, u, \eta) \in \mathcal{D}(\mathcal{A})$  such that

$$\mathcal{A}U = F.$$

Equivalently, we shall consider the existence of unique solution of the system

$$\begin{cases} \Phi = f_1 & \text{in } H_*^1(0, L), \\ \frac{\alpha}{\rho}V_{xx} - \frac{\gamma\beta}{\rho} = f_2 & \text{in } L^2(0, L), \\ \Theta = f_3 & \text{in } H_*^1(0, L), \\ \frac{\beta}{\mu}P_{xx} - \frac{\gamma\beta}{\mu} = f_4 & \text{in } L^2(0, L), \\ -\frac{\alpha}{m_1}V_x(L, t) + \frac{\gamma\beta}{m_1}P_x(L, t) - \frac{\xi_1}{m_1}u = f_5, \\ -\frac{\beta}{m_2}P_x(L, t) + \frac{\gamma\beta}{m_2}V_x(L, t) - \frac{\xi_2}{m_2}\eta = f_6. \end{cases} \quad (2.12)$$

That is, since

$$\begin{aligned} \Phi &= f_1, & \Theta &= f_3, \\ u &= \Phi(L) = f_1(L), & \eta &= \Theta(L) = f_3(L), \end{aligned} \quad (2.13)$$

we need to prove the existence of unique solution of the system

$$\begin{cases} \alpha V_{xx} - \gamma\beta P_{xx} = \rho f_2, \\ \beta P_{xx} - \gamma\beta V_{xx} = \mu f_4, \\ -\alpha V_x(L, t) + \gamma\beta P_x(L, t) = m_1 f_5 + \xi_1 f_1(L), \\ -\beta P_x(L, t) + \gamma\beta V_x(L, t) = m_2 f_6 + \xi_2 f_3(L). \end{cases} \quad (2.14)$$

Consider a coercive and continuous and semi-linear operator  $\mathcal{G} : [H_*^1(0, L) \times H_*^1(0, L)]^2 \rightarrow \mathbb{C}$  defined by

$$\mathcal{G}((w_1, s_1), (w_2, s_2)) = \int_0^L (\alpha w_{1,x} \overline{w_{2,x}} - \gamma\beta w_{1,x} \overline{s_{2,x}} - \gamma\beta s_{1,x} \overline{w_{2,x}} + \beta s_{1,x} \overline{s_{2,x}}) dx,$$

and a continuous linear functional  $\mathcal{F} : H_*^1(0, L) \times H_*^1(0, L) \rightarrow \mathbb{C}$  defined by

$$\mathcal{F}(w, s) = - \int_0^L (\rho f_2 \overline{w} + \mu f_4 \overline{s}) dx - (m_1 f_5 + \xi_1 f_1(L)) \overline{w}(L) - (m_2 f_6 + \xi_2 f_3(L)) \overline{s}(L).$$

By using the Lax-Milgram theorem, we know that there exists a  $(V, P) \in H_*^1(0, L) \times H_*^1(0, L)$  satisfying

$$\mathcal{G}((V, P), (w, s)) = \mathcal{F}(w, s), \quad \text{for all } (w, s) \in H_*^1(0, L) \times H_*^1(0, L).$$

From the estimate and (2.13), there exists a constant  $C > 0$  such that

$$|\mathcal{G}(U, F)| \leq C \|U\|_{\mathcal{H}} \|F\|_{\mathcal{H}},$$

which implies that

$$\|U\|_{\mathcal{H}} \leq \|F\|_{\mathcal{H}} \iff \|\mathcal{A}^{-1}F\|_{\mathcal{H}} \leq \|F\|_{\mathcal{H}}.$$

Consequence, we conclude that the operator  $\mathcal{A}$  generates a  $C_0$ -semigroup  $\{\mathcal{S}_{\mathcal{A}}(t)\}_{t \geq 0}$  of contractions on the space  $\mathcal{H}$  by Lumer-Philips theorem [21]. Thus, the proof of the lemma is completed.  $\square$

Hence, using Lemma 2.1 and Lemma 2.2, we obtain the well-posedness result.

**Theorem 2.1** *Let  $U_0 \in \mathcal{D}(\mathcal{A})$ , there exists a unique solution  $U(t) = \mathcal{S}_{\mathcal{A}}(t)U_0$  of (2.10) such that*

$$U \in C([0, \infty); \mathcal{D}(\mathcal{A})) \cap C^1([0, \infty); \mathcal{H}).$$

### 3 Lack of Uniformly Stability

In this section, we are interested in studying the lack of uniformly stability of the solution of problem (2.3)-(2.7). To show that, we will use the following theorem as a tool.

**Theorem 3.1** ([10]) *Let  $\mathcal{S}(t) = e^{At}$  be a contraction  $C_0$ -semigroup on Hilbert space. Then*

$$\omega_0(\mathcal{S}(t)) = \max\{\omega_{ess}(\mathcal{S}(t)), s(\mathcal{A})\},$$

where  $\omega_0(\mathcal{S}(t))$  is the growth bound,  $\omega_{ess}(\mathcal{S}(t))$  is the essential growth bound, and  $s(\mathcal{A})$  is the spectral bound of the infinitesimal generator  $\mathcal{A}$  of  $\mathcal{S}(t)$ .

**Theorem 3.2** ([38, Weyl's Theorem]) *If the difference of the two operator is compact, then the essential spectrum radius are the same.*

**Proposition 3.1** ([10]) *For a strongly continuous semigroup  $\{e^{At}\}_{t \leq 0}$ , the following assertions are equivalent.*

- (1)  $\{e^{At}\}_{t \leq 0}$  is uniformly exponentially stable.
- (2)  $\{e^{At}\}_{t \leq 0}$  is uniformly stable.

**Lemma 3.1** *Let us fix  $\alpha, \beta, \gamma, \rho, \mu$  and the finite interval  $E = (a, b)$ . Assume that there exists a weak solution to equation*

$$\rho V_{tt} - \alpha V_{xx} + \gamma \beta P_{xx} = 0, \quad (x, t) \in (0, L) \times (0, T), \quad (3.1)$$

$$\mu P_{tt} - \beta P_{xx} + \gamma \beta V_{xx} = 0, \quad (x, t) \in (0, L) \times (0, T), \quad (3.2)$$

If  $q(x) = mx + n$ , ( $m, n \in \mathbb{R}$ ) and the functions

$$\begin{aligned} E_1(t) &= \int_E (\rho |V_t|^2 + \alpha_1 |V_x|^2 + \mu |P_t|^2 + \beta |\gamma V_x - P_x|^2) dx, \quad t \geq 0, \\ I(x, t) &= \rho |V_t(x, t)|^2 + \alpha_1 |V_x(x, t)|^2 + \mu |P_t(x, t)|^2 + \beta |(\gamma V_x - P_x)(x, t)|^2, \quad a \geq x \geq b, t \geq 0, \end{aligned}$$

are integrable in  $[a, b]$ , then there exists a non-negative constant  $M$  satisfying

$$\left| \int_0^T (q(b)I(b, t) - q(a)I(a, t)) dt - \int_0^T m E_1(t) dt \right| \leq M (E_1(T) + E_1(0)).$$

**Proof.** Multiplying (3.1) by  $q(x)\bar{V}_x$ , and integrating over  $E$ , we have

$$\int_a^b \rho V_{tt} q(x) \bar{V}_x dx - \frac{\alpha_1}{2} \int_a^b q(x) \frac{d}{dx} |V_x|^2 dx - \int_a^b \gamma \beta q(x) (\gamma V_{xx} - P_{xx}) \bar{V}_x dx = 0. \quad (3.3)$$

Multiplying (3.2) by  $q(x)\bar{P}_x$ , and integrating over  $E$ , we get

$$\int_a^b \mu P_{tt} q(x) \bar{P}_x dx - \int_a^b \beta q(x) (\gamma V_{xx} - P_{xx}) (-\bar{P}_x) dx = 0. \quad (3.4)$$

Adding (2.5) and (3.4), we obtain

$$\int_a^b (\rho V_{tt} q(x) \bar{V}_x + \mu P_{tt} q(x) \bar{P}_x) dx - \frac{\alpha_1}{2} \int_a^b q(x) \frac{d}{dx} |V_x|^2 dx - \frac{\beta}{2} \int_a^b q(x) \frac{d}{dx} |\gamma V_x - P_x|^2 dx = 0.$$

Integrating by parts over  $E$ , and using the fact of  $q'(x) = m$ , we can show

$$\begin{aligned} \int_a^b (\rho V_{tt} q(x) \bar{V}_x + \mu P_{tt} q(x) \bar{P}_x) dx - \frac{1}{2} [\alpha_1 q(x) |V_x|^2 + \beta q(x) |\gamma V_x - P_x|^2] \Big|_a^b \\ = \frac{1}{2} \int_a^b \alpha_1 m |V_x|^2 + \beta m |\gamma V_x - P_x|^2 dx. \end{aligned} \quad (3.5)$$

Integrating (3.5) over  $[0, T]$ , integrating by parts and applying the Fubini theorem, we obtain

$$\left| \int_0^T (q(b)I(b, t) - q(a)I(a, t)) dt - \int_0^T m E_1(t) dt \right| = 2 \left| \operatorname{Re} \int_E q(x) [\rho V_t \bar{V} + \mu P_t \bar{P}_x] \Big|_0^T dx \right|.$$

By using the Young's inequality and the Hölder's inequality, we can obtain

$$\begin{aligned} \left| \int_0^T (q(b)I(b, t) - q(a)I(a, t)) dt - \int_0^T m E_1(t) dt \right| \\ \leq 2 \|q\|_\infty \left| \operatorname{Re} \int_E [\rho V_t \bar{V} + \mu P_t \bar{P}_x] \Big|_0^T dx \right| \\ \leq 2 \|q\|_\infty \int_a^b [\rho^2 |V_t|^2 + |V_x|^2 + \mu^2 |P_t|^2 + |P_x|^2] \Big|_0^T dx \\ \leq 2 \|q\|_\infty \int_a^b [\rho^2 |V_t|^2 + (1 + 2\gamma^2) |V_x|^2 + \mu^2 |P_t|^2 + 2 |P_x|^2] \Big|_0^T dx \end{aligned}$$



$$\leq M(E_1(T) + E_1(0)),$$

where  $M = 2\|q\|_\infty \max\{\rho, (1 + 2\gamma^2)/\alpha_1, \mu, 2/\beta\}$ . The conclusion follows immediately.  $\square$

Then we consider the undamped piezoelectric beams with tip body

$$\rho\tilde{V}_{tt} - \alpha\tilde{V}_{xx} + \gamma\beta\tilde{P}_{xx} = 0, \quad (x, t) \in (0, L) \times (0, T), \quad (3.6)$$

$$\mu\tilde{P}_{tt} - \beta\tilde{P}_{xx} + \gamma\beta\tilde{V}_{xx} = 0, \quad (x, t) \in (0, L) \times (0, T), \quad (3.7)$$

with  $x \in (0, L), t \leq 0$  and boundary conditions

$$\begin{aligned} \tilde{V}(0, t) &= \alpha\tilde{V}_x(L, t) - \gamma\beta\tilde{P}_x(L, t) + m_1\tilde{u}_t(t) = 0, \quad t \in (0, +\infty), \\ \tilde{P}(0, t) &= \beta\tilde{P}_x(L, t) - \gamma\beta\tilde{V}_x(L, t) + m_2\tilde{\eta}_t(t) = 0, \quad t \in (0, +\infty), \end{aligned} \quad (3.8)$$

with the same initial condition as in (2.7)

$$\left(\tilde{V}(x, 0), \tilde{V}_t(x, 0), \tilde{P}(x, 0), \tilde{P}_t(x, 0), \tilde{u}(0), \tilde{\eta}(0)\right) = (V_0, V_1, P_0, P_1, u_0, \eta_0), \quad x \in (0, L). \quad (3.9)$$

Rewrite system (3.6)-(3.9) as the Cauchy problem

$$\begin{cases} \frac{d}{dt}\tilde{U}(t) = \mathcal{A}_0\tilde{U}(t) \\ \tilde{U}(0) = U_0 \end{cases} \quad (3.10)$$

where  $\tilde{U} = (\tilde{V}, \tilde{\Phi}, \tilde{P}, \tilde{\Theta}, \tilde{u}, \tilde{\eta})$ ,  $U_0 = (V_0, V_1, P_0, P_1, u_0, \eta_0)^T$  and the operator  $\mathcal{A}_0 : \mathcal{D}(\mathcal{A}_0) \subset \mathcal{H} \rightarrow \mathcal{H}$  is given by

$$\mathcal{A}_0 = \begin{bmatrix} 0 & \text{I} & 0 & 0 & 0 & 0 \\ \frac{\alpha}{\rho}\partial_{xx} & 0 & -\frac{\gamma\beta}{\rho}\partial_{xx} & 0 & 0 & 0 \\ 0 & 0 & 0 & \text{I} & 0 & 0 \\ -\frac{\gamma\beta}{\mu}\partial_{xx} & 0 & \frac{\beta}{\mu}\partial_{xx} & 0 & 0 & 0 \\ -\frac{\alpha}{m_1}\varsigma & 0 & \frac{\gamma\beta}{m_1}\varsigma & 0 & 0 & 0 \\ \frac{\gamma\beta}{m_2}\varsigma & 0 & -\frac{\beta}{m_2}\varsigma & 0 & 0 & 0 \end{bmatrix},$$

with  $\varsigma \circ \varphi = \varphi_x(L)$ ,  $\mathcal{D}(\mathcal{A}_0) = \mathcal{D}(\mathcal{A})$ . And the inner product of  $\mathcal{H}$  is given by

$$\text{Re}\langle \mathcal{A}_0\tilde{U}, \tilde{U} \rangle_{\mathcal{H}} = 0, \quad \forall \tilde{U} \in \mathcal{D}(\mathcal{A}_0). \quad (3.11)$$

Next, we will use the the classical semigroups theory to prove the well-posedness of system (3.10).

**Theorem 3.3** *Let  $U_0 \in \mathcal{D}(\mathcal{A}_0)$ , there exists a unique solution  $\tilde{U}(t) = \mathcal{S}_{\mathcal{A}_0}(t)\tilde{U}_0$  of (3.10) such that*

$$\tilde{U} \in C([0, \infty); \mathcal{D}(\mathcal{A}_0)) \cap C^1([0, \infty); \mathcal{H}).$$

**Proof.** From (3.10), the operator  $\mathcal{A}_0$  is skew-hermitian, conservative, closed and densely definite on  $\mathcal{D}(\mathcal{A}_0)$ . Indeed, by using the method similar to Lemma 2.2, we can straightforwardly prove that  $0 \in \rho(\mathcal{A}_0)$ . Thanks to the Lions theorem, we conclude that the operator  $\mathcal{A}_0$  is the infinitesimal generator of  $C_0$ -semigroup of contractions  $\{e^{\mathcal{A}_0 t}\}_{t \geq 0}$ . Then, the conclusion follows immediately.  $\square$

**Remark 3.1** From (3.11) and Theorem 3.3, we straightforward see that  $\{e^{A_0 t}\}_{t \leq 0}$  is a  $C_0$ -group unitary by Stone theorem. And the  $C_0$ -group unitary  $\{e^{A_0 t}\}_{t \leq 0}$  has essential spectrum radius 1. The detailed proof content can be found in reference [10, 37].

**Lemma 3.2** The set  $\{e^{At} - e^{A_0 t}\}_{t \leq 0}$  form a  $C_0$ -semigroup of compact operators.

**Proof.** For any bounded  $U_0^n = (V_0^n, V_1^n, P_0^n, P_1^n, u_0^n, \eta_0^n) \in \mathcal{H}$ , by using theorem 2.1, we have that

$$U^n = e^{At} U_0^n = (V^n, V_t^n, P^n, P_t^n, u^n, \eta^n) \in \mathcal{H}$$

are bounded solutions of (2.3)-(2.7), and thanks to theorem 3.3, we have that

$$\tilde{U}^n = e^{A_0 t} \tilde{U}_0^n = (\tilde{V}^n, \tilde{V}_t^n, \tilde{P}^n, \tilde{P}_t^n, \tilde{u}^n, \tilde{\eta}^n) \in \mathcal{H}$$

are bounded solutions of (3.6)-(3.9). Indeed, we define

$$\begin{aligned} \hat{V}_x^n &= V_x^n - \tilde{V}_x^n, & \hat{P}_x^n &= P_x^n - \tilde{P}_x^n, & \hat{V}_t^n &= V_t^n - \tilde{V}_t^n, & \hat{P}_t^n &= P_t^n - \tilde{P}_t^n, \\ \hat{u}^n &= u^n - \tilde{u}^n, & \hat{\eta}^n &= \eta^n - \tilde{\eta}^n \end{aligned}$$

satisfy the system

$$\rho \hat{V}_{tt}^n - \alpha \hat{V}_{xx}^n + \gamma \beta \hat{P}_{xx}^n = 0, \quad (x, t) \in (0, L) \times (0, T), \quad (3.12)$$

$$\mu \hat{P}_{tt}^n - \beta \hat{P}_{xx}^n + \gamma \beta \hat{V}_{xx}^n = 0, \quad (x, t) \in (0, L) \times (0, T), \quad (3.13)$$

with the boundary conditions

$$\begin{aligned} \hat{V}^n(0, t) &= \hat{P}^n(0, t) = 0, & t &\in (0, T), \\ \alpha \hat{V}_x^n(L, t) - \gamma \beta \hat{P}_x^n(L, t) + \xi_1 u^n(t) + m_1 \hat{u}_t^n(t) &= 0, & t &\in (0, +\infty), \\ \beta \hat{P}_x^n(L, t) - \gamma \beta \hat{V}_x^n(L, t) + \xi_2 \eta^n(t) + m_2 \hat{\eta}_t^n(t) &= 0, & t &\in (0, +\infty), \end{aligned} \quad (3.14)$$

and the initial conditions

$$(\hat{V}^n(x, 0), \hat{V}_t^n(x, 0), \hat{P}^n(x, 0), \hat{P}_t^n(x, 0), \hat{u}(0), \hat{\eta}(0)) = (0, 0, 0, 0, 0, 0), \quad x \in (0, L). \quad (3.15)$$

Then we can show that

$$\|(e^{At} - e^{A_0 t}) U_0^n\|_{\mathcal{H}} = \int_0^L \left( \rho |\hat{V}_t|^2 + \alpha_1 |\hat{V}_x|^2 + \mu |\hat{P}_t|^2 + \beta |\gamma \hat{V}_x - \hat{P}_x|^2 \right) dx + \frac{m_1}{2} |\hat{u}|^2 + \frac{m_2}{2} |\hat{\eta}|^2,$$

and the energy associated with problem (3.12)-(3.15) can be defined by

$$\hat{E}_n(t) = \frac{1}{2} \left\| (\hat{V}, \hat{V}_t, \hat{P}, \hat{P}_t, \hat{u}, \hat{\eta}) \right\|_{\mathcal{H}}^2.$$

Multiplying (3.12), (3.13) by  $\overline{\hat{V}_t^n}$ ,  $\overline{\hat{P}_t^n}$  respectively, integrating by parts over  $(0, L)$ , and using the boundary conditions (3.14), we can obtain

$$\frac{d}{dt} \left[ \int_0^L \left( \rho |\hat{V}_t|^2 + \alpha_1 |\hat{V}_x|^2 + \mu |\hat{P}_t|^2 + \beta |\gamma \hat{V}_x - \hat{P}_x|^2 \right) dx + \frac{m_1}{2} |\hat{u}|^2 + \frac{m_2}{2} |\hat{\eta}|^2 \right]$$

$$= -2\xi_1 \operatorname{Re} u^n(t) \overline{\widehat{u}^n(t)} - 2\xi_2 \operatorname{Re} \eta^n(t) \overline{\widehat{\eta}^n(t)}.$$

Integrating the above equation over  $[0, T]$  and use the initial conditions (3.15), we have

$$\begin{aligned} & \int_0^L \left( \rho |\widehat{V}_t|^2 + \alpha_1 |\widehat{V}_x|^2 + \mu |\widehat{P}_t|^2 + \beta |\gamma \widehat{V}_x - \widehat{P}_x|^2 \right) dx + \frac{m_1}{2} |\widehat{u}|^2 + \frac{m_2}{2} |\widehat{\eta}|^2 \\ &= -2\xi_1 \operatorname{Re} \int_0^T u^n(t) \overline{\widehat{u}^n(t)} dt - 2\xi_2 \operatorname{Re} \int_0^T \eta^n(t) \overline{\widehat{\eta}^n(t)} dt. \end{aligned}$$

Since the operator  $\mathcal{A}$  is dissipative and  $\mathcal{A}_0$  is conservative, we know that energy  $\widehat{E}_n(t)$  is non-increasing. From (2.9), energy  $E(T)$  is also non-increasing. That is,  $\widehat{E}_n(t) \leq \widehat{E}_n(0), E(t) \leq E(0), \forall t \geq 0$ .

Let  $b = L, a = 0$  and  $q(x) = x/L$  in Lemma 2.2, we have

$$\int_0^L \left( \rho |V_t(L, t)|^2 + \alpha_1 |V_x(L, t)|^2 + \mu |t P_t(L, t)|^2 + \beta |(\gamma V_x - P_x)(L, t)|^2 \right) dx \leq \left( \frac{T}{L} + 2M \right) E_1(0),$$

and

$$\int_0^L \left( \rho |\widehat{V}_t(L, t)|^2 + \alpha_1 |\widehat{V}_x(L, t)|^2 + \mu |\widehat{P}_t(L, t)|^2 + \beta |(\gamma \widehat{V}_x - \widehat{P}_x)(L, t)|^2 \right) dx \leq \left( \frac{T}{L} + 2M \right) E_1(0).$$

It implies that  $V_x^n(L, t), P_x^n(L, t), \widehat{V}_x^n(L, t), \widehat{P}_x^n(L, t), u^n(t), \eta^n(t), \widehat{u}^n(t), \widehat{\eta}^n(t)$  are bounded in  $L^2(0, T)$ . Meanwhile, using the boundary conditions (2.5), (2.6) and (3.14), we obtain that  $u_t^n(t), \eta_t^n(t), \widehat{u}_t^n(t), \widehat{\eta}_t^n(t)$  are also bounded in  $L^2(0, T)$ . We conclude that  $u^n(t), \eta^n(t), \widehat{u}^n(t), \widehat{\eta}^n(t)$  are bounded in  $H^1(0, L)$ . Thanks to the Rellich-Kondrachov theorem, we obtain that there exist strongly convergent subsequences  $u^{nk}(t), \eta^{nk}(t), \widehat{u}^{nk}(t), \widehat{\eta}^{nk}(t)$  in  $L^2(0, L)$ . Then, by using Young's inequality, we have

$$\begin{aligned} \|(e^{\mathcal{A}t} - e^{\mathcal{A}_0 t}) U_0^n\|_{\mathcal{H}} &\leq \xi_1 \left( \int_0^T |u^{nk}(t)|^2 dt + \int_0^T |\widehat{u}^{nk}(t)|^2 dt \right) \\ &\quad + \xi_2 \left( \int_0^T |\eta^{nk}(t)|^2 dt + \int_0^T |\widehat{\eta}^{nk}(t)|^2 dt \right) \\ &\rightarrow \mathcal{K}, \quad k \rightarrow \infty, \end{aligned}$$

where  $\mathcal{K}$  is a finite positive constant. □

**Theorem 3.4** *The  $C_0$  semigroup  $\{e^{\mathcal{A}t}\}_{t \leq 0}$  is not uniformly stable.*

**Proof.** We have know  $r_e(e^{\mathcal{A}_0 t}) = 1$ , and the difference  $\{e^{\mathcal{A}t} - e^{\mathcal{A}_0 t}\}$  is a compact operator. Then, thanks to Theorem 3.2, we obtain

$$r_e(e^{\mathcal{A}t}) = r_e(e^{\mathcal{A}_0 t}) = 1.$$

Using the relationship between  $r_e(e^{\mathcal{A}t})$  and  $\omega_e(\mathcal{A})$ , we obtain

$$\omega_e(\mathcal{A}) = 0.$$

On the other hand, since the operator  $\mathcal{A}$  is dissipative, we have  $s(\mathcal{A}) \leq 0$ . By using Lemma 3.1, we get

$$\omega_0(\mathcal{S}(t)) = \max\{\omega_{ess}(\mathcal{S}(t)), s(\mathcal{A})\} = 0.$$

From the definition of the growth bound in [10], we have that  $\{e^{At}\}_{t \leq 0}$  is uniformly exponentially stable if and only if  $\omega_0 < 0$ . So we have  $\{e^{At}\}_{t \leq 0}$  is not uniformly exponentially stable. And it is known that  $\{e^{At}\}_{t \leq 0}$  is a  $C_0$ -semigroup, which means that it must also be a strongly continuous semigroup. By using Proposition 3.1, we conclude that  $\{e^{At}\}_{t \leq 0}$  is not uniformly stable.  $\square$

## 4 Polynomial stability

In the previous section, we have shown that the piezoelectric beam system (2.3)-(2.8) is not uniformly stability. In this section, we will state and prove the polynomial stability of our system in this section. It will be achieved by using the following result of Borichev and Tomilov and two lemmas.

**Theorem 4.1** ([5]) *Assume that  $\mathcal{S}(t)_{t \geq 0}$  be a bounded  $C_0$ -semigroup on Hilbert space  $H$ . Let  $\mathcal{A}$  be the infinitesimal generator of  $\mathcal{S}(t)_{t \geq 0}$  such that  $i\mathbb{R} \subset \rho(\mathcal{A})$ . Then, for any  $k > 0$ , the following conditions are equivalent:*

- (1)  $\|(i\lambda I - \mathcal{A})^{-1}\|_{\mathcal{L}(\mathcal{H})} = o(|\lambda|^K), \lambda \rightarrow \infty;$
- (2)  $\|\mathcal{S}(t)\mathcal{A}^{-1}\|_{\mathcal{L}(\mathcal{H})} = o(t^{-\frac{1}{k}}), t \rightarrow \infty.$

The spectral equation is given by

$$i\lambda U - \mathcal{A}U = F. \quad (4.1)$$

Rewriting (4.1) in term of its components, we have

$$\begin{cases} i\lambda V - \Phi = F_1 & \text{in } H_*^1(0, L), \\ i\lambda \rho \Phi - \alpha V_{xx} + \gamma \beta P_{xx} = \rho F_2, & \text{in } L^2(0, L), \\ i\lambda P - \Theta = F_3 & \text{in } H_*^1(0, L), \\ i\lambda \mu \Theta - \beta P_{xx} + \gamma \beta V_{xx} = \mu F_4, & \text{in } L^2(0, L), \\ i\lambda m_1 u + \alpha V_x(L) - \gamma \beta P_x(L) + \xi_1 u = m_1 F_5, \\ i\lambda m_2 \eta + \beta P_x(L) - \gamma \beta V_x(L) + \xi_2 \eta = m_2 F_6, \end{cases} \quad (4.2)$$

where  $\lambda \in \mathbb{R}$ ,  $F = (F_1, F_2, F_3, F_4, F_5, F_6) \in \mathcal{H}$  and

$$\Phi(L) = u, \quad \Theta(L) = \eta. \quad (4.3)$$

From (2.11) and (4.3), we have

$$\xi_1 |u|^2 + \xi_2 |\eta|^2 = \xi_1 |\Phi(L)|^2 + \xi_2 |\Theta(L)|^2 \leq C \|U\|_{\mathcal{H}} \|F\|_{\mathcal{H}}. \quad (4.4)$$

For further proof, we introduce the following functionals and notions.

$$\begin{aligned} I_V &= \rho q(L)|\Phi(L)|^2 + \alpha_1 q(L)|V_x(L, t)|^2; \\ I_P &= \mu q(L)|\Theta(L)|^2 + \beta q(L)|(\gamma V_x - P_x)(L, t)|^2; \\ \mathcal{N}^2 &= \int_0^L \rho |\Phi|^2 dx + \int_0^L \mu |\Theta|^2 dx + \int_0^L \alpha_1 |V_x|^2 dx + \int_0^L \beta |\gamma V_x - P_x|^2 dx. \end{aligned}$$

**Lemma 4.1** *Let us consider  $F = (f_1, f_2, f_3, f_4, f_5, f_6) \in \mathcal{H}$ ,  $\lambda \in \mathbb{R}$ , and  $U = (V, \Phi, P, \Theta, u, \eta) \in \mathcal{D}(\mathcal{A})$  such that  $(i\lambda U - \mathcal{A}U) = F$ . For  $q \in C^2([0, L])$ ,  $q(0) = 0$ , we have*

$$\begin{aligned} I_V + I_P - \int_0^L \rho q_x |\Phi|^2 dx - \int_0^L \mu q_x |\Theta|^2 dx - \int_0^L \alpha_1 q_x |V_x|^2 dx - \int_0^L \beta q_x |\gamma V_x - P_x|^2 dx \\ = -R_1 - R_2, \end{aligned}$$

where

$$\begin{aligned} R_1 &= \operatorname{Re} \int_0^L (2\mu q f_4 \bar{P}_x + 2\mu q \bar{f}_{3,x} \Theta) dx \\ R_2 &= \operatorname{Re} \int_0^L (2\rho q f_2 \bar{V}_x - 2\rho q \Phi \bar{f}_{1,x}) dx. \end{aligned}$$

**Proof.** Multiplying (4.2)<sub>2</sub> by  $q\bar{V}_x$  and integrating on  $[0, L]$ , we get

$$\int_0^L (-i\lambda \rho \Phi q \bar{V}_x + \alpha q V_{xx} \bar{V}_x - \gamma \beta q P_{xx} \bar{V}_x) dx = - \int_0^L \rho q f_2 \bar{V}_x dx. \quad (4.5)$$

Using (4.2)<sub>1</sub>, we obtain

$$\int_0^L -i\lambda \rho \Phi q \bar{V}_x dx = \int_0^L \overline{(i\lambda V_x)} \rho q \Phi dx = \int_0^L \rho q \Phi \overline{(\Phi_x + f_{1,x})} dx. \quad (4.6)$$

Multiplying (4.2)<sub>4</sub> by  $q\bar{P}_x$  and integrating on  $[0, L]$ , we have

$$\int_0^L (-i\lambda \rho \Theta q \bar{P}_x + \beta q P_{xx} \bar{P}_x - \gamma \beta q V_{xx} \bar{P}_x) dx = - \int_0^L \mu q f_4 \bar{P}_x dx. \quad (4.7)$$

Using (4.2)<sub>3</sub>, we obtain

$$\int_0^L -i\lambda \rho \Theta q \bar{P}_x dx = \int_0^L \overline{(i\lambda P_x)} \mu q \Theta dx = \int_0^L \mu q \Theta \overline{(\Theta_x + f_{3,x})} dx. \quad (4.8)$$

By combining (4.5) with (4.7), and employing (4.6) and (4.8) into it, we conclude that

$$\begin{aligned} \int_0^L \rho q \frac{d}{dx} |\Phi|^2 dx + \int_0^L \alpha_1 q \frac{d}{dx} |V_x|^2 dx + \int_0^L \mu q \frac{d}{dx} |\Theta|^2 dx + \int_0^L \beta q \frac{d}{dx} |\gamma V_x - P_x|^2 dx \\ = \operatorname{Re} \int_0^L (-2\mu q f_4 \bar{P}_x - 2\mu q \bar{f}_{3,x} \Theta - 2\rho q f_2 \bar{V}_x - 2\rho q \Phi \bar{f}_{1,x}) dx. \end{aligned} \quad (4.9)$$

Then, integrating by part, we obtain that the relation in Lemma 4.1 is correct.  $\square$

**Lemma 4.2** *Let  $\mathcal{N}$ ,  $I_V, I_P$  be functionals defined above, then they satisfy*

$$\mathcal{N}^2 \leq C (I_V + I_P + \|F\|_{\mathcal{H}}^2), \quad (4.10)$$

where  $C$  is a constant.

**Proof.** Let  $q(x) = x, x \in [0, L]$ . From the result of Lemma (4.1), we have

$$\mathcal{N}^2 = L (I_V + I_P) - R_1 - R_2. \quad (4.11)$$

Since the definition of  $R_1, R_2$ , we conclude that

$$|R_1| \leq C\mathcal{N}\|F\|_{\mathcal{H}}, |R_2| \leq C\mathcal{N}\|F\|_{\mathcal{H}}. \quad (4.12)$$

Thanks to the estimate (4.12) and Cauchy-Schwartz inequality, it is straightforward to verify that the relation (4.10) is valid.  $\square$

**Theorem 4.2**  *$i\mathbb{R} \in \rho(\mathcal{A})$ , and  $\rho(\mathcal{A})$  is the resolvent set of the operator  $\mathcal{A}$ .*

**Proof.** Since the fact of  $0 \in \rho(\mathcal{A})$  which we have proved in Section 2, we have that the set

$$\mathcal{M} = \{\beta > 0 : (-i\beta, i\beta) \subset \rho(\mathcal{A})\} \neq \emptyset.$$

If  $\sup_{\beta > 0} \mathcal{M} = \infty$ , there is nothing to prove. Next, we will consider  $\sup \mathcal{M} < \infty$  by using reduction to absurdity. Assume that there exists  $\lambda > 0$  such that  $\sup \mathcal{M} = \lambda < \infty$ . Clearly  $\lambda \notin \mathcal{M}$ . Therefore, there exist  $\lambda_n \in \mathcal{M}$  and  $\overline{F}_n \in \mathcal{H}$  with  $\|\overline{F}_n\| = 1$  such that

$$\|(i\lambda_n I - \mathcal{A})^{-1} \overline{F}_n\|_{\mathcal{H}} \rightarrow \infty.$$

Let us define  $\overline{U}_n = (i\lambda_n I - \mathcal{A})^{-1} \overline{F}_n$ . Then we have that  $i\lambda_n \overline{U}_n - \mathcal{A} \overline{U}_n = \overline{F}_n$ . Denoting  $U_n = \frac{\overline{U}_n}{\|(i\lambda_n - \mathcal{A})^{-1} \overline{F}_n\|_{\mathcal{H}}}$ . Clearly,  $U_n$  satisfies

$$i\lambda_n U_n - \mathcal{A} U_n = F_n,$$

where  $F_n = \frac{\overline{F}_n}{\|(i\lambda_n - \mathcal{A})^{-1} \overline{F}_n\|_{\mathcal{H}}}$ . Since  $\|\overline{F}_n\| = 1$  and  $\|(i\lambda I - \mathcal{A})^{-1} \overline{F}_n\|_{\mathcal{H}} \rightarrow \infty$ , we have  $F_n \rightarrow 0$ . Taking inner product with  $U_n$  on  $\mathcal{H}$ , we obtain

$$i\lambda_n \|U_n\|^2 - \langle \mathcal{A} U_n, U_n \rangle_{\mathcal{H}} = \langle F_n, U_n \rangle_{\mathcal{H}}.$$

By taking the real part and the fact of  $F_n \rightarrow 0$ , we have that

$$-Re \langle \mathcal{A} U_n, U_n \rangle_{\mathcal{H}} = Re \langle F_n, U_n \rangle_{\mathcal{H}} \rightarrow 0,$$

which implies that

$$\xi_1 |u_n(t)|^2 + \xi_2 |\eta_n(t)|^2 \rightarrow 0.$$

Thanks to (2.1), we obtain  $\Phi_n(L), \Theta_n(L) \rightarrow 0$ . Using (2.5) (2.6) and the fact of  $u_n(t), \eta_n(t) \rightarrow 0$ , we have  $V_{x,n}(L, t), P_{x,n}(L, t) \rightarrow 0$  which implies that  $I_V + I_P \rightarrow 0$ . By using Lemma 4.2 and the fact of  $F_n, u_n(t), \eta_n(t) \rightarrow 0$ , we conclude that  $U_n \rightarrow 0$ .

This relation contracts with  $\|U_n\| = 1$ . Therefore, by using reduction to absurdity, we have proved the theorem.  $\square$

Next, by recalling the fact of Borichev and Tomilov theorem and Lemma 4.2, we prove our result of polynomial stability.

**Theorem 4.3** *The piezoelectric system (2.3)-(2.7) with tip body decays polynomially as*

$$\|U(t)\|_{\mathcal{H}} \leq \frac{C}{\sqrt{t}} \|U_0\|_{\mathcal{D}(\mathcal{A})}.$$

**Proof.** Thanks to (4.2)<sub>1</sub>, (4.2)<sub>3</sub> and (4.11), we arrive at

$$I_V + I_P \leq C(1 + |\lambda|^2) \|U\|_{\mathcal{H}} \|F\|_{\mathcal{H}} + C \|F\|_{\mathcal{H}}^2,$$

and by using (4.10), we can obtain

$$\mathcal{N}^2 \leq C(1 + |\lambda|^2) \|U\|_{\mathcal{H}} \|F\|_{\mathcal{H}} + C \|F\|_{\mathcal{H}}^2.$$

Then, from relations (4.10) together with the definition of norm in  $\mathcal{H}$ , we get

$$\|U\|_{\mathcal{H}} \leq C|\lambda|^2 \|F\|_{\mathcal{H}}$$

for  $|\lambda| > 1$  large enough. Finally, we can get the result of polynomial stability by using Theorem 4.1.  $\square$

## Acknowledgments

This work was supported by the National Natural Science Foundation of China [grant number 11771216], the Key Research and Development Program of Jiangsu Province (Social Development) [grant number BE2019725] and the Qing Lan Project of Jiangsu Province.

## Declarations

### Conflict of interest

The authors declare that they have no conflict of interest.

## References

- [1] M. Akil, Y. Chitouret, M. Ghader and A. Wehbe, Stability and exact controllability of a Timoshenko system with only one fractional damping on the boundary, *Asymptot. Anal.* **119** (2020), no. 3-4, 221–280.

- [2] M. S. Alves and R. N. Monteiro, Stabilization for partially dissipative laminated beams with non-constant coefficients, *Z. Angew. Math. Phys.* **71** (2020), no. 5, Paper No. 165, 15 pp.
- [3] H. T. Banks, R. C. Smith and Y. Wang, *Smart material structures-Modeling, estimation and control*, Chichester, United Kingdom and New York/Paris: John Wiley Sons/Masson, 1996.
- [4] F. Belhannache and S. A. Messaoudi, On the General Stability of a Viscoelastic Wave Equation with an Integral Condition, *Acta Math. Appl. Sin. Engl. Ser.* **36** (2020), no. 4, 857–869.
- [5] A. Borichev and Y. Tomilov, Optimal polynomial decay of functions and operator semigroups, *Math. Ann.* **347** (2010), no. 2, 455–478.
- [6] C. L. Cardozo, M. A. Jorge Silva, T. F. Ma and J. E. Muñoz Rivera, Stability of Timoshenko systems with thermal coupling on the bending moment, *Math. Nachr.* **292** (2019), no. 12, 2537–2555.
- [7] A. Cuc, V. Giurgiutiu, S. Joshi and Z. Tidwell, Structural health monitoring with piezoelectric wafer active sensors for space applications, *AIAA J.* **45** (2007), no. 12, 2838–2850.
- [8] C. Dagdeviren et al., Conformal piezoelectric energy harvesting and storage from motions of the heart, lung, and diaphragm, *P. Natl. Acad. Sci. USA.* **111** (2014), no. 5, 1927–1932.
- [9] J. M. Dietl, A. M. Wickenheiser and E. Garcia, A Timoshenko beam model for cantilevered piezoelectric energy harvesters, *Smart. Mater. Struct.* **19** (2010), no. 5, 055018.
- [10] K. J. Engel and R. Nagel, *One-parameter semigroups for linear evolution equations*, Graduate Texts in Mathematics, 194, Springer-Verlag, New York, 2000.
- [11] A. Erturk and D. J. Inman, A distributed parameter electromechanical model for cantilevered piezoelectric energy harvesters, *J. Vib. Acoust.* **130** (2008), no. 4.
- [12] A. Erturk and D. J. Inman, *Piezoelectric energy harvesting*, John Wiley & Sons, 2011.
- [13] B. Feng, T. F. Ma, R. N. Monteiro and C. A. Raposo, Dynamics of laminated Timoshenko beams, *J. Dynam. Differential Equations* **30** (2018), no. 4, 1489–1507.
- [14] C. Galassi et al., eds. *Piezoelectric materials: advances in science, technology and applications*. Vol. 76. Springer Science Business Media, 2012.
- [15] G. Y. Gu, L. M. Zhu, C. Y. Su, H. Ding and S. Fatikow, Modeling and control of piezo-actuated nanopositioning stages: A survey, *IEEE. T. Autom. Sci. Eng.* **13** (2014), no. 1, 313–332.
- [16] Z.-J. Han, G. Wang and J. Wang, Explicit decay rate for a degenerate hyperbolic-parabolic coupled system, *ESAIM Control Optim. Calc. Var.* **26** (2020), Paper No. 116, 20 pp.
- [17] F. Hassine and N. Souayah, Stability for coupled waves with locally disturbed Kelvin-Voigt damping, *Semigroup Forum* **102** (2021), no. 1, 134–159.



- [18] M. A. Jorge Silva and S. B. Pinheiro, Improvement on the polynomial stability for a Timoshenko system with type III thermoelasticity, *Appl. Math. Lett.* **96** (2019), 95–100.
- [19] H. Kawai, The piezoelectricity of poly (vinylidene fluoride), *Jpn. J. Appl. Phys.* **8** (1969), no. 7, 975.
- [20] A. A. Keddi, T. A. Apalara and S. A. Messaoudi, Exponential and polynomial decay in a thermoelastic-Bresse system with second sound, *Appl. Math. Optim.* **77** (2018), no. 2, 315–341.
- [21] J. U. Kim and Y. Renardy, Boundary control of the Timoshenko beam, *SIAM J. Control Optim.* **25** (1987), no. 6, 1417–1429.
- [22] C. Li and T. J. Xiao, Polynomial stability for wave equations with Wentzell boundary conditions, *J. Nonlinear Convex Anal.* **18** (2017), no. 10, 1801–1814.
- [23] W. Liu, X. Kong and G. Li, Lack of exponential decay for a laminated beam with structural damping and second sound, *Ann. Polon. Math.* **124** (2020), no. 3, 281–289.
- [24] W. Liu and W. Zhao, Stabilization of a thermoelastic laminated beam with past history, *Appl. Math. Optim.* **80** (2019), no. 1, 103–133.
- [25] A. Lo and N. Tatar, Stabilization of laminated beams with interfacial slip, *Electron. J. Differential Equations* **2015** (2015), No. 129, 14 pp.
- [26] T. K. Maryati, J. E. Muñoz Rivera, A. Rambaud and O. Vera, Stability of an  $N$ -component Timoshenko beam with localized Kelvin-Voigt and frictional dissipation, *Electron. J. Differential Equations* **2018** (2018), Paper No. 136, 18 pp.
- [27] T. R. Meeker, Publication and proposed revision of ANSI/IEEE standard 176-1987, *IEEE. T. Ultrason. Ferr.* **43** (1996), no. 5, 717–772.
- [28] S. A. Messaoudi and W. Al-Khulaifi, General and optimal decay for a viscoelastic equation with boundary feedback, *Topol. Methods Nonlinear Anal.* **51** (2018), no. 2, 413–427.
- [29] K. Morris and A. Ö. Özer, Strong stabilization of piezoelectric beams with magnetic effects, *52nd IEEE Conference on Decision and Control* **2013**, Paper No. 3014, 6 pp.
- [30] K. A. Morris and A. Ö. Özer, Modeling and stabilizability of voltage-actuated piezoelectric beams with magnetic effects, *SIAM J. Control Optim.* **52** (2014), no. 4, 2371–2398.
- [31] J. E. Muñoz Rivera and A. I. Ávila, Rates of decay to non homogeneous Timoshenko model with tip body, *J. Differential Equations* **258** (2015), no. 10, 3468–3490.
- [32] M. I. Mustafa, Optimal energy decay result for nonlinear abstract viscoelastic dissipative systems, *Z. Angew. Math. Phys.* **72** (2021), no. 2, 67.

- [33] G. R. Peralta, Stabilization of the wave equation with acoustic and delay boundary conditions, *Semigroup Forum* **96** (2018), no. 2, 357–376.
- [34] A. J. A. Ramos, M. M. Freitas, D. S. Almeida, S. S. Jesus and T. R. S. Moura, Equivalence between exponential stabilization and boundary observability for piezoelectric beams with magnetic effect, *Z. Angew. Math. Phys.* **70** (2019), no. 2, Paper No. 60, 14 pp.
- [35] C. A. Raposo, O. Vera Villagrán, J. E. Muñoz Rivera and M. S. Alves, Hybrid laminated Timoshenko beam, *J. Math. Phys.* **58** (2017), no. 10, 101512, 11 pp.
- [36] M. Sunar, 2.22 Piezoelectric Materials, *Comprehensive Energy Systems*, 2018.
- [37] D. H. Vargas, Stability of a hybrid system with tip load damped, *J. Differential Equations* **269** (2020), no. 9, 7042–7058.
- [38] H. Weyl, Über gewöhnliche Differentialgleichungen mit Singularitäten und die zugehörigen Entwicklungen willkürlicher Funktionen, *Math. Ann.* **68** (1910), no. 2, 220–269.
- [39] C. Yang and J. M. Wang, Exponential stability of an active constrained layer beam actuated by a voltage source without magnetic effects, *J. Math. Anal. Appl.* **448** (2017), no. 2, 1204–1227.
- [40] J. S. Yang, A review of a few topics in piezoelectricity, *Appl. Mech. Rev. Nov.* **59** (2006), no. 6, 335–345.