

A NON-HIERARCHICAL ATTENTION NETWORK WITH MODALITY DROPOUT FOR TEXTUAL RESPONSE GENERATION IN MULTIMODAL DIALOGUE SYSTEMS

Rongyi Sun¹ Borun Chen¹ Qingyu Zhou² Yinghui Li¹ Yunbo Cao² Hai-Tao Zheng^{1*}

¹Shenzhen International Graduate School, Tsinghua University

²Tencent Cloud Xiaowei

ABSTRACT

Existing text- and image-based multimodal dialogue systems use the traditional Hierarchical Recurrent Encoder-Decoder (HRED) framework, which has an utterance-level encoder to model utterance representation and a context-level encoder to model context representation. Although pioneer efforts have shown promising performances, they still suffer from the following challenges: (1) the interaction between textual features and visual features is not fine-grained enough. (2) the context representation can not provide a complete representation for the context. To address the issues mentioned above, we propose a non-hierarchical attention network with modality dropout, which abandons the HRED framework and utilizes attention modules to encode each utterance and model the context representation. To evaluate our proposed model, we conduct comprehensive experiments on a public multimodal dialogue dataset. Automatic and human evaluation demonstrate that our proposed model outperforms the existing methods and achieves state-of-the-art performance.

Index Terms— Multimodal Dialogue Systems, HRED, Non-Hierarchical, Attention, Modality Dropout.

1. INTRODUCTION

With the development of social media, dialogue systems are no longer confined to the textual form, and pictures are gradually playing an essential role in online conversations [1]. As shown in Figure 1, the customer expresses requirements and questions about products, and the chatbot generates the multimodal responses according to the context, which remarkably demonstrates that “one picture is worth a thousand words”. Inspired by this, incorporating images into the traditional textual dialogue systems, i.e., multimodal dialogue systems, has been attracting more and more research interest [1, 2, 3, 4, 5].

Most existing methods build multimodal dialogue systems by adding a multimodal feature fusion module to the traditional textual dialogue systems. Along this line, [1, 2, 3, 4] take the traditional Hierarchical Recurrent Encoder-Decoder (HRED) [6] as the basic framework and propose different fusion modules. Although these models have shown promising




Fig. 1. An example of multimodal dialogues between a user and a chatbot.

performances, they still suffer from two problems. Firstly, the interaction between textual features and visual features is not fine-grained enough. For each utterance in the context, they first compute a sentence embedding vector to represent texts and then get the utterance representation by interacting this sentence embedding vector with image feature vectors. This may lead to some word-related attribute features in the images being ignored because the sentence embedding vector tends to focus more on the global information of texts. Secondly, the output of the context-level encoder, i.e., the context representation, may not provide a complete representation for the context. For each utterance, the context-level encoder updates the context representation by encoding the output of the utterance-level encoder. This hierarchical architecture makes the context-level encoder not see the complete utterance because the utterance-level encoder encodes the utterance into a feature vector, which leads to a loss of word-level information. However, we argue that which information is lost should be determined by the context-level encoder rather than the utterance-level encoder.

To address the issues mentioned above, we propose a non-hierarchical attention network with modality dropout. For the first problem, we use a self-attention module to extract textual features and a text-enhanced image module to extract textual-visual features in each encoding layer. Both of the modules are based on word level. Thus texts and images are capable

* Corresponding author. (E-mail: zheng.haitao@sz.tsinghua.edu.cn)




Fig. 2. The overall framework of our proposed model, from left to right they are: the inner architecture of an encoding layer, the architecture of the encoder, the entire model, and the architecture of the decoder. The encoder has L sub-layers and PE denotes positional embedding. The decoder generates textual responses according to the output of the encoder.

of interacting with each other at a finer granularity. Besides, to fully utilize features and prevent the model from overfitting to one specific modality, we propose a modality dropout strategy to fuse textual and textual-visual features. For the second problem, we abandon the hierarchical architecture and design a history updater, which updates context history information after fusing features in each encoding layer instead of the last encoding layer.

We conduct comprehensive experiments on a public multimodal dialogue dataset.

Experimental results show that our model outperforms state-of-the-art methods on automatic evaluation metrics. We also perform human evaluation to verify the quality of generated textual responses. The results indicate that the generated textual responses of our model are fluent and relevant to the context.

2. METHODOLOGY

2.1. Problem Formulation

Given a set of multimodal dialogue utterances between a user and a chatbot $U_C = \{(T^c, I^c)\}_{c=1}^C$ and a user query (T^q, I^q) , the task is to generate the system response (T^r, I^r) . Here, $T^c = \{w_i^c\}_{i=1}^{m_c}$ denotes the c -th text utterance containing m_c words, and $I^c = \{i_j^c\}_{j=1}^{n_c}$ denotes the c -th image utterance containing n_c images. Similarly, $T^q = \{w_i^q\}_{i=1}^{m_q}$ contains m_q words and $I^q = \{i_j^q\}_{j=1}^{n_q}$ contains n_q images. Mainstream methods treat textual responses generation and image responses as two separate tasks, and generate the responses by selectively assembling the texts and images manually [1, 2, 3, 4]. In this paper, we only focus on generating

more appropriate textual responses. Therefore, our goal is to maximize the probability of generating the textual response $T^r = \{w_i^r\}_{i=1}^{m_r}$, which is computed by

$$p(T^r|U_C; T^q; I^q; \theta) = \prod_{i=1}^{m_r} p(w_i^r|U_C; T^q; I^q; w_{<i}^r; \theta), \quad (1)$$

where $w_{<i}^r$ denotes generated words and θ denotes model parameters.

2.2. Model Architecture

As shown in Figure 2, our model has an encoder-decoder architecture like Transformer [7]. In this section, we mainly introduce the encoder, which processes each utterance in the context sequentially and utilizes a history updater to maintain the context history information.

2.2.1. Processing Utterance

For the c -th utterance in U_C , we first convert texts T^c into text embeddings $T_0^c \in \mathbb{R}^{m_c \times d_{model}}$ and extract visual features $I_0^c \in \mathbb{R}^{n_c \times d_{model}}$ from images I^c by Resnet [8], where d_{model} is the dimension of word embeddings and visual features. The encoder, having L sub-layers, computes the textual features T_l^c by text self-attention module and computes textual-visual features I_l^c by text-enhanced image module. Both of the modules are implemented by multi-head attention mechanism [7]. More specifically, at the l -th layer, textual features T_l^c are computed by:

$$\tilde{T}_l^c = MultiHeadAttention(T_{l-1}^c, T_{l-1}^c, T_{l-1}^c), \quad (2)$$

$$T_l^c = \text{LayerNormalization}(\tilde{T}_l^c) + T_{l-1}^c, \quad (3)$$

and textual-visual I_l^c features are computed by:

$$\tilde{I}_l^c = \text{MultiHeadAttention}(T_{l-1}^c, I_{l-1}^c, I_{l-1}^c), \quad (4)$$

$$I_l^c = \text{LayerNormalization}(\tilde{I}_l^c) + T_{l-1}^c. \quad (5)$$

Both of T_l^c and I_l^c are based on word level and thus have more fine-grained information. To fully utilize these features and prevent the model from overfitting to one specific modality, we propose a modality dropout strategy here to compute the fusion features M_l^c . We denote the dropout rate in network as $p_{net} \in [0, 1]$. Then a random variable $U^l \in [0, 1]$ is sampled uniformly for each layer l to influence the calculation process of M_l^c :

$$M_l^c = \mathbb{I}(U^l < \frac{p_{net}}{2}) \cdot T_l^c + \mathbb{I}(U^l > 1 - \frac{p_{net}}{2}) \cdot I_l^c \\ + \frac{1}{2} \times \mathbb{I}(\frac{p_{net}}{2} \leq U^l \leq 1 - \frac{p_{net}}{2}) \cdot (T_l^c + I_l^c), \quad (6)$$

where $\mathbb{I}(\cdot)$ is the indicator function. In this way, for each layer, there is a probability $\frac{p_{net}}{2}$ that only textual features T_l^c or textual-visual features I_l^c are used; w.p. $1 - p_{net}$, both features are used. Note that p_{net} is set to 0 in the inference phase regardless of what p_{net} is during training process.

2.2.2. History Updater

Instead of computing context representation after the last encoding layer, we propose a history updater to maintain the context history information H_l^c after fusing features in each encoding layer:

$$\tilde{H}_l^c = \text{MultiHeadAttention}(M_l^c, H_{l-1}^c, H_{l-1}^c), \quad (7)$$

$$\hat{H}_l^c = \text{LayerNormalization}(\tilde{H}_l^c) + M_l^c, \quad (8)$$

$$H_l^c = \text{LayerNormalization}(\text{FFN}(\hat{H}_l^c)) + \hat{H}_l^c, \quad (9)$$

where FFN is a fully connected feed-forward network consisting of two linear transformations with a ReLU activation in between [7]. As shown in Figure 2, the context history information H_l^c is integrated throughout the entire encoding process and we finally get H_L^c , which will be fed into decoder as the context representation.

In this process, when $c \neq 1$ and $l = 0$, the context history information H_0^c comes from the output of the previous time step H_L^{c-1} :

$$H_0^c = H_L^{c-1}. \quad (10)$$

When $c = 1$, there is no H_L^0 to initialize H_0^1 . Instead of random initialization, we add a history parameter H and use it to

initialize H_0^1 . During the training process, we also optimize the history parameter H to maximize the probability of generating textual responses. Then the Eqn.(1) can be reformulated as:

$$p(T^r | U_C; T^q; I^q; \theta) = \prod_{i=1}^{m_r} p(w_i^r | U_C; T^q; I^q; w_{<i}^r; \theta; H). \quad (11)$$

3. EXPERIMENTS

3.1. Dataset

We conduct experiments on a large-scale Multimodal Dialogue (MMD) dataset [1]. The MMD dataset includes 105,439/225,95/225,95 (train/valid/test) conversations between users and chatbots, and each conversation has an average of 40 utterances. Each utterance can be divided into three categories: text-only utterance, image-only utterance, and multimodal utterance.

3.2. Evaluation metrics

Following previous work [2, 3, 5], we use both automatic and human evaluation methods to measure the performance of our proposed model. For automatic metrics, we utilize BLEU [9] and NIST [10] to measure the similarity between the generated and reference responses. For human evaluation, we randomly select 300 generated responses of our model and corresponding responses of MAGIC to get 300 response pairs. Then we ask three experts to compare these pairs on fluency, relevance, and logical consistency. If two responses in a pair are both meaningful or inappropriate, the comparison of this pair is labeled as ‘‘tie’’, otherwise each response is tagged with a ‘‘win’’ or ‘‘lose’’. Ultimately, we compute the average result of three experts and calculate their kappa scores [11] which indicate a moderate agreement among the annotators.

3.3. Baselines and Hyper-parameters

To evaluate our proposed model, we compare it with the following baselines: Seq2Seq [12], HRED [6], MHRED [1], UMD [2], MAGIC [3], OAM [4] and MATE [5]. Following previous work, we take Resnet18 [8] as a visual feature extractor and resize input images into (3, 224, 224) before feeding them into Resnet. The context size is 2. For each utterance in context, the max number of images is 4 and the max length of sentence is 32. For our model, it has 2 sub layers in encoder and decoder. The dimension of word embedding is 512. The number of heads for multi-head attention is 8. The word embedding parameters are shared between encoder and decoder. We optimize the model with Adam [13] method that the initial learning rate is 0.0004. We use 4 Tesla-V100 GPUs to train 10 epochs with 150 batch size.

Methods		BLEU1	BLEU2	BLEU3	BLEU4	NIST
Text-only	Seq2Seq [†] [12]	35.39	28.15	23.81	20.65	3.3261
	HRED [†] [6]	35.44	26.15	20.81	17.27	3.1007
Multimodal	MHRED [†] [1]	32.60	25.14	23.21	20.52	3.0901
	UMD [†] [2]	44.97	35.06	29.22	25.03	3.9831
	OAM [†] [4]	48.30	38.24	32.03	27.42	4.3236
	MAGIC [3]	51.05	40.31	33.87	28.91	4.3162
	MATE [†] [5]	56.55	47.89	42.48	38.06	6.0604
	Our	62.80	54.88	48.77	43.03	5.6495

Table 1. Objective performance comparison between our proposed model and baselines. [†] denotes the results reported by [5].

Opponent	Fluency				Relevance				Logical Consistency			
	Win	Loss	Tie	Kappa	Win	Loss	Tie	Kappa	Win	Loss	Tie	Kappa
Our vs. MAGIC	35.3%	5.9%	58.8%	0.51	51.6%	3.8%	44.6%	0.74	52.5%	5.3%	42.2%	0.77
MATE vs. MAGIC [†]	25.8%	15.2%	59.0%	0.65	48.8%	21.3%	29.9%	0.53	49.6%	15.6%	34.8%	0.51

Table 2. Human evaluation results. [†] denotes the evaluation results reported by [5].

Setting	BLEU1	BLEU2	BLEU3	BLEU4	NIST
p = 0.0	61.19	53.22	47.03	41.30	5.4516
p = 0.2	61.63	53.64	47.45	41.67	5.4517
p = 0.4	62.80	54.88	48.77	43.03	5.6495
p = 0.6	61.41	53.42	47.26	41.50	5.4268
p = 0.8	60.73	52.72	46.49	40.73	5.4168
p = 1.0	60.22	52.28	46.13	40.44	5.3761

Table 3. Different p_{net} for modality dropout.

Setting	BLEU1	BLEU2	BLEU3	BLEU4	NIST
MATE	56.55	47.89	42.48	38.06	6.0604
p = 0.0	61.19	53.22	47.03	41.30	5.4516

Table 4. The effect of history updater.

Setting	BLEU1	BLEU2	BLEU3	BLEU4	NIST
fixed	59.95	52.53	46.78	41.37	5.3599
training	62.80	54.88	48.77	43.03	5.6495

Table 5. Different strategies are applied to H .

3.4. Results

3.4.1. Automatic Evaluation and Human Evaluation

As shown in Table 1, our proposed model outperforms all baselines on BLEU. For example, it improves the BLEU-4 score by 14.12 and 4.97 compared with the state-of-the-art models MAGIC and MATE. Although it does not surpass MATE in terms of NIST (5.6495 vs. 6.0604), it is still far ahead of other baselines. This superior performance demonstrates the effectiveness of the novel architecture. As for why our model does not perform as well as MATE in terms of NIST, we believe this is because NIST focuses more on some keywords that occur less frequently, while MATE uses external knowledge to help the generation of keywords.

Table 2 presents the human evaluation results. Since the source code of MATE is not released, we can not compare MATE with our model directly. Therefore, we do this indirectly by comparing our model with MAGIC. As shown in Table 2, our model shows a greater advantage than MATE when taking MAGIC as a reference. This demonstrates that our model is capable of generating more natural responses.

3.4.2. Ablation Study

To further verify the effectiveness of the modality dropout and the history updater, we design the corresponding ablation studies. **Firstly**, we investigate the effect of different p_{net} on performance. As shown in Table 3, we set $p_{net} \in \{0.0, 0.2, 0.4, 0.6, 0.8, 1.0\}$ and we can see that the performance of the model shows a trend of rising at first and then falling as p_{net} increases. Especially when $p_{net} = 0.4$, the model has the best performance. This result reflects the improvement brought by the modality dropout. **Secondly**, we prove the history updater is effective. When p_{net} equals to 0, the modality dropout strategy is not working and only the history updater is working. Compared with MATE, which uses Transformer and concatenates the features of each utterance as a context representation, we can see our model performs better from Table 4. **Thirdly**, we set $p_{net} = 0.4$ and do not optimize the history parameter H in the training process. As we can see, the performance dramatically drops when we choose to fix the history parameter H after random initialization, which demonstrates that the history parameter is capable of helping the model start a new conversation.

4. CONCLUSION

In this paper, we propose a non-hierarchical attention network with modality dropout strategy for textual responses generation in multimodal dialogue systems, which allows for finer-grained interaction between multimodal features, and encodes contextual representations without information loss. Experimental results demonstrates that our proposed model brings a leap in performance to multimodal dialogue systems.

5. REFERENCES

- [1] Amrita Saha, Mitesh Khapra, and Karthik Sankaranarayanan, “Towards building large scale multimodal domain-aware conversation systems,” *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 32, no. 1, Apr. 2018.
- [2] Chen Cui, Wenjie Wang, Xuemeng Song, Minlie Huang, Xin-Shun Xu, and Liqiang Nie, “User attention-guided multimodal dialog systems,” in *Proceedings of the 42nd International ACM SIGIR Conference on Research and Development in Information Retrieval*, New York, NY, USA, 2019, SIGIR’19, p. 445–454, Association for Computing Machinery.
- [3] Liqiang Nie, Wenjie Wang, Richang Hong, Meng Wang, and Qi Tian, “Multimodal dialog system: Generating responses via adaptive decoders,” in *Proceedings of the 27th ACM International Conference on Multimedia*, New York, NY, USA, 2019, MM ’19, p. 1098–1106, Association for Computing Machinery.
- [4] Hardik Chauhan, Mauajama Firdaus, Asif Ekbal, and Pushpak Bhattacharyya, “Ordinal and attribute aware response generation in a multimodal dialogue system,” in *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, Florence, Italy, July 2019, pp. 5437–5447, Association for Computational Linguistics.
- [5] Weidong He, Zhi Li, Dongcai Lu, Enhong Chen, Tong Xu, Baoxing Huai, and Jing Yuan, “Multimodal dialogue systems via capturing context-aware dependencies of semantic elements,” in *Proceedings of the 28th ACM International Conference on Multimedia*, New York, NY, USA, 2020, MM ’20, p. 2755–2764, Association for Computing Machinery.
- [6] Iulian Serban, Alessandro Sordoni, Yoshua Bengio, Aaron C. Courville, and Joelle Pineau, “Hierarchical neural network generative models for movie dialogues,” *ArXiv*, vol. abs/1507.04808, 2015.
- [7] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin, “Attention is all you need,” in *Advances in Neural Information Processing Systems*, I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, Eds. 2017, vol. 30, Curran Associates, Inc.
- [8] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun, “Deep residual learning for image recognition,” in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2016.

- [9] Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu, “Bleu: A method for automatic evaluation of machine translation,” in *Proceedings of the 40th Annual Meeting on Association for Computational Linguistics*, USA, 2002, ACL ’02, p. 311–318, Association for Computational Linguistics.
- [10] George Doddington, “Automatic evaluation of machine translation quality using n-gram co-occurrence statistics,” in *Proceedings of the Second International Conference on Human Language Technology Research*, San Francisco, CA, USA, 2002, HLT ’02, p. 138–145, Morgan Kaufmann Publishers Inc.
- [11] Fleiss and L. Joseph, “Measuring nominal scale agreement among many raters.,” *Psychological Bulletin*, vol. 76, no. 5, pp. 378–382, 1971.
- [12] Ilya Sutskever, Oriol Vinyals, and Quoc V Le, “Sequence to sequence learning with neural networks,” in *Advances in Neural Information Processing Systems*, Z. Ghahramani, M. Welling, C. Cortes, N. Lawrence, and K. Q. Weinberger, Eds. 2014, vol. 27, Curran Associates, Inc.
- [13] Diederik P Kingma and Jimmy Ba, “Adam: A method for stochastic optimization,” *arXiv preprint arXiv:1412.6980*, 2014.