

Computing Matching Statistics on Repetitive Texts

Younan Gao

Dalhousie University
Halifax, Canada
yn803382@dal.ca

Abstract

Computing the *matching statistics* of a string $P[1..m]$ with respect to a text $T[1..n]$ is a fundamental problem which has application to genome sequence comparison. In this paper, we study the problem of computing the matching statistics upon highly repetitive texts. We design three different data structures that are similar to LZ-compressed indexes. The space costs of all of them can be measured by γ , the size of the smallest string attractor [STOC'2018] and δ , a better measure of repetitiveness [LATIN'2020].

Introduction

The *matching statistics*, MS, of a pattern $P[1..m]$ with respect to a text $T[1..n]$ are an array of m integers such that the i -th entry $MS[i]$ stores the length of the longest prefix of $P[i..m]$ that occurs in T . For example, given that $T = \text{“}aaabbbcc\text{”}$ and $P = \text{“}ccabb\text{”}$, the matching statistics MS of P w.r.t. T , store an array of 5 integers, $\{2, 1, 3, 2, 1\}$. Originally, the matching statistics were introduced by Chang and Lawler [1] to solve the approximate string matching problem, i.e., given a text $T[1..n]$ and a pattern $P[1..m]$, the problem asks for all the locations in the text where $P[1..m]$ appears, with at most k differences (including substitutions, insertions, and deletions) being allowed, where k is not necessarily a constant. The approximate string matching plays an important role in computational genomics. In terms of sequence alignment, the reads might not match the genome exactly because of the sequencing error, natural variance (i.e., differences in DNA among individuals of the same species), etc. Therefore, the algorithms for the exact string matching might not be sufficient, and the approximate string matching is expected. Matching statistics are also used in a variety of other applications such as finding the longest common substring between P and T [2].

A textbook solution [2] shows that a *suffix tree* data structure augmented with *suffix links* on the tree nodes can be used to compute matching statistics in $O(m \lg \sigma)$ time, where σ represents the size of the alphabet that T is drawn from. The data structure uses $O(n)$ words of space. Ohlebusch et al. [3] considered this problem on a fully compressed text indexes built upon T . Their indexes consist of a *wavelet tree* data structure that supports the LF-Mapping and the backward search, a LCP-array, and a data structure that supports fast-navigating on a *LCP-interval tree*. The indexes take $n \lg \sigma + 4n + o(n \lg \sigma)$ bits of space and achieve the same computing time as the textbook solution. In the genomic databases, the texts are always massive and highly repetitive. However, the compressed indexes based on statistical entropy might not capture repetitiveness [4]. Bannai et al. [5] considered to compute MS

for a highly repetitive text. They augmented a *run-length BWT* with $O(r)$ words of space, where r is the number of *runs* in the BWT for T , and their indexes support computing MS in $O(m \lg \lg n)$ time, assume that each element in T can be accessed in $O(\lg \lg n)$ time. Let z denotes the number of phrases in the *Lempel-Ziv parsing* (LZ). It has been proved that $r = O(z \lg^2 n)$ holds for every text T [6]. However, to our knowledge, the LZ-based indexes on computing MS have not been known by now.

Recently, the new compressibility measures γ , the size of the smallest *string attractor*, and δ , a better measure of repetitiveness have been proposed. Both new measures better capture the compressibility of repetitive strings. It has been proved that $\delta \leq \gamma \leq z = O(\delta \lg \frac{n}{\delta})$ [7, 8]. In this paper, we design the first string attractor based indexes (, which is also workable upon LZ-parsing) to support computation of the matching statistics with space cost measured by γ and δ . Similar to the LZ-based indexes, the computing time using string attractor based indexes might not be as efficient as the one using BWT-based indexes by Bannai et al. [5], but the indexes in the prior category always have an advantage of space cost.

Our Results. The results can be summarized as Theorem 1. In the first solution, we apply a data structure similar to the LZ-compressed indexes. Instead of using LZ parsing, we define the phrases upon the smallest string attractor. We store a Patricia tree [9] for the reversed phrases and another one for the suffixes following the phrase boundaries. To access the text $T[1..n]$ within compressed space, we apply the string indexing data structure by Kociumaka et al. [8] with space cost measured by δ . We give a simple and practical algorithm that reduces the problem of computing MS into $O(m^2)$ times of 2D orthogonal range predecessor queries upon γ points on the grid. In the second solution, we apply the data structure framework by Abedin et al. [10]. Originally, they used the framework to find the longest common substring (LCS) between P and T . Naively, computing MS of $P[1..m]$ can be reduced to m times of LCS queries. Given that each LCS query can be computed in $O(m \lg \gamma \lg \lg \gamma)$ time, the naive method would take $O(m \cdot m \cdot \lg \gamma \lg \lg \gamma)$ time. We adjust their framework to computing MS and improve the query time to be $O(m \cdot (m + \lg \gamma \lg \lg \gamma))$.

Theorem 1 *There is a data structure constructed upon a text $T[1..n]$ that supports to compute MS of a pattern $P[1..m]$ with respect to T :*

- i) in $O(m^2 \lg^\epsilon \gamma + m \lg n)$ time using $O(\delta \lg \frac{n}{\delta})$ words of space;*
- ii) in $O(m^2 + m \lg \gamma \lg \lg \gamma + m \lg n)$ time using $O(\gamma \lg \gamma + \delta \lg \frac{n}{\delta})$ words of space.*

If the text $T[1..n]$ is drawn from constant-size alphabet, we can further improve the computation time to be $O(m^2 + m \lg n)$ time using an $O(\gamma \lg \gamma + \delta \lg \frac{n}{\delta})$ word data structure. The third solution can be achieved by combining the first and second solution: i) when $m = O(\lg \gamma \lg \lg \gamma)$, we can directly apply the second solution to achieve the target bound for the query time; ii) otherwise, we update the first solution using the technique solving the *ball inheritance* problem [11] to improve the query time without decreasing the space cost. Due to the space limitation, the proof of the third solution is deferred to the full version of this paper.

Preliminaries

We describe the notations and the previous results used in our solutions. Throughout this paper, we denote ϵ to be any small positive constant, and we study all problems in the standard *word RAM* model.

Compressibility Measures. We give the precise definitions of the compressibility measures γ and δ that are mentioned above.

Definition 1 [7] *A string attractor of a string $T[1..n]$ is a set of γ' positions $\Gamma' = \{j_1, \dots, j_{\gamma'}\}$ such that every substring $T[i..j]$ has an occurrence $T[i'..j'] = T[i..j]$ with $j_k \in [i', j']$ for some $j_k \in \Gamma'$.*

Let Γ^* denote $\{1, \Gamma, n\}$, where Γ denotes the smallest size string attractor storing positions sorted increasingly. For each $2 \leq i \leq |\Gamma^*|$, we call $T[\Gamma^*[i-1], \Gamma^*[i]]$ a *parsing phrase*. Let γ denote the size of Γ . It follows that given any substring $T[i..j]$, there must be an occurrence $T[i'..j'] = T[i..j]$ such that $T[i'..j']$ crosses the phrase boundary. Kociumaka et al. [8] defined a new measure δ , which is even smaller than γ . Furthermore, different from γ , δ can be computed in linear time.

Definition 2 [8] *Let $d_k(S)$ be the number of distinct length- k substrings in S . Then*

$$\delta = \max\{d_k(S)/k : k \in [1..n]\}.$$

Induced-Check and Find Partner. Let T_1 and T_2 be two trees on the same set of n leaves. A node from T_1 and a node from T_2 are *induced* together if they have a common leaf descendant [12]. The *partner* operation [10] is defined upon the inducing relationship, which can be used to find the *longest common substring*.

Definition 3 [10] *Given a pair of trees T_1 and T_2 , the partner of a node $x \in T_1$ w.r.t a node $y \in T_2$, denoted by $\text{partner}(x/y)$, is the lowest ancestor y' of y , such that x and y' are induced. Likewise, $\text{partner}(y/x)$ is the lowest ancestor x' of x , such that x' and y are induced.*

It has been proved that the induced relationship can be solved using 2D orthogonal range emptiness queries, while finding the partner can be reduced to 2D orthogonal range predecessor/successor queries.

Lemma 1 [10] *(Induced-Check). Given two nodes x, y , where $x \in T_1$ and $y \in T_2$, we can check if they are induced or not i) in $O(\lg \lg n)$ time using an $O(n \lg \lg n)$ space structure, or ii) in $O(\lg^\epsilon n)$ time using an $O(n)$ space structure.*

Lemma 2 [10] *(Find Partner). Given two nodes x, y where $x \in T_1$ and $y \in T_2$, we can find $\text{partner}(x/y)$ as well as $\text{partner}(y/x)$ i) in $O(\lg \lg n)$ time using an $O(n \lg \lg n)$ space structure, or ii) in $O(\lg^\epsilon n)$ time using an $O(n)$ space structure.*

String Indexing. Recently, Kociumaka et al. [8] shows that with $O(\delta \lg \frac{n}{\delta})$ words of space, one can represent and index a string of n characters.

Lemma 3 [8] *Given a string $T[1..n]$ with measure δ , there exists a data structure of size $O(\delta \lg \frac{n}{\delta})$ that can be built in $O(n \lg n)$ expected time and can retrieve any substring $S[i..i + \ell]$ in time $O(\ell + \lg n)$.*

Computing MS within $O(\delta \lg \frac{n}{\delta})$ Words of Space

In this section, we describe our most space-efficient solution for computing MS. The data structure part is similar to LZ-compressed indexes used for computing Longest Common Substrings [12]. Instead of using phrases in the LZ parse, we store the parsing phrases defined upon the γ different positions in the smallest size string attractor of $T[1..n]$. We store a data structure supporting substring queries in T by Lemma 3. We store one Patricia tree T_{rev} for the reversed parsing phrases and another T_{suf} for the suffixes of T starting at different phrase boundaries. We sort the γ phrases $T[i + 1, j]$ and their corresponding suffixes $T[j + 1, n]$ in the lexicographic order, respectively. We construct a $\gamma \times \gamma$ grid, on which we store a point (x, y) iff the lexicographically x -th phrase $T[i + 1, j]$ is followed by the lexicographically y -th suffix $T[j + 1, n]$ in the text T . And we assign the x -coordinate of the point to the reversed phrase $T[i + 1, j]^{rev}$ ¹ and the y -coordinate of the point to the suffix $T[j + 1, n]$. It follows that the points on the grid are in rank space, i.e., they have coordinates on the integer grid $[\gamma]^2 = \{1, 1, 2, \dots, \gamma\}^2$. We store a linear space data structure implemented by part i) of Lemma 1 supporting 2D orthogonal range emptiness queries as induced-check, and a linear space data structure by part ii) of Lemma 2 supporting 2D orthogonal range predecessor/successor queries as **partner**-finding upon the γ points on the grid. Storing the string attractor, both Patricia trees, and the data structures for orthogonal range searching uses $O(\gamma)$ words of space. The data structure for string indexing requires $O(\delta \lg \frac{n}{\delta})$ words by Lemma 3. Overall, the data structure requires $O(\delta \lg \frac{n}{\delta})$ words of space, since $\gamma = O(\delta \lg \frac{n}{\delta})$ [8].

As the pattern has m entries, P can be split into $m - 1$ different prefix and suffix pairs, namely, $P[1..i]$ and $P[i + 1..m]$, for each $1 \leq i \leq m - 1$. Given a pair of such prefix and suffix, we can use Lemma 4 to find the loci of $(P[1..i])^{rev}$ in T_{rev} and the loci of $P[i + 1..m]$ in T_{suf} , respectively.

Lemma 4 *Given a pattern $P[1..m]$, for all $1 \leq i \leq m - 1$, we can find the longest common prefix (LCP) of $(P[1..i])^{rev}$ and the path label of the node where the search in T_{rev} terminates, and the LCP of $P[i + 1..m]$ and the path label of the node where the search in T_{suf} terminates in $O(m^2 + m \lg n)$ time.*

Proof: For each $1 \leq i \leq m - 1$, a query need to access T to check that the path labels of the nodes where the searches terminate are really prefixed by some prefixes of $(P[1..i])^{rev}$ and $P[i + 1..m]$, which can be solved by the substring queries using Lemma 3. As there are $m - 1$ different pairs of $(P[1..i])^{rev}$ and $P[i + 1..m]$ and the

¹Given a string $s = \text{“abcd”}$, the formula s^{rev} represents the string “dbca” .

†ComputingMS1($P[1..m]$, T_{suf} , T_{rev})

```

1:  $MS[1..m] \leftarrow \{0 \cdots 0\}$ 
2: for  $i = 1, 2, \dots, m - 1$  do
3:   Find  $\text{loci}_1$  of  $(P[1..i])^{rev}$  in  $T_{rev}$ 
4:   Find  $\text{loci}_2$  of  $(P[i + 1..m])$  in  $T_{suf}$ 
5:    $v \leftarrow \text{loci}_1$ 
6:   while  $v$  is not NULL do
7:      $u \leftarrow \text{partner}(v/\text{loci}_2)$ 
8:      $vp \leftarrow \text{parent}(v)$ 
9:      $j \leftarrow \text{len}(\text{str}(v))$ 
10:    while  $j > \text{len}(\text{str}(vp))$  do
11:       $\ell \leftarrow j + \text{len}(\text{str}(u))$ 
12:      if  $\ell > MS[i - j + 1]$  then
13:         $MS[i - j + 1] \leftarrow \ell$ 
14:       $j \leftarrow j - 1$ 
15:     $v \leftarrow vp$ 

```

†ComputingMS2($S[1..m]$)

```

1:  $MS[1..m] \leftarrow \{0 \cdots 0\}$ 
2:  $max \leftarrow 0$ 
3: for  $i = 1, 2, \dots, m - 1$  do
4:   if  $max \leq S[i]$  then
5:      $max \leftarrow S[i]$ 
6:    $MS[i] \leftarrow max$ 
7:   if  $max > 0$  then
8:      $max \leftarrow max - 1$ 

```

total number of characters that each pair of them contain is m , the searching time is $O(m^2 + m \lg n)$. \square

Next, we present the query algorithm. For $1 \leq i \leq m - 1$, we search for $(P[1..i])^{rev}$ in T_{rev} and for $P[i + 1..m]$ in T_{suf} ; access T to find the longest common prefix (*LCP*) of $(P[1..i])^{rev}$ and the path label of the node where the search in T_{rev} terminates, and the *LCP* of $P[i + 1..m]$ and the path label of the node where the search in T_{suf} terminates; take loci_1 and loci_2 to be the loci of those LCPs. Given a pair of locus loci_1 and loci_2 , we iterate through the path from loci_1 to the root of T_{rev} . At each node v visited, we retrieve the node u in T_{suf} such that $u = \text{partner}(v/\text{loci}_2)$. Following the partner definition, u is the lowest ancestor of loci_2 that is induced together with v . Given any tree node w , we use $\text{str}(w)$ to denote the path label of w ². It follows that $(\text{str}(v))^{rev}.\text{str}(u)$ ³ could be the longest substring of P starting at the position $(i - \text{len}(\text{str}(v)) + 1)$ that matches substring somewhere in T , and thus we set $MS[i - \text{len}(\text{str}(v)) + 1]$ to be $\text{len}(\text{str}(v).\text{str}(u))$ temporarily. Given a position $k \in [1..m - 1]$, the longest substring of P starting at k can appear crossing $m - k + 1$ different types of phrase boundaries, i.e. the boundaries whose immediately left phrase ends with $P[j]$ and immediately right phrase starts with $P[j + 1]$ for each $k \leq j \leq m - 1$. And $MS[i]$ finally store the maximum length of those different types of longest substrings. To achieve that, whenever a longer prefix of $P[i..m]$ that crosses some phrase boundary and matches somewhere in T was found, $MS[i]$ should be updated accordingly. The algorithm is shown in ComputingMS1.

We analyze the query time of the algorithm. As shown in Lemma 4, all locus of

²If v (resp. u) is the loci, then the longest matched prefix of $(P[1..i])^{rev}$ (resp. $P[i + 1..m]$) could be a proper substring of the path label of v (resp. u). In that case, we let $\text{str}(v)$ (resp. $\text{str}(u)$) denote the longest matched prefix of $(P[1..i])^{rev}$ (resp. $P[i + 1..m]$). And $\text{str}(\text{root})$ is always 0.

³For example, “abc”.“efg”=“abcefg”.

[†]W.l.o.g., we assume that $m > 1$. $MS[m]$ is set to 1, if the loci of $P[m]$ on T_{suf} is a non-root node; Otherwise, $MS[m]$ is set to 0.

LCPs can be found in $O(m^2 + m \lg n)$ time. For each $1 \leq i \leq m - 1$, the while loop block can be operated $O(i)$ times. And all $O(i)$ iterations would call totally $O(i)$ times of **partner**-finding queries and fill at most i entries in MS. If only $O(\gamma)$ words of space is allowed, each **partner**-finding query requires $O(\lg^\epsilon \gamma)$ time as shown in part ii) of Lemma 2. Therefore, the overall query time is $O(m^2 + m \lg n + \sum_{i=1}^{m-1} O(i \cdot \lg^\epsilon \gamma + i)) = O(m^2 \lg^\epsilon \gamma + m \lg n)$ time. The first solution completes.

Towards Improving the Computing Time

In this section, we are trying to get rid of the factor $\lg^\epsilon \gamma$ from the term $m^2 \lg^\epsilon \gamma$ shown in the computing time before. As a result, the space cost of the new data structure gets worse a little bit. Before showing our new solutions, we introduce a new definition *locally potential maximal exact matching (LPMEM)*

Definition 4 *Given a phrase boundary $k' \in \Gamma$ matching with the pattern $P[1..m]$ somewhere between $P[k]$ and $P[k + 1]$, if $P[i..k]$ and $T[k' - k + i..k']$ match with each other but $P[i - 1..k]$ and $T[k' - k + i - 1..k']$ do not and $P[k + 1..j]$ and $T[k' + 1, k' + j - k]$ match with each other but $P[k + 1..j + 1]$ and $T[k' + 1, k' + j - k + 1]$ do not, then we call $P[i..j]$ a locally potential maximal exact matching (LPMEM) that crosses the phrase boundary at the position k' .*

Let v (resp. u) denote an ancestor node of loci_1 (resp. loci_2) in T_{rev} (resp. T_{suf}); let $\text{Path}(v, \text{loci}_1, T_{rev})$ denote the path between v and loci_1 on T_{rev} ; let $\text{Path}(u, \text{loci}_2, T_{suf})$ denote the path between u and loci_2 on T_{suf} . It follows that if i) v and u are induced together; ii) the child of v on $\text{Path}(v, \text{loci}_1, T_{rev})$ does not induce with the node u in T_{suf} ; iii) and the child of u on $\text{Path}(u, \text{loci}_2, T_{suf})$ does not induce with the node v in T_{rev} , then v and u together induce a LPMEM, which is $(\text{str}(v))^{rev} \cdot \text{str}(u)$.

Basic Properties of LPMEMs. We discuss the properties of LPMEMs. Those properties will be useful for designing the data structures and the query algorithm of the second solution. For simplicity, we call the set of all substrings of $P[1..m]$ that appear as LPMEM's in the text $T[1..n]$ the LPMEMs of P .

Lemma 5 *Given a pattern $P[1..m]$ and all occ LPMEMs of P , we can construct MS of P in $O(\text{occ} + m)$ time.*

Proof: Given that all occ LPMEMs have been found, each LPMEM can be represented by its starting position i in P and its length $\ell(i)$. We store an array $S[1..m]$ such that for each $1 \leq i \leq m$, if $P[i, i + \ell - 1]$ is a LPMEM, then we set $S[i]$ to $\ell(i)$. If there are multiple LPMEMs sharing the same starting position i in P , we store the one with the largest $\ell(i)$. It follows that for each $1 \leq i \leq m$, $MS[i]$ is equal to $\max(MS[i - 1] - 1, S[i])$, where $MS[0]$ is 0. We can apply ComputingMS2 to compute $MS[1..m]$. Computing $S[1..m]$ takes $O(\text{occ} + m)$ time and ComputingMS2 requires m steps. Hence, the computing time is $O(\text{occ} + m)$, where $\text{occ} \leq m(m - 1)/2$ ⁴. \square

⁴A pattern P with m characters can have at most $\binom{m}{2}$ substrings that appear as LPMEM's in the text $T[1..n]$.

We compute the *heavy path decomposition* [13] of T_{rev} and T_{suf} that are constructed before. Given a node u on a heavy path H , we use `hp_root(u)` (resp. `hp_leaf(u)`) to denote the highest (resp. lowest) node of H . And we call the highest node of each heavy path *light*. As T_{rev} and T_{suf} each has γ leaf nodes, the path from the root to any leaf traverses at most $O(\lg \gamma)$ light nodes. We give a new definition *special skyline node list* borrowing the ideas of *skyline node list* from [12] and *special nodes* from [10].

Definition 5 For each light node $w \in T_{suf}$, we identify a set, `SpecialLeaves(w)`, of leaf nodes in T_{rev} and a set, `SpecialSkylineList(w)`, of internal nodes in T_{rev} as follows: a leaf node $l \in T_{rev}$ is special iff l and w are induced with each other. Given special leaves x and y , we define a special skyline node $v \in \text{SpecialSkylineList}(w)$ if v is a proper ancestor of `lca(x, y)` and the child of v on `Path($v, \text{lca}(x, y), T_{rev})$` does not induce with `partner($v/\text{hp_leaf}(w)$)`. Following [10], we identify a set, `Special(w)`, of nodes in T_{rev} such that *i*) for each $x \in \text{SpecialLeaves}(w)$, $x \in \text{Special}(w)$; and *ii*) for each $x, y \in \text{SpecialLeaves}(w)$, `lca(x, y)` $\in \text{Special}(w)$.

As shown before, for each $1 \leq i \leq m - 1$, we search for $(P[1..i])^{rev}$ in T_{rev} and for $P[i + 1..m]$ in T_{suf} ; take `loci1(i)` and `loci2(i)` to be the loci of those LCPs. Let u and v denote some ancestor nodes of `loci1(i)` and `loci2(i)` on T_{rev} and T_{suf} , respectively. Let $root_1$ (resp. $root_2$) denote the root node of T_{rev} (resp. T_{suf}). Henceforth, if u and v induce a LPMEM, $(\text{str}(u))^{rev}.\text{str}(v)$ ⁵, then we call u the *beginning* node and v the *ending* of that LPMEM. Clearly, the beginning node of all LPMEMs crossing the boundary between $P[i]$ and $P[i + 1]$ are on `Path(partner(loci2(i)/loci1(i), loci1(i), $T_{rev})$ and the ending nodes are on Path(partner(loci1(i)/loci2(i), loci2(i), $T_{suf})$.`

Let w_1, \dots, w_k denote a sequence of light nodes on `Path($root_2, \text{loci}_2(i), T_{suf})$` sorted increasingly by the node depths such that `partner(loci1(i)/loci2(i))` is contained in the heavy path rooted by w_1 , and w_k is the lowest light node above `loci2(i)`. Similarly, let t_1, \dots, t_k denote the nodes on `Path($root_2, \text{loci}_2(i), T_{suf})$` such that $t_k = \text{loci}_2(i)$ and $t_h = \text{parent}(w_{h+1})$ for $h < k$. Let α_f be `partner($t_f/\text{loci}_1(i)$)` and β_f be `partner($w_f/\text{loci}_1(i)$)`, for each $1 \leq f \leq k$.

Lemma 6 For each $1 \leq f \leq k$, β_f and `partner($\beta_f/\text{loci}_2(i)$)` induce a LPMEM, and α_f and `partner($\alpha_f/\text{loci}_2(i)$)` induce a LPMEM.

Proof: Let u denote `partner($\alpha_f/\text{loci}_2(i)$)` in T_{suf} . Since α_f in T_{rev} and t_f in T_{suf} are induced together, u must be in the subtree of t_f . Suppose that the child c of α_f on `Path($\alpha_f, \text{loci}_1(i), T_{rev})$` is induced with u . As t_f is an ancestor of u , t_f in T_{suf} and c in T_{rev} must be induced together, which contradicts with the claim that α_f is `partner($t_f/\text{loci}_1(i)$)`. Therefore, c can not be induced with u in T_{suf} . Following the definition of `partner`, the child of u on `Path($u, \text{loci}_2(i), T_{suf})$` cannot be induced with α_f . Hence, u and α_f induce a LPMEM. The claim that `partner($\beta_f/\text{loci}_2(i)$)` and β_f induce a LPMEM follows similarly. \square

⁵To compute the matching statistics, reporting a LPMEM $(\text{str}(u))^{rev}.\text{str}(v)$ verbatim is unnecessary. What we need are its starting position in $P[1..m]$, which is $i - \text{len}(\text{str}(u)) + 1$, and the length of the LPMEM, which is $\text{len}(\text{str}(u)) + \text{len}(\text{str}(v))$.

Lemma 7 *Given a node u on T_{rev} and a node v on T_{suf} , such that u and v induce a LPMEM, if $v \in \text{Path}(w_f, t_f, T_{suf})$ for some $1 \leq f \leq k$, then $u \in \text{Path}(\alpha_f, \beta_f, T_{rev})$.*

Proof: The proof is similar to the one shown as [10, Lemma 12]. Suppose u is a proper ancestor of α_f . Since α_f and t_f are induced together, v (as an ancestor of t_f) is also induced with α_f . Due to this, u and v can not induce a LPMEM, which is a contradiction. Therefore, u must be in the subtree of α_f . Suppose u is in the proper subtree of β_f . Since u and v are induced together and v is in the subtree rooted at w_f , u and w_f are induced together, which contradicts with the claim that β_f is $\text{partner}(w_f/\text{loci}_1(i))$. Therefore, u must be an ancestor of β_f . \square

Lemma 8 [10, Lemma 14] *For each $1 \leq f \leq k$ and any $x \in \text{Path}(\alpha_f, \beta_f, T_{rev}) \setminus \{\alpha_f\}$, $\text{partner}(x/\text{loci}_2(i)) = \text{partner}(x/t_f) = \text{partner}(x/\text{hp_leaf}(w_f))$ always holds.*

Lemma 9 *For each $v \in \text{SpecialSkylineList}(w_f)$, it follows that $v \in \text{Special}(w_f)$.*

Proof: Let x and y be a pair of special leaves under v such that the child c of v on $\text{Path}(v, \text{lca}(x, y), T_{rev})$ does not induce with $\text{partner}(v/\text{hp_leaf}(w_f))$. Since $\text{partner}(v/\text{hp_leaf}(w_f))$ and v are induced together by some special leaf ℓ under the sibling node of c , it follows that $\text{lca}(x, \ell)$ or $\text{lca}(y, \ell)$ is v , and $v \in \text{Special}(w_f)$. \square

Lemma 10 *Given a node u on $\text{Path}(\alpha_f, \beta_f, T_{rev})$ and an ancestor node v of $\text{loci}_2(i)$ on T_{suf} , if u and v induce a LPMEM, and $u \notin \{\text{SpecialSkylineList}(w_f) \cup \alpha_f \cup \beta_f\}$, then $u = \text{lca}(\ell, \ell')$ for some pair of $\ell, \ell' \in \text{SpecialLeaves}(w_f)$.*

Proof: Since β_f and w_f are induced together, and u is a proper ancestor of β_f , there is a special leaf ℓ as the common descendent of β_f and u . As u and v induce a LPMEM and u is not α_f , $v = \text{partner}(u/\text{loci}_2(i)) = \text{partner}(u/t_f)$ by Lemma 8. Since u and w_f are induced together by ℓ , v must be a descendent of w_f . There is at least one leaf ℓ' under u that makes u and v induced with each other, and ℓ' is a special leaf because it is induced with w_f . If ℓ' and ℓ are the same, then β_f and v are induced together, which contradicts with the claim that u and v induce a LPMEM. There are at least two special leaves ℓ and ℓ' under u . Since $u \notin \text{SpecialSkylineList}(w_f)$, $u = \text{lca}(\ell, \ell')$. The proof completes. From Lemma 8 and Definition 5, we know that for each node $x \in \{\text{SpecialSkylineList}(w_f) \setminus (\alpha_f \cup \beta_f)\}$, x and $\text{partner}(x/\text{hp_leaf}(w_f))$ always induce a LPMEM. \square

The Second Solution. We apply the induced subtree defined in [10, Definition 18] to support finding LPMEM. An induced subtree $T_{rev}(w)$ w.r.t a light node $w \in T_{suf}$ is a tree having exactly $|\text{Special}(w)|$ nodes such that i) each node $l \in \text{Special}(w)$ has a corresponding node \hat{l} in $T_{rev}(w)$; and ii) for each pair of $\ell, \ell' \in \text{Special}(w)$, node $\text{lca}(\ell, \ell')$ in T_{rev} has a corresponding node in $T_{rev}(w)$ as lca of $\hat{\ell}$ and $\hat{\ell}'$. To support finding LPMEMs, we revise the induced subtrees as follows. For each internal node \hat{v} of $T_{rev}(w)$, we maintain a pointer e_0 pointing to its lowest proper ancestor \hat{v}' (if exists) that belongs to $\text{SpecialSkylineList}(w)$ and a pointer e_1 pointing to its

corresponding node v in T_{rev} ; for each special skyline node \hat{v} of $T_{rev}(w)$, we maintain a pointer e_2 pointing to $\text{partner}(v/\text{hp_leaf}(w))$ in T_{suf} .

Since $\sum_w |\text{Special}(w)| = O(\gamma \lg \gamma)$ for all light nodes $w \in T_{suf}$, all revised induced subtrees totally use $O(\gamma \lg \gamma)$ words of space. Abedin et al. [10, Lemma 19] show that given a node $\ell \in \text{Special}(w)$, one can find its corresponding node $\hat{\ell}$ in $T_{rev}(w)$ in $O(\lg \lg \gamma)$ time by maintaining an $O(\gamma \lg \gamma)$ word data structure. In addition, the data structures introduced in the first solution are also required occupying extra $O(\delta \lg \frac{n}{\delta})$ words of space. Therefore, the overall space cost is $O(\delta \lg \frac{n}{\delta}) + O(\gamma \lg \gamma)$ words.

We show how to find LPMEMs between P and T . By Lemma 4, we can find the locus $\text{loci}_1(i)$ and $\text{loci}_2(i)$ on T_{rev} and T_{suf} in $O(m^2 + m \lg n)$ time for all $1 \leq i \leq m - 1$. We compute $\text{partner}(\text{loci}_2(i)/\text{loci}_1(i))$ and $\text{partner}(\text{loci}_1(i)/\text{loci}_2(i))$. Each partner operation takes $O(\lg \lg \gamma)$ time by part i) of Lemma 2. If $\text{loci}_1(i)$ and $\text{loci}_2(i)$ are induced with each other, then there is only one LPMEM crossing the phrase boundary between $P[i]$ and $P[i+1]$, which is $(\text{str}(\text{loci}_1(i)))^{rev}.\text{str}(\text{loci}_2(i))$, and we continue to search for LPMEMs crossing the phrase boundary between $P[i+1]$ and $P[i+2]$. Otherwise, we iterate through $\text{Path}(\text{root}_2, \text{loci}_2(i), T_{suf})$ to find the light nodes w_1, \dots, w_k and t_1, \dots, t_k as described before, and compute α_f and β_f for all $1 \leq f \leq k$. Since $\beta_1 = \text{partner}(w_1/\text{loci}_1(i)) = \text{loci}_1(i)$ and $\alpha_k = \text{partner}(t_k/\text{loci}_1(i)) = \text{partner}(\text{loci}_2(i)/\text{loci}_1(i))$, each of those LPMEMs has its beginning node on $\text{Path}(\beta_1, \alpha_k, T_{rev})$. We traverse the path from β_1 to α_k . In general, the beginning nodes on the subpath from β_f to α_f consist of 3 parts: α_f , β_f , and some special nodes between α_f (excluding α_f) and β_f (excluding β_f). Finding LPMEMs induced by α_f and $\text{partner}(\alpha_f/\text{loci}_2(i))$, and β_f and $\text{partner}(\beta_f/\text{loci}_2(i))$ is straightforward, and each takes $O(\lg \lg \gamma)$ time. There are $2k$ such LPMEMs, and finding all of them takes $O(\lg \gamma \lg \lg \gamma)$ time, since $k = O(\lg \gamma)$.

It remains to find the LPMEMs with their beginning nodes between α_f (excluding α_f) and β_f (excluding β_f). Given an internal tree node x , we use $\text{lMost}(x)$ (resp. $\text{rMost}(x)$) to denote the index of the leftmost (resp. rightmost) leaf descendant of x . Since β_f is $\text{partner}(w_f/\text{loci}_1(i))$, there exists at least a special leaf of T_{rev} as a descendent of β_f that belongs to $\text{SpecialLeaves}(w_f)$, and we use ℓ to denote the leftmost one. We also find the rightmost special leaf ℓ' from the $\text{lMost}(x) - 1$ leaves of T_{rev} in the left side and the leftmost special leaf ℓ'' after the $\text{rMost}(w_f)$ -th leaf of T_{rev} in the right side. It follows that the lowest special node v above β_f is the lower one between $\text{lca}(\ell', \ell)$ and $\text{lca}(\ell, \ell'')$. Once v is found, we check whether it is a beginning node of some LPMEM: If the child of v on $\text{Path}(v, \text{loci}_1(i), T_{rev})$ does not induce with $\text{partner}(v/\text{loci}_1(i))$, then we report a LPMEM induced by v and $\text{partner}(v/\text{loci}_1(i))$. Since v is a special node, we find its corresponding node \hat{v} on $T_{rev}(w)$ in $O(\lg \lg \gamma)$ time by [10, Lemma 19]. Following the pointer e_0 stored at \hat{v} , we can find the lowest special skyline node \hat{v}' above \hat{v} . Note that \hat{v}' is a beginning node of some LPMEM. We can find that LPMEM following the pointers e_1 and e_2 stored at \hat{v}' in $O(1)$ time. We repeat this procedure to iterate over each special skyline node above \hat{v} , and stop once we found a node whose pointer e_1 pointing to α_f . Each of ℓ, ℓ', ℓ'' can be found in $O(\lg \lg \gamma)$ time by 2D orthogonal range successor

queries⁶, e.g., the leaf index of ℓ is the x -coordinate of the leftmost point in the query range $[\mathbf{lMost}(\beta_f), \mathbf{rMost}(\beta_f)] \times [\mathbf{lMost}(w_f), \mathbf{rMost}(w_f)]$. After finding the lowest special node \hat{v} , reporting the LPMEMs associated with $\mathbf{SpecialSkylineList}(w_f)$ takes $O(\text{occ}(w_f))$ time, where $\text{occ}(w_f)$ denotes the number of reported LPMEMs. As there are k different such different $\mathbf{SpecialSkylineList}(w_f)$, finding occ_i LPMEMs between $\text{loci}_1(i)$ and $\text{loci}_2(i)$ requires $O(k \lg \lg \gamma + \text{occ}_i) = O(\lg \gamma \lg \lg \gamma + \text{occ}_i)$ time, since $k = O(\lg \gamma)$. Considering there are $m - 1$ different pairs of locus $\text{loci}_1(i)$ and $\text{loci}_2(i)$, finding all LPMEMs between P and T takes $O(m \lg \gamma \lg \lg \gamma + \text{occ})$ time. The overall query time is $O(m^2 + m \lg \gamma \lg \lg \gamma + m \lg n)$, since $\text{occ} = O(m^2)$. After finding all the LPMEMs, we can use Algorithm 2 to compute the matching statistics.

Computing MS for a Text Drawn from Constant-Size Alphabet.

In the genomic databases, the constant-size texts arise frequently, e.g., the DNA sequence is drawn from $\{A, C, G, T\}$. When the alphabet size is constant, we can further improve the computation time to be $O(m^2 + m \lg n)$, while maintaining the overall space cost. In this section, we first give the third solution to the general case such that $T[1..n]$ is drawn from the alphabet $[\sigma]$. After that we present the result particularly when σ is constant. The new solution will apply **rank** and **select** operations from the succinct data structures.

Lemma 11 [14] *Let $A[1..n']$ be an array of n' characters drawn from alphabet $[\sigma']$. There exists a data structure constructed upon A using $O(n' \lg \sigma')$ bits of space, supporting $\mathbf{rank}_c(A, i)$ queries in $O(\lg \lg \sigma')$ time and $\mathbf{select}_c(A, i)$ queries in constant time, where $\mathbf{rank}_c(A, i)$ counts the number of character c that appears in $A[1..i]$, and $\mathbf{select}_c(A, i)$ gives the position of the i -th occurrence of character c in the sequence.*

As shown in the second solution, whenever $m = \Omega(\lg \gamma \lg \lg \gamma)$, the query time is bounded by $O(m^2 + m \lg n)$. Therefore, we only need to consider the case when $m = O(\lg \gamma \lg \lg \gamma)$. We will modify the data structure used in the first solution applying the technique that solves the ball inheritance problem [11].

Before showing the updated data structure, we review the query algorithm in the first solution. Given a pair of locus $\text{loci}_1(i)$ and $\text{loci}_2(i)$ in T_{rev} and T_{suf} achieved by searching for the longest prefixes of $(P[1..i])^{rev}$ and $P[i + 1..m]$ in T_{rev} and T_{suf} , respectively, we iterate over each node v on $\mathbf{Path}(\text{loci}_1(i), \text{root}_1, T_{rev})$, and compute $\mathbf{partner}(v/\text{loci}_2(i))$ to find the potential longest common prefix between $P[i - \text{len}(\text{str}(v)) + 1..]$ and T . As shown as [10, Lemma 10], the partner-finding operation $\mathbf{partner}(v/\text{loci}_2(i))$ can be reduced to a range emptiness query in the range $[\mathbf{lMost}(v), \mathbf{rMost}(v)] \times [\mathbf{lMost}(\text{loci}_2(i)), \mathbf{rMost}(\text{loci}_2(i))]$, finding the y -coordinate of the lowest point (a.k.a. a range successor query) within $[\mathbf{lMost}(v), \mathbf{lMost}(v)] \times (\mathbf{rMost}(\text{loci}_2(i)), +\infty)$, and finding the y -coordinate of the highest point (a.k.a. a range predecessor query) within $[\mathbf{lMost}(v), \mathbf{rMost}(v)] \times (-\infty, \mathbf{lMost}(\text{loci}_2(i)))$. We observe that: i) as v is changed from $\text{loci}_1(i)$ to root_1 , the query range along y -axis is fixed; ii) given any two nodes s and t in $\mathbf{Path}(\text{root}_1, \text{loci}_1(i), T_{rev})$, if s is an ancestor of

⁶The 2D orthogonal range successor query is also used for answering the **partner** operation.

t , then $[\mathbf{lMost}(t), \mathbf{rMost}(t)] \subset [\mathbf{lMost}(s), \mathbf{rMost}(s)]$. We will apply these observations to improve the overall query time for multiple partner-finding operations. Henceforth, we take the predecessor query along y -axis within the range $[\mathbf{lMost}(v), \mathbf{rMost}(v)] \times (-\infty, \mathbf{lMost}(\mathbf{loci}_2(i)))$ for each node v on $\text{Path}(\mathbf{loci}_1(i), \text{root}_1, T_{rev})$ as an example to describe the solution, while the 2D range emptiness queries and 2D range successor queries can be answered similarly.

We number the tree levels of T_{rev} incrementally starting from the root level, which is level 0; call the first $\lg^{1+\epsilon} \gamma$ tree levels the *active tree levels* for any small constant $\epsilon > 0$. Let v denote any internal node of T_{rev} at some active level; let $\mathbf{size}(v)$ denote the number of leaves in the subtree rooted by v ; let $\ell(v)$ denote its tree level. We associate node v with a sequence $S(v)[1..\mathbf{size}(v)]$ storing the points whose x -coordinates in the range $[\mathbf{lMost}(v), \mathbf{rMost}(v)]$ and make sure these points are sorted by their y -coordinates. Given sequences $S(v)$, the predecessor query along y -axis within $[\mathbf{lMost}(v), \mathbf{rMost}(v)] \times (-\infty, \mathbf{lMost}(\mathbf{loci}_2(i)))$ can be reduced to finding the predecessor of $\mathbf{lMost}(\mathbf{loci}_2(i))$ in one dimension, and the coordinates of $S(v)[g]$ can be accessed immediately. However, storing all these $S(v)$'s would occupy $O(\gamma \lg^{1+\epsilon} \gamma)$ words of space. For saving space, we only store $S(\text{root}_1)$ at the root node, but give a space-efficient data structure that allows to access the coordinates of $S(v)[g]$ for any node v on the active tree level.

We use the technique that solves the ball inheritance problem in a reversed way. Let τ be $\lg^\epsilon \gamma$. For simplicity, we assume that both $1/\epsilon$ and τ are integers. We assign a color to each active level of T_{rev} : Level-0 is assigned color $1/\epsilon + 1$, while any other Level- ℓ is assigned color $c(\ell)$, where $c(\ell) = \max\{c \mid (\lg^{1+\epsilon} \gamma - \ell) \text{ is a multiple of } \tau^c \text{ and } 0 \leq c \leq 1/\epsilon + 1\}$. At each internal node v on the active level, we store $(\tau - 1) \cdot c(\ell(v))$ arrays of *skipping pointers*. For each $0 \leq t \leq c(\ell(v)) - 1$ and $1 \leq k \leq \tau - 1$, the j -th entry of array $\mathbf{SP}(v, t, k)$ stores the descendant of v at level $\ell(v) + \tau^t \cdot k$ containing the point $S(v)[j]$, and the descendant is encoded by its rank among all the descendants of v at the level $\ell(v) + \tau^t \cdot k$ in the left-to-right order. We use Lemma 11 to support $O(1)$ -time **select** over array $\mathbf{SP}(v, t, k)$. Since both $S(v)$ and $S(\mathbf{SP}(v, t, k)[j])$ order points by y -coordinate, a **select** $_{\mathbf{SP}(v, t, k)[j]}(\mathbf{SP}(v, t, k), g)$ query gives the position of the point $S(\mathbf{SP}(v, t, k)[j])[g]$ in $S(v)$. In general, to compute the point coordinates of $S(v)[g]$, we find the lowest ancestor v' of v such that $c(\ell(v')) > c(\ell(v))$, and then use the query **select** $_{r(v)}(\mathbf{SP}(v', c(\ell(v)), \frac{\ell(v) - \ell(v')}{\tau^{c(\ell(v))}}), g)$ to locate the position of $S(v)[g]$ in $S(v')$, where $r(v)$ denotes the rank of v among all the descendants of v' at the level $\ell(v)$.⁷ One hop from v to v' increases the node color by at least one. Therefore, after at most $1/\epsilon + 1 - c(v)$ hops, we reach the root level, where we retrieve the point coordinates stored in $S(\text{root}_1)$. Since each **select** query takes constant time, the overall query time is $O(1)$.

We analyze the space cost for storing all $\mathbf{SP}(v, t, k)$'s. As the size of the alphabet that $T[1..n]$ drawn from is σ , the out-degree of each node in T_{rev} is σ . There are $\sigma^{\tau^t \cdot k}$ descendants of v on the tree level $\ell(v) + \tau^t \cdot k$, and the rank of each of them can be encoded in $\lg(\sigma^{\tau^t \cdot k})$ bits of space. Clearly, there are $\frac{\lg^{1+\epsilon} \gamma}{\tau^c}$ active levels colored in c

⁷Since there is unique ancestor v' of v that v can hop over to, we simply store a pointer that pointing to v' and the rank $r(v)$ w. r. t. v' at node v in the preprocessing stage.

for each $0 \leq c \leq 1/\epsilon + 1$, and all $\text{SP}(v, t, k)$'s at the same tree level have γ entries in total. Therefore, the overall space cost in bits is as follows:

$$\gamma \sum_{c=0}^{1/\epsilon+1} \left(\frac{\lg^{\epsilon+1} \gamma}{\tau^c} \sum_{t=0}^{c-1} \left(\sum_{k=1}^{\tau-1} (\lg(\sigma^{\tau^t \cdot k})) \right) \right) \leq \gamma \lg \sigma \sum_{c=0}^{1/\epsilon+1} \left(\frac{\lg^{\epsilon+1} \gamma}{\tau^c} \tau^{c-1} \sum_{k=1}^{\tau-1} k \right) = O(\gamma \lg \sigma \lg^{2\epsilon+1} \gamma)$$

Note that the data structure supporting `select` queries upon $\text{SP}(v, t, k)$ has the same space upper bound as the one for storing $\text{SP}(v, t, k)$. Hence, Lemma 12 follows.

Lemma 12 *We can build a data structure of $O(\gamma \lg \sigma \lg^{2\epsilon+1} \gamma)$ bits of space upon T_{rev} such that later, given a node v on any active level, one can find the point coordinates of $S(v)[g]$ in constant time.*

Next, we show the data structure that can support computing multiple partner-finding operations efficiently: We construct a sequence $R(v)[1..\text{size}(v)]$ at each internal node v on the active tree level such that if the point $S(v)[j]$ is stored in $S(v_s)$ in the next level, where v_s denotes the s -th child of v in the left-to-right order, then $R(v)[j]$ is set to be s ; use Lemma 11 to support $O(\lg \lg \sigma)$ -time `rank` over $R(v)$. Since the out-degree of each node in T_{rev} is σ , $R(v)$ and its associated data structure uses $O(\text{size}(v) \lg \sigma)$ bits of space. All $R(v)$'s stored on the active levels use $O(\gamma \lg \sigma \lg^{1+\epsilon} \gamma)$ bits of space. Finally, we use Lemma 12 to access the coordinates of $S(v)[g]$, which occupies $O(\gamma \lg \sigma \lg^{2\epsilon+1} \gamma)$ bits of space additionally.

We describe how to find the predecessor along y -axis within $[\text{lMost}(v), \text{rMost}(v)] \times (-\infty, \text{lMost}(\text{loci}_2(i)))$ for each node v on $\text{Path}(\text{loci}_1(i), \text{root}_1, T_{rev})$. We traverse through $\text{Path}(\text{loci}_1(i), \text{root}_1, T_{rev})$ reversely, i.e., from the root node to $\text{loci}_1(i)$. At the root node, the index j of the proper predecessor of $\text{lMost}(\text{loci}_2(i))$ in $S(\text{root}_1)$ is $\text{lMost}(\text{loci}_2(i)) - 1$, because $S(\text{root}_1)$ contains all the coordinates of γ points in rank space and those points are increasingly sorted by y -coordinates. We immediately return the y -coordinate of $S(\text{root}_1)[j]$ in constant time. In general, given two nodes u and v on $\text{Path}(\text{loci}_1(i), \text{root}_1, T_{rev})$ such that v is the e -th child of u in the left-to-right order, if we know the index j_u of the predecessor of $\text{lMost}(\text{loci}_2(i))$ in $S(u)$, then the index j_v of the predecessor of $\text{lMost}(\text{loci}_2(i))$ in $S(v)$ can be located in $O(\lg \lg \sigma)$ time by $\text{rank}_e(R(u), j_u)$; and then we use Lemma 12 to access the y -coordinate of $S(v)[j_v]$ in constant time. As there are i characters in $(P[1..i])^{rev}$, there are at most i nodes on $\text{Path}(\text{loci}_1(i), \text{root}_1, T_{rev})$. Hence, all predecessor queries along the path can be answered in $O(i \lg \lg \sigma)$ time. As a result, the `partner`($v/\text{loci}_2(i)$) queries for all v on $\text{Path}(\text{loci}_1(i), \text{root}_1, T_{rev})$ can be answered in $O(i \lg \lg \sigma)$ time. Considering there are $m - 1$ different pairs of $\text{loci}_1(i)$ and $\text{loci}_2(i)$, the query time of computing MS is $\sum_{i=1}^{m-1} O(i \lg \lg \sigma) = O(m^2 \lg \lg \sigma)$ time, given that all pairs of locus are available. Since finding $m - 1$ pairs of locus requires $O(m^2 + m \lg n)$ time by Lemma 4, the overall query time is $O(m^2 \lg \lg \sigma + m \lg n)$. This completes the third solution:

Theorem 2 *Given a text $T[1..n]$ drawn from $[\sigma]$, we can build a data structure for $T[1..n]$ with $O(\gamma \lg \gamma + \delta \lg \frac{n}{\delta} + \frac{\gamma}{\log_{\sigma} n} \lg^{2\epsilon+1} \gamma)$ words of space, for any small constant $\epsilon > 0$, such that later, given $P[1..m]$, we can compute MS for P with respect to T in $O(m^2 \lg \lg \sigma + m \lg n)$ time, assuming that the number of bits in a word is $\Omega(\lg n)$.*

Corollary 1 *Given a text $T[1..n]$ drawn from constant-size alphabet, we can build a data structure for $T[1..n]$ with $O(\gamma \lg \gamma + \delta \lg \frac{n}{\delta})$ words of space, such that later, given $P[1..m]$, we can compute MS for P with respect to T in $O(m^2 + m \lg n)$ time.*

Acknowledgements. The author would like to thank Travis Gagie and Meng He for discussing various topics related to the compact data structures, and especially thank Travis for sharing this research topic as a course project.

- [1] William I. Chang and Eugene L. Lawler, “Sublinear approximate string matching and biological applications,” *Algorithmica*, vol. 12, no. 4, pp. 327–344, 1994.
- [2] Dan Gusfield, “Algorithms on stings, trees, and sequences: Computer science and computational biology,” *Acm Sigact News*, vol. 28, no. 4, pp. 41–60, 1997.
- [3] Enno Ohlebusch, Simon Gog, and Adrian Kügel, “Computing matching statistics and maximal exact matches on compressed full-text indexes,” in *International Symposium on String Processing and Information Retrieval*. Springer, 2010, pp. 347–358.
- [4] Gonzalo Navarro and Veli Mäkinen, “Compressed full-text indexes,” *ACM Computing Surveys (CSUR)*, vol. 39, no. 1, pp. 2–es, 2007.
- [5] Hideo Bannai, Travis Gagie, and I Tomohiro, “Refining the r-index,” *Theoretical Computer Science*, vol. 812, pp. 96–108, 2020.
- [6] Dominik Kempa and Tomasz Kociumaka, “Resolution of the burrows-wheeler transform conjecture,” in *2020 IEEE 61st Annual Symposium on Foundations of Computer Science (FOCS)*. IEEE, 2020, pp. 1002–1013.
- [7] Dominik Kempa and Nicola Prezza, “At the roots of dictionary compression: string attractors,” in *Proceedings of the 50th Annual ACM SIGACT Symposium on Theory of Computing*, 2018, pp. 827–840.
- [8] Tomasz Kociumaka, Gonzalo Navarro, and Nicola Prezza, “Towards a definitive measure of repetitiveness,” in *Latin American Symposium on Theoretical Informatics*. Springer, 2021, pp. 207–219.
- [9] Donald R Morrison, “Patricia—practical algorithm to retrieve information coded in alphanumeric,” *Journal of the ACM (JACM)*, vol. 15, no. 4, pp. 514–534, 1968.
- [10] Paniz Abedin, Sahar Hooshmand, Arnab Ganguly, and Sharma V Thankachan, “The heaviest induced ancestors problem revisited,” in *Annual Symposium on Combinatorial Pattern Matching (CPM 2018)*. Schloss Dagstuhl-Leibniz-Zentrum fuer Informatik, 2018.
- [11] Timothy M Chan, Kasper Green Larsen, and Mihai Pătraşcu, “Orthogonal range searching on the ram, revisited,” in *Proceedings of the twenty-seventh annual symposium on Computational geometry*, 2011, pp. 1–10.
- [12] Travis Gagie, Paweł Gawrychowski, and Yakov Nekrich, “Heaviest induced ancestors and longest common substrings,” *arXiv preprint arXiv:1305.3164*, 2013.
- [13] Dov Harel and Robert Endre Tarjan, “Fast algorithms for finding nearest common ancestors,” *siam Journal on Computing*, vol. 13, no. 2, pp. 338–355, 1984.
- [14] Alexander Golynski, J Ian Munro, and S Srinivasa Rao, “Rank/select operations on large alphabets: a tool for text indexing,” in *SODA*, 2006, vol. 6, pp. 368–373.