

Competitive Algorithms for Online Weighted Bipartite Matching and its Variants

Nguyễn Kim Thăng
IBISC, University Paris-Saclay, France

Abstract

Online bipartite matching has been extensively studied. In the unweighted setting, Karp et al. [19] gave an optimal $(1 - 1/e)$ -competitive randomized algorithm. In the weighted setting, optimal algorithms have been achieved only under assumptions on the edge weights. For the general case, little was known beyond the trivial $1/2$ -competitive greedy algorithm. Recently, Fahrbach et al. [10] have presented an 0.5086 -competitive algorithm (for the problem in a model, namely free-disposal), overcoming the long-standing barrier of $1/2$. Besides, in designing competitive algorithms for the online matching problem and its variants, several techniques have been developed, in particular the primal-dual method. Specifically, Devanur et al. [7] gave a primal-dual framework, unifying previous approaches and Devanur and Jain [6] provided another scheme for a generalization of the online matching problem.

In this paper, we present competitive algorithms for the online weighted bipartite matching in different models; in particular we achieve the *optimal* $(1 - 1/e)$ competitive ratio in the free-disposal model and in other model, namely stochastic reward. Our work also unifies the approaches by Devanur et al. [7] and Devanur and Jain [6] by the mean of the primal-dual technique with configuration linear programs.

1 Introduction

Matching is fundamental in combinatorial optimization and operations research with wide applications from students/colleges admission, kidney exchange to ad-auctions. Online bipartite matching, motivated by advertising markets, labor markets, etc., has been intensively studied. Informally, in the online bipartite matching, there are a set of agents (advertisers) given in advance and a set of items (impressions) that are released online one by one. When an item arrives, its edges to the agents are revealed and one needs to assign the item irrevocably to an agent (or assign to no one). For unweighted bipartite graphs, Karp et al. [19] gave an elegant algorithm RANKING which always outputs a matching of size at least $(1 - 1/e)$ times that of the optimum solution [19, 3]. They also proved that was the best achievable *competitive ratio*. The competitive ratio of an algorithm is defined as the worst ratio between the objective of the algorithm solution and that of the optimum solution. However, for edge-weighted bipartite graphs, no algorithm is competitive with the objective of maximizing the total (edge-) weight of the output matching (see for example, [10]).

In order to circumvent the issue due to edge weights and also to abstract more appropriately the practical motivations, in particular the advertising, adwords settings, new models have been proposed. In the *free-disposal* model [11], multiple items can be assigned to an agent but only the maximum weight is acknowledged for that agent. The objective in this model is to maximize the sum of the heaviest edge weighted assigned to each agent. In the *additive-budget* model (Ad-auctions) [23], each agent has additionally an budget and the revenue received from an agent is

defined to be the minimum between the total edge weight assigned to the agent and the budget of the agent. The objective is to maximize the total revenue received from all agents. In the *stochastic reward* model [22], each agent has a weight and each item has additionally a successful probability to be matching to an agent. The objective is to maximize the expected number of successfully matched agents, multiplied by their weights. In the *concave return* model [6], a generalization of the additive-budget model, the revenue of each an agent is a concave function on the total edge weight assigned to the agent. The objective is again to maximize the total revenue received from all agents.

The online matching problem has been extensively studied in those models. In the free-disposal model, Fahrbach et al. [10] have recently made a breakthrough by providing a 0.5086-competitive algorithm, breaking the long-standing competitive ratio barrier of $1/2$. It revives the hope of potential improvements toward the upper bound of $(1 - 1/e)$ on this problem. In the additive-budget model, $(1 - 1/e)$ -competitive algorithms have been given with additional assumptions: either the edge weights are small compared to the agents’s budgets [23, 4] or the weight of each edge is the same for every agent (agent-independent) [1]. In this model, the existence of an $(1 - 1/e)$ -competitive algorithm has been conjectured but still remains open. In the concave-return model, Devanur and Jain [6] gave an optimal online algorithm where the competitive ratio is characterized by a system of differential equations.

The primal-dual method has been widely used to study the online bipartite matching problem and its generalizations (including the aforementioned models). Devanur et al. [7] provided an elegant online primal-dual framework that unified previous results by showing how they arose from essentially the same dual update function. That unifying technique paves a way for many developments on online matching and its variants. However, there is an exception, another primal-dual scheme by Devanur and Jain [6] in the concave-return model, which is not encompassed by the framework in [7]. It is intriguing to understand the nature of those different schemes, that potentially leads to improved results for the online matching problems.

1.1 Our Contributions

In this paper, we present an unified primal-dual approach based on configuration linear programs and give *optimal* algorithms with competitive ratio of $(1 - 1/e)$ for online matching problem in the free-disposal and the stochastic reward models, resolving long-standing open questions. Moreover, we provide competitive algorithms for a general model that captures the concave return model as a special case. The variable update schemes are built on previous work, in particular [7, 8]. The key element is the use of the primal-dual method with configuration LPs that allows improvements and the unification. This can be seen as the last piece to complete the picture which have been widely drawn by previous works.

In the following, we define a generalization of the online bipartite matching problem, present our approach and the results.

1.1.1 Model and Approach

General problem. We are given a bipartite graph $G(L \cup R, E)$ where vertices L on the left-hand side are given in advance and vertices R on the right-hand side are released in an online manner. When an online vertex $j \in R$ arrives, its incident edges are revealed and an algorithm decides to assign vertex j to an offline neighbour in L or not to assign j to any neighbor. The reward function $c : 2^E \rightarrow \mathbb{R}_{\geq 0}$ is given so that if M is an assignment of online vertices to offline vertices, the reward received from this assignment is $c(M)$. Note that if M is a infeasible assignment (an online vertex

is assigned to strictly more than one neighbor) then one can define $c(M) = 0$. The objective is to maximize the reward of the output assignment.

This problem generalizes the models mentioned earlier. Given an assignment M , let M_i be the set of online vertices assigned to i in M . In the free-disposal model, an edge between $j \in R$ and $i \in L$ has weight $w_{ij} \geq 0$; several online vertices can be assigned to an offline vertex i but only the weight of the heaviest edge counts in the final matching. Hence, the reward function can be defined as $\sum_{i \in L} \max_{j \in M_i} w_{ij}$. In the additive-budget model, each offline vertex i additionally has a budget W_i and given an assignment M of online vertices to offline vertices, the reward can be expressed as $c(M) = \sum_{i \in L} \min\{W_i, \sum_{j \in M_i} w_{ij}\}$. In the online matching problem with stochastic rewards, each offline vertex i has a weight w_i and each online vertex j has a successful matching probability p_{ij} to offline vertex i . That probability, known in advance, means that if an algorithm decides to match j to i , this event succeeds with probability p_{ij} (and with probability $1 - p_{ij}$, i and j are not matched). The goal is to maximize the expected number of successfully matched offline vertices, multiplied by their weights. In this problem, given an assignment M of online vertices to offline vertices, the reward is $c(M) = \sum_{i \in L} w_i \cdot \min\{1, \sum_{j \in M_i} p_{ij}\}$.

Approach. The changing point of view in our approach, compared to the previous ones, is to deal directly with the non-linear objective functions. Consider the additive-budget model with the reward function $c(M) = \sum_{i \in L} \min\{W_i, \sum_{j \in M_i} w_{ij}\}$. In the previous approaches, the problem is typically formulated as

$$\max \sum_{i,j} w_{ij} x_{ij} \quad \text{s.t.} \quad \sum_i x_{ij} \leq 1 \quad \forall j, \quad \sum_j w_{ij} x_{ij} \leq W_i \quad \forall i, \quad x_{ij} \geq 0 \quad \forall i, j,$$

in which the reward function is “linearized” by using additional constraints (the second constraint). In our approach, we directly study the reward function $c(M) = \sum_{i \in L} \min\{W_i, \sum_{j \in M_i} w_{ij}\}$. The latter is not linear and it raises issues to current techniques. In order to circumvent this obstacle, we consider the primal-dual approach based on configuration LPs [25]. The configuration LPs have been used by Huang and Zhang [14] for the stochastic-reward matching problem but their approach is different to ours.

First, we formulate an LP for the general problem. Let x_{ij} be a variable indicating whether $j \in R$ is assigned to $i \in L$. Let z_M be a variable indicating whether an assignment $M \subseteq E$ is selected (output assignment). Consider the following formulation and the dual of its relaxation.

$$\begin{array}{ll} \max \sum_{M \subseteq E} c(M) z_M & \min \sum_{j \in R} \bar{\alpha}_j + \bar{\beta} \\ (\bar{\alpha}_j) \quad \sum_{i \in L} x_{ij} \leq 1 & \forall j \in R \quad \bar{\alpha}_j \geq \bar{\gamma}_{i,j} \quad \forall i \in L, j \in R \\ (\bar{\beta}) \quad \sum_{M \subseteq E} z_M = 1 & \bar{\beta} + \sum_{(i,j) \in M} \bar{\gamma}_{i,j} \geq c(M) \quad \forall M \subseteq E \\ (\bar{\gamma}_{i,j}) \quad \sum_{M: (i,j) \in M} z_M = x_{ij} & \forall i \in L, j \in R \quad \bar{\alpha}_j \geq 0 \quad \forall j \in R \\ & x_{ij}, z_M \in \{0, 1\} \quad \forall i \in L, S \subseteq R \end{array}$$

In the formulation, the first constraint ensures that an online vertex j can be assigned to at most one online vertex i . The second constraint guarantees that there must be an output assignment.

The third constraint imposes that if an edge (i, j) is chosen then among all assignments containing (i, j) , exactly one will be the output assignment.

In the approach, given variables x_{ij} such that $\sum_i x_{ij} \leq 1$ for all $j \in R$, we always maintain $z_M = \prod_{(i,j) \in M} x_{ij} \prod_{(i,j) \notin M} (1 - x_{ij})$ for all $M \subseteq E$. By that, the primal constraints $\sum_M z_M = 1$ and $\sum_i \sum_{M:(i,j) \in M} z_M \leq 1$ always hold true (see Section 2 for the detail). Let \mathbf{x} be the vector $(x_{ij})_{(i,j) \in E}$. The primal objective can be expressed as $C(\mathbf{x})$ where $C : [0, 1]^{|E|} \rightarrow \mathbb{R}_{\geq 0}$ is the *multilinear extension* of the reward function c , defined as

$$C(\mathbf{x}) = \sum_{M \subseteq E} c(M) \prod_{(i,j) \in M} x_{ij} \prod_{(i,j) \notin M} (1 - x_{ij}).$$

Note that $C(\mathbf{x})$ can be seen as $\mathbb{E}_M[c(M)]$ where an edge (i, j) is randomly included in M with probability x_{ij} . This view help us to derive updating scheme for dual variables and also make the rounding scheme obvious. Given assignment variables x_{ij} 's to i , it is sufficient to independently round the variables in order to get the objective value of $C(\mathbf{x})$.

In the primal-dual method, the dual variables often guide the primal assignment via complementary slackness conditions. In particular, one complementary slackness condition reads that $x_{ij} > 0$ implies $\bar{\alpha}_j = \bar{\gamma}_{i,j}$. This indicates the allocation of j to $\arg \max \bar{\gamma}_{i,j}$. That guides the strategy of allocating online arrival vertex to offline vertices which are $\arg \max$ of some terms (corresponding to $\bar{\gamma}_{i,j}$) in previous algorithms for online matching problems. We also adopt this strategy in our algorithms. However, for simplicity and for a better unification/comparison with previous works, we consider the following formulation, which is more compact but equivalent to the previous one (by combining the first and last primal constraints) and prove bounds using this formulation. (Even though the aforementioned strategy is less clear from the new dual.)

$$\begin{aligned} & \max \sum_{M \subseteq E} c(M) z_M & \min \sum_{j \in R} \alpha_j + \beta \\ (\alpha_j) \quad & \sum_{i \in L} \sum_{M:(i,j) \in M} z_M \leq 1 \quad \forall j \in R & \beta + \sum_i \sum_{j:(i,j) \in M} \alpha_j \geq c(M) \quad \forall M \subseteq E \\ (\beta) \quad & \sum_M z_M = 1 & \alpha_j \geq 0 \quad \forall j \in R \\ & z_M \in \{0, 1\} \quad \forall M \subseteq E \end{aligned}$$

1.1.2 Results

Building on our approach and the primal-dual schemes of previous works, we provide the following results.

- An optimal $(1 - 1/e)$ -competitive algorithm in the free-disposal model.
- We revisit the problem in the additive-budget model and give an $(e^{-R_{\max}} - 1/e)$ -competitive algorithm where $R_{\max} = \max_{i,j} w_{ij}/W_i$. This slightly improves the bound of $(1 - R_{\max})(1 - (1 + R_{\max})^{-1/R_{\max}})$ [4]. More importantly, the algorithm yields the optimal competitive ratio of $(1 - 1/e)$ for the online stochastic-reward matching problem with vanishing probability.

- A $(1 - \kappa)(1 - 1/e)$ -competitive algorithm for the general problem where the reward functions are sub-additive¹ and κ is the curvature of those functions (defined in Section 5).
- A competitive fractional algorithm for the general problem with a concavity assumption. We characterize the competitive ratio by system of differential equations. This result recovers the one provided by Devanur and Jain [6] in the concave-return model.

1.2 Related works

There is an extensive literature on online weighted bipartite matching problems. In terms of techniques, significant efforts have been investigated in order to unify different approaches. Specifically, Devanur et al. [7] provided an elegant online primal-dual framework showing how different approaches arise from essentially the same dual update function. That unifying technique paves a way for many current developments on online matching and its variants [8, 15, 10, 16, 14]. In the following, we summarize the most relevant works to ours and refer the readers to the survey of [21].

Online matching with free-disposal. Having been introduced by Feldman et al. [11] in the context of display advertising, the problem is widely applied due to its natural economic interpretation [20]. However, it had been a long-standing open question whether there exists an algorithm with competitive ratio strictly larger than the obvious bound of $1/2$. Recently, in their breakthrough, Fahrback et al. [10] provided a 0.5086-competitive algorithm, resolving this question. It revives the hope for improvements towards the upper bound of $1 - 1/e$. However, as mentioned in [10], their approach would not lead to a bound better than $5/9$ and in order to obtain a bound closer to $1 - 1/e$, fundamentally new ideas are required.

Online matching with additive-budget. Mehta et al. [23] introduced the problem (Adwords problem) and gave an optimal $(1 - 1/e)$ competitive ratio when $R_{\max} = \max_{i,j} w_{ij}/W_i$ is small. Buchbinder et al. [4] simplified the analysis by a primal-dual analysis. Aggarwal et al. [1] studied another particular case in which for each i , the weights w_{ij} 's are the same for every j . They obtained the optimal $(1 - 1/e)$ competitive ratio with the generalization of the RANKING algorithm [19]. In this problem (without any assumption), the existence of an $(1 - 1/e)$ -competitive algorithm has been conjectured but still remains open. Huang et al. [16] recently presented a 0.5016-competitive algorithm for this problem.

Online matching with stochastic reward. Mehta and Panigrahi [22] initiated the study this problem and gave a 0.567-competitive algorithm for the uniform weights and identical vanishing probabilities. Moreover, they showed that no algorithm, even in the setting of identical vanishing probabilities, has a competitive ratio better than $0.621 < (1 - 1/e)$ against a natural LP. Recently, Goyal and Udvani [13] gave an $(1 - 1/e)$ -competitive algorithm for the setting where the (vanishing) probabilities p_{ij} can be decomposed as $p_{ij} = p_i p_j$ for all i, j (so this includes the identical vanishing probability setting as a particular case). Independently, Huang and Zhang [14] provided algorithms with competitive ratios of 0.576 and 0.572 in the settings of vanishing equal probabilities and vanishing unequal probabilities, respectively.

Online matching with concave return. Devanur and Jain [6] considered a generalization of the Adwords problem in which fractional allocation is allowed and the rewards are arbitrary

¹A function $c : 2^E \rightarrow \mathbb{R}^+$ is sub-additive if $c(M_1 \cup M_2) \leq c(M_1) + c(M_2)$ for all $M_1, M_2 \subseteq E$

monotone concave function. They characterized the optimal achievable competitive ratio by system of differential equations and provided matching upper and lower bounds. The primal-dual scheme by Devanur and Jain [6] is not captured by the framework of [7]. It is intriguing to understand the nature of those algorithms and potentially unify them in a principle approach for online matching problems.

2 Preliminaries

We provide some useful facts and notations. We use bold letters, for example \mathbf{x}, \mathbf{v} , to denote vectors. Let \mathcal{M} be a set of all feasible sub-assignments of online vertices to offline vertices. Recall that for any sub-assignment $M \in \mathcal{M}$, each online vertex is assigned to at most one offline vertex. Given $M \in \mathcal{M}$, denote $M_i := \{j \in R : (i, j) \in M\}$ (so $M_i \cap M_{i'} = \emptyset$ for any feasible $M \in \mathcal{M}$). In the paper, we consider the following formulation and its dual.

$$\begin{array}{ll}
 \text{PRIMAL} & \text{DUAL} \\
 \max \sum_M c(M) z_M & \min \sum_{j \in R} \alpha_j + \beta \\
 (\alpha_j) \quad \sum_{i \in L} \sum_{M: (i,j) \in M} z_M \leq 1 & \forall j \in R \quad \beta + \sum_{i \in L} \sum_{j \in M_i} \alpha_j \geq c(M) \quad \forall M \in \mathcal{M} \\
 (\beta) \quad \sum_{M \in \mathcal{M}} z_M = 1 & \alpha_j \geq 0 \quad \forall j \in R \\
 z_M \in \{0, 1\} & \forall M \in \mathcal{M}
 \end{array}$$

In order to prove the competitive ratio of an algorithm, we will bound the objective value of the primal (due to the decisions of the algorithm) and that of the dual (by a dual feasible solution).

Given a reward function on the assignments $c : \mathcal{M} \rightarrow \mathbb{R}_{\geq 0}$, let $C : [0, 1]^{|E|} \rightarrow \mathbb{R}_{\geq 0}$ be the multilinear extension of c , defined as

$$C(\mathbf{x}) = \sum_{M \in \mathcal{M}} c(M) \prod_{(i,j) \in M} x_{ij} \prod_{(i,j) \notin M} (1 - x_{ij}).$$

where $\mathbf{x} = (x_{ij})_{(i,j) \in E}$. $C(\mathbf{x})$ can be seen as $\mathbb{E}_M[c(M)]$ where an edge (i, j) is randomly included in M with probability x_{ij} . The increasing rate of $C(\mathbf{x})$ while varying x_{ij} is

$$\begin{aligned}
 \frac{\partial C(\mathbf{x})}{x_{ij}} &= C(\mathbf{x}_{-(i,j)}, 1) - C(\mathbf{x}_{-(i,j)}, 0) \\
 &= \mathbb{E}_{M' \sim \mathbf{x}_{-(i,j)}} [c(M' \cup (i, j)) - c(M')]
 \end{aligned} \tag{1}$$

where $\mathbf{x}_{-(i,j)}$ denote the vector \mathbf{x} without coordinate (i, j) . Here, $M' \sim \mathbf{x}_{-(i,j)}$ is a random assignment in \mathcal{M} in which an edge $(i', j') \neq (i, j)$ is included with probability $x_{i', j'}$.

Given variables x_{ij} such that $\sum_i x_{ij} \leq 1$ for all $j \in R$, in our algorithms we always maintain $z_M = \prod_{(i,j) \in M} x_{ij} \prod_{(i,j) \notin M} (1 - x_{ij})$. The variable z_M can be interpreted as the probability that the assignment M is selected. By that, $\sum_{M \in \mathcal{M}} z_M = 1$. Moreover, for every $j \in R$,

$$\sum_{i \in L} \sum_{M: (i,j) \in M} z_M = \sum_i \left(x_{ij} \cdot \sum_{M': (i,j) \notin M'} z_{M'} \right) \leq \sum_i x_{ij} \leq 1.$$

Hence, given x_{ij} 's satisfying $\sum_i x_{ij} \leq 1$ for all $j \in R$, the variables z_M are feasible.

In the paper, we use functions $g(y) = \frac{e^y - 1}{1 - 1/e}$ and $G(y) = \frac{e^y - 1 - y/e}{1 - 1/e}$, the primitive integral of $g(y)$. Note that both g, G are increasing, $G(0) = 0$, $G(1) = 1$, and $1 - G(y) + g(y) = \frac{1}{1 - 1/e}$.

Moreover, in the paper, we denote random variables by capital letters (e.g., A) and realizations of random assignments by calligraphic letters (e.g., \mathcal{E}). Given a realization \mathcal{E} , we denote $A | \mathcal{E}$ as the variable A given \mathcal{E} .

3 Online Weighted Matching with Free-Disposal

In this section, we consider the online weighted matching problem in the free-disposal model in which the reward function $c(M) = \sum_i \max_{(i,j) \in M} b_{ij}$ for $M \in \mathcal{M}$. For each $i \in L$, define a function $c_i : R \rightarrow \mathbb{R}^+$ such that $c_i(S) = \max_{j \in S} b_{ij}$ for $S \subseteq R$. By this notation, $c(M) = \sum_{i \in L} c_i(M_i)$.

Algorithm. Let X_{ij} be a 0 – 1 random variable indicating whether $j \in R$ is assigned to vertex $i \in L$, and $x_{ij} = \mathbb{P}[X_{ij} = 1]$. Let $Y_i(w)$ be a 0 – 1 random variable indicating whether at least one online vertex j such that $w_{ij} \geq w$ is assigned to $i \in L$. In other words, $\mathbb{P}[Y_i(w)]$ is the probability that i receives a reward larger than w .

Informally, when an online vertex j arrives, given the realization \mathcal{E} of the random assignment, we select vertices $i \in L$ that maximize $w_{ij} - (B_{i'} | \mathcal{E})$ among all i' such that $w_{i'j}$ is larger than the heaviest weight $w_{i',\sigma(i')}$ currently assigned to i' in \mathcal{E} . (Note that the selection of i depends on the realization \mathcal{E} of the rounding.) We continuously increase x_{ij} by dx . By doing that, $\mathbb{P}[Y_i(w) = 1]$ is increased by dx for $w_{i,\sigma(i)} < w \leq w_{ij}$ (and remain unchanged for other w). In the algorithm, we also maintain two random variables A_j and B_i in the algorithm. We increase variables A_j and B_i by rules in Step 9. Intuitively, A_j, B_i represent the dual variables to be defined later. In the end of the while loop when the online vertex j is completely considered, j is assigned to i independently with probability x_{ij} .

Algorithm 1 Algorithm for Edge-Weighted Matching with Free Disposal.

- 1: All primal and dual variables are initially set to 0.
- 2: **for** each arrival of a new vertex j **do**
- 3: Let \mathcal{E} be the realization of the random assignment before arrival of j .
- 4: For each $i \in L$, let $\sigma(i)$ be the online vertex with heaviest weight currently assigned to i in \mathcal{E} .
- 5: **while** $\sum_i x_{ij} < 1$ **and** $w_{i,\sigma(i)} < w_{ij}$ for some $i \in L$ **do**
- 6: **for** every $i \in L$ in $\arg \max_{i'} \{w_{i',j} - (B_{i'} | \mathcal{E}) : w_{i',j} > w_{i',\sigma(i')}\}$ **do**
- 7: Increase the probability of assigning j to i by dx , i.e., $x_{ij} \leftarrow x_{ij} + dx$.
- 8: Maintain $Y_i(w) = X_{ij}$ for $w_{i,\sigma(i)} < w \leq w_{ij}$.
 (The previous step implies $\mathbb{P}[Y_i(w) = 1] \leftarrow \mathbb{P}[Y_i(w) = 1] + dx$ for $w_{i,\sigma(i)} < w \leq w_{ij}$.)
- 9: Increase B_i and A_j by the following rules respectively,

$$dB_i = \left(\int_{w_{i,\sigma(i)}}^{w_{ij}} g(Y_i(w)) dw | \mathcal{E} \right) dx \quad \text{and} \quad dA_j = (w_{ij} - B_i) dx.$$

- 10: **end for**
 - 11: **end while**
 - 12: For every i , assign j to i with probability x_{ij} .
 - 13: **end for**
-

Primal/dual variables. Given x_{ij} 's, we always maintain primal variables $z_M = \prod_{(i,j) \in M} x_{ij} \prod_{(i,j) \notin M} (1 - x_{ij})$ for every $M \in \mathcal{M}$. As argued in Section 2, these primal variables are feasible. Moreover, we define dual variables as $\alpha_j := \mathbb{E}[A_j]$ and $\beta := \sum_{i \in L} \beta_i$ where $\beta_i := \mathbb{E}[B_i]$.

Lemma 1 *For any realization \mathcal{E} of the assignment during the execution of the algorithm, the following inequality holds.*

$$\mathbb{E}[B_i | \mathcal{E}] \geq \mathbb{E} \left[\int_0^\infty G(Y_i(w)) dw \mid \mathcal{E} \right]$$

Proof We prove by induction on R . Initially, when $R = \emptyset$, both sides are 0 so the identity hold trivially. Assume that the inequality holds for any realization of the random assignment over online vertices released before j . Let \mathcal{E} be an arbitrary realization of the random assignment before j arrives. Conditional on \mathcal{E} , for every $i \in L$, we have

$$\mathbb{E}[dB_i | \mathcal{E}] = \mathbb{E} \left[\int_{w_{i,\sigma(i)}}^{w_{ij}} g(Y_i(w)) dw \mid \mathcal{E} \right] dx = \mathbb{E} \left[\int_0^\infty g(Y_i(w)) dY_i(w) dw \mid \mathcal{E} \right] = \mathbb{E} \left[\int_0^\infty dG(Y_i(w)) dw \mid \mathcal{E} \right].$$

The second equality holds since, conditional on \mathcal{E} , during the increase of x_{ij} $Y_i(w) = 1$ for $w \leq w_{i,\sigma(i)}$; so $dY_i(w) = 0$ for $w \leq w_{i,\sigma(i)}$ during this period. (Recall that if i is not selected in Step 6 then the increase of x_{ij} is 0.)

Integrating both sides of the above equality and note that $G(0) = 0$ and $B_i \geq 0$ at any time, we get

$$\mathbb{E}[B_i | \mathcal{E}] \geq \mathbb{E} \left[\int_0^\infty G(Y_i(w)) dw \mid \mathcal{E} \right]$$

□

Lemma 2 *The dual solution is feasible, i.e., $\beta + \sum_i \sum_{j:j \in M_i} \alpha_j \geq c(M) \forall M \in \mathcal{M}$.*

Proof Recall that for $M \in \mathcal{M}$, $M_i = \{j \in R : (i, j) \in M\}$ and $c_i(S) = \max_{j \in S} b_{ij}$ for $S \subseteq R$. By definition of the dual variables and the reward function, we need to prove that for every $M \in \mathcal{M}$

$$\sum_{i \in L} \beta_i + \sum_{i \in L} \sum_{j \in M_i} \alpha_j \geq \sum_{i \in L} \max_{(i,j) \in M} b_{ij} = \sum_{i \in L} c_i(M_i)$$

Indeed, we will prove a stronger inequality. That is, for any vertex $i \in L$ and subset $S \subseteq R$, it always holds that

$$\beta_i + \sum_{k \in S} \alpha_k \geq c_i(S)$$

This inequality subsequently implies the feasibility of the dual variables.

Fix a vertex $i \in L$ and a subset $S \subseteq R$. We prove the above inequality by induction on R . Initially, when $R = \emptyset$, the inequality holds since both sides are 0. Assume that the inequality holds before the arrival of vertex j .

Case 1: $j \notin S$ or $j \notin \arg \max_{k \in S} w_{ik}$. Then $c_i(S) = c_i(S \setminus \{j\})$. As the inequality holds before the arrival of j , i.e., $\beta_i + \sum_{k \in S \setminus \{j\}} \alpha_k \geq c_i(S \setminus \{j\})$, and β_i is non-decreasing and $\alpha_j \geq 0$, the inequality after the arrival of j also holds, $\beta_i + \sum_{k \in S} \alpha_k \geq c_i(S) = c_i(S \setminus \{j\})$.

Case 2: $j \in S$ and $w_{ij} \geq w_{ik} \forall j \neq k \in S$ and $\beta_i \geq w_{ij}$. The constraint immediately follows again by the non-negativity of α_k and $c_i(S) = w_{ij}$.

Case 3: $j \in S$ and $w_{ij} \geq w_{ik} \forall j \neq k \in S$ and $w_{ij} > \beta_i$. We will prove a stronger statement: $\beta_i + \alpha_j \geq w_{ij}$. This will imply $\beta_i + \sum_{k \in S} \alpha_k \geq \beta_i + \alpha_j \geq w_{ij} = c_i(S)$.

Let \mathcal{F} be the event that $w_{i,\sigma(i)} < w_{ij}$. In this event, the while loop must have ended with $\sum_i x_{ij} = 1$. Throughout the loop (by the condition of the for loop), dA_j/dx is always at least $(w_{ij} - B_i)$. Therefore,

$$(A_j | \mathcal{F}) = \int_0^1 \frac{d(A_j | \mathcal{F})}{dx} dt \geq \int_0^1 (w_{ij} - (B_i | \mathcal{F})) dt = w_{ij} - (B_i | \mathcal{F}).$$

Hence, $(A_j + B_i | \mathcal{F}) \geq w_{ij}$.

In case of negated event to \mathcal{F} , by Lemma 1, we have

$$\begin{aligned} \mathbb{E} \left[B_i | \neg \mathcal{F} \right] &\geq \mathbb{E} \left[\int_0^\infty G(Y_i(w)) dw | \neg \mathcal{F} \right] \geq \mathbb{E} \left[\int_0^{w_{i,\sigma(i)}} G(Y_i(w)) dw \right] \\ &= \int_0^{w_{i,\sigma(i)}} G(1) dw = w_{i,\sigma(i)} \geq w_{ij} \end{aligned}$$

Combining both cases, we deduce $\beta_i + \alpha_j = \mathbb{E}[A_j + B_i] \geq w_{ij}$. \square

Theorem 1 *The randomized Algorithm 1 is $(1 - 1/e)$ -competitive.*

Proof We prove that for every online vertex j , the increase of the primal is at least $(1 - 1/e)$ that of the dual. Fix an arbitrary realization \mathcal{E} before the arrival of vertex j . When x_{ij} increases, by Equation (1), the increasing rate of the primal is

$$\mathbb{E}_{M' \sim \mathbf{x}_{-(i,j)}} [c(M' \cup (i, j)) - c(M') | \mathcal{E}] = w_{ij} - w_{i,\sigma(i)}$$

where $w_{i,\sigma(i)}$ is the heaviest weight assigned to i in \mathcal{E} .

Besides, given a realization \mathcal{E} , $\int_0^{w_{i,\sigma(i)}} G(Y_i(w)) dw = \int_0^{w_{i,\sigma(i)}} G(1) dw = \int_0^{w_{i,\sigma(i)}} 1 dw$. Therefore, conditional on the realization \mathcal{E} ,

$$\begin{aligned} \mathbb{E} \left[\frac{dA_j}{dx} | \mathcal{E} \right] &= w_{ij} - \mathbb{E} \left[B_i | \mathcal{E} \right] \leq w_{ij} - \mathbb{E} \left[\int_0^\infty G(Y_i(w)) dw | \mathcal{E} \right] \\ &= \int_0^{w_{ij}} 1 dw - \mathbb{E} \left[\int_0^{w_{i,\sigma(i)}} G(1) dw \right] - \mathbb{E} \left[\int_{w_{i,\sigma(i)}}^\infty G(Y_i(w)) dw | \mathcal{E} \right] \\ &= \mathbb{E} \left[\int_{w_{i,\sigma(i)}}^{w_{ij}} (1 - G(Y_i(w))) dw - \int_{w_{ij}}^\infty G(Y_i(w)) dw | \mathcal{E} \right] \\ &\leq \mathbb{E} \left[\int_{w_{i,\sigma(i)}}^{w_{ij}} (1 - G(Y_i(w))) dw | \mathcal{E} \right] \end{aligned}$$

where the first inequality is due to Lemma 1.

We deduce that, conditional on the realization \mathcal{E} ,

$$\begin{aligned} \mathbb{E} \left[\frac{dA_j}{dx} + \frac{dB_i}{dx} | \mathcal{E} \right] &\leq \mathbb{E} \left[\int_{w_{i,\sigma(i)}}^{w_{ij}} (1 - G(Y_i(w)) + g(Y_i(w))) dw | \mathcal{E} \right] \\ &= \int_{w_{i,\sigma(i)}}^{w_{ij}} \frac{dw}{1 - 1/e} = \frac{w_{ij} - w_{i,\sigma(i)}}{1 - 1/e} \end{aligned}$$

Note that whenever x_{ij} increases, only β_i increases whereas $\beta_{i'}$'s for $i' \neq i$ remain unchanged. Hence, the increase of the primal is at least $(1 - 1/e)$ that of the dual for any realization \mathcal{E} . As it holds for any realization, it holds in expectation and the theorem follows. \square

Remark 1 Algorithm 1 has the structure similar to the algorithm for the fractional version of the online matching with free-disposal [8, Algorithm 2]. However, there is a small but crucial difference. In [8, Algorithm 2], the update rate of β -variable is $\int_{w_{i,j'}}^{w_{i,j}} g(y_i(w))dw$ where $w_{i,j'}$ is the *smallest* edge-weight among the weights already assigned to i with positive probability. This update is based on the complementary cumulative distribution function viewpoint. Our update in Step 9 (on the random variable counterparts) is guided by the configuration LP approach. Specifically, we update B_i at the rate of $\int_{w_{i,\sigma(i)}}^{w_{ij}} g(Y_i(w))dw$ where $w_{i,\sigma(i)}$ is the *heaviest* edge-weight among the weights already assigned to i (in the current realization).

Remark 2 As a sanity check, we consider Algorithm 1 in the online unweighted matching problem, especially applying to the graph corresponding to the upper triangular matrix — it is the worst example for the KVV algorithm of Karp et al. [19]. In this setting, the graph has vertex sets ($L = R = \{1, \dots, n\}$). One samples a uniformly random permutation π of the set $[n]$ and define the edge set of the graph to be $E = \{(\pi(i), j) : i \geq j\}$. Note that π is unknown to the algorithm. The online vertices in R arrive in the order $j = 1, 2, \dots, n$. The optimal solution is the perfect matching consisting of the edges $(\pi(j), j)$ for $1 \leq j \leq n$. On this input, at the arrival of an online vertex j , Algorithm 1 increases x_{ij} uniformly for all unmatched offline neighbors of j . This results in these offline nodes' dual variables increasing uniformly, resulting in the next allocation of the next iteration again being uniform among the unmatched neighbors, and so on. The integral (random) allocation then matches each online node j to each of its free neighbors uniformly random. Implementing Algorithm 1 and comparing to KVV algorithm on this example, we observe in [9] that they both have the theoretically predicted competitive ratio $(1 - 1/e \approx 0.632)$.

4 Online Weighted Matching with Additive Budgets

In this section, we consider first the online weighted matching problem in the additive-budget model in which for $M \in \mathcal{M}$, the reward function $c(M) = \sum_{i \in L} c_i(M_i)$ where $c_i(S) = \min\{\sum_{j \in S} w_{ij}, W_i\}$ for $S \subseteq R$, for all i . Subsequently, we deduce the performance guarantee for the problem in the stochastic-reward model as a corollary.

Algorithm. Recall X_{ij} is the 0-1 random variable indicating whether j is assigned to i . In the algorithm, we maintain a random variable Y_i intuitively (but not exactly) representing the fraction of the consumed budget of i . Moreover, as the previous algorithm, we also maintain additional random variables A_j and B_i that help the algorithm's decisions and the definitions of dual variables.

Informally, when an online vertex j arrives, given the current assignment \mathcal{E} , we continuously increase x_{ij} by dx if i maximizes the term $\min\{w_{i',j}, \max\{0, W_{i'} - \sum_{j':(i',j') \in \mathcal{E}} w_{i',j'}\}\} \cdot (1 - \frac{B_{i'} | \mathcal{E}}{W_{i'}})$ among all i' . Here, the coefficient of $\min\{w_{i',j}, \max\{0, W_{i'} - \sum_{j':(i',j') \in \mathcal{E}} w_{i',j'}\}\}$, as we will argue later, is the rate of the primal when x_{ij} varies. (The choice of this coefficient shows the usefulness of the configuration LP approach.) Intuitively, given an assignment \mathcal{E} before j is released, $\min\{w_{i,j}, \max\{0, W_i - \sum_{j':(i,j') \in \mathcal{E}} w_{i,j'}\}\}$ is the increase of the total reward if j is (integrally) assigned to i . Subsequently, we increase variables A_j and B_i by rules in Step 7.

Primal/dual variables. As in the previous section, given x_{ij} 's, we define primal variables $z_{i,S} = \prod_{j \in S} x_{ij} \prod_{j \notin S} (1 - x_{ij})$ for every $i \in L$, $S \subseteq R$ and dual variables $\alpha_j = \mathbb{E}[A_j]$, $\beta_i = \mathbb{E}[B_i]$ and $\beta = \sum_{i \in L} \beta_i$.

Algorithm 2 Algorithm for Edge-Weighted Matching with Additive Budgets.

- 1: Initially, all primal/dual variables and the corresponding probabilities of random variables X_{ij}, Y_i, A_j, B_i are set to 0.
 - 2: **for** each arrival of a new vertex j **do**
 - 3: Let \mathcal{E} be the realization of the random assignment before arrival of j .
 - 4: **while** $\sum_i x_{ij} < 1$ and $(Y_i | \mathcal{E}) < 1$ for some $i \in L$ **do**
 - 5: **for** every $i \in L$ in $\arg \max_{i'} \{ \min\{w_{i',j}, \max\{0, W_{i'} - \sum_{j':(i',j') \in \mathcal{E}} w_{i',j'}\}\} \cdot (1 - \frac{B_{i'} | \mathcal{E}}{W_{i'}}) \}$ **do**
 - 6: Increase the probability of assigning j to i by dx , i.e., $x_{ij} \leftarrow x_{ij} + dx$.
 - 7: Update Y_i, B_i and A_j by the following rules respectively,
$$Y_i = (Y_i | \mathcal{E}) + \min\{w_{ij}, W_i - \sum_{j':(i,j') \in \mathcal{E}} w_{ij'}\} \cdot \frac{1}{W_i} \cdot X_{ij},$$

$$dB_i = \min\{w_{ij}, \max\{0, W_i - \sum_{j':(i,j') \in \mathcal{E}} w_{ij'}\}\} \cdot g(Y_i) dx,$$

$$dA_j = \min\{w_{ij}, \max\{0, W_i - \sum_{j':(i,j') \in \mathcal{E}} w_{ij'}\}\} \cdot \left(1 - \frac{B_i}{W_i}\right) dx.$$
 - 8: **end for**
 - 9: **end while**
 - 10: For every i , assign j to i with probability x_{ij} .
 - 11: **end for**
-

Lemma 3 For any realization \mathcal{E} of the random assignment and for every $i \in L$, the following invariant always holds

$$\mathbb{E}[B_i | \mathcal{E}] = \mathbb{E}[W_i \cdot G(Y_i) | \mathcal{E}].$$

Proof Fix an arbitrary vertex $i \in L$. Again, we prove by induction on R . For the base case where $R = \emptyset$, both side are 0 so the invariant holds trivially. Assume that the invariant holds for any realization of the assignment before the arrival of vertex j . Let \mathcal{E} be a realization of the random assignment before the arrival of j . During the consideration of j , it holds that

$$\mathbb{E}[dB_i | \mathcal{E}] = \mathbb{E}[\min\{w_{ij}, \max\{0, W_i - \sum_{j':(i,j') \in \mathcal{E}} w_{ij'}\}\} \cdot g(Y_i) dx | \mathcal{E}] = \mathbb{E}[W_i g(Y_i) dY_i | \mathcal{E}]$$

where the last equality is due to the definition of Y_i . Integrating both sides, the lemma follows. \square

Recall that $R_{\max} = \max_{i,j} w_{i,j}/W_i$. The following lemma shows that the dual constraints are feasible up to a factor of $G(1 - R_{\max})$.

Lemma 4 For every vertex $i \in L$ and subset $S \subseteq R$, it holds that

$$\beta_i + \sum_{j \in S} \alpha_j \geq G(1 - R_{\max}) \cdot c_i(S).$$

Consequently, it implies that for any $M \in \mathcal{M}$, $\beta + \sum_{i \in L} \sum_{j \in M_i} \alpha_j \geq G(1 - R_{\max}) \cdot c(M)$.

Proof Fix a vertex $i \in L$ and a subset $S \subseteq R$. We prove that, given an arbitrary realization \mathcal{E} of the random assignment,

$$\mathbb{E}[B_i + \sum_{j \in S} A_j \mid \mathcal{E}] \geq G(1 - R_{\max}) \cdot c_i(S) \quad (2)$$

If $(Y_i \mid \mathcal{E}) = 1$ then $(B_i \mid \mathcal{E}) = W_i$, so the lemma inequality holds. In the following, assume that $(Y_i \mid \mathcal{E}) < 1$ after the arrival of the last vertex in S . By the while loop condition, $\sum_i x_{ij} = 1$ for every $j \in S$. For every vertex $j \in S$, let \mathcal{E}_j be the assignment before the arrival of j . (Note that $\mathcal{E}_j \subseteq \mathcal{E}$.) By the condition of the for loop, dA_j/dx must be at least $\min\{w_{ij}, \max\{0, W_i - \sum_{j':(i,j') \in \mathcal{E}_j} w_{ij'}\}\} \cdot (1 - \frac{(B_i \mid \mathcal{E}_j)}{W_i})$. Therefore, given \mathcal{E} (in particular \mathcal{E}_j),

$$\begin{aligned} A_j &= \int_0^1 \frac{dA_j}{dx} dt \geq \int_0^1 \min\{w_{ij}, \max\{0, W_i - \sum_{j':(i,j') \in \mathcal{E}_j} w_{ij'}\}\} \cdot (1 - \frac{(B_i \mid \mathcal{E}_j)}{W_i}) dt \\ &= \min\{w_{ij}, \max\{0, W_i - \sum_{j':(i,j') \in \mathcal{E}_j} w_{ij'}\}\} \cdot (1 - \frac{(B_i \mid \mathcal{E}_j)}{W_i}) \\ &\geq \min\{w_{ij}, \max\{0, W_i - \sum_{j':(i,j') \in \mathcal{E}_j} w_{ij'}\}\} \cdot (1 - \frac{(B_i \mid \mathcal{E})}{W_i}). \end{aligned}$$

where the last inequality holds since the value of B_i is non-decreasing as long as online vertices arrive.

Assume that there exists $k \in S$ such that $\min\{w_{ik}, \max\{0, W_i - \sum_{j':(i,j') \in \mathcal{E}_k} w_{ij'}\}\} = W_i - \sum_{j':(i,j') \in \mathcal{E}_k} w_{ij'}$, meaning that $(Y_i \mid \mathcal{E}_k) \geq 1 - \frac{w_{ik}}{W_i}$. In this case,

$$\begin{aligned} \mathbb{E}[B_i + \sum_{j \in S} A_j \mid \mathcal{E}] &\geq \mathbb{E}[B_i \mid \mathcal{E}_k] \geq \mathbb{E}[W_i G(Y_i) \mid \mathcal{E}_k] \\ &\geq W_i G\left(1 - \frac{w_{ik}}{W_i}\right) \geq W_i G(1 - R_{\max}). \end{aligned}$$

In the remaining, assume that for every $j \in S$, $\min\{w_{ij}, \max\{0, W_i - \sum_{j':(i,j') \in \mathcal{E}_j} w_{ij'}\}\} = w_{ij}$. Given \mathcal{E} , we have

$$\begin{aligned} \mathbb{E}\left[B_i + \sum_{j \in S} A_j \mid \mathcal{E}\right] &\geq \mathbb{E}\left[B_i + \sum_{j \in S} w_{ij} \left(1 - \frac{B_i}{W_i}\right) \mid \mathcal{E}\right] \\ &= \mathbb{E}\left[B_i + \left(1 - \frac{B_i}{W_i}\right) \sum_{j \in S} w_{ij} \mid \mathcal{E}\right] \\ &\geq \mathbb{E}\left[B_i + \left(1 - \frac{B_i}{W_i}\right) \cdot \min\left\{W_i, \sum_{j \in S} w_{ij}\right\} \mid \mathcal{E}\right] \\ &= \min\left\{W_i, \sum_{j \in S} w_{ij}\right\} + \left(1 - \frac{\min\{W_i, \sum_{j \in S} w_{ij}\}}{W_i}\right) \mathbb{E}[B_i \mid \mathcal{E}] \\ &\geq \min\left\{W_i, \sum_{j \in S} w_{ij}\right\} = c_i(S). \end{aligned}$$

where the second inequality is due to $1 - \frac{W_i}{B_i} \geq 0$. As Inequality (2) holds for any realization \mathcal{E} , we deduce that

$$\beta_i + \sum_{j \in S} \alpha_j \geq G(1 - R_{\max}) \cdot c_i(S).$$

Consequently, for any $M \in \mathcal{M}$, applying the above inequality for $S = M_i$ and summing over all $i \in L$, we have $\beta + \sum_{i \in L} \sum_{j \in M_i} \alpha_j \geq G(1 - R_{\max}) \cdot c(M)$. \square

Theorem 2 *The randomized Algorithm 2 has the competitive ratio of $G(1 - R_{\max}) \cdot (1 - 1/e) = e^{-R_{\max}} - e^{-1}$.*

Proof We prove that for every online vertex, the increase of the primal is at least $(1 - 1/e)$ that of the dual. Fix an arbitrary realization \mathcal{E} before the arrival of vertex j . When dx amount of j is allocated to i , by Equation (1), the increasing rate of the primal is

$$\mathbb{E}_{M' \sim \mathbf{x}_{-(i,j)}}[c(M' \cup (i, j)) - c(M') \mid \mathcal{E}] = \min\{w_{ij}, \max\{0, W_i - \sum_{j':(i,j') \in \mathcal{E}} w_{ij'}\}\}.$$

Conditional on the realization \mathcal{E} , the expected increasing rate of the dual is

$$\begin{aligned} \mathbb{E}\left[\frac{dA_j}{dx} + \frac{dB_i}{dx} \mid \mathcal{E}\right] &= \min\{w_{ij}, \max\{0, W_i - \sum_{j':(i,j') \in \mathcal{E}} w_{ij'}\}\} \cdot \mathbb{E}\left[1 - \frac{B_i}{W_i} + g(Y_i) \mid \mathcal{E}\right] \\ &= \min\{w_{ij}, \max\{0, W_i - \sum_{j':(i,j') \in \mathcal{E}} w_{ij'}\}\} \cdot \mathbb{E}[1 - G(Y_i) + g(Y_i) \mid \mathcal{E}] \\ &= \min\{w_{ij}, \max\{0, W_i - \sum_{j':(i,j') \in \mathcal{E}} w_{ij'}\}\} \cdot \frac{1}{1 - 1/e}. \end{aligned}$$

So, given a realization \mathcal{E} , the ratio between the increasing rates of the primal and the dual is $1 - 1/e$. This holds for any realization. Therefore, by Lemma 6 and the weak duality, the competitive ratio of Algorithm 2 is $G(1 - R_{\max}) \cdot (1 - 1/e) = e^{-R_{\max}} - e^{-1}$. \square

Corollary 1 *Algorithm 2 is $(1 - 1/e)$ -competitive for the online stochastic-reward matching problem with vanishing probability.*

Proof In the online matching problem with stochastic rewards, the reward function $c(M)$ can be expressed as $\sum_{i \in L} c_i(M_i)$ where $c_i(S) = w_i \cdot \min\{1, \sum_{j \in S} p_{ij}\} = \min\{w_i, \sum_{j \in S} p_{ij} w_i\}$ for $S \subseteq R$. Applying Theorem 2 and using the vanishing probability property ($R_{\max} = \max p_{ij} \rightarrow 0$), we deduce the competitive ratio of $(1 - 1/e)$. \square

5 Online Weighted Matching with Sub-Additive Rewards

In this section, we consider the online weighted matching problem in a general model in which the reward function is sub-additive, i.e., $c(M_1 \cup M_2) \leq c(M_1) + c(M_2)$. Without loss of generality, assume that $c(M) \leq 1$ for all M (this can be done by scaling).

Given a sub-additive function $f : 2^E \rightarrow [0, 1]$, define the *total curvature* κ_f of f as

$$\kappa_f = 1 - \min_{\emptyset \neq M \subseteq E} \min_{e \in M} \frac{f(M) - f(M \setminus \{e\})}{f(\{e\})}. \quad (3)$$

This definition generalizes the notion of curvature for submodular functions introduced by Conforti and Cornuéjols [5]. A function $f : 2^E \rightarrow \mathbb{R}_{\geq 0}$ is submodular if $f(M_1 \cup \{e\}) - f(M_1) \geq f(M_2 \cup \{e\}) - f(M_2)$ for all $M_1 \subseteq M_2 \subseteq E$. In the context of submodular functions, the curvature [5] is defined as $1 - \min_{e \in E} \frac{f(E) - f(E \setminus \{e\})}{f(\{e\})}$. The latter is exactly the same as (3) since for submodular functions, $\min_{M \subseteq E} \{f(M) - f(M \setminus \{e\})\} = f(E) - f(E \setminus \{e\})$. Intuitively, the total curvature measures how far away f is from being *modular*. The concept of curvature is widely used in the context of submodular optimization; for example in determining both upper and lower bounds on the approximation ratios for many submodular and learning problems [5, 12, 2, 26, 17, 24].

Denote $\kappa = \kappa_c$. We will bound the competitive ratio in this section as a function of κ . Note that if the reward function can be decomposed as $c(M) = \sum_{i \in L} c_i(M_i)$ for every $M \in \mathcal{M}$ where $c_i : 2^R \rightarrow \mathbb{R}^+$ then $\kappa = \kappa_c = \max_i \kappa_{c_i}$.

Algorithm. Recall that $C : [0, 1]^{|E|} \rightarrow [0, 1]$ be the multilinear extension of $c : 2^E \rightarrow [0, 1]$. The algorithm for the online matching with sub-additive reward is a generalization of the previous algorithms. The main difference is that in this algorithm, we deal directly with fractional variables instead of random variables and realizations of random assignments. The reason is that in the previous sections, our goal is to achieve the tight competitive ratio of $(1 - 1/e)$ whereas in this general setting, we aim for a weaker guarantee, given the hardness result² of [18].

Algorithm 3 Algorithm for Edge-Weighted Matching with Sub-Additive Rewards.

- 1: All primal and dual variables are initially set to 0.
- 2: **for** each arrival of a new vertex j **do**
- 3: **while** $\sum_{i \in L} x_{ij} < 1$ **and** $\beta < 1$ **do**
- 4: **for** every $i \in L$ in $\arg \max_{i'} \left\{ \frac{\partial C(\mathbf{x})}{\partial x_{i',j}} \right\}$ **do**
- 5: Increase x_{ij} by dx .
- 6: Increase β and α_j by the following rules respectively,

$$d\beta = \frac{\partial C(\mathbf{x})}{\partial x_{ij}} g(C(\mathbf{x})) dx \quad \text{and} \quad d\alpha_j = \frac{\partial C(\mathbf{x})}{\partial x_{ij}} (1 - \beta) dx.$$

- 7: **end for**
 - 8: **end while**
 - 9: For every i , assign j to i with probability x_{ij} .
 - 10: **end for**
-

Note that in the algorithm, $\frac{\partial C(\mathbf{x})}{\partial x_{ij}} = \mathbb{E}_{M' \sim \mathbf{x}_{-(i,j)}} [c(M' \cup (i, j)) - c(M')]$ can be computed (up to any precision) based on already arrival vertices (since $x_{(i',j')} = 0$ for every j' unreleased so far).

Primal/dual variables. Again, we define primal variables $z_M = \prod_{(i,j) \in M} x_{ij} \prod_{(i,j) \notin M} (1 - x_{ij})$ and dual variables α_j, β are constructed in the algorithm.

Lemma 5 *During the execution of the algorithm, the following invariant holds*

$$\beta = G(C(\mathbf{x}))$$

²No randomized algorithm is $1/2$ -competitive unless $\text{NP} = \text{RP}$, even for submodular rewards (a sub-class of sub-additive rewards).

Proof Fix a vertex $i \in L$. By the algorithm, whenever a variable x_{ij} for some $j \in R$ is increased by an amount dx , $\frac{d\beta}{dx} = \frac{\partial C(\mathbf{x})}{\partial x_{ij}} g(C(\mathbf{x})) = \frac{\partial G(C(\mathbf{x}))}{\partial x_{ij}}$. Together with the property $G(0) = G(C(\mathbf{0})) = 0$, the invariant follows. \square

Lemma 6 *For every $M \in \mathcal{M}$, it holds that*

$$\beta + \sum_{i \in L} \sum_{j \in M_i} \alpha_j \geq (1 - \kappa)c(M)$$

In other words, the dual variables are feasible up to a factor $(1 - \kappa)$.

Proof Fix $M \in \mathcal{M}$. If $\beta \geq 1$ then the lemma inequality holds (recall that $c(M) \leq 1$). In the following, assume that $\beta < 1$. By the conditions of the loops, for every vertex $j \in M_i$, $\frac{d\alpha_j}{dx}$ must be at least $\frac{\partial C(\mathbf{x})}{\partial x_{ij}} (1 - \beta)$ since β is non-decreasing. Besides, by the definition of multilinear extension, C is linear function w.r.t x_{ij} . In other words, $\frac{\partial C(\mathbf{x})}{\partial x_{ij}}$ is constant when x_{ij} varies. Therefore,

$$\alpha_j = \int_0^1 \frac{d\alpha_j}{dx} dt \geq \int_0^1 \frac{\partial C(\mathbf{x})}{\partial x_{ij}} (1 - \beta) dt = \frac{\partial C(\mathbf{x})}{\partial x_{ij}} (1 - \beta).$$

We have

$$\begin{aligned} \beta + \sum_{i \in L} \sum_{j \in M_i} \alpha_j &\geq \beta + \sum_{i \in L} \sum_{j \in M_i} \frac{\partial C(\mathbf{x})}{\partial x_{ij}} (1 - \beta) \\ &\geq \beta + (1 - \beta) \cdot \min \left\{ 1, \sum_{(i,j) \in M} \frac{\partial C(\mathbf{x})}{\partial x_{ij}} \right\} \\ &= \min \left\{ 1, \sum_{(i,j) \in M} \frac{\partial C(\mathbf{x})}{\partial x_{ij}} \right\} + \left(1 - \min \left\{ 1, \sum_{(i,j) \in M} \frac{\partial C(\mathbf{x})}{\partial x_{ij}} \right\} \right) \beta \\ &\geq \min \left\{ 1, \sum_{(i,j) \in M} \frac{\partial C(\mathbf{x})}{\partial x_{ij}} \right\} \\ &= \min \left\{ 1, \sum_{(i,j) \in M} \mathbb{E}_{M' \sim \mathbf{x}_{-(i,j)}} [c(M' \cup (i,j)) - c(M')] \right\} \\ &\geq \min \left\{ 1, \sum_{(i,j) \in M} \mathbb{E}_{M' \sim \mathbf{x}_{-(i,j)}} [(1 - \kappa)c(i,j)] \right\} \\ &= \min \left\{ 1, (1 - \kappa) \sum_{(i,j) \in M} c(i,j) \right\} \\ &\geq (1 - \kappa)c(M). \end{aligned}$$

The second inequality holds since $1 - \beta \geq 0$. The second equality is due to property (1) of multilinear extensions. The third inequality follows the definition of curvature. The last inequality is due to the sub-additivity of c and $c(M) \leq 1$. The lemma inequality follows. \square

Theorem 3 *Algorithm 3 is $(1 - \kappa)(1 - 1/e)$ -competitive.*

Proof We bound the increasing rates of the primal and the dual. Assume that dx amount of j is allocated to i . The increase in the primal is $\frac{\partial C(\mathbf{x})}{\partial x_{ij}} dx$. The increase of the dual is

$$\begin{aligned} d\alpha_j + d\beta_i &= \frac{\partial C(\mathbf{x})}{\partial x_{ij}} (1 - \beta) dx + \frac{\partial C(\mathbf{x})}{\partial x_{ij}} g(C(\mathbf{x})) dx \\ &= \left(1 - G(C(\mathbf{x})) + g(C(\mathbf{x})) \right) \frac{\partial C(\mathbf{x})}{\partial x_{ij}} dx = \frac{1}{1 - 1/e} \cdot \frac{\partial C(\mathbf{x})}{\partial x_{ij}} dx. \end{aligned}$$

By Lemma 6 and the weak duality, the competitive ratio follows. \square

6 Online Fractional Weighted Matching with Concave Rewards

The main goal of this section is to build the connection with the primal-dual scheme in [6] by showing that the latter can be described and analyzed similarly as algorithms in previous sections. Consider the online weighted matching problem in the general model in which the multilinear extension $C : [0, 1]^{|E|} \rightarrow [0, 1]$ (of the reward function c) is *concave*.

Given a function $\mathbf{v} : [0, 1]^{|E|} \rightarrow [0, 1]^{|E|}$, for $\mathbf{x} \in [0, 1]^{|E|}$, we can write $\mathbf{v}(\mathbf{x}) = (v_{i,j}(\mathbf{x}))_{(i,j) \in E}$. Define $r > 0$ as the largest constant such that the following system of differential equations has a solution $\mathbf{v} : [0, 1]^{|E|} \rightarrow [0, 1]^{|E|}$

$$\frac{1}{r} \cdot \frac{\partial C(\mathbf{x})}{\partial x_{ij}} = \frac{\partial C(\mathbf{v}(\mathbf{x}))}{\partial v_{ij}(\mathbf{x})} - \left\langle \mathbf{v}(\mathbf{x}), \frac{\partial}{\partial x_{ij}} \nabla_{\mathbf{v}} C(\mathbf{v}(\mathbf{x})) \right\rangle \quad \forall i \in L, j \in R, \quad (4)$$

$$\frac{\partial \mathbf{v}(\mathbf{x})}{\partial x_{ij}} \geq 0 \quad \forall i \in L, j \in R, \quad (5)$$

$$\frac{\partial^2 C(\mathbf{v}(\mathbf{x}))}{\partial x_{ij} \partial v_{ij}(\mathbf{x})} \leq 0 \quad \forall i \in L, j \in R, \quad (6)$$

with boundary conditions $\mathbf{v}(\mathbf{0}) = \mathbf{0}$. Note that the last inequality guarantees that $\frac{\partial C(\mathbf{v}(\mathbf{x}))}{\partial v_{ij}(\mathbf{x})}$ is non-increasing when x_{ij} increases.

Let \mathbf{v} be a solution of the system with r . Denote $\nabla_{\mathbf{v}} C(\mathbf{v}(\mathbf{x})) = \left(\frac{\partial C(\mathbf{v}(\mathbf{x}))}{\partial v_{ij}(\mathbf{x})} \right)_{(i,j) \in E}$. Consider the following algorithm, building from the salient ideas of the previous ones.

Lemma 7 *For every $M \in \mathcal{M}$, it holds that*

$$\beta + \sum_{i \in L} \sum_{j \in M_i} \alpha_j \geq c(M)$$

Proof Fix $M \in \mathcal{M}$. For any vertex $i \in L$ and $j \in M_i$, at every time during the execution of the algorithm, the increasing rate of α_j is at least the current value of $\frac{\partial C(\mathbf{v}(\mathbf{x}))}{\partial v_{ij}(\mathbf{x})}$. Moreover, the latter is non-increasing (by (6)). Therefore,

$$\alpha_j = \int_0^1 \frac{\partial C(\mathbf{v}(\mathbf{x}))}{\partial v_{ij}(\mathbf{x})} dt \geq \frac{\partial C(\mathbf{v}(\mathbf{x}))}{\partial v_{ij}(\mathbf{x})}.$$

We have

$$\begin{aligned} \beta + \sum_{i \in L} \sum_{j \in M_i} \alpha_j &\geq C(\mathbf{v}(\mathbf{x})) - \langle \mathbf{v}(\mathbf{x}), \nabla_{\mathbf{v}} C(\mathbf{v}(\mathbf{x})) \rangle + \sum_{(i,j) \in M} \frac{\partial C(\mathbf{v}(\mathbf{x}))}{\partial v_{ij}(\mathbf{x})} \\ &= C(\mathbf{v}(\mathbf{x})) + \langle \nabla_{\mathbf{v}} C(\mathbf{v}(\mathbf{x})), \mathbf{1}_M - \mathbf{v}(\mathbf{x}) \rangle \\ &\geq C(\mathbf{v}(\mathbf{x})) + C(\mathbf{1}_M) - C(\mathbf{v}(\mathbf{x})) \\ &= C(\mathbf{1}_M) = c(M) \end{aligned}$$

Algorithm 4 Algorithm for Edge-Weighted Matching with Concave Rewards.

- 1: All primal and dual variables are initially set to 0.
- 2: **for** each arrival of a new vertex j **do**
- 3: **while** $\sum_{i \in L} x_{ij} < 1$ **do**
- 4: **for** every $i \in L$ in $\arg \max_{i'} \left\{ \frac{\partial C(\mathbf{v}(\mathbf{x}))}{\partial v_{i',j}(\mathbf{x})} \right\}$ **do**
- 5: Allocate a $dx = dx_{ij}$ amount of j to i .
- 6: Increase α_j by the following rule:

$$\frac{d\alpha_j}{dx_{ij}} = \frac{\partial C(\mathbf{v}(\mathbf{x}))}{\partial v_{ij}(\mathbf{x})}.$$

- 7: **end for**
 - 8: Always maintain $\beta = C(\mathbf{v}(\mathbf{x})) - \langle \mathbf{v}(\mathbf{x}), \nabla_{\mathbf{v}} C(\mathbf{v}(\mathbf{x})) \rangle$.
 - 9: **end while**
 - 10: **end for**
-

where $\mathbf{1}_M$ is the indicator vector of M , i.e., $(\mathbf{1}_M)_e = 1$ if $e \in M$ and $(\mathbf{1}_M)_e = 0$ otherwise. The last inequality is due to the concavity of C . \square

Theorem 4 *Algorithm 4 is r -competitive for the fractional online matching problem under the assumption that C is concave.*

Proof Initially, when no online vertex is released, the objective values of the primal and the dual are 0. At any time in the execution of the algorithm when an online vertex j is released, the increasing rate of the dual is

$$\begin{aligned} \frac{d\alpha_j}{dx_{ij}} + \frac{d\beta}{dx_{ij}} &= \frac{\partial C(\mathbf{v}(\mathbf{x}))}{\partial v_{ij}(\mathbf{x})} - \frac{\partial}{\partial x_{ij}} \left(C(\mathbf{v}(\mathbf{x})) - \langle \mathbf{v}(\mathbf{x}), \nabla_{\mathbf{v}} C(\mathbf{v}(\mathbf{x})) \rangle \right) \\ &= \frac{\partial C(\mathbf{v}(\mathbf{x}))}{\partial v_{ij}(\mathbf{x})} - \left\langle \mathbf{v}(\mathbf{x}), \frac{\partial}{\partial x_{ij}} \nabla_{\mathbf{v}} C(\mathbf{v}(\mathbf{x})) \right\rangle. \end{aligned}$$

Besides, the increasing rate of the primal is $\frac{\partial C(\mathbf{x})}{\partial x_{ij}}$. The competitive ratio follows the definition of r . \square

Connection to the scheme of Devanur and Jain [6]. Consider the setting in [6] in which each edge between $i \in L$ and $j \in R$ has weight $w_{ij} \geq 0$ and the reward function of each offline vertex $i \in L$ can be expressed as $P(\sum_j w_{ij} x_{ij})$ where $P : \mathbb{R}^+ \rightarrow \mathbb{R}^+$ is a 1-dim concave function and x_{ij} is the fraction of online vertex j assigned to i . The total reward is $\sum_{i \in L} P(\sum_j w_{ij} x_{ij})$. In this setting, using $\sum_{i \in L} P$ instead of C in (4, 5, 6) and Algorithm 4, after a simplification (due to the separability of the reward on each offline vertex in the total reward), the system of differential equations characterizing the competitive ratio reads

$$\begin{aligned} \frac{1}{r} \cdot P'(u) &= P'(v(u)) - [v(u)P''(v(u))] \frac{dv(u)}{du} \\ \frac{dv(u)}{du} &\geq 0 \end{aligned}$$

with boundary condition $v(0) = 0$. The system becomes simpler as P is one-variable function. Note that in this system, we name (1-dim) variable u (instead of x) and the condition (6), written as

$$d\left(\frac{\partial P(v(u))}{\partial v(u)}\right)/du = P''(v(u))\frac{dv(u)}{du} \leq 0,$$

always holds (by the concavity of P and the condition $\frac{dv(u)}{du} \geq 0$). This system is exactly the one given in [6]. For completeness, we give it below.

$$\begin{aligned} \frac{1}{r} \cdot P'(u) &= P'(v(u)) + Y'(v(u))\frac{dv(u)}{du} \\ \frac{dv(u)}{du} &\geq 0 \end{aligned}$$

with boundary condition $Y(0) = 0$ where the function $Y(v) = P(v) - vP'(v)$.

7 Conclusion

In this paper, we have presented a primal-dual framework with configuration LPs for the online bipartite matching problem that unifies previous approaches and provides optimal $(1 - 1/e)$ competitive ratio in some models, resolving long-standing open questions. We believe that the use of primal-dual with configuration LPs (for example, to circumvent hard constraints, etc) will find other applications and lead to improvements in different problems. Related to our paper, an open question is to study whether the bounds given in Sections 5 and 6 are tight.

References

- [1] Gagan Aggarwal, Gagan Goel, Chinmay Karande, and Aranyak Mehta. Online vertex-weighted bipartite matching and single-bid budgeted allocations. In *Proc. 22nd Symposium on Discrete Algorithms*, pages 1253–1264, 2011.
- [2] Maria-Florina Balcan and Nicholas J. A. Harvey. Learning submodular functions. In *Proc. Machine Learning and Knowledge Discovery in Databases*, pages 846–849, 2012.
- [3] Benjamin Birnbaum and Claire Mathieu. On-line bipartite matching made simple. *Acm Sigact News*, 39(1):80–87, 2008.
- [4] Niv Buchbinder, Kamal Jain, and Joseph Seffi Naor. Online primal-dual algorithms for maximizing ad-auctions revenue. In *European Symposium on Algorithms*, pages 253–264, 2007.
- [5] Michele Conforti and Gérard Cornuéjols. Submodular set functions, matroids and the greedy algorithm: tight worst-case bounds and some generalizations of the rado-edmonds theorem. *Discrete applied mathematics*, 7(3):251–274, 1984.
- [6] Nikhil R Devanur and Kamal Jain. Online matching with concave returns. In *Proc. 44th ACM symposium on Theory of computing*, pages 137–144, 2012.
- [7] Nikhil R Devanur, Kamal Jain, and Robert D Kleinberg. Randomized primal-dual analysis of ranking for online bipartite matching. In *Proc. 24th Symposium on Discrete algorithms*, pages 101–107, 2013.

- [8] Nikhil R Devanur, Zhiyi Huang, Nitish Korula, Vahab S Mirrokni, and Qiqi Yan. Whole-page optimization and submodular welfare maximization with online bidders. *ACM Transactions on Economics and Computation (TEAC)*, 4(3):1–20, 2016.
- [9] Christoph Dürr and Nguyen Kim Thang. Implementation on upper triangular graph, September 2021. URL <https://www.ibisc.univ-evry.fr/~thang/matching.html>.
- [10] Matthew Fahrbach, Zhiyi Huang, Runzhou Tao, and Morteza Zadimoghaddam. Edge-weighted online bipartite matching. In *Proc. 61st Symposium on Foundations of Computer Science*, 2020.
- [11] Jon Feldman, Nitish Korula, Vahab Mirrokni, Shanmugavelayutham Muthukrishnan, and Martin Pál. Online ad assignment with free disposal. In *Workshop on internet and network economics (WINE)*, pages 374–385, 2009.
- [12] Michel X Goemans, Nicholas JA Harvey, Satoru Iwata, and Vahab Mirrokni. Approximating submodular functions everywhere. In *Proc. 20th Symposium on Discrete algorithms*, pages 535–544, 2009.
- [13] Vineet Goyal and Rajan Udwani. Online matching with stochastic rewards: Optimal competitive ratio via path based formulation. In *Proc. 21st ACM Conference on Economics and Computation*, pages 791–791, 2020.
- [14] Zhiyi Huang and Qiankun Zhang. Online primal dual meets online matching with stochastic rewards: configuration lp to the rescue. In *Proc. 52nd ACM Symposium on Theory of Computing*, pages 1153–1164, 2020.
- [15] Zhiyi Huang, Ning Kang, Zhihao Gavin Tang, Xiaowei Wu, Yuhao Zhang, and Xue Zhu. Fully online matching. *Journal of the ACM (JACM)*, 67(3):1–25, 2020.
- [16] Zhiyi Huang, Qiankun Zhang, and Yuhao Zhang. Adwords in a panorama. In *Proc. 61st Symposium on Foundations of Computer Science*, 2020.
- [17] Rishabh K Iyer, Stefanie Jegelka, and Jeff A Bilmes. Curvature and optimal algorithms for learning and minimizing submodular functions. In *Advances in Neural Information Processing Systems*, pages 2742–2750, 2013.
- [18] Michael Kapralov, Ian Post, and Jan Vondrák. Online submodular welfare maximization: Greedy is optimal. In *Proc. 24th ACM-SIAM Symposium on Discrete algorithms*, pages 1216–1225, 2013.
- [19] Richard M Karp, Umesh V Vazirani, and Vijay V Vazirani. An optimal algorithm for on-line bipartite matching. In *Proc. 22nd ACM symposium on Theory of computing*, pages 352–358, 1990.
- [20] Nitish Korula, Vahab S Mirrokni, and Morteza Zadimoghaddam. Bicriteria online matching: Maximizing weight and cardinality. In *International conference on web and internet economics*, pages 305–318, 2013.
- [21] Aranyak Mehta. Online matching and ad allocation. *Foundations and Trends® in Theoretical Computer Science*, 8(4):265–368, 2013.
- [22] Aranyak Mehta and Debmalaya Panigrahi. Online matching with stochastic rewards. In *53rd Symposium on Foundations of Computer Science*, pages 728–737, 2012.

- [23] Aranyak Mehta, Amin Saberi, Umesh Vazirani, and Vijay Vazirani. Adwords and generalized online matching. *Journal of the ACM*, 54(5):22–es, 2007.
- [24] Maxim Sviridenko, Jan Vondrák, and Justin Ward. Optimal approximation for submodular and supermodular optimization with bounded curvature. *Mathematics of Operations Research*, 2017.
- [25] Nguyen Kim Thang. Online primal-dual algorithms with configuration linear programs. In *Proc. 31st International Symposium on Algorithms and Computation*, 2020.
- [26] Jan Vondrák. Submodularity and curvature: The optimal algorithm. *RIMS Kokyuroku Bessatsu*, 2010.