

On the Complexity of Dynamic Submodular Maximization

Xi Chen
Columbia University
xichen@cs.columbia.edu

Binghui Peng
Columbia University
bp2601@columbia.edu

April 19, 2022

Abstract

We study dynamic algorithms for the problem of maximizing a monotone submodular function over a stream of n insertions and deletions. We show that any algorithm that maintains a $(0.5 + \epsilon)$ -approximate solution under a cardinality constraint, for any constant $\epsilon > 0$, must have an amortized query complexity that is *polynomial* in n . Moreover, a linear amortized query complexity is needed in order to maintain a 0.584-approximate solution. This is in sharp contrast with recent dynamic algorithms of [LMNF⁺20, Mon20] that achieve $(0.5 - \epsilon)$ -approximation with a $\text{polylog}(n)$ amortized query complexity.

On the positive side, when the stream is insertion-only, we present efficient algorithms for the problem under a cardinality constraint and under a matroid constraint with approximation guarantee $1 - 1/e - \epsilon$ and amortized query complexities $O(\log(k/\epsilon)/\epsilon^2)$ and $k^{\tilde{O}(1/\epsilon^2)} \log n$, respectively, where k denotes the cardinality parameter or the rank of the matroid.

1 Introduction

Initiated by the classical work of [NWF78, NW78] in the 1970s, submodular maximization has developed into a central topic of discrete optimization during past decades [CCPV11, FNS11, Von13, CVZ14, BFSS15] (see [BF18] for a survey). Capturing the natural notion of diminishing returns, submodular functions and their optimization problems have found numerous applications in areas such as machine learning [GK11, WIB15], data mining [LB11], algorithmic game theory [Rou10], social networks [KKT03], etc. The canonical form of the problem is to maximize a monotone submodular function under a cardinality constraint k , for which the greedy algorithm of [NWF78] achieves the optimal approximation ratio of $1 - 1/e$ [NW78, Fei98]. However, despite the simplicity and optimality of this celebrated algorithm, there has been a surge of recent research effort to reexamine the problem under a variety of computational models motivated by unique challenges of working with massive datasets. These include streaming algorithms [BMKK14, FNFSZ20], parallel algorithms [BS18a, BRS19a, EN19, FMZ19, BRS19b, CQ19, ENV19], learning algorithms [BH11, BRS17] and distributed algorithms [BENW15, MZ15, BENW16].

Dynamic submodular maximization. We study the power and limitations of *dynamic* algorithms for submodular maximization. In this model, the set of elements that one can choose from is subject to changes incurred by a stream of n insertions and deletions. Letting V_t denote the current set of elements after the first t operations, an algorithm needs to maintain a subset $S_t \subseteq V_t$ of size at most k that achieves a certain approximation guarantee for every round t , and its performance is measured by its amortized query complexity (i.e., the average number of queries it makes per operation on the underlying unknown monotone submodular function); see the formal definition of the model in Section 2.

The dynamic model is motivated by real-world applications of submodular maximization over massive datasets that evolve frequently. Many of these applications arise in machine learning and data mining tasks, including the data subset selection problem [WIB15, GK11], movie recommendation system [BS18b], influence maximization in social networks [KKT03], etc. As an example, in influence maximization, one is given a social network as well as a stochastic diffusion model, and the goal is to select a seed set of size at most k to maximize the influence spread over the network. The spread function is submodular for many well-studied models and therefore, the problem becomes submodular maximization with a cardinality constraint. Given that social networks, like Twitter or Facebook, are involving continuously over time, an old seed set could become outdated quickly. A natural rescue is to have an efficient dynamic algorithm that maintains a seed set over time.

The problem of dynamic submodular maximization under a cardinality constraint was studied in two recent papers [Mon20, LMNF⁺20], giving algorithms that achieve an $(1/2 - \epsilon)$ -approximation guarantee with amortized query complexities that are $O(k^2 \log^2 n \cdot \epsilon^{-3})$ and $O(\log^8 n \cdot \epsilon^{-6})$ in a stream of length n . Compared with the $1 - 1/e$ approximation guarantee of the offline greedy algorithm, however, a natural open question posted by [LMNF⁺20] is whether the $1/2$ can be further improved under the dynamic setting, or even under the setting when the stream is insertion-only.

1.1 Our results

We resolve the open question of [LMNF⁺20] by showing that any algorithm with an approximation ratio of $1/2 + \epsilon$ must have amortized query complexity polynomial in the stream length n :

Theorem 1.1. *For any constant $\epsilon > 0$, there is a constant $C_\epsilon > 0$ with the following property. When $k \geq C_\epsilon$, any randomized algorithm that achieves an approximation ratio of $1/2 + \epsilon$ for dynamic submodular maximization under cardinality constraint k requires amortized query complexity $n^{\tilde{\Omega}(\epsilon)}/k^3$.*

Moreover, we show that any algorithm with approximation ratio 0.584 must have an amortized query complexity that is linear in n :

Theorem 1.2. *There is a constant $C > 0$ with the following property. When $k \geq C \log n$, any randomized algorithm for dynamic submodular maximization under cardinality constraint k that obtains an approximation guarantee of 0.584 must have amortized query complexity at least $\Omega(n/k^3)$.*

In the proof of both theorems we construct a family of hard functions to hide a secret matching. The main challenge is to achieve the following two properties at the same time: The first one, which we will refer to as the *large-gap* property, states that any dynamic algorithm with a certain approximation guarantee can only succeed by recovering the secret matching hidden in the function. On the other hand, the second so-called *indistinguishability* property shows that each query made by an algorithm can only reveal very little information about the secret matching. The construction for Theorem 1.2 uses a simple bipartite structure but requires a more detailed analysis to optimize for the constant 0.584. The construction for Theorem 1.1, on the other hand, is based on a more sophisticated $(1/\epsilon)$ -level tree structure which, at a high level, can be viewed as a novel tree extension of the path-alike construction from [FNFSZ20]. We discuss in more details about our lower bound proofs in Section 1.3.

On the positive side, when the stream is insertion only, we obtain an algorithm that achieves an approximation guarantee of $1 - 1/e - \epsilon$ with amortized query complexity $O(\log(k/\epsilon)/\epsilon^2)$:

Theorem 1.3. *Given any $\epsilon > 0$, there is a deterministic algorithm that achieves an approximation guarantee of $1 - 1/e - \epsilon$ for dynamic submodular maximization under cardinality constraint k over insertion-only streams. The amortized query complexity of the algorithm is $O(\log(k/\epsilon)/\epsilon^2)$.*

We also obtain a randomized algorithm that achieves an approximation guarantee of $1 - 1/e - \epsilon$ for the problem under a matroid constraint, with amortized query complexity $k^{\tilde{O}(1/\epsilon^2)} \log n$.

Theorem 1.4. *Given any $\epsilon > 0$, there is a randomized algorithm that achieves an approximation guarantee of $1 - 1/e - \epsilon$ for dynamic submodular maximization under matroid constraints over insertion-only streams. The amortized query complexity of the algorithm is $k^{\tilde{O}(1/\epsilon^2)} \log n$, where k is the rank of the matroid.*

Our algorithms are inspired by the classic greedy solution and we turn it into a dynamic algorithm via techniques involving lazy update, multilinear extension and accelerated continuous greedy, together with the introduction of a $O(1/\epsilon)$ -pass prune-greedy algorithm that could be of independent interest. We elaborate about the intuition behind our algorithms in Section 1.3.

Remark 1.5. *The best offline algorithm for maximizing monotone submodular function with cardinality constraints requires $O(n \log(1/\epsilon))$ queries [BFS17]. Our dynamic algorithm incurs only poly-logarithmic overheads. While for matroid constraints, even the state-of-art offline algorithm requires $O(n\sqrt{k})$ value queries [BFS17]. Hence, for matroid constraints, our focus is to design dynamic algorithms with $\text{poly}(k)$ amortized query complexity.*

We review related work and then give a technical overview of our results in Section 1.3.

1.2 Related work

Dynamic submodular maximization has only been studied recently, and the work of [Mon20, LMNF⁺20] are most relevant to us. The concurrent work of [Mon20] and [LMNF⁺20] give $(1/2 - \epsilon)$ -approximation algorithm to the dynamic submodular maximization problem under cardinality constraints, with amortized query complexity $O(k^2 \log^2 n \cdot \epsilon^{-3})$ and $O(\log^8 n \cdot \epsilon^{-6})$ respectively.

Our work is also closely related to the streaming setting. For cardinality constraints, [BMKK14] give an $(1/2 - \epsilon)$ -approximation algorithm in the streaming model. The approximation is tight, Feldman et al. [FNFSZ20] prove $\Omega(\epsilon n/k^3)$ space is necessary for achieving $(1/2 + \epsilon)$ approximation. For matroid constraints, [CGQ15] give an $1/4$ -approximation algorithm and the approximation ratio is improved to 0.3178 by [FNFSZ21]. We remark the algorithm of [BMKK14] and [CGQ15] can be implemented in the insertion-only dynamic setting with the same approximation guarantee, and the amortized running query complexity are $O(\epsilon^{-1} \log(k/\epsilon))$ and $O(k)$ respectively.

On lower bound side, our work make use of the symmetric gap techniques of [MSV08, Von13] and the weight scheduling of [FNFSZ20].

1.3 Technical overview

We provide a streamlined technique overview of our approach.

A linear lower bound for 0.584-approximation. Our lower bound is based on the construction of a family of monotone submodular functions with the following properties. They share the same ground set V which is partitioned into $2m$ sets $V = A_1 \cup \dots \cup A_m \cup B_1 \cup \dots \cup B_m$ and the algorithm knows both V and the partition. Each A_i or B_j contains $O(k)$ elements to be specified later. What is hidden inside the function is a secret bijection $\pi : [m] \rightarrow [m]$, which is unknown to the algorithm, and we write the function as $\mathcal{F}_\pi : 2^V \rightarrow [0, 1]$. The three main properties we need about \mathcal{F} are:

- i) For any $j \in [m]$, there is an $S \subseteq A_{\pi(j)} \cup B_j$ of size k that achieves the optimal $\mathcal{F}_\pi(S) = 1$;
- ii) **Large gap:** For any $j \in [m]$, every $S \subseteq A_1 \cup \dots \cup A_m \cup B_j$ of size at most k has $\mathcal{F}_\pi(S) \leq \kappa$ for some (as small as possible) parameter $\kappa > 0$, unless $S \cap A_{\pi(j)} \neq \emptyset$; and
- iii) **Indistinguishability:** Every query made by the algorithm reveals very little information about π . (Looking ahead, we show that each query on \mathcal{F}_π is roughly equivalent to no more than $O(k)$ queries on π , each of the limited form as “whether $\pi(a)$ is equal b or not.”)

With these properties in hand, we use the following simple dynamic stream of length $\Theta(mk)$ in our lower bound proof: A_1, \dots, A_m are inserted first and then we insert B_1 , delete B_1 , insert B_2 , delete B_2, \dots , until B_m is inserted and deleted. The large-gap property (ii) ensures that any algorithm with an approximation guarantee of κ must recover each entry $\pi(j)$ of the hidden π after each set B_j is inserted.¹ The indistinguishability property (iii), on the other hand, shows that $\Omega(m^2/k)$ queries are needed to recover the hidden bijection π (by a standard calculation) and thus, the amortized query complexity is at least $\Omega(m/k^2) = \Omega(n/k^3)$ by plugging in the stream length $n = \Theta(mk)$. The main challenge is to find a construction that satisfies (i) and (iii) and at the same time satisfies (ii) with a parameter κ that is as small as possible (optimized to be 0.584 at the end).

We focus on minimizing κ in the large-gap property (ii) in this part, given that achieving the indistinguishability (iii) will become more challenging in the polynomial lower bound for $(0.5 + \epsilon)$ -approximation later and will be what we focus on there. Our first attempt is the following simple coverage function \mathcal{F} (though our final construction will not be a coverage function). Let U be a large universe set (for intuition consider U to be arbitrarily large so that every expectation about random sets we draw holds exactly). For each $j \in [m]$ we randomly partition U into two parts $U_{j,1}$ and $U_{j,2}$ of the same size: the union of elements of $A_{\pi(j)}$ (which correspond to subsets of U) will be $U_{j,1}$ and the union of elements of B_j will be $U_{j,2}$. Each B_j is further partitioned into w groups $B_{j,1}, \dots, B_{j,w}$, where w is a large enough constant, such that each $B_{j,\ell}$ has size $k/2$ and corresponds

¹Note that we are a bit sloppy here given that the dynamic algorithm only needs to output a set S_j after B_j is inserted to overlap with $A_{\pi(j)}$. But given that $|S_j| \leq k$, this can be considered almost as good as knowing $\pi(j)$.

to an even $(k/2)$ -way random partition of $U_{i,2}$. The same happens with $A_{\pi(j)}$. Now imagine that the algorithm does not know $\pi(j)$ and returns $S \subset A_i \cup B_j$ with $i \neq \pi(j)$ by picking $k/2$ elements randomly from A_i and $k/2$ elements randomly from B_j . Simple calculation shows that elements in S would together cover $0.5(1 - 1/e) + 0.25(1 - 1/e^2) \approx 0.53$, which is very close to our goal of 0.5, and splitting elements not evenly between A_i and B_j can only cover less.

However, the algorithm can deviate by (1) not picking elements randomly from A_i and B_j and furthermore, (2) picking from not just $A_i \cup B_j$ but also the much bigger set of $A_1 \cup \dots \cup A_m$. For (1), if the algorithm manages to find out all $k/2$ elements of group $A_{i,\ell}$ and all $k/2$ elements of group $B_{j,\ell'}$ for some ℓ, ℓ' , then together they would cover $3/4$. For (2), the algorithm can pick one random element each from k different A_i 's to cover $1 - 1/e$. In our final construction, we overcame (1) by applying a symmetric function constructed from [MSV08] on top of the coverage function above. It guarantees that no algorithm (with a small number of queries) can ever pick a set of elements from any of A_i or B_j that is non-negligibly “unbalanced,” by having noticeably more elements from any group $A_{i,\ell}$ or $B_{j,\ell}$ than the average among A_i or B_j . Accordingly, the large-gap property (ii) needed can be updated to be the following weaker version:

- ii) **Large gap, updated:** For any $j \in [m]$, every “balanced” $S \subseteq A_1 \cup \dots \cup A_m \cup B_j$ of size at most k has $\mathcal{F}_\pi(S) \leq \kappa$ for some parameter $\kappa > 0$, unless $S \cap A_{\pi(j)} \neq \emptyset$;

To address the challenge of (2), we use two parameters to introduce a different type of *unbalancedness*: First, U is no longer partitioned 50-50; instead $U_{j,1}$ is β -fraction and $U_{j,2}$ is $(1 - \beta)$ -fraction of U . Second, it is no longer the case that all groups $A_{i,\ell}$ and $B_{j,\ell}$ have size $k/2$; instead every $A_{i,\ell}$ has size αk and every $B_{j,\ell}$ has size $(1 - \alpha)k$. With a detailed analysis we show that κ can be set to 0.584 in the updated version of the large-gap property (ii), when $\alpha = 0.56$ and $\beta = 0.42$.

A polynomial lower bound for $(1/2 + \epsilon)$ -approximation. Hard instances for our linear lower bound sketched earlier reduce at the end to a simple problem of recovering a hidden matching. To obtain a polynomial lower bound for $(1/2 + \epsilon)$ -approximation, we need to further extend the idea to amplify the (hardness of) approximation ratio by creating a depth- L tree structure with $L = 1/\epsilon$ to hide multiple bijections at every level. Let m_1, \dots, m_L be a sequence of positive integers: $m_L = 1$ but the other integers will be specified at the end. The ground set V is then defined using a depth- L tree T , in which each internal node at depth ℓ ($\ell \in [0 : L - 1]$) has $m_{\ell+1}$ children. Let U_ℓ denote the set of nodes $u = (u_1, \dots, u_\ell) \in [m_1] \times \dots \times [m_\ell]$ at depth ℓ ; its children are given by $(u, 1), \dots, (u, m_{\ell+1})$. The ground set is defined as $V = \cup_{u \in U_1 \cup \dots \cup U_L} A_u$, where each A_u contains ϵk elements.

In the dynamic update stream, we perform a limited DFS walk on the tree, meaning that after reaching a node u , one only explores the first $d := n^\epsilon$ children $(u, 1), \dots, (u, d)$ of u (except when u is at depth $L - 1$ in which case we just explore the only child of u). Let $U_L^* := [d]^{L-1} \times \{1\}$ be the set of leaves visited by the DFS walk. We design the stream in a way such that whenever a leaf u is reached, the current set of elements is given by

$$W_u := \bigcup_{\ell \in [L]} \bigcup_{i \in [m_\ell]} A_{u_1, \dots, u_{\ell-1}, i},$$

i.e., the union of sets of nodes that are children of any node along the path from the root to u . Let $\mathcal{A}_u = A_{u_1} \cup \dots \cup A_{u_1, \dots, u_{L-1}}$. The first two properties of our $\mathcal{F} : 2^V \rightarrow [0, 1]$ can now be stated:

- i) Let $S = \mathcal{A}_u \cup A_u$. We have $|S| = k$ and $\mathcal{F}(S)$ achieves the optimal $\mathcal{F}(S) = 1$;
- ii) **Large gap:** For any $S \subseteq W_u$ of size at most k , $\mathcal{F}(S) < 1/2 + \epsilon$ unless $S \cap \mathcal{A}_u \neq \emptyset$.

At a high level, the construction of our monotone submodular function \mathcal{F} can be viewed as a novel tree extension of a path-alike construction from [FNFSZ20] (for one-way communication complexity of submodular maximization). In particular, we adopted a weight sequence $\{w_\ell\}$ from [FNFSZ20] to play the role of parameter β in our linear lower bound discussed earlier, in order to achieve the large-gap property (ii) above no matter how the S is spread among different levels of the tree.

Now \mathcal{F} is only the base function that we use to construct the family of hard functions. To this end, we introduce the notion of a *shuffling* π of tree T , which consists of one bijection π_u at every internal node u of T to shuffle its children. Let \mathcal{F}_π be the function obtained after applying a hidden shuffling π on \mathcal{F} . Under the same stream, at the time when a leaf $u \in U_L^*$ arrives, the current set of elements remains to be W_u but the \mathcal{A}_u we care about becomes

$$\mathcal{A}_u^\pi := A_{\pi_\gamma(u_1)} \cup A_{u_1, \pi_{u_1}(u_2)} \cup \dots \cup A_{u_1, \dots, u_{L-2}, \pi_{u_1, \dots, u_{L-2}}(u_{L-1})},$$

where π_γ denotes the hidden bijection at the root, π_{u_1} denotes the hidden bijection at the depth-1 node u_1 , so on and so forth. The two properties (i) and (ii) hold after replacing \mathcal{A}_u with \mathcal{A}_u^π . So finding $S \subseteq W_u$ of size at most k with $\mathcal{F}(S) \geq 1/2 + \epsilon$ requires the algorithm to (essentially) identify one of the edges along the path after shuffling, i.e., one of the entries $\pi_\epsilon(u_1), \pi_{u_1}(u_2), \dots, \pi_{u_1, \dots, u_{L-2}}(u_{L-1})$ in the hidden bijections. The challenge left is to establish the indistinguishability property:

- iii) **Indistinguishability:** Every query made by the algorithm reveals very little information about π . (More formally, we show that each query on \mathcal{F}_π is roughly equivalent to no more than $O(k^2)$ queries on π , each of the limited form as “whether $\pi_u(a)$ for some u is equal b .”)

With (iii) if an algorithm tries to win by finding out $\pi_{u_1, \dots, u_{L-2}}(u_{L-1})$ every time a leaf u is reached then each hidden entry requires $\Omega(m_{L-1}/k^2)$ queries and thus, $\Omega(m_{L-1}d^{L-1}/k^2)$ queries in total. In general if an algorithm keeps working on $\pi_{u_1, \dots, u_\ell}(u_{\ell+1})$, the total number of queries needed is $\Omega(m_{\ell+1}d^{\ell+1}/k^2)$. Setting $m_\ell = n^{(L-\ell+1)\epsilon}/(2k)$ for each ℓ leads to a lower bound of $\Omega(n^{1+\epsilon}/k^3)$ for the total query complexity in all cases, while maintaining the stream length to be n . (It is also not difficult to show that mixing effort among different levels does not help.)

Finally let’s discuss how the indistinguishability property (iii) is implemented. The first trick is to cap the function and have the final function take the form as

$$\mathcal{F}_\pi^*(S) = \min \{ \mathcal{F}_\pi(S) + \epsilon|S|/k, 1 \}.$$

This simple modification changes the value of solutions S we care about slightly, no more than ϵ , given that $|S| \leq k$, and at the same time guarantees no algorithm makes any query of size more than k/ϵ ; otherwise the value returned is trivially 1 and reveals no information. This implies that each query S made by an algorithm can only involve no more than k/ϵ nodes in the tree; let U_S denote the set of such nodes. A final key observation is that the function \mathcal{F}_π on S is uniquely determined by the structure of the tree formed by paths of nodes in U_S to the root after applying the shuffling π . The latter is uniquely determined by the depth of the lowest common ancestor of every pair of nodes in U_S after shuffling π , which in turn can be obtained by making at most one query to π of the form described in (iii) for each pair in U_S . The bound $O(k^2)$ follows given that $|U_S| \leq k/\epsilon$.

Insertion-only streams: Submodular maximization with a cardinality constraint. Our starting point is the classic (offline) greedy approach, where in each round an element with the maximum marginal contribution is added to the solution set. We adapt the greedy algorithm to the dynamic setting. For simplicity, let’s assume in the overview that a value OPT is given to the algorithm at the beginning and its goal is to maintain a set that achieves a $(1 - 1/e - \epsilon)$ -approximation when the actual optimal value reaches OPT . While it is impossible to find the element with the

maximum margin before having all of them in hands, we can instead choose one whose margin gives a moderate improvement, i.e., add any element that satisfies $f_S(e) \geq (\text{OPT} - f(S))/k$, where S is the current solution set. This suffices to achieve the optimal $(1 - 1/e)$ -approximation. A naive implementation, however, requires $O(k)$ amortized query complexity since the threshold $(\text{OPT} - f(S))/k$ is updated every time a new element is added to solution set, and the algorithm needs to scan over all elements in the worst case. We circumvent this with the idea of *lazy update*. We divide the marginal contribution into $O(1/\epsilon)$ buckets, with the i -th buckets containing marginal smaller than $i \cdot (\epsilon \text{OPT}/k)$. We don't update the margin value every time the solution set is augmented. Instead, each time a new element is inserted, the algorithm only checks the bucket whose marginal is larger than the current threshold. One can show either a new element is added to S , or it is pushed down to the next level. The latter can happen at most $O(1/\epsilon)$ times, and after that, the element has negligible marginal contribution that can be ignored safely.

Insertion-only streams: Submodular maximization with a matroid constraint. We first provide a deterministic combinatorial algorithm that achieves a $(1/2 - \epsilon)$ -approximation. We build upon the previous idea, but with significant adaptations. Again, our goal is to simulate an offline greedy algorithm but this time, one cannot relax the condition and hope to augment the solution set whenever the margin has a moderate improvement. The analysis of the offline greedy algorithm relies crucially on picking the maximum margin element in each step. Our first idea is to find the element with approximate maximum margin and branch over all possibilities. In particular, we divide the marginal gain into $L = O(\epsilon^{-1} \log(k/\epsilon))$ many levels, where the ℓ -th level corresponds to $[(1 + \epsilon)^{-\ell+1} \text{OPT}, (1 + \epsilon)^{-\ell} \text{OPT}]$. When working on an insertion-only stream, we proceed to the $(\ell + 1)$ -th level only when there is no element in the ℓ -th level anymore. Of course, we still don't know when the ℓ -th level becomes empty so that we can move to $\ell + 1$, but we can enumerate over all possibilities and guarantee that there exists one branch that fits the sequence of the offline approximate greedy algorithm. The caveat is that the total number of branch is $\binom{k}{L}$, which is quasi-polynomial in k . We further reduce this number by considering a pruned version of the offline approximate greedy algorithm, where the algorithm prunes extra element in each level and only keeps the majority. We prove the algorithm still guarantees a $(1/2 - \epsilon)$ -approximation and the total number of branch reduces to $k^{\tilde{O}(1/\epsilon)}$. It requires careful analysis to make the idea work, but the very high level intuition is that one needs to be more careful in the first few buckets (since the marginal is large) and less careful at the end. To amplify the approximation ratio to $(1 - 1/e - \epsilon)$, we make use of the multi-linear extension and use the accelerated continuous greedy framework [BV14]. In each iteration, we use the above combinatorial algorithm to find the direction of improvement of the multi-linear extension. We remark a similar amplifying procedure has been used in the previous work on adaptive submodular maximization [CQ19, BRS19b].

Organization. We begin by presenting the linear lower bound for 0.584-approximation under fully dynamic stream in Section 3. Section 4 is devoted to prove the polynomial lower bound on $(1/2 + \epsilon)$ -approximation. We then turn to the insertion-only stream and provide our algorithms and analysis. The algorithm for a cardinality constraint is presented in Section 5, and we provide an efficient $(1 - 1/e)$ -approximation algorithm for a matroid constraint in Section 6. We discuss future research directions in Section 7.

2 Preliminary

Submodular functions. Let V be a finite ground set. A function $f : 2^V \rightarrow \mathbb{R}$ is *submodular* if

$$f(S \cup T) + f(S \cap T) \leq f(S) + f(T)$$

for all pairs of sets $S, T \subseteq V$. We say f is *nonnegative* if $f(S) \geq 0$ for all $S \subseteq V$ and f is *monotone* if $f(S) \leq f(T)$ whenever $S \subseteq T \subseteq V$. We study submodular functions that are both nonnegative and monotone, and assume without loss of generality that $f(\emptyset) = 0$ (see Remark 2.2). We say an algorithm has query access to f if it can adaptively pick subsets $S \subseteq V$ to reveal the value of $f(S)$.

Given $f : 2^V \rightarrow \mathbb{R}$ and $S, T \subseteq V$, the marginal gain of adding e to S is defined as

$$f_S(T) := f(S \cup T) - f(S).$$

When $T = \{e\}$ is a singleton, we write $f_S(e)$ to denote $f_S(\{e\})$ for convenience. Monotonicity and submodularity can be defined equivalently using marginal gains: f is monotone iff $f_S(e) \geq 0$ for all $e \in V$ and $S \subseteq V$; f is submodular iff $f_S(e) \geq f_T(e)$ for any $e \notin T$ and $S \subseteq T \subseteq V$.

Dynamic submodular maximization under a cardinality constraint. Given V , a positive integer k and query access to a nonnegative, monotone submodular function $f : V \rightarrow \mathbb{R}$, the goal is to find a γ -approximate solution S_i of size at most k at the end of each round i when making a pass on a dynamic stream of insertions and deletions (the stream is *insertion-only* if no deletions are allowed). More formally, starting with $V_0 = \emptyset$, an element $e_i \in V$ is either inserted or deleted at the beginning of round $i = 1, \dots$, so that the current ground set V_i is set to be either $V_{i-1} \cup \{e_i\}$ if e_i is inserted or $V_i = V_{i-1} \setminus \{e_i\}$ if e_i is deleted. After this, the algorithm makes queries to f to find a γ -approximate solution S_i of f with respect to V_i . This means that $|S_i| \leq k$ and

$$f(S_i) \geq \gamma \text{OPT}_i, \quad \text{where} \quad \text{OPT}_i := \max_{T \subseteq V_i, |T| \leq k} f(T)$$

We emphasize that an algorithm remembers every query it has made so far. Thus results of queries made in previous rounds may help finding S_i in the current round.

We will consider algorithms that are both deterministic and randomized. We say a deterministic dynamic algorithm achieves an approximation guarantee of γ if given n and any stream of length n , it returns a γ -approximate solution S_i of the i -th round for every $i \in [n]$. We say a randomized dynamic algorithm achieves an approximation guarantee of γ if given n and any stream of length n , with probability at least $2/3$ it returns a γ -approximate solution S_i for every round $i \in [n]$ at the same time. We say an (deterministic or randomized) algorithm has *amortized* query complexity Q if the total number of queries it makes is no more than $n \cdot Q$.

Remark 2.1. *We discuss some details of the model behind our upper and lower bounds:*

1. *Our lower bounds hold even if the algorithm is given V and it is allowed to query during the i -th round any set S of elements that have appeared in V_j for some $j \leq i$; our algorithms only query sets in V_i and does not need to know V initially.*
2. *Our lower bounds hold even if the algorithm is given n , the stream length; our algorithms do not need to know n and meet the stated amortized bounds at the end of every round.*

Dynamic submodular maximization under a matroid constraint A set system $\mathcal{M} \subseteq 2^V$ is a *matroid* if it satisfies (i) $\emptyset \in \mathcal{M}$, (ii) the *downward closed* and (iii) *augmentation* properties. A set system \mathcal{M} is downward closed if $T \in \mathcal{M}$ implies $S \in \mathcal{M}$ for all $S \subseteq T$. The augmentation property is that if $S, T \in \mathcal{M}$ and $|S| < |T|$, then there must be an element $e \in T \setminus S$ such that $S \cup \{e\} \in \mathcal{M}$. When $S \in \mathcal{M}$, we say S is *feasible* or *independent*. The rank of the matroid \mathcal{M} , denoted as $\text{rank}(\mathcal{M})$, is the maximum size of an independent set in \mathcal{M} .

The setting of dynamic submodular maximization under a matroid constraint is similar. In addition to V and query access to f , the algorithm is given query access to a matroid \mathcal{M} over V :

it can pick any $S \subseteq V$ to query if $S \in \mathcal{M}$ or not. The goal is to find a γ -approximate solution S_i of f with respect to V_i at the end of every round. This means that $S_i \subseteq V_i$, $S_i \in \mathcal{M}$ and

$$f(S_i) \geq \gamma \cdot \text{OPT}_i, \quad \text{where} \quad \text{OPT}_i := \max_{T \in \mathcal{M}, T \subseteq V_i} f(T).$$

When measuring the amortized query complexity, we count queries to both f and \mathcal{M} .

Remark 2.2. *In both problems, one can assume without loss of generality that $f(\emptyset) = 0$ (since any γ -approximate solution to g with respect to V_i , where $g(S) := f(S) - f(\emptyset)$, must be a γ -approximate solution to f with respect to V_i as well). We will make this assumption in the rest of the paper.*

The multilinear extension The multilinear extension $F : [0, 1]^{|V|} \rightarrow \mathbb{R}^+$ of a function f maps a point $\mathbf{x} \in [0, 1]^{|V|}$ to the expected value of a random set $S \sim \mathbf{x}$, i.e.

$$F(\mathbf{x}) = \sum_{S \subseteq V} \prod_{e \in S} x_e \prod_{e' \in V \setminus S} (1 - x_{e'}) f(S)$$

We write $F(\mathbf{x}) = \mathbb{E}_{S \sim \mathbf{x}}[f(S)]$ for simplicity. For any $\mathbf{x} \in [0, 1]^{|V|}$, $\lambda \in [0, 1]$, $S \subseteq V$, we write $F(\mathbf{x} + \lambda S)$ to denote $F(\mathbf{x}')$, where $x'_i = x_i$ if $i \notin S$ and $x'_i = \min\{x_i + \lambda, 1\}$ if $i \in S$.

For a continuous function $F : [0, 1]^{|V|} \rightarrow \mathbb{R}$, we say it is monotone if $\frac{\partial F}{\partial x_i} \geq 0$ and it is submodular if $\frac{\partial^2 F}{\partial x_i \partial x_j} \leq 0$ for every i, j . When f is monotone and submodular, the multilinear extension F is also monotone and submodular.

3 A linear lower bound for 0.584-approximation

We restate the main theorem of this section:

Theorem 1.2. *There is a constant $C > 0$ with the following property. When $k \geq C \log n$, any randomized algorithm for dynamic submodular maximization under cardinality constraint k that obtains an approximation guarantee of 0.584 must have amortized query complexity at least $\Omega(n/k^3)$.*

3.1 Construction of the symmetric function

Let w be a positive integer and let $\epsilon > 0$ be a small constant to be fixed later. Given $x \in [0, 1]^w$, we let $\bar{x} = \sum_{i=1}^w x_i / w$. Consider the following function f over $[0, 1]^w$ and its symmetric version g :

$$f(x) := 1 - \prod_{i \in [w]} (1 - x_i) \quad \text{and} \quad g(x) := 1 - (1 - \bar{x})^w.$$

The following theorem is from [MSV08]. We need to make some minor changes on the choice of parameters and include a proof in Appendix A for completeness.

Theorem 3.1 ([MSV08]). *Given any positive integer w and $\epsilon > 0$, let $\gamma = \gamma(w, \epsilon) := w^{-1} \exp(-4w^6/\epsilon)$. There is a monotone submodular function $\hat{f} : [0, 1]^w \rightarrow [0, 1]$ with the following two properties:*

1. *Whenever $\max_{i, j \in [w]} |x_i - x_j| \leq \gamma$, we have $\hat{f}(x) = g(x)$;*
2. *For any $x \in [0, 1]^w$, we have $f(x) - \epsilon \leq \hat{f}(x) \leq f(x)$.*

Let m be a positive integer. We use \hat{f} from Theorem 3.1 to construct a function $\hat{F} : [0, 1]^{mw} \rightarrow \mathbb{R}$ as follows: Writing $x \in [0, 1]^{mw}$ as $x = (x_1, \dots, x_s)$ and $x_i = (x_{i,1}, \dots, x_{i,w}) \in [0, 1]^w$, we have

$$\hat{F}(x) := 1 - \prod_{i \in [m]} (1 - \hat{f}(x_i)). \quad (1)$$

We also define its symmetric version $G : [0, 1]^{mw} \rightarrow \mathbb{R}^+$ as

$$G(x) := 1 - \prod_{i \in [m]} (1 - g(x_i)) = 1 - \prod_{i \in [m]} (1 - \bar{x}_i)^w.$$

Here are some basic properties we need about \hat{F} , we defer detailed proof to Appendix A.

Lemma 3.2. *\hat{F} satisfies the following properties:*

- \hat{F} is monotone, submodular and satisfies $\hat{F}(x) \in [0, 1]$ for all $x \in [0, 1]^{mw}$.
- $\hat{F}(x) = G(x)$ when $x \in [0, 1]^{mw}$ satisfies

$$\max_{i \in [m], j, j' \in [w]} |x_{i,j} - x_{i,j'}| \leq \gamma$$

and in this case, $\hat{F}(x)$ depends on $\bar{x}_1, \dots, \bar{x}_m$ only.

- $\hat{F}(x) \geq 1 - \epsilon$ when x satisfies $x_{i,j} = 1$ for some $i \in [m]$ and $j \in [w]$,

3.2 Construction of the hard functions $\mathcal{F}_{c,\pi}$

We now present the construction of the family of hard functions that will be used in the proof.

Choice of parameters. Let n be the length of the dynamic stream. Let $\epsilon > 0$ be a constant. Let α and β be two constants in $(0, 1)$ that we fix at the end of the proof.² Let

$$w = 10 \left(\frac{1}{\alpha\epsilon} + \frac{1}{(1-\alpha)\epsilon} \right) \quad \text{and} \quad \gamma = w^{-1} \exp \left(-\frac{4w^6}{\epsilon} \right)$$

be two constants. Let k be the cardinality constraint parameter that is at most $n^{1/3}$ (otherwise the lower bound $\Omega(n/k^3)$ in the main theorem becomes trivial) and satisfies

$$k \geq \frac{10}{\epsilon\gamma\alpha^2(1-\alpha)^2} \cdot \log n.$$

Finally, let m be such that $n = (2 - \alpha)mkw$ so we have $m = \Omega(n^{2/3})$.

The ground set V . We start with the definition of the ground set V , where

$$V = A \cup B, \quad A = \bigcup_{i=1}^m A_i \quad \text{and} \quad B = \bigcup_{i=1}^m B_i,$$

where each A_i has αkw elements and each B_j has $(1 - \alpha)kw$ elements and they are pairwise disjoint.

²Looking ahead, we will choose α and β to minimize the quantity $Q(\alpha, \beta)$ discussed in Lemma 3.7; we will set them to be $\alpha = 0.56$ and $\beta = 0.42$, respectively.

The function $\mathcal{F}_{c,\pi}$. Let $c : V \rightarrow [w]$. We say c is a *proper w -coloring* of V if each $A_{i,j}$, the set of elements in A_i with color $j \in [w]$, has size αk and each $B_{i,j}$, the set of elements in B_i with color j , has size $(1 - \alpha)k$. (So $A_{i,1}, \dots, A_{i,w}$ form an even partition of A_i and $B_{i,1}, \dots, B_{i,w}$ form an even partition of B_i .) Let $\pi : [m] \rightarrow [m]$ be a bijection which we will view as matching $A_{\pi(i)}$ with B_i for each $i \in [m]$. Given any proper w -coloring c of V and any bijection $\pi : [m] \rightarrow [m]$, we define a function $\mathcal{F}_{c,\pi} : 2^V \rightarrow \mathbb{R}$ as follows.

For any $S \subseteq V$, let $y^S \in [0, 1]^{mw}$ and $z^S \in [0, 1]^{mw}$ be defined from S as

$$y_{i,j}^S = \frac{|S \cap A_{i,j}|}{\alpha k} \quad \text{and} \quad z_{i,j}^S = \frac{|S \cap B_{i,j}|}{(1 - \alpha)k}.$$

For any $I \subseteq [m]$, let $x^{S,I,\pi} \in [0, 1]^{mw}$ be

$$x_{i,j}^{S,I,\pi} = \begin{cases} y_{\pi(i),j}^S & \text{if } i \in I \\ z_{i,j}^S & \text{if } i \notin I \end{cases}.$$

Finally we define $\mathcal{F}_{c,\pi} : 2^V \rightarrow \mathbb{R}$: For any $S \subseteq V$,

$$\mathcal{F}_{c,\pi}(S) = \min \left\{ \sum_{I \subseteq [m]} \beta^{|I|} (1 - \beta)^{m - |I|} \cdot \widehat{F}(x^{S,I,\pi}) + \frac{\epsilon}{k} |S|, 1 \right\}. \quad (2)$$

We state some basic properties of the function $\mathcal{F}_{c,\pi}$.

Lemma 3.3. *For any c and π , $\mathcal{F}_{c,\pi}$ satisfies the following two properties:*

1. $\mathcal{F}_{c,\pi}$ is monotone, submodular and $\mathcal{F}_{c,\pi}(S) \in [0, 1]$ for any $S \subseteq V$.
2. When $|S| \geq k/\epsilon$, $\mathcal{F}_{c,\pi}(S) = 1$.
3. For any $i \in [m]$ and $j \in [w]$, we have $|A_{\pi(i),j} \cup B_{i,j}| = k$ and $\mathcal{F}_{c,\pi}(A_{\pi(i),j} \cup B_{i,j}) \geq 1 - \epsilon$.

Proof. We start with the first claim. By Lemma 3.2, \widehat{F} is monotone and submodular. Hence, it is easy to see that for each $I \subseteq [m]$, $\widehat{F}(x^{S,I,\pi})$ is monotone and submodular in S . As addition and the min operation keep both submodularity and monotonicity, $\mathcal{F}_{c,\pi}$ is both monotone and submodular.

For the second claim, since \widehat{F} is nonnegative, $\mathcal{F}_{c,\pi}(S) \geq \min\{\epsilon|S|/k, 1\} = 1$ when $|S| \geq k/\epsilon$.

For the last claim, note that $|A_{\pi(i),j}| = \alpha k$, $|B_{i,j}| = (1 - \alpha)k$ and $A_{\pi(i),j} \cap B_{i,j} = \emptyset$. Therefore, $|A_{\pi(i),j} \cup B_{i,j}| = k$. Let $S = A_{\pi(i),j} \cup B_{i,j}$. We have $x_{i,j}^{S,I,\pi} = 1$ for all $I \subseteq [m]$ since $y_{\pi(i),j}^S = z_{i,j}^S = 1$. By Lemma 3.2, $\widehat{F}(x^{S,I,\pi}) \geq 1 - \epsilon$ for all I and thus,

$$\mathcal{F}(S) = \min \left\{ \sum_{I \subseteq [m]} \beta^{|I|} (1 - \beta)^{m - |I|} \cdot \widehat{F}(x^{S,I,\pi}) + \frac{\epsilon}{k} |S|, 1 \right\} \geq \min \left\{ (1 - \epsilon) + \frac{\epsilon}{k} |S|, 1 \right\} \geq 1 - \epsilon.$$

This finishes the proof of the lemma. □

For any subset $S \subseteq V$, we say S is *balanced* with respect to c if

$$\max_{\substack{i \in [m] \\ j, j' \in [w]}} |y_{i,j}^S - y_{i,j'}^S| \leq \gamma \quad \text{and} \quad \max_{\substack{i \in [m] \\ j, j' \in [w]}} |z_{i,j}^S - z_{i,j'}^S| \leq \gamma.$$

Define $\mathcal{G}_\pi : 2^V \rightarrow \mathbb{R}$ as

$$\mathcal{G}_\pi(S) = \min \left\{ \sum_{I \subseteq [m]} \beta^{|I|} (1 - \beta)^{m - |I|} \cdot G(x^{S, I, \pi}) + \frac{\epsilon}{k} |S|, 1 \right\}. \quad (3)$$

Recall the function $G(x)$ only depends on $\bar{x}_i, i \in [m]$. As a result, $\mathcal{G}_\pi(S)$ only depends on $|S \cap A_i|$ and $|S \cap B_i|, i \in [m]$. The following Lemma is a direct consequence of Lemma 3.2:

Lemma 3.4. *When $S \subseteq V$ is balanced with respect to c , we have $\mathcal{F}_{c, \pi}(S) = \mathcal{G}_\pi(S)$.*

Given any $S \subseteq V$, the next lemma captures the minimal information needed to evaluate $\mathcal{G}_\pi(S)$ without full knowledge of c and π . The proof can be found at Appendix A.

Lemma 3.5. *Let $S \subseteq V$ and let $\pi, \pi' : [m] \rightarrow [m]$ be two bijections. Then we have $\mathcal{G}_\pi(S) = \mathcal{G}_{\pi'}(S)$ when the following condition holds: For each $i \in [m]$, we have $\pi(i) = \pi'(i)$ if 1) $S \cap B_i \neq \emptyset$ and 2) either $S \cap A_{\pi(i)} \neq \emptyset$ or $S \cap A_{\pi'(i)} \neq \emptyset$.*

Remark 3.6. *Let $S \subseteq V$. If (1) S is known to be balanced with respect to c and (2) we are given*

$$\{(i, \pi(i)) : i \in [m], S \cap B_i \neq \emptyset \text{ and } S \cap A_{\pi(i)} \neq \emptyset\}, \quad (4)$$

then one can evaluate $\mathcal{F}_{c, \pi}(S)$ without more information about c and π . To see this, (1) implies that it suffices to evaluate $\mathcal{G}_\pi(S)$. Lemma 3.5 implies that $\mathcal{G}_\pi(S)$ is uniquely determined given (4).

We delay the proof of the following lemma to Appendix A. This is where we need to choose the two parameters α and β carefully to minimize the constant 0.584 in the lemma.

Lemma 3.7. *Fix any $i^* \in [m]$. Let $S \subseteq A \cup B_{i^*}$ be a set such that S is balanced with respect to c and $S \cap A_{\pi(i^*)} = \emptyset$. Then we have $\mathcal{F}_{c, \pi}(S) \leq 0.5839 + 3\epsilon$.*

3.3 Lower bound for dynamic submodular maximization

Hard streams. The ground set is V , which is known to the algorithm; the monotone submodular function $\mathcal{F}^* : 2^V \rightarrow \mathbb{R}$ is $\mathcal{F}_{c, \pi}$, where c is a proper w -coloring of V and $\pi : [m] \rightarrow [m]$ is a bijection, both of which are unknown to the algorithm. In the stream we first insert all elements of A , which takes αmkw insertions. We then divide the rest of the stream into m batches: For the t -th batch, we first insert all elements of B_t and then delete them. So the total length is $n = (2 - \alpha)mkw$. This is the only stream we will use in the proof but the function is determined by the unknown c and π .

We will focus on the $0.1m$ rounds when elements of B_t , for each $t = 1, \dots, 0.1m$, has just been inserted. To ease the presentation we consider the following dynamic problem that consists of $0.1m$ stages. During the t -th stage, an algorithm can query $\mathcal{F}^* : 2^V \rightarrow \mathbb{R}$ about any $S \subseteq A \cup B_1 \cup \dots \cup B_t$ and can choose to start the next stage at any time by outputting a set $S_t \subseteq A \cup B_t$ of size at most k . The algorithm succeeds after $0.1m$ stages if $\mathcal{F}^*(S_t) > 0.5839 + 3\epsilon$ for every $t \in [0.1m]$. We prove that any randomized algorithm that succeeds with probability at least $2/3$ must have total query complexity of at least $\Omega(n^2/k^3)$. It then follows from Lemma 3.3 (part 3) that any randomized algorithm for dynamic submodular maximization with an approximation guarantee of $0.5839 + 4\epsilon$ must have amortized query complexity $\Omega(n/k^3)$.

Proof of Theorem 1.2. Let **ALG** be a randomized algorithm for the $0.1m$ -stage problem described above that succeeds with probability at least $2/3$. By Lemma 3.3, we may assume that **ALG** never

queries a set of size more than k/ϵ . To lower bound the query complexity of **ALG** we consider the following simple $0.1m$ -stage game.

In the game there is a hidden proper w -coloring c of V and a hidden bijection $\pi : [m] \rightarrow [m]$. The game similarly consists of $0.1m$ stages. During each round of stage t , the algorithm can make a query by either (1) picking a subset S of V of size at most k/ϵ or (2) picking a number $i \in [m]$. In case (1) the c -oracle returns “balanced” or “unbalanced,” as whether S is balanced with respect to c or not; when receiving “unbalanced” the algorithm wins the whole game. In case (2) the π -oracle returns “matched” or “not matched,” as whether $\pi(t) = i$ or not; after receiving “matched,” the algorithm can choose to proceed to the next stage, and it wins the game if it passes all $0.1m$ stages.

We show that any randomized algorithm that wins the game with probability at least $2/3$ must use at least $\Omega(m^2)$ queries. To this end, we consider the distribution of $(\mathbf{c}, \boldsymbol{\pi})$ where \mathbf{c} and $\boldsymbol{\pi}$ are drawn uniformly and independently, and show that any deterministic algorithm that wins the game with probability at least $2/3$ must use $\Omega(m^2)$ queries.

Showing this distributional $\Omega(m^2)$ lower bound for each subgame is easy. For the subgame of finding an unbalanced set with respect to \mathbf{c} , we have for any set S of size at most k/ϵ that

$$\begin{aligned} \Pr [y_{i,j}^S - y_{i,j'}^S > \gamma] &= \Pr [|S \cap A_{i,j}| - |S \cap A_{i,j'}| > \gamma\alpha k] \\ &\leq \exp\left(-\frac{\epsilon\gamma^2\alpha^2k^2}{2k}\right) \leq \frac{1}{n^5}, \quad \text{and} \\ \Pr [z_{i,j}^S - z_{i,j'}^S > \gamma] &= \Pr [|S \cap B_{i,j}| - |S \cap B_{i,j'}| > \gamma(1-\alpha)k] \\ &\leq \exp\left(-\frac{\epsilon\gamma^2(1-\alpha)^2k^2}{2k}\right) \leq \frac{1}{n^5} \end{aligned}$$

for any fixed i and $j \neq j'$, given our choice of k . Therefore, any deterministic algorithm that finds an unbalanced set with probability at least $1/3$ requires $\Omega(n^5)$ queries. For the subgame about $\boldsymbol{\pi}$, at the beginning of each stage t , any of the remaining $m - (t-1)$ indices (other than $\pi(1), \dots, \pi(t-1)$) is equally likely to be $\pi(t)$. Given that $m - (t-1) \geq 0.9m$, it takes $\Omega(m)$ queries to pass each of the $0.1m$ stages and thus, any deterministic algorithm that wins the subgame about $\boldsymbol{\pi}$ with probability at least $1/3$ requires $\Omega(m^2)$ queries.

Back to the original game, if a deterministic algorithm \mathcal{A} can win with probability at least $2/3$, then it can either win the first or the second subgame with probability at least $1/3$. Assuming for example it is the latter case, we get a randomized algorithm for winning the second subgame over $\boldsymbol{\pi}$ with probability at least $1/3$ by first drawing \mathbf{c} and then simulating \mathcal{A} on the original game. Given that the number of queries is at most that of \mathcal{A} , we have that query complexity of \mathcal{A} is $\Omega(m^2)$.

To finish the proof we show how to use **ALG** to play the game. Let c be the hidden coloring and π be the hidden bijection. We simulate the execution of **ALG** on $\mathcal{F}^* = \mathcal{F}_{c,\pi}$ as follows:

1. During the first stage (of both the dynamic problem of maximizing \mathcal{F}^* over $A \cup B_1$ and the game), letting $S \subseteq A \cup B_1$ of size at most k/ϵ be any query made by **ALG**, we make one query S on the c -oracle (to see if S is balanced or not) and make one query i on the π -oracle for each $i \in [m]$ with $S \cap A_i \neq \emptyset$ (to see if $\pi(1) = i$). If S is not balanced, we already won the game; otherwise, we know $\mathcal{F}^*(S) = \mathcal{G}_\pi(S)$ and the latter can be computed (see Remark 3.6) using information returned by the π -oracle, so that we can continue the simulation of **ALG**. When **ALG** decides to output $S_1 \subseteq A \cup B_1$ of size at most k , we query S_1 on the c -oracle and query each i on the π -oracle with $S_1 \cap A_i \neq \emptyset$. If S_1 is unbalanced, we won the game; if $\pi(1) = i$ for some i queried, we move to stage 2 (in both the dynamic problem and the

game); if S_1 is balanced and $\pi(1) \neq i$ for any $i : S_1 \cap A_i \neq \emptyset$, it follows from Lemma 3.7 that ALG has failed so we terminate the simulation and fail the game.

2. During the t -th stage (of both the dynamic problem and the game), we similarly simulate each query $S \subseteq A \cup B_1 \cup \dots \cup B_t$ of ALG. The only difference is that, given that we have passed the first $(t - 1)$ stages of the game, we already know $\pi(1), \dots, \pi(t - 1)$ and thus, information returned by the π -oracle would be enough for us to evaluate $\mathcal{F}^*(S)$. When ALG returns S_t , we query S_t and each i with $S_t \cap A_i \neq \emptyset$, and act according to results similarly.

To summarize, the simulation has three possible outcomes: (1) we won the game because an unbalanced set has been found; (2) we won the game because we have passed all $0.1m$ stages; or (3) ALG fails to find S_t with $\mathcal{F}_{c,\pi}(S_t) \geq 0.5839 + 3\epsilon$ for some t . Given that (3) only happens with probability at most $1/3$, we obtain an algorithm for the game that succeeds with probability at least $2/3$ and thus, must use $\Omega(m^2)$ queries. To finish the proof, we note that if ALG has total query complexity q then the algorithm we obtain for the game has total query complexity at most

$$q \cdot \left(1 + \frac{k}{\epsilon}\right) + 0.1m \cdot (1 + k),$$

which implies $q = \Omega(m^2/k)$ and thus, the amortized complexity of ALG is $\Omega(m/k^2) = \Omega(n/k^3)$. Taking $\epsilon = 3 \times 10^{-5}$, we get the lower bound on approximation ratio. \square

4 A Polynomial Lower Bound for $1/2 + \epsilon$ Approximation

We restate the main theorem of this section:

Theorem 1.1. *For any constant $\epsilon > 0$, there is a constant $C_\epsilon > 0$ with the following property. When $k \geq C_\epsilon$, any randomized algorithm that achieves an approximation ratio of $1/2 + \epsilon$ for dynamic submodular maximization under cardinality constraint k requires amortized query complexity $n^{\tilde{\Omega}(\epsilon)}/k^3$.*

4.1 The construction

Let $\epsilon > 0$ be a positive constant. We assume that both $1/\epsilon$ and ϵk are positive integers. Our goal is to show that any randomized algorithm for dynamic submodular maximization under a cardinality constraint of k with approximation $1/2 + \tilde{O}(\epsilon)$ must have amortized query complexity $\Omega(n^\epsilon/k^3)$.

We start with the construction of a monotone submodular function $\mathcal{F} : V \rightarrow \mathbb{R}$. The family of functions used in our lower bound proof will be obtained from \mathcal{F} by carefully shuffling elements of V . Let $L = 1/\epsilon \in \mathbb{N}$ and let $m = (m_1, \dots, m_L)$ be a tuple of positive integers to be fixed later, with m_L set to be 1. Let T be a tree of depth L , where the root is at depth 0 and its leaves are at depth L . Each internal node of T at depth $\ell \in [0 : L - 1]$ has $m_{\ell+1}$ children; the number of nodes at depth $\ell \in [L]$ is $m_1 \cdots m_\ell$. We use γ to refer to the root of T and write $U_0 = \{\gamma\}$; for each $\ell \in [L]$, we use $V_\ell = [m_1] \times \dots \times [m_\ell]$ to refer to nodes of T at depth ℓ . So the set of nodes is $U_0 \cup U_1 \cup \dots \cup U_L$ and whenever we refer to a node u of T at depth ℓ , it should be considered as a tuple $(u_1, \dots, u_\ell) \in U_\ell$. Children of $u \in U_\ell$, $\ell \leq L - 1$, are given by $(u_1, \dots, u_\ell, 1), \dots, (u_1, \dots, u_\ell, m_{\ell+1})$.

The ground set V of \mathcal{F} is defined as follows. For each node $u \in U := U_1 \cup \dots \cup U_L$, we introduce a set $A_u = \{a_{u,1}, \dots, a_{u,w}\}$ of $w := \epsilon k$ new elements. We define V as the union of A_u for all $u \in U$. To construct $\mathcal{F} : 2^V \rightarrow \mathbb{R}$, we will utilize a weight sequence $\{w_\ell\}_{\ell \in [0:L]}$ from [FNFSZ20] to define a probability distribution \mathcal{D} over subsets of nodes of T . We specify the sequence later in Lemma 4.5; for now it suffices to know that $w_0 = 0$, w_ℓ 's are nonnegative, and they sum to 1.

Algorithm 1 Sample

1: **Input:** A node v of T at depth $\ell \in [0 : L]$

2: Let p_ℓ be given as below:

$$p_\ell = \frac{w_\ell}{1 - \sum_{i=0}^{\ell-1} w_i} \in [0, 1].$$

3: With probability p_ℓ , return v .

▷ Since $p_L = 1$, this always happen when $\ell = L$

4: Otherwise, run **Sample**(v_i) independently on each child v_i of v in the tree and return the union

We define the distribution of \mathcal{D} over 2^U as follows. Drawing a sample from $\mathbf{R} \sim \mathcal{D}$ can be done by calling the recursive procedure **Sample** in Algorithm 1 on the root of T . Informally, starting with $\mathbf{R} = \emptyset$, **Sample** performs a DFS walk on T . Whenever reaching a node v at depth ℓ , it adds v to \mathbf{R} and does not explore any of its children with probability p_ℓ (see Algorithm 1; note that $p_0 = 0$ and $p_L = 1$); otherwise, it continues the DFS walk to visit each of its children. Because $p_0 = 0$, the root is never included in the set and thus, \mathbf{R} is always a subset of U .

We need the following properties about \mathbf{R} , the proof can be found at Appendix B.

Lemma 4.1. *Let $\mathbf{R} \sim \mathcal{D}$, we need have the following properties*

- For any node u of T at depth ℓ , the probability of $u \in \mathbf{R}$ with $\mathbf{R} \sim \mathcal{D}$ is w_ℓ .
- For any root-to-leaf path of T , every R in the support of \mathcal{D} has exactly one node in the path.

Let $P_1 \subseteq U$ and $P_2 \subseteq U$ be two subsets of nodes of T and let τ be a bijection from P_1 to P_2 such that (1) u and $\tau(u)$ are at the same depth for every $u \in P_1$; and (2) for any $u, v \in P_1$, the depth of the lowest common ancestor (LCA) of u and v is the same as that of $\tau(u)$ and $\tau(v)$. The following lemma follows from how the procedure **Sample** works:

Lemma 4.2. *The distribution of $P_2 \cap \mathbf{R}$, $\mathbf{R} \sim \mathcal{D}$, is distributed the same as first drawing $\mathbf{R} \sim \mathcal{D}$, taking $P_1 \cap \mathbf{R}$ and applying τ on $P_1 \cap \mathbf{R}$.*

Proof. Let T_1 (or T_2) be the subtree that consists of paths from nodes in P_1 (or P_2) to the root. Using conditions (1) and (2), one can show (by induction) that τ can be extended to obtain an isomorphism from P_1 to P_2 . Then $P_1 \cap \mathbf{R}$ and $P_2 \cap \mathbf{R}$ can be obtained by running **Sample** on the same tree and the two distributions are the same under τ . \square

We use \mathcal{D} to define \mathcal{F} . Given $S \subseteq V$, we define $x^S \in [0, 1]^U$ as the vector indexed by $u \in U$ with

$$x_u^S = \frac{|S \cap A_u|}{\epsilon k} \in [0, 1].$$

For any R in the support of \mathcal{D} we define $g_R : [0, 1]^U \rightarrow [0, 1]$ and $\mathcal{G} : [0, 1]^U \rightarrow [0, 1]$ as

$$g_R(x) := 1 - \prod_{u \in R} (1 - x_u) \quad \text{and} \quad \mathcal{G}(x) = \mathbb{E}_{\mathbf{R} \sim \mathcal{D}} [g_{\mathbf{R}}(x)]. \quad (5)$$

We are now ready to define \mathcal{F} over 2^V as

$$\mathcal{F}(S) = \min \left\{ \mathcal{G}(x^S) + \frac{\epsilon}{k} |S|, 1 \right\}, \quad \text{for any set } S \subseteq V. \quad (6)$$

We state some basic properties of \mathcal{F} . The detailed proof can be found at Appendix B.

Lemma 4.3. \mathcal{F} is monotone submodular and $\mathcal{F}(S) \in [0, 1]$ for any $S \subseteq V$. Moreover, $\mathcal{F}(S) = 1$ whenever $|S| \geq k/\epsilon$.

For each leaf $u \in U_L$, we define two important subsets of V . The first set, \mathcal{A}_u , is the union of A 's along the path from u 's parent to the root (not including the root):

$$\mathcal{A}_u := A_{u_1} \cup A_{u_1, u_2} \cup \dots \cup A_{u_1, \dots, u_{L-1}}.$$

The other set W_u is the union of A 's of nodes that are children of nodes along the root-to- u path:

$$W_u := \bigcup_{\ell \in [L]} \bigcup_{j \in [m_\ell]} A_{u_1, \dots, u_{\ell-1}, j}.$$

The following lemma shows that $\mathcal{F}(\mathcal{A}_u \cup A_u)$ is large:

Lemma 4.4. For any leaf $u \in U_L$, we have $|\mathcal{A}_u \cup A_u| = k$ and $\mathcal{F}(\mathcal{A}_u \cup A_u) = 1$.

Proof. Since these $L = 1/\epsilon$ sets are pairwise disjoint and each has size ϵk , S has size k . The second part follows from the second part of Lemma 4.1 and the definition of g_R . \square

We would like to show in the next lemma that any set $S \subseteq W_u$ that has size at most k and does not overlap with \mathcal{A}_u must have a small $\mathcal{F}(S)$. For this we need to specify the weight sequence $\{w_\ell\}$ that we will use from [FNFSZ20] (recall that $w_0 = 0$).

Definition 4.5 (Weight sequence). Define $\{\delta_\ell\}_{\ell \in [L]}$, $\{a_\ell\}_{\ell \in [L]}$ and the weight sequence $\{w_\ell\}_{\ell \in [L]}$ inductively as follow. We set $\delta_L = 1$ and for $\ell = L - 1, L - 2, \dots, 1$, let

$$\delta_\ell = 1 + \left(\frac{1 + \sqrt{1 + 4/\delta_{\ell+1}}}{2} \right) \cdot \delta_{\ell+1}$$

and

$$a_\ell = \prod_{i=1}^{\ell-1} \left(\frac{\delta_i - 1}{\delta_{i+1}} \right) = \prod_{i=1}^{\ell-1} \frac{1}{1 - 1/\delta_i},$$

the weight sequence $\{w_\ell\}_{\ell \in [L]}$ is defined as $w_\ell = a_\ell / \sum_{\ell \in [L]} a_\ell$.

The proof of the following lemma is adapted from Lemma 5.3 in [FNFSZ20] with some generalizations, and the proof can be found in Appendix B.

Lemma 4.6. For any leaf $u \in U_L$ and $S \subseteq W_u$ with $|S| \leq k$ and $S \cap \mathcal{A}_u = \emptyset$, we have

$$\mathcal{F}(S) \leq 0.5 + O(\epsilon \log^2(1/\epsilon)).$$

As it will become clear soon at the beginning of the next subsection, our goal behind the family of hard streams is to have the dynamic algorithm solve repeatedly the question of finding an $S \subseteq W_u$ with $|S| \leq k$ and $S \cap \mathcal{A}_u \neq \emptyset$, for a large number of leafs u of T . These questions are, however, only interesting after we shuffle nodes of T in the fashion to be described next.

A *shuffling* π of T consists of a bijection $\pi_u : [m_{\ell+1}] \rightarrow [m_{\ell+1}]$ for every $u \in U_\ell$, $\ell \in [0 : L - 1]$. We use π to shuffle each node $u \in U$ to $\pi(u)$ as follows: $\pi(\gamma) = \gamma$; for each u of depth $\ell \in [L]$, set

$$\pi(u) = (u_1, \dots, u_{\ell-1}, \pi_{u_1, \dots, u_{\ell-1}}(u_\ell)).$$

A shuffling π induces a bijection $\rho_\pi : V \rightarrow V$: For each element $a_{u,i}$ for some $u \in U$ and $i \in [w]$, we set $\rho_\pi(a_{u,i}) = a_{\pi^{-1}(u),i}$. Finally we define for each shuffling π of T ,

$$\mathcal{F}_\pi(S) := \mathcal{F}(\rho_\pi(S)).$$

It is clear that Lemma 4.3 holds for \mathcal{F}_π for any shuffling π .

Given a leaf $u \in U_L$ of T and a shuffling π , let

$$\mathcal{A}_u^\pi := A_{u_1, \dots, u_{L-2}, \pi_{u_1, \dots, u_{L-2}}(u_{L-1})} \cup \dots \cup A_{u_1, \pi_{u_1}}(u_2) \cup A_{\pi_\epsilon}(u_1).$$

We get the following corollary of Lemma 4.4 and Lemma 4.6:

Corollary 4.7. *For any shuffling π of T , we have*

- For any leaf $u \in U_L$, we have $|\mathcal{A}_u^\pi \cup A_u| = k$ and $\mathcal{F}_\pi(\mathcal{A}_u^\pi \cup A_u) = 1$.
- For any leaf u and $S \subseteq W_u$ with $|S| \leq k$ and $S \cap \mathcal{A}_u^\pi = \emptyset$, we have

$$\mathcal{F}_\pi(S) \leq 0.5 + O(\epsilon \log^2(1/\epsilon)). \quad (7)$$

Proof. The first part follows from Lemma 4.4 and the observation that $\rho_\pi(\mathcal{A}_u^\pi \cup A_u) = \mathcal{A}_u \cup A_u$. The second part follows from $\rho_\pi(S) \subseteq W_u$, $\rho_\pi(S) \cap \mathcal{A}_u = \emptyset$ and Lemma 4.6. \square

We need a corollary of Lemma 4.2. Similar to Lemma 3.5, it captures the minimal information needed about π to evaluate \mathcal{F}_π at a given set $S \subseteq V$:

Corollary 4.8. *Let $S \subseteq V$ and let π, π' be two shufflings of T . We have $\mathcal{F}_\pi(S) = \mathcal{F}_{\pi'}(S)$ when the following condition holds: For every two nodes u, v of T such that $S \cap A_u$ and $S \cap A_v$ are nonempty, the LCA of $\pi^{-1}(u)$ and $\pi^{-1}(v)$ is at the same depth as the LCA of $\pi'^{-1}(u)$ and $\pi'^{-1}(v)$, both in T .*

Proof. Let $P_1 = \{\pi^{-1}(u) : u \in U \text{ and } S \cap A_u \neq \emptyset\}$ and P_2 be the set of nodes defined similarly using π' . It follows from Lemma 4.2 that $\mathbf{R} \cap P_1$ is the same as $\mathbf{R} \cap P_2$, $\mathbf{R} \sim \mathcal{D}$, under the natural bijection between P_1 and P_2 . The statement follows from the definition of \mathcal{F} . \square

Remark 4.9. *To evaluate $\mathcal{F}_\pi(S)$, it suffices to know the LCA of $\pi^{-1}(u)$ and $\pi^{-1}(v)$ for every u, v with $S \cap A_u \neq \emptyset$ and $S \cap A_v \neq \emptyset$. The LCA of $\pi^{-1}(u)$ and $\pi^{-1}(v)$ can be determined as follows.*

1. First consider the case when u is a prefix of v or v is a prefix of u . Let $u = (u_1, \dots, u_\ell)$ and $v = (u_1, \dots, u_\ell, v_{\ell+1}, \dots)$. (The case when v is a prefix is similar.) Then the depth of LCA of $\pi(u)$ and $\pi^{-1}(v)$ is either ℓ if $\pi_{u_1, \dots, u_{\ell-1}}(u_\ell) = v_{\ell+1}$, or $\ell - 1$ otherwise.
2. Assume that $u = (u_1, \dots, u_\ell, u_{\ell+1}, \dots)$ and $v = (v_1, \dots, v_\ell, v_{\ell+1}, \dots)$ with $u_1 = v_1, \dots, u_\ell = v_\ell$ but $u_{\ell+1} \neq v_{\ell+1}$. We have three subcases. If both u and v have length strictly longer than $\ell + 1$, then the depth of LCA of $\pi^{-1}(u)$ and $\pi^{-1}(v)$ is ℓ . If both u and v have length $\ell + 1$, then the depth of LCA of $\pi^{-1}(u)$ and $\pi^{-1}(v)$ is also ℓ . (So in these two subcases we do not need to know anything about π .) Finally, if u has length $\ell + 1$ and v has length longer than $\ell + 1$, then the depth of LCA of $\pi^{-1}(u)$ and $\pi^{-1}(v)$ is $\ell + 1$ if $\pi_{v_1, \dots, v_\ell}(v_{\ell+1}) = u_{\ell+1}$, and is ℓ otherwise. The case when u has length longer than $\ell + 1$ and v has length $\ell + 1$ is similar.

To summarize, to determine the depth we only need to know whether a particular entry of π is equal to a certain value or not. Moreover, the entry is either $\pi_{u_1, \dots, u_{\ell-1}}(u_\ell)$ or $\pi_{v_1, \dots, v_{\ell-1}}(v_\ell)$ for some ℓ .

Algorithm 2 TRANVERSE

```
1: Input: A node  $u$  of  $T$  at depth  $\ell \in [0 : L - 1]$ 
2: if  $\ell = L - 1$  then
3:   Insert all elements of  $A_{u_1, \dots, u_{L-1}, 1}$  and then delete them
4: else
5:   Insert all elements in  $A_{u_1, \dots, u_\ell, i}$  for each  $i \in [m_{\ell+1}]$ 
6:   for  $i$  from 1 to  $d$  do
7:     Call TRANVERSE on  $(u_1, \dots, u_\ell, i)$ 
8:   end for
9:   Delete all elements in  $A_{u_1, \dots, u_\ell, i}$  for each  $i \in [m_{\ell+1}]$ 
10: end if
```

4.2 Lower bound for dynamic submodular maximization

Choices of parameters. Let $L = 1/\epsilon$ be a positive integer. Let k be a positive integer such that $k^2 \leq n^\epsilon$ (as otherwise the lower bound we aim for becomes trivial) and $w = \epsilon k$ is a positive integer. Let n be the length of dynamic streams and $d = n^\epsilon$. Set $m_L = 1$ and

$$m_\ell = \frac{n^{(L-\ell+1)\epsilon}}{2k}, \quad \text{for each } \ell \in [L - 1].$$

Hard streams. The ground set is V , which is known to the algorithm; the monotone submodular function $\mathcal{F}^* : 2^V \rightarrow \mathbb{R}$ is \mathcal{F}_π , where π is a shuffling of T , which is unknown to the algorithm. The stream is constructed by running TRANVERSE in Algorithm 2, and is independent of π . It can be viewed as a DFS over the tree T , starting at the root, except that every time it reaches a node v , it inserts all children of v but only explores the first d children, and deletes all children of v at the end of the exploration.

We first bound the total number of operations by n . For each $\ell \in [0 : L - 2]$, TRANVERSE visits d^ℓ nodes and creates $2m_{\ell+1} \cdot w$ operations for each of them. TRANVERSE visits d^{L-1} nodes at depth $L - 1$ and creates $2w$ operations for each of them. Hence, the total number of operations is

$$\sum_{\ell=0}^{L-2} d^\ell \cdot m_{\ell+1} \cdot 2w + d^{L-1} \cdot 2w \leq \sum_{\ell=0}^{L-2} \epsilon n + \epsilon n \leq n.$$

To gain some intuition behind the stream, we note that leaves of T that appear in the stream are exactly those in $U_L^* := [d]^{L-1} \times \{1\}$, and they appear in the stream under the lexicographical order (which we will denote by \prec). For each such leaf $u \in U_L^*$, at the time when the set A_u was inserted, the current set of elements is W_u . Inspired by Corollary 4.7 we will consider the following simplified d^{L-1} -stage dynamic problem, where stages are indexed using leaves in U_L^* under the lexicographical order. During the u -th stage, an algorithm can query \mathcal{F}^* about any subset $S \subseteq \cup_{u' \in U_L^*; u' \prec u} W_{u'}$ and can choose to start the next stage at any time by returning an $S_u \subseteq W_u$ of size at most k . We say an algorithm succeeds if $\mathcal{F}^*(S_u) \geq 0.5 + \tilde{O}(\epsilon)$ as on the RHS of (7) for every stage. We show below that any randomized algorithm that succeeds with probability at least $2/3$ must have total query complexity $\Omega(n^{1+\epsilon}/k^3)$. It follows from Corollary 4.7 that any randomized algorithm for dynamic submodular maximization with an approximation guarantee of $0.5 + \tilde{\Omega}(\epsilon)$ must have amortized query complexity $\Omega(n^\epsilon/k^3)$.

Proof of Theorem 1.1. Let π be a shuffling of T drawn uniformly at random (i.e., every bijection in π is drawn independently and uniformly). Consider any deterministic algorithm ALG that succeeds

with probability $2/3$ on the d^{L-1} -stage dynamic problem described above with $\mathcal{F}^* = \mathcal{F}_\pi$. By Lemma 4.3 we assume without loss of generality that ALG only queries sets of size at most k/ϵ . When ALG succeeds on $\mathcal{F}^* = \mathcal{F}_\pi$ for some shuffling π , we have from Corollary 4.7 that the S_u it outputs during the u -th stage must satisfy $S_u \cap \mathcal{A}_u^\pi \neq \emptyset$, which implies (using the definition of \mathcal{A}_u^π) that

$$S_u \cap A_{u_1, \dots, u_\ell, \pi_{u_1, \dots, u_\ell}(u_{\ell+1})} \neq \emptyset \quad (8)$$

for some $\ell \in [0 : L - 2]$. By an averaging argument, we have that there exists an $\ell \in [0 : L - 2]$ such that with probability at least $2/(3L)$ over π , at least $(1/L)$ -fraction of S_u returned by ALG satisfy (8) for this ℓ . Fix such an ℓ and this inspires us to introduce the following simple game.

In the game there are d^ℓ hidden bijections $\pi_{v_1, \dots, v_\ell} : [m_{\ell+1}] \rightarrow [m_{\ell+1}]$, for each $v_1, \dots, v_\ell \in [d]$. The game consists of $d^{\ell+1}$ stages; each stage is indexed by a $v = (v_1, \dots, v_{\ell+1}) \in [d]^{\ell+1}$ and ordered by the lexicographical order. During the v -th stage of the game, an algorithm can send a number $i \in [m_{\ell+1}]$ to the oracle and the latter reveals if $\pi_{v_1, \dots, v_\ell}(v_{\ell+1}) = i$. We say the algorithm wins the v -th stage if it queries an i that matches $\pi_{v_1, \dots, v_\ell}(v_{\ell+1})$ during the v -th stage. At any time it can choose to give up and move forward to the next stage, in which case $\pi_{v_1, \dots, v_\ell}(v_{\ell+1})$ is revealed to the algorithm. We say an algorithm succeeds if it wins at least $(1/L)$ -fraction of the $d^{\ell+1}$ stages.

We prove the following lower bound for this game in Appendix B:

Claim 4.10. *When the hidden bijections are drawn independently and uniformly, any deterministic algorithm that succeeds with probability at least $2/(3L)$ has total query complexity $\Omega(m_{\ell+1}d^{\ell+1})$.*

To finish the proof, we show that ALG can be used to play the game as follows:

1. We start by drawing a random bijection for every node in the tree T except for those at $(v_1, \dots, v_\ell) \in [d]^\ell$. Let π be the shuffling when they are combined with hidden bijections π_{v_1, \dots, v_ℓ} in the game. We simulate ALG on \mathcal{F}_π over the stream TRANVERSE and maintain the following invariant. During the v -th stage of the game, with $v = (v_1, \dots, v_{\ell+1}) \in [d]^{\ell+1}$, we simulate ALG through its stages for leaves $u \in U_L^*$ that have v as a prefix and assume that we already know $\pi_{w_1, \dots, w_\ell}(w_{\ell+1})$ for all $w = (w_1, \dots, w_{\ell+1}) \prec v$ and $w \in [d]^{\ell+1}$.
2. During the u -th stage of the simulation of ALG for some leaf $u \in U_L^*$, we are in the v -th stage of the game with $v = (u_1, \dots, u_{\ell+1}) \in [d]^{\ell+1}$. For each query $S \subseteq \cup_{u' \in U_L^* : u' \preceq u} W_{u'}$ (of size at most k/ϵ) made by ALG, it follows from Remark 4.9 that, to evaluate S at \mathcal{F}_π , we only need to know the depth of LCA of $\pi^{-1}(u'')$ and $\pi^{-1}(v'')$ in T for no more than $(k/\epsilon)^2$ many pairs of u'', v'' with $S \cap A_{u''} \neq \emptyset$ and $S \cap A_{v''} \neq \emptyset$. For each such pair, it follows from Remark 4.9 again that either we know the answer already or we need to compare $\pi_{u''_1, \dots, u''_\ell}(u''_{\ell+1})$ or $\pi_{v''_1, \dots, v''_\ell}(v''_{\ell+1})$ with a certain value. Given that $u'' \preceq v$ and $v'' \preceq v$, either the answer is already known or we just need to make a query to the game oracle. So we only need to make at most $(k/\epsilon)^2$ queries to continue the simulation of ALG. At the end of the u -th stage of ALG, let S_u be the set that ALG returns. For every i such that $S_u \cap A_{u_1, \dots, u_\ell, i} \neq \emptyset$ (note that there are at most k such i given that $|S| \leq k$), we query i on the game oracle. Note that we would have won the v -th stage of the game by now if (8) holds for S_u . We then continue to simulate ALG on the next stage of the dynamic problem. If the next stage of ALG is about a new leaf u with $v \prec (u_1, \dots, u_{\ell+1})$, then we also move to the next stage in the game.

It is clear from the simulation that for any π , if ALG running on \mathcal{F}_π satisfies (8) for at least $(1/L)$ -fraction of leaves in U_L^* , then we win the game when π is the shuffling we get by combining our own random samples at the beginning with hidden bijections in the game. Using the promise about ALG at the beginning, we get a randomized algorithm that succeeds in the game with probability

at least $2/(3L)$ when the hidden bijections are drawn independently and uniformly at random. On the other hand, if the query complexity of **ALG** is q , then our simulation uses

$$q \cdot \left(\frac{k}{\epsilon}\right)^2 + d^{L-1} \cdot k$$

Combining with Claim 4.10 we have $q = \Omega(n^{1+\epsilon}/k^3)$. □

5 Insertion-only streams under a cardinality constraint

We consider insertion-only streams and give a deterministic $(1 - 1/e - \epsilon)$ -approximation algorithm with $O(\log(k/\epsilon)/\epsilon^2)$ amortized query complexity. As discussed in Remark 2.1, our algorithm does not need to know the ground set V or the number of rounds n at the beginning.

Theorem 1.3. *Given any $\epsilon > 0$, there is a deterministic algorithm that achieves an approximation guarantee of $1 - 1/e - \epsilon$ for dynamic submodular maximization under cardinality constraint k over insertion-only streams. The amortized query complexity of the algorithm is $O(\log(k/\epsilon)/\epsilon^2)$.*

To prove Theorem 1.3, we give a deterministic algorithm with the following performance guarantees. We follow standard arguments to finish the proof of Theorem 1.3 in Appendix C.

Lemma 5.1. *There is a deterministic algorithm that satisfies the following performance guarantees. Given a positive integer k , $\epsilon > 0$ and $\text{OPT} > 0$, the algorithm runs on an insertion-only stream and outputs a set $S_t \subseteq V_t$ of size at most k at the end of each round t such that (1) $S_1 \subseteq S_2 \subseteq \dots$ and (2) when $\text{OPT}_t \geq \text{OPT}$ for the first time, S_t must satisfy $f(S_t) \geq (1 - 1/e - \epsilon) \text{OPT}$. The amortized query complexity of the algorithm is $O(1/\epsilon)$.*

Proof. The algorithm is described in Algorithm 3 with $\Delta := \epsilon \text{OPT} / (k)$. We first run INITIALIZE and then run INSERT(e_t) when the t -th element e_t is inserted in the stream. It outputs S at the end of INSERT(e_t) as S_t . It is clear that $S_1 \subseteq S_2 \subseteq \dots$ given that the algorithm only grows S by adding elements to it.

We prove the approximation guarantee of the algorithm. Let t be the first time $\text{OPT}_t \geq \text{OPT}$. We first consider the case when $|S_t| = k$. Let $S_t = \{s_1, \dots, s_k\}$ where s_i is the i -th element inserted to S . Let $T_i = \{s_1, \dots, s_i\}$ for each $i \in [0 : k]$ (so $T_k = S_t$ and $T_0 = \emptyset$ with $f(T_0) = 0$). Given that

$$f_S(e) \geq \frac{\text{OPT} - f(S)}{k} - \Delta,$$

whenever the algorithm adds an element e to S (line 7 and line 18), we have

$$f_{T_i}(s_{i+1}) \geq \frac{\text{OPT} - f(T_i)}{k} - \Delta$$

Algorithm 3 Dynamic submodular maximization with a cardinality constraint.

```

1: procedure INITIALIZE( $k, \epsilon, \text{OPT}$ )
2:   Initialize  $S = \emptyset$ ,  $\Delta = \epsilon \text{OPT} / k$  and  $B_\ell = \emptyset$  for each  $\ell = 0, 1, \dots, \lfloor 1/\epsilon \rfloor$ 
3: end procedure
4:
5: procedure INSERT( $e$ )
6:   if  $f_S(e) \geq (\text{OPT} - f(S))/k - \Delta$  and  $|S| < k$  then
7:     Update  $S \leftarrow S \cup \{e\}$  and call REVOKE
8:   else
9:     Update  $B_\ell \leftarrow B_\ell \cup \{e\}$  with  $\ell = \lfloor f_S(e)/\Delta \rfloor$   $\triangleright \ell \leq \lfloor 1/\epsilon \rfloor$  given  $f_S(e) < \text{OPT}/k$ 
10:  end if
11: end procedure
12:
13: procedure REVOKE
14:   Let  $r = \lfloor (\text{OPT} - f(S))/(k\Delta) \rfloor$ .
15:   if  $|S| < k$  and there exists an index  $\ell \geq r$  with  $B_\ell \neq \emptyset$  then
16:     Let  $\ell$  be any such index and let  $e'$  be any element in  $B_\ell$ .
17:     if  $f_S(e') \geq (\text{OPT} - f(S))/k - \Delta$  then
18:       Update  $S \leftarrow S \cup \{e'\}$  and  $B_\ell \leftarrow B_\ell \setminus \{e'\}$ 
19:     else
20:       Update  $B_\ell \leftarrow B_\ell \setminus \{e'\}$ ,  $B_{\ell'} \leftarrow B_{\ell'} \cup \{e'\}$  with  $\ell' = \lfloor f_S(e')/\Delta \rfloor$   $\triangleright 0 \leq \ell' < r \leq \ell$ 
21:     end if
22:     Go to Line 14.
23:   end if
24: end procedure

```

for each $i \in [k]$. By standard calculation, one has

$$\begin{aligned}
\text{OPT} - f(S_t) &= \text{OPT} - f(T_k) = \text{OPT} - f(T_{k-1}) - f_{T_{k-1}}(s_k) \\
&\leq \text{OPT} - f(T_{k-1}) - \frac{\text{OPT} - f(T_{k-1})}{k} + \Delta \\
&= \left(1 - \frac{1}{k}\right) (\text{OPT} - f(T_{k-1})) + \Delta \\
&\quad \vdots \\
&\leq \left(1 - \frac{1}{k}\right)^k (\text{OPT} - f(T_0)) + k\Delta \\
&\leq \frac{1}{e} \cdot \text{OPT} + \epsilon \cdot \text{OPT}.
\end{aligned}$$

which implies that $f(S_t) \geq (1 - 1/e - \epsilon) \text{OPT}$.

Next consider the case when $|S_t| < k$. In this case we have that every element inserted is either in S_t or in one of the buckets B_ℓ . Let the optimal solution be $O_t = \{o_1, \dots, o_k\}$ and let

$$r = \left\lfloor \frac{\text{OPT} - f(S_t)}{k\Delta} \right\rfloor.$$

Then at the end of round t (after INSERT), we must have that every o_i with $o_i \notin S_t$ lies in a bucket

B_ℓ with $\ell < r$ and thus,

$$f_{S_t}(o_i) < (\ell + 1)\Delta \leq r\Delta \leq \frac{\text{OPT} - f(S_t)}{k}. \quad (9)$$

This is because the algorithm makes sure that at any time, any element $e' \in B_\ell$ satisfies $f_S(e') < (\ell + 1)\Delta$. To see this is the case, we note that the inequality holds when e' is added to B_ℓ and that S only grows over time. We conclude that $f(S_t) \geq (1 - \epsilon)\text{OPT}$; otherwise, one has

$$\text{OPT} \leq f(O_t) \leq f(S_t) + \sum_{i \in [k]} f_{S_t}(o_i) < f(S_t) + \sum_{i=1}^k \frac{\text{OPT} - f(S_t)}{k} = \text{OPT},$$

a contradiction. The second step above follows from the submodularity and monotonicity, the third step follows from Eq. (9) and $f(S_t) < (1 - \epsilon)\text{OPT}$.

Finally we bound the amortized query complexity of the algorithm. We charge the two queries made in the evaluation of $f_S(e)$ (line 6 or 17) to e and show that the number of queries charged to e is at most $O(1/\epsilon)$. To see this, we note that e is charged twice when it is just inserted. Every time e is charged during REVOKE, either it is added to S so that it is never charged again, or it gets moved to a bucket with a strictly smaller ℓ , which can only happen $O(1/\epsilon)$ many times. \square

6 Insertion-only stream: efficient algorithm for matroid constraints

We present an efficient $(1 - 1/e - \epsilon)$ -approximation algorithm under the general matroid constraint. We first give a $(1/2 - \epsilon)$ -approximate deterministic combinatorial algorithm (Section 6.1), we then embed it into the accelerated continuous greedy framework of [BV14] to achieve $(1 - 1/e - \epsilon)$ approximation (Section 6.2).

6.1 The combinatorial algorithm

Given k as the rank of the matroid \mathcal{M} , we define L, R and \mathcal{A} as

$$L = \left\lceil \frac{\log(k/\epsilon)}{\epsilon} \right\rceil, \quad R = \left\lceil \frac{2\log(k/\epsilon)}{\epsilon^2} \right\rceil \quad \text{and} \quad \mathcal{A} = \left\{ (a_1, \dots, a_L) \in \mathbb{Z}_{\geq 0}^L : \sum_{\ell \in [L]} a_\ell \leq R \right\}.$$

We note the size of \mathcal{A} can be upper bounded by

$$|\mathcal{A}| = \sum_{d=0}^R \binom{d+L-1}{L-1} \leq (R+1) \cdot \binom{R+L-1}{L-1} \leq (R+1) \left(\frac{2eR}{L} \right)^L = k^{\tilde{O}(1/\epsilon)}. \quad (10)$$

Both of our deterministic algorithm and randomized algorithm use a deterministic subroutine called PRUNE-GREEDY described in Algorithm 4. The inputs of PRUNE-GREEDY include k as the rank of the underlying matroid \mathcal{M} , a positive number OPT , a tuple $a \in \mathcal{A}$, as well as query access to both f and \mathcal{M} . When running on an insertion-only stream, PRUNE-GREEDY may decide to terminate at the end of a round and output a set S . A complication due to the application of this subroutine in the randomized algorithm is that we will give it query access to a perturbed version of f : We say $h : V \rightarrow \mathbb{R}$ is a κ -close of f if $h(S) = f(S) \pm \kappa$ for every $S \subseteq V$.

We state its performance guarantees in the following lemma:

Algorithm 4 PRUNE-GREEDY

1: **procedure** INITIALIZE($k, \text{OPT}, a, h, \mathcal{M}$) $\triangleright a \in \mathcal{A}$
2: Initialize $S \leftarrow \emptyset$ and $c_\ell \leftarrow a_\ell \Delta$ for each $\ell \in [L]$, where

$$\Delta := \frac{\epsilon^2 \text{OPT}}{\log(k/\epsilon)}.$$

3: Let ℓ^* be the smallest $\ell \in [L]$ with $c_\ell > 0$
4: **end procedure**
5:
6: **procedure** INSERT(e)
7: **if** $S \cup e \in \mathcal{M}$ and $h_S(e) \geq (1 + \epsilon)^{-\ell^*} \text{OPT}$ **then**
8: Update $c_{\ell^*} \leftarrow c_{\ell^*} - h_S(e)$ and $S \leftarrow S \cup \{e\}$
9: **if** $c_{\ell^*} \leq 0$ **then**
10: Call REVOKE
11: **end if**
12: **end if**
13: **end procedure**
14:
15: **procedure** REVOKE
16: Update ℓ^* to be the smallest ℓ with $c_\ell > 0$; **Terminate** and return S **if** no such ℓ exists
17: **for** each element e_i inserted so far (in the order of insertions) **do**
18: **if** $S \cup e_i \in \mathcal{M}$ and $h_S(e_i) \geq (1 + \epsilon)^{-\ell^*} \text{OPT}$ **then**
19: Update $c_{\ell^*} \leftarrow c_{\ell^*} - h_S(e_i)$ and $S \leftarrow S \cup \{e_i\}$,
20: **end if**
21: **end for**
22: Go to line 16 **if** $c_{\ell^*} \leq 0$
23: **end procedure**

Lemma 6.1. *There is a deterministic algorithm that, given a positive integer k , $\text{OPT} > 0$, $a \in \mathcal{A}$ and query access to a matroid \mathcal{M} over V of rank k and a function $h : V \rightarrow \mathbb{R}$ that is κ -close to a nonnegative and monotone submodular function $f : V \rightarrow \mathbb{R}$, where $\kappa = \epsilon^3 \text{OPT} / k$. The algorithm runs on insertion-only streams with amortized query complexity $O(L)$ and has the following performance guarantee. Given any insertion-only stream e_1, \dots, e_t such that $\text{OPT} \leq \text{OPT}_t \leq (1 + \epsilon) \text{OPT}$, there exists an $a^* \in \mathcal{A}$ such that when given OPT and a^* as input, the algorithm terminates before the end of round t and outputs a feasible set $S \subseteq V_t$ that satisfies*

$$f(S) \geq (1 - O(\epsilon))f_S(O), \quad \text{for any set } O \text{ such that } O \in \mathcal{M} \text{ and } O \subseteq V_t.$$

Proof. The algorithm is described in Algorithm 4, with

$$\Delta := \frac{\epsilon^2 \text{OPT}}{\log(k/\epsilon)}.$$

Let e_1, \dots, e_t be the stream with $\text{OPT} \leq \text{OPT}_t \leq (1 + \epsilon) \text{OPT}$. To specify the $a^* \in \mathcal{A}$ in the statement of the lemma, we consider the following L -pass greedy algorithm. The algorithm maintains a set $T \in \mathcal{M}$. It starts with $T = \emptyset$ and updates $T \rightarrow T \cup T_\ell$ at the end of the ℓ -th pass (so we have $T = T_1 \cup \dots \cup T_\ell$ at the end of the ℓ -th pass). During the ℓ -th pass, we set $S_\ell = \emptyset$ and go through e_1, \dots, e_t . For each e_i , the algorithm checks if $T \cup S_\ell \cup \{e_i\} \in \mathcal{M}$ and

$h_{T \cup S_\ell}(e_i) \geq (1 + \epsilon)^{-(\ell-1)} \text{OPT}$. If so, e_i is added to S_ℓ . At the end of the ℓ -th pass, we do *not* add all elements S_ℓ to T . Instead, we further prune S_ℓ to get T_ℓ : Let e_{i_1}, e_{i_2}, \dots be elements added to S_ℓ during the ℓ -th pass. T_ℓ is set to be $\{e_{i_1}, \dots, e_{i_j}\}$ such that j is the smallest integer such that

$$h_{T_1 \cup \dots \cup T_{\ell-1}}(T_\ell) \geq \Delta \left\lfloor \frac{h_{T_1 \cup \dots \cup T_{\ell-1}}(S_\ell)}{\Delta} \right\rfloor,$$

where $T_\ell = \emptyset$ when the RHS above is 0. This finishes the ℓ -th pass and the algorithm updates T with $T \cup T_\ell$. Let (S_1, \dots, S_L) and (T_1, \dots, T_L) be the two sequences of sets obtained from this L -pass algorithm. Let $a^* \in \mathbb{Z}_{\geq 0}^L$ be defined as $a_\ell^* = \lfloor h_{T_1 \cup \dots \cup T_{\ell-1}}(S_\ell) / \Delta \rfloor$ for each $\ell \in [L]$. It is easy to see that

$$\begin{aligned} \Delta \sum_{\ell \in [L]} a_\ell^* &= \Delta \sum_{\ell \in [L]} \left\lfloor \frac{h_{T_1 \cup \dots \cup T_{\ell-1}}(S_\ell)}{\Delta} \right\rfloor \\ &\leq \sum_{\ell=1}^L h_{T_1 \cup \dots \cup T_{\ell-1}}(T_\ell) \leq f(T) + 2\kappa < 2 \text{OPT}. \end{aligned}$$

Hence $\sum_{\ell \in [L]} a_\ell^* \leq R$ and thus, $a^* \in \mathcal{A}$. The following lemma connects PRUNE-GREEDY with this L -pass greedy algorithm:

Lemma 6.2. *Suppose that PRUNE-GREEDY is given a^* at the beginning, then it terminates before the end of the t -th round and outputs exactly $T = T_1 \cup \dots \cup T_L$.*

Given Lemma 6.2, it suffices to prove that

$$f(T) \geq (1 - O(\epsilon))f_T(O), \quad \text{for every feasible set } O \subseteq V_t.$$

Fix an $O \in \mathcal{M}$ and $O \subseteq V_t$. The following Lemma is a folklore.

Lemma 6.3. *Let \mathcal{M} be a matroid and $T \in \mathcal{M}$ with $T = T_1 \cup \dots \cup T_L$ such that T_1, \dots, T_L are pairwise disjoint. Then any $O \in \mathcal{M}$ can be partitioned into pairwise disjoint O_1, \dots, O_L such that*

1. *If $|O| \geq |T|$ then $|O_i| = |T_i|$ for all $i < L$; If $|O| < |T|$, letting ℓ be the smallest integer such that $|O| \leq \sum_{i < \ell} |T_i|$, then $|O_i| = |T_i|$ for all $i < \ell$ and $|O_\ell| = |O| - \sum_{i < \ell} |O_i|$. (Note that we always have $|O_i| \leq |T_i|$ except for $i = L$.)*
2. *For all $i < j$, $T_i \cap O_j = \emptyset$ and for every $i < L$,*

$$T_1 \cup \dots \cup T_i \cup O_{i+1} \cup \dots \cup O_L \in \mathcal{M}.$$

Recall S_1, \dots, S_L from the L -pass greedy algorithm. We have for every $\ell \in [L]$,

$$T_1 \cup \dots \cup T_{\ell-1} \cup S_\ell \in \mathcal{M}.$$

For the analysis we partition O into pairwise disjoint sets $E_0, E_1, \dots, E_{L-2}, P_1, \dots, P_L$ as follows.

1. $P_1 = O_1$;
2. For each $\ell \geq 2$ and each $o \in O_\ell$, we consider two cases. If $T_1 \cup \dots \cup T_{\ell-2} \cup S_{\ell-1} \cup \{o\} \in \mathcal{M}$ then we have $o \in P_\ell$; otherwise, we have $o \in E_r$ where $r \geq 0$ is the largest integer such that $T_1 \cup \dots \cup T_{r-1} \cup S_r \cup \{o\} \in \mathcal{M}$ and $T_1 \cup \dots \cup T_r \cup S_{r+1} \cup \{o\} \notin \mathcal{M}$. Note that $r \leq \ell - 2$ and such an $r \geq 0$ always exists given that the condition when $r = 0$ is just that $\{o\} \in \mathcal{M}$.

The following claim about the size of E_ℓ follows from the definition, the detailed proof can be found at Appendix D.

Claim 6.4. $|E_\ell| \leq |S_{\ell+1} \setminus T_{\ell+1}|$.

Now we have

$$\begin{aligned} f_T(O) &\leq \sum_{\ell \in [L]} f_{T_1 \cup \dots \cup T_{\ell-1}}(O_\ell) \\ &\leq f(O_1) + \sum_{\ell \in [2:L]} \sum_{r \in [0:\ell-2]} f_{T_1 \cup \dots \cup T_{\ell-1}}(O_\ell \cap E_r) + \sum_{\ell \in [2:L]} f_{T_1 \cup \dots \cup T_{\ell-1}}(P_\ell), \end{aligned} \quad (11)$$

where both steps follow from the submodularity of f .

We first bound the first and last term.

Lemma 6.5. *We have*

$$f(O_1) + \sum_{\ell \in [2:L]} f_{T_1 \cup \dots \cup T_{\ell-1}}(P_\ell) \leq (1 + \epsilon)f(T) + 6\epsilon \text{OPT}.$$

We will need the following fact, the proof can be found at Appendix D:

Fact 6.6. *Suppose f is a monotone submodular function. For any three sets A, B and C we have*

$$f_A(C) \leq f_{A \cup B}(C) + f_A(B).$$

Proof of Lemma 6.5. Recall that for every $o \in P_\ell$ with $\ell \geq 2$, we have $T_1 \cup \dots \cup T_{\ell-2} \cup S_{\ell-1} \cup \{o\} \in \mathcal{M}$. We have

$$\begin{aligned} \sum_{\ell \in [2:L]} f_{T_1 \cup \dots \cup T_{\ell-1}}(P_\ell) &\leq \sum_{\ell \in [2:L]} f_{T_1 \cup \dots \cup T_{\ell-2} \cup S_{\ell-1}}(P_\ell) + f_{T_1 \cup \dots \cup T_{\ell-1}}(S_{\ell-1} \setminus T_{\ell-1}) \\ &\leq \sum_{\ell \in [2:L]} f_{T_1 \cup \dots \cup T_{\ell-2} \cup S_{\ell-1}}(P_\ell) + 2\epsilon \text{OPT} \\ &\leq \sum_{\ell \in [2:L]} \sum_{o \in P_\ell} f_{T_1 \cup \dots \cup T_{\ell-2} \cup S_{\ell-1}}(o) + 2\epsilon \text{OPT} \\ &\leq \sum_{\ell \in [2:L]} |O_\ell| (1 + \epsilon)^{-\ell+2} \text{OPT} + 3\epsilon \text{OPT} \end{aligned}$$

The first step comes from Fact 6.6. The second step follows from

$$\begin{aligned} f_{T_1 \cup \dots \cup T_{\ell-1}}(S_{\ell-1} \setminus T_{\ell-1}) &= f_{T_1 \cup \dots \cup T_{\ell-2}}(S_{\ell-1}) - f_{T_1 \cup \dots \cup T_{\ell-2}}(T_{\ell-1}) \\ &\leq h_{T_1 \cup \dots \cup T_{\ell-2}}(S_{\ell-1}) - h_{T_1 \cup \dots \cup T_{\ell-2}}(T_{\ell-1}) + 4\kappa \\ &\leq h_{T_1 \cup \dots \cup T_{\ell-2}}(S_{\ell-1}) - \Delta \left\lfloor \frac{h_{T_1 \cup \dots \cup T_{\ell-2}}(S_{\ell-1})}{\Delta} \right\rfloor + 4\kappa \\ &\leq \Delta + 4\kappa \end{aligned} \quad (12)$$

and that $(\Delta + 4\kappa)L \leq 2\epsilon \text{OPT}$. The third step comes from the submodularity. The fourth step holds since $T_1 \cup \dots \cup T_{\ell-2} \cup S_{\ell-1} \cup \{o\}$ is feasible for each $o \in P_\ell$, by the L -pass greedy algorithm,

$$f_{T_1 \cup \dots \cup T_{\ell-2} \cup S_{\ell-1}}(o) \leq h_{T_1 \cup \dots \cup T_{\ell-2} \cup S_{\ell-1}}(o) + \kappa \leq (1 + \epsilon)^{-\ell+2} \text{OPT} + \kappa$$

and that $k\kappa \leq \epsilon \text{OPT}$. On the other hand, we have $f(O_1)$ is 0 if $|O_1| = 0$ or when $|O_1| > 0$ (and thus, $|T_1| > 0$),

$$f(O_1) \leq \text{OPT}_t \leq (1 + \epsilon) \text{OPT} \leq |O_1|(1 + \epsilon) \text{OPT}.$$

In summary, we have

$$\begin{aligned} f(O_1) + \sum_{\ell \in [2:L]} f_{T_1 \cup \dots \cup T_{\ell-1}}(P_\ell) &\leq \sum_{\ell \in [L]} |O_\ell|(1 + \epsilon)^{-\ell+2} \text{OPT} + 3\epsilon \text{OPT} \\ &\leq \sum_{\ell \in [L-1]} |T_\ell|(1 + \epsilon)^{-\ell+2} \text{OPT} + 4\epsilon \text{OPT} \end{aligned}$$

where we used $k(1 + \epsilon)^{-L+2} \text{OPT} \leq \epsilon \text{OPT}$. To connect with $f(T)$, we have from the greedy algorithm that

$$f(T) = \sum_{\ell \in [L]} f_{T_1 \cup \dots \cup T_{\ell-1}}(T_\ell) \geq \sum_{\ell \in [L]} h_{T_1 \cup \dots \cup T_{\ell-1}}(T_\ell) - 2L\kappa \geq \sum_{\ell \in [L]} |T_\ell|(1 + \epsilon)^{-\ell+1} \text{OPT} - \epsilon \text{OPT}.$$

As a result, we have

$$f(O_1) + \sum_{\ell \in [2:L]} f_{T_1 \cup \dots \cup T_{\ell-1}}(P_\ell) \leq (1 + \epsilon)(f(T) + \epsilon \text{OPT}) + 4\epsilon \text{OPT} \leq (1 + \epsilon)f(T) + 6\epsilon \text{OPT}. \quad (13)$$

□

We bound the second term of Eq. (11) as follow.

Lemma 6.7. *We have*

$$\sum_{\ell \in [2:L]} \sum_{r \in [0:\ell-2]} f_{T_1 \cup \dots \cup T_{\ell-1}}(O_\ell \cap E_r) \leq 8\epsilon \text{OPT}.$$

Proof. The proof can be derived via the following chain of inequalities.

$$\begin{aligned}
\sum_{\ell \in [2:L]} \sum_{r \in [0:\ell-2]} f_{T_1 \cup \dots \cup T_{\ell-1}}(O_\ell \cap E_r) &= \sum_{r \in [0:L-2]} \sum_{\ell \in [r+2:L]} f_{T_1 \cup \dots \cup T_{\ell-1}}(O_\ell \cap E_r) \\
&\leq \sum_{r \in [0:L-2]} f_{T_1 \cup \dots \cup T_r}(E_r) \\
&\leq \sum_{r \in [0:L-2]} f_{T_1 \cup \dots \cup T_{r-1} \cup S_r}(E_r) + \sum_{r \in [0:L-2]} f_{T_1 \cup \dots \cup T_r}(S_r \setminus T_r) \\
&\leq \sum_{r \in [0:L-2]} f_{T_1 \cup \dots \cup T_{r-1} \cup S_r}(E_r) + 2\epsilon \text{OPT} \\
&\leq \sum_{r \in [0:L-2]} \sum_{o \in E_r} f_{T_1 \cup \dots \cup T_{r-1} \cup S_r}(o) + 2\epsilon \text{OPT} \\
&\leq \sum_{r \in [0:L-2]} \sum_{o \in E_r} h_{T_1 \cup \dots \cup T_{r-1} \cup S_r}(o) + 3\epsilon \text{OPT} \\
&\leq \sum_{r \in [0:L-2]} |E_r| (1 + \epsilon)^{-r+1} \text{OPT} + 3\epsilon \text{OPT} \\
&\leq \sum_{r \in [0:L-2]} |S_{r+1} \setminus T_{r+1}| (1 + \epsilon)^{-r+1} \text{OPT} + 3\epsilon \text{OPT} \\
&\leq (1 + \epsilon) \sum_{r=0}^{L-2} f_{T_1 \cup \dots \cup T_{r+1}}(S_{r+1} \setminus T_{r+1}) + 4\epsilon \text{OPT} \\
&\leq 8\epsilon \text{OPT}. \tag{14}
\end{aligned}$$

The second step holds due to the submodularity and monotonicity. The third step holds due to Fact 6.6, and the fourth step holds due to Eq. (12). The fifth step follows from submodularity. The sixth step holds since h is κ -close to f and using $2k\kappa \leq \epsilon \text{OPT}$. The seventh step holds since every $o \in E_r$ has $T_1 \cup \dots \cup T_{r-1} \cup S_r \cup \{o\} \in \mathcal{M}$. Hence, it follows from the L -pass greedy algorithm that

$$h_{T_1 \cup \dots \cup T_{r-1} \cup S_r}(o) \leq (1 + \epsilon)^{-r+1} \text{OPT}.$$

The seventh step holds due to Claim 6.4 that $|E_r| \leq |S_{r+1} \setminus T_{r+1}|$. The eighth step holds since

$$f_{T_1 \cup \dots \cup T_{r+1}}(S_{r+1} \setminus T_{r+1}) \geq h_{T_1 \cup \dots \cup T_{r+1}}(S_{r+1} \setminus T_{r+1}) - \kappa \geq |S_{r+1} \setminus T_{r+1}| (1 + \epsilon)^{-r} \text{OPT} - \kappa,$$

and the last step holds due to (12). \square

Combining Lemma 6.5, Lemma 6.7 and Eq. (11), we have $f_T(O) \leq (1 + \epsilon)f(T) + 11\epsilon \text{OPT}$. Since this holds for all feasible sets, and in particular, it holds for the set O_t . Taking a linear combination, we have

$$f(T) \geq \frac{1}{1 + \epsilon} ((1 - 11\epsilon)f_T(O) + 11\epsilon f_T(O_t) - 11\epsilon \text{OPT}) \geq \frac{1}{1 + \epsilon} ((1 - 11\epsilon)f_T(O) - 11\epsilon f(T)).$$

Rearranging the term, we get the desired.

Finally, we bound the amortized query complexity of the algorithm. We charge the two queries made in the evaluation of $h_S(e)$ (line 7 or 18) to e and show that the number of queries charged to e is at most $O(L)$. To see this, we note that e is charged twice when it is just inserted. Every time e is charged during REVOKE, either it is added to S so that it is never charged again, or its marginal contribution is small and won't be queried in the ℓ -th level later. Hence, e has been queried for at most $O(L)$ times. We conclude the proof here. \square

By standard argument, we conclude

Lemma 6.8. *Given a matroid \mathcal{M} , let $t > 0$, $\text{OPT} \leq \text{OPT}_t \leq (1 + \epsilon) \text{OPT}$. After inserting the t -th element, our algorithm outputs a feasible set S that satisfies $f(S) \geq (1/2 - O(\epsilon)) \text{OPT}$. The expected number of oracles per operation is $k^{\tilde{O}(1/\epsilon)}$.*

The proof can be found at Appendix D. Combine with Lemma C.1, we have

Theorem 6.9. *Given any matroid \mathcal{M} , for any $\epsilon > 0$, there is a combinatorial algorithm that maintains a feasible set S with $(1/2 - \epsilon)$ -approximation at each iteration. Moreover, the amortized number of queries per update is $k^{\tilde{O}(1/\epsilon)}$.*

6.2 Amplification via accelerated continuous greedy

We amplify the approximation ratio of the combinatorial algorithm via the accelerated continuous greedy framework [BV14]. Let $m = O(1/\epsilon)$ and

$$D = \{\text{OPT}, (1 + \epsilon)^{-1} \text{OPT}, \dots, (1 + \epsilon)^{-\lceil 4 \log(1/\epsilon)/\epsilon \rceil} \text{OPT}\} \cup \{0\}.$$

We run a separate branch for each $\mathbf{d} \in D^m$ and $\mathbf{a} \in \mathcal{A}^m$. Intuitively, $d_\tau \in D$ should be seen as an estimate on the progress of optimal solution in the τ -th iteration, and $a_\tau \in \mathcal{A}$ is a guess on the greedy sequence. Our algorithm segregates answer from all branches and outputs the one with the maximum value. In order to return an integral solution, the algorithm rounds the fractional solution via the swap rounding approach [CVZ10]. The algorithm description is presented in Algorithm 5.

Algorithm 5 Amplification via accelerated continuous greedy

- 1: **Input:** $\mathbf{d} \in D^m, \mathbf{a} \in \mathcal{A}^m$
 - 2: Initialize $\mathbf{x} \leftarrow \mathbf{0}$
 - 3: **for** $\tau = 1, 2, \dots, m$ **do**
 - 4: Define $g(S) = F(\mathbf{x} + \frac{1}{m}S) - F(\mathbf{x})$ for all $S \subseteq V$
 - 5: Invoke PRUNE-GREEDY(d_τ, a_τ, g), and wait until it returns a solution S_τ
 - 6: $\mathbf{x} \leftarrow \mathbf{x} + \frac{1}{m}S_\tau$
 - 7: **end for**
-

We need the following lemma in our analysis. The proof idea follows from [BV14] and it appears in [BRS19b]. It has some minor difference with previous work and we provide a proof for completeness.

Lemma 6.10. *Let $\text{OPT} \leq \text{OPT}_t \leq (1 + \epsilon) \text{OPT}$. Suppose in each iteration of Algorithm 5, PRUNE-GREEDY returns a set S that satisfies*

$$g(S) \geq (1 - O(\epsilon)) \sum_{i \in [L]} g_{S \setminus (O_i \cup \dots \cup O_L)}(O_i) - \epsilon^2 \text{OPT}, \quad (15)$$

for some partition $O = O_1 \cup \dots \cup O_L$ of O and some partition $S = S_1 \cup \dots \cup S_L$ of S such that $\forall i \in [L], S_1 \cup \dots \cup S_i \cup O_{i+1} \cup \dots \cup O_L \in \mathcal{M}$ and $S_i \cap (O_{i+1} \cup \dots \cup O_L) = \emptyset$. Then the final solution \mathbf{x} satisfies

$$F(\mathbf{x}) \geq (1 - 1/e - O(\epsilon)) \text{OPT}.$$

Proof. For any $\tau \in [m]$, let \mathbf{x}_τ denote the fractional solution at the end of τ -th iteration, i.e. after the update at Line 6 of Algorithm 5. The we claim

$$F(\mathbf{x}_\tau) - F(\mathbf{x}_{\tau-1}) \geq \frac{1}{m}(1 - O(\epsilon))(F(O) - F(\mathbf{x}_{\tau-1})) - \epsilon^2 \text{OPT}. \quad (16)$$

This is true since whenever $g(S) = F(\mathbf{x}_\tau) - F(\mathbf{x}_{\tau-1}) \leq \frac{1}{m}(F(O) - F(\mathbf{x}_{\tau-1}))$, one has

$$\begin{aligned} F(\mathbf{x}_\tau) - F(\mathbf{x}_{\tau-1}) &= g(S) \geq (1 - O(\epsilon)) \sum_{i \in [L]} g_{S \setminus (O_i \cup \dots \cup O_L)}(O_i) - \epsilon^2 \text{OPT} \\ &\geq \frac{1}{m} \left(1 - \frac{1}{m}\right) (1 - O(\epsilon))(F(O) - F(\mathbf{x}_{\tau-1})) - \epsilon^2 \text{OPT} \\ &= \frac{1}{m}(1 - O(\epsilon))(F(O) - F(\mathbf{x}_{\tau-1})) - \epsilon^2 \text{OPT} \end{aligned}$$

where the second step follows from the assumption (see Eq. (15)), the third step follows from Claim 6.11 below and the last step follows from the choice of parameter $m = O(1/\epsilon)$.

Recurring the Equation (16) for all $\tau \in [m]$, via standard calculation, one can show that

$$F(T) \geq (1 - 1/e - O(\epsilon))F(O) = (1 - 1/e - O(\epsilon)) \text{OPT}. \quad \square$$

Claim 6.11 (Adapted from Lemma 7 in [BRS19b]). *For any $\tau \in [m]$, suppose that*

$$g(S) \leq \frac{1}{m} (F(O) - F(\mathbf{x}_{\tau-1})),$$

then we have

$$\sum_{i \in [L]} g_{S \setminus (O_i \cup \dots \cup O_L)}(O_i) \geq \frac{1}{m} \left(1 - \frac{1}{m}\right) (F(O) - F(\mathbf{x}_{\tau-1})).$$

Proof. We have

$$\begin{aligned} \sum_{i \in [L]} g_{S \setminus (O_i \cup \dots \cup O_L)}(O_i) &= \sum_{i \in [L]} F_{\mathbf{x}_{\tau-1} + \frac{1}{m} S \setminus (O_i \cup \dots \cup O_L)} \left(\frac{1}{m} O_i \right) \\ &\geq \sum_{i \in [L]} F_{\mathbf{x}_{\tau-1} + (O_1 \cup \dots \cup O_{i-1}) + \frac{1}{m} S} \left(\frac{1}{m} O_i \right) \\ &\geq \frac{1}{m} \sum_{i \in [L]} F_{\mathbf{x}_{\tau-1} + O_{1:i-1} + \frac{1}{m} S}(O_i) = \frac{1}{m} F_{\mathbf{x}_{\tau-1} + \frac{1}{m} S}(O), \end{aligned}$$

where the first step follows from $S \setminus (O_i \cup \dots \cup O_L) \cap O_i = \emptyset$, the second step follows from submodularity, the third step follows from multi-linearity. Moreover, we have

$$\begin{aligned} F_{\mathbf{x}_{\tau-1} + \frac{1}{m} S}(O) &= F_{\mathbf{x}_{\tau-1}} \left(O + \frac{1}{m} S \right) - F_{\mathbf{x}_{\tau-1}} \left(\frac{1}{m} S \right) \geq F_{\mathbf{x}_{\tau-1}}(O) - \frac{1}{m} (F(O) - F(\mathbf{x}_{\tau-1})) \\ &\geq \left(1 - \frac{1}{m}\right) (F(O) - F(\mathbf{x}_{\tau-1})), \end{aligned}$$

where the second step comes from the condition that $g(S) \leq \frac{1}{m}(F(O) - F(\mathbf{x}_{\tau-1}))$. Combining the above two inequalities, we conclude the proof. \square

Theorem 1.4. *Given any $\epsilon > 0$, there is a randomized algorithm that achieves an approximation guarantee of $1 - 1/e - \epsilon$ for dynamic submodular maximization under matroid constraints over insertion-only streams. The amortized query complexity of the algorithm is $k^{\tilde{O}(1/\epsilon^2)} \log n$, where k is the rank of the matroid.*

Proof. With Lemma C.1, it suffices to prove for any t , when $\text{OPT} \leq \text{OPT}_t \leq (1 + \epsilon) \text{OPT}$, our algorithm returns a solution set S with $f(S) \geq (1 - 1/e - O(\epsilon)) \text{OPT}_t$. Let O be the optimal solution. For each $\tau = 1, \dots, m$ (with $\mathbf{x}_0 = 0$), we define $g^{(\tau)}$, $O^{(\tau)}$, d_τ , a_τ and S_τ round by round as follows:

1. First given $\mathbf{x}_{\tau-1}$ we define $g^{(\tau)}$ and $O^{(\tau)}$ as

$$g^{(\tau)}(S) := F\left(\mathbf{x}_{\tau-1} + \frac{1}{m}S\right) \quad \text{and} \quad O^{(\tau)} = \arg \max_{S \in \mathcal{M}} g^{(\tau)}(S).$$

2. Let ℓ be the integer that satisfies $(1 + \epsilon)^{-\ell} \text{OPT} \leq g^{(\tau)}(O^{(\tau)}) \leq (1 + \epsilon)^{-\ell+1} \text{OPT}$. When $\ell \leq \lceil 4 \log(1/\epsilon)/\epsilon \rceil$, we take $d_\tau = (1 + \epsilon)^{-\ell} \text{OPT}$ and we know $d_\tau \leq g^{(\tau)}(O^{(\tau)}) \leq (1 + \epsilon)d_\tau$; otherwise, we set $d_\tau = 0$. When $d_\tau = 0$, we set $S_\tau = \emptyset$ and set a_τ to be an arbitrary element in \mathcal{A} . When $d_\tau > 0$, we set $a_\tau \in \mathcal{A}$ in the same way as in the proof regarding $g^{(\tau)}$ and d_τ . We run Prune-Greedy on $g^{(\tau)}$ using d_τ and a_τ and let S_τ be the set it returns.

It is clear that the branch of the algorithm that runs with d and a defined above would return $\mathbf{x} = \frac{1}{m} \sum_{\tau \in [m]} S_\tau$. We prove below that each set S_τ satisfies

$$g^{(\tau)}(S_\tau) \geq (1 - O(\epsilon)) \sum_{i \in [L]} g_{S_\tau \setminus (O_i \cup \dots \cup O_L)}^{(\tau)}(O_i) - \epsilon^2 \text{OPT} \quad (17)$$

for some partition $O = O_1 \cup \dots \cup O_L$ of O and some partition $S_\tau = T_1 \cup \dots \cup T_L$ that satisfy for every $i \in [L]$, $T_1 \cup \dots \cup T_i \cup O_{i+1} \cup \dots \cup O_L \in \mathcal{M}$ and $T_i \cap (O_{i+1} \cup \dots \cup O_L) = \emptyset$; note that both partitions depend on τ . It follows from Lemma 6.10 that $F(\mathbf{x}) \geq (1 - 1/e - O(\epsilon)) \text{OPT}$. Given \mathbf{x} , we round the fractional solution to an integral one. The solution is the convex combination of at most $O(1/\epsilon)$ independent sets, it takes only $O(k^2/\epsilon)$ query to perform the swap rounding [CVZ10].

To prove Eq. (17), note that the right hand side of the first line of (11) is

$$\sum_{i \in [L]} g_{T_1 \cup \dots \cup T_{i-1}}^{(\tau)}(O_i).$$

where T_1, \dots, T_L is a partition of S_τ and O_1, \dots, O_L is a partition of O that satisfy for every $i \in [L]$, $T_1 \cup \dots \cup T_i \cup O_{i+1} \cup \dots \cup O_L \in \mathcal{M}$ and $T_i \cap (O_{i+1} \cup \dots \cup O_k) = \emptyset$. On the other hand, the second line of (11) can be bounded from above using Lemma 6.5 and Lemma 6.7 by

$$(1 + \epsilon)g^{(\tau)}(S_\tau) + O(\epsilon)g^{(\tau)}(O^{(\tau)}).$$

It follows from (11) that

$$g^{(\tau)}(S_\tau) \geq (1 - O(\epsilon)) \sum_{i \in [L]} g_{T_1 \cup \dots \cup T_{i-1}}^{(\tau)}(O_i) - O(\epsilon)g^{(\tau)}(O^{(\tau)}) \quad (18)$$

In addition we have

$$\sum_{i \in [L]} g_{T_1 \cup \dots \cup T_{i-1}}^{(\tau)}(O_i) \geq \sum_{\ell \in [L]} g_{S_\tau \setminus (O_\ell \cup \dots \cup O_L)}^{(\tau)}(O_\ell) \quad (19)$$

due to submodularity and the fact that $T_1 \cup \dots \cup T_{i-1} \in S_\tau$ and $T_1 \cup \dots \cup T_{i-1} \cap (O_i \cup \dots \cup O_L) = \emptyset$. Combining Eq. (18) and Eq. (19), we have

$$g^{(\tau)}(S_\tau) \geq (1 - O(\epsilon)) \sum_{i \in [L]} g_{S_\tau \setminus (O_i \cup \dots \cup O_L)}^{(\tau)}(O_i) - O(\epsilon) g^{(\tau)}(O^{(\tau)}). \quad (20)$$

To get rid of low order term, we note by Lemma 6.8 that

$$g^{(\tau)}(S_\tau) \geq \left(\frac{1}{2} - O(\epsilon) \right) g^{(\tau)}(O^{(\tau)}) - \epsilon^2 \text{OPT}, \quad (21)$$

the additive term comes when $d_\tau = 0$ and make RHS no more than 0 in that case. Adding Eq. (20) and Eq. (21), we proved Eq. (17).

For the amortized query complexity, the total number of branch equals

$$|\mathcal{A}^m| \cdot |D^m| = k^{\tilde{O}(1/\epsilon^2)} \cdot (1/\epsilon)^{\tilde{O}(1/\epsilon)} = k^{\tilde{O}(1/\epsilon^2)}.$$

For each branch, there are $O(1/\epsilon)$ iterations, and in each iteration, we run our combinatorial algorithm with a schedule sequence $a_\tau \in \mathcal{A}$. By Lemma 6.1, the amortized number of query (to function g) equals $O(L) = O(\log(k/\epsilon)/\epsilon)$. We note that in the accelerated continuous greedy algorithm, a query to function g is equivalent to two queries of the multilinear extension. To satisfy the requirement of Lemma 6.1, one evaluates the value of multilinear extension with error $\pm \epsilon^3/k$ and confidence $\delta = \frac{\epsilon}{\text{poly}(n) \cdot |\mathcal{A}^m| \cdot |D^m| \cdot L}$ using $\tilde{O}(\epsilon^{-8} k^2 \log n)$ queries to the original function f . Thus in total, the amortized number of query is at most

$$k^{\tilde{O}(1/\epsilon^2)} \cdot \epsilon^{-1} \cdot \epsilon^{-1} \log(k/\epsilon) \cdot \tilde{O}(\epsilon^{-8} k^2 \log n) = k^{\tilde{O}(1/\epsilon^2)} \log n.$$

Hence, the overall amortized query complexity is $k^{\tilde{O}(1/\epsilon^2)} \log n$. \square

7 Conclusions

We study the power and limitations of dynamic algorithms for submodular maximization. On the lower bound side, we prove a polynomial lower bound on the amortized query complexity for achieving a $(1/2 + \epsilon)$ -approximation, together with a linear lower bound for 0.584-approximation, under fully dynamic streams with insertions and deletions. On the algorithmic side, we develop efficient $(1 - 1/e)$ -approximation algorithms for insertion-only streams under both cardinality and matroid constraints. There are many interesting directions for further investigations:

- Many submodular functions important in practice can be accessed in white box models instead of query models, e.g., the MAX- k coverage problem, influence maximization (see [Pen21] for an example). Can ideas in this paper be extended to obtain upper/lower bounds on amortized time complexity for these problems?
- Can we extend results (algorithm or hardness) to non-monotone submodular maximization? As far as we know, there is no known constant-factor approximation algorithm with $\text{poly}(k)$ amortized query complexity for the non-monotone setting under fully dynamic streams. How does the dynamic model compare to the streaming model [AEF⁺20] under this setting?
- For matroid constraints, can one improve the query complexity to $O(\sqrt{k})$ over insertion-only streams? Also, for fully dynamic streams, there is no known constant-factor approximation algorithm with $\text{poly}(k)$ amortized queries for matroid constraints.

Acknowledgement

Research of X.C. and B.P. were supported in part by NSF grants CCF-1703925, IIS-1838154, CCF-2106429, CCF-2107187, CCF-1763970, CCF-1910700 and DMS-2134059. We would like to thank Paul Liu for pointing out a mistake in an earlier version of the paper.

References

- [AEF⁺20] Naor Alaluf, Alina Ene, Moran Feldman, Huy L. Nguyen, and Andrew Suh. Optimal Streaming Algorithms for Submodular Maximization with Cardinality Constraints. In *47th International Colloquium on Automata, Languages, and Programming (ICALP 2020)*, pages 6:1–6:19, 2020.
- [BENW15] Rafael Barbosa, Alina Ene, Huy Nguyen, and Justin Ward. The power of randomization: Distributed submodular maximization on massive datasets. In *International Conference on Machine Learning*, pages 1236–1244. PMLR, 2015.
- [BENW16] Rafael da Ponte Barbosa, Alina Ene, Huy L Nguyen, and Justin Ward. A new framework for distributed submodular maximization. In *2016 IEEE 57th Annual Symposium on Foundations of Computer Science (FOCS)*, pages 645–654. Ieee, 2016.
- [BF18] Niv Buchbinder and Moran Feldman. Submodular functions maximization problems., 2018.
- [BFS17] Niv Buchbinder, Moran Feldman, and Roy Schwartz. Comparing apples and oranges: Query trade-off in submodular maximization. *Mathematics of Operations Research*, 42(2):308–329, 2017.
- [BFSS15] Niv Buchbinder, Moran Feldman, Joseph Seffi, and Roy Schwartz. A tight linear time (1/2)-approximation for unconstrained submodular maximization. *SIAM Journal on Computing*, 44(5):1384–1402, 2015.
- [BH11] Maria-Florina Balcan and Nicholas JA Harvey. Learning submodular functions. In *Proceedings of the forty-third annual ACM symposium on Theory of computing*, pages 793–802, 2011.
- [BMKK14] Ashwinkumar Badanidiyuru, Baharan Mirzasoleiman, Amin Karbasi, and Andreas Krause. Streaming submodular maximization: Massive data summarization on the fly. In *Proceedings of the 20th ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 671–680, 2014.
- [BRS17] Eric Balkanski, Aviad Rubinfeld, and Yaron Singer. The limitations of optimization from samples. In *Proceedings of the 49th Annual ACM SIGACT Symposium on Theory of Computing*, pages 1016–1027, 2017.
- [BRS19a] Eric Balkanski, Aviad Rubinfeld, and Yaron Singer. An exponential speedup in parallel running time for submodular maximization without loss in approximation. In *Proceedings of the Thirtieth Annual ACM-SIAM Symposium on Discrete Algorithms*, pages 283–302. SIAM, 2019.

- [BRS19b] Eric Balkanski, Aviad Rubinfeld, and Yaron Singer. An optimal approximation for submodular maximization under a matroid constraint in the adaptive complexity model. In *Proceedings of the 51st Annual ACM SIGACT Symposium on Theory of Computing*, pages 66–77, 2019.
- [BS18a] Eric Balkanski and Yaron Singer. The adaptive complexity of maximizing a submodular function. In *Proceedings of the 50th Annual ACM SIGACT Symposium on Theory of Computing*, pages 1138–1151, 2018.
- [BS18b] Eric Balkanski and Yaron Singer. Approximation guarantees for adaptive sampling. In *International Conference on Machine Learning*, pages 384–393. PMLR, 2018.
- [BV14] Ashwinkumar Badanidiyuru and Jan Vondrák. Fast algorithms for maximizing submodular functions. In *Proceedings of the twenty-fifth annual ACM-SIAM symposium on Discrete algorithms*, pages 1497–1514. SIAM, 2014.
- [CCPV11] Gruia Calinescu, Chandra Chekuri, Martin Pal, and Jan Vondrák. Maximizing a monotone submodular function subject to a matroid constraint. *SIAM Journal on Computing*, 40(6):1740–1766, 2011.
- [CGQ15] Chandra Chekuri, Shalmoli Gupta, and Kent Quanrud. Streaming algorithms for submodular function maximization. In *International Colloquium on Automata, Languages, and Programming*, pages 318–330. Springer, 2015.
- [CQ19] Chandra Chekuri and Kent Quanrud. Parallelizing greedy for submodular set function maximization in matroids and beyond. In *Proceedings of the 51st Annual ACM SIGACT Symposium on Theory of Computing*, pages 78–89, 2019.
- [CVZ10] Chandra Chekuri, Jan Vondrák, and Rico Zenklusen. Dependent randomized rounding via exchange properties of combinatorial structures. In *2010 IEEE 51st Annual Symposium on Foundations of Computer Science*, pages 575–584. IEEE, 2010.
- [CVZ14] Chandra Chekuri, Jan Vondrák, and Rico Zenklusen. Submodular function maximization via the multilinear relaxation and contention resolution schemes. *SIAM Journal on Computing*, 43(6):1831–1879, 2014.
- [EN19] Alina Ene and Huy L Nguyen. Submodular maximization with nearly-optimal approximation and adaptivity in nearly-linear time. In *Proceedings of the Thirtieth Annual ACM-SIAM Symposium on Discrete Algorithms*, pages 274–282. SIAM, 2019.
- [ENV19] Alina Ene, Huy L Nguyen, and Adrian Vladu. Submodular maximization with matroid and packing constraints in parallel. In *Proceedings of the 51st annual ACM SIGACT symposium on theory of computing*, pages 90–101, 2019.
- [Fei98] Uriel Feige. A threshold of $\ln n$ for approximating set cover. *Journal of the ACM*, 45(4):634–652, 1998.
- [FMZ19] Matthew Fahrbach, Vahab Mirrokni, and Morteza Zadimoghaddam. Submodular maximization with nearly optimal approximation, adaptivity and query complexity. In *Proceedings of the Thirtieth Annual ACM-SIAM Symposium on Discrete Algorithms*, pages 255–273. SIAM, 2019.

- [FNFSZ20] Moran Feldman, Ashkan Norouzi-Fard, Ola Svensson, and Rico Zenklusen. The one-way communication complexity of submodular maximization with applications to streaming and robustness. In *Proceedings of the 52nd Annual ACM SIGACT Symposium on Theory of Computing*, pages 1363–1374, 2020.
- [FNFSZ21] Moran Feldman, Ashkan Norouzi-Fard, Ola Svensson, and Rico Zenklusen. Streaming submodular maximization with matroid and matching constraints. *arXiv preprint arXiv:2107.07183*, 2021.
- [FNS11] Moran Feldman, Joseph Naor, and Roy Schwartz. A unified continuous greedy algorithm for submodular maximization. In *2011 IEEE 52nd Annual Symposium on Foundations of Computer Science*, pages 570–579. IEEE, 2011.
- [GK11] Daniel Golovin and Andreas Krause. Adaptive submodularity: Theory and applications in active learning and stochastic optimization. *Journal of Artificial Intelligence Research*, 42:427–486, 2011.
- [KKT03] David Kempe, Jon Kleinberg, and Éva Tardos. Maximizing the spread of influence through a social network. In *Proceedings of the ninth ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 137–146, 2003.
- [LB11] Hui Lin and Jeff Bilmes. A class of submodular functions for document summarization. In *Proceedings of the 49th Annual Meeting of the Association for Computational Linguistics: Human Language Technologies*, pages 510–520, 2011.
- [LMNF⁺20] Silvio Lattanzi, Slobodan Mitrović, Ashkan Norouzi-Fard, Jakub Tarnawski, and Morteza Zadimoghaddam. Fully dynamic algorithm for constrained submodular optimization. *Advances in Neural Information Processing Systems*, 2020.
- [Mon20] Morteza Monemizadeh. Dynamic submodular maximization. *Advances in Neural Information Processing Systems*, 33, 2020.
- [MSV08] Vahab Mirrokni, Michael Schapira, and Jan Vondrák. Tight information-theoretic lower bounds for welfare maximization in combinatorial auctions. In *Proceedings of the 9th ACM conference on Electronic commerce*, pages 70–77, 2008.
- [MZ15] Vahab Mirrokni and Morteza Zadimoghaddam. Randomized composable core-sets for distributed submodular maximization. In *Proceedings of the forty-seventh annual ACM symposium on Theory of computing*, pages 153–162, 2015.
- [NW78] George L Nemhauser and Laurence A Wolsey. Best algorithms for approximating the maximum of a submodular set function. *Mathematics of operations research*, 3(3):177–188, 1978.
- [NWF78] George L Nemhauser, Laurence A Wolsey, and Marshall L Fisher. An analysis of approximations for maximizing submodular set functions. *Mathematical programming*, 14(1):265–294, 1978.
- [Pen21] Binghui Peng. Dynamic influence maximization. *Advances in Neural Information Processing Systems*, 34, 2021.
- [Rou10] Tim Roughgarden. Algorithmic game theory. *Communications of the ACM*, 53(7):78–86, 2010.

- [Von13] Jan Vondrák. Symmetry and approximability of submodular maximization problems. *SIAM Journal on Computing*, 42(1):265–304, 2013.
- [WIB15] Kai Wei, Rishabh Iyer, and Jeff Bilmes. Submodularity in data subset selection and active learning. In *International Conference on Machine Learning*, pages 1954–1963. PMLR, 2015.

A Missing proof from Section 3

A.1 Missing proof from Section 3.1

Let $x \in [0, 1]^w$ and $\bar{x} = \frac{1}{w} \sum_{i=1}^w x_i$. Consider the function

$$f(x) = 1 - \prod_{i=1}^w (1 - x_i)$$

and its symmetric version

$$g(x) = 1 - (1 - \bar{x})^w.$$

The follow Lemma comes from Lemma 2.4 of [MSV08], we make some minor modifications and provide the proof here for completeness.

Theorem A.1 (Restatement of Theorem 3.1). *For any $w \in \mathbb{Z}$, $\epsilon > 0$ let $\gamma = w^{-1} \exp(-4w^6/\epsilon)$. There is a function $\hat{f} : [0, 1]^w \rightarrow [0, 1]$ satisfies*

- When $\max_{i,j} |x_i - x_j| \leq \gamma$, $\hat{f}(x) = g(x)$.
- For any $x \in [0, 1]^w$, $f(x) \geq \hat{f}(x) \geq f(x) - \epsilon$.

Let $h(x) : [0, 1]^w \rightarrow [0, 1]$ be the difference of $f(x)$ and $g(x)$, i.e., $h(x) = f(x) - g(x)$. Here are some basic properties of $h(x)$.

Lemma A.2 (Claim of [MSV08]). *Let $h(x) = f(x) - g(x)$, and $\max_{i,j \in [w]} |x_i - x_j| = \delta$, then one has*

- $h(x) \leq w\delta(1 - \bar{x})^{w-1}$.
- $h(x) \geq w^{-4}\delta^2(1 - \bar{x})^{w-2}$
- $|\frac{\partial h}{\partial x_j}| \leq w\delta(1 - \bar{x})^{w-2}$, i.e. $|\frac{\partial h}{\partial x_j}| \leq w^3(1 - \bar{x})^{w/2-1} \sqrt{h(x)}$.

Define $\tilde{f}(x) = f(x) - \phi(h(x))$ where $\phi : [0, 1] \rightarrow [0, 1]$ controls the interpolation between $f(x)$ and $g(x)$.

Lemma A.3 ([MSV08]). *Let $\epsilon_1 = w\gamma = \exp(-4w^6/\epsilon)$, $\epsilon_2 = \exp(-2w^6/\epsilon)$, $\alpha = \frac{1}{2}w^{-6}\epsilon$, There is a function $\phi : [0, 1] \rightarrow [0, 1]$ that satisfies*

- For $t \in [0, \epsilon_1]$, $\phi(t) = t$.
- For $t \in [\epsilon_1, \epsilon_2]$, the second derivative is $\phi''(t) = -\alpha/t$ and the first derivative of ϕ is continuous at $t = \epsilon_1$, hence,

$$\phi'(t) = 1 - \int_{\epsilon_1}^t \frac{\alpha}{\tau} d\tau = 1 - \alpha \log \frac{t}{\epsilon_1}.$$

- For $t > \epsilon_2$, we set $\phi(t) = \phi(\epsilon_2) < 1$.

Next, we show that \tilde{f} is close to a monotone submodular function, by bounding its first derivative and second derivative.

Lemma A.4. For any $i, j \in [w]$, one has

$$\frac{\partial \tilde{f}}{\partial x_j} \geq 0 \quad \text{and} \quad \frac{\partial^2 \tilde{f}}{\partial x_i \partial x_j} \leq \frac{1}{2} \epsilon (1 - \bar{x})^{w-2}.$$

Proof. For the first derivative, we have

$$\frac{\partial \tilde{f}}{\partial x_j} = \frac{\partial f}{\partial x_j} - \phi'(h) \frac{\partial h}{\partial x_j} = (1 - \phi'(h)) \frac{\partial f}{\partial x_j} + \phi'(h) \frac{\partial g}{\partial x_j}.$$

Since $0 \leq \phi'(h) \leq 1$, and $\frac{\partial g}{\partial x_j}, \frac{\partial f}{\partial x_j} \geq 0$, the first partial derivative is always non-negative. \square

For the second partial derivatives, we have

$$\begin{aligned} \frac{\partial^2 \tilde{f}}{\partial x_i \partial x_j} &= \frac{\partial^2 f}{\partial x_i \partial x_j} - \phi'(h) \frac{\partial^2 h}{\partial x_i \partial x_j} - \phi''(h) \frac{\partial h}{\partial x_i} \frac{\partial h}{\partial x_j} \\ &= (1 - \phi'(h)) \frac{\partial^2 f}{\partial x_i \partial x_j} + \phi'(h) \frac{\partial^2 g}{\partial x_i \partial x_j} - \phi''(h) \frac{\partial h}{\partial x_i} \frac{\partial h}{\partial x_j} \end{aligned}$$

The first two terms are non-negative. To control the third term, we note that $\phi''(h) \leq \alpha/h$ (Lemma A.3) and by Lemma A.2

$$\left| \frac{\partial h}{\partial x_j} \right| \leq w^3 (1 - \bar{x})^{w/2-1} \sqrt{h(x)}$$

Hence, we conclude that

$$\frac{\partial^2 \tilde{f}}{\partial x_i \partial x_j} \leq \left| \phi''(h) \frac{\partial h}{\partial x_i} \frac{\partial h}{\partial x_j} \right| \leq \alpha w^6 (1 - \bar{x})^{w-2} = \frac{1}{2} \epsilon (1 - \bar{x})^{w-2}$$

Proof of Theorem A.1. In order to make \tilde{f} a submodular function, we need to make the second partial derivatives non-positive. Note that $\frac{\partial^2 g}{\partial x_i \partial x_j} = -\frac{w-1}{w} (1 - \bar{x})^{w-2}$. Therefore, it suffices to take

$$\hat{f}(x) = \frac{1}{1 + \epsilon} \left(\tilde{f}(x) + \epsilon g(x) \right).$$

It is clear that \hat{f} is nonnegative and $f(x) \leq \frac{1}{1+\epsilon} (\tilde{f}(x) + \epsilon g(x)) \leq \frac{1}{1+\epsilon} (1 + \epsilon) = 1$. The function \hat{f} is monotone since both \tilde{f} and g are monotone. For second partial derivatives, by Lemma A.4 one has

$$\frac{\partial^2 \hat{f}}{\partial x_i \partial x_j} \leq \frac{2}{2 + \epsilon} \left(\frac{1}{2} \epsilon (1 - \bar{x})^{w-2} - \epsilon \frac{w-1}{w} (1 - \bar{x})^{w-2} \right) \leq 0.$$

Hence, we proved \hat{f} is sbumodular. When $\max_{i,j} |x_i - x_j| \leq \gamma$, one has $h(x) \leq w\gamma(1 - \bar{x})^{w-1} \leq w\gamma = \epsilon_1$. Therefore, $\phi(h(x)) = h(x) = f(x) - g(x)$ and

$$\begin{aligned} \hat{f}(x) &= \frac{1}{1 + \epsilon} \left(\tilde{f}(x) + \epsilon g(x) \right) = \frac{1}{1 + \epsilon} (f(x) - \phi(h(x)) + \epsilon g(x)) \\ &= \frac{1}{1 + \epsilon} (g(x) + \epsilon g(x)) = g(x). \end{aligned}$$

While for any $x \in [0, 1]$, one has

$$\widehat{f}(x) = \frac{1}{1+\epsilon} \left(\widetilde{f}(x) + \epsilon g(x) \right) \leq \frac{1}{1+\epsilon} (f(x) + \epsilon f(x)) = f(x)$$

and

$$\widehat{f}(x) \geq \frac{1}{1+\epsilon} \widetilde{f}(x) \geq \frac{1}{1+\epsilon} (f(x) - \epsilon_2) \geq f(x) \geq f(x) - \epsilon.$$

□

We next provide the proof for Lemma 3.2, which provides basic properties of \widehat{F} .

Proof of Lemma 3.2. Since $\widehat{f}(x_i) \in [0, 1]$, we have $\widehat{F}(x) \in [0, 1]$. \widehat{F} is monotone, because for any $i \in [m], j \in [w]$,

$$\frac{\partial \widehat{F}}{\partial x_{i,j}} = \frac{\partial \widehat{f}}{\partial x_{i,j}} \prod_{\ell \neq i} (1 - \widehat{f}(x_\ell)) \geq 0.$$

Next we show that \widehat{F} is submodular. For any $i, i' \in [m], j, j' \in [w]$, when $i \neq i'$, one has

$$\frac{\partial^2 \widehat{F}}{\partial x_{i,j} \partial x_{i',j'}} = -\frac{\partial \widehat{f}}{\partial x_{i,j}} \frac{\partial \widehat{f}}{\partial x_{i',j'}} \prod_{\ell \neq i, i'} (1 - \widehat{f}(x_\ell)) \leq 0$$

given that \widehat{f} is monotone. When $i = i'$, since \widehat{f} is submodular, one has

$$\frac{\partial^2 \widehat{F}}{\partial x_{i,j} \partial x_{i',j'}} = \frac{\partial^2 \widehat{f}}{\partial x_{i,j} \partial x_{i',j'}} \prod_{\ell \neq i} (1 - \widehat{f}(x_\ell)) \leq 0.$$

Hence, we conclude \widehat{F} is submodular.

The second property directly follows from Theorem 3.1. For the last property, suppose $x_{i,j} = 1$. Then we have $\widehat{f}(x_i) \geq f(x_i) - \epsilon = 1 - \epsilon$. Hence,

$$\widehat{F}(x) = 1 - \prod_{i \in [s]} (1 - \widehat{f}(x_i)) \geq 1 - \epsilon.$$

This finishes the proof of the lemma. □

A.2 Missing proof from Section 3.2

We provide the proof for Lemma 3.5.

Proof of Lemma 3.5. Let S_B be the index defined as

$$S_B := \{i : S \cap B_i \neq \emptyset, i \in [m]\}.$$

We also define index set $S_{A,\pi}$ for the bijection π, π'

$$S_{A,\pi} := \{i : S \cap A_{\pi(i)} \neq \emptyset, i \in [m]\} \quad \text{and} \quad S_{A,\pi'} := \{i : S \cap A_{\pi'(i)} \neq \emptyset, i \in [m]\}.$$

Suppose π, π' satisfies the condition of the Lemma, we conclude that

$$S_B \cap S_{A,\pi} = S_B \cap S_{A,\pi'} = \{i : S \cap B_i \neq \emptyset \text{ and } S \cap (A_{\pi(i)} \cup A_{\pi'(i)}) \neq \emptyset, i \in [m]\}.$$

Consider the following mapping $\sigma : [m] \rightarrow [m]$, σ is identity on $[m] \setminus (S_{A,\pi} \cup S_{A,\pi'} \setminus S_B)$, and it forms an one-to-one mapping on $S_{A,\pi} \cup S_{A,\pi'} \setminus S_B$, such that for any $i \in S_{A,\pi}$, $\pi(i) = \pi'(\sigma(i))$. One can prove such mapping always exists when the condition of the Lemma holds. and it is an one-to-one mapping on $[m]$.

We can extend σ and define $\sigma(I) := \{\sigma(i) : i \in I\}$ for any $I \subseteq [m]$. Since σ is an one-to-one mapping on $[m]$, we have that σ forms a bijection on $2^{[m]}$ and $|\sigma(I)| = |I|$. In order to show $\mathcal{G}_\pi(S) = \mathcal{G}_{\pi'}(S)$, it suffices to prove

$$\sum_{I \subseteq [m]} \beta^{|I|} (1 - \beta)^{m-|I|} G(x^{S,I,\pi}) = \sum_{I \subseteq [m]} \beta^{|I|} (1 - \beta)^{m-|I|} G(x^{S,I,\pi'}). \quad (22)$$

Let $\bar{x}_i^{S,I,\pi} := \frac{1}{w} \sum_{j \in [w]} z_{i,j}^S = \frac{1}{w} \sum_{j \in [w]} \frac{|S \cap B_{i,j}|}{(1-\alpha)k} = \frac{1}{w} \frac{|S \cap B_i|}{(1-\alpha)k}$ for $i \notin I$ and $\bar{x}_i^{S,I,\pi} := \frac{1}{w} \sum_{j \in [w]} \bar{y}_{\pi(i),j}^S = \frac{1}{w} \sum_{j \in [w]} \frac{|S \cap A_{\pi(i),j}|}{\alpha k} = \frac{1}{w} \frac{|S \cap A_{\pi(i)}|}{\alpha k}$. We define $\bar{x}_i^{S,I,\pi'}$ accordingly. Then we have

$$\begin{aligned} G(x^{S,I,\pi}) &= 1 - \prod_{i \in [m]} (1 - g(x_i^{S,I,\pi})) = 1 - \prod_{i \in [m]} (1 - \bar{x}_i^{S,I,\pi})^w \\ &= 1 - \prod_{i \in [m] \setminus I} \left(1 - \frac{1}{w} \frac{|S \cap B_i|}{(1-\alpha)k}\right)^w \prod_{i \in I} \left(1 - \frac{1}{w} \frac{|S \cap A_{\pi(i)}|}{\alpha k}\right)^w \\ &= 1 - \prod_{i \in [m] \setminus I} \left(1 - \frac{1}{w} \frac{|S \cap B_i|}{(1-\alpha)k}\right)^w \prod_{i \in I} \left(1 - \frac{1}{w} \frac{|S \cap A_{\pi'(\sigma(i))}|}{\alpha k}\right)^w \\ &= 1 - \prod_{i \in [m] \setminus \sigma(I)} \left(1 - \frac{1}{w} \frac{|S \cap B_i|}{(1-\alpha)k}\right)^w \prod_{i \in \sigma(I)} \left(1 - \frac{1}{w} \frac{|S \cap A_{\pi'(i)}|}{\alpha k}\right)^w \\ &= 1 - \prod_{i \in [m]} (1 - \bar{x}_i^{S,\sigma(I),\pi'})^w = 1 - \prod_{i \in [m]} (1 - g(x_i^{S,\sigma(I),\pi'})) G(x^{S,\sigma(I),\pi}). \end{aligned} \quad (23)$$

The first three steps holds due to the definition G . The fourth step follows from for any $i \in S_{A,\pi}$, $\pi(i) = \pi'(\sigma(i))$, and for $i \notin S_{A,\pi}$, $|S \cap A_{\pi(i)}| = 0 = |S \cap A_{\pi'(\sigma(i))}|$, and therefore $|S \cap A_{\pi(i)}| = |S \cap A_{\pi'(\sigma(i))}|$ holds for all $i \in [m]$. The fifth step follows from σ is identity on S_B , and hence,

$$\prod_{i \in [m] \setminus I} \left(1 - \frac{1}{w} \frac{|S \cap B_i|}{\alpha k}\right)^w = \prod_{i \in [m] \setminus \sigma(I)} \left(1 - \frac{1}{w} \frac{|S \cap B_i|}{(1-\alpha)k}\right)^w.$$

The last three steps follow from the definition of G .

Note that Eq. (23) implies Eq. (22) as σ creates an one-to-on mapping from $2^{[m]}$ to $2^{[m]}$ and $|I| = |\sigma(I)|$ for any $I \subseteq [m]$. \square

Next, we prove Lemma 3.7.

Proof of Lemma 3.7. Let S be a set that is balanced, and we assume it consists of λk element from B_{i^*} and $(1 - \lambda k)$ from the A_1, \dots, A_m .

For any $I \subseteq [m]$, suppose $i^* \in I$. For any $i \notin I$, we know that $\bar{x}_i^{S,I,\pi} := \frac{1}{w} \sum_{j \in [w]} \frac{|B_{i,j} \cap S|}{(1-\alpha)k} = 0$

and for any $i \in I$, $\bar{x}_i^{S,I,\pi} = \bar{y}_{\pi(i)}^S := \sum_{j \in [w]} \frac{|S \cap A_{\pi(i),j}|}{\alpha k}$, hence, we have

$$\begin{aligned}
\widehat{F}(x^{S,I,\pi}) &= G(x^{S,I,\pi}) = 1 - \prod_{i \in I} \left(1 - \frac{\bar{x}_i^{S,I,\pi}}{\alpha w k} \right)^w \\
&\leq 1 - \prod_{i \in I} \exp \left(-w(1 + \epsilon) \frac{\bar{x}_i^{S,I,\pi}}{\alpha w k} \right) \\
&= 1 - \exp \left(-(1 + \epsilon) \frac{\sum_{i \in I} \bar{x}_i^{S,I,\pi}}{\alpha k} \right) \\
&\leq 1 - \exp \left(-\frac{\sum_{i \in I} \bar{x}_i^{S,I,\pi}}{\alpha k} \right) + \epsilon.
\end{aligned} \tag{24}$$

The first step holds since S is balanced, the second step follows from the definition. The third step follows from $1 - x \geq e^{-(1+\epsilon)x}$ when $x \leq \epsilon/10$ and $\frac{x_i^{S,I,\pi}}{\alpha w k} \leq \frac{(1-\lambda)k}{\alpha w k} \leq \frac{1}{\alpha w} \leq \epsilon/10$. The last step follows from $\exp(-c(1+\epsilon)) \geq \exp(-c) - \epsilon$ for any $\epsilon > 0$ and $c > 0$.

For any $i \in [m]$, let $X_i^{S,I,\pi}$ be a random variable such that $X_i^{S,I,\pi} = \bar{x}_i^{S,I,\pi}$ with probability β and $X_i^{S,I,\pi} = 0$ with probability $1 - \beta$. Let $K(x) : \mathbb{R}^m \rightarrow \mathbb{R}$, and for any $x \in \mathbb{R}^m$, $K(x) = 1 - \exp(\sum_{i=1}^m x_i / \alpha k)$. It is easy to verify that K is concave and one has

$$\begin{aligned}
\sum_{I \subseteq [m], i^* \in I} \beta^{|I|} (1 - \beta)^{m-|I|} \widehat{F}(x^{S,I,\pi}) &\leq \sum_{I \subseteq [m], i^* \in I} \beta^{|I|} (1 - \beta)^{m-|I|} \left(1 - \exp \left(-\frac{\sum_{i \in I} \bar{x}_i^{S,I,\pi}}{\alpha k} \right) + \epsilon \right) \\
&= \sum_{I \subseteq [m], i^* \in I} \beta^{|I|} (1 - \beta)^{m-|I|} \left(1 - \exp \left(-\frac{\sum_{i \in I} \bar{x}_i^{S,I,\pi}}{\alpha k} \right) \right) + \beta \epsilon \\
&= \beta \mathbb{E}_{X_1^{S,I,\pi}, \dots, X_m^{S,I,\pi}} \left[K(X_1^{S,I,\pi}, \dots, X_m^{S,I,\pi}) \right] + \beta \epsilon \\
&\leq \beta K(\bar{x}_1^{S,I,\pi}, \dots, \bar{x}_m^{S,I,\pi}) + \beta \epsilon \\
&= \beta \left(1 - \exp \left(\frac{-(1-\lambda)\beta}{\alpha} \right) \right) + \beta \epsilon.
\end{aligned} \tag{25}$$

The first step follows from Eq. (24), the third step follows from $\pi(i^*) \notin S$, and therefore, $\bar{x}_{i^*}^{S,I,\pi} = 0$ when $i^* \in I$. The fourth step follows the Jensen's inequality and the concavity of K . The last step follows from $\sum_{i \in [m]} \bar{x}_i^{S,I,\pi} = (1 - \lambda)k$.

Similarly, when $i^* \notin I$, we have $\bar{x}_i^{S,I,\pi} = \bar{y}_{\pi(i)}^S := \sum_{j \in [w]} \frac{|S \cap A_{\pi(i),j}|}{\alpha k}$ for $i \in I$, $\bar{x}_{i^*}^{S,I,\pi} = \bar{z}_{i^*}^S =$

$\frac{\lambda k}{(1-\alpha)kw} = \frac{\lambda}{(1-\alpha)w}$ and $\bar{x}_i^{S,I,\pi} = \frac{1}{w} \sum_{j \in w} \frac{|B_{i,j} \cap S|}{(1-\alpha)k} = 0$ for $i \in [m] \setminus (I \cup \{i^*\})$. Therefore,

$$\begin{aligned}
\widehat{F}(x^{S,I,\pi}) &= G(x^{S,I,\pi}) = 1 - \prod_{i \in I} \left(1 - \frac{\bar{x}_i^{S,I,\pi}}{\alpha w k}\right)^w \left(1 - \bar{x}_{i^*}^{S,I,\pi}\right)^w \\
&= 1 - \prod_{i \in I} \left(1 - \frac{\bar{x}_i^{S,I,\pi}}{\alpha w k}\right)^w \left(1 - \frac{\lambda}{(1-\alpha)w}\right)^w \\
&\leq 1 - \prod_{i \in I} \exp\left(-w(1+\epsilon) \frac{\bar{x}_i^{S,I,\pi}}{\alpha w k}\right) \exp\left(-w(1+\epsilon) \frac{\lambda}{(1-\alpha)w}\right) \\
&= 1 - \exp\left(-(1+\epsilon) \frac{\sum_{i \in I} \bar{x}_i^{S,I,\pi}}{\alpha k}\right) \exp\left(-(1+\epsilon) \frac{\lambda}{1-\alpha}\right) \\
&\leq 1 - \exp\left(-\frac{\sum_{i \in I} \bar{x}_i^{S,I,\pi}}{\alpha k}\right) \exp\left(-\frac{\lambda}{1-\alpha}\right) + 2\epsilon. \tag{26}
\end{aligned}$$

The fourth step follows from $1 - x \geq e^{-(1+\epsilon)x}$ when $x \leq \epsilon/10$, $\frac{\bar{x}_{S,A,i}}{\alpha w k} \leq \frac{(1-\lambda)k}{\alpha w k} \leq \frac{1}{\alpha w} \leq \epsilon/10$ and $\frac{\lambda}{(1-\alpha)w} \leq \frac{1}{(1-\alpha)w} \leq O(\epsilon)$. The sixth step follows from $\exp(-c(1+\epsilon)) \geq \exp(-c) - \epsilon$ for any $\epsilon > 0$ and $c > 0$.

Hence, we have

$$\begin{aligned}
&\sum_{I \subseteq [m], i^* \notin I} \beta^{|I|} (1-\beta)^{m-|I|} \widehat{F}(x^{S,I,\pi}) \\
&\leq \sum_{I \subseteq [m], i^* \notin I} \beta^{|I|} (1-\beta)^{m-|I|} \left(1 - \exp\left(-\frac{\sum_{i \in I} x_i^{S,I,\pi}}{\alpha k}\right) \exp\left(-\frac{\lambda}{1-\alpha}\right) + 2\epsilon\right) \\
&= \sum_{I \subseteq [m], i^* \notin I} \beta^{|I|} (1-\beta)^{m-|I|} \left(1 - \exp\left(-\frac{\sum_{i \in I} x_i^{S,I,\pi}}{\alpha k}\right) \exp\left(-\frac{\lambda}{1-\alpha}\right)\right) + 2(1-\beta)\epsilon \\
&\leq (1-\beta) \left(1 - \exp\left(\frac{(1-\lambda)\beta}{\alpha}\right) \exp\left(-\frac{\lambda}{1-\alpha}\right)\right) + 2(1-\beta)\epsilon. \tag{27}
\end{aligned}$$

The first step holds due to Eq. (26), the third step holds due to concavity and Jensen's inequality.

Summing these up, we have

$$\begin{aligned}
\mathcal{F}_{c,\pi}(S) &= \min \left\{ \sum_{I \subseteq [m]} \beta^{|I|} (1-\beta)^{m-|I|} \widehat{F}(x^{S,I,\pi}) + \frac{\epsilon}{k} |S|, 1 \right\} \\
&= \sum_{I \subseteq [m]} \beta^{|I|} (1-\beta)^{m-|I|} \widehat{F}(x^{S,I,\pi}) + \epsilon \\
&= \sum_{I \subseteq [m], i^* \in I} \beta^{|I|} (1-\beta)^{m-|I|} F(x^{S,I,\pi}) + \sum_{I \subseteq [m], i^* \notin I} \beta^{|I|} (1-\beta)^{m-|I|} \widehat{F}(x^{S,I,\pi}) \\
&\leq \beta \left(1 - \exp\left(\frac{-(1-\lambda)\beta}{\alpha}\right)\right) + \beta\epsilon + (1-\beta) \left(1 - \exp\left(\frac{(1-\lambda)\beta}{\alpha}\right) \exp\left(-\frac{\lambda}{1-\alpha}\right)\right) + 2(1-\beta)\epsilon \\
&\leq \beta \left(1 - \exp\left(\frac{-(1-\lambda)\beta}{\alpha}\right)\right) + (1-\beta) \left(1 - \exp\left(\frac{(1-\lambda)\beta}{\alpha}\right) \exp\left(-\frac{\lambda}{1-\alpha}\right)\right) + 3\epsilon \\
&:= F(\alpha, \beta, \lambda) + 3\epsilon.
\end{aligned}$$

The fourth step holds due to Eq. (25) (27).

It remains to solve

$$\min_{\alpha, \beta \in (0,1)} \max_{\lambda \in (0,1)} F(\alpha, \beta, \lambda).$$

Recalls that α and β is up to our choice, where λ is chosen by the algorithm to maximize its approximation ratio, by taking $\alpha = 0.56$, $\beta = 0.42$, one can verify that

$$Q(\alpha, \beta) := \max_{\lambda \in (0,1)} F(\alpha, \lambda, \beta) < 0.5839.$$

□

B Missing proof from Section 4

B.1 Missing proof from Section 4.1

We first provide the proof of Lemma 4.1, which provides basic properties of \mathbf{R} .

Proof of Lemma 4.1. For the first property, for any node $u = (u_1, \dots, u_\ell)$ at depth ℓ , $u \in \mathbf{R}$ iff (1) none of the nodes on the leaf-to-root path get sampled, i.e., $u_1 \notin \mathbf{R}, \dots, (u_1, \dots, u_{\ell-1}) \notin \mathbf{R}$, (2) u is sampled. The probability can be calculated as

$$\prod_{i=1}^{\ell-1} (1 - p_i) p_\ell = \prod_{i=1}^{\ell-1} \frac{1 - \sum_{j=1}^i w_j}{1 - \sum_{j=1}^{i-1} w_j} \cdot \frac{w_\ell}{1 - \sum_{i=0}^{\ell-1} w_i} = w_\ell.$$

The second property follows directly from the `Sample` procedure and the fact that $p_L = 1$. □

We first provide the proof of Lemma 4.3, which provides basic properties of \mathcal{F} .

Proof of Lemma 4.3. For the first claim, for any $S \subseteq V$ and any R in the support of \mathcal{D} , it is clear that g_R is (continuous) monotone and submodular. By the definition of x_u^S , this implies monotonicity and submodularity on the discrete function. As addition and min operation keep monotonicity and submodularity, we have that \mathcal{F} is monotone and submodular. For the second claim, when $|S| \geq k/\epsilon$, one has $\mathcal{F}(S) \geq \min\{\epsilon|S|/k, 1\} = 1$. □

Recall we define the objective function $\mathcal{F} : 2^V \rightarrow \mathbb{R}^+$ as

$$\mathcal{F}(S) = \min \left\{ \mathcal{G}(x^S) + \frac{\epsilon}{k}|S|, 1 \right\} = \min \left\{ \mathbb{E}_{\mathbf{R} \sim \mathcal{D}} [g_{\mathbf{R}}(x^S)] + \frac{\epsilon}{k}|S|, 1 \right\},$$

and

$$g_R(x) := 1 - \prod_{u \in R} (1 - x_u) \quad \text{and}$$

The following Lemma can be seen an extension of Lemma 5.3 in [FNFSZ20].

Lemma B.1 (Restatement of Lemma 4.6). *For any leaf $u \in U_L$ and $S \subseteq W_u$ with $|S| \leq k$ and $S \cap \emptyset$, we have*

$$\mathcal{F}(S) \leq 0.5 + O(\epsilon \log^2(1/\epsilon)).$$

For any $\ell \in [L]$, define $A_{\geq i} = \sum_{\ell=i}^L a_i$, where a_i is defined in Definition 4.5. We know that $a_1 = 1$. Here are some simple facts of $\{a_i\}_{i \in [L]}$ and $\{A_{\geq i}\}_{i \in [L]}$.

Lemma B.2 (Lemma 5.2 in [FNFSZ20]). *The weights $w_1, \dots, w_L > 0$, and for every $j = 1, \dots, L$,*

$$a_j \prod_{i=1}^{j-1} \left(1 - \frac{a_i}{A_{\geq i}}\right) = 1, \quad (28)$$

$$\sum_{i=j}^L \left(2 - \frac{a_i}{A_{\geq i}}\right) = \frac{A_{\geq j}}{a_j}, \quad (29)$$

$$2j - H_j \leq \frac{A_{\geq L-j+1}}{a_{L-j+1}} \leq 2j - 1. \quad (30)$$

Here, we use H_j to denote the harmonic number of $\sum_{i=1}^j \frac{1}{i}$.

Proof of Lemma B.1. For any $\ell \in \{1, \dots, L-1\}$, and $T_1 \subseteq [m_1] \setminus \{u_1\}, \dots, T_\ell \subseteq [m_\ell] \setminus \{u_\ell\}$, the Sample procedure guarantees

$$\Pr_{\mathbf{R} \sim \mathcal{D}} \left[\mathbf{R} \cap (W_u \setminus \mathcal{A}_u) = \bigcup_{i \in [\ell]} \bigcup_{j \in T_i} A_{u_1, \dots, u_{\ell-1}, j} \right] = w_\ell \prod_{i=1}^{\ell} \left(\frac{a_i}{A_{\geq i}} \right)^{|T_i|} \left(1 - \frac{a_i}{A_{\geq i}} \right)^{m_i - |T_i|}. \quad (31)$$

Let R be in the support of \mathcal{D} and $R \cap (W_u \setminus \mathcal{A}_u) = \bigcup_{i \in [\ell]} \bigcup_{j \in T_i} A_{u_1, \dots, u_{\ell-1}, j}$, then for any fixed subset $S \subseteq W_u \setminus \mathcal{A}_u$, the function value is determined only by the restriction $S \cap \bigcup_{i \in [\ell]} \bigcup_{j \in T_i} A_{u_1, \dots, u_{\ell-1}, j}$, as

$$g_R(x^S) = 1 - \prod_{i=1}^{\ell} \prod_{j \in T_i} \left(1 - \frac{|A_{u_1, \dots, u_{\ell-1}, j} \cap S|}{\epsilon k} \right). \quad (32)$$

Therefore, for any $S \subseteq W_u$, we have that

$$\begin{aligned} & \mathcal{G}(x^S) \\ &= \mathbb{E}_{\mathbf{R} \sim \mathcal{D}} [g_{\mathbf{R}}(x^S)] \\ &= \sum_{\ell=1}^{L-1} \sum_{T_1 \subseteq [m_1] \setminus \{u_1\}} \cdots \sum_{T_\ell \subseteq [m_\ell] \setminus \{u_\ell\}} \Pr \left[R \cap (W_u \setminus \mathcal{A}_u) = \bigcup_{i \in [\ell]} \bigcup_{j \in T_i} A_{u_1, \dots, u_{\ell-1}, j} \right] \cdot g_R(x^S) \\ & \quad + \sum_{T_1 \subseteq [m_1] \setminus \{u_1\}} \cdots \sum_{T_{L-1} \subseteq [m_{L-1}] \setminus \{u_{L-1}\}} \Pr \left[R \cap (W_u \setminus \mathcal{A}_u) = \bigcup_{i \in [\ell]} \bigcup_{j \in T_i} A_{u_1, \dots, u_{\ell-1}, j} \cup A_{u_1, \dots, u_L} \right] \cdot g_R(x^S) \\ &\leq \sum_{\ell=1}^{L-1} \sum_{T_1 \subseteq [m_1] \setminus \{u_1\}} \cdots \sum_{T_\ell \subseteq [m_\ell] \setminus \{u_\ell\}} \Pr \left[R \cap (W_u \setminus \mathcal{A}_u) = \bigcup_{i \in [\ell]} \bigcup_{j \in T_i} A_{u_1, \dots, u_{\ell-1}, j} \right] \cdot g_R(x^S) + w_L \\ &= \sum_{\ell=1}^{L-1} \sum_{T_1 \subseteq [m_1] \setminus \{u_1\}} \cdots \sum_{T_\ell \subseteq [m_\ell] \setminus \{u_\ell\}} w_\ell \prod_{i=1}^{\ell} \left(\frac{a_i}{A_{\geq i}} \right)^{|T_i|} \left(1 - \frac{a_i}{A_{\geq i}} \right)^{m_i - |T_i|} \left(1 - \prod_{i=1}^{\ell} \prod_{j \in T_i} \left(1 - \frac{|A_{u_1, \dots, u_{\ell-1}, j} \cap S|}{\epsilon k} \right) \right) \\ & \quad + w_L \\ &= \sum_{\ell=1}^{L-1} w_\ell \left(1 - \prod_{i=1}^{\ell} \prod_{j \in [m_i]} \left(1 - \frac{a_i}{A_{\geq i}} \frac{|A_{u_1, \dots, u_{\ell-1}, j} \cap S|}{\epsilon k} \right) \right) + w_L := \tilde{f}(S). \end{aligned}$$

The third step holds since the second term is bounded by w_L . The fourth step follows from Eq. (31) (32) and the fifth step follows from calculations.

For any $S \subseteq W_u \setminus \mathcal{A}_u$, $\ell \in \{1, \dots, L-1\}$, $j \in [m_\ell]$, let $y_{\ell,j}^S = \frac{|A_{u_1, \dots, u_{\ell-1}, j} \cap S|}{\epsilon k}$. Define the feasible region $\tilde{D} \subseteq \mathbb{R}^{m_1 + \dots + m_{L-1}}$ as

$$\tilde{D} = \left\{ (y_{1,1}, \dots, y_{1,m_1}, \dots, y_{L-1,1}, \dots, y_{L-1,m_{L-1}}) \in \mathbb{R}_+^{m_1 + \dots + m_{L-1}} : \sum_{\ell \in L} \sum_{j \in [m_\ell]} y_{\ell,j} \leq L, y_{\ell,j} \leq 1 \right\}.$$

Different from Lemma 5.4 of [FNFSZ20], a direct continuous relaxation of \tilde{f} is not concave. Instead, we consider a concave upper bound \hat{f} on it

$$\begin{aligned} \tilde{f}(S) &= w_L + \sum_{\ell=1}^{L-1} w_\ell \left(1 - \prod_{i=1}^{\ell} \prod_{j \in [m_i]} \left(1 - \frac{a_i}{A_{\geq i}} y_{i,j}^S \right) \right) \\ &\leq w_L + \sum_{\ell=1}^{L-1} w_\ell \left(1 - \prod_{i=1}^{\ell} \prod_{j \in [m_i]} \left(1 - \frac{a_i}{A_{\geq i}} \right)^{y_{i,j}^S} \right) \\ &= w_L + \sum_{\ell=1}^{L-1} w_\ell \left(1 - \prod_{i=1}^{\ell} \left(1 - \frac{a_i}{A_{\geq i}} \right)^{\sum_{j \in [m_i]} y_{i,j}^S} \right) := \hat{f}(S) \end{aligned} \quad (33)$$

The second step holds since $(1 - as) \geq (1 - a)^s$ holds for any $a, s \in [0, 1]$ (see Claim B.4 for verification).

One can extend \hat{f} to a continuous concave function $\hat{F} : \mathbb{R}_+^{L-1} \rightarrow \mathbb{R}_+$. Concretely, let the new feasible region be $\hat{D} \subseteq \mathbb{R}^{L-1}$, $\hat{D} = \{(z_1, \dots, z_{L-1}) \in \mathbb{R}_+^{L-1}, \sum_{\ell=1}^{L-1} z_\ell \leq L\}$. For intuition, one should think $z_\ell = \sum_{j \in [m_\ell]} y_{\ell,j}$. For any $z = (z_1, \dots, z_{L-1})$, we define

$$\hat{F}(z) = w_L + \sum_{\ell=1}^{L-1} w_\ell \left(1 - \prod_{i=1}^{\ell} \left(1 - \frac{a_i}{A_{\geq i}} \right)^{z_\ell} \right)$$

One can verify that \hat{F} is monotone and concave, since each term in the summation is concave and monotone.

For any $S \subseteq W_u \setminus \mathcal{A}_u$, $\ell \in \{1, \dots, L-1\}$, let $z_\ell^S = \sum_{j \in [m_\ell]} y_{\ell,j}^S = \sum_{j \in [m_\ell]} \frac{|A_{u_1, \dots, u_{\ell-1}, j} \cap S|}{\epsilon k}$. We know that $z^S \in \hat{D}$ for any $S \in W_u \setminus \mathcal{A}_u$. Take an arbitrary tuple $(u'_1, \dots, u'_{L-1}) \in [m_1] \times \dots \times [m_{L-1}]$ such that $u_\ell \neq u'_\ell$ holds for all $\ell \in \{1, \dots, L-1\}$, and let $S = A_{u'_1} \cup \dots \cup A_{u_1, \dots, u_{L-2}, u'_{L-1}} \cup A_{u_1, \dots, u_L}$. It is easy to verify that $S \subseteq W_u \setminus \mathcal{A}_u$, $|S| = k$. Furthermore, we have

$$\begin{aligned} \max_{z \in \hat{D}} \hat{F}(z) &\leq \hat{F}(\mathbf{1}) + \max_{z \in \hat{D}} \langle \nabla \hat{F}(\mathbf{1}), z - \mathbf{1} \rangle = \tilde{f}(S) + \max_{z \in \hat{D}} \langle \nabla \hat{F}(\mathbf{1}), z - \mathbf{1} \rangle \\ &= w_L + \sum_{\ell=1}^{L-1} w_\ell \left(1 - \prod_{i=1}^{\ell} \left(1 - \frac{a_i}{A_{\geq i}} \right) \right) + \max_{z \in \hat{D}} \langle \nabla \hat{F}(\mathbf{1}), z - \mathbf{1} \rangle \\ &\leq \frac{L}{2L - H_L} + \max_{z \in \hat{D}} \langle \nabla \hat{F}(\mathbf{1}), z - \mathbf{1} \rangle \\ &= \frac{1}{2} + O(\epsilon \log(1/\epsilon)) + \max_{z \in \hat{D}} \langle \nabla \hat{F}(\mathbf{1}), z - \mathbf{1} \rangle \end{aligned} \quad (34)$$

The first step follows from the concavity, the second step follows from the definition, the third step holds due to Eq (33), the fourth step holds due to Eq. (28) and the fact that $A_{\geq 1} \geq 2L - H_L$ (taking $j = L$ in Eq. (30)). The last step holds due to $L = 1/\epsilon$.

It remains to bound the second term as

$$\begin{aligned}
\max_{z \in \widehat{D}} \langle \nabla \widehat{F}(\mathbf{1}), z - \mathbf{1} \rangle &= L \max_{\ell \in [L-1]} \frac{\partial \widehat{F}}{\partial z_\ell} - \sum_{\ell=1}^{L-1} \frac{\partial \widehat{F}}{\partial z_\ell}(\mathbf{1}) \\
&\leq \frac{1}{A_{\geq 1}} \left(\frac{L}{2} - \sum_{\ell=1}^{L-1} \left(\frac{1}{2} - \frac{H_{L+1-\ell}}{L+1-\ell} \right) \right) \\
&= \frac{1}{A_{\geq 1}} \sum_{\ell=1}^L \frac{H_\ell}{\ell} \\
&\leq \frac{1}{A_{\geq 1}} \log^2(L) \lesssim \epsilon \log^2(1/\epsilon)
\end{aligned} \tag{35}$$

The second step follows from Lemma B.3, the last step holds due to $L = 1/\epsilon$, $A_{\geq 1} \geq 2L - 1 = 2/\epsilon - 1$ (see Lemma B.2). Finally, we conclude the proof by noticing for any $S \subseteq W'$, $|S| = k$,

$$\begin{aligned}
\mathcal{F}(S) &= \min \left\{ \mathcal{G}(x) + \frac{\epsilon}{k} |S|, 1 \right\} \leq \mathbb{E}_{\mathbf{R} \sim \mathcal{D}} [g_{\mathbf{R}}(x^S)] + \epsilon = \widetilde{f}(S) + \epsilon \leq \max_{z \in \widehat{D}} \widehat{F}(z) + \epsilon \\
&\leq \frac{1}{2} + O(\epsilon \log^2(1/\epsilon))
\end{aligned}$$

The second step holds due to $|S| \leq k$, the fourth step holds due to Eq. (33), the fifth step holds due to Eq. (34) and Eq. (35). \square

Lemma B.3 (Claim 5.4 in [FNFSZ20]). *For any $\ell = 1, \dots, L$, one has*

$$\frac{1}{A_{\geq 1}} \left(\frac{1}{2} - \frac{H_{L+1-\ell}}{L+1-\ell} \right) \leq \frac{\partial \widehat{F}}{\partial z_\ell}(\mathbf{1}) \leq \frac{1}{A_{\geq 1}} \cdot \frac{1}{2}$$

Claim B.4. *For any $a, s \in [0, 1]$, $(1 - as) \geq (1 - a)^s$.*

Proof. We fix $a \in [0, 1]$ and define $h(s) = 1 - as - (1 - a)^s$. Notice that $h(s) = 0$ when $s = 0$ and $s = 1$. Hence, it suffices to prove the $h'(s)$ is positive at the $s = 0$ and it is monotone decreasing. This can be true, as

$$h'(s) = 1 - a - \log(1 - a)(1 - a)^s$$

when $s = 0$, $h'(0) = 1 - a - \log(1 - a) \geq 0$ and $h'(s)$ is monotone decreasing with s . \square

B.2 Missing proof from Section 4.2

We next provide the proof for Claim 4.10, which gives a lower bound on the $d^{\ell+1}$ -stage game for finding hidden bijections.

Proof of Claim 4.10. The hidden bijections are drawn independently and uniformly. Let $v = (v_1, \dots, v_{\ell+1}) \in [d]^{\ell+1}$ and let X_v denote the number of query for the algorithm to recover $\pi_{v_1, \dots, v_\ell}(v_{\ell+1})$. It is easy to see that $\Pr[X_v | \{X_{v'}\}_{v' \in [d]^{\ell+1} \setminus \{v\}}] \leq \frac{m_{\ell+1}}{16L} \leq \frac{1}{4L}$. Let Y_v be an indicator such that $Y_v = 1\{X_v \leq \frac{m_{\ell+1}}{16L}\}$. Then by Azuma-Hoeffding bound, one has

$$\Pr \left[\sum_{v \in [d]^{\ell+1}} Y_v \geq \frac{1}{2L} d^{\ell+1} \right] \leq \exp(-d^{\ell+1}/12L) \leq 1/n^4.$$

Hence, we conclude that with probability at least $1 - 1/n^4$, the number of stage that requires less than $\frac{m_{\ell+1}}{16L}$ queries is no more than $\frac{d^{\ell+1}}{2L}$, hence the algorithm needs to pay at least $\frac{m_{\ell+1}}{16L} \cdot \frac{d^{\ell+1}}{2L} = \Omega(m_{\ell+1}d^{\ell+1})$ queries. \square

C Missing proof from Section 5

We provide a generic reduction and show that one can assume knowing the value of OPT in dynamic submodular maximization. This brings an overhead of $O(\epsilon^{-1} \log(k/\epsilon))$ on amortized running time.

Lemma C.1. *Consider dynamic submodular maximization in an insertion-only stream, suppose there is an algorithm that maintains an α -approximate solution given an estimate of OPT within a multiplicate error of $(1 + \epsilon)$, and makes $O(\mathcal{T})$ amortized queries per update. Then, there is an algorithm that achieves $(\alpha - \epsilon)$ -approximation (without knowing OPT) with amortized query complexity $O(\mathcal{T} \log(k/\epsilon)/\epsilon)$.*

Proof. Let v_t be the maximum value of a singleton at time t , i.e. $v_t = \max_{e \in V_t} f(e)$. In an insertion-only stream, $\{v_t\}_{t \geq 1}$ is monotone and we assume $v_1 = 1$ for simplicity. The algorithm maintains multiple copies of the baseline algorithm, where the i -th copy guesses $(1 + \epsilon)^i$ on OPT. At time t , the algorithm instantiate threads $i_t, \dots, i_t + \epsilon^{-1} \log k + 1$, where $i_t = \lfloor \log_{1+\epsilon} v_t \rfloor$, and it returns the maximum solution set among these threads. For amortized query complexity, the algorithm maintains $O(\epsilon^{-1} \log k)$ threads at each step and for each element in the stream, it is covered by at most $\epsilon^{-1} \log(k/\epsilon)$ threads. To see the later, consider the t -th element in the stream, it is taken account by threads $i_t, \dots, i_t + \epsilon^{-1} \log(k/\epsilon)$. For thread $i > i_t + \epsilon^{-1} \log(k/\epsilon)$, it doesn't need to consider element before time t , as their marginal contribution can be at most $k \cdot v_t \leq k(1 + \epsilon)^{i_t+1} \leq \epsilon(1 + \epsilon)^i$ in the solution set. Hence, we lose at most ϵ factor in the approximation ratio and the amortized query complexity is at most $O(\mathcal{T} \log(k/\epsilon)/\epsilon)$. For approximation guarantee. We know $v_t \leq \text{OPT}_t \leq kv_t$, and therefore, one of the thread will guess OPT_t within $(1 + \epsilon)$ error. Since we only filter element smaller than $\epsilon \text{OPT}_t/k$, the algorithm maintains an $(\alpha - \epsilon)$ -approximation solution. \square

D Missing proof from Section 6

We first prove the following fact.

Fact D.1 (Restatement of Fact 6.6). *Suppose f is a monotone submodular function, then for any subset A, B, C , one has*

$$f_A(C) \leq f_{A \cup B}(C) + f_A(B)$$

Proof. One has

$$\begin{aligned} f_A(C) - f_A(B) &= f(A \cup C) - f(A) - f(A \cup B) + f(A) = f(A \cup C) - f(A \cup B) \\ &\leq f(A \cup B \cup C) - f(A \cup B) = f_{A \cup B}(C) \end{aligned}$$

Hence, we conclude

$$f_A(C) \leq f_{A \cup B}(C) + f_A(B).$$

\square

We next prove Claim 6.4.

Proof of Claim 6.4. For any $e \in E_\ell$, by definition, we have $T_1 \cup \dots \cup T_\ell \cup S_{\ell+1} \cup e \notin M$ and $e \in O_{\ell+2} \cup \dots \cup O_L$. Due to Lemma 6.3, $T_1 \cup \dots \cup T_{\ell+1} \cup O_{\ell+2} \cup \dots \cup O_L \in M$, and therefore, by the augmentation property, we know that

$$\begin{aligned} |E_\ell| &\leq |O_{\ell+2} \cup \dots \cup O_L| - (|T_1 \cup \dots \cup T_{\ell+1} \cup O_{\ell+2} \cup \dots \cup O_L| - |T_1 \cup \dots \cup T_\ell \cup S_{\ell+1}|) \\ &= |S_{\ell+1} \setminus T_{\ell+1}|. \end{aligned} \quad \square$$

We next prove Lemma 6.8.

Proof of Lemma 6.8. For the approximation guarantee, we prove one of the branches will yield a good solution. By Lemma 6.1, we know there is a branch $a \in \mathcal{A}$ that returns a solution set S_a and satisfies

$$f(S_a) \geq (1 - O(\epsilon))f_{S_a}(O).$$

for any feasible set $O \subseteq V_t$. Taking $O = O_t$, we get

$$f(S_a) \geq (1 - O(\epsilon))f_{S_a}(O_t) \geq (1 - O(\epsilon))(f(O_t) - f(S_a)) \quad \Rightarrow \quad f(S_a) \geq (1/2 - O(\epsilon)) \text{OPT}.$$

For the amortized query complexity, by Eq. (10), the total number of the branch is bounded by $k^{\tilde{O}(1/\epsilon)}$, and by Lemma 6.1, the amortized query per branch is $O(L) = O(\epsilon^{-1} \log(k/\epsilon))$. Hence, the total amortized number of query is at most $k^{\tilde{O}(1/\epsilon)}$. \square