

# Interpreting Dense Retrieval as Mixture of Topics

Jingtao Zhan<sup>1</sup>, Jiaxin Mao<sup>2</sup>, Yiqun Liu<sup>1\*</sup>, Jiafeng Guo<sup>3</sup>, Min Zhang<sup>1</sup>, Shaoping Ma<sup>1</sup>

<sup>1</sup> Department of Computer Science and Technology, Institute for Artificial Intelligence, Beijing National Research Center for Information Science and Technology, Tsinghua University, Beijing 100084, China

<sup>2</sup> Beijing Key Laboratory of Big Data Management and Analysis Methods, Gaoling School of Artificial Intelligence, Renmin University of China, Beijing 100872, China

<sup>3</sup> CAS Key Lab of Network Data Science and Technology, Institute of Computing Technology, Chinese Academy of Sciences, Beijing, China

jingtaozhan@gmail.com, maojiaxin@gmail.com, yiqunliu@tsinghua.edu.cn, guojiafeng@ict.ac.cn

## ABSTRACT

Dense Retrieval (DR) reaches state-of-the-art results in first-stage retrieval, but little is known about the mechanisms that contribute to its success. Therefore, in this work, we conduct an interpretation study of recently proposed DR models. Specifically, we first discretize the embeddings output by the document and query encoders. Based on the discrete representations, we analyze the attribution of input tokens. Both qualitative and quantitative experiments are carried out on public test collections. Results suggest that DR models pay attention to different aspects of input and extract various high-level topic representations. Therefore, we can regard the representations learned by DR models as a mixture of high-level topics.

## KEYWORDS

dense retrieval, neural ranking, explainability

## 1 INTRODUCTION

Dense Retrieval (DR) achieves state-of-the-art first-stage retrieval performance through representing text with dense embeddings and utilizing (approximate) nearest neighbor search to retrieve candidates [5, 7, 10, 11, 16, 17]. However, the mechanisms that contribute to its outstanding performance remain unclear.

We address this problem by conducting an interpretation study. Firstly, we propose RepMoT, which discretizes the output of query and document encoders. The discrete representations make interpretation study easier by modeling text relationships more explicitly than continuous embeddings. Secondly, we investigate DR models based on RepMoT with attribution techniques. We qualitatively analyze the word importance with respect to different discrete sub-vectors. Then we quantitatively measure the word importance by masking the input and observing the output change.

We conduct experiments on two widely-adopted benchmark datasets. Experimental results show RepMoT achieves ranking performance on par with state-of-the-art DR models and thus justifies analyzing DR models based on RepMoT. The analysis results suggest DR models pay attention to different aspects of the input and capture mixture of high-level topics. Therefore, the representations encoded by DR models can be regarded as mixture of high-level topic representations.

\*Corresponding author

## 2 RELATED WORKS

DR models embed queries and documents to low-dimension dense vectors and utilize their vector similarity to predict relevance [4, 7, 8, 16, 19]. Formally, let  $q$  be the user query and  $d$  be the document. We use  $f$  to denote the DR model. Thus,  $\mathbf{q} = f(q) \in \mathbb{R}^D$  and  $\mathbf{d} = f(d) \in \mathbb{R}^D$ , where  $D$  is the embedding dimension.

Previous DR models usually embed text to a continuous embedding space, such as ANCE [14] and ADORE [16]. Recently, several studies jointly optimize DR models with Product Quantization [9] and produce discrete document representations, such as JPQ [15] and RepCONC [17]. Our proposed RepMoT further discretizes query representations based on RepCONC [17].

Here is a brief note about the term ‘‘Topic’’. ‘‘Topic’’ in the context of topic models usually refers to clusters of similar words and is mined based on word statistics [2]. In this paper, the term ‘‘Topic’’ is used in its idiomatic sense, and we investigate which words DR models pay attention to. Future works may further explore the relationships between RepMoT and topic models.

## 3 METHODOLOGY

### 3.1 Discrete Representations

It is difficult to directly interpret the DR models in the continuous embedding space because we need to manually set a threshold for the *soft* matching score to determine whether two pieces of texts are semantically similar or not. Inspired by Product Quantization [9], we propose to discretize the query and document representations. The discrete representations explicitly characterize the relationship between different texts. The queries or documents assigned to the same discrete sub-vectors are similar and those to different ones are dissimilar.

Now we describe how to discretize continuous representations. 1) We first split the output of DR models to  $M$  sub-vectors of dimension  $D/M$ . We use  $f_i(\text{text}) \in \mathbb{R}^{D/M}$  to denote the  $i$ -th sub-vector. 2) Next, we define  $M$  embedding pools, each of which involves  $K$  embeddings of dimension  $D/M$ . We use  $\mathbf{c}_{i,j} \in \mathbb{R}^{D/M}$  to denote the  $j$ -th embedding from the  $i$ -th pool. 3) Finally, we replace each sub-vector  $f_i(\text{text})$  with the nearest embedding in the corresponding pool  $\{\mathbf{c}_{i,j}\}$ . Let  $\hat{\mathbf{d}}$  be the discrete document representation. It is the concatenation of  $M$  sub-vectors  $\hat{\mathbf{d}}_i$ :

$$\begin{cases} \hat{\mathbf{d}} &= \hat{\mathbf{d}}_1, \hat{\mathbf{d}}_2, \dots, \hat{\mathbf{d}}_M \\ \hat{\mathbf{d}}_i &= \mathbf{c}_{i, \varphi_i(d)} \text{ and } \varphi_i(d) = \arg \min_j \|f_i(d) - \mathbf{c}_{i,j}\| \end{cases} \quad (1)$$

**Table 1: Retrieval results on TREC 2019 Deep Learning Track. M denotes the number of discrete sub-vectors per passage/document.**

Model	Discrete			MARCO Passage		DL Passage		MARCO Doc	
	Query	Doc	M	MRR@10	R@100	NDCG@10	R@100	MRR@100	R@100
ANCE [14]			\	0.330	0.852	0.648	0.437	0.377	0.894
ADORE [16]			\	0.347	0.876	0.683	0.473	0.405	0.919
OPQ [9]		✓	48	0.290	0.830	0.591	0.417	0.340	0.880
JPQ [15]		✓	48	0.332	0.863	0.644	0.447	0.384	0.905
RepCONC [17]		✓	48	0.340	0.864	0.668	0.492	0.399	0.911
OPQ-SDC [9]	✓	✓	48	0.285	0.822	0.592	0.404	0.338	0.873
RepMoT	✓	✓	48	0.335	0.854	0.661	0.441	0.394	0.905

where commas denote concatenation. Query representations are defined in the same way. Each embedding pool splits the corpus into  $K$  groups, and the texts in the same group are considered similar. The discrete representation is still very expressive because the total number of combinations is  $K^M$ .

Inspired by RepCONC [17], we end-to-end optimize the dual-encoders  $f$  and embedding pools  $\{c_{i,j}\}$  with the weighted sum of a ranking-oriented loss and a clustering loss. The ranking-oriented loss replaces the continuous embeddings in the common ranking loss functions [12, 14, 16] with the discrete embeddings:

$$L_r = -\log \frac{e^{\langle \hat{q}, \hat{d}^+ \rangle}}{e^{\langle \hat{q}, \hat{d}^+ \rangle} + \sum_{d^-} e^{\langle \hat{q}, \hat{d}^- \rangle}} \quad (2)$$

where  $\hat{q}$  and  $\hat{d}$  are discrete query and document representations. The clustering loss is the MSE loss between the discrete and continuous embeddings:

$$L_m = \frac{1}{2} (\|f(d) - \hat{d}\|^2 + \|f(q) - \hat{q}\|^2) \quad (3)$$

We utilize their weighed sum  $L_r + \lambda L_m$  as the final loss function. We also adopt the uniform clustering constraint [17] when discretizing document embeddings during training, which, according to RepCONC [17], helps maximize the distinguishability of discrete representations. We refer readers to RepCONC [17] for details.

We name our method RepMoT because the following sections will show it captures Mixture of high-level Topics.

### 3.2 Attribution Analysis

We aim to interpret DR on word level by quantifying the contributions of each word to each discrete sub-vector by a scalar score. For example, say the DR model takes the input of the sentence “*his food is tasty*”. “*food*” and “*tasty*” are likely to have high contribution scores because they are important for the semantic meanings. “*is*” carries little information and thus has low score.

We adopt a popular attribution method, Integrated Gradients (IG) [13], to measure the word importance. It interpolates the input features from the baseline input to the actual input and computes the partial derivatives of the model output with respect to the input. Formally, let  $x = (x_1, \dots, x_n) \in \mathbb{R}^{n \times dim}$  be the actual input word embeddings, and  $x' = (x'_1, \dots, x'_n) \in \mathbb{R}^{n \times dim}$  be the baseline input.

The baseline can be a sequence of “*<unk>*” tokens<sup>1</sup>. Let  $F$  be a neural model. The attribution of  $j$ -th word equals to:

$$(x_j - x'_j) \cdot \int_{\alpha=0}^1 \frac{\partial F(x' + \alpha(x - x'))}{\partial x_j} d\alpha \quad (4)$$

Recall that RepMoT encodes the input text to the concatenation of multiple discrete sub-vectors. To study whether different discrete sub-vectors pay attention to different words, we investigate the attribution scores with respect to each output sub-vector. We use the following formula to compute the  $j$ -th word’s attribution for  $i$ -th output sub-vector.

$$(x_j - x'_j) \cdot \int_{\alpha=0}^1 \frac{\partial - \|\hat{d}_i - f_i(x' + \alpha(x - x'))\|^2}{\partial x_j} d\alpha \quad (5)$$

The above attribution scores evaluate which words contribute to the selection of the discrete sub-vectors  $\hat{d}_i$ . We do not directly use the output of  $f_i$  but instead utilize the negative MSE. It is because as shown in Eq. (1), MSE is important for selecting discrete representations while the exact output of DR models is not. In other words,  $f_i(x' + \alpha(x - x'))$  is equivalent to  $f_i(x)$  as long as it is closer to  $\hat{d}_i$  than to other embeddings from the pool. To model this characteristic, we use the MSE to compute gradients in Eq. (5).

We compare the attribution distribution of the same text for different  $\hat{d}_i : 1 \leq i \leq M$ , and also analyze the highly attributed words of different text for the same  $\hat{d}_i$ . Note, this paper focuses on analyzing document representations and leaves investigating query representations to future research.

## 4 EXPERIMENTS

This section presents our experimental results. We conduct experiments on TREC 2019 Deep Learning Track [1, 3]. The passage ranking task has a corpus of 8.8M passages, 0.5M training queries, 7k development queries (henceforth, MARCO Passage), and 43 test queries (DL Passage). The document ranking task has a corpus of 3.2M documents, 0.4M training queries, 5k development queries (MARCO Doc).

The following sections first justify our analysis based on RepMoT, and then show DR models capture high-level topics.

<sup>1</sup>According to Zhan et al. [18], removing stop words leads to unexpected behaviors of BERT. Thus, we keep all stop words for the baseline input.



**Table 3: MSE error when only 5% words are retained. “12”, “24”, and “48” denote the number of sub-vectors. \* denotes MoT performs significantly better than all baselines at  $p < 0.01$  level using two-tailed pairwise t-test. Best method is marked bold.**

Method \ Setup	MARCO Passage			MARCO Document		
	12	24	48	12	24	48
<b>Position-based</b>						
Tail	4.20	2.66	1.82	3.06	2.24	1.14
Rand	4.18	2.64	1.80	3.22	2.27	1.16
Head	3.52	2.31	1.60	2.09	1.48	0.82
<b>Frequency-based</b>						
IDF	4.17	2.65	1.82	3.40	2.40	1.23
TF	3.63	2.32	1.58	2.01	1.49	0.80
TF-IDF	3.46	2.24	1.54	1.96	1.45	0.78
<b>Attribution-based</b>						
RandT	3.36	2.25	1.59	1.90	1.45	0.81
GlobalT	3.08	2.07	1.45	1.50	1.15	0.64
MoT	<b>2.73*</b>	<b>1.87*</b>	<b>1.26*</b>	<b>1.39*</b>	<b>1.05*</b>	<b>0.54*</b>

4.3.2 *Results.* Table 3 presents the experimental results. It clearly shows that MoT performs significantly better than all masking baselines, demonstrating the word importance is different for different discrete sub-vectors. Therefore, we validate the finding in our qualitative analysis that DR models pay attention to different aspects of input to extract different high-level representations.

## 5 CONCLUSION AND FUTURE WORK

Recently, DR models yield strong first-stage retrieval performance, but the internal mechanisms leading to its success remain unknown. Therefore, we propose RepMoT to discretize embeddings and then analyze DR models based on RepMoT. Results suggest DR models pay attention to different aspects of the input and capture different high-level topics. Therefore, we regard the representations encoded by DR models as mixture of topics.

We highlight several promising directions for building explainable DR. One is based on RepMoT, which can be regarded as rewriting the text with “discrete vector terms”. Researchers may manually design the connections between those “discrete vector terms” and “natural language terms” during training. The other is teaching DR models how to capture topics by designing attention patterns with some heuristics, e.g., topic models. We leave these to future research.

## REFERENCES

- [1] Payal Bajaj, Daniel Campos, Nick Craswell, Li Deng, Jianfeng Gao, Xiaodong Liu, Rangan Majumder, Andrew McNamara, Bhaskar Mitra, Tri Nguyen, et al. 2016. Ms marco: A human generated machine reading comprehension dataset. *arXiv preprint arXiv:1611.09268* (2016).
- [2] David M Blei. 2012. Probabilistic topic models. *Commun. ACM* 55, 4 (2012), 77–84.
- [3] Nick Craswell, Bhaskar Mitra, Emine Yilmaz, Daniel Campos, and Ellen M. Voorhees. 2020. Overview of the TREC 2019 deep learning track. In *Text REtrieval Conference (TREC)*. TREC.
- [4] Luyu Gao and Jamie Callan. 2021. Unsupervised corpus aware language model pre-training for dense passage retrieval. *arXiv preprint arXiv:2108.05540* (2021).
- [5] Luyu Gao, Zhuyun Dai, Zhen Fan, and Jamie Callan. 2021. Complementing lexical retrieval with semantic residual embedding. In *Proceedings of the 42nd European Conference in Information Retrieval*.
- [6] Tiezheng Ge, Kaiming He, Qifa Ke, and Jian Sun. 2013. Optimized product quantization. *IEEE transactions on pattern analysis and machine intelligence* 36, 4 (2013), 744–755.
- [7] Sebastian Hofstätter, Sheng-Chieh Lin, Jheng-Hong Yang, Jimmy Lin, and Allan Hanbury. 2021. Efficiently Teaching an Effective Dense Retriever with Balanced Topic Aware Sampling. In *Proceedings of the 44th International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR’21)*. 113–122.
- [8] Jui-Ting Huang, Ashish Sharma, Shuying Sun, Li Xia, David Zhang, Philip Pronin, Janani Padmanabhan, Giuseppe Ottaviano, and Linjun Yang. 2020. Embedding-based Retrieval in Facebook Search. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*. 2553–2561.
- [9] Herve Jegou, Matthijs Douze, and Cordelia Schmid. 2010. Product quantization for nearest neighbor search. *IEEE transactions on pattern analysis and machine intelligence* 33, 1 (2010), 117–128.
- [10] Vladimir Karpukhin, Barlas Oguz, Sewon Min, Patrick Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen-tau Yih. 2020. Dense Passage Retrieval for Open-Domain Question Answering. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*.
- [11] Yi Luan, Jacob Eisenstein, Kristina Toutanova, and Michael Collins. 2020. Sparse, dense, and attentional representations for text retrieval. *arXiv preprint arXiv:2005.00181* (2020).
- [12] Yingqi Qu, Yuchen Ding, Jing Liu, Kai Liu, Ruiyang Ren, Wayne Xin Zhao, Daxiang Dong, Hua Wu, and Haifeng Wang. 2021. RocketQA: An optimized training approach to dense passage retrieval for open-domain question answering. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*. 5835–5847.
- [13] Mukund Sundararajan, Ankur Taly, and Qiqi Yan. 2017. Axiomatic attribution for deep networks. In *International Conference on Machine Learning*. 3319–3328.
- [14] Lee Xiong, Chenyan Xiong, Ye Li, Kwok-Fung Tang, Jialin Liu, Paul N. Bennett, Junaid Ahmed, and Arnold Overwijk. 2021. Approximate Nearest Neighbor Negative Contrastive Learning for Dense Text Retrieval. In *International Conference on Learning Representations*.
- [15] Jingtao Zhan, Jiaxin Mao, Yiqun Liu, Jiafeng Guo, Min Zhang, and Shaoping Ma. 2021. Jointly Optimizing Query Encoder and Product Quantization to Improve Retrieval Performance. In *Proceedings of the 30th ACM International Conference on Information and Knowledge Management (CIKM’21)*.
- [16] Jingtao Zhan, Jiaxin Mao, Yiqun Liu, Jiafeng Guo, Min Zhang, and Shaoping Ma. 2021. Optimizing Dense Retrieval Model Training with Hard Negatives. In *Proceedings of the 44th International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR’21)*. 1503–1512.
- [17] Jingtao Zhan, Jiaxin Mao, Yiqun Liu, Jiafeng Guo, Min Zhang, and Shaoping Ma. 2022. Learning Discrete Representations via Constrained Clustering for Effective and Efficient Dense Retrieval. In *Proceedings of The 15th ACM International Conference on Web Search and Data Mining (WSDM’22)*.
- [18] Jingtao Zhan, Jiaxin Mao, Yiqun Liu, Min Zhang, and Shaoping Ma. 2020. An Analysis of BERT in Document Ranking. In *Proceedings of the 43rd International ACM SIGIR Conference on Research and Development in Information Retrieval*. 1941–1944.
- [19] Jingtao Zhan, Jiaxin Mao, Yiqun Liu, Min Zhang, and Shaoping Ma. 2020. RepBERT: Contextualized Text Embeddings for First-Stage Retrieval. *arXiv preprint arXiv:2006.15498* (2020).