Omnisolver: an extensible interface to Ising spin glass solvers

Konrad Jałowiecki[a,b], Łukasz Pawela[b]

[a]*Institute of Theoretical and Applied Informatics, Polish Academy of Sciences, Bałtycka 5, 44-100 Gliwice, Poland*
[b]*Institute of Physics, University of Silesia, Bankowa 12, 40-007 Katowice, Poland*

arXiv:2112.11131v1 [cs.SE] 21 Dec 2021

Abstract

We introduce a new framework for implementing Binary Quadratic Model (BQM) solvers called omnisolver. The framework provides an out-of-the-box dynamically built command-line interface as well as input/output system, thus heavily reducing the effort required for implementing new algorithms for solving BQMs. The proposed software should be of benefit for researchers focusing on quantum annealers or discrete optimization algorithms as well as groups utilizing discrete optimization as a part of their daily work. We demonstrate the ease of use of the proposed software by presenting a step-by-step, concise implementation of an example plugin.

Keywords: QUBO, spin-glass, discrete optimization, quantum annealing

Required Metadata

Nr.	Code metadata description	Please fill in this column
C1	Current code version	v0.1.0
C2	Permanent link to code/repository used for this code version	`https://github.com/euro-hpc-pl/omnisolver`
C4	Legal Code License	Apache 2.0
C5	Code versioning system used	git
C6	Software code languages, tools, and services used	Python, YAML
C7	Compilation requirements, operating environments & dependencies	Linux, `Python >= 3.9`, `dimod`, `pluggy`, plugins may require additional Python packages and build dependencies
C8	If available Link to developer documentation/manual	`https://omnisolver.readthedocs.io/`
C9	Support email for questions	`lpawela@iitis.pl`

Table 1: Code metadata (mandatory)

1. Motivation and significance

The rapidly developing field of quantum information brings us ever closer to developing practical quantum computers. Currently, we are living in an era marked by the so-called Noisy Intermediate-Scale Quantum (NISQ) [1] devices. It comes as no surprise that these machines have attracted attention from both the scientific and business communities. This attention results in a myriad of proposed potential applications for NISQ devices. One of the potential obstacles in developing quantum software, which this work aims to remedy, is the cost of testing on actual NISQ devices.

The main way to cut quantum infrastructure access costs is to utilize frameworks that simulate their behavior. Nonetheless, if we try this approach, we quickly run into another problem: there are multiple frameworks available, each of which can be based on different numerical algorithms. Here, we are concerned with one particular NISQ architecture – the D-Wave annealer. The behavior of this machine can be simulated using a tensor network approach [2, 3], dynamical system approach [4], neural networks [5] and, for sufficiently small problem sizes, through a brute-force approach [6].

The downside of this multitude of options is that the implementations of each of these approaches have incompatible input/output APIs. In this

work, we introduce the `omnisolver` package which, provides an extensible, unified API for Ising spin-glass solvers and the actual D-Wave annealer.

2. Software description

Describe the software in as much as is necessary to establish a vocabulary needed to explain its impact.

2.1. Software Architecture

Omnisolver is built in a modular fashion and comprises the following elements:

- main Omnisolver framework,
- plugins providing samplers built on top of `dimod` library [7].

The framework handles input/output operations, including parsing command line arguments, reading an input problem file, and outputting solutions computed by samplers. It can be extended via plugin system built using `pluggy` [8] library. The plugins are responsible for implementing algorithms solving Binary Quadratic Models and providing descriptions of available parameters. Figure 1 demonstrates the relationship between the main framework and plugins, as well as the typical execution flow of the solver. The plugin definition comprises:

- `name` of the plugin,
- the `create_sampler` function used to construct new sampler instances,
- the `populate_parser` callback used for defining command line arguments used for creating sampler and running its `sample` method.
- `init_args` and `sample_args` determining which command line arguments should be passed respectively to sampler's initializer and `sample` method.

Omnisolver extensions should provide one or more callables decorated with `omnisolver.plugin.plugin_impl` returning an instance of `Plugin` class.




Figure 1: Omnisolver's architecture diagram

2.2. Software Functionalities

The major functionality of the omnisolver project is providing a framework for implementing arbitrary solvers of classical Ising spin–glasses. To this end, the core `omnisolver` package provides:

- plugin system for registering solvers inheriting from `dimod.Sampler`,
- helper functions for implementing most typical plugins which remove the burden of writing plugin boilerplate from the end–user,
- input/output system automatically wired to the plugins. Currently, this allows reading spin–glass instances from coordinate format and writing solutions as a comma separated value (CSV) file,
- dynamically generated command line interface (CLI). The CLI takes into account information provided by the registered plugins, and hence is able to correctly recognize parameters that need to be passed to each solver.

Apart from the core `omnisolver` package, we also implemented several plugins, including:

- `omnisolver-pt` providing implementation of parallel-tempering algorithm, available at `https://github.com/euro-hpc-pl/omnisolver-pt`

- `omnisolver-bruteforce` providing implementation of the exhaustive search which can optionally be accelerated using CUDA–enabled GPU, available at `https://github.com/euro-hpc-pl/omnisolver-bruteforce`.

2.3. Sample code snippets analysis

Code snippets in this section demonstrate an example implementation of an omnisolver plugin, providing a dummy solver returning random solutions. While this example is clearly artificial, it should be easy for the reader to extend it to an implementation of an arbitrary nontrivial solver. The plugin is implemented as a Python package called `dummysolver`. The layout of the package is shown in the Listing 1, and the Fig. 2 summarizes relationship between package's essential components.

```
+-- dummysolver
|   |-- dummy.yml
|   |-- __init__.py
|   +-- solver.py
|-- MANIFEST.in
|-- setup.cfg
+-- setup.py
```

Listing 1: Directory structure of dummy omnisolver plugin




Figure 2: Omnisolver's plugin architecture diagram

The `dummysolver/solver.py` file, presented in Listing 2, contains the actual implementation of the solver. The `DummySolver` class inherits from `dimod.Sampler` and provides implementation of its abstract `sample` method. This method accepts an instance of `dimod.BinaryQuadraticModel` (required

by the base class' `sample` method) and an additional keyword parameter `num_solutions` indicating how many solutions should be returned.

```
import dimod
import random


class DummySolver(dimod.Sampler):
    """A dummy sampler returning random solutions for given
   BinaryQuadraticModel."""

    @property
    def parameters(self):
        """Parameters accepted by this sampler."""
        return {"num_solutions": []}

    @property
    def properties(self):
        """Properties of this sampler."""
        return {}

    def sample(self, bqm, **parameters):
        """Uniformly sample given BQM."""
        num_samples = parameters.pop("num_solutions", 1)
        assert (
            not parameters
        ), f"Unrecognized parameters: {parameters}"

        possible_values = tuple(bqm.vartype.value)
        solutions = [
            [
                random.choice(possible_values)
                for _ in range(bqm.num_variables)
            ]
            for _ in range(num_samples)
        ]

        return dimod.SampleSet.from_samples_bqm(
            solutions, bqm
        ).aggregate()
```

Listing 2: `dummysolver/solver.py`

To inform omnisolver's plugin system about `DummySolver`, one needs to provide information about solver's class, displayed name, parameters accepted by the solver and their command line counterparts. The easiest way to achieve this is by providing the information in the YAML file, as exemplified by Listing 3.

```
schema_version: 1
```

```yaml
name: "dummy"
sampler_class: "dummysolver.solver.DummySolver"
description: "Uniformly random dummy sampler"


init_args: []
sample_args:
  - name: "num_solutions"
    help: "number of sampled solutions"
    type: int
    default: 1
```

Listing 3: dummysolver/dummy.yml

One also needs to define the plugin's entrypoint, which in this case is located in the package's initialization file (Listing 4). Here, we used omnisolver's convenience function `plugin_from_specification` for building the plugin from the definition read from the YAML file. Finally, the entrypoint has to be defined in the package's setup file (Listing 5) to be picked up by the plugin system.

```python
from omnisolver.plugin import (
    plugin_from_specification,
    plugin_impl,
)
from pkg_resources import resource_stream
from yaml import safe_load


@plugin_impl
def get_plugin():
    """Construct plugin from given yaml file."""
    specification = safe_load(
        resource_stream("dummysolver", "dummy.yml")
    )
    return plugin_from_specification(specification)
```

Listing 4: dummysolver/__init__.py

```
[metadata]
name = dummysolver
description = Dummy solver plugin for omnisolver

[options]
packages = dummysolver
python_requires = >= 3.7
install_requires =
    omnisolver >= 0.0.1
include_package_data = True
```

```
[options.package_data]
dummysolver = "dummysolver.yml"

[options.entry_points]
omnisolver =
    dummy = dummysolver
```

Listing 5: `setup.cfg`

3. Illustrative Examples

Examples in this section assume that `omnisolver`, `omnisolver-pt` and `dummysolver` (presented in Subsection 2.3) are installed in the current Python environment.

The available solvers can be displayed by running `omnisolver -h`, as exemplified in Listing 6

```
usage: omnisolver [-h] {pt,dummy,random} ...

optional arguments:
  -h, --help          show this help message and exit

Solvers:
  {pt,dummy,random}
```

Listing 6: Example of running `omnisolver -h`

Help for the specific solver can be obtained by running `omnisolver <solver-name> -h`. Listing 7 shows an example output of running command `omnisolver pt -h`.

```
usage: omnisolver pt [-h] [--output OUTPUT] [--vartype {
 SPIN,BINARY}] [--num_replicas NUM_REPLICAS] [--
 num_pt_steps NUM_PT_STEPS] [--num_sweeps NUM_SWEEPS] [--
 beta_min BETA_MIN] [--beta_max BETA_MAX] input

Parallel tempering sampler

positional arguments:
  input                 Path of the input BQM file in COO
 format. If not specified, stdin is used.

optional arguments:
  -h, --help            show this help message and exit
  --output OUTPUT       Path of the output file. If not
 specified, stdout is used.
  --vartype {SPIN,BINARY}
                        Variable type
  --num_replicas NUM_REPLICAS
```

```
                        number of replicas to simulate (
default 10)
 --num_pt_steps NUM_PT_STEPS
                        number of parallel tempering steps
 --num_sweeps NUM_SWEEPS
                        number of Monte Carlo sweeps per
parallel tempering step
 --beta_min BETA_MIN    inverse temperature of the hottest
replica
 --beta_max BETA_MAX    inverse temperature of the coldest
replica
```

Listing 7: Specific help message for the `omnisolver-pt` plugin

Finally, let us demonstrate solving an instance of the Ising spin-glass using a chosen solver. To this end, let us assume that the instance file `instance.txt` as presented in Listing 8 is present in the current directory. Running `omnisolver pt instance.txt --vartype=SPIN` yields result similar to the one presented in Listing 9.

```
1 2 1.5
0 1 -1
0 2 -3
```

Listing 8: Example file with an instance of Ising spin-glass

```
0,1,2,energy,num_occurrences
1,-1,1,-3.5,1
```

Listing 9: Example output of running omnisolver on specific Ising spin-glass

4. Impact

This software has two main contributions. Firstly, it provides a unified framework for implementing Ising or QUBO solvers. As such, it should accelerate process of implementing new algorithms, saving the developers the time needed for writing code handling CLI and input/output system. For the researchers, common CLI and input/output interface should make it easier to interchangeably use a variety of solvers, thus decreasing time needed for preparing and running experiments. In particular, this will mainly benefit entities that face combinatorial optimization problems in their daily routine, such as railway companies. As an example of such application, we refer an interested reader to the works [9, 10].

Secondly, Omnisolver provides new, faster implementation of the brute-force algorithm utilizing Gray's codes. As such, it allows us to find exact low-energy spectrum for larger (up to 64 variables) problems, similar in size to the largest cliques embeddable on present-day D-Wave hardware.

5. Conclusions

We provide the community interested in quantum computing with a tool which provides an extensible framework allowing for communication with various computational backends. These can include various numerical solvers to these instances as well as actual quantum computing devices, such as the D-Wave annealer.

During the development of our future solver backends, we will provide accompanying plugins for `omnisolver` in order to provide a unified input/output interface. The broader community is also encouraged to provide their own implementations when coming up with interesting approaches to solving Ising instances.

6. Conflict of Interest

No conflict of interest exists: We wish to confirm that there are no known conflicts of interest associated with this publication and there has been no significant financial support for this work that could have influenced its outcome.

Acknowledgements

This work was supported by the Foundation for Polish under the TEAM-NET programme.

References

[1] J. Preskill, Quantum Computing in the NISQ era and beyond, Quantum 2 (2018) 79. doi:10.22331/q-2018-08-06-79.
URL https://doi.org/10.22331/q-2018-08-06-79

[2] U. Schollwöck, The density-matrix renormalization group in the age of matrix product states, Annals of physics 326 (1) (2011) 96–192.

[3] R. Orús, A practical introduction to tensor networks: Matrix product states and projected entangled pair states, Annals of Physics 349 (2014) 117–158.

[4] E. S. Tiunov, A. E. Ulanov, A. Lvovsky, Annealing by simulating the coherent ising machine, Optics express 27 (7) (2019) 10288–10295.

[5] D. Wu, L. Wang, P. Zhang, Solving statistical mechanics using variational autoregressive networks, Physical review letters 122 (8) (2019) 080602.

[6] K. Jałowiecki, M. M. Rams, B. Gardas, Brute-forcing spin-glass problems with cuda, Computer Physics Communications 260 (2021) 107728.

[7] D-Wave Systems Inc., dimod.
URL `https://github.com/dwavesystems/dimod`

[8] H. Krekel, pluggy - a minimalist production ready plugin system.
URL `https://github.com/pytest-dev/pluggy`

[9] K. Domino, M. Koniorczyk, K. Krawiec, K. Jałowiecki, B. Gardas, Quantum computing approach to railway dispatching and conflict management optimization on single-track railway lines, arXiv preprint arXiv:2010.08227 (2020).

[10] K. Domino, M. Koniorczyk, K. Krawiec, K. Jałowiecki, S. Deffner, B. Gardas, Quantum annealing in the nisq era: railway conflict management, arXiv preprint arXiv:2112.03674 (2021).