

MDFEND: Multi-domain Fake News Detection

Qiong Nan^{1,2,3}, Juan Cao^{1,2,*}, Yongchun Zhu^{1,2}, Yanyan Wang^{1,2}, Jintao Li¹

¹Key Lab of Intelligent Information Processing of Chinese Academy of Sciences (CAS), Institute of Computing Technology, CAS, Beijing, China ²University of Chinese Academy of Sciences, Beijing, China

³State Key Laboratory of Media Convergence Production Technology and Systems, Beijing, China
{nanqiong19z,caojuan,zhuyongchun18s,wangyanyan18s,jtli}@ict.ac.cn

ABSTRACT

Fake news spread widely on social media in various domains, which lead to real-world threats in many aspects like politics, disasters, and finance. Most existing approaches focus on single-domain fake news detection (SFND), which leads to unsatisfying performance when these methods are applied to multi-domain fake news detection. As an emerging field, multi-domain fake news detection (MFND) is increasingly attracting attention. However, data distributions, such as word frequency and propagation patterns, vary from domain to domain, namely domain shift. Facing the challenge of serious domain shift, existing fake news detection techniques perform poorly for multi-domain scenarios. Therefore, it is demanding to design a specialized model for MFND. In this paper, we first design a benchmark of fake news dataset for MFND with domain label annotated, namely Weibo21, which consists of 4,488 fake news and 4,640 real news from 9 different domains. We further propose an effective **Multi-domain Fake News Detection Model** (MDFEND) by utilizing a domain gate to aggregate multiple representations extracted by a mixture of experts. The experiments show that MDFEND can significantly improve the performance of multi-domain fake news detection. Our dataset and code are available at <https://github.com/kennqiang/MDFEND-Weibo21>.

CCS CONCEPTS

• **Computing methodologies** → **Transfer learning**; • **Information systems** → *Data mining*.

KEYWORDS

fake news detection; multi-domain; social media; dataset

ACM Reference Format:

Qiong Nan^{1,2,3}, Juan Cao^{1,2,*}, Yongchun Zhu^{1,2}, Yanyan Wang^{1,2}, Jintao Li¹. 2021. MDFEND: Multi-domain Fake News Detection. In *Proceedings of the 30th ACM International Conference on Information and Knowledge Management (CIKM '21)*, November 1–5, 2021, Virtual Event, QLD, Australia. ACM, New York, NY, USA, 5 pages. <https://doi.org/10.1145/3459637.3482139>

*Juan Cao is the corresponding author.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

CIKM '21, November 1–5, 2021, Virtual Event, QLD, Australia

© 2021 Copyright held by the owner/author(s). Publication rights licensed to ACM.

ACM ISBN 978-1-4503-8446-9/21/11...\$15.00

<https://doi.org/10.1145/3459637.3482139>

1 INTRODUCTION

In recent years, with the rapid popularization of the Internet, social media such as Sina Weibo [2] and Twitter [3], has become an important source to acquire news. However, it also serves as an ideal platform for fake news dissemination. According to Weibo's 2020 annual report on refuting rumors [41], there are 76,107 fake news pieces treated by authority all year round. Since fake news can cause devastating consequences to individuals and society, fake news detection is a critical problem that needs to be addressed.

To solve the problem, a variety of approaches have been proposed, and most of them [6, 15, 18, 22, 23] focus on single-domain fake news detection (SFND), e.g., politics, health. However, for a certain domain, the amount of fake news can be extremely limited. Therefore, based on such inadequate single-domain data, the performance of these detection models is unsatisfying. In practical scenarios, the real-world news platforms release various news in different domains everyday [35]. Therefore, it is promising to solve the data sparsity problem and improve the performance of all domains by exploiting data from multiple domains, called multi-domain fake news detection (MFND).

However, the data distributions vary from domain to domain, called domain shift [28, 46]. First, different domains have different word usage, for example, the most commonly used words in military news are "navy", "army", etc, while in educational news, "students", "university", "teacher", etc; Second, the propagation patterns vary a lot in different domains [35]. Facing the problem of serious domain shift, MFND can therefore be quite challenging. Moreover, some domains only contain very little labeled data, and this phenomenon further increases the difficulty in MFND, which remains unsolved yet with existing methods.

To study MFND, we build a comprehensive dataset Weibo21, which contains news from 9 domains, including Science, Military, Education, Disasters, Politics, Health, Finance, Entertainment and Society. Every domain contains news content, released timestamp, corresponding pictures and comments. Since fake news is intentionally created for financial or political gain, it often contains opinionated and inflammatory language. It is reasonable to exploit linguistic features of news content to detect fake news [34]. Timestamp and comments are also included with news, as timestamp can be used to do sequential analyses [23]. And comments can provide auxiliary signals especially when the posts don't contain abundant information [42]. In the end, Weibo21 contains 4,488 fake news and 4,640 real news from 9 different domains.

Due to the lack of systematic work of MFND, we adopt several multi-domain learning baselines [26, 31, 35, 40] and evaluate these multi-domain methods as well as several popular single-domain fake news detection methods [16, 23] on our proposed dataset

Weibo21. In addition, we propose a simple but effective Multi-domain Fake News Detection Model, namely MDFEND, which utilizes a domain gate to aggregate multiple representations extracted by a mixture of experts. Our experiments demonstrate the significant effectiveness improvement of the proposed MDFEND compared with the aforementioned baselines.

The main contributions of this work are summarized into three folds: (1) We construct Weibo21, an MFND dataset. To the best of our knowledge, this data repository is the first MFND dataset collected from one platform and contains the richest domains. (2) We proposed a simple but effective method named MDFEND for MFND. (3) We systematically evaluate MFND performance of different methods on our proposed Weibo21 dataset.

2 RELATED WORK

I. Fake News Detection. Many approaches have been proposed to tackle the challenges of fake news detection. Earlier studies used hand-craft features [5, 6, 10, 18]. Some recent research works use propagation patterns for structural modeling [11, 23, 24, 36], others jointly used both textual and visual features for multi-modal modeling [14, 30]. Ma et al. [25] and Li et al. [20] incorporated related tasks to assist fake news detection. Wang et al. [40] adopted the idea of the minimax game to extract event-invariant (domain-invariant) features, but neglected domain-specific features. Silver et al. [35] proposed to jointly preserve domain-specific as well as cross-domain knowledge to detect fake news from different domains, but they didn’t make full use of the domain information explicitly. **II. Multi-domain (multi-task) learning.** The thought of multi-domain (multi-task) learning is to jointly learn a group of domains (tasks), which has been proved effective in many applications [26, 31, 43–45]. These researches focus on capturing relationships of different tasks with multiple representations. And each task is reinforced by the interconnections, including inter-task relevance difference. However, these multi-domain (multi-task) frameworks aren’t fit for fake news detection. Therefore, it is necessary to design an appropriate and effective method for MFND.

Datasets. A few datasets have been constructed for fake news detection, including LIAR [39], CoAID [7], FakeHealth [8], Twitter16 [23] and Weibo [23, 42], however, they don’t have multi-domain information. FakeNewsNet [33] only contains two domains, including Politifact and GossipCop, which are insufficient for multi-domain fake news detection. Therefore, an appropriate multi-domain fake news dataset is desperately in need.

Table 1: Data Statistics of Weibo21

domain	Science	Military	Education	Disasters	Politics
real	143	121	243	185	306
fake	93	222	248	591	546
all	236	343	491	776	852

domain	Health	Finance	Entertainment	Society	All
real	485	959	1000	1198	4640
fake	515	362	440	1471	4488
all	1000	1321	1440	2669	9128

3 WEIBO21: A NEW DATASET FOR MFND

In this section, we describe the process of data collection for Weibo21, a multi-domain fake news dataset in Chinese, as well as how we determine the domain category of news pieces. Further, we conduct a preliminary data analysis based on news content, the most

straightforward clue in fake news detection, to show some domain differences explicitly.

3.1 Data Collection

We collect both fake and real news from Sina Weibo [2] ranging from **December 2014** to **March 2021**.

Initial Data Crawling. For fake data, we collect news pieces judged as misinformation officially by Weibo Community Management Center [4]. For real data, we gather real news pieces in the same period as the fake news, which have been verified by NewsVerify [1] (a platform that focuses on discovering and verifying suspicious news pieces on Weibo). For each piece of news, we collect (1) the most straightforward information, **news content**, (2) different modality, *i.e.*, **pictures**, (3) sequential signals, *i.e.*, **timestamp**, and (4) social context, *i.e.*, **comments**. Further, we gather **judgement information** for fake news, which can provide evidence to people and increase the credibility of our dataset.

Deduplication. The raw data contains lots of duplication, which may cause data leakage in training procedure, so we perform deduplication in one-pass clustering. Finally, 4,488 pieces of fake news and 4,640 pieces of real news are obtained.

3.2 Domain Annotation

After data collection, we perform categorization on crowd-sourcing. First, in order to work out the categorization criterion, we refer to domain lists from several well-known fact-checking websites, including Zhuoyaoji [47], Liuyanbaike [21], Jiaozhen [13], and Ruijianshiyao [32], as well as some research papers and reports, including Vosoughi et al. [38], 2017 Tencent Rumor Governance Report [37] and China Joint Internet Rumor-Busting Platform [29]. Considering the congruence as well as the appropriateness of granularity, we end with nine domains: **Science, Military, Education, Disasters, Politics, Health, Finance, Entertainment, and Society**. Then, we annotate all pieces of news into the above nine domains. To ensure the fairness of our annotation, 10 experts are employed to manually annotate the news. At first, the 10 experts annotate all the news independently, *i.e.* each piece of news is labeled by 10 experts; then they check the annotation with each other; The final domain label can be determined if more than 8 experts choose the same one, otherwise, they will discuss with each other till reaching to an agreement. The statistics of the collected datasets are shown in Table 1.

3.3 Preliminary Data Analysis

Weibo21 has multidimensional information related to news content, pictures, timestamp and comments. In order to quantify the differences among these domains, we perform some analyses. For example, news content is the most straightforward clue we can use for fake news detection. Therefore, we analysis the topic distribution of news among different domains. Figure 1 shows significant differences in the frequently used words. Due to limited space, we only demonstrate four of nine domains.

4 MDFEND: MULTI-DOMAIN FAKE NEWS DETECTION MODEL

In this section, we propose a novel framework, namely MDFEND, for MFND. Same as the single domain methods, we treat multi-domain fake news detection as a binary classification problem. The overall framework is shown as Figure 2.

Table 2: Multi-domain Fake News Detection Performance (f1-score)

model	Science	Military	Education	Accidents	Politics	Health	Finance	Entertainment	Society	All
TextCNN_single	0.7470	0.778	0.8882	0.8310	0.8694	0.9053	0.7909	0.8591	0.8727	0.8380
BiGRU_single	0.4876	0.7169	0.7067	0.7625	0.8477	0.8378	0.8109	0.8308	0.6067	0.7342
BERT_single	0.8192	0.7795	0.8136	0.7885	0.8188	0.8909	0.8464	0.8638	0.8242	0.8272
TextCNN_all	0.7254	0.8839	0.8362	0.8222	0.8561	0.8768	0.8638	0.8456	0.8540	0.8686
BiGRU_all	0.7269	0.8724	0.8138	0.7935	0.8356	0.8868	0.8291	0.8629	0.8485	0.8595
BERT_all	0.7777	0.9072	0.8331	0.8512	0.8366	0.9090	0.8735	0.8769	0.8577	0.8795
EANN	0.8225	0.9274	0.8624	0.8666	0.8705	0.9150	0.8710	0.8957	0.8877	0.8975
MMOE	0.8755	0.9112	0.8706	0.8770	0.8620	0.9364	0.8567	0.8886	0.8750	0.8947
MOSE	0.8502	0.8858	0.8815	0.8672	0.8808	0.9179	0.8672	0.8913	0.8729	0.8939
EDDFN	0.8186	0.9137	0.8676	0.8786	0.8478	0.9379	0.8636	0.8832	0.8689	0.8919
MDFEND	0.8301	0.9389	0.8917	0.9003	0.8865	0.9400	0.8951	0.9066	0.8980	0.9137

single domain at a time (e.g., train **TextCNN_single** on **Science** domain), and the results in the last column are the average of the ones in the former columns. In **mixed-domain baselines**, we perform experiment with one model on all domains at a time (e.g., train **TextCNN_all** on **all** domains), and calculate the f1-score of each domain respectively, while the results in the last column are not just the average of the ones in the former columns as in single domain baselines, but calculated using data from all domains. Models used in **multi-domain baselines** combine data from different domains according to their structures.

To make the baseline models work for MFND, based on their original designs, we made the following modifications in our experiments. **BERT** [9]: In our experiments, we freeze all layers in BERT, and average the word embeddings in the last layer as the sentence representation. A multi-layer perception (MLP) is stacked on the top to perform binary classification. **TextCNN** [16]: We employ the same convolutional structure as in our expert module. The input feature of TextCNN is embedded by word2vec. **BiGRU** [23]: Different from [23], we model each news piece as a sequential input to the BiGRU in order to preserve the sequential information. **EANN** [40]: We use this model to extract domain-independent features. We only use the textual branch, which is consistent with TextCNN in model structure. **MMOE** [26] and **MOSE** [31]: These two models are proposed for multi-task learning. We assume that fake news detection in multiple domains are different tasks, and use the two models for multi-domain fake news detection. **EDDFN** [35]: it is a model for cross-domain fake news detection, which models different domains implicitly and jointly preserves domain-specific and cross-domain knowledge. In our experiments, we abandon the domain discovery module and use our manually labeled domains for multi-domain fake news detection.

5.2 Experiment Setting

The details of our dataset Weibo21 are listed in Table 1. For a fair comparison, we set the same parameters for all methods. The MLP in these models uses the same structure with one dense layer (384 hidden units). For all experiments, the max length of the sentence is 170, and the dimension of embedding vectors of words is fixed to 768 for BERT [9] and 200 for Word2Vec [19, 27]. We employ the Adam [17] optimizer and search its learning rate from $1e-6$ to $1e-2$. For all methods, the mini-batch size is 64. In order to enhance the

credibility of our experiments, the process is performed for 10 times and the average f1-score is reported.

5.3 Results

We compare our MDFEND model with single-domain, mixed-domain and multi-domain methods to testify the effectiveness. The results are shown in Table 2. Experimental results further reveal several insightful observations.

- (1) Mixed-domain models and multi-domain models work much better than single-domain models in general, which demonstrates that additional data is of great importance.
- (2) Compared with mixed-domain models, multi-domain models perform better in general. This illustrates that multi-domain learning is useful and necessary for MFND.
- (3) Note that there are single-domain models performing better on a specific domain than the corresponding mixed-domain model (e.g., TextCNN_single v.s. TextCNN_all on Health domain), which illustrates that simply combining data from different domains may result in negative effect from additional data.
- (4) MFND models domain relationships better by feeding both domain embedding and content to the gate. Moreover, combining multiple domains softly is better than decouple domain-shared and domain-specific features roughly (EDDFN). Therefore, MDFEND model performs better than other multi-domain models.

6 CONCLUSION

In this paper, we study the problem of multi-domain fake news detection (MFND). We construct Weibo21, a MFND dataset. To the best of our knowledge, it is the first MFND dataset collected from one platform with richest domains; We propose a simple but effective method named MDFEND for MFND, which utilizes domain gate to aggregate multiple representations extracted by mixture-of-experts; We also systematically evaluated MFND performance with different methods on the proposed Weibo21 dataset, and experiments show the effectiveness of our MDFEND model.

ACKNOWLEDGMENTS

This work was supported by the Zhejiang Provincial Key Research and Development Program of China (2021C01164), and the National Natural Science Foundation of China (U1703261).

REFERENCES

- [1] [n.d.]. Newsverify. <http://service.account.weibo.com/>.
- [2] [n.d.]. Sina Weibo. <http://www.weibo.com>.
- [3] [n.d.]. Twitter. <http://www.twitter.com>.
- [4] [n.d.]. WeiboService. <https://www.newsverify.com/>.
- [5] Oluwaseun Ajao, Deepayan Bhowmik, and Shahrzad Zargari. 2019. Sentiment Aware Fake News Detection on Online Social Networks. In *ICASSP 2019-2019 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*. IEEE, 2507–2511.
- [6] Carlos Castillo, Marcelo Mendoza, and Barbara Poblete. 2011. Information Credibility on Twitter. In *Proceedings of the 20th international conference on World wide web*. 675–684.
- [7] Limeng Cui and Dongwon Lee. 2020. CoAID: COVID-19 Healthcare Misinformation Dataset. *arXiv preprint arXiv:2006.00885* (2020).
- [8] Enyan Dai, Yiwei Sun, and Suhang Wang. 2020. Ginger Cannot Cure Cancer: Battling Fake Health News with a Comprehensive Data Repository. In *Proceedings of the International AAAI Conference on Web and Social Media*, Vol. 14. 853–862.
- [9] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*. 4171–4186.
- [10] Anastasia Giachanou, Paolo Rosso, and Fabio Crestani. 2019. Leveraging Emotional Signals for Credibility Detection. In *Proceedings of the 42nd International ACM SIGIR Conference on Research and Development in Information Retrieval*. 877–880.
- [11] Han Guo, Juan Cao, Yazi Zhang, Junbo Guo, and Jintao Li. 2018. Rumor Detection with Hierarchical Social Attention Network. In *Proceedings of the 27th ACM International Conference on Information and Knowledge Management*. 943–951.
- [12] Robert A Jacobs, Michael I Jordan, Steven J Nowlan, and Geoffrey E Hinton. 1991. Adaptive Mixtures of Local Experts. *Neural computation* 3, 1 (1991), 79–87.
- [13] Jiaozhen. 2020. Jiaozhen Platform. <http://fact.qq.com/>. Accessed: June, 2021.
- [14] Zhiwei Jin, Juan Cao, Han Guo, Yongdong Zhang, and Jiebo Luo. 2017. Multimodal Fusion with Recurrent Neural Networks for Rumor Detection on Microblogs. In *Proceedings of the 25th ACM international conference on Multimedia*. 795–816.
- [15] Zhiwei Jin, Juan Cao, Han Guo, Yongdong Zhang, Yu Wang, and Jiebo Luo. 2017. Detection and Analysis of 2016 US Presidential Election Related Rumors on Twitter. In *International conference on social computing, behavioral-cultural modeling and prediction and behavior representation in modeling and simulation*. Springer, 14–24.
- [16] Yoon Kim. 2014. Convolutional Neural Networks for Sentence Classification. In *EMNLP*. 1746–1751.
- [17] Diederik P Kingma and Jimmy Ba. 2015. Adam: A Method for Stochastic Optimization. In *Proceedings of the 3rd International Conference Learning Representations (Poster)*.
- [18] Sejeong Kwon, Meeyoung Cha, Kyomin Jung, Wei Chen, and Yajun Wang. 2013. Prominent Features of Rumor Propagation in Online Social Media. In *2013 IEEE 13th international conference on data mining*. IEEE, 1103–1108.
- [19] Quoc Le and Tomas Mikolov. 2014. Distributed Representations of Sentences and Documents. In *Proceedings of the 31st International Conference on Machine Learning-Volume 32*. II–1188.
- [20] Quanzhi Li, Qiong Zhang, and Luo Si. 2019. Rumor Detection By Exploiting User Credibility Information, Attention and Multi-task Learning. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*. 1173–1179.
- [21] Liuyanbaike. 2020. Liuyanbaike Category. <https://liuyanbaike.com/category/>. Accessed: June, 2021.
- [22] Ben Ma, Dazhen Lin, and Donglin Cao. 2017. Content Representation for Microblog Rumor Detection. In *Advances in Computational Intelligence Systems*. Springer, 245–251.
- [23] Jing MA, Wei GAO, Prasenjit MITRA, Sejeong KWON, Bernard J JANSEN, Kam-Fai WONG, and Meeyoung CHA. [n.d.]. Detecting rumors from microblogs with recurrent neural networks.(2016). In *Proceedings of the 25th International Joint Conference on Artificial Intelligence (IJCAI 2016)*. 3818–3824.
- [24] Jing Ma, Wei Gao, and Kam-Fai Wong. 2017. Detect Rumors in Microblog Posts Using Propagation Structure via Kernel Learning. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*. 708–717.
- [25] Jing Ma, Wei Gao, and Kam-Fai Wong. 2018. Detect Rumor and Stance Jointly by Neural Multi-task Learning. In *Companion proceedings of the the web conference 2018*. 585–593.
- [26] Jiaqi Ma, Zhe Zhao, Xinyang Yi, Jilin Chen, Lichan Hong, and Ed H Chi. 2018. Modeling Task Relationships in Multi-task Learning with Multi-gate Mixture-of-Experts. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*. 1930–1939.
- [27] Tomas Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. 2013. Efficient Estimation of Word Representations in Vector Space. *arXiv preprint arXiv:1301.3781* (2013).
- [28] Sinno Jialin Pan and Qiang Yang. 2009. A Survey on Transfer Learning. *IEEE Transactions on knowledge and data engineering* 22, 10 (2009), 1345–1359.
- [29] China Joint Internet Rumor-Busting Platform. 2020. Piyao. <http://www.piyao.org.cn/>. Accessed: June, 2021.
- [30] Peng Qi, Juan Cao, Tianyun Yang, Junbo Guo, and Jintao Li. 2019. Exploiting Multi-domain Visual Information for Fake News Detection. In *2019 IEEE International Conference on Data Mining (ICDM)*. IEEE, 518–527.
- [31] Zhen Qin, Yicheng Cheng, Zhe Zhao, Zhe Chen, Donald Metzler, and Jingzheng Qin. 2020. Multitask Mixture of Sequential Experts for User Activity Streams. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*. 3083–3091.
- [32] Ruijianshiyao. 2020. Ruijianshiyao. <http://www.newsverify.com>. Accessed: June, 2021.
- [33] Kai Shu, Deepak Mahudeswaran, Suhang Wang, Dongwon Lee, and Huan Liu. 2020. FakeNewsNet: A Data Repository with News Content, Social Context, and Spatiotemporal Information for Studying Fake News on Social Media. *Big Data* 8, 3 (2020), 171–188.
- [34] Kai Shu, Amy Sliva, Suhang Wang, Jiliang Tang, and Huan Liu. 2017. Fake News Detection on Social Media: A Data Mining Perspective. *ACM SIGKDD explorations newsletter* 19, 1 (2017), 22–36.
- [35] Amila Silva, Ling Luo, Shanika Karunasekera, and Christopher Leckie. 2021. Embracing Domain Differences in Fake News: Cross-domain Fake News Detection using Multimodal Data. In *Proceedings of the AAAI Conference on Artificial Intelligence*, Vol. 35. 557–565.
- [36] Changhe Song, Cheng Yang, Huimin Chen, Cunchao Tu, Zhiyuan Liu, and Maosong Sun. 2019. CED: Credible Early Detection of Social Media Rumors. *IEEE Transactions on Knowledge and Data Engineering* (2019).
- [37] Tencent. 2020. Tencent Rumor Government Report. <https://tech.qq.com/a/20171220/026316.htm>. Accessed: June, 2021.
- [38] Soroush Vosoughi, Deb Roy, and Sinan Aral. 2018. The Spread of True and False News Online. *Science* 359, 6380 (2018), 1146–1151.
- [39] William Yang Wang. 2017. “Liar, Liar Pants on Fire”: A New Benchmark Dataset for Fake News Detection. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*. 422–426.
- [40] Yaqing Wang, Fenglong Ma, Zhiwei Jin, Ye Yuan, Guangxu Xun, Kishlay Jha, Lu Su, and Jing Gao. 2018. EANN: Event Adversarial Neural Networks for Multimodal Fake News Detection. In *Proceedings of the 24th acm sigkdd international conference on knowledge discovery & data mining*. 849–857.
- [41] Weibopiyao. 2020. Weibo 2020’s Annual Report on Refuting Rumors. https://weibo.com/weibopiyao?profile_ftype=1&is_all=1&is_search=1&key_word=2020. Accessed: June, 2021.
- [42] Xueyao Zhang, Juan Cao, Xirong Li, Qiang Sheng, Lei Zhong, and Kai Shu. 2021. Mining Dual Emotion for Fake News Detection. In *Proceedings of the Web Conference 2021*. 3465–3476.
- [43] Jiejie Zhao, Bowen Du, Leilei Sun, Fuzhen Zhuang, Weifeng Lv, and Hui Xiong. 2019. Multiple Relational Attention Network for Multi-task Learning. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*. 1123–1131.
- [44] Yongchun Zhu, Yudan Liu, Ruobing Xie, Fuzhen Zhuang, Xiaobo Hao, Kaikai Ge, Xu Zhang, Leyu Lin, and Juan Cao. 2021. Learning to Expand Audience via Meta Hybrid Experts and Critics for Recommendation and Advertising. In *Proceedings of the 27th ACM SIGKDD Conference on Knowledge Discovery & Data Mining (Virtual Event, Singapore) (KDD ’21)*. Association for Computing Machinery, New York, NY, USA, 4005–4013.
- [45] Yongchun Zhu, Fuzhen Zhuang, and Deqing Wang. 2019. Aligning Domain-Specific Distribution and Classifier for Cross-Domain Classification from Multiple Sources. In *Proceedings of the AAAI Conference on Artificial Intelligence*, Vol. 33. 5989–5996.
- [46] Fuzhen Zhuang, Zhiyuan Qi, Keyu Duan, Dongbo Xi, Yongchun Zhu, Hengshu Zhu, Hui Xiong, and Qing He. 2020. A Comprehensive Survey on Transfer Learning. *Proc. IEEE* 109, 1 (2020), 43–76.
- [47] Zhuoyaoji. 2020. Top Rumors from Six Domains. <https://weibo.com/6590980486/Gsv5rF7nL>. Accessed: June, 2021.