
THE DARK SIDE OF THE LANGUAGE: PRE-TRAINED TRANSFORMERS IN THE DARKNET

Leonardo Ranaldi (*,*)

Aria Nourbakhsh (*)

Arianna Patrizi (*)

Elena Sofia Ruzzetti (*)

(*) Department of Innovation and Information Engineering,
Guglielmo Marconi University, 00193 Roma,
Italy;
{l.ranaldi}@unimarconi.it

Dario Onorati (*,◇)

Francesca Fallucchi(*,*)

Fabio Massimo Zanzotto

(*) ART Group

Department of Enterprise Engineering,
University of Rome Tor Vergata,
Viale del Politecnico, 1, 00133 Rome,
Italy;

(◇) Department of Computer, Automation and Management Engineering,
University of Rome "Sapienza",
P. A. Moro 2, Roma, Italy,
Italy;

ABSTRACT

Pre-trained Transformers are challenging human performances in many natural language processing tasks. The gigantic datasets used for pre-training seem to be the key for their success on existing tasks. In this paper, we explore how a range of pre-trained natural language understanding models perform on truly novel and unexplored data, provided by classification tasks over a DarkNet corpus. Surprisingly, results show that syntactic and lexical neural networks largely outperform pre-trained Transformers. This seems to suggest that pre-trained Transformers have serious difficulties in adapting to radically novel texts.

Keywords Natural Language Processing · Machine Learning · Darkweb · Cyberspace

1 Introduction

Pre-trained Transformers [36, 15, 54, 38] are outperforming humans in many natural language processing tasks [48, 47] and, thus, are wiping out all other methods for natural language understanding. Pre-training seems to give Transformers crystal clear models of target languages. BERT is pre-trained on an English corpus of 3,300M words consisting of books [56] and Wikipedia. The English version of the last ERNIE [44] is trained on an even bigger corpus, and its Chinese version is trained on 14TB corpus. MEGATRON-LM [41] is trained on an incredible corpus of 174 GB. The race is always towards training over bigger corpora.

The gigantic datasets used for pre-training seem to be the key to the success of Transformers. It may seem that Transformers have success in downstream tasks because they have seen large parts of possible sentences. Sometimes,

this possible shortcoming is taken into consideration when a novel Transformer is introduced [39, 41]. Radford et al. [39] have excluded Wikipedia pages for pre-training as it is a common data source for other datasets. Yet, when using off-the-shelf pre-trained models, this effect is generally disregarded. For example, the discovering ongoing conversation (DOC) task was found challenging for humans but BERT baseline model achieved the astonishing 88.4 F1 score [47]. DOC consists of determining if two utterances are contiguous in classical theatrical plays. These plays may be included in the book dataset [56] used for pre-training BERT.

Corpora and related tasks derived from the DeepWeb and DarkWeb [6, 12] offer a tremendous opportunity to study the effect of overfitting for different natural language understanding models. Indeed, it is extremely rare that texts extracted from these sources are included in pre-training corpora. Moreover, language on the DarkNet may have very different characteristics with respect to the one accessible from the surface web [12].

In this paper, we aim to explore how pre-trained natural language understanding models behave on really unseen data or really unexplored linguistic registers and styles. This unseen data is given by the DarkNet corpus along with a classification task. We experimented with: Stylistic Classifiers based on the bleaching text model [45], with Lexical Neural Networks based on GloVe [35] and word2vec[29], with Syntactic-based neural networks based on KERMIT [53], and with holistic Transformers such as BERT [15], XLNet [52], ERNIE [54] and Electra [13]. Results show that syntactic and lexical neural networks surprisingly outperform pre-trained Transformers. This seems to suggest that pre-trained Transformers have serious difficulty in adapting to really unseen texts.

The rest of the paper is organized in: Material and Methods; Results and Discussion; and, Conclusions.

2 Material and Methods

2.1 Material: A Dark Web Dataset

Corpora scraped from DarkWeb to fight illegal actions are good testbeds for studying large pre-trained models on totally new texts, as these are not covered by the corpora used for pre-training.

Nabki et al. [32], following Choshen et al. [12]’s instructions, sampled “Darknet Usage Text Addresses” (DUTA-10k) from the DarkWeb. This dataset proposes the task of classifying legal and illegal activities on the domain of forums and drug markets.

To compare with the data from surface web, Nabki et al. [32] have extracted item descriptions from eBay as well.

The descriptions were selected by searching the keywords (marijuana, weed, grass, and drug); these were divided by paragraphs and filtered, producing a corpus without repetition. The texts of the corpus were extracted from links provided by Choshen et al. [12]¹ and pre-processed by removing: HTML tags, non-linguistic content such as buttons, encryption keys, metadata, and common words such as “Show more results”.

The corpus DUTA-10k contains data collected and divided into five different subsets: (1) eBay items, (2) legal drugs, (3) illegal drugs, (4) forums discussing legal activities and (5) forums discussing illegal topics. The number of samples of each dataset and their corresponding categories is presented in table 1. Since the aim is to classify legal vs illegal activities [12], the subsets are used for four different experiments: (1) eBay vs. legal drugs, (2) legal vs illegal drugs, (3) legal vs illegal forums and finally, (4) legal and illegal drugs training data vs the test set of legal and illegal forums.

2.2 Methods: Classification Models

This section introduces the models which we used to investigate the role of pre-training in transformers when applied to truly uncovered texts.

Stylistic Classifier Legal and illegal activities may be described with different styles of language: a formal language vs a more informal style of writing. For this reason, we tested an SVM classifier that uses some stylistic characteristics captured from the surface properties of the tokens. This classifier is used to determine if analyzed tasks are purely stylistic.

Bleaching text [45] is a model proposed to capture the style of writing at the word level. Originally, it has been applied for cross-lingual author’s gender prediction. To capture the style, this model converts sequences of tokens, e.g., ‘1x Pcs Mobile Case! ? US\$65’, into abstract sequences according to the following rules presented with the effect on the example:

¹data and code are available in Choshen et al. [12] GitHub repository <https://github.com/huji-nlp/cyber>

dataset	# tokens	# samples	# samples in class	
Ebay vs legal drugs	24,795	924	Ebay 456	legal drugs 468
- train				
- dev	2,623	103	53	50
- test	2,802	115	62	53
Onion forums	15,409	924	illegal 468	legal 456
- train				
-dev	1,478	103	50	53
-test	1,640	115	53	62
Onion drugs	25,582	924	illegal 468	legal 456
- train				
-dev	2,416	103	50	53
-test	2,995	115	53	62

Table 1: Distribution of examples and classes

Corpus	Size
BooksCorpus [57]	800M words
2010-and-2014-English Wikipedia dump	2,500M words
Giga5 [34]	16GB
Common Crawl [14]	110GB
ClueWeb [10]	19GB
Penn Treebank [28]	1M words

Table 2: Pre-training corpora with their size. All corpora are derived from the surface web.

(1) each token is replaced by its length (effect: ‘02 03 06 06 05’); (2) alphanumeric characters are merged into one single letter and other characters are kept (effect: ‘W W W W!? W\$W’);

(3) punctuation marks are transformed into a unified character (effect: ‘W W W WPP W’); (4)

upper case letters are replaced with ‘u’, lower case letters with ‘l’, digits with ‘d’, and the rest to ‘x’ (effect: ‘dl ull ull ullxx uuxdd’); (5) consonants are replaced with ‘c’, vowels to ‘v’ and the rest to ‘o’ (effect: ‘oc ccc cvcvcv cvcvoovcoco’). Finally, a sample is represented by the concatenation of all the above transformations. For classification, we use a linear SVM classifier with a binary bag of word representation.

Lexical-based Neural Networks To investigate the role of pre-trained word embeddings, we used a classifier based on a vanilla feed-forward neural networks (FFN) over a bag-of-words-embedding (BoE) representation of sentences. In BoE, sentence representations are computed as the sum of word embeddings representing their words.

We experimented with two versions of the classifier: BoE(GloVe) and BoE(re-train). BoE(GloVe) uses GloVe word embeddings [35] trained on 2014 Wikipedia dumps and Giga5 (see Table 1). BoE(re-train) uses word embeddings learnt on the novel corpus using a CBOW model of word2vec [29]. This latter model is trained with 300 dimensions for 5 epochs.

The supporting FFNs of BoE(GloVe) and BoE(re-train) are slightly different. In BoE(GloVe), the FFN consists of an input layer of dimension 300, 2 hidden layers of 150 and 50 dimensions with the *ReLU* activation function. In the BoE(re-train), the FFN consists of two layers of 150 neurons. *tanh* activation function is used for each layer.

Syntactic-based Neural Networks To evaluate the role of “pre-trained” universal syntactic models, we used the Kernel-inspired Encoder with Recursive Mechanism for Interpretable Trees (KERMIT) [53]. This model positively exploits parse trees in neural networks as it increases performances of pre-trained Transformers when it is used in combined models.

The version used in the experiments encodes parse trees in vectors of 4,000 dimensions. The rest of the feed-forward network is composed of 2 hidden layers of dimension 4,000 and 2,000 respectively, finally the output layer of dimension 2. Between each layer the *ReLU* activation function and a dropout of 0.1 is used to avoid overfitting on the train data.

Even in this case, the model is somehow ‘pre-trained’. In fact, KERMIT exploits parse trees produced by a traditional parser. In our experiments, we used the English constituency-based parser in CoreNLP [55]. The parser is trained on the standard WSJ Penn Treebank [28], which contains only around 1M words.

	eBay/Legal Drugs	Drugs	Forums	Drugs/Forums
<i>NB (POS)</i> [12]	91.4	77.6	74.1	78.4
<i>SVM (POS)</i> [12]	63.8	63.8	85.3	62.1
Holistic Transformers				
<i>BERT_{base}</i>	65.30(±2.6)	64.63(±3.4)	52.60(±0.7)	47.40(±3.93)
<i>BERT_{multi}</i>	49.50(±2.3)	51.30(±2.93)	51.32(±2.42)	48.29(±3.85)
<i>Electra</i>	70.20(3.8)	58.60(±4.36)	52.70(±2.84)	49.39(±4.62)
<i>XLNet</i>	57.30(±3.6)	54.30(±2.77)	51.60(±1.93)	50.83(±2.68)
<i>Ernie</i>	67.65(±4.73)	56.87(±4.29)	50.61(±3.8)	48.25(±2.53)
Lexical Models				
<i>BoE(GloVe)</i>	91.50(±0.5)	81.60(±1.4)	54.60(±1.4)	53.50(±1.5)
<i>BoE(re-trained)</i>	87.13(±0.01)	74.08(±0.01)	57.22(±0.01)	50.26(±0.02)
Syntactic Models: KERMIT	90.50(±1.0)	79.00(±1.0)	66.60(±1.4)	58.37(±1.26)
Stylistic models: Bleaching text	81.73	79.13	55.65	54.78
Lexical and Syntactic Models				
<i>BoE(GloVe) + KERMIT</i>	93.54 (±1.46)	83.10 (±1.4)	66.20(±1.4)	54.30(±2.34)
<i>BoE(re-trained)+KERMIT</i>	88.69(±1.23)	80.03(±0.97)	58.50(±1.4)	52.34(±2.3)

Table 3: Accuracy of the different pre-trained models on the Legal vs. Illegal Classification Task on the DarkWeb Corpus [12]. The first two lines are results provided in [12]. Experiments with neural networks are obtained over 5 runs with different seeds.

Holistic Transformers We tested the following Transformers to cover the majority of cases of pre-training size (see Table 2) and models:

- *BERT_{base}* [15], the architecture Bidirectional Encoder Representations from Transformers, trained on the BooksCorpus [57] and English Wikipedia and the Multi-lingual *BERT_{multi}* [37] trained on a Wikipedia dump of 100 languages. Both implementations are from the Huggingface’s Transformers library [50];
- XLNet [52], which is based on a generalised autoregressive pre-training technique that allows the learning of bidirectional contexts by maximising the expected likelihood over all permutations of the factorization order and to its autoregressive formulation. XLNet is trained on 32.89 billion tokens, taken from datasets gathered from the surface web or publicly available datasets, such as Wikipedia, Bookcorpus, Giga5, Clueweb and Common Crawl.
- ERNIE [44] introduced a language model representation that addresses the inadequacy of BERT and utilises external knowledge graph for named entities. ERNIE is pre-trained on Wikipedia corpus and Wikidata knowledge base.
- ELECTRA [13] Compared to BERT, instead of masking an input token, they “corrupt” it by replacing it with a token that potentially fits the place. Training procedure is a classification of each token on if it is a corrupted input or not. To make its performance comparable to BERT, they have trained the model on the same dataset that BERT was trained on.

3 Results and Discussion

We explored the performance of all the pre-trained models on the dataset and the tasks described in section 2.1. Results reported in Table 3 show unexpected behavior of these models.

The proposed tasks cannot be solved using only stylistic features. Stylistic models are performing worse with respect to lexical, syntactic and combined models in three tasks out of four. The task where stylistic models are performing better is the one where models are trained on legal/illegal Drugs and tested on legal/illegal Forums. In this case, lexicon only cannot help in drawing decisions and stylistic features are useful discriminating factors.

General lexical knowledge is basically important when dealing with completely novel texts. Indeed, pre-trained lexical models have generally higher results with respect to re-trained lexical models: BoE(Glove) outperforms BoE(re-trained) on three out of the four tasks (see Table 3). Hence, re-training word embeddings with a small corpus seem to be useless. In fact, re-training adds information in only one sub-task: dealing with legal vs. illegal forums (57.22 vs. 54.60).

Surprisingly, holistic Transformers have poor performance on this totally uncovered corpus and on the defined tasks. *BERT_{base}*, *BERT_{multi}*, *Electra*, *XLNet* and *Ernie* have worse performances with respect to all the other models.

Considering that there is an overlap between the data used for training the *BoE(GloVe)* model and the transformer-based models, their poor performance is unexpected.

However, neural network models based on syntax have extremely interesting performances on this dataset. KERMIT [53] behaves better than holistic Transformers, showing that these tasks are sensitive with respect to syntactic information. The major difference is that KERMIT uses a parser [27], which is pre-trained on a definitely smaller training set.

Moreover, the combined “pre-trained” lexical and syntactic model, that is, *BoE(GloVe)* + KERMIT, outperforms previous state-of-the-art on two subtasks out of four. This shows that the two combined models can exploit their pre-training on totally new, unseen language and tasks.

In conclusion, selected tasks are on a completely novel dataset and are sensitive with respect to lexical and syntactic information. Yet, pre-trained Transformers seem not to be able to solve these tasks, although these Transformers are able to deal with lexical and syntactic information [24, 21, 22]. This contradiction seems to be a possible evidence of the fact that large pre-training may force Transformers to overfit on seen data. This overfitting possibly happens at the sentence level so they cannot capture stylistic and syntactic differences.

4 Conclusion

Transformers are successful on many downstream tasks, and it stems from the huge corpora that they are trained on. As a result, investigation of their strengths and weaknesses is important. In this paper, we aimed to explore how pre-trained natural language understanding models perform in totally unknown and unprecedented contexts, such as the DarkNet. We conducted extensive experiments to investigate the performance of stylistic, lexical style, syntactic, and holistic approaches. The results show that syntactic and lexical neural networks surprisingly outperform pre-trained Transformers, which indicates that Transformers have difficulty adapting to unknown texts.

References

- [1] Alfred V. Aho and Jeffrey D. Ullman. *The Theory of Parsing, Translation and Compiling*, volume 1. Prentice-Hall, Englewood Cliffs, NJ, 1972.
- [2] Mhd Wesam Al Nabki, Eduardo Fidalgo, Enrique Alegre, and Ivan de Paz. Classifying illegal activities on tor network based on web textual contents. In *Proceedings of the 15th Conference of the European Chapter of the Association for Computational Linguistics: Volume 1, Long Papers*, pages 35–43, Valencia, Spain, April 2017. Association for Computational Linguistics.
- [3] American Psychological Association. *Publications Manual*. American Psychological Association, Washington, DC, 1983.
- [4] Rie Kubota Ando and Tong Zhang. A framework for learning predictive structures from multiple tasks and unlabeled data. *Journal of Machine Learning Research*, 6:1817–1853, December 2005.
- [5] Galen Andrew and Jianfeng Gao. Scalable training of L1-regularized log-linear models. In *Proceedings of the 24th International Conference on Machine Learning*, pages 33–40, 2007.
- [6] Georgia Avarikioti, Roman Brunner, Aggelos Kiayias, Roger Wattenhofer, and Dionysis Zindros. Structure and content of the visible darknet, 2018.
- [7] Georgia Avarikioti, Roman Brunner, Aggelos Kiayias, Roger Wattenhofer, and Dionysis Zindros. Structure and content of the visible darknet. *CoRR*, abs/1811.01348, 2018.
- [8] Alex Biryukov, Ivan Pustogarov, Fabrice Thill, and Ralf-Philipp Weinmann. Content and popularity analysis of tor hidden services. *2014 IEEE 34th International Conference on Distributed Computing Systems Workshops (ICDCSW)*, pages 188–193, 2014.
- [9] Rubel Biswas, Eduardo Fidalgo, and Enrique Alegre. Recognition of service domains on tor dark net using perceptual hashing and image classification techniques. In *8th International Conference on Imaging for Crime Detection and Prevention (ICDP 2017)*, pages 7–12, 2017.
- [10] Jamie Callan, Mark Hoy, Changkuk Yoo, and Le Zhao. Clueweb09 data set, 2009.
- [11] Ashok K. Chandra, Dexter C. Kozen, and Larry J. Stockmeyer. Alternation. *Journal of the Association for Computing Machinery*, 28(1):114–133, 1981.
- [12] Leshem Choshen, Dan J. Eldad, Daniel Hershovich, Elior Sulem, and Omri Abend. The language of legal and illegal activity on the darknet. In *ACL*, 2019.

- [13] Kevin Clark, Minh-Thang Luong, Quoc V. Le, and Christopher D. Manning. ELECTRA: Pre-training text encoders as discriminators rather than generators. In *ICLR*, 2020.
- [14] Common Crawl. Common crawl. URL: <http://commoncrawl.org>, 2019.
- [15] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding, 2019.
- [16] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics.
- [17] Susan Dumais and Hao Chen. Hierarchical classification of web content. In *Proceedings of the 23rd Annual International ACM SIGIR Conference on Research and Development in Information Retrieval*, SIGIR '00, page 256–263, New York, NY, USA, 2000. Association for Computing Machinery.
- [18] Eduardo Fidalgo, Enrique Alegre, Víctor González-Castro, and Laura Fernández-Robles. Illegal activity categorisation in darknet based on image classification using creic method. pages 600–609, 01 2018.
- [19] Michał Graczyk and Kevin Kinningham. Automatic product categorization for anonymous marketplaces. 2015.
- [20] Dan Gusfield. *Algorithms on Strings, Trees and Sequences*. Cambridge University Press, Cambridge, UK, 1997.
- [21] John Hewitt and Christopher D. Manning. A structural probe for finding syntax in word representations. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4129–4138, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics.
- [22] Jennifer Hu, Jon Gauthier, Peng Qian, Ethan Wilcox, and Roger Levy. A systematic assessment of syntactic generalization in neural language models. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 1725–1744, 2020.
- [23] George Hurlburt. Shining light on the dark web. *Computer*, 50(4):100–105, 2017.
- [24] Ganesh Jawahar, Benoît Sagot, and Djamé Seddah. What does bert learn about the structure of language. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 3651–3657, 2019.
- [25] Min-Yen Kan. Web page classification without the web page. In *Proceedings of the 13th International World Wide Web Conference on Alternate Track Papers & Posters*, WWW Alt. '04, page 262–263, New York, NY, USA, 2004. Association for Computing Machinery.
- [26] Taku Kudo and John Richardson. Sentencepiece: A simple and language independent subword tokenizer and detokenizer for neural text processing, 2018.
- [27] Christopher Manning, Mihai Surdeanu, John Bauer, Jenny Finkel, Steven Bethard, and David McClosky. The Stanford CoreNLP natural language processing toolkit. In *Proceedings of 52nd Annual Meeting of the Association for Computational Linguistics: System Demonstrations*, pages 55–60, Baltimore, Maryland, June 2014. Association for Computational Linguistics.
- [28] Mitchell P. Marcus, Beatrice Santorini, and Mary Ann Marcinkiewicz. Building a large annotated corpus of English: The Penn Treebank. *Computational Linguistics*, 19(2):313–330, 1993.
- [29] Tomas Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. Efficient estimation of word representations in vector space. *arXiv preprint arXiv:1301.3781*, 2013.
- [30] Daniel Moore and Thomas Rid. Cryptopolitik and the darknet. *Survival*, 58(1):7–38, 2016.
- [31] Steven J. Murdoch. Hot or not: Revealing hidden services by their clock skew. In *Proceedings of the 13th ACM Conference on Computer and Communications Security*, CCS '06, page 27–36, New York, NY, USA, 2006. Association for Computing Machinery.
- [32] Mhd Wesam Al Nabki, Eduardo FIDALGO, Enrique Alegre, and Laura Fernández-Robles. Torank: Identifying the most influential suspicious domains in the tor network. *Expert Syst. Appl.*, 123:212–226, 2019.
- [33] L. Overlier and P. Syverson. Locating hidden servers. In *2006 IEEE Symposium on Security and Privacy (S P'06)*, pages 15 pp.–114, 2006.
- [34] R Parker, D Graff, J Kong, K Chen, and K Maeda. English gigaword fifth edition ldc2011t07 (tech. rep.). Technical report, Technical Report. Linguistic Data Consortium, Philadelphia, 2011.

- [35] Jeffrey Pennington, Richard Socher, and Christopher Manning. GloVe: Global vectors for word representation. In *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 1532–1543, Doha, Qatar, October 2014. Association for Computational Linguistics.
- [36] Matthew E. Peters, Mark Neumann, Mohit Iyyer, Matt Gardner, Christopher Clark, Kenton Lee, and Luke Zettlemoyer. Deep contextualized word representations. In *Proc. of NAACL*, 2018.
- [37] Telmo Pires, Eva Schlinger, and Dan Garrette. How multilingual is multilingual bert?, 2019.
- [38] Alec Radford and Karthik Narasimhan. Improving language understanding by generative pre-training. 2018.
- [39] Alec Radford, Jeff Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language models are unsupervised multitask learners. 2019.
- [40] Mohammad Sadegh Rasooli and Joel R. Tetreault. Yara parser: A fast and accurate dependency parser. *Computing Research Repository*, arXiv:1503.06733, 2015. version 2.
- [41] Mohammad Shoeybi, Mostofa Ali Patwary, Raul Puri, Patrick LeGresley, Jared Casper, and Bryan Catanzaro. Megatron-LM: Training multi-billion parameter language models using model parallelism. *ArXiv*, abs/1909.08053, 2019.
- [42] Weifeng Su, Jiyang Wang, and Frederick Lochovsky. Automatic hierarchical classification of structured deep web databases. In *Proceedings of the 7th International Conference on Web Information Systems, WISE'06*, page 210–221, Berlin, Heidelberg, 2006. Springer-Verlag.
- [43] Aixin Sun, Ee-Peng Lim, and Wee-Keong Ng. Web classification using support vector machine. In *Proceedings of the 4th International Workshop on Web Information and Data Management, WIDM '02*, page 96–99, New York, NY, USA, 2002. Association for Computing Machinery.
- [44] Yu Sun, Shuohuan Wang, Shikun Feng, Siyu Ding, Chao Pang, Junyuan Shang, Jiayang Liu, Xuyi Chen, Yanbin Zhao, Yuxiang Lu, Weixin Liu, Zhihua Wu, Weibao Gong, Jianzhong Liang, Zhizhou Shang, Peng Sun, Wei Liu, Xuan Ouyang, Dianhai Yu, Hao Tian, Hua Wu, and Haifeng Wang. Ernie 3.0: Large-scale knowledge enhanced pre-training for language understanding and generation. *ArXiv*, abs/2107.02137, 2021.
- [45] Rob van der Goot, Nikola Ljubešić, Ian Matroos, Malvina Nissim, and Barbara Plank. Bleaching text: Abstract features for cross-lingual gender prediction. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 383–389, Melbourne, Australia, July 2018. Association for Computational Linguistics.
- [46] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pages 5998–6008, 2017.
- [47] Alex Wang, Yada Pruksachatkun, Nikita Nangia, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel R. Bowman. SuperGlue: A stickier benchmark for general-purpose language understanding systems, 2020.
- [48] Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel Bowman. GLUE: A multi-task benchmark and analysis platform for natural language understanding. In *Proceedings of the 2018 EMNLP Workshop BlackboxNLP: Analyzing and Interpreting Neural Networks for NLP*, pages 353–355, Brussels, Belgium, November 2018. Association for Computational Linguistics.
- [49] Gabriel Weimann. Going dark: Terrorism on the dark web. *Studies in Conflict & Terrorism*, 39(3):195–206, 2016.
- [50] Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, R’emi Louf, Morgan Funtowicz, and Jamie Brew. HuggingFace’s Transformers: State-of-the-art Natural Language Processing. *ArXiv*, abs/1910.0, 2019.
- [51] He-Xiang Xu, Xiu-Lan Hao, Shu-Yun Wang, and Yun-Fa Hu. A method of deep web classification. In *2007 International Conference on Machine Learning and Cybernetics*, volume 7, pages 4009–4014, 2007.
- [52] Zhilin Yang, Zihang Dai, Yiming Yang, Jaime G. Carbonell, Ruslan Salakhutdinov, and Quoc V. Le. Xlnet: Generalized autoregressive pretraining for language understanding. In *NeurIPS*, 2019.
- [53] Fabio Massimo Zanzotto, Andrea Santilli, Leonardo Ranaldi, Dario Onorati, Pierfrancesco Tommasino, and Francesca Fallucchi. KERMIT: Complementing transformer architectures with encoders of explicit syntactic interpretations. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 256–267, Online, November 2020. Association for Computational Linguistics.
- [54] Zhengyan Zhang, Xu Han, Zhiyuan Liu, Xin Jiang, Maosong Sun, and Qun Liu. Ernie: Enhanced language representation with informative entities, 2019.

- [55] Muhua Zhu, Yue Zhang, Wenliang Chen, Min Zhang, and Jingbo Zhu. Fast and accurate shift-reduce constituent parsing. In *Proceedings of the 51st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 434–443, Sofia, Bulgaria, August 2013. Association for Computational Linguistics.
- [56] Yukun Zhu, Ryan Kiros, Rich Zemel, Ruslan Salakhutdinov, Raquel Urtasun, Antonio Torralba, and Sanja Fidler. Aligning books and movies: Towards story-like visual explanations by watching movies and reading books. In *2015 IEEE International Conference on Computer Vision (ICCV)*, pages 19–27, 2015.
- [57] Yukun Zhu, Ryan Kiros, Richard Zemel, Ruslan Salakhutdinov, Raquel Urtasun, Antonio Torralba, and Sanja Fidler. Aligning books and movies: Towards story-like visual explanations by watching movies and reading books, 2015.