Conditional entropy minimization principle for learning domain invariant representation features

Thuan Nguyen*, Boyang Lyu*, Prakash Ishwar[†], Matthias Scheutz[‡] and Shuchin Aeron*

*Department of Electrical and Computer Engineering, Tufts University, Medford, MA 02155

[†]Department of Electrical and Computer Engineering, Boston University, Boston, MA 02215

[‡]Department of Computer Science, Tufts University, Medford, MA 02155

Email: Thuan.Nguyen@tufts.edu, Boyang.Lyu@tufts.edu, pi@bu.edu, Matthias.Scheutz@tufts.edu, Shuchin@ece.tufts.edu

Abstract-Invariance principle-based methods, for example, Invariant Risk Minimization (IRM), have recently emerged as promising approaches for Domain Generalization (DG). Despite promising theory, invariance principle-based approaches the fail in common classification tasks due to the mixture of the true invariant features and the spurious invariant features. In this paper, we propose a framework based on the conditional entropy minimization principle to filter out the spurious invariant features leading to a new algorithm with a better generalization capability. We theoretically prove that under some particular assumptions, the representation function can precisely recover the true invariant features. In addition, we also show that proposed approach is closely related to the well-known the Information Bottleneck framework. Both the theoretical and numerical results are provided to justify our approach.

I. INTRODUCTION

A fundamental assumption in most statistical machine learning algorithms is that the training data and the test data are independently and identically distributed (i.i.d). However, this fundamental assumption is usually violated in practice due to a phenomenon called distribution shift where the training data and the test data might not share the same distribution, leading to a deterioration of generalization. To address these failures, Domain Generalization which aims to learn a model from several different seen domains so that it generalizes well to unseen related domains has recently received much attention.

Over the past decade, many methods are proposed to overcome the challenging settings of Domain Generalization. Notably, Invariant Risk Minimization [1] [2] emerged as one of the most promising methods which is constructed based on a widely accepted assumption that the representations are general and transferable if the feature representations remain invariant from domain to domain. Despite the promising theory, invariance principle-based approaches, for example, Invariant Risk Minimization, fail in many simple settings where the spurious invariant features exist. A particular example is the problem of classification the cow and the camel images [3] [4] where the label is a deterministic function of the invariant features, for example, the shape of animals and does not depend on the spurious features, for example, the background. However, because the cow usually appears in a picture with a greenfield while the camel lives in a desert with a yellow background, the background becomes a spurious invariant feature. Classification based on spurious features might be

dangerous, for example, if the cow is placed in a yellow field, then it may be misclassified to a camel. Therefore, even though the invariance principle-based approach is able to learn invariant features, it may still fail in the classification task if the extracted features contain not only the true invariant features but also the spurious invariant features. We also note that these spurious features can be eliminated if one can observe a large enough number of domains [5] [6]. For example, if the seen domain contains a picture of a cow walking on a desert, then the greenfield background is obviously not an invariant feature. However, noting that in practice, collecting the data of all possible domains is expensive.

To address this issue, one needs a framework to deal with spurious invariant features. For example, in [7], Ahuja et al. want to minimize the entropy of the extracted features to filter out the spurious features. Although a theoretical justification is provided, this approach is limited at some points. First, the work in [7] only considers linear classifiers which might not be the optimal one in practice. Second, even though the approach in [7] is stated based on Information Bottleneck framework, its objective function is not directly motivated by the idea of Information Bottleneck [8]. A similar approach which is directly based on Information Bottleneck objective function for eliminating the spurious invariant features can be found in [9] [10]. Despite their numerical results significantly outperforming the state-of-the-art methods, the results in [9] [10] are lack of theory, leading to heuristic algorithms.

Unlike other existing work, to extract the true invariant features, we motivate the use of conditional entropy minimization principle which can be shown as a special case of Deterministic Information Bottleneck [11]. Particularly, our contributions include:

- We proposed a new objective function that is motivated by the conditional entropy minimization principle. In addition, we show that this objective function is explicitly related to the Deterministic Information Bottleneck principle.
- We theoretically show that under some particular assumptions, minimizing the proposed objective function is able to filter out the spurious features.
- Our approach is general and can be applied for arbitrary invariance principle-based methods and arbitrary classi-

fiers including non-linear classifiers.

The intuition of our approach is first to learn a good representation function that can capture all the extracted invariant features including both the true invariant features and the spurious invariant features and then relies on the conditional entropy minimization principle to filter out the spurious invariant features. In practice, we use Invariant Risk Minimization algorithm [1] to perform the first step for capturing all invariant features. However, we note that our idea is not limited to the Invariant Risk Minimization algorithm. Indeed, our method can be integrated with arbitrary methods as long as these methods are able to extract invariant features. We also acknowledged that the Invariant Risk Minimization algorithm might not work in some particular cases [6] [12] [13] [14], but for the sake of the implementation simplicity, we use Invariant Risk Minimization to approximate extracted invariant representation features in this paper.

The remainder of this paper is structured as follows. In Section II, we summarize the recent work on Domain Generalization and briefly introduce Invariant Risk Minimization algorithm and Information Bottleneck framework. In Section III, we formally define the problem setup and clarify the notations. Section IV provides our main theoretical results which motivate our practical approach in Section V. Finally, we provide the numerical results in Section VI and conclude in Section VII.

II. RELATED WORK

A. Domain Generalization

Numerous domain generalization methods have been proposed in the past ten years which can be categorized in some major directions including data manipulation, representation learning, and meta-learning. The performance of a learning model often relies on the quantity and diversity of the training data and data manipulation is one of the cheapest methods to generate samples from a given set of limited data. Data manipulation can be employed via data augmentation [15] [16], domain randomization [17], or adversarial data augmentation [18], [19]. On the other hand, the representation learning approach aims to learn a good representation feature by decomposing the prediction function into a representation function followed by a classifier. Over the past decade, many methods are designed for better representation learning which can be categorized into two different learning principles: domaininvariant representation learning and feature disentanglement. Domain-invariant representation learning is constructed based on the assumption that the representations are general and transferable to different domains if the representation features remain invariant from domain to domain [20]. Notably, domain-invariant representation learning has emerged as one of the most common and efficient approaches in Domain Generalization and provided many promising results [1] [2] [7] [9] [10] [21] [22] [23] [24]. Finally, meta-learning methods aim to learn the algorithm itself by learning from previous experience or tasks, i.e., learning-to-learn. Even though metalearning is a general learning framework, it is recently applied for Domain Generalization tasks [10] [25] [26]. For more details, we refer the reader to the recent surveys on Domain Generalization in [27] and [28].

B. Information Bottleneck Principle

Information Bottleneck method aims to find the best tradeoff between accuracy and complexity (compression) when summarizing a random variable [8]. Particularly, Information Bottleneck aims to find a good representation function f^* via minimizing the following objective function:

$$f^* = \operatorname*{arg\,min}_{f} I(X;Z) - \theta I(Y;Z) \tag{1}$$

where I(X; Z) denotes the mutual information between the input X and its representation variable Z = f(X), I(Y; Z) denotes the mutual information between the label Y and representation variable Z.

Deterministic Information Bottleneck [11] generalizes the original Information Bottleneck which aims to minimize the following objective function:

$$f^* = \underset{f}{\operatorname{arg\,min}} H(Z) - \theta I(Y;Z) \tag{2}$$

where H(Z) denotes the entropy of the representation variable Z = f(X). For $\theta = 1$, $H(Z) - \theta I(Y;Z) = H(Z|Y)$ which is the conditional entropy between the representation variable Z and the label Y. Since $H(Z) \ge I(X;Z)$, Deterministic Information Bottleneck acts as an upper bound for Information Bottleneck.

C. Invariant Risk Minimization Framework

Invariant Risk Minimization (IRM) algorithm assumes the invariance of feature-conditioned label distribution [1]. Particularly, the Invariant Risk Minimization algorithm aims to search a representation function f such that E[Y|f(X) = Z] is invariant where $E[\cdot]$ denotes the expectation. We say that a data representation function f induces an invariant predictor g across the set of training environments if there is a predictor g that simultaneously achieves the minimum risk. The objective of Invariant Risk Minimization is given by:

$$\underset{f,g}{\operatorname{arg\,min}} \sum_{i=1}^{m} R^{(i)}(g \circ f)$$
$$t.: \qquad g \in \underset{\hat{g}}{\operatorname{arg\,min}} R^{(i)}(\hat{g} \circ f)$$

where $R^{(i)}$ denotes the cross-entropy loss for domain *i*. Since the IRM objective function involves a constraint, in [1], firstorder approximation is adopted and the practical loss function is:

$$\underset{f}{\operatorname{arg\,min}} \ L_{IRM} = \sum_{i=1}^{m} R^{(i)}(f) + \alpha ||\Delta_{g|g=1.0} R^{(i)}(g \circ f)|| \quad (3)$$

where $g \in \mathbb{R}$ is a dummy classifier [1].

s.

In this paper, we rely on the Invariant Risk Minimization algorithm [1] to extract the invariant features and use the conditional entropy minimization principle to filter out the spurious invariant features. Noting that our approach is applicable to any representation learning methods that can capture the invariant features, and we select Invariant Risk Minimization as a practical approach. Next, based on the assumption that the learned extracted feature is a linear mixture of true invariant features and spurious features and invariant features are independent with spurious features for a given object (label), we show that minimizing conditional entropy principle, which is a special case of the Deterministic Information Bottleneck principle, is able to filter out spurious features. This assumption may remind the reader about the setting of Blind Source Separation methods, for example, Independent Component Analysis [29], [30], [31] where one wants to extract independent components from a linear mixture signal. That said, we believe Blind Source Separation methods, in particular, Independent Component Analysis can be used to extract the true invariant feature, however, we prefer to use the information-based methods, for example, minimizing conditional entropy principle in our paper due to their strong theoretical supports.

III. PROBLEM FORMULATION

A. Notations

Consider a classification task where the learning algorithm has access to i.i.d. data from the set of m domains $\mathbb{D} = \{D_1, D_2, \ldots, D_m\}$. Each domain D_i is a set of n sample $x_j \in \mathbb{X} \in \mathbb{R}^d$ and its label $y_j \in \mathbb{Y} \in \mathbb{R}^k$, $j = 1, 2, \ldots, n$.

The domain generalization task is to learn a representation function $f : \mathbb{R}^d \to \mathbb{R}^{d'}, d' \leq d$, and a classifier $g : \mathbb{R}^{d'} \to \mathbb{R}^k$ that generalizes well to an unseen domain $D_s \notin \mathbb{D}$.

We use X to denote the data random variable, Z to denote the extracted feature random variable, and Y to denote the label random variable. We use $E[\cdot]$ to denote the expectation, $\sigma(\cdot)$ to denote the variance, $H(\cdot)$ to denote both the discrete entropy and the differential entropy and $I(\cdot)$ to denote the mutual information.

Following the previous work, we want to learn a good representation function f such that the extracted representation feature Z = f(X) is able to capture all the true invariant features.

B. Assumptions

Due to a finite number of observed domains, it is possible that the invariant representation features might contain spurious invariant features which are invariant for all observed domains but variant for the unseen domain [5] [6]. Specifically, we assume that the invariant extractor algorithm is good enough such that the extracted feature Z = f(X) is composed of two elements: the (true) invariant features Z_i and the spurious invariant features Z_s . Formally, we assume that:

$$f(X) = Z = \Theta(Z_i, Z_s). \tag{4}$$

Next, we provide three assumptions on Z_i, Z_s and $\Theta(\cdot)$ that will be used in Section IV.

Assumption 1. The (true) invariant feature Z_i is independent with the spurious invariant feature Z_s for a given label Y. Formally, $Z_i \perp \perp Z_s | Y$.

Assumption 2. A classifier based on invariant feature Z_i provides a higher accuracy than a classifier based on spurious invariant feature Z_s . Formally, we assume the following conditional entropy inequality $H(Z_i|Y) < H(Z_s|Y)$.

Conditional entropy is used as a measurement of impurity in clustering algorithm, for example, in the famous C4.5 decision tree [37] [38] [39] [40]. Since minimizing impurity is equivalent to maximizing the purity, a lower conditional entropy between the data and its cluster (label), a higher purity the cluster is. Therefore, by assuming that $H(Z_i|Y) <$ $H(Z_s|Y)$, one assumes that a clustering/classification algorithm based on invariant feature Z_i is able to provide a higher clustering purity, or equivalently, a higher accuracy than a clustering/classification algorithm based on spurious invariant feature Z_s . It is worth noting that this assumption is reasonable since if the spurious invariant feature Z_s can provide a better classification accuracy, then one should rely on Z_s instead of Z_i to predict the label and all the invariance principle-based approaches will, of course, fail.

Assumption 3. The invariant representation learning algorithm is able to learn a representation function f such that $f(X) = Z = \Theta(Z_i, Z_s) = aZ_i + bZ_s$ and $\sigma(Z|Y) = \sigma(Z_i|Y) = \sigma(Z_s|Y) = 1$.

First, we assume that representation learning algorithms, for example, the Invariant Risk Minimization algorithm, are good enough to find a representation function f which outputs the extracted feature Z including both the (true) invariant feature Z_i and the spurious invariant feature Z_s . Next, we assume a simple model where Z is a linear combination of Z_i and Z_s i.e., $\Theta(Z_i, Z_s) = aZ_i + bZ_s$ which is similar to the linear model used in [1] [7]. This simple linear model allows us to provide some theoretical results in the next section. In the future, to deal with a non-linear function $\Theta(\cdot)$, we intend to use more sophisticated techniques, for example, non-linear Independent Component Analysis [41] or non-linear Invariant Risk Minimization [2] to filter out the spurious features as previously discussed at the end of Section II.

On the other hand, the assumption $\sigma(Z|Y) = \sigma(Z_i|Y) =$ $\sigma(Z_s|Y) = 1$ is a crucial assumption and originates from the similarity between our proposed method and Blind Source Separation (BSS) methods, for example, Independent Component Analysis (ICA), which aim for recovering original sources from their linear mixture model. Particularly, for a given mixture signal M produced by two independent sources S_1, S_2 i.e., $M = aS_1 + bS_2$ and $S_1 \perp S_2$, ICA aims to recover original sources S_1 and S_2 [29], [30], [31]. However, since $S_1 \perp \!\!\!\perp S_2$, it is also true that $aS_1 \perp \!\!\!\perp bS_2$. Thus, there is no way to tell about the order of sources and their scales, leading to the so-called *permutation ambiguity* and *scaling ambiguity* in ICA [29], [30], [31]. To fix the arbitrary scaling factor, it is common to require independent components to have unit variance [29], [30], [31]. Due to the similar goal of the proposed method in this paper and Blind Source Separation methods, which both aim to extract independent components, we assume a similar condition such that $\sigma(Z|Y) = \sigma(Z_i|Y) = \sigma(Z_s|Y) = 1$.

IV. MAIN RESULTS

Our proposed approach is based on two fundamental steps. The first step is to extract all the invariant features Z from source domains. These extracted invariant features may include both the true invariant feature Z_i and the spurious invariant feature Z_s . The next step is to remove the spurious feature in order to construct a classifier that purely relies on the true invariant features Z_i . For example, in the cowcamel setting, the first step is to learn all extracted invariant features which might contain the color of the background. However, this spurious feature needs to be removed in the second step. Similar to the recent work in [7], [9], we rely on the Invariant Risk Minimization framework to perform the first step, but noting that our approach is general, and can be employed by any invariant representation learning algorithms. Next, we show that minimizing the conditional entropy principle, particularly, minimizing H(Z|Y) supports filtering the spurious invariant features.

Specifically, we want to design a representation function f^* to minimize the following objective function:

$$f^* = \operatorname*{arg\,min}_{f} L_{IRM}$$

s.t. $H(Z|Y) \leq \gamma$

where L_{IRM} is the Invariant Risk Minimization loss function defined in (3), $H(Z|Y) \leq \gamma$ acts as a constraint to filter out the spurious invariant feature Z_s . Noting that H(Z|Y) =H(Z) - I(Z;Y) shares a similar form with the Deterministic Information Bottleneck function in (2). Next, we show that by minimizing H(Z|Y), or equivalently, by selecting a suitable γ , one is able to extract the (true) invariant feature Z_i .

Lemma 1. Under the settings in Assumption 1, Assumption 2, and Assumption 3,

$$H(Z|Y) = H(aZ_i + bZ_s|Y) \ge H(Z_i|Y)$$
(5)

and the equality happens if and only if a = 1 and b = 0.

Proof. First, we want to remind that $H(\cdot)$ is used to denote both the discrete entropy and the differential entropy. Next, under Assumption 1 and Assumption 3, we first show that $a^2 + b^2 = 1$. Indeed,

$$I = \sigma(Z|Y)$$

$$= E[[aZ_i + bZ_s|Y]^2] - [E[aZ_i + bZ_s|Y]]^2$$

$$= E[a^2[Z_i|Y]^2] + E[b^2[Z_s|Y]^2] + E[2abZ_iZ_s|Y]$$

$$- [E[aZ_i|Y]]^2 - [E[bZ_s|Y]]^2 - 2abE[Z_i|Y]E[Z_s|Y]$$

$$= a^2 \Big(E[[Z_i|Y]^2] - [E[Z_i|Y]]^2 \Big) + b^2 \Big(E[[Z_s|Y]^2] - [E[Z_s|Y]]^2 \Big)$$

$$+ 2ab \Big(E[(Z_i|Y)(Z_s|Y)] - E[Z_i|Y]E[Z_s|Y] \Big)$$

$$= a^2 \sigma(Z_i|Y) + b^2 \sigma(Z_s|Y)$$
(6)
$$= a^2 + b^2$$
(7)

where (6) due to $Z_i \perp Z_s | Y$, thus $E[(Z_i | Y)(Z_s | Y)] = E[Z_i | Y]E[Z_s | Y]$, (7) due to the assumption that $\sigma(Z_i | Y) = \sigma(Z_s | Y) = 1$.

Next, to shorten the proof, we utilize the results from [42]. Particularly, for a given $Y = y_i$, from Eq. (7) in [42]:

$$H(aZ_i + bZ_s|Y = y_i) \tag{8}$$

$$= H(aZ_i|Y = y_i + bZ_s|Y = y_i)$$
(9)

$$\geq a^{2}H(Z_{i}|Y=y_{i}) + b^{2}H(Z_{s}|Y=y_{i})$$
(10)

$$= a^{2}H(Z_{i}|Y = y_{i}) + b^{2}H(Z_{i}|Y = y_{i})$$
(11)
$$+ b^{2}H(Z_{i}|Y = y_{i}) - b^{2}H(Z_{i}|Y = y_{i})$$
(12)

$$+ b^{2}H(Z_{s}|Y = y_{i}) - b^{2}H(Z_{i}|Y = y_{i})$$
(12)

$$= H(Z_i|Y=y_i) + b^2 (H(Z_s|Y=y_i) - H(Z_i|Y=y_i)), (13)$$

with (9) due to $p((aZ_i + bZ_s)|y_i) = t$ is equivalent to $p(aZ_i|y_i + bZ_s|y_i) = t, \forall t$, thus, $H(aZ_i + bZ_s|Y = y_i) = H(aZ_i|Y = y_i + bZ_s|Y = y_i)$, (10) due to Eq. (7) in [42] and the fact that $a^2 + b^2 = 1$, (13) due to $a^2 + b^2 = 1$. Next,

$$H(Z|Y) \tag{14}$$

$$= H(aZ_i + bZ_s|Y) \tag{15}$$

$$= \sum_{y_i \in \mathbb{Y}} p(y_i) H(aZ_i + bZ_s | Y = y_i)$$
(16)

$$\geq \sum_{y_i \in \mathbb{Y}} p(y_i) H(Z_i | Y = y_i)$$
(17)

+
$$\sum_{y_i \in \mathbb{Y}} p(y_i) b^2 (H(Z_s | Y = y_i) - H(Z_i | Y = y_i))$$
 (18)

$$= H(Z_i|Y) + b^2 (H(Z_s|Y) - H(Z_i|Y))$$
(19)

$$\geq H(Z_i|Y) \tag{20}$$

with (17) due to (13), (18) due to $\sum_{y_i \in \mathbb{Y}} p(y_i) H(Z_s|Y = y_i) = H(Z_s|Y)$ and $\sum_{y_i \in \mathbb{Y}} p(y_i) H(Z_i|Y = y_i) = H(Z_i|Y)$, (20) due to $H(Z_s|Y) > H(Z_i|Y)$ which is stated in Assumption 2.

Obviously that the equality $H(Z|Y) = H(Z_i|Y)$ happens if and only if a = 1 and b = 0, or equivalently, $Z = Z_i$.

Theorem 1. Under the settings in Lemma 1, there exits a γ^* such that $f^*(X) = Z = Z_i$ where:

$$f^* = \arg\min_{f} L_{IRM}$$

$$H(Z|Y) \leq \gamma^*.$$

s.t

Proof. The proof directly follows from the result in Lemma 1. Indeed, from the Assumption 3, minimizing Invariant Risk loss

function is able to produce a class of representation function f such that $f(X) = Z = aZ_i + bZ_s$. Now, by selecting a smaller value of γ , it encourages to select f such that H(Z|Y) is minimized. Indeed, from Lemma 1, H(Z|Y) is global lower bounded by $H(Z_i|Y)$ i.e., $H(Z|Y) \ge H(Z_i|Y)$, and from the constraint $H(Z|Y) \le \gamma$, we have $\gamma \ge H(Z|Y) \ge H(Z_i|Y)$. Thus, for a small enough value of γ i.e., by selecting $\gamma \rightarrow \gamma^* = H(Z_i|Y)$, $H(Z|Y) = H(Z_i|Y)$ forom Lemma 1, $H(Z|Y) = H(Z_i|Y)$. From Lemma 1, $H(Z|Y) = H(Z_i|Y)$ if and only if b = 0, thus, selecting $\gamma^* = H(Z_i|Y)$ will lead to a representation function f^* such that $f^*(X) = Z = Z_i$.

Next, to simplify the proposed constrained optimization problem, in practice, we want to optimize the following unconstrained objective function:

$$f^* = \underset{f}{\operatorname{arg\,min}} L_{IRM} + \beta H(Z|Y). \tag{21}$$

Remark 1. We acknowledge that in practice, to achieve a high prediction accuracy, the classifier may use both the invariant feature and the spurious or background feature [3] [4] [43]. That said, our proposed method does not aim to completely remove all the spurious features. Indeed, via controlling the hyper-parameter β , the goal is to reduce the effect of the spurious features and find the optimal value of β to balance the use of invariant features and spurious features. A larger value of β , a higher chance that the invariant feature Z_i is outputted, but it may not guarantee the best classification performance.

Remark 2. In [7], the entropy of the latent variable H(Z) is used as the Information Bottleneck objective function to filter out the spurious features. However, H(Z) does not recall about the Information Bottleneck Method (IBM) which is designed for controlling the trade-off between compression and accuracy [8]. However, since H(Z|Y) = H(Z)-I(Y;Z), minimizing H(Z|Y) is equivalent to minimize the Deterministic Information Bottleneck [11] a generalized version of IBM [8]. In the other words, our objective function H(Z|Y) captures the balance between compression i.e., minimizing H(Z) and accuracy i.e., maximizing I(Y;Z).

V. PRACTICAL APPROACH

A. Objective Function

We want to find the optimal representation function f^* via minimizing the following objective function:

$$\arg\min_{f} \sum_{i=1}^{m} R^{(i)}(f) + \alpha ||\Delta_{g|g=1.0} R^{(i)}(g \circ f)|| + \beta H(Z|Y)$$
(22)

where the first two terms are from the Invariant Risk Minimization function in (3) and the last term is the conditional entropy term, α and β are two hyperparameters that control the trade-off between minimizing the Invariant Risk loss or minimizing the conditional entropy loss.

B. Loss Function Design

We utilize the proposed method in [1] to minimize the Invariant Risk term L_{IRM} . Next, we discuss how to minimize the conditional entropy term H(Z|Y) in practice. From:

$$H(Z|Y) = H(Z) - I(Z;Y) = H(Z) - H(Y) + H(Y|Z)$$

and noting that H(Y) is given and independent with the representation function, we look forward to construct a tractable upper bound for H(Z) and H(Y|Z). First, we utilize the proposed method in [7] to approximate H(Z). Second, based on the proposed method in [44], we construct a tractable upper bound for H(Y|Z). Particularly, using the reparameterization trick [45] [46], a bit of noise is added into the last layer of the learning model which allows for computing the gradient and back-tracking to optimize H(Y|Z).

Finally, it is worth noting that there are many approximation methods for optimizing the conditional entropy [44] [46] [47] that are all suitable for applying in our framework.

VI. EXPERIMENTS

A. Datasets

AC-CMNIST [1]. Anti-causal-CMNIST dataset is a synthetic binary classification dataset derived from MNIST dataset which is proposed in [1] and also used in [7]. While the original MNIST images are grayscale, the images in AC-CMNIST are colored either red or green in a way that correlates strongly (but spuriously) with the class label. By construction, the label is more strongly correlated with the color than with the digit, so any algorithm purely minimizing training error will tend to explore the color and thus fail at the test phase. For training and testing, there are three environments in AC-CMNIST: two training environments containing 25,000 data points each, and one test environment containing 10,000 data points. For a fair comparison, we utilize the same construction of AC-CMNIST dataset as in [1] [7].

CS-CMNIST [32]. Covariate-Shift-CMNIST dataset is a synthetic classification dataset derived from Colored-MNIST (CMNIST) dataset which is proposed in [32] and also used in [7]. CS-CMNIST relies on selection bias to induce spurious correlations from a synthetic generative model. We follow the same construction based on [7] to set up a ten-class classification task, where the ten classes are the ten digits. For each digit class, we have an associated color. There are also three environments: two training environments containing 20,000 data points each, one test containing 20,000 data points. That said, the color (spurious feature) does not carry any extra information about the label in this dataset. More detail about CS-CMNIST and the model for generating this dataset can be found in Section 7.2.1.A of [32]. For a fair comparison, we utilize the same construction of CS-CMNIST dataset as in [7].

B. Compared Methods

We compare our proposed method, named Conditional Entropy and Invariant Risk Minimization (CE-IRM) against Empirical Risk Minimization (ERM) [48], the original Invariant Risk Minimization (IRM) [1], Information Bottleneck Empirical Risk Minimization (IB-ERM) [7], and Information Bottleneck Invariant Risk Minimization (IB-IRM) [7].

C. Implementation Details

Our implementation is mainly based on the results from [7] and [44]. Particularly, we utilize the implementation from [7] for minimizing the Invariant Risk term and use the method in [44] for optimizing the conditional entropy term.

In [7], the numerical results are reported based on two tuning parameters methods: (a) train-domain validation set tuning procedure [14], and (b) test-domain validation set tuning procedure [14]. For a fair comparison, we use both the train-domain validation set tuning procedure and test-domain validation set procedure in this paper. To construct the validation set, we split seen data into training set and validation set with the ratio of 95% - 5% and choose the model maximizing the accuracy on the validation set.

For AC-CMNIST, we utilize the learning model in [1] [7] which is based on a simple Multi-Layer Perceptron (MLP) with two fully connected layers each having output size 256 followed by an output layer of size two which aims to identify whether the digit is less than 5 or more than 5. Adam optimizer is used for training with a learning rate of 10^{-4} , batch size of 64, and the number of epochs is set to 500. To find the best representation, we perform a search for the weight of Invariant Risk term and the weight of conditional entropy term $\alpha, \beta \in \{0.1, 1, 10, 10^2, 10^3, 10^4\}$.

For CS-CMNIST, we utilize the learning model in [7] which is composed of three convolutional layers with feature map dimensions of 256, 128, and 64. Each convolutional layer is followed by a ReLU activation and batch normalization layer. The last layer is a linear layer that aims to classify the digit back to 10 classes. We use SGD optimizer for training with a batch size of 128, learning rate of 10^{-1} and decay every 600 steps with the total number of steps is set to 2,000. Similar to AC-CMNIST, we perform a search for the weight of Invariant Risk term and the weight of conditional entropy term $\alpha, \beta \in \{0.1, 1, 10, 10^2, 10^3, 10^4\}$.

Our algorithm runs on a Mac-book Pro 2020, Processor 2.3 GHz Quad-Core Intel Core I7, Memory 32 GB 3733 MHz LPDDR4X. The training times are 14 hours for AC-CMNIST dataset and 20 hours for CS-CMNIST dataset.

D. Results and Discussion

We run each experiment 5 times and only report the average accuracy together with its standard deviation.

The numerical results for train-domain validation set tuning procedure [14] are shown in Table I. As seen, none of the methods work for the AC-CMNIST dataset using train-domain validation set tuning procedure [14] which also confirms the results in Section 8.1.3 of [7]. For the CS-CMNIST dataset, CE-IRM (our) method outperforms the runner-up IB-IRM with the gap of 8%.

The numerical results for test-domain validation set tuning procedure [14] are shown in Table II. For the AC-CMNIST,

CE-IRM is comparable with other methods, however, it outperforms IB-IRM 9.6% on the CS-CMNIST dataset.

In addition, we do not intend to compare our results against the results from [9] due to the different setup, however, it is worth noting that our accuracy also outperforms the accuracy in [9] for the CS-CMNIST dataset.

The numerical results can be explained by the way the dataset is generated. Indeed, by construction, the spurious features (for example, the colors) are added independently for each digit (label), thus, it seems like our Assumption 1 which states that $Z_s \perp L_i | Y$ holds for the tested datasets. Noting that our assumption is not true in general as discussed at the paragraph below Assumption 1.

For future work, we aim to integrate the non-linear Invariant Risk Minimization algorithm [2] and Blind Source Separation methods, for example, non-linear Independent Component Analysis [41] to deal with non-linear mixture models of invariant features and spurious features. To strengthen our numerical results, we also want to numerically verify our assumptions on the tested datasets and test our proposed approach for other Domain Generalization datasets. Our implementation and new numerical results will be updated on https://github.com/thuan2412/Conditional_entropy_minimization_for_Do-

Datasets	ERM	IRM	IB-ERM	IB-IRM	CE-IRM (our)				
AC-CMNIST	17.2 ± 0.6	16.5 ± 2.5	17.7 ± 0.5	18.4 ± 1.4	17.5 ± 1.3				
CS-CMNIST	60.3 ± 1.2	61.5 ± 1.5	71.8 ± 0.7	71.8 ± 0.7	85.7 ± 0.9				
TABLE I									

Average accuracy of compared methods for AC-CMNIST and CS-CMNIST using train-domain validation set tuning procedure.

Datasets	ERM	IRM	IB-ERM	IB-IRM	CE-IRM (our)
AC-CMNIST	16.8 ± 0.8	67.0 ± 1.7	50.2 ± 0.5	67.7 ± 1.8	68.8 ± 1.2
CS-CMNIST	61.3 ± 1.4	62.0 ± 1.6	71.7 ± 0.8	71.9 ± 0.8	87.2 ± 0.7

TABLE II

Average accuracy of compared methods for AC-CMNIST and CS-CMNIST using test-domain validation set tuning procedure.

VII. CONCLUSIONS

In this paper, we investigate the problem of using the conditional entropy minimization principle for filtering out the spurious features, leading to a new Domain Generalization approach. Our practical method combines the well-known Invariant Risk Minimization algorithm and the conditional entropy minimization principle to achieve comparable performances with the state-of-the-art Domain Generalization methods. In addition, we show that our objective function is closely related to the Deterministic Information Bottleneck, and theoretically prove that under certain conditions, our proposed method can truly extract the invariant features. Even though our results are limited by assuming a linear mixture model, the idea of filtering the spurious invariant features is general and can be extended for non-linear models via more sophisticated techniques, for example, the Non-linear Independent Component Analysis.

REFERENCES

- [1] M. Arjovsky, L. Bottou, I. Gulrajani, and D. Lopez-Paz, "Invariant risk minimization," arXiv preprint arXiv:1907.02893, 2019.
- C. Lu, Y. Wu, J. M. Hernández-Lobato, and B. Schölkopf, "Nonlin-[2] ear invariant risk minimization: A causal approach," arXiv preprint arXiv:2102.12353. 2021.
- V. Nagarajan, A. Andreassen, and B. Neyshabur, "Understanding the [3] failure modes of out-of-distribution generalization," arXiv preprint arXiv:2010.15775, 2020.
- [4] M.-H. Bui, T. Tran, A. Tran, and D. Phung, "Exploiting domainspecific features to enhance domain generalization," Advances in Neural Information Processing Systems, vol. 34, 2021.
- Y. Chen, E. Rosenfeld, M. Sellke, T. Ma, and A. Risteski, "Iterative fea-[5] ture matching: Toward provable domain generalization with logarithmic environments," arXiv preprint arXiv:2106.09913, 2021.
- E. Rosenfeld, P. Ravikumar, and A. Risteski, "The risks of invariant risk minimization," arXiv preprint arXiv:2010.05761, 2020.
- [7] K. Ahuja, E. Caballero, D. Zhang, Y. Bengio, I. Mitliagkas, and I. Rish, "Invariance principle meets information bottleneck for out-of-distribution generalization," arXiv preprint arXiv:2106.06607, 2021.
- N. Tishby, F. C. Pereira, and W. Bialek, "The information bottleneck method," *arXiv preprint physics/0004057*, 2000.
- B. Li, Y. Shen, Y. Wang, W. Zhu, C. J. Reed, J. Zhang, D. Li, [9] K. Keutzer, and H. Zhao, "Invariant information bottleneck for domain generalization," arXiv preprint arXiv:2106.06333, 2021.
- [10] Y. Du, J. Xu, H. Xiong, Q. Qiu, X. Zhen, C. G. Snoek, and L. Shao, "Learning to learn with variational information bottleneck for domain generalization," in European Conference on Computer Vision. Springer, 2020, pp. 200-216.
- [11] D. Strouse and D. J. Schwab, "The deterministic information bottleneck," Neural computation, vol. 29, no. 6, pp. 1611-1630, 2017.
- [12] B. Aubin, A. Słowik, M. Arjovsky, L. Bottou, and D. Lopez-Paz, "Linear unit-tests for invariance discovery," arXiv preprint arXiv:2102.10867, 2021
- [13] P. Kamath, A. Tangella, D. Sutherland, and N. Srebro, "Does invariant risk minimization capture invariance?" in International Conference on Artificial Intelligence and Statistics. PMLR, 2021, pp. 4069-4077.
- [14] I. Gulrajani and D. Lopez-Paz, "In search of lost domain generalization," arXiv preprint arXiv:2007.01434, 2020.
- [15] N. H. Nazari and A. Kovashka, "Domain generalization using shape representation," in European Conference on Computer Vision. Springer, 2020, pp. 666-670.
- [16] F. C. Borlino, A. D'Innocente, and T. Tommasi, "Rethinking domain generalization baselines," in 2020 25th International Conference on Pattern Recognition (ICPR). IEEE, 2021, pp. 9227-9233.
- [17] R. Khirodkar, D. Yoo, and K. Kitani, "Domain randomization for scene-specific car detection and pose estimation," in 2019 IEEE Winter Conference on Applications of Computer Vision (WACV). IEEE, 2019, pp. 1932-1940.
- [18] K. Zhou, Y. Yang, T. Hospedales, and T. Xiang, "Deep domain-adversarial image generation for domain generalisation," in *Proceedings* of the AAAI Conference on Artificial Intelligence, vol. 34, no. 07, 2020, pp. 13 025-13 032.
- [19] F.-E. Yang, Y.-C. Cheng, Z.-Y. Shiau, and Y.-C. F. Wang, "Adversarial teacher-student representation learning for domain generalization," Advances in Neural Information Processing Systems, vol. 34, 2021.
- [20] S. Ben-David, J. Blitzer, K. Crammer, F. Pereira et al., "Analysis of representations for domain adaptation," Advances in neural information processing systems, vol. 19, p. 137, 2007.
- [21] Y. Ganin, E. Ustinova, H. Ajakan, P. Germain, H. Larochelle, F. Laviolette, M. Marchand, and V. Lempitsky, "Domain-adversarial training of neural networks," The journal of machine learning research, vol. 17, no. 1, pp. 2096–2030, 2016.
- [22] D. Mahajan, S. Tople, and A. Sharma, "Domain generalization using causal matching," in International Conference on Machine Learning. PMLR, 2021, pp. 7313-7324.

- [23] F. Zhou, Z. Jiang, C. Shui, B. Wang, and B. Chaib-draa, "Domain generalization with optimal transport and metric learning," arXiv preprint arXiv:2007.10573, 2020.
- [24] K. Ahuja, K. Shanmugam, K. Varshney, and A. Dhurandhar, "Invariant risk minimization games," in International Conference on Machine Learning. PMLR, 2020, pp. 145–155. [25] D. Li, Y. Yang, Y.-Z. Song, and T. Hospedales, "Learning to generalize:
- Meta-learning for domain generalization," in Proceedings of the AAAI Conference on Artificial Intelligence, vol. 32, no. 1, 2018.
- Y. Balaji, S. Sankaranarayanan, and R. Chellappa, "Metareg: Towards [26] domain generalization using meta-regularization," Advances in Neural Information Processing Systems, vol. 31, pp. 998-1008, 2018.
- [27] J. Wang, C. Lan, C. Liu, Y. Ouyang, and T. Qin, "Generalizing to unseen domains: A survey on domain generalization," arXiv e-prints, pp. arXiv-2103, 2021.
- K. Zhou, Z. Liu, Y. Qiao, T. Xiang, and C. C. Loy, "Domain general-[28] ization: A survey," *arXiv preprint arXiv:2103.02503*, 2021. [29] E. Oja and A. Hyvarinen, "Independent component analysis: A tutorial,"
- Helsinki University of Technology, Helsinki, 2004.
- [30] A. Hyvärinen and E. Oja, "Independent component analysis: algorithms and applications," Neural networks, vol. 13, no. 4-5, pp. 411-430, 2000.
- [31] G. R. Naik and D. K. Kumar, "An overview of independent component analysis and its applications," *Informatica*, vol. 35, no. 1, 2011.
- [32] K. Ahuja, J. Wang, A. Dhurandhar, K. Shanmugam, and K. R. Varshney, "Empirical or invariant risk minimization? a sample complexity perspective," arXiv preprint arXiv:2010.16412, 2020.
- [33] Z. Wang, M. Loog, and J. van Gemert, "Respecting domain relations: Hypothesis invariance for domain generalization," in 2020 25th International Conference on Pattern Recognition (ICPR). IEEE, 2021, pp. 9756-9763.
- [34] K. Zhang, M. Gong, P. Stojanov, B. Huang, Q. Liu, and C. Glymour, "Domain adaptation as a problem of inference on graphical models," arXiv preprint arXiv:2002.03278, 2020.
- [35] M. Maathuis, M. Drton, S. Lauritzen, and M. Wainwright, Handbook of graphical models. CRC Press, 2018.
- [36] E. C. Neto, "Causality-aware counterfactual confounding adjustment for feature representations learned by deep models," arXiv preprint arXiv:2004.09466, 2020.
- [37] J. R. Quinlan, C4. 5: programs for machine learning. Elsevier, 2014.
- D. Burshtein, V. Della Pietra, D. Kanevsky, and A. Nadas, "Minimum [38] impurity partitions," The Annals of Statistics, pp. 1637-1646, 1992.
- D. Coppersmith, S. J. Hong, and J. R. Hosking, "Partitioning nominal attributes in decision trees," *Data Mining and Knowledge Discovery*, [39] vol. 3, no. 2, pp. 197-217, 1999.
- [40] T. Nguyen, H. Le, and T. Nguyen, "Constant approximation algorithm for minimizing concave impurity," in ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP). IEEE, 2021, pp. 3635-3639.
- [41] A. Hyvärinen and P. Pajunen, "Nonlinear independent component analysis: Existence and uniqueness results," Neural networks, vol. 12, no. 3, pp. 429-439, 1999.
- [42] S. Verdú and D. Guo, "A simple proof of the entropy-power inequality," IEEE Transactions on Information Theory, vol. 52, no. 5, pp. 2165-2166, 2006.
- [43] F. Khani and P. Liang, "Removing spurious features can hurt accuracy and affect groups disproportionately," in Proceedings of the 2021 ACM Conference on Fairness, Accountability, and Transparency, 2021, pp. 196-205.
- [44] A. A. Alemi, I. Fischer, J. V. Dillon, and K. Murphy, "Deep variational information bottleneck," arXiv preprint arXiv:1612.00410, 2016.
- [45] D. P. Kingma and M. Welling, "Auto-encoding variational bayes," arXiv preprint arXiv:1312.6114, 2013.
- [46] A. Kirsch, C. Lyle, and Y. Gal, "Unpacking information bottlenecks: Unifying information-theoretic objectives in deep learning," arXiv preprint arXiv:2003.12537, 2020.
- [47] A. Kolchinsky, B. D. Tracey, and D. H. Wolpert, "Nonlinear information bottleneck," Entropy, vol. 21, no. 12, p. 1181, 2019.
- V. N. Vapnik, "An overview of statistical learning theory," IEEE trans-[48] actions on neural networks, vol. 10, no. 5, pp. 988-999, 1999.